



Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: GL-5 80W90 LS 1403
Product Code: GER00005,
Emergency Phone: CHEMTREC: (800) 424-9300
International: (703) 527-3887
Poison Control Center: (800) 222-1222
Company: Auto 1 Motor Oil
1325 East State St
Lehi, UT 84043
Information Phone: +01 (801) 766-8370 +01 (801) 766-8370

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact
Target Organs: Skin
Chemical Interactions: No chemical interaction known to affect toxicity.
Conditions Aggravated by Exposure: Personnel with pre-existing skin disorders should avoid contact with this product.

Acute Health Effects:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage. May cause skin irritation.
Skin Absorption: May cause irritation and minor systemic damage.
Eye Contact: Can cause minor irritation.
Ingestion Irritation: No hazard in normal industrial use. Small amounts (a tablespoonful) swallowed during normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury.

Chronic Health Effects:

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

HMIS Ratings:

Health: 2
Fire: 1
Reactivity: 0
PPE: B

NFPA Ratings:

Health: 2
Fire: 1
Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme



Safety Data Sheet

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Residual oils, petroleum, solvent-refined	30 - 60	64742-01-4	No PEL
Petroleum distillates, hydrotreated heavy paraffinic	30 - 60	64742-54-7	5 mg/m ³
Petroleum distillates, hydrotreated middle	0.1 - 1	64742-46-7	5 mg/m ³

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

IV. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen and get medical attention immediately.
Eyes:	None expected to be needed, however, use an eye wash to remove a chemical from your eye regardless of the level of hazard.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Seek medical advice if symptoms persist.
Ingestion:	No hazard in normal industrial use. Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
Notes to Doctor:	Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

V. FIRE FIGHTING MEASURES

Flammability	Combustible at elevated temperatures
Summary:	
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous Combustion Products:	Carbon monoxide, Smoke

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.



Safety Data Sheet

VII. HANDLING AND STORAGE

Handling Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer.

Storage Conditions: Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye Protection: No special requirements under normal industrial use.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

Control Parameters:

Chemical Name	ACGIH TLV -TWA	ACGIH STEL	IDLH	OSHA STEL
Residual oils, petroleum, solvent-refined	No TLV	No STL	No IDLH	No STEL
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3	10 mg/m3	No IDLH	No STEL
Petroleum distillates, hydrotreated middle	5 mg/m3	10 mg/m3	No IDLH	No STEL



Safety Data Sheet

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Brown
Odor:	Mild
pH:	Not determined
Viscosity (cSt at 40°C):	134.8
Solubility in Water:	Negligible; 0-1%
Octanol/Water	Not determined
Partition Coefficient:	
Evaporation Rate:	Not determined
Vapor Density:	Not determined
Vapor Pressure:	<0.20
Boiling Point (°C):	Not determined
Freezing Point (°C):	Not determined
Specific Gravity:	0.89
Density:	7.4
Flash Point (°C):	218
Flash Point Method:	COC
Upper Flammability	Not established
Limit, % in air:	
Lower Flammability	Not established
Limit, % in air:	

X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions. Hazardous polymerization will not occur
Conditions to Avoid:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Materials to Avoid:	Strong oxidizing agents
Hazardous Decomp.	Carbon monoxide, Smoke
Products:	
Hazardous	Will not occur.
Polymerization:	

XI. TOXICOLOGICAL

INFORMATION Acute Toxicity:

Ingestion:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Inhalation:	Harmful! Can cause systemic damage (see "Target Organs").
Absorption:	May cause irritation and minor systemic damage.
Eyes:	The material is likely to be moderately irritating to eyes based on animal data.
Skin:	This material is likely to be moderately irritating to skin based on animal data.
Sensitization:	No data available to indicate product or components may be a skin sensitizer.

Component Toxicology Data:

Chemical Name	CAS #	LD ₅₀ /LC ₅₀
Residual oils (petroleum), solvent-refined	64742-01-4	Inhalation LC ₅₀ Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD ₅₀ Rat 5000 mg/kg (Source: IUCLID); Dermal LD ₅₀ Rabbit 2000 mg/kg (Source: IUCLID)
Distillates (petroleum), hydrotreated heavy	64742-54-7	Inhalation LC ₅₀ Rat 2.18 mg/L 4 h; Oral



Safety Data Sheet

paraffinic

Polysulfides, di-tert-butyl

Petroleum distillates, hydrotreated middle

68937-96-2

64742-46-7

LD50 Rat 2000 mg/kg; Dermal LD50 Rabbit 2000 mg/kg

Oral LD50 Rat 6500 mg/kg (Source: IUCLID)

Inhalation LC50 Rat 4.6 mg/L 4 h (Source: IUCLID); Oral LD50 Rat 7400 mg/kg (Source: IUCLID); Dermal LD50 Rabbit 2000 mg/kg (Source: IUCLID)

XII. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Persistence:	No data.
Bioconcentration:	Bioconcentration may occur.
Degradability:	Biodegrades slowly.

Toxicity to Aquatic Invertebrates:	CAS #	Results
Residual oils (petroleum), solvent-refined	64742-01-4	48 Hr EC50 Daphnia magna: 1000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC50 Daphnia magna: 1000 mg/L
Toxicity to Fish:	CAS #	Results
Residual oils (petroleum), solvent-refined	64742-01-4	96 Hr LC50 Oncorhynchus mykiss: 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC50 Oncorhynchus mykiss: 5000 mg/L
Polysulfides, di-tert-butyl	68937-96-2	96 Hr LC50 Pimephales promelas: 250 - 500 mg/L [static]; 96 Hr LC50 Pimephales promelas: 1000 mg/L [semi-static]
Petroleum distillates, hydrotreated middle	64742-46-7	96 Hr LC50 Pimephales promelas: 35 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 10000 mg/L [static]

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging:	Recycle containers whenever possible. Containers of this material may be hazardous when emptied.
Disposal Methods:	Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

XIV. TRANSPORTATION INFORMATION

D.O.T.	Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).
---------------	--

XV. REGULATORY INFORMATION

TSCA Status:	All components of this material are on the US TSCA Inventory or are exempt.
State Restrictions:	Not applicable
WHMIS:	Uncontrolled product according to WHMIS classification criteria

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		
GL-5 80W90 LS	1403		Page 5 of 6



Safety Data Sheet

Chemical Name	Regulation	CAS #	% Range
Vinyl acetate	SARA 313	108-05-4	0.001- 0.01
Naphthalene	SARA 313	91-20-3	<10ppm
Ethyl acrylate	SARA 313	140-88-5	<10ppm
1,4-Dioxane	SARA 313	123-91-1	<10ppm
Ethylene oxide	SARA 313	75-21-8	<10ppm
Propylene oxide	SARA 313	75-56-9	<10ppm
None.	SARA 302-EHS		
None.	TSCA 12b export notification		
Naphthalene	CA Prop 65 – Cancer	91-20-3	<10ppm
Ethyl acrylate	CA Prop 65 – Cancer	140-88-5	<10ppm
1,4-Dioxane	CA Prop 65 – Cancer	123-91-1	<10ppm
Ethylene oxide	CA Prop 65 – Cancer	75-21-8	<10ppm
Propylene oxide	CA Prop 65 – Cancer	75-56-9	<10ppm
Ethylene oxide	CA Prop 65 - Dev. Toxicity	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod –fem	75-21-8	<10ppm
Ethylene oxide	CA Prop 65 - Reprod –male	75-21-8	<10ppm
Hydrotreated middle distillate (petroleum)	Canadian WHMIS List	64742-46-7	0.1 - 1
None.	Massachusetts RTK List		
None.	New Jersey RTK List		
None.	Pennsylvania RTK List		
None.	Minnesota Hazardous Substance List		

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

XVI. ADDITIONAL INFORMATION

Supersedes:	3/28/2014 12:14:02 PM
Revision Date:	7/25/2014 12:34:25 PM
Created by:	HAZEMS
Disclaimer:	This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.