

**Telecommunications and Information Exchange Between Systems**

**ISO/IEC JTC 1/SC 6**

<b>Document Number:</b>	N14166
<b>Date:</b>	2009-12-30
<b>Replaces:</b>	
<b>Document Type:</b>	Liaison organization contribution
<b>Document Title:</b>	ITU-T Rapporteur's comments on 6N14092, Text for PDAM ballot, Amendment 2 to ISO/IEC9594-All parts
<b>Document Source:</b>	ITU-T Rapporteur
<b>Project Number:</b>	
<b>Document Status:</b>	For your information.
<b>Action ID:</b>	FYI
<b>Due Date:</b>	
<b>No. of Pages:</b>	3
ISO/IEC JTC1/SC6 Secretariat Ms. Jooran Lee, KSA (on behalf of KATS) Korea Technology Center #701-7 Yeoksam-dong, Gangnam-gu, Seoul, 135-513, Republic of Korea ; Telephone: +82 2 6009 4808 ; Facsimile: +82 2 6009 4819 ; Email : <a href="mailto:jooran@kisi.or.kr">jooran@kisi.or.kr</a>	

# ITU-T Q.2/17 Rapporteur comments on 6N14092 PDAM 2 on Password Policy for ISO/IEC 9594

#	Reference	Type	Comment	Proposed change
1	28.6.1 of 9594-2	M	All DSA-DSA binds should be <i>identical</i> .	<p><i>Change:</i></p> <pre>dsaOperationalBindingManagementBind OPERATION ::= directoryBind</pre> <p><i>to:</i></p> <pre>dsaOperationalBindingManagementBind OPERATION ::= dsaBind</pre>
2	9594 general		It should be further analysed what are the procedures when binding to DSA not holding the password.	
3	11.1 of 9594-4	M	Password Policy has no relevance for DSA-DSA bindings.	<p><i>Replace the DSABind with:</i></p> <pre>dsaBind OPERATION ::= {   ARGUMENT  DsaBindArgument   RESULT    DsaBindResult   ERRORS    {dsaBindError} }</pre> <pre>DsaBindArgument ::= SET {   credentials [0] DsaCredentials OPTIONAL,   versions    [1] Versions DEFAULT {v1},   ... }</pre> <pre>DsaCredentials ::= CHOICE {   simple           [0] DsaSimpleCredentials,   strong           [1] StrongCredentials,   externalProcedure [2] EXTERNAL,   spkm             [3] SpkmCredentials,   sasl             [4] SaslCredentials,   ... }</pre> <pre>DsaSimpleCredentials ::= SEQUENCE {   name      [0] DistinguishedName,   validity  [1] SET {     time1    [0] CHOICE {       utc      UTCTime,       gt       GeneralizedTime} OPTIONAL,     time2    [1] CHOICE {       utc      UTCTime,       gt       GeneralizedTime} OPTIONAL,     random1   [2] BIT STRING OPTIONAL,     random2   [3] BIT STRING OPTIONAL} OPTIONAL,   password   [2] CHOICE {     unprotected OCTET STRING,     protected   HASH{OCTET STRING}} OPTIONAL,   ... }</pre> <pre>DsaBindResult ::= DsaBindArgument</pre>

4	7.4.1 of 9594-2	M	All DSA-DSA binds should be <i>identical</i> .	<p><i>Change:</i></p> <p><b>dSAShadowBind OPERATION ::= directoryBind</b></p> <p><i>to:</i></p> <p><b>dSAShadowBind OPERATION ::= dsaBind</b></p>
---	-----------------	---	--	---