
**Information technology — Syntax for
high-capacity automatic data capture
(ADC) media**

*Technologies de l'information — Syntaxe pour supports de capture
automatique de données (SAD) à haute capacité*



Reference number
ISO/IEC 15434:2005(E)

© ISO 2005

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

| | |
|---|----|
| Foreword..... | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms, definitions and documentation notation conventions | 2 |
| 3.1 Terms and definitions..... | 2 |
| 3.2 Documentation notation conventions | 2 |
| 4 Message format..... | 2 |
| 4.1 Message Envelope | 3 |
| 4.1.1 Message Header..... | 3 |
| 4.1.2 Message Trailer..... | 4 |
| 4.2 Format Envelope..... | 4 |
| 4.2.1 Format Header..... | 4 |
| 4.2.2 Format Header "00" - Reserved format | 6 |
| 4.2.3 Format Header "01" - Transportation | 6 |
| 4.2.4 Format Header "02" - Complete EDI message / transaction | 6 |
| 4.2.5 Format Header "03" - Structured data using ASC X12 segments | 6 |
| 4.2.6 Format Header "04" - Structured data using UN/EDIFACT segments..... | 7 |
| 4.2.7 Format Header "05" - Data using EAN/UCC Application Identifiers | 7 |
| 4.2.8 Format Header "06" - Data using ASC MH 10 Data Identifiers | 7 |
| 4.2.9 Format Header "07" - Free form text data | 7 |
| 4.2.10 Format Header "08" - Structured data using CII syntax rules..... | 8 |
| 4.2.11 Format Header "09" - Binary data | 8 |
| 4.2.12 Format Header ("10"- "99") - Reserved formats | 8 |
| 4.2.13 Format Trailer | 8 |
| 4.3 Data format | 9 |
| 4.3.1 Format "00" (Reserved)..... | 9 |
| 4.3.2 Format "01" Carrier sortation and tracking (Transportation) | 9 |
| 4.3.3 Format "02" (Complete EDI message / transaction) | 11 |
| 4.3.4 Format "03" (Structured data using ASC X12 segments)..... | 12 |
| 4.3.5 Format "04" (Structured data using UN/EDIFACT segments)..... | 12 |
| 4.3.6 Format "05" (Using EAN/UCC Application Identifiers) | 12 |
| 4.3.7 Format "06" (Using ASC MH 10 Data Identifiers) | 12 |
| 4.3.8 Format "07" (Free form text format) | 12 |
| 4.3.9 Format "08" (Structured data using CII syntax rules)..... | 12 |
| 4.3.10 Format "09" (Binary data) | 13 |
| 4.3.11 Format "10" - "99" (Reserved)..... | 13 |
| 5 Maintenance | 13 |
| Annex A (informative) Subset of ISO 646 (Table of hexadecimal and decimal values) | 15 |
| Bibliography | 16 |

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 15434 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 31, *Automatic identification and data capture techniques*.

This second edition cancels and replaces the first edition (ISO/IEC 15434:1999), which has been technically revised.

Introduction

This International Standard defines the manner in which data is transferred to high capacity ADC media from a supplier's information system and the manner in which data is transferred to the recipient's information system. This International Standard does not define the internal data storage format for specific high capacity ADC media. This International Standard does not specify the application of data structures provided by a specific data syntax format. The application of the data structure is specified by industry conventions.

Users of automatic data capture (ADC) technologies benefit by being able to receive data in a standard form and by being able to provide data in a standard form. Static ADC technologies such as bar code symbologies, magnetic stripe, optical character recognition, surface acoustical wave (SAW), and Weigand effect typically encode a single field of data. Most applications of these technologies involve the encoding of a single field of data by the supplier of the medium and the subsequent decoding of the data field by the recipient. Encoding single fields of data permits the supplier to perform the encodation from a single field within the supplier's information system. Decoding single fields of data permits the recipient to input this data into a single field in the recipient's information system, in lieu of key entry.

High capacity ADC technologies such as two-dimensional symbols, RFID transponders, contact memories, and smart cards encode multiple fields of data. These multiple fields usually are parsed by the recipient's information system and then mapped to specific fields of data in the recipient's information system. This International Standard defines the syntax for high capacity ADC media, so as to enable ADC users to utilize a single mapping utility, regardless of which high capacity ADC media is employed.

Information technology — Syntax for high-capacity automatic data capture (ADC) media

1 Scope

This International Standard specifies a transfer structure, syntax, and coding of messages and data formats when using high capacity ADC media between trading partners (specifically between suppliers and recipients) and, where applicable, in support of carrier applications, such as bills of lading and carrier sortation and tracking.

The data encoded according to this International Standard include

- data which may be used in the shipping, receiving, and inventory of transport units;
- data which may be contained within supporting documentation, in paper or electronic form, related to unit loads or transport packages;
- data which may be used in the sortation and tracking of transport units.

This International Standard describes the ISO 646 syntax for automatic data capture.

This International Standard is not the controlling specification for data structures (e.g. CII) referenced in this International Standard.

This International Standard does not supersede or replace any applicable safety or regulatory marking or labeling requirements. This International Standard is to be applied in addition to any other mandated labeling requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 646, *Information technology — ISO 7-bit coded character set for information interchange*

ISO/IEC 19762 (all parts), *Information technology — Automatic identification and data capture (AIDC) techniques — Harmonized vocabulary*

ANS MH10.8.2, *ASC MH 10 Data Identifiers and Application Identifiers*

ANS MH10.8.3, *ASC MH 10 Syntax for high capacity ADC media*

ANS X12, *Electronic Data Interchange*

CII Syntax Rule (Vers 3.00), *CII Syntax Rule Specifications (3.00) (Electronic Data Interchange — Japan)*

General EAN.UCC Specifications, EAN International and Uniform Code Council, Inc.

3 Terms, definitions and documentation notation conventions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 19762 (all parts) apply.

3.2 Documentation notation conventions

This International Standard uses the following typographical conventions in message examples

- a) **BOLD, ALL CAPITALS** Text that must be entered exactly as it appears. (In this International Standard, F_S , G_S , U_S , R_S , E_{OT} are used to represent non-printable special characters. The ISO 646 representation of special characters used in this International Standard can be found in Annex A.),
- b) *italic, lower case* Variable Parameters. The user must supply an appropriate value. In some cases default values are recommended in this International Standard.

4 Message format

This clause defines how data shall be transferred from a High Capacity ADC Media reading device to the user's application software.

To allow multiple data Formats to be contained within a data stream, a two level structure of enveloping is employed. The outermost layer of the message is a Message Envelope that defines the beginning and end of the message. Within the Message Envelope are one or more Format Envelopes that contain the data. (See Figure 1). Multiple formats in a single message should only be employed with bi-lateral agreements of the trading partners.

The Message Envelope shall consist of

- A Message Header,
- One or more Format Envelope(s), and,
- A Message Trailer (when required).

Each Format Envelope within the Message Envelope shall consist of

- A Format Header,
- Data, formatted according to the rules defined for that Format, and,
- A Format Trailer (when required).




Figure 1 — Enveloping Structure

NOTE Annex A shows the Decimal and Hexadecimal values of ISO 646 characters

4.1 Message Envelope

The Message Envelope defines the start and end of the data contained within the data stream, and provides the following functions:

- Indication that the message contained within this media is formatted in compliance with the rules of this standard
- Indicates the character which has been defined to separate Formats within this Message.
- Provide an unique character to indicate the end of the Message.

The structure within a data stream is as follows:

A Message, containing one or more Formats

A Format, containing one or more Segments

A Segment, containing one or more Data Elements

A Data Element (Field), potentially containing one or more Sub-elements (Sub-fields).

4.1.1 Message Header

The Message Header consists of two parts:

- the three character Compliance Indicator, and
- the Format Trailer Character.

The complete Message Header is: $[] >^R_S$

4.1.1.1 Compliance Indicator

The Compliance Indicator shall be the first three characters in the Message Header. The Compliance Indicator shall be **[]>** (left bracket, right parenthesis, and greater than). See Annex A for a table of ISO 646 decimal and hexadecimal values.

4.1.1.2 Format Trailer Character

The Format Trailer Character shall be the fourth character in the Message Header. The Format Trailer Character shall be the non-printable ISO 646 character "**R_S**" (see Annex A). The Format Trailer Character is used throughout the message to indicate the end of a data Format envelope. (See 4.2.13)

4.1.2 Message Trailer

The Message Trailer identifies the end of the message within the data stream. The Message Trailer shall be the End Of Transaction character, "**E_{OT}**" (see Annex A). The Message Trailer character shall not be used elsewhere in the message except in Format "09" (binary data) where the "**E_{OT}**" character may appear.

The Message Trailer shall **not** be used with Formats "02" (Complete EDI message / transaction) and "08" (Structured data using CII Syntax Rules).

4.2 Format Envelope

The Format Envelope defines the start and end of data in a given Format and provides the following functions:

- Identifies the data Format used within the envelope,
- Defines the character(s) used to separate the Segments, Data Elements (Fields), and Sub-elements (Sub-fields) within this data Format, and,
- Indicates any applicable date, release, or control information.

4.2.1 Format Header

A Format Header shall consist of two parts:

- A Format Indicator (a two-digit numeric identifier which identifies the rules governing the Format),
- and
- Variable data (if any) which defines the separators used and version and release, date, or control information of the applicable standards.

Table 1 lists the Format Indicators and variable data associated with the Format Header.

Table 1 — Format header table showing associated separators

| Format Indicator | Variable Header Data | Format Trailer | Format Description |
|------------------|---|----------------|---|
| 00 | | | Reserved for future use |
| 01 | $G_{S^{vv}}$ | R_S | Transportation |
| 02 | | | Complete EDI message / transaction |
| 03 | $vvvrrr^F_S G_S U_S$ | R_S | Structured data using ANSI ASC X12 Segments |
| 04 | $vvvrrr^F_S G_S U_S$ | R_S | Structured data using UN/EDIFACT Segments |
| 05 | G_S | R_S | Data using EAN/UCC Application Identifiers |
| 06 | G_S | R_S | Data using ASC MH 10 ¹⁾ Data Identifiers |
| 07 | | R_S | Free form text |
| 08 | $vvvvrrnn$ | | Structured data using CII Syntax Rules |
| 09 | $G_S ttt...t G_S ccc...c G_S nnn...n G_S$ | R_S | Binary data (file type) (compression technique) (number of bytes) |
| 10-99 | | | Reserved for future use |

NOTE 1 vv represents the two-digit version of Format '01' being used

NOTE 2 R_S represents the Format Trailer character (See 4.2.13).

NOTE 3 F_S represents the Segment Terminator (See 4.2.1.1.1).

NOTE 4 G_S represents the Data Element Separator (See 4.2.1.1.2).

NOTE 5 U_S represents the Sub-Element Separator (See 4.2.1.1.3).

NOTE 6 $vvvrrr$ represents the three digit Version (vvv) followed by the three digit Release (rrr) (See 4.2.5).

NOTE 7 $vvvvrrnn$ represents the four digit Version (vvvv) followed by the two digit Release (rr) followed by the two digit Edition indicator (nn) (See 4.2.10).

NOTE 8 $ttt...t$ represents the file type name (See 4.2.11).

NOTE 9 $ccc...c$ represents the compression technique name (See 4.2.11).

NOTE 10 $nnn...n$ represents the number of bytes (See 4.2.11).

4.2.1.1 Separators and terminators

The Separators and Terminators are an integral part of the data stream. The Separator and Terminator characters shall not be used in non-binary data elsewhere in the message. For binary data strings (Format "09") special considerations apply (see 4.2.11).

1) Previously known as FACT Data Identifiers.

4.2.1.1.1 Segment Terminator

Each segment in Format "03" shall be terminated by the Segment Terminator character, the non-printable character " F_S " (see Annex A).

4.2.1.1.2 Data Element Separator

Data elements in Formats "01," "03," "05," and "06" shall be separated by the Data Element Separator, the non-printable character " G_S " (see Annex A).

4.2.1.1.3 Sub-element Separator

Sub-elements in Format "03" shall be terminated by the Sub-element Separator character, the non-printable character " U_S ", (see Annex A).

4.2.2 Format Header "00" - Reserved format

Format header "00" is reserved for future assignment by the maintenance body this standard.

4.2.3 Format Header "01" - Transportation

The Format Header shall be represented as:

01 G_S vv

where:

- G_S is the Data Element Separator to be used between Data Elements
- vv represents the two-digit version assigned by the maintenance body of this standard

4.2.4 Format Header "02" - Complete EDI message / transaction

The Format Header shall be represented as:

02

There is no variable header data for this data Format. (See 4.3.3).

4.2.5 Format Header "03" - Structured data using ASC X12 segments

The Format Header shall be represented as:

03 $vvvrrr$ F_S G_S U_S

where:

- $vvvrrr$ represents the three-digit Version (vvv) and three-digit Release (rrr) indicator for the drafts of ASC X12 used,
- F_S is the Segment Terminator to be used to indicate the end of an EDI segment,
- G_S is the Data Element Separator to be used between EDI Data Elements,

- U_S is the Sub-element Separator to be used between EDI Sub-elements in a Composite Data Element.

Format Header "03" employs ANSI ASC X12 segments, used in North America. For international trade Format Header "04" should be used. Format "03" is intended for use within North America only.

4.2.6 Format Header "04" – Structured data using UN/EDIFACT segments

The Format Header shall be represented as:

$04vvvrrrF_SG_SU_S$

where

- $vvvrrr$ represents the three-digit Version (vvv) and three-digit Release (rrr) indicator for the UN/EDIFACT level used,
- F_S is the Segment Terminator to be used to indicate the end of an EDI segment,
- G_S is the Data Element Separator to be used between EDI Data Elements,
- U_S is the Sub-element Separator to be used between EDI Sub-elements in a Composite Data Element.

4.2.7 Format Header "05" - Data using EAN/UCC Application Identifiers

The Format Header shall be represented as:

$05G_S$

where:

- G_S is the Data Element Separator to be used between data Fields

4.2.8 Format Header "06" - Data using ASC MH 10 Data Identifiers

The Format Header shall be represented as:

$06G_S$

where:

- G_S is the Data Element Separator to be used between data Fields

4.2.9 Format Header "07" - Free form text data

The Format Header shall be represented as:

07

There is no variable header data for this data Format. (See 4.3.8).

4.2.10 Format Header "08" - Structured data using CII syntax rules

The Format Header shall be represented as:

08vvvvrrnn

where:

- vvvvrrnn represents the four-digit Version (vvvv), two-digit Release (rr), and two-digit edition (nn) indicator for the CII level used. This equates to the BPID in CII Syntax Rules. (See 4.3.9).

Format Header "08" employs CII syntax rules, used in Japan. For international trade Format Header "04" should be used. Format "08" is intended for use within Japan only.

4.2.11 Format Header "09" - Binary data

The Format Header shall be represented as:

09 G_S ttt...t G_S ccc...c G_S nnn...n G_S

where:

- G_S is the Data Element Separator to be used between Fields in this header and at the end of the last data field
- ttt...t represents the identification of the binary file type, e.g., JPEG, TIFF, PCX, BMP, CSV, CGM, GIF. This field is a variable length of 1-30 characters (including version if applicable). This field shall be terminated by the " G_S " character. The binary file type and the means by which to represent the binary file type should be mutually agreed upon between the trading partners.
- ccc...c represents the compression technique employed. This field is a variable length of 0-30 characters. If no compression is used, this field shall be left blank. In any case this field shall be terminated by the " G_S " character. The compression technique and the means by which to represent the compression technique should be mutually agreed upon between the trading partners.
- nnn...n represents the number of bytes in the binary message. This field is a variable length field of 1-15 digits. The count does not include the length of the data format header or the data format trailer. This field shall be terminated by the " G_S " character, which is not part of the byte count.

4.2.12 Format Header ("10"-"99") - Reserved formats

Format headers "10" - "99" are reserved for future assignment by the maintenance body for this standard.

4.2.13 Format Trailer

The Format Trailer identifies the end of a Format Envelope. The Format Trailer shall consist of the Format Trailer Character, the non-printable ISO 646 character " R_S " (see Annex A). The Format Trailer Character shall not be used in non-binary data elsewhere in the Message.

The Format Trailer shall **not** be used with Formats "02" (Complete EDI message / transaction) and "08" (CII - Complete Message).

4.3 Data format

Within a given Format Envelope, the data shall be formatted using one and only one of the following methods:

- Transportation
- Complete EDI Message / Transaction (ASC X12, UN/EDIFACT or CII standard)
- Structured Text (ASC X12 or UN/EDIFACT subset)
- Data structured using the rules of EAN/UCC Application Identifiers
- Data structured using the rules of ASC MH 10 Data Identifiers
- Free form text
- CII Message Record without Message-group header and trailer
- Binary Data

If more than one Format is included in a Message, Format '01', if used, shall be the first Format in the Message.

4.3.1 Format "00" (Reserved)

This Format type is reserved for future assignment and should not be used prior to the issuance of a revision or draft standard for trial use of this document.

4.3.2 Format "01" Carrier sortation and tracking (Transportation)

Format '01' consists of two areas: the first is mandatory data which is common to all carrier sortation and tracking applications, the second area is optional data which may be useful to specific applications between trading partners.

The organization controlling the data structure within this format is identified through the version indicator in the Format Header. At the time that this standard was published the following versions had been identified.

- Version '02' - Formatted according to the rules of ASC MH10/SC 8 (using measurement qualifiers of pounds ["LB"] and kilograms ["KG"])
- Version '06' - Formatted according to the rules of the International Air Transport Association (IATA)
- Version '56' - Formatted according to the rules of International Federation of Freight Forwarders Association (FIATA)
- Version '96' - Formatted according to the rules of ASC MH10/SC 8 (using measurement qualifier of pounds only)

4.3.2.1 Format "01" Version "02"

4.3.2.1.1 Mandatory data

This data is required within the "01" Format. The following Data Elements shall be ordered as listed below, immediately following the Format Header. Each Data Element is defined as either fixed or variable length. Where Fields are variable in length the minimum Field length and the maximum Field length (min...max) are shown below. All Fields are separated by the Data Element Separator character ("^GS") (see Annex A) defined in the Format Header.

| | |
|--|----------------------------|
| Ship To Postal Code | (an 00...11) |
| Ship To Country Code (ISO 3166) | (n 03) |
| Class of Service (Assigned by carrier) | (an 01...03) ²⁾ |
| Tracking Number (controlled by carrier) | (an 01...20) |
| Origin Carrier SCAC | (an 02...04) |
| <i>(Standard Carrier Alpha Code (SCAC) of the carrier intended to transport the package)</i> | |

4.3.2.1.2 Optional data

There are nine optional Data Elements. Optional Data Elements, if used, shall immediately follow Mandatory Data, in the order specified below. Each Data Element is defined as either fixed or variable length. Where Fields are variable in length the minimum Field length and the maximum Field length (min...max) are shown below. All optional Fields, including blank ones, shall be separated by the Data Element Separator character ("**G_S**") (see Annex A). Trailing Data Element Separators shall be suppressed.

Data that has been identified as Optional Data may not be needed in all applications. The Optional Data fields and associated lengths are shown below:

| | |
|--|--------------------------------|
| Carrier Assigned Shipper ID (pick-up Location) | (an 01...10) |
| Julian Day of Pickup | (n 03) |
| Shipment ID Number | (an 01 ... 30) |
| n/x (container n of x total containers) | (n 01...04 / n 01...04) |
| Weight ("LB" or "KG") (decimal is a character if used) | (r 01...08, a02) ³⁾ |
| Cross match (value is Y or N) | (a 01) |
| Ship To Street Address | (an 01...35) |
| Ship To City | (an 01...35) |
| Ship To State/Province | (an 02) |
| Ship To Name | (an 01...35) |

4.3.2.2 Format "01" Version "96"

4.3.2.2.1 Mandatory data

This data is required within the "01" Format. The following Data Elements shall be ordered as listed below, immediately following the Format Header. Each Data Element is defined as either fixed or variable length. Where Fields are variable in length the minimum Field length and the maximum Field length (min...max) are shown below. All Fields are separated by the Data Element Separator character ("**G_S**") (see Annex A) defined in the Format Header.

2) It is recommended that the Class of Service be 3 digits of numeric data.

3) The weight qualifier is appended directly to the value without an intervening space and is in uppercase letters. An example of this format would be if shipment weight is 117,6 kg, this data stream would appear as 117.6 KG. For historic reasons the encoded decimal mark is ISO 646 value "2E_{HEX}" as defined in ISO 646.

| | |
|--|----------------------------|
| Ship To Postal Code | (an 03...11) |
| Ship To Country Code (ISO 3166) | (n 03) |
| Class of Service (Assigned by carrier) | (an 01...03) ⁴⁾ |
| Tracking Number (controlled by carrier) | (an 01...20) |
| Origin Carrier SCAC (Standard Carrier Alpha Code (SCAC) of the carrier intended to transport the package) | (an 02...04) |

4.3.2.2.2 Optional data

There are nine optional Data Elements. Optional Data Elements, if used, shall immediately follow Mandatory Data, in the order specified below. Each Data Element is defined as either fixed or variable length. Where Fields are variable in length the minimum Field length and the maximum Field length (min...max) are shown below. All optional Fields, including blank ones, shall be separated by the Data Element Separator character ("G_S") (see Annex A). Trailing Data Element Separators shall be suppressed.

Data that has been identified as Optional Data may not be needed in all applications. The Optional Data fields and associated lengths are shown below:

| | |
|--|-------------------------|
| Carrier Assigned Shipper ID (pick-up Location) | (an 01...10) |
| Julian Day of Pickup | (n 03) |
| Shipment ID Number | (an 01 ... 30) |
| n/x (container n of x total containers) | (n 01...04 / n 01...04) |
| Weight (lb) (decimal is a character if used) | (r 01...10) |
| Cross match (value is Y or N) | (a 01) |
| Ship To Street Address | (an 01...35) |
| Ship To City | (an 01...35) |
| Ship To State/Province | (an 02) |

4.3.3 Format "02" (Complete EDI message / transaction)

This Format is used to encode an entire EDI transaction / message with the intent of passing it directly to an EDI translator. The Format shall be either ASC X12, UN/EDIFACT or CII-Standard. Enveloping structures as defined by the applicable standard shall be included, e.g., ISA, GS, ST, SE, GE, and IEA segments (for ASC X12) or UNA, UNB, UNH, UNT, and UNZ segments (for UN/EDIFACT), or Message-group-header, Message and Message-group-trailer Record (for CII Standard).

The Message Trailer character "E_{OT}" and the Format Trailer character "R_S" shall **not** be used with Format "02".

There shall be no more than one "02" Format in a Message Envelope. Format "02" shall **not** be combined with any other data format within a Message Envelope.

4) It is recommended that the Class of Service be 3 digits of numeric data.

4.3.4 Format "03" (Structured data using ASC X12 segments)

This Format is used to represent data, such as Ship To and Ship From, etc., structured according to ASC X12 rules. This format allows the encodation of data represented by either individual ASC X12 segments without enveloping, i.e., ISA/IEA, GS/GE, and ST/SE; or a single ASC X12 transaction set with enveloping, i.e., ST/SE. This data is not intended to be passed directly to an EDI translator.

For Format "03," the version of ASC X12 format is contained in the Format Header. The character "**F_S**" shall be used as the ASC X12 Segment Terminator. The character "**G_S**" shall be used as the ASC X12 Data Element Separator. The character "**U_S**" shall be used as the ASC X12 Sub-element Separator. (See Annex A for hexadecimal and decimal values of Terminators and Separators.)

EDI segments such as BIN that encode binary data shall not be used in Format "03." Binary data should be encoded only in Format "09" (see 4.3.10).

Format Header "03" employs ANSI ASC X12 segments, used in North America. For international trade Format Header "04" should be used. Format "03" is intended for use within North America only.

4.3.5 Format "04" (Structured data using UN/EDIFACT segments)

This Format is used to represent data, such as Ship To and Ship From, etc., structured according to UN/EDIFACT rules.

This format allows the encodation of data represented by either individual UN/EDIFACT segments without enveloping, i.e., UNB/UNA/UNZ and UNH/UNT; or a single UN/EDIFACT message with enveloping, i.e., UNH/UNT. This data is not intended to be passed directly to an EDI translator.

For Format type "04," the version of UN/EDIFACT format is contained in the Format Header. The character "**F_S**" shall be used as the UN/EDIFACT Segment Terminator. The character "**G_S**" shall be used as the UN/EDIFACT Data Element Separator. The character "**U_S**" shall be used as the UN/EDIFACT Sub-element Separator. (See Annex A for hexadecimal and decimal values of Terminators and Separators.)

4.3.6 Format "05" (Using EAN/UCC Application Identifiers)

Each Data Element in this Format shall be preceded by the appropriate EAN/UCC Application Identifier (AI) code and followed by the Data Element Separator character "**G_S**" unless the data element is the last field in the data Format, i.e., the last Format "05" data element is followed by the Format Trailer Character "**R_S**". (See Annex A for hexadecimal and decimal values of Terminators and Separators.)

4.3.7 Format "06" (Using ASC MH 10 Data Identifiers)

Each Data Element in this Format shall be preceded by the appropriate ASC MH10 Data Identifier (DI) code and followed by the Data Element Separator character "**G_S**" unless the data element is the last field in the data Format, i.e., the last Format "06" data element is followed by the Format Trailer Character "**R_S**". (See Annex A for hexadecimal and decimal values of Terminators and Separators.)

4.3.8 Format "07" (Free form text format)

This Format permits free-form text information. There is no variable header data for this data Format. Complete sentences will be followed by a period and, if the sentence is not the last sentence in a paragraph, two spaces. Two line feeds will be used between paragraphs.

4.3.9 Format "08" (Structured data using CII syntax rules)

This Format is structured data according to CII standards, as defined by the Center for Informatization of Industry - Japan. Format "08" contains only one CII-Message-Record. Format-end and Message-end in Format "08" shall be indicated by the CII-Message-trailer.

The Message Trailer character "**E_{OT}**" and the Format Trailer character "**R_S**" shall **not** be used with Format "08".

Format "08" shall **not** be combined with any other data Format within a Message Envelope.

Format Header "08" employs CII Syntax Rules, used in Japan. For international trade Format Header "04" should be used. Format "08" is intended for use within Japan only.

4.3.10 Format "09" (Binary data)

This Format is for binary data in any format. The length and format of the data shall be identified in the format header. Binary files must be defined as to the type, compression technique, and number of bytes used in the data stream.

Binary data strings, such as those that represent digital image data, may be included in messages exchanged by and agreed upon between trading partners. CAD/CAM drawings, picture files, various raster and vector graphic images, as well as 2D and 3D images are examples of the kinds of data that could be compressed and encoded for exchange. Typically such binary data files will be encoded and formatted according to an image file representation standard such as JPEG, TIFF, PCX, BMP, CSV, CGM, GIF, and CCITT Group 4, that will include header data followed by image data. The contents of the binary file data groupings, in order to be intelligible, need to be encapsulated within an identifying envelope that separates the binary image data from the other types of message information normally represented as ISO 646 characters.

By definition, binary data may include any eight-bit character, even those that have special meaning elsewhere in this standard. Care should be taken not to misinterpret binary values as characters having special meaning elsewhere in this standard.

The Data Element Separator character ("**G_S**") shall be used in the header of Format "09" to separate **both** the data elements **and** to terminate the header because all fields in the header are variable length. Though the number of bytes is given in the header, the Format Trailer Character shall follow the binary data to complete the format envelope.

4.3.11 Format "10"-"99" (Reserved)

These Format types are reserved for future assignment and should not be used prior to the issuance of a revision or draft standard for trial use of this document.

5 Maintenance

The Syntax Maintenance Committee of ISO/IEC JTC 1/SC 31 is responsible for the maintenance of this document. Maintenance includes the assignments of new formats and new versions within formats whose versions are controlled by this standard.

Requests for new formats and requests for new versions of formats controlled by this standard should be submitted to the ISO 15434 Maintenance Committee who can be reached as follows:

Chairman, SC 31/WG 2
AI Research Institute, Inc.
6-35-6 Kisabe, Katano-city, Osaka 576-0052, Japan
(V): +81-72-810-2755
(F): +81-72-810-2754
(E): toshihiro.yoshioka@ai-soken.com (Toshihiro Yoshioka)

Project Editor, ISO/IEC 15434
Q.E.D. Systems
P.O. Box 2524
Cedar Rapids, IA 52406-2524
United States of America
Tel: +1 319/364 02 12
Fax: +1 319/365 88 14
Email: craig.harmon@qed.org (Craig K. Harmon)

Requests for new Formats or new versions of Formats whose version control rests with the Maintenance Committee of this standard will be evaluated on the following criteria:

- a) Requests shall be submitted by a National Body having membership or technical liaison status to ISO/IEC JTC 1/SC 31;
- b) Requestors shall demonstrate that the requested Format or version will be used by multi-sectoral interests, preferably on a multi-national basis;
- c) Requestors shall demonstrate the support of the requested Formats by multiple economic entities, specifically, more than one company;
- d) Requestors shall demonstrate that the requested Format is to be used in an open interchange environment; and
- e) Requestors shall within a reasonable timeframe, preferably within 12 months of the date of assignment of the Format or version, provide proof of the implementation of the new Format or version to the Maintenance Committee.

Annex A

(informative)

Subset of ISO 646 (Table of hexadecimal and decimal values)

Table A.1 — Subset of ISO 646 (Table of hexadecimal and decimal values)

| HEX | DEC | ISO 646 | HEX | DEC | ISO 646 | HEX | DEC | ISO 646 |
|-----|-----|---------|-----|-----|---------|-----|-----|---------|
| 00 | 00 | NUL | 30 | 48 | 0 | 60 | 96 | ' |
| 01 | 01 | SOH | 31 | 49 | 1 | 61 | 97 | a |
| 02 | 02 | STX | 32 | 50 | 2 | 62 | 98 | b |
| 03 | 03 | ETX | 33 | 51 | 3 | 63 | 99 | c |
| 04 | 04 | EOT | 34 | 52 | 4 | 64 | 100 | d |
| 05 | 05 | ENQ | 35 | 53 | 5 | 65 | 101 | e |
| 06 | 06 | ACK | 36 | 54 | 6 | 66 | 102 | f |
| 07 | 07 | BEL | 37 | 55 | 7 | 67 | 103 | g |
| 08 | 08 | BS | 38 | 56 | 8 | 68 | 104 | h |
| 09 | 09 | HT | 39 | 57 | 9 | 69 | 105 | i |
| 0A | 10 | LF | 3A | 58 | : | 6A | 106 | j |
| 0B | 11 | VT | 3B | 59 | ; | 6B | 107 | k |
| 0C | 12 | FF | 3C | 60 | < | 6C | 108 | l |
| 0D | 13 | CR | 3D | 61 | = | 6D | 109 | m |
| 0E | 14 | SO | 3E | 62 | > | 6E | 110 | n |
| 0F | 15 | SI | 3F | 63 | ? | 6F | 111 | o |
| 10 | 16 | DLE | 40 | 64 | @ | 70 | 112 | p |
| 11 | 17 | DC1 | 41 | 65 | A | 71 | 113 | q |
| 12 | 18 | DC2 | 42 | 66 | B | 72 | 114 | r |
| 13 | 19 | DC3 | 43 | 67 | C | 73 | 115 | s |
| 14 | 20 | DC4 | 44 | 68 | D | 74 | 116 | t |
| 15 | 21 | NAK | 45 | 69 | E | 75 | 117 | u |
| 16 | 22 | SYN | 46 | 70 | F | 76 | 118 | v |
| 17 | 23 | ETB | 47 | 71 | G | 77 | 119 | w |
| 18 | 24 | CAN | 48 | 72 | H | 78 | 120 | x |
| 19 | 25 | EM | 49 | 73 | I | 79 | 121 | y |
| 1A | 26 | SUB | 4A | 74 | J | 7A | 122 | z |
| 1B | 27 | ESC | 4B | 75 | K | 7B | 123 | { |
| 1C | 28 | FS | 4C | 76 | L | 7C | 124 | |
| 1D | 29 | GS | 4D | 77 | M | 7D | 125 | } |
| 1E | 30 | RS | 4E | 78 | N | 7E | 126 | ~ |
| 1F | 31 | US | 4F | 79 | O | 7F | 127 | DEL |
| 20 | 32 | SP | 50 | 80 | P | | | |
| 21 | 33 | ! | 51 | 81 | Q | | | |
| 22 | 34 | " | 52 | 82 | R | | | |
| 23 | 35 | # | 53 | 83 | S | | | |
| 24 | 36 | \$ | 54 | 84 | T | | | |
| 25 | 37 | % | 55 | 85 | U | | | |
| 26 | 38 | & | 56 | 86 | V | | | |
| 27 | 39 | ' | 57 | 87 | W | | | |
| 28 | 40 | (| 58 | 88 | X | | | |
| 29 | 41 |) | 59 | 89 | Y | | | |
| 2A | 42 | * | 5A | 90 | Z | | | |
| 2B | 43 | + | 5B | 91 | [| | | |
| 2C | 44 | , | 5C | 92 | \ | | | |
| 2D | 45 | - | 5D | 93 |] | | | |
| 2E | 46 | . | 5E | 94 | ^ | | | |
| 2F | 47 | / | 5F | 95 | _ | | | |

Bibliography

- [1] ISO 9735-1, *Electronic data interchange for administration, commerce and transport (EDIFACT) — Application level syntax rules (Syntax version number: 4, Syntax release number: 1) — Part 1: Syntax rules common to all parts*
- [2] ISO/IEC 15418, *Information technology — EAN/UCC Application Identifiers and Fact Data Identifiers and Maintenance*

ISO/IEC 15434:2005(E)