Industrial UHF handheld rfid reader (Android 13)

Ultra-Long Range | Massive 9600mAh Battery | Professional Data Capture

Product Overview

This high-performance industrial grade handheld rfid reader is designed specifically for large-scale material management, intelligent warehousing, and complex logistics environments. Equipped with the latest Android 13 operating system and an efficient 8-core 2.0GHz processor, it not only provides an extremely smooth running experience, but also integrates industry-leading UHF RFID and 1D/2D barcode scanning technology.

The most significant advantage of this device is its 9600mAh ultra large capacity battery, which can provide more than 12 hours of continuous working time, completely solving the pain point of endurance for high-intensity operations. The built-in Impinj E-series chip ultra-high frequency RFID module, paired with a 4dBi circularly polarized antenna, achieves a stable reading distance of up to 20 meters and a group reading rate of up to 2000 tags per 10 seconds, significantly improving asset inventory efficiency.



Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp: +86-18025491886
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Basic information	
processor	8 core CPU ARM 4×A53 2.0GHz+4×A53 1.5GHz
Operating system	Android 13
(RAM +ROM)	3GB+32GB (standard), 4GB+64GB (optional)
Expand memory	Micro SD block, Maximum support 256GB
display screen	5.5 inch resolution ratio 720*1440
Touch screen	Industrial grade capacitive screen,Multi touch support
Rear Camera	1600W Pixel HD camera,Supports autofocus.flash lamp
front camera	500W Pixel camera (optional)
audio frequency	Built in microphone * 1 Speaker (1.2W) * 1, Earpiece * 1
prompt	Vibration prompt/LED prompt/audio prompt
keyboard	6 keys in total: 2 side scan keys, 1 side power key, volume+/- keys, and handle buttons
cassette	nano SIM card *2& nano SIM card x 1 + T_FLASH * 1
sensor	Light proximity sensor, gravity sensor;
battery	9600mAh polymer lithium battery Standby time>350 hours Working hours>10 hours (depending on usage environment) Supports 18W fast charging Charging time 3-4 hours, using standard power adapter and data cable
Charging method	Type-C charging, 5V 2A

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Communication transmission	
USB interface	Type-C USB x 1,Support OTG function
WLAN function	Dual band 2.4GHz/5GHz, supporting IEEE 802 a/b/g/n/ac protocol
Bluetooth	Support Bluetooth 2.1+EDR/3.0+HS/4.1+HS+5.0
GPS	Support GPS,Galileo,Glonass,Beidou
Wireless Wide Area Network (Data Services)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless Wide Area Network (Network Frequency)	2G:GSM(B2/B3/B5/B8) 3G:WCDMA(B1/B2/B5/B8) 4G:FDD:B1/B2/B3/B5/B7/B8 TDD:B34/B38/B39/B40/B41
UHF RFID	
UHF RFID	Ultra high frequency module, readable and writable, distance 1-20 meters Operating frequency (860-960 MHz, frequency band can be customized according to requirements) Chinese frequency: 920-925 MHz US frequency: 902-928 MHz Other frequencies: Other multinational frequency standards (customized) Protocol standards: EPC C1 GEN2/ISO18000-6C, GJB7377.1A-2018 (optional) Antenna: 4dBi circularly polarized antenna, designed using the four arm spiral principle Reading distance: 1-20m (depending on the label and actual environment)

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

	Group read rate: 2000 tags/10 seconds
Optional RFID module	Built in Impinj E-series chip ultra-high frequency Rfid module
scan engine	
Optional	Barcode, QR code scanning
Environmental parameters	
operation temperature	-20℃~55℃ *For safety reasons, do not charge in low temperature environments
storage temperature	-40℃~70℃(Without battery)
humidity	0~95%(No condensation)
Drop specifications	1.2 meters of cement ground has fallen multiple times
protection grade	IP67(Only for the host part, excluding shield and handle)
Electrostatic Discharge	±15KV(air discharge),±8KV(Contact discharge)
development support	
development language	Java
Develop API	Android standard interface
structure parameters	
Size(mm)	171mm *88mm *138mm
weight	680g
Equipment accessories	

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Standard accessories	Adapter, data cable, protective film
optional	Charging dock

Provide ODM and OEM customized services

- We work closely with our partners and can provide various one-stop customized solutions.
- Appearance customization: supports customization of product nameplates, product packaging, and promotional materials.
- Hardware customization: Supports customization of functional modules and optional hardware functions.
- Software customization: supports customization of boot interface, boot program, kernel clipping, and API interface.
- Technical support: Provide SDK development kits and application software development technical services.

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp: +86-18025491886
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.