HT600-handheld pda scanner

HT600 is a high-performance intelligent data acquisition terminal independently developed by Lianqiang Youchuang. Android 13 operating system, equipped with a high-performance 8-core 2.2GHz clock speed processor, 6-inch high-definition large screen, and 16 million camera; Standard memory 4G+64G, optional 6G+128G, barcode scanning (optional scanning head model) NFC。 IP68 protection level, strong industry adaptability, widely used in various application fields such as logistics, retail, warehousing, medical, power, one card, parking fees, government projects, etc., helping users quickly achieve information management and improve enterprise operation efficiency.



Basic Information	
processor	8-core 2.2GHz high-performance processor
operating system	Android 13
Memory(RAM+ROM)	4GB+64GB (optional 6G+128GB)
expand memory	Micro SD card, supports up to 256GB
display screen	6-inch IPS display screen resolution 720 * 1440, optional 2160X1080P
touch screen	Multi touch, can be operated with water on the screen or wearing gloves
rear camera	1600W pixel high-definition camera, supporting autofocus and flash
front camera	500W pixel camera (optional)
audio	Speaker (mono), microphone x 2, earpiece
prompt	Vibration prompt/LED prompt/audio prompt
keyboard	Silicone buttons: power button, volume+/- button, scan button x 2
booth	Nano SIM card x1/PSM card x1 (TF card)
battery	Rechargeable polymer battery (standard 3.8V 8000mAh) (low temperature -30 ℃ 7600mAh) (low temperature -40 ℃ 7000 mAh) Standby time>350 hours Working hours>12 hours (depending on the usage environment) Supports fast charging, detachable battery, and supports replacing RTC battery

	without shutting down Charging time<3 hours (using standard fast charging power adapter and data cable)
sensor	Light proximity sensor, distance sensor, gravity sensor Optional: gyroscope, electronic compass
Communication transmission	
USB port	Type-C USB x 1, Support OTG function
WLAN function	Dual band 2.4GHZ/5Ghz, supporting IEEE 802 a/b/g/n/ac protocols
Bluetooth	Supports BT 5.0, with a transmission distance of 5-10 meters
GPS	Supports GPS, Galileo, Glonass, Beidou
Wireless Wide Area Network	2G: GSM (Mobile/Unicom), CDMA (Telecom) 3G: WCDMA (China Unicom), CDMA 2000 (China Telecom), TD-SCDMA (China Mobile) 4G: TD-LTE (Mobile), FDD-LTE (China Unicom, China Telecom)
Optional configuration	
2D scanning engine	Soft solution: MD5066/Honeywell N5703/CM60 Hard solution: N660
Support 2D barcode type	PDF417,Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code,Micro QR Code, MaxiCode,Hanxin Code,etc.
Optional configuration	
NFC	Working frequency: 13.56MHz Protocol standards: Supports ISO14443A/B and 15693 protocols
Low frequency RFID (optional)	Support, 125K (distance 3-5cm)/134.2K (distance 10-17cm)
environmental parameters	
Operating Temperature	-30 ℃ to 60 ℃ *For safety reasons, please do not charge in low temperature environments
Storage temperature	-40 ℃ to 70 ℃
humidity	5% RH -95% RH (no condensation)
drop specification	Within the operating temperature range, all six sides can withstand a height of 1.8 meters 30 impacts of falling onto marble floors
Protection level	IP68
Development support	
development language	Java
Develop API	Android Standard Interface
structural parameters	
Size (mm)	169.5mm×83.2mm×18.2mm
weight	<350g (Depending on the device's functional configuration)
Equipment accessories	
standard configuration	Adapter, data cable, protective film, instruction manual, hand rope
optional	charging dock