HT600 Industrial-grade Handheld PDA Printer (Android 13)

High-performance 2D scanning | 70mm/s high-speed thermal printing | IP68 military-grade protection

Product Overview

HT600 is a ruggedized smart terminal specifically designed for high-intensity mobile work. It deeply integrates a 58mm thermal printer on the basis of traditional PDAs, supporting the printing of receipts, adhesive labels, and black labels, truly achieving a one-stop office experience of "scanning, processing, and issuing tickets" simultaneously.

Equipped with the Android 13 operating system and a 2.0GHz octa-core processor, this device ensures seamless processing of complex business logic. Its sturdy body boasts an IP68 rating (main unit) and can withstand a drop from a height of 1.5 meters, perfectly adapting to various harsh industrial environments. Equipped with an 8000mAh ultra-large capacity battery (optional) and 18W fast charging technology, it ensures ample power during long shifts, making it an ideal tool for logistics, retail, parking management, and on-site law enforcement.



Summary of Core Technical Specifications

Category Key parameters

System / Performance: Android 13 / 8-core 2.0GHz / Up to 4GB+64GB

Printing function: 58mm thermal printing / 70mm/s high speed / support for label adhesive

Display screen 6.0" IPS (720P / 1080P) / Glove & Wet Touch

Scanning engine: Optional professional 2D hardware decoding (Honeywell N5703, etc.)

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp: +86-18025491886
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Battery capacity: Max 8000mAh / 18W fast charging / supports battery removal

Protection/Weight: IP68 (main unit) / 1.5m drop resistance / weight <350g

Recognition module: NFC, LF RFID (125K/134.2K)

Key Highlights

· **Trinity, efficient operation:**

Professional printing: Equipped with a built-in 57mm thermal printer, it boasts a printing speed of 70mm/s. It not only supports regular thermal paper but also supports adhesive label printing, meeting on-site labeling needs.

Accurate measurement: Equipped with internationally renowned 2D scanning engines such as Honeywell, it easily identifies various damaged, low-quality, or screen barcodes.

Multi-dimensional collection: Integrates NFC and low-frequency RFID (125K/134.2K).

· **Robust performance and the latest system:**

Running the latest Android 13 system, it offers higher security and stronger compatibility.

Equipped with an 8-core 2.0GHz processor, it can be optionally configured with up to 6GB+128GB storage combination, ensuring smooth processing of big data without any lag.

· **Excellent industrial durability:**

IP68 protection level: The main unit is completely dustproof and waterproof.

Drop-resistant design: Capable of withstanding multiple drop impacts from a height of 1.5 meters on all six sides.

24/7 Interaction: With a 6-inch IPS HD screen, it supports touch operation with water or wearing gloves, making it unafraid of rain or extreme weather.

· **Long battery life and fast charging:**

Offers a detachable battery option of 4000/8000mAh, with a standby time of up to 750 hours.

Supports 18W PD fast charging, fully recharging in less than 3 hours.

Ideal Applications

· Logistics and Warehouse Management: On-site receipt printing, shelf adhesive label replacement, and package scanning.

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

· Smart parking and traffic police enforcement: printing of violation parking tickets, on-site ticket processing, and vehicle license recognition.

· Retail and catering: mobile cashier, mobile ordering, promotional label printing, and takeout receipt printing.

· Public utility inspection: meter reading and payment for water and electricity, asset inventory and positioning.

Basic Information	
processor	8-core 2.0GHz high-performance processor
operating system	Android 13
Memory (RAM+ROM)	3GB+32GB (optional: 4GB+64GB, 6G+128GB)
expand memory	Micro SD card, supports up to 256GB
display screen	6-inch IPS display screen resolution 1440 × 720P, optional 2160X1080P
touch screen	Multi touch, can be operated with water on the screen or wearing gloves
rear camera	1600W pixel high-definition camera, supporting autofocus and flash
front camera	500W pixel camera (optional)
audio	Speaker (mono), microphone x 2, earpiece
prompt	Vibration prompt/LED prompt/audio prompt
keyboard	Silicone buttons: power button, volume+/- button, scan button x 2
booth	Nano SIM card x1/PSM card x1 (TF card)
battery	Rechargeable polymer battery (standard 7.7V/3.85V 4000/8000mAh) Standby time>750 hours Working hours>12 hours (depending on different working conditions) Supports 18W fast charging and detachable battery RTC power down retention for 5 minutes Charging time<3 hours (using standard fast charging power adapter and data cable)
sensor	Light proximity sensor, distance sensor, gravity sensor Optional: gyroscope, electronic compass
Communication transmission	
USB port	Type-C USB x 1, Support OTG function
WLAN function	Dual band 2.4GHZ/5Ghz, supporting IEEE 802 a/b/g/n/ac protocols
Bluetooth	Supports BT 5.0, with a transmission distance of 5-10 meters
GPS	Supports GPS, Galileo, Glonass, Beidou
Wireless Wide Area Network	2G: GSM (Mobile/Unicom), CDMA (Telecom) 3G: WCDMA (China Unicom), CDMA 2000 (China Telecom), TD-SCDMA (China Mobile) 4G: TD-LTE (Mobile), FDD-LTE (China Unicom, China Telecom)
thermal printing	
Print speed	70mm/s
Printing points	384dots

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Printing paper width	57mm
Printing paper diameter	35mm
Printing paper type	Support sticker printing, thermal paper printing, and black label printing
Optional configuration	
2D scanning engine	Soft solution: MD5066/Honeywell N5703/CM60 Hard solution: N660
Support 2D barcode type	PDF417,Micro PDF417,GS1 Composite,Aztec Code,Data Matrix,QR Code,Micro QR Code, MaxiCode,Hanxin Code,etc.
Optional configuration	
NFC	Working frequency: 13.56MHz Protocol standards: Supports ISO14443A/B and 15693 protocols
Low frequency RFID (optional)	Support, 125K (distance 3-5cm)/134.2K (distance 10-17cm)
Fingerprint recognition	Support the authentication of fingerprint modules by the Ministry of Public Security
environmental parameters	
Operating Temperature	-20℃至 60℃ *For safety reasons, please do not charge in low temperature environments
Storage temperature	-40 ℃ to 70 ℃
humidity	5% RH -95% RH (no condensation)
drop specification	Within the operating temperature range, all 6 sides of the host can withstand a height of 1.5 meters (excluding the printing paper compartment)
Protection level	Host IP68 (excluding printing paper compartment)
Development support	
development language	Java
Develop API	Android Standard Interface
structural parameters	
Size (mm)	169.5×83.2×18.2mm(The host does not include a print head)
weight	＜350g （Depends on the device's functional configuration）
Equipment accessories	
Standard configuration	Adapter, data cable, protective film, instruction manual, hand rope
optional	charging dock

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.