## Y100- (5G)-10.1 inch multifunctional rugged tablet android

Y100-5G is a multifunctional rugged tablet developed independently by LQVIS. 10.1-inch high-definition large screen, equipped with high-performance processor; 5G communication 8-core 2.7GHz, WIFI, GPS, BT. Android 13 operating system, standard memory: 4GB+64GB; Optional: 6G+128G, 8G+128G, 8G+256G. Built in 10000mAh high-capacity battery with IP67 protection level. Supporting optional options: barcode, QR code scanning, NFC, Ultra high frequency RFID module, fingerprint module, RTK high-precision positioning module, night vision camera, thermal imager, UWB ranging positioning module and other modules. Strong industry adaptability, widely used in livestock breeding management, bank material management, military equipment material management, clothing inventory, warehouse management, smart factories, medical, municipal and other application fields. Help users quickly achieve information management and improve enterprise operational efficiency.



| Basic Information | |
|---|---|
| processor | UNISOC 7885（ 1*A76@2.7GHz+3*A76@2.3GHz+4*A55@2.1GHz） |
| operating system | Android 13 |
| Memory (RAM+ROM) | 4GB +64GB ； Optional: 6G+128G; 8G+128G； 8G+256G |
| Expand memory | Micro SD card, supports up to 512GB |
| display | 10.1 inches, resolution: 800 * 1280 550 nits.<br>Optional: 10.1-inch/1920 * 1200/IPS 600nits/Supports glove mode/wet hand mode |
| Touch Screen | Capacitive screen: supports multi touch and glove touch |
| Rear camera | Rear 1600W pixels support autofocus and flash |
| Front Camera | Front 500W pixel (optional) |
| audio | Main MIC * 1, noise reduction and echo cancellation * 1 |
| | Speaker (4W) * 1 |
| prompt | 2 RGB lights |
| | Vibrating motors |
| keystroke | Left: Volume +-, Scan key<br>Right side: Power on button<br>Front: 4 custom function keys |
| External interfaces | Left: TYPC-A<br>Right side: SIM card holder+TF card holder, TYPC-C |
| Booths | Nano SIM card * 2&Nano SIM card x 1+T_FLASH * 1 |
| sensor | Light proximity sensor, gravity sensor<br>optional :Compass, air pressure sensor |
| battery | 10000 mAh polymer lithium battery,<br>Standby time> 350 hours<br>Working time> 12 hours (depending on the usage environment)<br>The charging time is 3-4 hours, using the standard power adapter and data cable<br>10000 mAh + larger battery (customized). |
| Charging method | Type-C 30W PD fast charging |
| **Communication Transmission** | |
| WLAN function | 2.4/5G, 802.11a/b/g/n/ac |
| Bluetooth | BT5.0 |
| GNSS | GPS/GLONASS/Galileo/Beidou, L1 |
| Wireless WAN (Network Frequency) | 5G NR: n1/n3/n5/n8/n28/n41/n78/n79<br>LTE-FDD: B1/B3/B5/B8<br>LTE-TDD: B34/B38/B39/B40/B41<br>WCDMA: B1/B5/B8<br>GSM: B3/B8 |
| **Optional functions** | |
| Front Camera | Front 500W pixel (optional) |
| High definition and bright screen | 1920 * 1200/IPS 600nits/NTSC 72%/contrast ratio 1200:1/7H cover/10 point touch/industrial grade touch IC/support glove mode glove thickness ≥ |

| | |
|---|---|
| | 3mm/support wet hand mode |
| sensor | Compass, air pressure sensor |
| **NFC（optional）** | Operating frequency: 13.56MHz<br>Support agreement:： ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2<br>Tag standard: M1 card(S50, S70), CPU card, NFC tag, etc<br>Reading and writing distance: 1-3cm |
| **Barcode Scanning（optional）** | |
| Scan engine | E60\CM60\N1 |
| 1D Symbologies | UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc. |
| 2D Symbologies | PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch, Postal (KIX), etc. |
| **UHF RFID（optional）** | |
| Engine | module based on ImpinjE710 |
| Operating frequency | North America: 902-928MHz FCC (NA, SA)<br>Europe: 865-868MHz (ETSI)<br>China: 920-925MHz (CMIIT)<br>Full frequency range: 860-960MHz (OPEN ) |
| Protocol | EPC global UHF Class 1 Gen 2 (ISO 18000-6C) |
| Antenna | Circular polarization, 4dBi |
| Power | 1W(30dBm, +5dBm to +30dBm adjustable)<br>2W Optional ( 33dBm, for Latin America, etc.) |
| Max Read Range | Up to 15 m (open outdoors, Impinj MR6 tag) |
| Fastest Read Rate | 150+tags/sec |
| Engine（optional） | module based on Impinj E510 |
| | module based on Impinj indy R2000 |
| **fingerprint （optional ）** | One touch can obtain a complete fingerprint image,with effective pixels of 256 *360 and a resolution of 508DPIquickly and accurately identifyingfingerprint information |
| **Environmental parameters** | |
| Operating temperature | -20℃~55℃<br>*For safety reasons, do not charge in a low temperature environment |
| Storage temperature | -40°C~70°C (without battery) |
| humidity | 0~95% (no condensation) |
| Drop Specs | The 1.2-meter concrete floor fell many times |
| Ingress protection | IP67 |
| Electrostatic discharge | ±15KV (air discharge), ±8KV (contact discharge) |
| **Development support** | |
| Development language | Java |

| | |
|---|---|
| Develop APIs | Android standard interface |
| **Structural parameters** | |
| Dimensions (mm). | 290.6*182.5*18.5mm |
| Weight as standard | 980g |
| **Equipment accessories** | |
| Standard accessories | Adapters, data cables, protective films |

**Provide ODM and OEM customized services**

- We work closely with our partners and can provide various one-stop customized solutions.
- Appearance customization: supports customization of product nameplates, product packaging, and promotional materials.
- Hardware customization: Supports customization of functional modules and optional hardware functions.
- Software customization: supports customization of boot interface, boot program, kernel clipping, and API interface.
- Technical support: Provide SDK development kits and application software development technical services.