10.1-inch Professional Rugged GNSS RTK Tablet (Android 13)

Centimeter level positioning accuracy | 1408 channel full constellation tracking | 10000mAh long-lasting battery life

Product Overview

This 10.1-inch reinforced tablet is a top of the line mobile terminal designed specifically for high-precision surveying, geographic information systems (GIS), precision agriculture, and geological exploration. It perfectly integrates the smooth interaction of consumer grade tablets with professional grade RTK positioning technology, aiming to provide centimeter level real-time positioning capability in complex outdoor environments.

The device is equipped with a high-performance MT6789 eight core processor (with a maximum frequency of 2.2GHz) and the latest Android 13 operating system, which can smoothly run various complex professional surveying software. Its built-in high-performance RTK module has 1408 channels and fully supports GPS, Beidou, Galileo, and GLONASS constellation tracking. In RTK mode, it can achieve a horizontal positioning accuracy of 2.5cm. Equipped with a 10000mAh large capacity battery and 30W PD fast charging technology, it ensures the power continuity of long-distance field operations.



Key Highlights

Centimeter level high-precision positioning:

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Multi constellation tracking: Built in 1408 channel GNSS chip, supporting GPS (L1C/A, L2C, L5), BDS (B1, B2, B2a, B31), Galileo (E1, E5a), and GLONASS (L1, L2).

Rapid convergence: RTK initialization time<10 seconds, providing high-precision horizontal positioning of 1.5cm+1ppm.

Professional interface: The top of the body is equipped with a dedicated RTK antenna interface, which can be connected to an external measurement antenna to obtain better signals.

Excellent processing performance:

Equipped with a 6nm MT6789 processor, it comes standard with 6GB RAM and 128GB ROM (up to 8GB+256GB optional), and supports 512GB TF card expansion.

Whether dealing with large-scale base maps or running 3D models, it can respond quickly.

Long lasting battery life and fast charging:

Equipped with a 10000mAh ultra large capacity polymer lithium battery, the working time exceeds 10 hours.

Supports 30W PD fast charging, which can be fully charged in just 2-3 hours, significantly reducing waiting time.

Durable and sturdy industrial design:

Protection level: It has IP67 dust and water protection capability, and is not afraid of rain, mud, and dust.

Drop resistance: Passed multiple 1-meter cement floor drop tests.

Interaction optimization: 10.1-inch high brightness screen supports glove touch; There are 4 custom function keys on the front for engineers to quickly launch measurement applications.

Comprehensive connection and collection:

Supports 4G full network, dual band WiFi, Bluetooth 5.0 to ensure real-time data transmission.

Equipped with a 1600W pixel rear high-definition camera (supporting autofocus and flash) for easy on-site image retention.

Typical Application Scenarios (Ideal Applications)

Land Surveying&Mapping

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Precision Agriculture Navigation

Digital Construction and Utility Inspection

GIS Data Acquisition

· Geological Survey and Disaster Monitoring

Technical Specifications Summary

· System/chip: Android 13/MT6789 8-core 2.2GHz

Screen: 10.1 inches (800x1280 or 1200x1920) with support for multi-point/glove touch

· Positioning accuracy: RTK 1.5cm (H)/GNSS 2.5m CEP

· Battery/Charging: 10000mAh/30W PD Fast Charge

· Protection level: IP68/1m Drop Resistance

· Size/Weight: 290.6 * 182.5 * 18.5mm/980g

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp: +86-18025491886
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Basic Information	
processor	MT6789 (2 Arm) ® Cortex-A76 core, operating frequency of 2.2GHz, 6 Arm ® Cortex-A55 core, operating at a frequency of 2.0GHz
operating system	Android 13
RAM+ROM	6G+128G Optional: 8G+128G ; 8G+256G
Expand memory	Micro SD card, supports up to 512GB
display	10.1 inches, resolution: 800 * 1280 550 nits. Optional: 10.1-inch/1920 * 1200/IPS 600nits/Supports glove mode/wet hand mode
Touch Screen	Capacitive screen: supports multi touch, glove touch
Rear camera	Rear 1600W pixels support autofocus and flash
Front Camera	Front 500W pixel (optional)
audio	Main MIC*1, Noise Reduction and Echo Cancellation*1
	Speaker (4W) * 1
prompt	2 RGB lights
	Vibrating motors
keystroke	Left: Volume +-, Scan key Right side: Power on button Front: 4 custom function keys
External interfaces	Left: TYPC-A Right side: SIM card holder + TF card holder, TYPC-C Top: RTK antenna interface
Booths	Nano SIM card * 2&Nano SIM card x 1+T_FLASH * 1
sensor	Light sensing+distance, gravity sensor+6-axis gyroscope optional： Compass, air pressure sensor
battery	10000 mAh polymer lithium battery, Standby time> 350 hours Working time> 10 hours (depending on the usage environment)

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Charging method	Type-C 30W PD fast charging The charging time is 2-3 hours, using the standard power adapter and data cable
Communication Transmission	
WLAN function	Dual-band 2.4GHZ/5Ghz, support IEEE 802 a/b/g/n/ac protocol
Bluetooth	Supports Bluetooth 2.1+EDR/3.0+HS/4.1+HS+5.0
GNSS	Supports GPS, Galileo, Glonass, Beidou
Wireless WAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless WAN (Network Frequency)	2G：GSM（B2/B3/B5/B8） 3G：WCDMA（B1/B2/B5/B8） 4G：FDD:B1/B2/B3/B5/B7/B8/B20/B25/B26/B28 TDD:B34/B38/B39/B40/B41
RTK	
parameter	performance indicators
GNSS tracking channel	1408
GNSS receiving frequency point	GPS/QZSS: L1C/A, L2C, L5
	BDS: B1, B2, B2a, B31.
	Galileo: E1. E5a
	GLONASS: L1,L2.
Data update rate	PVT maximum value 10Hz
	RTK maximum value 5Hz
positioning accuracy	GNSS 2.5m CEP
	D-GNSS <1.0m CEP
	RTK 1.5cm+ 1ppm(H)
Speed and time accuracy	GNSS 0.1m/s CEP
	1PPS 20ns
Time of first	Hot start for 2 seconds

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

positioning (TTFF)	Cold start for 24 seconds
	RTK convergence time<10s
sensitivity	Cold start -148dBm
	Hot start -158dBm
	Re capture -160dBm
	Tracking&Navigation -1 62 dBm
Application limits	Speed 515 meters per second
	Height 18000 meters
Optional functions	
NFC	Operating frequency: 13.56MHz agreement ：ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2 Tag standard: M1 card(S50, S70), CPU card, NFC tag, etc Reading and writing distance: 1-3cm
Environmental parameters	
Operating temperature	-20℃~55℃ *For safety reasons, do not charge in a low temperature environment
Storage temperature	-40℃~70℃ (without battery)
humidity	0~95% (no condensation)
Drop Specs	The 1-meter concrete floor fell many times
Ingress protection	IP68
Electrostatic discharge	±15KV (air discharge), ±8KV (contact discharge)
Development support	
Development language	Java
Develop APIs	Android standard interface
Structural parameters	

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp: +86-18025491886
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Dimensions (mm).	290.6*182.5*18.5mm
Weight as standard	980g
Equipment accessories	
Standard accessories	Adapters, data cables, protective films

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.