Rugged Tablet with GNSS RTK-High-Precision GNSS Positioning

The Y100-RTK (5G) is an 5G GNSS RTK Rugged Tablets from Iqvis. 10.1-inch high-definition large screen, equipped with a high-performance 8-core 2.7GHz processor, Android 13 operating system, and 5G communication. Standard configuration includes 4G+64G memory, optional options: 6G+128G, 8G+128G, 8G+256G. Built in 10000mAh high-capacity battery with IP67 protection level.

Integrated high-sensitivity GNSS module, built-in RTK algorithm, paired with four arm spiral antenna, supporting centimeter level accuracy. Support BDS, GPS, GALILEQ, GLONASS, QZSS full system GNSS.

Strong industry adaptability, widely used in application fields such as land, electricity, forestry, environmental protection, highways, railways, ship monitoring, oil and gas pipelines, mining exploration, etc.



Basic Information	
processor	UNISOC 7885（ 1*A76@2.7GHz+3*A76@2.3GHz+4*A55@2.1GHz）
operating system	Android 13
RAM+ROM	4GB +64GB ； Optional: 6G+128G; 8G+128G； 8G+256G
Expand memory	Micro SD card, supports up to 512GB
display	10.1 inches, resolution: 800 * 1280 550 nits. Optional: 10.1-inch/1920 * 1200/IPS 600nits/Supports glove mode/wet hand mode
Touch Screen	Capacitive screen: supports multi touch, glove touch
Rear camera	Rear 1600W pixels support autofocus and flash
Front Camera	Front 500W pixel (optional)
audio	Main MIC*1, Noise Reduction and Echo Cancellation*1
	Speaker (4W) * 1
prompt	2 RGB lights
	Vibrating motors
keystroke	Left: Volume +-, Scan key Right side: Power on button Front: 4 custom function keys
External interfaces	Left: TYPC-A Right side: SIM card holder + TF card holder, TYPC-C Top: PSAM card holder (optional), RTK antenna interface (optional) Underside: 4PIN charging interface Back: Expansion interface (customized)
Booths	Nano SIM card * 2&Nano SIM card x 1+T_FLASH * 1
sensor	Light proximity sensor, gravity sensor optional :Compass, air pressure sensor
battery	10000 mAh polymer lithium battery, Standby time> 350 hours Working time> 12 hours (depending on the usage environment) The charging time is 3-4 hours, using the standard power adapter and data cable 10000 mAh + larger battery (customized).
Charging method	Type-C 30W PD fast charging
Communication Transmission	
WLAN function	2.4/5G, 802.11a/b/g/n/ac
Bluetooth	BT5.0
GNSS	GPS/GLONASS/Galileo/Beidou, L1
Wireless WAN (Network Frequency)	5G NR: n1/n3/n5/n8/n28/n41/n78/n79 LTE-FDD: B1/B3/B5/B8 LTE-TDD: B34/B38/B39/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8
RTK	
parameter	performance indicators

GNSS tracking channel	1408
GNSS receiving frequency point	GPS/QZSS: L1C/A, L2C, L5
	BDS: B1, B2, B2a, B31.
	Galileo: E1. E5a
	GLONASS: L1,L2.
Data update rate	PVT maximum value 10Hz
	RTK maximum value 5Hz
positioning accuracy	GNSS 2.5m CEP
	D-GNSS <1.0m CEP
	RTK 1.5cm+ 1ppm(H)
Speed and time accuracy	GNSS 0.1m/s CEP
	1PPS 20ns
Time of first positioning (TTFF)	Hot start for 2 seconds
	Cold start for 24 seconds
	RTK convergence time<10s
sensitivity	Cold start -148dBm
	Hot start -158dBm
	Re capture -160dBm
	Tracking&Navigation -1 62 dBm
Application limits	Speed 515 meters per second
	Height 18000 meters
Optional functions	
NFC	Operating frequency: 13.56MHz agreement ： ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2 Tag standard: M1 card(S50, S70), CPU card, NFC tag, etc Reading and writing distance: 1-3cm
Environmental parameters	
Operating temperature	-20℃~55℃ *For safety reasons, do not charge in a low temperature environment
Storage temperature	-40°C~70°C (without battery)
humidity	0~95% (no condensation)
Drop Specs	The 1.2-meter concrete floor fell many times
Ingress protection	IP67
Electrostatic discharge	±15KV (air discharge), ±8KV (contact discharge)
Development support	
Development language	Java
Develop APIs	Android standard interface
Structural parameters	
Dimensions (mm).	290.6*182.5*18.5mm

Weight as standard	980g
Equipment accessories	
Standard accessories	Adapters, data cables, protective films

Provide ODM and OEM customized services

- We work closely with our partners and can provide various one-stop customized solutions.
- Appearance customization: supports customization of product nameplates, product packaging, and promotional materials.
- Hardware customization: Supports customization of functional modules and optional hardware functions.
- Software customization: supports customization of boot interface, boot program, kernel clipping, and API interface.
- Technical support: Provide SDK development kits and application software development technical services.