10.1-inch RFID Rugged Tablet

Equipped with Impinj ® E-series Core | Powerful Eight Core MT6789 | 10 meter Ultra Long Distance RFID Acquisition

Product Overview

The Y100 10.1-inch reinforced RFID tablet is a mobile workstation designed specifically for extremely harsh work environments. It not only has the smooth interaction of a consumer grade tablet, but also has industrial grade durability. The core is equipped with an MT6789 (Helio G99 level) eight core processor, combined with the latest Android 16 operating system, which can easily handle high-intensity industrial software operation and massive data concurrency.

The core competitive advantage of this device lies in its professional RFID reading and writing capabilities. Optional Impinj ® The E-series chip (performance benchmark) achieves outdoor ultra long distance reading of up to 10 meters, with a reading speed of over 150 tags per second. Combined with a 10000mAh ultra large capacity battery and 30W PD fast charging, it can provide uninterrupted power support in high-intensity asset inventory and warehouse
management.



Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Basic Information	
processor	MT6789 (2 Arm) ® Cortex-A76 core, operating frequency of 2.2GHz, 6 Arm ® Cortex-A55 core, operating at a frequency of 2.0GHz
operating system	Android 16
Memory (RAM+ROM)	8G+128G Optional:8G+256G
Expand memory	Micro SD card, supports up to 1TB
display	10.1 inches, resolution: 800 * 1280550 nits. Optional: 10.1-inch/1920 * 1200/IPS 600nits/Supports glove mode/wet hand mode
Touch Screen	Capacitive screen: supports multi touch, glove touch
Rear camera	Rear 1600W pixels support autofocus and flash
Front Camera	Front 500W pixel (optional)
audio	Main MIC*1
	Speaker (4W) * 1
prompt	2 RGB lights
	Vibrating motors
keystroke	Left: Volume +-, Scan key Right side: Power on button
External interfaces	Left: TYPC-A*1 Right side: SIM card holder + TF card holder, TYPC-C*1
sensor	Light sensing+distance, gravity sensor+6-axis gyroscope Optional: Compass, air pressure sensor
battery	10000 mAh polymer lithium battery, Standby time> 350 hours

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

	Working time> 10 hours (depending on the usage environment)
Charging method	Type-C 30W PD fast charging The charging time is 2-3 hours, using the standard power adapter and data cable
Communication Transmission	
WLAN function	Dual-band 2.4GHZ/5Ghz, support IEEE 802 a/b/g/n/ac protocol
Bluetooth	Supports Bluetooth 2.1+EDR/3.0+HS/4.1+HS+5.0
GNSS	Supports GPS, Galileo, Glonass, Beidou
Wireless WAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless WAN (Network Frequency)	2G：GSM（B2/B3/B5/B8） 3G：WCDMA（B1/B2/B5/B8） 4G：FDD:B1/B2/B3/B5/B7/B8/B20/B25/B26/B28 TDD:B34/B38/B39/B40/B41
UHF RFID	
Engine	module based on lmpinjE710
	module based on lmpinj E510
	module based on lmpinj indy R2000
Operating frequency	North America: 902-928MHz FCC (NA, SA) Europe: 865-868MHz (ETSI) China: 920-925MHz (CMIIT) Full frequency range: 860-960MHz (OPEN)
Protocol	EPC global UHF Class 1 Gen 2 (ISO 18000-6C)
Antenna	Circular polarization, 4dBi
Power	1W(30dBm, +5dBm to +30dBm adjustable)

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

	2W Optional (33dBm, for Latin America, etc.)
Max Read Range	Up to 10 m (open outdoors, lmpinj MR6 tag)
Fastest Read Rate	150+tags/sec
Optional functions	
Barcode Scanning（optional）	
Scan engine	E60\CM60\N1
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch, Postal (KIX), etc.
NFC（optional）	
NFC	Operating frequency: 13.56MHz Support agreement:： ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2 Tag standard: M1 card(S50, S70), CPU card, NFC tag, etc Reading and writing distance: 1-3cm
Environmental parameters	
Operating temperature	-20℃~55℃ *For safety reasons, do not charge in a low temperature environment
Storage temperature	-40°C~70°C (without battery)
humidity	0~95% (no condensation)
Drop Specs	The 1-meter concrete floor fell many times
Ingress protection	IP67
Electrostatic discharge	±15KV (air discharge), ±8KV (contact discharge)

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Development support	
Development language	Java
Develop APIs	Android standard interface
Structural parameters	
Dimensions (mm).	290.6*182.5*18.5mm
Weight as standard	980g
Equipment accessories	
Standard accessories	Adapters, data cables, protective films

Due to irregular product updates, if there are any changes to the content, the actual shipment shall prevail.

Provide ODM and OEM customized services

- We work closely with our partners and can provide various one-stop customized solutions.
- Appearance customization: supports customization of product nameplates, product packaging, and promotional materials.
- Hardware customization: Supports customization of functional modules and optional hardware functions.
- Software customization: supports customization of boot interface, boot program, kernel clipping, and API interface.
- Technical support: Provide SDK development kits and application software development technical services.

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.