10.1-inch Android rugged tablet (Android 16)

Powerful eight-core performance | 1D/2D barcode scanning | Ultimate UHF RFID reading and writing | 10000 mAh large-capacity battery life

Product Overview

This 10.1-inch Android rugged tablet is a versatile mobile terminal designed for extremely harsh industrial environments. It is equipped with a high-performance MT6789 eight-core processor (with a maximum frequency of 2.2 GHz) and the Android 16 operating system, providing smooth computing support for complex industrial applications. The device is equipped with a 10000 mAh ultra-large capacity polymer lithium battery and supports 30W PD fast charging, ensuring excellent endurance in outdoor or long-shift operations.

The most prominent feature of this tablet is its powerful data collection capability. It not only supports optional high-performance 1D/2D barcode scanning but also optional Built in Impinj E-series chip ultra-high frequency Rfid module, achieving ultra long distance reading of up to 15 meters and group reading efficiency of processing more than 1500 labels every 10 seconds. Its IP68 protection level and anti drop design make it an ideal tool for logistics warehousing, asset management, power inspection, outdoor surveying and other
fields.



© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Basic Information	
processor	MT6789 (2 Arm) ® Cortex-A76 core, operating frequency of 2.2GHz, 6 Arm ® Cortex-A55 core, operating at a frequency of 2.0GHz
operating system	Android 16
Memory	8G+128G Optional: 8G+256G
Expand memory	Micro SD card, supports up to 1TB
display	10.1 inches, resolution: 800 * 1280 550 nits. Optional: 10.1-inch/1920 * 1200/IPS 600nits/Supports glove mode/wet hand mode
Touch Screen	Capacitive screen: supports multi touch, glove touch
Rear camera	Rear 1600W pixels support autofocus and flash
Front Camera	Front 500W pixel (optional)
audio	Main MIC*1, Noise Reduction and Echo Cancellation*1
	Speaker (4W) * 1
prompt	2 RGB lights
	Vibrating motors
keystroke	Left: Volume +-, Scan key Right side: Power on button Front: 4 custom function keys
usb	TYPC-A*1 TYPC-C *1 (USB 2.0 OTG)
Booths	Nano SIM card * 2&Nano SIM card x 1+T_FLASH * 1
sensor	Light sensing+distance, gravity sensor+6-axis gyroscope optional： Compass, air pressure sensor

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

battery	10000 mAh polymer lithium battery Standby time> 350 hours Working time> 10 hours (depending on the usage environment)
Charging method	Type-C 30W PD fast charging The charging time is 2-3 hours, using the standard power adapter and data cable
Communication Transmission	
WLAN function	Wi- Fi 5（802.11 a/b/g/n/ac，2.4G+5G）
Bluetooth	Bluetooth 5.2
GNSS	Supports GPS, Galileo, Glonass, Beidou
Wireless WAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
Wireless WAN (Network Frequency)	2G:GSM (B2/B3/B5/B8) 3G:WCDMA(B1/B2/B5/B8) 4G:FDD:B1/B2/B3/B5/B7/B8/B20/B25/B26/B28 TDD:B34/B38/B39/B40/B41
Optional functions	
Barcode Scanning	1D code, 2D code scanning head
NFC	Operating frequency: 13.56MHz Supported Protocols:ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2 Tag standard: M1 card(S50, S70), CPU card, NFC tag, etc Reading and writing distance: 1-3cm
UHF RFID	Built in Impinj E-series chip ultra-high frequency Rfid module North America: 902-928MHz FCC (NA, SA) Europe: 865-868MHz (ETSI) China: 920-925MHz (CMIIT) Full frequency range: 860-960MHz (OPEN)

© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

	EPC global UHF Class 1 Gen 2 (ISO 18000-6C) Antenna:Circular polarization, 4dBi Up to 15 m (open outdoors, lmpinj MR6 tag) 1500+tags/10sec
Fingerprint module	FAP20 capacitive fingerprint module
Environmental parameters	
Operating temperature	-20°C~55°C *For safety reasons, do not charge in a low temperature environment
Storage temperature	-40°C~70°C (without battery)
humidity	0~95% (no condensation)
Drop Specs	The 1.2 meter concrete floor fell many times
Ingress protection	IP68
Electrostatic discharge	±15KV (air discharge), ±8KV (contact discharge)
Development support	
Development language	Java
Develop APIs	Android standard interface
Structural parameters	
Dimensions (mm).	290.6*182.5*18.5mm
Weight as standard	980g
Equipment accessories	
Standard accessories	Adapters, data cables, protective films

Due to irregular product updates, if there are any changes to the content, the actual shipment shall prevail.

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.

Provide ODM and OEM customized services

- We work closely with our partners and can provide various one-stop customized solutions.
- Appearance customization: supports customization of product nameplates, product packaging, and promotional materials.
- Hardware customization: Supports customization of functional modules and optional hardware functions.
- Software customization: supports customization of boot interface, boot program, kernel clipping, and API interface.
- Technical support: Provide SDK development kits and application software development technical services.

Website: https://www.lqvis.com/ Email: info@lqvis.com Tel/WhatsApp/WeChat: +86 13418456718
Address: 307 Runhui Business Center, No. 1001 Xinqu Avenue, Longhua District, Shenzhen
© 2026 Shenzhen Lianqiang Youchuang Information Technology Co., Ltd. All rights reserved.