

# Bayesian Optimization for Hyperparameter Optimization

## Introduction to Bayesian Optimization

Bernd Bischl   Frank Hutter   Lars Kotthoff  
Marius Lindauer   Joaquin Vanschoren

# Blackbox Optimization for Hyperparameter Optimization

- Consider the **global optimization problem** of finding:

$$\lambda^* \in \arg \min_{\lambda \in \Lambda} f(\lambda)$$

- In the most general form, function  $f$  is a **blackbox function**:

$$\lambda \rightarrow \blacksquare \rightarrow f(\lambda)$$

- ▶ Only mode of interaction with  $f$ : querying  $f$ 's value at a given  $\lambda$
- ▶ Function  $f$  may not be available in closed form, not differentiable, noisy, etc.

# Blackbox Optimization for Hyperparameter Optimization

- Consider the **global optimization problem** of finding:

$$\lambda^* \in \arg \min_{\lambda \in \Lambda} f(\lambda)$$

- In the most general form, function  $f$  is a **blackbox function**:

$$\lambda \rightarrow \blacksquare \rightarrow f(\lambda)$$

- ▶ Only mode of interaction with  $f$ : querying  $f$ 's value at a given  $\lambda$
  - ▶ Function  $f$  may not be available in closed form, not differentiable, noisy, etc.
- Today, we'll discuss a **Bayesian** approach for solving such blackbox optimization problems

# Blackbox Optimization for Hyperparameter Optimization

- Consider the **global optimization problem** of finding:

$$\lambda^* \in \arg \min_{\lambda \in \Lambda} f(\lambda)$$

- In the most general form, function  $f$  is a **blackbox function**:

$$\lambda \rightarrow \blacksquare \rightarrow f(\lambda)$$

- Only mode of interaction with  $f$ : querying  $f$ 's value at a given  $\lambda$
  - Function  $f$  may not be available in closed form, not differentiable, noisy, etc.
- Today, we'll discuss a **Bayesian** approach for solving such blackbox optimization problems
- Blackbox optimization can be used for hyperparameter optimization (HPO)
  - Define  $f(\lambda) := \mathcal{L}(\mathcal{A}_\lambda, \mathcal{D}_{train}, \mathcal{D}_{valid})$

# Blackbox Optimization for Hyperparameter Optimization

- Consider the **global optimization problem** of finding:


$$\lambda^* \in \arg \min_{\lambda \in \Lambda} f(\lambda)$$

- In the most general form, function  $f$  is a **blackbox function**:


$$\lambda \rightarrow \blacksquare \rightarrow f(\lambda)$$

- ▶ Only mode of interaction with  $f$ : querying  $f$ 's value at a given  $\lambda$
  - ▶ Function  $f$  may not be available in closed form, not differentiable, noisy, etc.
- Today, we'll discuss a **Bayesian** approach for solving such blackbox optimization problems
- Blackbox optimization can be used for hyperparameter optimization (HPO)
  - ▶ Define  $f(\lambda) := \mathcal{L}(\mathcal{A}_\lambda, \mathcal{D}_{train}, \mathcal{D}_{valid})$
  - ▶ Note: for formulations of HPO that go beyond blackbox optimization, see next lecture


# Bayesian Optimization of a blackbox function in a nutshell



# Bayesian Optimization of a blackbox function in a nutshell




# Bayesian Optimization of a blackbox function in a nutshell






# Bayesian Optimization of a blackbox function in a nutshell



# Bayesian Optimization of a blackbox function in a nutshell

## General approach


- Fit a **probabilistic model** to the collected function samples  $\langle \lambda, c(\lambda) \rangle$
- Use the model to guide optimization, trading off **exploration vs exploitation**



# Bayesian Optimization of a blackbox function in a nutshell

## General approach


- Fit a **probabilistic model** to the collected function samples  $\langle \lambda, c(\lambda) \rangle$
- Use the model to guide optimization, trading off **exploration vs exploitation**



# Bayesian Optimization of a blackbox function in a nutshell

## General approach

- Fit a **probabilistic model** to the collected function samples  $\langle \lambda, c(\lambda) \rangle$
- Use the model to guide optimization, trading off **exploration vs exploitation**



# Bayesian Optimization of a blackbox function in a nutshell


## General approach

- Fit a **probabilistic model** to the collected function samples  $\langle \lambda, c(\lambda) \rangle$
- Use the model to guide optimization, trading off **exploration vs exploitation**

## Popular approach in the statistics literature since Mockus et al. [1978]

- Efficient in **#function evaluations**
- Works when objective is **nonconvex**, **noisy**, has **unknown derivatives**, etc.
- Recent **convergence** results

[Srinivas et al. 2009; Bull et al. 2011; de Freitas et al. 2012; Kawaguchi et al. 2015]



# Bayesian Optimization: Pseudocode

---

BO loop

---

**Require:** Search space  $\Lambda$ , cost function  $c$ , acquisition function  $u$ , predictive model  $\hat{c}$ , maximal number of function evaluations  $T$

**Result :** Best configuration  $\hat{\lambda}$  (according to  $\mathcal{D}$  or  $\hat{c}$ )

- 1 Initialize data  $\mathcal{D}^{(0)}$  with initial observations
  - 2 **for**  $t = 1$  **to**  $T$  **do**
  - 3     Fit predictive model  $\hat{c}^{(t)}$  on  $\mathcal{D}^{(t-1)}$
  - 4     Select next query point:  $\lambda^{(t)} \in \arg \max_{\lambda \in \Lambda} u(\lambda; \mathcal{D}^{(t-1)}, \hat{c}^{(t)})$
  - 5     Query  $c(\lambda^{(t)})$
  - 6     Update data:  $\mathcal{D}^{(t)} \leftarrow \mathcal{D}^{(t-1)} \cup \{(\lambda^{(t)}, c(\lambda^{(t)}))\}$
-

# Bayesian Optimization: Origin of the Name

- Bayesian optimization uses Bayes' theorem:

$$P(A|B) = \frac{P(B|A) \times P(A)}{P(B)} \propto P(B|A) \times P(A)$$

- Bayesian optimization uses this to compute a posterior over functions:

$$P(f|\mathcal{D}_{1:t}) \propto P(\mathcal{D}_{1:t}|f) \times P(f), \quad \text{where } \mathcal{D}_{1:t} = \{\boldsymbol{\lambda}_{1:t}, c(\boldsymbol{\lambda}_{1:t})\}$$

# Bayesian Optimization: Origin of the Name

- Bayesian optimization uses Bayes' theorem:

$$P(A|B) = \frac{P(B|A) \times P(A)}{P(B)} \propto P(B|A) \times P(A)$$

- Bayesian optimization uses this to compute a posterior over functions:

$$P(f|\mathcal{D}_{1:t}) \propto P(\mathcal{D}_{1:t}|f) \times P(f), \quad \text{where } \mathcal{D}_{1:t} = \{\boldsymbol{\lambda}_{1:t}, c(\boldsymbol{\lambda}_{1:t})\}$$

- Meaning of the individual terms:
  - ▶  $P(f)$  is the prior over functions, which represents our belief about the space of possible objective functions before we see any data
  - ▶  $\mathcal{D}_{1:t}$  is the data (or observations, evidence)
  - ▶  $P(\mathcal{D}_{1:t}|f)$  is the likelihood of the data given a function
  - ▶  $P(f|\mathcal{D}_{1:t})$  is the posterior probability over functions given the data



# Bayesian Optimization: Advantages and Disadvantages

## Advantages

- Sample efficient
- Can handle noise
- Native incorporation of priors
- Does not require gradients
- Theoretical guarantees

# Bayesian Optimization: Advantages and Disadvantages

## Advantages

- Sample efficient
- Can handle noise
- Native incorporation of priors
- Does not require gradients
- Theoretical guarantees

## Disadvantages

- Overhead because of model training in each iteration
- Crucially relies on robust surrogate model
- Inherently sequential (in its basic form)

# Learning Goals of this Lecture

After this lecture, students can ...

- Explain the basics of Bayesian optimization
- Derive [simple acquisition functions](#)
- Describe [advanced acquisition functions](#)
- Describe possible [surrogate models](#) and their pros and cons
- Discuss the [limits of Bayesian optimization](#) and extensions to tackle these
- Describe the [alternative Bayesian optimization approach of TPE](#)
- Discuss [success stories](#) of Bayesian optimization