

# Policy Evaluation

## Summary: Policy Evaluation

Marius Lindauer



Leibniz  
Universität  
Hannover



Winter Term 2021

# Bias/Variance of Model-free Policy Evaluation Algorithms

- ▶ Return  $G_t$  is an unbiased estimate of  $V^\pi(s_t)$
- ▶ TD target  $[r_t + \gamma V^\pi(s_{t+1})]$  is biased estimate of  $V^\pi(s)$
- ▶ But often TD much lower variance than a single return  $G_t$ 
  - ▶ MC: Return function of multi-step sequence of random actions, states & rewards
  - ▶ TD target only has one random action, reward and next state


# Bias/Variance of Model-free Policy Evaluation Algorithms

- ▶ Return  $G_t$  is an unbiased estimate of  $V^\pi(s_t)$
- ▶ TD target  $[r_t + \gamma V^\pi(s_{t+1})]$  is biased estimate of  $V^\pi(s)$
- ▶ But often TD much lower variance than a single return  $G_t$ 
  - ▶ MC: Return function of multi-step sequence of random actions, states & rewards
  - ▶ TD target only has one random action, reward and next state
- ▶ MC:
  - ▶ Unbiased (for first visit MC)
  - ▶ High variance
  - ▶ Consistent (converges to true) even with function approximation

# Bias/Variance of Model-free Policy Evaluation Algorithms

- ▶ Return  $G_t$  is an unbiased estimate of  $V^\pi(s_t)$
- ▶ TD target  $[r_t + \gamma V^\pi(s_{t+1})]$  is biased estimate of  $V^\pi(s)$
- ▶ But often TD much lower variance than a single return  $G_t$ 
  - ▶ MC: Return function of multi-step sequence of random actions, states & rewards
  - ▶ TD target only has one random action, reward and next state
- ▶ MC:
  - ▶ Unbiased (for first visit MC)
  - ▶ High variance
  - ▶ Consistent (converges to true) even with function approximation
- ▶ TD
  - ▶ Some bias
  - ▶ Lower variance
  - ▶ TD(0) converges to true value with tabular representation
  - ▶ TD(0) does not always converge with function approximation

## AB Example [Sutton & Barto, 2018]



- ▶ Two states  $A, B$  with  $\gamma = 1$
- ▶ Given 8 episodes of experience:
  - ▶  $A, 0, B, 0$
  - ▶  $B, 1$  (observed 6 times)
  - ▶  $B, 0$
- ▶ Under batch (offline) solution for this finite set of observations, what do MC and TD(0) converge to?
- ▶ Imagine run TD updates over data infinite number of times?

## AB Example [Sutton & Barto, 2018]

- ▶ Given 8 episodes of experience:
  - ▶  $A, 0, B, 0$
  - ▶  $B, 1$  (observed 6 times)
  - ▶  $B, 0$
- ▶ For  $B$ :
  - ▶ MC:  $V(B) = \frac{6}{8} = 0.75$
  - ▶ TD:  $V(B) = \frac{6}{8} = 0.75$

## AB Example [Sutton & Barto, 2018]

- ▶ Given 8 episodes of experience:
  - ▶  $A, 0, B, 0$
  - ▶  $B, 1$  (observed 6 times)
  - ▶  $B, 0$
- ▶ For  $B$ :
  - ▶ MC:  $V(B) = \frac{6}{8} = 0.75$
  - ▶ TD:  $V(B) = \frac{6}{8} = 0.75$
- ▶ For  $A$ :
  - ▶ MC: only one episode with  $A \rightsquigarrow V(A) = 0$
  - ▶ TD: bootstraps from  $V(B) \rightsquigarrow V(A) = 0.75$

$$V^\pi(s) = V^\pi(s) + \alpha(\underbrace{[r_t + \gamma V^\pi(s_{t+1})]}_{\text{TD target}} - V^\pi(s))$$

- ~ Monte Carlo in batch setting converges to minimal **MSE** (mean squared error)
- ~ TD(0) converges to DP policy  $V^\pi$  for the MDP with the **maximum likelihood model estimates**

# Efficiency

- ▶ Data efficiency & Computational efficiency
- ▶ In simplest TD, use  $(s, a, r, s')$  once to update  $V(s)$ 
  - ▶  $O(1)$  operation per update
  - ▶ In an episode of length  $L$ ,  $O(L)$
- ▶ In MC have to wait till episode finishes, then also  $O(L)$
- ▶ MC can be more data efficient than simple TD in non-Markov domains
- ▶ TD can exploit Markov structure  $\leadsto$  leveraging this is helpful



# Summary: Policy Evaluation

Estimating the expected return of a particular policy if don't have access to true MDP models.  
Example: evaluating average purchases per session of new product recommendation system

- ▶ Dynamic Programming
- ▶ Monte Carlo policy evaluation
  - ▶ Policy evaluation when we don't have a model of how the world works
- ▶ Temporal Difference (TD)
- ▶ Metrics to evaluate and compare algorithms
  - ▶ Robustness to Markov assumption
  - ▶ Bias/variance characteristics
  - ▶ Data efficiency
  - ▶ Computational efficiency