SEGMENTS

ID	CARRIER	FROM	TO	CABLE	L mm	END A	END B
W20b	B2-CASS	P1	back-right corner	4 x 18 AWG (2 per pole), Class 2	920	Mini-Fit Jr 10-way plug (with W24)	Mini-Fit Jr 10-way receptacle (with W24), tail through the corner slot S-CNR
W20c	R1-CASS	P2 (corner, in R1-CASS)	the column joint P8	4 x 18 AWG (2 per pole), Class 2	1060	Mini-Fit Jr 10-way plug (with W24) (mated in P2 through the felt slot FS-CNR)	Mini-Fit Jr 10-way receptacle (with W24) in P8 behind the column, mated with W20d
W30b	B2-CASS	P1	back-right corner	4 x 16 AWG (2 per pole), Class 2	920	Mini-Fit Jr 4-way plug	Mini-Fit Jr 4-way receptacle, tail through the corner slot S-CNR
W30c	R1-CASS	P2 (corner, in R1-CASS)	kit drop P3-KIT	4 x 16 AWG (2 per pole), Class 2	1050	Mini-Fit Jr 4-way plug (mated in P2 through the felt slot FS-CNR)	Mini-Fit Jr 4-way receptacle, capped with an empty plug housing (the kit outlet: one 24 V Class 2 feed, two pins per pole, 5 A fuse, 60 W peak)
W24b	B2-CASS	P1	back-right corner	6 x 24 AWG screened, Class 2	920	shares W20's 10-way plug	shares W20's 10-way receptacle, tail through the corner slot S-CNR
W24c	R1-CASS	P2 (corner, in R1-CASS)	the column joint P8	6 x 24 AWG screened, Class 2	1060	shares W20's 10-way plug (mated in P2 through the felt slot FS-CNR)	shares W20's 10-way receptacle
W31b	B2-CASS	P1	back-right corner	Cat6 U/UTP	920	RJ45 inline coupler	RJ45 inline coupler, tail through the corner slot S-CNR
W31c	R1-CASS	P2 (corner, in R1-CASS)	kit drop P3-KIT	Cat6 U/UTP	1050	RJ45 inline coupler (in P2)	RJ45 keystone jack, capped (the kit's data link)

FORMBOARD 1:2.5 (lengths to scale along the line; a plug pair, a strip feed ring or a stroke at each end)

MATERIAL FOR THIS HARNESS (its share of the parts list lines, counted from the segments above)

PART NO.	NAME	QTY
718024	ELECTRICAL - CABLE - 4 X 18 AWG - CLASS 2 - SOUTHWIRE R40049-1	1.98 m
718025	ELECTRICAL - CABLE - 6 X 24 AWG SCREENED - CLASS 2 - BELDEN 9536	1.98 m
718028	ELECTRICAL - CABLE - CAT6 U/UTP - BELDEN 3612	1.97 m
718055	ELECTRICAL - CABLE - 4 X 16 AWG - CLASS 2 - SOUTHWIRE 94664	1.97 m
718032	ELECTRICAL - CONNECTOR - MINI-FIT JR RECEPTACLE 4 WAY V-0 - MOLEX 39-01-2045 (5557-04R)	2 pc
718033	ELECTRICAL - CONNECTOR - MINI-FIT JR PLUG 4 WAY V-0 - MOLEX 39-01-3049 (5559-04P1)	3 pc
718034	ELECTRICAL - CONNECTOR - MINI-FIT JR RECEPTACLE 10 WAY V-0 - MOLEX 39-01-2105 (5557-10R)	2 pc
718035	ELECTRICAL - CONNECTOR - MINI-FIT JR PLUG 10 WAY V-0 - MOLEX 39-01-3109 (5559-10P1)	2 pc
718039	ELECTRICAL - RJ45 INLINE COUPLER - CAT6 - PANDUIT CC688IW	3 pc
718040	ELECTRICAL - RJ45 KEYSTONE JACK - CAT6 - WITH DUST CAP - PANDUIT NK688MWH	1 pc

Bushings, cordgrips and edge-protected slots it passes: S-CNR (edge strip Heyco 12431, 718042).
Terminals: Mini-Fit Jr female 39-00-0039 (718036) and male 39-00-0041 (718037) on 18 AWG, one per way; the kit feed's 16 AWG: female 39-00-0078 (718056) and male 39-00-0082 (718057); 24 AWG cores: female 39-00-0047 (718077) and male 39-00-0049 (718078).

NOTES
Segments, ends and lengths from the harness list (710000_P01_ELECTRICAL-HARNESS-LIST_SPEC.csv), same revision.
UNITS: mm. GENERAL TOLERANCE: harness segment lengths +20/-0 mm; positions taken from the route model +/-5 mm;
sheet-metal parts ISO 2768-m (their DXF or drawing rules). Status of every number: parts list and harness list.
Every harness segment is tested in the factory before it ships (D-87): continuity, polarity, no shorts, latch pull,
label with its ID. Cables clip to the cassette tray only (D-26). Supply side = receptacle (female contacts).
Bought parts are named from their datasheets (those still on HOLD give their reason in the parts list 710000); no order, no supplier contact. From the electrical model and parts data.

PROJECT	FocusPod v2 - Spaceship
TITLE	**ELECTRICAL - HARNESS - TRUNK - B2/R1: ASSEMBLY**
DWG / PART NO.	710021 (assembly)
REV / STATUS	P01 / DRAFT - not for production
UNITS / SCALE	mm / formboard 1:2.5; tables not to scale
SHEET	1 of 1 (A2)
DATE / BY	2026-11-01 / Autonomous
SOURCE	electrical_model.py, electrical_parts.py