## SEGMENTS

| ID | CARRIER | FROM | TO | CABLE | L mm | END A | END B |
|---|---|---|---|---|---|---|---|
| W20b | B2-CASS | P1 | back-right corner | 4 x 18 AWG (2 per pole), Class 2 | 920 | Mini-Fit Jr 10-way plug (with W24) | Mini-Fit Jr 10-way receptacle (with W24), tail through the corner slot S-CNR |
| W20c | R1-CASS | P2 (corner, in R1-CASS) | air column chase | 4 x 18 AWG (2 per pole), Class 2 | 1260 | Mini-Fit Jr 10-way plug (with W24) (mated in P2 through the felt slot FS-CNR) | Mini-Fit Jr 10-way receptacle (with W24), tail into the column |
| W30b | B2-CASS | P1 | back-right corner | 4 x 16 AWG (one pair per feed), Class 2 | 920 | Mini-Fit Jr 4-way plug | Mini-Fit Jr 4-way receptacle, tail through the corner slot S-CNR |
| W30c | R1-CASS | P2 (corner, in R1-CASS) | kit drop P3-KIT | 4 x 16 AWG (one pair per feed), Class 2 | 1050 | Mini-Fit Jr 4-way plug (mated in P2 through the felt slot FS-CNR) | Mini-Fit Jr 4-way receptacle, capped with an empty plug housing (the kit outlet: two 12 V feeds, 5 A fuse and up to 48 W each, never joined) |
| W24b | B2-CASS | P1 | back-right corner | 6 x 24 AWG screened, Class 2 | 920 | shares W20's 10-way plug | shares W20's 10-way receptacle, tail through the corner slot S-CNR |
| W24c | R1-CASS | P2 (corner, in R1-CASS) | air column chase | 6 x 24 AWG screened, Class 2 | 1260 | shares W20's 10-way plug (mated in P2 through the felt slot FS-CNR) | shares W20's 10-way receptacle |
| W31b | B2-CASS | P1 | back-right corner | Cat6 U/UTP | 920 | RJ45 inline coupler | RJ45 inline coupler, tail through the corner slot S-CNR |
| W31c | R1-CASS | P2 (corner, in R1-CASS) | kit drop P3-KIT | Cat6 U/UTP | 1050 | RJ45 inline coupler (in P2) | RJ45 keystone jack, capped (the kit's data link) |

## FORMBOARD 1:2.5 (lengths to scale along the line; a plug pair, a strip feed ring or a stroke at each end)

## MATERIAL FOR THIS HARNESS (its share of the parts list lines, counted from the segments above)

| PART NO. | NAME | QTY |
|---|---|---|
| 718024 | ELECTRICAL - CABLE - 4 X 18 AWG - CLASS 2 | 2.18 m |
| 718025 | ELECTRICAL - CABLE - 6 X 24 AWG SCREENED - CLASS 2 | 2.18 m |
| 718028 | ELECTRICAL - CABLE - CAT6 U/UTP | 1.97 m |
| 718055 | ELECTRICAL - CABLE - 4 X 16 AWG - CLASS 2 | 1.97 m |
| 718032 | ELECTRICAL - CONNECTOR - MINI-FIT JR RECEPTACLE 4 WAY V-0 | 2 pc |
| 718033 | ELECTRICAL - CONNECTOR - MINI-FIT JR PLUG 4 WAY V-0 | 3 pc |
| 718034 | ELECTRICAL - CONNECTOR - MINI-FIT JR RECEPTACLE 10 WAY V-0 | 2 pc |
| 718035 | ELECTRICAL - CONNECTOR - MINI-FIT JR PLUG 10 WAY V-0 | 2 pc |
| 718039 | ELECTRICAL - RJ45 INLINE COUPLER - CAT6 | 3 pc |
| 718040 | ELECTRICAL - RJ45 KEYSTONE JACK - CAT6 - WITH DUST CAP | 1 pc |

Bushings and edge-protected slots it passes: S-CNR (Heyco 2836 / edge strip, parts list 718041, 718042).
Terminals: Mini-Fit Jr female 39-00-0039 (718036) and male 39-00-0041 (718037), one per way; the kit feeds' 16 AWG: female 39-00-0078 (718056) and male (718057).

**NOTES**
Segments, ends and lengths from the harness list (710000_P01_ELECTRICAL-HARNESS-LIST_SPEC.csv), same revision.
UNITS: mm. GENERAL TOLERANCE: harness segment lengths +20/-0 mm; positions taken from the route model +/-5 mm;
sheet-metal parts ISO 2768-m (their DXF or drawing rules). Status of every number: parts list and harness list.
Every harness segment is tested in the factory before it ships (D-87): continuity, polarity, no shorts, latch pull,
label with its ID. Cables clip to the cassette tray only (D-26). Supply side = receptacle (female contacts).
Bought parts are on HOLD: no order, no supplier contact. From the electrical model and parts data.

| | |
|---|---|
| PROJECT | FocusPod v2 - Spaceship |
| TITLE | **ELECTRICAL - HARNESS - TRUNK - B2/R1: ASSEMBLY** |
| DWG / PART NO. | 710021 (assembly) |
| REV / STATUS | P01 / DRAFT - not for production |
| UNITS / SCALE | mm / formboard 1:2.5; tables not to scale |
| SHEET | 1 of 1 (A2) |
| DATE / BY | 2026-11-01 / Autonomous |
| SOURCE | electrical_model.py, electrical_parts.py |