

FACE OF THE POWER UNIT, seen from inside the pod (looking toward +Y), 1:3



1 GFCI receptacle, tamper-resistant duplex NEMA 5-15R, UL 943 Class A (718007, HOLD)
in a decorator opening 33.6 x 67, two 6-32 plate screws 96.8 apart (718054)
2 LAN keystone jacks, Cat6, snapped into 14.9 x 19.4 openings (718040, HOLD)
3 breaker 1P 15 A, UL 489, through its 19 x 45 window (718003, HOLD)
US 120 V 60 Hz, UL-listed parts (D-133)

Plate 320 x 284 over the unit (X 95-391, Z 870-1130 in the pod), 2 mm off the felt; 4 x M4 at 42 / 22 from the plate's edges.

DEPTH SECTION THROUGH B2, 2:1 (toward the skin to the right)



Unit fixed to B2's frame (fixing HOLD, WALL IF-12); cassette cut-out 4 mm clear all round (floating lining).

PARTS OF 710001

ITEM	PART NO.	NAME	QTY	UNIT	MATERIAL / FINISH	STATUS
1	711001	ELECTRICAL - POWER UNIT - ENCLOSURE BODY	1	pc	aluminium 5052-H32 1.0 mm, mill finish (hidden, D-79)	DRAFT; HOLD features: the fixing to B2's frame (WALL, IF-12) and the earth stud hole (PEM data)
2	711002	ELECTRICAL - POWER UNIT - FRONT PLATE	1	pc	aluminium 5052-H32 1.5 mm, black anodised AA20 (visible aluminium, D-67)	DRAFT; HOLD features: the GFCI receptacle's decorator opening and the two keystone openings, set by the picked parts' drawings (D-133)
3	718001	ELECTRICAL - 12 V SUPPLY - 60 W CLASS 2	1	pc	potted plastic case, IP67	HOLD (bought part: no order, no supplier contact; guideline 4.3)
4	718081	ELECTRICAL - 24 V SUPPLY - 60 W CLASS 2	1	pc	potted plastic case, IP67	HOLD (bought part: no order, no supplier contact; guideline 4.3)
5	718082	ELECTRICAL - 24 V SUPPLY - 96 W CLASS 2 - VOICE KIT	1	pc	aluminium case, potted, IP67	HOLD (bought part: no order, no supplier contact; guideline 4.3)
6	718002	ELECTRICAL - LED CONTROLLER - 3 CHANNEL 12 V PWM - RS-485	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
7	718003	ELECTRICAL - CIRCUIT BREAKER - 1P 15 A C - UL 489	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
8	718004	ELECTRICAL - APPLIANCE INLET - POWERCON TRUE1 TOP	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
9	718005	ELECTRICAL - INLET SEALING CAP	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
10	718006	ELECTRICAL - LAN FEED-THROUGH - ETHERCON	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
11	718007	ELECTRICAL - RECEPTACLE - GFCI TR DUPLEX 15 A - NEMA 5-15R	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
12	718010	ELECTRICAL - DIN RAIL - TS35 X 7.5 - 100 MM	1	pc	steel, zinc plated	HOLD (bought part: no order, no supplier contact; guideline 4.3)
13	718011	ELECTRICAL - FUSE HOLDER - ATO BLADE - INLINE	2	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
14	718012	ELECTRICAL - FUSE - ATO 5 A 32 V	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
15	718013	ELECTRICAL - FUSE - ATO 5 A 32 V - LIGHTS	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
16	718019	ELECTRICAL - SCREW - M4 X 8 - ISO 7045 A2 PAN HEAD	4	pc	stainless steel, plain (A2 stainless)	HOLD (bought part: no order, no supplier contact; guideline 4.3)
17	718049	ELECTRICAL - SPACER - M4 X 2 MM - NYLON, BLACK	4	pc	nylon 6/6, black, as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
18	718054	ELECTRICAL - SCREW - 6-32 X 1/2 - OVAL HEAD, BLACK	2	pc	steel, black oxide	HOLD (bought part: no order, no supplier contact; guideline 4.3)
19	718047	ELECTRICAL - CLINCH NUT - M4 - FOR 1.0 MM ALUMINIUM	4	pc	aluminium, plain, as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
20	718014	ELECTRICAL - EARTH STUD - M5 SELF-CLINCHING	1	pc	aluminium, plain, as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
21	718015	ELECTRICAL - BONDING WASHER - SERRATED M6 A2	1	pc	stainless A2	HOLD (bought part: no order, no supplier contact; guideline 4.3)
22	718016	ELECTRICAL - RING TERMINAL - INSULATED 16-14 AWG	5	pc	tinned copper	HOLD (bought part: no order, no supplier contact; guideline 4.3)
23	718017	ELECTRICAL - CONDUIT - FLEXIBLE NONMETALLIC 1/2 IN	0.6	m	PVC, UL 1660 liquidtight flexible nonmetallic (LFNC-B)	HOLD (bought part: no order, no supplier contact; guideline 4.3)
24	838001	HARDWARE - SOCKET HEAD BOLT - M6 X 16 - ISO 4762 8.8 ZINC	4	pc	steel, zinc plated	HOLD (bought part: no order, no supplier contact; guideline 4.3)
25	838004	HARDWARE - WASHER - M6 LARGE - ISO 7093-1 6.4 X 18 A2	4	pc	stainless steel, plain (A2 stainless)	HOLD (bought part: no order, no supplier contact; guideline 4.3)
26	838003	HARDWARE - RIVET NUT - M6 - SHEREX CAH3-610-4.2	4	pc	aluminium, plain, as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
27	718020	ELECTRICAL - WIRE - UL 1015 14 AWG (BLACK, WHITE, GREEN)	2.76	m	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
28	718021	ELECTRICAL - WIRE - UL 1015 14 AWG (BLACK, WHITE)	1.5	m	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
29	718022	ELECTRICAL - WIRE - UL 1015 14 AWG GREEN	0.3	m	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)
30	718073	ELECTRICAL - CURRENT SENSE MODULE - 24 V 0-5 A	1	pc	as supplied	HOLD (bought part: no order, no supplier contact; guideline 4.3)

ISO first angle

NOTES
Wiring inside the unit: wiring diagram sheet 1 (710000). Leads out: W10a top (6-way), W20a/W24a/W30a/W31a right side.
Factory test of the unit before B2 ships (US 120 V, D-133): ground continuity <= 0.1 ohm; dielectric withstand 1240 V AC for 1 min, mains to ground (1000 V + 2 x 120 V); the GFCI's TEST button trips it; rails 24 V (PS1, PS2) and 12 V (PS3) +/-3 %.
UNITS: mm. GENERAL TOLERANCE: harness segment lengths +20/-0 mm; positions taken from the route model +/-5 mm;
sheet-metal parts ISO 2768-m (their DXF or drawing rules). Status of every number: parts list and harness list.
Every harness segment is tested in the factory before it ships (D-87): continuity, polarity, no shorts, latch pull,
label with its ID. Cables clip to the cassette tray only (D-26). Supply side = receptacle (female contacts).
Bought parts are on HOLD: no order, no supplier contact. From the electrical model and parts data.

PROJECT	FocusPod v2 - Spaceship
TITLE	**ELECTRICAL - POWER UNIT - B2: ASSEMBLY**
DWG / PART NO.	710001 (assembly)
REV / STATUS	P01 / DRAFT - not for production
UNITS / SCALE	mm / 1:3 face, 2:1 section (schematic)
SHEET	1 of 1 (A2)
DATE / BY	2026-11-01 / Autonomous
SOURCE	electrical_model.py, electrical_parts.py