

ScrivWeb App Summary

What it is

ScrivWeb (titled **Scriv2WN** in index.html) is a static web reader for serialized fiction, with story-specific theming, chapter navigation, and extras. It renders chapter JSON and style config from local repo data files directly in the browser.

Who it's for

Primary persona: online readers of the Firebrand/Paragate stories, with additional mode flags for reviewer/editor/author workflows.

What it does

- URL-driven loading of story, mode, and chapter via query params (?story=...&mode;=...&chapter;=...).
- On-demand chapter fetch + in-session caching from data/sectioned/<story>/<act>/<chapter>.json.
- TOC panel with release-aware chapter gating/locks by access level (Reader, Reviewer, Special, Author).
- Scroll-driven theme interpolation (POV-aware colors/backgrounds) using CSS custom properties.
- Reader controls for font size, line height, justification, image headers, and datetime headers.
- Extras system that loads announcements JSON and story-specific extras HTML into side panels.
- Local persistence of chapter position and reader preferences in per-story localStorage keys.

How it works (repo evidence)

- Client app: index.html + main.js (compiled from main.ts) manage rendering, theming, navigation, and UI state.
- Core runtime components in main.ts: LocalStorageAndSrcVars, StoryConfig, TableOfContents, ChapterBinder, ThemeDriver, and StoryExtrasWindow.
- Primary data flow: browser fetches data/StoryConfig.json -> data/TOC/TOC_*.json -> section files under data/sectioned/; extras come from data/Announcements.json and extra/extras_*.html.
- Supporting pipeline: scripts/python/Scriv2WebNovel.py generates data/output, data/sectioned, data/TOC, GPT exports, and PDF HTML/PDF build artifacts.
- Backend/API service for live processing: **Not found in repo.**

How to run (minimal)

1. Serve the repo root over local HTTP (the app uses fetch() for JSON/HTML assets). Exact server command: **Not found in repo.**
2. Open index.html in that server context (example path: /index.html?story=Paragate).
3. Optional URL params: story, chapter, and mode (reader/reviewer/editor/author aliases are parsed in main.ts).
4. If editing TypeScript, recompile main.ts to main.js; exact compile command/tooling bootstrap: **Not found in repo.**

Evidence scope: repository files only (no external assumptions).