EOTWSG SURVIVAL LIBRARY



Lifetime Collection

Every EOTWSG pack — PKG-001 through PKG-013 — with future revisions of those packs

ALL 13 PACKS · 178 PDFS · 853 PAGES

PACK FILES ONLY · FUTURE REVISIONS INCLUDED

REV 2026-11-04 · PRINT-READY PDF · A4 + US LETTER

72-Hour Bug-Out Bag Checklist

EOTWSG | MODULE 01 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to a compact, offline checklist for assembling and validating a household evacuation kit for the first 72 hours after a disruption. Pack for the people, conditions, mobility limits, and routes actually relevant to your household.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (01) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Mission Profile section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: A compact, offline checklist for assembling and validating a household evacuation kit for the first 72 hours after a disruption. Pack for the people, conditions, mobility limits, and routes actually relevant to your household.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

Emergency Planning — Printable Tactical Checklist

Mission Profile

A compact, offline checklist for assembling and validating a household evacuation kit for the first 72 hours after a disruption. Pack for the people, conditions, mobility limits, and routes actually relevant to your household.

USE THIS IN THREE PASSES

1. Draft your kit list. 2. Physically stage and label the items. 3. Conduct a timed load-out and correct every failure.

Household Loadout

Person / role	Pack, size, or mobility note
Primary adult	**Name:** _____
Second adult / caregiver	**Name:** _____
Child / dependent	**Name and needs:** _____
Pet / service animal	**Carrier, food, medication:** _____
Medical / accessibility needs	**Critical accommodations:** _____

Core Checklist

Water & food **Shelter & clothing**

Rainwater Harvesting & Purification Plumbing Layout

EOTWSG | MODULE 03 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to credit: Excerpts, schematics, and tactical protocols adapted from the End of the World Survival Guide (EOTWSG) by Matthew Danielson. Reproduce only for off-grid resilience and survival training.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (03) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Sizing Basis section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: Credit: Excerpts, schematics, and tactical protocols adapted from the End of the World Survival Guide (EOTWSG) by Matthew Danielson. Reproduce only for off-grid resilience and survival training.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

600 sq ft Catchment — 40 in Rainfall — Multi-Stage Treatment

Sizing Basis

Input	Value	Review note
Catchment area	600 sq ft roof footprint	Confirm actual contributing area, bypasses, overflow, and roof material.
Annual rainfall	40 in / 1,000 mm	Use local rainfall records and design storm intensity for storage and overflow.
Efficiency factor	0.95 metal-roof factor	Confirm first-flush, debris, losses, and actual runoff conditions.

Resolved Yield Formula

ANNUAL USABLE YIELD

Catchment Area (sq. ft.) × Rainfall (inches) × 0.623 × 0.95 = Usable Yield (gallons)

600 sq ft × 40 inches × 0.623 × 0.95 = 14,204 gallons/year

Meals-in-a-Jar Dehydration Cookbook & Layering Guide

EOTWSG | MODULE 01 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to these recipes are dry-meal assembly guides for properly dehydrated or freeze-dried ingredients. They are not canning recipes. Use clean, completely dry ingredients and packaging rated for dry food storage. Add the oxygen absorber only immediately before sealing when the food and package are appropriate for that method.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (01) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Use and Limits section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: These recipes are dry-meal assembly guides for properly dehydrated or freeze-dried ingredients. They are not canning recipes. Use clean, completely dry ingredients and packaging rated for dry food storage. Add the oxygen absorber only immediately before sealing when the food and package are appropriate for that method.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

Shelf-Stable Dry Meals — Layering, Rehydration, and Cooking

Use and Limits

These recipes are dry-meal assembly guides for properly dehydrated or freeze-dried ingredients. They are not canning recipes. Use clean, completely dry ingredients and packaging rated for dry food storage. Add the oxygen absorber only immediately before sealing when the food and package are appropriate for that method.

CRITICAL FOOD-SAFETY WARNING

Improper canning or anaerobic packaging can result in botulism, a potentially fatal illness. Use only current, research-tested USDA/NCHFP procedures for the exact food, jar size, pack style, processing time, pressure, and altitude. Inspect every seal. If a jar or pouch is swollen, leaking, spurting, moldy, oddly colored, or smells abnormal, do not taste it; discard it safely.

Layering Rule

Place heavier, larger pieces at the bottom and powders above them. Keep seasoning powders away from the seal area. The sequence below is bottom-to-top. Leave the manufacturer's recommended headspace and verify the finished package is fully dry before sealing.

Negative-Pressure Quarantine Room Blueprint

EOTWSG | MODULE 12 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to this is an expedient planning aid, not a certified airborne infection isolation room. A residential room may not provide the pressure control, outdoor exhaust, filtration, monitoring, fire rating, or infectioncontrol performance of a healthcare AIIR. Contact public health and qualified HVAC/infection-control personnel for suspected airborne disease.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (12) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Scope and Limitation section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: This is an expedient planning aid, not a certified airborne infection isolation room. A residential room may not provide the pressure control, outdoor exhaust, filtration, monitoring, fire rating, or infection-control performance of a healthcare AIIR. Contact public health and qualified HVAC/infection-control personnel for suspected airborne disease.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

Residential Isolation Planning — Airflow, Barriers, and HEPA Exhaust

Scope and Limitation

This is an expedient planning aid, not a certified airborne infection isolation room. A residential room may not provide the pressure control, outdoor exhaust, filtration, monitoring, fire rating, or infection-control performance of a healthcare AIIR. Contact public health and qualified HVAC/infection-control personnel for suspected airborne disease.

Off-Grid Electrical & Solar Power Schematic

EOTWSG | MODULE 01 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to nEC/NFPA 70 and CEC Part I requirements must be checked against the adopted local editions and amendments.Project review basis: NEC 2023 / CEC 2024 as specified in the EOTWSG technical baseline.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (01) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Design Basis section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: NEC/NFPA 70 and CEC Part I requirements must be checked against the adopted local editions and amendments.Project review basis: NEC 2023 / CEC 2024 as specified in the EOTWSG technical baseline.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

6.0 kW PV — 48 V LiFePO4 — NEC 2023 / CEC 2024

Design Basis

Parameter	Locked input	Review note
PV array	6.0 kW roof-mounted	Verify roof attachment, wind uplift, fire access, and module/string layout.
Battery	48 V DC nominal LiFePO4	Confirm BMS, thermal limits, enclosure, ventilation, and listing.
Conductors	Marine-grade UL 1426 tinned copper	Minimum 10 AWG PV string runs; 4/0 AWG battery interconnects.
Codes	NEC 2023 / CEC 2024	Local amendments and AHJ review govern.

Tactical Cabin Structural Blueprint & Load Data

EOTWSG | MODULE 02 | REV 2026-09-22 | STATUS: SOURCE-VERIFIED ONLY

Authored by: EOTWSG

REVISION LOG

Date	Revision	Description
2026-09-22	REV 2026-09-22	Front-matter standardization: cover block, revision log, action card, and local fields added; source normalized to house Typst dialect.

ACTION CARD

Use this guide to credit: Excerpts, schematics, and tactical protocols adapted from the End of the World Survival Guide (EOTWSG) by Matthew Danielson. Reproduce only for off-grid resilience and survival training.. Carry one copy in the master box and one copy in the working binder.

Step	Do this now	Completion check	Stop / escalate when
1	Confirm this copy is current: check the module ID (02) and REV date on the cover.	Module ID and REV noted on the working copy.	If the REV predates 2026-09-22, replace this copy before use.
2	Work through the Design Basis section against your household's actual people, conditions, and equipment.	Section completed with household-specific entries; gaps flagged.	If a required capability is missing, flag it in the binder and resolve before the next drill.
3	Record completion, date, and any deviations in the working binder; schedule the next review.	Binder entry dated and filed.	If the household situation changes, re-run the guide.

PURPOSE AND ACTIVATION

Purpose: Credit: Excerpts, schematics, and tactical protocols adapted from the End of the World Survival Guide (EOTWSG) by Matthew Danielson. Reproduce only for off-grid resilience and survival training.

Activation triggers: utility failure, evacuation order, sudden service uncertainty, or a planned verification drill. This module is usable on its own; linked module IDs preserve the shared decision order from the master index.

20 ft × 30 ft — 600 sq ft — 4:12 Shed Roof — Owen Sound Basis

Design Basis

Parameter	Locked input	Design / review note
Footprint	20 ft × 30 ft = 600 sq ft	Confirm setbacks, occupancy, fire separation, and site survey.
Roof	Shed-style, single slope, 4:12 pitch	Standing-seam metal; verify drainage, snow drift, attachment, and solar loads.
Snow	60 psf minimum / 2.8 kPa	Engineer to confirm ground, roof, drift, importance, and combinations.
Wind	105 mph / 170 km/h, 3-second gust	Engineer to confirm exposure, components, cladding, uplift, and connections.
Foundation	Helical piles or reinforced concrete piers below 48 in frost line	Geotechnical, frost, lateral, uplift, and settlement review required.
Framing	2×6 studs at 16 in O.C.	Coordinate sheathing, headers, bracing, insulation, penetrations, and fire protection.