

CSE185

Introduction to Computer Vision

Lab 04: Frequency Domain Operation

Instructor: Daniel Leung

TA: Mohammadkazem Ebrahimpour

Xueqing Deng

# Overview

---

- Task 1: Splitting low-frequency and high-frequency



Input Image

# Overview

---

- Task 1: Splitting low-frequency and high-frequency



Low-Frequency Part




High-Frequency Part

# Overview

---

- Task 2: Hybrid Image



Input 1




Input 2

# Overview

---

- Task 2: Hybrid Image




Input 1 low frequency +  
Input 2 high frequency



Input 2 low frequency +  
Input 1 high frequency

# Fourier Transform

- *Discrete Fourier Transform*: decomposes a signal into its frequency components
- *Fast Fourier Transform (FFT)*: an algorithm to compute discrete Fourier Transform in  $O(N \log N)$  time (Direct method:  $O(N^2)$  time )






# Fourier Transform

- Apply Fourier Transform to an image:



Input Image



Frequency Map

# Fourier Transform in MATLAB

---

- Step 1: Use `fft2 ( )` to apply fast Fourier Transform:

```
img = im2double(imread('images/lena.jpg'));  
frequency_map = fft2(img);  
  
figure, imshow( log(abs(frequency_map) + 1), []);
```

- Display frequency map in MATLAB:

- `abs ( )`: take frequency magnitude
- `log ( )`: compress range
- `+1`: avoid `log(0)`
- `imshow (x, [ ] )`: auto adjust range by:

$$x = \frac{x - \min(x)}{\max(x) - \min(x)}$$



# Fourier Transform in MATLAB

- Step 1: Use `fft2()` to apply fast Fourier Transform:


```
img = im2double(imread('images/lena.jpg'));  
frequency_map = fft2(img);  
  
figure, imshow( log(abs(frequency_map) + 1), []);
```

Low frequency parts  
are at corners

Low frequency parts  
are at corners

Low frequency parts  
are at corners


Low frequency parts  
are at corners



# Fourier Transform in MATLAB

- Step 2: Use `fftshift()` to rearrange the frequency map

```
img = im2double(imread('images/lena.jpg'));  
frequency_map = fft2(img);  
frequency_map_shifted = fftshift(frequency_map);
```



# Fourier Transform in MATLAB

- Step 3: compute a low-frequency mask

```
y1 = ???
```

```
y2 = ???
```

```
x1 = ???
```


```
x2 = ???
```

```
mask = zeros(size(img));
```

```
mask(y1 : y2, x1 : x2, :) = 1;
```

Something related to ratio

Remember the third dimension



# Fourier Transform in MATLAB

- Step 3: compute a low-frequency mask (TODO)

```
y1 = ???
```

```
y2 = ???
```

```
x1 = ???
```


```
x2 = ???
```

```
mask = zeros(size(img));
```

```
mask(y1 : y2, x1 : x2, :) = 1;
```

Something related to ratio



Remember the third dimension



# Fourier Transform in MATLAB

- Step 4: Split low-frequency and high-frequency parts

```
low_frequency_map_shifted =  
    frequency_map_shifted .* mask;  
high_frequency_map_shifted =  
    frequency_map_shifted .* (1 - mask);
```







# Fourier Transform in MATLAB

- Step 5: Use `ifftshift()` to shift frequency map back

```
low_frequency_map =  
    ifftshift(low_frequency_map_shifted);  
high_frequency_map =  
    ifftshift(high_frequency_map_shifted);
```





# Fourier Transform in MATLAB

- Step 6: Use `ifft2()` to convert from frequency domain to image domain

```
low_pass_img = real(ifft2(low_frequency_map));  
high_pass_img = real(ifft2(high_frequency_map));
```

Take the real part only

- To show/save the high-frequency parts, add 0.5 offset for better visualization

```
figure, imshow(low_pass_img);  
figure, imshow(high_pass_img + 0.5);  
  
imwrite(low_pass_img, 'lena_low_pass.jpg');  
imwrite(high_pass_img + 0.5, 'lena_high_pass.jpg');
```

# Split Frequency

---

- Ratio = 0.1



low-frequency part




high-frequency part

# Split Frequency

- Ratio = 0.25



low-frequency part



high-frequency part


# Split Frequency

---

- Ratio = 0.5



low-frequency part



high-frequency part


# Split Frequency

---

- Ratio = 1



low-frequency part




high-frequency part

# Summary of Task 1

---

1. Apply `fft2()` to input image
2. Use `fftshift()` to shift frequency map
3. Compute low-frequency mask
4. Separate low frequency and high frequency maps
5. Use `ifftshift()` to shift frequency maps back
6. Apply `ifft2()` to convert frequency maps to images





# Summary of Task 1

---

- In `separate_frequency.m`:

```
function [low_pass_img, high_pass_img] =  
    separate_frequency(img, ratio)  
  
    %% apply FFT  
    frequency_map = fft2(img);  
  
    %% shift the frequency map  
  
    %% compute low-frequency mask  
  
    %% separate low-frequency and high-frequency maps  
  
    %% shift frequency maps back  
  
    %% apply Inverse FFT  
    low_pass_img = real(ifft2(frequency_map));  
    high_pass_img = real(ifft2(frequency_map));  
end
```

Replace frequency map with  
your low/high frequency maps

# Summary of Task 1

---

- Create lab04.m:

```
%% Task 1: Split Frequency
img = im2double(imread('images/cameraman.jpg'));

ratio = 0.1;


[low_pass_img, high_pass_img] =
    separate_frequency(img, ratio);

imwrite(low_pass_img, 'cameraman_low_pass.jpg');
imwrite(high_pass_img + 0.5,
    'cameraman_high_pass.jpg');
```

# Hybrid Image

---

- Take 2 input images



Input 1



Input 2

# Hybrid Image


---

- Splitting into low/high-pass images



# Hybrid Image

- Merge low and high frequency images



# Hybrid Image

---

- Make use of your function `separate_frequency.m` in `hybrid_image.m`:

```
function img_merged = hybrid_image(img1, img2, ratio)

    %% split img1 and img2 into low/high frequency
    maps

    %% combine the low-frequency map of img1 with the
    high-frequency map of img2
    img_merged = ???;

end
```



# Hybrid Image

- In lab04.m:

```
%% Task 2: Hybrid Image
```

```
name1 = 'images/cat.jpg';
```

```
name2 = 'images/dog.jpg';
```

Try other image pairs

```
img1 = im2double(imread(name1));
```

```
img2 = im2double(imread(name2));
```

```
ratio = 0.2;
```

Try other ratio

```
img_merged = hybrid_image(img1, img2, ratio);
```

```
figure, imshow(img_merged);
```

# TODO

---

1. Implement `separate_frequency.m`
2. Use  $\text{ratio} = 0.1$ , and save the image as `cameraman_low_0.1.jpg` and `cameraman_high_0.1.jpg`
3. Use  $\text{ratio} = 0.2$ , and save the image as `cameraman_low_0.2.jpg` and `cameraman_high_0.2.jpg`
4. Implement `hybrid_image.m`
5. Use any ratio to merge the low-frequency of `cat.jpg` and the high frequency of `dog.jpg`, and save the image as `hybrid_1.jpg`
6. Use any ratio to merge the low-frequency of `dog.jpg` and the high frequency of `cat.jpg`, and save the image as `hybrid_2.jpg`
7. Upload your output images and `separate_frequency.m`, `hybrid_image.m`, and `lab04.m`

# One more thing...

- Display gray-scale frequency map:

```
figure, imshow(log(abs(frequency_map) + 1), []);
```

- Display color frequency map:

```
figure, imagesc(log(abs(frequency_map) + 1)), colormap jet;
```



Should be single channel

- Try to display the frequency of square.bmp, gaussian.bmp, sea.bmp, and bridge.bmp

```
img = im2double(imread('images/square.bmp'));  
frequency_map = fftshift(fft2(img));  
figure, imagesc(log(abs(frequency_map) + 1)), colormap jet;
```

# One more thing...

- More horizontal edges  $\Rightarrow$  higher response on vertical direction



# One more thing...

- The Fourier transform of a box signal is a sinc function
- The Fourier transform of a Gaussian signal is still a Gaussian function

