

# LDAP

Lightweight Directory Access Protocol

wangth

國立陽明交通大學資工系資訊中心


Computer Center of Department of Computer Science, NYCU

# What is Directory Service?

## □ What is Directory Service (目錄服務)

- Highly optimized for reads
- Implements a distributed model for storing information
- Can extend the type of information it stores
- Has advanced search capabilities
- Has loosely consistent replication among directory servers

## □ Domain Name Service




# What is LDAP?

## □ Lightweight Directory Access Protocol (LDAP)

- LDAPv3: RFC 3377
- RFC 2251-2256, 2829, 2830, 3377

## □ Why **L**DAP is lightweight

- A subset of the X.500 standard
- X.500 is based on OSI model
- LDAP is based on TCP/IP model
- LDAP omits many X.500 operations that are rarely used
- Provides a smaller and simpler set of operations



# LDAP Directory Information Tree (DIT)


dc: domain component

ou: organization unit

cn: common name


o: organizationName

c: countryName



**cn=tzute,ou=People,dc=na,dc=nctucs,dc=cc**  
**o="na, nctucs, cc", c=TW**  
**o=na.nctucs.cc**

# LDAP Directory Information Tree (DIT)



DN (distinguished name):

`cn=tzute,ou=People,dc=na,dc=nctucs,dc=cc`

**RDN: Relative Distinguished Name**

# LDAPv3 Overview – LDIF (1/4)


## □ LDAP Interchange Format (LDIF)

- Defined in RFC 2849
- Standard text file format for storing LDAP configuration information and directory contents
- An LDIF file is
  1. A collection of entries separated from each other by blank lines
  2. A mapping of attribute names to values
  3. A collection of directives that instruct the parser how to process the information
- The data in the LDIF file must obey the schema rules of your LDAP directory

# LDAPv3 Overview – LDIF (2/4)

## □ Sample LDIF

```
# A sample entry
# Format: <Attribute>: <Value>
dn: cn=tzute,ou=people,dc=na,dc=nctucs,dc=cc
objectClass: person
cn: tzute
telephoneNumber: 123-4567
```






# LDAPv3 Overview – LDIF (3/4)

## □ Sample LDIF – Modify one DN

```
# Modify user info
dn: cn=tzute,ou=people,dc=na,dc=nctucs,dc=cc
changetype: modify
add: description
description: NA TA
-
replace: telephoneNumber
telephoneNumber: 0987654321
```





# LDAPv3 Overview – LDIF (4/4)

## □ Sample LDIF – Modify more than one DN

```
# Modify user info
dn: cn=tzute,ou=people,dc=na,dc=nctucs,dc=cc
changetype: modify
add: description
description: NA TA

```

```
dn: cn=tcyuan,ou=people,dc=na,dc=nctucs,dc=cc
changetype: modify
add: description
description: NA TA
```

# LDAPv3 Overview – objectClass


□ /usr/local/etc/openldap/schema/core.schema

```
objectclass ( 2.5.6.6 NAME 'person'  
  DESC 'RFC2256: a person'  
  SUP top STRUCTURAL  
  MUST ( sn $ cn )  
  MAY ( userPassword & telephoneNumber & seeAlso & description ))
```

ObjectClassDescription = "(" whsp  
 numericoid whsp ; ObjectClass identifier  
 [ "Name" qdescrs ]  
 [ "DESC" qdstring ]  
 [ "OBSOLETE" whsp ]  
 [ "SUP" oids ] ; Superior ObjectClasses  
 [ ( "ABSTRACT" / "STRUCTURAL" / "AUXILIARY" ) whsp ]  
 ; default structural  
 [ "MUST" oids ] ; AttributeTypes  
 [ "MAY" oids ] ; AttributeTypes  
 Whsp ")"

<http://www.openldap.org/doc/admin24/schema.html>

# LDAPv3 Overview – objectClass (Cont.)



<http://www.openldap.org/doc/admin24/schema.html>

# LDAPv3 Overview – Attribute

```
Attributetype ( 2.5.4.20 NAME 'telephoneNumber'  
  DESC 'RFC2256: Telephone Number'  
  EQUALITY telephoneNumberMatch  
  SUBSTR telephoneNumberSubstringsMatch  
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.50{32} )
```

Matching Rules Types

Table 8.3: Commonly Used Syntaxes

Name	OID	Description
boolean	1.3.6.1.4.1.1466.115.121.1.7	boolean value
directoryString	1.3.6.1.4.1.1466.115.121.1.15	Unicode (UTF-8) string
distinguishedName	1.3.6.1.4.1.1466.115.121.1.12	LDAP DN
integer	1.3.6.1.4.1.1466.115.121.1.27	integer
numericString	1.3.6.1.4.1.1466.115.121.1.36	numeric string
OID	1.3.6.1.4.1.1466.115.121.1.38	object identifier
octetString	1.3.6.1.4.1.1466.115.121.1.40	arbitrary octets

Server should support values of this length

# Comparison with relational databases

- It is tempting to think that having a RDBMS backend to the directory solves all problems. However, it is wrong.
- This is because the data models are very different. Representing directory data with a relational database is going to require splitting data into multiple tables.



# OpenLDAP



An open source implementation of the Lightweight  
Directory Access Protocol

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

# OpenLDAP on FreeBSD

## □ Three main components

- slapd – stand-alone LDAP daemon and associated modules and tools
- libraries implementing the LDAP protocol and ASN.1 Basic Encoding Rules (BER)
- client software: ldapsearch, ldapadd, ldapdelete, and others

## □ Installation

- pkg install openldap-server
- cd /usr/ports/net/openldap-server24; make install clean

## □ slapd.conf

- Blank lines and lines beginning with a pound sign (#) are ignored
- Parameters and associated values are separated by whitespace characters
- A line with a blank space in the first column is considered to be a continuation of the previous one.



# slapd.conf

```
include      /usr/local/etc/openldap/schema/core.schema
pidfile      /var/run/openldap/slapd.pid
argsfile     /var/run/openldap/slapd.args
loglevel     256
modulepath   /usr/local/libexec/openldap
moduleload   back_mdb
moduleload   back_ldap

database     mdb
maxsize      1073741824
suffix       "dc=na,dc=nctucs,dc=cc"
rootdn       "cn=Manager,dc=na,dc=nctucs,dc=cc"
rootpw       <generated by slappasswd>
directory   /var/db/openldap-data

# Indices to maintain
index       objectClass eq
# ACL rules here for specific database
```

# Directory ACL

```
# access to <what> [ by <who> [<accesslevel>] [<control>] ]+
access to dn.exact="cn=Manager,dc=na,dc=nctucs,dc=cc"
    by peername.ip="127.0.0.1" auth
    by users none
    by anonymous none
    by * none

access to attrs=userPassword
    by self write
    by anonymous auth
    by dn.base="cn=Manager,dc=na,dc=nctucs,dc=cc" write
    by * none

access to attrs=englishname,birthdate
    by self write
    by users read
    by anonymous read
```

If one access directive is more specific than another in terms of the entries it selects, it should appear first in the configuration

# Directory ACL

<http://www.openldap.org/doc/admin24/access-control.html>

## □ Access Entity Specifiers (Who)


Specifier	Entities
*	All, including anonymous and authenticated users
anonymous	Anonymous (non-authenticated) users
users	Authenticated users
self	User associated with target entry
dn[.<basic-style>]=<regex>	Users matching a regular expression
dn.<scope-style>=<DN>	Users within scope of a DN

## □ Access Levels

Level	Privileges	Description
none =	0	no access
disclose =	d	needed for information disclosure on error
auth =	dx	needed to authenticate (bind)
compare =	cdx	needed to compare
search =	scdx	needed to apply search filters
read =	rscdx	needed to read search results
write =	wrscdx	needed to modify/rename
manage =	mwrscdx	needed to manage

# Overlays

- ❑ Software components that provide hooks to functions analogous to those provided by backends, which can be stacked on top of the backend calls and as callbacks on top of backend responses to alter their behavior
- ❑ Frontend
  - handles network access and protocol processing
- ❑ Backend
  - deals strictly with data storage




<https://www.openldap.org/doc/admin24/overlays.html>

<https://en.wikipedia.org/wiki/OpenLDAP#Overlays>

# Overlays – memberOf

## □ Membership



objectClass: posixGroup  
objectClass: top  
objectClass: posixAccount  
cn: tzute  
gidNumber: 1234

objectClass: posixGroup  
objectClass: top  
cn: nata  
displayName: nata  
description: Domain Unix group  
gidNumber: 1234



# Overlays – memberOf

## □ Installation

- Ports
- make config □ enable option

```
+ [ ] LMPASSWD      With LM hash password support (DEPRECATED)
+ [x] MDB           With Memory-Mapped DB backend
+ [ ] MEMBEROF     With Reverse Group Membership overlay
+ [ ] ODBC         With SQL backend
+ [ ] OUTLOOK      Force caseIgnoreOrderingMatch on name attribute
+ [ ] PASSWD       With Passwd backend
+ [ ] PERL         With Perl backend
+ [ ] PPOLICY      With Password Policy overlay
+ [ ] PROXYCACHE   With Proxy Cache overlay
+ [ ] REFINT       With Referential Integrity overlay
+ [ ] RELAY        With Relay backend
+ [ ] RETCODE      With Return Code testing overlay
+ [ ] BLOCKING     With reverse lookup of client hostnames
```

<https://www.openldap.org/doc/admin24/overlays.html>

# Overlays – memberOf

- Edit /usr/local/etc/openldap/slapd.conf

```
# MemberOf  
Overlay memberof
```

- restart slapd
- Query Result

```
dn: cn=nata,ou=MemberGroup,dc=na,dc=nctucs,dc=cc  
objectclass: groupOfNames  
cn: nata  
member: cn=tzute,ou=People,dc=na,dc=nctucs,dc=cc
```

<https://www.openldap.org/doc/admin24/overlays.html>




# OLC – Online Configuration (1/3)

- ❑ OpenLDAP Version 2.3    ❑ New feature
- ❑ OpenLDAP Version 2.4    ❑ Still optional
- ❑ Uses a configuration DIT to control the operational configuration
- ❑ Modifying entries in this DIT immediate changes to slapd's operational behavior

<https://www.openldap.org/doc/admin24/slapdconf2.html>

<https://www.zytrax.com/books/ldap/ch6/slapd-config.html>

# OLC – Online Configuration (2/3)



# OLC – Online Configuration (3/3)

```
# {1}mdb, config
dn: olcDatabase={1}mdb,cn=config
objectClass: olcDatabaseConfig
objectClass: olcMdbConfig
olcDatabase: {1}mdb
olcDbDirectory: /var/db/openldap-data/na
olcSuffix: dc=na,dc=nctucs,dc=cc
olcAddContentAcl: FALSE
olcLastMod: TRUE
olcMaxDerefDepth: 15
olcReadOnly: FALSE
olcRootDN: cn=Manager,dc=na,dc=nctucs,dc=cc
olcRootPW: secret
```

# Enable slapd

- Edit /etc/rc.conf
  - slapd\_enable="YES"
  - slapd\_flags for specific options
  
- service slapd start

<http://www.openldap.org/doc/admin24/runningslapd.html>

# slapd tools

## ❑ slapcat

- This tool reads records from a slapd database and writes them to a file or standard output

## ❑ slapadd

- This tool reads LDIF entries from a file or standard input and writes the new records to a slapd database

## ❑ slapindex

- This tool regenerates the indexes in a slapd database

## ❑ slappasswd

- This tool generates a password hash suitable for use as an `AuthSource` in `slapd.conf`

# LDAP tools

- `ldapsearch`
  - This tool issues LDAP search queries to directory servers
- `ldapadd`, `ldapmodify`
  - These tools send updates to directory servers
- `ldapcompare`
  - This tool server to compare two values
- `ldapdelete`
  - This tool deletes entries from an LDAP directory

# ldapsearch

## □ Options

- -b searchbase
- -s {base|one|sub|children} # default is sub
- -D binddn
- -x # Use simple authentication instead of SASL
- -W # password for simple authentication
- -H ldapuri


## □ ldapsearch [options] filter

- default filter, (objectClass=\*)
- ldapsearch -H ldap://ldap.na.nctucs.cc  
-D "cn=tzute,dc=na,dc=nctucs,dc=cc"  
-b "dc=na,dc=nctucs,dc=cc" -s one

## □ man ldapsearch



# ldapsearch (Cont.)




# ldap.conf

❑ `ldapsearch -H ldap://ldap.na.nctucs.cc`  
`-b "dc=na,dc=nctucs,dc=cc" cn=tzute`

❑ Edit `/usr/local/etc/openldap/ldap.conf`

```
# See ldap.conf(5) for details
# This file should be world readable but not world writable.
BASE      dc=na,dc=nctucs,dc=cc
URI       ldap://ldap.na.nctucs.cc
```



=> `ldapsearch -x "cn=tzute"`

# ldapsearch – searchbase vs. filter

## ❑ Search by dn

```
# ldapsearch dn="cn=tzute,dc=na,dc=nctucs,dc=cc"
```

- It does not work!

## ❑ Use search base

```
# ldapsearch -b "cn=tzute,dc=na,dc=nctucs,dc=cc" -s base
```

- It works!


## ❑ Why?

- You have got full dn, don't need to search

# Ldapsearch – searchbase vs. filter

## □ Example


- Assume there are two kinds of searchbase
- **dc=na,dc=nctucs,dc=cc**
- **ou=People, dc=na,dc=nctucs,dc=cc**



# ldapsearch – searchbase vs. filter

## □ Example (Cont.)

- filter – search for all entries that have cn=nata
- **cn=nata**
- **cn=nata** □ Can't be found, because the cn=nata is not in this subtree



# LDAP Authentication

國立陽明交通大學資工系資訊中心

Computer Center of Department of Computer Science, NYCU

# LDAP Authentication (1/3)

- ❑ `pkg install nss-pam-ldapd`
- ❑ Edit `/usr/local/etc/nslcd.conf`
- ❑ Edit `/etc/nsswitch.conf`
- ❑ Edit `/etc/pam.d/system`



# LDAP Authentication (2/3)

- Edit /usr/local/etc/nslcd.conf
  - Just like ldap.conf

```
# The user and group nslcd should run as.  
uid nslcd  
gid nslcd  
uri ldap://ldap.na.nctucs.cc  
base dc=na,dc=nctucs,dc=cc
```

# LDAP Authentication (3/3)

□ Edit /etc/nsswitch.conf

<https://www.freebsd.org/doc/en/articles/ldap-auth/client.html>

```
# nsswitch.conf(5) - name service switch configuration file
# $FreeBSD: releng/11.1/etc/nsswitch.conf
group: files ldap
passwd: files ldap
```

# References

- Understanding Directory Services
  - Beth Sheresh, Doug Sheresh - Sams Publishing
- LDAP System Administration: Putting Directories to Work
  - Gerald Carter - O'Reilly Media, Inc.
- The Lightweight Directory Access Protocol: X.500 Lite
  - Timothy A. Howes
- Internet protocol suite – Wikipedia
  - [https://en.wikipedia.org/wiki/Internet\\_protocol\\_suite#Comparison\\_of\\_TCP/IP\\_and\\_OSI\\_layering](https://en.wikipedia.org/wiki/Internet_protocol_suite#Comparison_of_TCP/IP_and_OSI_layering)