

**Brookshear-Computer Science: An Overview, 9<sup>th</sup> edition**

**Test Bank—Chapter Five (Algorithms)**

**Multiple Choice Questions**

1. Which of the following is an activity?

- A. Algorithm      B. Program      C. Process

2. Which of the following is a representation?

- A. Algorithm      B. Program      C. Process

3. Which of the following set of instructions defines an algorithm in the formal, strict sense?

- A.  $X \leftarrow 3;$   
    while  $(X < 5)$  do  
do  
     $(X \leftarrow X)$
- B.  $X \leftarrow 3;$   
    while  $(X < 5)$  do  
do  
     $(X \leftarrow X + 1)$
- C.  $X \leftarrow 3;$   
    while  $(X < 5)$  do  
do  
     $(X \leftarrow X - 1)$

4. Which of the following is not a means of repeating a block of instructions?

- A. Pretest loop      B. Posttest loop      C. Recursion      D. Assignment statement

5. When searching within the list

Lewis, Maurice, Nathan, Oliver, Pat, Quincy, Roger, Stan, Tom

which of the following entries will be found most quickly using the sequential search algorithm?

- A. Lewis      B. Pat      C. Tom

6. When searching within the list

Lewis, Maurice, Nathan, Oliver, Pat, Quincy, Roger, Stan, Tom

which of the following entries will be found most quickly using the binary search algorithm?

- A. Lewis      B. Pat      C. Tom

7. Which of the following lists would not be obtained at some point when applying the insertion sort algorithm to the list below?

Sylvia  
Nancy  
Lois  
Alice

- |          |          |          |         |
|----------|----------|----------|---------|
| A. Nancy | B. Alice | C. Alice | D. Lois |
| Sylvia   | Lois     | Sylvia   | Nancy   |
| Lois     | Nancy    | Nancy    | Sylvia  |
| Alice    | Sylvia   | Lois     | Alice   |

8. In general, an algorithm in which of the following categories is considered more efficient?

- A.  $\Theta(\lg n)$       B.  $\Theta(n)$       C.  $\Theta(n \lg n)$       D.  $\Theta(n^2)$

9. The insertion sort algorithm is an example of an algorithm in which of the following classes?

- A.  $\Theta(\lg n)$       B.  $\Theta(n)$       C.  $\Theta(n \lg n)$       D.  $\Theta(n^2)$

10. The binary search algorithm is an example of an algorithm in which of the following classes?

- A.  $\Theta(\lg n)$       B.  $\Theta(n)$       C.  $\Theta(n \lg n)$       D.  $\Theta(n^2)$

11. Under the assumption that X takes on only integer values, which of the following is the termination condition for the following loop?

```
while (X < 5) do
  ( . . . )
```

- A.  $X < 5$  B.  $X > 4$       C.  $X < 4$

12. Under the assumption that X takes on only integer values, which of the following is the termination condition for the following loop?

```
repeat ( . . . )
until (X < 5)
```

- A.  $X < 5$  B.  $X > 4$       C.  $X > 5$

13. Under the assumption that N takes on only integer values, which of the following is the termination condition in the following recursive procedure?

```
procedure xxx (N)
if (N < 5) then (apply the procedure xxx to the value N + 1)
else (print the value of N)
```

- A.  $N < 5$  B.  $N > 4$       C.  $N < 4$

14. Under the assumption that N takes on only integer values, which of the following is the termination condition in the following recursive procedure?

```
procedure xxx (N)
if (N < 5) then (print the value of N)
else (apply the procedure xxx to the value N - 1)
```

- A.  $N < 5$  B.  $N > 4$       C.  $N > 5$

15. Which of the following is a loop invariant at the point at which the test for termination is performed in the following loop structure?

```
X ← 3;
while (X < 5) do
  (X ← X + 2)
```

- A.  $X > 5$  B.  $X < 5$       C.  $X \geq 5$       D.  $X \leq 5$

16. Which of the following is a loop invariant at the point at which the test for termination is performed in the following loop structure?

```
X ← 3;
repeat (X ← X + 2)
until (X > 5)
```

- A.  $X > 5$  B.  $X < 8$  C.  $X \geq 5$  D.  $X \leq 6$

17. Which of the following is the base case in the recursive procedure below?

```
procedure xxx (N)
if (N = 0) then (print the value of N)
else (apply the procedure xxx to the value N - 1)
```

- A.  $N > 0$  B.  $N = 0$  C.  $N < 0$

18. Preconditions, postconditions, and loop invariants are examples of which of the following?

- A. Pseudocode B. Iterative structures C. Assertions D. Recursion

19. Which of the following does not print the same sequence of numbers as the others?

A. $X \leftarrow 5$ while $(X < 6)$ do (print the value of X; $X \leftarrow X + 1$ )	B. $X \leftarrow 4$ while $(X < 5)$ do ( $X \leftarrow X + 1$ ; print the value of X)	C. $X \leftarrow 5$ repeat (print the value of X; $X \leftarrow X + 1$ ) until $(X > 6)$
---	--	--

20. Which of the following is not a way of representing algorithms?

- A. Stepwise refinement B. Pseudocode C. Flowchart D. Programming language

## Fill-in-the-blank/Short-answer Questions

1. Define each of the following terms.

- A. Algorithm \_\_\_\_\_
- B. Program \_\_\_\_\_
- C. Process \_\_\_\_\_

2. List three of the primitives in the pseudocode developed in this chapter.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

3. What sequence of values will be printed when the following instructions are executed?

```

X ← 5;
if (X < 7) then (print the value 6;
                Y ← 6)
            else (print the value 4;
                Y ← 4)
if (Y < 5) then (print the value 3)
            else (print the value 2)

```

---

4. What sequence of values will be printed when the following instructions are executed?

```

X ← 5;
while (X < 7) do
    (print the value of X;
     X ← X + 1)
print the value of X;
while (X > 2) do
    (print the value of X;
     X ← X - 2)

```

---

5. What sequence of values would be printed if the procedure xxx described below were executed with the value of N being 9?

```

procedure xxx (N)
if (N < 4) then (print the value of N;
                apply the procedure yyy to the value 7)
            else (apply the procedure yyy to the value 2;
                print the value of N)

procedure yyy (N)
if (N < 5) then (print the value of N;
                apply the procedure zzz to the value 6)
            else (apply the procedure zzz to the value 5)

procedure zzz (N)
if (N = 5) then (print the value 7)
            else (print the value 8)

```

---

6. When searching for the entry X within the list

R, S, T, U, V, W, Z

how many entries will be considered before discovering that the entry is not present? (Note that the list is in alphabetical order.)

---

7. When searching for the entry X within the list

R, S, T, U, V, W, Z

how many entries will be considered before discovering that the entry is not present? (Note that the list is in alphabetical order.)

\_\_\_\_\_

8. Suppose the binary search algorithm was being used to search for the entry Tom in the list

Nathan, Oliver, Pat, Quincy, Rodger, Stan, Tom

A. What would be the first entry in the list to be considered? \_\_\_\_\_

B. What would be the second entry in the list to be considered? \_\_\_\_\_

9. At most, how many entries in a list of 5000 names will be interrogated when using the binary search algorithm?

\_\_\_\_\_

10. At most, how many entries in a list of 5000 names will be interrogated when using the sequential search algorithm?

\_\_\_\_\_

11. Which of the sequential or binary search algorithms would find the name Kelly in the list

John, Kelly, Lewis, Maurice, Nathan, Oliver, Pat, Quincy, Roger, Stan, Tom

more quickly?

\_\_\_\_\_

12. Which of the sequential or binary search algorithms would find the name Roger in the list

John, Kelly, Lewis, Maurice, Nathan, Oliver, Pat, Quincy, Roger, Stan, Tom

more quickly?

\_\_\_\_\_

13. What would be printed if the following instructions were executed?

```
X ← 3;
print the value of X;
Y ← 5;
if (X < Y) then (print the value 6)
               else (print the value 7)
```

\_\_\_\_\_

14. What would be printed if the following instructions were executed?

```
X ← 3;
while (X > 0) do
  (print the value of X;
```

$X \leftarrow X - 1)$

---

15. Answer the following questions in terms of the procedure xxx below.

```
procedure xxx (N)
  if (N < 7) then (print the value of N)
  else (add 3 to the value of N and
        print the value of N)
```

A. What value would be printed if the following procedure were executed with the value of N being 4?

---

B. What value would be printed if the following procedure were executed with the value of N being 9?

---

16. What sequence of numbers would be printed if the following procedure were executed with the value of N being 0?

```
procedure xxx (N)
  while (N < 4) do
    (print the value of N;
     N  $\leftarrow$  N + 2;
     print the value of N
    )
```

---

17. What sequence of numbers would be printed if the following procedure were executed with the value of N being 0?

```
procedure xxx (N)
  print the value of N;
  if (N < 5) then (apply the procedure xxx to the value N + 2);
  print the value of N
```

---

18. What sequence of numbers would be printed if the following procedure were executed with the value of N being 0?

```
procedure xxx (N)
  print the value of N;
  if (N < 2) then (apply the procedure xxx to the value N + 1)
  else (print the value of N)
  print the value of N
```

---

19. What sequence of numbers would be printed if the procedure named xxx as described below were executed with the value of N being 2?

```

procedure xxx (N)
print the value of N;
if (N < 3)
    then (apply procedure yyy
          to the value 4);
print the value of N

```

```

procedure yyy (N)
print the value of N;
apply the procedure xxx to the value 5;
print the value of N

```

20. Circle the portion of the program below in which control of the loop is initialized. Draw a rectangle around the portion in which the test for termination is performed. Underline the portion in which the state of the loop is moved toward the termination condition.

```

X ← 3;
while (X < 9) do
    (X ← X + 1)

```

21. Fill in the blank in the procedure below so that the procedure prints the integers from 0 up to the integer value it was given for N. That is, if the procedure is executed with the value of N being 3, it should print 0, 1, 2, 3.

```

procedure xxx (N)
if (_____) then (apply the procedure xxx to the value N - 1);
print the value of N)

```

22. Identify a loop invariant associated with the point in the loop below at which a test for termination is performed.

```

X ← 0;
repeat (print the value of X;
        X ← X + 2)
until (X > 6)

```

## Vocabulary (Matching) Questions

The following is a list of terms from the chapter along with descriptive phrases that can be used to produce questions (depending on the topics covered in your course) in which the students are ask to match phrases and terms. An example would be a question of the form, "In the blank next to each phrase, write the term from the following list that is best described by the phrase."

### Term

algorithm  
pseudocode  
assignment statement  
if-then-else statement  
stepwise refinement  
loop invariant

procedure  
recursion

### Descriptive Phrase

The fundamental concept in computer science  
An informal notation for representing algorithms  
A means of saving the result of a computation for future use  
A means of producing different actions depending on a condition  
A divide and conquer approach to problem solving  
A statement that is true each time a specific point in a repetitive process is reached  
A program segment isolated as a unit  
The technique of applying a program segment within itself

pretest loop	Looks before it leaps
proof of correctness	A formal means of verifying software
sequential search	Less efficient than the binary method
primitive	A basic building block

## General Format Questions

1. Rewrite the following routine using a pretest while statement.

```
repeat (print the value of X;
      X ← X + 1)
until (X > 5)
```

2. If numeric values are represented in two's complement notation, does the following program represent an infinite process? Explain your answer.

```
X ← 2
while (X > 0) do
  (X ← X + 1)
```

3. Identify a flaw in the control of the following loop.

```
X ← 3
while (X ≠ 8) do
  (X ← X + 2)
```

4. Do the following instructions define an algorithm? Explain your answer.

Write down all the positive odd integers.  
 Select the integer in the middle of the list.  
 Print the even integer that is one less than the selected odd integer.

5. Use a repeat loop structure to produce a non-recursive program segment that prints the same sequence of numbers as the following recursive procedure.

```
procedure xxx (N)
print the value of N:
if (N < 5) then (apply the procedure xxx to the value N + 1)
```

6. Use a while loop structure to produce a non-recursive program segment that prints the same sequence of numbers as the following recursive procedure.

```
procedure xxx (N)
print the value of N:
if (N < 5) then (apply the procedure xxx to the value N + 1)
```

7. Use a repeat loop rather than a while loop to accomplish the same results as the following program segment. Assume that X will have only integer values. (You may also use an if statement if you like.)

```
while (X < 5) do
  (print the value of X;
   X ← X + 1)
```



8. Suppose the statement “X is an integer and  $X < 5$ ” is a loop invariant at the point at which the test for termination is performed in the loop outlined below. What can be concluded about the value of X immediately after the loop is terminated?

```
repeat ( . . . )  
until (X > 3)
```

9. The pseudocode used in this chapter included both an if-then statement and an if-then-else statement. Show how the statement

```
if (X = 5) then ( . . . )  
    else ( . . . )
```

can be simulated with a program segment using only if-then statements.

10. The following procedure was designed to compute the largest integer whose square is no greater than N, where N is assumed to be a positive number. (If N is 5, then the procedure should report the value 2.) Find and correct the error.

```
procedure squareroot (N)  
X ← 0;  
while ( $X^2 \leq N$ ) do  
    (X ← X + 1);  
report the value of X
```