call void @llvm.dbg.value(metadata i32 %k.0, metadata !1007, metadata !DIExpression()), !dbg !1010 %cmp19 = icmp slt i32 %k.0, 5, !dbg !1014 br i1 %cmp19, label %for.body20, label %for.end35, !dbg !1015 [3/4] for.body20: ; preds = % for .cond18 %idxprom21 = sext i32 %i10.0 to i64, !dbg !1016 %arrayidx22 = getelementptr inbounds [100 x [10 x [5 x i32]]], [100 x [10 x [5 x i32]]]\* %a, i64 0, i64 %idxprom21, !dbg !1016 %idxprom23 = sext i32 %j14.0 to i64, !dbg !1016 %arrayidx24 = getelementptr inbounds [10 x [5 x i32]], [10 x [5 x i32]]\* %arrayidx22, i64 0, i64 %idxprom23, !dbg !1016 %sub = sub nsw i32 %k.0, 1, !dbg !1018 %idxprom25 = sext i32 %sub to i64, !dbg !1016 ; preds = % for.body20%arrayidx26 = getelementptr inbounds [5 x i32], [5 x i32]\* %arrayidx24, i64 0, i64 %idxprom25, !dbg !1016 %inc34 = add nsw i32 %k.0, 1, !dbg !1023 %0 = load i32, i32\* %arrayidx26, align 4, !dbg !1016 call void @llvm.dbg.value(metadata i32 %inc34, metadata !1007, metadata !DIExpression()), !dbg !1010 %add = add nsw i32 %0, 1, !dbg !1019 br label %for.cond18, !dbg !1024, !llvm.loop !1025 %idxprom27 = sext i32 %i10.0 to i64, !dbg !1020 %arrayidx28 = getelementptr inbounds [100 x [10 x [5 x i32]]], [100 x [10 x [5 x i32]]]\* %a, i64 0, i64 %idxprom27, !dbg !1020 %idxprom29 = sext i32 %j14.0 to i64, !dbg !1020 %arrayidx30 = getelementptr inbounds [10 x [5 x i32]], [10 x [5 x i32]]\* %arrayidx28, i64 0, i64 %idxprom29, !dbg !1020 %idxprom31 = sext i32 %k.0 to i64, !dbg !1020 %arrayidx32 = getelementptr inbounds [5 x i32], [5 x i32]\* %arrayidx30, i64 0, i64 %idxprom31, !dbg !1020 store i32 %add, i32\* %arrayidx32, align 4, !dbg !1021

br label %for.inc33, !dbg !1022

[2/5]

%k.0 = phi i32 [ 1, %for.body17 ], [ %inc34, %for.inc33 ], !dbg !1012

; preds = %for.inc33, %for.body17

for.cond18:

[0/1]

for.inc33: