

Community structure of the pseudofractal web

Alexei Vazquez^{1,*}

¹*Nodes & Links Ltd, Salisbury House, Station Road, Cambridge, CB1 2LA, UK*

(Dated: July 2, 2026)

The Ramsey community number r_κ is the smallest network size at which a graph is better described by a partition into communities than by no partition, under a prescribed detection rule. On a scale-free graph this question is confounded: a block model can split the network merely to absorb its degree distribution. I compute r_κ *analytically* for the deterministic pseudofractal scale-free web of Dorogovtsev, Goltsev, and Mendes, separating genuine community structure from degree heterogeneity with two closed-form detection rules. Under a plain Bernoulli stochastic block model, the web’s natural recursive bipartition is unpreferred while small and breaks at $r_\kappa = 1095$ nodes, with a log-evidence growing as $(\ln 3 - \frac{2}{3} \ln 2)n$. Under a degree-corrected model tested against the configuration-model null, the same partition survives, breaking far earlier at $r_\kappa = 42$, with a log-evidence growing as $(2 \ln 3 - \frac{4}{3} \ln 2)n$ —exactly twice the plain slope, and independent of the prior. Degree correction reverses the ordering of the candidate cuts, demoting the hub–leaf split and elevating the recursive one. Because the web is self-similar, the best description is not two communities but a nested hierarchy: the degree-corrected evidence keeps rising as the partition is refined, and is maximised at of order $\sqrt{n}$ communities of $\sim \sqrt{n}$ nodes. A purely local recursive rule thus builds true hierarchical community structure, over and above the scale-free degree sequence it also produces, in an exactly solvable setting.

I. INTRODUCTION

Community structure—the organisation of nodes into groups more densely connected internally than to the rest of the network—is one of the most studied features of complex networks [1–3]. It is usually attributed to node heterogeneity, but node heterogeneity is not a necessary condition: networks grown by purely local rules [4] routinely acquire communities as they grow [5]. To make this quantitative, Ref. [5] introduced the *Ramsey community number* r_κ , the minimum graph size that guarantees, with near-certainty, that a prescribed detection method reports two or more communities; the name evokes Ramsey theory, in which a large enough structure unavoidably contains ordered substructures [6]. A companion paper computed r_κ analytically for the circulant ring lattice $C_n(1, \dots, c)$, a homogeneous locally wired graph, using a Bernoulli stochastic block model (SBM) with symmetric Beta priors as the detection rule: the plain cycle ($c = 1$) is never partitioned ($r_\kappa = \infty$), while the next-nearest neighbour ring ($c = 2$) acquires a finite r_κ of a few tens of nodes, with a log-evidence growing as $(\ln 2) n$ [?].

Those results rest on a special feature of the ring: it is *degree regular*. In a regular graph a two-block partition can only capture assortative community structure, because there is no degree variation to be explained away. Most networks of interest are not regular, and the sharpest test of the emergence idea is a graph that is strongly heterogeneous, where the naive question “does it want to split?” becomes confounded. On a scale-free graph a plain block model will happily split the network into a high-degree core and a low-degree periphery, not

because the two groups form communities but simply because they have different mean degrees. Distinguishing genuine community structure from this degree artefact is the central issue of degree-corrected community detection [7].

Here I address both questions at once, analytically, for a canonical deterministic scale-free graph: the pseudofractal web of Dorogovtsev, Goltsev, and Mendes [8]. This graph is built by a fixed recursive rule, has a power-law degree distribution with exponent $\gamma = 1 + \ln 3 / \ln 2 \simeq 2.585$, and—crucially for an exact treatment—has a natural recursive bipartition whose block sizes and edge counts are known in closed form at every generation. I compute the Bayesian evidence for this partition under two detection rules. The first is the plain Bernoulli SBM. The second is a degree-corrected Poisson SBM tested against the configuration-model null, which holds the degree sequence fixed and asks whether the partition explains structure *beyond* what the degrees already imply. Both evidences are single closed-form expressions, so the transition and r_κ follow exactly.

The answers are clean and complementary. Under the plain SBM the web is unpartitioned while small and breaks at $r_\kappa = 1095$ nodes, with $\log R \sim (\ln 3 - \frac{2}{3} \ln 2)n$. Under degree correction the same partition breaks much earlier, $r_\kappa = 42$, with a log-evidence growing exactly twice as fast, $\log R_{dc} \sim (2 \ln 3 - \frac{4}{3} \ln 2)n$, and both slopes are independent of the prior. Degree correction reverses the ordering that the plain model assigns to the competing cuts: the hub–leaf split that the plain model most prefers is demoted, and the recursive split is elevated. Pushing this further, the self-similarity of the web makes the optimal description a nested hierarchy of communities, refined down to $\sim \sqrt{n}$ blocks. The recursion therefore builds true hierarchical community structure on top of its scale-free degree sequence. The rest of the paper de-

* alexei.vazquez@gmail.com




FIG. 1. (a) Posterior weight of the recursive branch partition, Eq. (7), versus network size n (log scale). Red: plain Bernoulli SBM; blue: degree-corrected (config-null) model. Line styles denote $\alpha = 0.5$ (dotted), 1 (solid), 2 (dashed). The dash-dotted line marks $q = 0.99$; vertical guides mark the Ramsey community numbers $r_\kappa^{\text{plain}} = 1095$ and $r_\kappa^{\text{dc}} = 123$ at that certainty. (b) The magnitude of the log-evidence ratio, $|\log R|$; both models grow linearly in n , with prior-independent slopes $\ln 3 - \frac{2}{3} \ln 2$ (plain) and $2 \ln 3 - \frac{4}{3} \ln 2$ (degree-corrected), the latter exactly twice the former.

finer the web and the partition (Sec. II), derives the plain evidence ratio and its transition (Sec. III), constructs the degree-corrected evidence and shows the partition survives it (Sec. IV), resolves the hierarchical community structure (Sec. V), reports the Ramsey community numbers (Sec. VI), and concludes (Sec. VII).

II. MODEL AND DETECTION RULE

A. The pseudofractal web

The pseudofractal scale-free web [8] is grown deterministically. Start ($t = 0$) from a triangle: three vertices and three edges. At each subsequent generation, every existing edge spawns one new vertex, joined to both endpoints of that edge; old edges are retained. Counting gives, at generation t ,

$$n_t = \frac{3}{2}(3^t + 1), \quad E_t = 3^{t+1}, \quad (1)$$

so the mean degree $2E_t/n_t \rightarrow 4$ and the graph is sparse. A vertex introduced at generation τ has its degree doubled at every later generation, so degrees take the values $2^{t-\tau+1}$ and their distribution is a power law $P(k) \sim k^{-\gamma}$ with $\gamma = 1 + \ln 3 / \ln 2 \simeq 2.585$. The three seed vertices are permanent hubs of maximal degree 2^{t+1} .

B. The recursive branch bipartition

Every non-seed vertex descends from exactly one edge, which in turn belongs to one of the three “branches” rooted on the three sides of the initial triangle. This assigns a branch label $b \in \{0, 1, 2\}$ to each of the $n_t - 3$ non-seed vertices, $(3^t - 1)/2$ per branch, while the three seed hubs are shared. The natural recursive bipartition places one branch together with the three hubs in block 1, and the other two branches in block 2; it respects the $\mathbb{Z}_2$ symmetry exchanging the two branches of block 2. Writing $T \equiv t$ for brevity, the block sizes and the within/between edge counts are all closed form (verified against direct construction through $T = 8$):

$$n_1 = \frac{1}{2}(3^T + 5), \quad n_2 = 3^T - 1, \quad (2)$$

$$E_1 = 3^T + 2, \quad E_2 = 2 \cdot 3^T + 2 - 2^{T+2}, \quad (3)$$

$$E_{12} = 2^{T+2} - 4, \quad (4)$$

with $n_1 + n_2 = n_T$ and $E_1 + E_2 + E_{12} = E_T = 3^{T+1}$. The seam between the two blocks is thin: $E_{12} = 2^{T+2} - 4$ grows only as $2^T = n^{\ln 2 / \ln 3} \simeq n^{0.631}$, so the fraction of crossing edges $E_{12}/E_T \sim (2/3)^T \rightarrow 0$. The two branches are joined by a vanishing density of edges (Fig. 2)—the structural fact that drives everything below.

C. Stochastic block model evidence

The detection rule is Bayesian model comparison between the bipartition of Sec. IIB and the

Hub-leaf cut (Fork 1, plain Bernoulli SBM)
core vs periphery | $\log R = 150.8$




FIG. 3. The hub-leaf (core-periphery) partition of the same web ($T = 4$), separating the highest-degree vertices (core) from the low-degree leaves (periphery). The plain Bernoulli SBM rates this cut far above the recursive one of Fig. 2, but it merely tracks the degree gradient: the configuration-model null absorbs it, and the degree-corrected model demotes it (Table III).

T	n	cut	plain $\log R$	$\log R_{dc}$
5	366	branch	-52.08	159.92
5	366	hub-leaf	508.74	19.32
7	3282	branch	505.52	2554.23
7	3282	hub-leaf	4844.88	209.25

TABLE III. Which cut wins depends on the null ($\alpha = 1$). The plain SBM prefers the hub-leaf cut (a degree artefact); the degree-corrected model prefers the recursive branch cut (genuine community structure).

persists once degrees are fixed. (A local search over all bipartitions under R_{dc} finds an optimum that overlaps the branch cut by $\approx 65\%$; the closed-form branch cut is thus a tractable witness of the degree-corrected structure, not necessarily its global optimum—mirroring the role of the balanced arc for the ring.)

V. HIERARCHICAL COMMUNITY STRUCTURE

The branch cut of Sec. IV lumps two of the three descent branches into one block, so the thin seam between them is misread as within-block structure. Separating all three branches should therefore fit better. Placing each branch with one seed hub in its own block gives a symmetric three-community partition whose counts are again

Three-community partition (one branch each)
three thin seams | $\log R_{dc} = 101.7$




FIG. 4. The symmetric three-community partition of the web ($T = 4$), one descent branch per block. All three within-block densities exceed the configuration-model expectation and all three seams (highlighted) vanish as $(2/3)^T$, so the degree-corrected evidence, Eq. (20), beats the two-block cut of Fig. 2.

closed form (verified through $T = 8$):

$$n_r = \frac{1}{2}(3^T + 1), \quad \kappa_r = 2 \cdot 3^T, \quad e_{rr} = 3^T - 2^T, \quad e_{rs} = 2^T, \quad (18)$$

for each block r and each pair $r \neq s$. With $\Omega_{rr} = 3^T/3$ and $\Omega_{rs} = 2 \cdot 3^T/3$ from Eq. (9), every block is assortative and every seam vanishing,

$$\frac{e_{rr}}{\Omega_{rr}} = 3(1 - (2/3)^T) \rightarrow 3, \quad \frac{e_{rs}}{\Omega_{rs}} = \frac{3}{2}(2/3)^T \rightarrow 0, \quad (19)$$

a genuine three-community structure. Its degree-corrected evidence exceeds the two-block value at every size (Fig. 4) and grows as

$$\log R_{dc}^{(3)} \sim 2 \ln 3 n \approx 2.197 n, \quad (20)$$

larger than the two-block slope (17) by exactly $\frac{4}{3} \ln 2 n$ —the evidence the branch cut forfeited by merging two communities.

The construction is self-similar, so the refinement does not stop at three. Each branch is itself a pseudofractal web grown from an edge, and removing the generation- d edge set partitions the graph into 3^{d+1} statistically identical sub-webs. The degree-corrected evidence keeps rising as the resolution is refined (Table IV); at fixed level d it grows as

$$\log R_{dc}^{(d)} \sim 2(d+1) \ln 3 n, \quad (21)$$

so each additional level adds a further $\simeq 2 \ln 3 n$. Deeper partitions win until the blocks shrink to where the seams

r_κ with the branching number—each within reach of the present closed-form approach.

ACKNOWLEDGMENTS

The calculations, computer scripts, and text of this manuscript were generated by Claude Opus 4.8 (Anthropic). The analytical results were verified with an accompanying open-source script, and the closed-form edge and degree counts were checked against direct construction of the web through eight generations.

-
- [1] M. Girvan and M. E. J. Newman, *Proc. Natl. Acad. Sci. U.S.A.* **99**, 7821 (2002).
 - [2] S. Fortunato, *Phys. Rep.* **486**, 75 (2010).
 - [3] S. Fortunato and D. Hric, *Phys. Rep.* **659**, 1 (2016).
 - [4] A. Vazquez, *Phys. Rev. E* **67**, 056104 (2003).
 - [5] A. Vazquez, *Phys. Rev. E* **111**, 064314 (2025).
 - [6] F. P. Ramsey, *Proc. London Math. Soc.* **s2-30**, 264 (1930).
 - [7] B. Karrer and M. E. J. Newman, *Phys. Rev. E* **83**, 016107 (2011).
 - [8] S. N. Dorogovtsev, A. V. Goltsev, and J. F. F. Mendes, *Phys. Rev. E* **65**, 066122 (2002).
 - [9] M. E. J. Newman, *Proc. Natl. Acad. Sci. U.S.A.* **103**, 8577 (2006).
 - [10] T. P. Peixoto, *Phys. Rev. X* **4**, 011047 (2014).