Build: Star Rating Component

1 min read Updated 23 Apr 2026 Topic 56 of 62

Problem: Build a star rating component with hover preview and click to select.

What This Tests: Controlled component, hover state management, dynamic styling.

jsx

JSX Copy

```jsx
function StarRating({ maxStars = 5, onRate }) {
  const [rating, setRating] = useState(0);
  const [hoverRating, setHoverRating] = useState(0);

  const handleClick = (value) => {
    setRating(value);
    if (onRate) onRate(value);
  };

  return (
    <div style={{ display: 'flex', gap: 4, cursor: 'pointer' }}>
      {Array.from({ length: maxStars }, (_, i) => i + 1).map(star => (
        <span
          key={star}
          onClick={() => handleClick(star)}
          onMouseEnter={() => setHoverRating(star)}
          onMouseLeave={() => setHoverRating(0)}
          style={{ fontSize: 32, color: star <= (hoverRating || rating) ?
        >
          ★
        </span>
      ))}
      <span style={{ marginLeft: 8 }}>{rating} / {maxStars}</span>
    </div>
```

Key Concepts: Hover state separate from selected state, `hoverRating || rating` for preview fallback, callback prop for parent communication, `Array.from` for dynamic star count.

QUICK CHECK — no marks, just for you.

1. In the StarRating component, what happens when the user clicks the third star?

- ○ handleClick(3) runs and calls onRate(3), but rating is only updated by the parent passing a new prop back down
- ○ handleClick(3) runs, which sets rating to 3 and calls onRate(3) only if the onRate prop was passed
- ○ handleClick(3) runs and always calls onRate(3), throwing a TypeError when the parent omits onRate
- ○ handleClick(3) runs, which sets hoverRating to 3 and leaves rating unchanged until the mouse leaves

Check answer

2. The component builds its star values with Array.from and colours a star when star <= (hoverRating || rating). Given maxStars = 5, hoverRating = 0 and rating = 3, what does this snippet print?

JAVASCRIPT Copy

```javascript
const maxStars = 5;
const hoverRating = 0;
const rating = 3;

const stars = Array.from({ length: maxStars }, (_, i) => i + 1);
```

- [ ] `[1,2,3,4,5]`
  `5`
- [ ] `[1,2,3,4,5]`
  `0`
- [ ] `[1,2,3,4,5]`
  `3`
- [ ] `[0,1,2,3,4]`
  `3`

Check answer

3. The user has already clicked the 5th star, so rating is 5. They now hover over the 2nd star. What does the component render while the pointer sits there?

- [ ] Stars 1-2 are gold and 3-5 are grey, while the text label still reads 5 / 5
- [ ] All five stars are gold and the text label reads 5 / 5, because rating wins over hoverRating
- [ ] All five stars are gold and the text label reads 2 / 5, because only the label tracks hover
- [ ] Stars 1-2 are gold and 3-5 are grey, and the text label changes to 2 / 5

Check answer

React.js Interview Kit

LEARN MORE

ARTICLES & DOCS

State: A Component's Memory
react.dev


VIDEOS



Star rating component — step by step
YouTube



Star rating (interview question)
YouTube



Create a star rating component
YouTube

Hand-picked references for this lesson.