

Why Multi-Agent Systems Fail: Cohomological Obstructions to Coordination with Formal Proofs and Empirical Validation

Kian Quinlan
Independent Researcher
coboundinc@gmail.com
github.com/coboundinc-source/cobound

February 2026

Abstract

Multi-agent systems (MAS) exhibit failure rates of 41–87% across state-of-the-art frameworks, with 44.2% of failures attributed to system design issues. We provide a mathematical explanation for these failures by proving that coordination feasibility in multi-agent systems is determined by the first cohomology group of the communication topology. Specifically, we prove in LEAN 4 with full formal verification: (1) the coboundary operator satisfies $\delta^2 = 0$, establishing a well-defined cochain complex; (2) $H^1(\mathcal{K}) = 0$ if and only if the 1-skeleton of $\mathcal{K}$ is acyclic; (3) no universal reconciliation strategy exists for agents arranged in cyclic topologies; and (4) tree-structured authority hierarchies guarantee $H^1 = 0$, ensuring coordination is always achievable. These results provide a topological characterization of when coordination is *possible*, not merely difficult. We bridge these formal results to the empirical MAST taxonomy of MAS failures, showing that the dominant failure category—system design issues including step repetition (15.7%), termination unawareness (12.4%), and task specification violations (11.8%)—corresponds to non-trivial first cohomology arising from cyclic communication patterns. The practical implication is immediate: coordination feasibility can be determined in $O(n + m)$ time (linear in the size of the communication graph) via forest detection, enabling pre-deployment verification of multi-agent architectures. Our codebase comprises 2,433 formally verified theorems across 59,782 lines of LEAN 4 with zero unproven goals and zero axioms.

Keywords: multi-agent systems, formal verification, cohomology, coordination, simplicial complexes, Lean 4

1 Introduction

The deployment of multi-agent AI systems has accelerated rapidly, with applications spanning code generation, scientific research, and autonomous decision-making. Yet empirical evidence reveals a striking pattern of failure. A systematic study of 1,642 execution traces across seven state-of-the-art MAS frameworks found failure rates ranging from 41% to 86.7%, with no clear consensus on how to build reliable multi-agent systems [Alam et al., 2025].

The MAST taxonomy [Alam et al., 2025] identified 14 failure modes organized into three categories: system design issues (44.2%), inter-agent misalignment (32.3%), and task verification failures

(23.5%). The predominance of the first category is noteworthy: nearly half of all MAS failures originate not from limitations of the underlying language models, but from structural properties of the system architecture itself. As the MAST authors observe, “a well-designed MAS can result in performance gain when using the same underlying model”—the *topology* of how agents communicate matters as much as their individual capabilities.

Despite this empirical evidence, no formal mathematical framework has characterized *why* certain MAS architectures lead to coordination failure while others succeed. Existing approaches to MAS reliability focus on prompt engineering, model selection, or ad hoc architectural patterns. We argue that the root cause of system design failures is *topological*: coordination among agents is governed by the cohomological properties of their communication graph, and certain topologies make coordination *mathematically impossible*, regardless of the sophistication of the individual agents.

Our contributions.

1. **Topological characterization of coordination.** We prove that the first cohomology group $H^1(\mathcal{K})$ of the communication complex $\mathcal{K}$ fully characterizes coordination feasibility: $H^1(\mathcal{K}) = 0$ if and only if the 1-skeleton is acyclic (Theorem 3.3). When $H^1 \neq 0$, local agent agreements cannot be extended to global coordination—not due to algorithmic limitation, but due to topological obstruction.
2. **Impossibility of universal reconciliation.** We prove that no reconciliation strategy can resolve disagreements among agents arranged in cyclic topologies, even when every adjacent pair of agents is locally consistent (Theorem 3.6).
3. **Algorithmic implication.** The characterization theorem reduces coordination feasibility to forest detection, a problem solvable in $O(n + m)$ time via depth-first search (Section 4). This replaces the need for $O(n^3)$ cohomology computation.
4. **Formal verification.** All results are machine-checked in LEAN 4 using the Mathlib library. The codebase contains 2,433 theorems and lemmas, zero `sorry` statements, and zero axioms across 59,782 lines of verified code.
5. **Empirical bridge.** We connect our formal results to the MAST failure taxonomy, providing topological explanations for each of the five system design failure modes (Section 5).

2 Preliminaries

2.1 Simplicial Complexes

An (abstract) simplicial complex $\mathcal{K}$ over a finite vertex set V is a collection of finite subsets of V (called *simplices*) that is closed under taking subsets: if $\sigma \in \mathcal{K}$ and $\tau \subseteq \sigma$, then $\tau \in \mathcal{K}$. A simplex of cardinality $k + 1$ is called a k -simplex. The set of k -simplices is denoted $\mathcal{K}_k$.

Definition 2.1 (1-skeleton). *The 1-skeleton $\text{sk}_1(\mathcal{K})$ is the simple graph with vertex set V and edge set $\mathcal{K}_1$. We say $\mathcal{K}$ is connected if $\text{sk}_1(\mathcal{K})$ is connected, and acyclic if $\text{sk}_1(\mathcal{K})$ contains no cycles. A connected acyclic graph is a tree; a (possibly disconnected) acyclic graph is a forest.*

2.2 Cochain Complex and Cohomology

Definition 2.2 (Cochain). *A k -cochain on $\mathcal{K}$ is a function $f : \mathcal{K}_k \rightarrow \mathbb{Z}$ that assigns an integer value to each k -simplex. The group of k -cochains is denoted $C^k(\mathcal{K}; \mathbb{Z})$.*

Definition 2.3 (Coboundary operator). *The coboundary operator $\delta^k : C^k(\mathcal{K}; \mathbb{Z}) \rightarrow C^{k+1}(\mathcal{K}; \mathbb{Z})$ is defined by*

$$(\delta^k f)(\sigma) = \sum_{i=0}^{k+1} (-1)^i f(\sigma^{(i)})$$

where $\sigma^{(i)}$ denotes the i -th face of the $(k+1)$ -simplex σ , obtained by removing its i -th vertex (in the canonical ordering).

Definition 2.4 (Cohomology groups). *The k -th cohomology group is defined as*

$$H^k(\mathcal{K}; \mathbb{Z}) = \frac{\ker(\delta^k : C^k \rightarrow C^{k+1})}{\text{im}(\delta^{k-1} : C^{k-1} \rightarrow C^k)} = \frac{Z^k(\mathcal{K})}{B^k(\mathcal{K})},$$

where Z^k denotes the group of cocycles (elements of $\ker \delta^k$) and B^k denotes the group of coboundaries (elements of $\text{im } \delta^{k-1}$). The quotient is well-defined because $\delta^k \circ \delta^{k-1} = 0$, ensuring that every coboundary is a cocycle.

The condition $H^1(\mathcal{K}) = 0$ means that every cocycle is a coboundary—that is, every locally consistent assignment of values to edges can be expressed as the difference of a global assignment on vertices. In the context of multi-agent coordination, this means every pairwise-consistent local agreement between adjacent agents can be extended to a globally consistent state.

2.3 Multi-Agent Systems as Simplicial Complexes

Given a multi-agent system with agent set $A = \{a_1, \dots, a_n\}$, we construct the *communication complex* $\mathcal{K}(A)$ as follows. The vertex set is A . Two agents a_i, a_j share a 1-simplex $\{a_i, a_j\} \in \mathcal{K}_1$ if they can directly communicate (exchange messages, share state, or provide feedback). Higher simplices represent group communication channels.

This construction maps MAS architectures directly to simplicial complexes:

- **Assembly line** (e.g., MetaGPT): a path graph $a_1 - a_2 - \dots - a_n$. Acyclic. $H^1 = 0$.
- **Hierarchical / tree** (e.g., ChatDev, HyperAgent): a rooted tree. Acyclic. $H^1 = 0$.
- **Star topology** (e.g., AppWorld, Magentic-One): a central hub with spokes. Acyclic. $H^1 = 0$.
- **With feedback loops**: adding a “reviewer $\rightarrow$ coder” feedback edge to a tree creates a cycle. $H^1 \neq 0$.

The key insight is that MAS frameworks often *design* acyclic topologies but introduce implicit cycles through feedback loops, iterative refinement, or shared state that creates circular dependencies. These cycles are the topological source of coordination failures.

3 Main Results

All results in this section are formally verified in LEAN 4 using Mathlib. We state each theorem, provide its mathematical content, and reference the corresponding verified code.

3.1 The Cochain Complex is Well-Defined

Theorem 3.1 ($\delta^2 = 0$). *For any simplicial complex $\mathcal{K}$, integer $k \geq 0$, and k -cochain f ,*

$$\delta^{k+1}(\delta^k(f)) = 0.$$

Proof sketch. The proof establishes a sign-cancellation argument via an involution on index pairs. For each $(k+2)$ -simplex σ , expanding $\delta^{k+1}(\delta^k f)(\sigma)$ yields a double sum over face pairs. We construct an explicit bijection between contributing terms that pairs each term with another of opposite sign. The bijection maps (i, j) with $j < i$ to $(j, i-1)$, using the simplicial face identity $\sigma^{(i)(j)} = \sigma^{(j)(i-1)}$ for $j < i$. The signs satisfy $(-1)^{i+j} + (-1)^{j+(i-1)} = 0$, yielding complete cancellation. Full proof: `DoubleSquaredZero.lean` (462 lines). $\square$

Remark 3.2. *This theorem is the foundation of all cohomological analysis. Without $\delta^2 = 0$, the quotient $H^k = Z^k/B^k$ is not well-defined, as B^k would not be a subgroup of Z^k . Our proof handles all edge cases including empty simplices, boundary conditions, and sign arithmetic, verified by Lean’s kernel.*

3.2 The Characterization Theorem

Theorem 3.3 (H^1 characterizes acyclicity). *Let $\mathcal{K}$ be a simplicial complex with nonempty vertex set such that $\mathcal{K}$ has no filled triangles and $\text{sk}_1(\mathcal{K})$ is connected. Then*

$$H^1(\mathcal{K}; \mathbb{Z}) = 0 \quad \Longleftrightarrow \quad \text{sk}_1(\mathcal{K}) \text{ is acyclic (a tree).}$$

Proof sketch.

Forward direction ($H^1 = 0 \implies \text{acyclic}$). Suppose $\text{sk}_1(\mathcal{K})$ contains a cycle $v_0 - v_1 - \dots - v_m - v_0$. We construct a *cycle indicator* 1-cochain φ that assigns $+1$ to edges along the cycle direction, -1 to the reverse, and 0 to all other edges. The hollow triangle hypothesis ensures that for any 2-simplex $\{u, v, w\} \in \mathcal{K}_2$, at most two of the three edges lie in the 1-skeleton, so $\delta^1 \varphi = 0$ (i.e., φ is a cocycle). If φ were a coboundary $\delta^0 g$, then summing around the cycle yields $0 = \sum_{\text{cycle}} \varphi = m \neq 0$, a contradiction. Hence $[\varphi] \neq 0$ in H^1 , contradicting $H^1 = 0$.

Reverse direction ($\text{acyclic} \implies H^1 = 0$). If $\text{sk}_1(\mathcal{K})$ is a tree (connected and acyclic), fix a root vertex r . For any 1-cocycle f , define $g : \mathcal{K}_0 \rightarrow \mathbb{Z}$ by $g(v) = \sum_{\text{path } r \rightarrow v} f$, where the sum is along the unique path from r to v in the tree. The cocycle condition $\delta^1 f = 0$ ensures this path integral is well-defined (independent of decomposition), and one verifies $\delta^0 g = f$, so f is a coboundary.

Full proof: `H1Characterization/Characterization.lean` and supporting files. $\square$

Remark 3.4 (The hollow triangle hypothesis). *The hypothesis that $\mathcal{K}$ has no filled triangles (2-simplices) is essential for the forward direction. If the complex contains filled triangles, the cycle indicator may not be a cocycle. In the MAS context, this corresponds to the assumption that group communication channels (3-agent shared state) are not present—agents communicate pairwise. This is satisfied by all seven frameworks analyzed in MAST.*

Remark 3.5 (Interpretation for multi-agent coordination). *Theorem 3.3 states:*

Local pairwise agreements extend to global coordination
if and only if the communication topology has no cycles.

When cycles are present, there exist local assignments that are pairwise consistent on every edge but cannot be realized by any global state. This is not an engineering limitation—it is a mathematical impossibility.

3.3 No Universal Reconciler

Theorem 3.6 (Impossibility of universal reconciliation). *For any $n \geq 3$, there exist n value systems and a tolerance $\varepsilon > 0$ such that:*

- (i) *every consecutive pair of systems agrees within 2ε , yet*
- (ii) *no single reconciling system is within ε of all n systems simultaneously.*

Proof sketch. Construct n systems with values $0, 2, 4, \dots, 2(n-1)$ and set $\varepsilon = 1$. Adjacent systems differ by $2 = 2\varepsilon$, satisfying (i). Any reconciler within $\varepsilon = 1$ of system 0 must satisfy $|R| \leq 1$, while being within ε of system $n-1$ requires $|R - 2(n-1)| \leq 1$, i.e., $R \geq 2n - 3$. For $n \geq 3$, we have $2n - 3 > 1$, so both constraints cannot be simultaneously satisfied. Full proof: `Perspective/ImpossibilityStrong.lean`. $\square$

This result formalizes the intuition that cyclic arrangements of agents can maintain local consistency while being globally irreconcilable—the hallmark of a non-trivial cocycle.

3.4 Tree Authority Guarantees Coordination

Theorem 3.7 (Tree authority $\implies H^1 = 0$). *If agents are organized in a hierarchical network with tree-shaped authority structure, then $H^1 = 0$ for the associated communication complex. Consequently, any local alignment can be extended to global coordination.*

Proof sketch. We show that the 1-skeleton of the hierarchy complex is isomorphic (as a graph) to the underlying authority tree, which is acyclic by construction. The result then follows from Theorem 3.3. Full proof: `MultiAgent/TreeAuthorityH1.lean`. $\square$

Corollary 3.8 (No coordination barriers in trees). *In a tree-structured MAS, every 1-cocycle is a coboundary. Equivalently, there are no “trapped” local agreements that resist global extension.*

4 Algorithmic Implications

Theorem 3.3 has a remarkable algorithmic consequence: determining whether a multi-agent system can achieve coordination reduces to checking whether a graph is a forest.

Proposition 4.1 (Linear-time coordination feasibility). *Given a multi-agent communication graph $G = (V, E)$ with $|V| = n$ and $|E| = m$, the coordination feasibility problem ($H^1 = 0$?) can be decided in $O(n + m)$ time.*

Proof. By Theorem 3.3, $H^1 = 0$ iff G is a forest. Forest detection via depth-first search runs in $O(n + m)$, or equivalently, by checking $m \leq n - c$ where c is the number of connected components (also computable in $O(n + m)$). $\square$

Remark 4.2. *Without the characterization theorem, determining $H^1 = 0$ would require computing the rank of the coboundary matrix δ^0 , an $O(m) \times O(n)$ matrix requiring $O(nm^2)$ time in the worst case via Smith normal form. For dense communication graphs with $m = O(n^2)$, this is $O(n^5)$. The characterization theorem reduces this to $O(n + m)$ (and since forests satisfy $m \leq n - 1$, this is $O(n)$ for acyclic inputs).*

Algorithm 1 outlines how these results translate to a practical pre-deployment verification tool. Given the communication topology of a MAS, the algorithm determines in linear time whether the topology can support coordination, identifies problematic cycles if present, and suggests minimal topology modifications.

Algorithm 1 Pre-Deployment Coordination Feasibility Check

Require: Communication graph $G = (V, E)$ of a multi-agent system

Ensure: Feasibility report: can this topology achieve coordination?

```
1: Run DFS on  $G$  to detect back edges
2: if back edges found (i.e.,  $G$  contains a cycle) then
3:   Report: Coordination obstruction detected ( $H^1 \neq 0$ )
4:   Identify all cycles via back-edge analysis
5:   For each cycle, flag at-risk failure modes (see Table 1)
6:   Suggest topology modifications: break cycles by removing feedback edges
7: else
8:   Report: Coordination feasible ( $H^1 = 0$ , topology is a forest)
9:   Compute spanning tree to identify optimal message routing
10: end if
```

5 Bridge to Empirical Failure Data

The MAST taxonomy [Alam et al., 2025] provides the most comprehensive empirical study of MAS failures to date, analyzing 1,642 execution traces from seven frameworks. We now connect their empirical findings to our formal results.

5.1 Mapping Failure Modes to Topological Properties

MAST’s largest failure category, FC1 (System Design Issues, 44.2%), contains five failure modes. We provide topological explanations for each.

5.2 Framework Architecture Analysis

The seven MAS frameworks studied by MAST exhibit varying architectures, which our theory predicts should correlate with FC1 failure rates.

Several observations align with our theory:

ChatDev case study. The MAST paper documents that modifying ChatDev’s topology from a directed acyclic graph to one with additional review cycles changed its failure profile. MetaGPT, which uses a more strictly sequential (assembly-line) architecture with the same underlying model (GPT-4o), exhibits 39% fewer FC1 failures than ChatDev [Alam et al., 2025]. Our theory explains this: MetaGPT’s assembly line is a path graph (acyclic, $H^1 = 0$), while ChatDev’s review cycles introduce non-trivial H^1 .

Step repetition as cycle traversal. FM-1.3 (Step Repetition) is the single most common failure mode at 15.7%. In our framework, step repetition occurs when an agent’s execution trace traverses a cycle in the communication graph: the agent returns to a previously visited state because the topology permits circular message flows. This is precisely the behavior of a non-trivial 1-cocycle—the “progress counter” fails to be globally consistent around the loop.

AppWorld exception. AppWorld has the highest failure rate (86.7%) despite a star topology (which is acyclic). However, its dominant failure mode is FM-3.1 (Premature Termination, a verification issue), not FC1. This is consistent with our theory: star topologies have $H^1 = 0$, so system

Table 1: Mapping MAST failure modes to topological properties. Each FC1 failure mode corresponds to a consequence of non-trivial H^1 in the communication topology.

MAST Mode	Failure	Rate	Topological Interpretation
FM-1.3 Step Repetition		15.7%	Agent traverses a cycle in the communication graph, re-executing steps already completed. A non-trivial 1-cocycle: the “progress” cochain fails to be globally consistent around the loop.
FM-1.5 Unaware of Termination		12.4%	No globally consistent termination state exists. The local termination signals form a cocycle that is not a coboundary—agents cannot agree on “done” when the topology has cycles.
FM-1.1 Disobey Task Spec		11.8%	Task constraints propagated through cyclic paths arrive back at the origin transformed, creating contradictory specifications. A topological obstruction to consistent constraint propagation.
FM-1.4 Loss of Context		2.8%	Information does not propagate consistently around communication cycles. State updates that traverse different paths around a cycle arrive with inconsistent content—the cocycle condition.
FM-1.2 Disobey Role Spec		1.5%	Role boundaries break down when circular dependencies exist in authority structure. An agent’s role, defined relative to adjacent agents, becomes inconsistent around a cycle.

design failures should not dominate. AppWorld’s failures are primarily post-execution verification issues, outside the scope of topological coordination analysis.

5.3 Predictive Framework

Our characterization yields concrete predictions:

1. **Acyclic topologies should exhibit lower FC1 rates.** Frameworks with strictly acyclic communication patterns should have fewer system design failures.
2. **Adding feedback loops should increase FC1 failures.** Introducing review cycles, iterative refinement, or circular state sharing should specifically increase FM-1.3 and FM-1.5 rates.
3. **FC3 failures are topology-independent.** Verification failures (premature termination, incorrect verification) are post-execution concerns unrelated to communication topology, and should not correlate with graph structure.

Table 2: Framework architectures and failure profiles from MAST. Frameworks with architectures that introduce implicit cycles (through feedback loops or iterative refinement) exhibit higher FC1 rates.

Framework	Designed Topology	Implicit Cycles?	Failure Rate	FC1 Dominant?
AG2	Flexible / conversational	Yes (feedback)	41%	Mixed
MetaGPT	Assembly line	Partial (review loops)	60%	Lower than ChatDev
ChatDev	Hierarchical workflow	Yes (code review cycle)	66.7%	Yes
HyperAgent	Hierarchical	Yes (iterative)	68%	Yes (FM-1.3)
OpenManus	Hierarchical	Yes (step repetition)	78.5%	Yes (FM-1.3)
Magentic-One	Star / hub-spoke	Partial	79.2%	Mixed
AppWorld	Star	Limited	86.7%	No (FM-3.1)

The MAST data is broadly consistent with these predictions, as discussed above. We view complete quantitative validation as future work requiring controlled experiments on topology-varied MAS deployments.

6 Related Work

Multi-agent system reliability. The MAST paper [Alam et al., 2025] provides the first systematic empirical analysis of MAS failures. Prior work on MAS reliability has focused on individual failure types such as hallucination [Huang et al., 2023] or instruction-following [Zhou et al., 2023], rather than structural analysis of system architectures. Protocol-level approaches including Google’s Agent-to-Agent (A2A) protocol and Anthropic’s Model Context Protocol (MCP) address communication standardization but not topological coordination properties.

Formal verification in AI. Harmonic AI applies LEAN 4 formal verification to eliminate hallucinations in mathematical reasoning. LeanDojo [Yang et al., 2024] provides tools for AI-assisted theorem proving. DeepMind’s AlphaProof [Trinh et al., 2024] demonstrated competition-level mathematical reasoning with formal proofs. Our work applies formal verification not to mathematical reasoning per se, but to proving *structural properties of AI systems themselves*.

Topological data analysis. The use of cohomology in distributed systems has precedent in the study of consensus [Herlihy et al., 2013] and distributed computing [Ghrist and Muhammad, 2007]. Herlihy et al. showed that the topology of input/output complexes determines solvability of distributed tasks. Our work extends this tradition to the specific context of LLM-based multi-agent systems, providing the first formal connection between cohomological obstructions and empirically observed failure rates.

Information cohomology. Baudot and Bennequin [Baudot and Bennequin, 2015] developed cohomological methods for information theory. Our approach differs in focusing on coordination feasibility rather than information-theoretic quantities, and in providing machine-checked proofs of all results.

7 Discussion

Design implications. Our results provide actionable guidance for MAS architects: *keep communication topologies acyclic*. When feedback is necessary, structure it as a tree-shaped authority hierarchy (Theorem 3.7) rather than a peer-to-peer cycle. If cycles are unavoidable, our framework quantifies the coordination cost: the dimension of H^1 (equal to the cycle rank $|E| - |V| + c$ of the communication graph) measures the number of independent coordination obstructions.

Limitations. Our characterization applies to the *static* communication topology. Dynamic topologies—where communication patterns change during execution—require extensions to our framework. The hollow triangle hypothesis (no filled 2-simplices) excludes group communication channels; extending to higher-dimensional complexes is future work. Finally, our MAST bridge provides explanatory interpretations rather than controlled causal experiments; definitive causal validation requires controlled deployment studies.

The gap between locally correct and globally correct. The philosophical core of our result is that *local correctness does not imply global correctness*. Each pair of adjacent agents may exchange perfectly valid, mutually consistent information—yet the global state may be contradictory. This is a topological phenomenon familiar from gauge theory in physics (holonomy around a loop), from distributed computing (the impossibility of consensus), and now from multi-agent AI systems. The mathematical unity of these phenomena through cohomology suggests that topological methods deserve a more prominent role in AI system design.

8 Conclusion

We have proven, with full formal verification in LEAN 4, that the coordination feasibility of multi-agent systems is characterized by the first cohomology group of their communication topology. This provides a mathematical explanation for the empirically observed 44.2% of MAS failures attributed to system design issues: cyclic communication patterns create topological obstructions that make coordination impossible regardless of agent sophistication.

The practical implication is that coordination feasibility can be checked in linear time before deployment, enabling a new class of pre-deployment verification tools for multi-agent AI systems.

Our codebase of 2,433 formally verified theorems across 59,782 lines of LEAN 4 is publicly available, establishing a foundation for *verified AI infrastructure*—systems whose correctness properties are not merely tested or hoped for, but mathematically proven.

Acknowledgments. AI writing assistants were used for drafting and editing prose. All mathematical results were formalized and verified in LEAN 4 by the author. The complete verified codebase is available at <https://github.com/coboundinc-source/cobound>.

References

- Alam, M. D., Shan, C., Zhang, Y., Jansen, P., and Mihalcea, R. Why Do Multi-Agent LLM Systems Fail? *arXiv preprint arXiv:2503.13657*, 2025.
- Baudot, P. and Bennequin, D. The homological nature of entropy. *Entropy*, 17(5):3253–3318, 2015.

- Ghrist, R. and Muhammad, A. Coverage and hole-detection in sensor networks via homology. *International Journal of Robotics Research*, 2007.
- Herlihy, M., Kozlov, D., and Rajsbaum, S. *Distributed Computing Through Combinatorial Topology*. Morgan Kaufmann, 2013.
- Huang, L., Yu, W., Ma, W., et al. A survey on hallucination in large language models. *arXiv preprint arXiv:2311.05232*, 2023.
- Trinh, T. H. et al. AlphaProof: AI achieves silver-medal standard at International Mathematical Olympiad. Google DeepMind Blog, 2024.
- Yang, K., Swope, A., Gu, A., Chalapathy, R., Song, P., Yu, S., et al. LeanDojo: Theorem proving with retrieval-augmented language models. *NeurIPS*, 2024.
- Zhou, J., Lu, T., Mishra, S., et al. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023.

A Codebase Summary

Table 3: Codebase statistics for the COBOUND verification project.

Metric	Count
Total LEAN 4 source files	159
Total lines of code	59,782
Theorems and lemmas	2,433
sorry (unproven goals)	0
Axioms	0
Multi-agent specific files	25

The multi-agent module includes formalized theories of: coordination topology, consensus obstruction, coalition cohomology, game-theoretic H^1 , tree authority structures, hierarchical networks, equilibrium topology, memory consistency, mechanism design, scalable H^1 computation, global-local duality, nerve complexes, and observation equivalence.

B Key Theorem Statements in Lean 4

Listing 1: $\delta^2 = 0$: The coboundary of a coboundary is zero.

```
theorem delta_squared_zero (K : SimplicialComplex) (k : N)
  (f : Cochain K k) :
  d K (k + 1) (d K k f) = 0
```

Listing 2: $H^1 = 0 \iff$ acyclic: The main characterization.

```
theorem h1_trivial_iff_oneConnected (K : SimplicialComplex)
  [Nonempty K.vertexSet]
  (hhollow : hasNoFilledTriangles K)
  (hconn : (oneSkeleton K).Connected) :
  H1Trivial K <-> OneConnected K
```

Listing 3: No universal reconciler for cyclic arrangements.

```
theorem no_universal_reconciler_strong [Nonempty S]
  (n : N) (hn : n >= 3) :
  exists (e : Q) (_he : e > 0)
    (systems : Fin n -> ValueSystem S),
  (forall i : Fin n, forall hi : i.val + 1 < n,
    forall s : S,
    |(systems i).values s -
      (systems {i.val + 1, hi}).values s| <= 2 * e) /\
  (not exists R : ValueSystem S,
    forall i : Fin n, Reconciles R (systems i) e)
```

Listing 4: Tree authority guarantees $H^1 = 0$.

```
theorem tree_authority_h1_trivial
```

```
(H : HierarchicalNetwork S) :
H1Trivial (hierarchyComplex H)
```

Listing 5: No coordination gap in forest topologies.

```
theorem no_gap_forest {V : Type*} [DecidableEq V]
  (f : LocalAssignment V) (N : AgentNetwork)
  (hf : N.isForest) (hcons : f.consistent N) :
  not (hasGap f N)
```

C Proof of the Hollow Triangle Test Case

As a concrete example, we verify that the hollow triangle (three vertices, three edges, no filled 2-simplex) has non-trivial H^1 :

The cycle $0 \rightarrow 1 \rightarrow 2 \rightarrow 0$ produces a 1-cocycle (the cycle indicator) that is not a coboundary. The single-edge complex (two vertices, one edge) is verified to be acyclic, confirming $H^1 = 0$. Both test cases are fully proven in `H1Characterization/Characterization.lean`.