



# Avail – Project

## Substrate Security Assessment

Prepared by: Halborn

Date of Engagement: November 3rd, 2023 – January 8th, 2024

Visit: [Halborn.com](https://Halborn.com)

DOCUMENT REVISION HISTORY	4
CONTACTS	4
1 EXECUTIVE OVERVIEW	5
1.1 INTRODUCTION	6
1.2 ASSESSMENT SUMMARY	7
1.3 TEST APPROACH & METHODOLOGY	8
2 RISK METHODOLOGY	10
2.1 EXPLOITABILITY	11
2.2 IMPACT	12
2.3 SEVERITY COEFFICIENT	14
2.4 SCOPE	16
3 ASSESSMENT SUMMARY & FINDINGS OVERVIEW	18
4 FINDINGS & TECH DETAILS	19
4.1 (HAL-01) VECTOR INPUT OVERLOAD IN MULTIPLE RPC FUNCTIONS – MEDIUM(5.5)	21
Description	21
Code Location	21
Proof of Concept	23
BVSS	24
Recommendation	25
4.2 (HAL-02) WEIGHT CALCULATION DISCREPANCY ON MULTIPLE FUNCTIONS – MEDIUM(5.5)	26
Description	26
Code Location	26
Proof of Concept	27

	BVSS	28
	Recommendation	28
4.3	(HAL-03) LACK OF RPC RATE LIMITING - MEDIUM(5.5)	29
	Description	29
	BVSS	29
	Recommendation	29
5	MANUAL TESTING	30
5.1	TESTS RELATED WITH PROOFS	31
	Fake Leaf Data Test	31
	Manipulated Proof Array Test	31
	Incorrect Root Hash Verification Test	31
	Leaf Index Bounds Test	31
	Non-Existent Leaf Proof Test	31
	Proof Length Mismatch Test	31
	Hash Function Collision Test	31
	Sequential Data Manipulation Test	31
5.2	TEST RELATED WITH HEADER BUILDER	32
	Grid Generation Failure	32
	Polynomial Grid Failure	32
	Extended Commitment Calculation	32
	Commitment Serialization	32
	Dimension Calculations	32
	Feature Flag Impact	32
	Header Extension Construction	32
5.3	TEST RELATED WITH 'finalize' FUNCTION	33
	Temporary Storage Cleanup	33

	Storage Root Calculation	33
	Block Hash Pruning Logic	33
	OpaqueExtrinsic Decoding	33
	Data Root Calculation	33
	Version Handling	33
	AppExtrinsic Transformation	33
	Header Construction	33
	Logging and Error Reporting	34
6	AUTOMATED TESTING	34
6.1	AUTOMATED ANALYSIS	36
	Description	36

## DOCUMENT REVISION HISTORY

VERSION	MODIFICATION	DATE
0.1	Document Creation	01/05/2024
0.2	Document Updates	01/08/2024
0.3	Draft Review	01/10/2024

## CONTACTS

CONTACT	COMPANY	EMAIL
Rob Behnke	Halborn	Rob.Behnke@halborn.com
Steven Walbroehl	Halborn	Steven.Walbroehl@halborn.com
Gabi Urrutia	Halborn	Gabi.Urrutia@halborn.com
Piotr Cielas	Halborn	Piotr.Cielas@halborn.com
Alpcan Onaran	Halborn	Alpcan.Onaran@halborn.com



# EXECUTIVE OVERVIEW

## 1.1 INTRODUCTION

Avail is a base layer blockchain platform emphasizing data availability. It enables light clients to verify data availability through a peer-to-peer network, simplifying blockchain integration for developers. Avail supports various execution environments, including EVM and WASM, and focuses on transaction ordering and publishing. Its design allows users to verify block data availability without downloading entire blocks.

In this security assessment, we examined key components of Avail blockchain infrastructure to ensure they adhere to high security standards. Our focus was on identifying any vulnerabilities or weaknesses that could potentially compromise the security, functionality, and integrity of Avail systems.

**The specific areas under scrutiny were:**

**Header Builder** - Located at `pallets/system/src/header_builder.rs`, this component plays a crucial role in the Avail blockchain architecture. Our review focused on ensuring that the header builder, which has undergone modifications from the default Substrate implementation, securely processes and structures blockchain headers.

**KateRPC** - The KateRPC, found at `rpc/kate-rpc/src/lib.rs`, is essential for Avail RPC interface. We thoroughly reviewed its implementation, including the specific functionalities at `rpc/kate-rpc/src/lib.rs#L299`, to ensure secure and efficient communication within the Avail network.

**Core and Kate Folders** - Within the `avail-core` folders, we focused on the core and kate directories, excluding the examples' subfolder. Our analysis aimed to identify any security issues in these fundamental areas of the codebase.

### **Additional Components**

`node/src/chains/da_block_import.rs` - This file was examined for its role in block importation processes.

`pallets/dactr` and `pallets/system` - These directories were reviewed for



potential security concerns in their respective pallets.

Throughout the assessment, we paid close attention to common and advanced security threats, including but not limited to data integrity issues, incorrect implementations, and vulnerabilities that could be exploited. Our goal was to ensure that each component functions as intended and provides a secure and reliable infrastructure for Avail .

Avail engaged Halborn to conduct a security assessment on their pallet, beginning on November 3rd, 2023 and ending on January 8th, 2024 .

## 1.2 ASSESSMENT SUMMARY

The team at Halborn was provided about two months for the engagement and assigned a full-time security engineer to verify the security of the Substrate pallet. The security engineer is a blockchain and smart-contract security expert with advanced penetration testing and smart-contract hacking skills, and deep knowledge of multiple blockchain protocols.

The purpose of this assessment was to achieve the following:

- Identify and mitigate potential security issues with the business logic of the pallet
- Identify Substrate related vulnerabilities, including improper weight calculations, missing storage deposits, and unchecked sized iterations
- Review and ensure the security of storage of sensitive information, such as cryptographic keys and hashes
- Evaluate the security of pallet functions and ensure proper authorization checks are in place
- Identify and mitigate potential Rust related security issues with the pallet, such as memory safety issues and integer overflow vulnerabilities
- Review and test the pallet's input validation and verify user input is handled in a secure way
- Review and test the pallet's error handling and logging mechanisms to ensure they do not reveal sensitive information



- Evaluate the external dependencies and libraries to ensure they do not introduce additional security vulnerabilities
- Identify and assess potential attack vectors

In summary, Halborn identified some improvements to reduce the likelihood and impact of multiple issues. The main ones were the following:

#### **(HAL-01) VECTOR INPUT OVERLOAD IN MULTIPLE RPC FUNCTIONS**

`query_proof` and `query_rows` functions lack the mechanism to limit the size of the input vectors, allowing an attacker to pass an excessively large number of Vector and Cell objects. Which leads to resource exhaustion, potentially causing a Denial of Service (DoS) attack.

#### **(HAL-02) WEIGHT CALCULATION DISCREPANCY ON MULTIPLE FUNCTIONS**

A Weight Calculation Discrepancy vulnerability exists in the `remark_with_event` function within the System's pallet of the Avail blockchain. The vulnerability is due to the improper casting of the length of a Vec (`remark`) to an u32 for weight calculation. This casting leads to an integer overflow when the remark vector's length exceeds `u32::MAX`. Such an overflow can result in incorrect weight calculations for the extrinsic, potentially allowing an attacker to exploit the system by submitting extrinsic that consume more resources than anticipated.

#### **(HAL-03) LACK OF RPC RATE LIMITING**

The lack of rate-limiting on Substrate RPC endpoints poses a security risk, as it allows attackers to flood the system with excessive requests. This can lead to resource exhaustion and potential Denial of Service (DoS) attacks, compromising the network's stability and availability.

## **1.3 TEST APPROACH & METHODOLOGY**

Halborn performed a combination of the manual view of the code and automated security testing to balance efficiency, timeliness, practicality, and accuracy regarding the scope of the blockchain architecture assessment. While manual testing is recommended to uncover flaws in logic, process, and implementation, automated testing techniques help enhance

the coverage of the blockchain architecture. They can quickly identify items that do not follow security best practices. The following phases and associated tools were used throughout the term of the assessment:

- Research into the architecture, purpose, and use of the platform.
- Manual code review and walkthrough to identify any logic issue.
- Mapping out possible attack vectors
- Thorough assessment of safety and usage of critical Rust variables and functions in scope that could lead to arithmetic vulnerabilities.
- Finding unsafe Rust code usage (`cargo-geiger`)
- On chain testing of core functions(`polkadot.js`).
- Active Fuzz testing {`cargo-fuzz`, `honggfuzz`}
- Scanning dependencies for known vulnerabilities (`cargo audit`).

## 2. RISK METHODOLOGY

Every vulnerability and issue observed by Halborn is ranked based on **two sets** of **Metrics** and a **Severity Coefficient**. This system is inspired by the industry standard Common Vulnerability Scoring System.

The two **Metric sets** are: **Exploitability** and **Impact**. **Exploitability** captures the ease and technical means by which vulnerabilities can be exploited and **Impact** describes the consequences of a successful exploit.

The **Severity Coefficients** is designed to further refine the accuracy of the ranking with two factors: **Reversibility** and **Scope**. These capture the impact of the vulnerability on the environment as well as the number of users and smart contracts affected.

The final score is a value between 0-10 rounded up to 1 decimal place and 10 corresponding to the highest security risk. This provides an objective and accurate rating of the severity of security vulnerabilities in smart contracts.

The system is designed to assist in identifying and prioritizing vulnerabilities based on their level of risk to address the most critical issues in a timely manner.

## 2.1 EXPLOITABILITY

### Attack Origin (AO):

Captures whether the attack requires compromising a specific account.

### Attack Cost (AC):

Captures the cost of exploiting the vulnerability incurred by the attacker relative to sending a single transaction on the relevant blockchain. Includes but is not limited to financial and computational cost.

### Attack Complexity (AX):

Describes the conditions beyond the attacker's control that must exist in order to exploit the vulnerability. Includes but is not limited to macro situation, available third-party liquidity and regulatory challenges.

### Metrics:

Exploitability Metric ( $m_E$ )	Metric Value	Numerical Value
Attack Origin (AO)	Arbitrary (AO:A)	1
	Specific (AO:S)	0.2
Attack Cost (AC)	Low (AC:L)	1
	Medium (AC:M)	0.67
	High (AC:H)	0.33
Attack Complexity (AX)	Low (AX:L)	1
	Medium (AX:M)	0.67
	High (AX:H)	0.33

Exploitability  $E$  is calculated using the following formula:

$$E = \prod m_e$$

## 2.2 IMPACT

### Confidentiality (C):

Measures the impact to the confidentiality of the information resources managed by the contract due to a successfully exploited vulnerability. Confidentiality refers to limiting access to authorized users only.

### Integrity (I):

Measures the impact to integrity of a successfully exploited vulnerability. Integrity refers to the trustworthiness and veracity of data stored and/or processed on-chain. Integrity impact directly affecting Deposit or Yield records is excluded.

### Availability (A):

Measures the impact to the availability of the impacted component resulting from a successfully exploited vulnerability. This metric refers to smart contract features and functionality, not state. Availability impact directly affecting Deposit or Yield is excluded.

### Deposit (D):

Measures the impact to the deposits made to the contract by either users or owners.

### Yield (Y):

Measures the impact to the yield generated by the contract for either users or owners.

## Metrics:

Impact Metric ( $m_I$ )	Metric Value	Numerical Value
Confidentiality (C)	None (I:N)	0
	Low (I:L)	0.25
	Medium (I:M)	0.5
	High (I:H)	0.75
	Critical (I:C)	1
Integrity (I)	None (I:N)	0
	Low (I:L)	0.25
	Medium (I:M)	0.5
	High (I:H)	0.75
	Critical (I:C)	1
Availability (A)	None (A:N)	0
	Low (A:L)	0.25
	Medium (A:M)	0.5
	High (A:H)	0.75
	Critical	1
Deposit (D)	None (D:N)	0
	Low (D:L)	0.25
	Medium (D:M)	0.5
	High (D:H)	0.75
	Critical (D:C)	1
Yield (Y)	None (Y:N)	0
	Low (Y:L)	0.25
	Medium: (Y:M)	0.5
	High: (Y:H)	0.75
	Critical (Y:H)	1

Impact  $I$  is calculated using the following formula:

$$I = \max(m_I) + \frac{\sum m_I - \max(m_I)}{4}$$

## 2.3 SEVERITY COEFFICIENT

### Reversibility (R):

Describes the share of the exploited vulnerability effects that can be reversed. For upgradeable contracts, assume the contract private key is available.

### Scope (S):

Captures whether a vulnerability in one vulnerable contract impacts resources in other contracts.

Coefficient ( $C$ )	Coefficient Value	Numerical Value
Reversibility ( $r$ )	None (R:N)	1
	Partial (R:P)	0.5
	Full (R:F)	0.25
Scope ( $s$ )	Changed (S:C)	1.25
	Unchanged (S:U)	1

Severity Coefficient  $C$  is obtained by the following product:

$$C = rs$$



The Vulnerability Severity Score  $S$  is obtained by:

$$S = \min(10, EIC * 10)$$

The score is rounded up to 1 decimal places.

Severity	Score Value Range
Critical	9 - 10
High	7 - 8.9
Medium	4.5 - 6.9
Low	2 - 4.4
Informational	0 - 1.9

## 2.4 SCOPE

### Code Repositories:

#### 1. Avail

- Repository: [avail](#)
- Specific Commits:
  - [df16508b5061db31f5ad7acc826809ff12cc202c](#)

#### 2. Avail Core

- Repository: [avail-core](#)
- Commit ID: [8ec83d7415c89834948f38a3fdc66d274180a732](#)

### Components in Scope:

- **Header Builder:**
  - Location: [header\\_builder.rs](#)
  - Description: Reviewing the header builder for modifications over the default Substrate implementation.
- **KateRPC:**
  - Location: [KateRPC lib.rs](#)
  - Focus: Examining the KateRPC implementation, including specific functions at [KateRPC lib.rs#L299](#).

### Avail-Core Folders in Scope:

- Core Folder: Reviewing changes in the header and other core functionalities.
- Kate Folder: Focused analysis, excluding the examples' subfolder.
- Ignored: Nomad folder.

### On Avail Repo Itself:

- `rpc/kate-rpc/src/lib.rs`
- `pallets/system/header_builder.rs`
- `node/src/chains/da_block_import.rs`
- `runtime/src/apis.rs`: Reviewing `DataAvailApi` and `ExtensionBulder` APIs.
- `pallets/dactr/src/benchmarking.rs`: Analyzing the data root logic as part of the `dactr` pallet.

DRAFT

### 3. ASSESSMENT SUMMARY & FINDINGS OVERVIEW

CRITICAL	HIGH	MEDIUM	LOW	INFORMATIONAL
0	0	3	0	0

SECURITY ANALYSIS	RISK LEVEL	REMEDIATION DATE
(HAL-01) VECTOR INPUT OVERLOAD IN MULTIPLE RPC FUNCTIONS	Medium (5.5)	-
(HAL-02) WEIGHT CALCULATION DISCREPANCY ON MULTIPLE FUNCTIONS	Medium (5.5)	-
(HAL-03) LACK OF RPC RATE LIMITING	Medium (5.5)	-



# FINDINGS & TECH DETAILS




## 4.1 (HAL-01) VECTOR INPUT OVERLOAD IN MULTIPLE RPC FUNCTIONS – MEDIUM (5.5)

### Description:

The `query_proof` and `query_rows` functions in the implementation lack a mechanism to limit the size of the input vector, which comprises vector and cell objects. This absence of input size validation allows an attacker to pass an excessively large number of Cell objects to the function. This can potentially lead to resource exhaustion, whereby the system's resources are over-consumed, resulting in a Denial of Service (DoS) attack. This vulnerability can cause significant disruption to the service, making it unavailable for legitimate use.

Below is the exploit overview of this vulnerability:



### Code Location:

Down below is the code snippet from the `query_proof` function:

Listing 1: `/rpc/kate-rpc/src/lib.rs` (Line 337)

```

330     async fn query_proof(&self, cells: Vec<Cell>, at: Option<
    ↳ HashOf<Block>>) -> RpcResult<Vec<u8>> {
331         let signed_block = self.get_signed_and_finalized_block(at)
    ↳ ?;
332         let evals = self.get_eval_grid(&signed_block).await?;
333         let polys = self.get_poly_grid(&signed_block).await?;
334
335         let proof = cells
336             .par_iter()

```



```

337         .map(|cell| {
338             let Ok(row) = usize::try_from(cell.row.0) else {
339                 return Err(internal_err!("cell row did not fit
↳ in usize"));
340             };
341             let Ok(col) = usize::try_from(cell.col.0) else {
342                 return Err(internal_err!("cell row did not fit
↳ in usize"));
343             };
344             let Some(data) = evals.get::<usize, usize>(row,
↳ col) else {
345                 let e = internal_err!("Invalid cell {:?} for
↳ dims {:?}", cell, evals.dims());
346                 return Err(e);
347             };
348             let proof = match polys.1.proof(&self.
↳ multiproof_srs, cell) {
349                 Ok(x) => x,
350                 Err(e) => return Err(internal_err!("Unable to
↳ make proof: {:?}", e)),
351             };
352
353             let data = data.to_bytes().expect("Ser cannot fail
↳ ").to_vec();
354             let proof = proof.to_bytes().expect("Ser cannot
↳ fail").to_vec();
355
356             Ok([proof, data].into_iter().flatten().collect::<
↳ Vec<_>>())
357         })
358         .collect::<Result<Vec<_>, _>>()?;
359         let proof: Vec<u8> = proof.into_iter().flatten().collect()
↳ ;
360         Ok(proof)
361     }
362

```

## Proof of Concept:

Listing 2

```

0      #[async_std::test]
1      pub async fn HAL01_query_proof_dos() {
2          let client = establish_a_connection().await.unwrap();
3          let (txc, rpc) = (client.tx(), client.rpc());
4
5          let example_data = "ExampleData".as_bytes();
6          assert_eq!(example_data.len(), 11);
7
8          let block_hash = send_da_example_data(&txc, example_data).
↳ await.unwrap();
9          let submitted_block = get_submitted_block(rpc, block_hash)
↳ .await.unwrap();
10         let app_extrinsics = get_block_app_extrinsics(&
↳ submitted_block).unwrap();
11
12         // Grid Creation
13         let grid = EvaluationGrid::from_extrinsics(app_extrinsics,
↳ 4, 256, 256, [0u8; 32]).unwrap();
14         let extended_grid = grid.extend_columns(NonZeroU16::new(2)
↳ .unwrap()).unwrap();
15         let poly_grid = extended_grid.make_polynomial_grid().
↳ unwrap();
16
17         assert_eq!(grid.dims(), Dimensions::new(1, 8).unwrap());
18         assert_eq!(extended_grid.dims(), Dimensions::new(2, 8).
↳ unwrap());
19         assert_eq!(grid.row(0), extended_grid.row(0));
20         assert_eq!(grid.row(0), extended_grid.row(1));
21
22         let mut cells = vec![
23             Cell::new(BlockLengthRows(0), BlockLengthColumns(0)),
24             Cell::new(BlockLengthRows(0), BlockLengthColumns(1)),
25             Cell::new(BlockLengthRows(0), BlockLengthColumns(2)),
26             Cell::new(BlockLengthRows(0), BlockLengthColumns(3)),
27             Cell::new(BlockLengthRows(0), BlockLengthColumns(4)),
28             Cell::new(BlockLengthRows(0), BlockLengthColumns(5)),
29             Cell::new(BlockLengthRows(0), BlockLengthColumns(6)),
30             Cell::new(BlockLengthRows(0), BlockLengthColumns(7)),
31         ];
32
33         let original_cells = cells.clone();

```

```

34         while cells.len() < 100000 {
35             cells.extend(original_cells.clone());
36         }
37
38         let multiproof_srs = kate::testnet::multiproof_params(256,
↳ 256);
39         let expected_proof: Vec<Vec<u8>> = cells
40             .iter()
41             .map(|cell| {
42                 let row = usize::try_from(cell.row.0).unwrap();
43                 let col = usize::try_from(cell.col.0).unwrap();
44                 let data = extended_grid.get::(row,
↳ col).unwrap();
45                 let proof = poly_grid.proof(&multiproof_srs, cell)
↳ .unwrap();
46
47                 let data = data.to_bytes().expect("Ser cannot fail
↳ ").to_vec();
48                 let proof = proof.to_bytes().expect("Ser cannot
↳ fail").to_vec();
49
50                 [proof, data].into_iter().flatten().collect::

```

BVSS:

A0:A/AC:L/AX:L/C:N/I:M/A:H/D:N/Y:N/R:P/S:C (5.5)

**Recommendation:**

Following solutions are recommended to address this issue:

**Input Size Validation:** Introduce checks to limit the number of vector and Cell objects that can be processed in a single request. Define a maximum threshold for the vector size.

**Rate Limiting:** Implement rate limiting on the number of requests a user can make to the query\_proof function within a specified time frame to prevent abuse.

## 4.2 (HAL-02) WEIGHT CALCULATION DISCREPANCY ON MULTIPLE FUNCTIONS – MEDIUM (5.5)

### Description:

A **Weight Calculation Discrepancy** due to integer casting overflow vulnerability has been identified in the `remark_with_event` function, and following functions (`remark`, `set_storage`, `kill_storage`) within the System's pallet of the Avail blockchain. This vulnerability arises from the improper casting of the length of a `Vec<u8>` (`remark`) to a `u32` for weight calculation. When the length of the `remark` vector exceeds `u32::MAX`, it results in an integer overflow. This overflow leads to incorrect weight calculations for the extrinsic, allowing an attacker to submit extrinsic that consume more resources than the system anticipates, potentially exploiting the system.

Incorrect weight calculations can lead to an imbalance in resource allocation, potentially allowing an attacker to consume excessive network resources. This could result in slower block processing, network congestion, or even Denial of Service (DoS) attacks if the attacker exploits this vulnerability to create and broadcast extrinsic with underestimated weights

### Code Location:

Here is the code snippet of the `remark_with_event` function:

**Listing 3:** `/pallets/system/src/lib.rs` (Lines 549,552)

```
545     /// Make some on-chain remark and emit event.
546     #[pallet::call_index(7)]
547     #[pallet::weight(T::SystemWeightInfo::remark_with_event(
    ↳ remark.len() as u32))]
548     pub fn remark_with_event(
549         origin: OriginFor<T>,
550         remark: Vec<u8>,
```

```

551         ) -> DispatchResultWithPostInfo {
552             let maybe_who = ensure_signed_or_root(origin)?;
553             let hash = T::Hashing::hash(&remark[..]);
554
555
556
557             let event = match maybe_who {
558                 Some(who) => Event::Remarked { sender: who, hash
559 ↪ },
560                 None => Event::RemarkedByRoot { hash },
561             };
562
563             Self::deposit_event(event);
564             Ok(()).into()
565         }

```

#### Proof of Concept:

The exploit script demonstrates the weight calculation overflow attack.

#### Listing 4

```

0 #[test]
1 fn HAL02_poc_remark_with_event_weight_calc_issue() {
2     new_test_ext().execute_with(|| {
3         let call_maker = |n| RuntimeCall::System(Call::remark {
4 ↪ remark: vec![n] }).encode();
5         let extrinsics = [call_maker(1), call_maker(2)];
6
7         let len: usize = u32::MAX as usize + 2; //remark.len()
8 ↪ triggers casting overflow
9         //let len: usize = 50000;
10        let dispace_info = System::remark_with_event(
11            RuntimeOrigin::from(RawOrigin::Signed(1u64)).
12 ↪ into(),
13            vec![0u8; len]
14        );
15
16        assert_ok!(dispace_info);
17        println!("{:?}", dispace_info);
18    });
19 }

```

BVSS:

A0:A/AC:L/AX:L/C:N/I:M/A:H/D:N/Y:N/R:P/S:C (5.5)

Recommendation:

Following solutions are recommended to address this issue:

1. **Input Validation:** Implement strict validation on the input length to ensure it does not exceed `u32::MAX` before casting.
2. **Safe Casting:** Utilize safe casting methods or checks to prevent integer overflow when converting from `usize` to `u32`.



## 4.3 (HAL-03) LACK OF RPC RATE LIMITING - MEDIUM (5.5)

### Description:

In the current implementation, the lack of rate-limiting on Substrate RPC endpoints poses a security risk, as it allows attackers to flood the system with excessive requests. This can lead to resource exhaustion and potential Denial of Service (DoS) attacks, compromising the network's stability and availability.

### BVSS:

A0:A/AC:L/AX:L/C:N/I:M/A:H/D:N/Y:N/R:P/S:C (5.5)

### Recommendation:

It is recommended to implement a rate-limit control or restrict the RPC access.



# MANUAL TESTING

## 5.1 TESTS RELATED WITH PROOFS

### Fake Leaf Data Test:

- Check if the system fails verification when leaf data is altered. **PASSED**

### Manipulated Proof Array Test:

- Test detection of tampered elements in a Merkle proof. **PASSED**

### Incorrect Root Hash Verification Test:

- Confirm failure when verifying against a wrong root hash. **PASSED**

### Leaf Index Bounds Test:

- Ensure correct handling of proofs near the dataset bounds. **PASSED**

### Non-Existent Leaf Proof Test:

- Verify handling of proofs for invalid leaf indices. **PASSED**

### Proof Length Mismatch Test:

- Detect incorrect proof array lengths. **PASSED**

### Hash Function Collision Test:

- Test for robustness against hash collision attacks. **PASSED**

### Sequential Data Manipulation Test:

- Check for vulnerabilities in handling sequential data. **PASSED**

## 5.2 TEST RELATED WITH HEADER BUILDER

### Grid Generation Failure:

- Test handling of invalid app\_extrinsics. PASSED

### Polynomial Grid Failure:

- Check error handling with problematic data. PASSED

### Extended Commitment Calculation:

- Test for failures in commitment calculations. PASSED

### Commitment Serialization:

- Ensure serialization works with edge-case data. PASSED

### Dimension Calculations:

- Verify accuracy of dimension calculations. PASSED

### Feature Flag Impact:

- Test behavior with header\_extension\_v2 enabled and disabled. PASSED

### Header Extension Construction:

- Test construction of `HeaderExtension` for various inputs. PASSED

## 5.3 TEST RELATED WITH ‘finalize’ FUNCTION

### Temporary Storage Cleanup:

- Confirm removal of all temporary storage entries. PASSED

### Storage Root Calculation:

- Test accurate calculation of storage root. PASSED

### Block Hash Pruning Logic:

- Verify block hash removal for different block numbers. PASSED

### OpaqueExtrinsic Decoding:

- Check decoding of valid and invalid extrinsic. PASSED

### Data Root Calculation:

- Test correct calculation of extrinsics\_root. PASSED

### Version Handling:

- Ensure proper storage root decoding for different versions. PASSED

### AppExtrinsic Transformation:

- Test transformation of `OpaqueExtrinsic` to `AppExtrinsic`. PASSED

### Header Construction:

- Verify correct construction of block headers. PASSED

## Logging and Error Reporting:

- Ensure accurate logging and error reporting. **PASSED**

DRAFT



# AUTOMATED TESTING



## 6.1 AUTOMATED ANALYSIS

### Description:

Halborn used automated security scanners to assist with detection of well-known security issues and vulnerabilities. Among the tools used was `cargo audit`, a security scanner for vulnerabilities reported to the RustSec Advisory Database. All vulnerabilities published in <https://crates.io> are stored in a repository named The RustSec Advisory Database. `cargo audit` is a human-readable version of the advisory database which performs a scanning on Cargo.lock. Security Detections are only in scope. To better assist the developers maintaining this code, the auditors are including the output with the dependencies tree, and this is included in the `cargo audit` output to better know the dependencies affected by unmaintained and vulnerable crates.

ID	package	Short Description
<a href="#">RUSTSEC-2022-0093</a>	ed25519-dalek 1.0.1	Double Public Key Signing Function Oracle Attack on 'ed25519-dalek'

### Listing 5

```

1 ed25519-dalek 1.0.1
2   sp-io 23.0.0
3     try-runtime-cli 0.10.0-dev
4       data-avail 1.8.0
5     sp-runtime 24.0.0
6       try-runtime-cli 0.10.0-dev
7     substrate-state-trie-migration-rpc 4.0.0-dev
8       data-avail 1.8.0
9     substrate-rpc-client 0.10.0-dev
10      try-runtime-cli 0.10.0-dev
11    frame-remote-externalities 0.10.0-dev
12      try-runtime-cli 0.10.0-dev

```

ID	package	Short Description
<a href="#">RUSTSEC-2023-0074</a>	zerocopy 0.7.20	Some Ref methods are unsound with some type parameters

Listing 6

```

1 zerocopy 0.7.20
2 ahash 0.8.6
3   sp-trie 22.0.0
4     substrate-state-trie-migration-rpc 4.0.0-dev
5       data-avail 1.8.0
6     sp-transaction-storage-proof 4.0.0-dev
7       try-runtime-cli 0.10.0-dev
8         data-avail 1.8.0
9       sc-service 0.10.0-dev
10        sc-cli 0.10.0-dev
11          try-runtime-cli 0.10.0-dev
12            frame-benchmarking-cli 4.0.0-dev
13              data-avail 1.8.0
14                data-avail 1.8.0
15                  frame-benchmarking-cli 4.0.0-dev
16                    data-avail 1.8.0
17                      data-avail 1.8.0

```

ID	package	Short Description
<a href="#">RUSTSEC-2021-0145</a>	atty 0.2.14	Potential unaligned read

Listing 7

```

1 atty 0.2.14
2   sc-tracing 4.0.0-dev
3     sc-service 0.10.0-dev
4       sc-cli 0.10.0-dev
5         try-runtime-cli 0.10.0-dev
6           data-avail 1.8.0
7             frame-benchmarking-cli 4.0.0-dev
8               data-avail 1.8.0
9                 data-avail 1.8.0
10                  frame-benchmarking-cli 4.0.0-dev

```

DRAFT

THANK YOU FOR CHOOSING

// HALBORN