Python For Data Science Cheat Sheet

Pandas Basics

Learn Python for Data Science Interactively at www.DataCamp.com



Pandas

The **Pandas** library is built on NumPy and provides easy-to-use data structures and data analysis tools for the Python programming language. pandas [.....]

Use the following import convention:

>>> import pandas as pd

Pandas Data Structures


Series

A one-dimensional labeled array capable of holding any data type



>>> s = pd.Series([3, -5, 7, 4], index=['a', 'b', 'c', 'd'])

DataFrame



A two-dimensional labeled data structure with columns of potentially different types

```
>>> data = {'Country': ['Belgium', 'India', 'Brazil'],
           'Capital': ['Brussels', 'New Delhi', 'Brasília'],
           'Population': [11190846, 1303171035, 207847528]
>>> df = pd.DataFrame(data,
                     columns=['Country', 'Capital', 'Population']) >>> s['a']
```

Asking For Help

>>> help(pd.Series.loc)

Selection

Also see NumPy Arrays

Getting

```
>>> s['b']
>>> df[1:]
   Country
              Capital Population
    India New Delhi 1303171035
  2 Brazil
             Brasília 207847528
```

Get one element

Get subset of a DataFrame

Selecting, Boolean Indexing & Setting

By Position

```
>>> df.iloc[[0],[0]]
 'Belgium'
>>> df.iat([0],[0])
 'Belgium'
```

By Label

```
>>> df.loc[[0], ['Country']]
 'Belgium'
>>> df.at([0], ['Country'])
 'Belgium'
```

By Label/Position

```
>>> df.ix[2]
 Country
             Brazil
 Capital
           Brasília
 Population 207847528
>>> df.ix[:,'Capital']
       Brussels
      New Delhi
      Brasília
>>> df.ix[1,'Capital']
```

Boolean Indexing

'New Delhi'

>>> s(~(s > 1)					
>>> s[(s < -1)		(s	>	2)]	
1001000	-	A 10			20

>>> df[df['Population']>1200000000]

Select single value by row & column

Select single value by row & column labels

Select single row of subset of rows

Select a single column of subset of columns

Select rows and columns

Series s where value is not >1 s where value is <-1 or >2

Use filter to adjust DataFrame

Set index a of Series s to 6

Read and Write to SQL Query or Database Table

```
>>> pd.read csv('file.csv', header=None, nrows=5)
>>> df.to csv('myDataFrame.csv')
```

Read and Write to Excel

Read and Write to CSV

```
>>> pd.read excel('file.xlsx')
>>> df.to excel('dir/myDataFrame.xlsx', sheet_name='Sheet1')
 Read multiple sheets from the same file
```

>>>	xlsx	= pd.ExcelFile('file.xls')	4
>>>	df =	pd.read_excel(xlsx, 'Sheet1')

>>> from sqlalchemy import create engine

```
>>> engine = create engine('sglite:///:memory:')
>>> pd.read sql("SELECT * FROM my table;", engine)
>>> pd.read sql table('my table', engine)
>>> pd.read sql query("SELECT * FROM my table;", engine)
```

read sql() is a convenience wrapper around read sql table() and read sql query()

```
>>> df.to sql('myDf', engine)
```

Dropping

>>>	s.drop(['a', 'c'])	Drop values from rows (axis=0)
>>>	<pre>df.drop('Country',</pre>	axis=1)	Drop values from columns(axis=1)

Sort & Rank

```
>>> df.sort index()
                                             Sort by labels along an axis
>>> df.sort_values(by='Country')
>>> df.rank()
                                             Sort by the values along an axis
                                             Assign ranks to entries
```

Retrieving Series/DataFrame Information

Basic Information

```
>>> df.shape
                             (rows,columns)
 >>> df.index
                             Describe index
>>> df.columns
                             Describe DataFrame columns
>>> df.info()
                             Info on DataFrame
>>> df.count()
                             Number of non-NA values
```

Summary

>>>	df.sum()	Sum of values
>>>	df.cumsum()	Cummulative sum of values
>>>	<pre>df.min()/df.max()</pre>	Minimum/maximum values
>>>	<pre>df.idxmin()/df.idxmax()</pre>	Minimum/Maximum index value
>>>	df.describe()	Summary statistics
>>>	df.mean()	Mean of values
>>>	df.median()	Median of values
	**	

Applying Functions

```
>>> f = lambda x: x*2
>>> df.apply(f)
                            Apply function
                            Apply function element-wise
>>> df.applymap(f)
```

Data Alignment

Internal Data Alignment

NA values are introduced in the indices that don't overlap:

```
>>> s3 = pd.Series([7, -2, 3], index=['a', 'c', 'd'])
>>> s + s3
       10.0
       NaN
       5.0
       7.0
```

Arithmetic Operations with Fill Methods

You can also do the internal data alignment yourself with the help of the fill methods:

```
>>> s.add(s3, fill value=0)
    10.0
      -5.0
     5.0
 C
 d
     7.0
>>> s.sub(s3, fill value=2)
>>> s.div(s3, fill value=4)
>>> s.mul(s3, fill value=3)
```

DataCamp Learn Python for Data Science Interactively