

C Programming (W4)



Welcome!!

Please check attendance individually.
(Mobile App)

Things to do today


- 01** | Ch.1 ~ Ch.3
- 02** | Debugging in VSC
- 03** | Variables & Data types
- 04** |

Debugging

- Practice with debugger
- VSC (launch.json, tasks.json)
 - github.com/prof-kweon/2025-Fall-C-Language/blob/main/Reference/lauch.json
 - github.com/prof-kweon/2025-Fall-C-Language/blob/main/Reference/tasks.json

Variables & Data types

- Variable: A memory space where **data** can be stored. (bowl)
 - The bowl can hold rice, side dishes, and water.



- Variable creation and rules and features
 - Reserved words (keywords) cannot be used (for, if, else,...)
 - Spaces cannot be included
 - Only English letters and underscores (_) can be used as the first letter (number x)
 - Special characters other than underscores (_) cannot be used
 - Case sensitive

Variables & Data types

- Data types: To use memory space efficiently, data types of appropriate shape and size must be used.

Data Type	Description	Size (bytes)	Range	Example
int	Integer data type for whole numbers.	4	-2,147,483,648 to 2,147,483,647	int num = 10;
short	Short integer data type. Smaller range than int.	2	-32,768 to 32,767	short num = 100;
long	Long integer data type, typically used for larger numbers.	8	-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807	long num = 1000000L;
long long	Extended long integer data type, used for even larger numbers.	8	-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807	long long num = 1234567890123LL;
unsigned int	Unsigned integer, stores only positive values.	4	0 to 4,294,967,295	unsigned int num = 10U;
unsigned short	Unsigned short integer, stores only positive values.	2	0 to 65,535	unsigned short num = 100U;
unsigned long	Unsigned long integer, stores only positive values.	8	0 to 18,446,744,073,709,551,615	unsigned long num = 1000000UL;
unsigned long long	Unsigned long long integer, stores only positive values.	8	0 to 18,446,744,073,709,551,615	unsigned long long num = 1234567890123ULL;
char	Character data type, used to store single characters.	1	-128 to 127 (signed) or 0 to 255 (unsigned)	char letter = 'A';
unsigned char	Unsigned character, stores only positive character values (0 to 255).	1	0 to 255	unsigned char letter = 65U;
float	Single-precision floating point number.	4	$\pm 1.5 \times 10^{-45}$ to $\pm 3.4 \times 10^{38}$	float num = 3.14f;
double	Double-precision floating point number, provides higher precision than float.	8	$\pm 5.0 \times 10^{-324}$ to $\pm 1.7 \times 10^{308}$	double num = 3.141592;
long double	Extended precision floating point number (depends on the system).	10 or 16	Varies by system, typically $\pm 3.4 \times 10^{-4932}$ to $\pm 1.1 \times 10^{4932}$	long double num = 3.141592653589793;
_Bool	Boolean type (from C99 standard), stores true or false.	1	0 (false), 1 (true)	_Bool isTrue = 1;
void	Void type, used to indicate the absence of data or return type for functions.	N/A	N/A	void function() {}

See you next week!

DO NOT miss the classes

