

Lab 8 grading sheet

1) Name Last_____ First_____ EID_____

2) Name Last_____ First_____ EID_____

Use same spelling as listed on Canvas

1. All source files that you have changed or added (like **ADC.c and **Lab8.c**) should be **committed to SVN**. Please do not commit other file types. The basic idea of SVN is to submit enough files so your partner and your TA can compile and run your application.**

2. Deliverables 20%:

0) This sheet

Combine the following components in this order into one pdf file and commit it to Lab8 folder in SVN before your checkout time. Have this file open on the computer during demonstration.

- 1) Circuit diagram showing the position sensor and LCD, hand-drawn or PCB Artist, like Figure 8.1 (part a),
- 2) Time measurements and a photo showing the ADC/LCD execution time profile, like Figure 8.6 part d)
- 3) Calibration data, like the first three columns of Table 8.1 (part d)
- 4) Final version of distance meter with SysTick, ADC, convert, and main (parts c, e, f, g and h)
- 5) A photo or screenshot verifying the sampling rate is 40 Hz, like Figure 8.8 part h)
- 6) Accuracy data and accuracy calculation, Table 8.2 (part i)

3. Performance 35%:

Does it handle correctly all situations as specified?

How pretty is the software?

4. Adhere to coding standard 5%:

Good Names have meaning, Variables have units in comments

Consistent indentation, Consistent use of braces, C99 style

1)

2)

5. Demonstration 40% (TAs will ask similar, but not exactly identical questions):

You will show the TA your program operation on the actual TM4C123 board. The TA may look at your data and expect you to understand how the data was collected and how the ADC and interrupts work. You should be able to explain how the potentiometer converts distance into resistance, and how the circuit converts resistance into voltage. Also be prepared to explain how your software works and to discuss other ways the problem could have been solved. What will you change in your program if the potentiometer were to be connected to a different ADC pin? How would this system be different if the units of measurement were inches instead of cm? What's your sampling rate? What does sampling rate? What is the difference between the sampling rate and the 125 kHz ADC clock? What is the ADC range, resolution and precision? How do you initialize SysTick interrupt? How can you change your sampling rate? Be prepared to prove what the sampling rate is using a calculator and the manual. Explain how, when an interrupt occurs, control reaches the interrupt service routine. Why is it extremely poor style to output the converted data to the LCD inside the SysTick ISR? Where is the interrupt vector located? What are the differences between an interrupt and a subroutine? What will happen if you increase your sampling rate a lot? At what point do you think your program will crash? What is the Nyquist Theorem? How does it apply to this lab?

1)

2)

Total:

There will be a 10 points penalty if you do not use your Lab 7 software.