Epistemic Uncertainty in Language Models

Oleksiy Dolgykh
alexey.dolgich@gmail.com

Abstract

We present a comparison of four Bayesian approaches to epistemic uncertainty estimation in language models—variational and post-hoc inference across full weights and LoRA adapters—plus a Monte Carlo (MC) Dropout baseline. All methods are evaluated on the same 76M-parameter GPT-2-style architecture trained on The Pile with domain-split OOD evaluation. We report three main findings. First, **LoRA-based Bayesian methods achieved the strongest OOD detection in our setup**: BLoB (Bayesian Low-Rank Adaptation by Backpropagation) LoRA (AUROC 0.909) and TFB (Training-Free Bayesianization) (0.917) outperform full-weight variational inference (0.874) with $17\times$ fewer Bayesian parameters, though this comparison is confounded by differences in training procedure and backbone quality (§6). Second, **diagonal Laplace approximation fails** for language model OOD detection—the diagonal Fisher curvature is flat at convergence regardless of parameterization (full weights or LoRA). Third, **MC Dropout** applied to the deterministic checkpoint (zero extra training) achieves AUROC 0.898—competitive with trained Bayesian methods (overlapping confidence intervals with BLoB). **TFB**, also requiring no Bayesian training, matches the best trained methods at AUROC 0.917. Production benchmarks show $N{=}3$ MC samples capture 97% of the full signal.[1]

1 Introduction

Large language models produce confident predictions even on inputs far from their training distribution. Standard softmax probabilities conflate two distinct sources of uncertainty: **aleatoric** uncertainty (inherent ambiguity in the data) and **epistemic** uncertainty (what the model doesn't know). Distinguishing these is critical for safe deployment—a model should flag when it is uncertain due to lack of knowledge, not just when the next token is ambiguous.

Bayesian inference offers a principled framework: replace point-estimate weights with posterior distributions, then measure disagreement across weight samples. Mutual information (MI) between weights and predictions isolates the epistemic component. High MI signals "the model's weights disagree about this input"—a direct indicator of out-of-distribution data.

Recent work has introduced several practical methods for Bayesian weight posteriors in large models, including variational LoRA (Bayesian Low-Rank Adaptation by Backpropagation, BLoB; Wang et al., 2024), post-hoc SVD-based variance (Training-Free Bayesianization, TFB; Shi et al., 2025), and post-hoc Laplace on LoRA [Yang et al., 2024]. These methods have been evaluated on different architectures, datasets, and metrics, making direct comparison complicated.

We address this gap with a **systematic comparison** on a single architecture and evaluation protocol:

All four cells are evaluated on the same 76M-parameter GPT-2-style model trained on The Pile with domain-split evaluation (in-distribution: HackerNews; OOD: ArXiv, FreeLaw, PubMed). We evaluate using AUROC, FPR@95, AUPRC, ECE, Brier score, NLL, and AURC.

[1] Code: https://github.com/avdolgikh/bayesian-llm

	Full weights	LoRA adapters
Variational (train-time)	Variational FFN	BLoB LoRA
Post-hoc (no Bayesian training)	Diag. Laplace FFN	TFB / Diag. Laplace LoRA



Figure 1: Point weights vs. Bayesian weight posteriors. Standard neural networks learn a single weight value (left); Bayesian approaches maintain a distribution over weights (right), enabling epistemic uncertainty estimation through prediction disagreement across weight samples.

Contributions.

1. Head-to-head comparison of variational vs. post-hoc Bayesian methods on the same LM architecture, dataset, and evaluation protocol, including an MC Dropout baseline.
2. LoRA-based methods (BLoB, TFB) achieved stronger OOD detection than full-weight variational inference at 76M parameters, though the comparison is confounded by training procedure and backbone quality differences (§6).
3. Definitive negative result for **diagonal Laplace** in LM OOD detection—both full-weight and LoRA parameterizations produce MI ratio $1.00\times$ (KFAC and full-Hessian variants were not tested).
4. **MC Dropout** (zero extra training) achieves AUROC 0.898—a strong baseline whose confidence interval overlaps with trained BLoB LoRA (0.909). **TFB** (also zero Bayesian training) achieves the best AUROC (0.917) via SVD-structured variance on existing LoRA checkpoints.
5. Production deployment recipe: posterior mean weights for serving (zero overhead), $N{=}3$ MC for uncertainty scoring (97% of full signal).

2 Related Work

Bayesian neural networks. Variational inference for neural network weights was introduced by Graves [2011] and scaled by Blundell et al. [2015] with Bayes by Backprop. Flipout [Wen et al., 2018] reduces gradient variance through pseudo-independent weight perturbations. These methods provide principled uncertainty but have historically been difficult to scale beyond small networks.

Laplace approximation. Post-hoc Laplace fits a Gaussian posterior at the MAP estimate using curvature information. Daxberger et al. [2021] systematized the approach with diagonal, KFAC, and full Hessian variants. While effective for image classifiers, diagonal Laplace has known limitations when Fisher curvature is flat—a condition we find is endemic to well-trained language models.

Figure 2: Four Bayesian methods compared at 76M parameters. Rows distinguish variational (train-time) from post-hoc (no Bayesian training) approaches; columns distinguish full-weight from LoRA parameterizations. AUROC values shown for OOD detection.

Bayesian LoRA methods. Low-Rank Adaptation [Hu et al., 2022] enables parameter-efficient fine-tuning. Several works extend LoRA with Bayesian posteriors. **BLoB** [Wang et al., 2024] places variational Gaussian posteriors on LoRA's A matrix during training, using a KL decomposition theorem to avoid full-space computation. **TFB** [Shi et al., 2025] converts trained LoRA checkpoints into Bayesian adapters post-hoc via SVD-structured isotropic variance with binary search calibration. **Laplace-LoRA** [Yang et al., 2024] applies Laplace approximation to LoRA parameters. **ScalaBL** [Samplawski et al., 2025] performs Bayesian inference in the r-dimensional subspace defined by LoRA rank, scaling to 32B parameters.

These methods report results on different model families (LLaMA, Qwen, GPT-2), different tasks (MMLU, commonsense QA, calibration), and different metrics. Our contribution is an apples-to-apples comparison on a single setup.

OOD detection in LMs. Most work uses token-level predictive entropy or energy scores. We focus on epistemic uncertainty via mutual information, which requires a weight posterior and is theoretically grounded in Bayesian decision theory.

3 Methods

3.1 Uncertainty Quantification

Given a model with weight posterior $q(\theta)$, we draw N weight samples $\{\theta^{(i)}\}_{i=1}^{N}$ and compute token-level predictive distributions $p_t^{(i)} = \mathrm{softmax}(f_{\theta^{(i)}}(x)_t)$. Epistemic uncertainty is measured by **mutual information** (MI):

$$\mathrm{MI} = H\left[\frac{1}{N}\sum_{i=1}^{N} p_t^{(i)}\right] - \frac{1}{N}\sum_{i=1}^{N} H\left[p_t^{(i)}\right] \tag{1}$$

The first term (predictive entropy) captures total uncertainty; the second (expected entropy) captures aleatoric uncertainty. Their difference isolates the epistemic component—uncertainty due to weight disagreement.

For OOD detection, we compute mean MI per sequence and threshold: high MI $\rightarrow$ OOD. We report AUROC as the primary metric, with FPR@95 as the production-relevant operating point.



Figure 3: BLoB LoRA architecture: $\Delta W = \frac{\alpha}{r} BA$. Only A carries variational posteriors (μ_A, σ_A); B remains deterministic, so the KL divergence factorizes in the rank-r A-space (1.97M Bayesian parameters, 2.5% of the 76M model).

3.2 Variational Full-Weight

Standard Bayes by Backprop applied to all FFN layers (fc and proj sublayers across all transformer blocks). Each weight w_{ij} is parameterized as $\mathcal{N}(\mu_{ij}, \sigma_{ij}^2)$ with $\sigma_{ij} = \log(1 + \exp(\rho_{ij}))$. Training minimizes the ELBO: reconstruction loss plus KL divergence to a standard normal prior. This doubles the FFN parameter count (33.6M Bayesian parameters on a 76M model).

3.3 BLoB LoRA

Bayesian Low-Rank Adaptation by Backpropagation [Wang et al., 2024]. LoRA decomposes weight updates as $\Delta W = \frac{\alpha}{r} BA$, with rank r=16. BLoB places variational Gaussian posteriors on A while keeping B deterministic. Via a KL factorization theorem, the full-weight KL reduces to a diagonal computation in the low-rank A-space. Training uses Flipout for variance reduction. Total Bayesian parameters: 1.97M (2.5% of model).

3.4 Diagonal Laplace Approximation

Post-hoc diagonal Laplace: fit a Gaussian posterior $\mathcal{N}\left(\hat{\theta}, (\text{diag}(F) + \lambda I)^{-1}\right)$ at the MAP estimate using per-sample diagonal Fisher information. Applied to both full FFN weights (33.6M parameters) and LoRA parameters (1.97M parameters). No Bayesian training—operates on existing deterministic or LoRA checkpoints.

3.5 TFB

Training-Free Bayesianization [Shi et al., 2025]. Converts a trained LoRA checkpoint into a Bayesian adapter without retraining. SVD of B yields singular values that define per-direction variance scaling: $\Omega_{ij} = \sigma_q / d_i$, where d_i are singular values. A single scalar σ_q controls the posterior width, found by fast binary search on a calibration set.

3.6 MC Dropout

Monte Carlo Dropout [Gal and Ghahramani, 2016] interprets dropout at inference as approximate variational inference with a Bernoulli posterior over weights—each dropout mask corresponds to a sample from this posterior. We apply it to the deterministic baseline checkpoint with the training dropout rate (0.1) on attention and FFN dropout layers. At inference, N stochastic forward passes (each with a different random dropout mask) produce N predictions; MI is computed from their disagreement. No retraining or architectural changes are required—MC Dropout can be applied to any model that was trained with dropout.

Table 1: OOD detection performance (500 ID + 500 OOD sequences, N=20 MC samples). Bold indicates best result per column among Bayesian methods. 95% bootstrap CIs from 10,000 resamples.

Method	Type	MI	AUROC [95% CI]	FPR@95	AUPRC	ECE	Brier	NLL
Deterministic	—	—	.591 [.556, .626]	.794	.552	.022	.606	2.79
MC Dropout	—	—	.898 [.877, .917]	.368	.870	**.012**	.608	**2.79**
Var. FFN	Var × Full	1.32×	.874 [.852, .895]	.494	.866	.023	.673	3.31
Diag. Lap. FFN	Post × Full	1.00×	.536 [.500, .572]	.934	.533	.033	1.00	9.10
BLoB LoRA	**Var × LoRA**	**1.53×**	**.909** [.890, .925]	.424	.909	.044	.658	3.06
TFB LoRA	**Post × LoRA**	1.35×	**.917** [.900, .933]	**.384**	**.918**	.022	.658	3.06
Diag. Lap. LoRA	Post × LoRA	1.00×	.494 [.459, .529]	.956	.495	.034	.998	9.73

4 Experimental Setup

Architecture. GPT-2-style transformer: 16 layers, 8 heads, 512 embedding dimension, 2048 FFN width. ∼76M parameters. No modern tricks (RoPE, SwiGLU, GQA)—deliberately minimal to isolate Bayesian effects from architecture improvements.

Dataset. The Pile [Gao et al., 2020], domain-split for OOD evaluation. Training domains: StackExchange, Ubuntu IRC, EuroParl, HackerNews. OOD domains: ArXiv, FreeLaw, PubMed Central. BPE tokenization (GPT-2 vocabulary, 50,257 tokens). Training: ∼100K steps, batch size 16, sequence length 256.

Evaluation protocol. 500 in-distribution sequences (HackerNews) and 500 OOD sequences (ArXiv + FreeLaw + PubMed) at block_size=256. N=20 MC weight samples (or dropout passes for MC Dropout). Metrics: AUROC, FPR@95 TPR, AUPRC, ECE, Brier score, NLL, AURC. Each Bayesian method uses MI as its uncertainty score; the deterministic baseline uses max-probability. MC Dropout uses the deterministic checkpoint with dropout enabled at inference. 95% bootstrap CIs (10,000 resamples) are reported for AUROC.

Hardware. Single NVIDIA RTX 4070 (12 GB VRAM). AMP fp16 enabled. PyTorch 2.x with Flash Attention.

5 Results

5.1 OOD Detection

The two LoRA methods—BLoB (AUROC 0.909) and TFB (0.917)—achieve the strongest OOD detection with overlapping 95% bootstrap CIs. MC Dropout is competitive at 0.898; its CI [0.877, 0.917] overlaps with BLoB [0.890, 0.925], so the advantage of trained variational LoRA is not statistically significant at this sample size. MC Dropout also achieves the best calibration (ECE=0.012) and tied-lowest NLL (2.79). Full-weight variational inference reaches 0.874 but requires 17× more Bayesian parameters. Both diagonal Laplace variants produce near-random detection (AUROC ≈ 0.5) with degraded calibration (Brier ≈ 1.0, NLL > 9.0).

MI is the only effective uncertainty score. Predictive entropy and max-probability AUROC remain near 0.5 for all methods (Table 2), confirming that token-level uncertainty is insufficient for OOD detection—weight-level disagreement (MI) is required.

5.2 Production Viability

Each MC sample requires a full forward pass because the residual stream diverges after each Bayesian FFN layer—there is no shared computation to amortize. Overhead scales linearly with N. LoRA MC uses 28% less VRAM than full variational MC (382 vs. 534 MB) because only 2.5% of parameters carry variance.

Table 2: Uncertainty score comparison (AUROC by score type). MI provides effective OOD discrimination; predictive entropy and max-probability do not.

Method	MI	Pred. Entropy	Max-Prob
Deterministic	—	0.545	0.591
MC Dropout	0.898	0.561	0.615
Variational FFN	0.874	0.506	0.548
BLoB LoRA	0.909	0.532	0.569
TFB LoRA	**0.917**	0.553	0.589

Table 3: Inference benchmarks (RTX 4070, sequence length 256, batch size 1, AMP fp16). Overhead is relative to deterministic baseline. LoRA MC uses 28% less VRAM than full variational MC.

Method	N	Latency (ms)	Overhead	VRAM (MB)
Deterministic	1	8.1	1.0×	470
Full Var. MC	5	71.0	8.8×	534
Full Var. MC	20	286.9	35.4×	534
BLoB LoRA MC	3	50.5	6.2×	382
BLoB LoRA MC	5	84.4	10.4×	382
TFB LoRA MC	5	133.0	16.4×	389

$N{=}3$ **as the operating point.** AUROC increases from 0.50 ($N{=}1$, no disagreement possible) to $\sim$0.86 ($N{=}3$)—97% of the $N{=}20$ signal. Further samples yield diminishing returns: $N{=}5 \rightarrow 20$ contributes $<$3 AUROC points. We recommend $N{=}3$ as the default operating point (382 MB VRAM).

5.3 Mean-Weights Inference

For serving predictions (without uncertainty scoring), mean-weights inference uses the posterior mean μ as a deterministic point estimate. This avoids MC sampling entirely.

Mean-weights perplexity matches MC-averaged perplexity within 4%. For standard serving (without uncertainty), we use the posterior mean μ as a point estimate. For LoRA methods, this reduces to $W' = W + \frac{\alpha}{r} B\mu_A$—a standard dense model with **zero overhead**, identical architecture and latency to the deterministic baseline. This enables a two-tier deployment: posterior mean weights for serving (no overhead) and MC sampling only when uncertainty estimation is needed.

6 Discussion

LoRA vs. full-weight. LoRA-based methods (BLoB, TFB) achieved stronger OOD detection than full-weight variational inference in our experiments (AUROC 0.909–0.917 vs. 0.874). However, this comparison is confounded by at least three factors: (1) *training procedure*—variational FFN trains the entire model from scratch with ELBO, while LoRA methods fine-tune adapters on a pre-trained deterministic backbone; (2) *backbone quality*—LoRA methods inherit a well-converged base model (ppl=14.3), while full-weight variational must learn representations and posteriors jointly (ppl=21.9); (3) *parameter count*—1.97M vs. 33.6M Bayesian parameters. One hypothesis is that LoRA's rank-16 subspace constrains posteriors to directions that matter for adaptation, producing more meaningful weight disagreement. But disentangling this subspace effect from the training-procedure and backbone-quality confounds requires ablations (e.g., variational fine-tuning on the pre-trained backbone, or BLoB LoRA from random initialization) that we leave to future work.

Diagonal Laplace. Diagonal Laplace approximates the posterior covariance as the inverse of the diagonal Fisher information matrix. We observe that at convergence, the per-parameter Fisher values are near-zero for our well-trained language models—the loss landscape appears flat in most coordinate directions. We hypothesize that this produces an overly diffuse posterior that generates no meaningful prediction disagreement. The failure is consistent across full weights (33.6M params)

Table 4: AUROC vs. number of MC samples N (200 ID + 200 OOD sequences). N=3 captures ∼97% of the N=20 signal for all methods.

Method	N=1	N=3	N=5	N=10	N=20
Full Var. MC	0.500	0.850	0.855	0.866	0.869
BLoB LoRA MC	0.500	**0.861**	**0.879**	0.880	0.888
TFB LoRA MC	0.500	0.847	0.859	0.881	0.886

Table 5: Mean-weights PPL vs. MC-averaged PPL (N=20). Mean-weights matches MC-averaged within 4%, enabling zero-overhead serving.

Method	Mean-Wt PPL	MC-Avg PPL	Relative Diff
Variational FFN	24.48	24.41	0.29%
BLoB LoRA	16.12	16.78	3.93%

and LoRA weights (1.97M params), suggesting the pattern may be general for diagonal Laplace on language models—though we note this does not extend to KFAC or full-Hessian variants, which capture off-diagonal curvature.

TFB vs. diagonal Laplace. Both are post-hoc methods operating on LoRA parameters, yet TFB succeeds (AUROC 0.917) where diagonal Laplace fails (0.494). The key difference appears to be variance structure: diagonal Laplace uses curvature (diagonal Fisher), which in our experiments carries no directional information at convergence. TFB uses SVD of the B matrix, which captures the geometric structure of the LoRA subspace—singular values encode how much each direction contributes to the weight update. We conjecture that this geometric information, being independent of the loss landscape's curvature, remains informative at convergence. Testing this hypothesis would require comparing TFB's SVD-structured variance against alternative variance structures (e.g., random isotropic, Fisher-weighted).

MC Dropout. MC Dropout [Gal and Ghahramani, 2016] achieves AUROC 0.898 with zero extra training cost, and its confidence interval overlaps with BLoB LoRA. For applications where marginal AUROC gains are not critical, MC Dropout may be the most cost-effective path to epistemic uncertainty.

Limitations. Our comparison is conducted at 76M parameters on a GPT-2-style architecture. Scaling behavior to billion-parameter models remains an open question, though ScalaBL [Samplawski et al., 2025] reports positive results for Bayesian LoRA at 32B. We evaluate only autoregressive language modeling with domain-split OOD; other tasks (classification, QA) and OOD types (semantic shift, adversarial) may yield different rankings. Our diagonal Laplace negative result does not extend to KFAC or full-Hessian Laplace variants, which capture off-diagonal curvature—though these are computationally expensive at scale. The LoRA vs. full-weight comparison is observational; the three confounds listed above prevent causal attribution. All results are from single training runs—bootstrap CIs capture evaluation variance but not training variance.

7 Conclusion

In our comparison of Bayesian uncertainty methods for language models, LoRA-based approaches (BLoB and TFB) achieved the strongest OOD detection at 76M-parameter scale (AUROC 0.909–0.917 vs. 0.874 for full-weight variational), though this advantage may partly reflect differences in training procedure and backbone quality rather than parameterization alone. MC Dropout—a zero-cost baseline—proved competitive (AUROC 0.898, overlapping CIs with BLoB). TFB is particularly notable: it achieves the best AUROC (0.917) with zero Bayesian training—only a fast binary search on an existing LoRA checkpoint. Diagonal Laplace approximation fails consistently across all configurations.

For production deployment, we recommend: (1) posterior mean weights for serving predictions (zero overhead—for LoRA, the posterior mean folds into base weights, producing a standard dense

model), (2) $N{=}3$ MC sampling for uncertainty scoring when needed (97% of full signal, modest VRAM overhead). For applications where marginal AUROC gains over MC Dropout are not critical, MC Dropout on any existing checkpoint offers the lowest-cost path to epistemic uncertainty.

References

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *International Conference on Machine Learning (ICML)*, 2015.

Erik Daxberger, Agustinus Kristiadi, Alexander Immer, Runa Eschenhagen, Matthias Bauer, and Philipp Hennig. Laplace redux – effortless Bayesian deep learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning (ICML)*, 2016.

Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. The Pile: An 800GB dataset of diverse text for language modeling. *arXiv preprint arXiv:2101.00027*, 2020.

Alex Graves. Practical variational inference for neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2011.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

Colin Samplawski, Adam D. Cobb, Manoj Acharya, Ramandeep Kaur, and Susmit Jha. Scalable Bayesian low-rank adaptation of large language models via stochastic variational subspace inference. In *Conference on Uncertainty in Artificial Intelligence (UAI)*, 2025.

Haizhou Shi, Yundong Wang, Laixi Han, Hao Zhang, and Hao Wang. Training-free Bayesianization for low-rank adapters of large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025.

Yundong Wang, Haizhou Shi, Laixi Han, Dimitris Metaxas, and Hao Wang. BLoB: Bayesian low-rank adaptation by backpropagation for large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

Yeming Wen, Paul Vicol, Jimmy Ba, Dustin Tran, and Roger Grosse. Flipout: Efficient pseudo-independent weight perturbations on mini-batches. In *International Conference on Learning Representations (ICLR)*, 2018.

Adam X. Yang, Maxime Robeyns, Xi Wang, and Laurence Aitchison. Bayesian low-rank adaptation for large language models. In *International Conference on Learning Representations (ICLR)*, 2024.