

THE

# THERMO-CYCLER® GTR-9600

*The Energy Efficient **THERMO ROTATION®** System for Comfort Heating and Heat Recovery in Large Commercial and Industrial Buildings*

## **STANDARD FEATURES**

Heavy duty welded steel construction.  
Totally enclosed burner assembly  
Control cabinets contains all factory mounted controls.  
Locking enclosures prevent unauthorized entry.  
Low pressure belt driven fans deliver air quietly and efficiently.  
Premium efficiency fan motor reduces electrical consumption.  
Energy management setback controls for efficient operation.  
Precision engineered flame retention plate improves efficiency.  
Burner air collar for direct introduction of outside combustion air.  
Special design all stainless steel heat exchanger  
10 Year Limited Heat Exchanger Warranty



## **UNIT SPECIFICATIONS**

Unit Dimensions .....	124" x 60" x 168"
Shipping Weight .....	Approx. 3200 lbs. (3 sections)
Electrical .....	Premium efficiency, totally enclosed motors ( 4HP, 460V/ 3 Ph)
Burner .....	Midco Unipower G-Series Gas Burner - 1800 Mbh Input,
Gas Pressure Required .....	Natural Gas, 6 - 14" W.C., 2" Gas Train Piping
Flue Collar .....	10" ø approximately 9' 10" above floor
Controls .....	Electronic microprocessor based burner control Factory mounted including programable setback



**THERMO-CYCLER INDUSTRIES Inc.**

111 Hamilton St.

**UNION MILLS, IN 46382-0022**

Phone: (219) 767-2990 • Fax (219) 767-2991

[www.thermocycler.com](http://www.thermocycler.com)