Supplementary Material for Agent = Harness(Model): Five Mechanistic Primitives, and What Is Not One

Anonymous authors
Paper under double-blind review

This supplement is Appendix B of the paper: the evidence for every assignment in the deconstruction of §5. The accompanying archive holds the source files it was generated from (`evidence/`, one Markdown file per harness, and the brief the deconstruction followed) and the five minimal harnesses of Appendix A (`minimal/`).

B Evidence for the Deconstruction

Every assignment in §5, with its evidence. For harnesses with published source, a citation is a path and a line range at the pinned commit; for Claude Code it is a documentation page and section heading on the date read. The same files are published in the repository under `paper/evidence/`. **Path conventions** are given at the start of each harness; **not found** means the mechanism was looked for and not found, not that it is absent.

B.1 Claude Code

Source: https://code.claude.com/docs/en/overview (official docs; source not published) · **Version:** documentation as of 2026-10-15; the docs state no single CLI version (pages reference behaviours by version, the highest seen being v2.1.299; agent-loop page bundles "Claude Code v2.1.290 or later" in SDK v0.3.290). Engineering posts: claude.dev/blog "Prompt caching is everything" (2026-04-30), "A harness for every task" (2026-06-02), "Getting started with loops" (2026-06-30) · **Language:** not documented (docs describe a native binary and an npm package; troubleshooting refers to a "JavaScript heap") **Path conventions:** `D` = https://code.claude.com/docs/en ; `SDK` = `D/agent-sdk` ; `B` = https://claude.dev/blog ; every citation is `page § Section heading` and was read on 2026-10-15. Where a page did not say how something works I write "not documented". **What it is:** Claude Code is Anthropic's agentic coding harness: a terminal/IDE/desktop/web/CI program that wraps Claude models with file, search, shell and web tools, permission gating, memory loading and the loop that chains actions (`D/glossary § Agentic harness`). It reaches the model over the Anthropic Messages API (`/v1/messages`, SSE streaming) or via Amazon Bedrock, Google Cloud's Agent Platform, Microsoft Foundry or an LLM gateway (`D/llm-gateway-protocol § API formats`). The same loop is exposed as a library (Agent SDK, Python/TypeScript) and as `claude -p` for scripts (`SDK/overview § Compare the Agent SDK to other Claude tools`).

Control flow

- **Core loop:** "Claude continues calling tools and processing results until it produces a response with no tool calls"; each cycle (model output with tool calls → tools run → results fed back) is one turn, with no control returned to the caller between turns. `SDK/agent-loop § The loop at a glance`, `§ Turns and messages`
- **Stop condition / result:** the loop ends on a text-only response; the `ResultMessage.subtype` is `success`, `error_max_turns`, `error_max_budget_usd`, `error_during_execution` or `error_max_structured_output_retries`; `stop_reason` carries `end_turn`, `max_tokens` or `refusal`. `SDK/agent-loop § Handle the result`
- **Step budget:** `max_turns`/`--max-turns` "counts tool-use turns only"; no limit by default (print mode only). A message still queued when the limit ends a turn starts a new turn with a fresh count. `SDK/agent-loop § Turns and budget`; `D/cli-reference § CLI flags` (`--max-turns`)
- **Token/cost budget:** `max_budget_usd` is compared "after model responses arrive", so spend can pass the cap by one response; subagent spend counts; at the cap, spawning fails with `Budget limit reached` and background subagents are stopped. `SDK/agent-loop § Budget headroom`
- **Permission gate order (harness consumes the answer):** hooks → deny rules → ask rules → permission mode → allow rules → `canUseTool`/prompt; a hook `allow` never skips deny/ask; `dontAsk` denies at the last step. `SDK/permissions § How permissions are evaluated`; rule order "deny, then ask, then allow … first match" `D/permissions § Manage permissions`

- **Permission modes:** `default` (Manual), `acceptEdits`, `plan`, `auto`, `dontAsk`, `bypassPermissions`; auto is the built-in starting mode for interactive terminal/VS Code on v2.1.283+. `D/permission-modes § Available modes`, `§ Which mode a session starts in`
- **Auto-mode classifier gate:** a second model decides most tool calls; "runs on Claude Sonnet 5 by default rather than on your /model selection"; reads/working-dir edits skip it; it sees user messages, non-read-only tool calls and CLAUDE.md but "Tool results are stripped"; falls back to prompting after 3 blocks in a row or 20 total. `D/permission-modes § How auto mode evaluates actions`, `§ When auto mode falls back`
- **Plan mode:** edits stay blocked until a plan is approved; the approval prompt (`Yes, and use auto mode` / `Yes, manually approve edits` / `No, keep planning`) switches the session's permission mode. `D/permission-modes § Analyze before you edit with plan mode`, `§ Review and approve a plan`. Entering/leaving is itself a tool call (`EnterPlanMode`/`ExitPlanMode`) so the tool set never changes. `B/lessons-from-building-claude-code-prompt-caching-is-everything § Using Plan Mode to design around the cache`
- **Stop hook as loop extender:** a `Stop` hook returning `decision: "block"` keeps Claude working; capped at 8 consecutive continuations (reset on tool use), `CLAUDE_CODE_STOP_HOOK_BLOCK_CAP`. `D/hooks § Stop`; `D/env-vars § Variables` (`CLAUDE_CODE_STOP_HOOK_BLOCK_CAP`)
- **Goal loop:** `/goal` "is a wrapper around a session-scoped prompt-based Stop hook"; after each turn the condition plus conversation go to the small fast model, which returns Not yet met / Met / Impossible; the loop halts if no tool use for several turns. `D/goal § How evaluation works`
- **PostToolBatch gate:** fires once after all tool calls in a batch resolve, "before the next model request"; `decision: "block"` or `continue: false` stops the loop before the next model call. `D/hooks § PostToolBatch`
- **Sub-agent delegation (Agent tool):** the model spawns a subagent in its own context; depth default 3 layers (`CLAUDE_CODE_MAX_SUBAGENT_SPAWN_DEPTH`, `1` disables nesting); at most 20 concurrent (`CLAUDE_CODE_MAX_CONCURRENT_SUBAGENTS`); only the final message returns to the parent. `D/sub-agents § Let subagents spawn their own subagents`, `§ Concurrent subagent limit`; `SDK/subagents § What subagents inherit`
- **Foreground vs background sequencing:** order of decision: teammates → `CLAUDE_CODE_DISABLE_BACKGROUND_TASKS=1` → fork mode on (background, Claude can't request foreground) → fork mode off (background by default, foreground when Claude needs the result); background results arrive later as a completion notification. `D/sub-agents § Run subagents in foreground or background`
- **Model keyed to work:** `opusplan` "Uses opus in plan mode, then switches to sonnet for execution"; subagent model order: per-invocation `model` → frontmatter `model` → `CLAUDE_CODE_SUBAGENT_MODEL` → main model; background functionality (titles, summaries, goal evaluator) uses the Haiku-class model. `D/model-config § Model aliases`, `§ Environment variables`; `D/sub-agents § Choose a model`; `D/sessions § Name your sessions`
- **Dynamic workflows (model-written program sequencing model calls):** "A dynamic workflow is a JavaScript script that orchestrates many subagents"; `agent()`, `parallel()`, `pipeline()`; up to 16 concurrent agents, 4,096 items per call, 1,000 agents per run; no mid-run user input; `Date.now()`/`Math.random()` throw so a relaunch replays deterministically. `D/workflows § What the saved script looks like`, `§ Behavior and limits`, `§ Edit a saved script`
- **Workflow resume:** completed agents return saved results; the first agent whose prompt differs, and every agent after it, runs again. `D/workflows § Which agents run again`
- **Agent teams (outer harness of peer sessions):** lead + teammates with a shared task list and a per-agent mailbox JSON file at `~/.claude/teams/{team-name}/inboxes/{agent-name}.json`; experimental, `CLAUDE_CODE_EXPERIMENTAL_AGENT_TEAMS=1`; no nested teams. `D/agent-teams § Architecture`, `§ Limitations`
- **Prompt- and agent-based hooks (harness-sequenced model calls):** `type: "prompt"` sends hook input to a model (default: the background-functionality model, 30 s timeout) to allow/block; `type: "agent"` spawns a subagent with tools (60 s). `D/hooks § Prompt-based hooks`, `§ Agent-based hooks`
- **Scheduled turns:** `/loop` creates cron tasks; "The scheduler checks every second for due tasks and enqueues them at low priority"; fires between turns, never mid-response; 7-day expiry; self-paced loops end via `ScheduleWakeup` with `stop: true`. `D/scheduled-tasks § How scheduled tasks run`, `§ Stop a loop`
- **Non-interactive exit wait:** after the turn ends, a `claude -p` run stays open for background work; "stops whatever is still running after 10 minutes of continuous idle waiting" (`CLAUDE_CODE_PRINT_BG_WAIT_CEILING_MS`). `D/headless § Background tasks at exit`

Input

- **Prompt capture:** interactive terminal prompt, `claude "query"`, `claude -p "query"`, and piped stdin ("Piped stdin is capped at 10MB"). `D/cli-reference § CLI commands`; `D/headless § Pipe data through Claude`
- **Mid-turn message queue:** a message typed while Claude works is queued; "Claude Code passes it to Claude as soon as those tool calls finish, within the same turn"; commands are held until the turn ends. `D/interactive-mode § When Claude Code sends what you queued`

- **Interrupt:** `Esc` cancels the running tool call and Claude waits; queued messages are sent next. `D/how-claude-code-works § Interrupt and steer`; `D/interactive-mode § General controls`
- **Model-consumed answers:** `AskUserQuestion` returns the user's choice to the model; questions stay open until answered unless `askUserQuestionTimeout` (60s/5m/10m) is set. `D/tools-reference § AskUserQuestion tool behavior`
- **Tool results as input:** each tool execution yields a `UserMessage` carrying the tool result back to the model. `SDK/agent-loop § Message types`
- **Event/stream inputs:** `--input-format stream-json` accepts user messages over stdin; `Monitor` feeds "each output line back to Claude" and can treat WebSocket messages as events; channels push external events into the session. `D/cli-reference § CLI flags`; `D/tools-reference § Tools reference` (`Monitor` row); `D/glossary § Channel`
- **Non-human turns captured through the same entry:** `UserPromptSubmit` "also fires for scheduled tasks, background subagent reports, and messages from other sessions". `D/hooks § UserPromptSubmit`
- **Rich input:** `Ctrl+V` pastes an image as an `[Image #N]` chip; `@path` mentions expand file content; `@server:protocol://resource` fetches MCP resources as attachments. `D/interactive-mode § General controls`; `SDK/modifying-system-prompts § Turn off the context your agent replaces` (`CLAUDE_CODE_DISABLE_FILE_MENTIONS`); `D/mcp § Use MCP resources`
- **MCP elicitation:** a server's mid-task form/URL request is shown as a dialog and the answer goes back to the server (not the model); an `Elicitation` hook can answer it. `D/mcp § Respond to MCP elicitation requests`

Context

- **Request layering (what one call contains):** system prompt (core instructions + tool definitions) → project context (CLAUDE.md, auto memory, unscoped rules) → conversation (messages, tool results); ordered most- to least-stable for prefix caching. `D/prompt-caching § How the cache is organized`
- **Two system prompts:** full vs "a shorter one with abbreviated tool descriptions"; newer models get the short one unless `CLAUDE_CODE_SIMPLE_SYSTEM_PROMPT=0`. `D/env-vars § Variables` (`CLAUDE_CODE_SIMPLE_SYSTEM_PROMPT`)
- **System prompt attribution block:** "a short attribution block to the system prompt containing the client version and a fingerprint"; stripped by `api.anthropic.com`; `CLAUDE_CODE_ATTRIBUTION_HEADER=0` omits it. `D/llm-gateway-protocol § System prompt attribution block`
- **CLAUDE.md delivery:** loaded "as a user message after the system prompt"; all discovered files are concatenated root→working directory, `CLAUDE.local.md` after `CLAUDE.md`; subdirectory files load "once Claude reads, writes, or edits another file in that subdirectory". `D/glossary § CLAUDE.md`; `D/memory § How CLAUDE.md files load`
- **Imports and rules:** `@path` imports expand at launch; `.claude/rules/*.md` load every session, or on demand when `paths:` frontmatter matches a file Claude touches; a CLAUDE.md over 4 MiB is skipped. `D/memory § Import additional files`, `§ Path-specific rules`, `§ How it works`
- **Auto memory (model-kept record):** `~/.claude/projects/<project>/memory/MEMORY.md`; "The first 200 lines of MEMORY.md, or the first 25KB, whichever comes first, are loaded"; topic files read on demand; a write past the limit returns an error telling Claude to rewrite the index. `D/memory § How it works`, `§ Storage location`
- **System reminders:** harness-added context delivered "wrapped in `<system-reminder>` tags inside a user message, or … a separate message with the `system` role": CLAUDE.md, output style, hook `additionalContext`, skill list, file-changed notes, attribution lines. `D/glossary § System reminder`
- **Output style injection:** "Claude Code sends the active style's instructions with every request" as a conversation message, so the cached prefix survives a switch. `D/output-styles § How output styles work`; `D/prompt-caching § Changing output style`
- **Skills in context:** descriptions (truncated at 1,536 chars) are always in context; the body loads on invocation as a user message and stays for the session; `disable-model-invocation: true` keeps the description out. `D/skills § Frontmatter fields`, `§ Controlling visibility and context cost`; `D/prompt-caching § Invoking skills and commands`
- **Skill dynamic context:** `!command` runs a shell command before the model sees the skill and splices the output in. `D/skills § Dynamic context injection`
- **MCP tool search (deferred definitions):** only names and server instructions load; schemas arrive via the `ToolSearch` tool; `ENABLE_TOOL_SEARCH auto` loads upfront while definitions are under 10% of context; description caps 4,096 (upfront) / 16,384 (deferred) chars. `D/mcp § Scale with MCP tool search`, `§ Configure tool search`
- **Environment and git snapshot:** working directory, platform, shell, OS and a git branch/status/recent-commits block are added at session start; `includeGitInstructions: false` drops the git snapshot. `D/context-window` (Environment info event); `SDK/modifying-system-prompts § Turn off the context your agent replaces`; `D/prompt-caching § Cache scope`

- **Fitting tool results:** Bash output inline "up to roughly 30,000 characters"; past that a file path plus 2,000-char preview; MCP results capped at 25,000 tokens and text over 50,000 chars spilled to a file; `Read` returns at most 25,000 tokens per call and refuses whole files over 256 KB. `D/tools-reference § Output limits`, `§ Large files`; `D/mcp § Raise the limit for a specific tool`; `D/env-vars § Variables` (`MAX_MCP_OUTPUT_TOKENS`)
- **Auto-compaction trigger:** by default "compacts when the conversation reaches the model's context limit"; native-1M models compact "at about 967K tokens"; window settable 100K–1M via `/autocompact`, `autoCompactWindow`, `--autocompact`, `CLAUDE_CODE_AUTO_COMPACT_WINDOW`. `D/model-config § Default auto-compact thresholds`, `§ Set the auto-compact window`
- **Compaction order:** "It clears older tool outputs first, then summarizes the conversation if needed." `D/how-claude-code-works § When context fills up`
- **Compaction as a forked request:** the summarization call reuses the same system prompt, tools and history "plus a summarization instruction appended as a final user message"; inherits the session's thinking config. `D/prompt-caching § Compacting the conversation`; `D/context-window § What survives compaction`; `B/lessons-from-building-claude-code-prompt-caching-is-everything § COMPACTING WITHOUT BREAKING THE CACHE`
- **What survives compaction:** system prompt/output style still apply; project-root CLAUDE.md, auto memory, plan file re-injected from disk; up to five recently modified files re-read (over 5,000 tokens → path reference); invoked skill bodies re-injected "capped at 5,000 tokens per skill and 25,000 tokens total"; hook context is summarized away. `D/context-window § What survives compaction`
- **Hook-supplied context:** `additionalContext` is wrapped in a system reminder; `additionalContext`, `systemMessage`, `initialUserMessage` capped at 10,000 chars (longer saved to file with a 2,000-char preview); `PostToolUse.updatedToolOutput` replaces what Claude sees. `D/hooks § JSON output`, `§ Add context for Claude`, `§ PostToolUse`
- **Sub-agent context:** a non-fork subagent gets its own system prompt plus environment details, the task message, CLAUDE.md hierarchy (not for Explore/Plan), git snapshot, preloaded skills; not the parent history, output style or auto memory. A fork gets the full conversation, system prompt and tools. `D/sub-agents § What loads at startup`, `§ How forks differ from other subagents`
- **Sub-agent output scanning:** before the parent reads a report, control-tag imitations get a backslash and a `[harness: ...]` marker line is prepended; nothing is removed. `D/sub-agents § Subagent output scanning`; `SDK/subagents § What subagents inherit`

Model interface

- **Wire format:** Anthropic Messages format, "Inference requests post to `/v1/messages?beta=true`"; optional `/v1/messages/count_tokens` (falls back to a character estimate); headers `anthropic-version: 2023-06-01`, `anthropic-beta`, `x-claude-code-session-id`, `x-claude-code-agent-id`. `D/llm-gateway-protocol § API formats`, `§ Optional endpoints and startup traffic`, `§ Request headers`
- **Providers/backends:** `CLAUDE_CODE_USE_BEDROCK`, `CLAUDE_CODE_USE_VERTEX`, `CLAUDE_CODE_USE_FOUNDRY`, Claude Platform on AWS, or any gateway via `ANTHROPIC_BASE_URL`; Bedrock uses `invoke-with-response-stream` binary eventstream. `D/env-vars § Variables`; `D/llm-gateway-protocol § API formats`
- **Streaming receipt:** "Claude Code reads each streaming inference response event by event as it arrives"; expects the full sequence through `message_delta`/`message_stop`, else treats it as a dropped connection. `D/llm-gateway-protocol § Streaming`
- **Retry policy:** "retries transient failures up to 10 times with exponential backoff" (`CLAUDE_CODE_MAX_RETRIES`, capped at 15); retries server errors/529/timeouts before output starts, dropped connections (up to 2 after thinking), stalled streams (once), no-headers (once per request), temporary 429s; never re-runs after a completed text or tool block "because that could execute the same tool calls twice". `D/errors § Automatic retries`
- **529 backoff:** `CLAUDE_CODE_OVERLOADED_RETRY_BASE_DELAY_MS` 500 → `CLAUDE_CODE_OVERLOADED_RETRY_MAX_DELAY_MS` 32000; `retry-after` honoured, and >60 s stops retries outside watchdog sessions; `x-should-retry` read. `D/errors § Automatic retries`; `D/llm-gateway-protocol § Response headers`
- **Indefinite retry for unattended runs:** `CLAUDE_CODE_RETRY_WATCHDOG=1` "Retries 429 and 529 capacity errors indefinitely", backing off up to 5 minutes. `D/env-vars § Variables`
- **Timeouts and watchdogs:** `API_TIMEOUT_MS` default 600000; first-byte deadline 180 s (direct API) / 300 s (elsewhere) + 1 s per 32 KB of body; event-level watchdog 300 s; byte-level watchdog 180 s/300 s; body idle timeout 5 min. `D/env-vars § Variables` (`API_TIMEOUT_MS`); `D/network-config § Streaming idle watchdogs`
- **Backup model when the request can't be served:** `--fallback-model sonnet,haiku` / `fallbackModel` runs "when the primary model is overloaded, unavailable, or returns another non-retryable server error"; chain of ≤ 3; applies to the current turn only; subagents use it too. `D/model-config § Fallback model chains`

- **Safety-flag model fallback:** when a server safety classifier flags a request, Claude Code "can re-run it on a fallback model" (e.g. Opus 4.8 for cybersecurity); `switchModelsOnFlag`. `D/model-config § Automatic model fallback`
- **Capability-rejection recovery:** on a 400 rejecting `thinking`, a mid-conversation system message, `cache_control`, the advisor tool or `output_config.effort`, Claude Code retries without that capability for the rest of the conversation; a rejected thinking signature strips earlier thinking blocks. `D/llm-gateway-protocol § Automatic retry and error forwarding`
- **Context-limit rejection:** a request rejected because input + `max_tokens` exceeds the limit is retried "with a reduced max_tokens", then compacted when no reduction fits. `D/errors § Automatic retries`
- **Prompt-cache markers and TTL:** `cache_control` on system blocks and messages; main conversation gets 1 h TTL on subscription usage, 5 min otherwise; subagents/compaction/titles get 5 min; `promptCacheTtl`, `FORCE_PROMPT_CACHING_5M`, `DISABLE_PROMPT_CACHING`. `D/prompt-caching § Which TTL each request gets`, `§ Choose the TTL yourself`, `§ Disable prompt caching`
- **Reasoning parameters on the wire:** `thinking: {"type": "adaptive"}` for 4.6+ models; effort and structured output in `output_config` with paired beta headers; `MAX_THINKING_TOKENS` fixed budget (≥1,024, ≤ max output - 1); `CLAUDE_CODE_MAX_OUTPUT_TOKENS` (default 32000 / cap 128000 for unknown IDs). `D/llm-gateway-protocol § Feature pass-through`; `D/env-vars § Variables`
- **Retry visibility:** a `system/api_retry` event (attempt, max_retries, retry_delay_ms, error_status, error category) is emitted in stream-json before each retry. `D/headless § Handle API retries`

Output

- **Built-in tool set:** Agent, AskUserQuestion, Bash, Edit, EndConversation, Glob, Grep, LSP, Monitor, NotebookEdit, PowerShell, Read, SendMessage, Skill, TaskCreate/TaskUpdate/TodoWrite, ToolSearch, WebFetch, WebSearch, Workflow, Write (+ MCP tools `mcp__<server>__<tool>`). `D/tools-reference § Tools reference` (table); `SDK/agent-loop § Built-in tools`
- **Concurrent execution of one response's calls:** "Read-only tools (like Read, Glob, Grep, and MCP tools marked as read-only) can run concurrently. Tools that modify state (like Edit, Write, and Bash) run sequentially"; custom tools opt in via `readOnlyHint`. `SDK/agent-loop § Parallel tool execution`
- **Bash executor:** default timeout 2 min (`BASH_DEFAULT_TIMEOUT_MS`), ceiling 10 min (`BASH_MAX_TIMEOUT_MS`); a foreground command that hits its timeout "moves it to the background instead of stopping it"; background commands get 30 min (max 2 h); env vars don't persist between commands; shell aliases/options captured in `~/.claude/shell-snapshots/`. `D/tools-reference § Timeout and output limits`, `§ Foreground commands that move to the background`, `§ Time limit for background commands`, `§ What persists between commands`; `D/claude-directory § Cleaned up automatically`
- **Sandbox technology:** macOS Seatbelt; Linux/WSL2 bubblewrap + socat; no sandbox on native Windows; covers Bash, PowerShell and Monitor commands only, not file tools, MCP servers or hooks. `D/sandboxing § OS-level enforcement`, `§ What runs outside the sandbox`
- **Sandbox network path:** "Claude Code runs the sandbox proxy on your machine, outside the sandbox, and directs commands to it with HTTP_PROXY, HTTPS_PROXY, ALL_PROXY"; the proxy checks hostnames against `allowedDomains`/`deniedDomains`, refuses names resolving only to local addresses, and can mask credentials with a sentinel (requires `tlsTerminate`). `D/sandboxing § Network isolation`, `§ Hostnames that resolve to local addresses`, `§ Mask credentials`
- **Sandbox filesystem path:** writable: working dir + per-user `$TMPDIR`; "Protected paths" (settings, hooks, MCP config) are denied even inside writable dirs; `excludedCommands` run unsandboxed; strict mode `allowUnsandboxedCommands: false`. `D/sandboxing § Filesystem isolation`, `§ Protected paths`, `§ Turn off the retry with strict sandbox mode`
- **WebFetch executor:** converts HTML to Markdown, "runs the prompt against the content in a separate model call, and Claude receives the result of that call rather than the raw page"; 15-min response cache; hostname first checked against an Anthropic blocklist at `api.anthropic.com` (`skipWebFetchPreflight`). `D/tools-reference § WebFetch tool behavior`; `D/data-usage § WebFetch domain safety check`
- **WebSearch:** server-side tool; "An interactive terminal session has a limit of 200 WebSearch calls" shared with subagents. `D/tools-reference § WebSearch tool behavior`, `§ Session search limit`
- **Read/Edit/Write executors:** Read returns numbered lines, resizes images (>500 KB re-encoded as JPEG), reads PDFs in ≤20-page ranges via `pdftoppm`; Edit/Write enforce read-before-edit on older models. `D/tools-reference § Read tool behavior`, `§ Edit tool behavior`, `§ Write tool behavior`
- **MCP executor:** stdio, HTTP (falls back to SSE), WebSocket transports; `MCP_TIMEOUT` 30 s startup, `MCP_TOOL_TIMEOUT` ~28 h, 60 s per HTTP request, idle timeout 5 min remote/30 min stdio, main-conversation calls auto-background after 2 min (`CLAUDE_CODE_MCP_AUTO_BACKGROUND_MS`); invalid schemas and names >128 chars

are excluded per tool. D/mcp § Transports, § Timeouts, § Tools with invalid input schemas, § Tools with names longer than 128 characters

- **Monitor executor:** Claude writes a script run in the background, or opens a WebSocket; deadline 5 min by default, max 30 min (10 min under -p). D/tools-reference § Monitor tool
- **Rendering the stream:** an AssistantMessage is emitted per content block; stream_event deltas (text_delta, input_json_delta) with --include-partial-messages; the spinner shows a live output-token count. SDK/streaming-output § Message flow; D/costs § Read the token count beside the spinner
- **Structured output:** --output-format json|stream-json, --json-schema validated output in structured_output; up to 5 attempts (MAX_STRUCTURED_OUTPUT_RETRIES). D/headless § Get structured output; D/env-vars § Variables
- **Hook executors:** handler types command, http, mcp_tool, prompt, agent; "All matching hooks run in parallel. Identical handlers from multiple settings files run once"; defaults 600 s command/http/mcp_tool; exit 2 blocks (PreToolUse) with stderr fed to Claude; async: true detaches; PreToolUse.updatedInput rewrites tool arguments before execution. D/hooks § Configuration, § Exit code output, § Run hooks in the background, § PreToolUse
- **User-facing artifacts:** file checkpoints snapshot files "before each prompt you send that starts a turn", 100 most recent kept, /rewind restores code and/or conversation; Bash-made and subagent edits are not tracked. D/checkpointing § Automatic tracking, § Bash command changes not tracked, § Subagent edits not restored
- **EndConversation:** never prompts, PreToolUse hooks don't run for it, and deny rules/--tools can't remove it while any other tool remains. D/tools-reference § EndConversation tool behavior
- **Permission prompt surface:** Manual mode asks for Bash (except a built-in read-only set: ls, cat, git status…), file modification, WebFetch (except preapproved doc domains), WebSearch; "Yes, don't ask again" persists per repository. D/permissions § Permission system, § Read-only commands

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Input/Context (transcript, memory); Output (checkpoints); Control flow (resume)	Every message/tool use is appended to ~/.claude/projects/<project>/<session-id>.jsonl; swept after cleanupPeriodDays (30 d default); auto memory excluded from the sweep; file-history/<session>/ snapshots, plans/, tool-results/; --resume/--continue restore history, model, agent, permission mode, goal and cron tasks; --fork-session//branch copy to a new ID; SDK session_store mirrors transcripts; CLAUDE_CODE_TRANSCRIPT_LOCAL_GC trims history before the last compaction once the file passes 5 MB	D/sessions § Where transcripts are stored, § What a resumed session restores; D/claude-directory § Cleaned up automatically; D/memory § Storage location; SDK/agent-loop § Sessions and continuity; D/env-vars § Variables
Safety & security	Control flow (gates); Output (sandbox, executors); Context (scanning)	deny→ask→allow rules plus modes; auto-mode classifier with tool results stripped and a "server-side probe" over incoming tool results; critical paths (rm -rf /, ~, cwd) never approvable by allow rule or hook; protected paths; OS sandbox + domain allowlist + credential masking; subagent output scanning; teammate messages can't approve prompts; WebFetch summarised by a separate model call; -p runs project hooks/MCP without a trust dialog (--bare to skip); credentials in Keychain or a 0600 file; prompt-injection list	D/permission-modes § What the classifier blocks by default, § Critical paths, § Protected paths; D/sandboxing § What the sandbox restricts; D/subagents § Subagent output scanning; D/agent-teams § Messages between agents; D/security § Protect against prompt injection, § Additional safeguards; D/headless § Start faster with bare mode

Concern	Where it lives (primitive)	Mechanism	Evidence
Observability	Model interface (api events); Output (tool events); operator records	OpenTelemetry metrics (`claude_code.cost.usage`, `token.usage`, `session.count`, `lines_of_code.count`…) and events (`user_prompt`, `tool_result`, `api_request`, `api_error`, `tool_decision`) via `CLAUDE_CODE_ENABLE_TELEMETRY=1`; content opt-ins incl. `OTEL_LOG_RAW_API_BODIES=file:<dir>`; `/usage` session cost + `Prompt cache (main)` line; status-line `current_usage`/`prompt_cache`; debug log `~/.claude/debug/<session-id>.txt` with hook durations; stream-json `system/init`, `api_retry`, `compact_boundary`, `permission_denials`; gateway hint headers	`D/monitoring-usage § Metrics`, `§ Events`, `§ Content opt-in`; `D/costs § Prompt cache statistics`; `D/hooks § Debug hooks`; `D/headless § Read session metadata`; `D/llm-gateway-protocol § Gateway hint headers`
Resilience	Model interface (retries/watchdogs/fallback); Context (compaction); Control flow (resume/stall)	10 retries w/ exponential backoff, no re-run after a completed block (partial output kept + "may be incomplete" notice, `-p` auto-continues ≤3×); four streaming watchdogs; fallback model chain; context-limit retry with reduced `max_tokens` then compaction; auto-compact "stops auto-compacting after a few attempts" on thrashing; interrupted tool call marked cut-off on resume (`CLAUDE_CODE_RESUME_INTERRUPTED_TURN`); SIGTERM runs `SessionEnd` hooks and exits 143; workflow agents restart on stall up to 5×; `/goal` auto-retries 3× then pauses; usage-limit auto-wait (`autoContinueAtUsageLimit`); MCP auto-reconnect	`D/errors § Automatic retries`, `§ The response above may be incomplete`; `D/network-config § Streaming idle watchdogs`; `D/model-config § Fallback model chains`; `D/how-claude-code-works § When context fills up`; `D/troubleshooting § Auto-compaction stops with a thrashing error`; `D/sessions § What a resumed session restores`; `D/headless § Stop a run with SIGTERM`; `D/workflows § When an agent stalls and restarts`; `D/goal § Other errors retry or pause the goal`
Performance	Context (layering, deferral, trimming); Model interface (cache TTL); Output (parallel tools); Control flow (background)	Prefix-ordered requests and cache-safe updates via messages (system reminders); MCP schemas deferred; compaction as a forked cached request; `/rewind` truncates to a cached prefix; idle compaction before 1 h TTL expiry; read-only tools run concurrently; background subagents and auto-backgrounded commands; workflow fan-out holds siblings ≤5 s so they share the first agent's cache; WebFetch 15-min cache; `--bare` skips discovery; cache hit rate is alerted on internally	`D/prompt-caching § How the cache is organized`, `§ Compacting the conversation`, `§ Rewinding the conversation`, `§ Subagents and the cache`; `D/workflows § Prompt caching in a fan-out`; `SDK/agent-loop § Parallel tool execution`; `D/headless § Start faster with bare mode`; `B/lessons-from-building-claude-code-prompt-caching-is-everything § LESSONS LEARNED`

Concern	Where it lives (primitive)	Mechanism	Evidence
Evaluation	not documented for the harness itself	No harness test suite or agent evals are documented. Adjacent: `/insights` analyses up to 200 local sessions into a report; skills are evaluated by running prompts with the skill on/off (skill-creator plugin); the auto-mode classifier's first request "validates the Sonnet 5 default"; "Evals" listed as a workflow use case	`D/costs § Analyze your usage patterns`; `D/skills § Evaluating skills`; `D/permission-modes § How auto mode evaluates actions`; `B/a-harness-for-every-task-dynamic-workflows-in-claude-code § Use cases`

Design decisions (one line each: the choice this harness made within a primitive)

- Input: one entry point for everything that starts a turn (typed prompts, piped stdin, queued mid-turn messages delivered after the current tool batch, scheduled/cron prompts, cross-session and channel messages, background-subagent reports), all passing through `UserPromptSubmit`. `D/hooks § UserPromptSubmit`; `D/interactive-mode § When Claude Code sends what you queued`
- Context: a stable cached prefix (system prompt + tools, then project context) with every later update appended as a message or `<system-reminder>`; MCP schemas deferred behind `ToolSearch`; compaction on reaching the window via a forked request that re-injects CLAUDE.md, memory, five recent files and invoked skills. `D/prompt-caching § How the cache is organized`; `D/context-window § What survives compaction`
- Model interface: direct Anthropic Messages API with streaming, 10 exponential-backoff retries that never re-issue after a completed tool block, four idle watchdogs, a user-configured fallback model chain, and capability-rejection downgrade for gateways. `D/errors § Automatic retries`; `D/llm-gateway-protocol § Automatic retry and error forwarding`
- Output: a fixed built-in tool set plus MCP; read-only calls run concurrently, mutating calls sequentially; shell commands run under an OS sandbox (Seatbelt/bubblewrap) with a local domain-allowlist proxy; large results spill to files; file edits are checkpointed for `/rewind`. `SDK/agent-loop § Parallel tool execution`; `D/sandboxing § OS-level enforcement`; `D/checkpointing § Automatic tracking`
- Control flow: loop until a text-only response, with the decision to stop extendable by Stop hooks and `/goal`'s evaluator model; a six-step permission pipeline whose default gate is a second model (auto mode); delegation through an `Agent` tool (depth 3, 20 concurrent, background by default) and, at scale, a model-written JavaScript workflow the runtime executes. `SDK/agent-loop § Turns and messages`; `SDK/permissions § How permissions are evaluated`; `D/workflows § When to use a workflow`

Hard cases

- **WebFetch's inner model call:** a tool (output) that itself calls the model and decides what the main model sees (a summary, not the page). Resolved by rule 21: the tool call is output; the summarisation is a context decision (and a prompt-injection defence, `D/security § Additional safeguards`); the extra request is model interface. `D/tools-reference § WebFetch tool behavior`
- **Auto-mode classifier:** an approval gate the harness consumes (control flow) implemented as a separate model request with its own stripped-down context (`D/permission-modes § How auto mode evaluates actions`). Resolved: the decision is control flow; the request is model interface; the stripping of tool results is context assembly for that side call. Its "server-side classifier review" variant runs inside the API as part of the session's model requests, i.e. partly outside the harness. `D/permission-modes § Server-side classifier review`
- **Prompt/agent hooks and the `/goal` evaluator:** harness-sequenced model calls that decide whether to go again. Resolved by rule 27 (a program that sequences model calls is control flow). `D/hooks § Prompt-based hooks`; `D/goal § How evaluation works`
- **Dynamic workflows:** the model writes a JS program at run time whose `agent()` calls sequence model calls → control flow (rule 27); the `Workflow` tool call that launches it is output; the script's intermediate results live "in script variables" rather than any context. `D/workflows § How a workflow runs`
- **Compaction:** the trigger (window threshold) and the result (summary replaces history) are context; the summarisation is a model call (model interface); the thrashing stop after "a few attempts" is a loop decision (control flow/resilience). `D/model-config § Default auto-compact thresholds`; `D/troubleshooting § Auto-compaction stops with a thrashing error`

- **Context-limit retry with reduced `max_tokens`:** a retry of a failed request (model interface) that changes the request's parameters (context). Placed under model interface because the trigger is a rejected request and the content is unchanged; noted as a boundary case. `D/errors § Automatic retries`
- **Hook rewrites:** `PreToolUse.updatedInput` changes the action before execution (output executor side); `PostToolUse.updatedToolOutput` changes what the model is shown (context). Decomposed per rule 1. `D/hooks § PreToolUse`, `§ PostToolUse`
- **Two kinds of model switch:** `opusplan` (plan vs execution) and subagent `model` fields are keyed to the work → control flow; `--fallback-model` (overloaded/unavailable) and safety-flag fallback → model interface (rule 22). `D/model-config § Model aliases`, `§ Fallback model chains`, `§ Automatic model fallback`
- **Subagent output scanning:** modifies a tool result before the model reads it → context (what the model is shown) and a safety concern; not output, because nothing is executed. `D/sub-agents § Subagent output scanning`
- **Checkpoints and session titles:** file snapshots are a user artifact (output) that persists; the title is produced by a cheap-model call keyed to the work (control flow) and stored for the operator/user (persistence). `D/checkpointing § Automatic tracking`; `D/sessions § Name your sessions`
- **Queued messages mid-turn:** capturing the message is input; deciding to hand it to the model "as soon as those tool calls finish, within the same turn" is a loop decision (control flow). `D/interactive-mode § When Claude Code sends what you queued`
- **Agent teams' mailbox:** messages arrive as turns for the recipient (input) but the delivery, idle notifications and task-claim locking are an outer harness's control flow; the classifier reviewing each `SendMessage` is a safety gate. Depth: lead → teammates (no nested teams); results return via idle notifications containing the final answer. `D/agent-teams § Context and communication`, `§ Limitations`
- **Server-side classifier review and the server-side prompt-injection probe:** DOES NOT FIT the five primitives cleanly, because the safety decision is made inside the API during the model request rather than by the harness; the harness only consumes the verdict (denies when none arrives after ten responses). `D/permission-modes § Server-side classifier review`; `D/glossary § Prompt injection`
- **`EndConversation`:** a tool whose only effect is to stop the loop; by rule 21 the call is output and the stop is control flow; its un-removability is a safety choice. `D/tools-reference § EndConversation tool behavior`

Summary row

Input	Context	Model interface	Output	Control flow
Prompts, stdin, queued messages, events, tool results, AskUserQuestion answers	Cached prefix + appended reminders; CLAUDE.md/memory; deferred MCP; compaction	Messages API streaming; 10 retries, watchdogs, fallback chain	Built-in + MCP tools; sandboxed Bash; concurrent read-only calls; checkpoints	Loop until no tool calls; six-step permission gate; Agent/workflow delegation

B.2 OpenAI Codex CLI

Source: https://github.com/openai/codex · **Version:** commit f0c5077c34ec7a76b4ad9134835925e6ae3d72ec (2026-10-15) · **Language:** Rust (workspace under `codex-rs/`) **Path conventions:** all paths are relative to `codex-rs/`. `core/` = crate `codex-core`; `session/` = `core/src/session/`; `tools/` under core = `core/src/tools/`; top-level crates (`codex-api`, `sandboxing`, `rollout`, `otel`, `prompts`, `protocol`, ...) are siblings of `core/`. Line ranges are `L<start>--L<end>` at the pinned commit. **What it is:** Codex is OpenAI's terminal/IDE coding agent. A `Session` (one thread) receives `Op` submissions over a channel, runs each user turn as a task that loops "sample → run tool calls → sample again" until the model stops calling tools, and talks to the OpenAI Responses API over HTTP SSE or a Responses WebSocket. It wraps execution in OS sandboxes (Seatbelt / seccomp+bwrap / Windows restricted token), gates risky actions with user or "Guardian" (model-reviewer) approvals, persists every thread as a JSONL rollout, and can spawn sub-agent threads that are full `Session`s of their own.

Control flow

- **Submission loop (session-level dispatcher):** `submission_loop` `select!`s on shutdown, the `rx_sub` channel and mailbox updates, then matches each `Op` (TurnInput, Interrupt, ExecApproval, UserInputAnswer, Compact, Review, Shutdown...). `core/src/session/handlers.rs:L440--L727`
- **Turn admission modes:** `turn_input::handle` routes a TurnInput by mode: `StartOrSteer`, `StartIfIdle`, `ContinueIfIdle` (recovery requires an internal response item), `Steer { expected_turn_id }`. `core/src/session/turn_input.rs:L230--L296`

- **Task spawn replaces the active task:** `Session::spawn_task` first calls `abort_all_tasks(TurnAbortReason::Replaced)` then `start_task`, which registers the task on `active_turn`, seeds pending input from the mailbox, and sets a fresh `CancellationToken`. `core/src/tasks/mod.rs:L273--L340`
- **Abort / interrupt:** `abort_all_tasks` takes the active turn, cancels the task and clears pending approvals; on `Interrupted` it may immediately start a new turn for pending work. `core/src/tasks/mod.rs:L564--L592`
- **Outer task loop (RegularTask::run):** calls `run_turn` repeatedly until there is no pending input or a terminal error was recorded. `core/src/tasks/regular.rs:L105--L124`
- **Inner turn loop (run_turn):** `loop { drain pending input → capture StepContext → build sampling input → run_sampling_request → decide follow-up }; needs_follow_up = model_needs_follow_up || has_pending_input`; stops with `break` when `!needs_follow_up` after stop hooks run. `core/src/session/turn.rs:L453--L578`, `L604`, `L718--L821`
- **Stop condition from the model:** `try_run_sampling_request` sets `needs_follow_up = true` when any output item is a tool call, and on `ResponseEvent::Completed { end_turn: Some(false) }`. `core/src/stream_events_utils.rs:L351--L354`; `core/src/session/turn.rs:L3112--L3118`
- **Stop hooks can force another iteration:** `run_turn_stop_hooks` result `should_block` with a continuation prompt records a hook message, sets `stop_hook_active` and `continue`s the loop; `should_stop` breaks. `core/src/session/turn.rs:L718--L768`
- **Mid-turn roll-over on context limit:** `should_roll_over = auto_compaction_enabled && needs_follow_up && (new_context_window requested || token_limit_reached || background candidate ready)` triggers `run_auto_compact(..MidTurn..)` then `continue`. `core/src/session/turn.rs:L654--L716`
- **Steering (user message while a turn runs):** `steer_input` validates the active task is a Regular task (Review/Compact are non-steerable), then pushes the input onto `turn_state.pending_input` for the next loop iteration. `core/src/session/turn_input.rs:L799--L889`
- **Pending-input drain point:** `get_pending_input` splits off `turn_state.pending_input.items` and appends mailbox items only if the turn currently accepts mailbox delivery. `core/src/session/input_queue.rs:L400--L432`
- **Sampling retry loop:** `run_sampling_request` wraps `try_run_sampling_request` in a `loop` whose continuation is decided by `handle_response_stream_error` (retry budget `stream_max_retries`), and returns early with `needs_follow_up: true` on preempt. `core/src/session/turn.rs:L1707--L1835`
- **Approval gate consumed by harness (user):** `Session::request_command_approval` registers a `oneshot` under the approval id, emits `EventMsg::ExecApprovalRequest`, and awaits `rx_approve` (defaulting to `Abort` if dropped); `exec_approval` resolves it, and `Abort` calls `interrupt_task`. `core/src/session/mod.rs:L2923--L3012`; `core/src/session/handlers.rs:L177--L207`
- **Approval precedence:** hooks first, then Guardian (model reviewer) if enabled/strict, else user. `core/src/tools/approvals.rs:L479--L498`, `L541--L557`
- **Session-scoped approval cache:** `with_cached_approval` returns `ApprovedForSession` without asking when every cache key already holds that decision. `core/src/tools/sandboxing.rs:L72--L110`
- **Sub-agent spawn (effect of `spawn_agent` tool):** `thread_spawn::spawn` builds a `SessionSource::SubAgent(ThreadSpawn{parent_thread_id, depth, ...})` and calls `agent_control.spawn(SpawnRequest{ input: AgentInput::Message{ mode: TriggerTurn }, ... })`. `core/src/thread_spawn.rs:L58--L167`
- **Depth and fan-out limits:** `exceeds_thread_spawn_depth_limit(depth, max_depth)` (`depth > max_depth`) rejects a spawn with "Agent depth limit reached. Solve the task yourself."; `reserve_spawn_slot` returns `AgentLimitReached { max_threads }` when the registry is full. `core/src/agent/registry.rs:L85--L109`; `core/src/tools/handlers/multi_agents/spawn.rs:L74--L80`
- **Sub-agent results return:** `wait_agent` polls child status futures with `timeout_at(deadline, ...)` (default `DEFAULT_WAIT_TIMEOUT_MS`) and collects final statuses; `send_input` steers or starts a child turn through `start_or_steer_turn`. `core/src/tools/handlers/multi_agents/wait.rs:L95--L99`, `L181--L200`; `core/src/agent/control.rs:L137--L165`
- **Delegate (review / guardian) sub-session:** `run_codex_thread_one_shot → run_codex_thread_interactive → Session::spawn(SessionSpawnArgs{ thread_source: Subagent|GuardianReview, agent_control: Provided, ... })`; child events/ops are forwarded via `forward_session_io` tasks. `core/src/codex_delegate.rs:L105--L228`, `L231--L262`
- **Routing keyed to the work (review model):** the review task clones config, disables web search/collab, sets `base_instructions = REVIEW_PROMPT`, `approval_policy = Never`, and `model = config.review_model` before delegating. `core/src/tasks/review.rs:L105--L140`
- **Routing keyed to the work (guardian model):** the reviewer session resolves its own `review_model` and reasoning effort separately from the parent. `core/src/guardian/review_session.rs:L330--L372`
- **Code mode: model-written program sequences tools (output), but can call back into the harness:** nested calls from a cell go through `CodeModeCellDelegate::invoke_tool → DispatchMessage::InvokeTool` to

the turn worker; the program sequences tools only, not model calls. core/src/tools/code_mode/delegate.rs:L317--L360
- **Session token budget (stop):** record_rollout_budget_usage returns SessionBudgetExceeded once weighted usage reaches limit_tokens. core/src/agent/control/budget.rs:L12--L17; core/src/rollout_budget.rs:L48--L65
- **Model-requested context reset (new_context_window tool):** the handler calls session.request_new_context_window(), which the run_turn roll-over check consumes via take_new_context_window_request. core/src/tools/handlers/new_context_window.rs:L44--L56; core/src/session/turn.rs:L659--L663

Input

- **Op channel + public thread API:** CodexThread::submit(op) sends into io.tx_sub; next_event() reads io.rx_event. core/src/codex_thread.rs:L258--L260, L773--L775
- **User message submission op:** Op::TurnInput { request, mode, reply } is "Submit turn input using the requested routing behavior." protocol/src/protocol.rs:L703--L710
- **User turn ingestion:** start_or_steer builds task_input from merged additional context plus pending_turn_input(...) and calls spawn_task(turn_context, task_input, RegularTask::new()). core/src/session/turn_input.rs:L428--L449
- **Person's answer the MODEL consumes:** request_user_input tool awaits session.request_user_input(...) and serializes the RequestUserInputResponse back as the tool result; delivered by Op::UserInputAnswer { id, response }. core/src/tools/handlers/request_user_input.rs:L78--L100; protocol/src/protocol.rs:L791--L797
- **Tool results as input to the next request:** in-flight tool futures are drained in order and recorded via record_annotated_conversation_items. core/src/session/turn.rs:L2565--L2592
- **Inter-agent mail / mailbox:** Op::InterAgentCommunication and mailbox updates (mailbox_updates, notify_mailbox) feed pending input; mailbox delivery can preempt a response between items. core/src/session/handlers.rs:L447--L479, L649--L656; core/src/session/turn.rs:L2913--L2932
- **Hook-contributed input:** drain_async_hook_results records results of async hooks before/after the user prompt. core/src/hook_runtime.rs:L782; core/src/session/turn.rs:L185, L591

Context

- **Base instructions come from the model catalog:** render_model_instructions reads model_info.model_messages.instructions_template; the bundled default is BASE_INSTRUCTIONS = include_str!("../prompt.md") in models-manager, overridable by config.base_instructions. prompts/src/model_instructions.rs:L8--L17; models-manager/src/model_info.rs:L16, L46--L48
- **Prompt assembly per sampling request:** build_prompt packs input (history), tools = tool_router.model_visible_specs(), parallel_tool_calls: true, base_instructions, output_schema; with incremental tools (WebSocket continuation) tools and instructions are sent empty. core/src/session/turn.rs:L1666--L1694
- **History normalization before send:** for_prompt → normalize_history: ensure every call has an output, drop orphan outputs, strip images/audio the model can't take. core/src/context_manager/history.rs:L603--L617, L968--L982
- **Tool-output truncation on record:** record_item_with_metadata applies truncate_function_output_payload(output, policy, ...) to Function/CustomToolCallOutput using the model's truncation_policy (live history only; rollout keeps full payload). core/src/context_manager/history.rs:L517--L519, L568--L577
- **World-state sections (diff-injected context):** WorldStateSection trait — typed sections (agents_md, environment, permissions, tools, model, ...) each render a diff vs. the previous snapshot; WorldStateSnapshot::merge_patch_from produces an RFC 7386 merge patch. core/src/context/world_state/mod.rs:L302--L330, L381--L425
- **Per-step world-state injection:** record_step_world_state_if_changed renders the step's world state, records only the changed fragments into history, and persists a RolloutItem::WorldState patch. core/src/session/mod.rs:L3762--L3793
- **AGENTS.md discovery:** walks from project root (marker .git by default) down to cwd, concatenating every AGENTS.md, bounded by project_doc_max_bytes; skipped for untrusted projects. core/src/agents_md.rs:L1--L18, L58--L68; refreshed per step in capture_step_context_inner. core/src/session/mod.rs:L3915--L3924
- **AGENTS.md as a world-state section:** AgentsMdState renders replacement/removal notices when the instructions change. core/src/context/world_state/agents_md.rs:L11--L60

- **Environment context:** `FileSystemContext { workspace_roots, permission_profile }` and `NetworkContext` are rendered into the model-visible environment section. `core/src/context/environment_context.rs:L10--L30, L213`
- **Developer instructions + extension contributors:** `build_initial_context_with_world_state` collects developer sections, plugin recommendations, and `context_contributors().contribute_thread_context/turn_context` fragments into developer/user slots. `core/src/session/mod.rs:L4473--L4560`
- **Skills injected on mention:** `build_skills_and_plugins` loads prompts for explicitly mentioned skills (`load_skill_prompts`) and converts each fragment into a response item recorded into history. `core/src/session/turn.rs:L1099, L1165--L1190, L1222--L1236`; recorded at `L409--L416`
- **Memory read-path context:** `MemoryContextFragment::{ReadInstructions (developer), ExtractionEvidence (user)}`, capped below 10k tokens; memory root is `$CODEX_HOME/memories`. `core/src/context/memory.rs:L1--L30`; `memories/read/src/lib.rs:L13`
- **Tool catalog for the step:** `built_tools` builds a `ToolRouter` from MCP tools, connectors and tool-suggest candidates; `capture_step_context_inner` joins MCP refresh and tool build into a `StepContext`. `core/src/session/turn.rs:L1884--L1973`; `core/src/session/mod.rs:L3959--L4030`
- **Deferred tools (tool search):** `ToolExposure::Deferred` tools are omitted from the initial list and discoverable through the `tool_search` tool. `tools/src/tool_executor.rs:L48--L62`; `core/src/tools/handlers/tool_search.rs:L68--L85`
- **Compaction trigger math:** `context_window_token_status` computes `token_limit_reached` (auto-compact limit + fallback buffer, or `effective_context_window_percent` of the window) and `turn_end_compaction_threshold_reached` (`model_post_turn_compact_threshold_percent`). `core/src/session/context_window.rs:L53--L130`
- **Pre-turn / post-turn compaction:** `run_pre_sampling_compact` runs before the user input is recorded; post-turn compaction runs when `foreground_due || candidate.is_some()`. `core/src/session/turn.rs:L192--L212, L779--L817`
- **Compaction implementation selection:** `run_auto_compact` chooses token-budget reset (`Feature::TokenBudget`), remote `ResponsesCompactionV2`, or local summarization. `core/src/session/turn.rs:L1507--L1570`; `core/src/compact_remote_v2.rs:L112--L140`
- **Local summarization compaction:** `run_compact_task_inner_impl` sends history + `SUMMARIZATION_PROMPT` (`prompts/templates/compact/prompt.md`) to the model, then `build_compacted_history` keeps initial context + up to `COMPACT_USER_MESSAGE_MAX_TOKENS = 20_000` tokens of recent user messages + the summary. `core/src/compact.rs:L62--L64, L264--L330, L702--L760`
- **Background (speculative) compaction:** `async_compaction::maybe_start` launches a parallel compaction once usage passes `async_compaction_threshold_percent` of the window, deduped by history version/model/hash. `core/src/session/async_compaction.rs:L1--L9, L62--L95`
- **Model-queryable context remaining (`get_context_remaining` tool):** reports `base_window_tokens_remaining` from `context_window_token_status`. `core/src/tools/handlers/get_context_remaining.rs:L85--L92`

Model interface

- **Client lifetimes:** `ModelClient` lives for the session; `ModelClientSession` is created per turn, caches a Responses WebSocket and the `x-codex-turn-state` sticky-routing token. `core/src/client.rs:L1--L26, L295--L303`
- **Wire format:** `ResponsesApiRequest { model, input, tools, tool_choice: "auto", parallel_tool_calls, reasoning, store: false, stream: true, include: ["reasoning.encrypted_content", ...], prompt_cache_key, text, ... }` posted to `/responses`. `core/src/client.rs:L1040--L1095`; `codex-api/src/endpoint/responses.rs:L110--L139`
- **Transport selection + fallback:** `ModelClientSession::stream` tries `stream_responses_websocket` when the provider supports it and falls back to `ResponsesHttpExecutor::stream_responses_http`; `try_switch_fallback_transport` permanently disables WebSockets for the session. `core/src/client.rs:L2363--L2435`
- **SSE event parsing + idle timeout:** `process_sse` maps `response.output_item.done`, `response.output_text.delta`, `response.completed|incomplete` to `ResponseEvents`; each poll is `timeout(idle_timeout, stream.next())` with default `DEFAULT_STREAM_IDLE_TIMEOUT_MS = 300_000`. `codex-api/src/sse/responses.rs:L345--L470, L554--L558`; `model-provider-info/src/lib.rs:L66, L513--L516`
- **Retry policy:** `handle_response_stream_error`: terminal errors (context exceeded, usage limit, invalid request…) return `None` delay; retryable ones use server `Retry-After` else exponential backoff with ±10% jitter; budget `DEFAULT_STREAM_MAX_RETRIES = 5`; unbounded connection retries (5s→60s doubling) behind `Feature::UnboundedConnectionRetries`; after exhausting the budget on WebSocket it switches to HTTPS and resets

the counter. core/src/responses_retry.rs:L23--L24, L57--L176; protocol/src/error.rs:L410--L440; codex-client/src/retry.rs:L43--L52; model-provider-info/src/lib.rs:L67, L506--L508
- **Content-filter retry injects guidance (context effect):** on ContentFilter the retry path records a ContentFilterGuidance user fragment before retrying. core/src/responses_retry.rs:L67--L82
- **Receiving the stream:** try_run_sampling_request opens client_session.stream(prompt, model_info, ...) and loops on stream.next() under preempt/cancellation. core/src/session/turn.rs:L2667--L2715
- **Token usage from the wire:** on Completed { token_usage, ... } the session records usage (record_token_usage_info) and emits a token-count event. core/src/session/turn.rs:L3069--L3118, L3295--L3301
- **Auth-expiry recovery:** PendingUnauthorizedRetry retries a request once after refreshing credentials on 401. core/src/client.rs:L1582--L1636, L1781--L1925
- **Prompt cache key:** prompt_cache_key is sent per request (override or thread-derived) so the server reuses cached prefixes. core/src/client.rs:L646--L668, L1060, L1090

Output

- **Tool call recognition:** ToolRouter::build_tool_call turns FunctionCall, CustomToolCall, client-executed ToolSearchCall, etc. into a ToolCall. core/src/tools/router.rs:L257--L335
- **Dispatch:** handle_output_item_done logs the call, persists the item, and pushes tool_runtime.handle_tool_call(call, token) into the in-flight queue; non-tool items become turn items and are emitted to the client. core/src/stream_events_utils.rs:L315--L432
- **Concurrency of tool calls from one response:** ToolCallRuntime::handle_tool_call spawns each call on tokio; parallel-safe tools take a read lock on parallel_execution: RwLock<()>, others a write lock (serialized). core/src/tools/parallel.rs:L51, L141--L237; core/src/tools/router.rs:L246--L250
- **Streaming text to the person:** OutputTextDelta is parsed and emitted as assistant text deltas; the TUI appends them via on_agent_message_delta → handle_streaming_delta. core/src/session/turn.rs:L3120--L3135; tui/src/chatwidget/streaming.rs:L206--L208
- **Diff artifact for the user:** TurnDiffTracker accumulates file changes and emits EventMsg::TurnDiff { unified_diff } after each response. core/src/session/turn.rs:L441--L443, L3307--L3317
- **Exec tool (exec_command / write_stdin):** Unified Exec manages PTY processes with output caps (DEFAULT_MAX_OUTPUT_TOKENS = 10_000, UNIFIED_EXEC_OUTPUT_MAX_BYTES = 1 MiB) and yield-time bounds. core/src/unified_exec/mod.rs:L1--L25, L68--L76; core/src/tools/handlers/unified_exec/exec_command.rs:L109; core/src/tools/handlers/unified_exec/write_stdin.rs:L39
- **Exec timeout:** DEFAULT_EXEC_COMMAND_TIMEOUT_MS = 10_000; ExecExpiration::{Timeout, DefaultTimeout, Cancellation, TimeoutOrCancellation}. core/src/exec.rs:L63, L173--L223
- **Orchestrator (approval → sandbox → run → retry):** ExecApprovalRequirement::{Skip, Forbidden, NeedsApproval} decides whether to ask; on sandbox denial it retries without a sandbox only if policy allows (Never/OnRequest do not retry). core/src/tools/orchestrator.rs:L164--L222, L439--L470
- **Sandbox technology:** get_platform_sandbox → macOS MacosSeatbelt, Linux LinuxSeccomp (bwrap + seccomp + Landlock), Windows WindowsRestrictedToken/WindowsMxc. sandboxing/src/manager.rs:L50--L63; protocol/src/sandbox.rs:L29--L35; sandboxing/src/{seatbelt.rs,bwrap.rs,landlock.rs}; linux-sandbox/src/seccomp.rs
- **Remote executor:** codex-exec-server is a JSON-RPC server for spawning/controlling subprocesses via codex-utils-pty, used for non-local environments. exec-server/README.md (top), exec-server/src/lib.rs:L1--L12
- **Patch tool safety:** assess_patch_safety auto-approves patches confined to writable roots (still run in a sandbox), rejects under Never, otherwise asks. core/src/safety.rs:L67--L125, L146--L180
- **MCP tool calls:** handle_mcp_tool_call prepares the call, applies approval policy, and invokes the server via prepared_call.call_with_preparation. core/src/mcp_tool_call.rs:L131--L145, L473--L478
- **Code mode executor (exec tool):** the exec tool runs model-written JS in a V8 host process reached over gRPC; nested tool calls are brokered back to the harness. code-mode-protocol/src/lib.rs:L54; core/src/code_mode_host.rs:L1--L4; core/src/tools/code_mode/execute_handler.rs:L176--L179
- **Sub-agent tool surface:** spawn_agent, send_input, wait_agent, resume_agent, close_agent handlers. core/src/tools/handlers/multi_agents/{spawn.rs,send_input.rs,wait.rs,resume_agent.rs,close_agent.rs}
- **Review sub-agent as a tool-free delegate:** results come back as events through forward_events. core/src/codex_delegate.rs:L200--L228

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Input/Context (record of the conversation); Control flow (resume)	Every thread is a JSONL rollout at `~/.codex/sessions/.../rollout-<ts>-<id>.jsonl` written by `RolloutRecorder`; `should_persist_response_item` filters items; `reconstruct_rollout` replays from the latest compaction checkpoint on resume; SQLite mirrors metadata; approvals persist as execpolicy amendments; memories pipeline writes `$CODEX_HOME/memories`	`rollout/src/recorder.rs:L77--L88`; `rollout/src/policy.rs:L80--L100`; `core/src/session/rollout_reconstruction.rs:L208--L250`; `core/src/thread_manager.rs:L1319--L1332`; `state/src/lib.rs:L1--L5`; `core/src/session/handlers.rs:L184--L198`; `memories/README.md` (When it runs)
Safety & security	Output (sandbox, exec policy); Control flow (approvals, Guardian)	OS sandboxes per platform; execpolicy rules `Allow/Prompt/Forbidden` plus dangerous-command matcher; patch writable-root check; approval precedence hooks→Guardian→user; untrusted projects skip AGENTS.md; sub-agent depth/thread caps; tool-output metadata cleared before sending unless internal	`sandboxing/src/manager.rs:L50--L63`; `execpolicy/src/decision.rs:L9--L16`; `core/src/exec_policy.rs:L318--L400`; `core/src/safety.rs:L67--L125`; `core/src/tools/approvals.rs:L479--L498`; `core/src/agents_md.rs:L64--L66`; `core/src/agent/registry.rs:L85--L99`; `core/src/client.rs:L1072--L1076`
Observability	across primitives (what is recorded)	OTel spans per sampling (`codex.sampling`, `handle_responses` with `gen_ai.usage.*` fields), tool-decision and tool-result events, approval counters, per-call `call_trace`, analytics events, token-count events to the client	`core/src/session/turn.rs:L2653--L2658, L2715--L2729`; `otel/src/events/session_telemetry.rs:L637--L665, L1195--L1204, L1297--L1308`; `core/src/tools/sandboxing.rs:L100--L107`; `core/src/stream_events_utils.rs:L326--L331`
Resilience	Model interface (retries, fallback, timeouts); Context (compaction); Control flow (resume/recovery)	Stream retry budget with backoff and `Retry-After`; WS→HTTP fallback; 300 s idle timeout; auth-refresh retry; auto compaction pre/mid/post turn and background; `Op::RecoverTurn/ContinueIfIdle` for recovery; delegate failure cleanup	`core/src/responses_retry.rs:L57--L176`; `core/src/client.rs:L2363--L2435`; `codex-api/src/sse/responses.rs:L554--L558`; `core/src/session/turn.rs:L654--L716`; `core/src/session/handlers.rs:L574--L590`; `core/src/codex_delegate.rs:L170--L179`
Performance	Model interface (streaming, WS prewarm, cache key); Output (parallel tools); Context (truncation, deferred tools, diff-based world state)	WebSocket connection reuse and prewarm; `prompt_cache_key`; parallel tool execution gate; tool-output truncation; deferred tools kept out of the initial tool list; world-state merge-patch injection; background compaction	`core/src/client.rs:L17--L26, L1060`; `core/src/tools/parallel.rs:L213--L217`; `core/src/context_manager/history.rs:L568--L577`; `tools/src/tool_executor.rs:L57--L62`; `core/src/context/world_state/mod.rs:L404--L425`; `core/src/session/async_compaction.rs:L62--L95`

Concern	Where it lives (primitive)	Mechanism	Evidence
Evaluation	— (test suites)	~249 integration suites under `core/tests/suite/` driven by a wiremock Responses mock (`sse`, `ev_function_call`, `mount_sse_once_match`), plus unit tests colocated as `*_tests.rs`	`core/tests/suite/` (listing); `core/tests/common/responses.rs:L27--L31`, `L753`, `L971`, `L1133`

Design decisions (one line each: the choice this harness made within a primitive)

- Input: a single `Op` channel per thread; user text during a running turn is queued (steer) rather than starting a new turn, and the model's questions come back as a typed `UserInputAnswer` op.
- Context: history is the Responses item list itself; environment/instructions are typed "world-state sections" injected as diffs, tool outputs are token-truncated in live history only, and compaction is pluggable (local summary, remote v2, or budget reset).
- Model interface: Responses API only (`WireApi::Responses`), WebSocket-first with session-wide HTTP fallback, server-advised retry timing, `store: false` with encrypted reasoning replay.
- Output: every risky action goes through one orchestrator (approval → platform sandbox → run → sandbox-denied retry); tools run concurrently under a read/write gate; a V8 "code mode" lets the model batch tool calls in JS.
- Control flow: one task per turn, inner loop until the model emits no tool call (or `end_turn=false`), with compaction roll-over, stop hooks, and sub-agents that are full `Session`s coordinated by `AgentControl` with depth/thread caps.

Hard cases

- **Guardian (auto-review of approvals):** a harness-consumed gate (control flow) whose decision is produced by a *model* in a separate `Session` (`ThreadSource::GuardianReview`). Rule: "an approval the harness consumes is control flow"; the reviewer itself is an inner harness (multi-agent rule). Placed as control flow, with the reviewer's own loop as a nested harness. `core/src/guardian/mod.rs:L1--L3`; `core/src/codex_delegate.rs:L133--L137`
- **Content-filter retry that injects guidance:** retrying is model interface, but it also records a user fragment into history (context). Split per rule "assign by function". `core/src/responses_retry.rs:L67--L82`
- **Incremental tools over WebSocket:** `build_prompt` deliberately sends empty tools/instructions when the server already holds them (`previous_response_id`). What the model is shown is unchanged, but the request contents depend on transport state — placed as model interface with a context dependency. `core/src/session/turn.rs:L1675--L1689`; `core/src/client.rs:L2137--L2160`
- **Remote compaction v2:** the *server* summarizes (`CompactionImplementation::ResponsesCompactionV2`); the harness decides when (context) but the summarizer is the model/provider. Placed as context (the fitting step) with the call as model interface. `core/src/compact_remote_v2.rs:L112--L140`
- **Code mode:** the model-written program runs in V8 and sequences only tools (output per rule), yet nested calls re-enter the harness's approval/sandbox path, so each nested call is a normal output-side tool call. `core/src/tools/code_mode/delegate.rs:L317--L360`
- **`new_context_window` / `get_context_remaining` tools:** tools whose only effect is on context (reset request) or that expose context state to the model; the call is output, the effect is context/control flow per the "effect" rule. `core/src/tools/handlers/new_context_window.rs:L44--L56`
- **World-state diffing:** context mechanism that also writes a `RolloutItem::WorldState` for persistence; the model-facing part is context, the file write is persistence. `core/src/session/mod.rs:L3762--L3793`
- **Steer vs. mailbox vs. hooks as inputs:** three different channels (user steer queue, inter-agent mailbox, async hook results) all merge into `pending_input` before the next request; all are input, drained by control flow. `core/src/session/input_queue.rs:L400--L432`
- **DOES NOT FIT (partially): plan mode streaming parser.** `PlanModeStreamState` parses the assistant's streamed text into a "proposed plan" item and can suppress/redirect deltas — it is output rendering that also changes what is recorded as the last agent message (feeds control flow's stop decision). It straddles output and control flow by design. `core/src/session/turn.rs:L1992`, `L2709`, `L2846--L2858`

Summary row

Input	Context	Model interface	Output	Control flow
Op channel; steer queue; mailbox; UserInputAnswer	Responses items + world-state diffs; truncation; 3 compaction modes	Responses API, WS→HTTP fallback, 5 retries w/ backoff	Sandboxed exec/patch/MCP; parallel gate; V8 code mode	Task per turn; loop until no tool call; approvals; sub-agent Sessions

B.3 OpenCode

Source: https://github.com/anomalyco/opencode · **Version:** commit 654b79b27e79da735d6b07d766c8d7431a71d1b7 (2026-10-15); `@opencode/core` package version 2.0.29 · **Language:** TypeScript (Bun runtime, Effect 4 library) **Path conventions:** `core/` = `packages/core/src/`, `ai/` = `packages/ai/src/`, `schema/` = `packages/schema/src/`, `codemode/` = `packages/codemode/src/`, `server/` = `packages/server/src/`, `recorder/` = `packages/http-recorder/src/`. Line ranges are `Lstart--Lend` at the pinned commit. Note: the brief's expected layout (`packages/opencode/src/session/prompt.ts`, `processor.ts`, `llm.ts`, `system.ts`) no longer exists at this commit; the equivalents are `core/session/prompt.ts` (input preparation), `core/session/runner/llm.ts` (the loop), `core/session/runner/step.ts` (one model call plus its tools), `core/session/model-request.ts` (request assembly), `core/session/compaction.ts`, `core/session/system-prompt.ts`. **What it is:** OpenCode is an open-source coding agent harness by Anomaly (anomalyco) that runs as a local server with TUI, desktop, and web clients; a session is a durable, event-sourced record in SQLite that a per-session "runner" fiber drains step by step. The model is reached through the in-house `@opencode/ai` client, which compiles a canonical `LLMRequest` into a provider protocol (Anthropic Messages, OpenAI Responses, Bedrock Converse, Gemini, ...) over HTTP/SSE or a stateful WebSocket, with a Vercel AI SDK bridge for third-party provider packages.

Control flow

- **Entry: `Session.prompt` admits input then rings the doorbell:** reconciles the inbox row, prepares the prompt, admits it, and calls `execution.wake(sessionID)` unless `resume === false`. `core/session/session.ts:L145--L178`
- **Run coordinator (one execution fiber per session):** `loop` drains, then re-drains while a `pendingWake` doorbell was rung mid-drain; `wake` coalesces scopes ("input" subsumes "steer"); `interrupt` marks `stopping`, claims recorded wakes and interrupts the owner fiber. `core/session/run-coordinator.ts:L74--L85`, `L136--L145`, `L147--L167`
- **Execution service routes drains and handles `DrainResult`:** `Complete` ends, `Moved` and `Reloaded` re-enter `drain` with a continuation step. `core/session/execution.ts:L87--L110`; `DrainResult` enum `core/session/runner/index.ts:L23--L28`
- **The outer loop (`SessionRunner.drain`):** `while (true) { next = advanceToStep(); if not Ready return; continuing = runStep(ctx, step); step++ }`. `core/session/runner/llm.ts:L191--L198`
- **Step boundary (`advanceToStep`):** at each boundary the runner checks `lifecycle.isClosed()`, pulls the next inbox item under a per-session lock, handles `compaction` and `move` controls inline, and otherwise promotes pending steers/queued input before loading context; a promoted input resets `step = 1`. `core/session/runner/llm.ts:L74--L189`
- **Steer vs queue delivery:** `Promotable` doc: "steer" promotes steers only (mid-work), "input" also admits one queued item at an idle boundary. `core/session/inbox.ts:L43--L48`; `nextPromotable` `L407--L424`; `promote` `L496--L531`; a pending compaction is pulled ahead of earlier steers `L533--L550`; `Delivery = "steer" | "queue"` `schema/session-inbox.ts:L11`
- **Inner step policy (`runStep`):** before every attempt it runs auto-compaction (`compacted.status === "completed"` → new assistant id and `continue`), then prepares the request and dispatches on the attempt `Outcome`. `core/session/runner/llm.ts:L209--L330`
- **Stop condition:** `needsContinuation = toolChoice !== "none" && record.needsContinuation` (a step with executed tool calls continues; a text-only finish hands back); `finish === "length"` → `OutputLimit`. `core/session/runner/step.ts:L281--L283`
- **Step budget:** `stepLimitReached = agent.info.steps !== undefined && step >= agent.info.steps`; on the final step the runner appends `MAX_STEPS_PROMPT` as an assistant message and sets `toolChoice: "none"` while keeping tool definitions to preserve the cached prefix. `core/session/runner/llm.ts:L226--L247`; prompt text `core/session/runner/max-steps.ts:L1--L16`; `steps` field `schema/agent.ts:L33`; tool calls on that step fail with "Tools are disabled after the maximum agent steps" `core/session/runner/step.ts:L91--L101`
- **Output-limit continuation:** after `finish === "length"` the runner reads the last 3 user/assistant rows; if all three are assistant `length` finishes it fails with `output-limit`, else publishes the synthetic `CONTINUE_AFTER_OUTPUT_LIMIT` and goes again. `core/session/runner/llm.ts:L290--L319`; constant `L38--L39`

- **Interrupted-stream continuation:** `Continue` outcome waits the retry delay, publishes `CONTINUE_AFTER_INCOMPLETE_STREAM` and starts a fresh assistant message. `core/session/runner/llm.ts:L281--L289`; constant `L35--L36`
- **Retry wait is part of the loop:** `Retry` outcome → `retry.wait` (publishes `RetryScheduled`, sleeps) then the `while (true)` re-attempts with refreshed context. `core/session/runner/llm.ts:L275--L280`, `L216--L219`; `wait` `core/session/runner/retry.ts:L97--L113`
- **Overflow → compact → go again:** `Compacted` outcome sets `recoverOverflow = false` (one overflow compaction per step) and re-attempts. `core/session/runner/llm.ts:L265--L271`, `L320--L323`
- **Approval gate consumed by the harness:** `Permission.assert` evaluates rules (`deny` → `BlockedError`, `allow` → continue, `ask` → create request and await a `Deferred`). `core/permission.ts:L231--L263`; the reply endpoint resolves it, `"always"` persists a rule, a `reject` with no message fails every pending ask in the session. `core/permission.ts:L265--L325`
- **A decline ends the step:** declined tool calls are failed with "The user declined this tool call" and the attempt is interrupted (`Effect.interrupt`) rather than returned to the model. `core/session/runner/step.ts:L207--L215`, `L274--L277`
- **Interrupt with resume:** after interrupting, if the next promotable item is a steer or a control, the coordinator is woken with scope "steer" so queued next-turn prompts stay parked. `core/session/execution.ts:L153--L170`
- **Sub-agent delegation (outer-harness side):** the `subagent` tool walks `parentID` to compute depth and refuses beyond `experimental.subagent_depth` (default 1); it creates a child session with `parentID`, prompts it, and in foreground blocks on the child's job; background returns immediately. `core/tool/plugin/subagent.ts:L117--L133`, `L185--L198`, `L205--L218`, `L229--L240`
- **Child session is a harness of its own:** the job's `run` is `sessions.resume(childSessionID)` and the result is the text of the last completed assistant message. `core/session/subagent-job.ts:L45--L63`
- **How results return:** foreground → tool result text wrapped in `<subagent sessionID=... state="completed">`; background → a synthetic user message delivered to the parent when the job settles. `core/tool/plugin/subagent.ts:L252--L266`; `core/session/subagent-completion.ts:L21--L46`
- **Routing to a cheap model keyed to the work (title):** the title agent uses `model.small(primary.providerID)` plus a minimal-reasoning variant (`none|minimal|low`), forked so it never delays the step. `core/session/context.ts:L95--L119`, `L186`; fork `core/session/runner/llm.ts:L177--L180`
- **Compaction model keyed to the work:** the `compaction` agent may carry its own model; otherwise the session model is used. `core/session/compaction.ts:L213--L219`
- **Agent profiles (bundles):** `build` (default, all-allow + question), `general`/`explore` sub-agents with deny lists and a custom system prompt, hidden `compaction`/`title`/`summary` agents. `core/plugin/agent.ts:L80--L140`; default ruleset `schema/agent.ts:L46--L51`
- **Plan mode (bundle):** a `plan` agent denies `edit` outside `~/.opencode/plan/*` (control flow), rewrites blocked-edit errors (output), and re-injects a `<system-reminder>` per request (context). `core/plugin/plan.ts:L33--L42`, `L44--L53`, `L57--L60`
- **Crash/restart resume:** at boot, sessions whose execution claim survived are resumed with a synthetic "The server restarted..." notice; a durable per-turn counter stops after `DEFAULT_MAX_ATTEMPTS = 10`. `core/session/execution/restart.ts:L77--L99`, `L193--L231`; budget `L33`

Input

- **HTTP handler → `session.prompt`:** `text`, `files`, `agents`, `skills`, `metadata`, `delivery`, `resume` are passed straight through. `server/handlers/session.ts:L307--L322`
- **Prompt preparation (`SessionPrompt.prepare`):** fires the plugin hook `session.prompt` (plugins may rewrite text/files/delivery), materializes attachments with concurrency 8, resolves `skills` to their text, and builds a `UserPayload`. `core/session/prompt.ts:L29--L91`
- **Attachments:** `data:` URLs or `file:` URIs; 20 MiB cap; `?start=&end=` line ranges for text; a directory becomes a sorted listing. `core/session/prompt.ts:L93--L133`, `L151--L201`, `L203`
- **Image normalization on input:** images are resized via `Image.Service` (resizer unavailable → passthrough). `core/session/prompt.ts:L135--L149`
- **Durable admission:** the inbox row is inserted into SQLite (`admit`, `reconcile`, `cancel`, `steer`, `queue`). `core/session/inbox.ts:L155`, `L169`, `L230--L256`, `L295`
- **Harness-originated input (synthetic):** `Session.synthetic` admits text the harness produced (restart notice, job completions) through the same inbox. `core/session/session.ts:L273--L314`
- **Answer the MODEL consumes (question tool):** the form answers are rendered as `User has answered your questions: ...` and returned as the tool result. `core/tool/plugin/question.ts:L38--L46`, `L62--L112`

- **Background shell completion event:** notifyWhenDone waits on the job and admits a synthetic message with the output. core/tool/plugin/shell.ts:L157--L189
- **Sub-agent completion event:** delivered as a synthetic message tagged <subagent ... state=...>. core/session/subagent-completion.ts:L37--L44

Context

- **Selection (SessionContext.select):** fixes session, agent, tool snapshot (narrowed by merged agent+session permissions) and instruction sources, loaded in parallel. core/session/context.ts:L121--L161; permission narrowing L131
- **Instruction ordering for cache reuse:** "Ordered from most to least shared across sessions so the baseline stays a reusable prompt-cache prefix": Code Mode catalog, MCP, references, skills, AGENTS.md discovery, builtins (date/env), per-session entries. core/session/context.ts:L147--L158
- **Load (SessionContext.load):** resolves the model and reads history after the latest replayable compaction. core/session/context.ts:L163--L179
- **System prompt assembly:** [agent.system ?? default prompt rendered with tool guidance, initial instructions]; messages via toLLMMessages. core/session/model-request.ts:L100--L120
- **Default system prompt text:** 15 lines ("You are an AI agent running in OpenCode..."), with ${OPENCODE_TOOL_GUIDANCE} filled per available tool. core/session/runner/prompt/system.txt:L1--L15; core/session/system-prompt.ts:L9--L28
- **Built-in instructions:** today's date and an <env> block (working dir, workspace root, git, platform, tmp). core/instructions/builtins.ts:L24--L53
- **AGENTS.md discovery:** global AGENTS.md plus ancestor-walk from the location to the project root, watched for changes. core/config/plugin/instruction.ts:L36--L62, L76--L86
- **Catalogs rendered into the baseline:** skills <available_skills> core/skill/instructions.ts:L16--L33; MCP <mcp_instructions> core/mcp/instructions.ts:L17--L29; Code Mode catalog core/codemode/instructions.ts:L9--L30
- **Instruction epochs:** changed instruction sources are frozen into a durable InstructionsUpdated event with rendered delta text, so later requests see "Today's date is now..." style updates as system messages. core/session/instruction-state.ts:L38--L61, L80--L87; rendered as Message.system core/session/runner/to-llm-message.ts:L291--L292
- **History read bounded by compaction:** rows from the latest completed compaction seq onward; native checkpoints only when the target model can replay them. core/session/history.ts:L21--L26, L78--L108, L118--L135
- **Projection of history into model messages:** synthetic/skill/shell messages become user role; a compaction becomes a <conversation-checkpoint> user message. core/session/runner/to-llm-message.ts:L269--L327, L330--L334
- **Tool definitions snapshot:** tools wholly denied by permission are dropped; codemode: false tools are advertised directly, the rest only inside the single execute tool; definitions sorted by name. core/tool.ts:L225--L287; JSON Schema generation core/tool/runtime.ts:L21--L27, L174--L188
- **Plugin hook that rewrites what the model sees:** session.context sees system, messages, tool descriptions/schemas and the default maxTokens; renamed tools are mapped back by object identity. core/session/model-request.ts:L236--L274
- **Media fitting:** unsupported modalities are replaced by an ERROR text; inline images are dropped from oldest once the total exceeds 25 MiB until under 15 MiB. core/session/model-request.ts:L43--L46, L132--L147, L189--L216; applied L297
- **Output token budget fitted to the window:** outputLimit = min(catalog limit, 256k), reduced to the room left after measured + estimated×1.15, floor 1,024. core/session/model-request.ts:L47--L57, L88--L98
- **Auto-compaction trigger:** due when estimateContext >= ceiling; ceiling = window - max(10 %, 16,000) or window - configured buffer; skipped right after a completed compaction or before a measured response. core/session/compaction.ts:L205--L240, L242--L251, L911--L920; defaults auto: true, keep: 15_000 L197; settings L41--L47
- **Prompt size estimate = provider-measured + locally estimated:** anchors on the last assistant message with a usage count from the same provider, estimates everything after at ~4 chars/token. core/session/compaction.ts:L880--L905, L924--L930, L950--L953
- **Summary compaction:** splits history into older (summarized) and recent (kept verbatim within keep tokens, starting at a user boundary); sends older + summary prompt; one template nudge before failing. core/session/compaction.ts:L272--L316, L708--L744; template L104--L135

- **Tool outputs in the verbatim part are cut to 1,250 chars.** core/session/compaction.ts:L100, L813--L826
- **Overflow compaction (provider said too long):** captured before any output starts, then compaction aims at 70 %/50 %/35 % of the rejected request size. core/session/runner/step.ts:L113--L120, L155--L167; SHRINK_STEPS core/session/compaction.ts:L95, L429--L448
- **Manual /compact:** an inbox control item processed at the step boundary. core/session/session.ts:L246--L264; core/session/runner/llm.ts:L115--L163
- **Native (provider-side) compaction:** for models with compaction.type === "native" the provider returns one opaque item that replaces the window; the harness only appends the newest user messages. core/session/compaction.ts:L318--L332
- **Tool result truncation before it enters history:** 2,000 lines / 50 KiB, overflow written to a file with a [showing lines 1-N of M; full output saved to ...] marker. core/tool-output.ts:L13--L16, L67--L118; applied in the step core/session/runner/step.ts:L127
- **Tool input repair (what the model's call is seen as):** stringified JSON, numeric strings, placeholder nulls are repaired against the schema before execution. core/plugin/tool-input-repair.ts:L7--L36
- **Prompt-cache key / affinity:** promptCacheKey and x-session-affinity derive from the root session (children and forks share the parent's). core/session/model-request.ts:L278--L295; core/session/affinity.ts:L6--L8
- **Searchable memory for the model:** not found (no model-facing memory store; core/environment/memory.ts is an in-memory filesystem).

Model interface

- **Streaming request:** the step calls llm.stream(request, options) and folds every LLMEvent through a publisher; it reads to the end "so the next request can reuse this response". core/session/runner/step.ts:L103--L138; client ai/route/client.ts:L602--L607, L618--L622
- **Request construction:** LLM.request({model, http.headers, promptCacheKey, system, messages, tools, toolChoice, generation, providerOptions}) with x-opencode-session-id/User-Agent headers. core/session/model-request.ts:L279--L302
- **Wire format:** per-provider protocol modules (anthropic-messages.ts, openai-responses.ts, bedrock-converse.ts, gemini.ts, ...) and framings (SSE) compile the canonical request and decode the stream. ai/protocols/ (directory), ai/route/client.ts:L423--L497
- **Route/header hooks:** session.model.request may change baseURL/headers; session.http.request/http.response wrap the raw HTTP exchange. core/session/model-request.ts:L305--L320, L337--L365
- **HTTP timeouts:** headers 300 s, inter-chunk 900 s, whole-request none by default. ai/route/transport/http.ts:L100--L146; defaults ai/schema/options.ts:L56, L62
- **Stateful WebSocket transport:** bound per session when model.transport === "websocket"; rotates after 55 min, 15 s connect, 30 min idle; after 5 consecutive stream failures the session stays on HTTP. core/session/model-request.ts:L368--L392; core/session/model-transport.ts:L22--L27, L186--L196, L308
- **Error classification:** isContextOverflowFailure and isRetryable (rate limit, provider internal, transport unless delivery rejected, incomplete stream, unknown; x-should-retry header overrides). ai/provider-error.ts:L72--L75, L81--L110
- **Retry policy:** exponential from 2 s capped at 10 s per gap, 10 retries, jittered; provider retry-after honored up to 15 min; at most 3 timeout retries; session.retry plugin hook may override the decision. core/session/runner/retry.ts:L31--L62, L64--L92
- **Retry vs continue vs recover-full:** before output started → Retry; after output started on an interrupted stream → Continue; WebSocket retry-full/rotate-and-retry-full → RecoverFull. core/session/runner/step.ts:L182--L204, L263--L271, L291--L295
- **Unknown finish reason is an error:** turned into InvalidProviderOutputError("incomplete-stream"). core/session/runner/step.ts:L171--L181
- **Model resolution:** session model must be in the available catalog, else ModelUnavailableError. core/session/runner/model.ts:L75--L91
- **Token usage and cost:** normalized input/output/reasoning/cache.read/cache.write, cost by context tier. core/session/usage.ts:L11--L19, L22--L36
- **Vercel AI SDK bridge:** AISDK.Service.model(RuntimeInfo) wraps a LanguageModelV3 as an @opencode/ai LanguageModel for third-party provider packages. core/aisdk.ts:L237--L252
- **Backup model for a request that could not be served (title only):** if the small model's attempt fails, the primary model is tried. core/session/title.ts:L129--L133

Output

- **Streaming render path:** provider events are published as durable `Text.Started/Delta/Ended`, `Reasoning.*`, `Tool.Called/Progress/Success/Failed`, `Step.Started/Streamed/Ended/Failed`; deltas batched every 100 ms. `core/session/runner/publish-llm-event.ts:L443--L470`, `L106`, `L194--L200`
- **Concurrent tool execution from one response:** each `tool-call` event forks a fiber immediately; all are awaited after the stream ends. `core/session/runner/step.ts:L121--L134`, `L151`
- **Tool executor:** `execute.before` hook → input decode/validate → `tool.execute` → `execute.after` hook → content normalization (image resize). `core/tool.ts:L103--L156`, `L263--L284`; validation `core/tool/runtime.ts:L29--L61`, `L88--L100`
- **Shell tool:** 2-minute default timeout, `AGENT=1 OPENCODE=1` env, jobs with foreground block or background; no OS sandbox found, gating is by permission after tree-sitter parsing of the command into per-command resources and touched directories. `core/tool/plugin/shell.ts:L24`, `L117--L155`, `L199--L279`; parser `core/shell/parse.ts:L7`, `L392`
- **Edit tool asks with a diff preview:** `permission.assert({action: "edit", metadata: {files: [preview]}})` before applying. `core/tool/plugin/edit.ts:L271--L283`
- **Read/external-directory gating:** `authorizeRead` asks `external_directory` for paths outside the location, then `read` per file. `core/file-access.ts:L125--L142`, `L144--L161`
- **MCP tools as output:** each discovered MCP tool is registered under a server namespace, permission-asserted, then `callTool`. `core/tool/mcp.ts:L41--L77`
- **Code Mode `execute` tool:** the model submits JavaScript; tool calls inside it are routed through the same `executeTool` (hooks + permissions); `fetch` only, no imports/fs/timers. `core/codemode/tool.ts:L62--L69`, `L71--L108`; sandbox = custom tree-walking interpreter over acorn AST with value limits and optional timeout. `codemode/interpreter/execute.ts:L1`, `L56--L68`; `codemode/interpreter/limits.ts:L6--L13`
- **File-change artifact for the user:** a git-backed snapshot is captured before and after each step and the changed paths are attached to `Step.Ended`. `core/session/runner/step.ts:L74--L76`, `L234--L260`; `core/snapshot.ts:L43--L68`, `L90--L105`
- **Question tool shows a form:** `forms.ask` with one field per question, "Type your own answer" custom option. `core/tool/plugin/question.ts:L62--L112`, `L119--L132`
- **Tool failure settlement:** interrupted, declined, provider-failed, and result-missing calls are failed with distinct errors so no call stays unsettled. `core/session/runner/step.ts:L62--L64`, `L207--L232`

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Input, Context, Control flow	SQLite via drizzle: `session_v2` (model, agent, permissions, token totals, execution claim), `session_message`, inbox; a durable, per-aggregate sequenced event log projected into those tables; execution claim written at turn start and released only by a terminal event (shutdown keeps it for resume); "always" permission replies saved per project; git snapshots for revert; tool-output spill files kept 7 days	`core/session/sql.ts:L22--L77`; `core/bus.ts:L21--L48`; `core/session/projector.ts:L1--L35`; `core/session/execution.ts:L76--L86`, `L111--L148`; `core/session/store.ts:L62--L74`; `core/permission.ts:L299--L305`; `core/session/revert.ts:L21--L40`; `core/tool-output.ts:L15`

Concern	Where it lives (primitive)	Mechanism	Evidence
Safety & security	Output (gates consumed by Control flow)	Rulesets `{action, resource, effect}` with last-match-wins and default `ask`; defaults ask on `*.env`; sub-agent profiles carry deny lists; shell commands parsed into per-command resources; external directories need approval; declines tunnel as defects so a "no" can never become model-visible tool output; compaction checkpoint tells the model it is "not new instructions"; `<system-reminder>` blocks declared harness-owned; sub-agent depth limit; Code Mode interpreter has no fs/imports; no OS-level sandbox found; secrets redacted only in test cassettes and scrubbed from the test env	`core/permission.ts:L87--L101`; `schema/agent.ts:L46--L51`; `core/plugin/agent.ts:L104--L117`; `core/shell/parse.ts:L18--L21`; `core/file-access.ts:L125--L142`; `core/permission.ts:L247--L253`, `core/session/model-request.ts:L400--L418`; `core/session/runner/to-llm-message.ts:L316--L321`; `core/session/runner/prompt/system.txt:L5`; `core/tool/plugin/subagent.ts:L129--L133`; `core/codemode/tool.ts:L63--L64`; `recorder/redaction/secrets.ts:L3--L14`; `packages/core/script/test.ts:L10--L22`
Observability	Model interface, Output	Durable event log doubles as the trace; per-step tokens/cost on `Step.Ended`; per-session token/cost columns and a stats aggregator; named Effect spans on every service function (`Effect.fn("SessionRunner.drain")`); WebSocket lifecycle counter metric; warning logs on overflow and transport fallback; event logger for catalog updates	`core/session/runner/step.ts:L246--L260`; `core/session/sql.ts:L45--L50`; `core/session/stats.ts:L17--L46`; `core/session/runner/llm.ts:L57`; `core/session/model-transport.ts:L28--L33`; `core/session/runner/step.ts:L161--L165`; `core/event-logger.ts:L7--L17`
Resilience	Model interface, Context, Control flow	Jittered exponential retry with retry-after and timeout caps; overflow-triggered compaction with shrinking targets; output-limit and interrupted-stream continuations; WebSocket→HTTP fallback after 5 failures; header/chunk timeouts; crash recovery from the execution claim with a 10-attempt budget; stale running compactions and tool calls settled on resume; pending permission asks rejected on shutdown	`core/session/runner/retry.ts:L42--L62`; `core/session/compaction.ts:L95`, `L429--L448`; `core/session/runner/llm.ts:L281--L319`; `core/session/model-transport.ts:L186--L196`; `ai/route/transport/http.ts:L100--L146`; `core/session/execution/restart.ts:L77--L99`; `core/session/runner/llm.ts:L332--L385`; `core/permission.ts:L133--L146`

Concern	Where it lives (primitive)	Mechanism	Evidence
Performance	Context, Model interface, Output	Baseline instructions ordered as a stable cache prefix; `promptCacheKey` shared across a session tree; tool definitions kept on the budget-exhausted step to keep the cached prefix; parallel context source loading; tool calls run concurrently as they stream; 100 ms delta batching; start snapshot captured while the request is in flight; Code Mode catalog and tool JSON-schema caches; tool output truncation and image byte budget	`core/session/context.ts:L147--L158`, `L142`; `core/session/model-request.ts:L295`; `core/session/runner/llm.ts:L243--L244`; `core/session/runner/step.ts:L121--L134`, `L74--L76`; `core/session/runner/publish-llm-event.ts:L106`; `core/tool.ts:L246--L254`; `core/tool/runtime.ts:L10--L19`; `core/tool-output.ts:L13--L14`; `core/session/model-request.ts:L43--L44`
Evaluation	— (all primitives)	164 test files under `packages/core/test` (e.g. `session-runner-recorded.test.ts` replays provider traffic from `@opencode/http-recorder` cassettes; `session-compaction.test.ts`, `permission.test.ts`, `session-run-coordinator.test.ts`); 52 under `packages/ai/test`; a simulated provider package; test runner scrubs provider keys from the environment. Model-graded or task-success agent evals: not found	`packages/core/test/session-runner-recorded.test.ts:L1--L30`; `packages/simulation/src/backend/simulated-provider.ts`; `packages/core/script/test.ts:L10--L22`

Design decisions (one line each: the choice this harness made within a primitive)

- Input: every input, including harness-generated notices, is a durable inbox row with a `steer` (interrupt the current step boundary) or `queue` (next turn) delivery, promoted only at step boundaries under a per-session lock.
- Context: history is event-sourced and re-projected into model messages on every call; compaction is a summary message in that history (or an opaque provider checkpoint), triggered at ~90 % of the window using provider-measured counts plus a local estimate, with the newest 15k tokens kept verbatim.
- Model interface: an in-house canonical `LLMRequest` compiled per provider protocol, streamed over HTTP/SSE or a stateful WebSocket, with retry decisions split by whether output had already started.
- Output: tool calls are executed concurrently as they stream, every tool is permission-asserted inside its own code, most tools are reachable only through a single `execute` tool that runs model-written JavaScript in a custom interpreter.
- Control flow: one fiber per session drains a durable inbox; a step continues while tool calls were made, stops on a text-only finish, and is bounded by an optional per-agent step count; sub-agents are full child sessions (depth 1 by default) whose results come back as tool text or a synthetic message.

Hard cases

- **Code Mode `execute` tool:** the model writes a program that sequences tool calls (`tools.ns["name"](input)`), which looked like control flow; rule "a program that sequences only tools is output" resolves it as output, and the interpreter cannot call the model (`core/codemode/tool.ts:L62--L69`). Its per-request catalog in the system prompt is context (`core/codemode/instructions.ts:L19--L30`).
- **`Permission.assert` lives inside each tool:** by file location it is output; by function it is an approval gate the harness consumes (the model never sees a plain decline, the step is interrupted), so it is control flow; the `"always"` rule save is persistence.
- **Question tool:** the form is output, the answers are input (the model consumes them), and a dismissal is treated like a permission decline (control flow) via the same defect tunnel (`core/tool/plugin/question.ts:L90--L97`).
- **Subagent tool:** the call is output; depth check, child creation, blocking and backgrounding are control flow; the child is a separate harness (`sessions.resume`); foreground results return as tool text, background results as a synthetic user message, which makes the same information input in one mode and output in the other.

- **Compaction service calls the model:** `SessionCompaction` decides when and what to summarize (context) but also issues `llm.stream` itself (`core/session/compaction.ts:L512`) and runs the retry policy (`L450--L459`). The brief says context "never calls the model"; resolved by assigning the trigger/split/budget to context, the summary request itself to model interface, and the `Compacted` → `re-attempt` loop to control flow. Partly DOES NOT FIT: native compaction (`L318--L332`) delegates context assembly to the provider, so the harness's context primitive holds only an opaque item it cannot inspect.
- **`MAX_STEPS_PROMPT` appended as an assistant message:** the step budget is control flow, but it is enforced by editing what the model sees (an assistant-role message plus `toolChoice: "none"`), so the mechanism straddles control flow and context (`core/session/runner/llm.ts:L240--L244`).
- **Instruction epochs:** changed AGENTS.md/date/env are frozen into durable `InstructionsUpdated` events rendered as system messages in the transcript; this is context, but it is implemented as persistence of history, and history is immutable, so stale instruction text stays in old events.
- **Plugin hooks (`session.context`, `session.model.request`, `http.request`, `tool.execute.before/after`, `permission.evaluate`, `session.retry`):** a single hook bus whose entries belong to five different primitives; decomposed by what each hook can change rather than where it is registered.
- **Durable event bus:** the same event log is persistence (projected into tables), observability (the trace), and the output channel (clients subscribe); the bus itself is out of scope as transport, its contents are assigned by what they record.
- **Title model fallback:** the "try the small model, then the primary" fallback (`core/session/title.ts:L129--L133`) is a backup model when a request could not be served (model interface), while choosing the small model in the first place is control flow.
- **WebSocket `RecoverFull`:** the transport reports it cannot replay an incremental exchange (model interface), but the decision to resend the full request is taken by the runner's outcome loop (control flow) (`core/session/runner/step.ts:L182--L188`, `core/session/runner/llm.ts:L324--L326`).
- **Synthetic messages:** "The server restarted…", "Your last response hit the output token limit…" are produced by control flow, admitted as input, and shown to the model as user-role messages; assigned as input with control-flow origin.

Summary row

Input	Context	Model interface	Output	Control flow
Durable inbox rows: user, synthetic, shell, skill; steer or queue	Event-sourced history re-projected; cached-prefix instructions; summary or native compaction	In-house LLMRequest compiled per protocol; SSE or WebSocket; split retry policy	Concurrent streamed tool fibers; permission-asserted tools; Code Mode interpreter	One fiber per session drains inbox; continue while tools called; child sessions

B.4 pi (pi-mono coding agent)

Source: https://github.com/badlogic/pi-mono · **Version:** commit 5ab7fe74c400097b386662205cd93900695b8a71 (2026-10-15) · **Language:** TypeScript (Node/Bun) **Path conventions:** `agent/` = `packages/agent/src/`; `ai/` = `packages/ai/src/`; `ca/` = `packages/coding-agent/src/`; `ex/` = `packages/coding-agent/examples/extensions/`; `ev/` = `packages/evals/`. All paths relative to the repo root. Package scope at this commit is `@earendil-works/*` (pi-agent-core, pi-ai, pi-coding-agent). **What it is:** pi is a terminal coding agent by Mario Zechner (badlogic) with a layered design: `pi-agent-core` holds a minimal agent loop, `pi-ai` holds provider adapters (Anthropic, OpenAI, Google, Bedrock, Mistral, …) behind one `StreamFunction`, and `pi-coding-agent` wraps both in an `AgentSession` with JSONL session trees, compaction, retries, built-in tools, and an extension system; interactive TUI, print, JSON, and RPC modes sit on top. The model is reached over HTTPS/SSE (or WebSocket for some providers) through provider SDKs or raw fetch, with `maxRetries: 0` so pi owns retry policy.

Control flow

- **Inner/outer loop (`runLoop`):** inner `while (hasMoreToolCalls || pendingMessages.length > 0)` issues one model call per iteration; outer `while (true)` re-enters only if follow-up messages arrived or `finishTurn` asked for one more context-only turn, else breaks and emits `agent_end`. `agent/agent-loop.ts:L163--L321`
- **Stop on error/abort:** an assistant `stopReason` of `"error"` or `"aborted"` is a hard exit: `finishTurn` is called, `turn_end`/`agent_end` emitted, loop returns. `agent/agent-loop.ts:L245--L256`

- **Go-again decision:** `hasMoreToolCalls = !executedToolBatch.terminate`; if the response had no tool calls and no steering/follow-up is queued, the loop ends. `agent/agent-loop.ts:L258--L278, L295--L318`
- **`finishTurn` decision hook:** returns `{action:"end"}` (stop now) or `{action:"continue"}` (force one more request); undefined keeps normal scheduling. `agent/agent-loop.ts:L286--L298, agent/types.ts:L146--L158`
- **Early termination from tools:** a batch ends the run only when every finalized tool result sets `terminate: true` (`shouldTerminateToolBatch`); a blocked `beforeToolCall` may set it too. `agent/agent-loop.ts:L690--L692, L745--L755, agent/types.ts:L66--L74`
- **Steering vs. follow-up queues:** `Agent.steer()` injects after the current turn's tools finish; `followUp()` waits until the agent would otherwise stop; drain modes `"one-at-a-time"` (default) or `"all"`. `agent/agent.ts:L143--L174, L247--L248, L299--L306, L496--L503`; polled in the loop at `agent/agent-loop.ts:L176, L204--L206, L295, L302--L308`
- **One run at a time:** `prompt()` throws if a run is active; `continue()` resumes from a user/toolResult tail, else drains steering/follow-up queues. `agent/agent.ts:L373--L381, L384--L411, L507--L530`
- **Abort:** `Agent.abort()` fires the run's `AbortController`; `AgentSession.abort()` also cancels retry backoff, compaction, branch summary, then waits for idle. `agent/agent.ts:L341--L343; ca/core/agent-session.ts:L2464--L2474`
- **Session post-run loop:** `_startRun` calls `agent.prompt(messages)` then loops `_handlePostAgentRun()` → `agent.continue()` while retry/overflow-recovery/queued messages/extension `agent_before_settle` ask for more. `ca/core/agent-session.ts:L1837--L1882, L1943--L1981, L1983--L2005`
- **Auto-retry budget (session level):** `_prepareRetry` increments `_retryAttempt`, stops past `maxRetries`, sleeps `retryDelayMs()` (abortable), omits the failed assistant message from projection, and returns true so the loop reissues the request. Defaults `enabled: true, maxRetries: 3, baseDelayMs: 2000`. `ca/core/agent-session.ts:L3792--L3832; ca/core/settings-defaults.ts:L18--L26`
- **Overflow recovery is one-shot:** `_checkCompaction` case 1 compacts and retries the turn once (`_overflowRecoveryAttempted` guard); case 2 (completed response) compacts without retry; case 3 threshold compacts without retry. `ca/core/agent-session.ts:L2977--L3115`
- **Virtual-model routing keyed to the work:** `prepareRequest` resolves a virtual model to a physical one per request with `reason: "user" | "continuation" | "retry"`, storing router state as a session entry; a router (extension-registered) picks the model. `ca/core/agent-session.ts:L815--L843; ca/core/model-runtime.ts:L1003--L1034; ca/core/virtual-models.ts:L1--L11, L43--L50`
- **Extension boundary hooks that can force another turn:** `turn_end` and `agent_before_settle` handlers return `continue: true` and may commit boundary drafts; the session validates `canContinue` first. `ca/core/agent-session.ts:L847--L897, L1983--L2005`
- **`tool_call` approval gate (extension):** `beforeToolCall` → `runner.emitToolCall`; first handler returning `{block:true}` wins; the `permission-gate` example asks `ctx.ui.select` and blocks when no UI. `ca/core/agent-session.ts:L659--L682; ca/core/extensions/runner.ts:L1249--L1267; ex/permission-gate.ts:L13--L33`
- **Project trust gate:** `resolveProjectTrusted` checks a persisted trust store, an extension `project_trust` handler, a `defaultProjectTrust` setting ("ask" default), then prompts; untrusted cwd means project `.pi/` extensions/skills/prompts/SYSTEM.md are not loaded. `ca/core/project-trust.ts:L47--L97; ca/core/trust-manager.ts:L30--L39, L45--L59, L67--L97`
- **Sub-agents (example extension, not core):** the `subagent` tool spawns a separate `pi --mode json -p --no-session` process per agent, in `single`, `parallel`, or `chain` modes, and returns the child's final output as the tool result (depth 1; results return as tool-result text). `ex/subagent/index.ts:L298, L342--L348, L470--L475; ex/subagent/README.md`
- **Nested tool calls from tools:** `ctx.executeTool()` runs through `runToolCall` with the session's hooks; ids are `<parent>/<n>` and never enter the transcript (sequences only tools → output by rule, but concurrency is serialized by a queue). `ca/core/nested-tool-calls.ts:L161--L200; agent/agent-loop.ts:L811--L819; ca/core/extensions/types.ts:L384--L395`

Input

- **TUI submit:** the editor's `onSubmit` trims text, handles slash commands locally, then `session.prompt(text)`; while streaming it calls `prompt(text, {streamingBehavior:"steer"})`; Alt+Enter queues `followUp`. `ca/modes/interactive/interactive-mode.ts:L3200--L3202, L3364--L3385, L4508`
- **Print/JSON mode:** initial message plus `messages[]` are sent via `session.prompt()` sequentially. `ca/modes/print-mode.ts:L131--L137`
- **RPC mode:** JSONL commands `prompt`, `steer`, `follow_up`, `abort`, `clear_queue` map onto session methods with `source: "rpc"`. `ca/modes/rpc/rpc-mode.ts:L394--L433`

- **@file arguments:** CLI @path args become text content and image attachments before the first prompt. ca/cli/file-processor.ts:L24--L25
- **AgentSession.prompt() capture path:** extension-command check → input extension handlers (transform/handled) → /skill: and prompt-template expansion → queue if streaming, else auth check and _startRun. ca/core/agent-session.ts:L2058--L2141, L2007--L2025; ca/core/extensions/runner.ts:L1525--L1564; ca/core/extensions/types.ts:L1171--L1187
- **Queue capture:** _queueSteer/_queueFollowUp build a user message (text + images) and hand it to agent.steer/followUp. ca/core/agent-session.ts:L2241--L2293
- **Prompt normalization in core:** a string prompt becomes {role:"user", content:[text, ...images]}. agent/agent.ts:L413--L430
- **Tool results as input:** each executed call becomes a toolResult message (content, details, isError, durationMs) pushed into context. agent/agent-loop.ts:L930--L944, L274--L277
- **Streamed tool output:** onUpdate partial results flow out as tool_execution_update events (bash emits snapshots of its OutputAccumulator). agent/agent-loop.ts:L779--L788, L821--L857; ca/core/tools/bash.ts:L276--L294
- **User !bash results:** executeBash runs a user command outside the model loop and records a bashExecution message that convertToLlm renders as a user message (unless !! excluded). ca/core/agent-session.ts:L3871--L3903; ca/core/messages.ts:L152--L161
- **Extension-injected messages:** before_agent_start handlers may return a custom message appended after the user prompt; pi.sendUserMessage starts a run. ca/core/agent-session.ts:L1926--L1936; ca/core/extensions/runner.ts:L1427--L1477
- **Image inputs:** prompt images are resized per the model's inputLimits before being attached. ca/core/agent-session.ts:L2027--L2040

Context

- **System prompt sections:** buildSystemPromptSections produces ordered sections preamble, tools, rules, docs, addendum, project_context, skills, cwd, plus custom sections, each wrapped in a same-named XML tag so later patches can replace one section. ca/core/system-prompt.ts:L128--L193
- **Default preamble/rules text:** "You are an expert coding assistant operating inside pi…"; rules merge per-tool guidelines, extension guidelines, and two fixed rules. ca/core/system-prompt.ts:L155--L169, L88--L125
- **Prompt diffing into the transcript:** diffSystemPromptSections yields a SystemMessage.sections patch only when changed; _preparePromptAndToolLoadout appends it before the next request. ca/core/system-prompt.ts:L217--L229; ca/core/agent-session.ts:L1743--L1755, L899--L933
- **Project instructions:** AGENTS.override.md/AGENTS.md/CLAUDE.md from ~/.pi/agent and every ancestor of cwd (worktree shadowing handled), rendered as <project_instructions path=...>. ca/core/resource-loader.ts:L184--L203, L232--L274; ca/core/system-prompt.ts:L79--L86
- **SYSTEM.md / APPEND_SYSTEM.md overrides:** project .pi/SYSTEM.md replaces the preamble; APPEND_SYSTEM.md becomes addendum. ca/core/resource-loader.ts:L1214--L1233; ca/core/agent-session.ts:L1714--L1730
- **Skills in prompt:** only name/description/location of each SKILL.md is listed under <available_skills>; the model loads the file with read. ca/core/skills.ts:L358--L388
- **Tool declarations as transcript deltas:** declareToolChanges computes toolsAdded/toolsRemoved on a system message before each request so replay yields exactly context.tools. agent/agent-loop.ts:L333--L363
- **Tool loadout/exposure:** tools have exposure direct | model-only | codemode | deferred | hidden; tool_search (BM25) activates deferred tools for the next request; hidden declarations are stripped from every request. ca/core/extensions/types.ts:L516; ca/extensions/tool-search/index.ts:L14, ca/extensions/tool-search/tool.ts:L192--L206; ca/core/agent-session.ts:L1772--L1790
- **Canonical context = session projection:** prepareRequest replaces context.messages with sessionManager.buildSessionProjection().messages, which walks the tree path, applies the newest compaction (firstKeptEntryId) and context_edit replacements. ca/core/agent-session.ts:L788--L811; ca/core/session-manager.ts:L476--L512, L543--L573
- **convertToLlm:** maps bashExecution, custom, branchSummary, compactionSummary roles to user messages with prefixes and passes system/user/assistant/toolResult through. ca/core/messages.ts:L148--L196
- **Extension context / context_with_system hooks:** run inside transformContext before every call; context sees non-system messages (clone), context_with_system owns the full list. ca/core/sdk.ts:L436--L440; ca/core/extensions/runner.ts:L1305--L1366; agent/agent-loop.ts:L388--L397
- **Forced prompt projection:** a before_agent_start systemPrompt override collapses system messages into one head for the request only; the transcript keeps structured sections. ca/core/agent-session.ts:L1792--L1807

- **Compaction trigger:** `shouldCompact` fires when `contextTokens > contextWindow - reserveTokens` (defaults `reserveTokens 16384`, `keepRecentTokens 20000`); checked before the next assistant response and after the run. `ca/core/compaction/compaction.ts:L120--L130`, `L267--L270`; `ca/core/agent-session.ts:L768--L786`, `L3079--L3113`
- **Cut point:** walks back from newest accumulating estimated tokens until `keepRecentTokens`, then picks the nearest valid cut (turn boundary; can split a turn and summarize its prefix). `ca/core/compaction/compaction.ts:L446--L480`, `L872--L905`
- **Summary generation:** a separate model call with a fixed structured prompt (`## Goal`, `## Constraints & Preferences`, `## Progress` ...), update prompt when a previous summary exists, `cacheRetention: "none"`, wrapped in `retryAssistantCall`. `ca/core/compaction/compaction.ts:L507--L520`, `L619--L639`, `L682--L693`
- **Compaction persisted as a tree entry:** `appendCompaction` stores `summary`, `firstKeptEntryId`, `tokensBefore`, usage, and the current system message. `ca/core/session-manager.ts:L1261--L1287`
- **Token estimation:** provider `usage.totalTokens` when present, else `chars / 3.5` and 4800 chars per image. `ai/utils/estimate.ts:L15--L19`, `L38--L40`
- **Tool-output trimming:** read/bash truncate to 2000 lines or 50 KB (head for read, tail for bash) with full output spilled to a temp file. `ca/core/tools/truncate.ts:L11--L12`; `ca/core/tools/bash.ts:L255`; `ca/core/tools/read.ts:L96`; `ca/core/bash-executor.ts:L56--L104`, `L130--L145`
- **Image policy in context:** `blockImages` setting strips images in `convertToLlm`; tool-result images are resized per model limits after `tool_result` hooks. `ca/core/sdk.ts:L296--L310`; `ca/core/agent-session.ts:L705--L711`
- **Branch summaries:** navigating the tree back can append a `branch_summary` entry rendered as a user message. `ca/core/session-manager.ts:L1600--L1615`; `ca/core/messages.ts:L170--L175`

Model interface

- `StreamFunction` **contract:** `(model, normalizedTranscript, options) => AssistantMessageEventStream`; errors must terminate the stream with `stopReason "error"|"aborted"`. `ai/types.ts:L379--L394`
- **Loop → stream boundary:** `streamAssistantResponse` resolves the API key via `getApiKey` (expiring tokens), calls `streamFunction`, and folds `start`/`*_delta`/`done`/`error` events into a partial `AssistantMessage` in context. `agent/agent-loop.ts:L399--L407`, `L414--L458`
- **Session stream function:** `modelRuntime.streamSimple` → `lazyStream` (async setup behind a sync stream) → `prepareRequest` (auth/headers) → provider `streamSimple`. `ca/core/sdk.ts:L420--L431`; `ca/core/model-runtime.ts:L723--L749`; `ai/api/lazy.ts:L46--L62`; `ai/models.ts:L907--L914`
- **Anthropic adapter:** builds a `@anthropic-ai/sdk` client (API key or OAuth bearer with Claude Code identity headers), calls `client.beta.messages.create(params, {maxRetries: 0, signal, timeout})`, decodes SSE by hand. `ai/api/anthropic-messages.ts:L603--L645`, `L1018--L1060`, `L475--L500`, `L534`
- **Provider-level retry:** `retryProviderRequest` mirrors SDK policy (408/409/429/5xx or `x-should-retry`), honors `retry-after(-ms)` up to `maxRetryDelayMs` (default 60 s, else fail fast so the outer policy sees it), otherwise `min(0.5·2^n, 8)s` with 25 % jitter, abortable. `ai/utils/provider-retry.ts:L25--L37`, `L53--L69`, `L107--L128`; `ai/api/anthropic-messages.ts:L658--L666`
- **Assistant-level retry classifier:** `isRetryableAssistantError` matches overloaded/429/5xx/network text but excludes quota/billing patterns; `retryAssistantCall` does bounded exponential backoff `baseDelayMs·2^(n-1)` capped at 60 s. `ai/utils/retry.ts:L7--L28`, `L30--L60`, `L121--L137`, `L196--L246`, `L257--L262`
- **Overflow detection:** regex table over provider error texts (`prompt is too long`, `request_too_large`, ...) with non-overflow exclusions (rate limit), used to divert to compaction instead of retry. `ai/utils/overflow.ts:L37--L63`, `L76--L80`; `ca/core/agent-session.ts:L3739--L3743`
- **Strict-tools fallback within the adapter:** a 400 "compiled grammar too large"/"Too many strict tools" rebuilds params without preferred strict schemas and retries once. `ai/api/anthropic-messages.ts:L667--L691`
- **Stream termination:** abort → `stopReason "aborted"`, exceptions → `"error"` with `errorMessage`; `done` carries the final message with usage and cost. `ai/api/anthropic-messages.ts:L897--L933`; `ai/utils/event-stream.ts:L26--L58`
- **Prompt caching:** `cache_control` on the last user/system block and last tool declaration; retention `short`/`long`/`none`; `sessionId` forwarded for cache-aware backends. `ai/api/anthropic-messages.ts:L1529--L1555`, `L1659`; `ai/types.ts:L239--L249`
- **Thinking mapping:** pi `ThinkingLevel` maps to Anthropic effort or `budget_tokens` (adaptive vs. budget thinking), interleaved-thinking beta header. `ai/api/anthropic-messages.ts:L944--L1012`, `L1296--L1305`, `L195`
- **Wire-level hooks:** `onPayload` (extension `before_provider_request` may replace the body), `onResponse` (`after_provider_response`), `onProviderStreamEvent`. `ai/api/anthropic-messages.ts:L653--L656`, `L693`, `L700`; `ca/core/sdk.ts:L382--L409`; `ai/types.ts:L174--L182`, `L218--L223`

- **Transport/options:** `transport: "sse"|"websocket"|...`, `timeoutMs`, `maxRetries`, `maxRetryDelayMs`, custom `fetch`, custom `headers`. `ai/types.ts:L144`, `L157--L210`, `L235--L238`
- **Credential handling:** OAuth tokens auto-refresh under a file lock with a timeout; `auth.json` written with mode `0o600` in a `0o700` dir. `ai/auth/resolve.ts:L119--L142`; `ca/core/auth-storage.ts:L37`, `L71`
- **Direct-route virtual model outside the loop:** `streamSimple` on a virtual model routes with `reason: "direct"` and withholds the caller's credentials when the provider differs. `ca/core/model-runtime.ts:L725--L743`

Output

- **Tool execution pipeline:** `prepareToolCall` (lookup, `prepareArguments`, schema validation, `beforeToolCall`) → `executePreparedToolCall` (`tool.execute(id, args, signal, onUpdate)` in try/catch, duration measured) → `finalizeExecutedToolCall` (`afterToolCall` may replace content/details/isError). `agent/agent-loop.ts:L708--L777`, `L821--L857`, `L859--L910`
- **Parallel vs. sequential:** default `"parallel"`: preflight sequentially, run allowed tools concurrently with `Promise.all`, emit results in source order; `"sequential"` if configured or any called tool has `executionMode: "sequential"`. `agent/agent-loop.ts:L508--L523`, `L586--L660`; `agent/types.ts:L308--L317`
- **Truncated-output guard:** if the response `stopReason` is `"length"`, every tool call is failed with an error result instead of executed. `agent/agent-loop.ts:L263--L270`, `L478--L503`
- **Built-in tool set:** `read, bash, powershell, edit, write, grep, find, ls` (default four: read, bash, edit, write). `ca/core/tools/index.ts:L95--L105`; `ca/core/system-prompt.ts:L64`
- **bash executor:** `spawn(shell, args, {cwd, detached, env: process.env + bin dir})`, stdout/stderr streamed, optional per-call timeout, abort kills the whole process group with `SIGKILL` (`taskkill /T` on Windows). `ca/core/tools/bash.ts:L97--L166`; `ca/utils/shell.ts:L138--L150`, `L187--L215`
- **edit tool:** exact unique `oldText`→`newText` replacements against the original file, BOM/LF normalization, fuzzy-match fallback with diff details; file mutations serialized per real path. `ca/core/tools/edit.ts:L152`, `L190--L194`; `ca/core/tools/edit-diff.ts:L28--L37`; `ca/core/tools/file-mutation-queue.ts:L32--L61`
- **read tool:** text with `offset`/`limit` and head truncation; images returned as image blocks (resized) or omitted for non-vision models. `ca/core/tools/read.ts:L96`, `L159--L177`, `L80--L83`
- **grep/find:** spawn ripgrep (`rg`, downloaded if missing). `ca/core/tools/grep.ts:L119--L121`, `L168`
- **MCP tools:** the built-in `mcp` extension registers each connected server's tools via `pi.registerTool` (hidden exposure when only reachable from codemode) and forwards calls with `client.callTool`. `ca/extensions/mcp/index.ts:L387--L460`; `ca/extensions/mcp/tools.ts:L337--L339`
- **codemode tool:** the model writes JavaScript that calls other tools; it runs in a QuickJS WASM sandbox (256 MiB heap, 2 workers max, 10k-token output cap, optional `timeout_ms`), with no Node/fs/network; nested calls use `ctx.executeTool`. `ca/extensions/codemode/tool.ts:L1--L10`, `L118--L120`; `ca/extensions/codemode/execute.ts:L50--L59`, `L254`, `L510--L522`
- **Rendering streamed fragments:** the TUI updates a streaming assistant component on each `message_update` and creates tool components as tool calls appear; JSON mode writes each event as one JSON line; print mode prints final assistant text. `ca/modes/interactive/interactive-mode.ts:L3524--L3536`; `ca/modes/print-mode.ts:L108--L112`, `L139--L158`
- **Extension UI as output:** `ctx.ui.select/confirm/input/editor` render dialogs (also used by approval gates). `ca/core/extensions/types.ts:L149--L157`, `L240`

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Context (session transcript)	Append-only JSONL under `~/.pi/agent/sessions/--<cwd>--/<ts>_<id>.jsonl`, v3 entries with `id`/`parentId` tree; file created on first user/assistant message; branches via `branch()`; model/thinking changes and usage persisted as entries; `context_edit` entries persist recovery omissions	`ca/core/session-manager.ts:L41`, `L589--L594`, `L1057--L1083`, `L1166--L1214`, `L1244`, `L1360`, `L1579--L1584`; `ca/core/agent-session.ts:L1147--L1168`, `L1241--L1257`

Concern	Where it lives (primitive)	Mechanism	Evidence
Safety & security	Control flow (gates), Output (sandbox), Model interface (secrets)	Project trust gate before loading repo-controlled extensions/skills; `tool_call` block hook (example permission gate); OS sandbox only via example extension (`@anthropic-ai/sandbox-runtime`: sandbox-exec/bubblewrap); codemode scripts in QuickJS with no fs/network; auth file 0600; bash inherits full `process.env` (no secret scrubbing found); nothing found for prompt-injection defenses beyond trust gating	`ca/core/project-trust.ts:L47--L97`; `ca/core/trust-manager.ts:L30--L39`; `ex/permission-gate.ts:L13--L33`; `ex/sandbox/index.ts:L1--L10`; `ca/extensions/codemode/tool.ts:L118`; `ca/core/auth-storage.ts:L37`; `ca/utils/shell.ts:L138--L150`
Observability	(observability)	Lifecycle events (`agent_start/turn_*/message_*/tool_execution_*`) to listeners/extensions; `usage` (input/output/cache/cost) on every assistant message and `usage` session entries; `getContextUsage`/`getSessionStats`; crash log; redacted bug-report bundle; `TelemetryContext` span interface passed through options but no `startSpan` call found in `ai/`	`agent/agent.ts:L565--L612`; `ai/types.ts:L451--L470`, `L583`; `ca/core/session-manager.ts:L1244`; `ca/core/agent-session.ts:L4267--L4290`; `ca/core/crash-log.ts:L124--L144`; `ca/core/bug-report.ts:L27`, `L51`; `packages/telemetry/src/index.ts:L1--L22`; `ai/types.ts:L159--L160`
Resilience	Model interface (retries), Context (compaction), Control flow (recovery loop)	Two retry tiers (provider HTTP retry with retry-after cap; assistant-level exponential backoff, 3 attempts); overflow → compact-and-retry once; `length` stop fails tool calls; abortable sleeps; resume from JSONL on restart; compaction itself retried	`ai/utils/provider-retry.ts:L107--L128`; `ai/utils/retry.ts:L196--L246`; `ca/core/agent-session.ts:L3040--L3077`, `L3792--L3832`; `agent/agent-loop.ts:L263--L270`; `ca/core/compaction/compaction.ts:L619--L639`
Performance	Model interface (cache), Output (parallel tools), Context (trimming)	Prompt `cache_control` + `sessionId`; `CacheWarmer` re-sends a 1-token request at 90 % of cache TTL when expected savings $\geq$ \$0.05; parallel tool execution; streaming; 50 KB/2000-line tool output caps; lazy provider module loading	`ai/api/anthropic-messages.ts:L1529--L1555`; `ca/core/cache-warmer.ts:L15--L32`, `L284--L296`; `agent/agent-loop.ts:L586--L660`; `ca/core/tools/truncate.ts:L11--L12`; `ai/api/lazy.ts:L74--L80`
Evaluation	(evaluation)	651 `*.test.ts` files (vitest) across packages (coding-agent 207, ai 180, agent 5), incl. agent-session retry/compaction/branching suites; `packages/evals` runs the real agent via `vitest-evals` harness with Docker variants and LLM-graded docs evals (`autoevals`)	`packages/coding-agent/test/` (listing); `ev/package.json:L1--L23`; `ev/evals/smoke.eval.ts:L5--L18`; `ev/src/harness.ts:L1--L50`

Design decisions (one line each: the choice this harness made within a primitive)

- Input: three capture surfaces (TUI editor, print/JSON CLI, JSONL RPC) all funnel into `AgentSession.prompt()`, with mid-run input split into "steer" (after this turn) vs. "follow-up" (after the agent would stop), one message at a time by default.
- Context: the transcript is a persisted tree; every request is a projection of the active branch (compaction entry + kept tail + context edits), the system prompt is a set of named XML sections diffed into system-message patches, and tool declarations are transcript deltas, so replaying the file reproduces the exact request.

- Model interface: one `StreamFunction` contract across ~15 provider adapters with SDK retries disabled (`maxRetries: 0`) and pi's own two-tier retry (HTTP-level with retry-after cap, assistant-level with error-text classification), overflow routed to compaction rather than retry.
- Output: tools are plain `{name, parameters (TypeBox), execute}` objects; parallel execution by default with per-file mutation serialization; no sandbox in core (OS sandboxing and permission prompts are extensions); a QuickJS-sandboxed `codemode` tool lets the model script tool calls.
- Control flow: a two-level loop in `pi-agent-core` (tool calls/steering inner, follow-ups outer) plus a session-level outer loop for retries/overflow recovery/extension continuations; sub-agents are not in core but an example spawns child `pi` processes; per-request model routing via virtual models.

Hard cases

- **`before_provider_request` payload hook:** lives in the adapter (`onPayload`) at the wire boundary, but an extension can rewrite the request body, i.e. decide what the model is shown. By the function rule it is Context when it changes content; the transport callback itself stays Model interface. `ai/api/anthropic-messages.ts:L653--L656`; `ca/core/sdk.ts:L382--L386`
- **Virtual-model routing:** `prepareRequest` chooses the physical model per request by reason (user/continuation/retry) — keyed to the work, so Control flow — even though it is implemented inside the model-runtime layer; the `reason: "retry"` branch after a failed request overlaps Model interface's "backup model" (resolved: the router decides based on work state, so Control flow). `ca/core/agent-session.ts:L815--L843`; `ca/core/model-runtime.ts:L1003--L1034`
- **Strict-tools 400 fallback:** an in-adapter request rebuild on a specific 400 (drops strict schemas). It alters the request contents, but the trigger is "request could not be served" — assigned Model interface by the unavailability rule. `ai/api/anthropic-messages.ts:L667--L691`
- **Compaction summary call:** a second model call issued by the Context primitive (summary generation). Rule: Context never calls the model; here it does, through the same `StreamFunction`. Resolved as Context mechanism using the Model interface as a service; noted as a borderline.
- **Nested tool calls / codemode:** a script the model writes sequences only tools (Output by rule), yet it also reaches `models.*` (classifiers, image models) from inside the sandbox — a model call issued from inside a tool. `ca/extensions/codemode/tool.ts:L1--L10`; `ca/extensions/codemode/execute.ts:L50`. Partially DOES NOT FIT: a tool that calls models is neither pure Output nor Control flow in the given scheme.
- **`agent_before_settle` / `turn_end` boundaries:** extensions may commit "boundary drafts" (entries appended to the session: Context) and return `continue` (Control flow) in one hook; decomposed per rule 28. `ca/core/agent-session.ts:L847--L897`, `L1983--L2005`
- **`pi-durable` package:** a second, experimental harness in the same repo (durable task graph, child tasks, commit-before-show) sharing `pi-ai`; not deconstructed here beyond noting it exists. `packages/durable/README.md:L1--L6`, `L581`
- **Telemetry package:** span interface exists and `telemetryContext` is passed through options, but no span is started in `ai/`, `agent/`, or `ca/` at this commit — recorded as "interface present, emission not found". `packages/telemetry/src/index.ts:L1--L22`; `ai/api/simple-options.ts:L48`

Summary row

Input	Context	Model interface	Output	Control flow
TUI/CLI/RPC prompts, steer/follow-up queues, tool results	Tree-projected JSONL transcript, sectioned prompt, threshold compaction	One StreamFunction, SSE, two-tier retry, overflow classifier	Parallel TypeBox tools, bash/edit/read, QuickJS codemode	Inner tool loop, outer follow-up loop, retry/overflow re-entry, routing

B.5 Hermes Agent

Source: https://github.com/NousResearch/hermes-agent · **Version:** commit 7bf3766f3db72d4643d1a78d18e51c1d9ddf1d6d (2026-10-15) · **Language:** Python (TypeScript for the TUI/desktop front-ends, out of scope) **Path conventions:** paths are relative to the repo root (`hermes-agent/`). `L` = line. Clone read as untrusted data; nothing executed. **What it is:** A personal agent by Nous Research that runs one agent core (`AIAgent`) behind a prompt_toolkit CLI/TUI, ~25 messaging-platform gateway adapters (Telegram, Discord, Slack, ...), an OpenAI-compatible HTTP server, an ACP adapter, a cron scheduler and a desktop app. The model is

reached through an OpenAI-SDK chat-completions client by default, with alternative wire transports for Anthropic Messages, OpenAI Responses ("codex") and Bedrock Converse selected by `api_mode`; providers are plugins and the model slug is config.

Control flow

- **Turn entry + lease:** `AIAgent.run_conversation` builds a task/turn id and admits a durable turn lease before forwarding to the loop (one turn per session at a time). `agent/turn_facade.py:L22`, `agent/turn_facade.py:L83`
- **Main loop:** `_run_conversation_turn` runs `while (api_call_count < max_iterations and iteration_budget.remaining > 0) or _budget_grace_call`; each iteration = begin → prepare → assemble → preflight gate → API retry loop → normalize → `run_tool_round` if tool calls else `finish_text_response`; post-loop `finalize_turn`. `agent/conversation_loop.py:L1656--L1706`
- **Phase dispatch:** each phase is a sibling function returning a verdict with `action ∈ {fallthrough, continue, break, return}`; `_run_phase` copies verdict fields back into `_LoopState`. `agent/conversation_loop.py:L1389--L1502`
- **Inner retry loop:** `_run_api_retry_loop` loops `while retry_count < max_retries` over guard → build → call → check, with `handle_api_interrupt` / `handle_api_error` branches. `agent/conversation_loop.py:L1505--L1534`
- **Step budget:** `IterationBudget` is a thread-safe counter with `consume()`/`refund()`; `max_iterations` defaults to `sys.maxsize` (unlimited, shared with subagents); a tool round whose only tool was `execute_code` refunds its iteration; a reasoning-only stall that triggers a model fallback sets `_budget_grace_call` for one extra call. `agent/iteration_budget.py:L25--L56`, `run_agent.py:L241`, `agent/turn_tool_round.py:L199--L200`, `agent/turn_truncation.py:L630--L635`
- **Stop gates (go again vs. hand back):** on a text answer, `apply_stop_gates` runs verify-on-stop → `pre_verify` plugin hook → kanban stop guard; a nudge appends a user-role row and continues the loop, holding the answer as a budget-exhaustion fallback. `agent/turn_stop_gates.py:L105--L140`, `agent/turn_stop_gates.py:L35--L50`
- **Tool-call guardrail halt:** a `ToolCallGuardrailController` decision can end the turn (`guardrail_halt`) after a tool round; identical-call stall threshold is 3. `agent/turn_tool_round.py:L179--L193`, `agent/tool_guardrails.py:L30`, `agent/tool_guardrails.py:L307`
- **Approval gate (harness consumes the answer):** `check_all_command_guards` runs floor blocks → yolo/`off` bypass (process `--yolo`, session `/yolo`, `approvals.mode`) → permanent allowlist → unattended-context policy → `detect_dangerous_command` → `_human_decision`; answers are `once/session/always/deny/timeout`; in gateway ask mode the tool returns `status="pending_approval"` instead of blocking. `tools/approval.py:L1151--L1200`, `tools/approval.py:L506--L510`, `tools/approval.py:L796--L802`, `tools/approval_prompt.py:L37`, `tools/terminal_tool.py:L1019--L1028`
- **Interrupt / redirect crossing a response:** if a redirect arrived while the request was in flight the response is discarded and a restart is armed; `_apply_active_turn_redirect` then appends a checkpoint + correction row so role alternation holds. `agent/turn_api_call.py:L148--L167`, `agent/conversation_loop.py:L322--L340`
- **Gateway steer:** a message arriving while a turn runs is injected via `agent.steer()` or queued; after a tool batch, pending steer is folded onto tool results once the per-turn budget is enforced. `gateway/run_inbound.py:L649--L664`, `agent/tool_executor.py:L1209--L1220`
- **Delegation (sub-agents):** `delegate_task` refuses when `_delegate_depth >= delegation.max_spawn_depth` (default 1 = flat); children are full `AIAgent` instances built with `child_depth = parent + 1` and role orchestrator/leaf derived from depth. `tools/delegate_tool.py:L520--L527`, `tools/delegate_tool_config.py:L151--L159`, `tools/delegate_tool.py:L199--L234`
- **Child run, parallelism and result return:** `_run_single_child` runs a pre-built child on a worker thread, heartbeats the parent, and returns `{status ∈ completed|interrupted|failed, exit_reason}`; a batch runs on `DaemonThreadPoolExecutor(max_workers=batch.max_children)` polled with short waits; `background=True` returns a dispatch handle. `tools/delegate_tool.py:L342--L406`, `tools/delegate_tool_dispatch.py:L118--L145`, `tools/delegate_tool_dispatch.py:L470--L478`
- **Work-keyed model routing (auxiliary):** titling, compression summaries, vision etc. resolve via `_resolve_auto_route` (main model → per-task fallback chain → discovery chain); titles come from one small-model call off the critical path. `agent/auxiliary_client.py:L4659--L4684`, `agent/title_generator.py:L1--L5`
- **Mixture-of-Agents turn:** `/moa` gathers reference-model context before each iteration while the normal loop keeps tool calling. `agent/moa_loop.py:L1--L5`
- **Cron turns:** the scheduler runs `agent.run_conversation` on a worker thread under an inactivity watchdog (default 600 s) on a fresh `AIAgent(platform="cron")`. `cron/scheduler.py:L1961--L1963`, `cron/scheduler.py:L2496--L2525`

- **Codex app-server handoff:** when `api_mode == "codex_app_server"` the whole turn is handed to an external codex subprocess; on failure a fallback is activated and the generic loop retries the same user turn. `agent/conversation_loop.py:L1650--L1651`, `agent/conversation_loop.py:L1537--L1552`

Input

- **CLI REPL:** a worker thread drains `_pending_input` (queue) and dispatches each input; `_looks_like_slash_command` routes to `process_command`, else `self.chat(...)`; `/skill-name` is rewritten into a user message. `hermes_cli/cli_tui_runtime_mixin.py:L31--L47`, `hermes_cli/cli_tui_runtime_mixin.py:L139`, `cli.py:L710`, `cli.py:L1300`
- **CLI chat turn:** `chat()` runs the agent on a daemon thread; input typed meanwhile goes to `_interrupt_queue` and is re-queued as the next turn; the call is `run_conversation(user_message, conversation_history[:-1], stream_callback, task_id, persist_user_message)`. `hermes_cli/cli_chat_turn_mixin.py:L49--L60`, `hermes_cli/cli_chat_turn_mixin.py:L115--L118`, `hermes_cli/cli_chat_turn_mixin.py:L326--L330`
- **Gateway event shape:** every adapter normalizes to `MessageEvent(text, message_type, user_id, ...)`; adapters subclass `BasePlatformAdapter`; in-tree adapters (signal, webhook, bluebubbles, weixin, yuanbao, whatsapp_cloud, api_server) plus plugin adapters (telegram, discord, slack, matrix, teams, email, irc, ...). `gateway/platforms/event.py:L45--L51`, `gateway/platforms/base.py:L1876`, `gateway/platforms/` (listing), `plugins/platforms/` (listing)
- **Gateway inbound pipeline:** `_handle_message` = admit → pending-reply intercepts → authority admission → running-session handling (steer/interrupt/preempt) → idle commands → `_handle_message_with_agent`. `gateway/run_inbound.py:L1196--L1300`
- **Authorization and bot-loop budget at admission:** unauthorized users get a pairing code (DM) or are ignored before any session state is touched; bot-authored messages are capped by a sliding window per conversation. `gateway/run_inbound.py:L201--L225`, `gateway/bot_loop_guard.py:L1--L5`
- **Gateway → agent call:** the turn runner calls `agent.run_conversation(api_message, **kwargs)` with `persist_user_message`, display kind and the raw platform message id. `gateway/run_turn_runner.py:L934--L936`
- **HTTP and webhook input:** OpenAI-compatible aiohttp server (`/v1/chat/completions`, `/v1/responses`, `/v1/runs`, ...); webhook payloads are treated as untrusted and get no file/system execution toolset. `gateway/platforms/api_server.py:L1--L5`, `toolsets.py:L41`
- **ACP input:** the ACP agent calls `agent.run_conversation(user_message=..., conversation_history=state.history)`. `acp_adapter/server.py:L816--L819`
- **Model asks the user (clarify):** `clarify` is an inline agent tool whose UI is a platform callback; the gateway intercepts the reply and its result returns to the model. `tools/clarify_tool.py:L1--L6`, `tools/clarify_tool.py:L111`, `gateway/run_inbound.py:L339`
- **Tool results captured:** every executed tool's result is committed as a `role: tool` row (`_commit_tool_result`); invalid names get an error tool row so each call has a matching result. `agent/tool_executor.py:L1066`, `agent/turn_tool_round.py:L116--L121`
- **Multimodal:** native image parts attached to the user turn stay visible to `vision_analyze` for the turn. `agent/conversation_loop.py:L1749`

Context

- **User message staging:** `messages = list(conversation_history)` + staged user dict appended; `current_turn_user_idx` recorded. `agent/turn_context.py:L1104--L1115`
- **System prompt as three cache tiers:** `stable` (SOUL.md from HERMES_HOME or default identity, guidance, pinned skills, coding brief) → `context` (caller `system_message`, project context files, workspace) → `volatile` (skills index, memory, plugin sections, profile line, timestamp, runtime environment). Never re-rendered mid-session. `agent/system_prompt.py:L730--L793`, `agent/system_prompt.py:L796--L805`, `agent/system_prompt.py:L544--L550`, `agent/prompt_builder.py:L1652--L1700`
- **Project context files:** `.hermes.md` → `AGENTS.md` chain → `CLAUDE.md` → `.cursorrules`, loaded from cwd at startup only; cap 20 000 chars floor, dynamic 6 % of the window up to 500 000, overridable by `context_file_max_chars`. `agent/prompt_builder.py:L1783--L1788`, `agent/system_prompt.py:L709--L722`, `agent/prompt_builder.py:L1156--L1171`
- **Memory files:** `MEMORY.md` (2 200 chars) and `USER.md` (1 375 chars) are rendered into the volatile tier; the `memory` tool edits them. `agent/system_prompt.py:L516--L541`, `tools/memory_tool_store.py:L186`, `tools/memory_tool_store.py:L618`

- **External memory providers:** one plugin provider at a time; `build_system_prompt()` block plus per-turn `prefetch_all(query)` text injected into the request. `agent/memory_manager.py:L1--L4`, `agent/memory_manager.py:L501--L511`, `agent/turn_context.py:L903--L931`
- **Skills index + progressive disclosure:** names/descriptions in the prompt; `skill_view` loads a SKILL.md on demand as a tool result. `agent/system_prompt.py:L301--L314`, `tools/skills_tool.py:L2--L5`
- **Byte-stable prompt restored from DB:** on resume the stored `system_prompt` row is reused if it matches the runtime; rebuilt only after compression (`invalidate_system_prompt`). `agent/conversation_loop.py:L749--L772`, `agent/system_prompt.py:L808--L826`, `hermes_state_common.py:L377--L380`
- **Tool definitions:** `get_tool_definitions(enabled/disabled toolsets)` at init; `_HERMES_CORE_TOOLS` is the always-present core. `agent/agent_init.py:L1118`, `model_tools.py:L215`, `toolsets.py:L11--L39`
- **Tool Search deferral:** MCP/plugin and selected core tools are replaced in the model-visible array by `tool_search / tool_describe / tool_call` bridge tools, catalog rebuilt per assembly. `tools/tool_search.py:L1--L7`
- **Request assembly order:** `build_api_messages` → MoA context → canonicalization; "ORDER IS LOAD-BEARING" for cache breakpoints; system row prepended. `agent/turn_request_assembly.py:L106--L130`, `agent/turn_context.py:L1344`
- **Compaction trigger:** `ContextCompressor(threshold_percent=0.50, protect_first_n=3, protect_last_n=20)`; `should_compress_info` fires when `tokens >= threshold_tokens` unless in cooldown or the ineffective breaker; per-model threshold overrides. `agent/context_compressor.py:L2811--L2832`, `agent/context_compressor.py:L3006--L3015`, `agent/context_compressor.py:L2659--L2671`
- **Compaction algorithm:** prune old tool-result bodies (no LLM) → pick boundaries on the pruned copy → auxiliary-model summary → clean orphaned tool pairs. `agent/context_compressor.py:L5528--L5575`, `agent/context_compressor.py:L3285--L3300`
- **Where compaction runs:** turn-start compaction; a pre-API preflight gate comparing the assembled request with the threshold (insufficient progress blocks further passes); 413 / context-length provider errors compress and restart. `agent/turn_context_compaction.py:L129`, `agent/turn_preflight_gate.py:L20--L120`, `agent/turn_overflow.py:L1--L6`, `agent/turn_overflow.py:L463`
- **Gateway session hygiene:** a second compaction layer at 0.85 of the window between turns. `gateway/run_turn_hygiene.py:L94--L102`
- **Tool-output truncation:** 40 % head / 60 % tail with one marker; limits 50 000 bytes, 2 000 lines, 2 000 chars/line; `read_file` pages by char budget and reports `next_offset`. `tools/tool_output_truncate.py:L1--L12`, `tools/tool_output_limits.py:L13--L15`, `tools/file_tools.py:L96--L113`
- **Spill-to-file instead of truncating:** results over the per-tool threshold are written to `$HERMES_HOME/cache/spillover/{id}.txt` and replaced by preview + path; `enforce_turn_budget` caps the batch. `tools/tool_result_storage.py:L1--L6`, `tools/tool_result_storage.py:L293--L300`, `tools/tool_result_storage.py:L359`
- **Subdirectory hints:** AGENTS.md/CLAUDE.md found while navigating are appended to the tool result, never to the system prompt. `agent/subdirectory_hints.py:L1--L5`
- **Untrusted-result wrapping:** web/browser/MCP results ≥ 32 chars are wrapped in `<untrusted_tool_result>` with delimiter neutralization. `agent/tool_dispatch_helpers.py:L484--L495`, `agent/tool_dispatch_helpers.py:L572--L595`
- **History source on resume:** CLI loads `get_messages_as_conversation(session_id, repair_alternation=True)`; gateway loads `load_transcript` then hygiene. `hermes_cli/cli_agent_setup_mixin.py:L593--L596`, `hermes_state_messages.py:L1537--L1545`, `gateway/run_turn_prepare.py:L693--L700`
- **Pluggable context engine:** `context.engine` selects a plugin that owns `should_compress/compress` and may expose tools. `agent/context_engine.py:L1--L7`

Model interface

- **Transport registry:** `anthropic`, `codex`, `chat_completions`, `bedrock` transports behind `ProviderTransport` (convert_messages/convert_tools/build_kwargs/normalize_response/validate_response). `agent/transports/__init__.py:L18--L31`, `agent/transports/base.py:L12--L51`
- **Client construction:** `_build_client` picks the Anthropic SDK, the MoA facade, boto3 Bedrock, or the OpenAI SDK client (shared httpx) by `api_mode`; GPT-5.x on a direct OpenAI URL auto-upgrades `chat_completions` → `codex_responses`. `agent/agent_init.py:L1029--L1042`, `agent/agent_init.py:L990--L1026`, `agent/agent_init.py:L482--L499`
- **Request kwargs:** `_build_api_kwargs_for_mode` branches anthropic / bedrock / codex / chat-completions builders. `agent/chat_completion_helpers.py:L1555--L1572`

- **Per-attempt request build:** re-apply reasoning echo for the provider, re-render prompt-cache decoration, strip images for rejecting models, LLM request middleware (trace kept), `pre_api_request` hook, optional `HERMES_DUMP_REQUESTS` dump. `agent/turn_api_request.py:L93--L205`, `agent/turn_api_request.py:L152--L153`
- **Prompt-cache decoration:** `build_prompt_cache_plan` places Anthropic `cache_control` markers; OpenAI-style history is converted to Anthropic content blocks. `agent/prompt_caching.py:L298--L308`, `agent/anthropic_message_convert.py:L1--L4`
- **Call issue:** `perform_api_call` chooses streaming (`_should_stream`: preferred even with no consumer, off for ACP/external-process providers) and runs through `run_llm_execution_middleware`. `agent/turn_api_call.py:L67--L167`, `agent/turn_api_call.py:L46--L64`
- **Streaming receive:** `_StreamingCall` issues `chat.completions.create(**stream_kwargs)` with `stream_options.include_usage`; the Anthropic path uses `messages.stream`; a cross-turn stale-stream breaker runs first. `agent/chat_completion_helpers.py:L3993--L4006`, `agent/chat_completion_helpers.py:L2734`, `agent/chat_completion_helpers.py:L2957--L2966`, `agent/chat_completion_helpers.py:L3412`
- **Non-stream call on a worker thread:** per-request client so interrupts close only that connection; a stale-call detector kills and raises. `agent/chat_completion_helpers.py:L1292--L1305`
- **Retry policy:** `api_max_retries` default 3; wait = provider `Retry-After` (capped) else `jittered_backoff(retry, base 2.0, max 60)` = min(base·2^(n-1), max) + jitter; adaptive policy for 429. `agent/agent_init.py:L1441--L1446`, `agent/turn_recovery.py:L1401--L1430`, `agent/retry_utils.py:L121--L130`, `agent/turn_api_error.py:L406--L417`
- **Error classification:** `classify_api_error` → structured `ClassifiedError` (retryable / should_compress / rotate credential / fallback); plugins may override via `transform_api_error_classification`. `agent/error_classifier.py:L974--L980`, `hermes_cli/plugins.py:L126--L130`
- **Backup model when unservable:** `try_activate_fallback` walks `_fallback_chain`, swapping client/model/provider in place, on classified failover or after retries exhaust; a persistent credential pool gives same-provider failover. `agent/chat_completion_helpers.py:L2086--L2121`, `agent/turn_api_error.py:L341`, `agent/turn_api_error.py:L380`, `agent/credential_pool.py:L1`
- **Post-exhaustion auto-recovery:** when retries and the chain are spent on a transient outage, the turn parks with a countdown and re-enters the retry loop (`auto_recovery_cycles` default 5). `agent/turn_recovery_autorecover.py:L1--L7`
- **Response validation + normalization:** `validate_response_shape` via the transport; `normalize_model_response` yields an assistant message with string content. `agent/turn_recovery.py:L1524--L1530`, `agent/turn_response_intake.py:L120--L128`
- **Degenerate-response ladders:** empty/thinking-only → partial-stream recovery → nudge → prefill continuation ×2 → budgeted retries → fallback provider; `finish_reason=length` → continuation nudges (up to 4), truncated tool-call retries with max_tokens boosts, repetition abort. `agent/turn_empty_response.py:L1--L5`, `agent/turn_truncation.py:L1--L6`, `agent/repetition_guard.py:L141`
- **Usage receipt:** `record_response_usage` folds `response.usage` into the compressor, session counters and state.db. `agent/turn_usage.py:L73--L79`

Output

- **Tool set:** core tools (terminal, process_manage, read/write/patch/search files, web, vision, image, skills, browser_, *todo, memory, session_search, clarify, execute_code, delegate_task, cronjob, kanban_*, computer_use). `toolsets.py:L11--L39`
- **Dispatch precedence:** inline agent-level tools (`INLINE_TOOL_EXECUTORS` table) → `delegate_task` → context-engine tools → memory-provider tools → registry via `handle_function_call`. `agent/tool_executor.py:L1669--L1733`, `agent/inline_tool_executors.py:L253--L313`
- **Batch planning:** >1 calls are split into parallel/sequential segments; the parallel-safe set is read-only tools plus path-non-overlapping file ops. `run_agent.py:L1299--L1325`, `agent/tool_dispatch_helpers.py:L212--L257`, `agent/tool_dispatch_helpers.py:L33--L44`
- **Concurrent execution:** `_ConcurrentBatch` runs on `DaemonThreadPoolExecutor(max_workers)` with a batch deadline; results appended in call order. `agent/tool_executor.py:L1573--L1620`, `agent/tool_executor.py:L1500--L1501`
- **Registry call path:** `handle_function_call` → aliases → bridge unwrap → request middleware → `_pre_dispatch_guards` (`pre_tool_call` hook, fail-closed on timeout) → `registry.dispatch` → `post_tool_call` → `transform_tool_result`. `model_tools.py:L873--L967`, `model_tools.py:L823--L846`, `hermes_cli/plugins_dispatch.py:L51`

- **Terminal tool:** plan → acquire env → bounded pre-exec guard → approval guards → foreground or background spawn; description tells the model output is auto-truncated to a file. `tools/terminal_tool.py:L1360--L1475`, `tools/terminal_tool.py:L160--L165`
- **Execution backends (sandboxes):** local, docker, singularity/apptainer, modal, daytona, vercel_sandbox, ssh, plus plugin envs; built by `_ENV_BUILDERS`. `tools/terminal_tool_backends.py:L54`, `tools/terminal_tool_backends.py:L239--L241`
- **Programmatic tool calling:** `execute_code` runs a model-written Python script in a persistent per-conversation kernel that calls Hermes tools over RPC; only stdout returns. `tools/code_execution_tool.py:L1--L10`, `tools/code_kernel.py:L1--L5`
- **Browser:** agent-browser CLI over local headless Chromium, cloud backends, a user CDP endpoint or Camofox; accessibility-tree snapshots with `@eN` refs. `tools/browser_tool.py:L1--L8`
- **Persist-before-execute:** the assistant tool-call row is flushed to SQLite before any tool runs; a failed append ends the turn. `agent/turn_tool_round.py:L131--L153`
- **Rendering and delivery:** single-writer stream ownership with delta/reasoning fan-out; open stream boxes flushed before tools; gateway `delivery.py` routes responses to targets and `response_filters.py` decides whether a turn is delivered to the chat. `agent/stream_delivery.py:L1--L3`, `agent/turn_tool_round.py:L160--L164`, `gateway/delivery.py:L1--L2`, `gateway/response_filters.py:L1--L4`
- **Sub-agent spawn tool:** `delegate_task` (output) whose effect is the control-flow delegation above. `tools/delegate_tool.py:L488`

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Output (persist-before-execute), Context (prompt/history restore), Input (session resume)	SQLite `state.db` in WAL mode: `sessions`, `messages` (role/content/tool_calls/reasoning/...), `system_prompts`, `session_model_usage`, FTS5 search; `_flush_messages_to_session_db` dedups by marker; memory in `MEMORY.md/USER.md`; spillover files; trajectories	`hermes_state.py:L177`, `hermes_state.py:L460--L466`, `hermes_state_common.py:L451--L470`, `agent/session_persistence.py:L467--L511`, `agent/turn_finalizer.py:L608`, `agent/turn_finalizer.py:L635`
Safety & security	Output (sandbox, approvals, path denies), Context (injection scans, untrusted wrapping), Control flow (gate decision)	OS is the only boundary; hardline + dangerous command regexes with human gate; write-denied credential paths (`.ssh`, `.env`, ...); SSRF-safe URL policy; secret redaction of logs/tool output; threat-pattern scan of context files, skills and tool results; `UnscopedSecretError` secret scoping	`SECURITY.md:L58--L65`, `tools/approval_detection.py:L107`, `tools/approval_detection.py:L228`, `agent/file_safety.py:L176--L196`, `agent/file_safety.py:L210`, `tools/url_safety.py:L1--L9`, `agent/redact.py:L1--L3`, `agent/prompt_builder.py:L83--L110`, `tools/skills_guard.py:L240--L253`, `agent/tool_dispatch_helpers.py:L544--L562`
Observability	across (recorded at Model interface and Output)	per-call usage folded into state.db; `pre/post_api_request`, `pre/post_tool_call`, `pre/post_auxiliary_call` plugin hooks; gateway monitoring events exported over OTLP (opt-in); `HERMES_DUMP_REQUESTS`; middleware traces on requests	`agent/turn_usage.py:L73--L79`, `hermes_state_common.py:L484`, `hermes_cli/plugins.py:L106--L135`, `agent/monitoring/events.py:L16--L66`, `agent/monitoring/otlp_exporter.py:L1--L5`, `agent/turn_api_request.py:L152--L153`

Concern	Where it lives (primitive)	Mechanism	Evidence
Resilience	Model interface (retries, fallback, auto-recovery), Context (compaction on overflow), Output (bounded guards)	3 retries with Retry-After/jittered backoff; fallback chain and credential pool; post-exhaustion ladder; 413/context-length → compress+restart; stale-stream breaker; turn liveness watchdog; cron inactivity watchdog; resume after restart from persisted tool-call rows	`agent/turn_recovery.py:L1401--L1430`, `agent/chat_completion_helpers.py:L2086--L2121`, `agent/turn_recovery_autorecover.py:L1--L7`, `agent/turn_overflow.py:L1--L6`, `agent/chat_completion_helpers.py:L4005`, `agent/turn_liveness.py:L90`, `cron/scheduler.py:L1961--L1963`, `agent/turn_tool_round.py:L131--L153`
Performance	Context (cache tiers, truncation, spill), Output (parallel tools), Model interface (streaming, cache_control)	system prompt byte-stable in stable→context→volatile tiers; compression is the only sanctioned cache break; head/tail truncation and spill files; parallel-safe tool segments; streaming by default; Anthropic cache markers; tool-definition cache	`agent/system_prompt.py:L730--L793`, `agent/system_prompt.py:L808--L826`, `tools/tool_output_truncate.py:L1--L12`, `agent/tool_dispatch_helpers.py:L212--L257`, `agent/turn_api_call.py:L46--L64`, `agent/prompt_caching.py:L298--L308`, `model_tools.py:L215`
Evaluation	across	6 392 pytest files run per-file-isolated by `scripts/run_tests.sh`; markers for `integration`/`live` provider canaries; `evals/` harnesses (compaction recall eval, provider_fallback, tool_search, token_accounting, ...); `batch_runner.py` runs the agent over JSONL datasets; `mini_swe_runner.py` runs SWE tasks in the execution environments	`scripts/run_tests.sh:L1--L15`, `pyproject.toml:L691--L700`, `evals/compaction/README.md:L1--L12`, `batch_runner.py:L1--L6`, `mini_swe_runner.py:L1--L6`, `tests/evals/` (listing)

Design decisions (one line each: the choice this harness made within a primitive)

- Input: one normalized `MessageEvent`/`run_conversation(user_message, conversation_history, task_id)` seam shared by CLI, ~25 gateway adapters, HTTP, ACP and cron; mid-turn messages become steer/redirect rather than new turns.
- Context: a three-tier byte-stable system prompt (identity → project files → volatile memory/skills/time) rebuilt only after compression; compaction at 50 % of the window by prune-then-summarize with a separate auxiliary model; oversized tool output is spilled to files, not dropped.
- Model interface: OpenAI chat-completions wire by default with pluggable transports (Anthropic, Responses, Bedrock) and provider plugins; streaming always on; 3 retries with backoff, then a configurable fallback chain, then a bounded auto-recovery wait.
- Output: a fixed core tool set sent on every call plus a Tool Search bridge for the long tail; tool batches split into parallel-safe segments; terminal execution behind pluggable sandboxes (local/docker/modal/...) and a regex-plus-human approval gate; tool-call rows persisted before execution.
- Control flow: synchronous phase-verdict loop with an unlimited default iteration budget, verify-on-stop nudges that re-enter the loop, flat delegation by default (`max_spawn_depth=1`) with threaded children, and task-keyed auxiliary model routing.

Hard cases

- **Tool Search bridge (`tool_search/tool_describe/tool_call`):** a tool call the model makes (output) whose only job is to decide which tool schemas the model sees (context); resolved by "assign by function": the catalog

read is context, the unwrapped `tool_call` re-dispatch is output. `tools/tool_search.py:L1--L7`, `model_tools.py:L701--L709`
- **`execute_code` programmatic tool calling:** a program the model writes at run time that sequences only tools → output (rule 27); but the loop refunds the iteration it used, which is control flow. `tools/code_execution_tool.py:L1--L10`, `agent/turn_tool_round.py:L199--L200`
- **Subdirectory hints and untrusted wrapping inside the tool result path:** code in the output executor that changes what the model is shown; assigned to context by rule 20. `agent/subdirectory_hints.py:L1--L5`, `agent/tool_dispatch_helpers.py:L572--L595`
- **Stop-gate nudges:** the harness appends a synthetic user row and goes again; the decision is control flow, the row's text is context, and it is not input (no person wrote it). `agent/turn_stop_gates.py:L105--L140`
- **Approval inside the terminal tool:** the gate runs inside the tool executor and blocks the worker thread (CLI) or returns `pending_approval` and ends the call (gateway); the person's answer is consumed by the harness → control flow by rule 26, even though the code lives in `tools/`. `tools/terminal_tool.py:L1013--L1047`
- **Reasoning-only stall → model fallback:** a model swap triggered by unusable output rather than an HTTP failure; placed in model interface because the request "could not be served" with content, not keyed to the work. `agent/turn_truncation.py:L630--L635`
- **Prompt-cache decoration:** `cache_control` markers are wire-format (model interface) but the tiered ordering of the system prompt exists only to keep them effective (context design); split across both. `agent/prompt_caching.py:L298--L308`, `agent/system_prompt.py:L730--L793`
- **Gateway session hygiene (0.85 compaction):** compaction performed by the gateway outside the agent turn; still context (fits the window) but hosted in a different process layer. `gateway/run_turn_hygiene.py:L94--L102`
- **Codex app-server mode — DOES NOT FIT cleanly:** with `api_mode == "codex_app_server"` the whole turn (loop, tool execution, model calls) is handed to an external OpenAI Codex subprocess and Hermes only projects its events into rows and arms a fallback on failure; the five primitives collapse into one opaque external harness that is not a sub-agent (no delegation, no outer loop). `agent/conversation_loop.py:L1650--L1651`, `agent/conversation_loop.py:L1537--L1552`
- **ACP / external-process "providers":** `acp://` base URLs make the "model" another agent process; streaming is disabled and the model interface boundary is another harness. `agent/turn_api_call.py:L46--L56`
- **Mixture-of-Agents:** several model calls per iteration issued by the harness (control flow) whose outputs are appended to the user message (context). `agent/moa_loop.py:L1--L5`

Summary row

Input	Context	Model interface	Output	Control flow
One MessageEvent seam: CLI, 25 gateways, HTTP, ACP, cron, steer	Tiered byte-stable prompt, memory files, 50 % prune-then-summarize compaction	Pluggable transports, streaming, 3 retries, fallback chain, auto-recovery	Core tools + bridge, parallel segments, sandboxed terminal, approval gate	Phase-verdict loop, unlimited budget, stop-gate nudges, flat threaded delegation

B.6 LangGraph (prebuilt ReAct agent on the Pregel runtime)

Source: https://github.com/langchain-ai/langgraph · **Version:** commit 5eb60aef6f3837a1fb632a8abc6cf8e8da81785b (2026-10-14; packages `langgraph` 1.2.15, `langgraph-prebuilt` 1.1.1, `langgraph-checkpoint`; the local clone holds this single squashed commit, so no file history is available) · **Language:** Python **Path conventions:** `LG/` = `libs/langgraph/langgraph/`; `PB/` = `libs/prebuilt/langgraph/prebuilt/`; `CP/` = `libs/checkpoint/langgraph/`; `T/` = `libs/*/tests/`. "User-written" marks a decision the framework leaves to the person building the graph. **What it is:** LangGraph (LangChain Inc.) is a framework for writing agent control flow as a graph of nodes over a shared, checkpointed state; the Pregel runtime executes the graph in bulk-synchronous supersteps. The canonical harness deconstructed here is `create_react_agent` (`PB/chat_agent_executor.py`): an `agent` node that calls a LangChain chat model and a `tools` node (`ToolNode`) that runs the model's tool calls, cycling until the model stops calling tools. The model is reached through a `langchain_core` `BaseChatModel` (`.invoke`/`.ainvoke`), which lives outside this repository; LangGraph itself contains no provider client.

Control flow

- **ReAct loop shape (user-written graph, built by the prebuilt):** `agent` and `tools` nodes are added and the `tools` node's edge returns to the entrypoint, so the loop is an edge, not a `while`. `PB/chat_agent_executor.py:L867--L872`, `L985--L990`
- **Go again / stop decision:** `should_continue` reads the last message; no `tool_calls` → `END` (or `post_model_hook` / `generate_structured_response`), otherwise route to `tools`. `PB/chat_agent_executor.py:L831--L859`; attached as a conditional edge `L964--L968`
- **v2 fan-out, one task per tool call:** `should_continue` returns one `Send("tools", ToolCallWithContext(...))` per tool call, so each call becomes its own Pregel task. `PB/chat_agent_executor.py:L849--L859`; `Send` type `LG/types.py:L738--L826`
- **`return_direct` hand-back:** tools flagged `return_direct` end the loop after they run; `route_tool_responses` returns `END` when the newest ToolMessages came from such a tool. `PB/chat_agent_executor.py:L597`, `L970--L990`
- **post_model_hook router (user-written hook, framework routing):** after the hook, pending tool calls without ToolMessages are re-sent to `tools`; a trailing ToolMessage routes back to the entrypoint; else END/structured. `PB/chat_agent_executor.py:L919--L962`
- **Step budget inside the agent (`remaining_steps`):** a managed value computed as `scratchpad.stop - scratchpad.step`. `LG/managed/is_last_step.py:L18--L24`; `stop = step + recursion_limit + 1` `LG/pregel/_loop.py:L1858--L1859`; `_are_more_steps_needed` returns True when `< 2` steps remain and the response has tool calls `PB/chat_agent_executor.py:L620--L634`; the model's response is then replaced by an AIMessage "Sorry, need more steps to process this request." `L684--L694`
- **Recursion limit (runtime step budget):** `tick()` sets `status = "out_of_steps"` when `step > stop`. `LG/pregel/_loop.py:L640--L643`; `stream()` then raises `GraphRecursionError` `LG/pregel/main.py:L3093--L3102`; error class `LG/errors.py:L68--L88`; default `DEFAULT_RECURSION_LIMIT = int(getenv("LANGGRAPH_DEFAULT_RECURSION_LIMIT", "10007"))` `LG/_internal/_config.py:L32`
- **Pregel superstep loop:** `while loop.tick(): ... runner.tick(...) ... loop.after_tick()`; channel updates from step N are visible only in step N+1. `LG/pregel/main.py:L3050--L3079`
- **Natural stop:** the loop ends when `prepare_next_tasks` yields no tasks (`status = "done"`). `LG/pregel/_loop.py:L686--L689`
- **Which node runs next (the scheduler):** `prepare_next_tasks` first consumes pending `Send` packets from the reserved `TASKS` topic (PUSH tasks), then PULL tasks for nodes whose trigger channels were updated. `LG/pregel/_algo.py:L391--L512` (PUSH `L441--L465`, PULL `L489--L511`); a node triggers when a trigger channel's version exceeds the version it last saw `L1259--L1276`
- **Apply writes between steps:** `apply_writes` sorts tasks by path for determinism, records `versions_seen`, updates channels and bumps versions. `LG/pregel/_algo.py:L254--L258`, `L293--L344`
- **Conditional edges as routing-by-channel:** `add_conditional_edges` stores a `BranchSpec` `LG/graph/state.py:L982--L1030`; at run time `_route` reads fresh state, calls the user's path function, maps results through `path_map`, and writes to `branch:to:<node>` channels `LG/graph/_branch.py:L146--L167`, `L192--L225`; `attach_branch` installs the branch as a writer on the source node `LG/graph/state.py:L1577--L1624`; plain edges write the same way `L1551--L1575`; each node is triggered by its own `branch:to:` ephemeral channel `L1525--L1532`
- **`Command(goto=...)` from a node or tool:** `_control_branch` turns `goto` into TASKS (`Send`) or `branch:to:` writes; `Command.PARENT` raises `ParentCommand`. `LG/graph/state.py:L1749--L1775`; `ParentCommand` is bubbled to the parent graph by `run_with_retry` `LG/pregel/_retry.py:L618--L631`; the exception class `LG/errors.py:L130--L134`
- **Send packets are tasks of the next (or same) superstep:** `prepare_push_task_send` turns `TASKS[idx]` into a task for the named node `LG/pregel/_algo.py:L937--L996`; `accept_push` schedules pushes emitted mid-step `LG/pregel/_loop.py:L584--L621`; `TASKS` is a non-accumulating `Topic(Send)` `LG/pregel/main.py:L814--L819`
- **Static breakpoints (`interrupt_before`/`interrupt_after`):** `should_interrupt` returns tasks whose node is listed, if any channel changed since the last interrupt `LG/pregel/_algo.py:L156--L186`; checked before running tasks `LG/pregel/_loop.py:L696--L701` and after the step is checkpointed `L787--L792`; the prebuilt passes the user's lists straight to `compile` `PB/chat_agent_executor.py:L995--L1002`
- **Dynamic pause (`interrupt()`):** first call in a task raises `GraphInterrupt` carrying an `Interrupt` whose id hashes the task namespace `LG/types.py:L1038--L1046`; on re-run it returns the stored resume value instead `L1019--L1036`; `GraphInterrupt` `LG/errors.py:L103--L108`
- **Pause bookkeeping:** the runner saves the interrupt as an `INTERRUPT` pending write `LG/pregel/_runner.py:L586--L592`; at the root graph the exception is swallowed, state is emitted and the run returns `LG/pregel/_loop.py:L1491--L1530`

- **Resume (harness-consumed answer):** `Command(resume=...)` maps to a `RESUME` write `LG/pregel/_io.py:L56--L78`; `_first` requires a checkpointer and demands interrupt ids when several interrupts are pending `LG/pregel/_loop.py:L992--L1009`; the task scratchpad looks up its resume value `LG/pregel/_algo.py:L1279--L1344`; resume is inferred from `None` input or a `Command` `LG/pregel/_loop.py:L915--L928`
- **Approval gate is user-written:** the framework ships only the `HumanInterrupt`/`HumanResponse` shapes (`accept`/`ignore`/`response`/`edit`); no code in the harness consumes them. `PB/interrupt.py:L51--L84`, `L87--L105`
- **Model routing keyed to the work (user-written):** `model` may be a callable `(state, runtime) -> BaseChatModel` resolved on every `agent` step. `PB/chat_agent_executor.py:L563--L564`, `L599--L618`, `L674--L677`
- **Second model call for structured output:** after the loop ends, `generate_structured_response` runs as its own node. `PB/chat_agent_executor.py:L744--L767`, wiring `L899--L910`
- **Node concurrency within a superstep:** all ready tasks are submitted to the executor and awaited with `FIRST_COMPLETED`; the first non-interrupt failure cancels the rest. `LG/pregel/_runner.py:L259--L290`, `L618--L636`, `L652--L699`
- **Cooperative drain (operator stop):** `RunControl.request_drain()` is checked at the superstep boundary; the loop sets `status="draining"` and `stream()` raises `GraphDrained` after checkpointing. `LG/runtime.py:L79--L104`; `LG/pregel/_loop.py:L706--L708`; `LG/pregel/main.py:L3103--L3106`; `LG/errors.py:L55--L65`
- **Per-node error-handler nodes (user-written handler, framework routing):** `compile` assigns default/explicit handler nodes `LG/graph/state.py:L1290--L1344`; the runner reroutes a failed task to its handler instead of panicking `LG/pregel/_runner.py:L298--L324`
- **Sub-agents / subgraphs:** a compiled agent is used as a node of another graph via `name` `PB/chat_agent_executor.py:L466--L468`; nesting is detected by `CONFIG_KEY_TASK_ID` in config `LG/pregel/_loop.py:L351`; a child's `Command(graph=PARENT, goto=[Send...])` is bubbled and merged by `ToolNode` so a tool can hand work to the parent `PB/tool_node.py:L903--L927`. Results return as channel writes to the parent task; depth is unbounded (namespace `parent|child:task_id`).
- **`tools_condition` helper:** standalone routing function (`"tools"` or `"__end__"`) for user-built loops. `PB/tool_node.py:L1616--L1619`
- **Hook nodes (user-written):** `pre_model_hook` runs before every `agent` step, `post_model_hook` after it; both are ordinary nodes the user supplies. `PB/chat_agent_executor.py:L876--L881`, `L891--L896`

Input

- **Person's message enters as graph input:** `map_input` turns the input dict into writes on the input channels. `LG/pregel/_io.py:L81--L97`; applied as a null-task write set on the first tick `LG/pregel/_loop.py:L1086--L1121`; the hidden `START` node forwards it into state `LG/graph/state.py:L1508--L1514`
- **Coercion of raw messages:** `add_messages` converts dicts/tuples to `BaseMessage`s and assigns UUIDs to id-less messages. `LG/graph/message.py:L190--L211`; ids are fixed before writes are stored `LG/pregel/_loop.py:L1087--L1089`, `L461--L463`
- **Tool results captured as `ToolMessage`:** raw tool returns are normalized (`Command`, `ToolMessage`, or list) `PB/tool_node.py:L1466--L1487`; non-string outputs are JSON-dumped `L317--L344`; failures become `ToolMessage(status="error")` `L1022--L1029`
- **Human answer the model consumes:** when a tool calls `interrupt()`, the resume value is returned to the tool code on re-run (`L1023--L1036` of `LG/types.py`) and becomes input only if the tool puts it in its `ToolMessage` (user-written). Shape: `PB/interrupt.py:L87--L105`
- **State edits from outside (`Command(update=...)`):** mapped to null-task channel writes. `LG/pregel/_io.py:L76--L78`
- **Run-scoped `context` (operator-supplied, not model-visible unless user code shows it):** built into `Runtime` and passed to nodes and tools. `LG/pregel/main.py:L2963--L2973`; `ToolRuntime.context` `PB/tool_node.py:L814--L825`

Context

- **Prompt assembly (user chooses form):** `_get_prompt_runnable` prepends a `SystemMessage` (from `str`/`SystemMessage`) to `state["messages"]`, or runs a user callable/Runnable over the whole state. `PB/chat_agent_executor.py:L137--L170`
- **What the model is shown each call:** `state["messages"]`, or `llm_input_messages` produced by `pre_model_hook` (which does not alter stored history). `PB/chat_agent_executor.py:L636--L658`; contract documented `L396--L424`

- **Tool descriptions:** `bind_tools(tool_classes + llm_builtin_tools)` unless the user already bound them; `_should_bind_tools` cross-checks names (OpenAI- and Anthropic-style schemas). `PB/chat_agent_executor.py:L582--L589`, `L173--L217`
- **Conversation as reducer-merged state:** `AgentState.messages` uses `add_messages`, which upserts by id and applies `RemoveMessage`. `PB/chat_agent_executor.py:L57--L62`; `LG/graph/message.py:L218--L237`
- **Window fitting (left to the user):** the only primitives are `RemoveMessage(id=REMOVE_ALL_MESSAGES)` to replace history `LG/graph/message.py:L212--L216` and the `pre_model_hook` slot `PB/chat_agent_executor.py:L396--L424`; trimming/summarization code: not found in this repository (grep for `trim_messages`/`summariz` hits only docstrings).
- **History validation before the call:** every `AIMessage.tool_calls` id must have a `ToolMessage`, else `INVALID_CHAT_HISTORY`. `PB/chat_agent_executor.py:L243--L271`
- **Node input is read from channels:** `_proc_input` collects the node's subscribed channels plus managed values, then applies the schema mapper. `LG/pregel/_algo.py:L1347--L1391`; conditional edges read a fresh copy including the node's own writes `L189--L225`; node reads/writes go through `CONFIG_KEY_READ`/`CONFIG_KEY_SEND` `LG/pregel/_read.py:L74--L91`, `LG/pregel/_write.py:L106--L126`
- **Long-term memory for the model (cross-thread store):** `BaseStore.get/put/search` `CP/store/base/__init__.py:L708`, `L756`, `L784`, `L866`; injected into tools via `InjectedStore` `PB/tool_node.py:L1441--L1449`; retrieval and what to show the model are user-written.
- **Hidden state injected into tools (not shown to the model):** `InjectedState`/`ToolRuntime` args are filled from graph state at call time and any model-supplied values for those names are stripped. `PB/tool_node.py:L1400--L1439`, `L1455--L1463`; `ToolRuntime` fields `L1756--L1764`
- **State snapshot travels with each tool task:** `ToolCallWithContext` carries `state` inside the `Send`; `_extract_state` hydrates it (or reads channels). `PB/tool_node.py:L306--L314`, `L1315--L1347`
- **Structured-output prompt:** an optional system prompt is prepended for the final structured call. `PB/chat_agent_executor.py:L756--L758`
- **Agent name stamped on responses:** `response.name = name` (used in multi-agent transcripts). `PB/chat_agent_executor.py:L681--L682`
- **Injection of `config`/`store`/`writer`/`runtime` into node functions by signature:** `LG/_internal/_runnable.py:L168--L219`, `L392--L419`

Model interface

- **The call:** `static_model.invoke(model_input, config)` (async `ainvoke`); the model is a `langchain_core` `BaseChatModel`, outside this repo. `PB/chat_agent_executor.py:L672--L679`, `L699--L707`; string ids resolved with `init_chat_model` `L569--L580`
- **Structured output call:** `model.with_structured_output(schema).invoke(messages, config)`. `PB/chat_agent_executor.py:L761--L766`
- **Receiving a token stream:** `StreamMessagesHandler` is a LangChain callback: `on_chat_model_start` records namespace/metadata, `on_llm_new_token` forwards each `ChatGenerationChunk`, `on_llm_end` emits the final message once. `LG/pregel/_messages.py:L139--L158`, `L160--L173`, `L175--L188`, `L106--L113`; installed when `"messages"` is in `stream_mode` `LG/pregel/main.py:L2902--L2918`; modes `LG/types.py:L131--L133`
- **Retries of a failed request (per node, user-configured):** `RetryPolicy(initial_interval=0.5, backoff_factor=2.0, max_interval=128.0, max_attempts=3, jitter=True, retry_on=default_retry_on)` `LG/types.py:L427--L446`; default predicate retries `ConnectionError` and HTTP 5xx, not `ValueError`/`TypeError`/`OSError` etc. `LG/_internal/_retry.py:L1--L29`; loop with exponential backoff and jitter `LG/pregel/_retry.py:L641--L682`; policy comes from the node or the graph `L579`; `create_react_agent` sets none and `Pregel` defaults to `()` `LG/pregel/main.py:L786`, `L832--L834`
- **Backup model when the request cannot be served:** not found. The dynamic-model callable is keyed to state/context, not to failure (`PB/chat_agent_executor.py:L599--L606`).
- **Timeouts per attempt:** `TimeoutPolicy(run_timeout, idle_timeout, refresh_on)` `LG/types.py:L461--L523`; async watchdog tasks race the node `LG/pregel/_retry.py:L422--L470`; `NodeTimeoutError` is deliberately retryable `LG/errors.py:L191--L207`; sync nodes cannot use timeouts `LG/pregel/_retry.py:L580--L583`
- **Sync/async mismatch guard:** an async model callable invoked synchronously raises. `PB/chat_agent_executor.py:L664--L670`

Output

- **Tool executor (`ToolNode`):** parses the last `AIMessage.tool_calls` (or a single `ToolCallWithContext`) `PB/tool_node.py:L1258--L1300`; runs all calls concurrently with a thread pool `executor.map` `L829--L832` or `asyncio.gather` `L863--L866`; results combined into `{"messages": [...]}` `L870--L895`
- **One call's execution:** `tool.invoke(call_args, config)` after injection `PB/tool_node.py:L960--L966`; unknown tool name → error `ToolMessage` listing valid tools `L1302--L1313`, template `L116--L118`
- **Error-to-message policy (user-configurable):** default handler only converts argument-validation errors (`ToolInvocationError`) and re-raises everything else `PB/tool_node.py:L391--L399`; `handle_tool_errors` may be bool/str/callable/exception types `L1002--L1029`; templates `L119--L129`
- **Interceptor around each call (user-written):** `wrap_tool_call(request, execute)` can retry, cache, rewrite or short-circuit a call. `PB/tool_node.py:L1061--L1088`
- **Tool returning `Command`:** validated and passed through so the tool's EFFECT (state update / goto) reaches the scheduler. `PB/tool_node.py:L1473--L1474`, `L897--L928`
- **Interrupt raised inside a tool is never caught:** `GraphBubbleUp` passes through the error handling. `PB/tool_node.py:L986--L996`
- **Rendering to the person (stream modes):** `values` after each step `LG/pregel/_loop.py:L751--L759`; `updates`/`tasks` per task `L1571--L1621`; `_emit` filters by subscribed modes `L1535--L1569`; final value of `invoke` is the last `values` chunk plus collected interrupts `LG/pregel/main.py:L4000--L4043`
- **Custom and tool-progress streams:** `stream_writer` for `"custom"` `LG/pregel/main.py:L2932--L2951`; `"tools"` mode installs `StreamToolCallHandler` (`on_tool_start`/`on_tool_end`) `L2921--L2929`, `LG/pregel/_tools.py:L35`, `L228--L258`; tools push partial output with `ToolRuntime.emit_output_delta` `PB/tool_node.py:L1766--L1784`
- **Sandboxing of tool execution:** not found; tools run in-process in the caller's executor (`PB/tool_node.py:L829--L832`).
- **Argument validation without execution:** `ValidationNode` checks tool calls against schemas and returns error `ToolMessage`s for the model to fix. `PB/tool_validator.py:L47`

Production concerns

Concern	Where it lives (primitive)	Mechanism	Evidence
Persistence	Control flow (loop state) and Context (conversation state)	`Checkpoint` = channel values + versions + versions_seen per thread; `BaseCheckpointSaver.put` after every superstep and `put_writes` per task; `durability` `sync`/`async`/`exit` (default `async`); `thread_id` required; backends `InMemorySaver`, `SqliteSaver`, `PostgresSaver`; resume loads latest checkpoint or a given `checkpoint_id` (time travel); cross-thread `BaseStore`	`CP/checkpoint/base/__init__.py:L93--L124`, `L301--L342`; `LG/pregel/_loop.py:L785--L786`, `L498--L528`, `L1261--L1263`, `L1479--L1489`; `LG/types.py:L98--L104`; `LG/pregel/main.py:L2682--L2686`, `L2695--L2696`, `L3078--L3079`; `LG/pregel/_loop.py:L1783--L1813`; `CP/checkpoint/memory/__init__.py:L34`; `libs/checkpoint-sqlite/langgraph/checkpoint/sqlite/__init__.py:L49`; `libs/checkpoint-postgres/langgraph/checkpoint/postgres/__init__.py:L45`

Concern	Where it lives (primitive)	Mechanism	Evidence
Safety & security	Output (tool args), Control flow (pauses), Persistence layer	No sandbox (not found). Approval = user-written `interrupt()` before/inside a tool. Model cannot forge `InjectedState`/`InjectedStore` args (stripped). Resume values failing an interrupt's `response_schema` are never fed back to the model. Checkpoint deserializer warns it must not see untrusted data; `LANGGRAPH_STRICT_MSGPACK` / msgpack allowlist; `EncryptedSerializer` wraps payloads; `TAG_HIDDEN` keeps nodes out of streams/breakpoints	`PB/tool_node.py:L1455--L1463`, `L997--L1001`; `CP/checkpoint/serde/jsonplus.py:L104--L135`; `CP/checkpoint/base/__init__.py:L742--L771`; `CP/checkpoint/serde/encrypted.py:L8--L35`; `LG/pregel/_algo.py:L175--L182`
Observability	Across (traces via LangChain callbacks)	`on_chain_start/end/error` per run with `ls_integration: langgraph` metadata; per-task metadata `langgraph_step/node/triggers/path/checkpoint_ns`; `checkpoints`/`tasks`/`debug` stream modes; retry attempts logged; `get_state`/`get_state_history`; `ExecutionInfo` (thread/run/task ids, attempt). Token accounting: not found in LangGraph (left to `langchain_core`/LangSmith).	`LG/pregel/main.py:L2865--L2890`, `L3108--L3112`; `LG/pregel/_algo.py:L653--L659`; `LG/pregel/_loop.py:L665--L684`, `L711`; `LG/pregel/_retry.py:L676--L680`; `LG/pregel/main.py:L1464`, `L1514`; `LG/runtime.py:L27--L52`
Resilience	Model interface (retry/timeout), Control flow (resume, error handlers), Output (tool errors)	`RetryPolicy` with backoff; `TimeoutPolicy` with idle/run watchdogs; `step_timeout` on a whole superstep; on resume, finished tasks' pending writes are re-applied so only unfinished tasks re-run; failed tasks routed to error-handler nodes; first failure cancels sibling tasks; `GraphDrained` on SIGTERM-style drain; tool errors returned to the model as messages. Compaction on overflow: not in framework (user `pre_model_hook`).	`LG/pregel/_retry.py:L641--L682`, `L422--L470`; `LG/pregel/main.py:L781`, `L3060`; `LG/pregel/_loop.py:L805--L821`, `L691--L694`; `LG/pregel/_runner.py:L298--L324`, `L652--L699`; `LG/pregel/_loop.py:L706--L708`; `PB/tool_node.py:L1022--L1029`
Performance	Output (parallel tools), Control flow (parallel nodes, caching), Model interface (streaming)	Tool calls run concurrently (thread pool / gather); nodes in a superstep run concurrently; node-level `CachePolicy(key_func, ttl)` with `BaseCache` lookup before execution; per-step input cache; `trigger_to_nodes` avoids scanning all nodes; token streaming; `durability="async"/"exit"` defers checkpoint writes	`PB/tool_node.py:L829--L832`, `L863--L866`; `LG/pregel/_runner.py:L259--L277`; `LG/types.py:L529--L538`; `LG/pregel/_loop.py:L1701--L1714`; `LG/pregel/main.py:L3056--L3057`; `LG/pregel/_algo.py:L667--L686`, `L1357--L1359`, `L474--L481`; `CP/cache/base/__init__.py:L15`
Evaluation	Across	Unit/integration test suites per package (prebuilt: `test_react_agent.py` 46 tests, `test_tool_node.py` 42; runtime: `test_pregel.py` 172, `test_retry.py` 105, `test_time_travel.py` 50, `test_interruption.py` 6); a `checkpoint-conformance` package for savers. Agent-quality evals: not found in this repository.	`libs/prebuilt/tests/test_react_agent.py`; `libs/prebuilt/tests/test_tool_node.py`; `libs/langgraph/tests/test_pregel.py`; `libs/langgraph/tests/test_retry.py`; `libs/checkpoint-conformance/tests/test_validate_memory.py`

Design decisions (one line each: the choice this harness made within a primitive)

- Input: everything (user message, tool result, resume value, external `Command(update)`) enters as a write to a named channel of a typed state, merged by a user-chosen reducer (`add_messages` upserts by message id).
- Context: the model sees exactly `state["messages"]` (optionally prefixed by one system message); fitting to the window is delegated entirely to a user-written `pre_model_hook`, with `REMOVE_ALL_MESSAGES` as the only built-in rewrite primitive.
- Model interface: no client of its own; a LangChain `BaseChatModel` is invoked once per `agent` node, with retries/timeouts expressed as per-node policies that are off by default.
- Output: `ToolNode` runs every tool call of a response concurrently in-process, converts results and (configurable) errors into `ToolMessage`s, and lets a tool return a `Command` to reach the scheduler.
- Control flow: the loop is a user-written graph executed as Pregel supersteps; "go again" is a conditional edge, "stop" is an empty task set or `recursion_limit`, pauses are exceptions persisted as checkpoint writes and resumed by re-running the node.

Hard cases

- **Conditional edge `should_continue`:** user code, but it decides go-again vs. stop and is executed by the scheduler as a writer on the node; placed in control flow by function (rule: assign by function). Note the whole graph is user-authored control flow; the prebuilt merely authors it for you.
- **`remaining_steps` managed value:** it is injected into the node's *state* (so it looks like context), but no model ever sees it; `call_model` uses it to replace the model's answer with a canned message. Placed in control flow (step budget). Its side effect — a synthetic AIMessage written into the conversation — is a context effect of a control-flow decision.
- **`Send("tools", ToolCallWithContext(state=...))`:** a scheduling packet (control flow) that also carries a state snapshot (context) to the tool task. Split: the `Send` is control flow; the snapshot and `_extract_state` are context.
- **Tool returning `Command(goto=...)` or `Command(graph=PARENT)`:** the tool call is output; its effect is routing, so `_combine_tool_outputs` and `_control_branch` are control flow (rule: a tool's EFFECT is assigned to what it changes).
- **`interrupt()` inside a tool and `HumanResponse`:** the pause/resume machinery is control flow, but the harness never consumes an approval; the framework hands the raw resume value to user code in the tool, which decides whether to execute. So the approval gate is user-written, and the value is input only if the tool shows it to the model.
- **Dynamic model callable:** a model change keyed to state/context (planning vs execution) is control flow by the rules, but the selection logic is user-written; the framework only re-resolves it before each call. No failure-keyed fallback exists, so "backup model" is absent from the model-interface primitive.
- **Checkpointer as conversation memory:** the same mechanism that makes the loop resumable (persistence of control-flow state) is what makes a `thread_id` a chat history (persistence of context). Recorded once under persistence, spanning both primitives.
- **Pregel channel/version scheduler:** it is a general dataflow scheduler (nodes fire when subscribed channels change), not a loop with explicit go-again/hand-back/stop. It fits control flow, but the "shape of the loop" is emergent from edges and versions rather than coded; the only explicit stop conditions are "no tasks" and the step budget.
- **`DEFAULT_RECURSION_LIMIT = "10007"`:** the value found at this commit (`LG/_internal/_config.py:L32`) differs from the widely documented default of 25; the clone has a single squashed commit, so the change cannot be traced. Recorded as found, not interpreted.
- **Run `context` / `Runtime`:** operator-supplied static data that is neither a person's message nor a tool result; it is closest to configuration (out of scope) but is delivered on the request path to tools, so it is noted under Input without a strong claim.
- **Error-handler nodes and `wrap_tool_call`:** both are user-written code that the framework schedules; they are resilience mechanisms whose primitive depends on what the user's code does (a retry inside `wrap_tool_call` is output-side; an error handler that routes is control flow).

Summary row

Input	**Context**	**Model interface**	**Output**	**Control flow**
Messages and tool results become reducer-merged channel writes	System prompt plus state messages; fitting left to user hook	One LangChain chat-model invoke per step; per-node retries optional	ToolNode runs tool calls concurrently, errors become ToolMessages	User-written graph run as Pregel supersteps; interrupts checkpointed