Numerical methods for plasma sheaths

Valentin Ayot, Averil Prost, Christian Tayou-Fotso,

Abstract

This article is a report of the project achieved during the CEMRACS 2022.

1 Plasma sheaths

Plasma sheaths draw interest since the observations of Irvin Langmuir in 1923. The physical phenomenon happens, for instance, when a metallic wall is in contact with a plasma. Both species will be absorbed by the wall, but with a rate proportional to their speed. Since the electrons are moving several order of magnitude faster than the ions, a positively charged layer (the *Debye sheath*) forms near the boundary.

The purpose of this work is to investigate numerically the formation of this sheath. Work on biblio! It follows previous work of ref travail Michel et Yann on a periodic case, and of ref Mehdi, Anaïs on a collisional model. Our aim is to study an ionization model with nonperiodic boundary conditions. The first section introduces the corresponding system, and derives the boundary conditions. The second section presents the numerical methods used to simulate the evolution of the plasma, and the third section gives some results and comparisons.

The model Let $t \in \mathbb{R}^+$ denote the time variable, $x \in [-1, 1]$ denote the spatial variable in a normalized one-dimensional domain, and $v \in \mathbb{R}$ denote the speed variable. The distribution of species is described through their density in the phase space, denoted by $f_i:(t,x,v)\in\mathbb{R}^+\times[-1,1]\times\mathbb{R}\mapsto\mathbb{R}$ for the ions, and $f_e:(t,x,v)\in\mathbb{R}^+\times[-1,1]\times\mathbb{R}\mapsto\mathbb{R}$ for the electrons. To these kinetic quantities, we add the spatial densities $n_{i,e}$ and currents $J_{i,e}$, defined by

$$n_{i,e}(t,x) := \int_{v \in \mathbb{P}} f_{i,e}(t,x,v) dv, \quad \text{and} \quad J_{i,e}(t,x) := \int_{v \in \mathbb{P}} v f_{i,e}(t,x,v) dv. \tag{1.1}$$

In the sequel, we will denote $n(t,x) := n_i(t,x) - n_e(t,x)$, and $J(t,x) := J_i(t,x) - J_e(t,x)$.

The evolution of the densities is modelled by the Vlasov-Poisson equations. Let $\varphi: \mathbb{R}^+ \times [-1,1] \to \mathbb{R}$ denote the electric potential. Then

$$\begin{cases} \partial_t f_i + v \partial_x f_i - \partial_x \varphi \, \partial_v f_i = \nu f_e \\ (t, x, v) \in \mathbb{R}_*^+ \times] - 1, 1[\times \mathbb{R}, \end{cases}$$
 (1.2a)

$$\begin{cases} \partial_t f_i + v \partial_x f_i - \partial_x \varphi \, \partial_v f_i = \nu f_e & (t, x, v) \in \mathbb{R}_*^+ \times] - 1, 1[\times \mathbb{R}, & (1.2a) \\ \partial_t f_i + v \partial_x f_e + \frac{\partial_x \varphi}{\mu} \, \partial_v f_e = 0 & (t, x, v) \in \mathbb{R}_*^+ \times] - 1, 1[\times \mathbb{R}, & (1.2b) \\ -\lambda^2 \partial_{xx}^2 \varphi = n(t, x) & (t, x) \in \mathbb{R}^+ \times] - 1, 1[. & (1.2c) \end{cases}$$

$$-\lambda^2 \partial_{xx}^2 \varphi = n(t, x) \qquad (t, x) \in \mathbb{R}^+ \times] -1, 1[. \tag{1.2c}$$

The physical parameters ν , μ and λ have the following meaning:

CNRS, UMR 5251, *Institut Mathématiques, Université de Bordeaux, F-33405 valentin.ayot@u-bordeaux.fr

[†]INSA de Rouen, LMI (EA 3226 - FR CNRS 3335), 685 Avenue de l'Université, 76801 St Etienne du Rouvray cedex, France. averil.prost@insa-rouen.fr

[‡]Labo. J. A. Dieudonné, UMR 6621, Université Nice-Sophia Antipolis, Parc Valrose, F-06108 Nice cedex 02, France. christian.tayou-fotso@unice.fr

- $-\nu \geqslant 0$ is the ionization frequency. It describes the rate of **creation** / **production** / **injection** ? of ions in presence of electrons.
- $-\mu := m_e/m_i$ is the mass ratio between electrons and ions.
- $-\lambda > 0$ is the Debye length.

In the sequel, we may use the electric field $E(t,x) := -\partial_x \varphi(t,x)$ in place of the potential. The, the second-order Poisson equation rewrites as

$$\lambda^2 \partial_x E(t, x) = n(t, x) \qquad (t, x) \in \mathbb{R}^+ \times] - 1, 1[. \tag{1.3}$$

Remark 1.1. To reduce the notations, we will use f_s , $s \in \{i, e\}$ to denote both the electronic and ionic distributions. The advection equations (1.2a) and (1.2b) rewrite

$$\partial f_s + v \partial_x f_s - c_s \partial_x \varphi \partial_v f_s = S_s,$$

with the speed coefficients c_s and source terms S_s defined as

$$c_i \coloneqq 1, \quad c_e \coloneqq -\frac{1}{\mu}, \quad S_i \coloneqq \nu f_e, \quad S_e \coloneqq 0.$$

The densities f_i and f_e are subject to initial and boundary conditions, given by

$$\begin{cases}
f_s(0, x, v) := f_s^0(x, v) & (x, v) \in] -1, 1[\times \mathbb{R}, \\
f_s(t, x = \pm 1, \pm v < 0) := 0 & t \in \mathbb{R}_*^+.
\end{cases} \tag{1.4a}$$

The homogeneous boundary condition (1.4b) stems from the non-emitting wall model: the boundary absorbs particles without any reflection.

To completely describe the model, we still need to provide boundary conditions for the Poisson problem (1.2c). A first one is given by the choice of a reference potential

$$\varphi(t,0) = 0 \qquad \forall t \in \mathbb{R}^+. \tag{1.5}$$

To derive a second boundary condition, we introduce a fundamental symmetry assumption.

Symmetry We will look for symmetric solutions satisfying

$$\varphi(t,x) = \varphi(t,-x) \qquad (t,x) \in \mathbb{R}^+ \times [-1,1]. \tag{1.6}$$

By derivation with respect to $x \in]-1,1[$, we immediatly obtain

$$\partial_x \varphi(t,x) = -\partial_x \varphi(t,-x)$$
, i.e. $E(t,x) = -E(t,-x)$.

In particular, the electric field vanishes at x = 0, and the Neumann boundary condition

$$\partial_x \varphi(t,0) = 0$$
 or equivalently $E(t,0) = 0$ (1.7)

may be used (with (1.5)) to close the Poisson equation (1.2c).

Let us notice that the advection equations (1.2a) and (1.2b) are driven by the vector fields

$$(t, x, v) \to (1, v, E(t, x)) =: V_i(t, x, v)$$
 and $(t, x, v) \to (1, v, -E(t, x)/\mu) =: V_e(t, x, v)$.

Both these fields satisfy the radial symmetry $V_s(t, x, v) = V_s(t, -x, -v)$. In consequence, if we assume that $f_s^0(x, v) = f_s^0(-x, -v)$, the solutions $f_s(t, x, v)$ will be radially symmetric around (t, 0, 0), i.e.

$$f_i(t, x, v) = f_i(t, -x, -v)$$
 and $f_e(t, x, v) = f_e(t, -x, -v)$ $\forall (t, x, v) \in \mathbb{R}^+ \times [-1, 1] \times \mathbb{R}$.

In particular, we have

$$n_{s}(t,x) = \int_{v \in \mathbb{R}} f_{s}(t,x,v) dv = \int_{w \in \mathbb{R}} f_{s}(t,x,-w) dw = \int_{w \in \mathbb{R}} f_{s}(t,-x,w) dw = n_{s}(t,-x), \text{ and }$$

$$J_{s}(t,x) = \int_{v \in \mathbb{R}} v f_{s}(t,x,v) dv = -\int_{w \in \mathbb{R}} w f_{s}(t,x,-w) dw = -\int_{w \in \mathbb{R}} w f_{s}(t,-x,w) dw = -J_{s}(t,-x).$$

Remark 1.2 (Additional symmetry of f_e). Notice that the function $f:(t,x,v) \to f_e(t,x,v) - f_e(t,x,-v)$ satisfies the linear equation

$$0 = \partial_t f(t, x, v) + v \partial_x f(t, x, v) - \frac{E(t, x)}{\mu} \partial_v f(t, x, v).$$

The boundary condition (1.4b) gives $f(t, \pm 1, \pm v < 0) = 0$. If, in addition, we assume that the initial condition f_e^0 satisfies $f_e^0(x, v) - f_e^0(x, -v) = 0$, then we obtain

$$f_e(t, x, v) = f_e(t, x, -v) \quad \forall (t, x, v) \in \mathbb{R}^+ \times [-1, 1] \times \mathbb{R}. \tag{1.8}$$

Another/Natural boundary condition The centered Neumann condition (1.7) enforces continuity of $\partial_x \varphi$ at x = 0. We may avoid this constraint by deriving another Neuman condition, given on the boundary $x = \pm 1$.

First, we derive with respect to time the Poisson equation (1.2c)

$$-\partial_t(\lambda^2 \partial_{rr}^2 \varphi) = \partial_t n,$$

and considering the difference between the v-integration of the Vlasov equations (1.2a) and (1.2b) gives

$$\partial_t n = \nu n_e - \partial_x J,$$

so that, using $E = -\partial_x \varphi$, we get

$$\partial_x(\lambda^2\partial_t E + J) = \nu n_e, \quad \forall x \in]-1,1[.$$

Integrating now in space leads to

$$\lambda^2 \partial_t E(t,1) + J(t,1) = \lambda^2 \partial_t E(t,-1) + J(t,-1) + \nu \int_{-1}^1 n_e(t,x) dx, \tag{1.9}$$

and using the symmetries E(t,1) = -E(t,-1) and J(t,1) = -J(t,-1), it comes

$$\lambda^2 \partial_t E(t, \pm 1) + J(t, \pm 1) = \pm \frac{\nu}{2} \int_{-1}^1 n_e(t, x) dx.$$
 (1.10)

Time integration gives a condition of the form $\partial_x \varphi(t,\pm 1) = C_{\pm}(t)$, where

$$C_{\pm}(t) \coloneqq \partial_x \varphi(0, \pm 1) + \frac{1}{\lambda^2} \int_0^t J(s, \pm 1) ds \mp \frac{\nu}{2\lambda^2} \int_0^t \int_{-1}^1 n_e(s, x) dx ds. \tag{1.11}$$

2 Numerical methods

2.1 Poisson equation

The Poisson problem is solved with integral representations of the variable E.

First, we consider the centered Neumann boundary condition (1.7). Then, integrating the Poisson problem (1.3) over [0, x] yields

$$E(t,x) = 0 + \int_0^x n(t,y)dy = \int_0^x \int_{v \in \mathbb{R}} [f_i(t,y,v) - f_e(t,y,v)]dvdy.$$
 (2.1)

Let us now consider the boundary condition (1.10). The spacial domain [-1,1] is split into its positive and negative part, and integrating (1.3) gives

$$E(t,x) = \begin{cases} E(t, 1) - \int_{x}^{1} n(t,y)dy = -C_{+}(t) - \int_{x}^{1} \int_{v \in \mathbb{R}} [f_{i}(t,y,v) - f_{e}(t,y,v)]dvdy & x \in [0,1] \\ E(t,-1) + \int_{-1}^{x} n(t,y)dy = C_{-}(t) + \int_{-1}^{x} \int_{v \in \mathbb{R}} [f_{i}(t,y,v) - f_{e}(t,y,v)]dvdy & x \in [-1,0[\end{cases}$$
 (2.2)

Note that here, the electric field may "jump" at x = 0. Both expressions may be approximated by quadrature formulas.

2.2 Finite Differences (FD)

Define a numerical computation domain $\Omega := [-1,1] \times [-\overline{V},\overline{V}]$, with a large enough maximum speed \overline{V} . Let $(x_j,v_k)_{k\in [\![0,K]\!]}^{j\in [\![0,J]\!]}$ be a cartesian grid of Ω of step $(\Delta x,\Delta v)$. We discretize the advection equations on the subgrid $(x_j,v_k)_{k\in [\![1,K-1]\!]}^{j\in [\![1,J-1]\!]}$ by an explicit Euler scheme in time, and the upwind scheme in space:

$$\frac{f_{s,j,k}^{n+1} - f_{s,j,k}^n}{\Delta t} + D_{j,k}^{-} f_s^n \begin{pmatrix} v_k \\ c_s E_j^n \end{pmatrix}_+ + D_{j,k}^{+} f_s^n \begin{pmatrix} v_k \\ c_s E_j^n \end{pmatrix}_- = S_{s,j,k}^n, \tag{2.3}$$

where $a_{+} = \max(a, 0)$ and $a_{-} = \min(a, 0)$ are respectively the pointwise positive and negative parts, and the decentered discrete differences are defined as

$$D_{j,k}^{\pm} f := \pm \left(\frac{f_{j\pm 1,k} - f_{j,k}}{\Delta x}, \frac{f_{j,k\pm 1} - f_{j,k}}{\Delta v} \right).$$

The values of $f_{s,j,k}^n$ on the boundary are taken as follows:

- the boundary condition (1.4b) yields $f_{s,j,k}^n = 0$ whenever $x_j = -1, v_k > 0$ or $x_j = 1, v_k < 0$.
- It is considered that \overline{V} is large enough to take the values on the speed boundary $v_k = \pm \overline{V}$ equal to 0.
- The remaining values $f_{s,j,k}^n, x_j = -1, -\overline{V} < v_k \le 0$ or $x_j = 1, 0 \le v_k < \overline{V}$ may be computed using the scheme (2.3), since the sign of the speed allows to use only inner points.

The upwind scheme is known to be diffusive, and stable under the CFL condition

$$1 - \max_{k} |v_k| \frac{\Delta t}{\Delta x} - |c_s| \max_{i} |E_j^n| \frac{\Delta t}{\Delta v} \geqslant 0 \quad \forall s \in \{i, e\} \text{ and } n \in [1, N].$$

Given Δx and Δv , we deduce a sufficiently small value of Δt with the bound

$$\Delta t \leqslant \min\left(\frac{\Delta x}{\overline{V}}, \min(1, \mu) \frac{\Delta v}{E_{\max}}\right), \quad E_{\max} > 0 \text{ postulated } a \text{ priori.}$$

2.3 Semi-Lagrangian (SL)

The full model (1.4) nicely lends itself to approximation by time splitting. Indeed, consider the following Strang splitting decomposition.

$$\begin{array}{lll} \frac{\Delta t}{2} & \begin{cases} \partial_t f_s + v \partial_x f_s = 0 & \text{Linear advection along } x, \\ \lambda^2 \partial_x E = n_i - n_e & \text{Poisson problem,} \end{cases} \\ \frac{\Delta t}{2} & \partial_t f_i = \nu f_e & \text{Ionization,} \\ \Delta t & \partial_t f_s + c_s E \partial_v f_s = 0 & \text{Linear advection along } v, \\ \frac{\Delta t}{2} & \partial_t f_i = \nu f_e & \text{Ionization,} \\ \frac{\Delta t}{2} & \begin{cases} \lambda^2 \partial_x E = n_i - n_e & \text{Poisson problem,} \\ \partial_t f_s + v \partial_x f_s = 0 & \text{Linear advection along } x. \end{cases} \end{array}$$

Each of the splitting step may be solved exactly. Indeed, the Poisson problems are solved by the integral representations (2.1) and (2.2). The ionization steps are pointwise ODE with time-independant source term, and are exactly solved by the explicit Euler scheme. Finally, notice that each advection is at constant speed with respect to the advection variable. This allows for the use of elementary 1D solvers.

Numerical treatment of the boundaries Let us focus on the elementary advection equation with constant speed a > 0

$$\partial_t f(t, x) + a \partial_x f(t, x) = 0, \quad f(t, -1) = 0, \quad \forall (t, x) \in \mathbb{R}_*^+ \times] - 1, 1[.$$

Let $(x_j)_{j\in \llbracket 0,J\rrbracket}$ be a space mesh of step $\Delta x := 2/J$, and $(t_n)_{n\in \llbracket 0,N\rrbracket}$ be a time mesh of step $\Delta t := T/N$. We follow the work of [CL20], and consider a semi-Lagrangian scheme defined as

$$f_j^{n+1} = \text{Lagrange interpolation} \left(f^n, x_j - a\Delta t \right) \coloneqq \sum_{k=-d}^d f_{j+k}^n L_k(x_j - a\Delta t),$$

with $(L_k)_{k \in [-d,d]}$ the Lagrange polynomes satisfying $L_k(x_l) = \delta_{kl}$. The stencil of the Lagrange interpolation uses 2d + 2 points, where $d \in \mathbb{N}$. The boundaries are treated as follow:

- the *inflow* side, corresponding to x = -1, relies on the analytical solution $f(t, x) = 0 \ \forall x \leq at$. Whenever the scheme needs a value f_j^n with j < 0, it may be exactly taken equal to 0.
- in the case d > 0, the Lagrange stencil may also need outflow values f_j^n with j > J. Such values may be determined by polynomial extrapolation. Let $k_b \in \mathbb{N}$, and let p be the unique polynomial of order k_b interpolating (x_j, f_j^n) for $j \in [\![J-kb, J]\!]$. The outflow ghost points will be defined by $f_j^n := p(-1+j\Delta x)$ $\forall j > N$.

3 Numerical results


3.1 1-species validation test case

We rely on the work of [MK20] to provide an analytical solution in a 1-species case. Consider the simplified stationary model describing the density of particles f = f(t, x, v), and the potential $\varphi = \varphi(t, x)$:

$$\begin{cases} \partial_t f + v \partial_x f - \partial_x \varphi \partial_v f = 0 & (t, x, v) \in \mathbb{R}_*^+ \times] - 1, 1[\times \mathbb{R}, & (3.1a) \\ \partial_{xx}^2 \varphi = \int_{v \in \mathbb{R}} f dv & (t, x) \in \mathbb{R}^+ \times] - 1, 1[. & (3.1b) \end{cases}$$

The initial and boundary conditions are given by

$$\begin{cases} f(0, x, v) := f^{0}(x, v), & f(t, x = \pm 1, \pm v < 0) = 0 \\ \varphi(t, 0) = \partial_{x} \varphi(t, 0) = 0 \end{cases}$$
(3.2a)






Figure 1: Malkov solutions (3.4) on [-1.5, 1.5]. Right: electric field E. Left: density f.

This model may be seen as a particular case of the two-species Vlasov-Poisson (1.4), upon taking the following parameters:

$$f_i^0 \equiv 0$$
, $\nu = 0$, $\mu = -1$, $\lambda = 1$, $f_e^0 = f^0$.

The reader may verify that (3.1) is solved in $\mathbb{R}^+ \times [-1,1] \times \mathbb{R}$ by the following stationary couple:

$$f(t, x, v) := \begin{cases} \frac{1}{\pi} \left(1 - x^2 - v^2 \right)^{-1/2} & \text{if } x^2 + z^2 < 1 \\ 0 & \text{otherwise} \end{cases}, \quad \text{and} \quad \varphi(t, x) := \frac{x^2}{2}. \tag{3.3}$$

It is numerically relevant to extend the Malkov solution (3.3) to spatial domains $x \in [-1 - \varepsilon, 1 + \varepsilon]$ by

$$f(t,x,v) := \begin{cases} \frac{1}{\pi} \left(1 - x^2 - v^2 \right)^{-1/2} & \text{if } x^2 + z^2 < 1 \\ 0 & \text{otherwise} \end{cases}, \quad \text{and} \quad \varphi(t,x) := \min\left(\frac{x^2}{2}, \frac{|x|}{2} \right). \tag{3.4}$$

Figure (1) illustrates the stationary solutions.

3.2 Comparison between (SL) and (FD)

References

- [CL20] Jean-François Coulombel and Frédéric Lagoutière. The Neumann numerical boundary condition for transport equations. *Kinetic & Related Models*, 13(1):1–32, 2020.
- [MK20] Evgeny A Malkov and Alexey N Kudryavtsev. Non-stationary antonov self-gravitating layer: analytics and numerics. *Monthly Notices of the Royal Astronomical Society*, 491(3):3952–3966, 2020.