

# seq\_analysis

Avery Katko

July 28, 2014

```
rm(list=ls())
library(ggplot2)
library(reshape2)
library(plyr)
library(bootstrap)
setwd("~/github/local/pragmods")
#source("useful.R")
d <- read.csv("seq_data/pragmods_seq.anondata.csv")
#head(d)
```

Exclude participants that either failed manipulation check or were rejected.

```
exclude <- d$assignmentstatus == "Rejected" |
  d$Answer.name_check_correct == "\"FALSE\""
sum(exclude)
```

```
## [1] 4
```

```
mean(exclude)
```

```
## [1] 0.04
```

```
d <- subset(d, exclude == FALSE)

d$Answer.choice_correct_1 <- factor(as.logical(d$Answer.choice_correct_1))
d$Answer.choice_correct_2 <- factor(as.logical(d$Answer.choice_correct_2))
d$Answer.choice_correct_3 <- factor(as.logical(d$Answer.choice_correct_3))
```

Restructure data to have trial variable. (working around mturk data submission limitations; can't safely submit arrays, so we have to use separate variables for each trial)

```
d$level_1 <- factor(ifelse(d$Answer.sequence_condition == "\"1w0w1b\"",1,0))
d$level_2 <- factor(ifelse(d$Answer.sequence_condition == "\"1w0w1b\"",0,1))
d$level_3 <- factor(rep(1,nrow(d)))

trial.df <- function(tn){
  df <- data.frame(id = d$workerid,
    seqCond = d$Answer.sequence_condition,
    trial = factor(rep(tn,nrow(d))),
    level = d[sprintf("level_%d",tn)],
    item = d[sprintf("Answer.item_%d",tn)],
    targetProp = d[sprintf("Answer.target_prop_%d",tn)],
    distractorProp = d[sprintf("Answer.distractor_prop_%d",tn)],
    targetPosition = d[sprintf("Answer.target_position_%d",tn)],
    distractorPosition = d[sprintf("Answer.distractor_position_%d",tn)],
```

```

        choice = d[sprintf("Answer.choice_%d",tn)],
        choiceCorrect = d[sprintf("Answer.choice_correct_%d",tn)])
names(df) <- c("id","seqCond","trial","level","item","targetProp","distractorProp",
              "targetPosition","distractorPosition","choice","choiceCorrect")
return(df)
}

d2 <- rbind(trial.df(1),trial.df(2),trial.df(3))
summary(d2)

```

```

##          id          seqCond    trial  level          item
##  Min.   : 1.0    "0w1w1b":123    1:96   0: 96    "boat"         :33
##  1st Qu.: 24.8    "1w0w1b":165    2:96   1:192   "Christmas tree":52
##  Median : 50.5                3:96                "friend"        :51
##  Mean   : 50.2                "pizza"         :44
##  3rd Qu.: 75.2                "snowman"       :50
##  Max.   :100.0                "sundae"        :58
##
##          targetProp          distractorProp targetPosition
##  "hat"           : 33    "hat"              : 36    "left"       :102
##  "chocolate"     : 23    "cherry"             : 22    "middle": 95
##  "star"           : 20    "glasses"            : 20    "right"      : 91
##  "whipped cream": 19    "mittens"            : 20
##  "scarf"          : 18    "whipped cream": 20
##  "glasses"        : 17    "star"              : 19
##  (Other)          :158    (Other)              :151
##  distractorPosition    choice    choiceCorrect
##  "left"       :97    "foil"       : 8    FALSE: 46
##  "middle":96    "logical": 38    TRUE :242
##  "right" :95    "target" :242
##
##
##
##

```

```

#statistics for boolean factors; copied from useful.R, with a slightly different mean function to work
l.mean <- function(...){mean(as.logical(...))}
l.theta <- function(x,xdata,na.rm=T) {l.mean(xdata[x],na.rm=na.rm)}
l.ci.low <- function(x,na.rm=T) {
  l.mean(x,na.rm=na.rm) - quantile(bootstrap(1:length(x),1000,l.theta,x,na.rm=na.rm)$thetastar,.025,na.rm=na.rm)
l.ci.high <- function(x,na.rm=T) {
  quantile(bootstrap(1:length(x),1000,l.theta,x,na.rm=na.rm)$thetastar,.975,na.rm=na.rm) - l.mean(x,na.rm=na.rm)
}


ms <- aggregate(choiceCorrect ~ seqCond + trial + level,data = d2,l.mean)
ms$cil <- aggregate(choiceCorrect ~ seqCond + trial + level, data = d2, l.ci.low)$choiceCorrect
ms$cih <- aggregate(choiceCorrect ~ seqCond + trial + level, data = d2, l.ci.high)$choiceCorrect

#colorblind-friendly color palettes
cbPalette <- c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442", "#0072B2", "#D55E00", "#CC79A7")
cbbPalette <- c("#000000", "#E69F00", "#56B4E9", "#009E73", "#F0E442", "#0072B2", "#D55E00", "#CC79A7")

```


Compare performance on trials, in chronological order; facet by ordering condition.

```
ggplot(data = ms, aes(x = trial, y = choiceCorrect, fill = level)) +
  geom_bar(stat = "identity", color = "black") +
  geom_errorbar(aes(ymin = choiceCorrect - cil, ymax = choiceCorrect + cih), width = 0.2) +
  facet_grid(. ~ seqCond) +
  theme_bw() +
  scale_fill_manual(values=cbPalette)
```




Compare performance on level-0 vs level-1 trials in the two conditions.

```
ggplot(data = subset(ms, trial != "3"), aes(x = level, y = choiceCorrect, fill = trial)) +
  geom_bar(stat = "identity", color = "black") +
  geom_errorbar(aes(ymin = choiceCorrect - cil, ymax = choiceCorrect + cih), width = 0.2) +
  facet_grid(. ~ seqCond) +
  theme_bw() +
  scale_fill_manual(values=cbPalette)
```



Compare performance on third trial (level-1, different stimuli)

```
ggplot(data = subset(ms, trial=="3"), aes(x = seqCond, y = choiceCorrect, fill = seqCond)) +
  geom_bar(stat = "identity", color = "black") +
  geom_errorbar(aes(ymin = choiceCorrect - cil, ymax = choiceCorrect + cih), width = 0.2) +
  theme_bw() +
  scale_fill_manual(values=cbPalette)
```



Chi-squared test between level-1 inferences in within trials

```
col_foil <- aggregate(choice ~ seqCond, data = d2[d2$level=="1" & d2$trial!="3",],
  function(...){sum(... == "\"foil\"")})

col_target <- aggregate(choice ~ seqCond, data = d2[d2$level=="1" & d2$trial!="3",],
  function(...){sum(... == "\"target\"")})

col_logical <- aggregate(choice ~ seqCond, data = d2[d2$level=="1" & d2$trial!="3",],
  function(...){sum(... == "\"logical\"")})

cont_table <- data.frame(cbind(col_foil,col_target[2],col_logical[2]))
names(cont_table) <- c("seqCond","foil","target","logical")

cont_table
```

```
##      seqCond foil target logical
## 1 "0w1w1b"    2    32      7
## 2 "1w0w1b"    1    38     16
```

```
chisq.test(cont_table[1:2,2:4])
```

```
## Warning: Chi-squared approximation may be incorrect
```

```
##
## Pearson's Chi-squared test
##
```

```
## data:  cont_table[1:2, 2:4]
## X-squared = 2.378, df = 2, p-value = 0.3045
```