



# **scribite! 3.0**

## **module developer documentation**

scribite! is a module for easy integration of WYSIWYG scripts Xinha, TinyMCE, FCKeditor, openWYSIWYG or nicEdit into textarea fields in order to make text editing a little bit nicer and comfortable.

scribite! in version 3.0 is only for Zikula 1.1 and higher.

This documentation is build for module developers. Module developers are able to integrate scribite! Into their own modules without big configurations in scribite! administration.

Author: Sven Schomacker (hilope)

URL: <http://trac.zikula.org/projects/scribite>

Published under GPL (pndocs/license.txt)

## 1. scribite! integration

The following example shows an easy call for scribite! with check for existence of scribite!.

```
if (pnModAvailable('scribite')) {  
    $scribite = pnModFunc('scribite','user','loader', array(  
        'modulename' => $args['modulename'],  
        'editor'     => $args['editor'],  
        'areas'      => $args['areas'],  
        'tpl'        => $args['tpl']));  
    PageUtil::AddVar('rawtext', $scribite);  
}
```

Required parameters are:

`$args['areas']` - array of textarea id's for the editor, (optionally „all“ for all)

Optional parameters are:

`$args['editor']` - the desired editor needs to exist  
(xinha, tiny\_mce, fckeditor, openwysiwyg, niceditor), uses  
default editor if not choosen (if choosen in administration!)

`$args['modulename']` - name of the module calling scribite!

`$args['tpl']` - template name (if file not exists, default template is used)

The configuration of the editor is taken from scribite! configuration, but can be override from special template. Permissions will be recognized! Users need at least „comment“ rights for scribite!.

The call should be done before the call of pnRender templates.

**Example (News module pn.8, file user.php, line 102ff):**

```
$pnRender->assign('preview', $preview);  
if (pnModAvailable('scribite')) {  
    $scribite = pnModFunc('scribite','user','loader', array('modulename' => 'News',  
        'editor'     => 'xinha',  
        'areas'      => array('news_bodytext',  
                             'news_hometext'),  
        'tpl'        => 'xinha_News.htm'));  
    PageUtil::AddVar('rawtext', $scribite);  
}  
// Return the output that has been generated by this function  
if (strtolower($type) == 'admin') {  
    return $pnRender->fetch('news_admin_new.htm');  
} else {  
    return $pnRender->fetch('news_user_new.htm');  
}
```