



Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

Module 03: CS31003: Compilers: Syntax Analysis or Parsing

Indranil Sengupta
Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

isg@iitkgp.ac.in
ppd@cse.iitkgp.ac.in

September 14, 15, 21 & 22, 2020



Module Objectives

Module 03

I Sengupta &
P P Das

Objectives & Outline

Infix \rightarrow
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

- Understand Parsing Fundamental
- Understand LR Parsing



Module Outline

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

- 1 Objectives & Outline
- 2 Infix \rightarrow Postfix
- 3 Grammar
 - Derivations
 - Parsing Fundamentals
- 4 RD Parsers
 - Left-Recursion
 - Ambiguous Grammar
- 5 Shift-Reduce Parser
 - SR Parsers



Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Infix \rightarrow Postfix



Resolving Ambiguity by Infix \rightarrow Postfix

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Let us recap what we did in PDS:

$$9 + 5 * 2 =$$





$$((9 + 5) * 2) = 28$$

$$(9 + (5 * 2)) = 19$$

$$9 - 5 + 2 =$$

$$((9 - 5) + 2) = 6$$

$$(9 - (5 + 2)) = 2$$





Expression Ambiguity Resolution: Infix \rightarrow Postfix

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar


LR Parsers

SR Parsers

$$9 + 5 * 2 = (9 + (5 * 2)) = 9 \ 5 \ 2 \ * \ +$$
$$((9 + 5) * 2) = 9 \ 5 \ + \ 2 \ *$$

$$9 - 5 + 2 = (9 - (5 + 2)) = 9 \ 5 \ 2 \ + \ -$$
$$((9 - 5) + 2) = 9 \ 5 \ - \ 2 \ +$$

Postfix notation is also called Reverse Polish Notation (RPN)





Associativity and Precedence

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Operators

- $*$, $/$ (left)
- $+$, $-$ (left)
- $<$, \leq , $>$, \geq (left)
- $!=$, $==$ (left)
- $=$ (right)



Infix \rightarrow Postfix: Examples

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Infix	Postfix
$A + B$	$A B +$
$A + B * C$	$A B C * +$
$(A + B) * C$	$A B + C *$
$A + B * C + D$	$A B C * + D +$
$(A + B) * (C + D)$	$A B + C D + *$
$A * B + C * D$	$A B * C D * +$

$A + B * C \rightarrow$

$A + (B * C) \rightarrow$

$A (B * C) + \rightarrow$

$A B C * +$



Infix \rightarrow Postfix: Rules

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

- 1 Print operands as they arrive.
- 2 If the stack is empty or contains a left parenthesis on top, push the incoming operator onto the stack.
- 3 If the incoming symbol is a left parenthesis, push it on the stack.
- 4 If the incoming symbol is a right parenthesis, pop the stack and print the operators until you see a left parenthesis. Discard the pair of parentheses.
- 5 If the incoming symbol has higher precedence than the top of the stack, push it on the stack.
- 6 If the incoming symbol has equal precedence with the top of the stack, use association. If the association is left to right, pop and print the top of the stack and then push the incoming operator. If the association is right to left, push the incoming operator.
- 7 If the incoming symbol has lower precedence than the symbol on the top of the stack, pop the stack and print the top operator. Then test the incoming operator against the new top of stack.
- 8 At the end of the expression, pop and print all operators on the stack. (No parentheses should remain.)



Operator Precedence Table

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

	Input						
	\$	+	−	*	/	()
\$		⟨⟨	⟨⟨	⟨⟨	⟨⟨	⟨⟨	
+	⟩⟩	⟩⟩	⟩⟩	⟨⟨	⟨⟨	⟨⟨	⟩⟩
−	⟩⟩	⟩⟩	⟩⟩	⟨⟨	⟨⟨	⟨⟨	⟩⟩
*	⟩⟩	⟩⟩	⟩⟩	⟩⟩	⟩⟩	⟨⟨	⟩⟩
/	⟩⟩	⟩⟩	⟩⟩	⟩⟩	⟩⟩	⟨⟨	⟩⟩
(⟨⟨	⟨⟨	⟨⟨	⟨⟨	⟨⟨	⟨⟨	=
)							



Infix \rightarrow Postfix: Rules

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

- **Requires operator precedence information**
- **Operands:** Add to postfix expression.
- **Close parenthesis:** Pop stack symbols until an open parenthesis appears.
- **Operators:** Pop all stack symbols until a symbol of lower precedence appears. Then push the operator.
- **End of input:** Pop all remaining stack symbols and add to the expression.



Infix \rightarrow Postfix: Rules

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers


SR Parsers

Expression:

$A * (B + C * D) + E$

becomes

$A B C D * + * E +$



	Current symbol	Operator Stack	Postfix string
1	A		A
2	*	*	A
3	(* (A
4	B	* (A B
5	+	* (+	A B
6	C	* (+	A B C
7	*	* (+ *	A B C
8	D	* (+ *	A B C D
9)	*	A B C D * +
10	+	+	A B C D * + *
11	E	+	A B C D * + * E
12			A B C D * + * E +



Evaluating Postfix Expression

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

- **Create a stack to store operands (or values)**
- **Scan the given expression and do following for every scanned element**
 - If the element is a number, push it into the stack
 - If the element is a operator, pop operands for the operator from stack. Evaluate the operator and push the result back to the stack
- **When the expression is ended, the number in the stack is the final answer**



Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

Grammar



Grammar

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

$G = \langle T, N, S, P \rangle$ is a (context-free) grammar where:

- T : Set of terminal symbols
- N : Set of non-terminal symbols
- S : $S \in N$ is the start symbol
- P : Set of production rules

Every production rule is of the form: $A \rightarrow \alpha$, where $A \in N$ and $\alpha \in (N \cup T)^*$.

Symbol convention:

a, b, c, \dots	Lower case letters at the beginning of alphabet	$\in T$
x, y, z, \dots	Lower case letters at the end of alphabet	$\in T^+$
A, B, C, \dots	Upper case letters at the beginning of alphabet	$\in N$
X, Y, Z, \dots	Upper case letters at the end of alphabet	$\in (N \cup T)$
$\alpha, \beta, \gamma, \dots$	Greek letters	$\in (N \cup T)^*$



Example Grammar: Derivations

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$G = \langle \{id, +, *, (,)\}, \{E, T, F\}, E, P \rangle$ where P is:

$$1: E \rightarrow E + T$$

$$2: E \rightarrow T$$

$$3: T \rightarrow T * F$$

$$4: T \rightarrow F$$

$$5: F \rightarrow (E)$$

$$6: F \rightarrow id$$

Left-most Derivation of $id + id * id \$$:

$$\begin{aligned} E \$ &\Rightarrow \underline{E} + T \$ &\Rightarrow \underline{T} + T \$ &\Rightarrow \underline{E} + T \$ \\ &\Rightarrow \underline{id} + T \$ &\Rightarrow \underline{id} + \underline{T * F} \$ &\Rightarrow \underline{id} + \underline{F} * F \$ \\ &\Rightarrow \underline{id} + \underline{id} * F \$ &\Rightarrow \underline{id} + \underline{id} * \underline{id} \$ \end{aligned}$$

Right-most Derivation of $id + id * id \$$:

$$\begin{aligned} E \$ &\Rightarrow \underline{E} + T \$ &\Rightarrow \underline{E} + \underline{T * F} \$ &\Rightarrow \underline{E} + T * \underline{id} \$ \\ &\Rightarrow \underline{E} + \underline{F} * id \$ &\Rightarrow \underline{E} + \underline{id} * id \$ &\Rightarrow \underline{T} + id * id \$ \\ &\Rightarrow \underline{F} + id * id \$ &\Rightarrow \underline{id} + id * id \$ \end{aligned}$$



Example Grammar: Derivations

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$G = \langle \{id, +, *, (,)\}, \{E, T, F\}, E, P \rangle$ where P is:

$$1: E \rightarrow E + T$$

$$2: E \rightarrow T$$

$$3: T \rightarrow T * F$$

$$4: T \rightarrow F$$

$$5: F \rightarrow (E)$$

$$6: F \rightarrow id$$

Left-most Derivation of $id * id + id \$$:

$$\begin{aligned} E \$ &\Rightarrow \underline{E + T} \$ &\Rightarrow \underline{T} + T \$ &\Rightarrow \underline{T * F} + T \$ \\ &\Rightarrow \underline{F} * F + T \$ &\Rightarrow id * \underline{F} + T \$ &\Rightarrow id * \underline{id} + T \$ \\ &\Rightarrow id * id + \underline{F} \$ &\Rightarrow id * id + \underline{id} \$ \end{aligned}$$

Right-most Derivation of $id * id + id \$$:

$$\begin{aligned} E \$ &\Rightarrow \underline{E + T} \$ &\Rightarrow \underline{E + F} \$ &\Rightarrow \underline{E + id} \$ \\ &\Rightarrow \underline{T} + id \$ &\Rightarrow \underline{T * F} + id \$ &\Rightarrow T * \underline{id} + id \$ \\ &\Rightarrow \underline{F} * id + id \$ &\Rightarrow \underline{id} * id + id \$ \end{aligned}$$



Parsing Fundamentals

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations

**Parsing
Fundamentals**

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Derivation	Parsing	Parser	Remarks
Left-most	Top-Down	Predictive: Recursive Descent, LL(1)	No Ambiguity No Left-recursion Tool: Antlr
Right-most	Bottom-Up	Shift-Reduce: SLR, LALR(1), LR(1)	Ambiguity okay Left-recursion okay Tool: YACC, Bison



Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

RD Parsers



Recursive Descent Parser

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$$S \rightarrow c A d$$

$$A \rightarrow ab \mid a$$

```

int main() {
    l = getchar();
    S(); // S is a start symbol

    // Here l is lookahead. If l = $, it represents the end of the string
    if (l == '$')
        printf("Parsing Successful");
    else printf("Error");
}

S() { // Definition of S, as per the given production
    match('c');
    A();
    match('d');
}

A() { // Definition of A as per the given production
    match('a');
    if (l == 'b') { match('b');
    }
}

match(char t) { // Match function
    if (l == t) { l = getchar();
    }
    else printf("Error");
}

```

Check with: **cad\$** ($S \Rightarrow cAd \Rightarrow cad$), **cabd\$** ($S \Rightarrow cAd \Rightarrow cabd$), **caad\$**



Recursive Descent Parser

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$$S \rightarrow c A d$$

$$A \rightarrow aAb \mid a$$

```

int main() {
    l = getchar();
    S(); // S is a start symbol.

    // Here l is lookahead. if l = $, it represents the end of the string
    if (l == '$')
        printf("Parsing Successful");
    else printf("Error");
}

S() { // Definition of S, as per the given production
    match('c');
    A();
    match('d');
}

A() { // Definition of A as per the given production
    match('a');
    if (l == 'a') {
        A();
        match('b');
    }
}

match(char t) { // Match function
    if (l == t) { l = getchar();
    }
    else printf("Error");
}

```

Check with: $\text{cad\$}$ ($S \Rightarrow cAd \Rightarrow cad$), $\text{cabd\$}$, $\text{caabd\$}$ ($S \Rightarrow cAd \Rightarrow caAbd \Rightarrow caabd$)

Compilers

I Sengupta & P P Das



Recursive Descent Parser

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$$\begin{aligned}
 E &\rightarrow a E' \\
 E' &\rightarrow + a E' \mid \epsilon
 \end{aligned}$$

```

int main() {
    l = getchar();
    E(); // E is a start symbol.
    // Here l is lookahead. If l = $, it represents the end of the string
    if (l == '$') printf("Parsing Successful");
    else printf("Error");
}

E() { // Definition of E, as per the given production
    match('a');
    E'();
}

E'() { // Definition of E' as per the given production
    if (l == '+') {
        match('+');
        match('a');
        E'();
    }
    else return (); // epsilon production
}

match(char t) { // Match function
    if (l == t) { l = getchar();
    }
    else printf("Error");
}

```

Check with: $a\$$ ($E \Rightarrow aE' \Rightarrow a$), $a+a\$$ ($E \Rightarrow aE' \Rightarrow a + aE' \Rightarrow a + a$), $a+a+a\$$
 ($E \Rightarrow aE' \Rightarrow a + aE' \Rightarrow a + a + aE' \Rightarrow a + a + a$)



Recursive Descent Parser

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

$E \rightarrow E + E \mid a$

```
int main() {
    l = getchar();
    E(); // E is a start symbol.

    // Here l is lookahead. if l = $, it represents the end of the string
    if (l == '$')
        printf("Parsing Successful");
    else printf("Error");
}

E() { // Definition of E as per the given production
    if (l == 'a') { // Terminate ?
        match('a');
    }

    E();           // Call ?
    match('+');
    E();
}

match(char t) { // Match function
    if (l == t) { l = getchar();
    }
    else printf("Error");
}
```

Check with: **a+a\$, a+a+a\$**



Curse or Boon 1: Left-Recursion

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

A grammar is left-recursive iff there exists a non-terminal A that can derive to a sentential form with itself as the leftmost symbol. Symbolically,

$$A \Rightarrow^+ A\alpha$$

We cannot have a recursive descent or predictive parser (with left-recursion in the grammar) because we do not know how long should we recur without consuming an input



Curse or Boon 1: Left-Recursion

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion


Ambiguous Grammar

LR Parsers

SR Parsers


Note that, $\begin{matrix} A & \rightarrow & A\alpha \\ A & \rightarrow & \beta \end{matrix}$ leads to:

$$\begin{array}{lclclclclclcl} A \$ & \Rightarrow & A\alpha \$ & \Rightarrow & A\alpha\alpha \$ & \Rightarrow & A\alpha\alpha\alpha \$ & \dots \\ & \Rightarrow & A\alpha^* \$ & \Rightarrow & \beta\alpha^* \$ & & & \end{array}$$



Removing left-recursion $\begin{matrix} A & \rightarrow & \beta A' \\ A' & \rightarrow & \alpha A' \end{matrix} \mid \epsilon$ leads to:

$$\begin{array}{lclclclclclcl} A \$ & \Rightarrow & \beta A' \$ & \Rightarrow & \beta\alpha A' \$ & \Rightarrow & \beta\alpha\alpha A' \$ & \dots \\ & \Rightarrow & \beta\alpha^* A' \$ & \Rightarrow & \beta\alpha^* \$ & & & \end{array}$$





Left-Recursive Example

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar


LR Parsers

SR Parsers

Grammar G_1 before Left-Recursion Removal


- 1: $E \rightarrow E + T$
- 2: $E \rightarrow T$
- 3: $T \rightarrow T * F$
- 4: $T \rightarrow F$
- 5: $F \rightarrow (E)$
- 6: $F \rightarrow \text{id}$

- These are syntactically equivalent. But what happens semantically?
- Can left recursion be effectively removed?
- What happens to Associativity?



Grammar G_2 after Left-Recursion Removal

- 1: $E \rightarrow T E'$
- 2: $E' \rightarrow + T E' \mid \epsilon$
- 3: $T \rightarrow F T'$
- 4: $T' \rightarrow * F T' \mid \epsilon$
- 5: $F \rightarrow (E)$
- 6: $F \rightarrow \text{id}$





Curse or Boon 2: Ambiguous Grammar

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

1: $E \rightarrow E + E$

2: $E \rightarrow E * E$

3: $E \rightarrow (E)$

4: $E \rightarrow \text{id}$

- Ambiguity simplifies. But, ...
 - Associativity is lost
 - Precedence is lost
- Can *Operator Precedence (infix \rightarrow postfix)* give us a clue?



Ambiguous Derivation of $\text{id} + \text{id} * \text{id}$

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers


Left-Recursion

Ambiguous Grammar


LR Parsers

SR Parsers

Correct derivation: $*$ has precedence over $+$

$$\begin{aligned} E \$ &\Rightarrow \underline{E + E} \$ \\ &\Rightarrow E + \underline{E * E} \$ \\ &\Rightarrow E + E * \underline{\text{id}} \$ \\ &\Rightarrow E + \underline{\text{id}} * \text{id} \$ \\ &\Rightarrow \underline{\text{id}} + \text{id} * \text{id} \$ \end{aligned}$$


Wrong derivation: $+$ has precedence over $*$

$$\begin{aligned} E \$ &\Rightarrow \underline{E * E} \$ \\ &\Rightarrow E * \underline{\text{id}} \$ \\ &\Rightarrow \underline{E + E} * \text{id} \$ \\ &\Rightarrow E + \underline{\text{id}} * \text{id} \$ \\ &\Rightarrow \underline{\text{id}} + \text{id} * \text{id} \$ \end{aligned}$$




Ambiguous Derivation of $\text{id} * \text{id} + \text{id}$

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations
Parsing
Fundamentals


RD Parsers

Left-Recursion
Ambiguous Grammar


LR Parsers

SR Parsers

Correct derivation: $*$ has precedence over $+$

$$\begin{aligned} E \$ &\Rightarrow \underline{E + E} \$ \\ &\Rightarrow \underline{E + id} \$ \\ &\Rightarrow \underline{E * E} + id \$ \\ &\Rightarrow \underline{E * id} + id \$ \\ &\Rightarrow \underline{id} * id + id \$ \end{aligned}$$


Wrong derivation: $+$ has precedence over $*$

$$\begin{aligned} E \$ &\Rightarrow \underline{E * E} \$ \\ &\Rightarrow \underline{E * E + E} \$ \\ &\Rightarrow \underline{E * E + id} \$ \\ &\Rightarrow \underline{E * id} + id \$ \\ &\Rightarrow \underline{id} * id + id \$ \end{aligned}$$




Remove: Ambiguity and Left-Recursion

Module 03

I Sengupta &
P P Das

Objectives & Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

1: $E \rightarrow E + E$
2: $E \rightarrow E * E$
3: $E \rightarrow (E)$
4: $E \rightarrow \text{id}$

Removing ambiguity:

1: $E \rightarrow E + T$
2: $E \rightarrow T$
3: $T \rightarrow T * F$
4: $T \rightarrow F$
5: $F \rightarrow (E)$
6: $F \rightarrow \text{id}$

Removing left-recursion:

1: $E \rightarrow T E'$
2|3: $E' \rightarrow + T E' \mid \epsilon$
4: $T \rightarrow F T'$
5|6: $T' \rightarrow * F T' \mid \epsilon$
7: $F \rightarrow (E)$
8: $F \rightarrow \text{id}$



Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

LR Parsers



Shift-Reduce Parser: Example: Grammar

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers

Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Sample grammar G_1 :

$$1: E \rightarrow E + T$$

$$2: E \rightarrow T$$

$$3: T \rightarrow T * F$$

$$4: T \rightarrow F$$

$$5: F \rightarrow (E)$$

$$6: F \rightarrow \mathbf{id}$$



Shift-Reduce Parser: Example: Parse Table

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix →
Postfix

Grammar

Derivations
Parsing
Fundamentals

RD Parsers

Left-Recursion
Ambiguous Grammar

LR Parsers

SR Parsers

State	Action						GO TO		
	id	+	*	()	\$	E	T	F
0	s5			s4			1	2	3
1		s6				acc			
2		r2	s7		r2	r2			
3		r4	r4		r4	r4			
4	s5			s4			8	2	3
5		r6	r6		r6	r6			
6	s5			s4				9	3
7	s5			s4					10
8		s6			s11				
9		r1	s7		r1	r1			
10		r3	r3		r3	r3			
11		r5	r5		r5	r5			



Shift-Reduce Parser: Example:

Parsing $\text{id} * \text{id} + \text{id}$

Module 03

I Sengupta &
P P Das

Objectives &
Outline

Infix \rightarrow
Postfix

Grammar

Derivations

Parsing
Fundamentals

RD Parsers


Left-Recursion

Ambiguous Grammar

LR Parsers

SR Parsers

Step	Stack	Symbols	Input	Act.
(1)	0		$\text{id} * \text{id} + \text{id} \$$	s5
(2)	0 5	id	$* \text{id} + \text{id} \$$	r6
(3)	0 3	F	$* \text{id} + \text{id} \$$	r4
(4)	0 2	T	$* \text{id} + \text{id} \$$	s7
(5)	0 2 7	T *	$\text{id} + \text{id} \$$	s5
(6)	0 2 7 5	T * id	$+ \text{id} \$$	r6
(7)	0 2 7 10	T * F	$+ \text{id} \$$	r3
(8)	0 2	T	$+ \text{id} \$$	r2
(9)	0 1	E	$+ \text{id} \$$	s6
(10)	0 1 6	E +	$\text{id} \$$	s5
(11)	0 1 6 5	E + id	$\$$	r6
(12)	0 1 6 3	E + F	$\$$	r4
(13)	0 1 6 9	E + T	$\$$	r1
(14)	0 1	E	$\$$	acc



1: E	\rightarrow	E + T
2: E	\rightarrow	T
3: T	\rightarrow	T * F
4: T	\rightarrow	F
5: F	\rightarrow	(E)
6: F	\rightarrow	id
E \$	\Rightarrow	E + T \$
	\Rightarrow	E + F \$
	\Rightarrow	E + id \$
	\Rightarrow	T + id \$
	\Rightarrow	T * F + id \$
	\Rightarrow	T * id + id \$
	\Rightarrow	F * id + id \$
	\Rightarrow	id * id + id \$

State	Action						GO TO		
	id	+	*	()	\$	E	T	F
0	s5			s4			1	2	3
1		s6				acc			
2		r2	s7		r2	r2			
3		r4	r4		r4	r4			
4	s5			s4			8	2	3
5		r6	r6		r6	r6			
6	s5			s4				9	3
7	s5			s4					10
8		s6			s11				
9		r1	s7		r1	r1			
10		r3	r3		r3	r3			
11		r5	r5		r5	r5			