Problem Solving Recipes Learned from Supporting Spark

Justin Pihony & Stavros Kontopolous Lightbend



Table of Contents

- 1. OOM
- 2. NoSuchMethod
- Perplexities of Size
- Struggles in Speculation

- StrategizingYour Joins
- 6. Safe Stream Recovery
- 7. Handling S3 w/o Hanging



Prologue





Memory Problems?







Out Of Memory (OOM)

"Thrown when the Java Virtual Machine cannot allocate an object because it is out of memory, and no more memory could be made available by the garbage collector."









spark.memory.fraction vs spark.memory.storageFraction



OOM Tips

- Don't jump straight to parameter tuning
 - But if you do => Sparklint
- Be aware of execution time object creation

```
rdd.mapPartitions{ iterator => // fetch remote file }
```



OOM Tips

 Plan the resources needed from your cluster manager before deploying - when possible

EXAMPLE

YARN

- Cluster vs client mode
- yarn.nodemanager.resource.memory-mb
- yarn.scheduler.minimum-allocationmb
- spark.yarn.driver.memoryOverhead



OOM



NoSuchMethod





NoSuchMethod

"Thrown if an application tries to call a specified method of a class (either static or instance), and that class no longer has a definition of that method. Normally, this error is caught by the compiler; this error can only occur at run time if the definition of a class has incompatibly changed."



java.lang.NoSuchMethodError:

org.apache.commons.math3.util.MathArrays.natural

"...spark 1.4.1 uses math3 3.1.1 which, as it turns out, doesn't have the natural method."

Dependency Collision



Compiled against version A Runtime used version B



Version B did not have the method!

Solutions

- Upgrade Spark or downgrade your library
 - If you're lucky...
- Enforce lib load order


```
spark-submit --class "MAIN_CLASS"

--driver-class-path commons-math3-3.3.jar YOURJAR.jar
```

- Shade your lib
 - sbt: https://github.com/sbt/sbt-assembly#shading
 - Maven: https://maven.apache.org/plugins/maven-shade-plugin/



Perplexities of Size





https://josephderosa.files.wordpress.com/2016/04/too-big-by-half.jpg

Perplexities of Size





Perplexities of Size

Summary Metrics for 8 Completed Tasks

Metric	Min	25th percentile	Median	75th percentile	Max
Duration	0,9 s	3 s	4 s	6 s	7 s
Task Deserialization Time	15 ms	16 ms	16 ms	16 ms	16 ms
GC Time	0 ms	0 ms	0 ms	0 ms	0 ms

Aggregated Metrics by Executor


Executor ID -	Address	Task Time	Total Tasks	Failed Tasks	Succeeded Tasks
driver	localhost:54071	32 s	8	0	8

Tasks

Index -	ID	Attempt	Status	Locality Level	Executor ID / Host	Launch Time	Duration	Task Deserialization Time	GC Time	Errors
0	0	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12 39 01	6 s	16 ms		
1	1	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	4 s	16 ms		
2	2	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	4 s	15 ms		
3	3	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	0,9 s	16 ms		
4	4	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	25	15 ms		
5	5	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	7 s	15 ms		
6	6	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	5 s	16 ms		
7	7	0	SUCCESS	PROCESS_LOCAL	driver / localhost	2016/04/22 12:39:01	3 s	16 ms		



Struggles in Speculation







Struggles in Speculation

- spark.speculation.interval
- spark.speculation.multiplier
- spark.speculation.quantile



Strategizing Your Joins





Common Issues

- Slow Joins
- Unavoidable Joins





Slow Joins

Avoid shuffling if one side of the join is small enough.

```
val df = largeDF.join(broadcast(smallDF), "key")
```

Check which strategy is actually used

```
df.explain
df.queryExecution.executedPlan
```

For broadcast you should see :

```
== Physical Plan ==
BroadcastHashJoin ... BuildRight
...
```



Join Strategies

- Broadcast
 - size < SQLConf.AUTO_BROADCASTJOIN_THRESHOLD
- Shuffle hash join
- Sort merge
 - spark.sql.join.preferSortMergeJoin (default = true)



Unavoidable Joins

```
val df = spark.sparkContext.parallelize(
   List(("Id1", 10, "London"), ("Id2", 20, "Paris"), ("Id2", 1, "NY"), ("Id2", 20, "London"))
).toDF("GroupId", "Amount", "City")
val grouped = df.groupBy("GroupId").agg(max("Amount"), first("City"))
grouped.collect().foreach(println)
```

Joining is the only way to retain all related columns for

```
val joined = df.as("a").join(grouped.as("b"),
    $"a.GroupId" === $"b.GroupId" && $"a.Amount" === $"b.max(Amount)", "inner")
joined.collect().foreach(println)
```

[ld1,10,London,ld1,10,London] [ld2,20,Paris,ld2,20,Paris] [ld2,20,London,ld2,20,Paris]



Safe Stream Recovery







```
val products = ssc.cassandraTable[(Int, String, Float)]
  (...)
   .map{ case (id, name, price) => (id, (name, price)) }
   .cache

orders.transform(rdd => {
   rdd.join(products)
})
```











ERROR JobScheduler: Error running job streaming job org.apache.spark.SparkException: RDD transformations and actions can only be invoked by the driver, not inside of other transformations; for example, rdd1.map(x => rdd2.values.count() * x) is invalid because the values transformation and count action cannot be performed inside of the rdd1.map transformation. For more information, see SPARK-5063.



ERROR JobScheduler: Error running job streaming job org.apache.spark.SparkException: RDD transformations and actions can only be invoked by the driver, not inside of other transformations; for example, rdd1.map(x => rdd2.values.count() * x) is invalid because the values transformation and count action cannot be performed inside of the rdd1.map transformation. For more information, see SPARK-5063.



```
val products = ssc.cassandraTable[(Int, String, Float)]
  (...)
   .map{ case (id, name, price) => (id, (name, price)) }
   .cache

orders.transform(rdd => {
   rdd.join(products)
})
```



```
val products = ssc.cassandraTable[(Int, String, Float)]
  (...)
   .map{ case (id, name, price) => (id, (name, price)) }
   .cache

orders.transform(rdd => {
   rdd.join products)
})
```



```
orders.transform(rdd => {
  val products = rdd.sparkContext.cassandraTable(...).map(...)
  rdd.join(products)
})
```



```
orders.transform(rdd => {
    val products = rdd.sparkContext.cassandraTable(...).map(...)
    rdd.join(products)
})
```



```
val products = ssc.cassandraTable[(Int, String, Float)]
  (...)
   .map{ case (id, name, price) => (id, (name, price)) }
   .cache

orders.transform(rdd => {
   rdd.join(products)
})
```



```
val products = ssc.cassandraTable[(Int, String, Float)]
  (...)
   .map{ case (id, name, price) => (id, (name, price)) }
   .cache

orders.transform(rdd => {
   rdd.join(products)
})
```






Safe Stream Recovery

```
orders.transform{ rdd => {
  val sc = rdd.sparkContext
  val productsOption = sc.getPersistentRDDs
    .values.filter(rdd => rdd.name == "foo").headOption
  val products = productsOption match {
    case Some(persistedRDD) =>
        persistedRDD.asInstanceOf[CassandraTableScanRDD[...]]
    case None => {
       val productsRDD = sc.cassandraTable(...).map(...)
        productsRDD.setName("foo")
        productsRDD.cache
    }
  }
  rdd.join(products)
}
```



Handling S3 w/o Hanging





Simple Streaming

```
val ssc = new StreamingContext(sc, Seconds(10))
val lines = ssc.textFileStream("s3n://some/folder")
lines.print
```



Simple Streaming, Right???


```
val ssc = new StreamingContext(sc, Seconds(10))
val lines = ssc.textFileStream("s3n://some/folder")
lines.print
```



Wrong!!!







Solutions

- Pace it with a script
- Custom s3n handler
- Explicit file handling
 - http://stackoverflow.com/a/34681877/779513
- Increase the heap
- Complain







THANK YOU.

justin.pihony@lightbend.com stavros.kontopolous@lightbend.com

