

Crappy CPU machine code equivalence

Antoine VIALLO

14 janvier 2020

Table des matières

1	Registers	6
2	High level instructions	6
2.1	ABRT	6
2.2	ADD	7
2.3	AND	7
2.4	CALL	7
2.5	CLR	7
2.6	CMP	7
2.7	DISP	7
2.8	HALT	8
2.9	INC	8
2.10	JBIT	8
2.11	JG	8
2.12	JGE	8
2.13	JL	8
2.14	JLE	8
2.15	JMP	8
2.16	JMPPTR	8
2.17	JNBIT	8
2.18	JNZ	9
2.19	JZ	9
2.20	LEDTGL	9
2.21	MOV	9
2.22	NEG	9
2.23	NOP	9
2.24	NOT	9
2.25	OR	9
2.26	RET	10
2.27	SHIFTL	10
2.28	SHIFTR	10
2.29	SLEEP	10
2.30	SUB	10
2.31	XOR	10

3	Instructions (low level)	10
3.1	default	10
3.1.1	default : 0x00	10
3.2	ADD	11
3.2.1	ADD_A_to_A : 0x01	11
3.2.2	ADD_A_to_U0 : 0x02	11
3.2.3	ADD_A_to_U1 : 0x03	11
3.2.4	ADD_A_to_U2 : 0x04	11
3.2.5	ADD_A_to_U3 : 0x05	11
3.2.6	ADD_A_to_mem : 0x06	11
3.2.7	ADD_B_to_A : 0x07	12
3.2.8	ADD_B_to_U0 : 0x08	12
3.2.9	ADD_B_to_U1 : 0x09	12
3.2.10	ADD_B_to_U2 : 0x0a	12
3.2.11	ADD_B_to_U3 : 0x0b	12
3.2.12	ADD_U0_to_A : 0x0c	12
3.2.13	ADD_U0_to_mem : 0x0d	13
3.2.14	ADD_U1_to_A : 0x0e	13
3.2.15	ADD_U1_to_mem : 0x0f	13
3.2.16	ADD_U2_to_A : 0x10	13
3.2.17	ADD_U2_to_mem : 0x11	13
3.2.18	ADD_U3_to_A : 0x12	13
3.2.19	ADD_U3_to_mem : 0x13	14
3.2.20	ADD_const_to_A : 0x14	14
3.2.21	ADD_const_to_U0 : 0x15	14
3.2.22	ADD_const_to_U1 : 0x16	14
3.2.23	ADD_const_to_U2 : 0x17	14
3.2.24	ADD_const_to_U3 : 0x18	14
3.2.25	ADD_const_to_const_in_A : 0x19	15
3.2.26	ADD_const_to_mem : 0x1a	15
3.2.27	ADD_mem_to_A : 0x1b	15
3.2.28	ADD_mem_to_U0 : 0x1c	15
3.2.29	ADD_mem_to_U1 : 0x1d	15
3.2.30	ADD_mem_to_U2 : 0x1e	16
3.2.31	ADD_mem_to_U3 : 0x1f	16
3.2.32	ADD_mem_to_mem : 0x20	16
3.3	AND	16
3.3.1	AND_A_B_to_itself : 0x21	16
3.3.2	AND_U0_B_to_itself : 0x22	16
3.3.3	AND_U1_B_to_itself : 0x23	17
3.3.4	AND_U2_B_to_itself : 0x24	17
3.3.5	AND_U3_B_to_itself : 0x25	17
3.4	CALL	17
3.4.1	CALL_addr : 0x26	17
3.5	CMP	17
3.5.1	CMP_A_B : 0x27	17
3.5.2	CMP_A_U0 : 0x28	17
3.5.3	CMP_A_U1 : 0x29	18
3.5.4	CMP_A_U2 : 0x2a	18
3.5.5	CMP_A_U3 : 0x2b	18

3.5.6	CMP_A_const : 0x2c	18
3.5.7	CMP_A_mem : 0x2d	18
3.5.8	CMP_U0_A : 0x2e	19
3.5.9	CMP_U0_const : 0x2f	19
3.5.10	CMP_U0_mem : 0x30	19
3.5.11	CMP_U1_A : 0x31	19
3.5.12	CMP_U1_const : 0x32	19
3.5.13	CMP_U1_mem : 0x33	20
3.5.14	CMP_U2_A : 0x34	20
3.5.15	CMP_U2_const : 0x35	20
3.5.16	CMP_U2_mem : 0x36	20
3.5.17	CMP_U3_A : 0x37	20
3.5.18	CMP_U3_const : 0x38	21
3.5.19	CMP_U3_mem : 0x39	21
3.6	COPY	21
3.6.1	COPY_A_to_A : 0x3a	21
3.6.2	COPY_A_to_B : 0x3b	21
3.6.3	COPY_A_to_U0 : 0x3c	21
3.6.4	COPY_A_to_U1 : 0x3d	21
3.6.5	COPY_A_to_U2 : 0x3e	22
3.6.6	COPY_A_to_U3 : 0x3f	22
3.6.7	COPY_A_to_cmp : 0x40	22
3.6.8	COPY_B_to_A : 0x41	22
3.6.9	COPY_B_to_B : 0x42	22
3.6.10	COPY_B_to_U0 : 0x43	22
3.6.11	COPY_B_to_U1 : 0x44	22
3.6.12	COPY_B_to_U2 : 0x45	22
3.6.13	COPY_B_to_U3 : 0x46	23
3.6.14	COPY_B_to_cmp : 0x47	23
3.6.15	COPY_U0_to_A : 0x48	23
3.6.16	COPY_U0_to_B : 0x49	23
3.6.17	COPY_U0_to_cmp : 0x4a	23
3.6.18	COPY_U1_to_A : 0x4b	23
3.6.19	COPY_U1_to_B : 0x4c	23
3.6.20	COPY_U1_to_cmp : 0x4d	23
3.6.21	COPY_U2_to_A : 0x4e	24
3.6.22	COPY_U2_to_B : 0x4f	24
3.6.23	COPY_U2_to_cmp : 0x50	24
3.6.24	COPY_U3_to_A : 0x51	24
3.6.25	COPY_U3_to_B : 0x52	24
3.6.26	COPY_U3_to_cmp : 0x53	24
3.6.27	COPY_mem : 0x54	24
3.6.28	COPY_mem_to_cmp : 0x55	25
3.7	DEC	25
3.7.1	DEC_A : 0x56	25
3.7.2	DEC_B : 0x57	25
3.7.3	DEC_U0 : 0x58	25
3.7.4	DEC_U1 : 0x59	25
3.7.5	DEC_U2 : 0x5a	25
3.7.6	DEC_U3 : 0x5b	26

3.7.7	DEC_mem : 0x5c	26
3.8	DISPLAY	26
3.8.1	DISPLAY_A : 0x5d	26
3.8.2	DISPLAY_B : 0x5e	26
3.8.3	DISPLAY_U0 : 0x5f	26
3.8.4	DISPLAY_U1 : 0x60	26
3.8.5	DISPLAY_U2 : 0x61	26
3.8.6	DISPLAY_U3 : 0x62	27
3.8.7	DISPLAY_mem : 0x63	27
3.9	FAIL	27
3.9.1	FAIL : 0x64	27
3.10	HALT	27
3.10.1	HALT : 0x65	27
3.11	INC	27
3.11.1	INC_A : 0x66	27
3.11.2	INC_B : 0x67	27
3.11.3	INC_U0 : 0x68	28
3.11.4	INC_U1 : 0x69	28
3.11.5	INC_U2 : 0x6a	28
3.11.6	INC_U3 : 0x6b	28
3.11.7	INC_mem : 0x6c	28
3.12	JMP	28
3.12.1	JMP_const : 0x6d	28
3.12.2	JMP_if_eq : 0x6e	29
3.12.3	JMP_if_ge : 0x6f	29
3.12.4	JMP_if_gt : 0x70	29
3.12.5	JMP_if_le : 0x71	29
3.12.6	JMP_if_lt : 0x72	29
3.12.7	JMP_if_neq : 0x73	29
3.12.8	JMP_not_sel_bit_0 : 0x74	30
3.12.9	JMP_not_sel_bit_1 : 0x75	30
3.12.10	JMP_not_sel_bit_2 : 0x76	30
3.12.11	JMP_not_sel_bit_3 : 0x77	30
3.12.12	JMP_not_sel_bit_4 : 0x78	30
3.12.13	JMP_not_sel_bit_5 : 0x79	30
3.12.14	JMP_not_sel_bit_6 : 0x7a	31
3.12.15	JMP_not_sel_bit_7 : 0x7b	31
3.12.16	JMP_ptr : 0x7c	31
3.12.17	JMP_sel_bit_0 : 0x7d	31
3.12.18	JMP_sel_bit_1 : 0x7e	31
3.12.19	JMP_sel_bit_2 : 0x7f	31
3.12.20	JMP_sel_bit_3 : 0x80	32
3.12.21	JMP_sel_bit_4 : 0x81	32
3.12.22	JMP_sel_bit_5 : 0x82	32
3.12.23	JMP_sel_bit_6 : 0x83	32
3.12.24	JMP_sel_bit_7 : 0x84	32
3.13	LED	32
3.13.1	LED_tgl : 0x85	32
3.14	LOAD	33
3.14.1	LOAD_const_to_A : 0x86	33

3.14.2	LOAD_const_to_B : 0x87	33
3.14.3	LOAD_const_to_U0 : 0x88	33
3.14.4	LOAD_const_to_U1 : 0x89	33
3.14.5	LOAD_const_to_U2 : 0x8a	33
3.14.6	LOAD_const_to_U3 : 0x8b	33
3.14.7	LOAD_ptr_to_A : 0x8c	34
3.14.8	LOAD_ptr_to_B : 0x8d	34
3.14.9	LOAD_ptr_to_U0 : 0x8e	34
3.14.10	LOAD_ptr_to_U1 : 0x8f	34
3.14.11	LOAD_ptr_to_U2 : 0x90	34
3.14.12	LOAD_ptr_to_U3 : 0x91	34
3.15	NEG	35
3.15.1	NEG_A : 0x92	35
3.15.2	NEG_B : 0x93	35
3.15.3	NEG_U0 : 0x94	35
3.15.4	NEG_U1 : 0x95	35
3.15.5	NEG_U2 : 0x96	35
3.15.6	NEG_U3 : 0x97	35
3.15.7	NEG_mem : 0x98	36
3.16	NOP	36
3.16.1	NOP : 0x99	36
3.17	NOT	36
3.17.1	NOT_A : 0x9a	36
3.17.2	NOT_B : 0x9b	36
3.17.3	NOT_U0 : 0x9c	36
3.17.4	NOT_U1 : 0x9d	36
3.17.5	NOT_U2 : 0x9e	37
3.17.6	NOT_U3 : 0x9f	37
3.18	OR	37
3.18.1	OR_A_B_to_itself : 0xa0	37
3.18.2	OR_U0_B_to_itself : 0xa1	37
3.18.3	OR_U1_B_to_itself : 0xa2	37
3.18.4	OR_U2_B_to_itself : 0xa3	37
3.18.5	OR_U3_B_to_itself : 0xa4	38
3.19	RET	38
3.19.1	RET : 0xa5	38
3.20	SHIFTL	38
3.20.1	SHIFTL_A : 0xa6	38
3.20.2	SHIFTL_B : 0xa7	38
3.20.3	SHIFTL_U0 : 0xa8	38
3.20.4	SHIFTL_U1 : 0xa9	38
3.20.5	SHIFTL_U2 : 0xaa	39
3.20.6	SHIFTL_U3 : 0xab	39
3.21	SHIFTR	39
3.21.1	SHIFTR_A : 0xac	39
3.21.2	SHIFTR_B : 0xad	39
3.21.3	SHIFTR_U0 : 0xae	39
3.21.4	SHIFTR_U1 : 0xaf	39
3.21.5	SHIFTR_U2 : 0xb0	40
3.21.6	SHIFTR_U3 : 0xb1	40

3.22 SLEEP	40
3.22.1 SLEEP_A : 0xb2	40
3.22.2 SLEEP_B : 0xb3	40
3.22.3 SLEEP_U0 : 0xb4	40
3.22.4 SLEEP_U1 : 0xb5	40
3.22.5 SLEEP_U2 : 0xb6	40
3.22.6 SLEEP_U3 : 0xb7	41
3.22.7 SLEEP_const : 0xb8	41
3.22.8 SLEEP_mem : 0xb9	41
3.23 STORE	41
3.23.1 STORE_A_to_address : 0xba	41
3.23.2 STORE_B_to_address : 0xbb	41
3.23.3 STORE_PCp1_to_address : 0xbc	41
3.23.4 STORE_U0_to_address : 0xbd	42
3.23.5 STORE_U1_to_address : 0xbe	42
3.23.6 STORE_U2_to_address : 0xbf	42
3.23.7 STORE_U3_to_address : 0xc0	42
3.23.8 STORE_const_to_address : 0xc1	42
3.24 SUB	42
3.24.1 SUB_A_to_A : 0xc2	42

1 Registers

Available registers :

- **A** : multi-purpose register. Is not overwritten quietly.
- **B** : work register. Used in many operations as a buffer
- **U#** : user registers. Will **never** be overwritten unless *explicitely* mentionned (see the instructions for more detail). There are only 4 of those currently.
- **ret** : not directly accessible. Used with **CALL** and **RET**
- **cmp** : not directly accessible. Used with **CMP** and **JMPxxx**
- **disp** : used to display something in decimal. Write-only.
- **C** : single bit register

2 High level instructions

2.1 ABRT

Set error bit and halt

- **ABRT** (size : 1, duration : 3)

2.2 ADD

Add a value from a register/memory address/const to a register or a memory address and save it in register A

- ADD A, U# (size : 1, duration : 6)
- ADD R, B (size : 1, duration : 5)
- ADD R, A (size : 1, duration : 6)
- ADD R, @0xHH (size : 2, duration : 9)
- ADD R, #0xHH (size : 2, duration : 7)
- ADD @0xHH, @0xHH (size : 3, duration : 13)
- ADD @0xHH, R (size : 2, duration : 9)
- ADD #0xHH, #0xHH (size : 3, duration : 9)
- ADD @0xHH, #0xHH (size : 3, duration : 10)

2.3 AND

AND two registers, save the result to the first operand

- AND R, B (size : 1, duration : 5)

2.4 CALL

Jump to specified address and save current PC in Ret register. Useful for subroutines.

- CALL #0xHH (size : 2, duration : 8)

2.5 CLR

Clear a register address.

- CLR A (size : 1, duration : 6)
- CLR U# (size : 1, duration : 6)
- CLR @0xHH (size : 3, duration : 7)

2.6 CMP

Compare two values (subtracts them) and store the result in CMP register. Overwrites B.

- CMP R, @0xHH (size : 2, duration : 12)
- CMP A, B (size : 1, duration : 8)
- CMP A, U# (size : 1, duration : 8)
- CMP R, #0xHH (size : 2, duration : 10)
- CMP U#, A (size : 1, duration : 8)
- CMP R (size : 1, duration : 4)
- CMP @0xHH (size : 2, duration : 7)

2.7 DISP

Display a value contained in specified register/memory address as an unsigned integer.

- DISP R (size : 1, duration : 4)
- DISP @0xHH (size : 2, duration : 7)

2.8 HALT

Halt the CPU

— HALT (size : 1, duration : 3)

2.9 INC

Increment register or value at memory address

— INC R (size : 1, duration : 5)

— INC @0xHH (size : 2, duration : 8)

2.10 JBIT

Go to specified address if selected bit of comparison register is 1.

— JBIT %b, #0xHH (size : 2, duration : 6)

2.11 JG

Go to specified address if comparison register is strictly positive.

— JG #0xHH (size : 2, duration : 6)

2.12 JGE

Go to specified address if comparison register is positive (or zero).

— JGE #0xHH (size : 2, duration : 6)

2.13 JL

Go to specified address if comparison register is strictly negative.

— JL #0xHH (size : 2, duration : 6)

2.14 JLE

Go to specified address if comparison register is negative or zero.

— JLE #0xHH (size : 2, duration : 6)

2.15 JMP

Go to specified address

— JMP @0xHH (size : 2, duration : 7)

— JMP #0xHH (size : 2, duration : 5)

2.16 JMPPTR

Go to address value at memory address.

— JMPPTR @0xHH (size : 2, duration : 7)

2.17 JNBIT

Go to specified address if selected bit of comparison register is 0.

— JNBIT %b, #0xHH (size : 2, duration : 6)

2.18 JNZ

Go to specified address if comparison register is NOT zero.

— JNZ #0xHH (size : 2, duration : 6)

2.19 JZ

Go to specified address if comparison register is zero.

— JZ #0xHH (size : 2, duration : 6)

2.20 LEDTGL

Toggle led. Useful for debugging.

— LEDTGL (size : 1, duration : 4)

2.21 MOV

Move a value from a register/memory address/const to a register or a memory address

— MOV A, R (size : 1, duration : 4)
— MOV B, R (size : 1, duration : 4)
— MOV U#, A (size : 1, duration : 4)
— MOV U#, B (size : 1, duration : 4)
— MOV R, @0xHH (size : 2, duration : 7)
— MOV R, #0xHH (size : 2, duration : 5)
— MOV @0xHH, R (size : 2, duration : 6)
— MOV @0xHH, @0xHH (size : 3, duration : 10)
— MOV @0xHH, #0xHH (size : 3, duration : 7)

2.22 NEG

Compute two's complement of register/memory (useful for subtractions), and store result in itself.

— NEG R (size : 1, duration : 6)
— NEG @0xHH (size : 2, duration : 9)

2.23 NOP

Go to next address

— NOP (size : 1, duration : 3)

2.24 NOT

Invert bit by bit register, and store result in itself

— NOT R (size : 1, duration : 5)

2.25 OR

OR two registers, save the result to the first operand

— OR A, B (size : 1, duration : 5)
— OR U#, B (size : 1, duration : 5)

2.26 RET

Revert PC to value saved in Ret register. Use with CALL.

— RET (size : 1, duration : 6)

2.27 SHIFTL

Shift register to the left

— SHIFTL R (size : 1, duration : 5)

2.28 SHIFTR

Shift register to the right

— SHIFTR R (size : 1, duration : 5)

2.29 SLEEP

Pause clock for specified amount of ticks

— SLEEP R (size : 1, duration : 4)

— SLEEP #0xHH (size : 1, duration : 5)

— SLEEP @0xHH (size : 1, duration : 7)

2.30 SUB

*Sub a value from a memory/register to register A and save it in register A.
Overwrites B.*

— SUB R, @0xHH (size : 2, duration : 12)

— SUB A, R (size : 1, duration : 9)

2.31 XOR

XOR two registers, save the result to the first operand

— XOR A, B (size : 1, duration : 5)

— XOR A, A (size : 1, duration : 6)

— XOR U#, U# (size : 1, duration : 6)

3 Instructions (low level)

3.1 default

3.1.1 default : 0x00

Micro-instructions :

1. outPC, loadRAM

2. outRAM, loadInstruction, incPC

3.2 ADD

3.2.1 ADD__A__to__A : 0x01

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outA, loadB | 3. outALU, loadA |
| 2. enableAdd, loadALU, outA | 4. clearMIconter |

3.2.2 ADD__A__to__U0 : 0x02

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outA, loadB | 3. outALU, loadU0 |
| 2. enableAdd, loadALU, outU0 | 4. clearMIconter |

3.2.3 ADD__A__to__U1 : 0x03

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outA, loadB | 3. outALU, loadU1 |
| 2. enableAdd, loadALU, outU1 | 4. clearMIconter |

3.2.4 ADD__A__to__U2 : 0x04

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outA, loadB | 3. outALU, loadU2 |
| 2. enableAdd, loadALU, outU2 | 4. clearMIconter |

3.2.5 ADD__A__to__U3 : 0x05

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outA, loadB | 3. outALU, loadU3 |
| 2. enableAdd, loadALU, outU3 | 4. clearMIconter |

3.2.6 ADD__A__to__mem : 0x06

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outA |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, storeRAM |
| 3. loadRAM, outMemAddr | |
| 4. outRAM, loadB | 7. clearMIconter |

3.2.7 ADD_B_to_A : 0x07

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableAdd, loadALU, outA | 3. clearMIconter |
| 2. outALU, loadA | |

3.2.8 ADD_B_to_U0 : 0x08

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAdd, loadALU, outU0 | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.2.9 ADD_B_to_U1 : 0x09

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAdd, loadALU, outU1 | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.2.10 ADD_B_to_U2 : 0x0a

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAdd, loadALU, outU2 | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.2.11 ADD_B_to_U3 : 0x0b

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAdd, loadALU, outU3 | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.2.12 ADD_U0_to_A : 0x0c

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outU0, loadB | 3. outALU, loadA |
| 2. enableAdd, loadALU, outA | 4. clearMIconter |

3.2.13 ADD_U0_to_mem : 0x0d

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU0 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, storeRAM |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.14 ADD_U1_to_A : 0x0e

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outU1, loadB | 3. outALU, loadA |
| 2. enableAdd, loadALU, outA | 4. clearMIconter |

3.2.15 ADD_U1_to_mem : 0x0f

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU1 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, storeRAM |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.16 ADD_U2_to_A : 0x10

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outU2, loadB | 3. outALU, loadA |
| 2. enableAdd, loadALU, outA | 4. clearMIconter |

3.2.17 ADD_U2_to_mem : 0x11

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU2 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, storeRAM |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.18 ADD_U3_to_A : 0x12

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outU3, loadB | 3. outALU, loadA |
| 2. enableAdd, loadALU, outA | 4. clearMIconter |

3.2.19 ADD_U3_to_mem : 0x13

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU3 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, storeRAM |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.20 ADD_const_to_A : 0x14

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outPC, loadRAM | 4. outALU, loadA |
| 2. outRAM, loadB, incPC | 5. clearMIconter |
| 3. enableAdd, loadALU, outA | |

3.2.21 ADD_const_to_U0 : 0x15

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outALU, loadU0 |
| 2. outRAM, loadB, incPC | 5. clearMIconter |
| 3. enableAdd, loadALU, outU0 | |

3.2.22 ADD_const_to_U1 : 0x16

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outALU, loadU1 |
| 2. outRAM, loadB, incPC | 5. clearMIconter |
| 3. enableAdd, loadALU, outU1 | |

3.2.23 ADD_const_to_U2 : 0x17

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outALU, loadU2 |
| 2. outRAM, loadB, incPC | 5. clearMIconter |
| 3. enableAdd, loadALU, outU2 | |

3.2.24 ADD_const_to_U3 : 0x18

Micro-instructions :

- | | |
|------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outALU, loadU3 |
| 2. outRAM, loadB, incPC | 5. clearMIconter |
| 3. enableAdd, loadALU, outU3 | |

3.2.25 ADD_const_to_const_in_A : 0x19

Micro-instructions :

- | | |
|-------------------------|-----------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outA |
| 2. outRAM, loadA, incPC | 6. outALU, loadA |
| 3. outPC, loadRAM | 7. clearMIconter |
| 4. outRAM, loadB, incPC | |

3.2.26 ADD_const_to_mem : 0x1a

Micro-instructions :

- | | |
|-------------------------------|--------------------------------------|
| 1. outPC, loadRAM | 6. enableAdd, loadALU, outRAM, incPC |
| 2. outRAM, loadMemAddr, incPC | |
| 3. loadRAM, outMemAddr | 7. outALU, storeRAM |
| 4. outRAM, loadB | 8. clearMIconter |
| 5. outPC, loadRAM | |

3.2.27 ADD_mem_to_A : 0x1b

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outA |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, loadA |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.28 ADD_mem_to_U0 : 0x1c

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU0 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, loadU0 |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.29 ADD_mem_to_U1 : 0x1d

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU1 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, loadU1 |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.30 ADD_mem_to_U2 : 0x1e

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU2 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, loadU2 |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.31 ADD_mem_to_U3 : 0x1f

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. enableAdd, loadALU, outU3 |
| 2. outRAM, loadMemAddr, incPC | 6. outALU, loadU3 |
| 3. loadRAM, outMemAddr | 7. clearMIconter |
| 4. outRAM, loadB | |

3.2.32 ADD_mem_to_mem : 0x20

Micro-instructions :

- | | |
|-------------------------|-----------------------------|
| 1. outPC, loadRAM | 7. outMemAddr, loadRAM |
| 2. outRAM, loadMemAddr | 8. outRAM, loadB, incPC |
| 3. outMemAddr, loadRAM | 9. loadALU, enableAdd, outA |
| 4. outRAM, loadA, incPC | 10. outALU, storeRAM |
| 5. outPC, loadRAM | 11. clearMIconter |
| 6. outRAM, loadMemAddr | |

3.3 AND

3.3.1 AND_A_B_to_itself : 0x21

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableAND, loadALU, outA | 3. clearMIconter |
| 2. outALU, loadA | |

3.3.2 AND_U0_B_to_itself : 0x22

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAND, loadALU, outU0 | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.3.3 AND_U1_B_to_itself : 0x23

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAND, loadALU, outU1 | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.3.4 AND_U2_B_to_itself : 0x24

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAND, loadALU, outU2 | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.3.5 AND_U3_B_to_itself : 0x25

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableAND, loadALU, outU3 | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.4 CALL

3.4.1 CALL_addr : 0x26

Micro-instructions :

- | | |
|------------------------------|------------------------------------|
| 1. outRetAddr, loadMemAddr | 4. outRAM, loadMemAddr |
| 2. outPCp1, storeRAM, incRet | 5. loadPC, cond_always, outMemAddr |
| 3. outPC, loadRAM | 6. clearMIconter |

3.5 CMP

3.5.1 CMP_A_B : 0x27

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outB, enableNOT, loadALU | 4. enableAdd, loadALU, outA |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.2 CMP_A_U0 : 0x28

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outU0, enableNOT, loadALU | 4. enableAdd, loadALU, outA |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.3 CMP_A_U1 : 0x29

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outU1, enableNOT, loadALU | 4. enableAdd, loadALU, outA |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.4 CMP_A_U2 : 0x2a

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outU2, enableNOT, loadALU | 4. enableAdd, loadALU, outA |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.5 CMP_A_U3 : 0x2b

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outU3, enableNOT, loadALU | 4. enableAdd, loadALU, outA |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.6 CMP_A_const : 0x2c

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outPC, loadRAM | 5. outALU, loadB |
| 2. outRAM, loadB, incPC | 6. enableAdd, loadALU, outA |
| 3. outB, enableNOT, loadALU | 7. outALU, loadCmp |
| 4. outALU, enableInc, loadALU | 8. clearMIconter |

3.5.7 CMP_A_mem : 0x2d

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 6. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 7. outALU, loadB |
| 3. outMemAddr, loadRAM | 8. enableAdd, loadALU, outA |
| 4. outRAM, loadB | 9. outALU, loadCmp |
| 5. outB, enableNOT, loadALU | 10. clearMIconter |

3.5.8 CMP_U0_A : 0x2e

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outA, enableNOT, loadALU | 4. enableAdd, loadALU, outU0 |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMcounter |

3.5.9 CMP_U0_const : 0x2f

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. outALU, loadB |
| 2. outRAM, loadB, incPC | 6. enableAdd, loadALU, outU0 |
| 3. outB, enableNOT, loadALU | 7. outALU, loadCmp |
| 4. outALU, enableInc, loadALU | 8. clearMcounter |

3.5.10 CMP_U0_mem : 0x30

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 6. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 7. outALU, loadB |
| 3. outMemAddr, loadRAM | 8. enableAdd, loadALU, outU0 |
| 4. outRAM, loadB | 9. outALU, loadCmp |
| 5. outB, enableNOT, loadALU | 10. clearMcounter |

3.5.11 CMP_U1_A : 0x31

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outA, enableNOT, loadALU | 4. enableAdd, loadALU, outU1 |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMcounter |

3.5.12 CMP_U1_const : 0x32

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. outALU, loadB |
| 2. outRAM, loadB, incPC | 6. enableAdd, loadALU, outU1 |
| 3. outB, enableNOT, loadALU | 7. outALU, loadCmp |
| 4. outALU, enableInc, loadALU | 8. clearMcounter |

3.5.13 CMP_U1_mem : 0x33

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 6. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 7. outALU, loadB |
| 3. outMemAddr, loadRAM | 8. enableAdd, loadALU, outU1 |
| 4. outRAM, loadB | 9. outALU, loadCmp |
| 5. outB, enableNOT, loadALU | 10. clearMIconter |

3.5.14 CMP_U2_A : 0x34

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outA, enableNOT, loadALU | 4. enableAdd, loadALU, outU2 |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.15 CMP_U2_const : 0x35

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. outALU, loadB |
| 2. outRAM, loadB, incPC | 6. enableAdd, loadALU, outU2 |
| 3. outB, enableNOT, loadALU | 7. outALU, loadCmp |
| 4. outALU, enableInc, loadALU | 8. clearMIconter |

3.5.16 CMP_U2_mem : 0x36

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 6. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 7. outALU, loadB |
| 3. outMemAddr, loadRAM | 8. enableAdd, loadALU, outU2 |
| 4. outRAM, loadB | 9. outALU, loadCmp |
| 5. outB, enableNOT, loadALU | 10. clearMIconter |

3.5.17 CMP_U3_A : 0x37

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outA, enableNOT, loadALU | 4. enableAdd, loadALU, outU3 |
| 2. outALU, enableInc, loadALU | 5. outALU, loadCmp |
| 3. outALU, loadB | 6. clearMIconter |

3.5.18 CMP_U3_const : 0x38

Micro-instructions :

- | | |
|-------------------------------|------------------------------|
| 1. outPC, loadRAM | 5. outALU, loadB |
| 2. outRAM, loadB, incPC | 6. enableAdd, loadALU, outU3 |
| 3. outB, enableNOT, loadALU | 7. outALU, loadCmp |
| 4. outALU, enableInc, loadALU | 8. clearMIconter |

3.5.19 CMP_U3_mem : 0x39

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 6. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 7. outALU, loadB |
| 3. outMemAddr, loadRAM | 8. enableAdd, loadALU, outU3 |
| 4. outRAM, loadB | 9. outALU, loadCmp |
| 5. outB, enableNOT, loadALU | 10. clearMIconter |

3.6 COPY

3.6.1 COPY_A_to_A : 0x3a

Micro-instructions :

- | | |
|----------------|------------------|
| 1. outA, loadA | 2. clearMIconter |
|----------------|------------------|

3.6.2 COPY_A_to_B : 0x3b

Micro-instructions :

- | | |
|----------------|------------------|
| 1. outA, loadB | 2. clearMIconter |
|----------------|------------------|

3.6.3 COPY_A_to_U0 : 0x3c

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outA, loadU0 | 2. clearMIconter |
|-----------------|------------------|

3.6.4 COPY_A_to_U1 : 0x3d

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outA, loadU1 | 2. clearMIconter |
|-----------------|------------------|

3.6.5 COPY_A_to_U2 : 0x3e

Micro-instructions :

1. outA, loadU2
2. clearMIcounter

3.6.6 COPY_A_to_U3 : 0x3f

Micro-instructions :

1. outA, loadU3
2. clearMIcounter

3.6.7 COPY_A_to_cmp : 0x40

Micro-instructions :

1. outA, loadCmp
2. clearMIcounter

3.6.8 COPY_B_to_A : 0x41

Micro-instructions :

1. outB, loadA
2. clearMIcounter

3.6.9 COPY_B_to_B : 0x42

Micro-instructions :

1. outB, loadB
2. clearMIcounter

3.6.10 COPY_B_to_U0 : 0x43

Micro-instructions :

1. outB, loadU0
2. clearMIcounter

3.6.11 COPY_B_to_U1 : 0x44

Micro-instructions :

1. outB, loadU1
2. clearMIcounter

3.6.12 COPY_B_to_U2 : 0x45

Micro-instructions :

1. outB, loadU2
2. clearMIcounter

3.6.13 COPY_B_to_U3 : 0x46

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outB, loadU3 | 2. clearMIconter |
|-----------------|------------------|

3.6.14 COPY_B_to_cmp : 0x47

Micro-instructions :

- | | |
|------------------|------------------|
| 1. outB, loadCmp | 2. clearMIconter |
|------------------|------------------|

3.6.15 COPY_U0_to_A : 0x48

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outU0, loadA | 2. clearMIconter |
|-----------------|------------------|

3.6.16 COPY_U0_to_B : 0x49

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outU0, loadB | 2. clearMIconter |
|-----------------|------------------|

3.6.17 COPY_U0_to_cmp : 0x4a

Micro-instructions :

- | | |
|-------------------|------------------|
| 1. outU0, loadCmp | 2. clearMIconter |
|-------------------|------------------|

3.6.18 COPY_U1_to_A : 0x4b

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outU1, loadA | 2. clearMIconter |
|-----------------|------------------|

3.6.19 COPY_U1_to_B : 0x4c

Micro-instructions :

- | | |
|-----------------|------------------|
| 1. outU1, loadB | 2. clearMIconter |
|-----------------|------------------|

3.6.20 COPY_U1_to_cmp : 0x4d

Micro-instructions :

- | | |
|-------------------|------------------|
| 1. outU1, loadCmp | 2. clearMIconter |
|-------------------|------------------|

3.6.21 COPY_U2_to_A : 0x4e

Micro-instructions :

- | | |
|-----------------|-------------------|
| 1. outU2, loadA | 2. clearMIcounter |
|-----------------|-------------------|

3.6.22 COPY_U2_to_B : 0x4f

Micro-instructions :

- | | |
|-----------------|-------------------|
| 1. outU2, loadB | 2. clearMIcounter |
|-----------------|-------------------|

3.6.23 COPY_U2_to_cmp : 0x50

Micro-instructions :

- | | |
|-------------------|-------------------|
| 1. outU2, loadCmp | 2. clearMIcounter |
|-------------------|-------------------|

3.6.24 COPY_U3_to_A : 0x51

Micro-instructions :

- | | |
|-----------------|-------------------|
| 1. outU3, loadA | 2. clearMIcounter |
|-----------------|-------------------|

3.6.25 COPY_U3_to_B : 0x52

Micro-instructions :

- | | |
|-----------------|-------------------|
| 1. outU3, loadB | 2. clearMIcounter |
|-----------------|-------------------|

3.6.26 COPY_U3_to_cmp : 0x53

Micro-instructions :

- | | |
|-------------------|-------------------|
| 1. outU3, loadCmp | 2. clearMIcounter |
|-------------------|-------------------|

3.6.27 COPY_mem : 0x54

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 5. outPC, loadRAM |
| 2. outRAM, loadMemAddr, incPC | 6. outRAM, loadMemAddr, incPC |
| 3. outMemAddr, loadRAM | 7. storeRAM, outB |
| 4. outRAM, loadB | 8. clearMIcounter |

3.6.28 COPY__mem__to__cmp : 0x55

Micro-instructions :

- | | |
|-------------------------------|--------------------|
| 1. outPC, loadRAM | 4. outRAM, loadCmp |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.7 DEC

3.7.1 DEC__A : 0x56

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outA, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadA | |

3.7.2 DEC__B : 0x57

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outB, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadB | |

3.7.3 DEC__U0 : 0x58

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU0, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.7.4 DEC__U1 : 0x59

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU1, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.7.5 DEC__U2 : 0x5a

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU2, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.7.6 DEC_U3 : 0x5b

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU3, enableDEC, loadALU | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.7.7 DEC_mem : 0x5c

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 4. outRAM, enableDEC, loadALU |
| 2. outRAM, loadMemAddr, incPC | 5. outALU, storeRAM |
| 3. outMemAddr, loadRAM | 6. clearMIconter |

3.8 DISPLAY

3.8.1 DISPLAY_A : 0x5d

Micro-instructions :

- | | |
|----------------------|------------------|
| 1. outA, loadDisplay | 2. clearMIconter |
|----------------------|------------------|

3.8.2 DISPLAY_B : 0x5e

Micro-instructions :

- | | |
|----------------------|------------------|
| 1. outB, loadDisplay | 2. clearMIconter |
|----------------------|------------------|

3.8.3 DISPLAY_U0 : 0x5f

Micro-instructions :

- | | |
|-----------------------|------------------|
| 1. outU0, loadDisplay | 2. clearMIconter |
|-----------------------|------------------|

3.8.4 DISPLAY_U1 : 0x60

Micro-instructions :

- | | |
|-----------------------|------------------|
| 1. outU1, loadDisplay | 2. clearMIconter |
|-----------------------|------------------|

3.8.5 DISPLAY_U2 : 0x61

Micro-instructions :

- | | |
|-----------------------|------------------|
| 1. outU2, loadDisplay | 2. clearMIconter |
|-----------------------|------------------|

3.8.6 DISPLAY_U3 : 0x62

Micro-instructions :

- | | |
|-----------------------|------------------|
| 1. outU3, loadDisplay | 2. clearMIconter |
|-----------------------|------------------|

3.8.7 DISPLAY_mem : 0x63

Micro-instructions :

- | | |
|-------------------------------|------------------------|
| 1. outPC, loadRAM | 4. outRAM, loadDisplay |
| 2. outRAM, loadMemAddr, incPC | |
| 3. loadRAM, outMemAddr | 5. clearMIconter |

3.9 FAIL

3.9.1 FAIL : 0x64

Micro-instructions :

1. error, halt

3.10 HALT

3.10.1 HALT : 0x65

Micro-instructions :

1. halt

3.11 INC

3.11.1 INC_A : 0x66

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outA, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadA | |

3.11.2 INC_B : 0x67

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outB, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadB | |

3.11.3 INC_U0 : 0x68

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU0, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.11.4 INC_U1 : 0x69

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU1, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.11.5 INC_U2 : 0x6a

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU2, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.11.6 INC_U3 : 0x6b

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outU3, enableInc, loadALU | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.11.7 INC_mem : 0x6c

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 4. outRAM, enableInc, loadALU |
| 2. outRAM, loadMemAddr, incPC | 5. outALU, storeRAM |
| 3. outMemAddr, loadRAM | 6. clearMIconter |

3.12 JMP

3.12.1 JMP_const : 0x6d

Micro-instructions :

- | | |
|--------------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadPC, cond_always | |

3.12.2 JMP__if__eq : 0x6e

Micro-instructions :

- | | |
|-------------------|------------------------------|
| 1. outPC, loadRAM | 3. outRAM, loadPC, cond_null |
| 2. incPC | 4. clearMIconter |

3.12.3 JMP__if__ge : 0x6f

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outPC, loadRAM | cond_null |
| 2. incPC | |
| 3. outRAM, loadPC, cond_pos, | 4. clearMIconter |

3.12.4 JMP__if__gt : 0x70

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outPC, loadRAM | cond_not_null |
| 2. incPC | |
| 3. outRAM, loadPC, cond_pos, | 4. clearMIconter |

3.12.5 JMP__if__le : 0x71

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outPC, loadRAM | cond_null |
| 2. incPC | |
| 3. outRAM, loadPC, cond_neg, | 4. clearMIconter |

3.12.6 JMP__if__lt : 0x72

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. outPC, loadRAM | cond_not_null |
| 2. incPC | |
| 3. outRAM, loadPC, cond_neg, | 4. clearMIconter |

3.12.7 JMP__if__neq : 0x73

Micro-instructions :

- | | |
|-------------------------------|------------------|
| 1. outPC, loadRAM | invert_cond |
| 2. incPC | |
| 3. outRAM, loadPC, cond_null, | 4. clearMIconter |

3.12.8 JMP__not_sel_bit_0 : 0x74

Micro-instructions :

- | | |
|---------------------------------------|------------------|
| 1. outPC, loadRAM | invert_cond |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.9 JMP__not_sel_bit_1 : 0x75

Micro-instructions :

- | | |
|---------------------------------------|------------------------|
| 1. outPC, loadRAM | invert_cond, selector0 |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.10 JMP__not_sel_bit_2 : 0x76

Micro-instructions :

- | | |
|---------------------------------------|------------------------|
| 1. outPC, loadRAM | invert_cond, selector1 |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.11 JMP__not_sel_bit_3 : 0x77

Micro-instructions :

- | | | |
|---------------------------------------|------------------|------------|
| 1. outPC, loadRAM | invert_cond, | selector0, |
| 2. incPC | selector1 | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter | |

3.12.12 JMP__not_sel_bit_4 : 0x78

Micro-instructions :

- | | |
|---------------------------------------|------------------------|
| 1. outPC, loadRAM | invert_cond, selector2 |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.13 JMP__not_sel_bit_5 : 0x79

Micro-instructions :

- | | | |
|---------------------------------------|------------------|------------|
| 1. outPC, loadRAM | invert_cond, | selector0, |
| 2. incPC | selector2 | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter | |

3.12.14 JMP__not_sel_bit_6 : 0x7a

Micro-instructions :

- | | | |
|---------------------------------------|------------------|------------|
| 1. outPC, loadRAM | invert_cond, | selector1, |
| 2. incPC | selector2 | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter | |

3.12.15 JMP__not_sel_bit_7 : 0x7b

Micro-instructions :

- | | | |
|---------------------------------------|----------------------|------------|
| 1. outPC, loadRAM | invert_cond, | selector0, |
| 2. incPC | selector1, selector2 | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter | |

3.12.16 JMP_ptr : 0x7c

Micro-instructions :

- | | |
|------------------------|--------------------------------|
| 1. outPC, loadRAM | 4. outRAM, loadPC, cond_always |
| 2. outRAM, loadMemAddr | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.12.17 JMP_sel_bit_0 : 0x7d

Micro-instructions :

- | | |
|-------------------|--------------------------------------|
| 1. outPC, loadRAM | 3. outRAM, loadPC, cond_selected_bit |
| 2. incPC | 4. clearMIconter |

3.12.18 JMP_sel_bit_1 : 0x7e

Micro-instructions :

- | | |
|---------------------------------------|------------------|
| 1. outPC, loadRAM | selector0 |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.19 JMP_sel_bit_2 : 0x7f

Micro-instructions :

- | | |
|---------------------------------------|------------------|
| 1. outPC, loadRAM | selector1 |
| 2. incPC | |
| 3. outRAM, loadPC, cond_selected_bit, | 4. clearMIconter |

3.12.20 JMP_sel_bit_3 : 0x80

Micro-instructions :

1. outPC, loadRAM selector0, selector1
2. incPC
3. outRAM, loadPC, cond_selected_bit, 4. clearMIconter

3.12.21 JMP_sel_bit_4 : 0x81

Micro-instructions :

1. outPC, loadRAM selector2
2. incPC
3. outRAM, loadPC, cond_selected_bit, 4. clearMIconter

3.12.22 JMP_sel_bit_5 : 0x82

Micro-instructions :

1. outPC, loadRAM selector0, selector2
2. incPC
3. outRAM, loadPC, cond_selected_bit, 4. clearMIconter

3.12.23 JMP_sel_bit_6 : 0x83

Micro-instructions :

1. outPC, loadRAM selector1, selector2
2. incPC
3. outRAM, loadPC, cond_selected_bit, 4. clearMIconter

3.12.24 JMP_sel_bit_7 : 0x84

Micro-instructions :

1. outPC, loadRAM selector0, selector1, selector2
2. incPC
3. outRAM, loadPC, cond_selected_bit, 4. clearMIconter

3.13 LED

3.13.1 LED_tgl : 0x85

Micro-instructions :

1. flipLed
2. clearMIconter

3.14 LOAD

3.14.1 LOAD__const__to__A : 0x86

Micro-instructions :

- | | |
|-------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadA, incPC | |

3.14.2 LOAD__const__to__B : 0x87

Micro-instructions :

- | | |
|-------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadB, incPC | |

3.14.3 LOAD__const__to__U0 : 0x88

Micro-instructions :

- | | |
|--------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadU0, incPC | |

3.14.4 LOAD__const__to__U1 : 0x89

Micro-instructions :

- | | |
|--------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadU1, incPC | |

3.14.5 LOAD__const__to__U2 : 0x8a

Micro-instructions :

- | | |
|--------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadU2, incPC | |

3.14.6 LOAD__const__to__U3 : 0x8b

Micro-instructions :

- | | |
|--------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadU3, incPC | |

3.14.7 LOAD_ptr_to_A : 0x8c

Micro-instructions :

- | | |
|-------------------------------|------------------|
| 1. outPC, loadRAM | 4. outRAM, loadA |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.14.8 LOAD_ptr_to_B : 0x8d

Micro-instructions :

- | | |
|-------------------------------|------------------|
| 1. outPC, loadRAM | 4. outRAM, loadB |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.14.9 LOAD_ptr_to_U0 : 0x8e

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outRAM, loadU0 |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.14.10 LOAD_ptr_to_U1 : 0x8f

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outRAM, loadU1 |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.14.11 LOAD_ptr_to_U2 : 0x90

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outRAM, loadU2 |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.14.12 LOAD_ptr_to_U3 : 0x91

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 4. outRAM, loadU3 |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outMemAddr, loadRAM | 5. clearMIconter |

3.15 NEG

3.15.1 NEG__A : 0x92

Micro-instructions :

- | | |
|-------------------------------|------------------|
| 1. outA, enableNOT, loadALU | 3. outALU, loadA |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.2 NEG__B : 0x93

Micro-instructions :

- | | |
|-------------------------------|------------------|
| 1. outB, enableNOT, loadALU | 3. outALU, loadB |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.3 NEG__U0 : 0x94

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outU0, enableNOT, loadALU | 3. outALU, loadU0 |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.4 NEG__U1 : 0x95

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outU1, enableNOT, loadALU | 3. outALU, loadU1 |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.5 NEG__U2 : 0x96

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outU2, enableNOT, loadALU | 3. outALU, loadU2 |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.6 NEG__U3 : 0x97

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outU3, enableNOT, loadALU | 3. outALU, loadU3 |
| 2. outALU, enableInc, loadALU | 4. clearMIconter |

3.15.7 NEG__mem : 0x98

Micro-instructions :

- | | |
|-------------------------------|-------------------------------|
| 1. outPC, loadRAM | 5. outALU, enableInc, loadALU |
| 2. outRAM, loadMemAddr | 6. outALU, storeRAM |
| 3. outMemAddr, loadRAM, incPC | 7. clearMIconter |
| 4. outRAM, enableNOT, loadALU | |

3.16 NOP

3.16.1 NOP : 0x99

Micro-instructions :

1. clearMIconter

3.17 NOT

3.17.1 NOT__A : 0x9a

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableNOT, loadALU, outA | 3. clearMIconter |
| 2. outALU, loadA | |

3.17.2 NOT__B : 0x9b

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableNOT, loadALU, outB | 3. clearMIconter |
| 2. outALU, loadB | |

3.17.3 NOT__U0 : 0x9c

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableNOT, loadALU, outU0 | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.17.4 NOT__U1 : 0x9d

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableNOT, loadALU, outU1 | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.17.5 NOT_U2 : 0x9e

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableNOT, loadALU, outU2 | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.17.6 NOT_U3 : 0x9f

Micro-instructions :

- | | |
|------------------------------|------------------|
| 1. enableNOT, loadALU, outU3 | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.18 OR

3.18.1 OR_A_B_to_itself : 0xa0

Micro-instructions :

- | | |
|----------------------------|------------------|
| 1. enableOR, loadALU, outA | 3. clearMIconter |
| 2. outALU, loadA | |

3.18.2 OR_U0_B_to_itself : 0xa1

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableOR, loadALU, outU0 | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.18.3 OR_U1_B_to_itself : 0xa2

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableOR, loadALU, outU1 | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.18.4 OR_U2_B_to_itself : 0xa3

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableOR, loadALU, outU2 | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.18.5 OR_U3_B_to_itself : 0xa4

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. enableOR, loadALU, outU3 | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.19 RET

3.19.1 RET : 0xa5

Micro-instructions :

- | | |
|------------------------|--------------------------------|
| 1. decRet | 3. outRAM, loadPC, cond_always |
| 2. outRetAddr, loadRAM | 4. clearMIconter |

3.20 SHIFTL

3.20.1 SHIFTL_A : 0xa6

Micro-instructions :

- | | |
|--------------------------------|------------------|
| 1. outA, enableSHIFTL, loadALU | 3. clearMIconter |
| 2. outALU, loadA | |

3.20.2 SHIFTL_B : 0xa7

Micro-instructions :

- | | |
|--------------------------------|------------------|
| 1. outB, enableSHIFTL, loadALU | 3. clearMIconter |
| 2. outALU, loadB | |

3.20.3 SHIFTL_U0 : 0xa8

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU0, enableSHIFTL, loadALU | 3. clearMIconter |
| 2. outALU, loadU0 | |

3.20.4 SHIFTL_U1 : 0xa9

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU1, enableSHIFTL, loadALU | 3. clearMIconter |
| 2. outALU, loadU1 | |

3.20.5 SHIFTL_U2 : 0xaa

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU2, enableSHIFTL, loadALU | 3. clearMCounter |
| 2. outALU, loadU2 | |

3.20.6 SHIFTL_U3 : 0xab

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU3, enableSHIFTL, loadALU | 3. clearMCounter |
| 2. outALU, loadU3 | |

3.21 SHIFTR

3.21.1 SHIFTR_A : 0xac

Micro-instructions :

- | | |
|--------------------------------|------------------|
| 1. outA, enableSHIFTR, loadALU | 3. clearMCounter |
| 2. outALU, loadA | |

3.21.2 SHIFTR_B : 0xad

Micro-instructions :

- | | |
|--------------------------------|------------------|
| 1. outB, enableSHIFTR, loadALU | 3. clearMCounter |
| 2. outALU, loadB | |

3.21.3 SHIFTR_U0 : 0xae

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU0, enableSHIFTR, loadALU | 3. clearMCounter |
| 2. outALU, loadU0 | |

3.21.4 SHIFTR_U1 : 0xaf

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU1, enableSHIFTR, loadALU | 3. clearMCounter |
| 2. outALU, loadU1 | |

3.21.5 SHIFTR__U2 : 0xb0

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU2, enableSHIFTR, loadALU | 3. clearMIconter |
| 2. outALU, loadU2 | |

3.21.6 SHIFTR__U3 : 0xb1

Micro-instructions :

- | | |
|---------------------------------|------------------|
| 1. outU3, enableSHIFTR, loadALU | 3. clearMIconter |
| 2. outALU, loadU3 | |

3.22 SLEEP

3.22.1 SLEEP__A : 0xb2

Micro-instructions :

- | | |
|---------------------------|------------------|
| 1. outA, loadSleep, incPC | 2. clearMIconter |
|---------------------------|------------------|

3.22.2 SLEEP__B : 0xb3

Micro-instructions :

- | | |
|---------------------------|------------------|
| 1. outB, loadSleep, incPC | 2. clearMIconter |
|---------------------------|------------------|

3.22.3 SLEEP__U0 : 0xb4

Micro-instructions :

- | | |
|----------------------------|------------------|
| 1. outU0, loadSleep, incPC | 2. clearMIconter |
|----------------------------|------------------|

3.22.4 SLEEP__U1 : 0xb5

Micro-instructions :

- | | |
|----------------------------|------------------|
| 1. outU1, loadSleep, incPC | 2. clearMIconter |
|----------------------------|------------------|

3.22.5 SLEEP__U2 : 0xb6

Micro-instructions :

- | | |
|----------------------------|------------------|
| 1. outU2, loadSleep, incPC | 2. clearMIconter |
|----------------------------|------------------|

3.22.6 SLEEP__U3 : 0xb7

Micro-instructions :

- | | |
|----------------------------|------------------|
| 1. outU3, loadSleep, incPC | 2. clearMIconter |
|----------------------------|------------------|

3.22.7 SLEEP__const : 0xb8

Micro-instructions :

- | | |
|-----------------------------|------------------|
| 1. outPC, loadRAM | 3. clearMIconter |
| 2. outRAM, loadSleep, incPC | |

3.22.8 SLEEP__mem : 0xb9

Micro-instructions :

- | | |
|-------------------------------|----------------------|
| 1. outPC, loadRAM | 4. outRAM, loadSleep |
| 2. outRAM, loadMemAddr, incPC | |
| 3. loadRAM, outMemAddr | 5. clearMIconter |

3.23 STORE

3.23.1 STORE__A__to__address : 0xba

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 3. storeRAM, outA |
| 2. outRAM, loadMemAddr, incPC | 4. clearMIconter |

3.23.2 STORE__B__to__address : 0xbb

Micro-instructions :

- | | |
|-------------------------------|-------------------|
| 1. outPC, loadRAM | 3. storeRAM, outB |
| 2. outRAM, loadMemAddr, incPC | 4. clearMIconter |

3.23.3 STORE__PCp1__to__address : 0xbc

Micro-instructions :

- | | |
|-------------------------------|----------------------|
| 1. outPC, loadRAM | 3. storeRAM, outPCp1 |
| 2. outRAM, loadMemAddr, incPC | 4. clearMIconter |

3.23.4 STORE_U0_to_address : 0xbd

Micro-instructions :

- | | |
|-------------------------------|--------------------|
| 1. outPC, loadRAM | 3. storeRAM, outU0 |
| 2. outRAM, loadMemAddr, incPC | 4. clearMCounter |

3.23.5 STORE_U1_to_address : 0xbe

Micro-instructions :

- | | |
|-------------------------------|--------------------|
| 1. outPC, loadRAM | 3. storeRAM, outU1 |
| 2. outRAM, loadMemAddr, incPC | 4. clearMCounter |

3.23.6 STORE_U2_to_address : 0xbf

Micro-instructions :

- | | |
|-------------------------------|--------------------|
| 1. outPC, loadRAM | 3. storeRAM, outU2 |
| 2. outRAM, loadMemAddr, incPC | 4. clearMCounter |

3.23.7 STORE_U3_to_address : 0xc0

Micro-instructions :

- | | |
|-------------------------------|--------------------|
| 1. outPC, loadRAM | 3. storeRAM, outU3 |
| 2. outRAM, loadMemAddr, incPC | 4. clearMCounter |

3.23.8 STORE_const_to_address : 0xc1

Micro-instructions :

- | | |
|-------------------------------|----------------------------|
| 1. outPC, loadRAM | 4. storeRAM, outRAM, incPC |
| 2. outRAM, loadMemAddr, incPC | |
| 3. outPC, loadRAM | 5. clearMCounter |

3.24 SUB

3.24.1 SUB_A_to_A : 0xc2

Micro-instructions :

- | | |
|-------------------------------|-----------------------------|
| 1. outA, loadB | 5. enableAdd, loadALU, outA |
| 2. outB, enableNOT, loadALU | 6. outALU, loadA |
| 3. outALU, enableInc, loadALU | |
| 4. outALU, loadB | 7. clearMCounter |