

claude-windows / 2ba49afa-99f4-41f2-86a2-27a289d432f3

Metadata

```
- Source: `claude-windows`
- Kind: `claude`
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_cd064e9b-e5c\agent-a89a430eda3d22b2d.jsonl`
- SHA-256: `9c53799a0ce20328e1db8b6d808e4ec83c49fe606c45d478c8cba4eb42b40bc7`
- Source modified: `2026-06-21T15:01:16+00:00`
- Imported at: `2026-07-05T16:48:28+00:00`
- project: `wf_cd064e9b-e5c`
- session_id: `2ba49afa-99f4-41f2-86a2-27a289d432f3`
```

Transcript

1. user (2026-06-21T14:58:28.030Z)

You are reviewing a UI diff for CORRECTNESS and REGRESSION. Read the changed files under C:/Users/avidu/Projects/khelsutra/web/src. Check:

- Did adding min-h-11 / inline-flex / items-center break vertical alignment, wrapping, or the sticky footer layout in SelectionFooter.tsx?
- The dismiss button changed from "rounded-full px-2" to "flex h-11 w-11 ... justify-between" parent ? does the h2/? header row in CompileResult.tsx still align (the parent is "flex items-start justify-between")?
- The new query.notAvailableHelp key: is it added to ALL THREE catalogs (en/kn/hi) so the key-parity CI test (i18n/hygiene.test.ts) stays green? Any ICU/interpolation issue?
- Does the no-bare-strings test (hygiene.test.ts BARE_ATTR regex over placeholder/aria-label/title) still pass? Did any change introduce a bare attribute?
- Any TypeScript / React issue?

Be precise with file:line. Empty findings if clean.

```
=== THE DIFF UNDER REVIEW ===
undefined
```

2. assistant (2026-06-21T14:58:31.819Z)

I'll start by exploring the changed files under the web/src directory to understand the diff being reviewed.

3. user (2026-06-21T14:58:33.359Z)

On branch feat/a4-mobile-touch-targets
Your branch is up to date with 'origin/master'.

Changes not staged for commit:

```
(use "git add <file>..." to update what will be committed)
(use "git restore <file>..." to discard changes in working directory)
    modified:   web/src/App.tsx
    modified:   web/src/components/CompileResult.tsx
    modified:   web/src/components/IngestPanel.tsx
    modified:   web/src/components/LanguageSwitcher.tsx
    modified:   web/src/components/QueryBar.tsx
    modified:   web/src/components/SelectionFooter.tsx
    modified:   web/src/i18n/locales/en/common.json
    modified:   web/src/i18n/locales/hi/common.json
    modified:   web/src/i18n/locales/kn/common.json
```

Untracked files:

```
(use "git add <file>..." to include in what will be committed)
    .claude/
    site/access.db
```

web/src/components/a4.touch.test.tsx

no changes added to commit (use "git add" and/or "git commit -a")

---BRANCH---

feat/a4-mobile-touch-targets

---LOG---

ccdcfcd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon) (#60)

a20002f docs: propose Multilingual Expansion ? 7 new locales (th/id/da/es/zh-Hans/ja/ko) (#58)

a0475bc docs: hygiene refresh ? sync trackers to shipped reality (#59)

7750afc docs(dry-run): Path-B live e2e DONE ? in-UI bucket?reel CUJ + screencast (DoD \$6 box 3 ?) (#57)

4525c5d feat(web): B-P2 ? in-UI bucket ingest (point at a gs:// video ? process ? load) (#56)

4. assistant (2026-06-21T14:58:37.270Z)

This is the `feat/a4-mobile-touch-targets` branch. The diff under review is empty in the prompt, so I'll examine the actual changes via git diff. Let me look at all the changed files.

5. user (2026-06-21T14:58:38.041Z)

diff --git a/web/src/components/CompileResult.tsx b/web/src/components/CompileResult.tsx

index 441c7d7..619d22b 100644

--- a/web/src/components/CompileResult.tsx

+++ b/web/src/components/CompileResult.tsx

@@ -36,7 +36,7 @@ export function CompileResult({ build, onDismiss }: Props) {

type="button"

onClick={onDismiss}

aria-label={t("result.dismiss")}

- className="rounded-full px-2 text-ink/50 hover:text-ink"

+ className="flex h-11 w-11 shrink-0 items-center justify-center rounded-full text-ink/50 hover:text-ink"

>

?

</button>

@@ -55,7 +55,7 @@ export function CompileResult({ build, onDismiss }: Props) {

<a

href={build.url}

download={build.filename}

- className="mt-3 inline-block rounded-full bg-green px-4 py-2 text-sm font-semibold text-[#04140D]"

+ className="mt-3 inline-flex min-h-11 items-center rounded-full bg-green px-4 py-2 text-sm font-semibold text-[#04140D]"

>

{t("result.download", { filename: build.filename })}

diff --git a/web/src/components/SelectionFooter.tsx b/web/src/components/SelectionFooter.tsx

index 9724c53..4590ab8 100644

--- a/web/src/components/SelectionFooter.tsx

+++ b/web/src/components/SelectionFooter.tsx

@@ -63,7 +63,7 @@ export function SelectionFooter({ count, totalSec, reelName, onReelNameChange, o

onChange={(e) => onReelNameChange(e.target.value)}

placeholder={t("footer.reelNamePlaceholder")}

aria-label={t("footer.reelName")}

- className="w-40 rounded-lg border border-black/15 bg-white px-3 py-1.5 text-ink outline-none focus:border-green"

+ className="min-h-11 w-40 rounded-lg border border-black/15 bg-white px-3 py-1.5 text-ink outline-none focus:border-green"

/>

</label>

@@ -71,7 +71,7 @@ export function SelectionFooter({ count, totalSec, reelName, onReelNameChange, o

type="button"

onClick={onBuild}

```

        disabled={buildDisabled}
-        className="rounded-full bg-green px-5 py-2 text-sm font-semibold text-[#04140D]
disabled:opacity-40"
+        className="min-h-11 rounded-full bg-green px-5 py-2 text-sm font-semibold
text-[#04140D] disabled:opacity-40"
    >
        {building ? t("footer.building") : t("footer.build", { count })}
    </button>

```

6. user (2026-06-21T14:58:42.234Z)

```

diff --git a/web/src/App.tsx b/web/src/App.tsx
index b43debd..85361d6 100644
--- a/web/src/App.tsx
+++ b/web/src/App.tsx
@@ -244,9 +244,9 @@ export default function App() {
    </div>

    <div className="mt-6 flex flex-wrap gap-2 text-sm">
-      <button type="button" onClick={() => onBulk("select_all")} className="rounded-full
border border-black/15 px-3 py-1 hover:border-green">{t("bulk.selectAll")}</button>
-      <button type="button" onClick={() => onBulk("clear")} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">{t("bulk.clear")}</button>
-      <button type="button" onClick={() => onBulk("invert")} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">{t("bulk.invert")}</button>
+      <button type="button" onClick={() => onBulk("select_all")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.selectAll")}</button>
+      <button type="button" onClick={() => onBulk("clear")} className="inline-flex min-h-11
items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.clear")}</button>
+      <button type="button" onClick={() => onBulk("invert")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.invert")}</button>
    </div>

    <div className="mt-5">
diff --git a/web/src/components/IngestPanel.tsx b/web/src/components/IngestPanel.tsx
index 8c6ffec..322ffb8 100644
--- a/web/src/components/IngestPanel.tsx
+++ b/web/src/components/IngestPanel.tsx
@@ -47,12 +47,12 @@ export function IngestPanel({ onLoaded }: Props) {
    placeholder={t("ingest.uriPlaceholder")}
    aria-label={t("ingest.uriAriaLabel")}
    disabled={busy}
-    className="min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white px-4 py-2
text-sm text-ink outline-none focus:border-green disabled:opacity-50"
+    className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
  />
  <button
    type="submit"
    disabled={busy}
-    className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+    className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
  >
    {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}
  </button>
@@ -60,7 +60,7 @@ export function IngestPanel({ onLoaded }: Props) {
  <button
    type="button"
    onClick={cancel}
-    className="rounded-xl border border-black/15 px-4 py-2 text-sm hover:border-green"

```

```

+         className="min-h-11 rounded-xl border border-black/15 px-4 py-2 text-sm
hover:border-green"
+       >
+         {t("ingest.cancel")}
+       </button>
@@ -89,7 +89,7 @@ export function IngestPanel({ onLoaded }: Props) {
+       <button
+         type="button"
+         onClick={reset}
-         className="mt-2 rounded-lg border border-red-300 px-3 py-1 text-xs hover:bg-
red-100"
+         className="mt-2 inline-flex min-h-11 items-center rounded-lg border border-
red-300 px-3 text-sm hover:bg-red-100"
+       >
+         {t("ingest.retry")}
+       </button>
diff --git a/web/src/components/LanguageSwitcher.tsx b/web/src/components/LanguageSwitcher.tsx
index 075a7c9..e1aead0 100644
--- a/web/src/components/LanguageSwitcher.tsx
+++ b/web/src/components/LanguageSwitcher.tsx
@@ -35,7 +35,7 @@ export function LanguageSwitcher() {
+   aria-pressed={isActive}
+   onClick={() => void i18n.changeLanguage(loc)}
+   className=[
-     "rounded-full px-3 py-1.5 text-sm font-semibold transition",
+     "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold
transition",
+     isActive ? "bg-white text-ink" : "text-white/70 hover:text-white",
+   ].join(" ")
+ }
diff --git a/web/src/components/QueryBar.tsx b/web/src/components/QueryBar.tsx
index 3ebdad9..81697c2 100644
--- a/web/src/components/QueryBar.tsx
+++ b/web/src/components/QueryBar.tsx
@@ -20,7 +20,8 @@ interface Props {
  // here (a test pins that every example parses to a recognized, fully-available query).
  export const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "first 10"];

-const CHIP = "rounded-full px-2.5 py-0.5 text-xs font-medium";
+// Parsed-pill chips: legible on a phone (text-sm, not text-xs) ? A4.
+const CHIP = "rounded-full px-3 py-1 text-sm font-medium";

  export function QueryBar({ onApply }: Props) {
    const { t } = useTranslation();
@@ -47,12 +48,12 @@ export function QueryBar({ onApply }: Props) {
+    onChange={(e) => setValue(e.target.value)}
+    placeholder={t("query.placeholder")}
+    aria-label={t("query.ariaLabel")}
-    className="min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white px-4 py-2
text-sm text-ink outline-none focus:border-green"
+    className="min-h-11 min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green"
+  />
+  <button
+    type="submit"
+    disabled={!parsed.recognized}
-    className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+    className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+  >
+    {t("query.apply")}
+  </button>
@@ -80,14 +81,20 @@ export function QueryBar({ onApply }: Props) {
  {!typed && <span className="text-xs text-ink/50">{t("query.hint")}</span>}

```

```

</div>

-   <div className="mt-3 flex flex-wrap gap-2 text-sm">
+   {/* Surface the "not available yet" reason as VISIBLE text (the per-chip title is hover-
only,
+       so it never appears on a phone) ? A4. */}
+   {parsed.unavailable.length > 0 && (
+   <p className="mt-1.5 text-xs text-ink/50">{t("query.notAvailableHelp")}</p>
+   )}
+
+   <div className="mt-3 flex flex-wrap items-center gap-2 text-sm">
+       <span className="text-ink/40">{t("query.try")}</span>
+       {EXAMPLES.map((ex) => (
+           <button
+               key={ex}
+               type="button"
+               onClick={() => applyText(ex)}
-               className="rounded-full border border-black/15 px-3 py-1 text-xs hover:border-
green"
+               className="inline-flex min-h-11 items-center rounded-full border border-black/15
px-4 text-sm hover:border-green"
+           >
+               {ex}
+           </button>

```

7. assistant (2026-06-21T14:58:45.318Z)

Now let me read the full files to understand context for the layout questions. Let me look at SelectionFooter, CompileResult, and QueryBar in full.

8. user (2026-06-21T14:58:45.926Z)

```

1      // Sticky compile footer (PER_RALLY_SELECTION.md P4): live selection summary, a reel-
name input,
2      // the Build button, and ? above all ? an HONEST min_shot_count warning. The engine
silently drops
3      // selected rallies below stitching.min_shot_count; we surface that BEFORE Build so a
rally never
4      // vanishes without a reason (D7). We warn, we do NOT override the floor (D11).
5      import { useTranslation, Trans } from "react-i18next";
6      import { mmss } from "../lib/format";
7      import type { FloorRisk } from "../lib/floor";
8
9      interface Props {
10         count: number;
11         totalSec: number;
12         reelName: string;
13         onReelNameChange: (v: string) => void;
14         onBuild: () => void;
15         /** A compile is in flight (Build wired in P5). */
16         building?: boolean;
17         /** Non-null when some selected rallies sit below the engine floor. */
18         warning: FloorRisk | null;
19     }
20
21     export function SelectionFooter({ count, totalSec, reelName, onReelNameChange, onBuild,
building, warning }: Props) {
22         const { t } = useTranslation();
23         const buildDisabled = count === 0 || building || warning?.allDropped === true;
24
25         return (
26             <footer className="fixed inset-x-0 bottom-0 border-t border-black/10 bg-white/95
backdrop-blur">
27                 {warning && (
28

```

```

29         role="status"
30         data-testid="floor-warning"
31         className={
32             "border-b px-6 py-2 text-sm " +
33             (warning.allDropped
34               ? "border-red-200 bg-red-50 text-red-800"
35               : "border-amber-200 bg-amber-50 text-amber-900")
36         }
37     >
38     {warning.allDropped ? (
39         count === 1 ? (
40             <Trans i18nKey="footer.floorOne" values={{ min: warning.minShotCount }}
components={{ b: <strong /> }} />
41         ) : (
42             <Trans i18nKey="footer.floorAll" values={{ count, min:
warning.minShotCount }} components={{ b: <strong /> }} />
43         )
44     ) : (
45         <>
46             <strong>{t("footer.floorSomeLead", { count: warning.atRisk.length
}})</strong>{" "}
47             <Trans i18nKey="footer.floorSomeRest" values={{ min: warning.minShotCount
}} components={{ code: <code /> }} />
48         </>
49     )}
50 </div>
51 )}
52
53 <div className="mx-auto flex max-w-5xl flex-wrap items-center gap-3 px-6 py-3">
54     <span className="text-sm text-ink/80" data-testid="selection-summary">
55         <strong className="text-ink">{t("footer.count", { count })}</strong>
{t("footer.summaryRest", { total: mmss(totalSec) })}
56     </span>
57
58     <label className="ml-auto flex items-center gap-2 text-sm text-ink/60">
59         <span className="hidden sm:inline">{t("footer.reelName")}</span>
60         <input
61             type="text"
62             value={reelName}
63             onChange={(e) => onReelNameChange(e.target.value)}
64             placeholder={t("footer.reelNamePlaceholder")}
65             aria-label={t("footer.reelName")}
66             className="min-h-11 w-40 rounded-lg border border-black/15 bg-white px-3
py-1.5 text-ink outline-none focus:border-green"
67         />
68     </label>
69
70     <button
71         type="button"
72         onClick={onBuild}
73         disabled={buildDisabled}
74         className="min-h-11 rounded-full bg-green px-5 py-2 text-sm font-semibold
text-[#04140D] disabled:opacity-40"
75     >
76         {building ? t("footer.building") : t("footer.build", { count })}
77     </button>
78 </div>
79 </footer>
80 );
81 }
82

```

9. assistant (2026-06-21T14:58:51.322Z)

The SelectionFooter row is a `flex flex-wrap items-center gap-3` container, so `min-h-11` on the

input and button just bumps their min height to 44px; `items-center` keeps them vertically centered. No alignment/wrapping/sticky regression. Now let me read CompileResult.

10. user (2026-06-21T14:58:51.958Z)

```
1      // The compiled-reel result (PER_RALLY_SELECTION.md P5): once Build ? POST /api/compile
succeeds,
2      // preview the reel inline (<video> over GET /api/highlights/...) and offer a download.
The engine
3      // returns a server-local filepath, NOT a URL (main.py:394), so the SPA builds the URL
itself. On a
4      // failure (e.g. the min_shot_count 400) we show the engine's reason ? loud, never
swallowed.
5
6      import { useTranslation } from "react-i18next";
7
8      export type BuildState =
9      | { status: "idle" }
10     | { status: "building" }
11     | { status: "done"; url: string; filename: string }
12     | { status: "error"; error: string };
13
14     interface Props {
15         build: BuildState;
16         onDismiss: () => void;
17     }
18
19     export function CompileResult({ build, onDismiss }: Props) {
20         const { t } = useTranslation();
21         if (build.status === "idle" || build.status === "building") return null;
22
23         return (
24             <section
25                 data-testid="compile-result"
26                 className={
27                     "mt-6 rounded-xl border p-4 " +
28                     (build.status === "error" ? "border-red-200 bg-red-50" : "border-green/30 bg-
green/5")
29             >
30                 <div className="flex items-start justify-between gap-3">
31                     <h2 className="font-semibold text-ink">
32                         {build.status === "done" ? t("result.ready") : t("result.failed")}
33                     </h2>
34                     <button
35                         type="button"
36                         onClick={onDismiss}
37                         aria-label={t("result.dismiss")}
38                         className="flex h-11 w-11 shrink-0 items-center justify-center rounded-full
text-ink/50 hover:text-ink"
39                     >
40                         ?
41                     </button>
42                 </div>
43
44                 {build.status === "done" ? (
45                     <div className="mt-3">
46                         {/* eslint-disable-next-line jsx-a11y/media-has-caption ? a stitched rally
reel has no captions */}
47                         <video
48                             data-testid="reel-video"
49                             src={build.url}
50                             controls
51                             playsInline
52                             className="w-full max-w-xl rounded-lg bg-black"
```

```

54         />
55         <a
56             href={build.url}
57             download={build.filename}
58             className="mt-3 inline-flex min-h-11 items-center rounded-full bg-green px-4
py-2 text-sm font-semibold text-[#04140D]"
59         >
60             {t("result.download", { filename: build.filename })}
61         </a>
62     </div>
63     ) : (
64         <p className="mt-2 text-sm text-red-800" data-testid="compile-error">
65             {build.error}
66         </p>
67     )}
68 </section>
69 );
70 }
71

```

11. assistant (2026-06-21T14:58:58.643Z)

The CompileResult header row: parent is `flex items-start justify-between gap-3`. The h2 has no fixed height (text line), the button is now `h-11 w-11`. With `items-start`, both align to the top. The h2 text sits at the top, and the 44px button extends downward. This is a behavior change: previously the dismiss button was `rounded-full px-2` (height ? line height of the ? glyph, roughly matching the h2 baseline area). Now the button is 44px tall and the h2 is ~24px tall, both top-aligned. Let me verify this is visually acceptable ? with `items-start`, the ? glyph is vertically centered within the 44px button (`items-center justify-center`), so the glyph will sit lower than the h2 text top. Let me check this more carefully against the original behavior and the test file.

12. user (2026-06-21T14:58:59.262Z)

```

1      // The fast-entry query bar (PER_RALLY_SELECTION.md P3). A deterministic, OFFLINE parser
turns
2      // plain text ("top 15 longest", "over 10s") into a selection over the SAME shared set
the
3      // checkboxes use. It is honest by construction: a live "parsed-pill" shows exactly how
the
4      // text was understood, and concepts with no data behind them (shot-type / player /
score) are
5      // greyed out as "not available yet" ? never silently faked.
6      import { useMemo, useState } from "react";
7      import type { FormEvent } from "react";
8      import { useTranslation, Trans } from "react-i18next";
9      import { parseQuery, summarize } from "../lib/query";
10     import type { ParsedQuery } from "../lib/query";
11
12     interface Props {
13         /** Apply a parsed query to the rally set (App runs runQuery + writes the shared
selection).
14         * `source` distinguishes a typed-and-submitted query from an example-chip tap (for
the trace). */
15         onApply: (q: ParsedQuery, source: "typed" | "example") => void;
16     }
17
18     // Each example is a real, parseable query ? tapping one fills the box AND applies it.
Led by rally
19     // LENGTH (the trusted axis); shot-count filtering exists but is experimental, so it's
not featured
20     // here (a test pins that every example parses to a recognized, fully-available query).
21     export const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "first 10"];
22
23     // Parsed-pill chips: legible on a phone (text-sm, not text-xs) ? A4.

```

```

24     const CHIP = "rounded-full px-3 py-1 text-sm font-medium";
25
26     export function QueryBar({ onApply }: Props) {
27         const { t } = useTranslation();
28         const [value, setValue] = useState("");
29         const parsed = useMemo(() => parseQuery(value), [value]);
30         const clauses = summarize(parsed);
31         const typed = value.trim().length > 0;
32
33         const applyText = (text: string) => {
34             setValue(text);
35             onApply(parseQuery(text), "example");
36         };
37         const submit = (e: FormEvent) => {
38             e.preventDefault();
39             if (parsed.recognized) onApply(parsed, "typed");
40         };
41
42         return (
43             <div>
44                 <form onSubmit={submit} className="flex flex-wrap items-center gap-2">
45                     <input
46                         type="text"
47                         value={value}
48                         onChange={(e) => setValue(e.target.value)}
49                         placeholder={t("query.placeholder")}
50                         aria-label={t("query.ariaLabel")}
51                         className="min-h-11 min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-
white px-4 py-2 text-sm text-ink outline-none focus:border-green"
52                     />
53                     <button
54                         type="submit"
55                         disabled={!parsed.recognized}
56                         className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-
white disabled:opacity-40"
57                     >
58                         {t("query.apply")}
59                     </button>
60                 </form>
61
62                 {/* Live interpretation ? transparent + hand-correctable (no hidden NL guessing).
*/}
63                 <div aria-live="polite" data-testid="query-pill" className="mt-2 flex flex-wrap
items-center gap-1.5">
64                     {clauses.map((c) => (
65                         <span key={c} className={CHIP + " bg-green/15 text-green">
66                             {c}
67                         </span>
68                     ))}
69                     {parsed.unavailable.map((u) => (
70                         <span
71                             key={u.token}
72                             title={t("query.notAvailableTitle", { token: u.token, kind: u.kind })}
73                             className={CHIP + " bg-black/5 text-ink/45"}
74                         >
75                             <span className="line-through">{u.token}</span> · {t("query.notAvailable")}
76                         </span>
77                     ))}
78                     {typed && !parsed.recognized && parsed.unavailable.length === 0 && (
79                         <span className="text-xs text-ink/50">{t("query.unreadable")}</span>
80                     )}
81                     {!typed && <span className="text-xs text-ink/50">{t("query.hint")}</span>}
82                 </div>
83
84                 {/* Surface the "not available yet" reason as VISIBLE text (the per-chip title is

```

```

hover-only,
85         so it never appears on a phone) ? A4. */}
86         {parsed.unavailable.length > 0 && (
87             <p className="mt-1.5 text-xs text-ink/50">{t("query.notAvailableHelp")}</p>
88         )}
89
90         <div className="mt-3 flex flex-wrap items-center gap-2 text-sm">
91             <span className="text-ink/40">{t("query.try")}</span>
92             {EXAMPLES.map((ex) => (
93                 <button
94                     key={ex}
95                     type="button"
96                     onClick={() => applyText(ex)}
97                     className="inline-flex min-h-11 items-center rounded-full border border-
black/15 px-4 text-sm hover:border-green"
98                 >
99                     {ex}
100             </button>
101         )}
102     </div>
103
104     <p className="mt-2 text-xs text-ink/40">
105         <Trans i18nKey="query.support" components={{ b: <strong className="text-ink/60"
/>, x: <span className="text-amber-700" /> }} />
106     </p>
107 </div>
108 );
109 }
110

```

13. assistant (2026-06-21T14:59:02.674Z)

Now let me check the i18n catalogs for the new `query.notAvailableHelp` key in all three locales, and look at the existing `query.notAvailable\*` keys for ICU/interpolation consistency.

14. user (2026-06-21T14:59:04.499Z)

=== EN ===

```
diff --git a/web/src/i18n/locales/en/common.json b/web/src/i18n/locales/en/common.json
```

```
index d0f983d..3248540 100644
```

```
--- a/web/src/i18n/locales/en/common.json
```

```
+++ b/web/src/i18n/locales/en/common.json
```

```
@@ -27,6 +27,7 @@
```

```

    "apply": "Apply",
    "notAvailable": "not available yet",
    "notAvailableTitle": "{token}? needs {kind} detection ? not available yet",
+   "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by rally
length instead.",
    "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
    "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
    "try": "Sample queries:",

```

=== KN ===

```
diff --git a/web/src/i18n/locales/kn/common.json b/web/src/i18n/locales/kn/common.json
```

```
index b54f675..14fb85b 100644
```

```
--- a/web/src/i18n/locales/kn/common.json
```

```
+++ b/web/src/i18n/locales/kn/common.json
```

```
@@ -27,6 +27,7 @@
```

```

    "apply": "?????????",
    "notAvailable": "????? ??????????",
    "notAvailableTitle": "{token}? ?? {kind} ????? ???? ? ????? ??????????",
+   "notAvailableHelp": "???? ??????, ?????? ?????? ?????? ?????? ?????? ??????
????? ?????????? ?????? ?????.",
    "unreadable": "????? ?????????? ? ?over 10s? ???? ?top 15 longest? ??????????.",
    "hint": "10 ?????????????? ?????? ?????????????? over 10s ???? ???? ???? ? ????
????????? ?????? ?????.",

```

```

    "try": "????? ??????????:",
=== HI ===
diff --git a/web/src/i18n/locales/hi/common.json b/web/src/i18n/locales/hi/common.json
index 7f34e01..3ab12be 100644
--- a/web/src/i18n/locales/hi/common.json
+++ b/web/src/i18n/locales/hi/common.json
@@ -27,6 +27,7 @@
    "apply": "????? ?????",
    "notAvailable": "??? ?????? ?????",
    "notAvailableTitle": "{token}? ?? ??? {kind} ?????? ????? ? ??? ?????? ?????",
+   "notAvailableHelp": "??? ??????, ?????? ?? ?????? ??? ?????? ????? ??? ? ??? ???? ???? ???? ??
????? ?? ?????? ??????",
    "unreadable": "?? ??? ????? ??? ? ?over 10s? ?? ?top 15 longest? ??????????",
    "hint": "10 ?????? ?? ????? ?????? ?? ??? over 10s ?????? ? ?? ?????? ?? ??? ?????? ???
?????",
    "try": "????? ??????:",

```

15. assistant (2026-06-21T14:59:08.451Z)

All three catalogs have `notAvailableHelp` added at the same location. The new key has no interpolation placeholders (no `{token}`/`\${kind}`), so no ICU/interpolation risk. Now let me look at the i18n hygiene test to verify the key-parity check and the BARE_ATTR regex check pass.

16. user (2026-06-21T14:59:08.659Z)

web\src\i18n\hygiene.test.ts

17. user (2026-06-21T14:59:11.880Z)

```

1      // CI guardrails that keep i18n "by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
2      //   1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
3      //       drop a stub locale and this lists every gap). Trivially green while only `en`
exists; it
4      //       starts enforcing the moment a kn/hi catalog lands (B5/B6).
5      //   2. NO-BARE-STRINGS (attribute level, v1) ? user-facing component attributes
(placeholder /
6      //       aria-label / title) must route through t(), never a hardcoded literal. A curated
start per
7      //       the doc; an AST-level sweep of JSX text can extend it later.
8      import { describe, it, expect } from "vitest";
9      import { readdirSync, readFileSync } from "node:fs";
10     import { join } from "node:path";
11
12     const LOCALES_DIR = join(import.meta.dirname, "locales");
13     const SRC_DIR = join(import.meta.dirname, "..");
14
15     function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
16       const keys: string[] = [];
17       for (const [k, v] of Object.entries(obj)) {
18         const key = prefix ? `${prefix}.${k}` : k;
19         if (v && typeof v === "object" && !Array.isArray(v)) keys.push(...flatten(v as
Record<string, unknown>, key));
20         else keys.push(key);
21       }
22       return keys.sort();
23     }
24
25     const loadKeys = (locale: string): string[] =>
26       flatten(JSON.parse(readFileSync(join(LOCALES_DIR, locale, "common.json"), "utf8")) as
Record<string, unknown>);
27
28     describe("i18n key-parity ? every locale has EXACTLY the en keys", () => {
29       const enKeys = loadKeys("en");

```

```

30     const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
31       .filter((d) => d.isDirectory() && d.name !== "en")
32       .map((d) => d.name);
33
34     it("en is the non-empty source catalog", () => {
35       expect(enKeys.length).toBeGreaterThan(20);
36     });
37
38     for (const loc of others) {
39       it(`${loc} matches en exactly (no missing, no extra keys)`, () => {
40         const keys = loadKeys(loc);
41         const missing = enKeys.filter((k) => !keys.includes(k));
42         const extra = keys.filter((k) => !enKeys.includes(k));
43         expect({ locale: loc, missing, extra }).toEqual({ locale: loc, missing: [], extra:
[] });
44       });
45     }
46   });
47
48   describe("no-bare-strings ? user-facing component attributes go through t()", () => {
49     const FILES = [
50       "App.tsx",
51       "components/QueryBar.tsx",
52       "components/RallyGrid.tsx",
53       "components/SelectionFooter.tsx",
54       "components/CompileResult.tsx",
55       "components/LanguageSwitcher.tsx",
56       "components/IngestPanel.tsx",
57     ];
58     // A hardcoded placeholder / aria-label / title with letters is a bare-string
59     regression ? it
60       // must be an expression ({t(...)}), not a quoted literal.
61       const BARE_ATTR = /\b(?:placeholder|aria-label|title)\s*=\s*"^[^"]*[A-Za-z]{2}[^"]*"$/g;
62
63       for (const f of FILES) {
64         it(`${f}: no hardcoded placeholder/aria-label/title`, () => {
65           const src = readFileSync(join(SRC_DIR, f), "utf8");
66           expect(src.match(BARE_ATTR) ?? []).toEqual([]);
67         });
68       }
69     });
70
71   describe("Indic fonts (B4) ? self-hosted OFL Noto, no runtime CDN", () => {
72     it("main.tsx bundles the OFL Noto Kannada + Devanagari fonts (self-hosted, not Google
Fonts)", () => {
73       const main = readFileSync(join(SRC_DIR, "main.tsx"), "utf8");
74       expect(main).toMatch(/@fontsource-variable\/noto-sans-kannada/);
75       expect(main).toMatch(/@fontsource-variable\/noto-sans-devanagari/);
76     });
77
78     it("the font stack falls back to Noto for Kannada + Devanagari glyphs", () => {
79       const css = readFileSync(join(SRC_DIR, "index.css"), "utf8");
80       expect(css).toMatch(/Noto Sans Kannada Variable/);
81       expect(css).toMatch(/Noto Sans Devanagari Variable/);
82     });
83   });
84
85   // The Studio SPA must render correctly on an AIR-GAPPED appliance (GPU/CPU/RAM, no
internet) ?
86   // every asset (fonts, styles, scripts) is bundled local, nothing pulled from a
CDN/Google Fonts.
87   describe("offline / self-contained ? no external runtime assets", () => {
88     const CDN = /googleapis|gstatic|fonts\.google|cdnjs|unpkg|jsdelivr|bcdn\[a-z]/i;
89     const FILES = [
90       "../index.html", // web/index.html
91       "main.tsx",

```

```

90     "index.css",
91   ];
92   for (const rel of FILES) {
93     it(`${rel}: no external font/CDN reference`, () => {
94       expect(readFileSync(join(SRC_DIR, rel), "utf8")).not.toMatch(CDN);
95     });
96   }
97   it("web/index.html loads no absolute-URL <link>/<script src> (everything is
bundled/local)", () => {
98     const html = readFileSync(join(SRC_DIR, "..", "index.html"), "utf8");
99     expect(html).not.toMatch(/(?:href|src)\s*=\s*["']https?:\/\//i);
100   });
101 });
102

```

18. assistant (2026-06-21T14:59:17.133Z)

Now I understand the BARE_ATTR regex. It matches `placeholder|aria-label|title` followed by `="..."` containing 2+ letters. The diff doesn't add any new quoted-literal placeholder/aria-label/title attributes ? all such attributes in the changed files still use `{t(...)}`. The new `notAvailableHelp` is rendered as `{t("query.notAvailableHelp")}` in a `

` body (not an attribute).

Let me run the hygiene test and the full web test suite to verify everything is green, per the pre-LGTM gate. Let me check the web tooling first.

19. user (2026-06-21T14:59:18.637Z)

```

C:/Users/avidu/Projects/khelsutra/web/package.json
{
  "name": "khelsutra-web",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "description": "KhelSutra Studio ? operator console SPA (drives the rally indexer engine).",
  "scripts": {
    "dev": "vite",
    "build": "vite build",
    "preview": "vite preview",
    "typecheck": "tsc --noEmit",
    "test": "vitest run"
  },
  "dependencies": {
    "@fontsource-variable/noto-sans-devanagari": "^5.2.8",
    "@fontsource-variable/noto-sans-kannada": "^5.2.9",
    "i18next": "^26.3.1",
    "i18next-browser-languagedetector": "^8.2.1",
    "i18next-icu": "^2.4.3",
    "react": "^19.0.0",
    "react-dom": "^19.0.0",
    "react-i18next": "^17.0.8"
  },
  "devDependencies": {
    "@tailwindcss/vite": "^4.0.0",
    "@testing-library/dom": "^10.4.1",
    "@testing-library/react": "^16.3.2",
    "@types/node": "^26.0.0",
    "@types/react": "^19.0.0",
    "@types/react-dom": "^19.0.0",
    "@vitejs/plugin-react": "^4.3.4",
    "jsdom": "^29.1.1",
    "tailwindcss": "^4.0.0",
    "typescript": "^5.7.0",
    "vite": "^6.0.0",
    "vitest": "^3.0.0"
  }
}

```

```
}  
}
```

20. assistant (2026-06-21T14:59:23.523Z)

Note `i18next-icu` is used ? so interpolation is ICU MessageFormat. ICU treats `{token}` as a placeholder. The new `notAvailableHelp` string contains no curly braces, so no ICU parse risk. Let me check the new test file and then run the suite. Let me look at the new a4.touch.test.tsx.

21. user (2026-06-21T14:59:23.813Z)

```
1      // @vitest-environment jsdom
2      //
3      // A4 ? non-tech-savvy mobile UX. Two guarantees a phone user depends on:
4      //   1. TOUCH TARGETS ? 44px (WCAG 2.5.5 / platform HIG) on every primary control ?
pinned via the
5      //       Tailwind min-h-11 (=2.75rem=44px) / h-11 class so a future "tighten the padding"
can't
6      //       silently shrink a tap target below the floor.
7      //   2. The "not available yet" REASON is VISIBLE text, not a hover-only title ? a touch
device never
8      //       surfaces `title=`, so the explanation must render in the DOM for a phone user to
read it.
9      import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
10     import { render, screen, cleanup, fireEvent } from "@testing-library/react";
11     import i18n from "../i18n/index";
12     import App from "../App";
13     import { QueryBar } from "../QueryBar";
14
15     // 44px floor: min-h-11 (buttons/inputs) or an explicit h-11 square (the ? dismiss).
16     const TAP_44 = /\b(?:min-h-11|h-11)\b/;
17
18     beforeEach(async () => {
19       vi.stubGlobal("fetch", vi.fn(() => Promise.reject(new Error("no engine in test"))));
20       window.localStorage.clear();
21       await i18n.changeLanguage("en");
22     });
23
24     afterEach(() => {
25       cleanup();
26       vi.unstubAllGlobals();
27     });
28
29     describe("A4: touch targets ? 44px on primary controls", () => {
30       it("the always-visible buttons carry a ?44px tap class", () => {
31         render(<App />);
32         for (const name of [
33           "Select all",
34           "Clear",
35           "Invert",
36           "Apply", // QueryBar submit
37           "Process video", // IngestPanel submit
38           "English", // LanguageSwitcher
39           "?????",
40           "??????",
41         ]) {
42           const btn = screen.getByRole("button", { name });
43           expect(btn.className, `${name} must be ?44px`).toMatch(TAP_44);
44         }
45         // The Build button label includes the live selection count ("Build reel (6)").
46         expect(screen.getByRole("button", { name: /Build reel/
47         })).className).toMatch(TAP_44);
48       });
49       it("the text inputs carry a ?44px tap class", () => {
```

```

50     render(<App />);
51     expect(screen.getByRole("textbox", { name: "Filter rallies by length, count or
order" })).className().toMatch(TAP_44);
52     expect(screen.getByRole("textbox", { name: "Reel name"
53     })).className().toMatch(TAP_44);
54     expect(
55     screen.getByRole("textbox", { name: "Video location ? a gs:// bucket URL or a path
on the engine host" })).className,
56     ).toMatch(TAP_44);
57
58     it("the sample-query chips are tappable (?44px)", () => {
59     render(<App />);
60     expect(screen.getByRole("button", { name: "over 10s" })).className().toMatch(TAP_44);
61     expect(screen.getByRole("button", { name: "top 15 longest"
62     })).className().toMatch(TAP_44);
63     });
64
65     describe("A4: the 'not available yet' reason is visible, not hover-only", () => {
66     const HELP = "Shot type, players and score aren't available yet ? filter by rally
length instead.";
67
68     it("hidden until an unsupported concept is typed, then shown as plain text", () => {
69     render(<QueryBar onApply={() => {}} />);
70     expect(screen.queryByText(HELP)).toBeNull(); // nothing typed ? no help line
71     fireEvent.change(screen.getByRole("textbox", { name: "Filter rallies by length,
count or order" })), {
72     target: { value: "smashes" }, // a shot-type token ? flagged "not available yet"
73     });
74     expect(screen.getByText(HELP)).toBeTruthy(); // the reason is now a visible DOM node
75     });
76     });
77

```

22. assistant (2026-06-21T14:59:28.805Z)

Now let me run the full web test suite, typecheck, and the hygiene test to verify green per the pre-LGTM gate.

23. user (2026-06-21T14:59:30.222Z)

node_modules present

24. user (2026-06-21T14:59:38.440Z)

```

> khelsutra-web@0.0.0 typecheck
> tsc --noEmit

```

25. assistant (2026-06-21T14:59:55.910Z)

Typecheck is clean. Now run the full test suite.

26. user (2026-06-21T15:00:03.601Z)

```

{"ts":"2026-06-21T15:00:02.982Z","level":"error","event":"api.network_error","cid":"9aed4d38-c200-4bac-969a-518763aa580a","method":"GET","url":"/api/config","error":"Error: no engine in test"}

```

```

stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >
offers a language switcher and persists the choice (persisted pref wins on next
visit)

```

```

{"ts":"2026-06-21T15:00:02.982Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error

```

```
calling GET /api/config"}
```

```
stdout | src/components/a4.touch.test.tsx > A4: touch targets ? 44px on  
primary controls > the sample-query chips are tappable (?44px)  
{ "ts": "2026-06-21T15:00:02.955Z", "level": "info", "event": "api.request", "cid": "66b932b4-  
ec1e-4635-82b8-e4779f6fa18e", "method": "GET", "url": "/api/config" }
```

```
stderr | src/components/a4.touch.test.tsx > A4: touch targets ?  
44px on primary controls > the sample-query chips are tappable (?44px)  
{ "ts": "2026-06-  
21T15:00:02.991Z", "level": "error", "event": "api.network_error", "cid": "66b932b4-ec1e-4635-82b8-  
e4779f6fa18e", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/components/a4.touch.test.tsx > A4: touch targets ?  
44px on primary controls > the sample-query chips are tappable (?44px)  
{ "ts": "2026-06-  
21T15:00:02.991Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error  
calling GET /api/config" }
```

```
? src/components/a4.touch.test.tsx (4 tests)  
487ms
```

```
? A4: touch targets ? 44px on primary controls > the always-  
visible buttons carry a ?44px tap class 365ms
```

```
stdout | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B5:  
switching to Kannada renders the kn catalog (Kannada copy, not English)  
{ "ts": "2026-06-21T15:00:02.997Z", "level": "info", "event": "api.request", "cid": "696089a8-  
d4ef-403a-acf9-ebcbae2b64e1", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >  
B5: switching to Kannada renders the kn catalog (Kannada copy, not English)  
{ "ts": "2026-06-  
21T15:00:03.026Z", "level": "error", "event": "api.network_error", "cid": "696089a8-d4ef-403a-acf9-  
ebcbae2b64e1", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >  
B5: switching to Kannada renders the kn catalog (Kannada copy, not English)  
{ "ts": "2026-06-  
21T15:00:03.026Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error  
calling GET /api/config" }
```

```
stdout | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B6:  
switching to Hindi renders the hi catalog (extensibility proof ? just a catalog)  
{ "ts": "2026-06-21T15:00:03.046Z", "level": "info", "event": "api.request", "cid": "941c4e52-  
0758-4be0-b8ad-5e32e4b1e0c5", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >  
B6: switching to Hindi renders the hi catalog (extensibility proof ? just a  
catalog)  
{ "ts": "2026-06-  
21T15:00:03.074Z", "level": "error", "event": "api.network_error", "cid": "941c4e52-0758-4be0-b8ad-  
5e32e4b1e0c5", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >  
B6: switching to Hindi renders the hi catalog (extensibility proof ? just a  
catalog)  
{ "ts": "2026-06-  
21T15:00:03.074Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error  
calling GET /api/config" }
```

```
stdout | src/i18n/i18n.test.tsx > i18n scaffold (B1) > a  
locale with no catalog falls back to English (never a raw key)  
{ "ts": "2026-06-21T15:00:03.091Z", "level": "info", "event": "api.request", "cid": "c3d5551a-  
dc8c-4e61-b0cb-1ba54c103d9f", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >
```

```

a locale with no catalog falls back to English (never a raw key)
{"ts":"2026-06-21T15:00:03.094Z","level":"error","event":"api.network_error","cid":"c3d5551a-dc8c-4e61-b0cb-1ba54c103d9f","method":"GET","url":"/api/config","error":"Error: no engine in test"}

stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) >
a locale with no catalog falls back to English (never a raw key)
{"ts":"2026-06-21T15:00:03.094Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error calling GET /api/config"}

stdout | src/i18n/i18n.test.tsx > browser-language negotiation (B1:
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?
never a locale we can't render
{"ts":"2026-06-21T15:00:03.113Z","level":"info","event":"api.request","cid":"25f49d6c-c2dc-4289-a602-e82c7f53b9db","method":"GET","url":"/api/config"}

stderr | src/i18n/i18n.test.tsx > browser-language negotiation (B1:
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?
never a locale we can't render
{"ts":"2026-06-21T15:00:03.117Z","level":"error","event":"api.network_error","cid":"25f49d6c-c2dc-4289-a602-e82c7f53b9db","method":"GET","url":"/api/config","error":"Error: no engine in test"}

stderr | src/i18n/i18n.test.tsx > browser-language negotiation (B1:
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?
never a locale we can't render
{"ts":"2026-06-21T15:00:03.117Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error calling GET /api/config"}

? src/i18n/i18n.test.tsx (13 tests)
587ms
? i18n scaffold (B1) > renders user-facing copy from the en
catalog (not raw keys) 320ms

Test Files 12 passed (12)
Tests 127 passed (127)
Start at 20:29:59
Duration 4.05s (transform 664ms, setup 200ms, collect 3.21s, tests 1.59s,
environment 8.50s, prepare 3.38s)

```

27. assistant (2026-06-21T15:00:11.406Z)

All 127 tests pass across 12 files, including the new a4.touch.test.tsx (4 tests), the i18n key-parity hygiene test, and the no-bare-strings test. Typecheck is clean. The error logs are expected (the test stubs fetch to reject, asserting the config-unavailable fallback path).

Now let me check if there's an ESLint config to run the lint portion of the gate, and check the LanguageSwitcher and IngestPanel full context for the alignment questions.

28. user (2026-06-21T15:00:11.724Z)

```

---scripts---
no lint script

```

29. assistant (2026-06-21T15:00:16.858Z)

No ESLint/lint script in the web package (the test file uses `eslint-disable-next-line` comments, but there's no configured lint run in this package ? CI relies on typecheck + vitest, both green). Let me verify the CompileResult header alignment concern more carefully and check the LanguageSwitcher full context.

30. user (2026-06-21T15:00:17.520Z)

```

1      import { useTranslation } from "react-i18next";
2      import { SUPPORTED_LOCALES, DEFAULT_LOCALE, type Locale } from "../i18n";
3
4      // Each locale's label is its own autonym, shown in its own script. Kannada renders
crisply once the
5      // bundled Noto Sans Kannada font lands (tracker B4); most devices already ship a system
Kannada font.
6      const LANG_LABEL_KEY: Record<Locale, string> = {
7          en: "lang.en",
8          kn: "lang.kn",
9          hi: "lang.hi",
10     };
11
12     /**
13      * A persistent language switcher. Selecting a locale calls i18next's changeLanguage,
which the
14      * detector caches to localStorage (LANG_STORAGE_KEY) ? so the choice is the top-
priority signal on
15      * the next visit (negotiation: persisted pref wins). Icon-free + non-color active state
via
16      * aria-pressed keeps it usable for non-tech-savvy users (FRIENDLY_AND_MULTILINGUAL §4).
17      */
18     export function LanguageSwitcher() {
19         const { t, i18n } = useTranslation();
20         // Highlight the user's CHOSEN locale (i18n.language), not the resolved-for-content
one:
21         // resolvedLanguage falls back to `en` when a catalog is missing, so picking Kannada
(content
22         // still English until the kn catalog lands, B5) must still show Kannada as selected.
Compare on
23         // the base subtag so a detected "en-IN" highlights "en".
24         const active = (i18n.language || DEFAULT_LOCALE).split("-")[0];
25
26         return (
27             <nav aria-label={t("lang.label")} className="flex items-center gap-1">
28                 {SUPPORTED_LOCALES.map((loc) => {
29                     const isActive = active === loc;
30                     return (
31                         <button
32                             key={loc}
33                             type="button"
34                             lang={loc}
35                             aria-pressed={isActive}
36                             onClick={() => void i18n.changeLanguage(loc)}
37                             className={[
38                                 "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold
transition",
39                                 isActive ? "bg-white text-ink" : "text-white/70 hover:text-white",
40                                 ].join(" ")}
41                             >
42                             {t(LANG_LABEL_KEY[loc])}
43                         </button>
44                     );
45                 })}
46             </nav>
47         );
48     }
49

```

31. assistant (2026-06-21T15:00:27.655Z)

LanguageSwitcher's parent `nav` is `flex items-center gap-1`, so the `min-h-11` buttons center fine. The `inline-flex items-center` ensures the text vertically centers within the 44px button. Good.

Now let me carefully reason about the CompileResult header alignment, which is the most plausible concern. The parent at line 31 is `flex items-start justify-between gap-3`. Previously the dismiss button was `rounded-full px-2` (intrinsic height = the ? line-box, roughly the same as the h2). With `items-start`, the top of the small button aligned with the top of the h2. Now the button is `h-11` (44px) with `items-center justify-center` internally. The button's top still aligns with the h2's top (parent `items-start`), and the ? glyph centers within the 44px box, so the glyph sits ~10px below the h2 text baseline-top. This is a minor cosmetic shift, not a break ? the close button being a 44px tap target top-aligned with the heading is a standard, acceptable pattern. The header row does not wrap or overflow. This is intentional per the A4 touch-target goal and acceptable.

Let me double-check there are no other JSX text bare-string concerns and confirm the IngestPanel retry button change (text-xs ? text-sm, py removed) doesn't affect anything. Let me also verify the App.tsx bulk buttons context.

32. user (2026-06-21T15:00:28.527Z)

```
38      <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
testid="ingest-panel">
39        <h2 className="text-lg font-bold">{t("ingest.title")}</h2>
40        <p className="mt-1 max-w-2xl text-sm text-ink/60">{t("ingest.intro")}</p>
41
42        <form onSubmit={onSubmit} className="mt-3 flex flex-wrap items-center gap-2">
43          <input
44            type="text"
45            value={uri}
46            onChange={(e) => setUri(e.target.value)}
47            placeholder={t("ingest.uriPlaceholder")}
48            aria-label={t("ingest.uriAriaLabel")}
49            disabled={busy}
50            className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-
white px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
51          />
52          <button
53            type="submit"
54            disabled={busy}
55            className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-
white disabled:opacity-40"
56          >
57            {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}
58          </button>
59          {busy && (
60            <button
61              type="button"
62              onClick={cancel}
63              className="min-h-11 rounded-xl border border-black/15 px-4 py-2 text-sm
hover:border-green"
64            >
65              {t("ingest.cancel")}
66            </button>
67          )}
68        </form>
69
70        <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>
71
72        {/* Live status (aria-live so screen readers hear progress). Indeterminate: the
engine reports
73         phase words ("hashing", "segmenting"), not a percentage ? so a spinner + the
phase word. */}
74        <div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
75          {busy && (
76            <p className="flex items-center gap-2 text-ink/70">
77              <Spinner />
78              <span>
79                {t("ingest.working")}
```

```

80         {phase.status === "polling" && phase.progress
81         ? ` . ${t("ingest.progress", { progress: phase.progress })}`
82         : ""}
83     </span>
84 </p>
85   )}
86   {phase.status === "error" && (
87     <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-
red-800" data-testid="ingest-error">
88       <p>{errorMsg}</p>
89       <button
90         type="button"
91         onClick={reset}
92         className="mt-2 inline-flex min-h-11 items-center rounded-lg border
border-red-300 px-3 text-sm hover:bg-red-100"
93       >
94         {t("ingest.retry")}
95       </button>
96     </div>
97   )}

```

33. assistant (2026-06-21T15:00:35.347Z)

All looks consistent. The IngestPanel form is `flex flex-wrap items-center gap-2`, so `min-h-11` controls center properly. The retry button at line 92 changed from `py-1 text-xs` to `inline-flex min-h-11 items-center ... text-sm` ? correct touch-target treatment, no layout break inside its `<div>` container.

Let me verify there are no remaining bare attribute literals anywhere in the changed files by running the actual regex from the test, just to be thorough.

34. user (2026-06-21T15:00:42.324Z)

scan done

35. assistant (2026-06-21T15:00:46.793Z)

No bare attributes. The no-bare-strings test is satisfied.

Let me do a final review of the App.tsx bulk buttons context to confirm the row wrapping is intact, and verify the QueryBar `notAvailableHelp` placement doesn't conflict with the existing `unreadable`/`hint` lines (e.g., showing both at once would be redundant but not a bug).

36. user (2026-06-21T15:00:47.517Z)

```

238   )}
239
240   <ModeBanner load={loadState} videoId={videoId} />
241
242   <div className="mt-6">
243     <QueryBar onApply={onApplyQuery} />
244   </div>
245
246   <div className="mt-6 flex flex-wrap gap-2 text-sm">
247     <button type="button" onClick={() => onBulk("select_all")} className="inline-
flex min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.selectAll")}</button>
248     <button type="button" onClick={() => onBulk("clear")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.clear")}</button>
249     <button type="button" onClick={() => onBulk("invert")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.invert")}</button>
250   </div>

```

```
251
252         <div className="mt-5">
253             <RallyGrid rallies={order} isSelected={sel.isSelected} onToggle={onToggle}
ordinalOf={ordinalOf} />
```

37. assistant (2026-06-21T15:00:54.523Z)

The bulk-buttons row is `flex flex-wrap gap-2`. The buttons gained `inline-flex min-h-11 items-center` and `px-3 py-1` ? `px-4` (padding-y removed, replaced by `min-h-11 + items-center` for vertical centering). This is correct: removing `py-1` is fine because `inline-flex min-h-11 items-center` now governs height and centering. No wrapping/alignment regression.

One last consideration on the QueryBar `notAvailableHelp` placement: it renders when `parsed.unavailable.length > 0`. In that state, the pill row (line 69-77) already shows per-token "not available" pills, and the `unreadable` line (line 78) is gated on `parsed.unavailable.length === 0`, so they're mutually exclusive ? no double messaging. The help line is additive and correctly gated. Good.

I have verified everything. Let me compile the findings.

38. user (2026-06-21T15:01:07.726Z)

Structured output provided successfully

39. assistant (2026-06-21T15:01:16.862Z)

Review complete. The diff is clean, no findings.

I verified all five requested concerns plus ran the full local gate:

```
- **typecheck**: `tsc --noEmit` clean
- **tests**: 127/127 passing across 12 files, including the new
`web/src/components/a4.touch.test.tsx`, the i18n key-parity test, and the no-bare-strings test
```

Concern-by-concern:

1. **SelectionFooter**

(`C:/Users/avidu/Projects/khelsutra/web/src/components/SelectionFooter.tsx:53,66,74`) ? the row is `flex flex-wrap items-center gap-3`; `min-h-11` only raises min height while `items-center` keeps vertical centering. No alignment/wrap/sticky-footer regression.

2. **CompileResult**

(`C:/Users/avidu/Projects/khelsutra/web/src/components/CompileResult.tsx:31,39`) ? parent `flex items-start justify-between`; the `h-11 w-11` dismiss button still top-aligns with the h2, glyph centered within the 44px box. Minor intentional cosmetic shift (standard top-aligned close-as-tap-target), not a break.

3. `query.notAvailableHelp` is in all three catalogs (`en`kn`hi`) at the same `query.*` path ? key-parity green. No ICU placeholders, so no interpolation risk.

4. `no-bare-strings` ? ran the test's exact `BARE_ATTR` regex over all 7 watched files: zero matches. The new help text is `{(...)}` in a `<p>` body, not an attribute.

5. `TS/React` ? clean; the help `<p>` (`QueryBar.tsx:86-88`) is gated on `parsed.unavailable.length > 0`, mutually exclusive with the `unreadable` line.