

claude-windows / b8be946b-bd13-4912-b478-1b1923b9478c

Metadata

```
- Source: `claude-windows`
- Kind: `claude`
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra-guru-khelsutra
--claude-worktrees-zealous-pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c.jsonl`
- SHA-256: `6b904a9009208a70c98bf0d9ebab10cf0c169c3c31fd7908deb92f53220e3735`
- Source modified: `2026-07-04T15:41:51+00:00`
- Imported at: `2026-07-05T16:48:20+00:00`
- project: `C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-
pike-7d0a85`
- session_id: `b8be946b-bd13-4912-b478-1b1923b9478c`
```

Transcript

1. user (2026-07-04T01:28:06.037Z)

In the khelsutra repo (C:/Users/avidu/Projects/khelsutra-guru/khelsutra), add a client-side upload-size guard to the ingest SPA so an oversized file fails INSTANTLY with a clear, localized message + a "trim/chunk it first" hint ? before any network round-trip.

Context (already verified):

- The engine (badminton-highlight-indexer `backend/api/uploads.py`) already fail-fasts: `/upload/init` returns 413 when `total_size_bytes > security.max_upload_mb` (default 4096 MB) BEFORE any part is transferred. So no bytes are wasted today ? but the SPA briefly shows "uploading" then flips to a generic "engine" error via classifyError`, with no size-specific message or chunk hint.`
- A companion engine change exposes `max_upload_mb`` in `GET /api/capabilities`` (see that PR). Consume it here.

Implement in `web/src/``:

1. `api/types.ts`` ? add `max_upload_mb`` to the `EngineCapabilities`` type.
2. `lib/errors.ts`` ? add a `"fileTooLarge"` `IngestErrorCode`` (carry the file size + cap so the message can show both).
3. `hooks/useUpload.ts`` ? `start(file)`` already rejects 0-byte files pre-network (line ~38); add a size guard right after it: `if `maxUploadBytes && file.size > maxUploadBytes` ? setPhase({status:'error', error:{code:'fileTooLarge', ...}})` and return, no network. Thread the cap in (param or a capabilities context).`
4. `components/IngestPanel.tsx`` ? localize the `fileTooLarge`` message with the actual size + cap, e.g. "This clip is 5.8 GB, over the 4 GB upload limit. Trim it to a shorter highlight first ? see scripts/chunk_video (or use the Google Drive path)."
5. i18n: add the `fileTooLarge`` string to all locale files (the SPA ships ~6 languages ? mirror the existing error strings).
6. Tests: extend `components/upload.test.tsx`` / the errors test for the new code + the pre-network reject.

Keep `useUpload`` i18n-free (return the code, not prose) per its existing contract ? IngestPanel maps the code to a localized string. Reference the chunking helper `scripts/chunk_video.py`` (added in the engine repo) in the message. Run the SPA test suite + typecheck + lint before opening the PR.

2. assistant (2026-07-04T01:28:13.147Z)

I'll start by getting oriented. Let me pull the latest and explore the relevant files.

3. user (2026-07-04T01:28:30.174Z)

There is no tracking information for the current branch.
Please specify which branch you want to merge with.
See `git-pull(1)` for details.

```
git pull <remote> <branch>
```

If you wish to set tracking information for this branch you can do so with:

```
git branch --set-upstream-to=origin/<branch> claude/zealous-pike-7d0a85
```

```
---BRANCH---
```

```
claude/zealous-pike-7d0a85
```

```
---HEAD---
```

```
b0f70a5 Show failed ingest verdict reasons
```

4. user (2026-07-04T01:28:30.273Z)

```
web\src\App.ingest.test.tsx
web\src\App.tsx
web\src\annotator\annotator.smoke.test.ts
web\src\annotator\annotator.ts
web\src\annotator\csv.ts
web\src\api\client.test.ts
web\src\api\client.ts
web\src\api\locale.test.ts
web\src\api\types.ts
web\src\api\upload.test.ts
web\src\components\AnnotatePanel.test.tsx
web\src\components\AnnotatePanel.tsx
web\src\components\CompileResult.tsx
web\src\components\FfmpegBanner.test.tsx
web\src\components\FfmpegBanner.tsx
web\src\components\IngestPanel.test.tsx
web\src\components\IngestPanel.tsx
web\src\components\LanguageSwitcher.tsx
web\src\components\QueryBar.examples.test.ts
web\src\components\QueryBar.test.tsx
web\src\components\QueryBar.tsx
web\src\components\RallyGrid.tsx
web\src\components\SelectionFooter.test.tsx
web\src\components\SelectionFooter.tsx
web\src\components\SetupWizard.test.tsx
web\src\components\SetupWizard.tsx
web\src\components>StatusChip.tsx
web\src\components\TapFilters.test.tsx
web\src\components\TapFilters.tsx
web\src\components\VideoLibrary.test.tsx
web\src\components\VideoLibrary.tsx
web\src\components\A4.touch.test.tsx
web\src\components\A8.status.test.tsx
web\src\components\build-error.test.tsx
web\src\components\upload.test.tsx
web\src\hooks\useIngestJob.test.ts
web\src\hooks\useIngestJob.ts
web\src\hooks\useRallySelection.ts
web\src\hooks\useUpload.test.ts
web\src\hooks\useUpload.ts
web\src\i18n\catalog-invariants.test.ts
web\src\i18n\hygiene.test.ts
web\src\i18n\i18n.test.tsx
web\src\i18n\index.ts
web\src\lib\errorText.test.ts
web\src\lib\errorText.ts
web\src\lib\errors.test.ts
web\src\lib\errors.ts
web\src\lib\floor.test.ts
web\src\lib\floor.ts
web\src\lib\format.test.ts
web\src\lib\format.ts
```

```
web\src\lib\log.ts
web\src\lib\query.test.ts
web\src\lib\query.ts
web\src\lib\selection.test.ts
web\src\lib\selection.ts
web\src\lib\video.test.ts
web\src\lib\video.ts
web\src\main.tsx
web\src\test\setup.ts
web\src\vite-env.d.ts
```

5. assistant (2026-07-04T01:28:33.779Z)

No upstream tracking for this fresh worktree branch ? that's expected; I'll proceed with the local checkout. Let me read the key files.

6. user (2026-07-04T01:28:34.789Z)

```
1      // Types mirror the engine's verified contract (badminton-highlight-indexer).
2      // Stable anchors: backend/infrastructure/database.py play_segments/candidate_segments,
3      // and engine routes/symbols for query, compile, highlights, config, videos, jobs, and
process.
4
5      export interface RallyMetadata {
6          /** Gemini's shuttle_exchange_count (fallback max(3, dur/0.8)); absent on some
detectors. */
7          shot_count?: number;
8          /** Gemini confidence STRING (often "Unknown") ? not a numeric meter. */
9          shot_count_confidence?: string;
10         detector?: string;
11         [key: string]: unknown;
12     }
13
14     export interface RallySegment {
15         /** The integer the UI selects and passes to /api/compile as segment_ids. */
16         id: number;
17         start_time: number;
18         end_time: number;
19         duration: number;
20         /** motion-segmenter FABRICATION (random) ? DO NOT surface (see
PER_RALLY_SELECTION.md). */
21         server: string | null;
22         /** motion-segmenter FABRICATION (random) ? DO NOT surface. */
23         receiver: string | null;
24         metadata: RallyMetadata;
25         /** motion-only fabricated sub-events ? DO NOT surface. */
26         events?: unknown[];
27     }
28
29     export interface QueryResponse {
30         play_segments: RallySegment[];
31     }
32
33     /** One row of the indexed-video library. GET /api/videos [engine list_videos route]
returns the most
34     * recent first so the console survives a reload. Every field but `video_id` is
optional/defensive. */
35     export interface VideoSummary {
36         /** The MD5 join key (the contract field). Optional defensively ? an older/regressed
engine may
37         * send only the raw `id`; read it through `lib/video.ts::videoId`, never directly.
*/
38         video_id?: string;
39         /** Raw DB fields an engine may send instead of the enriched contract (resilience
fallbacks). */
```

```

40     id?: string;
41     filepath?: string | null;
42     match_name?: string | null;
43     local_path?: string | null;
44     fps?: number | null;
45     resolution?: string | null;
46     created_at?: string | null;
47 }
48
49 export interface VideosResponse {
50     videos: VideoSummary[];
51 }
52
53 /** POST /api/annotations ? persist finished rally labels for a video as the annotator
CSV (P8).
54 * The engine writes the CSV verbatim (byte-compatible with the pipeline), keyed by the
file MD5. */
55 export interface AnnotationsResponse {
56     status: string;
57     num_rows?: number;
58     csv_uri?: string;
59     message?: string;
60 }
61
62 export interface CompileResponse {
63     status: string;
64     /** server-local path (NOT a URL) ? build the download URL with highlightUrl(). */
65     filepath: string;
66 }
67
68 /** The terminal RESULT of an async reel compile (#329): the job's `result` payload,
surfaced by
69 * GET /api/jobs/{id} once the stitch finishes. `status` is the pipeline verdict
("success" |
70 * "failed"); a "failed" result carries a `message`. The SPA builds the download URL
with
71 * highlightUrl() (split-origin-safe), but the engine also returns a same-origin
`download_url`. */
72 export interface CompileResult {
73     status: string;
74     filepath?: string;
75     download_url?: string;
76     message?: string;
77     video_id?: string;
78 }
79
80 export interface EngineConfig {
81     stitching?: {
82         /** The shot-count floor /api/compile silently enforces ? surface it, don't hide it.
*/
83         min_shot_count?: number;
84         [key: string]: unknown;
85     };
86     [key: string]: unknown;
87 }
88
89 /** GET /api/capabilities [backend/main.py] ? an HONEST probe of what THIS box can do,
rendered by
90 * the first-run wizard (PACKAGING_PLAN.md P2c). Presence-booleans only (never the Gemini
key value).
91 * Every field optional/defensive: a missing field degrades the wizard gracefully. */
92 export interface EngineCapabilities {
93     api_version?: number;
94     engine_version?: string;
95     segmenters?: string[];

```

```

96     default_segmenter?: string;
97     ffmpeg?: { ffmpeg?: boolean; ffprobe?: boolean; ffmpeg_path?: string; ffprobe_path?:
string };
98     gpu?: { nvidia_smi_present?: boolean };
99     /** Whether a Gemini key is PRESENT (never its value) ? drives the AI-highlights step.
*/
100     gemini_key_present?: boolean;
101     wasb_weights_present?: boolean;
102     /** `cloud_available` = can THIS server satisfy a per-request compute="cloud" dispatch
(a Cloud Run
103     * GPU Job)? The ingest compute-picker shows the "in the cloud" option only when
true. */
104     deployment?: { profile?: string; compute_target?: string; cloud_available?: boolean };
105     /** Which storage media THIS box can store INTO (P3). The medium picker renders only
`usable`
106     * backends; `free_gb` is `null` for a cloud bucket (no readable capacity). Absent on
older engines
107     * ? the SPA degrades to local-only (no picker). */
108     storage?: StorageCapabilities;
109     [key: string]: unknown;
110 }
111
112 /** One storable medium reported by GET /api/capabilities (P3). Presence/usable bools
only ? no
113     * secrets. `id`/`kind` are the backend name (local/gcs/s3/gdrive). */
114 export interface StorageBackendInfo {
115     id: string;
116     kind: string;
117     label: string;
118     usable: boolean;
119     /** Free space in whole GB, or `null` when unknowable (a cloud bucket). */
120     free_gb?: number | null;
121 }
122
123 export interface StorageCapabilities {
124     default_medium?: string;
125     backends?: StorageBackendInfo[];
126 }
127
128 /** POST /api/assets ? 201 (P4). The video was stored into the chosen medium and
registered as a
129     * library asset keyed by the whole-file MD5 (`video_id`). `stored_uri` is the durable
location to
130     * feed into POST /api/process (a bucket/Drive URI, or a local path for "this
computer"). */
131 export interface AssetResponse {
132     video_id: string;
133     /** The medium backend the asset lives in (local | s3 | gcs | gdrive). */
134     medium: string;
135     /** The durable, MD5-keyed location ? pass as video_path to processVideo(). */
136     stored_uri: string;
137     /** True when a durable copy was made (uploaded ? remote medium); false when
registered in place. */
138     copied: boolean;
139     sport?: string | null;
140     status?: string;
141 }
142
143 /** POST /api/process ? 202 [engine process route]. The job is queued; poll GET
/api/jobs/{job_id}. */
144 export interface ProcessResponse {
145     job_id: string;
146     /** Always "queued" at submit. */
147     status: string;
148     /** Relative poll path, e.g. "/api/jobs/<id>". */

```

```

149     poll: string;
150 }
151
152 /** Chunked upload (backend/api/uploads.py). The browser uploads a local file in
sequential parts
153 * ? max_part_mb, then `complete` returns a server-host `path` to feed straight into
POST /api/process. */
154 export interface UploadInitResponse {
155     upload_id: string;
156     /** Per-part ceiling in MB ? slice the file into parts this big. */
157     max_part_mb: number;
158     next_part: string;
159 }
160 export interface UploadPartResponse {
161     upload_id: string;
162     received_parts: number;
163     received_bytes: number;
164 }
165 export interface UploadCompleteResponse {
166     /** Absolute path on the engine host ? pass as video_path to POST /api/process. */
167     path: string;
168     video_id: string;
169     size_bytes: number;
170 }
171
172 /** GET /api/jobs/{job_id} [engine jobs route]. Two status layers:
173 * `status` = the EXECUTION state; `result.status` = the pipeline VERDICT
(success|failed).
174 * A `done` job whose `result.status` === "failed" should surface `result.message`.
175 * A successful job with an explicit empty `play_segments` array is the genuine no-
rallies case. */
176 export interface JobStatus {
177     job_id: string;
178     status: "queued" | "running" | "done" | "failed";
179     /** Free-text coarse phase ("hashing", "segmenting (gemini)", "finished") ? NOT a
percentage. */
180     progress?: string | null;
181     /** The canonical video_id, surfaced top-level on success (also in result.video_id).
*/
182     video_id?: string | null;
183     /** Execution error (worker crash / unexpected) when status === "failed". */
184     error?: string | null;
185     result?: { status?: string; video_id?: string; message?: string; play_segments?:
RallySegment[] } | null;
186 }
187

```

7. user (2026-07-04T01:28:35.797Z)

```

1     // Error helpers shared by the ingest flow and the build flow. Kept i18n-FREE: callers
map an
2     // IngestErrorCode to a localized string (so hooks stay testable without a translation
context),
3     // while the engine's own `detail` text passes through verbatim (it's the most specific
message).
4     import { ApiError } from "../api/client";
5
6     function isProxyBoilerplate(body: string): boolean {
7         const s = body.trim().toLowerCase();
8         if (!s) return false;
9         return (
10             s.startsWith("<!doctype html") ||
11             s.startsWith("<html") ||
12             /<html[\s>]/i.test(body) ||
13             /<\html>/i.test(body) ||

```

```

14         s.includes("error occurred while trying to proxy") ||
15         (s.includes("cloudflare") && s.includes("error"))
16     );
17 }
18
19 /** Pull FastAPI's {"detail": "..."} message out of an error body, else return safe
plain text. */
20 export function parseDetail(body: string): string {
21     try {
22         const j = JSON.parse(body) as { detail?: unknown };
23         if (j && typeof j.detail === "string") return j.detail;
24     } catch {
25         /* not JSON ? fall through to safe plain text handling */
26     }
27     if (isProxyBoilerplate(body)) return "";
28     return body;
29 }
30
31 /** Stable, localizable failure categories surfaced by the ingest flow.
32  * `engine` carries the engine's own message in `detail`; the rest are localized by
code. */
33 export type IngestErrorCode = "invalidUri" | "networkError" | "emptyResult" | "timeout"
| "engine";
34
35 export interface IngestError {
36     code: IngestErrorCode;
37     /** Present for `engine` ? the verbatim FastAPI detail / status; rendered as-is, not
translated. */
38     detail?: string;
39 }
40
41 /** Classify a thrown client error into a stable code. A network throw (ApiError with no
`status`)
42  * is the common "engine unreachable" case ? its own friendly code; any HTTP error
surfaces the
43  * engine's `detail` (e.g. an unsupported-scheme 400, a not-found 404). */
44 export function classifyError(err: unknown): IngestError {
45     if (err instanceof ApiError) {
46         if (err.status === undefined) return { code: "networkError" }; // fetch threw ?
engine truly unreachable
47         if (err.body) {
48             const detail = parseDetail(err.body);
49             if (detail) return { code: "engine", detail }; // a real engine message (e.g. a
400 unsupported-scheme)
50         }
51         // A bare 5xx with no body is almost always the engine being down / a gateway that
can't reach it
52         // (e.g. the dev proxy when :8000 is off) ? for a non-technical user a friendly "is
it running?"
53         // beats a cryptic "HTTP 500". A 4xx with no body keeps the status (it's a client-
side mistake).
54         if (err.status >= 500) return { code: "networkError" };
55         return { code: "engine", detail: `HTTP ${err.status}` };
56     }
57     return { code: "engine", detail: String(err) };
58 }
59

```

8. user (2026-07-04T01:28:36.793Z)

```

1     // Drives the in-UI file UPLOAD half of ingest (tracker T4): chunk a local file up to
the engine's
2     // /api/upload/* endpoints, report byte progress, then hand the returned server PATH to
the existing
3     // processing back-half (useIngestJob.submit). Alpha users have a FILE, not a gs:// URI

```

```

? this is the
4      // keystone that lets them point the tool at it from the browser.
5      //
6      // Kept i18n-FREE (returns stable IngestErrorCodes via classifyError, not prose) so it
unit-tests
7      // without a translation context ? IngestPanel maps codes to localized strings via
errorText. Abort
8      // is an AbortController: cancel/unmount/a superseding pick stops the in-flight upload
and the
9      // orchestrator best-effort DELETes the server-side partial.
10     import { useCallback, useEffect, useRef, useState } from "react";
11     import { uploadFile } from "../api/client";
12     import { classifyError, type IngestError } from "../lib/errors";
13     import { log, newCorrelationId } from "../lib/log";
14
15     export type UploadPhase =
16       | { status: "idle" }
17       | { status: "uploading"; pct: number; filename: string }
18       | { status: "error"; error: IngestError };
19
20     export function useUpload(onComplete: (path: string, filename: string) => void) {
21       const [phase, setPhase] = useState<UploadPhase>({ status: "idle" });
22       const ctrlRef = useRef<AbortController | null>(null);
23       // Keep the latest onComplete without making start depend on it (a parent re-render
won't restart).
24       const onCompleteRef = useRef(onComplete);
25       onCompleteRef.current = onComplete;
26
27       const stop = useCallback(() => {
28         ctrlRef.current?.abort();
29         ctrlRef.current = null;
30       }, []);
31
32       // Abort any in-flight upload on unmount.
33       useEffect(() => stop, [stop]);
34
35       const start = useCallback(
36         (file: File) => {
37           // A 0-byte "video" is never valid ? reject before touching the network (reuse
invalidUri copy).
38           if (!file || file.size === 0) {
39             setPhase({ status: "error", error: { code: "invalidUri" } });
40             return;
41           }
42
43           stop(); // supersede any prior upload
44           const ctrl = new AbortController();
45           ctrlRef.current = ctrl;
46           const cid = newCorrelationId();
47           setPhase({ status: "uploading", pct: 0, filename: file.name });
48           log("info", "upload.submit_start", { cid, filename: file.name, size: file.size });
49
50           void (async () => {
51             try {
52               const res = await uploadFile(file, {
53                 cid,
54                 signal: ctrl.signal,
55                 onProgress: ({ sentBytes, totalBytes }) => {
56                   if (ctrl.signal.aborted) return;
57                   const pct = totalBytes > 0 ? Math.min(100, Math.round((sentBytes /
totalBytes) * 100)) : 0;
58                   setPhase({ status: "uploading", pct, filename: file.name });
59                 },
60               });
61               if (ctrl.signal.aborted) return;

```



```

62         setPhase({ status: "idle" }); // hand off ? the engine processing phase takes
over
63         onCompleteRef.current(res.path, file.name);
64     } catch (err) {
65         // User-cancelled (abort) is silent, not an error.
66         if (ctrl.signal.aborted || (err instanceof DOMException && err.name ===
"AbortError")) return;
67         setPhase({ status: "error", error: classifyError(err) });
68         log("error", "upload.failed", { cid, filename: file.name, error: String(err)
});
69     }
70     })();
71     },
72     [stop],
73 );
74
75     const cancel = useCallback(() => {
76         stop();
77         setPhase({ status: "idle" });
78         log("info", "upload.cancel", {});
79     }, [stop]);
80
81     const reset = useCallback(() => {
82         stop();
83         setPhase({ status: "idle" });
84     }, [stop]);
85
86     const busy = phase.status === "uploading";
87     return { phase, start, cancel, reset, busy };
88 }
89

```

9. user (2026-07-04T01:28:37.359Z)

```

1     // The front-half ingest screen (appliance S1/S2; tracker B-P2 + T4). Two ways to point
the tool at a
2     // video: UPLOAD a local file (primary ? alpha users have a file, not a URI; chunked to
the engine's
3     // /api/upload/* endpoints) or paste a `gs://` bucket URI / host path (secondary). Both
converge on
4     // the SAME back-half: POST /api/process ? poll GET /api/jobs/{id} ? hand the video_id
to App. Honest
5     // by construction: the engine reports coarse phase WORDS (not a %), and a success-
shaped failure
6     // (done but no rallies) is shown, never silently treated as a load.
7     import { useEffect, useState } from "react";
8     import type { ChangeEvent, FormEvent } from "react";
9     import { useTranslation } from "react-i18next";
10    import { createAsset, getCapabilities } from "../api/client";
11    import type { StorageBackendInfo } from "../api/types";
12    import { useIngestJob } from "../hooks/useIngestJob";
13    import { useUpload } from "../hooks/useUpload";
14    import { classifyError, type IngestError } from "../lib/errors";
15    import { errorText } from "../lib/errorText";
16    import { log, newCorrelationId } from "../lib/log";
17    import { StatusChip, Spinner } from "../StatusChip";
18
19    type Compute = "local" | "cloud";
20    // The three storage-medium choices the picker offers. "bucket" covers s3 OR gcs (the
user pastes a
21    // full scheme'd URI); "drive" is a mounted Google Drive folder
(STUDIO_MEDIA_LIFECYCLE.md P5, D14).
22    type Medium = "local" | "bucket" | "drive";
23
24    interface Props {

```

```

25     /** Called with the engine's video_id once a submitted job finishes successfully. */
26     onLoaded: (videoId: string, displayName?: string) => void;
27     /** Lets the shell hide demo-only controls while a real ingest is in flight. */
28     onBusyChange?: (busy: boolean) => void;
29 }
30
31 function formatElapsed(totalSec: number): string {
32     const sec = Math.max(0, Math.floor(totalSec));
33     const mm = Math.floor(sec / 60);
34     const ss = sec % 60;
35     return `${mm}:${String(ss).padStart(2, "0")}`;
36 }
37
38 function sourceLabel(value: string): string | null {
39     const trimmed = value.trim();
40     if (!trimmed) return null;
41     try {
42         const parsed = new URL(trimmed);
43         const tail = parsed.pathname.split(/[\\\/]/).filter(Boolean).pop();
44         return tail ? decodeURIComponent(tail) : trimmed;
45     } catch {
46         return trimmed.split(/[\\\/]/).filter(Boolean).pop() ?? trimmed;
47     }
48 }
49
50 export function IngestPanel({ onLoaded, onBusyChange }: Props) {
51     const { t, i18n } = useTranslation();
52     const [uri, setUri] = useState("");
53     const [activeSource, setActiveSource] = useState<string | null>(null);
54     const { phase, submit, cancel: cancelIngest, reset: resetIngest, busy: ingestBusy } =
55 useIngestJob(onLoaded);
56     // The UI locale recorded with the submission (PMF analytics + the localized reel
57 watermark).
58     const locale = i18n.resolvedLanguage ?? i18n.language;
59
60     // Compute-picker (PACKAGING compute-picker, item 3): if this server can dispatch to a
61 cloud GPU
62     // (capabilities.deployment.cloud_available), let the user choose where DETECT runs.
63 Default LOCAL
64     // (free, no surprise cost); CLOUD requires an explicit cost acknowledgement before it
65 can run.
66     const [cloudAvailable, setCloudAvailable] = useState(false);
67     const [compute, setCompute] = useState<Compute>("local");
68     const [cloudAck, setCloudAck] = useState(false);
69     // Storage-medium picker (P5): which media THIS box can store into
70 (capabilities.storage.backends,
71 // usable-only). Absent/local-only ? no picker (today's flow unchanged).
72     const [backends, setBackends] = useState<StorageBackendInfo[]>([]);
73     const [medium, setMedium] = useState<Medium>("local");
74     const [mediumUri, setMediumUri] = useState("");
75     const [storing, setStoring] = useState(false);
76     const [storeError, setStoreError] = useState<IngestError | null>(null);
77     useEffect(() => {
78         let alive = true;
79         getCapabilities()
80             .then((c) => {
81                 if (!alive) return;
82                 setCloudAvailable(c.deployment?.cloud_available === true);
83                 setBackends(c.storage?.backends ?? []);
84             })
85             .catch((err) => log("warn", "capabilities.unavailable", { error: String(err) }));
86     }, []);
87     return () => {
88         alive = false;
89     };
90 }

```

```

84      // Only send a choice when the picker is actually shown; otherwise omit it (? server
default).
85      const sendCompute = cloudAvailable ? compute : undefined;
86      // CLOUD selected but the cost note not yet accepted ? block submit (don't silently
run local, and
87      // don't dispatch a paid job without consent).
88      const cloudBlocked = cloudAvailable && compute === "cloud" && !cloudAck;
89
90      // Which medium segments to offer: local always; "bucket" if s3 OR gcs is usable;
"drive" if a Drive
91      // mount is usable. The picker only appears when there's a REAL choice (a non-local
usable backend).
92      const canUse = (id: string) => backends.some((b) => b.id === id && b.usable);
93      const canBucket = canUse("s3") || canUse("gcs");
94      const canDrive = canUse("gdrive");
95      const mediumOptions: Medium[] = ["local", ...(canBucket ? ["bucket" as const] : []),
...(canDrive ? ["drive" as const] : [])];
96      const showMediumPicker = mediumOptions.length > 1;
97      const needsMediumUri = medium !== "local";
98      // A non-local medium needs a destination URI before anything can be stored/submitted.
99      const mediumBlocked = needsMediumUri && mediumUri.trim() === "";
100
101      // Store the obtained source (an uploaded local path, or a pasted at-rest URI) INTO
the chosen medium,
102      // then process the durable copy. A failed store is loud (surfaced like every other
ingest error).
103      const storeThenProcess = async (src: { uploadedPath?: string; sourceUri?: string },
displayName?: string) => {
104          const cid = newCorrelationId();
105          setStoreError(null);
106          setStoring(true);
107          try {
108              const asset = await createAsset({ ...src, mediumUri: mediumUri.trim() }, cid);
109              log("info", "asset.stored", { cid, video_id: asset.video_id, medium: asset.medium,
copied: asset.copied });
110              submit(asset.stored_uri, locale, sendCompute, displayName ??
sourceLabel(asset.stored_uri) ?? undefined); // index the stored copy
111          } catch (err) {
112              setStoreError(classifyError(err));
113              log("error", "asset.store_failed", { cid, error: String(err) });
114          } finally {
115              setStoring(false);
116          }
117      };
118
119      // On upload completion: local medium ? process the upload directly (today's flow); a
non-local
120      // medium ? store a durable copy into it first, then process. The arrow is recreated
each render
121      // (useUpload reads onCompleteRef.current), so `medium`/`mediumUri`/`sendCompute` are
always fresh.
122      const upload = useUpload((path, filename) => {
123          if (medium === "local") submit(path, locale, sendCompute, filename);
124          else void storeThenProcess({ uploadedPath: path }, filename);
125      });
126      const busy = ingestBusy || upload.busy || storing;
127      useEffect(() => {
128          onBusyChange?.(busy);
129          return () => {
130              if (busy) onBusyChange?.(false);
131          };
132      }, [busy, onBusyChange]);
133      // Disable the submit surfaces while busy, awaiting the cloud cost ack, or missing a
medium URI.
134      const inputsDisabled = busy || cloudBlocked || mediumBlocked;

```

```

135
136     const onSubmitUri = (e: FormEvent) => {
137         e.preventDefault();
138         if (inputsDisabled) return;
139         // The URI form is the SOURCE only in local mode (a bucket URL / host path to index
directly). For
140         // a non-local medium the source is the upload; the text box below is the
DESTINATION, not this.
141         const displayName = sourceLabel(uri);
142         setActiveSource(displayName);
143         submit(uri, locale, sendCompute, displayName ?? undefined);
144     };
145     const onFile = (e: ChangeEvent<HTMLInputElement>) => {
146         const file = e.target.files?.[0];
147         // Symmetric with onSubmitUri: never start while blocked (the disabled input already
prevents this).
148         if (file && !inputsDisabled) {
149             setActiveSource(file.name);
150             upload.start(file);
151         }
152         e.target.value = ""; // let re-picking the same file fire change again
153     };
154     const cancelAll = () => {
155         upload.cancel();
156         cancelIngest();
157         setActiveSource(null);
158     };
159     const resetAll = () => {
160         upload.reset();
161         resetIngest();
162         setStoreError(null);
163         setActiveSource(null);
164     };
165
166     // Shared mapping with the build flow (lib/errorText): an `engine` failure carries the
engine's own
167     // message (a 400 scheme/path/extension detail, a worker error); every other code maps
to a friendly
168     // localized line. Surface whichever half failed (upload or engine) ? they're mutually
exclusive.
169     const errorState =
170         upload.phase.status === "error"
171             ? upload.phase.error
172             : storeError ?? (phase.status === "error" ? phase.error : null);
173     const errorMsg = errorState ? errorText(t, errorState) : null;
174     const visibleSource = upload.phase.status === "uploading" ? upload.phase.filename :
activeSource;
175     const processingName =
176         phase.status === "submitting" || phase.status === "polling" ? phase.displayName :
undefined;
177
178     return (
179         <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
testid="ingest-panel">
180             <h2 className="text-lg font-bold">{t("ingest.title")}</h2>
181             <p className="mt-1 max-w-2xl text-sm text-ink/60">{t("ingest.intro")}</p>
182
183             {/* COMPUTE PICKER (item 3): shown only when this server can dispatch to a cloud
GPU. Default
184                 LOCAL; CLOUD reveals a cost note + a required acknowledgement before any
submit can run. */}
185             {cloudAvailable && (
186                 <fieldset className="mt-4 rounded-xl border border-black/10 p-3" data-
testid="compute-picker">
187                     <legend className="px-1 text-xs font-semibold uppercase tracking-wide text-

```

```

ink/40">
188         {t("ingest.compute.legend")}}
189     </legend>
190     <div className="mt-1 flex flex-wrap gap-2">
191         {[("local", "cloud") as const].map((opt) => (
192             <button
193                 key={opt}
194                 type="button"
195                 aria-pressed={compute === opt}
196                 disabled={busy}
197                 onClick={() => setCompute(opt)}
198                 className={
199                     "min-h-11 rounded-xl border px-4 py-2 text-sm font-semibold
disabled:opacity-40 " +
200                     (compute === opt
201                         ? "border-green bg-green/10 text-ink"
202                         : "border-black/15 text-ink/70 hover:border-green")
203                     }
204                 >
205                     {t(`ingest.compute.${opt}`)}
206                 </button>
207             )]}
208     </div>
209     {compute === "cloud" && (
210         <div className="mt-3" data-testid="compute-cost">
211             <p className="text-xs text-ink/60">{t("ingest.compute.cloudCost")}</p>
212             <label className="mt-2 flex items-center gap-2 text-sm text-ink/80">
213                 <input
214                     type="checkbox"
215                     checked={cloudAck}
216                     disabled={busy}
217                     onChange={(e) => setCloudAck(e.target.checked)}
218                     className="h-4 w-4"
219                 />
220                 {t("ingest.compute.ack")}
221             </label>
222             {cloudBlocked && (
223                 <p className="mt-1 text-xs text-amber-700" data-testid="compute-ack-
required">
224                     {t("ingest.compute.ackRequired")}
225                 </p>
226             )}
227             </div>
228         )}
229     </fieldset>
230 )}
231
232     /* MEDIUM PICKER (P5, D14): where to STORE this video. Rendered only from the
media this box can
233     actually use (capabilities.storage.backends, usable-only), and only when
there's a real
234     choice beyond local. A non-local medium reveals a destination-URI field; the
video is stored
235     there (a durable, MD5-keyed copy ? free-space checked) and then indexed. Self-
host posture. */}
236     {showMediumPicker && (
237         <fieldset className="mt-4 rounded-xl border border-black/10 p-3" data-
testid="medium-picker">
238             <legend className="px-1 text-xs font-semibold uppercase tracking-wide text-
ink/40">
239                 {t("ingest.medium.legend")}
240             </legend>
241             <div className="mt-1 flex flex-wrap gap-2">
242                 {mediumOptions.map((opt) => (
243                     <button

```

```

244         key={opt}
245         type="button"
246         aria-pressed={medium === opt}
247         disabled={busy}
248         onClick={() => {
249             setMedium(opt);
250             setStoreError(null);
251         }}
252         data-testid={`medium-${opt}`}
253         className={
254             "min-h-11 rounded-xl border px-4 py-2 text-sm font-semibold
disabled:opacity-40 " +
255             (medium === opt
256               ? "border-green bg-green/10 text-ink"
257               : "border-black/15 text-ink/70 hover:border-green")
258         }
259         >
260             {t(`storage.${opt}`)}
261         </button>
262     )}}
263 </div>
264 {needsMediumUri && (
265     <div className="mt-3" data-testid="medium-dest">
266         <input
267             type="text"
268             value={mediumUri}
269             onChange={(e) => setMediumUri(e.target.value)}
270             placeholder={medium === "drive" ? t("ingest.medium.drivePlaceholder") :
t("ingest.medium.bucketPlaceholder")}
271             aria-label={t("ingest.medium.destAria")}
272             disabled={busy}
273             className="min-h-11 w-full max-w-md rounded-xl border border-black/15
bg-white px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
274             />
275         <p className="mt-2 text-xs text-ink/50">{t("ingest.medium.destHint")}</p>
276         {mediumBlocked && (
277             <p className="mt-1 text-xs text-amber-700" data-testid="medium-
required">
278                 {t("ingest.medium.destRequired")}
279             </p>
280         )}
281     </div>
282 )}
283 </fieldset>
284 )}
285
286 {/* PRIMARY: upload a local file (T4). A native file input, visually a button
(?44px, A4). */}
287 <div className="mt-4">
288     <label
289         className={
290             // focus-within makes the visible button show a focus ring when the (sr-
only) input is
291             // focused ? a keyboard user needs a visible focus indicator (WCAG 2.4.7).
292             "inline-flex min-h-11 items-center rounded-xl bg-ink px-4 py-2 text-sm font-
semibold text-white hover:bg-ink2 focus-within:outline-none focus-within:ring-2 focus-
within:ring-green focus-within:ring-offset-2 " +
293             (inputsDisabled ? "pointer-events-none opacity-40" : "cursor-pointer")
294         }
295     >
296         {t("ingest.chooseFile")}
297     <input
298         type="file"
299         accept=".mp4,.mov,video/mp4,video/quicktime"
300         aria-label={t("ingest.uploadAria")}

```

```

301         disabled={inputsDisabled}
302         onChange={onFile}
303         className="sr-only"
304     />
305 </label>
306 <p className="mt-2 text-xs text-ink/40">{t("ingest.fileHint")}</p>
307 </div>
308
309    /* SECONDARY: in LOCAL mode, point at a cloud bucket / host path to index
directly. Hidden for a
310        non-local medium, where the destination field above owns the URI box and the
upload is the
311        source (avoids two conflicting URI inputs). */
312    {medium === "local" && (
313        <div className="mt-4 border-t border-black/5 pt-4">
314            <p className="text-xs font-semibold uppercase tracking-wide text-
ink/40">{t("ingest.orLink")}</p>
315            <form onSubmit={onSubmitUri} className="mt-2 flex flex-wrap items-center gap-2">
316                <input
317                    type="text"
318                    value={uri}
319                    onChange={(e) => setUri(e.target.value)}
320                    placeholder={t("ingest.uriPlaceholder")}
321                    aria-label={t("ingest.uriAriaLabel")}
322                    disabled={inputsDisabled}
323                    className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15
bg-white px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
324                />
325                <button
326                    type="submit"
327                    disabled={inputsDisabled}
328                    className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-
white disabled:opacity-40"
329                >
330                    {phase.status === "submitting" ? t("ingest.submitting") :
t("ingest.submit")}
331                </button>
332            </form>
333            <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>
334        </div>
335    )}
336
337    /* Live status (aria-live so screen readers hear progress) as icon+text chips ?
never icon-only
338        (A8). Upload shows a determinate % bar; the engine phase is indeterminate
(phase words). */
339    <div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
340        {upload.phase.status === "uploading" && (
341            <div data-testid="upload-progress">
342                /* Static chip label (not the per-tick %) so the aria-live region announces
once; the live
343                    % rides the progressbar's aria-valuenow + a sighted-only label (A8/T4).
*/
344                <StatusChip tone="info" icon={<Spinner />}
label={t("ingest.uploadingStatus")} />
345                <p className="mt-2 text-xs font-medium text-ink/70" data-testid="ingest-
source">
346                    {t("ingest.sourceFile", { filename: upload.phase.filename })}
347                </p>
348            <div className="mt-2 flex max-w-sm items-center gap-2">
349                <div
350                    className="h-1.5 flex-1 overflow-hidden rounded-full bg-black/10"
role="progressbar"
351                    aria-label={t("ingest.uploadProgress")}
352                    aria-valuenow={upload.phase.pct}

```

```

354         aria-valuemin={0}
355         aria-valuemax={100}
356     >
357         <div className="h-full bg-green transition-all" style={{ width:
358         `${upload.phase.pct}%` }> />
359         </div>
360         <span aria-hidden="true" className="text-xs tabular-nums text-ink/50">
361             {upload.phase.pct}%
362         </span>
363     </div>
364     <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
365     <button
366         type="button"
367         onClick={cancelAll}
368         className="mt-2 inline-flex min-h-11 items-center rounded-xl border
369         border-black/15 px-4 text-sm hover:border-green"
370     >
371         {t("ingest.cancel")}
372     </button>
373 </div>
374 }}
375 {storing && (
376     <div data-testid="ingest-storing">
377         <StatusChip tone="info" icon={<Spinner />}
378         label={t("ingest.medium.storing")} />
379         {visibleSource && (
380             <p className="mt-2 text-xs font-medium text-ink/70" data-testid="ingest-
381             source">
382                 {t("ingest.sourceFile", { filename: visibleSource })}
383             </p>
384         )}
385     </div>
386 )}
387 {ingestBusy && (
388     <div>
389         <StatusChip
390             tone="info"
391             icon={<Spinner />}
392             label={
393                 t("ingest.working") +
394                 (processingName ? ` · ${processingName} : "" ) +
395                 (phase.status === "polling" && phase.progress
396                 ? ` · ${t("ingest.progress", { progress: phase.progress })}`
397                 : "")
398             }
399         </div>
400         {visibleSource && (
401             <p className="mt-2 text-xs font-medium text-ink/70" data-testid="ingest-
402             source">
403                 {t("ingest.sourceFile", { filename: visibleSource })}
404             </p>
405         )}
406         {phase.status === "polling" && (
407             <div className="mt-2 space-y-1 text-xs text-ink/50" data-testid="ingest-
408             heartbeat">
409                 {phase.resumed && <p>{t("ingest.resumeNotice")}</p>}
410                 <p>
411                     {t("ingest.elapsed", { elapsed: formatElapsed(phase.elapsedSec) })} ·
412                 </p>
413                 <p>{t("ingest.reloadHint")}</p>
414             </div>
415         )}
416     </div>
417     /* Reassurance for slow uplinks: the job runs on the server, so it's safe
418     to wait. */}

```



```

411         <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
412         <button
413             type="button"
414             onClick={cancelAll}
415             className="mt-2 inline-flex min-h-11 items-center rounded-xl border
border-black/15 px-4 text-sm hover:border-green"
416         >
417             {t("ingest.cancel")}
418         </button>
419     </div>
420 )}
421 {errorMsg && (
422     <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-
red-800" data-testid="ingest-error">
423         <StatusChip tone="error" icon="?" label={t("ingest.statusFailed")} />
424         <p className="mt-2">{errorMsg}</p>
425         <button
426             type="button"
427             onClick={resetAll}
428             className="mt-2 inline-flex min-h-11 items-center rounded-lg border
border-red-300 px-3 text-sm hover:bg-red-100"
429         >
430             {t("ingest.retry")}
431         </button>
432     </div>
433 )}
434 </div>
435 </section>
436 );
437 }
438

```

10. assistant (2026-07-04T01:28:41.040Z)

Now let me read the error-text mapping, i18n setup, client, and the relevant tests.

11. user (2026-07-04T01:28:42.565Z)

```

1      // The ONE place a classified error (lib/errors.ts) becomes user-facing text. Both
surfaces use it:
2      // the ingest flow (IngestPanel) and the build flow (App.onBuild ? CompileResult), so a
5xx / engine-
3      // down failure reads the same friendly way everywhere instead of a raw "HTTP 500" /
fetch message.
4      //
5      // `engine` carries the engine's OWN message (the most specific) ? shown verbatim, never
translated.
6      // Every other code maps to a friendly localized line in the shared `errors.*`
namespace. Kept out of
7      // errors.ts so that module stays i18n-free and unit-testable without a translation
context.
8      import type { TFunction } from "i18next";
9      import type { IngestError } from "../errors";
10
11     export function errorText(t: TFunction, e: IngestError): string {
12         if (e.code === "engine") return e.detail ?? t("errors.engineGeneric");
13         return t(`errors.${e.code}`);
14     }
15

```

12. user (2026-07-04T01:28:43.613Z)

```

1      // @vitest-environment jsdom
2      //

```

```

3      // errorText is the single mapping from a classified error ? user-facing text, shared by
the ingest
4      // and build flows (A5). These pin: the engine message passes through verbatim, a
detail-less engine
5      // error degrades to a friendly localized line (never a raw key), and every non-engine
code resolves
6      // to a real catalog string in the shared `errors.*` namespace.
7      import { describe, it, expect, beforeAll } from "vitest";
8      import i18n from "../i18n";
9      import { errorText } from "../errorText";
10     import type { IngestErrorCode } from "../errors";
11
12     beforeAll(async () => {
13         await i18n.changeLanguage("en");
14     });
15
16     describe("errorText", () => {
17         it("an engine error shows the engine's own detail verbatim (most specific message)",
() => {
18             expect(errorText(i18n.t, { code: "engine", detail: "min_shot_count too low"
})).toBe("min_shot_count too low");
19         });
20
21         it("an engine error with no detail degrades to a friendly localized line (not a raw
key)", () => {
22             const s = errorText(i18n.t, { code: "engine" });
23             expect(s).toBe(i18n.t("errors.engineGeneric"));
24             expect(s).not.toMatch(/^errors\.\/);
25             expect(s.length).toBeGreaterThan(0);
26         });
27
28         it("networkError maps to the friendly 'is it running?' line", () => {
29             expect(errorText(i18n.t, { code: "networkError" })).toMatch(/is it running/i);
30         });
31
32         it("every non-engine code resolves to a real catalog string (never a raw key)", () =>
{
33             for (const code of ["invalidUri", "networkError", "emptyResult", "timeout"] as
IngestErrorCode[]) {
34                 const s = errorText(i18n.t, { code });
35                 expect(s, code).not.toMatch(/^errors\.\/);
36                 expect(s.length, code).toBeGreaterThan(0);
37             }
38         });
39
40         it("localizes per the active locale (Kannada network message)", async () => {
41             await i18n.changeLanguage("kn");
42             expect(errorText(i18n.t, { code: "networkError" })).toBe("Khe1Sutra ???????????????.
??? ?????????????????");
43             await i18n.changeLanguage("en");
44         });
45     });
46

```

13. user (2026-07-04T01:28:44.128Z)

```

1      import { describe, it, expect } from "vitest";
2      import { parseDetail, classifyError } from "../errors";
3      import { ApiError } from "../api/client";
4
5      describe("parseDetail", () => {
6          it("extracts FastAPI's {detail}", () => {
7              expect(parseDetail(JSON.stringify({ detail: "unsupported storage URI scheme"
}))).toBe(
8                  "unsupported storage URI scheme",

```

```

9         );
10    });
11    it("returns the raw body when it isn't JSON or has no string detail", () => {
12        expect(parseDetail("plain text")).toBe("plain text");
13        expect(parseDetail(JSON.stringify({ other: 1 }))).toBe(JSON.stringify({ other: 1
14    })));
15        expect(parseDetail(JSON.stringify({ detail: { nested: true }
16    }))).toBe(JSON.stringify({ detail: { nested: true } }));
17    });
18    it("suppresses proxy HTML/text boilerplate instead of treating it as an engine
19    detail", () => {
20        expect(parseDetail("<!DOCTYPE html><html><title>502 Bad
21    Gateway</title></html>")).toBe("");
22        expect(parseDetail("Error occurred while trying to proxy:
23    localhost:5173/api/query")).toBe("");
24    });
25    });
26    describe("classifyError", () => {
27        it("a network throw (ApiError with no status) ? networkError", () => {
28            expect(classifyError(new ApiError("net", { cid: "c" }))).toEqual({ code:
29    "networkError" });
30        });
31        it("an HTTP error with a body ? engine + the FastAPI detail", () => {
32            const err = new ApiError("x", { status: 400, body: JSON.stringify({ detail:
33    "unsupported storage URI scheme" }) });
34            expect(classifyError(err)).toEqual({ code: "engine", detail: "unsupported storage
35    URI scheme" });
36        });
37        it("a bare 5xx with no body ? networkError (friendly 'is the engine running?', not
38    'HTTP 500')", () => {
39            expect(classifyError(new ApiError("x", { status: 500 }))).toEqual({ code:
40    "networkError" });
41            expect(classifyError(new ApiError("x", { status: 502 }))).toEqual({ code:
42    "networkError" });
43        });
44        it("a 5xx WITH a detail still surfaces the engine's message", () => {
45            const err = new ApiError("x", { status: 500, body: JSON.stringify({ detail: "failed
46    to persist job record" }) });
47            expect(classifyError(err)).toEqual({ code: "engine", detail: "failed to persist job
48    record" });
49        });
50        it("a 5xx proxy HTML body ? networkError, not raw markup in the UI", () => {
51            const err = new ApiError("x", { status: 502, body: "<html><body>Bad
52    Gateway</body></html>" });
53            expect(classifyError(err)).toEqual({ code: "networkError" });
54        });
55        it("a 5xx proxy text body ? networkError, not a proxy implementation detail", () => {
56            const err = new ApiError("x", { status: 500, body: "Error occurred while trying to
57    proxy: localhost:5173/api/process" });
58            expect(classifyError(err)).toEqual({ code: "networkError" });
59        });
60        it("a 4xx with no body keeps the status (a client-side mistake, not unreachable)", ()
61    => {
62            expect(classifyError(new ApiError("x", { status: 404 }))).toEqual({ code: "engine",
63    detail: "HTTP 404" });
64        });
65        it("a non-ApiError ? engine + the stringified error", () => {
66            expect(classifyError(new Error("boom"))).toEqual({ code: "engine", detail: "Error:
67    boom" });
68        });
69    });
70    });
71    });

```

```

1      // @vitest-environment jsdom
2      //
3      // T4 end to end through IngestPanel: pick a local file ? it chunks up to /api/upload/*
? the returned
4      // server PATH is fed to POST /api/process ? poll ? onLoaded(video_id). The keystone for
alpha users
5      // who have a FILE, not a gs:// URI. Also pins that the file picker is present +
labelled (a11y/A4).
6      import { describe, it, expect, vi, beforeEach, afterEach } from "vitest";
7      import { render, screen, cleanup, fireEvent, act } from "@testing-library/react";
8      import i18n from "../i18n";
9      import { IngestPanel } from "../IngestPanel";
10
11      // Flush promise microtasks (the upload/process awaits) under fake timers ? waitFor
can't advance them.
12      async function flush(times = 15) {
13          for (let i = 0; i < times; i += 1) {
14              await act(async () => {
15                  await vi.advanceTimersByTimeAsync(0);
16              });
17          }
18      }
19
20      const MB = 1024 * 1024;
21      const ok = (j: unknown) => ({ ok: true, status: 200, json: async () => j, text: async ()
=> JSON.stringify(j) });
22
23      let processBody: { video_path?: string } | null = null;
24
25      function uploadThenProcessFetch() {
26          processBody = null;
27          return vi.fn(async (url: string | URL, init?: RequestInit) => {
28              const u = String(url);
29              const m = init?.method ?? "GET";
30              if (u === "/api/upload/init") return ok({ upload_id: "up1", max_part_mb: 1,
next_part: "/api/upload/up1/part/0" });
31              if (u.includes("/api/upload/up1/part/")) return ok({ upload_id: "up1",
received_parts: 1, received_bytes: (init?.body as Blob).size });
32              if (u.endsWith("/complete")) return ok({ path: "/srv/uploads/match.mp4", video_id:
"PRE", size_bytes: 1 });
33              if (u === "/api/process" && m === "POST") {
34                  processBody = JSON.parse(init!.body as string);
35                  return ok({ job_id: "j", status: "queued", poll: "/api/jobs/j" });
36              }
37              if (u.startsWith("/api/jobs/")) return ok({ job_id: "j", status: "done", video_id:
"VIDFINAL", result: { status: "success", video_id: "VIDFINAL" } });
38              throw new Error(`unexpected fetch ${m} ${u}`);
39          }) as unknown as typeof fetch;
40      }
41
42      const videoFile = (bytes: number) => new File([new Uint8Array(bytes)], "match.mp4", {
type: "video/mp4" });
43
44      const pickFile = (file: File) => {
45          const input = screen.getByLabelText("Choose a video file to upload");
46          Object.defineProperty(input, "files", { value: [file], configurable: true });
47          fireEvent.change(input);
48      };
49
50      beforeEach(async () => {
51          window.localStorage.clear();
52          await i18n.changeLanguage("en");
53      });
54
55      afterEach(() => {

```

```

56     cleanup();
57     vi.restoreAllMocks();
58     vi.unstubAllGlobals();
59     vi.useRealTimers();
60 });
61
62 describe("T4: in-UI file upload", () => {
63     it("offers a labelled file picker with a visible keyboard focus ring (WCAG 2.4.7)", ()
=> {
64         vi.stubGlobal("fetch", vi.fn());
65         render(<IngestPanel onLoaded={vi.fn()} />);
66         const input = screen.getByLabelText("Choose a video file to upload");
67         expect(input).toBeTruthy();
68         expect(screen.getByText("Choose a video file")).toBeTruthy();
69         // The sr-only input's focus must surface on the visible label (focus-within ring).
70         expect(input.closest("label")?.className).toMatch(/focus-within:ring/);
71     });
72
73     it("uploads the picked file, feeds the server path to /api/process, and loads the
resulting video_id", async () => {
74         vi.useFakeTimers();
75         vi.stubGlobal("fetch", uploadThenProcessFetch());
76         const onLoaded = vi.fn();
77         render(<IngestPanel onLoaded={onLoaded} />);
78
79         pickFile(videoFile(0.3 * MB));
80         expect(screen.getByTestId("ingest-source").textContent).toContain("match.mp4");
81
82         // Flush the upload chain (init ? part ? complete) + the process submit ? schedules
the poll.
83         await flush();
84         // The uploaded server PATH (not the URI) is what gets processed.
85         expect(processBody?.video_path).toBe("/srv/uploads/match.mp4");
86         expect(screen.getByTestId("ingest-source").textContent).toContain("match.mp4");
87         expect(screen.getByText(/Processing your video.*match\.mp4/i)).toBeTruthy();
88
89         // Poll tick ? done ? the job's canonical video_id is handed up.
90         await act(async () => {
91             await vi.advanceTimersByTimeAsync(1000);
92         });
93         await flush();
94         expect(onLoaded).toHaveBeenCalledWith("VIDFINAL", "match.mp4");
95     });
96 });
97

```

15. assistant (2026-07-04T01:28:48.284Z)

Now let me examine the i18n setup and locale files to understand their structure.

16. user (2026-07-04T01:28:49.768Z)

```

1     // i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
2     //
3     // Per docs/archives/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4     //   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5     //   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in
the catalog,
6     //     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7     //   - one negotiation order shared with the marketing site (B3);
8     //   - always-fallback to `en` so a missing translation degrades to English, never a raw
key.
9     import i18n from "i18next";
10    import { initReactI18next } from "react-i18next";
11    import LanguageDetector from "i18next-browser-language-detector";

```

```

12     import ICU from "i18next-icu";
13     // Catalogs are HOISTED to repo-root /locales (D-CATALOG-HOME) ? the single source of
truth shared
14     // by this SPA and the marketing site's t() shim (tracker B3). Vite resolves the
workspace root via
15     // the repo `.git` marker, so importing the parent-dir /locales works in dev, build, and
vittest.
16     import enCommon from "../../locales/en/common.json";
17     import knCommon from "../../locales/kn/common.json";
18     import hiCommon from "../../locales/hi/common.json";
19     import esCommon from "../../locales/es/common.json";
20     import daCommon from "../../locales/da/common.json";
21     import idCommon from "../../locales/id/common.json";
22
23     // Supported locales: en/kn/hi foundation (FRIENDLY D6) + MULTILINGUAL_EXPANSION Phase A
(es/da/id,
24     // Latin, catalog-only). Anything else falls back to `en`.
25     export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
26     export type Locale = (typeof SUPPORTED_LOCALES)[number];
27     export const DEFAULT_LOCALE: Locale = "en";
28
29     // ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker
B3), so a
30     // visitor's language choice carries across both surfaces.
31     export const LANG_STORAGE_KEY = "khelsutra.lang";
32
33     // Catalogs live in repo-root /locales (D-CATALOG-HOME), consumed by both surfaces. `kn`
+ `hi`
34     // shipped (B5/B6, AI-drafted ? native review pending). A missing key in any locale
still falls back
35     // to `en` ? the by-design invariant.
36     const resources = {
37         en: { common: enCommon },
38         kn: { common: knCommon },
39         hi: { common: hiCommon },
40         es: { common: esCommon },
41         da: { common: daCommon },
42         id: { common: idCommon },
43     } as const;
44
45     void i18n
46         .use(ICU)
47         .use(LanguageDetector)
48         .use(initReactI18next)
49         .init({
50             resources,
51             fallbackLng: DEFAULT_LOCALE,
52             supportedLngs: [...SUPPORTED_LOCALES],
53             nonExplicitSupportedLngs: true, // en-IN -> en
54             defaultNS: "common",
55             ns: ["common"],
56             interpolation: { escapeValue: false }, // React already escapes
57             returnNull: false,
58             // Negotiation order (I18N_PLAN §2.3): persisted pref -> ?lang= -> browser -> en.
59             detection: {
60                 order: ["localStorage", "querystring", "navigator"],
61                 lookupLocalStorage: LANG_STORAGE_KEY,
62                 lookupQuerystring: "lang",
63                 caches: ["localStorage"],
64             },
65             react: { useSuspense: false },
66         });
67
68     // Keep <html lang> in sync with the active locale (screen readers + SEO use it).
Reflects the

```

```

69     // resolved content language, so an `en` fallback for an absent locale still reads as
`en`.
70     function syncDocumentLang(lng: string) {
71         if (typeof document !== "undefined") {
72             document.documentElement.lang = (i18n.resolvedLanguage || lng ||
DEFAULT_LOCALE).split("-")[0];
73         }
74     }
75     i18n.on("languageChanged", syncDocumentLang);
76     syncDocumentLang(i18n.language ?? DEFAULT_LOCALE);
77
78     export default i18n;
79

```

17. user (2026-07-04T01:28:50.301Z)

No files found

18. user (2026-07-04T01:28:50.672Z)

No files found

19. assistant (2026-07-04T01:28:54.952Z)

Locale files live at repo root `/locales`. Let me find them and read the English catalog to understand the `errors.\*` and `ingest.\*` structure.

20. user (2026-07-04T01:28:55.034Z)

```

locales\da\common.json
locales\en\common.json
locales\es\common.json
locales\hi\common.json
locales\id\common.json
locales\kn\common.json

```

21. user (2026-07-04T01:28:58.289Z)

```

1      {
2          "app": {
3              "badge": "pick your rallies · alpha",
4              "title": "Pick the rallies for your reel",
5              "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-
tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want.",
6              "currentVideo": "Working on <b>{name}</b>",
7              "currentVideoUnknown": "your video"
8          },
9          "lang": {
10             "label": "Language",
11             "en": "English",
12             "kn": "?????",
13             "hi": "??????",
14             "es": "Español",
15             "da": "Dansk",
16             "id": "Bahasa Indonesia"
17         },
18         "bulk": {
19             "selectAll": "Select all",
20             "clear": "Clear",
21             "invert": "Invert"
22         },
23         "mode": {
24             "demo": "These are sample rallies ? process a video above to work on a real match.",
25             "loading": "Finding the rallies in your video?",

```

```

26     "error": "Couldn't load this video's rallies: {error}",
27     "loaded": "Found <b>{count}</b> rallies in your video."
28 },
29 "query": {
30     "placeholder": "e.g. over 10s · top 15 longest · shortest first",
31     "ariaLabel": "Filter rallies by length, count or order",
32     "apply": "Apply",
33     "notAvailable": "not available yet",
34     "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
35     "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by
rally length instead.",
36     "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
37     "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
38     "try": "Sample queries:",
39     "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
<x>experimental</x> (under development).",
40 },
41 "grid": {
42     "empty": "No rallies to show yet.",
43     "rally": "Rally {n}",
44     "inReel": "Rally {n}, in reel",
45     "notInReel": "Rally {n}, not in reel",
46     "start": "start",
47     "long": "long",
48     "shots": "~{count} shots · experimental",
49     "shotsTitle": "Shot count is experimental (under development) and may be
inaccurate{conf}. Filter by rally length instead.",
50     "shotsConfidence": " ? confidence: {conf}"
51 },
52 "footer": {
53     "count": "{count, plural, one {# rally} other {# rallies}}",
54     "summaryRest": "selected · {total} total",
55     "reelName": "Reel name",
56     "reelNamePlaceholder": "my-highlights",
57     "build": "Build reel ({count})",
58     "building": "Building?",
59     "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
be skipped, so the build would fail. Pick a longer rally.",
60     "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
they'd all be skipped, so the build would fail. Pick longer rallies.",
61     "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",
62     "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
63 },
64 "result": {
65     "share": "Share on WhatsApp",
66     "shareFile": "Share video",
67     "sharePreparing": "Preparing?",
68     "shareFallback": "File sharing isn't available here. Download the reel, then use
WhatsApp.",
69     "shareFailed": "Couldn't open sharing. Download the reel, then use WhatsApp.",
70     "shareText": "I made my badminton highlights reel with KhelSutra ? Try it:
khelsutra.guru",
71     "ready": "Your reel is ready",
72     "failed": "Build failed",
73     "building": "Stitching your reel?",
74     "buildingReassure": "Joining your selected rallies into one video ? this usually
only takes a moment.",
75     "dismiss": "Dismiss",
76     "download": "Download {filename}"
77 },
78 "build": {
79     "noVideo": "These are sample rallies ? process a real video first to build a reel."
80 },
81 "ingest": {

```



```

82         "title": "Process a video",
83         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
84         "uriPlaceholder": "gs://your-bucket/match.mp4",
85         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
86         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
87         "submit": "Process video",
88         "submitting": "Submitting?",
89         "cancel": "Cancel",
90         "working": "Processing your video?",
91         "progress": "{progress}",
92         "resumeNotice": "Resumed this processing job after refresh.",
93         "elapsed": "Elapsed {elapsed}",
94         "heartbeat": "Last checked just now",
95         "reloadHint": "You can reload this page ? KhelSutra will keep checking this job.",
96         "retry": "Try again",
97         "reassure": "Safe to wait ? KhelSutra keeps working even if your connection is slow;
a long video can take several minutes.",
98         "statusFailed": "Couldn't process",
99         "chooseFile": "Choose a video file",
100        "uploadAria": "Choose a video file to upload",
101        "fileHint": "Pick an .mp4 or .mov from this device ? it uploads, then KhelSutra
finds the rallies.",
102        "orLink": "Or use a cloud link",
103        "uploadingStatus": "Uploading?",
104        "sourceFile": "File: {filename}",
105        "uploadProgress": "Upload progress",
106        "compute": {
107            "legend": "Where should this run?",
108            "local": "On my computer",
109            "cloud": "In the cloud",
110            "cloudCost": "Cloud processing runs on a rented GPU ? faster for long videos, but
it may cost a little (often just a few cents per match).",
111            "ack": "I understand cloud processing may cost a little.",
112            "ackRequired": "Please accept the note above to run in the cloud."
113        },
114        "medium": {
115            "legend": "Where should we store this video?",
116            "destAria": "Storage destination ? a bucket URL or a Google Drive folder",
117            "bucketPlaceholder": "gcs://my-bucket/videos",
118            "drivePlaceholder": "gdrive://Matches",
119            "destHint": "We keep a durable copy here, keyed to the video ? after checking
there's room.",
120            "destRequired": "Enter a destination to store this video.",
121            "storing": "Storing in your medium?"
122        }
123    },
124    "errors": {
125        "networkError": "Can't reach KhelSutra. Is it running?",
126        "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
127        "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
128        "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
129        "engineGeneric": "Something went wrong. Please try again."
130    },
131    "tap": {
132        "title": "Tap to filter:",
133        "longest": "Longest first",
134        "shortest": "Shortest first",
135        "over10": "Over 10 seconds",
136        "over20": "Over 20 seconds",
137        "top5": "Top 5 longest",

```

```

138     "top10": "Top 10 longest"
139 },
140 "site": {
141     "reveal": {
142         "share": "Share on WhatsApp",
143         "shareText": "Check out KhelSutra ? it turns a full badminton match into a clean
highlights reel ? khelsutra.guru"
144     },
145     "join": {
146         "gpuLabel": "Do you have a powerful computer that could process videos on its
own?",
147         "gpuHint": "A gaming PC or laptop with a graphics card. No worries if not ? we can
run it in the cloud for you.",
148         "gpuYes": "Yes ? a gaming PC or laptop with a graphics card",
149         "gpuUnsure": "Not sure",
150         "gpuNo": "No",
151         "gpuCloud": "No ? please run it in the cloud for me",
152         "storageLabel": "Where do your match videos live? How would you share them?",
153         "storageHint": "(pick any)",
154         "storageGdrive": "Google Drive",
155         "storageOnedrive": "OneDrive / Microsoft 365",
156         "storageDropbox": "Dropbox",
157         "storageBucket": "A cloud storage bucket ? advanced (e.g. Amazon S3, Google
Cloud)",
158         "storageLocal": "SD card or the device itself",
159         "storageUnsure": "Not sure",
160         "sending": "Sending?",
161         "title": "Get into the KhelSutra alpha",
162         "intro": "Invite-only. Tell us a little about your setup ? it helps us get you the
best results, and shapes what we build next.",
163         "teaser": "<span aria-hidden=\\"true\\"></span> Sign up to watch the tool in action
? and a 30-second sample reel it made ? the moment you're in.",
164         "segLabel": "I'm a?",
165         "segAcademy": "Coaching academy / club",
166         "segIndividual": "Individual player",
167         "name": "Name",
168         "email": "Email",
169         "emailHint": "(so we can reach you)",
170         "city": "City",
171         "optional": "(optional)",
172         "orgName": "Academy / club name",
173         "courtsLabel": "How many courts do you record?",
174         "courtsSelect": "Select?",
175         "courts1": "1 court",
176         "courts2to4": "2-4 courts",
177         "courts5plus": "5+ courts",
178         "message": "Anything else?",
179         "messageHint": "(how you record, what you'd want?)",
180         "consent": "Okay to email me about the KhelSutra alpha.",
181         "note": "We never publish your footage; footage involving minors is never used to
improve the tool. See our <a href=\\"/privacy\\">Privacy Policy</a>.",
182         "done": "Thanks ? we've got it. We'll be in touch at the email you gave.
?<br><span style=\\"font-weight:400;color:var(--mut)\\">While you're here: see the tool in action,
and a real 30-second reel it made.</span>"
183     },
184     "nav": {
185         "how": "How it works",
186         "why": "Why it's hard",
187         "ownModel": "Own your model",
188         "flyer": "Flyer",
189         "roadmap": "Roadmap",
190         "faq": "FAQ",
191         "requestAccess": "Request access"
192     },
193     "hero": {

```

```

194         "title": "Every rally, indexed. <span class=\"hl\">The dead time, gone.</span>",
195         "eyebrow": "Invite-only alpha · Bengaluru",
196         "lead": "KhelSutra finds every rally in your session and strips out the knock-ups,
walks and gaps ? so a full match becomes a clean highlight reel you can watch and download. No
editing, no scrubbing.",
197         "ctaPrimary": "Request alpha access",
198         "ctaHow": "See how it works",
199         "ctaReel": "See it in action + a real reel",
200         "note": "A phone or GoPro on a tripod is all you need. No special hardware.",
201         "loop": {
202             "step1": "<b>1.</b> Auto-index rallies",
203             "step2": "<b>2.</b> Dead time removed",
204             "step3": "<b>3.</b> Download your reel"
205         },
206         "demo": {
207             "fileTag": "match_2026.mp4 · indexed",
208             "detected": "Rallies detected",
209             "found": "44 found",
210             "resultTitle": "Highlight reel · 44 rallies · 18 min",
211             "resultSub": "dead time removed · ready to download"
212         }
213     },
214     "record": {
215         "kicker": "Record it right",
216         "title": "Five minutes of setup ? reliably great reels",
217         "intro": "Highlight quality starts with the recording. Set the camera up once like
this and KhelSutra has everything it needs to find the rallies.",
218         "goldenRuleLead": "The golden rule: one match, one court, in full frame ? and
don't move the camera.",
219         "goldenRuleRest": "A single court in frame gives the best results today; busy
multi-court footage is the hard case we're still sharpening.",
220         "place": {
221             "title": "Place the camera",
222             "body": "Behind <b>one baseline</b>, elevated (a high tripod or a balcony),
tilted down ~30° ? the <b>whole court</b> in frame, players never cropped."
223         },
224         "settings": {
225             "title": "Settings",
226             "body": "<b>1080p+</b>, landscape, <b>30 fps</b> for badminton (60 fps for table
tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies."
227         },
228         "still": {
229             "title": "Keep it still",
230             "body": "Fixed tripod or mount. <b>No panning, no zooming</b> during play ? a
steady, full-court view is what the tool is tuned for."
231         },
232         "upload": {
233             "title": "Record & upload",
234             "body": "Even lighting, then record the <b>whole session</b> and upload it as-is
? KhelSutra finds the rallies and does the cutting."
235         },
236         "checklistCta": "Full 1-page capture checklist ?"
237     },
238     "capture": {
239         "diagram": {
240             "title": "Side view: where the camera goes",
241             "camera": "Camera ? behind the baseline, elevated",
242             "angle": "Tilt ~30° down",
243             "frame": "Whole court in frame ? players never cropped",
244             "net": "Net"
245         },
246         "title": "1-page capture checklist",
247         "intro": "Great highlights start with a steady, full-court recording. Five minutes
of setup makes a big difference to your reels.",
248         "ruleLead": "The golden rule: one match, one court, in full frame ? and don't move

```

```

the camera.",
249     "ruleRest": "Multi-court footage is the hard case we're still sharpening; a single
court in frame gives the best results today.",
250     "step1": {
251         "title": "Place the camera",
252         "b1": "Behind <b>one baseline</b>, elevated ? a high tripod, a few metres up, or
a balcony.",
253         "b2": "Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a
little margin and net headroom.",
254         "b3": "Players should never leave the frame."
255     },
256     "step2": {
257         "title": "Settings",
258         "b1": "<b>1080p or higher</b>, shot in <b>landscape</b>.",
259         "b2": "<b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table tennis.",
260         "b3": "<b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise
reduction off."
261     },
262     "step3": {
263         "title": "Keep it still",
264         "b1": "Fixed tripod or mount.",
265         "b2": "<b>No panning, no zooming</b> during play."
266     },
267     "step4": {
268         "title": "Light & record",
269         "b1": "Even indoor lighting; avoid backlight, glare and very dark halls.",
270         "b2": "Record the <b>whole session</b> and upload it as-is ? KhelSutra does the
cutting."
271     },
272     "doTitle": "Do",
273     "do1": "Fixed camera, full court, behind the baseline",
274     "do2": "1080p+, landscape, audio on",
275     "do3": "One match on one court",
276     "dontTitle": "Avoid",
277     "dont1": "Handheld or phone-in-hand",
278     "dont2": "Broadcast-style pans & zooming",
279     "dont3": "Several courts in one frame; very dark halls",
280     "consent": "Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.",
281     "questions": "Questions?",
282     "printTip": "Tip: press Ctrl/Cmd + P to print or save as PDF."
283 },
284     "ownModel": {
285         "requestAccess": "Request access ?",
286         "heroTitle": "Annotate your footage. <span class=\"hl\">Train a model that's
yours.</span>",
287         "heroLead": "You can't train Gemini or GPT on your court footage. KhelSutra's
direction is the inverse ? a small, <b style=\"color:#EAF3EE\">owned</b> rally model where the
moat is your consented dataset, on a commercially-clean, inspectable stack you control.",
288         "nav": {
289             "home": "? KhelSutra home",
290             "annotate": "Annotate",
291             "train": "Train your own model",
292             "setup": "Setup & use"
293         },
294         "sample": "? <b>Want to see what KhelSutra produces?</b> A real sample reel plays
the moment you <a href=\"/#join\">request access</a>.",
295         "annotate": {
296             "kicker": "Step 1 · real and shipping today",
297             "title": "Annotate your footage",
298             "pill": "live today",
299             "body": "<b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b>
that turns \"watch a match\" into golden labels. While you watch your own video in VLC, you mark
each rally's start and end plus how the point ended; it writes one row per rally to a plain CSV
next to your video. <b>Your footage never leaves your machine.</b> It covers five net-separated

```

```

racquet sports (badminton, tennis, table tennis, pickleball, padel).",
300         "cap1": "Enable it once: VLC ? View ? Rally Annotator.",
301         "cap2": "Mark each rally's start/end + ending reason, then Save Rally.",
302         "flowLead": "The flow, per rally:",
303         "step1": "<b>Mark START</b> on the serve-contact frame (pause/scrub for
accuracy).",
304         "step2": "<b>Mark END</b> when the shuttle is dead.",
305         "step3": "Pick an <b>ending reason</b>, optionally a shot count, then <b>Save
Rally</b> ? one CSV row.",
306         "step4": "Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video
later to continue.",
307         "note": "It's a click-driven dialog (no marking hotkeys yet), and targets <b>VLC
3.0.x</b>."
308     },
309     "train": {
310         "kicker": "Step 2 . the moat",
311         "title": "Train your own model",
312         "pill": "open pipeline . in build",
313         "reassureTitle": "You don't have to train anything to start.",
314         "reassureBody": "KhelSutra runs on a ready-made default, so you get rally
detection and reels <b>out of the box</b> ? nothing to set up. Training on your own footage
(below) is an <b>optional</b> power-up: a model tuned to your courts, your angles, your halls.",
315         "intro": "For those who want it, your labels feed an <b>owned</b> rally model ?
trained on <b>your</b> courts, <b>your</b> angles, <b>your</b> busy multi-court halls. The
pipeline is open and inspectable:",
316         "moat": {
317             "ownTitle": "You own it",
318             "ownBody": "A model and dataset that are yours to keep and improve ? not
rented inference.",
319             "cleanTitle": "Commercially clean",
320             "cleanBody": "MIT/Apache/BSD-only stack; we never train on a paid LLM's
output.",
321             "privateTitle": "Private & consented",
322             "privateBody": "Footage stays yours; training use is explicit opt-in, never
automatic.",
323             "minorsTitle": "Minors protected",
324             "minorsBody": "Footage involving minors is never used for training and never
published."
325         },
326         "honestTitle": "Read this honestly.",
327         "honestBody": "The labeling tool is real and shipping. The training pipeline is
<b>open and in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-
validation <b>mock</b>, and a real model needs a GPU. There is <b>no \"Train now\" button</b>
yet, and we make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise
here is <b>ownership, licensing, privacy and consent</b> ? not \"more accurate than Gemini,\"
and not \"one click to train.\""
328     },
329     "setup": {
330         "kicker": "Step 3 . for power users",
331         "title": "Setup & use",
332         "install": "<b>Install the plugin (VLC 3.0.x).</b> Copy
<code>rally_annotator.lua</code> into VLC's per-user Lua <code>extensions</code> folder (create
it if missing), then VLC ? Tools ? Plugins and extensions ? <i>Reload extensions</i>, and enable
it from <i>View ? Rally Annotator</i>:",
333         "record": "<b>Record</b> per the <a href=\"/capture\">one-page capture
checklist</a> (fixed tripod, full court, landscape, whole session) ? <b>annotate</b> in VLC ?
you get <code>&lt;video&gt;.rallies.csv</code>:",
334         "reasons": "<code>ending_reason</code> is one of: <code>unknown</code> .
<code>winner</code> . <code>forced_error</code> . <code>unforced_error</code> .
<code>service_fault</code> . <code>let</code> . <code>other</code>. Times are decimal seconds;
downstream tools read by column name.",
335         "train": "<b>Train</b> (developer CLI). A GPU-free dry run validates the whole
pipeline on a CPU mock; a real model needs a GPU:",
336         "joinRule": "One join rule: keep the video <b>byte-identical</b> to what you
annotated (don't re-encode after labeling) ? labels match videos by content hash."

```

```

337     },
338     "not": {
339         "kicker": "So expectations stay honest",
340         "title": "What this is not",
341         "i1": "Not a one-click trainer ? training is an offline CLI today.",
342         "i2": "Not in-browser ? labeling runs in VLC on your machine.",
343         "i3": "Not an accuracy claim vs Gemini/GPT ? no such benchmark.",
344         "i4": "Shot-type, player and score detection are roadmap."
345     },
346     "cta": {
347         "title": "Want in?",
348         "button": "Request alpha access"
349     },
350     "foot": {
351         "flyer": "Academy flyer:",
352         "mark": "Reels carry a \"Generated by Khelsutra.guru\" mark."
353     }
354 },
355     "how": {
356         "kicker": "What it does today",
357         "title": "A full match, turned into rallies you can search",
358         "intro": "Upload a whole session or match. KhelSutra does the rest ? no editing
skill needed.",
359         "indexed": {
360             "title": "Every rally, indexed",
361             "body": "It finds each rally ? start, end and length ? and turns the whole match
into a searchable list. Long full-session videos are fine."
362         },
363         "deadtime": {
364             "title": "Dead time removed",
365             "body": "Knock-ups, walks, picking up the shuttle, the gaps between points ?
stripped out. What's left is only real play."
366         },
367         "reuse": {
368             "title": "Process once, reuse",
369             "body": "Come back later to watch or download your reel. Re-running a video
replaces its earlier result rather than piling up copies."
370         },
371         "stitch": {
372             "title": "Stitched reel + summary",
373             "body": "Your selection becomes one MP4 to download and share ? with a play-time
summary and a small ?Generated by Khelsutra.guru? mark."
374         }
375     },
376     "diff": {
377         "kicker": "The hard problem we crack",
378         "title": "Most academy halls run several courts at once",
379         "p1": "Academies already record a lot of video ? and then almost never watch it,
because cutting it into useful clips by hand is tedious. The good rallies stay buried.",
380         "p2": "A single recording of a busy, multi-court hall is exactly where ordinary
video tools choke. Pulling the <b style=\"color:var(--tx)\">>real</b> rallies out of busy, multi-
court footage is the hard problem KhelSutra is built for. It already works very well on clean,
single-court recordings ? and the multi-court case is what we're sharpening now.",
381         "tipPill": "Capture tip",
382         "tipTitle": "Best results: a steady, full-court shot",
383         "tipBody": "Camera behind the court, slightly elevated, whole court in frame. Keep
it still ? a fixed tripod beats handheld every time. Shoot landscape, record the whole session,
upload as-is. KhelSutra does the cutting."
384     },
385     "sharper": {
386         "kicker": "What makes it different",
387         "title": "It gets sharper from real academy footage",
388         "intro": "The footage real academies contribute ? especially the busy multi-court
halls ? is what makes KhelSutra better over time. Early users aren't just customers; they're co-
builders.",

```

```

389     "improve": {
390         "title": "Improves with the library",
391         "body": "When you choose to share footage and coaches confirm what it found,
that growing labelled library is what sharpens future versions ? rather than staying frozen."
392     },
393     "data": {
394         "title": "Your data stays yours",
395         "body": "We never use your video to improve the tool without your clear,
explicit opt-in. We never publish your footage. You decide what, if anything, you share."
396     },
397     "minors": {
398         "title": "Minors are protected",
399         "body": "Footage involving minors is never used to improve the tool and is never
published ? full stop."
400     },
401     "honestLead": "Read this honestly:",
402     "honestBody": "Today the tool gives you rally detection, reels, and summaries. It
does not retrain itself as you use it, and there's no per-person tracking. \"Gets sharper over
time\" is the model we're building toward, powered by contributed footage ? not a switch that's
already on."
403 },
404     "ask": {
405         "kicker": "Coming next to the alpha",
406         "title": "Soon: ask for the exact reel you want",
407         "intro": "Your match is already a clean index of rallies ? so the natural next
step is to let you build any reel just by describing it, in plain English. This is rolling out
to alpha users.",
408         "q1": "?Every rally over 10 seconds?",
409         "a1": "6 rallies · a 1:32 reel of the long, end-to-end battles",
410         "q2": "?Just the third game, longest first?",
411         "a2": "12 rallies, reordered by length ? that game only",
412         "q3": "?The 8 best rallies from today?",
413         "a3": "an 8-clip highlight from your latest session",
414         "note": "<b style=\"color:var(--tx)\">Rolling out now.</b> Targeted asks ? by
rally length, count, order, or which game ? come first; shot-type and player queries follow as
the deeper analysis arrives."
415     },
416     "roadmap": {
417         "kicker": "Where it's going",
418         "title": "Toward an AI assistant coach",
419         "intro": "Fed by the growing video library, KhelSutra is heading from \"finds
rallies\" to a genuine training companion. This is the direction ? not today's buttons.",
420         "shot": {
421             "title": "Shot detection",
422             "body": "Smashes, drops, net shots, serves and clears within each rally."
423         },
424         "deep": {
425             "title": "Deeper analysis",
426             "body": "Per-rally and per-match patterns ? what's working and what isn't."
427         },
428         "history": {
429             "title": "Per-match history",
430             "body": "Track progress over weeks and months, not just one clip."
431         },
432         "coach": {
433             "title": "Assistant coach",
434             "body": "Surfaces what to work on next ? supports the real coach, never
replaces."
435         },
436         "more": {
437             "title": "More sports & languages",
438             "body": "Table tennis next; Kannada and Hindi alongside English."
439         }
440     },
441     "not": {

```

```

442         "kicker": "So expectations stay honest",
443         "title": "What KhelSutra is not",
444         "li1": "An early, invite-only trial ? useful, but still improving. You'll hit
rough edges.",
445         "li2": "Not a line-calling, scoring, or umpiring system.",
446         "li3": "Not player tracking or identification.",
447         "li4": "Not a replacement for a coach ? a tool that saves time and adds insight.",
448         "li5": "Shot detection and deeper analytics are on the roadmap, not available
today.",
449         "li6": "Pricing isn't set ? today's invited use is about getting it right."
450     },
451     "faq": {
452         "kicker": "Quick answers",
453         "title": "Common questions",
454         "q1": {
455             "q": "How accurate is it?",
456             "a": "Very good on a clean, single-court recording. A busy multi-court hall is
harder ? and is exactly what we're improving. The best answer is to show you a sample reel of
your own court rather than quote a number."
457         },
458         "q2": {
459             "q": "Can I choose which rallies go in the reel?",
460             "a": "Today your reel includes the rallies KhelSutra found, with the dead time
removed. Choosing by length, count, order or which game ? just by asking in plain English ? is
rolling out to alpha users next; shot-type and player queries follow as the deeper analysis
arrives."
461         },
462         "q3": {
463             "q": "Do I need a special camera or hardware?",
464             "a": "No. A phone or GoPro on a tripod, behind the court, whole court in frame.
We provide a one-page capture checklist at setup."
465         },
466         "q4": {
467             "q": "Is my video private? What happens to it?",
468             "a": "We treat your footage as private: we never publish it, and we never use it
to improve the tool without your explicit opt-in. These are large videos that need real
processing, so your video is handled securely on our infrastructure to make your reel. Footage
involving minors is never used and never published."
469         },
470         "q5": {
471             "q": "Does it work for doubles and tournaments?",
472             "a": "It finds rallies in doubles too. Tournament footage varies ? a clean,
fixed, full-court recording works well; crowded multi-court tournament halls are the hard case
we're specifically working on."
473         },
474         "q6": {
475             "q": "Which sports?",
476             "a": "Badminton today. Table tennis and other racket sports are on the roadmap."
477         },
478         "q7": {
479             "q": "How do I join?",
480             "a": "It's an invite-only private trial. Just <a href=\"#join\">request
access</a> using the form ? it takes a minute, you'll see a real sample reel right away, and
we'll be in touch about recording your own court."
481         }
482     },
483     "footer": {
484         "tagline": "Automatic badminton highlights · Bengaluru, India",
485         "capture": "Capture checklist",
486         "privacy": "Privacy",
487         "flyer": "Academy flyer (print):",
488         "trust": "? Served securely over HTTPS · ? Run from Bengaluru, India · Reels carry
a \"Generated by Khelsutra.guru\" mark",
489         "copyright": "© 2026 KhelSutra · Invite-only alpha"
490     },

```



```

491     "privacy": {
492         "back": "? Back to KhelSutra",
493         "title": "Privacy Policy",
494         "sub": "How KhelSutra handles your information and your match videos ? and the
choices you have.",
495         "updated": "Last updated: 22 June 2026",
496         "lead": "KhelSutra (\"we\", \"us\") turns a full badminton match into a clean
highlight reel. We're an invite-only alpha run from Bengaluru, India. This page explains, in
plain language, what information we collect, how we use it, who else touches it, and how you
stay in control. Questions? Email <a
href=\"mailto:hello@khelsutra.guru\">hello@khelsutra.guru</a>.",
497         "tocHeading": "On this page",
498         "toc": {
499             "collect": "What we collect",
500             "use": "How we use it",
501             "video": "Your videos & how they're processed",
502             "sharing": "Who else touches your data",
503             "cookies": "Cookies & analytics",
504             "retention": "How long we keep it",
505             "rights": "Your choices & rights",
506             "minors": "Minors",
507             "security": "Security",
508             "changes": "Changes & contact"
509         },
510         "collect": {
511             "h": "1. What we collect",
512             "intro": "We only collect what we need to run the alpha and produce your
reels:",
513             "li1": "<b>Request-access details</b> ? when you fill in the access form: your
name and email, and optionally your city, academy/club name, how many courts you record, whether
you have a powerful (GPU) computer, where your videos live, and any message you send us.",
514             "li2": "<b>Match videos you choose to give us</b> ? the footage you upload or
share so we can index the rallies and build your reel.",
515             "li3": "<b>Basic technical data</b> ? like your approximate country and browser
type, handled by our hosting and edge-security provider (Cloudflare) to keep the site working
and safe.",
516             "note": "We do <b>not</b> ask for, or want, sensitive personal data, and we
don't run intrusive cross-site advertising trackers."
517         },
518         "use": {
519             "h": "2. How we use it",
520             "li1": "To <b>contact</b> you about the alpha</b> ? but only if you ticked the
consent box on the form.",
521             "li2": "To <b>provide the service</b> ? to index your match, strip the dead
time, and generate the reel you download.",
522             "li3": "To <b>understand demand and improve the product experience</b> in
aggregate (e.g. how many academies vs. individuals are interested).",
523             "note": "We do <b>not</b> sell, rent, or trade your personal data. We do
<b>not</b> use your footage to train or improve our models <b>unless</b> you give us clear,
explicit, opt-in permission</b> ? and even then, never footage involving minors."
524         },
525         "video": {
526             "h": "3. Your videos & how they're processed",
527             "intro": "Your match videos are large files that need real computing to analyse,
so here's exactly what happens to them:",
528             "li1": "We process your video on our own infrastructure to find the rallies and
build your reel.",
529             "li2": "As part of the analysis we may use <b>trusted third-party AI and cloud
services</b> (for example, Google's Gemini API) to detect rallies. When we do, we send only the
footage needed for that step.",
530             "li3": "We <b>never publish</b> your footage, and we never make it public.",
531             "li4": "We never use your footage to improve the tool without your explicit opt-
in (see above).",
532             "boxTitle": "If you run your own model:",
533             "boxBody": "The \"own your model\" path lets advanced users process footage on

```

their own hardware. In that case your video stays on your machine and is not sent to us or to third-party AI services."

```
534     },
535     "sharing": {
536         "h": "4. Who else touches your data",
537         "intro": "We keep the list of processors small and name them honestly:",
538         "li1": "<b>Cloudflare</b> ? hosts the website, secures it at the edge, and
provides privacy-friendly analytics.",
539         "li2": "<b>Google (Gemini API)</b> ? used, when applicable, to analyse footage
and detect rallies.",
540         "li3": "<b>Email delivery</b> ? to send the messages you asked us to send about
the alpha.",
541         "note": "These providers act on our behalf to deliver the service. We don't give
anyone your data to use for their own marketing."
542     },
543     "cookies": {
544         "h": "5. Cookies & analytics",
545         "intro": "We keep this light:",
546         "li1": "We store a single <b>language preference</b> in your browser so the site
remembers the language you picked. That's a functional preference, not a tracking cookie.",
547         "li2": "We use <b>privacy-first analytics</b> (Cloudflare Web Analytics) to
count visits and see which pages are useful. It does not use tracking cookies and does not build
a profile of you across other sites."
548     },
549     "retention": {
550         "h": "6. How long we keep it",
551         "body": "We keep your information and footage only as long as we need it to run
the alpha and provide the service, and then delete or anonymise it. You can ask us to delete
your uploaded videos and your account details at any time ? see your rights below."
552     },
553     "rights": {
554         "h": "7. Your choices & rights",
555         "intro": "You're in control. At any time you can ask us to:",
556         "li1": "See what personal data we hold about you;",
557         "li2": "Correct anything that's wrong;",
558         "li3": "Delete your data and uploaded footage;",
559         "li4": "Withdraw your consent to be emailed (every email we send also has an
easy opt-out).",
560         "note": "To exercise any of these, just email <a
href=\"mailto:hello@khelsutra.guru\">hello@khelsutra.guru</a> and we'll take care of it."
561     },
562     "minors": {
563         "h": "8. Minors",
564         "body": "We take footage involving minors seriously. Footage involving minors is
<b>never</b> used to improve the tool and is <b>never</b> published ? full stop. If you believe
a minor's personal data has been shared with us inappropriately, contact us and we'll remove
it."
565     },
566     "security": {
567         "h": "9. Security",
568         "body": "The site is served only over <b>HTTPS</b> with an auto-renewing TLS
certificate, so your connection is encrypted. The alpha app itself is gated behind an
authenticated, invite-only sign-in, and access to the processing system is restricted. No system
is perfectly secure, but we take reasonable, layered measures to protect your data."
569     },
570     "changes": {
571         "h": "10. Changes & contact",
572         "body": "This policy reflects our current alpha practices and may change as the
product evolves; we'll update the \"last updated\" date above when it does. For any privacy
question or request, email <a href=\"mailto:hello@khelsutra.guru\">hello@khelsutra.guru</a>."
573     },
574     "authoritative": "This page is provided in several languages for convenience. If
anything differs between versions, the English version is the one that applies.",
575     "home": "Home",
576     "footTrust": "? Served securely over HTTPS · © 2026 KhelSutra · Invite-only alpha"
```

```

577     },
578     "meta": {
579         "index": {
580             "title": "KhelSutra ? every rally indexed, the dead time gone"
581         },
582         "capture": {
583             "title": "KhelSutra ? 1-page capture checklist"
584         },
585         "ownModel": {
586             "title": "KhelSutra ? Annotate your footage & train your own model"
587         },
588         "privacy": {
589             "title": "Privacy Policy ? KhelSutra"
590         }
591     }
592 },
593 "wizard": {
594     "title": "Welcome to KhelSutra",
595     "intro": "Three quick steps and you're ready to turn a match into a highlights
reel.",
596     "step": "Step {n} of 3",
597     "checking": "Checking what this device can do?",
598     "offline": "Couldn't reach KhelSutra ? start it, then reopen setup. You can skip for
now.",
599     "back": "Back",
600     "next": "Next",
601     "skip": "Skip",
602     "done": "Get started",
603     "key": {
604         "title": "AI highlights (optional)",
605         "connected": "Gemini is connected ? you'll get AI-assisted highlights.",
606         "missing": "No AI key yet ? that's fine. KhelSutra works offline with the built-in
motion detector.",
607         "how": "Want sharper highlights? Get a free Gemini key, add GEMINI_API_KEY=? to
the .env file in your KhelSutra folder, then restart.",
608         "getKey": "Get a free Gemini key"
609     },
610     "compute": {
611         "title": "Where it runs",
612         "local": "Everything runs on this device ? your videos never leave it.",
613         "detector": "Detector: {name}",
614         "ffmpegOk": "Video tools (ffmpeg) ready.",
615         "ffmpegMissing": "ffmpeg not found ? install it so KhelSutra can cut and join
clips.",
616         "gpu": "A GPU was detected ? the high-quality shuttle tracker can run here
later.",
617         "noGpu": "No GPU needed ? the offline motion detector runs on any computer."
618     },
619     "videos": {
620         "title": "Add a video",
621         "body": "When you're ready, pick a video file or paste a cloud link and KhelSutra
finds the rallies for you.",
622         "ready": "You're all set."
623     }
624 },
625 "annotate": {
626     "tab": "Annotate",
627     "tabPick": "Pick rallies",
628     "title": "Annotate rallies",
629     "hint": "Play the video, mark each rally's start and end, pick how the point ended,
then save.",
630     "sport": "Sport",
631     "markStart": "Mark start",
632     "markEnd": "Mark end",
633     "start": "Start",

```

```

634     "end": "End",
635     "reason": "Ending reason",
636     "shots": "Shots (optional)",
637     "save": "Save rally",
638     "undo": "Undo last",
639     "recent": "Saved rallies",
640     "recentEmpty": "No rallies saved yet.",
641     "saving": "Saving?",
642     "saved": "Saved to your library",
643     "saveError": "Couldn't save your rallies.",
644     "retry": "Retry",
645     "errNoMedia": "Play or scrub the video first ? there's no time to mark yet.",
646     "errMarks": "Check the start and end ? end must be after start.",
647     "errDuplicate": "That rally number already exists."
648 },
649 "library": {
650     "title": "Your videos",
651     "intro": "Open a match you've already added ? or add a new one below.",
652     "loading": "Loading your videos?",
653     "empty": "No videos yet ? add your first one below.",
654     "errorLoad": "Couldn't load your videos. Is KhelSutra running?",
655     "unnamed": "Untitled match",
656     "open": "Open",
657     "openAria": "Open {name}"
658 },
659 "selection": {
660     "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
661 },
662 "storage": {
663     "local": "This computer",
664     "bucket": "Cloud bucket",
665     "drive": "Google Drive"
666 },
667 "ffmpeg": {
668     "missingTitle": "FFmpeg not detected on this computer",
669     "missingBody": "KhelSutra needs FFmpeg (and ffprobe) to index videos and build
highlight reels. Install it and restart the app ? until then, adding a video and downloading a
reel won't work.",
670     "installLink": "How to install FFmpeg"
671 }
672 }
673

```

22. assistant (2026-07-04T01:29:20.265Z)

Let me read the client, format lib, and the i18n hygiene/invariant tests that enforce catalog parity.

23. user (2026-07-04T01:29:21.282Z)

```

1      // Typed client for the engine FastAPI. Default = SAME-ORIGIN relative `/api/*` (the
single-origin
2      // appliance reverse-proxies UI + engine behind one origin; in dev Vite proxies `/api` ?
:8000).
3      // Every call carries a correlation id (header + logs) so a journey is traceable end to
end.
4      import { log, newCorrelationId } from "../lib/log";
5      import type {
6          RallySegment,
7          QueryResponse,
8          CompileResult,
9          EngineConfig,
10         EngineCapabilities,
11         ProcessResponse,
12         JobStatus,

```

```

13     UploadInitResponse,
14     UploadPartResponse,
15     UploadCompleteResponse,
16     VideoSummary,
17     VideosResponse,
18     AnnotationsResponse,
19     AssetResponse,
20 } from "./types";
21
22 /** Resolve the engine API base. Default same-origin `"/api"`. For a SPLIT deploy ? SPA
on
23 * Cloudflare Pages + the engine on a separate `api.*` cloudflared tunnel
(HOSTING_PLAN.md §2) ?
24 * set `VITE_API_BASE` at build time to the engine's API base **including the `/api`
path**
25 * (e.g. `https://api.khelsutra.guru/api`), and lock the engine's
`RALLY_CORS_ALLOW_ORIGINS` to the
26 * Pages origin + put CF Access in front of both hostnames. A trailing slash is trimmed
so
27 * `` `${base}/process` `` never double-slashes. */
28 export function apiBase(): string {
29     return (import.meta.env.VITE_API_BASE ?? "/api").replace(/\/+$/, "");
30 }
31
32 const BASE = apiBase();
33
34 export class ApiError extends Error {
35     readonly cid?: string;
36     readonly status?: number;
37     readonly body?: string;
38     constructor(message: string, opts: { cid?: string; status?: number; body?: string;
cause?: unknown } = {}) {
39         super(message);
40         this.name = "ApiError";
41         this.cid = opts.cid;
42         this.status = opts.status;
43         this.body = opts.body;
44         if (opts.cause !== undefined) (this as { cause?: unknown }).cause = opts.cause;
45     }
46 }
47
48 interface RequestOpts {
49     method?: string;
50     body?: string;
51     headers?: Record<string, string>;
52     /** Correlation id to thread through this call; auto-generated if absent. */
53     cid?: string;
54 }
55
56 async function request<T>(path: string, opts: RequestOpts = {}): Promise<T> {
57     const cid = opts.cid ?? newCorrelationId();
58     const url = `${BASE}${path}`;
59     const method = opts.method ?? "GET";
60     log("info", "api.request", { cid, method, url });
61
62     let res: Response;
63     try {
64         res = await fetch(url, {
65             method,
66             body: opts.body,
67             headers: { "content-type": "application/json", "x-correlation-id": cid,
...(opts.headers ?? {}) },
68         });
69     } catch (err) {
70         // Loud failure, never silent (LOCAL_APPLIANCE_ARCHITECTURE.md §5).

```

```

71     log("error", "api.network_error", { cid, method, url, error: String(err) });
72     throw new ApiError(`Network error calling ${method} ${url}`, { cid, cause: err });
73 }
74
75 if (!res.ok) {
76     const body = await res.text().catch(() => "");
77     log("error", "api.http_error", { cid, method, url, status: res.status, body:
body.slice(0, 500) });
78     throw new ApiError(`${method} ${url} failed: ${res.status}`, { cid, status:
res.status, body });
79 }
80
81 const data = (await res.json()) as T;
82 log("info", "api.response", { cid, method, url, status: res.status });
83 return data;
84 }
85
86 /** Submit a video (a `gs://`/`gcs://`/`s3://` bucket URI, or a path on the engine host)
for
87 * processing. POST /api/process {video_path} ? 202 {job_id, ...} [engine process
route]. Fast-fails 400
88 * (unsupported scheme / out-of-allowed-root) or 404 (missing LOCAL file) ? surfaced as
ApiError. */
89 export async function processVideo(
90     videoPath: string,
91     cid?: string,
92     locale?: string,
93     compute?: string,
94 ): Promise<ProcessResponse> {
95     // `locale` (the UI language) is recorded for PMF analytics (which markets use the
tool). `compute`
96     // is the compute-picker choice ("local" | "cloud") ? where DETECT runs; omitted ? the
server
97     // default. Both optional + omitted when absent (JSON.stringify drops undefined).
98     return request<ProcessResponse>("/process", {
99         method: "POST",
100         body: JSON.stringify({ video_path: videoPath, locale, compute }),
101         cid,
102     });
103 }
104
105 /** Poll a submitted job. GET /api/jobs/{job_id} [engine jobs route]. 404 ? unknown
job_id. */
106 export async function getJob(jobId: string, cid?: string): Promise<JobStatus> {
107     return request<JobStatus>(`/jobs/${encodeURIComponent(jobId)}`, { method: "GET", cid
});
108 }
109
110 /** List indexed videos, newest first ? the "my videos" library. GET /api/videos [engine
list_videos route].
111 * Reload-survival: a past match can be reopened without re-processing. Returns [] on
an empty box. */
112 export async function listVideos(cid?: string): Promise<VideoSummary[]> {
113     const data = await request<VideosResponse>("/videos", { method: "GET", cid });
114     return data.videos ?? [];
115 }
116
117 /** The source-video stream URL for annotation playback. GET /api/source/{video_id}
(P8). The engine
118 * serves a frame-identical proxy; labels stay keyed to the master's MD5
(STUDIO_MEDIA_LIFECYCLE D4). */
119 export function sourceUrl(videoId: string): string {
120     return `${BASE}/source/${encodeURIComponent(videoId)}`;
121 }
122

```

```

123     /** Persist finished rally labels as the annotator CSV. POST /api/annotations {video_id,
csv} (P8).
124     * Sent as the byte-compatible CSV (serializeRows) so the engine writes it verbatim
into the corpus. */
125     export async function postAnnotations(videoId: string, csv: string, cid?: string):
Promise<AnnotationsResponse> {
126         return request<AnnotationsResponse>("/annotations", {
127             method: "POST",
128             body: JSON.stringify({ video_id: videoId, csv }),
129             cid,
130         });
131     }
132
133     /** Store a video into the user's chosen medium + register it as a library asset (P4,
D14).
134     * POST /api/assets {uploaded_path? | source_uri?, medium_uri, sport?} ? 201 {video_id,
stored_uri}.
135     * Exactly ONE source: an `uploadedPath` (a just-uploaded local file ? a durable
MD5-keyed copy is
136     * put into the medium, the local upload kept as the working copy) OR a `sourceUri` (a
video already
137     * at rest, registered as-is). Feed `stored_uri` into processVideo(). Fast-fails 400
(bad medium /
138     * both-or-neither source), 403 (hosted posture), 404 (missing file), 507 (no space),
502 (put) ?
139     * surfaced as ApiError. */
140     export async function createAsset(
141         args: { uploadedPath?: string; sourceUri?: string; mediumUri: string; sport?: string
},
142         cid?: string,
143     ): Promise<AssetResponse> {
144         return request<AssetResponse>("/assets", {
145             method: "POST",
146             body: JSON.stringify({
147                 uploaded_path: args.uploadedPath,
148                 source_uri: args.sourceUri,
149                 medium_uri: args.mediumUri,
150                 sport: args.sport,
151             }),
152             cid,
153         });
154     }
155
156     /** List a video's detected rallies. POST /api/query {video_id} ? {play_segments}
[engine query route]. */
157     export async function listRallies(videoId: string, cid?: string):
Promise<RallySegment[]> {
158         const data = await request<QueryResponse>("/query", {
159             method: "POST",
160             body: JSON.stringify({ video_id: videoId }),
161             cid,
162         });
163         return data.play_segments ?? [];
164     }
165
166     // Compile-job poll cadence (mirrors useIngestJob): a long ffmpeg stitch must not block
the request.
167     const COMPILE_POLL_MIN_MS = 1000;
168     const COMPILE_POLL_MAX_MS = 5000;
169     const COMPILE_POLL_BACKOFF = 1.5;
170     const COMPILE_POLL_CEILING_MS = 10 * 60 * 1000; // a wedged 'running' compile won't poll
forever
171
172     /** Stitch selected rallies into one reel. ASYNC (#329): POST /api/compile returns 202 +
a job_id;

```

```

173     * the ffmpeg stitch runs on the worker and we POLL GET /api/jobs/{id} for the reel ? a
long stitch
174     * would otherwise exceed the ~100 s edge/proxy timeout (524) while the reel actually
built. Resolves
175     * with the job's CompileResult on success; throws ApiError on a failed/timed-out
compile.
176     * `locale` (the UI language) localizes the reel watermark engine-side (omitted when
absent). */
177     export async function compileReel(
178         videoId: string,
179         segmentIds: number[],
180         outputFilename: string,
181         cid?: string,
182         locale?: string,
183     ): Promise<CompileResult> {
184         const c = cid ?? newCorrelationId();
185         const submitted = await request<ProcessResponse>("/compile", {
186             method: "POST",
187             body: JSON.stringify({ video_id: videoId, segment_ids: segmentIds, output_filename:
outputFilename, locale }),
188             cid: c,
189         });
190         return pollCompileJob(submitted.job_id, c);
191     }
192
193     /** Poll a submitted compile job to its terminal state. Returns the reel result on
success; throws an
194     * ApiError for an engine job-failure, a success-shaped FAILURE (done but the stitch
failed / no URL),
195     * or a poll timeout ? so the caller's existing classifyError/errorText mapping
surfaces it like ingest. */
196     async function pollCompileJob(jobId: string, cid: string): Promise<CompileResult> {
197         const startedAt = Date.now();
198         let delay = COMPILE_POLL_MIN_MS;
199         for (;;) {
200             const job = await getJob(jobId, cid);
201             if (job.status === "done") {
202                 const result = (job.result ?? {}) as CompileResult;
203                 if (result.status === "failed" || !result.download_url) {
204                     // A real stitch failure carries an engine message ? surface it as an `engine`
detail (status +
205                     // body set) so classifyError shows it verbatim, NOT the no-status "engine
unreachable" fallback.
206                     const msg = result.message || "Highlight stitching failed.";
207                     throw new ApiError(msg, { cid, status: 502, body: msg });
208                 }
209                 return result;
210             }
211             if (job.status === "failed") {
212                 const msg = job.error || "Compile job failed.";
213                 throw new ApiError(msg, { cid, status: 502, body: msg });
214             }
215             if (Date.now() - startedAt > COMPILE_POLL_CEILING_MS) {
216                 throw new ApiError("Compile timed out.", { cid, status: 504, body: "Compile timed
out." });
217             }
218             await new Promise((resolve) => setTimeout(resolve, delay));
219             delay = Math.min(delay * COMPILE_POLL_BACKOFF, COMPILE_POLL_MAX_MS);
220         }
221     }
222
223     /** The stream/download URL for a compiled reel. GET
/api/highlights/{video_id}/{filename} [engine highlights route]. */
224     export function highlightUrl(videoId: string, filename: string): string {
225         return

```



```

226     }
227
228     /** Read engine config (for the stitching floor). GET /api/config [engine config route]. */
229     export async function getConfig(cid?: string): Promise<EngineConfig> {
230         return request<EngineConfig>("/config", { method: "GET", cid });
231     }
232
233     /** What THIS box can do ? drives the first-run wizard. GET /api/capabilities (PACKAGING_PLAN P2c). */
234     export async function getCapabilities(cid?: string): Promise<EngineCapabilities> {
235         return request<EngineCapabilities>("/capabilities", { method: "GET", cid });
236     }
237
238     /** The shot-count floor /api/compile silently enforces ? the UI must warn, not hide [engine compile floor]. */
239     export function minShotCount(cfg: EngineConfig): number | undefined {
240         return cfg.stitching?.min_shot_count;
241     }
242
243     // ?? chunked upload (backend/api/uploads.py) ??????????????????????????????????????????
244     // A browser uploads a LOCAL file in sequential parts ? max_part_mb (free-tier edge proxies cap
245     // bodies ~100 MB), then `complete` returns a server-host `path` to feed straight into /api/process.
246
247     /** Start a chunked upload. 400 = bad extension; 413 = over the size limit [backend/api/uploads.py]. */
248     export async function uploadInit(filename: string, totalSizeBytes: number, cid?: string): Promise<UploadInitResponse> {
249         return request<UploadInitResponse>("/upload/init", {
250             method: "POST",
251             body: JSON.stringify({ filename, total_size_bytes: totalSizeBytes }),
252             cid,
253         });
254     }
255
256     /** Append ONE part (raw bytes ? not JSON). Parts are strictly sequential 0,1,2,? [backend/api/uploads.py]. */
257     export async function uploadPart(
258         uploadId: string,
259         index: number,
260         chunk: Blob,
261         cid?: string,
262         signal?: AbortSignal,
263     ): Promise<UploadPartResponse> {
264         const c = cid ?? newCorrelationId();
265         const url = `${BASE}/upload/${encodeURIComponent(uploadId)}/part/${index}`;
266         log("info", "api.request", { cid: c, method: "PUT", url });
267         let res: Response;
268         try {
269             res = await fetch(url, {
270                 method: "PUT",
271                 body: chunk,
272                 headers: { "content-type": "application/octet-stream", "x-correlation-id": c },
273                 signal,
274             });
275         } catch (err) {
276             log("error", "api.network_error", { cid: c, method: "PUT", url, error: String(err) });
277             throw new ApiError(`Network error calling PUT ${url}`, { cid: c, cause: err });
278         }
279         if (!res.ok) {
280             const body = await res.text().catch(() => "");

```

```

281     log("error", "api.http_error", { cid: c, method: "PUT", url, status: res.status,
body: body.slice(0, 500) });
282     throw new ApiError(`PUT ${url} failed: ${res.status}`, { cid: c, status: res.status,
body });
283   }
284   log("info", "api.response", { cid: c, method: "PUT", url, status: res.status });
285   return (await res.json()) as UploadPartResponse;
286 }
287
288 /** Finalize: returns {path, video_id} ? feed `path` to processVideo()
[backend/api/uploads.py]. */
289 export async function uploadComplete(uploadId: string, totalParts: number, cid?:
string): Promise<UploadCompleteResponse> {
290   return
request<UploadCompleteResponse>(`/upload/${encodeURIComponent(uploadId)}/complete`, {
291     method: "POST",
292     body: JSON.stringify({ total_parts: totalParts }),
293     cid,
294   });
295 }
296
297 /** Abort an in-flight upload (best-effort cleanup of the server-side partial)
[backend/api/uploads.py]. */
298 export async function uploadAbort(uploadId: string, cid?: string): Promise<void> {
299   await request<unknown>(`/upload/${encodeURIComponent(uploadId)}`, { method: "DELETE",
cid });
300 }
301
302 export interface UploadProgress {
303   sentBytes: number;
304   totalBytes: number;
305 }
306
307 /** Upload a local File end to end: init ? sequential parts (byte progress, abortable) ?
complete.
308 * On ANY failure or abort it best-effort DELETES the server-side partial, then
rethrows so the
309 * caller can classify it (the engine's 400/413 detail survives). Returns {path,
video_id}.
310 * Note: a per-part 413 (over the per-part limit) aborts the upload server-side ?
recovery is a
311 * fresh init (re-pick the file), which the UI's retry does. */
312 export async function uploadFile(
313   file: File,
314   opts: { cid?: string; signal?: AbortSignal; onProgress?: (p: UploadProgress) => void }
= {},
315 ): Promise<UploadCompleteResponse> {
316   const cid = opts.cid ?? newCorrelationId();
317   const init = await uploadInit(file.name, file.size, cid);
318   // Honor the engine's max_part_mb, but never let a missing/NaN value collapse the math
to NaN (which
319   // would silently upload zero parts) ? fall back to the engine's 95 MB default.
320   const partMb = Number.isFinite(init.max_part_mb) && init.max_part_mb > 0 ?
init.max_part_mb : 95;
321   const partBytes = partMb * 1024 * 1024;
322   const totalParts = Math.max(1, Math.ceil(file.size / partBytes));
323   log("info", "upload.start", { cid, filename: file.name, size: file.size, parts:
totalParts, part_mb: init.max_part_mb });
324   let sent = 0;
325   try {
326     for (let i = 0; i < totalParts; i++) {
327       if (opts.signal?.aborted) throw new DOMException("Upload aborted", "AbortError");
328       const chunk = file.slice(i * partBytes, Math.min((i + 1) * partBytes, file.size));
329       await uploadPart(init.upload_id, i, chunk, cid, opts.signal);
330       sent += chunk.size;

```

```

331         opts.onProgress?.({ sentBytes: sent, totalBytes: file.size });
332     }
333     const done = await uploadComplete(init.upload_id, totalParts, cid);
334     log("info", "upload.done", { cid, video_id: done.video_id, path: done.path, size:
done.size_bytes });
335     return done;
336 } catch (err) {
337     log("warn", "upload.aborting_partial", { cid, upload_id: init.upload_id, error:
String(err) });
338     await uploadAbort(init.upload_id, cid).catch(() => {});
339     throw err;
340 }
341 }
342

```

24. user (2026-07-04T01:29:22.285Z)

```

1     // Small pure formatters (node-testable, no React).
2
3     /** Seconds ? "m:ss" (e.g. 65 ? "1:05"). Rounds to the nearest second; clamps negatives
to 0. */
4     export function mmss(totalSeconds: number): string {
5         const s = Math.max(0, Math.round(totalSeconds || 0));
6         const m = Math.floor(s / 60);
7         return `${m}:${String(s % 60).padStart(2, "0")}`;
8     }
9
10    /** "3 rallies" / "1 rally" ? count with a correctly pluralized noun. */
11    export function pluralize(n: number, one: string, many = one + "s"): string {
12        return `${n} ${n === 1 ? one : many}`;
13    }
14
15    /** Turn a user reel name into a safe bare `.mp4` filename for POST /api/compile. The
engine's
16    * `safe_output_filename` (backend/utils/paths.py) rejects path separators / traversal /
absolute
17    * names, so we slugify to [a-z0-9-] and always end in `.mp4`. Empty ? "highlights.mp4".
*/
18    export function reelFilename(name: string): string {
19        const slug = (name || "")
20            .toLowerCase()
21            .replace(/^[a-z0-9-]+/g, "-")
22            .replace(/^-+|-+$/g, "")
23            .slice(0, 80);
24        return `${slug || "highlights"}.mp4`;
25    }
26

```

25. user (2026-07-04T01:29:23.292Z)

```

1     // Content regression guards for the localization catalogs ? the rules the adversarial
translation
2     // audit (#77) established, pinned so the specific bugs can never silently return. This
complements
3     // hygiene.test.ts (which proves key/placeholder PARITY) by asserting catalog CONTENT.
Each block maps
4     // to a concrete #77 bug class; the mutation that reintroduces the bug fails here. Pure
data assertions
5     // over repo-root /locales (D-CATALOG-HOME) ? no render context needed.
6     import { describe, it, expect } from "vitest";
7     import { readFileSync, readdirSync } from "node:fs";
8     import { join } from "node:path";
9
10    const LOCALES_DIR = join(import.meta.dirname, "..", "..", "..", "locales");
11

```

```

12     type Flat = Record<string, string>;
13     function flatEntries(obj: Record<string, unknown>, prefix = ""): Flat {
14         const out: Flat = {};
15         for (const [k, v] of Object.entries(obj)) {
16             const key = prefix ? `${prefix}.${k}` : k;
17             if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(out,
flatEntries(v as Record<string, unknown>, key));
18             else out[key] = String(v);
19         }
20         return out;
21     }
22     const load = (loc: string): Flat =>
23         flatEntries(JSON.parse(readFileSync(join(LOCALES_DIR, loc, "common.json"), "utf8"))) as
Record<string, unknown>);
24
25     const ALL_LOCALES = readdirSync(LOCALES_DIR, { withFileTypes: true })
26         .filter((d) => d.isDirectory())
27         .map((d) => d.name);
28     const en = load("en");
29
30     // (1) Internal-token / debug-tag leaks ? EVERY locale. The engine's internal
`min_shot_count` config
31     // name leaked into footer.floorSomeRest (#77, kn even wrapped it in <code>). No
developer/debug tag
32     // (kbd/samp/tt/var) or that token may reach any user-facing string. <code> is likewise
banned ?
33     // EXCEPT on the marketing site's developer "own your model" page (site.ownModel.*),
which intentionally
34     // renders inline <code> (the rally_annotator.lua filename, the ending_reason enum,
<video>.rallies.csv)
35     // through the site shim's data-i18n-html form. That namespace is the sole, deliberate
exception; the
36     // SPA console keys (where the #77 leak happened) still fail on any <code>.
37     describe("catalog content ? no internal token / debug-tag leaks (every locale)", () => {
38         const TOKEN = /min_shot_count/;
39         const DEBUG_TAG = /<\/?(?:kbd|samp|tt|var)\b/i;
40         const CODE_TAG = /<\/?code\b/i;
41         const codeAllowed = (key: string) => key.startsWith("site.ownModel.");
42         for (const loc of ALL_LOCALES) {
43             it(`${loc}: no 'min_shot_count' token or stray <code>/<kbd>/<samp>/<tt>/<var> tag`,
() => {
44                 const offenders = Object.entries(load(loc))
45                     .filter(([k, v]) => TOKEN.test(v) || DEBUG_TAG.test(v) || (CODE_TAG.test(v) &&
!codeAllowed(k)))
46                     .map(([k]) => k);
47                 expect(offenders).toEqual([]);
48             });
49         }
50     });
51
52     // (2) Brand ? never transliterated, and present (Latin) on EVERY key en uses it on. The
positive rule
53     // is the real guard: self-maintaining (auto-covers future brand keys, incl. errors.* /
ingest.hint that
54     // the old 3-key denylist missed) and it catches ANY transliteration spelling at once ?
a transliterated
55     // value simply won't contain Latin "KheISutra". The Indic-spelling denylist is cheap
defence-in-depth.
56     describe("catalog content ? the brand stays Latin 'KheISutra' everywhere en uses it", ()
=> {
57         const brandKeys = Object.keys(en).filter((k) => en[k].includes("KheISutra"));
58
59         it("en actually carries the brand on several keys (so the guard is meaningful)", () =>
{
60             expect(brandKeys.length).toBeGreaterThanOrEqual(6);

```

```

61     });
62
63     for (const loc of ["kn", "hi"] as const) {
64         it(`${loc}: Latin "KheḷSutra" is present on every key whose en value uses it`, () => {
65             const e = load(loc);
66             const missing = brandKeys.filter((k) => !(e[k] ?? "").includes("KheḷSutra"));
67             expect(missing).toEqual([]);
68         });
69     }
70
71     const TRANSLIT: Record<string, string> = { kn: "?????????", hi: "?????????" };
72     for (const loc of ["kn", "hi"] as const) {
73         it(`${loc}: the known Indic transliteration of the brand never appears`, () => {
74             const offenders = Object.entries(load(loc))
75                 .filter(([, v]) => v.includes(TRANSLIT[loc]))
76                 .map(([k]) => k);
77             expect(offenders).toEqual([]);
78         });
79     }
80 });
81
82 // (3) Engine/server/bucket/backend jargon only where en uses it (kn/hi). Self-
maintaining: a localized
83 // jargon term ? the Latin word OR an Indic transliteration ? is allowed ONLY on a key
whose en value
84 // also uses the English word. en avoids these in body copy (uses the brand / "cloud-
storage" / passive
85 // voice) EXCEPT the technical ingest.uriAriaLabel + uriPlaceholder; #77 leaked them
into kn/hi elsewhere.
86 describe("catalog content ? engine/server/bucket jargon only where en uses it (kn/hi)",
() => {
87     const ENGLISH = ["engine", "server", "bucket", "backend"] as const;
88     const TRANSLIT: Record<string, Record<(typeof ENGLISH)[number], string[]>> = {
89         kn: { engine: ["??????"], server: ["?????", "??????"], bucket: ["??????"], backend:
["??????????" ]},
90         hi: { engine: ["??????"], server: ["?????", "??????????"], bucket: ["??????"], backend:
["??????????" ]},
91     };
92     for (const loc of ["kn", "hi"] as const) {
93         it(`${loc}: a jargon term (Latin or transliterated) appears only where en uses the
English word`, () => {
94             const e = load(loc);
95             const violations: Array<{ key: string; term: string; en: string }> = [];
96             for (const [key, val] of Object.entries(e)) {
97                 const enUsesWord = (w: string) => new RegExp(`\\b${w}\\b`, "i").test(en[key] ??
"" );
98                 for (const w of ENGLISH) {
99                     const present = [
100                         ...(new RegExp(`\\b${w}\\b`, "i").test(val) ? [w] : []),
101                         ...TRANSLIT[loc][w].filter((t) => val.includes(t)),
102                     ];
103                     for (const term of present) if (!enUsesWord(w)) violations.push({ key, term,
en: en[key] ?? "(absent)" });
104                 }
105             }
106             expect(violations).toEqual([]);
107         });
108     }
109 });
110
111 // (4) Hindi de-Sanskritization (#77 class d) ? the over-Sanskritized / stiff terms must
stay replaced
112 // on the AUDITED keys. Key-scoped (not a repo-wide ban) so legitimate marketing prose
elsewhere is not

```

```

113 // constrained, while still catching a silent revert of the exact bug.
114 describe("catalog content ? Hindi de-Sanskritization stays fixed (#77 class d)", () => {
115   const hi = load("hi");
116   const BANNED: Array<[string, string]> = [
117     ["grid.shots", "?????????"], // "experimental" calque
118     ["grid.shotsTitle", "?????????"],
119     ["grid.shotsTitle", "?????????"], // "under development" bureaucratese
120     ["query.support", "?????????"],
121     ["query.support", "?????????"],
122     ["grid.shotsConfidence", "?????????"], // "faith" ? wrong sense for statistical
confidence
123     ["app.badge", "?????-????"], // "per-rally" calque
124   ];
125   for (const [key, term] of BANNED) {
126     it(`hi ${key} no longer contains the stiff "${term}"`, () => {
127       expect(hi).toHaveProperty(key);
128       expect(hi[key] ?? "").not.toContain(term);
129     });
130   }
131   it("hi keeps the friendlier replacements (???????? / ????? ?????)", () => {
132     expect(hi["grid.shots"]).toContain("????????");
133     expect(hi["grid.shotsTitle"]).toContain("????????");
134     expect(hi["query.support"]).toContain("????????");
135     expect(hi["grid.shotsConfidence"]).toContain("???? ?????");
136   });
137 });
138
139 // (5) Flagged mistranslations ? substring guard (.not.toContain) so a padded/wrapped
variant of the
140 // banned term ("???? ??????", a trailing space, ?) is still caught.
141 describe("catalog content ? flagged mistranslations stay fixed (kn/hi word choice)", ()
=> {
142   it("kn bulk.invert drops the 'rotate' mistranslation (????????)", () => {
143     expect(load("kn")["bulk.invert"]).not.toContain("????????");
144   });
145   it("kn result.dismiss drops the legalistic '????????'", () => {
146     expect(load("kn")["result.dismiss"]).not.toContain("????????");
147   });
148   it("hi result.dismiss drops the harsh '????'", () => {
149     expect(load("hi")["result.dismiss"]).not.toContain("????");
150   });
151 });
152

```

26. user (2026-07-04T01:29:23.903Z)

```

1 // CI guardrails that keep i18n "by design" (docs/archives/FRIENDLY_AND_MULTILINGUAL.md
$4):
2 // 1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
3 // drop a stub locale and this lists every gap). Trivially green while only `en`
exists; it
4 // starts enforcing the moment a kn/hi catalog lands (B5/B6).
5 // 2. NO-BARE-STRINGS (attribute level, v1) ? user-facing component attributes
(placeholder /
6 // aria-label / title) must route through t(), never a hardcoded literal. A curated
start per
7 // the doc; an AST-level sweep of JSX text can extend it later.
8 import { describe, it, expect } from "vitest";
9 import { readdirSync, readFileSync } from "node:fs";
10 import { join } from "node:path";
11
12 // Catalogs are hoisted to repo-root /locales (D-CATALOG-HOME): web/src/i18n ->
../.../locales.
13 const LOCALES_DIR = join(import.meta.dirname, "..", "..", "locales");

```

```

14     const SRC_DIR = join(import.meta.dirname, "..");
15
16     function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
17         const keys: string[] = [];
18         for (const [k, v] of Object.entries(obj)) {
19             const key = prefix ? `${prefix}.${k}` : k;
20             if (v && typeof v === "object" && !Array.isArray(v)) keys.push(...flatten(v as
Record<string, unknown>, key));
21             else keys.push(key);
22         }
23         return keys.sort();
24     }
25
26     const loadKeys = (locale: string): string[] =>
27         flatten(JSON.parse(readFileSync(join(LOCALES_DIR, locale, "common.json"), "utf8"))) as
Record<string, unknown>;
28
29     describe("i18n key-parity ? every locale has EXACTLY the en keys", () => {
30         const enKeys = loadKeys("en");
31         const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
32             .filter((d) => d.isDirectory() && d.name !== "en")
33             .map((d) => d.name);
34
35         it("en is the non-empty source catalog", () => {
36             expect(enKeys.length).toBeGreaterThan(20);
37         });
38
39         for (const loc of others) {
40             it(`${loc} matches en exactly (no missing, no extra keys)`, () => {
41                 const keys = loadKeys(loc);
42                 const missing = enKeys.filter((k) => !keys.includes(k));
43                 const extra = keys.filter((k) => !enKeys.includes(k));
44                 expect({ locale: loc, missing, extra }).toEqual({ locale: loc, missing: [], extra:
[] });
45             });
46         }
47     });
48
49     // Key-parity proves every locale has the same KEYS; this proves every locale's VALUE
keeps the same
50     // simple `{placeholder}` set as en ? so a translation can never silently drop a
{count}/{error}/{min}/
51     // {filename}/{n}/? and break interpolation. (ICU plural headers like `{count, plural,
?}` carry no
52     // simple {word} placeholder and match as empty on both sides, so they're correctly
ignored.)
53     describe("placeholder parity ? every locale preserves en's {placeholders}", () => {
54         function flatEntries(obj: Record<string, unknown>, prefix = ""): Record<string,
string> {
55             const out: Record<string, string> = {};
56             for (const [k, v] of Object.entries(obj)) {
57                 const key = prefix ? `${prefix}.${k}` : k;
58                 if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(out,
flatEntries(v as Record<string, unknown>, key));
59                 else out[key] = String(v);
60             }
61             return out;
62         }
63         const placeholders = (s: string) => (s.match(/\{(\w+)\}/g) ?? []).sort();
64         const load = (loc: string) => flatEntries(JSON.parse(readFileSync(join(LOCALES_DIR,
loc, "common.json"), "utf8")));
65         const enE = load("en");
66         const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
67             .filter((d) => d.isDirectory() && d.name !== "en")
68             .map((d) => d.name);

```

```

69
70     for (const loc of others) {
71         it(`${loc} preserves every {placeholder} that en uses`, () => {
72             const locE = load(loc);
73             const mismatches: Array<{ key: string; en: string[]; got: string[] }> = [];
74             for (const key of Object.keys(enE)) {
75                 if (!(key in locE)) continue; // missing keys are the key-parity test's job
76                 const a = placeholders(enE[key]);
77                 const b = placeholders(locE[key]);
78                 if (a.join(",") !== b.join(",")) mismatches.push({ key, en: a, got: b });
79             }
80             expect(mismatches).toEqual([]);
81         });
82     }
83 });
84
85 describe("es 3-form plural (CLDR one/many/other) ? MULTILINGUAL Phase A", () => {
86     // Spanish cardinal is {one, many, other}; every es ICU plural message MUST carry a
87     // (the `many` category fires on large/compact numbers) or intl-messageformat silently
88     // These are the plural-bearing keys in the catalog.
89     const es = JSON.parse(readFileSync(join(LOCALES_DIR, "es", "common.json"), "utf8")) as
Record<string, Record<string, string>>;
90     const pluralKeys: Array<[string, string]> = [
91         ["footer", "count"],
92         ["footer", "floorSomeLead"],
93         ["selection", "count"],
94     ];
95     for (const [ns, key] of pluralKeys) {
96         it(`es ${ns}.${key} carries one/many/other arms`, () => {
97             const msg = es[ns][key];
98             expect(msg, `${ns}.${key}`).toMatch(/\\bone\\s*\\{/);
99             expect(msg, `${ns}.${key}`).toMatch(/\\bmany\\s*\\{/);
100             expect(msg, `${ns}.${key}`).toMatch(/\\bother\\s*\\{/);
101         });
102     }
103 });
104
105 describe("no-bare-strings ? user-facing component attributes go through t()", () => {
106     const FILES = [
107         "App.tsx",
108         "components/QueryBar.tsx",
109         "components/TapFilters.tsx",
110         "components/RallyGrid.tsx",
111         "components/SelectionFooter.tsx",
112         "components/CompileResult.tsx",
113         "components/LanguageSwitcher.tsx",
114         "components/IngestPanel.tsx",
115         "components/SetupWizard.tsx",
116         "components/VideoLibrary.tsx",
117         "components/AnnotatePanel.tsx",
118     ];
119     // A hardcoded placeholder / aria-label / title with letters is a bare-string
120     // must be an expression ({t(...)}), not a quoted literal.
121     const BARE_ATTR = /\\b(?:placeholder|aria-label|title)\\s*=\\s*"\\^[^"]*[A-Za-z]{2}\\^[^"]*"\\/g;
122
123     for (const f of FILES) {
124         it(`${f}: no hardcoded placeholder/aria-label/title`, () => {
125             const src = readFileSync(join(SRC_DIR, f), "utf8");
126             expect(src.match(BARE_ATTR) ?? []).toEqual([]);
127         });
128     }
129 });

```



```

130
131     describe("Indic fonts (B4) ? self-hosted OFL Noto, no runtime CDN", () => {
132         it("main.tsx bundles the OFL Noto Kannada + Devanagari fonts (self-hosted, not Google
133         Fonts)", () => {
134             const main = readFileSync(join(SRC_DIR, "main.tsx"), "utf8");
135             expect(main).toMatch(/@fontsource-variable\/noto-sans-kannada/);
136             expect(main).toMatch(/@fontsource-variable\/noto-sans-devanagari/);
137         });
138         it("the font stack falls back to Noto for Kannada + Devanagari glyphs", () => {
139             const css = readFileSync(join(SRC_DIR, "index.css"), "utf8");
140             expect(css).toMatch(/Noto Sans Kannada Variable/);
141             expect(css).toMatch(/Noto Sans Devanagari Variable/);
142         });
143     });
144     // The Studio SPA must render correctly on an AIR-GAPPED appliance (GPU/CPU/RAM, no
145     internet) ?
146     // every asset (fonts, styles, scripts) is bundled local, nothing pulled from a
147     CDN/Google Fonts.
148     describe("offline / self-contained ? no external runtime assets", () => {
149         const CDN = /googleapis|gstatic|fonts\.google|cdnjs|unpkg|jsdelivr\bcdn\.[a-z]/i;
150         const FILES = [
151             "../index.html", // web/index.html
152             "main.tsx",
153             "index.css",
154         ];
155         for (const rel of FILES) {
156             it(`${rel}: no external font/CDN reference`, () => {
157                 expect(readFileSync(join(SRC_DIR, rel), "utf8")).not.toMatch(CDN);
158             });
159         }
160         it("web/index.html loads no absolute-URL <link>/<script src> (everything is
161         bundled/local)", () => {
162             const html = readFileSync(join(SRC_DIR, "..", "index.html"), "utf8");
163             expect(html).not.toMatch(/(?:href|src)\s*=\s*["']https?:\/\//i);
164         });
165     });

```

27. assistant (2026-07-04T01:30:56.201Z)

Let me read the upload hook test, the IngestPanel test, and the `errors` blocks of the other five locales to mirror their structure. Let me also check for any existing byte formatter.

28. user (2026-07-04T01:30:57.708Z)

```

1      // @vitest-environment jsdom
2      //
3      // The upload state machine (T4): start(file) ? uploading(%) ? hand the server PATH to
4      onComplete |
5      // error. Pins: an empty file is rejected before any network call, a happy upload calls
6      onComplete
7      // with the returned path + filename and returns to idle, and an engine rejection
8      surfaces a
9      // classified error.
10     import { describe, it, expect, vi, afterEach } from "vitest";
11     import { renderHook, act, waitFor } from "@testing-library/react";
12     import { useUpload } from "../useUpload";
13
14     type FetchFn = typeof fetch;
15     const MB = 1024 * 1024;
16     const ok = (j: unknown) => ({ ok: true, status: 200, json: async () => j, text: async ()
=> JSON.stringify(j) });
17     const httpErr = (status: number, detail: string) => ({
18         ok: false, status, json: async () => ({ detail }), text: async () => JSON.stringify({

```

```

detail }},
16     });
17
18     function uploadFetch(opts: { partFailsAt?: number } = {}): FetchFn {
19         return vi.fn(async (url: string | URL, init?: RequestInit) => {
20             const u = String(url);
21             const m = init?.method ?? "GET";
22             if (u === "/api/upload/init") return ok({ upload_id: "up1", max_part_mb: 1,
next_part: "/api/upload/up1/part/0" });
23             const part = u.match(/\d+$/);
24             if (part && m === "PUT") {
25                 if (opts.partFailsAt === Number(part[1])) return httpErr(413, "Part exceeds the
per-part limit");
26                 return ok({ upload_id: "up1", received_parts: 1, received_bytes: (init?.body as
Blob).size });
27             }
28             if (u.endsWith("/complete")) return ok({ path: "/srv/uploads/match.mp4", video_id:
"VID", size_bytes: 1 });
29             if (m === "DELETE") return ok({ status: "aborted" });
30             throw new Error(`unexpected ${m} ${u}`);
31         }) as unknown as FetchFn;
32     }
33
34     const videoFile = (bytes: number, name = "match.mp4") => new File([new
Uint8Array(bytes)], name, { type: "video/mp4" });
35
36     afterEach(() => {
37         vi.restoreAllMocks();
38         vi.unstubAllGlobals();
39     });
40
41     describe("useUpload", () => {
42         it("rejects an empty file before any network call", () => {
43             const f = vi.fn();
44             vi.stubGlobal("fetch", f as unknown as FetchFn);
45             const onComplete = vi.fn();
46             const { result } = renderHook(() => useUpload(onComplete));
47
48             act(() => result.current.start(videoFile(0)));
49
50             expect(result.current.phase).toEqual({ status: "error", error: { code: "invalidUri"
} });
51             expect(f).not.toHaveBeenCalled();
52             expect(onComplete).not.toHaveBeenCalled();
53         });
54
55         it("uploads a file and hands the returned server path and filename to onComplete",
async () => {
56             vi.stubGlobal("fetch", uploadFetch());
57             const onComplete = vi.fn();
58             const { result } = renderHook(() => useUpload(onComplete));
59
60             act(() => result.current.start(videoFile(0.3 * MB)));
61             await waitFor(() =>
expect(onComplete).toHaveBeenCalledWith("/srv/uploads/match.mp4", "match.mp4"));
62             expect(result.current.phase.status).toBe("idle"); // handed off ? the engine phase
takes over
63         });
64
65         it("surfaces a classified error when a part is rejected", async () => {
66             vi.stubGlobal("fetch", uploadFetch({ partFailsAt: 0 }));
67             const onComplete = vi.fn();
68             const { result } = renderHook(() => useUpload(onComplete));
69
70             act(() => result.current.start(videoFile(0.3 * MB)));

```

```

71     await waitFor(() => expect(result.current.phase.status).toBe("error"));
72     expect(onComplete).not.toHaveBeenCalled();
73     // a 413 with a {detail} body classifies as an engine error (its message survives)
74     expect(result.current.phase).toMatchObject({ status: "error", error: { code:
"engine" } });
75     });
76     });
77

```

29. user (2026-07-04T01:30:58.237Z)

```

1      // @vitest-environment jsdom
2      //
3      // The ingest screen end to end: type a URI ? submit ? (mocked engine) ? onLoaded gets
the video_id;
4      // and the two failure surfaces a non-technical user actually hits ? the engine's own
400 detail,
5      // and a friendly "is the engine running?" when it's unreachable. Mounts the real i18n
catalog.
6      import { describe, it, expect, vi, beforeEach, afterEach } from "vitest";
7      import { render, screen, fireEvent, cleanup, act, waitFor } from "@testing-
library/react";
8      import i18n from "../i18n/index";
9      import { IngestPanel } from "../IngestPanel";
10     import type { JobStatus } from "../api/types";
11
12     type FetchFn = typeof fetch;
13
14     function httpOk(status: number, json: unknown) {
15         return { ok: status >= 200 && status < 300, status, json: async () => json, text:
async () => JSON.stringify(json) };
16     }
17
18     function fetchSeq(process: unknown, jobs: JobStatus[]): FetchFn {
19         let i = 0;
20         return vi.fn(async (url: string | URL, init?: RequestInit) => {
21             const u = String(url);
22             // The panel probes /api/capabilities on mount (compute-picker) ? answer it benignly
so the
23             // ingest-flow assertions don't see a stray "unexpected fetch". No cloud ? no
picker.
24             if (u === "/api/capabilities") return httpOk(200, {});
25             if (u === "/api/process" && (init?.method ?? "GET") === "POST") return process;
26             if (u.startsWith("/api/jobs/")) {
27                 const body = jobs[Math.min(i, jobs.length - 1)];
28                 i += 1;
29                 return httpOk(200, body);
30             }
31             throw new Error(`unexpected fetch ${u}`);
32         }) as unknown as FetchFn;
33     }
34
35     /** Like fetchSeq but lets a test set the capabilities payload + capture the
/api/process body ? used
36     * to drive and assert the compute-picker. */
37     function fetchAll(opts: {
38         caps?: unknown;
39         process?: unknown;
40         jobs?: JobStatus[];
41         onProcessBody?: (body: Record<string, unknown>) => void;
42     }): FetchFn {
43         let i = 0;
44         const jobs = opts.jobs ?? [];
45         return vi.fn(async (url: string | URL, init?: RequestInit) => {
46             const u = String(url);

```

```

47     if (u === "/api/capabilities") return httpOk(200, opts.caps ?? {});
48     if (u === "/api/process" && (init?.method ?? "GET") === "POST") {
49         opts.onProcessBody?.(JSON.parse(String(init?.body ?? "{}"))) as Record<string,
unknown>);
50         return opts.process ?? httpOk(202, { job_id: "j", status: "queued", poll:
"/api/jobs/j" });
51     }
52     if (u.startsWith("/api/jobs/")) {
53         const body = jobs[Math.min(i, jobs.length - 1)];
54         i += 1;
55         return httpOk(200, body);
56     }
57     throw new Error(`unexpected fetch ${u}`);
58 }) as unknown as FetchFn;
59 }
60
61 beforeEach(async () => {
62     window.localStorage.clear();
63     window.history.replaceState(null, "", "/");
64     await i18n.changeLanguage("en"); // guarantees init completed + a known locale for the
assertions
65 });
66
67 afterEach(() => {
68     cleanup();
69     vi.restoreAllMocks();
70     vi.unstubAllGlobals();
71     vi.useRealTimers();
72 });
73
74 const typeUri = (value: string) =>
75     fireEvent.change(screen.getByLabelText(/video location/i), { target: { value } });
76 const clickProcess = () => fireEvent.click(screen.getByRole("button", { name: /process
video/i }));
77
78 describe("IngestPanel", () => {
79     it("submits a URI, polls, and hands the video_id to onLoaded", async () => {
80         vi.useFakeTimers();
81         vi.stubGlobal(
82             "fetch",
83             fetchSeq(httpOk(202, { job_id: "j", status: "queued", poll: "/api/jobs/j" }), [
84                 { job_id: "j", status: "running", progress: "segmenting" },
85                 { job_id: "j", status: "done", video_id: "vidZ", result: { status: "success",
video_id: "vidZ" } },
86             ]),
87         );
88         const onLoaded = vi.fn();
89         render(<IngestPanel onLoaded={onLoaded} />);
90         typeUri("gs://bucket/match.mp4");
91         clickProcess();
92
93         await act(async () => {
94             await vi.advanceTimersByTimeAsync(0); // flush submit ? start polling
95         });
96         await act(async () => {
97             await vi.advanceTimersByTimeAsync(1000); // running tick
98         });
99         await act(async () => {
100             await vi.advanceTimersByTimeAsync(1500); // done tick
101         });
102         expect(onLoaded).toHaveBeenCalledWith("vidZ", "match.mp4");
103     });
104
105     it("shows the engine's own 400 detail (e.g. an unsupported scheme)", async () => {
106         vi.stubGlobal("fetch", fetchSeq(httpOk(400, { detail: "unsupported storage URI

```

```

scheme: ftp://" }}, []));
107     render(<IngestPanel onLoaded={vi.fn()} />);
108     typeUri("ftp://nope");
109     clickProcess();
110     expect(await screen.findByText(/unsupported storage URI scheme/i)).toBeTruthy();
111     fireEvent.click(screen.getByRole("button", { name: /try again/i }));
112     expect(screen.queryByTestId("ingest-error")).toBeNull();
113 });
114
115 it("shows a failed pipeline verdict as the engine's reason, not as no rallies", async
() => {
116     vi.useFakeTimers();
117     vi.stubGlobal(
118         "fetch",
119         fetchSeq(httpOk(202, { job_id: "jFail", status: "queued", poll: "/api/jobs/jFail"
120     })), [
121         { job_id: "jFail", status: "done", video_id: "vidFail", result: { status:
"failed", message: "Video failed validation: blur: blurry" } },
122     ],
123     );
124     render(<IngestPanel onLoaded={vi.fn()} />);
125     typeUri("gs://bucket/blurry.mp4");
126     clickProcess();
127     await act(async () => {
128         await vi.advanceTimersByTimeAsync(0);
129     });
130     await act(async () => {
131         await vi.advanceTimersByTimeAsync(1000);
132     });
133     expect(screen.getByTestId("ingest-error").textContent).toMatch(/Video failed
validation: blur: blurry/i);
134     expect(screen.getByTestId("ingest-error").textContent).not.toMatch(/found no
rallies/i);
135 });
136
137 it("shows a friendly, localized message when the engine is unreachable", async () => {
138     vi.stubGlobal("fetch", vi.fn(async () => {
139         throw new Error("offline");
140     }) as unknown as FetchFn);
141     render(<IngestPanel onLoaded={vi.fn()} />);
142     typeUri("gs://bucket/match.mp4");
143     clickProcess();
144     expect(await screen.findByText(/can't reach khelsutra/i)).toBeTruthy();
145 });
146
147 it("rejects an empty URI with a hint and never submits to the engine", () => {
148     // The mount-time capabilities probe may fire; assert specifically that /api/process
never does.
149     const f = fetchAll({ caps: {} });
150     vi.stubGlobal("fetch", f);
151     render(<IngestPanel onLoaded={vi.fn()} />);
152     clickProcess();
153     expect(screen.getByTestId("ingest-error")).toBeTruthy();
154     const submitted = (f as unknown as { mock: { calls: unknown[][] }
}).mock.calls.some(
155         ([u]) => String(u) === "/api/process",
156     );
157     expect(submitted).toBe(false);
158 });
159 // --- compute-picker (item 3)
-----
160
161 it("hides the compute picker when the server can't dispatch to the cloud", async () =>
{

```

```

162     vi.stubGlobal("fetch", fetchAll({ caps: { deployment: { cloud_available: false } }
    }));
163     render(<IngestPanel onLoaded={vi.fn()} />);
164     await act(async () => {}); // let the capabilities probe resolve
165     expect(screen.queryByTestId("compute-picker")).toBeNull();
166 });
167
168 it("defaults to local and sends compute=local when the cloud is available", async ()
=> {
169     const bodies: Record<string, unknown>[] = [];
170     vi.stubGlobal(
171         "fetch",
172         fetchAll({
173             caps: { deployment: { cloud_available: true } },
174             onProcessBody: (b) => bodies.push(b),
175             jobs: [{ job_id: "j", status: "done", video_id: "vidL", result: { status:
"success", video_id: "vidL" } }],
176         }),
177     );
178     render(<IngestPanel onLoaded={vi.fn()} />);
179     await screen.findByTestId("compute-picker");
180     typeUri("gs://bucket/match.mp4");
181     clickProcess();
182     await act(async () => {});
183     expect(bodies).toHaveLength(1);
184     expect(bodies[0].compute).toBe("local");
185 });
186
187 it("shows a pasted host-path basename while processing and clears it on cancel", async
() => {
188     vi.useFakeTimers();
189     vi.stubGlobal(
190         "fetch",
191         fetchAll({
192             caps: {},
193             jobs: [{ job_id: "j", status: "running", progress: "hashing" }],
194         }),
195     );
196     render(<IngestPanel onLoaded={vi.fn()} />);
197
198     typeUri("C:\\videos\\Sunday Match.mov");
199     clickProcess();
200     await act(async () => {
201         await vi.advanceTimersByTimeAsync(0);
202     });
203
204     expect(screen.getByTestId("ingest-source").textContent).toContain("Sunday
Match.mov");
205     fireEvent.click(screen.getByRole("button", { name: /cancel/i }));
206     expect(screen.queryByTestId("ingest-source")).toBeNull();
207 });
208
209 it("shows a decoded URL basename while processing", async () => {
210     vi.useFakeTimers();
211     vi.stubGlobal(
212         "fetch",
213         fetchAll({
214             caps: {},
215             jobs: [{ job_id: "j", status: "running", progress: "hashing" }],
216         }),
217     );
218     render(<IngestPanel onLoaded={vi.fn()} />);
219
220     typeUri("https://cdn.example/video/Sunday%20Final.mp4?download=1");
221     clickProcess();

```

```

222     await act(async () => {
223         await vi.advanceTimersByTimeAsync(0);
224     });
225
226     expect(screen.getByTestId("ingest-source").textContent).toContain("Sunday
Final.mp4");
227     });
228
229     // --- medium picker (P5, store-into-medium)
-----
230
231     const capsBucket = {
232         storage: {
233             default_medium: "local",
234             backends: [
235                 { id: "local", kind: "local", label: "This computer", usable: true, free_gb: 100
},
236                 { id: "gcs", kind: "gcs", label: "GCS", usable: true, free_gb: null },
237                 { id: "s3", kind: "s3", label: "S3", usable: false, free_gb: null },
238                 { id: "gdrive", kind: "gdrive", label: "Drive", usable: false, free_gb: null },
239             ],
240         },
241     };
242
243     // A fetch mock that answers the full store?process choreography (upload ? assets ?
process ? job).
244     function fetchStore(opts: {
245         caps?: unknown;
246         jobs?: JobStatus[];
247         onAssetBody?: (b: Record<string, unknown>) => void;
248         onProcessBody?: (b: Record<string, unknown>) => void;
249     }): FetchFn {
250         let ji = 0;
251         const jobs = opts.jobs ?? [];
252         return vi.fn(async (url: string | URL, init?: RequestInit) => {
253             const u = String(url);
254             const m = init?.method ?? "GET";
255             if (u === "/api/capabilities") return httpOk(200, opts.caps ?? {});
256             if (u === "/api/upload/init") return httpOk(200, { upload_id: "up1", max_part_mb:
95, next_part: "/api/upload/up1/part/0" });
257             if (/^\api\upload\up1\part\ld+$.test(u)) return httpOk(200, { upload_id:
"up1", received_parts: 1, received_bytes: 3 });
258             if (/^\api\upload\up1\complete$.test(u)) return httpOk(200, { path:
"/srv/up/match.mp4", video_id: "mock", size_bytes: 3 });
259             if (u === "/api/assets" && m === "POST") {
260                 opts.onAssetBody?.(JSON.parse(String(init?.body ?? "{}"))) as Record<string,
unknown>);
261                 return httpOk(201, { video_id: "vidS", medium: "gcs", stored_uri:
"gcs://b/videos/vidS.mp4", copied: true, status: "stored" });
262             }
263             if (u === "/api/process" && m === "POST") {
264                 opts.onProcessBody?.(JSON.parse(String(init?.body ?? "{}"))) as Record<string,
unknown>);
265                 return httpOk(202, { job_id: "j", status: "queued", poll: "/api/jobs/j" });
266             }
267             if (u.startsWith("/api/jobs/")) {
268                 const b = jobs[Math.min(ji, jobs.length - 1)];
269                 ji += 1;
270                 return httpOk(200, b);
271             }
272             throw new Error(`unexpected fetch ${m} ${u}`);
273         }) as unknown as FetchFn;
274     }
275
276     it("hides the medium picker when only local is usable", async () => {

```

```

277     vi.stubGlobal("fetch", fetchAll({ caps: { storage: { backends: [{ id: "local", kind:
"local", label: "x", usable: true }] } } }));
278     render(<IngestPanel onLoaded={vi.fn()} />);
279     await act(async () => {});
280     expect(screen.queryByTestId("medium-picker")).toBeNull();
281   });
282
283   it("shows the picker and gates the upload until a destination is given", async () => {
284     vi.stubGlobal("fetch", fetchStore({ caps: capsBucket }));
285     render(<IngestPanel onLoaded={vi.fn()} />);
286     await screen.findByTestId("medium-picker");
287     fireEvent.click(screen.getByTestId("medium-bucket"));
288     // Destination empty ? blocked: the required hint shows and the file input is
disabled.
289     expect(screen.getByTestId("medium-required")).toBeTruthy();
290     const fileInput = document.querySelector('input[type="file"]') as HTMLInputElement;
291     expect(fileInput.disabled).toBe(true);
292     // Provide a destination ? the gate lifts.
293     fireEvent.change(screen.getByLabelText(/storage destination/i), { target: { value:
"gcs://b/videos" } });
294     expect(screen.queryByTestId("medium-required")).toBeNull();
295     expect(fileInput.disabled).toBe(false);
296     // The local-mode "or a cloud link" source form is hidden in a non-local medium.
297     expect(screen.queryByText(/or use a cloud link/i)).toBeNull();
298   });
299
300   it("offers Drive as a storage medium when the engine reports a usable mount", async ()
=> {
301     vi.stubGlobal(
302       "fetch",
303       fetchStore({
304         caps: {
305           storage: {
306             backends: [
307               { id: "local", kind: "local", label: "This computer", usable: true },
308               { id: "gdrive", kind: "gdrive", label: "Drive", usable: true },
309             ],
310           },
311         },
312       }),
313     );
314     render(<IngestPanel onLoaded={vi.fn()} />);
315     await screen.findByTestId("medium-picker");
316     fireEvent.click(screen.getByTestId("medium-drive"));
317     expect(screen.getByPlaceholderText("gdrive://Matches")).toBeTruthy();
318   });
319
320   it("stores an uploaded video into the chosen medium, then processes the stored copy",
async () => {
321     const assetBodies: Record<string, unknown>[] = [];
322     const processBodies: Record<string, unknown>[] = [];
323     vi.stubGlobal(
324       "fetch",
325       fetchStore({
326         caps: capsBucket,
327         onAssetBody: (b) => assetBodies.push(b),
328         onProcessBody: (b) => processBodies.push(b),
329         jobs: [{ job_id: "j", status: "done", video_id: "vidS", result: { status:
"success", video_id: "vidS" } }],
330       }),
331     );
332     render(<IngestPanel onLoaded={vi.fn()} />);
333     await screen.findByTestId("medium-picker");
334     fireEvent.click(screen.getByTestId("medium-bucket"));
335     fireEvent.change(screen.getByLabelText(/storage destination/i), { target: { value:

```



```

"gs://b/videos" } });
336     const file = new File([new Uint8Array([1, 2, 3])], "match.mp4", { type: "video/mp4"
});
337     const fileInput = document.querySelector('input[type="file"]') as HTMLInputElement;
338     await act(async () => {
339         fireEvent.change(fileInput, { target: { files: [file] } });
340     });
341     expect(screen.getByTestId("ingest-source").textContent).toContain("match.mp4");
342     // The upload ? createAsset ? process chain runs: the asset is stored MD5-keyed,
then the STORED
343     // uri (not the raw upload path) is what's indexed.
344     await waitFor(() => expect(assetBodies).toHaveLength(1));
345     expect(assetBodies[0]).toEqual({ uploaded_path: "/srv/up/match.mp4", medium_uri:
"gs://b/videos" });
346     await waitFor(() => expect(processBodies).toHaveLength(1));
347     expect(processBodies[0].video_path).toBe("gs://b/videos/vidS.mp4");
348 });
349
350 it("surfaces a store failure loudly (e.g. the engine's 507 no-space)", async () => {
351     const fetchFail = fetchStore({ caps: capsBucket });
352     // Override /api/assets to a 507.
353     const wrapped = vi.fn(async (url: string | URL, init?: RequestInit) => {
354         if (String(url) === "/api/assets") return httpOk(507, { detail: "Not enough free
disk space for store" });
355         return (fetchFail as unknown as (u: string | URL, i?: RequestInit) =>
Promise<unknown>)(url, init);
356     }) as unknown as FetchFn;
357     vi.stubGlobal("fetch", wrapped);
358     render(<IngestPanel onLoaded={vi.fn()} />);
359     await screen.findByTestId("medium-picker");
360     fireEvent.click(screen.getByTestId("medium-bucket"));
361     fireEvent.change(screen.getByLabelText(/storage destination/i), { target: { value:
"gs://b/videos" } });
362     const file = new File([new Uint8Array([1, 2, 3])], "match.mp4", { type: "video/mp4"
});
363     await act(async () => {
364         fireEvent.change(document.querySelector('input[type="file"]') as HTMLInputElement,
{ target: { files: [file] } });
365     });
366     expect(await screen.findByTestId("ingest-error")).toBeTruthy();
367 });
368
369 it("gates cloud on a cost ack, then sends compute=cloud", async () => {
370     const bodies: Record<string, unknown>[] = [];
371     vi.stubGlobal(
372         "fetch",
373         fetchAll({
374             caps: { deployment: { cloud_available: true } },
375             onProcessBody: (b) => bodies.push(b),
376             jobs: [{ job_id: "j", status: "done", video_id: "vidC", result: { status:
"success", video_id: "vidC" } }],
377         }),
378     );
379     render(<IngestPanel onLoaded={vi.fn()} />);
380     await screen.findByTestId("compute-picker");
381     // Type the URI while LOCAL (the input is enabled), then switch to CLOUD.
382     typeUri("gs://bucket/match.mp4");
383     fireEvent.click(screen.getByRole("button", { name: /in the cloud/i }));
384     // Cost note + ack appear; submit is gated until the cost is accepted.
385     expect(screen.getByTestId("compute-cost")).toBeTruthy();
386     expect(screen.getByTestId("compute-ack-required")).toBeTruthy();
387     const submitBtn = screen.getByRole("button", { name: /process video/i }) as
HTMLButtonElement;
388     expect(submitBtn.disabled).toBe(true);
389     clickProcess(); // a disabled button does nothing ? still no submit

```

```

390     expect(bodies).toHaveLength(0);
391     // Accept the cost ? the gate lifts ? run on the cloud.
392     fireEvent.click(screen.getByRole("checkbox"));
393     expect(submitBtn.disabled).toBe(false);
394     clickProcess();
395     await act(async () => {});
396     expect(bodies).toHaveLength(1);
397     expect(bodies[0].compute).toBe("cloud");
398   });
399 });
400

```

30. user (2026-07-04T01:30:59.942Z)

Found 6 files
 web\src\lib\query.ts
 web\src\hooks\useUpload.test.ts
 web\src\components\upload.test.tsx
 web\src\api\upload.test.ts
 web\src\api\types.ts
 web\src\api\client.ts

31. assistant (2026-07-04T01:31:05.451Z)

No existing byte formatter ? I'll add one. Now let me read the `errors` blocks of the other five locales to mirror their structure and tone.

32. user (2026-07-04T01:31:09.700Z)

```

=== kn ===
{
  "networkError": "KhelSutra ??????????????. ??? ??????????????",
  "invalidUri": "????? ?????? ?????????? ??????? ? gs:// ?????? KhelSutra ??????????????
  ?????? ??.",
  "emptyResult": "????????? ?????????? ??? ? ?????????? ?????? ?????????? ?????????? ??????????
  ?????? ?????????????? ?????????????.",
  "timeout": "????????????????? ?????? ??? ??????????????????????. ???? ?????? ?????????????????????? ? ??????
  ?????????????????? ??????? ????, ???? ?????? ?????????????.",
  "engineGeneric": "??? ??????????. ?????????? ?????? ?????????????."
}
--- ingest.medium.storing: ?????? ?????????????? ?????????????????????
--- storage: {"local": "? ??????????", "bucket": "???????? ??????", "drive": "????? ??????"}
=== hi ===
{
  "networkError": "KhelSutra ?? ?????? ?????? ?? ?????? ?? ?? ??? ????",
  "invalidUri": "????? ?????? ?? ?????? ?????? ? ?? gs:// ?????? KhelSutra ??? ??? ?????? ?? ??
  ?????",
  "emptyResult": "????????????? ?????? ??? ?? ?? ?????? ??? ??? ?????? ?????? ?????? ?? ?????? ???
  ?????????????? ??????????",
  "timeout": "?? ?????????? ?? ?????? ??? ?? ??? ??? ??? ??? ?? ?? ??? ?? ?????? ?? ? ?????? ?????? ??
  ??? ?????? ?????, ?? ??? ?? ?????? ??????",
  "engineGeneric": "??? ?????????? ?? ??? ?????? ??? ?? ?????? ??????"
}
--- ingest.medium.storing: ?????? ?????????? ?????? ?????? ?????? ?? ??? ???
--- storage: {"local": "?? ??????????", "bucket": "???????? ??????", "drive": "????? ??????"}
=== es ===
{
  "networkError": "No se puede conectar con KhelSutra. ¿Está en ejecución?",
  "invalidUri": "Primero indica la ubicación del video ? un enlace gs:// o una ruta en la
  máquina que ejecuta KhelSutra.",
  "emptyResult": "El procesamiento terminó pero no se encontraron jugadas en este video. Prueba
  con una grabación más clara del partido.",
  "timeout": "Esto está tardando más de lo esperado. El trabajo puede seguir en curso ? recarga
  con el enlace del video, o reintenta.",
}

```

```

    "engineGeneric": "Algo salió mal. Inténtalo de nuevo."
  }
  --- ingest.medium.storing: Guardando en tu medio?
  --- storage: {"local": "Este equipo", "bucket": "Bucket en la nube", "drive": "Google Drive"}
  === da ===
  {
    "networkError": "Kan ikke nå KhelSutra. Kører den?",
    "invalidUri": "Angiv først en videoplacering ? et gs://-link eller en sti på maskinen, der
    kører KhelSutra.",
    "emptyResult": "Behandlingen er færdig, men der blev ikke fundet nogen dueller i denne video.
    Prøv en tydeligere kampoptagelse.",
    "timeout": "Dette tager længere tid end forventet. Jobbet kører måske stadig ? genindlæs med
    videolinket, eller prøv igen.",
    "engineGeneric": "Noget gik galt. Prøv igen."
  }
  --- ingest.medium.storing: Gemmer i dit medie?
  --- storage: {"local": "Denne computer", "bucket": "Cloud-bucket", "drive": "Google Drev"}
  === id ===
  {
    "networkError": "Tidak dapat menghubungi KhelSutra. Apakah sedang berjalan?",
    "invalidUri": "Masukkan lokasi video dulu ? tautan gs:// atau path di mesin yang menjalankan
    KhelSutra.",
    "emptyResult": "Pemrosesan selesai tetapi tidak ada reli yang ditemukan di video ini. Coba
    rekaman pertandingan yang lebih jelas.",
    "timeout": "Ini memakan waktu lebih lama dari perkiraan. Tugas mungkin masih berjalan ? muat
    ulang dengan tautan video, atau coba lagi.",
    "engineGeneric": "Terjadi kesalahan. Silakan coba lagi."
  }
  --- ingest.medium.storing: Menyimpan di media Anda?
  --- storage: {"local": "Komputer ini", "bucket": "Bucket cloud", "drive": "Google Drive"}

```

33. assistant (2026-07-04T01:34:10.130Z)

I have a full picture. Let me read `format.test.ts` and grab the exact `engineGeneric` lines across locales for precise edits.

34. user (2026-07-04T01:34:11.635Z)

```

1      import { describe, it, expect } from "vitest";
2      import { mmss, pluralize, reelFilename } from "../format";
3
4      describe("mmss", () => {
5        it("formats seconds as m:ss", () => {
6          expect(mmss(0)).toBe("0:00");
7          expect(mmss(5)).toBe("0:05");
8          expect(mmss(65)).toBe("1:05");
9          expect(mmss(600)).toBe("10:00");
10       });
11      it("rounds to the nearest second and clamps junk to 0:00", () => {
12        expect(mmss(5.7)).toBe("0:06");
13        expect(mmss(-3)).toBe("0:00");
14        expect(mmss(undefined as unknown as number)).toBe("0:00");
15      });
16    });
17
18    describe("pluralize", () => {
19      it("uses the singular for 1, plural otherwise", () => {
20        expect(pluralize(1, "rally", "rallies")).toBe("1 rally");
21        expect(pluralize(3, "rally", "rallies")).toBe("3 rallies");
22        expect(pluralize(0, "rally", "rallies")).toBe("0 rallies");
23        expect(pluralize(2, "clip")).toBe("2 clips");
24      });
25    });
26
27    describe("reelFilename", () => {

```

```

28     it("slugifies to a safe bare .mp4 name", () => {
29         expect(reelFilename("Tuesday ? Long Points")).toBe("tuesday-long-points.mp4");
30         expect(reelFilename("Coach Priya's session #2")).toBe("coach-priya-s-
session-2.mp4");
31     });
32     it("falls back to highlights for empty/garbage", () => {
33         expect(reelFilename("")).toBe("highlights.mp4");
34         expect(reelFilename("   ")).toBe("highlights.mp4");
35         expect(reelFilename("****")).toBe("highlights.mp4");
36     });
37     it("never contains a path separator or traversal (engine-safe)", () => {
38         for (const n of ["../etc/passwd", "a/b\\c", "..", "."]) {
39             const f = reelFilename(n);
40             expect(f).not.toMatch(/[\/\\]/);
41             expect(f.endsWith(".mp4")).toBe(true);
42         }
43     });
44 });
45

```

35. user (2026-07-04T01:34:12.802Z)

```

kn\common.json:129:    "engineGeneric": "??? ??????????. ????????? ????? ???????????"
hi\common.json:129:    "engineGeneric": "??? ?????? ?? ??? ?????? ?? ? ?????? ??????"
da\common.json:129:    "engineGeneric": "Noget gik galt. Prøv igen."
id\common.json:129:    "engineGeneric": "Terjadi kesalahan. Silakan coba lagi."
es\common.json:129:    "engineGeneric": "Algo salió mal. Inténtalo de nuevo."
en\common.json:129:    "engineGeneric": "Something went wrong. Please try again."

```

36. assistant (2026-07-04T01:34:17.861Z)

All confirmed. Let me implement. Starting with the type, error code, formatter, and error-text mapping.

37. user (2026-07-04T01:34:18.895Z)

Chapter marked: "Upload-size guard implementation". Continue your current work.

38. user (2026-07-04T01:34:23.438Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/api/types.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

39. user (2026-07-04T01:34:33.490Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errors.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

40. assistant (2026-07-04T01:34:35.475Z)

Now the byte formatter in `lib/format.ts`:

41. user (2026-07-04T01:34:40.889Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

42. assistant (2026-07-04T01:34:44.113Z)

Now the `errorText.ts` mapping to localize `fileTooLarge` with size + cap:

43. user (2026-07-04T01:34:48.345Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errorText.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

44. assistant (2026-07-04T01:34:50.702Z)

Now the `useUpload.ts` hook ? thread the cap in and add the size guard:

45. user (2026-07-04T01:34:55.624Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/hooks/useUpload.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

46. user (2026-07-04T01:35:02.317Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/hooks/useUpload.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

47. assistant (2026-07-04T01:35:05.051Z)

Now `IngestPanel.tsx` ? capture `max\_upload\_mb` from capabilities and thread it into `useUpload`:

48. user (2026-07-04T01:35:12.548Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/components/IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

49. user (2026-07-04T01:35:17.333Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/components/IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

50. assistant (2026-07-04T01:35:27.198Z)

Now add `errors.fileTooLarge` to all six locale catalogs, inserting it before `engineGeneric`:

51. user (2026-07-04T01:35:28.808Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

52. user (2026-07-04T01:35:38.048Z)

```
124     "errors": {
125         "networkError": "Can't reach KhelSutra. Is it running?",
126         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
127         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
128         "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
129         "engineGeneric": "Something went wrong. Please try again."
130     },
```

53. assistant (2026-07-04T01:36:03.537Z)

I need to correct the path ? I must edit the **worktree** locale files, not the main-repo

copies. Let me read the worktree locale files' errors regions and edit those.

54. user (2026-07-04T01:36:03.603Z)

```
124     "errors": {
125         "networkError": "KhelSutra ??????????????. ??? ??????????????",
126         "invalidUri": "????? ?????? ?????????? ??????? ? gs:// ?????? KhelSutra
?????????????? ?????? ??.",
127         "emptyResult": "????????? ?????????? ??? ? ??????????? ?????? ?????????? ??????????
????????? ?????? ?????????????? ??????????.",
128         "timeout": "????????????? ?????? ??? ??????????????????????. ???? ?????? ??????????????????
? ?????? ?????????????????? ?????? ????, ???? ?????? ?????????????.",
129         "engineGeneric": "??? ??????????. ?????????? ?????? ???????????"
130     },
```

55. user (2026-07-04T01:36:03.685Z)

```
124     "errors": {
125         "networkError": "KhelSutra ?? ???? ?????? ?? ???? ???? ?? ?? ??? ???",
126         "invalidUri": "????? ?????? ?? ?????? ?????? ? ?? gs:// ???? ?? KhelSutra ??? ??? ????
?? ?? ?????",
127         "emptyResult": "????????????? ?????? ??? ?? ?? ?????? ??? ??? ???? ???? ?????? ?? ???? ???
????????????? ??????????",
128         "timeout": "?? ?????????? ?? ?????? ??? ?? ??? ???? ???? ???? ?? ?? ???? ?? ?????? ?? ? ??????
????? ?? ??? ?????? ?????, ?? ??? ?? ?????? ??????",
129         "engineGeneric": "??? ?????????? ?? ??? ?????? ??? ?? ?????? ??????"
130     },
```

56. user (2026-07-04T01:36:04.298Z)

```
124     "errors": {
125         "networkError": "No se puede conectar con KhelSutra. ¿Está en ejecución?",
126         "invalidUri": "Primero indica la ubicación del video ? un enlace gs:// o una ruta en
la máquina que ejecuta KhelSutra.",
127         "emptyResult": "El procesamiento terminó pero no se encontraron jugadas en este
video. Prueba con una grabación más clara del partido.",
128         "timeout": "Esto está tardando más de lo esperado. El trabajo puede seguir en curso
? recarga con el enlace del video, o reintenta.",
129         "engineGeneric": "Algo salió mal. Inténtalo de nuevo."
130     },
```

57. user (2026-07-04T01:36:05.250Z)

```
124     "errors": {
125         "networkError": "Kan ikke nå KhelSutra. Kører den?",
126         "invalidUri": "Angiv først en videoplacering ? et gs://-link eller en sti på
maskinen, der kører KhelSutra.",
127         "emptyResult": "Behandlingen er færdig, men der blev ikke fundet nogen dueller i
denne video. Prøv en tydeligere kampoptagelse.",
128         "timeout": "Dette tager længere tid end forventet. Jobbet kører måske stadig ?
genindlæs med videolinket, eller prøv igen.",
129         "engineGeneric": "Noget gik galt. Prøv igen."
130     },
```

58. user (2026-07-04T01:36:06.198Z)

```
124     "errors": {
125         "networkError": "Tidak dapat menghubungi KhelSutra. Apakah sedang berjalan?",
126         "invalidUri": "Masukkan lokasi video dulu ? tautan gs:// atau path di mesin yang
menjalankan KhelSutra.",
127         "emptyResult": "Pemrosesan selesai tetapi tidak ada reli yang ditemukan di video
ini. Coba rekaman pertandingan yang lebih jelas.",
128         "timeout": "Ini memakan waktu lebih lama dari perkiraan. Tugas mungkin masih
berjalan ? muat ulang dengan tautan video, atau coba lagi.",
```

```
129         "engineGeneric": "Terjadi kesalahan. Silakan coba lagi."
130     },
```

59. assistant (2026-07-04T01:36:09.872Z)

The worktree copies match. Now let me add `errors.fileTooLarge` to all six worktree catalogs:

60. user (2026-07-04T01:36:12.917Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/en/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

61. user (2026-07-04T01:36:23.137Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/kn/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

62. user (2026-07-04T01:36:26.629Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/hi/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

63. user (2026-07-04T01:36:29.108Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/es/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

64. user (2026-07-04T01:36:32.617Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/da/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

65. user (2026-07-04T01:36:35.194Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/id/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

66. assistant (2026-07-04T01:38:03.728Z)

Now the tests. Let me add coverage for the formatter, the error-text mapping, the hook guard, and the component-level pre-network reject.

67. user (2026-07-04T01:38:05.933Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

68. user (2026-07-04T01:38:13.128Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

69. assistant (2026-07-04T01:38:15.851Z)

Now the `errorText.test.ts` ? add a `fileTooLarge` case (placed before the locale-switching test

so it runs under `en`):

70. user (2026-07-04T01:38:19.558Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errorText.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

71. assistant (2026-07-04T01:38:22.838Z)

Now `useUpload.test.ts` ? pre-network reject guard, plus a within-cap sanity test:

72. user (2026-07-04T01:38:29.232Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/hooks/useUpload.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

73. assistant (2026-07-04T01:38:31.265Z)

Now the component-level test in `upload.test.tsx`:

74. user (2026-07-04T01:38:39.384Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/components/upload.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

75. assistant (2026-07-04T01:38:41.946Z)

All edits are done. Let me verify the web project's scripts, then run the test suite, typecheck, and lint.

76. user (2026-07-04T01:38:42.821Z)

```
1      {
2        "name": "khelsutra-web",
3        "private": true,
4        "version": "0.0.0",
5        "type": "module",
6        "description": "KhelSutra Studio ? operator console SPA (drives the rally indexer
engine).",
7        "scripts": {
8          "dev": "vite",
9          "build": "vite build",
10         "preview": "vite preview",
11         "typecheck": "tsc --noEmit",
12         "test": "vitest run",
13         "test:coverage": "vitest run --coverage",
14         "e2e": "playwright test -c e2e/playwright.config.mjs",
15         "e2e:ci": "vite build && node e2e/contract-smoke.mjs && playwright test -c
e2e/playwright.config.mjs",
16         "screencast": "vite build && playwright test -c e2e/playwright.config.mjs",
17         "screencast:mp4": "node e2e/to-mp4.mjs"
18       },
19       "dependencies": {
20         "@fontsource-variable/noto-sans-devanagari": "^5.2.8",
21         "@fontsource-variable/noto-sans-kannada": "^5.2.9",
22         "i18next": "^26.3.1",
23         "i18next-browser-languagedetector": "^8.2.1",
24         "i18next-icu": "^2.4.3",
25         "react": "^19.0.0",
26         "react-dom": "^19.0.0",
27         "react-i18next": "^17.0.8"
```



```

28     },
29     "devDependencies": {
30         "@playwright/test": "^1.56.0",
31         "@tailwindcss/vite": "^4.0.0",
32         "@testing-library/dom": "^10.4.1",
33         "@testing-library/react": "^16.3.2",
34         "@types/node": "^26.0.0",
35         "@types/react": "^19.0.0",
36         "@types/react-dom": "^19.0.0",
37         "@vitejs/plugin-react": "^4.3.4",
38         "@vitest/coverage-v8": "^3.2.6",
39         "jsdom": "^29.1.1",
40         "tailwindcss": "^4.0.0",
41         "typescript": "^5.7.0",
42         "vite": "^6.0.0",
43         "vitest": "^3.0.0"
44     }
45 }
46

```

77. assistant (2026-07-04T01:38:47.783Z)

No `lint` script in `web`. Let me check for an ESLint config and whether deps are installed, then run tests + typecheck.

78. user (2026-07-04T01:38:51.712Z)

```

node_modules: MISSING
--- eslint configs (web) ---
none in web/
--- repo-root configs ---
.github

```

79. assistant (2026-07-04T01:38:56.612Z)

node_modules is missing (fresh worktree). Let me check the CI workflow to see exactly what "lint" means here, and whether the main-repo `web` has installed deps I can leverage.

80. user (2026-07-04T01:39:00.146Z)

```

=== workflows ===
test.yml
=== grep for web ci steps (eslint/tsc/vitest/lint) ===
.github/workflows/test.yml:32:    # Operator-console SPA (web/): typecheck + unit tests (with a
coverage floor) + production build
.github/workflows/test.yml:47:    - run: npm run typecheck
.github/workflows/test.yml:48:    - run: npm run test:coverage
.github/workflows/test.yml:51:    run: npm run e2e:ci
.github/workflows/test.yml:79:    - run: npm run test:layout
.github/workflows/test.yml:82:    - run: npm run test:render
.github/workflows/test.yml:85:    - run: npm run test:ally
=== main-repo web node_modules? ===
present

```

81. user (2026-07-04T01:39:08.037Z)

```

28     - name: shell scripts parse-check
29       run: for f in scripts/*.sh; do echo "checking $f"; bash -n "$f"; done
30
31     web:
32       # Operator-console SPA (web/): typecheck + unit tests (with a coverage floor) +
production build
33       # + hermetic Playwright CUJs gate the merge. `test:coverage` fails if coverage drops
below the

```

```

34     # thresholds in vite.config.ts, so a merge can't silently regress test coverage.
35     runs-on: ubuntu-latest
36     defaults:
37       run:
38         working-directory: web
39     steps:
40       - uses: actions/checkout@v7
41       - uses: actions/setup-node@v6
42         with:
43           node-version: "24"
44           cache: "npm"
45           cache-dependency-path: web/package-lock.json
46       - run: npm ci
47       - run: npm run typecheck
48       - run: npm run test:coverage
49       - run: npx playwright install --with-deps chromium
50       - name: Playwright CUJs and mock contract smoke
51         run: npm run e2e:ci
52         env:
53           SCREENCAST_DIR: e2e-results
54       - uses: actions/upload-artifact@v5
55         if: failure()
56         with:
57           name: web-playwright-artifacts

```

82. user (2026-07-04T01:39:10.536Z)

Exit code 2
package-lock.json
lock present
23: // Coverage floor (CI runs `npm run test:coverage`): a merge can't DROP coverage below these
27: coverage: {
42: // coverage grows. (functions stays a touch looser: App.tsx is the engine-orchestrating shell,
vite.config.ts

83. assistant (2026-07-04T01:39:15.564Z)

CI is `npm ci` ? `typecheck` ? `test:coverage` (no separate ESLint ? strict `tsc` is the lint gate). Let me check the coverage floor, then install deps.

84. user (2026-07-04T01:39:16.281Z)

```

1     import { defineConfig } from "vitest/config";
2     import react from "@vitejs/plugin-react";
3     import tailwindcss from "@tailwindcss/vite";
4
5     // The SPA makes SAME-ORIGIN relative `/api/*` calls. In the appliance (prod) a reverse
6     // proxy serves the SPA and proxies `/api` to the engine on 127.0.0.1:8000
7     // (docs/LOCAL_APPLIANCE_ARCHITECTURE.md). In dev, Vite proxies `/api` to the local
engine
8     // (`python -m backend.main --server`, :8000). Override with VITE_ENGINE_ORIGIN if
needed.
9     export default defineConfig({
10       plugins: [react(), tailwindcss()],
11       server: {
12         proxy: {
13           "/api": { target: "http://localhost:8000", changeOrigin: true },
14         },
15       },
16       test: {
17         // Default env is node (the pure lib/parser tests); the i18n render test opts into
jsdom via a

```

```

18      // `// @vitest-environment jsdom` docblock. Match .test.tsx too so render tests are
discovered.
19      environment: "node",
20      include: ["src/**/*.test.{ts,tsx}"],
21      // DOM-env localStorage polyfill (jsdom under Node 26 ships none); node-env files
no-op.
22      setupFiles: ["src/test/setup.ts"],
23      // Coverage floor (CI runs `npm run test:coverage`): a merge can't DROP coverage
below these
24      // thresholds, so untested new code is caught. `all` counts every source file (not
only the ones a
25      // test imported), so deleting a test surfaces here too. Excludes are non-logic
files: the app
26      // entry/bootstrap, type-only declarations, and the test harness itself.
27      coverage: {
28        provider: "v8",
29        reporter: ["text", "text-summary"],
30        all: true,
31        include: ["src/**/*.test.{ts,tsx}"],
32        exclude: [
33          "src/**/*.test.{ts,tsx}", // the tests
34          "src/test/**", // jsdom localStorage shim (test harness, not shipped logic)
35          "src/main.tsx", // app entry: mounts <App/> + bundles fonts ? nothing to unit-
test
36          "src/api/types.ts", // type-only declarations (no runtime code)
37          "src/annotator/**", // VENDORED from rally-annotator (MIT) ? fully tested
upstream; a smoke test guards the copy
38          "**/*.d.ts",
39        ],
40        // Floor set just below current (stmts/lines 93.3, branches 88.1, funcs 85.9) ? a
real ratchet
41        // that fails CI on a meaningful drop, with a little slack so it doesn't flap.
Ratchet upward as
42        // coverage grows. (functions stays a touch looser: App.tsx is the engine-
orchestrating shell,
43        // costly to exercise fully in unit tests.)
44        thresholds: {
45          statements: 92,
46          branches: 87,
47          functions: 84,
48          lines: 92,
49        },
50      },
51    },
52  });
53

```

85. assistant (2026-07-04T01:39:28.979Z)

Coverage floor is 92/87/84/92 ? my additions are all tested (formatter, error-text branch, hook guard, both branches of the capabilities parse), so no regression. Let me install deps in the worktree and run the checks.

86. user (2026-07-04T01:39:42.762Z)

npm warn deprecated glob@10.5.0: Old versions of glob are not supported, and contain widely publicized security vulnerabilities, which have been fixed in the current version. Please update. Support for old versions may be purchased (at exorbitant rates) by contacting i@izs.me

added 241 packages, and audited 242 packages in 9s

50 packages are looking for funding
run `npm fund` for details

found 0 vulnerabilities

87. assistant (2026-07-04T01:39:44.892Z)

Deps installed. Now typecheck and the full coverage test run:

88. user (2026-07-04T01:39:52.437Z)

```
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
```

89. assistant (2026-07-04T01:39:54.367Z)

Typecheck clean. Now the full test suite with coverage (the CI gate):

90. user (2026-07-04T01:40:12.409Z)

```
{ "ts": "2026-07-04T01:40:11.566Z", "level": "info", "event": "ingest.queued", "cid": "e9b5c4a4-305f-4c0b-846e-742988232518", "uri": "gs://bucket/live-match.mp4", "job_id": "j-active" }
{ "ts": "2026-07-04T01:40:11.566Z", "level": "info", "event": "ingest.poll_start", "cid": "e9b5c4a4-305f-4c0b-846e-742988232518", "uri": "gs://bucket/live-match.mp4", "job_id": "j-active" }
```

```
stdout | src/App.ingest.test.tsx > App ingest handoff >
replaces demo rally controls while a real ingest job is active, then restores them on
cancel
{ "ts": "2026-07-04T01:40:11.616Z", "level": "info", "event": "upload.cancel" }
{ "ts": "2026-07-04T01:40:11.618Z", "level": "info", "event": "ingest.cancel", "job_id": "j-active" }
```

```
? src/App.ingest.test.tsx (1 test)
591ms
? App ingest handoff > replaces demo rally controls while a real
ingest job is active, then restores them on cancel 589ms
```

Test Files 30 passed (30)
Tests 290 passed (290)
Start at 07:09:58
Duration 13.45s (transform 3.55s, setup 912ms, collect 24.26s, tests 19.21s, environment 71.74s, prepare 11.71s)

% Coverage report from v8

File	% Stmts	% Branch	% Funcs	% Lines	Uncovered Line #s
All files	94.73	87.85	89.65	94.73	
src	74.08	77.77	27.77	74.08	
App.tsx	74.08	77.77	27.77	74.08	...27-344,401-403
src/api	94.22	87.3	100	94.22	
client.ts	94.22	87.3	100	94.22	211-220,276-278
src/components	98.87	90.7	96.42	98.87	
...tatePanel.tsx	100	88.88	92.3	100	39,52,55-56
...ileResult.tsx	100	95.12	100	100	28,53
FfmpegBanner.tsx	100	90.9	100	100	24
IngestPanel.tsx	97.33	91.08	100	97.33	46-47,380-387
...eSwitcher.tsx	100	83.33	100	100	27
QueryBar.tsx	100	88.88	100	100	30
RallyGrid.tsx	98.11	73.33	50	98.11	42
...ionFooter.tsx	100	100	100	100	
SetupWizard.tsx	97.93	91.3	100	97.93	18-19,112
StatusChip.tsx	100	100	100	100	
TapFilters.tsx	100	100	100	100	
VideoLibrary.tsx	100	89.47	100	100	33,82
src/hooks	97.49	81.33	100	97.49	
useIngestJob.ts	96.61	81.81	100	96.61	...93,108,193-195
...ySelection.ts	100	83.33	100	100	9
useUpload.ts	100	78.26	100	100	68-69,73,78

src/i18n		100		25		100		100		
index.ts		100		25		100		100		72-76
src/lib		97.59		93.2		100		97.59		
errorText.ts		100		77.77		100		100		17
errors.ts		100		93.1		100		100		8,15
floor.ts		100		100		100		100		
format.ts		100		100		100		100		
log.ts		81.81		88.88		100		81.81		13-14
query.ts		97.07		93.45		100		97.07		...95,284,286,288
selection.ts		100		92.3		100		100		30
video.ts		100		93.33		100		100		21
-----		-----		-----		-----		-----		-----

```

===== Coverage summary =====
Statements   : 94.73% ( 2284/2411 )
Branches     : 87.85% ( 709/807 )
Functions    : 89.65% ( 130/145 )
Lines        : 94.73% ( 2284/2411 )
=====

```

91. assistant (2026-07-04T01:41:10.392Z)

All 290 tests pass; coverage clears every threshold (stmts 94.73/92, branches 87.85/87, funcs 89.65/84, lines 94.73/92). The i18n key/placeholder parity and catalog-invariant tests are in that green suite, confirming my locale additions are clean.

One small polish: `errorText.ts` has an uncovered defensive branch (the `?? 0` fallbacks). Let me cover it with a test of the malformed-error path ? legitimate and it keeps branch coverage from dipping:

92. user (2026-07-04T01:41:14.667Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errorText.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

93. user (2026-07-04T01:41:32.008Z)

floor.ts		100		100		100		100		
format.ts		100		100		100		100		
log.ts		81.81		88.88		100		81.81		13-14
query.ts		97.07		93.45		100		97.07		...95,284,286,288
selection.ts		100		92.3		100		100		30
video.ts		100		93.33		100		100		21
-----		-----		-----		-----		-----		-----

```

===== Coverage summary =====
Statements   : 94.73% ( 2284/2411 )
Branches     : 88.08% ( 710/806 )
Functions    : 89.65% ( 130/145 )
Lines        : 94.73% ( 2284/2411 )
=====

```

94. assistant (2026-07-04T01:41:40.547Z)

Branches recovered to 88.08% (up from 87.85), now matching the base and comfortably above the floor. Let me confirm the full pass/fail summary explicitly:

95. user (2026-07-04T01:41:56.156Z)

```

{"ts":"2026-07-04T01:41:51.145Z","level":"warn","event":"upload.aborting_partial","cid":"353f6aed-09e2-4a7d-8819-341505154920","upload_id":"up1","error":"ApiError: PUT /api/upload/up1/part/0 failed: 413"}
{"ts":"2026-07-

```

```

04T01:41:51.146Z", "level": "error", "event": "upload.failed", "cid": "353f6aed-09e2-4a7d-8819-341505154920", "filename": "match.mp4", "error": "ApiError: PUT /api/upload/up1/part/0 failed: 413"}
{"ts": "2026-07-
04T01:41:51.351Z", "level": "warn", "event": "library.load_failed", "cid": "c393642c-6b22-40d7-a7b8-ed26a66355e5", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-
04T01:41:51.715Z", "level": "error", "event": "annotate.persist_failed", "cid": "1a2bc4e4-a9ed-4e63-987b-a3cdcd88fa8", "video_id": "vid1", "error": "ApiError: POST /api/annotations failed: 500"}
{"ts": "2026-07-
04T01:41:51.751Z", "level": "error", "event": "annotate.retry_failed", "cid": "5fdcaad1-91df-4c61-8c60-3213bff53d84", "video_id": "vid1", "error": "ApiError: POST /api/annotations failed: 500"}
stdout | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
stdout | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
stdout | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
stdout | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
stdout | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
stderr | src/components/IngestPanel.test.tsx > IngestPanel >
shows a failed pipeline verdict as the engine's reason, not as no rallies
{"ts": "2026-07-
04T01:41:52.787Z", "level": "error", "event": "ingest.pipeline_failed", "cid": "8e87895e-acc0-4e7d-a3aa-29acbf49df79", "uri": "gs://bucket/blurry.mp4", "job_id": "jFail", "code": "engine", "detail": "Video failed validation: blur: blurry"}
{"ts": "2026-07-
04T01:41:52.066Z", "level": "warn", "event": "video.name_resolve_failed", "video_id": "vidX", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-
04T01:41:52.068Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: GET /api/config failed: 500"}
{"ts": "2026-07-04T01:41:52.219Z", "level": "warn", "event": "library.load_failed", "cid": "ff77edc1-5618-419a-8d37-c616fd4d39b5", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-
04T01:41:52.301Z", "level": "error", "event": "build.failed", "cid": "26b5d633-2031-4249-9340-4abf0c281c33", "video_id": "vidX", "filename": "highlights.mp4", "code": "networkError", "error": "ApiError: Network error calling POST /api/compile"}
{"ts": "2026-07-04T01:41:52.335Z", "level": "warn", "event": "library.load_failed", "cid": "aca61533-84b0-4631-8613-e144d297b900", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-04T01:41:52.509Z", "level": "warn", "event": "library.load_failed", "cid": "44926b5f-0c3f-432d-ade8-ef35f5b4880f", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-
04T01:41:52.527Z", "level": "warn", "event": "video.name_resolve_failed", "video_id": "vidX", "error": "ApiError: Network error calling GET /api/videos"}
{"ts": "2026-07-
04T01:41:52.528Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: GET /api/config failed: 500"}

```

96. assistant (2026-07-04T01:42:00.069Z)

Those are expected structured-log lines from error-path tests, not failures. Let me grab just the summary lines:

97. user (2026-07-04T01:42:16.320Z)

Test Files 30 passed (30)

98. user (2026-07-04T01:42:32.724Z)

```

stdout | src/hooks/useIngestJob.test.ts > useIngestJob >
surfaces a done-but-failed pipeline verdict with the engine message ? never as no

```

```
rallies
stdout | src/hooks/useIngestJob.test.ts > useIngestJob >
surfaces a done-but-failed pipeline verdict with the engine message ? never as no
rallies
stderr | src/hooks/useIngestJob.test.ts > useIngestJob >
surfaces a done-but-failed pipeline verdict with the engine message ? never as no
rallies
{"ts":"2026-07-04T01:42:33.390Z","level":"error","event":"ingest.pipeline_failed","cid":"936cab96-9a1c-4890-b588-c5d6b335434d","uri":"gs://b/x.mp4","job_id":"j2","code":"engine","detail":"Video failed validation: blur: blurry"}
{"ts":"2026-07-04T01:42:33.396Z","level":"error","event":"ingest.job_failed","cid":"7d7fffc2-d400-4ea5-baa2-0ad736f1600a","uri":"gs://b/x.mp4","job_id":"j3","code":"engine","detail":"RuntimeError: boom"}
Duration 9.67s (transform 2.91s, setup 878ms, collect 19.07s, tests 14.01s,
environment 57.13s, prepare 9.42s)
```

99. user (2026-07-04T01:42:53.782Z)

```
Test Files 30 passed (30)
Tests 291 passed (291)
```

100. assistant (2026-07-04T01:43:07.427Z)

All 291 tests pass (+8 new), typecheck clean, coverage above floor and non-regressing. There's no ESLint in this repo ? the SPA's lint gate in CI is strict `tsc --noEmit`, which passes. Let me review the complete diff and confirm no stray changes leaked into the main-repo checkout.

101. user (2026-07-04T01:43:10.799Z)

=== WORKTREE status ===

```
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M web/src/api/types.ts
M web/src/components/IngestPanel.tsx
M web/src/components/upload.test.tsx
M web/src/hooks/useUpload.test.ts
M web/src/hooks/useUpload.ts
M web/src/lib/errorText.test.ts
M web/src/lib/errorText.ts
M web/src/lib/errors.ts
M web/src/lib/format.test.ts
M web/src/lib/format.ts
```

=== files changed ===

locales/da/common.json	1 +
locales/en/common.json	1 +
locales/es/common.json	1 +
locales/hi/common.json	1 +
locales/id/common.json	1 +
locales/kn/common.json	1 +
web/src/api/types.ts	5 +++++
web/src/components/IngestPanel.tsx	8 ++++++-
web/src/components/upload.test.tsx	26 ++++++
web/src/hooks/useUpload.test.ts	28 ++++++
web/src/hooks/useUpload.ts	14 ++++++-
web/src/lib/errorText.test.ts	15 ++++++
web/src/lib/errorText.ts	5 +++++
web/src/lib/errors.ts	9 +++++--
web/src/lib/format.test.ts	19 ++++++-

```
web/src/lib/format.ts | 13 ++++++++
16 files changed, 143 insertions(+), 5 deletions(-)
```

=== MAIN REPO status (should be clean ? no leaked edits) ===

102. assistant (2026-07-04T01:43:18.392Z)

Main repo is clean ? no leaked edits. All 16 changed files are intentional and contained to the worktree. Let me do a final review of the core source diff:

103. user (2026-07-04T01:43:20.402Z)

```
diff --git a/web/src/api/types.ts b/web/src/api/types.ts
index 586aa14..71d7c09 100644
--- a/web/src/api/types.ts
+++ b/web/src/api/types.ts
@@ -99,6 +99,11 @@ export interface EngineCapabilities {
  /** Whether a Gemini key is PRESENT (never its value) ? drives the AI-highlights step. */
  gemini_key_present?: boolean;
  wasb_weights_present?: boolean;
+ /** The largest upload THIS box accepts, in MB (engine `security.max_upload_mb`, default
+ 4096).
+  * /upload/init already 413s an oversized file BEFORE any part transfers; the SPA consumes
+  this to
+  * reject it INSTANTLY client-side (no wasted round-trip). Absent on older engines ? the
+  guard is
+  * skipped and the engine's server-side fail-fast still applies. */
+  max_upload_mb?: number;
  /** `cloud_available` = can THIS server satisfy a per-request compute="cloud" dispatch (a
  Cloud Run
    * GPU Job)? The ingest compute-picker shows the "in the cloud" option only when true. */
  deployment?: { profile?: string; compute_target?: string; cloud_available?: boolean };
diff --git a/web/src/components/IngestPanel.tsx b/web/src/components/IngestPanel.tsx
index 0c12f17..3d5afd0 100644
--- a/web/src/components/IngestPanel.tsx
+++ b/web/src/components/IngestPanel.tsx
@@ -68,6 +68,9 @@ export function IngestPanel({ onLoaded, onBusyChange }: Props) {
  const [mediumUri, setMediumUri] = useState("");
  const [storing, setStoring] = useState(false);
  const [storeError, setStoreError] = useState<IngestError | null>(null);
+ // The engine's max upload size (BYTES), so an oversized file fails INSTANTLY client-side
+ instead of
+ // uploading into a 413. Absent ? undefined ? no guard (the engine still fail-fasts).
+ const [maxUploadBytes, setMaxUploadBytes] = useState<number | undefined>(undefined);
  useEffect(() => {
    let alive = true;
    getCapabilities()
@@ -75,6 +78,9 @@ export function IngestPanel({ onLoaded, onBusyChange }: Props) {
    if (!alive) return;
    setCloudAvailable(c.deployment?.cloud_available === true);
    setBackends(c.storage?.backends ?? []);
+    setMaxUploadBytes(
+      typeof c.max_upload_mb === "number" && c.max_upload_mb > 0 ? c.max_upload_mb * 1024 *
+ 1024 : undefined,
+    );
  });
  .catch((err) => log("warn", "capabilities.unavailable", { error: String(err) }));
  return () => {
@@ -122,7 +128,7 @@ export function IngestPanel({ onLoaded, onBusyChange }: Props) {
  const upload = useUpload((path, filename) => {
    if (medium === "local") submit(path, locale, sendCompute, filename);
    else void storeThenProcess({ uploadedPath: path }, filename);
-  });
+ }, maxUploadBytes);
  const busy = ingestBusy || upload.busy || storing;
```



```

    useEffect(() => {
      onBusyChange?.(busy);
diff --git a/web/src/hooks/useUpload.ts b/web/src/hooks/useUpload.ts
index af127c4..68660cf 100644
--- a/web/src/hooks/useUpload.ts
+++ b/web/src/hooks/useUpload.ts
@@ -17,12 +17,16 @@ export type UploadPhase =
  | { status: "uploading"; pct: number; filename: string }
  | { status: "error"; error: IngestError };

-export function useUpload(onComplete: (path: string, filename: string) => void) {
+export function useUpload(onComplete: (path: string, filename: string) => void,
+maxUploadBytes?: number) {
  const [phase, setPhase] = useState<UploadPhase>({ status: "idle" });
  const ctrlRef = useRef<AbortController | null>(null);
  // Keep the latest onComplete without making start depend on it (a parent re-render won't
  restart).
  const onCompleteRef = useRef(onComplete);
  onCompleteRef.current = onComplete;
+ // The engine's max upload size (BYTES) from GET /api/capabilities ? read through a ref so
+ `start`
+ // stays stable when the capability loads (same pattern as onCompleteRef). Absent/0 ? no
+ client guard.
+ const maxUploadBytesRef = useRef(maxUploadBytes);
+ maxUploadBytesRef.current = maxUploadBytes;

  const stop = useCallback(() => {
    ctrlRef.current?.abort();
@@ -39,6 +43,14 @@ export function useUpload(onComplete: (path: string, filename: string) =>
void)
    setPhase({ status: "error", error: { code: "invalidUri" } });
    return;
  }
+ // Oversized file: fail INSTANTLY (no wasted round-trip) ? /upload/init would 413 anyway.
+ Carry
+ // the size + cap so IngestPanel can localize a "trim/chunk it first" message. No cap ?
+ skip the
+ // guard (the engine still fail-fasts server-side).
+ const cap = maxUploadBytesRef.current;
+ if (cap && file.size > cap) {
+   setPhase({ status: "error", error: { code: "fileTooLarge", sizeBytes: file.size,
+ capBytes: cap } });
+   return;
+ }

  stop(); // supersede any prior upload
  const ctrl = new AbortController();
diff --git a/web/src/lib/errorText.ts b/web/src/lib/errorText.ts
index 2f556e6..e520a29 100644
--- a/web/src/lib/errorText.ts
+++ b/web/src/lib/errorText.ts
@@ -7,8 +7,13 @@
// errors.ts so that module stays i18n-free and unit-testable without a translation context.
import type { TFunction } from "i18next";
import type { IngestError } from "../errors";
+import { formatFileSize } from "../format";

export function errorText(t: TFunction, e: IngestError): string {
  if (e.code === "engine") return e.detail ?? t("errors.engineGeneric");
+ // The client-side upload-size guard shows BOTH the file size and the cap, plus a "trim/chunk
+ it
+ // first" hint (the code carries them in bytes; format them here at the view layer).
+ if (e.code === "fileTooLarge")
+   return t("errors.fileTooLarge", { size: formatFileSize(e.sizeBytes ?? 0), cap:
+ formatFileSize(e.capBytes ?? 0) });

```

```

    return t(`errors.${e.code}`);
  }
diff --git a/web/src/lib/errors.ts b/web/src/lib/errors.ts
index 156de45..3b63fa5 100644
--- a/web/src/lib/errors.ts
+++ b/web/src/lib/errors.ts
@@ -29,13 +29,18 @@ export function parseDetail(body: string): string {
}

/** Stable, localizable failure categories surfaced by the ingest flow.
- * `engine` carries the engine's own message in `detail`; the rest are localized by code. */
-export type IngestErrorCode = "invalidUri" | "networkError" | "emptyResult" | "timeout" |
"engine";
+ * `engine` carries the engine's own message in `detail`; the rest are localized by code.
+ * `fileTooLarge` is the client-side upload-size guard (rejected pre-network, carries size +
+ cap). */
+export type IngestErrorCode = "invalidUri" | "networkError" | "emptyResult" | "timeout" |
"fileTooLarge" | "engine";

export interface IngestError {
  code: IngestErrorCode;
  /** Present for `engine` ? the verbatim FastAPI detail / status; rendered as-is, not
translated. */
  detail?: string;
+ /** Present for `fileTooLarge` ? the picked file's size and the engine's cap, both in BYTES,
+ so the
+ * localized message can show both ("This clip is 5.8 GB, over the 4 GB upload limit?"). */
+ sizeBytes?: number;
+ capBytes?: number;
}

/** Classify a thrown client error into a stable code. A network throw (ApiError with no
`status`)
diff --git a/web/src/lib/format.ts b/web/src/lib/format.ts
index ff74437..84e9b53 100644
--- a/web/src/lib/format.ts
+++ b/web/src/lib/format.ts
@@ -12,6 +12,19 @@ export function pluralize(n: number, one: string, many = one + "s"): string {
  return `${n} ${n === 1 ? one : many}`;
}

+/** Bytes ? a short human size for user copy (the upload size-guard message). ? 1 GB renders as
+GB
+ * with up to one decimal, trailing ".0" trimmed ("4 GB", "5.8 GB"); smaller renders as whole
+MB
+ * ("512 MB"). Clamps negatives/NaN to 0 and never returns below "1 MB" for a positive size.
+ */
+export function formatFileSize(bytes: number): string {
+  const b = Math.max(0, Number.isFinite(bytes) ? bytes : 0);
+  const gb = b / 1024 ** 3;
+  if (gb >= 1) {
+    const rounded = Math.round(gb * 10) / 10;
+    return `${Number.isInteger(rounded) ? rounded : rounded.toFixed(1)} GB`;
+  }
+  return `${Math.max(1, Math.round(b / 1024 ** 2))} MB`;
+}
+
+/** Turn a user reel name into a safe bare `.mp4` filename for POST /api/compile. The engine's
+ * `safe_output_filename` (backend/utils/paths.py) rejects path separators / traversal /
absolute
+ * names, so we slugify to [a-z0-9-] and always end in `.mp4`. Empty ? "highlights.mp4". */

```

104. assistant (2026-07-04T01:43:45.749Z)

The full diff is clean and correct, main repo untouched. Let me check the remote/branch

situation before deciding on committing and opening a PR.

105. user (2026-07-04T01:43:49.242Z)

```
=== remotes ===
origin https://github.com/avidullu/khelsutra.git (fetch)
origin https://github.com/avidullu/khelsutra.git (push)
=== branch/HEAD ===
claude/zealous-pike-7d0a85
b0f70a5 Show failed ingest verdict reasons
=== base master ref ===
b0f70a5 Show failed ingest verdict reasons
```

106. assistant (2026-07-04T01:44:14.141Z)

There's an origin remote, and my worktree branch `claude/zealous-pike-7d0a85` sits cleanly on `b0f70a5` (= master) with no sibling commits. The task is framed around opening a PR after the checks pass, so I'll commit my explicit paths, push, and open the PR. Let me stage precisely (no `-A`) and commit:

107. user (2026-07-04T01:44:18.250Z)

```
=== branch re-verify ===
claude/zealous-pike-7d0a85
b0f70a5 Show failed ingest verdict reasons
=== origin/master ===
b0f70a5 Show failed ingest verdict reasons
```

108. assistant (2026-07-04T01:44:21.953Z)

origin/master is also at `b0f70a5` ? no divergence, clean base. Staging explicit paths and committing:

109. user (2026-07-04T01:44:25.850Z)

```
=== staged ===
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
web/src/api/types.ts
web/src/components/IngestPanel.tsx
web/src/components/upload.test.tsx
web/src/hooks/useUpload.test.ts
web/src/hooks/useUpload.ts
web/src/lib/errorText.test.ts
web/src/lib/errorText.ts
web/src/lib/errors.ts
web/src/lib/format.test.ts
web/src/lib/format.ts
```

110. user (2026-07-04T01:44:37.149Z)

```
[claude/zealous-pike-7d0a85 0969059] Guard oversized uploads client-side in the ingest SPA
 16 files changed, 143 insertions(+), 5 deletions(-)
=== committed ===
0969059 Guard oversized uploads client-side in the ingest SPA
```

111. assistant (2026-07-04T01:44:39.698Z)

`origin/master..HEAD` lists only my single commit ? no sibling work absorbed. Now push and open the PR:

112. user (2026-07-04T01:44:43.915Z)

```
remote:
remote: Create a pull request for 'claude/zealous-pike-7d0a85' on GitHub by visiting:
remote:   https://github.com/avidullu/khelsutra/pull/new/claude/zealous-pike-7d0a85
remote:
branch 'claude/zealous-pike-7d0a85' set up to track 'origin/claude/zealous-pike-7d0a85'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      claude/zealous-pike-7d0a85 -> claude/zealous-pike-7d0a85
```

113. user (2026-07-04T01:45:06.381Z)

<https://github.com/avidullu/khelsutra/pull/153>

114. assistant (2026-07-04T01:45:24.118Z)

PR opened: **<https://github.com/avidullu/khelsutra/pull/153>**

Let me check whether a session handoff exists for this project to keep it current (per the handoff convention):

115. user (2026-07-04T01:45:26.787Z)

no memory dir / MEMORY.md for this project

116. assistant (2026-07-04T01:45:48.118Z)

No existing memory/handoff for this project ? nothing to update, and a single self-contained PR is fully recorded in git, so I won't add memory noise.

Done ? PR #153

Added a client-side upload-size guard to the ingest SPA: an oversized file now fails **instantly**, before any network round-trip, with a size-specific, localized message + a "trim/chunk it first" hint ? replacing the old "uploading" ? generic engine-error flip.

? **<https://github.com/avidullu/khelsutra/pull/153>**

What changed (web/src/)

```
| File | Change |
|---|---|
| [api/types.ts](web/src/api/types.ts) | `max_upload_mb` added to `EngineCapabilities` |
| [lib/errors.ts](web/src/lib/errors.ts) | new `fileTooLarge` `IngestErrorCode` carrying `sizeBytes` + `capBytes` (bytes) |
| [lib/format.ts](web/src/lib/format.ts) | `formatFileSize` ? `5.8 GB` / `512 MB` |
| [hooks/useUpload.ts](web/src/hooks/useUpload.ts) | size guard right after the 0-byte reject; no network when it fires; cap threaded in via a param (held in a ref so `start` stays stable); stays i18n-free (returns the code) |
| [components/IngestPanel.tsx](web/src/components/IngestPanel.tsx) | reads the cap from capabilities, threads it into `useUpload`; existing `errorText` maps the code ? localized string |
| 6 locale catalogs | `errors.fileTooLarge` in en/kn/hi/es/da/id, referencing `scripts/chunk_video.py` + the Google Drive path |
```

Example (en): **"This clip is 5.8 GB, over the 4 GB upload limit. Trim it to a shorter highlight first ? see scripts/chunk_video.py (or use the Google Drive path)."**

Design notes

- I put the code?prose mapping in `errorText.ts` (the shared "one place a classified error becomes user-facing text"), which `IngestPanel` already calls ? so the hook stays i18n-free per its contract and the message interpolates size + cap at the view layer.
- Guard is opt-in on the cap: absent/0 `max\_upload\_mb` ? guard skipped, and the engine's server-side 413 fail-fast still applies.

Verification

- **typescript**: clean (`tsc --noEmit`)
- **tests**: **291 passed** (30 files) ? includes hook pre-network reject + within-cap upload, `errorText` formatting, `formatFileSize`, and a component-level 5 GB-vs-4 GB reject asserting no upload/process call
- **coverage**: 94.73% stmts / 88.08% branches / 89.65% funcs / 94.73% lines ? above the CI floor (92/87/84/92), branches non-regressing; key/placeholder-parity + catalog-invariant i18n guards green
- **lint**: this repo has no ESLint ? the SPA's CI lint gate is strict `tsc`, which passes

I verified behavior through the automated suite (the component test renders the real `IngestPanel` with the real i18n catalog) rather than a browser preview ? meaningfully exercising it live would need a running engine that reports `max\_upload\_mb` plus picking a >4 GB file, which the tests cover deterministically instead.

Two things worth flagging: I depended only on `max\_upload\_mb`, so this PR assumes the companion engine change that exposes it in `/api/capabilities` lands; and I caught early that a stray path had me editing the main-repo checkout instead of the worktree ? corrected, and confirmed the main repo is clean with all changes contained to the branch.

117. user (2026-07-04T01:45:50.413Z)

In the fix, please also identify some way to help the user trim the video if he doesnt already know

118. assistant (2026-07-04T01:46:51.585Z)

The current message points at `scripts/chunk\_video.py` and "the Google Drive path" ? fine for a developer, useless for a badminton coach who's never trimmed a video. And this SPA must work **air-gapped** (the hygiene tests forbid external links/CDN), so I can't just link out to a how-to article ? the guidance has to be **inline**. Let me scout the exact rendering/i18n constraints before designing.

119. user (2026-07-04T01:46:54.260Z)

```
web\src\App.tsx:305:      <Trans i18nKey="app.intro" components={{ b: <strong />, i: <em />
}} />
web\src\App.tsx:317:      <Trans
web\src\App.tsx:417:      <Trans i18nKey="mode.demo" components={{ code: <code /> }} />
web\src\App.tsx:424:      <Trans i18nKey="mode.loading" values={{ videoId }} components={{
code: <code /> }} />
web\src\App.tsx:431:      <Trans i18nKey="mode.error" values={{ videoId, error: load.error }}
components={{ code: <code /> }} />
web\src\App.tsx:437:      <Trans i18nKey="mode.loaded" values={{ count: load.count }}
components={{ b: <strong className="text-ink/70" /> }} />
web\src\i18n\i18n.test.tsx:35:    expect(container.textContent).toContain("rally length"); //
<Trans> hero intro + query support
web\src\components\QueryBar.tsx:110:      <Trans i18nKey="query.support" components={{ b:
<strong className="text-ink/60" />, x: <span className="text-amber-700" /> }} />
web\src\components\SelectionFooter.tsx:40:      <Trans i18nKey="footer.floorOne"
values={{ min: warning.minShotCount }} components={{ b: <strong /> }} />
web\src\components\SelectionFooter.tsx:42:      <Trans i18nKey="footer.floorAll"
values={{ count, min: warning.minShotCount }} components={{ b: <strong /> }} />
web\src\components\SelectionFooter.tsx:47:      <Trans i18nKey="footer.floorSomeRest"
values={{ min: warning.minShotCount }} components={{ code: <code /> }} />
```

120. user (2026-07-04T01:46:55.793Z)

Found 13 files

```
web\src\components\IngestPanel.tsx
web\src\i18n\i18n.test.tsx
web\src\components\VideoLibrary.tsx
web\src\components\TapFilters.tsx
web\src\components\SetupWizard.tsx
```

web\src\components\SelectionFooter.tsx
web\src\components\RallyGrid.tsx
web\src\components\QueryBar.tsx
web\src\components\LanguageSwitcher.tsx
web\src\components\FfmpegBanner.tsx
web\src\components\CompileResult.tsx
web\src\components\AnnotatePanel.tsx
web\src\App.tsx

121. user (2026-07-04T01:46:56.332Z)

No files found

122. user (2026-07-04T01:46:56.380Z)

No files found

123. assistant (2026-07-04T01:49:43.833Z)

Two constraints locked from scouting: (1) the SPA renders formatted strings via `` lead-ins), and (2) `**scripts/chunk_video.py` doesn't exist in this repo**` (it's in the engine repo) and the app must run `**air-gapped**` ? so the help has to be inline, non-technical steps, with the Python script demoted to an "advanced" line rather than the headline.

Design decision: refine the top-line message to be coach-friendly, and add a collapsible `***How do I trim it?***` disclosure with concrete phone/computer steps (keeping `scripts/chunk_video.py` + Google Drive as the advanced option`). Since this touches 6 locales including Kannada/Hindi (with ICU/jargon/parity pitfalls), I'll orchestrate the copy vetting + translation + adversarial hygiene verification as a workflow, then implement and test.

124. user (2026-07-04T01:50:34.941Z)

Workflow launched in background. Task ID: wrk6l0s5w
Summary: Vet + translate the "how to trim your video" upload-guard help copy across 6 locales
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-
pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c\subagents\workflows\wf_62eafba6-2ec
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-
pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c\workflows\scripts\trim-help-i18n-wf_62eafba6-2ec.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c\workflows\scripts\trim-help-i18n-wf_62eafba6-2ec.js"} to iterate without resending the script.)
Run ID: wf_62eafba6-2ec
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c\workflows\scripts\trim-help-i18n-wf_62eafba6-2ec.js", resumeFromRunId: "wf_62eafba6-2ec"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

125. assistant (2026-07-04T01:50:53.019Z)

While the workflow runs, let me make the copy-independent structural change to `IngestPanel.tsx` (the keys are fixed regardless of final wording). First the Trans` import:`

126. user (2026-07-04T01:50:54.235Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-
pike-7d0a85/web/src/components/IngestPanel.tsx has been updated successfully. (file state is

current in your context ? no need to Read it back)

127. user (2026-07-04T01:51:05.806Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/components/IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

128. assistant (2026-07-04T01:51:22.234Z)

The structural change is in. Let me typecheck it early (tsc doesn't validate i18n keys against the catalog, so it'll pass before the strings land) to catch any TSX error in the new block:

129. user (2026-07-04T01:51:29.829Z)

```
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
```

130. assistant (2026-07-04T01:51:40.581Z)

Structural change compiles cleanly. The translation/copy workflow is running in the background (design panel ? 5-locale translation ? adversarial hygiene verification). I've already wired up `IngestPanel.tsx`:

- Refined the top-line `fileTooLarge` message to be coach-friendly (dev references demoted).
- Added a keyboard-accessible `***How do I trim it?***` `<details>` disclosure in the error card, rendering inline phone/computer/advanced steps via <Trans> ? no external links, so it works air-gapped.`

`**Why this shape:**` a badminton coach who hit a 4 GB limit needs `*actionable*` help, not a Python script path. The disclosure gives the two things almost any coach can actually do (trim on their phone's Photos/Gallery, or in Windows Photos / Mac QuickTime), and keeps ``scripts/chunk_video.py`` + the Google Drive route as an "Advanced" line for whoever runs the box.

I'll finish once the workflow returns the vetted copy + verified translations: drop the 6-locale strings into the catalogs, update the error-text/component tests, run the full suite + typecheck, and push to the PR. Waiting on the workflow now.

131. user (2026-07-04T01:56:22.267Z)

```
<task-notification>
<task-id>wrk6l0s5w</task-id>
<tool-use-id>toolu_01RTjbX4kr7sgawQNsxpjCgM</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra-guru-
khelsutra--claude-worktrees-zealous-
pike-7d0a85\b8be946b-bd13-4912-b478-1b1923b9478c\tasks\wrk6l0s5w.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "Vet + translate the "how to trim your video" upload-guard help copy
across 6 locales" completed</summary>
<result>{"en":{"message_en":"This clip is {size}, just over the {cap} upload limit, so trim it
to your best rally or two and upload that shorter version.", "summary_en":"No worries, trimming
takes about a minute, here's how.", "phone_en":"&lt;b&gt;On a phone:&lt;/b&gt; open the clip in
your Photos or Gallery app, drag the two handles at the ends of the video to keep just the rally
you want, then save and upload that shorter clip.", "computer_en":"&lt;b&gt;On a
computer:&lt;/b&gt; open the clip in the Photos app on Windows or QuickTime Player on Mac, drag
the ends inward to keep only the part you want, then save the shorter clip and upload
it.", "advanced_en":"&lt;b&gt;Advanced:&lt;/b&gt; if you'd rather keep the full match, whoever
runs the setup can split it into smaller parts with scripts/chunk_video.py, or upload the whole
video to Google Drive instead.", "rationale":"Message: took Proposal 1/3's warm \"just over the
{cap} upload limit\" framing (softens the rejection to a small step) and Proposal 1's badminton-
concrete \"your best rally or two,\" ending with the clear action \"upload that shorter
version.\" Both required placeholders {size} and {cap} are kept verbatim with no other braces;
help strings carry no placeholders. Summary: chose Proposal 1's reassuring \"No worries,
```

trimming takes about a minute, here's how.\" over the plainer \"How do I trim it?\" because it lowers anxiety for a coach who has never trimmed a video while still labeling the collapsible help. Phone: Proposal 1's \"drag the two handles at the ends of the video\" is the clearest first-timer gesture, plus \"save and upload that shorter clip\" for the full follow-through; kept \"Photos or Gallery\" and the badminton \"rally.\" Computer: Proposal 1's \"drag the ends inward to keep only the part you want, then save the shorter clip and upload it\" ? the most beginner-proof physical description; correctly names Photos on Windows and QuickTime Player on Mac (both genuinely trim natively), and avoids VLC. I deliberately dropped Proposal 2's literal \"Edit then Trim\" menu path to keep it to one simple gesture and avoid overloading a novice. Advanced: merged Proposal 1's friendly \"if you'd rather keep the full match\" reframe with Proposal 3's \"whoever runs the setup\" signal that this path isn't for the coach; preserves both required deliverables verbatim ? scripts/chunk_video.py (plain text) and the Google Drive fallback. All lines are single sentences, air-gapped (no URLs or \"search online\"), use only the permitted lead-in label, and keep every product name verbatim.\"},\"locales\":{\"code\":\"kn\",\"ok\":true,\"issues\":[\"Orthography (quality, not a linter-enumerated rule): 'phone' and 'computer' spell \\\"app\\\" as ????? = U+0C86 (? , independent vowel AA) + U+0CCD (virama) + ? + ? + virama. A virama can only attach to a CONSONANT to kill its inherent vowel; placing it on the independent vowel letter ? is malformed Kannada and renders with a broken/dotted-circle halant on many stacks. The existing kn catalog uses the well-formed ??? 4x (dominant/correct) vs the broken ????? only 1x. Corrected both occurrences to ??? . This does NOT fail any of the six enumerated linter rules, so ok=true; it is a surfaced quality fix.\" ,\"Note (not a defect): the English 'message' line ends '...upload that shorter version'; the candidate renders 'version' as ?????? (well-formed, matches catalog site.sharper.improve.body). Kept as-is.\"],\"message\":\"? ????? {size} ???, {cap} ?????? ?????? ?????? ?????? ? ?????? ?????? ?????? ?????? ?????? ?????? ? ?????? ?????? ?????? ????.\" ,\"summary\":\"???? ???? , ????????? ?????? ???? ????? ???? ? ?????? ??????\" ,\"phone\":\"?????????: ;???? Photos ??? Gallery ?????? ?????? ?????? , ?????? ??? ?????????? ?????????? ????? ????? ????? ?????????????? ?????????? , ??? ???? ? ???? ?????? ?????? ?????? ??????\" ,\"computer\":\"?????????????: ; Windows ????? Photos ????????? ???? Mac ????? QuickTime Player ????? ?????? ?????????, ????????? ?????? ????? ?????? ?????? ?????? ???? ? ???? ?????? ?????? ???? ???? ???? ????\" ,\"advanced\":\"?????????: ; ????? ????? ?????????? ?????????? ?????? , ?????????????? ?????????????? scripts/chunk_video.py ??? ?????? ?????? ?????? ?????? ?????? , ?????? ??? ?????????? ?????? ?????????? ??????\" ,\"code\":\"hi\",\"ok\":true,\"issues\":[],\"message\":\"? ????? {size} ?? ??, ?? {cap} ?? ????? ???? ?? ????? ? ? ?????? ?? , ????? ???? ???? ???? ???? ???? ?-?? ???? ?? ??? ???? ???? ???? ????\" ,\"summary\":\"???? ? ???? ???? ???? , ?????? ????? ???? ? ? ???? ???? ? , ?? ????\" ,\"phone\":\"???? ??: ;???? Photos ?? Gallery ?? ??? ?????? ?????? , ?????? ?? ????? ???? ? ???? ? ? ?????? ?????? ???? ???? ? ???? ???? , ?? ???? ???? ???? ???? ???? ????\" ,\"computer\":\"???????? ??: ; Windows ?? Photos ?? ? Mac ?? QuickTime Player ?? ????? ?????? , ????? ???? ? ???? ? ? ?????? ?????? ???? ???? ? ?????? ???? , ?? ? ???? ???? ???? ???? ????\" ,\"advanced\":\"??? ? ???? ;??? ? ???? ;??? ? ? ???? ???? ? ? ???? ???? ? , ?? ? ???? ???? ???? ???? ???? ? ? ? scripts/chunk_video.py ? ? ? ????-???? ?????? ? ? ???? ???? ? , ?? ? ???? ???? ???? Google Drive ? ? ???? ? ? ???? ?\"},{\"code\":\"es\",\"ok\":true,\"issues\":[],\"message\":\"Este clip pesa {size}, apenas por encima del límite de subida de {cap}, así que recórtalo a tu mejor jugada o dos y sube esa versión más corta.\" ,\"summary\":\"Tranquilo, recortar toma cerca de un minuto, aquí te explicamos cómo.\" ,\"phone\":\"En el teléfono: abre el clip en tu app Photos o Gallery, arrastra los dos controles de los extremos del video para dejar solo la jugada que quieres, luego guarda y sube ese clip más corto.\" ,\"computer\":\"En la computadora: abre el clip en la app Photos en Windows o en QuickTime Player en Mac, arrastra los extremos hacia adentro para dejar solo la parte que quieres, luego guarda el clip más corto y súbelo.\" ,\"advanced\":\"Avanzado: si prefieres conservar el partido completo, quien maneje la configuración puede dividirlo en partes más pequeñas con scripts/chunk_video.py, o subir el video entero a Google Drive.\"},{\"code\":\"da\",\"ok\":true,\"issues\":[],\"message\":\"Dette klip fylder {size}, lige over uploadgrænsen på {cap}, så klip det ned til dit bedste rally eller to, og upload den kortere version.\" ,\"summary\":\"Bare rolig, det tager cirka et minut at klippe til, og her er hvordan.\" ,\"phone\":\"På en telefon: åbn klippet i din Photos- eller Gallery-app, træk de to håndtag i hver ende af videoen, så du kun beholder det rally, du vil have, og gem og upload så det kortere klip.\" ,\"computer\":\"På en computer: åbn klippet i Photos-appen på Windows eller QuickTime Player på Mac, træk enderne indad, så du kun beholder den del, du vil have, og gem så det kortere klip og upload det.\" ,\"advanced\":\"Avanceret: hvis du hellere vil beholde hele kampen, kan

den, der står for opsætningen, dele den op i mindre dele med scripts/chunk_video.py, eller du kan uploade hele videoen til Google Drev i stedet."},{ "code": "id", "ok": true, "issues": [], "message": "Klip ini berukuran {size}, sedikit melebihi batas unggah {cap}, jadi potong saja menjadi satu atau dua reli terbaikmu lalu unggah versi yang lebih pendek itu.", "summary": "Tenang saja, memotong video hanya butuh sekitar satu menit, begini caranya.", "phone": "Di ponsel: buka klipnya di aplikasi Photos atau Gallery, geser dua pegangan di kedua ujung video untuk menyisakan reli yang kamu mau, lalu simpan dan unggah klip yang lebih pendek itu.", "computer": "Di komputer: buka klipnya di aplikasi Photos pada Windows atau QuickTime Player pada Mac, geser kedua ujungnya ke dalam untuk menyisakan bagian yang kamu mau, lalu simpan klip yang lebih pendek itu dan unggah.", "advanced": "Tingk... (truncated 240 chars, full result in C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra-guru-khelsutra--claude-worktrees-zealous-pike-7d0a85b8be946b-bd13-4912-b478-1b1923b9478c\tasks\wrk6l0s5w.output)</result><usage><agent_count>14</agent_count><subagent_tokens>573026</subagent_tokens><tool_uses>52</tool_uses><duration_ms>347285</duration_ms></usage></task-notification>

132. assistant (2026-07-04T01:56:30.682Z)

The workflow finished ? all 5 locales verified `ok=true` (Kannada got a proactive orthography fix: `?????`?). The `id` result is truncated; let me read the full output file to get exact strings.

133. user (2026-07-04T01:56:33.821Z)

```
1      {
2      "summary": "Vet + translate the \"how to trim your video\" upload-guard help copy
across 6 locales",
3      "agentCount": 14,
4      "logs": [],
5      "result": {
6      "en": {
7      "message_en": "This clip is {size}, just over the {cap} upload limit, so trim it
to your best rally or two and upload that shorter version.",
8      "summary_en": "No worries, trimming takes about a minute, here's how.",
9      "phone_en": "<b>On a phone:</b> open the clip in your Photos or Gallery app, drag
the two handles at the ends of the video to keep just the rally you want, then save and upload
that shorter clip.",
10     "computer_en": "<b>On a computer:</b> open the clip in the Photos app on Windows
or QuickTime Player on Mac, drag the ends inward to keep only the part you want, then save the
shorter clip and upload it.",
11     "advanced_en": "<b>Advanced:</b> if you'd rather keep the full match, whoever runs
the setup can split it into smaller parts with scripts/chunk_video.py, or upload the whole video
to Google Drive instead.",
12     "rationale": "Message: took Proposal 1/3's warm \"just over the {cap} upload
limit\" framing (softens the rejection to a small step) and Proposal 1's badminton-concrete
\"your best rally or two,\" ending with the clear action \"upload that shorter version.\" Both
required placeholders {size} and {cap} are kept verbatim with no other braces; help strings
carry no placeholders. Summary: chose Proposal 1's reassuring \"No worries, trimming takes about
a minute, here's how.\" over the plainer \"How do I trim it?\" because it lowers anxiety for a
coach who has never trimmed a video while still labeling the collapsible help. Phone: Proposal
1's \"drag the two handles at the ends of the video\" is the clearest first-timer gesture, plus
\"save and upload that shorter clip\" for the full follow-through; kept \"Photos or Gallery\"
and the badminton \"rally.\" Computer: Proposal 1's \"drag the ends inward to keep only the part
you want, then save the shorter clip and upload it\" ? the most beginner-proof physical
description; correctly names Photos on Windows and QuickTime Player on Mac (both genuinely trim
natively), and avoids VLC. I deliberately dropped Proposal 2's literal \"Edit then Trim\" menu
path to keep it to one simple gesture and avoid overloading a novice. Advanced: merged Proposal
1's friendly \"if you'd rather keep the full match\" reframe with Proposal 3's \"whoever runs
the setup\" signal that this path isn't for the coach; preserves both required deliverables
verbatim ? scripts/chunk_video.py (plain text) and the Google Drive fallback. All lines are
single sentences, air-gapped (no URLs or \"search online\"), use only the permitted <b> lead-in
label, and keep every product name verbatim."
13     },
```

```

14     "locales": [
15         {
16             "code": "kn",
17             "ok": true,
18             "issues": [
19                 "Orthography (quality, not a linter-enumerated rule): 'phone' and 'computer'
spell \"app\" as ????? = U+0C86 (? , independent vowel AA) + U+0CCD (virama) + ? + ? + virama. A
virama can only attach to a CONSONANT to kill its inherent vowel; placing it on the independent
vowel letter ? is malformed Kannada and renders with a broken/dotted-circle halant on many
stacks. The existing kn catalog uses the well-formed ??? 4x (dominant/correct) vs the broken
???? only 1x. Corrected both occurrences to ??? . This does NOT fail any of the six enumerated
linter rules, so ok=true; it is a surfaced quality fix.",
20                 "Note (not a defect): the English 'message' line ends '...upload that shorter
version'; the candidate renders 'version' as ?????? (well-formed, matches catalog
site.sharper.improve.body). Kept as-is."
21             ],
22             "message": "? ????? {size} ???, {cap} ?????? ?????? ?????? ?????? ?
??????? ?????? ???????? ?????????? ?????????, ? ????? ?????????????? ????????? ?????.",
23             "summary": "????? ???, ?????????? ?????? ??? ?????? ? ?????? ??????.",
24             "phone": "<b>?????????:</b> ????? Photos ??? Gallery ?????? ??????
????????, ?????? ??? ?????????? ?????????? ?????? ?????? ?????? ?????????????? ??????????,
????? ??? ? ?????? ?????? ?????? ?????? ?????.",
25             "computer": "<b>?????????????:</b> Windows ????? Photos ?????? ??? Mac
????? QuickTime Player ?????? ?????? ??????, ?????????? ?????? ?????? ?????? ??????
????????????, ??? ? ?????? ?????? ?????? ??? ?????? ?????.",
26             "advanced": "<b>?????????????:</b> ??? ?????? ?????????? ?????????? ??????,
????????????? ?????????????? scripts/chunk_video.py ??? ?????? ?????? ??????????
????? ??? ?????????? ?????? ?????????? ?????????? ?????????."
27         },
28         {
29             "code": "hi",
30             "ok": true,
31             "issues": [],
32             "message": "? ? {size} ?? ??, ?? {cap} ?? ????? ?? ????? ?? ??????
??, ????? ?? ??? ?????? ??-?? ????? ?? ?? ?? ?? ?? ?????? ?????? ??????",
33             "summary": "????? ?? ??? ?? ?????, ?????? ?????? ?? ?? ?? ?????? ??, ?? ???
?????",
34             "phone": "<b>????? ??:</b> ??? Photos ?? Gallery ?? ??? ?????? ?????, ?????? ??
????? ?????? ?? ?? ?? ?????? ?? ?????? ?????? ?????? ?? ?? ?? ?? ??, ?? ?? ?? ?????? ??
????? ?????? ??????",
35             "computer": "<b>????????? ??:</b> Windows ?? Photos ?? ?? Mac ?? QuickTime Player
??? ?????? ?????, ?????? ?????? ?? ?????? ?? ?????? ?????? ?????? ?? ?????? ?????, ?? ??
????? ??? ?????? ??????",
36             "advanced": "<b>??? ?? ??????:</b> ??? ?? ?????? ?? ?? ?????? ?????? ??, ?? ??
????????? ?????? ?????????? ?? ?? scripts/chunk_video.py ?? ??? ?????-???? ?????????? ??
????? ?????? ??, ??
??? ?????? ?????? Google Drive ?? ?????? ?? ?????? ??"
37         },
38         {
39             "code": "es",
40             "ok": true,
41             "issues": [],
42             "message": "Este clip pesa {size}, apenas por encima del límite de subida de
{cap}, así que recórtalo a tu mejor jugada o dos y sube esa versión más corta.",
43             "summary": "Tranquilo, recortar toma cerca de un minuto, aquí te explicamos
cómo.",
44             "phone": "<b>En el teléfono:</b> abre el clip en tu app Photos o Gallery,
arrastra los dos controles de los extremos del video para dejar solo la jugada que quieres,
luego guarda y sube ese clip más corto.",
45             "computer": "<b>En la computadora:</b> abre el clip en la app Photos en Windows
o en QuickTime Player en Mac, arrastra los extremos hacia adentro para dejar solo la parte que
quieres, luego guarda el clip más corto y súbelo.",
46             "advanced": "<b>Avanzado:</b> si prefieres conservar el partido completo, quien
maneje la configuración puede dividirlo en partes más pequeñas con scripts/chunk_video.py, o
subir el video entero a Google Drive."
47         },

```

```

48         {
49             "code": "da",
50             "ok": true,
51             "issues": [],
52             "message": "Dette klip fylder {size}, lige over uploadgrænsen på {cap}, så klip
det ned til dit bedste rally eller to, og upload den kortere version.",
53             "summary": "Bare rolig, det tager cirka et minut at klippe til, og her er
hvordan.",
54             "phone": "<b>På en telefon:</b> åbn klippet i din Photos- eller Gallery-app,
træk de to håndtag i hver ende af videoen, så du kun beholder det rally, du vil have, og gem og
upload så det kortere klip.",
55             "computer": "<b>På en computer:</b> åbn klippet i Photos-appen på Windows eller
QuickTime Player på Mac, træk enderne indad, så du kun beholder den del, du vil have, og gem så
det kortere klip og upload det.",
56             "advanced": "<b>Avanceret:</b> hvis du hellere vil beholde hele kampen, kan den,
der står for opsætningen, dele den op i mindre dele med scripts/chunk_video.py, eller du kan
uploade hele videoen til Google Drev i stedet."
57         },
58         {
59             "code": "id",
60             "ok": true,
61             "issues": [],
62             "message": "Klip ini berukuran {size}, sedikit melebihi batas unggah {cap}, jadi
potong saja menjadi satu atau dua reli terbaikmu lalu unggah versi yang lebih pendek itu.",
63             "summary": "Tenang saja, memotong video hanya butuh sekitar satu menit, begini
caranya.",
64             "phone": "<b>Di ponsel:</b> buka klipnya di aplikasi Photos atau Gallery, geser
dua pegangan di kedua ujung video untuk menyisakan reli yang kamu mau, lalu simpan dan unggah
klip yang lebih pendek itu.",
65             "computer": "<b>Di komputer:</b> buka klipnya di aplikasi Photos pada Windows
atau QuickTime Player pada Mac, geser kedua ujungnya ke dalam untuk menyisakan bagian yang kamu
mau, lalu simpan klip yang lebih pendek itu dan unggah.",
66             "advanced": "<b>Tingkat lanjut:</b> kalau kamu lebih suka menyimpan seluruh
pertandingan, orang yang mengurus penyiapan bisa membaginya menjadi bagian-bagian lebih kecil
dengan scripts/chunk_video.py, atau unggah saja seluruh videonya ke Google Drive."
67         }
68     ]
69 },
70 "workflowProgress": [
71     {
72         "type": "workflow_phase",
73         "index": 1,
74         "title": "Design"
75     },
76     {
77         "type": "workflow_phase",
78         "index": 2,
79         "title": "Translate"
80     },
81     {
82         "type": "workflow_phase",
83         "index": 3,
84         "title": "Verify"
85     },
86     {
87         "type": "workflow_agent",
88         "index": 1,
89         "label": "design:v1",
90         "phaseIndex": 1,
91         "phaseTitle": "Design",
92         "agentId": "a470abd3c2fffa433",
93         "model": "claude-opus-4-8",
94         "state": "done",
95         "startedAt": 1783129834985,
96         "queuedAt": 1783129834952,

```

```

97         "attempt": 1,
98         "lastToolName": "StructuredOutput",
99         "lastToolSummary": "This clip is {size}, just over the {cap} upload limit, so l?",
100        "promptPreview": "You are a product UX writer for KhelSutra (turns a badminton
match into a highlights reel). Refine the copy for the \"your upload is too big ? here is how to
trim it\" help shown after an oversized file is rejected client-side.\n\nImprove on this
baseline (keep its structure/keys; sharpen wording):\n\n  \"message_en\": \"This clip is
{size}, over the {cap} upload limit. Trim it to a shorter highlight firs?\",
101        "lastProgressAt": 1783129847478,
102        "tokens": 29903,
103        "toolCalls": 1,
104        "durationMs": 12493,
105        "resultPreview": "{ \"message_en\": \"This clip is {size}, just over the {cap}
upload limit, so let's trim it to your best rally or two and it will upload
fine.\", \"summary_en\": \"No worries, trimming takes about a minute, here's
how.\", \"phone_en\": \"<b>On a phone:</b> open the clip in your Photos or Gallery app, drag the
two handles at the ends of the video to keep just the part you want, then save and upload that
shorter cli?\"
106      },
107      {
108        "type": "workflow_agent",
109        "index": 2,
110        "label": "design:v2",
111        "phaseIndex": 1,
112        "phaseTitle": "Design",
113        "agentId": "a0b664dc7b5b76205",
114        "model": "claude-opus-4-8",
115        "state": "done",
116        "startedAt": 1783129834987,
117        "queuedAt": 1783129834952,
118        "attempt": 1,
119        "lastToolName": "StructuredOutput",
120        "lastToolSummary": "This clip is {size}, over the {cap} limit ? trim it to a sh?",
121        "promptPreview": "You are a product UX writer for KhelSutra (turns a badminton
match into a highlights reel). Refine the copy for the \"your upload is too big ? here is how to
trim it\" help shown after an oversized file is rejected client-side.\n\nImprove on this
baseline (keep its structure/keys; sharpen wording):\n\n  \"message_en\": \"This clip is
{size}, over the {cap} upload limit. Trim it to a shorter highlight firs?\",
122        "lastProgressAt": 1783129847764,
123        "tokens": 29916,
124        "toolCalls": 1,
125        "durationMs": 12777,
126        "resultPreview": "{ \"message_en\": \"This clip is {size}, over the {cap} limit ?
trim it to a shorter highlight, then upload again.\", \"summary_en\": \"How do I trim
it?\", \"phone_en\": \"<b>On a phone:</b> open the clip in Photos or Gallery, drag the trim
handles to keep just the rally you want, then upload that shorter
clip.\", \"computer_en\": \"<b>On a computer:</b> open it in Photos on Windows or QuickTime Player
on Mac, use Edit?\"
127      },
128      {
129        "type": "workflow_agent",
130        "index": 3,
131        "label": "design:v3",
132        "phaseIndex": 1,
133        "phaseTitle": "Design",
134        "agentId": "a33ce3700a141c1e2",
135        "model": "claude-opus-4-8",
136        "state": "done",
137        "startedAt": 1783129834987,
138        "queuedAt": 1783129834952,
139        "attempt": 1,
140        "lastToolName": "StructuredOutput",
141        "lastToolSummary": "This clip is {size}, just over the {cap} upload limit, so t?",
142        "promptPreview": "You are a product UX writer for KhelSutra (turns a badminton
match into a highlights reel). Refine the copy for the \"your upload is too big ? here is how to

```

```

trim it\" help shown after an oversized file is rejected client-side.\n\nImprove on this
baseline (keep its structure/keys; sharpen wording):\n{\n  \"message_en\": \"This clip is
{size}, over the {cap} upload limit. Trim it to a shorter highlight first?\",
143    \"lastProgressAt\": 1783129865717,
144    \"tokens\": 33692,
145    \"toolCalls\": 2,
146    \"durationMs\": 30730,
147    \"resultPreview\": \"{\\\"message_en\\\":\\\"This clip is {size}, just over the {cap}
upload limit, so trim it down to the key moment and upload that shorter
version.\\\",\\\"summary_en\\\":\\\"How do I trim it down?\\\",\\\"phone_en\\\":\\\"<b>On a phone:</b> open the
clip in your Photos or Gallery app, drag the two ends of the trim slider to keep just the rally
or point you want, then upload that shorter clip.\\\",\\\"computer_en\\\":\\\"<b>On a computer:</b> ?\"
148  },
149  {
150    \"type\": \"workflow_agent\",
151    \"index\": 4,
152    \"label\": \"design:synth\",
153    \"phaseIndex\": 1,
154    \"phaseTitle\": \"Design\",
155    \"agentId\": \"a7d50e2706d03861f\",
156    \"model\": \"claude-opus-4-8\",
157    \"state\": \"done\",
158    \"startedAt\": 1783129865718,
159    \"queuedAt\": 1783129865718,
160    \"attempt\": 1,
161    \"lastToolName\": \"StructuredOutput\",
162    \"lastToolSummary\": \"This clip is {size}, just over the {cap} upload limit, so t?\",
163    \"promptPreview\": \"Synthesize the single BEST English version of this upload-trim
help from 3 proposals. Pick the strongest line from each, resolve conflicts toward correctness +
warmth + brevity.\n\nBaseline:\n{\n  \"message_en\": \"This clip is {size}, over the {cap}
upload limit. Trim it to a shorter highlight first, then upload again.\\\",\\n  \"summary_en\":
\\\"How do I trim it?\\\",\\n  \"phone_en\": \"<b>On a phone:</b> open the cli?\",
164    \"lastProgressAt\": 1783129879117,
165    \"tokens\": 31789,
166    \"toolCalls\": 1,
167    \"durationMs\": 13399,
168    \"resultPreview\": \"{\\\"message_en\\\":\\\"This clip is {size}, just over the {cap}
upload limit, so trim it to your best rally or two and upload that shorter
version.\\\",\\\"summary_en\\\":\\\"No worries, trimming takes about a minute, here's
how.\\\",\\\"phone_en\\\":\\\"<b>On a phone:</b> open the clip in your Photos or Gallery app, drag the
two handles at the ends of the video to keep just the rally you want, then save and upload that
shorter ?\"
169  },
170  {
171    \"type\": \"workflow_agent\",
172    \"index\": 5,
173    \"label\": \"translate:kn\",
174    \"phaseIndex\": 2,
175    \"phaseTitle\": \"Translate\",
176    \"agentId\": \"a1d301aa1659e3db7\",
177    \"model\": \"claude-opus-4-8\",
178    \"state\": \"done\",
179    \"startedAt\": 1783129879138,
180    \"queuedAt\": 1783129879122,
181    \"attempt\": 1,
182    \"lastToolName\": \"StructuredOutput\",
183    \"lastToolSummary\": \"? ?????? {size} ???, {cap} ???????? ???????? ???????? ?????? ?
??????? ?????? ????????\",
184    \"promptPreview\": \"Translate this KhelSutra \\\"how to trim your video\\\" upload-help
into Kannada (kn). Locale notes: This SPA already uses ?????? (rally), ?????? (video), ??????
?????? (Google Drive), ???????? (upload). Brand stays Latin \\\"KhelSutra\\\" (never ??????????). Do
NOT use ??????/?????/???????/?????/?????????.\n\nFINALIZED ENGLISH SOURCE:\n{\n  \"message_en\":
\\\"This clip is {size}, just over the {cap} upload limit, so tr?\",
185    \"lastProgressAt\": 1783129947668,
186    \"tokens\": 52221,

```

```
187         "toolCalls": 5,
188         "durationMs": 68529,
189         "resultPreview": "{\n\"message\": \"? ????? {size} ???, {cap} ?????? ??????
???????? ? ? ?????? ?????? ?????? ?????? ?????? ? ?????? ??????
???????? ????.\",\n\"summary\": \"? ????? ???? ???? ?????? ???? ???? ???? ?
????????.\",\n\"phone\": \"<b>?????????:</b> ???? Photos ??? Gallery ?????????? ??????
???????? ???? ?????????? ?????? ?????? ?????? ?????? ??????\"
190     },
191     {
192         "type": "workflow_agent",
193         "index": 6,
194         "label": "translate:hi",
195         "phaseIndex": 2,
196         "phaseTitle": "Translate",
197         "agentId": "af4ee13ebe68f26dd",
198         "model": "claude-opus-4-8",
199         "state": "done",
200         "startedAt": 1783129879141,
201         "queuedAt": 1783129879122,
202         "attempt": 1,
203         "lastToolName": "StructuredOutput",
204         "lastToolSummary": "? ? {size} ? ? , ? {cap} ? ? ???? ???? ? ? ???? ?
????? ? , ???? ? ? ? ",
205         "promptPreview": "Translate this KhelSutra \"how to trim your video\" upload-help
into Hindi (hi). Locale notes: Use everyday Hindi (avoid over-Sanskritized terms). Brand stays
Latin \"KhelSutra\" (never ??????). Do NOT use ???/????/????/????/??. ??? ????? for
Google Drive.\n\nFINALIZED ENGLISH SOURCE:\n{\n  \"message\": \"This clip is {size}, just over
the {cap} upload limit, so trim it to your best rally or two?\",
206         "lastProgressAt": 1783129903548,
207         "tokens": 30155,
208         "toolCalls": 1,
209         "durationMs": 24407,
210         "resultPreview": "{\n\"message\": \"? ????? {size} ? ? , ? {cap} ? ? ???? ???? ?
???? ? ? ?????? ? , ???? ? ? ???? ???? ???? ?-? ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
?????\",\n\"summary\": \"? ????? ? ? ? ? ? ? ? , ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? , ? ? ?
?????\",\n\"phone\": \"<b>??? ??:</b> ??? Photos ? Gallery ? ? ? ? ? ? ? ? ? , ???? ? ? ????
???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? , ? ? ? \"
211     },
212     {
213         "type": "workflow_agent",
214         "index": 7,
215         "label": "translate:es",
216         "phaseIndex": 2,
217         "phaseTitle": "Translate",
218         "agentId": "ac6c853663fde306d",
219         "model": "claude-opus-4-8",
220         "state": "done",
221         "startedAt": 1783129879142,
222         "queuedAt": 1783129879122,
223         "attempt": 1,
224         "lastToolName": "StructuredOutput",
225         "lastToolSummary": "Este clip pesa {size}, apenas por encima del límite de subi?",
226         "promptPreview": "Translate this KhelSutra \"how to trim your video\" upload-help
into Spanish (es). Locale notes: Latin-American-neutral, friendly. \"clip\"/\"video\"/\"Google
Drive\" as-is.\n\nFINALIZED ENGLISH SOURCE:\n{\n  \"message\": \"This clip is {size}, just over
the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, here's ?\",
227         "lastProgressAt": 1783129896266,
228         "tokens": 30085,
229         "toolCalls": 1,
230         "durationMs": 17124,
231         "resultPreview": "{\n\"message\": \"Este clip pesa {size}, apenas por encima del
límite de subida de {cap}, así que recórtalo a tu mejor jugada o dos y sube esa versión más
corta.\",\n\"summary\": \"Tranquilo, recortar toma cerca de un minuto, aquí te explicamos
cómo.\",\n\"phone\": \"<b>En el teléfono:</b> abre el clip en tu app Photos o Gallery, arrastra los
```

dos controles de los extremos del video para dejar solo la jugada que quier?"

```
232     },
233     {
234         "type": "workflow_agent",
235         "index": 8,
236         "label": "translate:da",
237         "phaseIndex": 2,
238         "phaseTitle": "Translate",
239         "agentId": "a2c004d626bae2917",
240         "model": "claude-opus-4-8",
241         "state": "done",
242         "startedAt": 1783129879143,
243         "queuedAt": 1783129879122,
244         "attempt": 1,
245         "lastToolName": "StructuredOutput",
246         "lastToolSummary": "Dette klip fylder {size}, lige over uploadgrænsen på {cap},?",
247         "promptPreview": "Translate this KhelSutra \"how to trim your video\" upload-help
into Danish (da). Locale notes: Google Drive is \"Google Drev\" in this catalog. Friendly,
plain.\n\nFINALIZED ENGLISH SOURCE:\n\n \"message\": \"This clip is {size}, just over the
{cap} upload limit, so trim it to your best rally or two and upload that shorter version.\",\n
\"summary\": \"No worries, trimming takes about a minute, here's how.\",\n ?",
248         "lastProgressAt": 1783129895882,
249         "tokens": 30076,
250         "toolCalls": 1,
251         "durationMs": 16739,
252         "resultPreview": "{ \"message\": \"Dette klip fylder {size}, lige over uploadgrænsen
på {cap}, så klip det ned til dit bedste rally eller to, og upload den kortere
version.\", \"summary\": \"Bare rolig, det tager cirka et minut at klippe til, og her er
hvordan.\", \"phone\": \"<b>På en telefon:</b> åbn klippet i din Photos- eller Gallery-app, træk
de to håndtag i hver ende af videoen, så du kun beholder det rally, du vil have, og g?\"
253     },
254     {
255         "type": "workflow_agent",
256         "index": 9,
257         "label": "translate:id",
258         "phaseIndex": 2,
259         "phaseTitle": "Translate",
260         "agentId": "a9a18bf8d08100af0",
261         "model": "claude-opus-4-8",
262         "state": "done",
263         "startedAt": 1783129879144,
264         "queuedAt": 1783129879122,
265         "attempt": 1,
266         "lastToolName": "StructuredOutput",
267         "lastToolSummary": "Klip ini berukuran {size}, sedikit melebihi batas unggah {c?",
268         "promptPreview": "Translate this KhelSutra \"how to trim your video\" upload-help
into Indonesian (id). Locale notes: Friendly, plain Bahasa Indonesia. \"Google Drive\" as-
is.\n\nFINALIZED ENGLISH SOURCE:\n\n \"message\": \"This clip is {size}, just over the {cap}
upload limit, so trim it to your best rally or two and upload that shorter version.\",\n
\"summary\": \"No worries, trimming takes about a minute, here's how.\",\n \"ph?",
269         "lastProgressAt": 1783129897734,
270         "tokens": 30082,
271         "toolCalls": 1,
272         "durationMs": 18590,
273         "resultPreview": "{ \"message\": \"Klip ini berukuran {size}, sedikit melebihi batas
unggah {cap}, jadi potong saja menjadi satu atau dua reli terbaikmu lalu unggah versi yang lebih
pendek itu.\", \"summary\": \"Tenang saja, memotong video hanya butuh sekitar satu menit, begini
caranya.\", \"phone\": \"<b>Di ponsel:</b> buka klipnya di aplikasi Photos atau Gallery, geser dua
pegangan di kedua ujung video untuk menyisakan reli yang ?\"
274     },
275     {
276         "type": "workflow_agent",
277         "index": 10,
278         "label": "verify:da",
279         "phaseIndex": 3,
```

```

280     "phaseTitle": "Verify",
281     "agentId": "a7c190831090b537a",
282     "model": "claude-opus-4-8",
283     "state": "done",
284     "startedAt": 1783129895897,
285     "queuedAt": 1783129895883,
286     "attempt": 1,
287     "lastToolName": "StructuredOutput",
288     "lastToolSummary": "Dette klip fylder {size}, lige over uploadgrænsen på {cap},?",
289     "promptPreview": "Adversarially VERIFY this Danish (da) translation of the
KhelSutra upload-trim help against the linter rules. Assume it is WRONG until proven right;
check each rule explicitly.\n\nEnglish source:\n{\n  \"message\": \"This clip is {size}, just
over the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, here's?\",
290     "lastProgressAt": 1783129938186,
291     "tokens": 75141,
292     "toolCalls": 5,
293     "durationMs": 42289,
294     "resultPreview": "{\n  \"ok\": true,\n  \"issues\": [],\n  \"message\": \"Dette klip fylder
{size}, lige over uploadgrænsen på {cap}, så klip det ned til dit bedste rally eller to, og
upload den kortere version.\",\n  \"summary\": \"Bare rolig, det tager cirka et minut at klippe til,
og her er hvordan.\",\n  \"phone\": \"<b>På en telefon:</b> åbn klippet i din Photos- eller Gallery-
app, træk de to håndtag i hver ende af videoen, så du kun beholder det ra?\"
295   },
296   {
297     "type": "workflow_agent",
298     "index": 11,
299     "label": "verify:es",
300     "phaseIndex": 3,
301     "phaseTitle": "Verify",
302     "agentId": "a36f559eeb5edc68f",
303     "model": "claude-opus-4-8",
304     "state": "done",
305     "startedAt": 1783129896268,
306     "queuedAt": 1783129896267,
307     "attempt": 1,
308     "lastToolName": "StructuredOutput",
309     "lastToolSummary": "Este clip pesa {size}, apenas por encima del límite de subi?",
310     "promptPreview": "Adversarially VERIFY this Spanish (es) translation of the
KhelSutra upload-trim help against the linter rules. Assume it is WRONG until proven right;
check each rule explicitly.\n\nEnglish source:\n{\n  \"message\": \"This clip is {size}, just
over the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, here'?",
311     "lastProgressAt": 1783129944084,
312     "tokens": 37333,
313     "toolCalls": 4,
314     "durationMs": 47816,
315     "resultPreview": "{\n  \"ok\": true,\n  \"issues\": [],\n  \"message\": \"Este clip pesa {size},
apenas por encima del límite de subida de {cap}, así que recórtalo a tu mejor jugada o dos y
sube esa versión más corta.\",\n  \"summary\": \"Tranquilo, recortar toma cerca de un minuto, aquí te
explicamos cómo.\",\n  \"phone\": \"<b>En el teléfono:</b> abre el clip en tu app Photos o Gallery,
arrastra los dos controles de los extremos del video para dejar so?\"
316   },
317   {
318     "type": "workflow_agent",
319     "index": 12,
320     "label": "verify:id",
321     "phaseIndex": 3,
322     "phaseTitle": "Verify",
323     "agentId": "aae900df2d91a1758",
324     "model": "claude-opus-4-8",
325     "state": "done",
326     "startedAt": 1783129897742,
327     "queuedAt": 1783129897741,
328     "attempt": 1,

```



```

329         "lastToolName": "StructuredOutput",
330         "lastToolSummary": "Klip ini berukuran {size}, sedikit melebihi batas unggah {c?}",
331         "promptPreview": "Adversarially VERIFY this Indonesian (id) translation of the
KhelSutra upload-trim help against the linter rules. Assume it is WRONG until proven right;
check each rule explicitly.\n\nEnglish source:\n{\n  \"message\": \"This clip is {size}, just
over the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, he?\",
332         \"lastProgressAt\": 1783129989689,
333         \"tokens\": 51468,
334         \"toolCalls\": 11,
335         \"durationMs\": 91947,
336         \"resultPreview\": \"{\\\"ok\\\":true,\\\"issues\\\":[],\\\"message\\\":\\\"Klip ini berukuran
{size}, sedikit melebihi batas unggah {cap}, jadi potong saja menjadi satu atau dua reli
terbaikmu lalu unggah versi yang lebih pendek itu.\\\",\\\"summary\\\":\\\"Tenang saja, memotong video
hanya butuh sekitar satu menit, begini caranya.\\\",\\\"phone\\\":\\\"<b>Di ponsel:</b> buka klipnya di
aplikasi Photos atau Gallery, geser dua pegangan di kedua ujung video untuk?\"
337     },
338     {
339         \"type\": \"workflow_agent\",
340         \"index\": 13,
341         \"label\": \"verify:hi\",
342         \"phaseIndex\": 3,
343         \"phaseTitle\": \"Verify\",
344         \"agentId\": \"a520c5005146ed756\",
345         \"model\": \"claude-opus-4-8\",
346         \"state\": \"done\",
347         \"startedAt\": 1783129903550,
348         \"queuedAt\": 1783129903548,
349         \"attempt\": 1,
350         \"lastToolName\": \"StructuredOutput\",
351         \"lastToolSummary\": \"?? ????? {size} ?? ??, ?? {cap} ?? ????? ??? ? ???? ?
????? ??, ????? ??? ?\",
352         \"promptPreview\": \"Adversarially VERIFY this Hindi (hi) translation of the
KhelSutra upload-trim help against the linter rules. Assume it is WRONG until proven right;
check each rule explicitly.\n\nEnglish source:\n{\n  \"message\": \"This clip is {size}, just
over the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, here's ?\",
353         \"lastProgressAt\": 1783129950207,
354         \"tokens\": 37311,
355         \"toolCalls\": 3,
356         \"durationMs\": 46657,
357         \"resultPreview\": \"{\\\"ok\\\":true,\\\"issues\\\":[],\\\"message\\\":\\\"?? ????? {size} ?? ??,
?? {cap} ?? ????? ??? ? ???? ? ???? ? ???? ? ???? ? ???? ? ???? ? ???? ? ???? ? ???? ?
?? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
?? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
?? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
?? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
?? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
358     },
359     {
360         \"type\": \"workflow_agent\",
361         \"index\": 14,
362         \"label\": \"verify:kn\",
363         \"phaseIndex\": 3,
364         \"phaseTitle\": \"Verify\",
365         \"agentId\": \"a615a7e3ae04d9171\",
366         \"model\": \"claude-opus-4-8\",
367         \"state\": \"done\",
368         \"startedAt\": 1783129947670,
369         \"queuedAt\": 1783129947669,
370         \"attempt\": 1,
371         \"lastToolName\": \"StructuredOutput\",
372         \"lastToolSummary\": \"? ????? {size} ???, {cap} ?????? ???? ? ???? ? ???? ?
????? ? ???? ? ???? ?\",
373         \"promptPreview\": \"Adversarially VERIFY this Kannada (kn) translation of the
KhelSutra upload-trim help against the linter rules. Assume it is WRONG until proven right;
check each rule explicitly.\n\nEnglish source:\n{\n  \"message\": \"This clip is {size}, just

```

```

over the {cap} upload limit, so trim it to your best rally or two and upload that shorter
version.\",\n  \"summary\": \"No worries, trimming takes about a minute, here?\",
374      \"lastProgressAt\": 1783130182209,
375      \"tokens\": 73854,
376      \"toolCalls\": 15,
377      \"durationMs\": 234539,
378      \"resultPreview\": \"{\\\"ok\\\":true,\\\"issues\\\":[\\\"Orthography (quality, not a linter-
enumerated rule): 'phone' and 'computer' spell \\\"app\\\" as ????? = U+0C86 (? , independent
vowel AA) + U+0CCD (virama) + ? + ? + virama. A virama can only attach to a CONSONANT to kill
its inherent vowel; placing it on the independent vowel letter ? is malformed Kannada and
renders with a broken/dotted-circle halant on many stacks. The existin?\"
379      }
380  ],
381  \"totalTokens\": 573026,
382  \"totalToolCalls\": 52
383  }

```

134. assistant (2026-07-04T01:58:34.519Z)

All five non-English locales passed adversarial verification (`ok=true`), and the Kannada verifier caught and fixed a genuine orthography bug (`?????`???, a malformed virama on an independent vowel). I have the final, vetted copy. Now let me update the catalogs ? replace the old `fileTooLarge` message and add the `fileTooLargeHelp` block in all six locales.

135. user (2026-07-04T01:58:39.522Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/en/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

136. user (2026-07-04T01:59:17.135Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/kn/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

137. user (2026-07-04T01:59:29.622Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/hi/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

138. user (2026-07-04T01:59:38.872Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/es/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

139. user (2026-07-04T01:59:50.372Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/da/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

140. user (2026-07-04T02:00:01.056Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/locales/id/common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

141. assistant (2026-07-04T02:00:05.005Z)

All six catalogs updated. Now fix the tests that assumed the old message. First

`errorText.test.ts` ? the message no longer contains `scripts/chunk\_video.py` (that moved to the help disclosure):

142. user (2026-07-04T02:00:11.989Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errorText.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

143. assistant (2026-07-04T02:00:15.341Z)

Now enhance the component test to assert the new trim-help disclosure renders (phone guidance + the advanced `chunk\_video.py` line):

144. user (2026-07-04T02:00:22.636Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/components/upload.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

145. assistant (2026-07-04T02:00:25.614Z)

Let me validate the JSON parses in all six locales, then run typecheck and the full suite:

146. user (2026-07-04T02:00:29.763Z)

en OK
kn OK
hi OK
es OK
da OK
id OK

147. user (2026-07-04T02:00:50.273Z)

```
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
```

```
=== TESTS ===
  Test Files   30 passed (30)
     Tests    291 passed (291)
```

148. assistant (2026-07-04T02:00:54.978Z)

Typecheck clean; all 291 tests pass ? including the i18n key-parity, placeholder-parity, and catalog-invariant guards, which now validate the new `fileTooLargeHelp.\*` keys and `**` tags across all six locales. Let me confirm coverage still clears the floor:**

149. user (2026-07-04T02:01:09.950Z)

```
stdout | src/components/IngestPanel.test.tsx > IngestPanel > gates cloud on a cost ack, then
sends compute=cloud
stdout | src/components/IngestPanel.test.tsx > IngestPanel > gates cloud on a cost ack, then
sends compute=cloud
stdout | src/components/IngestPanel.test.tsx > IngestPanel > gates cloud on a cost ack, then
sends compute=cloud
stdout | src/components/IngestPanel.test.tsx > IngestPanel > gates cloud on a cost ack, then
sends compute=cloud
  ? src/components/IngestPanel.test.tsx (15 tests) 2038ms
    ? IngestPanel > submits a URI, polls, and hands the video_id to onLoaded 661ms
File      | % Stmts | % Branch | % Funcs | % Lines | Uncovered Line #s
  IngestPanel.tsx | 97.46 | 91.17 | 100 | 97.46 | 46-47,380-387
Statements : 94.76% ( 2301/2428 )
```

```
Branches      : 88.11% ( 712/808 )
Functions     : 89.65% ( 130/145 )
Lines        : 94.76% ( 2301/2428 )
```

150. assistant (2026-07-04T02:01:22.557Z)

Coverage clears every threshold (stmts 94.76 / branches 88.11 / funcs 89.65 / lines 94.76), and IngestPanel is at 97.46%. Let me review the new diff since the last commit and re-verify branch safety before committing:

151. user (2026-07-04T02:01:27.532Z)

```
=== branch/HEAD ===
claude/zealous-pike-7d0a85
0969059 Guard oversized uploads client-side in the ingest SPA
=== fetch + origin/master ===
b0f70a5 Show failed ingest verdict reasons
=== changed since HEAD ===
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M web/src/components/IngestPanel.tsx
M web/src/components/upload.test.tsx
M web/src/lib/errorText.test.ts
=== diffstat ===
 locales/da/common.json      | 8 ++++++--
 locales/en/common.json      | 8 ++++++--
 locales/es/common.json      | 8 ++++++--
 locales/hi/common.json      | 8 ++++++--
 locales/id/common.json      | 8 ++++++--
 locales/kn/common.json      | 8 ++++++--
 web/src/components/IngestPanel.tsx | 23 ++++++-----
 web/src/components/upload.test.tsx | 9 ++++++--
 web/src/lib/errorText.test.ts | 6 +++---
 9 files changed, 74 insertions(+), 12 deletions(-)
```

152. assistant (2026-07-04T02:01:32.666Z)

Branch is clean, `origin/master` unchanged, only my commit on top. Staging the 9 explicit paths and committing the enhancement:

153. user (2026-07-04T02:01:42.801Z)

```
[claude/zealous-pike-7d0a85 76b97ed] Add "how do I trim it?" help to the oversized-upload guard
 9 files changed, 74 insertions(+), 12 deletions(-)
76b97ed Add "how do I trim it?" help to the oversized-upload guard
0969059 Guard oversized uploads client-side in the ingest SPA
```

154. assistant (2026-07-04T02:01:45.671Z)

`origin/master..HEAD` shows only my two commits. Pushing to update PR #153:

155. user (2026-07-04T02:01:49.118Z)

```
To https://github.com/avidullu/khelsutra.git
 0969059..76b97ed claude/zealous-pike-7d0a85 -> claude/zealous-pike-7d0a85
```

156. assistant (2026-07-04T02:01:55.087Z)

Pushed. Let me update the PR description to cover the new trim-help affordance:

157. user (2026-07-04T02:02:15.111Z)

<https://github.com/avidullu/khelsutra/pull/153>

158. assistant (2026-07-04T02:02:27.723Z)

Let me confirm a clean tree and that the main-repo checkout stayed untouched:

159. user (2026-07-04T02:02:31.027Z)

```
=== worktree status (should be clean) ===
clean
=== main repo status (should be clean) ===
=== commits on branch ===
76b97ed Add "how do I trim it?" help to the oversized-upload guard
0969059 Guard oversized uploads client-side in the ingest SPA
```

160. assistant (2026-07-04T02:02:48.168Z)

Done. Both trees are clean, the main-repo checkout is untouched, and PR #153 now has both commits.

Summary

I extended the fix so a user who **doesn't** know how to trim gets actual, self-service help ? not a Python script path.

The problem with the first version: the message led with ``scripts/chunk_video.py``, which doesn't even exist in this repo (it's in the engine repo), and means nothing to a badminton coach. Two constraints shaped the solution: the SPA must run **air-gapped** (the hygiene tests forbid external links/CDN), so I couldn't link out to a how-to; and the SPA renders formatted strings via ``<Trans>``, so I could use inline ``<b>`` lead-ins.

What I added ? a keyboard-accessible native ``<details>`` **"How do I trim it?"** disclosure in the ``fileTooLarge`` error card (`[IngestPanel.tsx](web/src/components/IngestPanel.tsx)`):

- **On a phone** ? trim in Photos/Gallery (drag the end handles), then upload the shorter clip.
- **On a computer** ? trim in Windows Photos or Mac QuickTime Player (both trim natively ? I dropped a VLC suggestion because it has no beginner-friendly trim).
- **Advanced** ? split with ``scripts/chunk_video.py``, or upload the whole video to Google Drive.

I also softened the top-line message so it no longer leads with dev jargon: **"This clip is 5.8 GB, just over the 4 GB upload limit, so trim it to your best rally or two and upload that shorter version."**

How I built the copy: I ran a multi-agent workflow ? a 3-way judge panel refined the English, then per-locale agents translated into all six languages, each adversarially verified against the catalog's linter rules (placeholder/key parity, kn/hi jargon bans, no ``<code>`` tags, ICU-apostrophe pitfalls). All five non-English locales passed; the Kannada verifier caught and fixed a real orthography bug (a malformed virama on the independent vowel in "app", ``?????`?)`` that would have rendered as a broken glyph.

Verification: typecheck clean; **291 tests pass**; coverage 94.76/88.11/89.65/94.76 ? above the CI floor (92/87/84/92), no regression. The component test renders the real ``IngestPanel`` with the real i18n catalog and asserts the disclosure shows the phone/computer/advanced guidance while making zero network calls.

One judgment call worth flagging: I moved the ``scripts/chunk_video.py`` reference out of the headline message and into the "Advanced" help line. It's still on the same error surface (satisfying the original "reference the chunk helper" requirement), but it no longer greets a non-technical coach first ? which is the whole point of your follow-up.

I verified through the automated suite rather than a browser preview: meaningfully exercising this live needs a running engine that reports ``max_upload_mb`` plus picking a >4 GB file, which the tests simulate deterministically instead.

161. user (2026-07-04T03:01:32.770Z)

Can you ptal at the review comments of #153

162. assistant (2026-07-04T03:01:39.835Z)

Let me pull the review comments on PR #153 via the `gh` CLI.

163. user (2026-07-04T03:01:44.146Z)

=== PR REVIEWS (state + body) ===

--- avidullu [COMMENTED] @2026-07-04T02:59:42Z

I like the direction here and the added coverage is helpful. I found one correctness issue in the new early-return path and one user-facing edge in the size formatter, so I've left inline notes below.

164. assistant (2026-07-04T03:01:47.871Z)

There's a top-level review pointing to inline notes. Let me fetch the inline comments:

165. user (2026-07-04T03:01:51.928Z)

=== INLINE REVIEW COMMENTS ===

????????????????????????????

FILE: web/src/hooks/useUpload.ts:52 (avidullu)

DIFF HUNK:

```
@@ -39,6 +43,14 @@ export function useUpload(onComplete: (path: string, filename: string) => void)
```

```
    setPhase({ status: "error", error: { code: "invalidUri" } });
    return;
```

```
  }
```

```
+    // Oversized file: fail INSTANTLY (no wasted round-trip) ? /upload/init would 413 anyway.
```

Carry

```
+    // the size + cap so IngestPanel can localize a "trim/chunk it first" message. No cap ?
```

skip the

```
+    // guard (the engine still fail-fasts server-side).
```

```
+    const cap = maxUploadBytesRef.current;
```

```
+    if (cap && file.size > cap) {
```

```
+        setPhase({ status: "error", error: { code: "fileTooLarge", sizeBytes: file.size,
capBytes: cap } });
```

```
+        return;
```

COMMENT:

Because this returns before `stop()`, a previous upload stays alive if the user repicks an oversized file while another upload is already in flight. That older async task can still finish and call `onCompleteRef.current(...)`, so we can end up processing file A after showing the `fileTooLarge` error for file B. Could we abort first (or move `stop()` ahead of the early-return guards) and add a regression test for `small upload in flight -> pick oversized file`?

????????????????????????????

FILE: web/src/lib/format.ts:22 (avidullu)

DIFF HUNK:

```
@@ -12,6 +12,19 @@ export function pluralize(n: number, one: string, many = one + "s"): string {
    return `${n} ${n === 1 ? one : many}`;
}
```

```
+/** Bytes ? a short human size for user copy (the upload size-guard message). ? 1 GB renders as GB
```

```
+ * with up to one decimal, trailing ".0" trimmed ("4 GB", "5.8 GB"); smaller renders as whole MB
```

```
+ * ("512 MB"). Clamps negatives/NaN to 0 and never returns below "1 MB" for a positive size.
```

```
*/
```

```
+export function formatFileSize(bytes: number): string {
```

```
+    const b = Math.max(0, Number.isFinite(bytes) ? bytes : 0);
```

```
+ const gb = b / 1024 ** 3;
+ if (gb >= 1) {
+   const rounded = Math.round(gb * 10) / 10;
```

COMMENT:

This rounding can make the rejected file and the cap display as the same value right at the threshold. With a 4 GiB cap, anything up to roughly 50 MiB over still formats as `4 GB`, so the new error can read like "This clip is 4 GB, just over the 4 GB upload limit" even though the two numbers look identical. We probably need either more precision here or comparison-aware formatting when `sizeBytes > capBytes` but the rounded strings match.

166. assistant (2026-07-04T03:05:53.267Z)

Both are real, well-reasoned findings. Let me summarize what the reviewer (avidullu) flagged before I fix them:

****1. `useUpload.ts` ? race on supersede.**** The oversized/0-byte guards `return` *before* `stop()`, so if a small upload is already in flight and the user then picks an oversized file, the old upload isn't aborted ? it can complete and call `onComplete(...)` , processing file A after we've shown a `fileTooLarge` error for file B. Fix: `stop()` first, before the guards. Add a regression test.

****2. `format.ts` ? threshold collision.**** Rounding can make the file and the cap render identically ("This clip is 4 GB, just over the 4 GB upload limit") for a file up to ~50 MiB over a 4 GiB cap. Fix: comparison-aware formatting so the two always read differently.

Both are correct. Let me fix them. First, `stop()` first in the hook:

167. user (2026-07-04T03:06:01.939Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/hooks/useUpload.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

168. assistant (2026-07-04T03:06:04.125Z)

Now the comparison-aware formatter in `format.ts`:

169. user (2026-07-04T03:06:11.591Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

170. assistant (2026-07-04T03:06:14.186Z)

Now wire `errorText.ts` to use the pair formatter:

171. user (2026-07-04T03:06:20.878Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/errorText.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

172. assistant (2026-07-04T03:06:24.533Z)

Now the tests. First the supersede regression test in `useUpload.test.ts`:

173. user (2026-07-04T03:06:31.212Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/hooks/useUpload.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

174. assistant (2026-07-04T03:06:33.392Z)

Now the `formatSizeOverCap` tests in `format.test.ts`:

175. user (2026-07-04T03:06:40.732Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

176. assistant (2026-07-04T03:06:43.201Z)

Update the `format.test.ts` import:

177. user (2026-07-04T03:06:45.045Z)

The file C:/Users/avidu/Projects/khelsutra-guru/khelsutra/.claude/worktrees/zealous-pike-7d0a85/web/src/lib/format.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

178. assistant (2026-07-04T03:06:51.271Z)

Let me run typecheck, tests, and coverage:

179. user (2026-07-04T03:07:10.053Z)

```
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
```

=== TESTS+COVERAGE ===

```
Test Files  30 passed (30)
Tests       295 passed (295)

File          | % Stmts | % Branch | % Funcs | % Lines | Uncovered Line #s
---          -
  useUpload.ts |    100 |    83.33 |    100 |    100 | 73-74,78,83
  errorText.ts |    100 |    100 |    100 |    100 |
  format.ts    |    100 |    100 |    100 |    100 |
Statements   : 94.79% ( 2313/2440 )
Branches     : 88.52% ( 725/819 )
Functions    : 89.79% ( 132/147 )
Lines        : 94.79% ( 2313/2440 )
```

180. assistant (2026-07-04T03:07:18.221Z)

All 295 tests pass (+4 new), and coverage improved on every axis (branches 88.11?88.52).
`format.ts` and `errorText.ts` are now 100% covered; the `useUpload.ts` uncovered lines (73-74, 78, 83) are pre-existing cancel/reset/unmount paths, not the new code. Let me re-verify branch safety and review the diff before committing:

181. user (2026-07-04T03:07:23.007Z)

```
=== HEAD / origin/master ===
76b97ed Add "how do I trim it?" help to the oversized-upload guard
b0f70a5 Show failed ingest verdict reasons
=== pending ===
M web/src/hooks/useUpload.test.ts
M web/src/hooks/useUpload.ts
M web/src/lib/errorText.ts
M web/src/lib/format.test.ts
M web/src/lib/format.ts
=== main repo clean? ===
```

182. assistant (2026-07-04T03:07:28.837Z)

Branch clean, `origin/master` unchanged, main repo untouched. Committing the review fixes:

183. user (2026-07-04T03:07:40.098Z)

[claude/zealous-pike-7d0a85 00109b8] Address review: supersede race + threshold display collision

5 files changed, 84 insertions(+), 7 deletions(-)

00109b8 Address review: supersede race + threshold display collision

76b97ed Add "how do I trim it?" help to the oversized-upload guard

0969059 Guard oversized uploads client-side in the ingest SPA

To <https://github.com/avidullu/khelsutra.git>

76b97ed..00109b8 claude/zealous-pike-7d0a85 -> claude/zealous-pike-7d0a85

184. assistant (2026-07-04T03:07:44.093Z)

Pushed as `00109b8`. Now let me reply to the two review threads so the reviewer knows each is addressed. First I need the comment IDs:

185. user (2026-07-04T03:07:46.904Z)

3522464221 web/src/hooks/useUpload.ts:58

3522464223 web/src/lib/format.ts:22

186. user (2026-07-04T03:08:01.881Z)

https://github.com/avidullu/khelsutra/pull/153#discussion_r3522472324

https://github.com/avidullu/khelsutra/pull/153#discussion_r3522472350

187. assistant (2026-07-04T03:08:18.655Z)

Done. Here's the review and what I did about it.

The review (from avidullu on PR #153)

A top-level "I like the direction" with **two inline findings ? both genuine correctness bugs**, now fixed in commit `00109b8` (pushed) with replies on each thread.

1. `useUpload.ts` ? supersede race

Finding: the 0-byte and oversized guards `return` *before* `stop()`. So if a small upload is already in flight and the user then picks an oversized file, the old upload is never aborted ? it can finish and call `onComplete(...)` , processing file A *after* the UI has shown a `fileTooLarge` error for file B.

Fix: moved `stop()` to the very top of `start()`, before any guard. A superseding pick now aborts the prior upload first; once its controller is aborted, the old async task hits its `signal.aborted` checks and returns without touching `onComplete` or the error phase. This also closes the same latent race on the pre-existing 0-byte guard. Added the requested regression test: *small upload in flight ? pick oversized ? assert `onComplete` never fires and the phase stays `fileTooLarge`.*

2. `format.ts` ? threshold display collision

Finding: rounding can make the file and the cap render identically ? a file up to ~50 MiB over a 4 GiB cap reads *"This clip is 4 GB, just over the 4 GB upload limit."*

Fix: added `formatSizeOverCap(size, cap)`. When the normal short forms collide, it re-renders **both** in a finer unit (whole MB, then raw bytes) so they always read differently and the size still reads as the larger. `errorText` uses it for the message. At the threshold, a 4 GiB cap + ~30 MiB file now reads *"4126 MB ? 4096 MB"* instead of *"4 GB ? 4 GB."* Tests cover the clear case, the GB collision, and the sub-MB bytes fallback.

Verification

- `tsc` clean; **295 tests pass** (+4 new).

- Coverage **94.79 / 88.52 / 89.79 / 94.79** ? up on every axis vs. before (branches

88.11?88.52), above the CI floor (92/87/84/92). `format.ts` and `errorText.ts` are now 100% covered.

Both fixes are on the branch and the reviewer's threads have replies pointing at commit `00109b8`. The reviewer caught two real bugs I'd missed ? the race in particular was a genuine correctness hole, not a style nit.

188. user (2026-07-04T03:13:41.672Z)

can you check the PR comments again

189. assistant (2026-07-04T03:13:49.858Z)

Let me pull the latest reviews and inline comments on PR #153, including anything new since my fixes.

190. user (2026-07-04T03:13:55.003Z)

=== REVIEWS ===

--- avidullu [COMMENTED] @2026-07-04T02:59:42Z

I like the direction here and the added coverage is helpful. I found one correctness issue in the new early-return path and one user-facing edge in the size formatter, so I've left inline notes below.

--- avidullu [COMMENTED] @2026-07-04T03:08:00Z

--- avidullu [COMMENTED] @2026-07-04T03:08:01Z

=== ISSUE COMMENTS (general) ===

--- cloudflare-workers-and-pages[bot] @2026-07-04T01:45:12Z

**Deploying with {
14 const locales = readdirSync(SRC, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name);
15 assert.ok(locales.length >= 3, "expected at least en/kn/hi catalogs in /locales");
16
17 const shipped = new Set(readdirSync(PUB, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name));
18 for (const loc of locales) {
19 const src = readFileSync(join(SRC, loc, "common.json"), "utf8");
20 assert.ok(shipped.has(loc), `site/public/locales/${loc} is missing ? run npm run
copy:locales`);
21 const pub = readFileSync(join(PUB, loc, "common.json"), "utf8");
22 assert.equal(pub, src, `site/public/locales/${loc}/common.json drifted from
/locales/${loc} ? run npm run copy:locales`);
23 }
24 // No stale extra locales shipped that aren't in the source of truth.
25 for (const loc of shipped) {
26 assert.ok(locales.includes(loc), `site/public/locales/${loc} has no source in
/locales ? run npm run copy:locales`);
27 }
28 });
29

```

#### 196. user (2026-07-04T03:14:25.316Z)

```

site\public\locales\da\common.json
site\public\locales\en\common.json
site\public\locales\es\common.json
site\public\locales\hi\common.json
site\public\locales\id\common.json
site\public\locales\kn\common.json

```

#### 197. assistant (2026-07-04T03:14:34.580Z)

The drift test requires `site/public/locales/\*` to be byte-identical to `/locales/\*`. I updated the source catalogs but never re-ran the copy. Let me look at the copy script and run it.

#### 198. user (2026-07-04T03:14:35.897Z)

```

1 // Mirror the single-source-of-truth catalogs (repo-root /locales, D-CATALOG-HOME) into
the site's
2 // static public/ dir, so the dependency-free marketing site can fetch them at runtime
via the
3 // t()/data-i18n shim (public/i18n.js). This copy is the ONLY build step the otherwise
no-build site
4 // has. Run on demand (`npm run copy:locales`) or automatically before deploy
(`predeploy`).
5 //
6 // The committed copy under site/public/locales/ is what actually ships (static hosts
serve it with
7 // no build); the drift-guard test (src/locales-drift.test.js) fails CI if it goes stale

```

```

vs /locales.
8 import { cpSync, rmSync, mkdirSync, readdirSync } from "node:fs";
9 import { join } from "node:path";
10
11 const SRC = join(import.meta.dirname, "..", "..", "locales");
12 const DEST = join(import.meta.dirname, "..", "public", "locales");
13
14 rmSync(DEST, { recursive: true, force: true });
15 mkdirSync(DEST, { recursive: true });
16 cpSync(SRC, DEST, { recursive: true });
17
18 console.log(`copy-locales: ${readdirSync(DEST).join(", ")} -> site/public/locales/`);
19

```

#### 199. assistant (2026-07-04T03:14:38.995Z)

Simple mirror copy. Let me run it and verify the drift test passes:

#### 200. user (2026-07-04T03:14:41.766Z)

```

copy-locales: da, en, es, hi, id, kn -> site/public/locales/
=== drift test ===
? tests 1
? pass 1
? fail 0

```

#### 201. assistant (2026-07-04T03:14:49.217Z)

Drift test passes. Let me check exactly what the CI `site` job runs (so I verify the right command) and see the resulting diff:

#### 202. user (2026-07-04T03:14:51.543Z)

```

=== site job in test.yml ===
8: site:
9- runs-on: ubuntu-latest
10- defaults:
11- run:
12- working-directory: site
13- steps:
14- - uses: actions/checkout@v7
15- - uses: actions/setup-node@v6
16- with:
17- node-version: "24" # node:sqlite is unflagged; server.test.js boots the VM host
18- cache: "npm"
19- cache-dependency-path: site/package-lock.json
20- # jsdom is a TEST-ONLY devDep (the behavioral landing-page UX tests run the real inline
21- # script in a DOM); the Cloudflare Worker + VM-host RUNTIMES stay dependency-free. `npm
test`
22- # runs ALL paths: Worker+D1 logic (index.test.js), the booted VM host (server.test.js),
the
23- # static content contract (assets.test.js), and the UX behaviour (ux.dom.test.js).
24- - run: npm ci
25- - run: npm test
26- # Syntax-check the ops shell scripts (provision/teardown/smoke/parity) so a broken
27- # script can't ship to the runbook. `bash -n` parses without executing.
28- - name: shell scripts parse-check
=== git diff stat (site mirror) ===
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json

```

### 203. assistant (2026-07-04T03:15:10.807Z)

The `site` job runs `npm ci && npm test` (`node --test` over all `\*.test.js`). The 6 mirror files are updated. The drift test (the exact blocker) passes. Let me run the full site suite to confirm nothing else regressed ? checking deps/node first:

### 204. user (2026-07-04T03:15:12.495Z)

v26.1.0  
node\_modules: MISSING

### 205. user (2026-07-04T03:15:23.566Z)

8 packages are looking for funding  
run `npm fund` for details

```
found 0 vulnerabilities
=== FULL SITE TEST SUITE (npm test) ===
? site/public/locales mirrors repo-root /locales exactly (else: npm run copy:locales)
(20.7089ms)
? [VM host] server.js serves the form (251.3838ms)
? [VM host] serves /capture and /og.png (6.4479ms)
? [VM host] serves the tool screencast as video/mp4 (plays in the post-signup reveal) (3.5527ms)
? [VM host] serves /own-model (9.4989ms)
? [VM host] serves /privacy as a clean URL (parity with Cloudflare asset html-handling)
(4.7156ms)
? [VM host] serves the academy flyers (/flyer, /flyer-kn, /flyer-hi) as clean URLs (8.6815ms)
? [VM host] POST /api/request-access persists to SQLite (17.1367ms)
? [VM host] honeypot + bad email are rejected without persisting (6.0375ms)
? [VM host] GET /api/request-access -> 405 (1.1479ms)
? [VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page (3.5716ms)
? [VM host · N8] ?lang= overrides the browser language (2.8013ms)
? [VM host · N8] the persisted cookie beats Accept-Language (returning user keeps their choice)
(1.6577ms)
? [VM host · N8] the Privacy Policy localizes too (es browser -> es-rendered /privacy)
(1.7574ms)
? [VM host · N8] unsupported/absent language falls back to en (never a locale we can't serve)
(3.5066ms)
? [VM host · N8] non-localized assets are NOT rewritten (only the localized marketing pages
negotiate) (1.5096ms)
? [VM host] serves the shared catalogs the shim fetches (/locales/*/common.json as JSON)
(1.9811ms)
? submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?') (380.8325ms)
? on failure the button is restored ? never stuck on a frozen 'Sending?' (81.2942ms)
? after sign-up BOTH videos appear and a ? closes the reveal (67.2421ms)
? A2: after sign-up the reveal offers a WhatsApp share of the reel (wa.me, safe, localizable)
(81.5993ms)
? the auto-close HOLDS while the reel is playing (no mid-watch cut-off) (65.7126ms)
? tests 95
? suites 0
? pass 95
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 2433.0857
```

### 206. assistant (2026-07-04T03:15:32.990Z)

Full site suite is green (95 tests, 0 fail). Let me commit the regenerated mirror and push. Re-verifying branch safety first:

### 207. user (2026-07-04T03:15:38.841Z)

HEAD:  
00109b8 Address review: supersede race + threshold display collision  
origin/master:  
b0f70a5 Show failed ingest verdict reasons  
=== stage + commit ===  
M site/public/locales/da/common.json  
M site/public/locales/en/common.json  
M site/public/locales/es/common.json  
M site/public/locales/hi/common.json  
M site/public/locales/id/common.json  
M site/public/locales/kn/common.json

#### 208. user (2026-07-04T03:15:48.927Z)

[claude/zealous-pike-7d0a85 c5abf0d] Resync site/public/locales mirror with /locales (fixes site CI)  
6 files changed, 42 insertions(+)  
c5abf0d Resync site/public/locales mirror with /locales (fixes site CI)  
00109b8 Address review: supersede race + threshold display collision  
76b97ed Add "how do I trim it?" help to the oversized-upload guard  
0969059 Guard oversized uploads client-side in the ingest SPA  
To <https://github.com/avidullu/khelsutra.git>  
00109b8..c5abf0d claude/zealous-pike-7d0a85 -> claude/zealous-pike-7d0a85

#### 209. assistant (2026-07-04T03:15:54.567Z)

Pushed as `c5abf0d`. Let me reply to the reviewer's comment confirming the fix, then watch CI re-run:

#### 210. user (2026-07-04T03:16:00.411Z)

<https://github.com/avidullu/khelsutra/pull/153#issuecomment-4880462211>

#### 211. assistant (2026-07-04T03:16:05.184Z)

Comment posted. Let me check whether CI has picked up the new commit:

#### 212. user (2026-07-04T03:16:07.802Z)

Workers Builds: hidden-king-khelsutra pending 0  
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/9eebb848-1692-481c-8918-f679243e719a>  
layout pending 0  
<https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318725>  
site pending 0  
<https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318730>  
web pending 0  
<https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318731>

#### 213. assistant (2026-07-04T03:16:23.735Z)

CI is running on the new commit. Let me watch until the checks complete (the `site` job is fast; `web` takes ~2 min):

#### 214. user (2026-07-04T03:18:09.341Z)

Workers Builds: hidden-king-khelsutra pass 0  
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/9eebb848-1692-481c-8918-f679243e719a>  
site pass 19s  
<https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318730>  
web pending 0  
<https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318731>  
layout pass 1m17s

```
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318725
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9eebb848-1692-481c-8918-f679243e719a
layout pass 1m17s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318725
site pass 19s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318730
web pass 2m1s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318731
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9eebb848-1692-481c-8918-f679243e719a
layout pass 1m17s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318725
site pass 19s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318730
web pass 2m1s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318731
```

#### 215. assistant (2026-07-04T03:18:20.044Z)

All four checks are now green: `**`site` ? (19s)**`, ``web` ? (2m1s)`, ``layout` ?`, Cloudflare deploy `?`.

#### What the latest comments said, and what I did

The two inline code findings were already resolved in my prior commit ? the reviewer confirmed at 03:12: `"the supersede-abort change and the threshold-formatting follow-up both look good."` But they flagged a `**remaining CI blocker**` I had missed:

`**The `site` job was red.**` The marketing site ships a byte-identical mirror of the locale catalogs under ``site/public/locales/*``, guarded by ``src/locales-drift.test.js``. I'd edited the source ``/locales/*/common.json`` (the ``fileTooLarge`` + trim-help strings) across three commits but never re-ran the copy step ? so the mirror had drifted:

```
> `site/public/locales/da/common.json drifted from /locales/da ? run npm run copy:locales`
```

`**Fix (commit `c5abf0d`):**` ran ``npm run copy:locales`` from ``site/`` and committed the 6 regenerated mirror files. Verified locally ? the drift test passes and the full site suite is green (95/95). I replied to the reviewer's comment confirming the fix.

CI has since re-run on the new head and `**all four checks pass**`. The PR is now green end-to-end, with both original code findings addressed and confirmed by the reviewer.

One honest note: this drift was my miss from the very first commit ? the repo has a single-source-of-truth convention for locales with a build step (``copy:locales``) I should have run as soon as I touched ``/locales``. Good to have the guardrail; I've now internalized that any ``/locales`` edit in this repo needs the mirror resync.

#### 216. user (2026-07-04T03:33:59.715Z)

merge the PR

#### 217. assistant (2026-07-04T03:34:09.848Z)

The user explicitly asked me to merge. Let me first verify the PR is in a clean mergeable state (checks green, no conflicts, no requested changes) before merging.

#### 218. user (2026-07-04T03:34:16.934Z)

```
{"base":"master","head":"claude/zealous-pike-7d0a85","mergeStateStatus":"CLEAN","mergeable":"MERGEABLE","reviewDecision":"","state":"OPEN","title":"Guard oversized uploads client-side in the ingest SPA","url":"https://github.com/avidullu/khelsutra/pull/153"}
```



```
=== latest checks ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9eebb848-1692-481c-8918-f679243e719a
layout pass 1m17s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318725
site pass 19s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318730
web pass 2m1s
https://github.com/avidullu/khelsutra/actions/runs/28693249780/job/85098318731
=== allowed merge methods ===
{"delete_branch_on_merge":false,"merge":true,"rebase":true,"squash":true}
```

#### 219. assistant (2026-07-04T03:34:37.533Z)

PR is **CLEAN** and **MERGEABLE**, all four checks pass, no requested changes blocking. The repo's history (`? (#151)``, `? (#149)``) shows a **squash-merge** convention. Let me do a final safety re-verify that only my commits are on the branch, then squash-merge:

#### 220. user (2026-07-04T03:34:41.667Z)

```
=== commits that will merge (origin/master..HEAD) ? must be ONLY mine ===
c5abf0d Resync site/public/locales mirror with /locales (fixes site CI)
00109b8 Address review: supersede race + threshold display collision
76b97ed Add "how do I trim it?" help to the oversized-upload guard
0969059 Guard oversized uploads client-side in the ingest SPA
=== origin/master ===
b0f70a5 Show failed ingest verdict reasons
```

#### 221. assistant (2026-07-04T03:34:46.659Z)

Confirmed ? only my 4 commits, ``origin/master`` unchanged at ``b0f70a5``, no sibling work. Squash-merging with a clean commit message:

#### 222. user (2026-07-04T03:34:56.830Z)

(Bash completed with no output)

#### 223. assistant (2026-07-04T03:34:59.687Z)

Let me confirm the merge landed:

#### 224. user (2026-07-04T03:35:04.678Z)

```
Unknown JSON field: "merged"
Available fields:
 additions
 assignees
 author
 autoMergeRequest
 baseRefName
 baseRefOid
 body
 changedFiles
 closed
 closedAt
 closingIssuesReferences
 comments
 commits
 createdAt
 deletions
 files
 fullDatabaseId
 headRefName
```

```
headRefOid
headRepository
headRepositoryOwner
id
isCrossRepository
isDraft
labels
latestReviews
maintainerCanModify
mergeCommit
mergeStateStatus
mergeable
mergedAt
mergedBy
milestone
number
potentialMergeCommit
projectCards
projectItems
reactionGroups
reviewDecision
reviewRequests
reviews
state
statusCheckRollup
title
updatedAt
url
```

=== origin/master now ===

383abd0 Guard oversized uploads client-side in the ingest SPA (#153)

b0f70a5 Show failed ingest verdict reasons

40853a7 Preserve video names in Studio (#151)

## 225. user (2026-07-04T03:35:11.281Z)

```
{"mergeCommit":"383abd01cc0102d8d6c1e30eb5ed1cc13cf119b0","mergedAt":"2026-07-04T03:34:56Z","mergedBy":"avidullu","state":"MERGED"}
```

## 226. assistant (2026-07-04T03:35:21.478Z)

Merged. ?

## PR #153 is merged

```
- **State:** `MERGED` at 2026-07-04 03:34 UTC
- **Squash commit:** [383abd0`](https://github.com/avidullu/khelsutra/commit/383abd01cc0102d8d6c1e30eb5ed1cc13cf119b0) ? "Guard oversized uploads client-side in the ingest SPA (#153)" ? now the tip of `master`, cleanly on top of `b0f70a5` (no sibling work absorbed).
- **Merge method:** squash, matching the repo's `?` (#NNN`) convention.
```

Before merging I verified: all four checks green (``web``, ``site``, ``layout``, Cloudflare deploy), ``mergeStateStatus: CLEAN``, ``mergeable: MERGEABLE``, no requested-changes blocking, and that ``origin/master..HEAD`` contained only my four commits.

## What shipped

An instant client-side oversized-upload guard for the ingest SPA ? a file over the engine's cap fails before any network round-trip, with a localized message and a keyboard-accessible `***How do I trim it?***` disclosure (phone/computer steps for a coach, plus the advanced ``scripts/chunk_video.py`` / Google Drive route), all inline so it works air-gapped. Includes the two review fixes (stop-first supersede race, comparison-aware threshold formatting) and the resynced ``site/public/locales`` mirror.

A couple of notes for cleanup: the remote branch ``claude/zealous-pike-7d0a85`` still exists (the repo doesn't auto-delete on merge, and I avoided ``--delete-branch`` since we're sitting in its

worktree) ? you can delete it whenever you retire this worktree. And this session's local branch is now behind `master`; nothing more to do here since the work is merged.