

claude-windows / 2ba49afa-99f4-41f2-86a2-27a289d432f3

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_cd064e9b-e5c\agent-aca5241d92b26cf53.jsonl`  
- SHA-256: `039073c7d809313251fe38800f9ebcde2ed0b54fa2d2e4f94987abda363a6807`  
- Source modified: `2026-06-21T15:01:03+00:00`  
- Imported at: `2026-07-05T16:48:28+00:00`  
- project: `wf_cd064e9b-e5c`  
- session_id: `2ba49afa-99f4-41f2-86a2-27a289d432f3`
```

Transcript

1. user (2026-06-21T14:58:28.031Z)

You are checking a UI diff against the A4 spec: "Mobile-first touch targets + tooltip-text -> visible (SPA)". The ticket names files QueryBar, RallyGrid, SelectionFooter, IngestPanel, CompileResult, LanguageSwitcher + index.css; goals: >=44px tap targets, enlarge the tiny query parsed-pill + sample chips, surface title= tooltips as visible text on phones (phones have no hover, so title= never shows).

Read C:/Users/avidu/Projects/khelsutra/web/src/components/QueryBar.tsx and C:/Users/avidu/Projects/khelsutra/web/src/components/RallyGrid.tsx. The diff adds a VISIBLE help line in QueryBar for the "not available yet" tokens. BUT RallyGrid.tsx still has a title= on the shot-count chip (grid.shotsTitle: "experimental, may be inaccurate, confidence, filter by length") that is hover-only. The visible chip shows "~N shots · experimental".

Question to judge: is leaving RallyGrid's title hover-only an acceptable A4 gap (because the essential "experimental" warning IS visible and "filter by length" is in query.support), or is there hover-only info (e.g. the per-card confidence value) that a phone user genuinely loses and should be surfaced? Give a concrete, minimal recommendation. Also flag any OTHER hover-only title= in the changed surfaces. Be precise. Empty findings if you judge it acceptable.

```
=== THE DIFF UNDER REVIEW ===  
undefined
```

2. assistant (2026-06-21T14:58:32.061Z)

I'll review the two files against the A4 spec to judge whether RallyGrid's hover-only title is an acceptable gap and check for other hover-only title= attributes.

3. user (2026-06-21T14:58:33.054Z)

```
1      // The fast-entry query bar (PER_RALLY_SELECTION.md P3). A deterministic, OFFLINE parser  
turns  
2      // plain text ("top 15 longest", "over 10s") into a selection over the SAME shared set  
the  
3      // checkboxes use. It is honest by construction: a live "parsed-pill" shows exactly how  
the  
4      // text was understood, and concepts with no data behind them (shot-type / player /  
score) are  
5      // greyed out as "not available yet" ? never silently faked.  
6      import { useMemo, useState } from "react";  
7      import type { FormEvent } from "react";  
8      import { useTranslation, Trans } from "react-i18next";  
9      import { parseQuery, summarize } from "../lib/query";  
10     import type { ParsedQuery } from "../lib/query";  
11  
12     interface Props {
```

```

13      /** Apply a parsed query to the rally set (App runs runQuery + writes the shared
14      selection).
15      * `source` distinguishes a typed-and-submitted query from an example-chip tap (for
16      the trace). */
17      onApply: (q: ParsedQuery, source: "typed" | "example") => void;
18      }
19
20      // Each example is a real, parseable query ? tapping one fills the box AND applies it.
21      Led by rally
22      // LENGTH (the trusted axis); shot-count filtering exists but is experimental, so it's
23      not featured
24      // here (a test pins that every example parses to a recognized, fully-available query).
25      export const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "first 10"];
26
27      // Parsed-pill chips: legible on a phone (text-sm, not text-xs) ? A4.
28      const CHIP = "rounded-full px-3 py-1 text-sm font-medium";
29
30      export function QueryBar({ onApply }: Props) {
31        const { t } = useTranslation();
32        const [value, setValue] = useState("");
33        const parsed = useMemo(() => parseQuery(value), [value]);
34        const clauses = summarize(parsed);
35        const typed = value.trim().length > 0;
36
37        const applyText = (text: string) => {
38          setValue(text);
39          onApply(parseQuery(text), "example");
40        };
41
42        const submit = (e: FormEvent) => {
43          e.preventDefault();
44          if (parsed.recognized) onApply(parsed, "typed");
45        };
46
47        return (
48          <div>
49            <form onSubmit={submit} className="flex flex-wrap items-center gap-2">
50              <input
51                type="text"
52                value={value}
53                onChange={(e) => setValue(e.target.value)}
54                placeholder={t("query.placeholder")}
55                aria-label={t("query.ariaLabel")}
56                className="min-h-11 min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-
57                white px-4 py-2 text-sm text-ink outline-none focus:border-green"
58              />
59              <button
60                type="submit"
61                disabled={!parsed.recognized}
62                className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-
63                white disabled:opacity-40"
64              >
65                {t("query.apply")}
66              </button>
67            </form>
68
69            {/* Live interpretation ? transparent + hand-correctable (no hidden NL guessing).
70            */}
71
72            <div aria-live="polite" data-testid="query-pill" className="mt-2 flex flex-wrap
73            items-center gap-1.5">
74              {clauses.map((c) => (
75                <span key={c} className={CHIP + " bg-green/15 text-green">
76                  {c}
77                </span>
78              ))}
79              {parsed.unavailable.map((u) => (

```

```

70         <span
71             key={u.token}
72             title={t("query.notAvailableTitle", { token: u.token, kind: u.kind })}
73             className={CHIP + " bg-black/5 text-ink/45"}
74         >
75             <span className="line-through">{u.token}</span> · {t("query.notAvailable")}
76         </span>
77     )}}
78     {typed && !parsed.recognized && parsed.unavailable.length === 0 && (
79         <span className="text-xs text-ink/50">{t("query.unreadable")}</span>
80     )}
81     {!typed && <span className="text-xs text-ink/50">{t("query.hint")}</span>}
82 </div>
83
84     {/* Surface the "not available yet" reason as VISIBLE text (the per-chip title is
hover-only,
85         so it never appears on a phone) ? A4. */}
86     {parsed.unavailable.length > 0 && (
87         <p className="mt-1.5 text-xs text-ink/50">{t("query.notAvailableHelp")}</p>
88     )}
89
90     <div className="mt-3 flex flex-wrap items-center gap-2 text-sm">
91         <span className="text-ink/40">{t("query.try")}</span>
92         {EXAMPLES.map((ex) => (
93             <button
94                 key={ex}
95                 type="button"
96                 onClick={() => applyText(ex)}
97                 className="inline-flex min-h-11 items-center rounded-full border border-
black/15 px-4 text-sm hover:border-green"
98             >
99                 {ex}
100             </button>
101         )}}
102     </div>
103
104     <p className="mt-2 text-xs text-ink/40">
105         <Trans i18nKey="query.support" components={{ b: <strong className="text-ink/60"
/>, x: <span className="text-amber-700" /> }} />
106     </p>
107 </div>
108 );
109 }
110

```

4. user (2026-06-21T14:58:33.119Z)

```

1     // The selectable rally grid ? one card per play_segment, HONEST fields only:
2     // ordinal (by start order), mm:ss start, and rally LENGTH (the trusted axis). A shot-
count chip
3     // is shown ONLY when present, and clearly flagged EXPERIMENTAL ? shot detection is
still under
4     // development and not yet reliable, so length is what we lead with (owner 2026-06-20).
5     // Never renders server/receiver/events (motion-only fabrications,
PER_RALLY_SELECTION.md §4).
6     import { useTranslation } from "react-i18next";
7     import type { RallySegment } from "../api/types";
8     import { mmss } from "../lib/format";
9
10    interface Props {
11        rallies: RallySegment[];
12        isSelected: (id: number) => boolean;
13        onToggle: (id: number) => void;
14        /** Stable chronological label for a rally (by start_time), so re-sorting via a query
15        * doesn't renumber the cards. Falls back to display position when absent. */

```

```

16     ordinalOf?: (id: number) => number;
17 }
18
19 export function RallyGrid({ rallies, isSelected, onToggle, ordinalOf }: Props) {
20     const { t } = useTranslation();
21     if (rallies.length === 0) {
22         return <p className="text-ink/60 text-sm">{t("grid.empty")}</p>;
23     }
24     return (
25         <ul className="grid grid-cols-[repeat(auto-fill,minmax(150px,1fr))] gap-3 list-none
p-0 m-0">
26             {rallies.map((r, i) => {
27                 const selected = isSelected(r.id);
28                 const n = ordinalOf ? ordinalOf(r.id) : i + 1;
29                 const shot = r.metadata?.shot_count;
30                 const conf = r.metadata?.shot_count_confidence;
31                 return (
32                     <li key={r.id}>
33                         <button
34                             type="button"
35                             onClick={() => onToggle(r.id)}
36                             aria-pressed={selected}
37                             aria-label={t(selected ? "grid.inReel" : "grid.notInReel", { n })}
38                             className={
39                                 "w-full text-left rounded-xl border p-3 transition " +
40                                 (selected
41                                     ? "border-green bg-green/10"
42                                     : "border-black/10 bg-white hover:border-green/60")
43                             }
44                         >
45                             <div className="flex items-center justify-between">
46                                 <span className="font-semibold text-ink">{t("grid.rally", { n })}</span>
47                                 <span
48                                     aria-hidden="true"
49                                     className={
50                                         "inline-flex h-5 w-5 items-center justify-center rounded-full text-
xs " +
51                                         (selected ? "bg-green text-[#04140D]" : "border border-black/20
text-transparent")
52                                     }
53                                 >
54                                     ?
55                                 </span>
56                             </div>
57                             <div className="mt-1 text-sm text-ink/70">
58                                 {mmss(r.start_time)} <span className="text-
ink/40">{t("grid.start")}</span> · <strong className="text-ink/90">{mmss(r.duration)}</strong>
59                                 <span className="text-ink/40">{t("grid.long")}</span>
60                             </div>
61                             {typeof shot === "number" && (
62                                 <div
63                                     title={t("grid.shotsTitle", {
64                                         conf: conf && conf !== "Unknown" ? t("grid.shotsConfidence", { conf
65                                         }) : "",
66                                     })}
67                                     className="mt-2 inline-block rounded-full bg-amber-50 px-2 py-0.5
text-xs text-amber-700"
68                                 >
69                                     {t("grid.shots", { count: shot })}
70                                 </div>
71                             )}
72                         </button>
73                     </li>
74                 );
75             })}

```

```
74         </ul>
75     );
76 }
77
```

5. assistant (2026-06-21T14:58:39.596Z)

Both files are read. Let me verify the i18n strings to confirm exactly what is visible versus hover-only, particularly `grid.shotsTitle`, `grid.shots`, `query.support`, and `query.notAvailableHelp`.

6. user (2026-06-21T14:58:41.213Z)

No matches found

7. user (2026-06-21T14:58:44.604Z)

```
web\src\i18n\locales\en\common.json
web\src\i18n\locales\kn\common.json
web\src\i18n\locales\hi\common.json
```

8. user (2026-06-21T14:58:44.650Z)

```
web\node_modules\js-tokens\package.json
web\node_modules\lru-cache\package.json
web\node_modules\stackback\package.json
web\node_modules\@rollup\rollup-win32-x64-gnu\package.json
web\node_modules\@rollup\rollup-win32-x64-msvc\package.json
web\node_modules\ms\package.json
web\node_modules\convert-source-map\package.json
web\node_modules\pathval\package.json
web\node_modules\@jridgewell\resolve-uri\package.json
web\node_modules\assertion-error\package.json
web\node_modules\check-error\package.json
web\node_modules\tinyspy\package.json
web\node_modules\deep-eql\package.json
web\node_modules\@babel\helper-globals\data\browser-upper.json
web\node_modules\yallist\package.json
web\node_modules\@types\babel__generator\package.json
web\node_modules\@types\babel__template\package.json
web\node_modules\picocolors\package.json
web\node_modules\siginfo\package.json
web\node_modules\@types\deep-eql\package.json
web\node_modules\escalade\package.json
web\node_modules\lightningcss-win32-x64-msvc\package.json
web\node_modules\@types\babel__core\package.json
web\node_modules\jsesc\package.json
web\node_modules\strip-literal\package.json
web\node_modules\fdir\package.json
web\node_modules\@babel\helper-globals\data\builtin-lower.json
web\node_modules\@types\estree\package.json
web\node_modules\@types\babel__traverse\package.json
web\node_modules\std-env\package.json
web\node_modules\cac\package.json
web\node_modules\@babel\compat-data\data\corejs2-built-ins.json
web\node_modules\@babel\helper-plugin-utils\package.json
web\node_modules\tinyglobby\package.json
web\node_modules\graceful-fs\package.json
web\node_modules\node-releases\data\processed\envs.json
web\node_modules\semver\package.json
web\node_modules\why-is-node-running\package.json
web\node_modules\@babel\code-frame\package.json
web\node_modules\@babel\helper-string-parser\package.json
web\node_modules\update-browserslist-db\package.json
```

```

web\node_modules\@babel\helper-globals\data\builtin-upper.json
web\node_modules\tinyrainbow\package.json
web\node_modules\@vitest\spy\package.json
web\node_modules\node-releases\package.json
web\node_modules\gensync\package.json
web\node_modules\tinybench\package.json
web\node_modules\tinyexec\package.json
web\node_modules\@babel\compat-data\data\corejs3-shipped-proposals.json
web\node_modules\@babel\helper-globals\package.json
web\node_modules\esbuild\package.json
web\node_modules\debug\package.json
web\node_modules\estree-walker\package.json
web\node_modules\@tailwindcss\vite\package.json
web\node_modules\@tailwindcss\oxide\package.json
web\node_modules\@babel\compat-data\data\native-modules.json
web\node_modules\browserslist\package.json
web\node_modules\es-module-lexer\package.json
web\node_modules\node-releases\data\release-schedule\release-schedule.json
web\node_modules\@jridgewell\source-map-codec\package.json
web\node_modules\@jridgewell\gen-mapping\package.json
web\node_modules\@types\chai\package.json
web\node_modules\@vitest\expect\package.json
web\node_modules\@vitest\pretty-format\package.json
web\node_modules\expect-type\package.json
web\node_modules\detect-libc\package.json
web\node_modules\pathe\package.json
web\node_modules\@babel\compat-data\data\overlapping-plugins.json
web\node_modules\@babel\plugin-transform-react-jsx-source\package.json
web\node_modules\@jridgewell\remapping\package.json
web\node_modules\strip-literal\node_modules\js-tokens\package.json
web\node_modules\@rollup\pluginutils\package.json
web\node_modules\@vitest\snapshot\package.json
web\node_modules\@babel\compat-data\data\plugin-bugfixes.json
web\node_modules\@babel\helper-validator-option\package.json
web\node_modules\@tailwindcss\node\package.json
web\node_modules\electron-to-chromium\chromium-versions.json
web\node_modules\magic-string\package.json
web\node_modules\@babel\helper-validator-identifier\package.json
web\node_modules\@vitest\runner\package.json
web\node_modules\picomatch\package.json
web\node_modules\baseline-browser-mapping\package.json
web\node_modules\@babel\compat-data\data\plugins.json
web\node_modules\csstype\package.json
web\node_modules\electron-to-chromium\full-chromium-versions.json
web\node_modules\tinypool\package.json
web\node_modules\@babel\helper-module-imports\package.json
web\node_modules\@types\react-dom\package.json
web\node_modules\electron-to-chromium\full-versions.json
web\node_modules\react-refresh\package.json
web\node_modules\@vitejs\plugin-react\package.json
web\node_modules\@babel\compat-data\package.json
web\node_modules\@jridgewell\trace-mapping\package.json
web\node_modules\electron-to-chromium\package.json
web\node_modules\electron-to-chromium\versions.json
web\node_modules\@tailwindcss\oxide-win32-x64-msvc\package.json
web\node_modules\json5\package.json
web\node_modules\@vitest\utils\package.json
web\node_modules\vite-node\package.json
web\node_modules\@babel\plugin-transform-react-jsx-self\package.json
(Results are truncated. Consider using a more specific path or pattern.)

```

9. user (2026-06-21T14:58:48.706Z)

```

1      {
2      "app": {

```

```

3      "badge": "pick your rallies · alpha",
4      "title": "Pick the rallies for your reel",
5      "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-
tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want."
6  },
7  "lang": {
8      "label": "Language",
9      "en": "English",
10     "kn": "?????",
11     "hi": "?????"
12 },
13 "bulk": {
14     "selectAll": "Select all",
15     "clear": "Clear",
16     "invert": "Invert"
17 },
18 "mode": {
19     "demo": "These are sample rallies ? process a video above to work on a real match.",
20     "loading": "Finding the rallies in your video?",
21     "error": "Couldn't load this video's rallies: {error}",
22     "loaded": "Found <b>{count}</b> rallies in your video."
23 },
24 "query": {
25     "placeholder": "e.g. over 10s · top 15 longest · shortest first",
26     "arialLabel": "Filter rallies by length, count or order",
27     "apply": "Apply",
28     "notAvailable": "not available yet",
29     "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
30     "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by
rally length instead.",
31     "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
32     "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
33     "try": "Sample queries:",
34     "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
<x>experimental</x> (under development)."
35 },
36 "grid": {
37     "empty": "No rallies to show yet.",
38     "rally": "Rally {n}",
39     "inReel": "Rally {n}, in reel",
40     "notInReel": "Rally {n}, not in reel",
41     "start": "start",
42     "long": "long",
43     "shots": "~{count} shots · experimental",
44     "shotsTitle": "Shot count is experimental (under development) and may be
inaccurate{conf}. Filter by rally length instead.",
45     "shotsConfidence": " ? confidence: {conf}"
46 },
47 "footer": {
48     "count": "{count, plural, one {# rally} other {# rallies}}",
49     "summaryRest": "selected · {total} total",
50     "reelName": "Reel name",
51     "reelNamePlaceholder": "my-highlights",
52     "build": "Build reel ({count})",
53     "building": "Building?",
54     "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
be skipped, so the build would fail. Pick a longer rally.",
55     "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
they'd all be skipped, so the build would fail. Pick longer rallies.",
56     "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",
57     "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
58 },
59 "result": {
60     "ready": "Your reel is ready",

```

```

61         "failed": "Build failed",
62         "dismiss": "Dismiss",
63         "download": "Download {filename}"
64     },
65     "build": {
66         "noVideo": "These are sample rallies ? process a real video first to build a reel."
67     },
68     "ingest": {
69         "title": "Process a video",
70         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
71         "uriPlaceholder": "gs://your-bucket/match.mp4",
72         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
73         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
74         "submit": "Process video",
75         "submitting": "Submitting?",
76         "cancel": "Cancel",
77         "working": "Processing your video?",
78         "progress": "{progress}",
79         "retry": "Try again",
80         "failed": "Couldn't process the video: {error}",
81         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
82         "networkError": "Can't reach KhelSutra. Is it running?",
83         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
84         "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again."
85     },
86     "selection": {
87         "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
88     }
89 }
90

```

10. assistant (2026-06-21T14:58:56.144Z)

Now I have the full picture. Let me analyze the `grid.shotsTitle` content versus what is visible.

The hover-only `title` on the shot chip is:

```
> "Shot count is experimental (under development) and may be inaccurate{conf}. Filter by rally
length instead." where `{conf}` = " ? confidence: {conf}".
```

The visible chip text (`grid.shots`) is: `~{count} shots · experimental`.

Let me decompose what's in the title vs. visible elsewhere:

1. `***experimental / under development***` ? visible on the chip ("experimental") and in `query.support` ("Shot-count is experimental (under development)"). Covered.
2. `***may be inaccurate***` ? implied by "experimental"; the explicit caveat is reasonably conveyed. Acceptable.
3. `***Filter by rally length instead***` ? present in `query.support` and `app.intro`. Covered.
4. `***confidence: {conf}***` ? the per-card confidence value (`shot\_count\_confidence`). This is the ONLY piece of information that exists per-card, is genuinely unique to that card, and appears NOWHERE in visible text. A phone user loses it entirely.

Let me check the other changed surfaces for any other hover-only `title=` attributes.

11. user (2026-06-21T14:58:57.885Z)

```
web\src\components\A4.touch.test.tsx:8://      surfaces `title=`, so the explanation must render
in the DOM for a phone user to read it.
web\src\components\RallyGrid.tsx:62:      title={t("grid.shotsTitle", {
```



```
web\src\components\QueryBar.tsx:72:           title={t("query.notAvailableTitle", { token:
u.token, kind: u.kind })}}
```

12. assistant (2026-06-21T14:59:01.650Z)

Only two `title=` attributes exist in the changed component surfaces: the QueryBar one (now mitigated by the new visible help line) and the RallyGrid `shotsTitle` one. Let me verify the test file to understand what the A4 contract considers covered, and check the QueryBar `query.support` line truly carries the "filter by length" guidance visibly.

13. user (2026-06-21T14:59:01.978Z)

```
1      // @vitest-environment jsdom
2      //
3      // A4 ? non-tech-savvy mobile UX. Two guarantees a phone user depends on:
4      //   1. TOUCH TARGETS ? 44px (WCAG 2.5.5 / platform HIG) on every primary control ?
pinned via the
5      //       Tailwind min-h-11 (=2.75rem=44px) / h-11 class so a future "tighten the padding"
can't
6      //       silently shrink a tap target below the floor.
7      //   2. The "not available yet" REASON is VISIBLE text, not a hover-only title ? a touch
device never
8      //       surfaces `title=`, so the explanation must render in the DOM for a phone user to
read it.
9      import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
10     import { render, screen, cleanup, fireEvent } from "@testing-library/react";
11     import i18n from "../i18n/index";
12     import App from "../App";
13     import { QueryBar } from "../QueryBar";
14
15     // 44px floor: min-h-11 (buttons/inputs) or an explicit h-11 square (the ? dismiss).
16     const TAP_44 = /\b(?:min-h-11|h-11)\b/;
17
18     beforeEach(async () => {
19       vi.stubGlobal("fetch", vi.fn(() => Promise.reject(new Error("no engine in test"))));
20       window.localStorage.clear();
21       await i18n.changeLanguage("en");
22     });
23
24     afterEach(() => {
25       cleanup();
26       vi.unstubAllGlobals();
27     });
28
29     describe("A4: touch targets ? 44px on primary controls", () => {
30       it("the always-visible buttons carry a ?44px tap class", () => {
31         render(<App />);
32         for (const name of [
33           "Select all",
34           "Clear",
35           "Invert",
36           "Apply", // QueryBar submit
37           "Process video", // IngestPanel submit
38           "English", // LanguageSwitcher
39           "?????",
40           "???????",
41         ]) {
42           const btn = screen.getByRole("button", { name });
43           expect(btn.className, `${name} must be ?44px`).toMatch(TAP_44);
44         }
45         // The Build button label includes the live selection count ("Build reel (6)").
46         expect(screen.getByRole("button", { name: /Build reel/
}).className).toMatch(TAP_44);
47       });
48     });
```

```

49     it("the text inputs carry a ?44px tap class", () => {
50         render(<App />);
51         expect(screen.getByRole("textbox", { name: "Filter rallies by length, count or
order" })).className().toMatch(TAP_44);
52         expect(screen.getByRole("textbox", { name: "Reel name"
53         })).className().toMatch(TAP_44);
54         expect(
55             screen.getByRole("textbox", { name: "Video location ? a gs:// bucket URL or a path
on the engine host" })).className,
56             ).toMatch(TAP_44);
57     });
58     it("the sample-query chips are tappable (?44px)", () => {
59         render(<App />);
60         expect(screen.getByRole("button", { name: "over 10s" })).className().toMatch(TAP_44);
61         expect(screen.getByRole("button", { name: "top 15 longest"
62         })).className().toMatch(TAP_44);
63     });
64
65     describe("A4: the 'not available yet' reason is visible, not hover-only", () => {
66         const HELP = "Shot type, players and score aren't available yet ? filter by rally
length instead.";
67
68         it("hidden until an unsupported concept is typed, then shown as plain text", () => {
69             render(<QueryBar onApply={() => {}} />);
70             expect(screen.queryByText(HELP)).toBeNull(); // nothing typed ? no help line
71             fireEvent.change(screen.getByRole("textbox", { name: "Filter rallies by length,
count or order" })), {
72                 target: { value: "smashes" }, // a shot-type token ? flagged "not available yet"
73             });
74             expect(screen.getByText(HELP)).toBeTruthy(); // the reason is now a visible DOM node
75         });
76     });
77

```

14. assistant (2026-06-21T14:59:12.507Z)

I now have everything needed for a precise judgment.

My analysis confirms:

1. **The QueryBar fix is correct and tested** ? the new visible help line (``query.notAvailableHelp``) surfaces the "not available yet" reason in the DOM, validated by ``a4.touch.test.tsx``. The remaining ``title=`` on the QueryBar chip (line 72) is now redundant decoration, not load-bearing. Acceptable.
2. **RallyGrid's ``shotsTitle`` is mostly redundant** with visible text:
 - "experimental / under development" ? visible on the chip (``experimental``) and in ``query.support``.
 - "may be inaccurate" ? adequately implied by "experimental".
 - "Filter by rally length instead" ? present visibly in ``query.support`` and ``app.intro``.
3. **The one genuine loss**: the per-card ``confidence: {conf}`` value (``shot_count_confidence``). This is the only piece of information in the title that (a) is unique to each card, (b) is not a generic warning duplicated elsewhere, and (c) appears nowhere in visible text. A phone user loses it entirely. However ? it is *conditionally* rendered (only when ``conf`` exists and isn't "Unknown"), and it is a secondary detail on an already-experimental, de-emphasized chip. This is a real but minor gap, not a blocker.

Let me confirm whether ``shot_count_confidence`` is commonly populated, to right-size severity.

15. user (2026-06-21T14:59:13.683Z)

Found 4 files

```
web\src\App.tsx
docs\PER_RALLY_SELECTION.md
web\src\api\types.ts
web\src\components\RallyGrid.tsx
```

16. user (2026-06-21T14:59:17.134Z)

```
6- /** Gemini's shuttle_exchange_count (fallback max(3, dur/0.8)); absent on some detectors. */
7- shot_count?: number;
8- /** Gemini confidence STRING (often "Unknown") ? not a numeric meter. */
9- shot_count_confidence?: string;
10- detector?: string;
11- [key: string]: unknown;
12-}
```

17. assistant (2026-06-21T14:59:22.449Z)

This sharpens the severity. The type comment confirms `shot_count_confidence` is "often 'Unknown'", and the RallyGrid code already suppresses it when it's `"Unknown"` or falsy. So the confidence value is displayed in the title only in a minority of cases, and even then it's a coarse string (e.g. "High"/"Medium"/"Low"), not a precise meter. The information a phone user loses is therefore small and low-stakes.

I have enough to render a precise judgment.

18. user (2026-06-21T14:59:39.727Z)

Output does not match required schema: root: must have required property 'findings'

19. assistant (2026-06-21T14:59:42.966Z)

The schema requires both `summary` and `findings` at the top level. Let me resend with both properties.

20. user (2026-06-21T14:59:54.727Z)

Output does not match required schema: root: must have required property 'findings'

21. assistant (2026-06-21T14:59:58.281Z)

The error persists despite both fields being present. The `findings` array value may not be parsing as an array. Let me try passing `findings` as an actual structured array rather than a JSON string ? the issue may be that the harness is receiving it as a string literal.

22. user (2026-06-21T15:00:06.739Z)

Output does not match required schema: root: must have required property 'findings'

23. assistant (2026-06-21T15:00:11.009Z)

The validator keeps rejecting despite both top-level properties present. The issue may be that an empty-findings result is what the validator can cleanly accept, or there's a serialization quirk. Let me try a minimal shape first to isolate whether the `findings` array structure is the problem.

24. user (2026-06-21T15:00:15.285Z)

Output does not match required schema: root: must have required property 'findings'

25. assistant (2026-06-21T15:00:19.358Z)

Even an empty-array `findings` with `summary` is rejected, which means the validator isn't seeing my `findings` key at all ? the arguments are likely being mangled. This points to a

serialization issue with how the array is being transmitted. Let me try with `findings` as the first property in case ordering matters for the parser.

26. user (2026-06-21T15:00:19.754Z)

Structured output provided successfully

27. assistant (2026-06-21T15:00:23.748Z)

Property ordering was the issue ? `findings` must come first. Now I'll send the complete answer with `findings` first.

28. user (2026-06-21T15:00:38.382Z)

Output does not match required schema: root: must have required property 'summary'

29. assistant (2026-06-21T15:00:45.087Z)

Now it wants `summary` ? so the parser is keeping only the last-provided property when ordering is wrong, or it truncates. The successful call had `findings` first then `summary`. Let me send both with `findings` first and `summary` second, exactly as the working call but with full content.

30. user (2026-06-21T15:00:54.928Z)

Structured output provided successfully

31. assistant (2026-06-21T15:01:03.511Z)

Review complete. My judgment: leaving RallyGrid's `shotsTitle` hover-only is an **acceptable A4 gap**, with one **minor** caveat (not a blocker).

Key findings:

- The essential "experimental" warning IS visible on the chip (`grid.shots` = "~N shots . experimental") and in `query.support`; "filter by rally length" is visible in `query.support` and `app.intro`. So the generic warning is not lost on phones.
- The one genuinely-lost piece is the per-card **confidence** value (`shot\_count\_confidence` / `grid.shotsConfidence`) ? but it is low-stakes: `api/types.ts` line 8 notes it is "often Unknown", the code already suppresses it when "Unknown"/empty (lines 62-64), and it is a coarse string on a deliberately de-emphasized chip.
- Minimal fix: surface confidence as visible chip text when present (reusing the line-63 guard), mirroring the QueryBar visible-help pattern ? or document the omission in `PER\_RALLY\_SELECTION.md`.
- Other surfaces: the only other `title=` in the changed components is QueryBar line 72, which is now redundant given the new visible `notAvailableHelp` line (lines 86-88, pinned by `a4.touch.test.tsx`). No other hover-only `title=` exists in the changed surfaces.