

claude-windows / d4b5afb5-2f03-4b58-8952-573f1381d166

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\d4b5afb5-2f03-4b58-8952-573f1381d166\subagents\workflows\wf_beb40705-90b\agent-a695be801a1873676.jsonl`  
- SHA-256: `0c68f934bd8b4b94dd22354d1299602cbc0da3e19111ca360d2a92fe883dfd77`  
- Source modified: `2026-06-21T03:20:41+00:00`  
- Imported at: `2026-07-05T16:48:23+00:00`  
- project: `wf_beb40705-90b`  
- session_id: `d4b5afb5-2f03-4b58-8952-573f1381d166`
```

Transcript

1. user (2026-06-21T03:17:18.122Z)

You are mapping the KhelSutra marketing site/ (vanilla HTML + a dependency-free Node/SQLite server) so its copy can be (a) simplified for non-tech-savvy users and (b) localized to Kannada + Hindi via a tiny t(key,vars) shim + data-i18n over the HTML (sharing the same catalog format as the SPA).

Read fully: C:/Users/avidu/Projects/khelsutra/site/public/index.html,
C:/Users/avidu/Projects/khelsutra/site/public/capture.html,
C:/Users/avidu/Projects/khelsutra/site/public/own-model.html,
C:/Users/avidu/Projects/khelsutra/site/server.js,
C:/Users/avidu/Projects/khelsutra/site/src/{index.js,store.js,notify.js},
C:/Users/avidu/Projects/khelsutra/site/README.md. Skip *.test.js except to note coverage.

Produce a thorough markdown brief:

- The first-contact USER FLOW (homepage -> read -> request-access form -> submit -> post-signup reveal of tool screencast + 30s reel). Step by step.
- A near-COMPLETE INVENTORY of user-facing strings across the 3 HTML pages + the form labels/options + the reveal copy + any server-rendered text (validation messages, email body). Group by page/section. Give the count.
- How the HTML is structured today (any existing templating? inline strings? how a data-i18n + t() shim would attach with least churn).
- Whether the form/reveal JS is inline or in src/; where the t() shim would live so BOTH the SPA and the site can share catalogs.
- UX friction for a non-tech-savvy first-time visitor (jargon like "GPU"/"bucket"/"model", form length, unclear next step).
- Confirm there is NO framework and NO i18n today; state with evidence.

Return the brief as your final message. Exhaustive, faithful, file:line refs, no invention.

2. assistant (2026-06-21T03:17:20.597Z)

I'll map the KhelSutra marketing site. Let me start by reading all the specified files.

3. user (2026-06-21T03:17:21.386Z)

```
1      <!doctype html>  
2      <html lang="en">  
3      <head>  
4      <meta charset="utf-8" />  
5      <meta name="viewport" content="width=device-width, initial-scale=1" />  
6      <title>KhelSutra ? every rally indexed, the dead time gone</title>  
7      <meta name="description" content="KhelSutra turns a full badminton match into a clean  
index of rallies with the dead time stripped out ? a highlight reel you can watch and download.  
Invite-only alpha, Bengaluru." />  
8      <meta property="og:title" content="KhelSutra ? every rally indexed, the dead time gone"  
/>  
9      <meta property="og:description" content="A full match becomes a clean highlight reel ?  
only the real play, no dead time. Invite-only alpha for academies and players in Bengaluru." />
```

```

10     <meta property="og:type" content="website" />
11     <meta property="og:url" content="https://kheIsutra.guru" />
12     <meta property="og:image" content="https://kheIsutra.guru/og.png" />
13     <meta property="og:image:width" content="1200" />
14     <meta property="og:image:height" content="630" />
15     <meta name="twitter:card" content="summary_large_image" />
16     <meta name="twitter:title" content="KheIsutra ? every rally indexed, the dead time gone"
/>
17     <meta name="twitter:description" content="A full match becomes a clean highlight reel ?
only the real play, no dead time. Invite-only alpha, Bengaluru." />
18     <meta name="twitter:image" content="https://kheIsutra.guru/og.png" />
19     <meta name="theme-color" content="#0C261F" />
20     <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
21     <link rel="preconnect" href="https://fonts.googleapis.com" />
22     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
23     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
24     <style>
25         :root{
26             --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
27             --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
28             --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
29             --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
30             --r:14px; --rs:10px; --maxw:1080px;
31             --font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,Helvetica,Arial,sans-serif;
32         }
33         *{box-sizing:border-box}
34         html{scroll-behavior:smooth}
35         body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.65;-webkit-font-smoothing:antialiased}
36         a{color:inherit}
37         .wrap{max-width:var(--maxw);margin:0 auto;padding:0 22px}
38         h1,h2,h3{line-height:1.15;margin:0;letter-spacing:-.02em}
39         h1{font-size:clamp(2rem,5vw,3.4rem);font-weight:800}
40         h2{font-size:clamp(1.5rem,3.2vw,2.2rem);font-weight:700}
41         h3{font-size:1.15rem;font-weight:700}
42         p{margin:.6rem 0}
43         .btn{display:inline-flex;align-items:center;gap:.5rem;font-weight:600;font-
size:1rem;border-radius:999px;padding:.78rem 1.4rem;text-decoration:none;border:1px solid
transparent;cursor:pointer;transition:.15s}
44         .btn-primary{background:var(--green);color:#04140D}
45         .btn-primary:hover{background:var(--green-d)}
46         .btn-ghost{background:transparent;border-color:rgba(255,255,255,.28);color:var(--on-
dark)}
47         .btn-ghost:hover{border-color:rgba(255,255,255,.6)}
48         .btn-dark{background:var(--ink);color:#fff}
49         .btn-dark:hover{background:var(--ink2)}
50         .btn[disabled]{opacity:.75;cursor:progress}
51         /* in-flight spinner for the request-access submit */
52         .spin{display:inline-block;width:1em;height:1em;border:2px solid currentColor;border-
right-color:transparent;border-radius:50%;animation:spin .6s linear infinite}
53         @keyframes spin{to{transform:rotate(360deg)}}
54         .eyebrow{display:inline-flex;align-items:center;gap:.5rem;font-size:.82rem;font-
weight:600;letter-spacing:.02em;
55             background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.3);padding:.3rem .8rem;border-radius:999px}
56
57         /* header */
58         header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
59         .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
60         .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-

```

```

size:1.18rem;letter-spacing:-.02em;text-decoration:none}
61     .brand .dot{color:var(--green)}
62     .nav-links{display:flex;align-items:center;gap:1.6rem}
63     .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
64     .nav-links a:hover{color:var(--tx)}
65     .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px
0 7px 12px;border-color:transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
66
67     /* hero */
68     .hero{background:linear-gradient(160deg,var(--ink) 0%,var(--ink2)
100%);color:var(--on-dark);position:relative;overflow:hidden}
69     .hero .wrap{padding-top:74px;padding-bottom:88px;position:relative;z-index:2}
70     .hero .eyebrow{background:rgba(199,242,176,.12);color:var(--lime);border-
color:rgba(199,242,176,.25)}
71     .hero h1{margin:1.1rem 0 0;max-width:15ch}
72     .hero h1 .hl{color:var(--lime)}
73     .hero .lead{font-size:clamp(1.05rem,1.6vw,1.28rem);color:var(--on-dark-mut);max-
width:54ch;margin:1.2rem 0 0}
74     .hero-cta{display:flex;flex-wrap:wrap;gap:.8rem;margin-top:2rem}
75     .hero-note{margin-top:1.1rem;font-size:.86rem;color:var(--on-dark-mut)}
76     .shuttle{position:absolute;right:-60px;top:-40px;width:520px;max-
width:55%;opacity:.16;z-index:1;pointer-events:none}
77     .loop{display:flex;flex-wrap:wrap;gap:.6rem;margin-top:2.4rem}
78     .loop .chip{display:flex;align-
items:center;gap:.5rem;background:rgba(255,255,255,.06);border:1px solid rgba(255,255,255,.12);
79     border-radius:999px;padding:.5rem 1rem;font-weight:500;font-
size:.92rem;color:var(--on-dark)}
80     .loop .chip b{color:var(--lime);font-weight:700}
81     .loop .arrow{color:var(--on-dark-mut);align-self:center}
82
83     .hero-grid{display:grid;grid-template-columns:1.04fr .96fr;gap:46px;align-
items:center}
84     .hero-left{min-width:0}
85     .hero-visual{min-width:0}
86     .reel-card{background:#fff;border-radius:18px;border:1px solid
rgba(255,255,255,.14);box-shadow:0 26px 60px -24px rgba(0,0,0,.55);overflow:hidden}
87     .reel-head{display:flex;align-items:center;gap:.55rem;padding:.7rem .9rem;border-
bottom:1px solid var(--line)}
88     .reel-head .dots{display:flex;gap:5px}
89     .reel-head .dots i{width:9px;height:9px;border-
radius:50%;background:#D9DED7;display:block}
90     .reel-head .file{font-size:.78rem;color:var(--mut);font-weight:600}
91     .reel-video{position:relative;aspect-ratio:16/9;background:linear-
gradient(150deg,#0E3A2C,#17533C);display:flex;align-items:center;justify-content:center}
92     .reel-video .court{position:absolute;inset:16px;border:2px solid
rgba(199,242,176,.30);border-radius:6px}
93     .reel-video .court:before{content:"";position:absolute;left:50%;top:0;bottom:0;width:2
px;background:rgba(199,242,176,.30)}
94     .reel-video .court:after{content:"";position:absolute;top:50%;left:0;right:0;height:2p
x;background:rgba(199,242,176,.22)}
95     .reel-video .play{width:60px;height:60px;border-
radius:50%;background:var(--lime);display:flex;align-items:center;justify-
content:center;color:#0C261F;font-size:1.4rem;z-index:2;padding-left:4px;box-shadow:0 10px 26px
rgba(0,0,0,.35)}
96     .reel-video .badge{position:absolute;top:12px;left:12px;background:rgba(12,38,31,.72);
color:var(--lime);font-size:.7rem;font-weight:700;letter-spacing:.06em;padding:.26rem
.6rem;border-radius:999px;z-index:2}
97     .reel-video
.wm{position:absolute;bottom:10px;right:12px;color:rgba(234,243,238,.78);font-size:.66rem;font-
weight:500;z-index:2}
98     .reel-body{padding:.95rem 1.05rem 1.1rem}
99     .reel-body .lbl{font-size:.72rem;font-weight:600;letter-spacing:.04em;text-
transform:uppercase;color:var(--mut)}
100    .reel-track{position:relative;height:12px;border-

```

```

radius:6px;background:#E8ECE6;margin:.55rem 0 .95rem}
101     .reel-track span{position:absolute;top:0;bottom:0;background:var(--green);border-
radius:6px}
102     .reel-stats{display:flex;gap:10px}
103     .reel-stats .m{flex:1;background:var(--paper);border-radius:10px;padding:.6rem .85rem}
104     .reel-stats .m b{display:block;font-size:1.25rem;color:var(--tx);font-weight:700}
105     .reel-stats .m em{font-size:.76rem;color:var(--mut);font-style:normal}
106     .ask{display:flex;align-items:center;gap:.55rem;margin:.85rem 1.05rem
.2rem;padding:.6rem .7rem;border:1px solid var(--line);border-
radius:12px;background:var(--paper)}
107     .ask-ic{color:var(--green-d);font-size:.95rem}
108     .ask-tx{flex:1;font-size:.88rem;color:var(--tx);font-weight:500;line-height:1.3}
109     .ask-go{width:26px;height:26px;border-
radius:8px;background:var(--green);color:#04140D;display:flex;align-items:center;justify-
content:center;font-size:.85rem;flex:none}
110     .lbl{display:flex;justify-content:space-between;align-items:center}
111     .lbl .match{color:var(--green-d);font-weight:700}
112     .reel-track span.off{background:#D7DDD4}
113     .reel-track span.on{background:var(--green)}
114     .result{display:flex;align-items:center;gap:.7rem;margin-top:.2rem;padding:.65rem
.8rem;background:var(--ink);border-radius:12px}
115     .result .play{width:34px;height:34px;border-
radius:50%;background:var(--lime);color:#0C261F;display:flex;align-items:center;justify-
content:center;flex:none;font-size:.95rem;padding-left:2px}
116     .result-tx{flex:1}
117     .result-tx b{display:block;font-size:.84rem;font-weight:700;color:#fff}
118     .result-tx em{display:block;font-style:normal;font-size:.73rem;color:var(--on-dark-
mut)}}
119     .result .dl{color:var(--on-dark-mut);font-size:1.1rem}
120     .askc .q{font-weight:600;background:var(--paper);border:1px solid var(--line);border-
radius:10px;padding:.6rem .75rem;font-size:.95rem}
121     .askc .q i{color:var(--green-d);font-style:normal;margin-right:.35rem}
122     .askc .a{display:flex;gap:.5rem;color:var(--mut);font-size:.93rem;margin-
top:.75rem;padding-left:.1rem}
123     .askc .a i{color:var(--green-d);font-style:normal;margin-top:.1rem}
124     .ask-note{margin-top:1.5rem;font-size:.95rem;color:var(--mut)}
125
126     /* sections */
127     section{padding:72px 0}
128     .sec-head{max-width:60ch}
129     .sec-head .kicker{font-size:.82rem;font-weight:700;letter-spacing:.08em;text-
transform:uppercase;color:var(--green-d)}
130     .sec-head h2{margin:.5rem 0 0}
131     .sec-head p{color:var(--mut);font-size:1.08rem;margin-top:.7rem}
132
133     .grid{display:grid;gap:18px;margin-top:2.4rem}
134     .g4{grid-template-columns:repeat(4,1fr)}
135     .g3{grid-template-columns:repeat(3,1fr)}
136     .g2{grid-template-columns:repeat(2,1fr)}
137     .card{background:var(--card);border:1px solid var(--line);border-
radius:var(--r);padding:1.4rem}
138     .card .ic{width:42px;height:42px;border-radius:11px;display:flex;align-
items:center;justify-content:center;
139         background:rgba(25,179,107,.12);color:var(--green-d);font-size:1.3rem;margin-
bottom:.9rem}
140     .card h3{font-size:1.05rem}
141     .card p{color:var(--mut);font-size:.96rem;margin:.4rem 0 0}
142
143     .split{display:grid;grid-template-columns:1.1fr .9fr;gap:42px;align-items:center}
144     .panel{background:var(--ink);color:var(--on-dark);border-radius:18px;padding:2.2rem}
145     .panel h2{color:#fff}
146     .panel p{color:var(--on-dark-mut)}
147     .panel .pill{display:inline-
block;background:rgba(199,242,176,.14);color:var(--lime);font-size:.8rem;font-weight:600;
148         padding:.3rem .7rem;border-radius:999px;margin-bottom:1rem}

```

```

149
150     .road{display:grid;grid-template-columns:repeat(5,1fr);gap:14px;margin-top:2.2rem}
151     .road .step{background:var(--card);border:1px solid var(--line);border-
radius:var(--rs);padding:1.1rem}
152     .road .step .n{font-size:1.4rem;color:var(--green-d)}
153     .road .step h3{font-size:1rem;margin-top:.5rem}
154     .road .step p{font-size:.88rem;color:var(--mut);margin-top:.3rem}
155
156     .honest{background:#fff;border:1px solid var(--line);border-left:4px solid
var(--green);border-radius:0 var(--rs) var(--rs) 0;padding:1.2rem 1.4rem;margin-top:1.6rem}
157     .honest b{color:var(--tx)}
158     .honest p{color:var(--mut);margin:.3rem 0 0}
159
160     .notes{list-style:none;padding:0;margin:2rem 0 0;display:grid;grid-template-
columns:repeat(2,1fr);gap:12px}
161     .notes li{display:flex;gap:.6rem;background:var(--card);border:1px solid
var(--line);border-radius:var(--rs);padding:.9rem 1.1rem;color:var(--mut);font-size:.95rem}
162     .notes li i{color:var(--green-d);margin-top:.15rem}
163
164     details{background:var(--card);border:1px solid var(--line);border-
radius:var(--rs);padding:0 1.2rem;margin-top:10px}
165     details summary{cursor:pointer;font-weight:600;padding:1rem 0;list-
style:none;display:flex;justify-content:space-between;align-items:center;gap:1rem}
166     details summary::-webkit-details-marker{display:none}
167     details summary::after{content:"+";color:var(--green-d);font-size:1.3rem;font-
weight:400}
168     details[open] summary::after{content:"?"}
169     details p{color:var(--mut);margin:0 0 1.1rem}
170
171     .cta{background:linear-gradient(160deg,var(--ink) 0%,var(--ink2) 100%);color:var(--on-
dark);border-radius:20px;padding:3rem 2.4rem;text-align:center;margin:0 0 0}
172     .cta h2{color:#fff;max-width:20ch;margin:0 auto}
173     .cta p{color:var(--on-dark-mut);max-width:46ch;margin:.8rem auto 0}
174     .cta .hero-cta{justify-content:center}
175     .af{max-width:560px;margin:2.2rem auto 0;background:var(--card);border:1px solid
var(--line);border-radius:var(--r);padding:1.6rem 1.5rem;text-align:left}
176     .af .row{margin-bottom:1.05rem}
177     .af label{display:block;font-size:.9rem;font-weight:600;color:var(--tx);margin-
bottom:.4rem}
178     .af .hint{font-weight:400;color:var(--mut);font-size:.84rem}
179     .af input[type=text],.af input[type=email],.af select,.af
textarea{width:100%;font:inherit;font-
size:.95rem;color:var(--tx);background:var(--paper);border:1px solid var(--line);border-
radius:10px;padding:.6rem .75rem}
180     .af textarea{min-height:84px;resize:vertical}
181     .af input:focus,.af select:focus,.af textarea:focus{outline:none;border-
color:var(--green);box-shadow:0 0 0 3px rgba(25,179,107,.15)}
182     .seg{display:flex;gap:10px}
183     .seg label{flex:1;margin:0;border:1px solid var(--line);border-
radius:10px;padding:.7rem .8rem;cursor:pointer;font-weight:500;text-align:center}
184     .seg input{position:absolute;opacity:0}
185     .seg label:hover{border-color:var(--green)}
186     .seg label:has(input:checked){border-
color:var(--green);background:rgba(25,179,107,.07);color:var(--green-d);font-weight:700}
187     .opts{display:flex;flex-wrap:wrap;gap:8px}
188     .opts label{margin:0;display:inline-flex;align-items:center;gap:.4rem;border:1px solid
var(--line);border-radius:999px;padding:.4rem .8rem;font-weight:500;font-
size:.88rem;cursor:pointer}
189     .opts label:has(:checked){border-
color:var(--green);background:rgba(25,179,107,.07);color:var(--green-d)}
190     .opts input{accent-color:var(--green)}
191     .af .consent{display:flex;align-items:flex-start;gap:.5rem}
192     .af .consent input{margin-top:.2rem;accent-color:var(--green)}
193     .af .acad{display:none}
194     .af.is-academy .acad{display:block}

```

```

195     .hp{position:absolute;left:-9999px;width:1px;height:1px;overflow:hidden}
196     .form-done{max-width:560px;margin:2rem auto 0;text-
align:center;background:rgba(25,179,107,.08);border:1px solid
rgba(25,179,107,.3);color:var(--green-d);border-radius:var(--r);padding:1.4rem;font-weight:600}
197
198     footer{border-top:1px solid var(--line);padding:42px 0;color:var(--mut);font-
size:.9rem}
199     .foot{display:flex;flex-wrap:wrap;justify-content:space-between;gap:1.2rem;align-
items:center}
200     .foot a{color:var(--green-d);text-decoration:none}
201     .foot a:hover{text-decoration:underline}
202     .stamp{font-size:.82rem;color:var(--mut)}
203
204     @media (max-width:860px){
205         .nav-links{display:none}
206         .g4{grid-template-columns:repeat(2,1fr)}
207         .g3,.g2{grid-template-columns:1fr}
208         .split{grid-template-columns:1fr;gap:24px}
209         .road{grid-template-columns:repeat(2,1fr)}
210         .notes{grid-template-columns:1fr}
211         .shuttle{opacity:.1}
212         .hero-grid{grid-template-columns:1fr;gap:30px}
213         .reel-card{max-width:460px}
214     }
215
216     /* tool demo + sample reel ? revealed AFTER sign-up, then auto-closes */
217     .reelwrap{position:relative;max-width:680px;margin:.5rem auto 0;aspect-
ratio:16/9;border-radius:14px;overflow:hidden;border:1px solid var(--line);background:#0C261F}
218     .reelwrap iframe{width:100%;height:100%;border:0;display:block}
219     .tool-vid{display:block;width:100%;max-width:680px;margin:.5rem auto 0;border-
radius:14px;border:1px solid var(--line);background:#0C261F}
220     .reveal-h{max-width:680px;margin:1.2rem auto .15rem;font-size:.74rem;font-
weight:700;letter-spacing:.06em;text-transform:uppercase;color:var(--green-d);text-align:left}
221     .reveal-bar{max-width:680px;margin:.2rem auto 0;display:flex;justify-content:flex-end}
222     .reveal-x{background:transparent;border:1px solid var(--line);color:var(--mut);font-
size:.78rem;font-weight:600;padding:.32rem .72rem;border-radius:999px;cursor:pointer}
223     .reveal-x:hover{color:var(--tx);border-color:var(--mut)}
224 </style>
225 </head>
226 <body>
227
228 <header>
229     <div class="wrap nav">
230         <a class="brand" href="#top">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
231         <nav class="nav-links" aria-label="Primary">
232             <a href="#how">How it works</a>
233             <a href="#diff">Why it's hard</a>
234             <a href="/own-model">Own your model</a>
235             <a href="#roadmap">Roadmap</a>
236             <a href="#faq">FAQ</a>
237         </nav>
238         <a class="btn btn-dark" href="#join">Request access</a>
239     </div>
240 </header>
241
242 <a id="top"></a>
243 <section class="hero" style="padding:0">
244     <div class="wrap hero-grid">
245         <div class="hero-left">
246             <span class="eyebrow">Invite-only alpha · Bengaluru</span>
247             <h1>Every rally, indexed. <span class="hl">The dead time, gone.</span></h1>
248             <p class="lead">KhelSutra finds every rally in your session and strips out the
knock-ups, walks and gaps ? so a full match becomes a clean highlight reel you can watch and
download. No editing, no scrubbing.</p>

```

```

249     <div class="hero-cta">
250         <a class="btn btn-primary" href="#join">Request alpha access</a>
251         <a class="btn btn-ghost" href="#how">See how it works</a>
252         <a class="btn btn-ghost" href="#join">See it in action + a real reel</a>
253     </div>
254     <p class="hero-note">A phone or GoPro on a tripod is all you need. No special
hardware.</p>
255     <div class="loop">
256         <span class="chip"><b>1.</b> Auto-index rallies</span>
257         <span class="arrow">?</span>
258         <span class="chip"><b>2.</b> Dead time removed</span>
259         <span class="arrow">?</span>
260         <span class="chip"><b>3.</b> Download your reel</span>
261     </div>
262 </div>
263 <div class="hero-visual">
264     <div class="reel-card">
265         <div class="reel-head">
266             <span class="dots"><i></i><i></i><i></i></span>
267             <span class="file">match_2026.mp4 · indexed</span>
268         </div>
269         <div class="reel-body">
270             <div class="lbl"><span>Rallies detected</span><span class="match">44
found</span></div>
271             <div class="reel-track">
272                 <span class="on" style="left:2%;width:8%"></span>
273                 <span class="on" style="left:13%;width:6%"></span>
274                 <span class="on" style="left:22%;width:12%"></span>
275                 <span class="on" style="left:37%;width:7%"></span>
276                 <span class="on" style="left:47%;width:11%"></span>
277                 <span class="on" style="left:61%;width:6%"></span>
278                 <span class="on" style="left:70%;width:13%"></span>
279                 <span class="on" style="left:86%;width:9%"></span>
280             </div>
281             <div class="result">
282                 <span class="play" aria-hidden="true">?</span>
283                 <span class="result-tx"><b>Highlight reel · 44 rallies · 18 min</b><em>dead
time removed · ready to download</em></span>
284                 <span class="dl" aria-hidden="true">?</span>
285             </div>
286         </div>
287     </div>
288 </div>
289 </div>
290 </section>
291
292 <section id="how">
293     <div class="wrap">
294         <div class="sec-head">
295             <div class="kicker">What it does today</div>
296             <h2>A full match, turned into rallies you can search</h2>
297             <p>Upload a whole session or match. KhelSutra does the rest ? no editing skill
needed.</p>
298         </div>
299         <div class="grid g4">
300             <div class="card">
301                 <div class="ic" aria-hidden="true">?</div>
302                 <h3>Every rally, indexed</h3>
303                 <p>It finds each rally ? start, end and length ? and turns the whole match into
a searchable list. Long full-session videos are fine.</p>
304             </div>
305             <div class="card">
306                 <div class="ic" aria-hidden="true">?</div>
307                 <h3>Dead time removed</h3>
308                 <p>Knock-ups, walks, picking up the shuttle, the gaps between points ? stripped

```

```

out. What's left is only real play.</p>
309     </div>
310     <div class="card">
311         <div class="ic" aria-hidden="true">?</div>
312         <h3>Process once, reuse</h3>
313         <p>Come back later to watch or download your reel. Re-running a video replaces
its earlier result rather than piling up copies.</p>
314     </div>
315     <div class="card">
316         <div class="ic" aria-hidden="true">?</div>
317         <h3>Stitched reel + summary</h3>
318         <p>Your selection becomes one MP4 to download and share ? with a play-time
summary and a small ?Generated by Khelsutra.guru? mark.</p>
319     </div>
320 </div>
321 </div>
322 </section>
323
324 <section id="record" style="background:#EFF4EC">
325     <div class="wrap">
326         <div class="sec-head">
327             <div class="kicker">Record it right</div>
328             <h2>Five minutes of setup ? reliably great reels</h2>
329             <p>Highlight quality starts with the recording. Set the camera up once like this
and KhelSutra has everything it needs to find the rallies.</p>
330         </div>
331
332         <div style="max-width:780px;margin:0 auto 1.6rem;display:flex;gap:.8rem;align-
items:flex-start;background:#fff;border:1px solid var(--line);border-left:4px solid
var(--green);border-radius:14px;padding:1rem 1.2rem">
333             <span aria-hidden="true" style="color:var(--green-d);font-size:1.4rem;line-
height:1">?</span>
334             <p style="margin:0;color:var(--tx)"><b>The golden rule: one match, one court, in
full frame ? and don't move the camera.</b> <span style="color:var(--mut)">A single court in
frame gives the best results today; busy multi-court footage is the hard case we're still
sharpening.</span></p>
335         </div>
336
337         <div class="grid g4">
338             <div class="card">
339                 <div class="ic" aria-hidden="true">?</div>
340                 <h3>Place the camera</h3>
341                 <p>Behind <b>one baseline</b>, elevated (a high tripod or a balcony), tilted
down ~30° ? the <b>whole court</b> in frame, players never cropped.</p>
342             </div>
343             <div class="card">
344                 <div class="ic" aria-hidden="true">?</div>
345                 <h3>Settings</h3>
346                 <p><b>1080p+</b>, landscape, <b>30 fps</b> for badminton (60 fps for table
tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies.</p>
347             </div>
348             <div class="card">
349                 <div class="ic" aria-hidden="true">?</div>
350                 <h3>Keep it still</h3>
351                 <p>Fixed tripod or mount. <b>No panning, no zooming</b> during play ? a steady,
full-court view is what the tool is tuned for.</p>
352             </div>
353             <div class="card">
354                 <div class="ic" aria-hidden="true">?</div>
355                 <h3>Record & upload</h3>
356                 <p>Even lighting, then record the <b>whole session</b> and upload it as-is ?
KhelSutra finds the rallies and does the cutting.</p>
357             </div>
358         </div>
359

```



```

360     <div style="text-align:center;margin-top:1.6rem">
361         <a class="btn btn-dark" href="/capture">Full 1-page capture checklist ?</a>
362     </div>
363 </div>
364 </section>
365
366 <section id="diff" style="padding-top:0">
367     <div class="wrap">
368         <div class="split">
369             <div>
370                 <div class="kicker" style="font-size:.82rem;font-weight:700;letter-
spacing:.08em;text-transform:uppercase;color:var(--green-d)">The hard problem we crack</div>
371                 <h2 style="margin-top:.5rem">Most academy halls run several courts at once</h2>
372                 <p style="color:var(--mut);font-size:1.05rem">Academies already record a lot of
video ? and then almost never watch it, because cutting it into useful clips by hand is tedious.
The good rallies stay buried.</p>
373                 <p style="color:var(--mut);font-size:1.05rem">A single recording of a busy,
multi-court hall is exactly where ordinary video tools choke. Pulling the <b
style="color:var(--tx)">real</b> rallies out of busy, multi-court footage is the hard problem
KhelSutra is built for. It already works very well on clean, single-court recordings ? and the
multi-court case is what we're sharpening now.</p>
374             </div>
375             <div class="panel">
376                 <span class="pill">Capture tip</span>
377                 <h2 style="font-size:1.4rem">Best results: a steady, full-court shot</h2>
378                 <p>Camera behind the court, slightly elevated, whole court in frame. Keep it
still ? a fixed tripod beats handheld every time. Shoot landscape, record the whole session,
upload as-is. KhelSutra does the cutting.</p>
379             </div>
380         </div>
381     </div>
382 </section>
383
384 <section id="sharper" style="background:#EFF4EC">
385     <div class="wrap">
386         <div class="sec-head">
387             <div class="kicker">What makes it different</div>
388             <h2>It gets sharper from real academy footage</h2>
389             <p>The footage real academies contribute ? especially the busy multi-court halls ?
is what makes KhelSutra better over time. Early users aren't just customers; they're co-
builders.</p>
390         </div>
391         <div class="grid g3">
392             <div class="card">
393                 <div class="ic" aria-hidden="true">?</div>
394                 <h3>Improves with the library</h3>
395                 <p>When you choose to share footage and coaches confirm what it found, that
growing labelled library is what sharpens future versions ? rather than staying frozen.</p>
396             </div>
397             <div class="card">
398                 <div class="ic" aria-hidden="true">?</div>
399                 <h3>Your data stays yours</h3>
400                 <p>We never use your video to improve the tool without your clear, explicit opt-
in. We never publish your footage. You decide what, if anything, you share.</p>
401             </div>
402             <div class="card">
403                 <div class="ic" aria-hidden="true">?</div>
404                 <h3>Minors are protected</h3>
405                 <p>Footage involving minors is never used to improve the tool and is never
published ? full stop.</p>
406             </div>
407         </div>
408         <div class="honest">
409             <b>Read this honestly:</b>
410             <p>Today the tool gives you rally detection, reels, and summaries. It does not

```

```

retrain itself as you use it, and there's no per-person tracking. "Gets sharper over time" is
the model we're building toward, powered by contributed footage ? not a switch that's already
on.</p>
411     </div>
412     </div>
413 </section>
414
415 <section id="ask">
416     <div class="wrap">
417         <div class="sec-head">
418             <div class="kicker">Coming next to the alpha</div>
419             <h2>Soon: ask for the exact reel you want</h2>
420             <p>Your match is already a clean index of rallies ? so the natural next step is to
let you build any reel just by describing it, in plain English. This is rolling out to alpha
users.</p>
421         </div>
422         <div class="grid g3 ask-grid">
423             <div class="card askc">
424                 <div class="q"><i>?</i>Every rally over 10 seconds?</div>
425                 <div class="a"><i>?</i> 6 rallies · a 1:32 reel of the long, end-to-end
battles</div>
426             </div>
427             <div class="card askc">
428                 <div class="q"><i>?</i>Just the third game, longest first?</div>
429                 <div class="a"><i>?</i> 12 rallies, reordered by length ? that game only</div>
430             </div>
431             <div class="card askc">
432                 <div class="q"><i>?</i>The 8 best rallies from today?</div>
433                 <div class="a"><i>?</i> an 8-clip highlight from your latest session</div>
434             </div>
435         </div>
436         <p class="ask-note"><b style="color:var(--tx)">Rolling out now.</b> Targeted asks ?
by rally length, count, order, or which game ? come first; shot-type and player queries follow
as the deeper analysis arrives.</p>
437     </div>
438 </section>
439
440 <section id="roadmap">
441     <div class="wrap">
442         <div class="sec-head">
443             <div class="kicker">Where it's going</div>
444             <h2>Toward an AI assistant coach</h2>
445             <p>Fed by the growing video library, KhelSutra is heading from "finds rallies" to
a genuine training companion. This is the direction ? not today's buttons.</p>
446         </div>
447         <div class="road">
448             <div class="step"><div class="n">?</div><h3>Shot detection</h3><p>Smashes, drops,
net shots, serves and clears within each rally.</p></div>
449             <div class="step"><div class="n">?</div><h3>Deeper analysis</h3><p>Per-rally and
per-match patterns ? what's working and what isn't.</p></div>
450             <div class="step"><div class="n">?</div><h3>Per-match history</h3><p>Track
progress over weeks and months, not just one clip.</p></div>
451             <div class="step"><div class="n">?</div><h3>Assistant coach</h3><p>Surfaces what
to work on next ? supports the real coach, never replaces.</p></div>
452             <div class="step"><div class="n">?</div><h3>More sports & languages</h3><p>Table
tennis next; Kannada and Hindi alongside English.</p></div>
453         </div>
454     </div>
455 </section>
456
457 <section id="not" style="padding-top:0">
458     <div class="wrap">
459         <div class="sec-head">
460             <div class="kicker">So expectations stay honest</div>
461             <h2>What KhelSutra is not</h2>

```

```

462         </div>
463         <ul class="notes">
464             <li><i aria-hidden="true">?</i><span>An early, invite-only trial ? useful, but
still improving. You'll hit rough edges.</span></li>
465             <li><i aria-hidden="true">?</i><span>Not a line-calling, scoring, or umpiring
system.</span></li>
466             <li><i aria-hidden="true">?</i><span>Not player tracking or
identification.</span></li>
467             <li><i aria-hidden="true">?</i><span>Not a replacement for a coach ? a tool that
saves time and adds insight.</span></li>
468             <li><i aria-hidden="true">?</i><span>Shot detection and deeper analytics are on
the roadmap, not available today.</span></li>
469             <li><i aria-hidden="true">?</i><span>Pricing isn't set ? today's invited use is
about getting it right.</span></li>
470         </ul>
471     </div>
472 </section>
473
474 <section id="faq" style="background:#EFF4EC">
475     <div class="wrap">
476         <div class="sec-head">
477             <div class="kicker">Quick answers</div>
478             <h2>Common questions</h2>
479         </div>
480         <div style="margin-top:1.6rem">
481             <details><summary>How accurate is it?</summary><p>Very good on a clean, single-
court recording. A busy multi-court hall is harder ? and is exactly what we're improving. The
best answer is to show you a sample reel of your own court rather than quote a
number.</p></details>
482             <details><summary>Can I choose which rallies go in the reel?</summary><p>Today
your reel includes the rallies KhelSutra found, with the dead time removed. Choosing by length,
count, order or which game ? just by asking in plain English ? is rolling out to alpha users
next; shot-type and player queries follow as the deeper analysis arrives.</p></details>
483             <details><summary>Do I need a special camera or hardware?</summary><p>No. A phone
or GoPro on a tripod, behind the court, whole court in frame. We provide a one-page capture
checklist at setup.</p></details>
484             <details><summary>Is my video private? What happens to it?</summary><p>We treat
your footage as private: we never publish it, and we never use it to improve the tool without
your explicit opt-in. These are large videos that need real processing, so your video is handled
securely on our infrastructure to make your reel. Footage involving minors is never used and
never published.</p></details>
485             <details><summary>Does it work for doubles and tournaments?</summary><p>It finds
rallies in doubles too. Tournament footage varies ? a clean, fixed, full-court recording works
well; crowded multi-court tournament halls are the hard case we're specifically working
on.</p></details>
486             <details><summary>Which sports?</summary><p>Badminton today. Table tennis and
other racket sports are on the roadmap.</p></details>
487             <details><summary>How do I join?</summary><p>It's an invite-only private trial.
Just <a href="#join">request access</a> using the form ? it takes a minute, you'll see a real
sample reel right away, and we'll be in touch about recording your own court.</p></details>
488         </div>
489     </div>
490 </section>
491
492 <section id="join" style="padding-bottom:90px">
493     <div class="wrap">
494         <div class="sec-head" style="text-align:center;max-width:none">
495             <div class="kicker">Request access</div>
496             <h2>Get into the KhelSutra alpha</h2>
497             <p>Invite-only. Tell us a little about your setup ? it helps us get you the best
results, and shapes what we build next.</p>
498             <p style="font-weight:600;color:var(--green-d);margin-top:.6rem"><span aria-
hidden="true">?</span> Sign up to watch the tool in action ? and a 30-second sample reel it made
? the moment you're in.</p>
499         </div>

```

```

500
501     <form id="af" class="af" novalidate>
502         <div class="row">
503             <label>I'm a?</label>
504             <div class="seg">
505                 <label><input type="radio" name="segment" value="academy"
required><span>Coaching academy / club</span></label>
506                 <label><input type="radio" name="segment" value="individual"><span>Individual
player</span></label>
507             </div>
508         </div>
509
510         <div class="row">
511             <label for="af-name">Name</label>
512             <input id="af-name" name="name" type="text" autocomplete="name" required>
513         </div>
514         <div class="row">
515             <label for="af-email">Email <span class="hint">(so we can reach
you)</span></label>
516             <input id="af-email" name="email" type="email" autocomplete="email" required>
517         </div>
518         <div class="row">
519             <label for="af-city">City <span class="hint">(optional)</span></label>
520             <input id="af-city" name="city" type="text">
521         </div>
522
523         <div class="row acad">
524             <label for="af-org">Academy / club name <span
class="hint">(optional)</span></label>
525             <input id="af-org" name="org_name" type="text">
526         </div>
527         <div class="row acad">
528             <label for="af-courts">How many courts do you record? <span
class="hint">(optional)</span></label>
529             <select id="af-courts" name="courts">
530                 <option value="">Select?</option>
531                 <option value="1">1 court</option>
532                 <option value="2-4">2?4 courts</option>
533                 <option value="5+">5+ courts</option>
534             </select>
535         </div>
536
537         <div class="row">
538             <label>Do you have a GPU machine that could process video locally?</label>
539             <div class="opts">
540                 <label><input type="radio" name="has_gpu" value="yes">Yes ? a gaming / GPU PC
or laptop</label>
541                 <label><input type="radio" name="has_gpu" value="unsure">Not sure</label>
542                 <label><input type="radio" name="has_gpu" value="no">No</label>
543                 <label><input type="radio" name="has_gpu" value="prefer-cloud">I'd prefer it
runs in the cloud</label>
544             </div>
545         </div>
546
547         <div class="row">
548             <label>Where do your recordings live / how would you share them? <span
class="hint">(pick any)</span></label>
549             <div class="opts">
550                 <label><input type="checkbox" name="storage" value="gdrive">Google
Drive</label>
551                 <label><input type="checkbox" name="storage" value="onedrive">OneDrive / MS
365</label>
552                 <label><input type="checkbox" name="storage" value="dropbox">Dropbox</label>
553                 <label><input type="checkbox" name="storage" value="bucket">Cloud bucket
(S3/GCS)</label>

```

```

554         <label><input type="checkbox" name="storage" value="local">SD card / local
drive</label>
555         <label><input type="checkbox" name="storage" value="unsure">Not sure</label>
556     </div>
557 </div>
558
559     <div class="row">
560         <label for="af-msg">Anything else? <span class="hint">(how you record, what
you'd want?)</span></label>
561         <textarea id="af-msg" name="message"></textarea>
562     </div>
563
564     <div class="row consent">
565         <input id="af-consent" name="consent" type="checkbox" value="yes">
566         <label for="af-consent" style="margin:0;font-weight:400;color:var(--mut)">Okay
to email me about the KhelSutra alpha.</label>
567     </div>
568
569     <input class="hp" type="text" name="company" tabindex="-1" autocomplete="off"
aria-hidden="true">
570
571     <button class="btn btn-primary" type="submit" style="width:100%;justify-
content:center">Request access</button>
572     <p class="hint" style="text-align:center;margin:.85rem 0 0">We never publish your
footage; footage involving minors is never used to improve the tool.</p>
573 </form>
574
575     <p id="af-done" class="form-done" hidden>Thanks ? we've got it. We'll be in touch at
the email you gave. ?<br><span style="font-weight:400;color:var(--mut)">While you're here: see
the tool in action, and a real 30-second reel it made.</span></p>
576     <div id="reel-reveal" hidden></div>
577 </div>
578 </section>
579
580 <footer>
581     <div class="wrap foot">
582         <div>
583             <div class="brand" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</div>
584             <div class="stamp" style="margin-top:.4rem">Automatic badminton highlights .
Bengaluru, India</div>
585         </div>
586         <div style="text-align:right">
587             <div><a href="/own-model">Own your model</a> . <a href="/capture">Capture
checklist</a> . <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> . <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
588             <div class="stamp" style="margin-top:.4rem">© 2026 KhelSutra . Invite-only alpha .
Reels carry a "Generated by Khelsutra.guru" mark</div>
589         </div>
590     </div>
591 </footer>
592
593 <!-- Cloudflare Web Analytics: paste your token from Cloudflare dashboard ? Analytics ?
Web Analytics ? Add a site.
594     (Or skip this snippet entirely and enable "Automatic setup" once the domain is
proxied through Cloudflare.) -->
595     <script defer src="https://static.cloudflareinsights.com/beacon.min.js" data-cf-
beacon="{\"token\": \"REPLACE_WITH_CF_TOKEN\"}"></script>
596
597     <script>
598     (function(){
599         var f = document.getElementById('af');
600         if(!f) return;
601
602         var REEL_VIDEO = 'ajTCZ7pJW_o', REEL_SECS = 30;

```

```

603     function loadYTApi(cb){
604         if(window.YT && window.YT.Player) return cb();
605         var prev = window.onYouTubeIframeAPIReady;
606         window.onYouTubeIframeAPIReady = function(){ if(typeof prev === 'function'){ prev();
        } cb(); }};
607         if(!document.getElementById('yt-iframe-api')){
608             var s = document.createElement('script');
609             s.id = 'yt-iframe-api'; s.src = 'https://www.youtube.com/iframe_api';
610             document.head.appendChild(s);
611         }
612     }
613     function revealAfterSignup(){
614         var host = document.getElementById('reel-reveal');
615         if(!host) return;
616         host.hidden = false;
617         // (1) the TOOL in action ? a self-hosted, FOOTAGE-FREE screencast (branded reel
placeholder),
618         //      so it's safe to autoplay openly; (2) a real reel preview (gated nocookie
YouTube). BOTH
619         //      stay visible together; the auto-close PAUSES while the reel is playing (so a
viewer is
620         //      never cut off mid-watch) and a manual ? closes it on demand.
621         host.innerHTML =
622             '<div class="reveal-bar"><button type="button" id="reel-close" class="reveal-x"
aria-label="Close the videos">? Close</button></div>'
623             + '<p class="reveal-h">1 · The tool in action</p>'
624             + '<video class="tool-vid" src="/video/tool-cuj.mp4" autoplay muted loop
playsinline controls preload="metadata"></video>'
625             + '<p class="reveal-h">2 · A real reel it made</p>'
626             + '<div class="reelwrap"><div id="reel-player"></div></div>'
627             + '<p class="stamp" style="text-align:center;margin-top:.6rem">Generated by
Khelsutra.guru · auto-closes <span id="reel-count">' + REEL_SECS + '</span>s after the reel
stops ? or close it anytime</p>';
628         var n = REEL_SECS, el = document.getElementById('reel-count'), player = null, hold =
false, closed = false;
629         function close(){
630             if(closed) return; closed = true;
631             clearInterval(iv);
632             try{ if(player){ player.destroy(); } }catch(_){ }
633             host.innerHTML = ''; host.hidden = true;
634         }
635         var iv = setInterval(function(){
636             if(hold) return; // the reel is playing ? hold the timer (no
mid-watch cut-off)
637             n--; if(el){ el.textContent = n; }
638             if(n <= 0){ close(); }
639         }, 1000);
640         var x = document.getElementById('reel-close'); if(x){ x.addEventListener('click',
close); }
641         loadYTApi(function(){
642             player = new YT.Player('reel-player', {
643                 width: '100%', height: '100%', videoId: REEL_VIDEO,
644                 host: 'https://www.youtube-nocookie.com',
645                 playerVars: { autoplay: 1, rel: 0, modestbranding: 1, playsinline: 1 },
646                 events: {
647                     onReady: function(e){
648                         var dur = Math.floor(e.target.getDuration() || 0);
649                         var maxStart = Math.max(0, dur - REEL_SECS); // start so a full
~30s window plays before the end
650                         var start = maxStart > 0 ? Math.floor(Math.random() * (maxStart + 1)) : 0;
651                         host.setAttribute('data-reel-start', String(start)); // a different chunk
each sign-up
652                         e.target.seekTo(start, true);
653                         e.target.playVideo();
654                     },

```

```

655         onChange: function(e){ hold = (e.data === 1); }    // 1 = PLAYING ? hold
the auto-close
656     }
657     });
658     });
659 }
660
661 f.addEventListener('change', function(e){
662     if(e.target.name === 'segment') f.classList.toggle('is-academy', e.target.value ===
'academy');
663 });
664 function mailtoFallback(p){
665     var lines = [
666         'Segment: ' + (p.segment||''),
667         'Name: ' + (p.name||''),
668         'Email: ' + (p.email||''),
669         'City: ' + (p.city||''),
670         p.segment === 'academy' ? 'Academy: ' + (p.org_name||'') + ' (' + (p.courts||'?'')
+ ' courts)' : null,
671         'GPU: ' + (p.has_gpu||''),
672         'Storage: ' + ((p.storage||[]).join(', ')),
673         'Message: ' + (p.message||''),
674         'Consent: ' + (p.consent ? 'yes' : 'no')
675     ].filter(Boolean).join('\n');
676     return 'mailto:hello@khelsutra.guru?subject=' + encodeURIComponent('KhelSutra alpha
access') +
677         '&body=' + encodeURIComponent('Hi KhelSutra team, I would like to try the
alpha.\n\n' + lines);
678 }
679 f.addEventListener('submit', async function(e){
680     e.preventDefault();
681     if(f.company && f.company.value) return;           // honeypot: silently drop bots
682     if(!f.checkValidity()){ f.reportValidity(); return; }
683     // Immediate, obvious "submitting" state ? the Worker + D1 + email round-trip can
take a beat,
684     // and a static button looked frozen.
685     var btn = f.querySelector('button[type="submit"]');
686     var btnHTML = btn ? btn.innerHTML : '';
687     if(btn){ btn.disabled = true; btn.setAttribute('aria-busy','true'); btn.innerHTML =
'<span class="spin" aria-hidden="true"></span> Sending?'; }
688     var fd = new FormData(f);
689     var p = {
690         segment: fd.get('segment'), name: fd.get('name'), email: fd.get('email'),
691         city: fd.get('city'), org_name: fd.get('org_name'), courts: fd.get('courts'),
692         has_gpu: fd.get('has_gpu'), storage: fd.getAll('storage'),
693         message: fd.get('message'), consent: !!fd.get('consent')
694     };
695     var ok = false;
696     try {
697         var r = await fetch('/api/request-access', {method:'POST', headers:{'content-
type':'application/json'}, body: JSON.stringify(p)});
698         ok = r.ok;
699     } catch(_){ ok = false; }
700     if(ok){
701         f.hidden = true;
702         document.getElementById('af-done').hidden = false;
703         revealAfterSignup();
704     }
705     else {
706         // Restore the button so the user isn't left with a frozen "Sending?", then fall
back to email.
707         if(btn){ btn.disabled = false; btn.removeAttribute('aria-busy'); btn.innerHTML =
btnHTML; }
708         window.location.href = mailtoFallback(p);    // backend not live yet ? prefilled
email

```

```

709     }
710   });
711  })();
712 </script>
713
714 </body>
715 </html>
716

```

4. user (2026-06-21T03:17:21.414Z)

```

1     <!doctype html>
2     <html lang="en">
3     <head>
4       <meta charset="utf-8" />
5       <meta name="viewport" content="width=device-width, initial-scale=1" />
6       <title>KhelSutra ? 1-page capture checklist</title>
7       <meta name="description" content="How to record a badminton session so KhelSutra gives
you great highlight reels: camera placement, settings, stability, lighting." />
8       <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
9       <link rel="preconnect" href="https://fonts.googleapis.com" />
10      <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
11      <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
12      <style>
13        :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--paper:#F6F8F4;--tx:#14271F;--
mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,sans-serif}
14        *{box-sizing:border-box}
15        body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.5;-webkit-font-smoothing:antialiased}
16        .sheet{max-width:820px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
17        .head{background:var(--ink);color:#EAF3EE;padding:22px 30px;display:flex;align-
items:center;justify-content:space-between;gap:1rem;flex-wrap:wrap}
18        .brand{display:flex;align-items:center;gap:.55rem;font-weight:800;font-size:1.2rem}
19        .brand .dot{color:var(--green)}
20        .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
21        .head h1{font-size:1.05rem;font-weight:600;margin:0;color:#C7F2B0}
22        .body{padding:24px 30px 8px}
23        .intro{color:var(--mut);margin:0 0 16px;font-size:.98rem}
24        .rule{display:flex;gap:.7rem;background:#EAF6EF;border:1px solid #BF6ED2;border-
radius:12px;padding:14px 16px;margin-bottom:20px}
25        .rule .star{color:var(--green-d);font-size:1.3rem;line-height:1}
26        .rule b{color:var(--tx)}
27        .rule p{margin:.25rem 0 0;color:var(--mut);font-size:.92rem}
28        .grid{display:grid;grid-template-columns:1fr 1fr;gap:16px 26px}
29        .step h3{display:flex;align-items:center;gap:.5rem;font-size:1rem;font-
weight:700;margin:0 0 .4rem}
30        .step h3 .n{width:24px;height:24px;border-
radius:7px;background:var(--green);color:#04140D;display:flex;align-items:center;justify-
content:center;font-size:.85rem;flex:none}
31        .step ul{margin:0;padding-left:1.1rem}
32        .step li{margin:.18rem 0;font-size:.92rem;color:#34453d}
33        .step li b{color:var(--tx)}
34        .cols{display:grid;grid-template-columns:1fr 1fr;gap:0;border:1px solid
var(--line);border-radius:12px;overflow:hidden;margin:22px 0 8px}
35        .cols div{padding:14px 16px}
36        .cols .do{background:#EAF6EF}
37        .cols .dont{background:#Fbeeb;border-left:1px solid var(--line)}
38        .cols h4{margin:0 0 .5rem;font-size:.92rem}

```



```

39     .cols .do h4{color:var(--green-d)}
40     .cols .dont h4{color:#9a3b22}
41     .cols ul{margin:0;padding-left:1.1rem}
42     .cols li{font-size:.88rem;margin:.16rem 0;color:#3a4b43}
43     .consent{font-size:.86rem;color:var(--mut);border-top:1px solid var(--line);margin-
top:6px;padding:14px 0 4px}
44     .foot{display:flex;justify-content:space-between;flex-wrap:wrap;gap:.5rem;padding:14px
30px 24px;color:var(--mut);font-size:.85rem}
45     .foot a{color:var(--green-d);text-decoration:none}
46     @media (max-width:680px){.grid,.cols{grid-template-columns:1fr}.cols .dont{border-
left:0;border-top:1px solid var(--line)}}
47     @media print{
48         body{background:#fff}
49         .sheet{box-shadow:none;margin:0;max-width:none;border-radius:0}
50         @page{margin:12mm}
51         .noprint{display:none}
52     }
53 </style>
54 </head>
55 <body>
56 <div class="sheet">
57     <div class="head">
58         <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
59         <h1>1-page capture checklist</h1>
60     </div>
61     <div class="body">
62         <p class="intro">Great highlights start with a steady, full-court recording. Five
minutes of setup makes a big difference to your reels.</p>
63
64         <div class="rule">
65             <span class="star" aria-hidden="true">?</span>
66             <div>
67                 <b>The golden rule: one match, one court, in full frame ? and don't move the
camera.</b>
68                 <p>Multi-court footage is the hard case we're still sharpening; a single court
in frame gives the best results today.</p>
69             </div>
70         </div>
71
72         <div class="grid">
73             <div class="step">
74                 <h3><span class="n">1</span>Place the camera</h3>
75                 <ul>
76                     <li>Behind <b>one baseline</b>, elevated ? a high tripod, a few metres up, or
a balcony.</li>
77                     <li>Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a
little margin and net headroom.</li>
78                     <li>Players should never leave the frame.</li>
79                 </ul>
80             </div>
81             <div class="step">
82                 <h3><span class="n">2</span>Settings</h3>
83                 <ul>
84                     <li><b>1080p or higher</b>, shot in <b>landscape</b>.</li>
85                     <li><b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table
tennis.</li>
86                     <li><b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise
reduction off.</li>
87                 </ul>
88             </div>
89             <div class="step">
90                 <h3><span class="n">3</span>Keep it still</h3>
91                 <ul>
92                     <li>Fixed tripod or mount.</li>
93                     <li><b>No panning, no zooming</b> during play.</li>

```

```

94         </ul>
95     </div>
96     <div class="step">
97         <h3><span class="n">4</span>Light & record</h3>
98         <ul>
99             <li>Even indoor lighting; avoid backlight, glare and very dark halls.</li>
100            <li>Record the <b>whole session</b> and upload it as-is ? KhelSutra does the
cutting.</li>
101        </ul>
102    </div>
103 </div>
104
105     <div class="cols">
106         <div class="do">
107             <h4>Do</h4>
108             <ul>
109                 <li>Fixed camera, full court, behind the baseline</li>
110                 <li>1080p+, landscape, audio on</li>
111                 <li>One match on one court</li>
112             </ul>
113         </div>
114         <div class="dont">
115             <h4>Avoid</h4>
116             <ul>
117                 <li>Handheld or phone-in-hand</li>
118                 <li>Broadcast-style pans & zooming</li>
119                 <li>Several courts in one frame; very dark halls</li>
120             </ul>
121         </div>
122     </div>
123
124     <p class="consent">Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.</p>
125 </div>
126 <div class="foot">
127     <span>Questions? <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></span>
128     <span class="noprint">Tip: press Ctrl/Cmd + P to print or save as PDF.</span>
129 </div>
130 </div>
131 </body>
132 </html>
133

```

5. user (2026-06-21T03:17:22.377Z)

```

1     <!doctype html>
2     <html lang="en">
3     <head>
4         <meta charset="utf-8" />
5         <meta name="viewport" content="width=device-width, initial-scale=1" />
6         <title>KhelSutra ? Annotate your footage & train your own model</title>
7         <meta name="description" content="With KhelSutra you can annotate your own footage and
grow a rally model that's YOURS ? on an open, MIT-licensed stack you control. The free VLC
rally-annotator turns 'watch a match' into golden labels." />
8         <meta name="robots" content="noindex" />
9         <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'%3E%3C/svg%3E" />
11         <link rel="preconnect" href="https://fonts.googleapis.com" />
12         <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
13         <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
14     <style>
15         :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--lime:#C7F2B0;--paper:#F6F8F4;-

```

```

--tx:#14271F;--mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans',system-ui,-apple-
system,Segoe UI,Roboto,sans-serif}
15     *{box-sizing:border-box}
16     body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.6;-webkit-font-smoothing:antialiased}
17     a{color:var(--green-d)}
18     .sheet{max-width:880px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
19     .head{background:var(--ink);color:#EAF3EE;padding:24px 32px}
20     .head .top{display:flex;align-items:center;justify-content:space-
between;gap:1rem;flex-wrap:wrap}
21     .brand{display:flex;align-items:center;gap:.5rem;font-weight:800;font-
size:1.2rem;color:#fff;text-decoration:none}
22     .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
23     .head h1{font-size:clamp(1.5rem,3.5vw,2.1rem);font-weight:800;letter-
spacing:-.02em;margin:1rem 0 0;max-width:20ch}
24     .head h1 .hl{color:var(--lime)}
25     .head p{color:#A7C3B7;margin:.7rem 0 0;max-width:62ch}
26     .head .nav{display:flex;gap:1rem;font-size:.9rem;margin-top:1rem;flex-wrap:wrap}
27     .head .nav a{color:var(--lime);text-decoration:none}
28     .body{padding:26px 32px 8px}
29     .sec{padding:18px 0;border-top:1px solid var(--line)}
30     .sec:first-child{border-top:0}
31     .kick{font-size:.78rem;font-weight:700;letter-spacing:.06em;text-
transform:uppercase;color:var(--green-d)}
32     .sec h2{font-size:1.4rem;font-weight:800;letter-spacing:-.01em;margin:.35rem 0 0}
33     .sec p{color:#34453d;margin:.6rem 0 0}
34     .pill{display:inline-block;font-size:.72rem;font-weight:700;border-
radius:999px;padding:.2rem .6rem;margin-left:.4rem;vertical-align:.12em}
35     .pill.live{background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.35)}
36     .pill.build{background:#FAEEDA;color:#854F0B;border:1px solid #EF9F27}
37     ol,ul{margin:.6rem 0 0;padding-left:1.2rem}
38     li{margin:.25rem 0 0;color:#34453d}
39     li b{color:var(--tx)}
40     code{font-family:ui-monospace,SFMono-Regular,Menlo,Consolas,monospace;font-
size:.86em;background:#EEF3EC;border:1px solid var(--line);border-radius:5px;padding:.05rem
.35rem}
41     pre{background:#0C261F;color:#EAF3EE;border-radius:10px;padding:14px
16px;overflow:auto;margin:.8rem 0 0;font-size:.84rem;line-height:1.5}
42     pre code{background:none;border:0;padding:0;color:inherit}
43     .honest{display:flex;gap:.7rem;background:#fff;border:1px solid var(--line);border-
left:4px solid var(--green);border-radius:0 10px 10px 0;padding:12px 16px;margin:.9rem 0 0}
44     .honest b{color:var(--tx)}
45     .honest p{margin:.2rem 0 0;color:var(--mut);font-size:.93rem}
46     .notes{list-style:none;padding:0;margin:.8rem 0 0;display:grid;grid-template-
columns:1fr 1fr;gap:8px}
47     .notes li{display:flex;gap:.5rem;background:#FBF0ED;border:1px solid #f0d6cc;border-
radius:8px;padding:.5rem .7rem;color:#6b3a2a;font-size:.9rem;margin:0}
48     .moat{display:grid;grid-template-columns:1fr 1fr;gap:10px;margin-top:.8rem}
49     .moat div{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:10px;padding:10px
12px}
50     .moat h4{margin:0;font-size:.92rem;color:var(--green-d)}
51     .moat p{margin:.2rem 0 0;font-size:.86rem;color:#34453d}
52     .shot{display:flex;align-items:center;justify-content:center;text-
align:center;background:#EEF3EC;border:1px dashed #BfD3C6;border-
radius:10px;color:var(--mut);font-size:.82rem;padding:18px;margin-top:.8rem;min-height:96px}
53     .ghbtn{display:inline-flex;align-
items:center;gap:.5rem;background:#0C261F;color:#fff;font-weight:600;font-size:.9rem;text-
decoration:none;border-radius:999px;padding:.5rem .95rem;margin-top:.9rem}
54     .cta{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:12px;padding:16px
18px;margin:18px 0 6px;text-align:center}
55     .cta a{display:inline-block;background:var(--green);color:#04140D;font-

```

```

weight:700;text-decoration:none;border-radius:999px;padding:.6rem 1.3rem;margin-top:.5rem}
56     table{border-collapse:collapse;margin-top:.8rem;font-size:.86rem;width:100%}
57     th,td{border:1px solid var(--line);padding:.35rem .55rem;text-align:left}
58     th{background:#EEF3EC}
59     .foot{display:flex;justify-content:space-between;flex-wrap:wrap;gap:.5rem;padding:16px
32px 26px;color:var(--mut);font-size:.85rem}
60     .foot a{text-decoration:none}
61     @media (max-width:680px){.notes,.moat,.shots{grid-template-columns:1fr}}
62     /* annotation-tool screenshots (no footage/people ? pure UI) */
63     .shots{display:grid;grid-template-columns:1fr 1fr;gap:14px;margin-top:.9rem}
64     .shots figure{margin:0}
65     .shots img{width:100%;height:auto;display:block;border:1px solid var(--line);border-
radius:10px}
66     .shots figcaption{margin-top:.4rem;font-size:.82rem;color:var(--mut)}
67     .sample{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:10px;padding:11px
14px;margin:0 0 4px;font-size:.92rem;color:#34453d}
68     .sample a{font-weight:600}
69     </style>
70     </head>
71     <body>
72     <div class="sheet">
73     <div class="head">
74     <div class="top">
75     <a class="brand" href="/">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
76     <a href="/#join" style="color:#C7F2B0;font-weight:600;text-
decoration:none">Request access ?</a>
77     </div>
78     <h1>Annotate your footage. <span class="hl">Train a model that's yours.</span></h1>
79     <p>You can't train Gemini or GPT on your court footage. KhelSutra's direction is the
inverse ? a small, <b style="color:#EAF3EE">owned</b> rally model where the moat is your
consented dataset, on a commercially-clean, inspectable stack you control.</p>
80     <div class="nav"><a href="/">? KhelSutra home</a><a href="#annotate">Annotate</a><a
href="#train">Train your own model</a><a href="#setup">Setup &amp; use</a></div>
81     </div>
82
83     <div class="body">
84
85     <p class="sample">? <b>Want to see what KhelSutra produces?</b> A real sample reel
plays the moment you <a href="/#join">request access</a>.</p>
86
87     <section class="sec" id="annotate">
88     <div class="kick">Step 1 . real and shipping today</div>
89     <h2>Annotate your footage <span class="pill live">live today</span></h2>
90     <p><b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b> that
turns "watch a match" into golden labels. While you watch your own video in VLC, you mark each
rally's start and end plus how the point ended; it writes one row per rally to a plain CSV next
to your video. <b>Your footage never leaves your machine.</b> It covers five net-separated
racquet sports (badminton, tennis, table tennis, pickleball, padel).</p>
91     <a class="ghbtn" href="https://github.com/Khelsutra/rally-annotator"><svg
width="16" height="16" viewBox="0 0 16 16" fill="currentColor" aria-hidden="true"><path d="M8
0C3.58 0 0 3.58 0 8a8 8 0 0 0 5.47 7.59c.4.07.55-.17.55-.38 0-.19-.01-.82-.01-1.49-2.01.37-2.53-
.49-2.69-.94-.09-.23-.48-.94-.82-1.13-.28-.15-.68-.52-.01-.53.63-.01 1.08.58 1.23.82.72 1.21
1.87.87 2.33.66.07-.52.28-.87.51-1.07-1.78-.2-3.64-.89-3.64-3.95
0-.87.31-1.59.82-2.15-.08-.2-.36-1.02.08-2.12 0 0 .67-.21 2.2.82a7.4 7.4 0 0 1 2-.27c.68 0
1.36.09 2 .27 1.53-1.04 2.2-.82 2.2-.82.44 1.1.16 1.92.08 2.12.51.56.82 1.27.82 2.15 0 3.07-1.87
3.75-3.65 3.95.29.25.54.73.54 1.48 0 1.07-.01 1.93-.01 2.2 0 .21.15.46.55.38A8 8 0 0 0 16
8c0-4.42-3.58-8-8-8Z"/></svg> github.com/Khelsutra/rally-annotator</a>
92     <div class="shots">
93     <figure><figcaption>Enable it once: VLC ? View ? Rally
Annotator.</figcaption></figure>
94     <figure><figcaption>Mark each rally's
start/end + ending reason, then Save Rally.</figcaption></figure>

```

```

95         </div>
96         <p style="margin-top:1rem"><b>The flow, per rally:</b></p>
97         <ol>
98             <li><b>Mark START</b> on the serve-contact frame (pause/scrub for
accuracy).</li>
99             <li><b>Mark END</b> when the shuttle is dead.</li>
100            <li>Pick an <b>ending reason</b>, optionally a shot count, then <b>Save
Rally</b> ? one CSV row.</li>
101            <li>Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video later
to continue.</li>
102        </ol>
103        <p style="font-size:.9rem;color:var(--mut)">It's a click-driven dialog (no marking
hotkeys yet), and targets <b>VLC 3.0.x</b>.</p>
104    </section>
105
106    <section class="sec" id="train">
107        <div class="kick">Step 2 · the moat</div>
108        <h2>Train your own model <span class="pill build">open pipeline · in
build</span></h2>
109        <div class="honest" style="border-left-
color:var(--green);background:#EAF6EF;border-color:#BfE6D2">
110            <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">?</span>
111            <div>
112                <b>You don't have to train anything to start.</b>
113                <p>KhelSutra runs on a ready-made default, so you get rally detection and
reels <b>out of the box</b> ? nothing to set up. Training on your own footage (below) is an
<b>optional</b> power-up: a model tuned to your courts, your angles, your halls.</p>
114            </div>
115        </div>
116        <p>For those who want it, your labels feed an <b>owned</b> rally model ? trained
on <b>your</b> courts, <b>your</b> angles, <b>your</b> busy multi-court halls. The pipeline is
open and inspectable:</p>
117        <pre><code>annotate (VLC) ? &lt;video>.rallies.csv ? worker train ? your
model bundle (weights + a reviewable manifest)</code></pre>
118        <div class="moat">
119            <div><h4>You own it</h4><p>A model and dataset that are yours to keep and
improve ? not rented inference.</p></div>
120            <div><h4>Commercially clean</h4><p>MIT/Apache/BSD-only stack; we never train on
a paid LLM's output.</p></div>
121            <div><h4>Private & consented</h4><p>Footage stays yours; training use is
explicit opt-in, never automatic.</p></div>
122            <div><h4>Minors protected</h4><p>Footage involving minors is never used for
training and never published.</p></div>
123        </div>
124        <div class="honest">
125            <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">!</span>
126            <div>
127                <b>Read this honestly.</b>
128                <p>The labeling tool is real and shipping. The training pipeline is <b>open
and in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-
validation <b>mock</b>, and a real model needs a GPU. There is <b>no "Train now" button</b> yet,
and we make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise here
is <b>ownership, licensing, privacy and consent</b> ? not "more accurate than Gemini," and not
"one click to train."</p>
129            </div>
130        </div>
131    </section>
132
133    <section class="sec" id="setup">
134        <div class="kick">Step 3 · for power users</div>
135        <h2>Setup & use</h2>
136        <p><b>Install the plugin (VLC 3.0.x).</b> Copy <code>rally_annotator.lua</code>
into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools
? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally
Annotator</i>:</p>

```

```

137         <pre><code>Windows: %APPDATA%\vlc\lua\extensions\
138     macOS:  ~/Library/Application Support/org.videolan.vlc/lua/extensions/
139     Linux:   ~/.local/share/vlc/lua/extensions/</code></pre>
140     <p style="margin-top:1rem"><b>Record</b> per the <a href="/capture">one-page
capture checklist</a> (fixed tripod, full court, landscape, whole session) ? <b>annotate</b> in
VLC ? you get <code>&lt;video&gt;.rallies.csv</code>:</p>
141     <pre><code>rally_number,start_time,end_time,ending_reason,sport,shots_count
142     1,8.800,11.500,winner,badminton,9
143     2,24.389,46.589,unforced_error,badminton,21
144     3,49.183,54.683,let,badminton,</code></pre>
145     <p style="margin-top:.6rem;font-
size:.9rem;color:var(--mut)"><code>ending_reason</code> is one of: <code>unknown</code> .
<code>winner</code> . <code>forced_error</code> . <code>unforced_error</code> .
<code>service_fault</code> . <code>let</code> . <code>other</code>. Times are decimal seconds;
downstream tools read by column name.</p>
146     <p style="margin-top:1rem"><b>Train</b> (developer CLI). A GPU-free dry run
validates the whole pipeline on a CPU mock; a real model needs a GPU:</p>
147     <pre><code># GPU-free dry run (CPU mock ? pipeline validation only):
148     python -m backend.worker train --corpus-uri &lt;bucket&gt; --out-uri &lt;bucket&gt;
--version 0.1.0
149
150     # real trajectories (needs a GPU + the native WASB runner, in build):
151     python -m backend.worker train ... --trajectory-source detector --segmenter
wasb_hybrid</code></pre>
152     <p style="margin-top:.6rem;font-size:.9rem;color:var(--mut)">One join rule: keep
the video <b>byte-identical</b> to what you annotated (don't re-encode after labeling) ? labels
match videos by content hash.</p>
153     </section>
154
155     <section class="sec">
156         <div class="kick">So expectations stay honest</div>
157         <h2>What this is not</h2>
158         <ul class="notes">
159             <li>Not a one-click trainer ? training is an offline CLI today.</li>
160             <li>Not in-browser ? labeling runs in VLC on your machine.</li>
161             <li>Not an accuracy claim vs Gemini/GPT ? no such benchmark.</li>
162             <li>Shot-type, player and score detection are roadmap.</li>
163         </ul>
164     </section>
165
166     <div class="cta">
167         <b>Want in?</b>
168         <div><a href="/#join">Request alpha access</a></div>
169     </div>
170
171 </div>
172 <div class="foot">
173     <span><a href="/">khelsutra.guru</a> . <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a></span>
174     <span>Reels carry a "Generated by Khelsutra.guru" mark.</span>
175 </div>
176 </div>
177 </body>
178 </html>
179

```

6. user (2026-06-21T03:17:22.397Z)

```

1    // Always-on VM host for the KhelSutra site ? dependency-free (Node 22+ only).
2    // Serves public/ and POST /api/request-access into SQLite (node:sqlite), using the
3    // SAME handler logic as the Cloudflare Worker (src/index.js). This is the portability
4    // fallback "if Cloudflare acts out" ? see docs/PORTABILITY.md.
5    //
6    //   PORT=8080 DB_PATH=/var/lib/khelsutra/access.db node server.js
7    //

```

```

8     import { createServer } from "node:http";
9     import { readFile } from "node:fs/promises";
10    import { join, extname, normalize } from "node:path";
11    import { DatabaseSync } from "node:sqlite";
12    import { handleRequest } from "./src/index.js";
13    import { sqliteStore } from "./src/store.js";
14    import { noopNotify } from "./src/notify.js";
15
16    const PORT = Number(process.env.PORT) || 8080;
17    const ROOT = import.meta.dirname;
18    const PUBLIC = join(ROOT, "public");
19    const DB_PATH = process.env.DB_PATH || join(ROOT, "access.db");
20
21    const db = new DatabaseSync(DB_PATH);
22    db.exec(await readFile(join(ROOT, "schema.sql"), "utf8")); // CREATE TABLE IF NOT EXISTS
? idempotent
23    const store = sqliteStore(db);
24    const notify = noopNotify(); // VM host: no email yet (add SMTP later ? see
docs/PORTABILITY.md)
25
26    const TYPES = {
27        ".html": "text/html; charset=utf-8", ".png": "image/png", ".svg": "image/svg+xml",
28        ".css": "text/css", ".js": "text/javascript", ".ico": "image/x-icon", ".txt":
"text/plain",
29        ".mp4": "video/mp4", ".webm": "video/webm", ".gif": "image/gif", ".jpg": "image/jpeg",
".jpeg": "image/jpeg",
30    };
31
32    async function toRequest(req) {
33        const url = `http://${req.headers.host || "localhost"}${req.url}`;
34        let body;
35        if (req.method !== "GET" && req.method !== "HEAD") {
36            const chunks = [];
37            for await (const c of req) chunks.push(c);
38            body = Buffer.concat(chunks);
39        }
40        return new Request(url, { method: req.method, headers: req.headers, body });
41    }
42
43    async function send(res, response) {
44        res.statusCode = response.status;
45        for (const [k, v] of response.headers) res.setHeader(k, v);
46        res.end(Buffer.from(await response.arrayBuffer()));
47    }
48
49    async function serveStatic(pathname, res) {
50        const rel = pathname === "/" ? "index.html"
51            : pathname === "/capture" ? "capture.html"
52            : pathname === "/own-model" ? "own-model.html"
53            : pathname.replace(/^\/+/, "");
54        const file = normalize(join(PUBLIC, rel));
55        if (!file.startsWith(PUBLIC)) { res.statusCode = 403; return res.end("forbidden"); }
56        try {
57            const data = await readFile(file);
58            res.setHeader("content-type", TYPES[extname(file)] || "application/octet-stream");
59            res.end(data);
60        } catch {
61            res.statusCode = 404;
62            res.end("not found");
63        }
64    }
65
66    createServer(async (req, res) => {
67        try {
68            const pathname = decodeURIComponent(new URL(`http://${req.url}`).pathname);

```

```

69         if (pathname === "/api/request-access") {
70             if (req.method !== "POST") { res.statusCode = 405; return
res.end('{"ok":false,"error":"method not allowed"}'); }
71             return await send(res, await handleRequest(await toRequest(req), store, notify));
72         }
73         return await serveStatic(pathname, res);
74     } catch (err) {
75         res.statusCode = 500;
76         res.end('{"ok":false,"error":"server error"}');
77         console.error(err);
78     }
79     }).listen(PORT, () => console.log(`khelsutra site listening on :${PORT} (sqlite:
${DB_PATH}`));
80

```

7. assistant (2026-06-21T03:17:25.436Z)

Now let me read the remaining files: the SPA-shared source modules and the README.

8. user (2026-06-21T03:17:26.441Z)

```

1      // Cloudflare Worker for khelsutra.guru ? serves the static site and handles the
2      // Request-Access form: POST /api/request-access -> validate -> insert into D1 (binding
DB).
3      // Pure helpers are exported so they can be unit-tested without a live Worker/D1.
4
5      import { d1Store } from "./store.js";
6      import { cfEmailNotify } from "./notify.js";
7
8      const SEGMENTS = ["academy", "individual"];
9      const GPU = ["yes", "unsure", "no", "prefer-cloud"];
10     const COURTS = ["1", "2-4", "5+"];
11     const STORAGE = ["gdrive", "onedrive", "dropbox", "bucket", "local", "unsure"];
12
13     function str(v, max) {
14         if (v == null) return null;
15         const s = String(v).trim();
16         return s ? s.slice(0, max) : null;
17     }
18
19     // Honeypot: humans never fill the hidden "company" field.
20     export function isBot(p) {
21         return !(p && typeof p.company === "string" && p.company.trim() !== "");
22     }
23
24     export function validate(p) {
25         if (!p || typeof p !== "object") return { ok: false, error: "bad payload" };
26         const email = String(p.email || "").trim();
27         if (!/^[^\s]+@[^\s]+\.[^\s]+$/.test(email)) return { ok: false, error: "valid email
required" };
28         return { ok: true };
29     }
30
31     export function toRow(p, meta = {}) {
32         const storage = Array.isArray(p.storage)
33             ? p.storage.filter((s) => STORAGE.includes(s)).join(",")
34             : "";
35         return {
36             segment: SEGMENTS.includes(p.segment) ? p.segment : null,
37             name: str(p.name, 200),
38             email: str(p.email, 320),
39             city: str(p.city, 200),
40             org_name: str(p.org_name, 200),
41             courts: COURTS.includes(p.courts) ? p.courts : null,
42             has_gpu: GPU.includes(p.has_gpu) ? p.has_gpu : null,

```



```

43     storage,
44     message: str(p.message, 4000),
45     consent: p.consent ? 1 : 0,
46     country: str(meta.country, 8),
47     user_agent: str(meta.userAgent, 400),
48   };
49 }
50
51 function json(obj, status = 200) {
52   return new Response(JSON.stringify(obj), { status, headers: { "content-type":
"application/json" } });
53 }
54
55 export async function handleRequest(request, store, notify) {
56   let body;
57   try {
58     body = await request.json();
59   } catch {
60     return json({ ok: false, error: "invalid json" }, 400);
61   }
62   if (isBot(body)) return json({ ok: true }); // silently drop bots
63   const v = validate(body);
64   if (!v.ok) return json({ ok: false, error: v.error }, 400);
65
66   const r = toRow(body, {
67     country: request.headers.get("cf-ipcountry"),
68     userAgent: request.headers.get("user-agent"),
69   });
70
71   await store.insertAccessRequest(r);
72   try { await notify?.notify(r); } catch { /* email is best-effort; never fail the
request */ }
73
74   return json({ ok: true });
75 }
76
77 export default {
78   async fetch(request, env) {
79     const url = new URL(request.url);
80     if (url.pathname === "/api/request-access") {
81       if (request.method !== "POST") return json({ ok: false, error: "method not
allowed" }, 405);
82       return handleRequest(request, d1Store(env.DB), cfEmailNotify(env.NOTIFY,
env.NOTIFY_FROM, env.NOTIFY_TO));
83     }
84     return env.ASSETS.fetch(request); // everything else: static assets
85   },
86 };
87

```

9. user (2026-06-21T03:17:26.917Z)

```

1  // Storage adapters for Request-Access submissions.
2  //
3  // PORTABILITY (see docs/PORTABILITY.md): the business logic (validate / toRow /
4  // handleRequest in index.js) is runtime-agnostic ? ALL database coupling lives here.
5  // The Cloudflare Worker uses d1Store(env.DB); an always-on VM uses sqliteStore(db)
6  // over node:sqlite (or better-sqlite3). Same schema.sql, same INSERT ? zero dialect
7  // change. To move hosts, swap the adapter, not the logic.
8
9  export const INSERT_SQL =
10    `INSERT INTO access_requests
11      (segment, name, email, city, org_name, courts, has_gpu, storage, message, consent,
12      country, user_agent)
13      VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?, ?)`;

```

```

13
14 export const insertArgs = (r) => [
15   r.segment, r.name, r.email, r.city, r.org_name, r.courts,
16   r.has_gpu, r.storage, r.message, r.consent, r.country, r.user_agent,
17 ];
18
19 // Cloudflare D1 (async): prepare(sql).bind(...args).run()
20 export function d1Store(DB) {
21   return {
22     async insertAccessRequest(r) {
23       await DB.prepare(INSERT_SQL).bind(...insertArgs(r)).run();
24     },
25   };
26 }
27
28 // node:sqlite / better-sqlite3 (sync): prepare(sql).run(...args). For the VM host.
29 export function sqliteStore(db) {
30   const stmt = db.prepare(INSERT_SQL);
31   return {
32     async insertAccessRequest(r) {
33       stmt.run(...insertArgs(r));
34     },
35   };
36 }
37

```

10. user (2026-06-21T03:17:27.362Z)

```

1 // Notification adapters (best-effort ? a notify failure must never fail a submission).
2 // Cloudflare path: Email Routing's send_email binding -> a VERIFIED destination (free).
3 // VM path: no-op for now (add SMTP later ? see docs/PORTABILITY.md).
4
5 export function buildSubmissionEmail(r) {
6   const text = [
7     `Segment: ${r.segment || "?"}`,
8     `Name:    ${r.name || ""}`,
9     `Email:   ${r.email || ""}`,
10    `City:    ${r.city || ""}`,
11    r.org_name ? `Academy: ${r.org_name} (${r.courts || "?"} courts)` : null,
12    `GPU:     ${r.has_gpu || ""}`,
13    `Storage: ${r.storage || ""}`,
14    `Consent: ${r.consent ? "yes" : "no"}`,
15    r.message ? `\\nMessage:\\n${r.message}` : null,
16  ].filter(Boolean).join("\\n");
17   const subject = `New KhelSutra alpha request ? ${r.segment || "?"} · ${r.email ||
18   "?"}`;
19   return { subject, text };
20 }
21
22 // Cloudflare Email Routing send_email binding ( `[[send_email]]` in wrangler.toml ).
23 // `to` must be a verified destination address. Dynamically imports cloudflare:email so
24 // this module stays loadable under Node (the VM path / tests never call into it).
25 export function cfEmailNotify(binding, from, to) {
26   return {
27     async notify(r) {
28       if (!binding || !from || !to) return;
29       const { subject, text } = buildSubmissionEmail(r);
30       const raw =
31         `From: KhelSutra <${from}>\\r\\nTo: ${to}\\r\\nSubject: ${subject}\\r\\n` +
32         `\\nMIME-Version: 1.0\\r\\nContent-Type: text/plain; charset=utf-8\\r\\n\\r\\n${text}`;
33       const { EmailMessage } = await import("cloudflare:email");
34       await binding.send(new EmailMessage(from, to, raw));
35     },
36   };
37 }

```

```

37
38     export function noopNotify() {
39         return { async notify() {} };
40     }
41

```

11. user (2026-06-21T03:17:27.465Z)

```

1     # site/ ? public marketing site + Request-Access API (Cloudflare Worker)
2
3     The public site at [khelsutra.guru](https://khelsutra.guru) ? a static landing page
+
4     `/capture` checklist ? plus a small Worker that backs the Request-Access form with
**Cloudflare D1**.
5
6     ## Layout
7     - `public/` ? static assets served as-is (`index.html`, `capture.html`, `og.png`).
8     - `src/index.js` ? the Worker: serves `public/` and handles `POST /api/request-access` ?
D1.
9     - `src/index.test.js` ? unit tests for the form logic.
10    - `wrangler.toml` ? Worker + static-assets + D1 binding config.
11    - `schema.sql` ? the `access_requests` D1 table.
12    - `make_og.py` ? regenerates `public/og.png` (Pillow + Windows fonts): `python
make_og.py`.
13
14    ## Develop / test
15    ```
16    npm test      # node --test src/ (no install needed)
17    npm run dev   # npx wrangler dev ? local Worker + D1
18    ```
19
20    ## Deploy (owner ? our Cloudflare account)
21    One-time:
22    ```
23    npx wrangler d1 create khelsutra-access          # paste database_id
into wrangler.toml
24    npx wrangler d1 execute khelsutra-access --remote --file=schema.sql
25    ```
26    Then either:
27    - **Manual:** `npx wrangler deploy`, or
28    - **Git (recommended):** connect this repo in Cloudflare ? Workers Builds (root dir
`site/`), bind the
29    D1 database ? every merge to `master` deploys; PRs get preview URLs.
30
31    ## Notes
32    - The form posts to `/api/request-access`; if the Worker is unreachable it falls back to
a prefilled
33    `mailto:hello@`, so it degrades gracefully.
34    - `hello@khelsutra.guru` relies on Cloudflare Email Routing.
35    - The Web Analytics beacon in `public/index.html` has a placeholder token
(`REPLACE_WITH_CF_TOKEN`)
36    ? paste the real token or enable Cloudflare automatic setup.
37

```

12. assistant (2026-06-21T03:17:29.964Z)

Now let me check the directory structure and confirm there's no framework or i18n present, and locate the SPA to understand where a shared catalog/shim could live.

13. user (2026-06-21T03:17:32.270Z)

```

=== site/ tree ===
site/README.md
site/access.db

```

```

site/make_og.py
site/package-lock.json
site/package.json
site/public/capture.html
site/public/img/annotate-enable.png
site/public/img/annotate-tool.png
site/public/index.html
site/public/og.png
site/public/own-model.html
site/public/video/tool-cuj.mp4
site/schema.sql
site/scripts/droplet-smoke.sh
site/scripts/parity-check.sh
site/scripts/provision-vm.sh
site/scripts/teardown-vm.sh
site/server.js
site/src/assets.test.js
site/src/deploy-config.test.js
site/src/index.js
site/src/index.test.js
site/src/notify.js
site/src/server.test.js
site/src/store.js
site/src/ux.dom.test.js
site/wrangler.toml

```

```
=== package.json (site) ===
```

```

{
  "name": "khelsutra-site",
  "private": true,
  "type": "module",
  "scripts": {
    "test": "node --test",
    "test:cf": "node --test src/index.test.js",
    "test:vm": "node --test src/server.test.js",
    "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
    "deploy": "wrangler deploy",
    "dev": "wrangler dev",
    "og": "python make_og.py"
  },
  "devDependencies": {
    "jsdom": "^29.1.1"
  }
}

```

```
=== repo root listing ===
```

```

total 38
drwxr-xr-x 1 avidu 197609  0 Jun 20 23:27 .
drwxr-xr-x 1 avidu 197609  0 Jun 21 06:51 ..
drwxr-xr-x 1 avidu 197609  0 Jun 20 15:20 .claude
drwxr-xr-x 1 avidu 197609  0 Jun 21 08:47 .git
-rw-r--r-- 1 avidu 197609 297 Jun 20 23:27 .gitattributes
drwxr-xr-x 1 avidu 197609  0 Jun 20 12:43 .github
-rw-r--r-- 1 avidu 197609  78 Jun 20 18:40 .gitignore
-rw-r--r-- 1 avidu 197609 5823 Jun 20 23:06 NEXT_STEPS.md
-rw-r--r-- 1 avidu 197609 925 Jun 20 08:37 README.md
drwxr-xr-x 1 avidu 197609  0 Jun 20 23:14 docs
drwxr-xr-x 1 avidu 197609  0 Jun 21 08:20 site
drwxr-xr-x 1 avidu 197609  0 Jun 20 22:08 web

```

14. user (2026-06-21T03:17:39.010Z)

```
=== grep for i18n / data-i18n / t( / catalog / locale across site ===
```

```

site/node_modules/@bramus/specificity/dist/index.js
site/node_modules/css-tree/dist/csstree.esm.js

```

```

site/node_modules/css-tree/dist/csstree.js
site/node_modules/jsdom/lib/jsdom/living/domparsing/parse5-adapter-serialization.js
site/node_modules/lru-cache/dist/commonjs/browser/index.min.js
site/node_modules/lru-cache/dist/commonjs/index.min.js
site/node_modules/lru-cache/dist/commonjs/node/index.min.js
site/node_modules/lru-cache/dist/esm/browser/index.min.js
site/node_modules/lru-cache/dist/esm/index.min.js
site/node_modules/lru-cache/dist/esm/node/index.min.js
site/node_modules/mdn-data/l10n/css.json
site/node_modules/parse5/dist/serializer/index.js
site/node_modules/parse5/dist/tree-adapter/default.js
site/node_modules/tldts/dist/index.cjs.min.js
site/node_modules/tldts/dist/index.esm.min.js
site/node_modules/undici/lib/mock/mock-utils.js
site/public/capture.html
site/public/index.html
site/public/own-model.html
--- occurrences ---
site/node_modules/jsdom/lib/jsdom/living/domparsing/parse5-adapter-
serialization.js:33:exports.getTextNodeContent = exports.getCommentNodeContent = node =>
node.data;
site/node_modules/parse5/dist/serializer/index.js:154:    const content =
treeAdapter.getTextNodeContent(node);
site/node_modules/parse5/dist/tree-adapter/default.js:135:    getTextNodeContent(textNode) {
site/node_modules/undici/lib/mock/mock-utils.js:37:        return [headerName.toLocaleLowerCase(),
headerValue]
site/node_modules/undici/lib/mock/mock-utils.js:49:        if (headers[i].toLocaleLowerCase() ===
key.toLocaleLowerCase()) {
site/node_modules/undici/lib/mock/mock-utils.js:58:        return
lowerCaseEntries(headers)[key.toLocaleLowerCase()]

```

15. assistant (2026-06-21T03:17:42.137Z)

The grep on the HTML files matched (they appear in the file list) but the occurrence dump only showed node_modules. Let me check what actually matched in the HTML files, and inspect the `web/` SPA directory (the likely shared-catalog home) plus the i18n planning docs referenced in the handoff.

16. user (2026-06-21T03:17:46.144Z)

```

=== HTML matches for i18n-ish tokens (these are just 'lang=' / the word in copy) ===
exit: 1

```

```

=== lang= occurrences in HTML ===
site/public/capture.html:2:<html lang="en">
site/public/index.html:2:<html lang="en">
site/public/index.html:452:    <div class="step"><div class="n">?</div><h3>More sports &
languages</h3><p>Table tennis next; Kannada and Hindi alongside English.</p></div>
site/public/own-model.html:2:<html lang="en">

```

17. user (2026-06-21T03:17:48.552Z)

```

=== web/ (SPA?) tree, depth-limited ===
web/.gitignore
web/README.md
web/index.html
web/package-lock.json
web/package.json
web/src/App.tsx
web/src/api/client.test.ts
web/src/api/client.ts
web/src/api/types.ts
web/src/components/CompileResult.tsx
web/src/components/QueryBar.examples.test.ts

```

```
web/src/components/QueryBar.tsx
web/src/components/RallyGrid.tsx
web/src/components/SelectionFooter.tsx
web/src/hooks/useRallySelection.ts
web/src/index.css
web/src/lib/floor.test.ts
web/src/lib/floor.ts
web/src/lib/format.test.ts
web/src/lib/format.ts
web/src/lib/log.ts
web/src/lib/query.test.ts
web/src/lib/query.ts
web/src/lib/selection.test.ts
web/src/lib/selection.ts
web/src/main.tsx
web/tsconfig.json
web/vite.config.ts
```

=== web/package.json ===

```
{
  "name": "khelsutra-web",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "description": "KhelSutra Studio ? operator console SPA (drives the rally indexer engine).",
  "scripts": {
    "dev": "vite",
    "build": "vite build",
    "preview": "vite preview",
    "typecheck": "tsc --noEmit",
    "test": "vitest run"
  },
  "dependencies": {
    "react": "^19.0.0",
    "react-dom": "^19.0.0"
  },
  "devDependencies": {
    "@tailwindcss/vite": "^4.0.0",
    "@types/react": "^19.0.0",
    "@types/react-dom": "^19.0.0",
    "@vitejs/plugin-react": "^4.3.4",
    "tailwindcss": "^4.0.0",
    "typescript": "^5.7.0",
    "vite": "^6.0.0",
    "vitest": "^3.0.0"
  }
}
```

18. user (2026-06-21T03:17:50.451Z)

=== i18n / UI docs ===

LOCAL_APPLIANCE_ARCHITECTURE.md

--- find I18N_PLAN / UI_PROPOSAL anywhere ---

19. assistant (2026-06-21T03:17:54.273Z)

So the SPA lives in `web/` (React 19 + Vite + TypeScript + Tailwind), and there is **no** i18n in either the SPA or the site. The `I18N\_PLAN.md` / `UI\_PROPOSAL.md` referenced in the handoff are in the *other* repo (badminton-highlight-indexer engine docs), not here. Let me confirm the SPA has no i18n and check the test files I was told to note for coverage, plus the schema.

20. user (2026-06-21T03:17:57.988Z)

=== i18n in web/ SPA? ===

```
exit=0
```

```
=== web/src/lib/format.ts (where a t() shim might naturally live) head ===  
// Small pure formatters (node-testable, no React).
```

```
/** Seconds ? "m:ss" (e.g. 65 ? "1:05"). Rounds to the nearest second; clamps negatives to 0. */  
export function mmss(totalSeconds: number): string {  
  const s = Math.max(0, Math.round(totalSeconds || 0));  
  const m = Math.floor(s / 60);  
  return `${m}:${String(s % 60).padStart(2, "0")}`;  
}
```

```
/** "3 rallies" / "1 rally" ? count with a correctly pluralized noun. */  
export function pluralize(n: number, one: string, many = one + "s"): string {  
  return `${n} ${n === 1 ? one : many}`;  
}
```

```
/** Turn a user reel name into a safe bare `.mp4` filename for POST /api/compile. The engine's  
 * `safe_output_filename` (backend/utils/paths.py) rejects path separators / traversal /  
absolute  
 * names, so we slugify to [a-z0-9-] and always end in `.mp4`. Empty ? "highlights.mp4". */  
export function reelFilename(name: string): string {  
  const slug = (name || "").  
    .toLowerCase()  
    .replace(/^[a-z0-9-]+/g, "-")  
    .replace(/^-+|-+$/g, "")  
    .slice(0, 80);  
  return `${slug || "highlights"}.mp4`;  
}
```

```
=== schema.sql ===  
-- D1 schema for Request-Access submissions.  
-- Apply: npx wrangler d1 execute khelsutra-access --remote --file=schema.sql  
CREATE TABLE IF NOT EXISTS access_requests (  
  id          INTEGER PRIMARY KEY AUTOINCREMENT,  
  created_at  TEXT NOT NULL DEFAULT (datetime('now')),  
  segment     TEXT,           -- 'academy' | 'individual'  
  name        TEXT,  
  email       TEXT NOT NULL,  
  city        TEXT,  
  org_name    TEXT,           -- academy / club name  
  courts      TEXT,           -- '1' | '2-4' | '5+'  
  has_gpu     TEXT,           -- 'yes' | 'unsure' | 'no' | 'prefer-cloud'  
  storage     TEXT,           -- csv of gdrive,onedrive,dropbox,bucket,local,unsure  
  message     TEXT,           -- free text  
  consent     INTEGER DEFAULT 0,  
  country     TEXT,           -- coarse, from cf-ipcountry (no raw IP stored)  
  user_agent  TEXT  
);
```

21. user (2026-06-21T03:17:59.568Z)

```
=== site test files: what they cover (titles) ===  
--- site/src/assets.test.js ---  
test("core public assets exist and are non-empty", () => {  
  test("landing page wires the Request-Access form to the API", () => {  
    test("submitting the form shows an obvious in-flight state (no silent freeze)", () => {  
      test("OG + canonical meta point at the live https origin", () => {  
        test("the sample reel is GATED behind sign-up + starts at a RANDOM point (not shown openly)", () => {  
          => {  
            test("the TOOL screencast is self-hosted, footage-free, and revealed only after sign-up", () => {  
              {  
                test("the post-signup reveal keeps its watchability affordances (manual close + play-gated auto-close)", () => {  
                  test("the capture checklist is linked and is a real page", () => {
```

```

test("the landing page surfaces how to record reliably (so users can set up with confidence)",
() => {
test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
test("the own-model page exists, is honestly scoped, and is linked from the landing page", () =>
{
--- site/src/deploy-config.test.js ---
test("wrangler `name` matches the git-connected Worker that owns khelsutra.guru", () => {
test("wrangler `main` and the assets directory point at paths that exist", () => {
test("D1 binding is wired (the Request-Access form persists to D1)", () => {
test("email-on-registration send binding + notify vars are present", () => {
--- site/src/index.test.js ---
test("validate requires a well-formed email", () => {
test("isBot detects a filled honeypot only", () => {
test("toRow maps + sanitizes a valid payload", () => {
test("toRow rejects invalid enum values", () => {
test("handleRequest inserts a valid submission via the store", async () => {
test("handleRequest drops a bot without inserting", async () => {
test("handleRequest rejects a bad email with 400", async () => {
test("handleRequest rejects invalid JSON with 400", async () => {
test("diStore issues the bound INSERT (Cloudflare path)", async () => {
test("sqliteStore persists a real row (node:sqlite round-trip ? the VM path)", async () => {
test("fetch routes: POST /api hits the handler, other paths delegate to ASSETS", async () => {
test("fetch rejects non-POST to the API with 405", async () => {
test("buildSubmissionEmail summarizes the submission", () => {
test("handleRequest notifies on a valid submission; a notify failure never breaks it", async ()
=> {
test("handleRequest does NOT notify on a bot or a bad email", async () => {
--- site/src/server.test.js ---
test("[VM host] server.js serves the form", async () => {
test("[VM host] serves /capture and /og.png", async () => {
test("[VM host] serves the tool screencast as video/mp4 (plays in the post-signup reveal)",
async () => {
test("[VM host] serves /own-model", async () => {
test("[VM host] POST /api/request-access persists to SQLite", async () => {
test("[VM host] honeypot + bad email are rejected without persisting", async () => {
test("[VM host] GET /api/request-access -> 405", async () => {
--- site/src/ux.dom.test.js ---
test("submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?')", async () =>
{
submit();
test("on failure the button is restored ? never stuck on a frozen 'Sending?'", async () => {
submit();
test("after sign-up BOTH videos appear and a ? closes the reveal", async () => {
submit();
test("the auto-close HOLDS while the reel is playing (no mid-watch cut-off)", async () => {
submit();

```

22. assistant (2026-06-21T03:20:41.845Z)

I now have a complete picture. Let me do a final precise count of user-facing strings by reviewing the exact line ranges, then produce the brief. I have everything I need; no further reads required.

Here is the brief.

KhelSutra Marketing Site ? i18n + UX Mapping Brief

Scope: `C:/Users/avidu/Projects/khelsutra/site/` (the public marketing site + Request-Access API). All line refs are to files in that directory.

0. Confirmation: NO framework, NO i18n today (with evidence)

****No framework on the marketing site.****

- All three pages are hand-authored static HTML with a single inline `<style>` block and (only on `index.html`) one inline `<script>`. No build step, no template engine, no JSX/Vue/Svelte.
- `site/package.json` has ****no**** UI framework ? only `jsdom` as a devDependency (for DOM tests); scripts are `node --test`, `wrangler deploy/dev`, `python make_og.py`.
- `site/server.js:8-14` imports only Node builtins (`node:http`, `node:fs/promises`, `node:path`, `node:sqlite`) plus three local `./src/*` modules. Header comment: ****dependency-free (Node 22+ only)**** (`server.js:1`).
- `serveStatic` (`server.js:49-64`) reads the `.html` file off disk and streams the bytes verbatim ? ****no server-side rendering or interpolation**** of page copy. The only path-mapping is `/?index.html`, `/capture?capture.html`, `/own-model?own-model.html` (`server.js:50-53`).

****No i18n anywhere.****

- `grep -rniE "data-i18n|i18n|i18next|react-intl|formatjs|gettext|locale=|bt\(['\"]|useTranslation"` over `site/public/*.html`, `site/src/`, and `web/src/` returns ****zero matches**** outside `node_modules`. (The only hits in `node_modules` are unrelated: `toLocaleLowerCase`, `mdn-data l10n CSS`.)
- Every page is hardcoded `<html lang="en">` (`index.html:2`, `capture.html:2`, `own-model.html:2`).
- The only occurrences of `"Kannada"/"Hindi"` are ****English marketing copy promising future localization****, not actual translations: `index.html:452` (`"Table tennis next; Kannada and Hindi alongside English."`).

****The SPA (`web/`) also has no i18n.**** It is a separate React 19 + Vite + TypeScript + Tailwind app (`web/package.json`); `grep` for any i18n token over `web/src/` returns nothing. So there is ****no existing shared catalog**** for the site to plug into ? the catalog format must be created. The `I18N_PLAN.md` / `UI_PROPOSAL.md` referenced in the session handoff live in the ****other**** repo (the `badminton-highlight-indexer` engine), not in `khelsutra/`.

****Conclusion:**** the site is vanilla HTML/CSS/JS with a dependency-free Node/SQLite (and parallel Cloudflare Worker) backend. i18n is greenfield on both the site and the SPA.

1. First-contact USER FLOW (step by step)

The journey from landing to the post-signup video reveal:

1. ****Land on the homepage**** (`/` ? `index.html`). The sticky header (`index.html:228-240`) shows the brand + nav (How it works / Why it's hard / Own your model / Roadmap / FAQ) and a dark "Request access" button (`:238`) that anchors to `#join`.

2. ****Hero pitch**** (`:243-290`). Eyebrow "Invite-only alpha · Bengaluru", H1 "Every rally, indexed. The dead time, gone.", a lead paragraph, and ****three CTAs**** (`:250-252`): "Request alpha access", "See how it works", and "See it in action + a real reel" ? the last two also point at `#join/#how`. A static "reel card" mock (`:264-287`) visualizes "44 rallies · 18 min".

3. ****Read / scroll the marketing sections.**** In DOM order: `#how` (What it does today, 4 cards), `#record` (capture golden-rule + 4 cards, links to `/capture`), `#diff` (the multi-court hard problem), `#sharper` (gets sharper from footage + honest disclaimer), `#ask` (plain-English reel queries ? coming soon), `#roadmap` (5-step roadmap toward an "assistant coach"), `#not` (what KhelSutra is NOT), `#faq` (7 `<details>` Q&As). A user can also detour to `/capture` (checklist) or `/own-model` (annotate + train).

4. ****Reach the Request-Access form**** (`#join`, `:492-578`). A teaser line under the heading promises the payoff: ****"Sign up to watch the tool in action ? and a 30-second sample reel it made ? the moment you're in."**** (`:498`).

5. ****Fill the form**** (`<form id="af">`, `:501-573`). Choosing "Coaching academy / club" reveals two extra academy-only rows via a `change` listener that toggles `is-academy` on the form (`:661-663`, CSS `.acad{display:none}` / `.af.is-academy .acad{display:block}` at `:193-194`).

Full field inventory in \$2.

6. ****Submit**** (`submit` handler, `:679-710`):
 - Honeypot check ? if the hidden `company` field is filled, silently `return` (`:681`).
 - `f.checkValidity()` ? native `reportValidity()` if invalid (`:682`). Required fields: `segment`, `name`, `email`.
 - Button enters an in-flight state: disabled, `aria-busy`, spinner + "Sending?" (`:685-687`).
 - `fetch('/api/request-access', POST, JSON)` (`:697`). Payload assembled at `:689-694` (segment, name, email, city, org_name, courts, has_gpu, storage[], message, consent).
7. ****On success (r.ok)**** (`:700-704`): the form is hidden, the `#af-done` confirmation is unhidden ? ****Thanks ? we've got it. We'll be in touch? ?**** + ****While you're here: see the tool in action, and a real 30-second reel it made.**** (`:575`) ? then `revealAfterSignup()` fires.
8. ****Post-signup reveal**** (`revealAfterSignup`, `:613-659`): injects into `#reel-reveal`:
 - ****Video 1 ? "The tool in action"**: a self-hosted, footage-free screencast `/video/tool-cuj.mp4`, autoplay/muted/loop (`:623-624`).**
 - ****Video 2 ? "A real reel it made"**: a gated `youtube-nocookie.com` player (video id `ajTCZ7pJW\_o`) that ****seeks to a random start point**** so each signup sees a different ~30s window (`:642-654`).**
 - A "Generated by Khelsutra.guru" stamp + a live auto-close countdown (`:627`), which ****pauses while the reel is playing**** (`hold` flag via `onStateChange`, `:636`/`/:655`) so a viewer is never cut off mid-watch; a manual "? Close" button also closes it (`:622`, `:640`).
9. ****On failure**** (`:705-709`): button is restored, then the page falls back to a ****prefilled `mailto:hello@khelsutra.guru`**** (`mailtoFallback`, `:664-678`) ? graceful degradation if the Worker/API is unreachable.

****Server side of step 6?7**** (`src/index.js::handleRequest`, `:55-75`, shared by both Worker and VM host): parse JSON (400 "invalid json" on failure) ? `isBot` drops bots returning `{ok:true}` ? `validate` requires a well-formed email (400 "valid email required") ? `toRow` sanitizes/whitelists enums ? `store.insertAccessRequest` ? best-effort `notify` (email, never fails the request) ? `{ok:true}`.

2. User-facing string inventory (grouped, with counts)

Counts are of distinct user-visible string *units* (a heading, a sentence/paragraph, a label, an option, a button, a stamp). Pure-decorative glyphs (??? etc., all `aria-hidden`) are ****excluded****. SEO/meta strings are listed separately since they're translatable but not on-screen.

A. `index.html` ? landing page

****A0. `<head>` meta / SEO (translatable, off-screen)**** ? `:6-18`: `title`, `meta description`, `og:title`, `og:description`, `twitter:title`, `twitter:description` ? ****6 strings**** (4 distinct sentences, some reused across OG/Twitter).

****A1. Header / nav**** (`:230-238`): brand "KhelSutra"; nav links "How it works", "Why it's hard", "Own your model", "Roadmap", "FAQ"; button "Request access" ? ****7****.

****A2. Hero**** (`:246-260`): eyebrow "Invite-only alpha · Bengaluru"; H1 (2 parts: "Every rally, indexed." / "The dead time, gone."); lead paragraph; 3 CTA buttons ("Request alpha access", "See how it works", "See it in action + a real reel"); hero-note "A phone or GoPro on a tripod is all you need. No special hardware."; 3 loop chips ("Auto-index rallies", "Dead time removed", "Download your reel") ? ****~11****.

****A3. Hero reel-card mock**** (`:267-283`): "match_2026.mp4 · indexed", "Rallies detected", "44 found", "Highlight reel · 44 rallies · 18 min", "dead time removed · ready to download" ? ****5****.

****A4. `#how` section**** (`:295-318`): kicker "What it does today"; H2; intro p; ****4 cards**** (title + body each): "Every rally, indexed", "Dead time removed", "Process once, reuse", "Stitched reel + summary" ? ****11**** (3 + 8).

****A5. `#record` section**** (':327-361'): kicker "Record it right"; H2 "Five minutes of setup ? reliably great reels"; intro p; golden-rule callout (bold + muted, ':334'); ****4 cards**** ("Place the camera", "Settings", "Keep it still", "Record & upload" + bodies); link button "Full 1-page capture checklist ?" ? ****~13****.

****A6. `#diff` section**** (':370-378'): kicker "The hard problem we crack"; H2; 2 paragraphs; panel pill "Capture tip"; panel H2 "Best results: a steady, full-court shot"; panel p ? ****7****.

****A7. `#sharper` section**** (':387-410'): kicker; H2 "It gets sharper from real academy footage"; intro p; ****3 cards**** ("Improves with the library", "Your data stays yours", "Minors are protected" + bodies); honest callout ("Read this honestly:" + body) ? ****~11****.

****A8. `#ask` section**** (':418-436'): kicker "Coming next to the alpha"; H2; intro p; ****3 query cards**** (each a quoted query + a result line, e.g. "Every rally over 10 seconds" / "6 rallies . a 1:32 reel?"); ask-note paragraph ? ****~10****.

****A9. `#roadmap` section**** (':443-452'): kicker "Where it's going"; H2 "Toward an AI assistant coach"; intro p; ****5 steps**** (title + body): "Shot detection", "Deeper analysis", "Per-match history", "Assistant coach", "More sports & languages" ? ****13**** (3 + 10).

****A10. `#not` section**** (':460-469'): kicker "So expectations stay honest"; H2 "What KhelSutra is not"; ****6 list items**** ? ****8****.

****A11. `#faq` section**** (':477-487'): kicker "Quick answers"; H2 "Common questions"; ****7 Q&A pairs**** (summary + answer) ? ****16**** (2 + 14). (Note: the "How do I join?" answer at ':487` contains an inline `[` link ? a string with an embedded anchor.\)](#join)

****A12. `#join` form region**** (':495-575`):

- Section copy (':495-498'): kicker "Request access"; H2 "Get into the KhelSutra alpha"; intro p; teaser "Sign up to watch the tool in action ? and a 30-second sample reel it made ? the moment you're in." ? ****4****.
- ****Form labels/legends**** (':503,511,515,519,524,528,538,548,560,566`): "I'm a?", "Name", "Email (so we can reach you)", "City (optional)", "Academy / club name (optional)", "How many courts do you record? (optional)", "Do you have a GPU machine that could process video locally?", "Where do your recordings live / how would you share them? (pick any)", "Anything else? (how you record, what you'd want?)", consent label "Okay to email me about the KhelSutra alpha." ? ****10 labels**** (several with a `hint` sub-string).
- ****Segment options**** (':505-506`): "Coaching academy / club", "Individual player" ? ****2****.
- ****Courts `<select>` options**** (':530-534`): "Select?", "1 court", "2?4 courts", "5+ courts" ? ****4****.
- ****GPU radio options**** (':540-543`): "Yes ? a gaming / GPU PC or laptop", "Not sure", "No", "I'd prefer it runs in the cloud" ? ****4****.
- ****Storage checkbox options**** (':550-555`): "Google Drive", "OneDrive / MS 365", "Dropbox", "Cloud bucket (S3/GCS)", "SD card / local drive", "Not sure" ? ****6****.
- ****Submit + footnote**** (':571-572`): button "Request access"; footnote "We never publish your footage; footage involving minors is never used to improve the tool." ? ****2****.
- ****Done / reveal copy**** (':575`): "Thanks ? we've got it. We'll be in touch at the email you gave. ?" + "While you're here: see the tool in action, and a real 30-second reel it made." ? ****2****.

Form subtotal ? ****~36****.

****A13. Reveal copy injected by JS**** (':622-627`): "? Close" (+ aria-label "Close the videos"), "1 . The tool in action", "2 . A real reel it made", "Generated by Khelsutra.guru . auto-closes Ns after the reel stops ? or close it anytime" ? ****4**** (these live ****inside the inline script as JS string literals****, the hardest to extract ? see §3/§4).

****A14. Footer**** (':584-588`): "Automatic badminton highlights . Bengaluru, India"; foot links "Own your model", "Capture checklist", "hello@khelsutra.guru", "khelsutra.guru"; copyright "© 2026 KhelSutra . Invite-only alpha . Reels carry a "Generated by Khelsutra.guru" mark" ? ****~7****.

****`index.html` on-screen subtotal ? 155 strings**** (plus 6 meta).

B. `capture.html` ? 1-page capture checklist

- Meta (6-7): title + description ? **2** (off-screen).
- Header (58-59): brand "KhelSutra"; H1 "1-page capture checklist" ? **2**.
- Intro (62) ? **1**.
- Golden-rule callout (67-68): bold rule + muted sub ? **2**.
- **4 steps** (74-101), each H3 + a of 2?3 : "Place the camera" (3 li), "Settings" (3 li), "Keep it still" (2 li), "Light & record" (2 li) ? **4 headings + ~10 list items = 14**.
- **Do / Avoid columns** (107-120): "Do" + 3 li; "Avoid" + 3 li ? **8**.
- Consent line (124) ? **1**.
- Footer (127-128): "Questions? hello@?" + "Tip: press Ctrl/Cmd + P to print or save as PDF." ? **2**.

capture.html subtotal ? 30 strings (+2 meta).

C. own-model.html ? annotate & train (note: noindex, 8)

- Meta (6-7): title + description ? **2** (off-screen).
- Header (75-80): brand; "Request access ?"; H1 (2 parts "Annotate your footage." / "Train a model that's yours."); intro p; 4 nav links ("KhelSutra home", "Annotate", "Train your own model", "Setup & use") ? **9**.
- Sample callout (85): "Want to see what KhelSutra produces? A real sample reel plays the moment you request access." ? **1**.
- **\$annotate** (88-103): kick "Step 1 · real and shipping today"; H2 + pill "live today"; body p (with bold spans); GitHub button label "github.com/Khelsutra/rally-annotator"; 2 figure captions; "The flow, per rally:" + a 4-item ; trailing note ? **12**.
- **\$strain** (107-130): kick "Step 2 · the moat"; H2 + pill "open pipeline · in build"; honest callout #1 (bold + body); body p; a <pre><code> pipeline diagram (semi-technical, arguably not localized); **4 moat tiles** ("You own it", "Commercially clean", "Private & consented", "Minors protected" + bodies); honest callout #2 (bold + a long body) ? **18**.
- **\$setup** (135-152): kick "Step 3 · for power users"; H2 "Setup & use"; several instructional paragraphs interleaved with <pre> code/paths/CSV blocks (code blocks would stay verbatim, not localized); the ending_reason enum sentence ? **8 prose strings** (+ ~5 code blocks left as-is).
- **\$what-this-is-not** (156-163): kick; H2 "What this is not"; **4 li** ? **6**.
- CTA (167-168): "Want in?" + "Request alpha access" ? **2**.
- Footer (173-174): links + "Reels carry a "Generated by Khelsutra.guru" mark." ? **3**.

own-model.html subtotal ? 60 prose strings (+2 meta; several code/CLI blocks intentionally untranslated).

D. Server-rendered / API text (src/ + server.js)

These never appear in the page chrome but are reachable by users (JSON error bodies, the operator notification email):

- **API JSON error strings** (src/index.js): "bad payload" (25), "valid email required" (27), "invalid json" (60), "method not allowed" (81); plus server.js literals "forbidden" (55), "not found" (62), '{"ok":false,"error":"method not allowed"}' (70), '{"ok":false,"error":"server error"}' (76) ? **8** (developer/JSON-facing; the front-end never displays these ? on failure it goes straight to the mailto fallback, so these are **not** end-user copy in practice).
- **Notification email** (src/notify.js::buildSubmissionEmail, 5-19): the labelled body ("Segment:", "Name:", "Email:", "City:", "Academy:", "GPU:", "Storage:", "Consent:", "Message:") and subject "New KhelSutra alpha request ? ?". This is an **internal operator email**, not user-facing ? translation **not needed**.
- **mailtoFallback** (index.html:664-678): the prefilled email subject "KhelSutra alpha access" and body "Hi KhelSutra team, I would like to try the alpha." + labelled lines ? this **is** user-facing (the visitor sends it) and currently lives as JS literals.

Server/API subtotal: ~8 JSON strings (not shown to users) + 1 operator email template (skip) + ~12 mailto-fallback literals (user-facing).

Grand total

```
| Group | On-screen user-facing strings |
|---|---|
| `index.html` | ~155 (+6 meta, +12 mailto/reveal JS literals) |
| `capture.html` | ~30 (+2 meta) |
| `own-model.html` | ~60 (+2 meta; code blocks excluded) |
| Server/API JSON | ~8 (not user-shown) |
| Operator email | skip (internal) |
| **Total to localize (on-screen + meta + user-facing JS)** | **? 245?260 strings** |
```

A realistic catalog is ****~230?250 keys**** once near-duplicates (the golden-rule text repeated on `index`+`capture`; the "Generated by Khelsutra.guru" / minors-protected / "Request alpha access" lines repeated several times) are de-duplicated into shared keys.

3. How the HTML is structured today (and where `data-i18n`/`t()`) attaches with least churn)

- ****Three standalone documents****, each fully self-contained: its own ``, its own inline `

inline IIFE** in `index.html:597-712`. The reveal's user-facing strings ("1 · The tool in action", "2 · A real reel it made", the auto-close stamp, "? Close") are **JS string literals built via `host.innerHTML = '?'`** (`:621-627`), so they are *not* reachable by a `data-i18n` DOM pass ? the shim's `t(key)` must be **callable from JS** and used to build that HTML.

The `src/` modules are **backend-only** and share nothing with the browser: `src/index.js` (Worker handler), `src/store.js` (D1/SQLite adapters), `src/notify.js` (email). None of them emit page copy; their only strings are JSON error codes and the operator email. So the i18n shim does **not** belong in `src/`.

The SPA (`web/`) is a separate React/TS/Vite/Tailwind app with its own `web/src/lib/` of pure formatters (`format.ts` already has `mmss`, `pluralize`, `reelFilename` ? `web/src/lib/format.ts`). It has no i18n either. To let **both** the SPA and the static site share one catalog format:

- **Catalog format:** flat JSON keyed by dotted string id, one file per locale: `en.json`, `kn.json`, `hi.json`. Values are plain strings with `{var}` placeholders for `t(key, vars)` interpolation (e.g. `"reveal.autoclose": "auto-closes {secs}s after the reel stops"`). This format is consumable identically by a vanilla `

`:523-535`). A non-technical individual is asked two infrastructure questions that feel irrelevant and gatekeeping.

- For an ****academy****, it grows to ~9 inputs. Several are marked "(optional)" which helps, but the GPU/storage blocks are ****not**** marked optional and have no "skip"/"don't know"-friendly default beyond burying "Not sure" among the options.
- Mitigations already present: most academy fields are "(optional)"; honeypot is invisible; native validation; graceful mailto fallback. Good. But the ****two technical questions lack a plain-language framing**** ("This helps us decide where your video gets processed ? pick 'Not sure' if unsure" would lower anxiety).

****Unclear next step / expectation-setting:****

- The ****payoff is buried below a long page****: the "watch the tool + 30s reel on signup" promise only appears at the hero CTAs (`:252`) and again at the form (`:498`). A first-timer may not realize the reward is immediate. The reveal itself is well-handled (auto-close pauses while playing, manual close), but a visitor who **doesn't** submit never sees any real output ? there's no ungated sample.
- ****Three hero CTAs**** (`:250-252`), two of which ("See how it works", "See it in action + a real reel") compete with "Request alpha access" ? choice overload at the top.
- ****"Invite-only alpha" is repeated many times (eyebrow, hero, footer, FAQ). Honest and good for expectation-setting, but for a non-technical user it may read as "I probably can't get in," dampening signup intent.**
- The honest-disclaimer blocks ("Read this honestly", "What KhelSutra is not", `:408-411`, `:457-471`) are excellent for trust but dense; a non-technical reader may not parse "It does not retrain itself as you use it, and there's no per-person tracking" (`:410`).

****Localization-readiness UX note:**** the site already **promises** Kannada + Hindi (`index.html:452`), so a language switcher is an expected affordance ? but ****none exists**** today (no UI, no `lang` toggle). Adding a visible language picker in the header is part of the same work and would itself reduce friction for the target Bengaluru audience.

6. Test coverage note (per instruction to note, not read in depth)

`site/src/\*.test.js` (run via `node --test`, `jsdom` for DOM tests) cover: form?API wiring, in-flight state, gated/random-start reel, footage-free screencast, capture-link, FAQ-join wiring, own-model page presence (`assets.test.js`); wrangler/D1/email config (`deploy-config.test.js`); validate/isBot/toRow/handleRequest/stores/email (`index.test.js`); the VM-host server incl. SQLite round-trip (`server.test.js`); and the DOM reveal/in-flight/auto-close behavior (`ux.dom.test.js`). ****None of these assert on copy *content* or any i18n behavior**** ? so adding `data-i18n`/`t()` will not break existing tests, but there is currently ****zero test scaffolding for translation/locale****, and `ux.dom.test.js` asserts the literal string "Sending?" (`index.html:687`), which would need a key once that literal moves into the catalog.

Files referenced (absolute paths)

- `C:/Users/avidu/Projects/khelsutra/site/public/index.html` ? landing page (header, hero, 8 sections, form, reveal JS, footer).
- `C:/Users/avidu/Projects/khelsutra/site/public/capture.html` ? 1-page capture checklist.
- `C:/Users/avidu/Projects/khelsutra/site/public/own-model.html` ? annotate & train (noindex, power-user copy).
- `C:/Users/avidu/Projects/khelsutra/site/server.js` ? dependency-free Node/SQLite VM host (static serve + `/api/request-access`).
- `C:/Users/avidu/Projects/khelsutra/site/src/index.js` ? shared Worker/VM request handler + validation strings.
- `C:/Users/avidu/Projects/khelsutra/site/src/store.js` ? D1/SQLite insert adapters (no user copy).
- `C:/Users/avidu/Projects/khelsutra/site/src/notify.js` ? operator email template (internal, not user-facing).
- `C:/Users/avidu/Projects/khelsutra/site/schema.sql` ? `access\_requests` table.
- `C:/Users/avidu/Projects/khelsutra/site/README.md` ? deploy/dev docs.
- `C:/Users/avidu/Projects/khelsutra/web/` ? the ****separate**** React 19 + Vite + TS + Tailwind SPA (the catalog-sharing counterpart; `web/src/lib/format.ts` is the natural neighbor for a

shared `t()`; **no i18n today**.