

claude-windows / 2ba49afa-99f4-41f2-86a2-27a289d432f3

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3.jsonl`  
- SHA-256: `7877e3fabac2f5b856b9f5dd1ec5ab8c56dea7869a3958761b88bb1b6740503a`  
- Source modified: `2026-06-21T19:07:32+00:00`  
- Imported at: `2026-07-05T16:48:17+00:00`  
- project: `C--Users-avidu-Projects-badminton-highlight-indexer`  
- session_id: `2ba49afa-99f4-41f2-86a2-27a289d432f3`
```

Transcript

1. user (2026-06-21T14:47:53.778Z)

? Picking up KhelSutra after the UX + runnable-tool session. State: the bucket?reel CUJ is fully UI-driven (B-P2, with a live screencast in the promo bucket), the SPA is trilingual (en+kn+hi), plain-language copy shipped (A1), and the 7-language expansion is owner-approved (#58).

? Read first (the "use the docs" rule): memory next-session-ux-localization.md (your full handoff ? you-are-here, ordered next steps, ramp-up kit, open owner decisions), then khelsutra/docs/FRIENDLY_AND_MULTILINGUAL.md §7, LOCAL_APPLIANCE_ARCHITECTURE.md §9 (T2/T4/T11) + §4, and MULTILINGUAL_EXPANSION.md.

? Clean slate: khelsutra master has #55?#60 merged; engine master has #284/#289; 0 of my PRs open.

? The engine/serving track (Cloud-Run M5?M12) is a CONCURRENT session ? do NOT touch COMPUTE_DECOUPLED_SERVING/, backend/compute/, or the engine DOC_STATUS/NEXT_STEPS. Shared checkout:
branch from origin/master, re-verify HEAD before commit, stage explicit paths.

Mission (in order; ONE PR per item, merge on green + rising coverage):

1. Finish the SPA UX A-items ? A4 (mobile ?44px touch targets + visible tooltips) ? A5 (friendly engine-error mapping on the BUILD path: reuse web/src/lib/errors.ts::classifyError, add a shared errors.* i18n namespace) ? A8 (background-processing reassurance + icon+text status chips).
2. B3 ? make the site/ marketing pages trilingual via a shared t()/data-i18n shim. Recommended: hoist catalogs to repo-root /locales/ + a tiny site prebuild copy (B3 ticket in the handoff); negotiation must match the SPA (localStorage khelsutra.lang ? ?lang= ? navigator ? en).
3. ? NORTH STAR (the goal ? runnable tool for alpha users): T4 ? in-UI file UPLOAD (wire the SPA to the EXISTING engine chunked-upload endpoints in backend/api/uploads.py; alpha users have a file, not a gs:// URI). T2 ? host SPA+engine behind Cloudflare Access on the CPU droplet (168.144.126.176) with Gemini/CPU (NOT GPU, NOT M12); rotate the GEMINI_API_KEY; reuse site/scripts/provision-vm.sh + PORTABILITY.md. T11 ? retention sweep.

Parallel line (owner-approved #58, owner-paced): MULTILINGUAL_EXPANSION ? add th/id/da/es/zh-Hans/ ja/ko. Phase A (es/da/id) is actionable now (es needs the 3-form ICU plural {one,many,other}). Phases B/C need owner answers (Q2 zh-Hans/Hant, Q3 CJK offline strategy, Q4 native reviewers).

Don't redo: the CUJ, B-P2, A1, the doc-hygiene, #58. A2 (WhatsApp/social) is DROPPED (separate scope) ? reel stays pure-download. Open owner decisions are in the handoff §3.

Ultracode's on ? fan out research/verification with workflows, verify against the docs, keep tight one-item PRs, merge the good ones on green. Let's make the appliance point-and-go for alpha. ?

2. assistant (2026-06-21T14:48:05.000Z)

I'll ramp up properly first ? per the repo-freshness rule, pull the repos, then read the handoff and docs before doing any work. Let me start in parallel.

3. user (2026-06-21T14:48:09.790Z)

```
=== KHELSUTRA ===
?? .claude/
?? site/access.db
--- branch ---
master
--- pull ---
Already up to date.
--- recent ---
ccdcfcd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon) (#60)
a20002f docs: propose Multilingual Expansion ? 7 new locales (th/id/da/es/zh-Hans/ja/ko) (#58)
a0475bc docs: hygiene refresh ? sync trackers to shipped reality (#59)
7750afc docs(dry-run): Path-B live e2e DONE ? in-UI bucket?reel CUJ + screencast (DoD $6 box 3 ?) (#57)
4525c5d feat(web): B-P2 ? in-UI bucket ingest (point at a gs:// video ? process ? load) (#56)
d0461fd docs: correct stale "bucket ingest is net-new" claims (B-P1 already shipped in M2/#280) (#55)
2421557 docs(dry-run): record Path-A local result (en+hi reel downloaded) + the engine fix it surfaced (#54)
113587f docs: set the dry-run CUJ as a tracked goal (UI drives a bucket video -> reel download, multilingual) (#53)
```

4. user (2026-06-21T14:48:09.835Z)

```
1      ---
2      name: next-session-ux-localization
3      description: "? START HERE for the khelsutra UX/localization + runnable-tool track.
Where we are + ordered next steps (SPA UX A-items ? B3 ? runnable-tool North Star) + the
approved 7-language line + open owner decisions + ramp-up kit. Refreshed 2026-06-21. NOTE: the
engine/serving track has its OWN handoff in session-handoff.md ? don't conflate."
4      metadata:
5          node_type: memory
6          type: project
7          originSessionId: 577fd4df-ed3f-43d3-854d-d63d732e2e07
8      ---
9
10     # Handoff ? khelsutra UX / localization / runnable-tool (refreshed 2026-06-21)
11
12     > This is the **khelsutra (web/ SPA + site/)** product track. The **engine/serving**
track (Cloud-Run M5?M12, a CONCURRENT session) has its own `session-handoff.md` ? **don't touch
its files** (`COMPUTE_DECOUPLED_SERVING`, `backend/compute/`, engine `DOC_STATUS`/`NEXT_STEPS`).
13
14     ## 1. You are here
15     The **bucket?reel CUJ is fully UI-driven + proven** (B-P2 shipped + live screencast),
the **SPA is trilingual (en+kn+hi)**, **plain-language copy (A1) is merged**, and the
**7-language expansion is owner-approved** (#58). The **North Star = make the tool
runnable/shareable for alpha users from the UI** ? a hosted SPA+engine behind edge auth. **It is
NOT GPU-gated and NOT M12** ? cheapest path = the existing **CPU droplet + Gemini**.
16
17     **Merged this session (all green):** engine
[284](https://github.com/Khelsutra/badminton-highlight-indexer/pull/284)(gs:// guard) .
[289](https://github.com/Khelsutra/badminton-highlight-indexer/pull/289)(compile-from-bucket
fix) . khelsutra [#55](https://github.com/avidullu/khelsutra/pull/55)(stale-doc) .
[#56](https://github.com/avidullu/khelsutra/pull/56)(B-P2 ingest) .
[#57](https://github.com/avidullu/khelsutra/pull/57)(DoD box3) .
[#59](https://github.com/avidullu/khelsutra/pull/59)(doc-hygiene) .
[#60](https://github.com/avidullu/khelsutra/pull/60)(A1 copy). Owner-merged
[#58](https://github.com/avidullu/khelsutra/pull/58)(MULTILINGUAL_EXPANSION). Screencast:
`gs://khelsutra-rally-corpus/promo/khelsutra-bucket-cuj-screencast.mp4`.
```

18

19 **## 2. Next steps ? ordered (one PR per item, off `origin/master`, merge on green +**
rising coverage)

20 ****A) SPA UX A-items, then B3** *(A1 ?; A2 DROPPED ? social/sharing is a separate**
scope):*

21 - ****A4 ? mobile touch targets + visible tooltip text.**** `web/src/components/{QueryBar,Ra
llyGrid,SelectionFooter,IngestPanel,CompileResult,LanguageSwitcher}.tsx` + `index.css`: ?44px
tap targets (`min-h-11/py), enlarge the tiny query parsed-pill + sample chips, surface `title`
tooltips as visible text on phones. (M)

22 - ****A5 ? friendly engine-error mapping (build path).**** Reuse
`web/src/lib/errors.ts::classifyError` (built for ingest) on `App.tsx::onBuild` (currently shows
raw ApiError for 5xx/network) ? localized message in `CompileResult`. Add a ****shared `errors.****
namespace** (recommend unifying IngestPanel onto it). (S?M)

23 - ****A8 ? background-processing reassurance + status as icon+text chips**** (never icon-
only) in IngestPanel progress + build state. (S?M)

24 - ****B3 ? `site/` trilingual via a shared `t()` shim.**** New ~70-LOC vanilla
`t(key,vars)`/`data-i18n` shim (`site/public/i18n.js`) over `index/capture/own-model.html` + a
switcher + `site/server.js` Accept-Language negotiation; extend
`site/src/{server,assets}.test.js` + a shim unit test. ****DECISION** (recommended by the spec
scan): hoist catalogs to repo-root `/locales/{en,kn,hi}/common.json` as the single source of
truth, re-point the SPA's 3 imports (or a Vite `@locales` alias), and a tiny `site` prebuild
copies them to `site/public/locales/` + a drift-guard test** (site is dependency-free/no-build
today; this is the only new build step). Negotiation must match the SPA exactly (localStorage
`khelsutra.lang` ? `?lang=` ? navigator ? en; en-fallback never a raw key). (M)

25

26 ****B) ? NORTH STAR ? runnable tool for alpha users (the crucial fresh-context work the**
owner paused for):**

27 - ****T4 ? in-UI local file UPLOAD (keystone).**** Alpha users have a ****file****, not a
`gs://` URI. Wire the SPA to the ****existing**** engine chunked-upload endpoints (`badminton-
highlight-indexer/backend/api/uploads.py`: `/api/upload/init|part|complete|DELETE`) + a file-
picker in/ beside `IngestPanel` ? on complete feed the server path to `/api/process` ? existing
poll?load?compile?download. New: `web/src/api/client.ts` upload helpers + upload mode; reused:
the back-half. (M?L)

28 - ****T2 ? droplet appliance shell (hosted + shareable).**** Serve the built SPA + reverse-
proxy `/api?engine` 127.0.0.1:8000 behind ****Cloudflare Access**** on the ****CPU droplet**
168.144.126.176**, engine on ****Gemini/CPU (no GPU)****; deploy the #281/#289-fixed engine +
`GEMINI\_API\_KEY` + `pip install google-cloud-storage`; ****rotate the chat-shared key****; reuse
`site/scripts/provision-vm.sh` + `docs/PORTABILITY.md`. (M?L, +owner Cloudflare Access)

29 - ****T11 ? retention sweep**** (`output/` + `uploads/`) before non-owner exposure. (S,
owner: window)

30

31 ****C) 7-language line ? APPROVED (#58), parallel/owner-paced****
(`MULTILINGUAL\_EXPANSION.md` §7): ****Phase A** (`es`/`da`/`id`) actionable now** (catalog-only;
****es`** needs the 3-form ICU plural `{one,many,other}`**). ****Phase B (Thai)**** = 1 small OFL font.
****Phase C** (`zh-Hans`/`ja`/`ko`)** = large OFL fonts + lazy-load + offline-subset ? ****blocked on**
owner Q2/Q3**. Native review (Q4) is the launch gate.

32

33 **## 3. Open owner decisions**

34 - ****7-lang** (`MULTILINGUAL\_EXPANSION.md` §8):** Q2 `zh-Hans` only or +`zh-Hant`? · Q3 CJK
offline strategy (ship-all-chunks / custom-subset / online-lazy) · Q4 native-reviewer sourcing ·
Q5 priority order.

35 - ****B3:**** confirm the catalog-hoist (repo-root `/locales/`) approach.

36 - ****T2:**** Cloudflare Access setup + ****GEMINI_API_KEY** rotation**. ****T11:**** retention
window. Plus the standing launch gates: native kn/hi review + owner-machine font eyeball.

37

38 **## 4. Ramp-up kit (read in order)**

39 1. This file ? `[[current-state]]` top (today's checkpoints).

40 2. `khelsutra/docs/`: `FRIENDLY\_AND\_MULTILINGUAL.md` §7 (active UX/l10n tracker) ·
`DRY\_RUN\_CUJ.md` §9 (delivered CUJ) · `LOCAL\_APPLIANCE\_ARCHITECTURE.md` §9 T2/T4/T11 + §4
topology (North Star) · `MULTILINGUAL\_EXPANSION.md` (7-lang plan).

41 3. Code: `khelsutra/web/src/{App.tsx, components/IngestPanel.tsx, lib/errors.ts,
api/client.ts, i18n/index.ts, i18n/hygiene.test.ts}`; `badminton-highlight-
indexer/backend/api/uploads.py` (T4 endpoints); `khelsutra/site/{public/*.html, server.js,
scripts/provision-vm.sh}` (B3 + T2).

42 4. Detailed B3/A4/A5/A8/North-Star tickets: spec workflow `wf\_b7edcaa8` (re-run skill or

```

check the transcript for file:line specs).
43
44     ## 5. Key decisions ? don't relitigate
45     - **A2 (WhatsApp/social) DROPPED** ? all social/sharing deferred to a separate scope;
reel = **pure download**.
46     - **Runnable-tool = hosted SPA+engine + edge auth; cheapest = droplet + Gemini/CPU. NOT
GPU, NOT M12.**
47     - **DON'T touch the serving track** (concurrent session):
`COMPUTE_DECOUPLED_SERVING`/`backend/compute`/`Cloud-Run M5?M12 (M1?M8 merged, M9 #290 open).
**Shared checkout** ? branch from `origin/master`, re-verify HEAD before commit, stage explicit
paths ([[gotcha-shared-checkout-branch-collisions]]).
48     - **Verify engine-surface claims at file:line before scoping** ([[lesson-verify-engine-
surface-before-scoping]]) ? B-P1 was already shipped.
49     - **Merge authorization:** Claude merges its own green UX/good-engineering PRs
([[working-agreement-merging]]); product/strategy + 7-lang Phase-C/native-review stay owner-
gated.
50

```

5. assistant (2026-06-21T14:48:19.029Z)

Clean slate confirmed (master, up to date, my last PRs merged). Let me read the key docs and current-state to finish ramping up.

6. user (2026-06-21T14:48:21.154Z)

<system-reminder>[Truncated: PARTIAL view ? showing lines 1-32 of 111 total (50742 tokens, cap 25000). Call Read with offset=33 limit=32 for the next page, or Grep to find a specific section. Do NOT answer from this page alone if the answer may be further in the file.]</system-reminder>

```

1      ---
2      name: current-state
3      description: "Live micro-checkpoint state for Claude ? updated every checkpoint (not
only on request). What just landed, what's next, open decisions."
4      metadata:
5          node_type: memory
6          type: project
7          originSessionId: b13673cc-f087-43b1-9527-35dc0b67b301
8      ---
9
10     # Current state ? updated continuously (see [[working-agreement-checkpoints]])
11
12     > **Scope of this file = LIVE only:** the current handoff + *today's* checkpoints + open
PRs/decisions. Keep it read-first-short (?1 page). Older checkpoints are archived in [[current-
state-archive]] ? when today's checkpoints age out (next clean-slate day), move them there,
don't let them pile up here.
13
14     ***? NEXT SESSION FOCUS (2026-06-21, after the big localization+dry-run session):** SPA
is fully **en+kn+hi (DONE)**; a real **UI?engine?reel?download CUJ ran (en+hi)**; a **critical
engine bug fixed** (#281). ***? NEXT BUILD (owner-picked): (1) Path B ? point at a bucket video
IN THE UI.** ? **B-P1 VERIFIED ALREADY DONE ? NO ENGINE CODE (do NOT re-scope it as a
feature):** `POST /api/process` has accepted `gs://`/`gcs://` URIs since **M2/#280** (submit
resolves the URI + skips the local-exists-404 for non-local backends `main.py:283`; the worker
fetches to scratch `acquire_local_input main.py:159` ? same hash?validate?segment?DB pipeline ?
queryable API-DB `video_id`); **TESTED**
(`tests/test_api_endpoints.py::test_process_nonlocal_uri_skips_exists_and_fetches` + hosted-
mode-reject / unknown-scheme-400 / CLI variants). Confirmed by a **3-skeptic verification
workflow (0 refuted, gaps:[])**. **Scope pin:** holds in DEFAULT single-user mode (hosted-mode
`allowed_video_root` correctly **400s** a bucket URI ? by design). Stale "local-path-only / net-
new" docs **CORRECTED ? khelsutra [#55]** (DRY_RUN_CUJ $1/2/4/6/8 + LOCAL_APPLIANCE + README).
***? So Path B = ONLY B-P2 = the SPA ingest/progress screen** (enter a `gs://` URI ? `POST
/api/process` ? poll `/api/jobs` ? load `result.video_id`; back-half already works) ? **100%
khelsutra `web/` SPA + i18n (en/kn/hi), ZERO engine code.** Ready B-P2 sketch: `DRY_RUN_CUJ.md`
$2 (new `web/src/{api/types,api/client,hooks/useIngestJob,components/IngestPanel}.tsx` +
`App.tsx` `videoId?state handoff + `ingest.` keys). See [[lesson-verify-engine-surface-before-
scoping]]. ** (2) Droplet deploy (opt 3):** deploy the FIXED engine to `168.144.126.176` (un-

```

provisioned, 2-core/3.8GB) ? re-run CUJ on Linux. ****STILL OPEN (localization DoD):**** B3 (`site/` marketing still English-only) + native-speaker review of the AI-drafted kn/hi. ****Ramp-up:**** `khelsutra/docs/DRY\_RUN\_CUJ.md` + `FRIENDLY\_AND\_MULTILINGUAL.md` §7 + the dry-run checkpoint below. ****Clean slate (at session start):**** both repos on master, 0 open PRs, no worktrees/VMS. khelsutra master `2421557` · engine master `2afd54f` (? origin/master `cee4baa`, #283 M4 squashed).

15

16 ****Checkpoint:**** 2026-06-21 (ENGINE SERVING M5+ ? OWNER BATCH-AUTHORIZED the independent path). Owner redirected: "first surface the owner-gated decisions so I can take them + unblock max independent PRs." Ran a 6-agent grounded gate-map ****workflow**** (`wf\_4849400f`) over README §2/§7/§8 + code ? a decision menu splitting every M5?M12 gate into ****a) default-OFF code I can merge now**** vs ****b) thin owner residual****. ****Owner answers (AskUserQuestion):**** ****a) BLANKET YES**** ? write+merge ALL default-OFF serving code (M5,M6,M8,M9-auth,M9-consent-cols,M11-plumbing,M12), one isolated PR each; ****b) SPEND OK up to \$100/?10k**** for due-diligence + ****production-grade testing/verification**** (so the real M6/M7 cloud runs are ALSO unblocked within the cap ? must respect it, DELETE resources after, confirm cmd+cost before each spend per [[gcp-vm-always-delete]]). ****c) MERGE each on green CI**** (OAuth real-testing deferred to a later rigorous pass). ****d) ALL recommended design picks**** "with generous budget in mind": ****co-located stitch**** (D4) · ****libx264 ENCODE + NVDEC DECODE-only**** (protect parity) · ****hard-reject <2GB v1**** (config knob) · confirm `COMPUTE\_DECOUPLED\_SERVING/` name · ****M6 = Cloud Run JOBS + bucket-poll completion****. ****e) PLANNED PR ORDER:**** A(doc: §8 resolutions + P3 reconcile + tracker housekeeping) ? B(M5 preset+startup-checks+L1?L4 parity test) ? C(M6 `backend/compute/` registry + Dockerfile + mocked-dispatch) ? D(M8 v6 migration + pricebook[\$0 placeholder] + USD/INR aggregation + /cost API) ? E(M9-auth Cf-Access JWT verify + tenant scoping; M9-consent inert NULL cols EXTEND D's v6 migration) ? F(M11 capture?store?shadow-eval?goldenize plumbing, `flywheel.\*`=OFF) ? G(M12 `GDriveApiStorage`+`gdrive-api://`, fake-Drive tests) + Ops-Agent codify into `deploy/gcp/provision.sh`. Coordinate: D/E/M9-consent share ONE v6 migration (author in D, extend in E). ****Genuinely owner-only residual:**** real GPU run (M5 runlog) [or I run on cloud GPU within cap], counsel ToS/DPA (M9-consent text), Google OAuth app (M12 real), real GCP prices+FX (M8 calibrate), CF team-domain/AUD+ingress-lock, repo rename, D0 droplet/token retire. ? shared checkout ? sibling merged ****#284**** (`06ff4b7`, bucket-URI regression guard) mid/just-before this session; RE-FETCH origin/master before each branch. ****PROGRESS (this session):**** ? ****PR-A [#285] MERGED**** (`fefa412`, doc: §8 D16/D17 resolutions + P3 reconcile + tracker housekeeping). ? ****M5 [#286] MERGED**** (`b5af66e`, all 7 CI green) ? `backend/config/startup.py` per-profile fail/warn-fast checks (cloud-serving+non-cloud-storage = the one fatal coherence error; GPU/creds = warnings) wired into server (`\_enforce\_startup\_or\_exit`?exit1) + worker (`cmd\_infer/`cmd_train`?rc2), **\*\*default-OFF + probe gated behind active profile (worker stays torch-free at profile=)\*\***; **\*\*L4 profile-parity test\*\*** (`tests/test_profile_parity.py`: same stub trajectory?byte-identical windows+ranges across truly-local/cpu-mock/no-profile + worker-vs-in-process); 4-lens adversarial review folded (`wf_34671ac1`: MAJOR torch-free fix + minors). Runlog template pre-staged; the real-GPU truly-local **\*\*runlog = owner L5\*\***. M5 ? in §7 tracker. ? **\*\*M6 [#287] MERGED\*\*** (`8cdf65c`, all 7 CI green) ? `backend/compute/` ComputeBackend registry: `get_compute_backend(config)` returns a backend ONLY for `compute_target=cloud_run` (else `None` ? worker's in-process path, **\*\*default-OFF\*\***); `CloudRunCompute` dispatches a Cloud Run **\*\*Job\*\*** (injectable `CloudRunJobClient`; real `GoogleCloudRunJobClient` lazy google-cloud-run) ? **\*\*bucket-polls\*\*** a done-marker via `execution_policy.poll_until`+storage (D16); container forced **\*\*inline\*\*** (`compute_target=local_gpu`+native, never re-dispatch); worker `--done-uri` writes a success marker. `deploy/cloudrun/{Dockerfile,README}` = L4 image (CUDA+ffmpeg+DejaVu fonts+`wasb` conda torch-1.11 env mirroring gpu\_setup.sh; weights staged per WASB-C3) + M7 runbook. 4-lens review (`wf_87b22fa4`) folded a **\*\*BLOCKER\*\*** (cloud `fetch` needs a dst ? reads silently returned `{}` on gcs/s3; tests passed only b/c local) + poll-wait test gap + `PolicyTimeout`?clean rc 4. Suite 1167 green. ? **\*\*M8 [#288] MERGED\*\*** (`43eccc1`, 7 CI green) ? `backend/billing.py` (pure `usage`+pricebook, USD source-of-truth / INR display) + **\*\*v6 migration\*\*** (NULLABLE cost cols on `jobs` + versioned `pricebook` seeded `placeholder-v0` at \$0; additive-NUL, idempotent) + `record_job_cost`/`get_job_cost`/`get_video_cost` + `GET /api/jobs|videos/{id}/cost` + `BillingConfig` (**\*\*default-OFF\*\***) + gated `_maybe_record_job_cost`. 3-lens review (`wf_498b24af`) folded a **\*\*MAJOR silent-GPU-under-bill\*\*** (an unpriced `gpu_type` is now SURFACED ? WARNING + `unpriced_gpu_seconds` breakdown line, not invisible \$0) + the **\*\*honest no-op\*\*** caveat (pipeline doesn't emit `result['usage']` yet ? cost 0 until a follow-up wires the metering; documented + tested) + margin/rounding reconciliation. Suite 1186 green. ****?? 4 SERVING PRs THIS SESSION, ALL MERGED: #285(docs §8 D16/D17 + P3 reconcile) + #286(M5 startup-checks+L4 parity) + #287(M6 Cloud Run dispatch shim+image) + #288(M8 cost ledger).**** Each default-OFF, isolated, adversarial-reviewed, full-suite+CI green, tracker+changelog in-PR. ****v6 is now SHIPPED (M8 took it) ? the NEXT migration is v7**** (M9-consent cols + per-video P1 `workspace\_uri` ? the earlier "extend v6" plan shifts to a fresh

```

v7 `_migrate_to_v7`). **? REMAINING authorized batch (ready to build next, blueprints loaded):**
**M9-auth** = add `PyJWT[crypto]`; a FastAPI dep extracts `Cf-Access-Jwt-Assertion` ?
fetch+cache the team JWKS ? verify sig/exp/iss/aud ? `user_id`; per-tenant scoping on the v4
`user_id` cols; tighten the placeholder CORS (`main.py:40`); all behind
`security.edge_auth_enabled=False`; offline RSA/fake-JWKS tests. **M9-consent** = inert NULL
`consent_status/is_adult_attested/retention_class` in a **v7** migration (safe no-train default)
? the ToS/DPA TEXT is owner/counsel. **M11** = `flywheel.capture/shadow_eval/promote_stub`
reusing `workspace.py::for_video` + `backend/eval/experiment.compare`(:485) +
`promotion.py::promote_if_served_safe`, behind `flywheel.*`=OFF + a faked `consent_attested`.
**M12** = `GDriveApiStorage(StorageBackend)` + a `gdrive-api://` scheme against an INJECTED fake
Drive (mirror `gcs.py` DI), keep the mount-only `gdrive://` (truly-local) untouched. **Ops-Agent
codify** into `deploy/gcp/provision.sh` (logging+monitoring APIs + SA metric/log-writer roles +
startup-script ? [[gcp-ops-agent-enable]]). **? owner-only residual:** real GPU run ? M5 truly-
local runlog (template pre-staged in `runlogs/`); GCP spend for the real M6/M7 run within the
**$100/?10k cap** (build the image per `deploy/cloudrun/README`, run on L4, capture
DEPLOY_REPORT, **DELETE after**); counsel ToS/DPA (M9-consent); real GCP prices+FX + the M8
usage-emission follow-up; Google OAuth app (M12 real); CF team-domain/AUD + ingress-lock; repo
rename; DO droplet/token retire. **?? REAL M7 CLOUD GPU RUN ? ? DONE + VERIFIED (owner:
"complete any and every cloud run with GPUs").** Provisioned an **L4** `rally-m7-gpu`
(`g2-standard-4`, **asia-southeast1-a** Singapore ? both Mumbai zones STOCKOUT for L4; reads the
Mumbai bucket cross-region) ? `bootstrap --gpu` + `gpu_setup.sh` (wasb conda env, **torch
1.11+cu113 cuda True on L4** via PTX-JIT) + staged the 5.82 MiB weights ? `worker -v infer
--video-uri gcs:///mahadevpura_smoke_180s.mp4 --out-uri gcs:/// --segmenter wasb_hybrid` ? **22
rallies** (5395 trajectory points, 2930 visible; Phase 2 WASB 363.7s) ? pushed `gs://khelsutra-
rally-corpus/outputs/05e0e577?/[intervals.csv,report.json]` (segment_count 22, status success).
**VM DELETED, audit 0 instances/0 disks ? $0** (~18 min ? **$0.21**, well under the cap). **?
SOLVED the long-flagged "cold-start gives 0 rallies" mystery ? THE MISSING PIECE = `--set
indexing.skip_ai_handoff=true`:** `wasb_hybrid` does a Phase-3 **Gemini handoff** by default;
with no `GEMINI_API_KEY` on the box it errors ? 0 segments. `skip_ai_handoff=true` = the
**fully-local** path ? emits the 22 WASB candidate windows directly as rallies (no Gemini). So a
no-Gemini cloud run MUST set `skip_ai_handoff=true` (this is exactly M5's truly-local preset,
which sets it). ? minor: `-v` is a TOP-LEVEL flag ? `worker -v infer` ? (not `infer -v`).
DEPLOY_REPORT runlog = TODO (after M9-auth). ? **M9-auth [#290] MERGED** (`aac7633`) ?
`backend/api/auth.py` Cf-Access JWT verify (RS256: sig+exp+iss+aud; lazy `PyJWT[crypto]`;
injectable JWKS ? fully-offline tests incl. alg=none + HS256-confusion rejection) +
`resolve_tenant` ? `create_job(owner_id=?)`;
`SecurityConfig.{edge_auth_enabled=False,cf_team_domain,cf_access_aud}` + CORS via
`RALLY_CORS_ALLOW_ORIGINS` env. **Default-OFF.** Security review (`wf_9b4c71d0`) found NO
bypass. ? **OPS-AGENT codify + DRY-RUN GUIDE [#291] MERGED** (`7835f34`, owner asked):
`deploy/gcp/create_gpu_vm.sh` (THE one-command way to spin a GPU VM ? zone-sweep L4
Mumbai?Singapore + **always bakes the Ops-Agent startup-script**) + `ops-agent-startup.sh` +
provision.sh (logging/monitoring APIs + SA metric/log-writer roles ? the empty-graphs root
cause) + **docs/CLOUD_GPU_DRYRUN_GUIDE.md** (step-by-step local-video?cloud-GPU?reel,
validated from the M7 run + the local `VideoCompiler` stitch; the **`skip_ai_handoff=true`** no-
Gemini path; `min_shot_count:0` so no rally is filtered). **?? 6 SERVING/INFRA PRs MERGED THIS
SESSION: #285,#286(M5),#287(M6),#288(M8),#290(M9-auth),#291(ops-agent+guide) + the REAL M7 L4
run (22 rallies, $0).** **? NEXT (owner "keep going"): M11** flywheel plumbing
(`flywheel.capture/shadow_eval/promote_stub` reusing `workspace.py::for_video` +
`backend/eval/experiment.compare` + `promotion.py::promote_if_served_safe`, behind
`flywheel.*`=OFF + a faked `consent_attested`) ? **M12**
`GDriveApiStorage(StorageBackend)`+`gdrive-api://` (injected fake-Drive DI; keep mount-only
`gdrive://`). ? M9-consent cols = a **v7** migration (M8 took v6). Ops-Agent codify = ? DONE
(#291; **owner CONFIRMED Observability live in the cloud console 2026-06-21**). ? **292
MERGED** (`2afbadf`) ? dry-run font fix (`bootstrap.sh` installs `fonts-dejavu-core`; a 2nd dry
run via `create_gpu_vm.sh` PROVED Ops-Agent auto-installs + found the watermark needs the font)
+ the **?UI-trigger tracking** (NEXT_STEPS ?P0-0 + [[ui-driven-cloud-serving-gap]]). **??
SESSION WRAPPED ? CLEAN SLATE: 7 PRs merged (#285/286/287/288/290/291/292) + the real M7 L4 run
(22 rallies); 0 open PRs; 0 GPU VMs (total spend ~$0.61); empty m11/m12 placeholder branches
deleted (they had ZERO commits ? the "13k pending lines" the owner saw = untracked
`artifacts/+scratch/+sibling docs, NOT my work).** ? **FRESH-SESSION ICEBREAKER = bottom of
[[session-handoff]] $"You are here".** ? Owner's #1 NEXT = make it **UI-DRIVEN + alpha-
shareable** (khelsutra `web/` B-P2 ingest screen + M7 Cloud-Run *service* deploy + M9-on + a
compute picker), THEN M11(flywheel, privacy-sensitive)/M12(gdrive-api). [[gcp-vm-always-delete]]
[[gcp-ops-agent-enable]] [[ui-driven-cloud-serving-gap]] [[working-agreement-merging]]
[[feedback-launch-quality-bar]] [[compute-stack-gcp-only]]

```

17

18 ****Checkpoint:**** 2026-06-21 (STALENESS-FIX / Path-B verify) ? owner: pick up Path B +
"fix all stale docs and stop next sessions spiralling into the staleness." ****? Verified-FIRST**
finding: B-P1 was ALREADY DONE **** ? `POST /api/process` accepts `gs://`/`gcs://` since**
****M2/#280**** (resolve?skip-exists-404?worker fetch?same pipeline?queryable API-DB `video\_id`) +
TESTED; confirmed by inline file:line trace AND a ****3-skeptic verification workflow (0/3**
refuted, gaps:[] ******. So the doc-scoped "build the gcs ingest endpoint" was a phantom; Path B =
****SPA-only (B-P2)****. ****DONE this session:**** (1) ****khelsutra [#55] MERGED**** (master `d0461fd`) ?
corrected `DRY\_RUN\_CUJ` \$1/2/4/6/\$8 + `LOCAL\_APPLIANCE` (`/api/health` EXISTS now M1/#268;
bucket-URI ingest NOT a net-new endpoint; T12 engine-half ? done) + `README`; added the anti-
spiral convention ****"re-verify engine-surface `[gap]`/`net-new` claims at a cited file:line ? the**
engine ships PRs between sessions." (2) ****Memory steering corrected**** (this NEXT-SESSION-FOCUS
block + the dry-run checkpoint were stale "local-path-only") + new lesson [[lesson-verify-
engine-surface-before-scoping]] + MEMORY.md index. (3) ****engine [#284] MERGED**** (master
`06ff4b7`, all CI green incl. full suite 2m32s) ? regression GUARD
`test\_process\_bucket\_uri\_yields\_queryable\_video\_id` (parametrized gs://+gcs://) pinning
`video\_id`=MD5(fetched bytes)` (not the URI) + `POST /api/query` queryability (the SPA contract;
previously only LOCAL had it); built+removed in an isolated worktree off `origin/master` (engine
checkout left on its concurrent-session branch). ****? NEXT: B-P2**** = the SPA ingest/progress
screen (enter gs:// URI ? /api/process ? poll /api/jobs ? load video_id; back-half already
works) ? ****100% `web/` + i18n (en/kn/hi), ZERO engine code****; ready sketch in `DRY\_RUN\_CUJ.md`
\$2 + the workflow synthesis
(`web/src/{api/types,api/client,hooks/useIngestJob,components/IngestPanel}.tsx` + `App.tsx`
videoId?state + `ingest.` keys). Then opt-3 droplet (deploy fixed engine + GCS creds + #281 fix
? re-run CUJ on Linux). ****? Repos SYNCED TO HEAD at session end:**** khelsutra master `d0461fd`;
****engine**** working tree `06ff4b7` ? NOTE the engine main checkout couldn't switch to `master`
(sibling worktree `tier1-windowing` holds it), so it's the merged-but-remote-gone
`feat/serving-m4-device-context` branch ****reset --hard to origin/master + upstream repointed to**
origin/master ****** (safe: tracked tree clean + the 2 divergent commits were the M4 #283 squash,
byte-identical to master; old tip tagged `\_pre\_sync\_m4\_44c9f01` + reflog). So `git pull --ff-
only` works there now; the branch NAME is cosmetic (points at master head).

19 - ****? B-P2 BUILT (in-UI bucket ingest) ? khelsutra**
[#56](https://github.com/avidullu/khelsutra/pull/56) OPEN, CI GREEN (web+site+CF build),
awaiting owner merge ****** (feature PR ? left for owner; precedent exists for me merging SPA PRs on
owner's "merge as you go"). 100% `web/` + i18n, ZERO engine code (rides B-P1). New `web/src/{api
/types,api/client(processVideo/getJob),lib/errors(parseDetail+classifyError),hooks/useIngestJob(
idle?submitting?polling?done|error; recursive-setTimeout poll backoff+10min-ceiling+1 cid;
success-shaped-failure?emptyResult),components/IngestPanel}` + `App.tsx` videoId
useMemo?useState + IngestPanel-when-!videoId + history.replaceState; `ingest.` en/kn/hi (AI-
draft, native-review-pending). ****123 web tests (+19), tsc/build green, browser-verified**** (panel
renders en+hi; live submit?friendly localized "is the engine running?"; cid logs). Live-fixed
UX: bare 5xx/proxy-down ? friendly `networkError`, not "HTTP 500". ****? ALL DONE + MERGED (owner:**
"merge green PRs, improve coverage, leave a CUJ screenshot in the promo bucket; proof-and-
validation-driven"): ****##56 MERGED**** (`4525c5d`). ****LIVE e2e CUJ recorded**** ? real local engine
(Gemini + `google-cloud-storage`+ADC for the gs:// fetch), Playwright-driven: SPA ingest
`gs://mahadevpura\_smoke\_180s.mp4` ? ****12 rallies**** ? Build ? ****reel downloaded (1080p, 76s)****.
****? Recording it SURFACED A REAL BUG:**** `/api/compile` 500'd on a bucket-ingested video ?
`videos.filepath` keeps the `gs://` source URI (M2 provenance), handed straight to the stitcher
? ffmpeg can't open `gs://`. ****FIXED ? engine [#289](https://github.com/Khelsutra/badminton-
highlight-indexer/pull/289) MERGED**** (`e68b583`): compile resolves the source via
`storage.acquire\_local\_input` first (identity local / fetch-to-scratch bucket) + regression
test; full suite ****1182?**. **ScreenCast ? `gs://khelsutra-rally-corpus/promo/khelsutra-bucket-
cuJ-screencast.mp4`** (42s, fast-forwarded Gemini wait + frozen reel-ready climax). ****DoD \$6**
box3 ? ? khelsutra [#57] MERGED** (`7750afc`, +\$9 run result). Engine+SPA+worktrees cleaned up.
? `google-cloud-storage` now pip-installed in the local engine env (enables local gs:// fetch).
****? DOC-SCAN + PLAN (2026-06-21, owner-directed):**** Ran 2 scans ? (a) ****Cloud-Run/serving**** is
the CONCURRENT session's active line (COMPUTE_DECOUPLED_SERVING; M1-M8 merged, M9 #290 open;
`backend/compute/cloud\_run.py` shim + `deploy/cloudrun/Dockerfile`; ****don't duplicate****; key gap
= API `/api/process` NOT yet wired to the ComputeBackend seam, only `backend.worker infer` is);
(b) ****all-docs next-steps**** ? prioritized roadmap. ****Owner clarification:**** "trigger from UI for
alpha users" is NOT M12 + NOT GPU-gated ? it = a ****hosted SPA+engine behind edge auth on a**
reachable box ******; cheapest = ****the parked CPU droplet + Gemini (CPU, no GPU sub needed)****.
****Droplet was parked only for the WASB/GPU CUJ; Gemini alpha doesn't need GPU.**** ****? EXECUTION**
PLAN (owner-approved, merge-on-green): **** doc-hygiene ? ? **B3** (site/ shared `t()`) shim ? NEXT)**
? ****A1**** (plain-lang copy) ? ****A4**** (mobile touch) ? ****A5**** (friendly error map) ? ****A8**** (bg-**

processing chips) ? ****NORTH STAR: runnable tool for alpha = T4 (in-UI file UPLOAD ? keystone; chunked-upload endpoints exist, SPA must call them) ? T2 (droplet appliance shell: serve SPA + reverse-proxy + Cloudflare Access + Gemini; rotate key) ? T11 (retention)**.** ****A2** (WhatsApp/social share) **DROPPED**** ? owner defers all social/sharing to a separate scope; reel stays pure-download (wa.me can't attach files; real file-share = Web Share API = own scope). ****DONE THIS SESSION (post-CUJ):**** ****[#58](https://github.com/avidullu/khelsutra/pull/58)** MULTILINGUAL_EXPANSION proposal OPEN ? owner will merge** (add th/id/da/es/zh-Hans/ja/ko, en/kn/hi-rigor; researched CLDR plurals [es=3-form {one,many,other}!] + OFL Noto fonts [CJK=tens-of-MB offline] + zh-Hans-vs-Hant; phases A Latin?B Thai?C CJK; ****do NOT start until owner approves E0****); ****[#59](https://github.com/avidullu/khelsutra/pull/59)** doc-hygiene **MERGED**** (`a0475bc` ? README DRY_RUN delivered + #58 ptr; LOCAL_APPLIANCE T12 ?; REQUEST_ACCESS P2 ?; PER_RALLY live-CUJ note). ? engine-side doc staleness (DOC_STATUS/NEXT_STEPS lag serving M5-M8; RALLY_QUALITY n=6-vs-15) LEFT for the serving session (avoid collision). [[gotcha-shared-checkout-branch-collisions]] [[working-agreement-merging]]

20

21 ****Checkpoint:**** 2026-06-21 (NEW SESSION ? UX+l10n focus STARTED) ? ramped up via a research+verification ****workflow**** (web/+site/ string maps, Indic-l10n prior art, ****5** adversarial verdicts:****** both surfaces ****ZERO i18n today****; recording-edu ****already shipped**** on the homepage gist + `capture`; `I18N\_PLAN` targets the ****dead**** `backend/api/static` so its P1/P3 wiring retargets to site/+web/). ****?** Isolated the work into ONE umbrella tracked project ? `khelsutra/docs/FRIENDLY\_AND\_MULTILINGUAL.md` (A: non-tech UX + B: kn/hi l10n; §7 P-tracker = source of truth; ****archive when en+kn+hi render on BOTH surfaces****). Pointers wired: khelsutra `docs/README` + `NEXT\_STEPS`; engine `I18N\_PLAN` + `UI\_PROPOSAL` banners + `DOC\_STATUS` §3a/§3b rows (engine edits in an ****isolated worktree off origin/master**** ? engine checkout is a concurrent session's branch; their findings-#1/#2 PR ****#274 merged mid-session**** ? master `03fa951`). ****Owner (AskUserQuestion) locked D6 (en+kn?hi) · D7 (OFL Noto self-host) · D8 (SPA-first) · D9 (catalogs in khelsutra); only D-BACKEND-DEPTH deferred. 3 PRs OPEN:****khelsutra docs **[#41](https://github.com/avidullu/khelsutra/pull/41);** engine pointers **[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275);** ****B1 SPA i18n scaffold + language switcher (en-only) ? [#42](https://github.com/avidullu/khelsutra/pull/42) ? CI GREEN (web+site pass), verified LIVE in-browser**** (switcher EN|???? persists; content falls back to en with no kn catalog; active-highlight follows the ***chosen*** locale ? a bug caught by browser verification + fixed). B1 = react-i18next + ICU + detector + `en` catalog + the SPA's FIRST jsdom render tests (79 tests green); deps MIT/BSD-clean. Engine pointer PR built in an isolated worktree (now removed); engine checkout kept flipping branches (concurrent session active) ? never disturbed. ****?** NEXT slices (tracker §7): B2** (full ~50-string extraction + key-parity/no-bare-strings CI) ? ****B3**** (site `t()` shim) ? ****B4/B5**** (Noto fonts + kn catalog via Gemini-draft?review). ****Also (owner ask, 2026-06-21): the en/kn/hi academy flyers already existed**** (a sibling merged PR ****#40**** ? master `37053b9`; flyer.html / flyer-kn.html / flyer-hi.html served at /flyer{-kn,-hi}) but were UNLINKED ? ****linked all three from the homepage footer + added VM-host clean routes ? [#43](https://github.com/avidullu/khelsutra/pull/43)** (MERGED ? master `f121c7f`)). ****Then **owner asked for MORE flyer placement ?** **[#44](https://github.com/avidullu/khelsutra/pull/44):** "Flyer" in the desktop top-nav + the 3-language links on own-model's foot** (44 site tests green; verified live). (Flyers use Google-Fonts Noto ? separate from the app's D7 self-host; not refactored.) ****Owner #41 comment ? added a rigorous §6.5 "automatic language-negotiation" testing strategy**** (matrix N1?N9: a kn/hi BROWSER auto-gets the respective version; DoD gate) ****+ concrete browser-language detection tests in B1 [#42]**** (N1/N3?N7; 84 web tests green). #41/#42/#275/#44 all merged. ****?** THEN owner: "take it to completion until you can run a screencast with a kannada-default browser ? right page renders ? switch hi ? en; merge PRs as you go." ? ? **DONE** for the `web/` SPA.**** Merged in sequence (I merged each on green CI, owner-authorized): **B2 [#45]**** (full ~50-string extraction + key-parity/no-bare-strings CI) · ****B4 [#46]**** (self-host OFL Noto Kannada/Devanagari, @fontsource-variable) · ****B5 [#47]**** (Kannada catalog) · ****B6 [#48]**** (Hindi catalog ? the extensibility proof: just a catalog + supported-list entry). ****SPA now fully en+kn+hi; 99 web tests green**** (incl. N1/N2 browser-detection, B5/B6 render, key-parity kn==hi==en, `` sync). ****? SCREENCAST PRODUCED**** (Playwright `locale: kn-IN` ? Kannada auto-renders ? switch hi ? en; `C:\Users\avidu\Projects\khelsutra-screencast\khelsutra-i18n-screencast.mp4` (9s) + per-locale frames). Tracker milestone ? **[#49].** ? ****kn/hi are AI-DRAFTED (me) ? native-speaker review pending**** before wide public launch. ****?** **REMAINING** for full §9 DoD (NOT archive-ready):**** **B3**** (the `site/` marketing surface ? homepage/capture still English-only ? via the shared `t()` shim) · ****A3**** recording-education kn/hi · the ****non-tech UX A-items**** (A1/A2/A4/A6...) · native review. Playwright installed in isolated `C:\Users\avidu\Projects\khelsutra-screencast\` (kept out of web/ deps). ****THEN** owner polish batch (2026-06-21) ? all merged:**** (1) **OFFLINE/self-contained verified + guarded ?** **[#50]:**** the SPA is air-gap-renderable (Noto = local woff2 via @fontsource, `@font-face`

url?local `/assets`, no Google-Fonts/CDN, `web/index.html` no external link); CI guard added so it can't regress. *(The marketing `site/` still uses Google-Fonts ? hosted/online surface, not the offline tool; self-host = optional follow-up.)* (2) **SCREENCAST uploaded ? `gs://khelsutra-rally-corpus/promo/khelsutra-i18n-screencast.mp4`** (+ local). (3) **Localized SAMPLE-QUERY PROMPT (en/kn/hi) ? [#51]:** `query.hint` = instructive "type `over 10s` for rallies >10s ? or tap a sample" + `query.try` labels pills "Sample queries"; verified live kn. (4) **\$6.5 testing rule:** i18n testing is now a MANDATORY merge-gate for any future query-parsing/semantic-understanding/NL work (parser is English-grammar-only today, A9). **103 web tests green.** NO open PRs. [[next-session-ux-localization]] [[doc-status-register]] [[working-agreement-tracked-project-docs]]

22

23 **Checkpoint:** 2026-06-21 (DRY-RUN CUJ + a CRITICAL ENGINE FIX) ? owner: "stitch the UI to the tool; dry-run a **GCS-bucket video** via the UI ? **reel downloaded local**"; repeat in Hindi. Run locally (opt 1) then droplet (opt 3); report both; identify fixes + merge." Chose **A-now-then-B**, **Gemini**. **Tracked goal ? `khelsutra/docs/DRY\_RUN\_CUJ.md`** ([#53]/[#54]). **? PATH-A LOCAL RUN DONE (en + hi):** isolated engine off origin/master (fresh DB/output worktree) + `.env` Gemini key ? `gsutil cp gs://khelsutra-rally-corpus/videos/mahadevpura\_smoke\_180s.mp4` ? `POST /api/process {gemini}` ? **12 rallies** (`video\_id 05e0e577`) ? SPA `npm run dev` (Vite proxies /api?:8000) `?video=05e0e577` ? loaded 12 real rallies ? **Build ? /api/compile ? reel (1080p, 76.5s) DOWNLOADED to `~/Downloads/khelsutra-dryrun/highlights\_local\_{en,hi}.mp4`** (50.9MB). **Hindi repeat ?** (page/cards/"??? ?"/"??? ?" all Hindi; reel downloaded). ***? CRITICAL BUG FOUND + FIXED ? engine [#281](https://github.com/Khelsutra/badminton-highlight-indexer/pull/281) MERGED:** running the documented `python -m backend.main --server` runs main.py as `\_\_main\_\_` (sets `\_\_main\_\_.db\_instance`), but `job\_worker`/`uploads` read `import backend.main` ? a SEPARATE module whose `db\_instance` stays None ? the async-job drain crashes silently on `None.claim\_due\_job()` ? **every /api/process job hangs in `queued` forever**. Latent: unit tests monkeypatch the executor inline; the UI was verified vs a STUB engine. Fix = dispatch `\_\_main\_\_`?`backend.main`; + `tests/test\_server\_entrypoint.py` (real subprocess guard, FAILS-without/PASSES-with). Full engine suite green (2m23s). **Unblocked the run via the single-module invocation** (`python -c "...; from backend import main as m; m.main()"`). ? **OPT-3 DROPLET (168.144.126.176) NOT YET RUN:** reachable (Linux, py3.12, ffmpeg, 2-core/3.8GB) but **un-provisioned** (no `~/rally` engine checkout) ? needs a from-scratch engine install OR a proper deploy of the FIXED engine (the fix applies there too). **? NEXT:** opt-3 droplet run (deploy fixed engine ? re-run CUJ); Path B (in-UI bucket ingest). **CORRECTION (next-session verify):** the "/api/process is local-path-only / net-new gcs ingest" note here was STALE** ? `api/process` already accepts `gs://` (M2/#280, tested); Path B is **SPA-only (B-P2)**, no engine endpoint. (The "worker writes CSV to the bucket not the API DB" bit is the *separate* `worker infer` CLI, not the API path ? that's what the stale claim conflated.) Docs fixed ? khelsutra [#55]; see the NEXT SESSION FOCUS block above + [[lesson-verify-engine-surface-before-scoping]]. [[monetization-plan]]

24

25 ***? HANDOFF (2026-06-20) ? KHELSTRA.GURU brand site: shipped, live, portable. Resume the product threads below.** Separate track from the indexer rally-detection handoff that follows. Full durable record + ramp-up: [[khelsutra-domain-launch]]. Repo = **`avidullu/khelsutra`** (NOT this indexer repo).

26 - ***? START HERE (2026-06-20, latest ? big session, ALL MERGED, NO open PRs).** Per-rally **MVP/M0 COMPLETE** + a full product/promo wave. **khelsutra master `a7214ad`** . **engine (Khelsutra/badminton-highlight-indexer) master has M1 [#268]**.

27 - **Per-rally MVP (khelsutra `web/` SPA):** P3 `parseQuery()` query bar [#28] (length/order/count/shot_count; greys shot-type/player/score "not available yet" ? never faked; **13 adversarial-review findings folded in**) . P4 `SelectionFooter`+honest `min\_shot\_count` warning [#30] (`web/src/lib/floor.ts` mirrors `main.py:362-383`; no-shot_count exempt; all-below ? Build DISABLED) . P5 real load `?video=<id>` + Build?`compileReel`?`<video>` preview+download [#31]. Full obs (`query.\*`/`build.\*`/one cid). **Then: lead-with-LENGTH, shot-count flagged EXPERIMENTAL** [#33] (cards show `m:ss long`; amber "experimental" chip; duration-led examples; badge `P5`?`alpha`; parseQuery still accepts shot-count, de-featured). Suite **75 green**.

28 - **Engine M1 [#268] (GCP/org repo, built in an ISOLATED git worktree off origin/master so the concurrent session's checkout was untouched):** `GET /api/health` ({status,sport,default_segmenter}) + `POST /api/compile` now returns **`download\_url`** (additive; `filepath` unchanged). Full engine suite **1019 passed/7 skipped**, ruff+mypy clean, CI green (coverage floor incl. torch). *(SPA can adopt `download\_url`/offline-banner as a follow-up.)*

29 - **GCS round-trip (reuse artifacts, CPU/no-GPU):** pulled `mahadevpura\_smoke\_180s.mp4` + intervals from the bucket ? **stitched a curated top-10-longest

```

highlight** (ffmpeg) ? **put it back** at `gs://khelsutra-rally-
corpus/highlights/curated_top10_longest.mp4` (61s).
30 - **3 screencasts (Playwright?webm?ffmpeg):** `promo_cuj.mp4` (old UI, real footage) .
**full_cuj_real.mp4** (NEW duration-first UI + REAL curated reel ? the definitive full-CUJ) ?
both in `gs://khelsutra-rally-corpus/promo/` (real footage ? bucket, NOT public repo) .
**site/public/video/tool-cuj.mp4** (NEW UI, **footage-free** branded-placeholder reel ? safe
to self-host). Local copies in `badminton-highlight-indexer/artifacts/promo/` (gitignored).
31 - **Site (excite-to-join) [#34/#35]:** after sign-up the reveal now shows **(1) the
tool in action** (self-hosted footage-free `tool-cuj.mp4`) **+ (2) a ~30s reel preview**
(`REEL_SECS` 90?30, gated nocookie YouTube ? real faces stay in the unlisted reel, not the
repo); `revealAfterSignup`; coherent CTA/teaser copy; `server.js` serves `.mp4` as `video/mp4`;
`.mp4`/`.gif` marked binary. Site suite **34 green**; **droplet re-synced + parity GREEN**
(index+mp4 byte-identical CF?VM:8787).
32 - **? GPU note:** could NOT spin a fresh GPU VM ? `GPUS_ALL_REGIONS=1` slot held by
the concurrent session's `rally-gpu` M2 training (did NOT disturb). Validated CUJ against the
first-L4-run REAL artifacts instead. A fresh live `/api/process` GPU inference stays
**deferred** until the GPU frees (low-risk existing path). **Owner observation ? [[machine-
pooling-idea]]** (pool GPUs vs spin/kill per task).

```

7. user (2026-06-21T14:48:21.253Z)

```

1 # Friendly & Multilingual ? non-tech-savvy UX + Hindi/Kannada localization
2
3 > **Status:** `DRAFT` ? owner-gated (implementation starts only on explicit approval) .
**Owner:** Avi Dullu . **Created:** 2026-06-21 . **Last updated:** 2026-06-21
4 > **Lifecycle:** `DRAFT ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when
DONE).
5 > **Tracking anchors:** $7 progress tracker is the source of truth; indexed in
`docs/README.md`; thread in `NEXT_STEPS.md`; pointer in engine `docs/DOC_STATUS.md`; memory
`current-state` + `next-session-ux-localization`.
6 > **Relation to existing docs:** this is the **implementation project** for two engine
design docs ? it *adapts & supersedes-in-practice* `badminton-highlight-
indexer/docs/I18N_PLAN.md` (localization) and the UX half of `?/docs/UI_PROPOSAL.md` (non-tech-
savvy console). Those stay the canonical *design*; this doc carries the *tracked execution*
against today's surfaces.
7 > **Honesty note:** each claim tagged `[verified]` (checked against code this session),
`[researched]` (needs sign-off), or `[design]` (proposed). Not legal advice ? the OFL font
question (D-FONT) is owner/counsel-gated.
8
9 ---
10
11 ## 0. TL;DR
12 A coach or parent in Bangalore should land on KhelSutra, feel at home, set up their
camera with confidence, and get highlights ? **in Kannada or Hindi**, with **zero hand-
holding**. This project isolates that goal into one tracked workstream-pair: **(A)** make the UI
super friendly for non-tech-savvy users, and **(B)** localize to Hindi + Kannada. Both surfaces
(`web/` React SPA + `site/` vanilla marketing) have **zero i18n today** `[verified]`, so the
foundation ? shared `locales/{en,kn,hi}` catalogs + a negotiation contract + CI parity ? is the
real deliverable; translations follow. **The single most important caveat:** translations are
**human-reviewed** (Gemini drafts are *inference only, never training* ? the standing
guardrail), and Kannada/Hindi rendering is **blocked on the OFL font decision (D-FONT)**. The
cheapest unblocked high-impact first slice is the **SPA i18n scaffold + language switcher (en-
only)** ? it locks the shared catalog/negotiation contract and adds the render-test safety net
the SPA currently lacks.
13
14 ## 1. Problem & goal
15 **Why now.** The public site (khelsutra.guru) is live, clean, honest, and tested. The
PMF beachhead is **Bangalore badminton academies**; many coaches, parents, and players are far
more comfortable in **Kannada** than English, and most are **not highly tech-savvy** `[verified
? design intent]` (`UI_PROPOSAL.md:25,28`, `I18N_PLAN.md:10-13`, `PMF_MARKET_RESEARCH.md:116`,
`KHELSUTRA_PRODUCT_OVERVIEW.md:13/50/61`). An English-only, knob-heavy product adds friction at
the exact point of first contact.
16
17 **Concrete outcome ("good" looks like):** a Kannada/Hindi-comfortable, phone-first, non-
technical coach/parent can ? without help ? (1) understand what the product does and how to

```

record reliably, (2) request access / use the console, (3) pick rallies and get a reel, and (4) share it on WhatsApp, **entirely in their language**.

18
19 **Read to get current:** this doc's §3?§4; the engine design `I18N\_PLAN.md` (canonical i18n design) + `UI\_PROPOSAL.md` §2 (personas, the 6 alpha screens, "teach recording *before* upload"); `VIDEO\_RECORDING\_GUIDELINES.md`; this repo's `PER\_RALLY\_SELECTION.md` (the honest SPA scope) + `REQUEST\_ACCESS\_FORM.md`.

20
21 ## 2. Decisions locked (structural ? owner directive 2026-06-21)
22 | # | Decision | Source / date | Implication |
23 |---|-----|-----|-----|
24 | D1 | **Isolate as ONE tracked project** spanning both workstreams (A: UX, B: kn/hi l10n) | owner, 2026-06-21 | This doc; §7 = source of truth; archived on DoD |
25 | D2 | **Home = `khelsutra/docs/`** (the implementation repo) | owner-gated tracked-doc convention | `web/` + `site/` both live here; §7 tracks khelsutra PRs; engine P2 backend-l10n is a cross-repo deferred row |

26 | D3 | **Adapt `I18N\_PLAN.md` to today's surfaces:** P1 (vanilla `t()`) shim ? `site/`; P3 (react-i18next) ? `web/`; **drop the dead `backend/api/static` retrofit** | `[verified]` the doc targets `backend/api/static` (`I18N\_PLAN.md:25,30,156,191`) which exists only in the engine repo, not here | The doc's framework-agnostic *foundation* (catalog format + negotiation + ICU plurals + CI) survives unchanged; only the wiring re-points |

27 | D4 | **Engine P2 backend-localization stays owner-gated + cross-repo** (not in this DoD) | `CLAUDE.md` guardrails | Dynamic engine error/report text localizes later; tracked as a deferred row |

28 | D5 | **Archive trigger = en+kn+hi live on BOTH surfaces** (+ the non-tech UX baseline), then run the engine `DOC\_STATUS.md` §2` archival checklist | owner, 2026-06-21 | See §9 |

29 | D6 | **D-LOCALES: `en` + `kn` for v1, `hi` next; always-fallback to `en`** | owner, 2026-06-21 | Kannada-first beachhead; `hi` = catalog-only (both 2-form CLDR) |

30 | D7 | **D-FONT: OFL-for-media carve-out ? self-host Noto Sans Kannada/Devanagari** (counsel may still confirm) | owner, 2026-06-21 | Unblocks B4/B5/A3 + the kn/hi reel watermark; an explicit exception to the MIT/Apache/BSD code guardrail (fonts = media) |

31 | D8 | **D-SURFACE-FIRST: lead with the `web/` SPA scaffold; SKIP the dead static-UI retrofit** | owner, 2026-06-21 (via B1 go-ahead) | B1 is greenlit; site recording-education localized early |

32 | D9 | **D-CATALOG-HOME: co-locate `locales/` + CI in `khelsutra`** (shared, consumed by SPA + site) | owner, 2026-06-21 (via B1 go-ahead) | No cross-repo coupling |

33
34 *Only **D-BACKEND-DEPTH** (§8.3) remains open ? and it's a deferred, cross-repo engine concern (B7), not a v1 blocker.*

35

36 ## 3. Foundation ? research / prior art

37 **Current-state facts `[verified]` this session** (adversarially checked against the working tree):

38 - **`web/` SPA: zero i18n.** `web/package.json` deps are only `react`/`react-dom`; no `i18next`/`react-intl`/`formatjs`; no `locales/` dir; no `t()`. `useTranslation`/`data-i18n` anywhere. User-facing English is hardcoded in `tsx` (e.g. `QueryBar.tsx:46-47,56,72,76,78`; `App.tsx:115,211,224`) ? ~50 literals + ~16 derived labels.

39 - **`site/` marketing: vanilla, zero i18n.** Three `

40 - **Recording-education is *not* greenfield.** The homepage "Record it right" gist (`index.html:324-364`) + the `capture` checklist (`capture.html`, routed `server.js:51`, guarded `assets.test.js:94`) already ship the user-facing best-practices surface. *Unshipped:* the empirical-threshold framing and the programmatic pre-flight validator (a code change, not a page).

41 - **Persona is design intent, not built.** kn/hi + zero-knobs are **proposed/owner-gated**; the app is English-only today (`KHELSUTRA\_PRODUCT\_OVERVIEW.md:61`). It's Kannada-**first**, Hindi-**next** ? not Kannada-only.

42

43 **Localization prior art `[researched]`:

44 - **CLDR plural categories:** Hindi = `{one, other}`; Kannada = `{one, other}`. Both are 2-form (same shape as English) ? once ICU MessageFormat is in the catalog, adding `hi`/`kn` plurals is **catalog-only**, no code. (ICU still required because English `count>1`'s:''' hand-

rolling ? present today in the SPA ? doesn't generalize.)

45 - **react-i18next** (web/): ``i18next` + `react-i18next` + `i18next-browser-languagedetector`` + an ICU/plural post-processor; lazy-load per-locale JSON; persist via ``localStorage``.

46 - **Shared catalog + tiny shim** (site/): the SAME i18next-flavored JSON consumed by a ~30-line ``t(key, vars)`` shim that walks ``data-i18n`` attributes ? no build step, no framework, mirrors i18next interpolation/plural rules for the 2-form languages.

47 - **Noto Sans Kannada / Noto Sans Devanagari** are **OFL-1.1**; OFL permits commercial bundling/redistribution (fonts = media, not code/weights). Self-host (e.g. ``@fontsource``) with ``font-display: swap`` + subsetting. **Gated on D-FONT.**

48 - **Non-tech-savvy / HCI4D patterns:** **icon** **++ text** (never icon-only), non-color selection indicators, large touch targets, mobile-first, WhatsApp as the share channel, a prominent persistent language switcher.

49

50 **## 4. Design / architecture**

51 **Two surfaces, one shared source of truth.**

52

53 `````

54 `locales/` # shared catalogs ? co-located in khelsutra (D-CATALOG-HOME, see §8)

55 `en/ common.json` # source of truth ? devs author keys here

56 `kn/ common.json` # Kannada (Gemini-draft ? human-review)

57 `hi/ common.json` # Hindi (next ? the extensibility proof)

58

59 `web/ ? react-i18next` # I18N_PLAN P3: provider in main.tsx; useTranslation in components

60 `site/ ? t(key,vars) shim` # I18N_PLAN P1 retargeted: data-i18n attrs over the static HTML

61 `````

62

63 - **Negotiation contract** (one order, both surfaces): **persisted pref** (localStorage) ? `switcher / ?lang=<code> ? navigator/Accept-Language ? "en"`. Supported locales in a single module; anything else falls back to ``en``; **a missing key degrades to English, never to a raw key.**

64 - **Keys, never prose** ? ``t("compile.button")``, with ICU for interpolation/plurals: ``"${count, plural, one {# rally} other {# rallies}}"``. This replaces the SPA's current hand-rolled ``Segment${count>1?'s':''}``.

65 - **Translation pipeline** (guardrail-clean): **dev authors** ``en`` keys ? ``scripts/i18n_draft.py``-style Gemini **draft** (inference only, never training; flags every value for review) ? **owner/native-speaker review** ? CI key-parity ? merge. Gemini never touches ``en``, never invents keys.

66 - **CI enforcement** (keeps it "by design"): (1) **key-parity** ? every locale has exactly the ``en`` key set (drop a stub ``ta.json`` ? CI lists every gap = the extensibility proof); (2) **no-bare-strings** ? flags user-facing literals not routed through ``t()`` (curated allowlist to start).

67 - **Fonts:** bundle Noto Sans Kannada + Devanagari **iff D-FONT = OFL carve-out**; this also unblocks a Kannada/Hindi **reel watermark** (engine ``WatermarkConfig.font_path`` already takes a path ? config, not code).

68

69 **Non-tech-savvy UX levers** (ranked impact × effort, grounded in personas; surface-tagged):

70

Lever	Surface	Impact	Effort	Note
Plain-language copy ? strip engine jargon, keep honest caveats	both	high	small	banners + footer carry backend vocabulary today
Localized WhatsApp share for the downloaded reel	both	high	small	WhatsApp is <i>the</i> channel for this audience
Language switcher persisted via a shared localStorage key	both	high	small	site promises kn/hi but ships no switcher
Localize recording-education (capture + gist)	kn?hi	site	high	medium gates input quality; the highest-leverage kn content
Mobile-first touch targets; tooltip-text ? visible	web	high	medium	tiny targets + desktop layout + invisible tooltips on phones
Icon ++ text + non-color selection indicator	web	medium	small	never icon-

```

only |
79      | Friendly engine-error mapping over raw FastAPI `detail` | web | medium | medium |
`CompileResult` passes engine text untranslated |
80      | Plain-language framing for the Request-Access GPU/storage Qs | site | medium | small |
"GPU"/"S3/GCS" are intimidating |
81      | Background-processing reassurance + status as icon chips | web | medium | small |
honest expectations on slow uplinks |
82      | Fix English-source recording gaps (a diagram) before translating | site | medium |
medium | the diagram is reusable across all 3 languages |
83      | Tap-only filter controls alongside the English query bar | web | medium | large | the
`parseQuery()` parser is English-grammar only |
84      | Keep the honest *today-vs-roadmap* split through translation | both | medium | small |
never soften "experimental"/"not available yet" |
85
86      **Reuse map (what's new vs reused):** *Reused* ? the i18next-flavored JSON + negotiation
contract + ICU plurals + key-parity/no-bare-strings CI + draft?review pipeline (all from
`I18N_PLAN.md`); the shipped recording pages; the SPA's `lib/format.ts`/`lib/query.ts`;
`site/src/assets.test.js` + the SPA's vitest harness. *New* ? `locales/` catalogs; the SPA
react-i18next provider + switcher; the site `t()` shim + `data-i18n` wiring; Noto font bundle
(gated); a jsdom render-test env for the SPA.
87
88      ## 5. Privacy / scope note
89      i18n touches **presentation only** ? no new personal-data collection, no biometrics,
minors-excluded posture unchanged. WhatsApp share opens the user's own client with a pre-filled
message; it sends nothing server-side. Gemini-draft translation is inference, not training (no
user data in the loop).
90
91      ## 6. Honest limits ? what this does NOT do
92      - A green CI / DONE status proves **key-parity + render + no-bare-strings**, **not**
translation *quality* ? that's human-gated and owner-paced.
93      - Kannada/Hindi will **not render** until the Noto fonts land (D-FONT); until then kn/hi
catalogs exist but display tofu/fallback.
94      - The SPA is **job-tethered**;; localizing **dynamic engine errors/report text** needs
engine P2 (owner-gated, cross-repo, D-BACKEND-DEPTH) ? out of this DoD.
95      - The query bar stays **English-grammar parsing**;; kn/hi users rely on tap-only controls
(a later, larger slice), not free-text Kannada queries.
96      - **Mobile-*perfect*** layout is an alpha non-goal (usable-on-phone is in scope; pixel-
perfect is not).
97
98      ## 6.5 Testing strategy ? automatic language negotiation (rigorous, owner-required)
99      **The bar (owner, #41):** a user whose **computer/browser language is Kannada or Hindi
must get the respective version automatically** ? that is the core promise and it is **proven by
tests at every layer, never assumed.** Auto-selection IS the negotiation order (persisted pref ?
`?lang=` ? browser/`Accept-Language` ? `en`); each step gets a test.
100
101      **Negotiation matrix ? every row is an automated test:**
102
103      | # | Signal under test | Setup | Expected | Proven in |
104      |---|---|---|---|---|
105      | N1 | **Browser/OS = Kannada** | no persisted pref, no `?lang`,
`navigator.languages=["kn-IN", ?]` | resolves to **kn** ? Kannada content (once the kn catalog
ships) | **B1** detection . **B5** content |
106      | N2 | **Browser/OS = Hindi** | `navigator.languages=["hi-IN", ?]` | resolves to **hi**
? Hindi content | **B6** (hi added to the supported set + catalog) |
107      | N3 | **`?lang=` override** | `?lang=kn`, browser = en | kn | B1 |
108      | N4 | **Persisted pref wins** | `localStorage=kn`, browser = en, no `?lang` | kn (a
returning user keeps their choice) | B1 |
109      | N5 | **Region subtag normalizes** | `navigator.language="kn-IN"` | base **kn** (not a
"kn-IN" miss) | B1 |
110      | N6 | **Unsupported language** | `navigator="ta-IN"` (Tamil, not yet supported) |
**en** fallback ? never a locale we can't serve | B1 |
111      | N7 | **Missing key in active locale** | kn active, a key absent from `kn/common.json`
| **en** fallback for that key (no raw key shown) | B1/B5 |
112      | N8 | **Static site (vanilla shim)** | `Accept-Language: kn` / `?lang=kn` on a `site/`
page | kn-rendered page (same order as the SPA) | B3 |

```

```

113 | N9 | **Backend (engine P2)** | `Accept-Language: kn` to the API | kn customer/report
text | B7 (owner-gated) |
114
115 **Levels & tooling:**
116 - **SPA (`web/`):** jsdom tests stub `navigator.language`/`navigator.languages`,
`localStorage`, and the `?lang` query ? assert `i18n.language`/`resolvedLanguage` + rendered
text per the matrix. *(B1 lands N1/N3?N7 at the **detection** level now ? `kn` is supported; the
kn/hi **content** assertions ride the catalogs in B5/B6.)*
117 - **Static site (B3):** the shared `t()` shim's negotiation is unit-tested the same way;
plus a server test that `Accept-Language: kn`/`?lang=kn` returns the kn-rendered page.
118 - **CI key-parity:** guarantees every locale has every key, so a correctly-negotiated
locale can never fall through to a raw key.
119 - **End-to-end (manual, owner machine ? per I18N_PLAN $6):** set the real OS/browser to
Kannada, then Hindi ? load both surfaces ? confirm the right language renders **and the Noto
fonts display** (the cloud CI container can't render fonts; the owner eyeball is the final
gate).
120 - **? Query parsing / semantic understanding (forward-looking, owner directive
2026-06-21) ? i18n testing is MANDATORY there.** The query bar is **English-grammar-only** today
(a documented limit, tracker A9): the user types English queries (`over 10s`, `top 15 longest`)
and a localized **sample-query prompt** shows them what to type in *every* locale (kn/hi
included). The **moment** the parser gains **semantic understanding** or accepts **Kannada/Hindi
query input** (e.g. typing a Kannada/Hindi phrase, or a conversational/NL builder ? I18N_PLAN
P4), i18n tests become a **merge gate**: a kn/hi query (typed or spoken) must parse to the
**correct selection**, the localized **parse-feedback** ("parsed-pill") must render in the
active locale, and the unsupported/empty-result messages must localize. **No query-NL /
semantic-parsing work merges without those tests.**
121
122 A locale that's reachable by the switcher but **not auto-selected from the browser
language is a bug, not a "later". ** This matrix is a DoD gate ($9).
123
124 ## 7. Deliverables & progress tracker ? **source of truth**
125 Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**,
branched from `origin/master`, no stacking.
126
127 | ID | Deliverable | Workstream | Depends on | Gated? | Status | PR |
128 |----|-----|-----|-----|-----|-----|----|
129 | P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |
[41](https://github.com/avidullu/khelsutra/pull/41) · engine
[275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275) |
130 | B1 | **SPA i18n scaffold + language switcher, en-only** (react-i18next + detector +
`en` catalog + switcher + persistence + **jsdom render tests** + **browser-language negotiation
tests** $6.5 N1/N3?N7) | B | P0 | No | ? | [42](https://github.com/avidullu/khelsutra/pull/42)
|
131 | B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys);
add **key-parity + no-bare-strings CI** | B | B1 | No | ? |
[45](https://github.com/avidullu/khelsutra/pull/45) |
132 | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color
selection) | A | B2 | No | ? | ? |
133 | B3 | Tiny shared `t()` shim + `data-i18n` plumbing for `site/`, en-only (proves shared
catalogs across surfaces) | B | B2 | D-CATALOG-HOME | ? | ? |
134 | A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
135 | A6 | Plain-language framing for Request-Access GPU/storage questions | A | B3 | No | ?
| ? |
136 | A7 | Fix English-source recording gaps (add a placement diagram) before localizing | A
| ? | No | ? | ? |
137 | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? *SPA done; reel
watermark `font_path` = engine follow-up* | B | ? | D-FONT | ? | ? |
[46](https://github.com/avidullu/khelsutra/pull/46) |
138 | B5 | **Kannada (`kn`) catalog** ? render ? *SPA done (AI-draft, native review
pending); `site/` rides B3* | B | B2/B4 | D-LOCALES | ? | ? |
[47](https://github.com/avidullu/khelsutra/pull/47) |
139 | A3 | Localize **recording-education** (capture + homepage gist) to kn | A | B3/B5 |
D-LOCALES+D-FONT | ? | ? |
140 | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? | ? |
141 | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) |

```

A | B2 | No | ? | ? |

142 | B6 | ****Hindi (`hi`) catalog**** ? render (the extensibility proof ? just a catalog) ?
SPA done (AI-draft, native review pending) | B | B5 | D-LOCALES ? | ? |
[#48](https://github.com/avidullu/khelsutra/pull/48) |

143 | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 |
No | ? | ? |

144 | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ?
| ? |

145 | B7 | ***(deferred, cross-repo)* Engine **P2 backend customer-facing localization****
(report `customer\_` + rejection reasons) | B | engine | ****D-BACKEND-DEPTH, owner-gated**** | ? |
? |

146

147 ***** MILESTONE ? SPA fully trilingual (2026-06-21):**** the `web/` Studio SPA now speaks
****en + kn + hi**** end to end (B1?B2?B4?B5?B6, all merged). A ****Kannada-default browser auto-**
renders Kannada**, and the switcher walks kn ? hi ? en ? ****proven by a Playwright screencast****
with `locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + `
lang>` tracked). This meets the owner's success criterion ****on the SPA surface****. ****Still open**
for the full §9 DoD:**** B3**** (the `site/` marketing surface via the shared `t()` shim ? the
homepage/capture pages are still English-only), ****A3**** (recording-education in kn/hi), the
****non-tech UX A-items****, and a ****native-speaker review**** of the AI-drafted kn/hi catalogs before
a wide public launch. Do ****not**** archive until both surfaces are trilingual.

148

149 **## 8. Open questions ? owner (blocking gates) `[design]`**

150 ***Status (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see §2 (D6?D9). Only**
D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

151 1. ****D-FONT ? ? LOCKED ? (a) OFL-for-media carve-out, self-host Noto Sans**
Kannada/Devanagari** (counsel may still confirm). An explicit exception to the MIT/Apache/BSD
code guardrail (fonts = media). Unblocks B4/B5/A3 + the kn/hi reel watermark.

152 2. ****D-LOCALES ? ? LOCKED ? `en` + `kn` for v1, `hi` next, always-fallback to `en`****
(both 2-form CLDR ? `hi` is catalog-only).

153 3. ****D-BACKEND-DEPTH ? ? OPEN (deferred, not a v1 blocker).**** Recommend ****customer**
verdict/report `customer\_` + validation-rejection reasons first; technical/operator text stays
English; phase two** (engine repo, owner-gated ? tracker row B7).

154 4. ****D-SURFACE-FIRST ? ? ADOPTED ? lead with the SPA scaffold (B1), localize site**
recording-education early, SKIP the dead static-UI retrofit.**

155 5. ****D-CATALOG-HOME ? ? ADOPTED ? co-locate `locales/` + CI in `khelsutra`**** (a shared
i18n dir consumed by both the SPA and the site). (The engine `I18N\_PLAN` assumed the indexer
repo; this is the adaptation.)

156

157 **## 9. Definition of done**

158 - [] ****Automatic language negotiation (§6.5) is green**** ? a ****Kannada browser gets**
Kannada and a Hindi browser gets Hindi** (N1/N2); persisted-pref / `?lang` / region-subtag /
unsupported-fallback / missing-key-fallback all proven (N3?N7) on the SPA, and the static-site
shim honors `Accept-Language` + `?lang` (N8).

159 - [] ****Manual cross-check (owner machine):**** OS/browser set to Kannada and to Hindi
each render the respective language on BOTH surfaces, with Noto fonts displaying.

160 - [] **`en + kn + hi` catalogs live and ****rendering**** on BOTH `web/` SPA and `site/`**
marketing (switcher + persistence + `en` fallback; no raw keys shown).

161 - [] ****Noto Sans Kannada + Devanagari render correctly**** ? owner eyeball on a real
machine.

162 - [] CI ****key-parity + no-bare-strings**** green; a stub locale flags every gap.

163 - [] ****Recording-education**** (capture + homepage gist) available in `kn` + `hi`.

164 - [] ****Non-tech UX baseline:**** plain-language copy (no raw engine jargon in user-facing
strings), mobile-usable touch targets, icon+text, WhatsApp share, honest today-vs-roadmap
preserved through translation.

165 - [] §7 all rows ? (or explicitly deferred with a reason) ? flip ****Status ? DONE**** +
completion note ? run engine `DOC\_STATUS.md §2` archival checklist ? `git mv` to
`docs/archives/`.

166

167 **## 10. References**

168 ****Internal code anchors `[verified]`:**** `web/package.json`,
`web/src/{App.tsx,main.tsx,components/QueryBar.tsx,components/CompileResult.tsx,lib/query.ts}`;
`site/public/{index,capture,own-model}.html`, `site/server.js`, `site/src/assets.test.js`.
****This repo's docs:**** `docs/PER\_RALLY\_SELECTION.md`, `docs/REQUEST\_ACCESS\_FORM.md`,
`docs/README.md`, `NEXT\_STEPS.md`. ****Engine design docs (canonical):**** `badminton-highlight-inde

```

xer/docs/{I18N_PLAN.md,UI_PROPOSAL.md,VIDEO_RECORDING_GUIDELINES.md,PMF_MARKET_RESEARCH.md,PMF_F
IELD_SIGNALS.md,KHELSUTRA_PRODUCT_OVERVIEW.md,DOC_STATUS.md}`. **External `[researched]`:**
Unicode CLDR plural rules (kn/hi = one/other); react-i18next + i18next-icu; SIL Open Font
License 1.1; Google Noto Sans Kannada/Devanagari.
169
170 ---
171
172 ### Changelog
173 - `2026-06-21` ? created. Isolated the UX + Hindi/Kannada work into one tracked project
(owner directive). Grounded in a multi-agent research+verification pass (web/+site/ string maps,
Indic-l10n prior art, 5 adversarial verdicts). Decisions D1?D5 locked; 5 product/licensing
decisions surfaced as open; $7 tracker seeded with B1 as the recommended first slice.
174 - `2026-06-21` ? owner locked **D6 (en+kn?hi)** + **D7 (OFL Noto carve-out)** and
adopted **D8 (SPA-first)** + **D9 (catalogs in khelsutra)**; only D-BACKEND-DEPTH remains open.
**B1 greenlit ? ? in progress.**
175 - `2026-06-21` ? **B1 opened ? [#42](https://github.com/avidullu/khelsutra/pull/42)**:
SPA i18n scaffold (react-i18next + ICU + detector) + `en` catalog + language switcher + the
SPA's first jsdom render tests. Verified typecheck/79-tests/build green + live in-browser
(switcher persists, en-fallback). Doc/pointer PRs opened: khelsutra
[#41](https://github.com/avidullu/khelsutra/pull/41), engine
[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275).
176 - `2026-06-21` ? **$6.5 Testing strategy added (owner ask, #41):** a rigorous
**automatic-negotiation matrix** (N1?N9) so a Kannada/Hindi **browser** auto-gets the respective
version ? proven at the detection level now (B1), at the content level with the catalogs
(B5/B6), on the static shim (B3), and by a manual font-render eyeball. Wired into the DoD ($9).
B1 (#42) gains the detection tests (N1/N3?N7).
177 - `2026-06-21` ? **? SPA MILESTONE: fully trilingual (owner directive "take it to
completion + screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ?
B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all
merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity.
**Playwright screencast** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ?
switch hi ? switch en, each with `<html lang>` tracked (`khelsutra-i18n-screencast.mp4` + per-
locale frames). kn/hi are **AI-drafted ? native review pending**.
```

****Remaining for full \$9 DoD:****
B3 (the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.

178

8. assistant (2026-06-21T14:48:42.431Z)

I've ramped up. Key context absorbed:

- **A1 already merged (#60)** ? though the \$7 tracker still shows A1 as ? (stale; I'll fix that).
- Mission order: **A4 ? A5 ? A8 ? B3 ? North Star (T4/T2/T11)** , plus the owner-approved 7-language line in parallel.
- Shared checkout discipline: branch from `origin/master`, don't touch the serving track.

Let me get oriented on the actual `web/` code surface before scoping. Let me look at the structure and key files.

9. user (2026-06-21T14:48:45.289Z)

```

=== web/src tree ===
web/src/App.tsx
web/src/api/client.test.ts
web/src/api/client.ts
web/src/api/types.ts
web/src/components/CompileResult.tsx
web/src/components/IngestPanel.test.tsx
web/src/components/IngestPanel.tsx
web/src/components/LanguageSwitcher.tsx
web/src/components/QueryBar.examples.test.ts
web/src/components/QueryBar.tsx
web/src/components/RallyGrid.tsx
web/src/components/SelectionFooter.tsx
web/src/hooks/useIngestJob.test.ts
web/src/hooks/useIngestJob.ts

```



```
web/src/hooks/useRallySelection.ts
web/src/i18n/hygiene.test.ts
web/src/i18n/i18n.test.tsx
web/src/i18n/index.ts
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
web/src/index.css
web/src/lib/errors.test.ts
web/src/lib/errors.ts
web/src/lib/floor.test.ts
web/src/lib/floor.ts
web/src/lib/format.test.ts
web/src/lib/format.ts
web/src/lib/log.ts
web/src/lib/query.test.ts
web/src/lib/query.ts
web/src/lib/selection.test.ts
web/src/lib/selection.ts
web/src/main.tsx
web/src/test/setup.ts
```

=== locales ===

```
web/src/i18n/locales
web/src/i18n/locales/en
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn
web/src/i18n/locales/kn/common.json
```

=== site tree (public html + server) ===

```
site/package-lock.json
site/package.json
site/public/capture.html
site/public/flyer-hi.html
site/public/flyer-kn.html
site/public/flyer.html
site/public/index.html
site/public/own-model.html
site/server.js
site/src/assets.test.js
site/src/deploy-config.test.js
site/src/index.js
site/src/index.test.js
site/src/notify.js
site/src/server.test.js
site/src/store.js
site/src/ux.dom.test.js
```

10. assistant (2026-06-21T14:48:50.976Z)

Now let me read the key files I'll be working with for the A-items. Reading the components, errors lib, CSS, and the en catalog in parallel.

11. user (2026-06-21T14:48:51.934Z)

```
1    import { useEffect, useMemo, useState } from "react";
2    import { useTranslation, Trans } from "react-i18next";
3    import { useRallySelection } from "../hooks/useRallySelection";
4    import { RallyGrid } from "../components/RallyGrid";
5    import { QueryBar } from "../components/QueryBar";
6    import { SelectionFooter } from "../components/SelectionFooter";
7    import { LanguageSwitcher } from "../components/LanguageSwitcher";
8    import { CompileResult, type BuildState } from "../components/CompileResult";
```

```

9      import { IngestPanel } from "../components/IngestPanel";
10     import { runQuery, type ParsedQuery } from "../lib/query";
11     import { floorRisk } from "../lib/floor";
12     import { reelFilename } from "../lib/format";
13     import { parseDetail } from "../lib/errors";
14     import { log, newCorrelationId } from "../lib/log";
15     import { ApiError, compileReel, getConfig, highlightUrl, listRallies, minShotCount }
from "../api/client";
16     import type { EngineConfig, RallySegment } from "../api/types";
17
18     /** One compact, structured description of how a query was understood (for the trace
log). */
19     function parseTrace(q: ParsedQuery) {
20         return {
21             raw: q.raw,
22             recognized: q.recognized,
23             filters: q.filters.map((f) => `${f.field}${f.op}${f.value}`),
24             sort: q.sort ? `${q.sort.key}:${q.sort.dir}` : null,
25             limit: q.limit ?? null,
26             unavailable: q.unavailable.map((u) => `${u.kind}:${u.token}`),
27         };
28     }
29
30     // Demo data shown when no ?video=<id> is supplied. Shape matches the verified
play_segments
31     // contract; only honest fields are surfaced. A real session loads from POST /api/query.
32     const DEMO_RALLIES: RallySegment[] = [
33         { id: 1, start_time: 12, end_time: 20, duration: 8, server: null, receiver: null,
metadata: { shot_count: 9, shot_count_confidence: "High" } },
34         { id: 2, start_time: 41, end_time: 47, duration: 6, server: null, receiver: null,
metadata: { shot_count: 5 } },
35         { id: 3, start_time: 63, end_time: 84, duration: 21, server: null, receiver: null,
metadata: { shot_count: 19, shot_count_confidence: "Medium" } },
36         { id: 4, start_time: 95, end_time: 101, duration: 6, server: null, receiver: null,
metadata: {} },
37         { id: 5, start_time: 130, end_time: 142, duration: 12, server: null, receiver: null,
metadata: { shot_count: 11 } },
38         { id: 6, start_time: 158, end_time: 187, duration: 29, server: null, receiver: null,
metadata: { shot_count: 24, shot_count_confidence: "High" } },
39     ];
40
41     type LoadState =
42     | { status: "demo" }
43     | { status: "loading" }
44     | { status: "loaded"; count: number }
45     | { status: "error"; error: string };
46
47     export default function App() {
48         const { t } = useTranslation();
49         // Job-tethered (D10): a finished job's video_id arrives via ?video=<id> ? seeded from
the URL,
50         // but now also SETTABLE so the in-UI ingest panel (B-P2) can hand off a freshly-
processed video
51         // without a reload (it also rewrites ?video= so a refresh is stable).
52         const [videoId, setVideoId] = useState<string | null>(
53             () => new URLSearchParams(window.location.search).get("video"),
54         );
55
56         const [rallies, setRallies] = useState<RallySegment[]>(videoId ? [] : DEMO_RALLIES);
57         const [order, setOrder] = useState<RallySegment[]>(videoId ? [] : DEMO_RALLIES);
58         const [loadState, setLoadState] = useState<LoadState>(videoId ? { status: "loading" }
: { status: "demo" });
59         const [reelName, setReelName] = useState("highlights");
60         const [build, setBuild] = useState<BuildState>({ status: "idle" });
61

```

```

62      // Display order is separate from selection: a query can re-sort the cards while the
shared
63      // selection set (sel) stays the single source of truth for what lands in the reel.
64      const sel = useRallySelection(rallies, "all");
65
66      // Load real rallies for a job's video (POST /api/query). Default ALL-selected (D8).
67      useEffect(() => {
68          if (!videoId) return;
69          const cid = newCorrelationId();
70          log("info", "rallies.load_start", { cid, video_id: videoId });
71          // Show "loading" even when videoId was set dynamically by the ingest panel (initial
state was
72          // "demo" in that path) ? the banner must reflect the load, not stale demo copy.
73          setLoadState({ status: "loading" });
74          let alive = true;
75          listRallies(videoId, cid)
76              .then((rs) => {
77                  if (!alive) return;
78                  setRallies(rs);
79                  setOrder(rs);
80                  sel.apply(rs.map((r) => r.id));
81                  setLoadState({ status: "loaded", count: rs.length });
82                  log("info", "rallies.loaded", { cid, video_id: videoId, count: rs.length });
83              })
84              .catch((err) => {
85                  if (!alive) return;
86                  setLoadState({ status: "error", error: String(err) });
87                  log("error", "rallies.load_failed", { cid, video_id: videoId, error: String(err)
});
88              });
89          return () => {
90              alive = false;
91          };
92          // videoId is stable for the page; sel.apply is a stable callback.
93          // eslint-disable-next-line react-hooks/exhaustive-deps
94      }, [videoId]);
95
96      // Read the engine's stitching.min_shot_count so the footer can WARN before a selected
rally is
97      // silently dropped at compile (P4 / D7). Offline (no engine) is fine: no config ? no
warning.
98      const [cfg, setCfg] = useState<EngineConfig | null>(null);
99      useEffect(() => {
100          let alive = true;
101          getConfig()
102              .then((c) => alive && setCfg(c))
103              .catch((err) => log("warn", "config.unavailable", { error: String(err) }));
104          return () => {
105              alive = false;
106          };
107      }, []);
108      const warning = floorRisk(rallies, sel.selected, cfg ? minShotCount(cfg) : undefined);
109
110      // Stable chronological ordinal (by start_time) so re-sorting never rennumbers a rally.
111      const ordinalOf = useMemo(() => {
112          const m = new Map<number, number>();
113          [...rallies].sort((a, b) => a.start_time - b.start_time).forEach((r, i) =>
m.set(r.id, i + 1));
114          return (id: number) => m.get(id) ?? 0;
115      }, [rallies]);
116
117      // Build ? POST /api/compile ? preview/download the stitched reel. One cid traces the
whole call.
118      const onBuild = async () => {
119          if (build.status === "building") return;

```

```

120     const cid = newCorrelationId();
121     const filename = reelFilename(reelName);
122     const ids = [...sel.selected];
123     if (!videoId) {
124         log("info", "build.no_video", { cid, selected: ids.length });
125         setBuild({
126             status: "error",
127             error: t("build.noVideo"),
128         });
129         return;
130     }
131     setBuild({ status: "building" });
132     log("info", "build.start", {
133         cid,
134         video_id: videoId,
135         filename,
136         selected: ids.length,
137         total_sec: Math.round(sel.totalSec),
138         below_floor: warning?.atRisk.length ?? 0,
139     });
140     try {
141         const res = await compileReel(videoId, ids, filename, cid);
142         const url = highlightUrl(videoId, filename);
143         setBuild({ status: "done", url, filename });
144         log("info", "build.done", { cid, video_id: videoId, filename, filepath:
res.filepath, url });
145     } catch (err) {
146         const status = err instanceof ApiError ? err.status : undefined;
147         const detail = err instanceof ApiError && err.body ? parseDetail(err.body) :
String(err);
148         setBuild({ status: "error", error: detail });
149         log("error", "build.failed", { cid, video_id: videoId, filename, status, error:
String(err) });
150     }
151 };
152
153     // Every query application is ONE correlatable journey: a `query.parse` line records
exactly how
154     // the text was understood, then a single outcome line (apply / skip / empty) shares
the same cid.
155     // Unsupported concepts and zero-result queries are logged loudly ? never silently
dropped.
156     const onApplyQuery = (q: ParsedQuery, source: "typed" | "example") => {
157         const cid = newCorrelationId();
158         log("info", "query.parse", { cid, source, ...parseTrace(q) });
159
160         // Demand signal + honest "we ignored this": surface every shot-type/player/score
the user asked
161         // for but we can't yet honour (PER_RALLY_SELECTION.md §3 roadmap fields).
162         if (q.unavailable.length > 0) {
163             log("info", "query.unavailable_request", { cid, source, raw: q.raw, unavailable:
q.unavailable });
164         }
165
166         if (!q.recognized) {
167             log("info", "query.skip", { cid, source, raw: q.raw, reason: "no actionable
clause" });
168             return; // empty / unparseable ? leave the user's curation untouched
169         }
170
171         try {
172             const { ordered, selectedIds } = runQuery(rallies, q);
173             setOrder(ordered);
174             sel.apply(selectedIds);
175             log("info", "query.apply", {

```

```

176         cid,
177         source,
178         filters: q.filters.length,
179         sort: q.sort ? `${q.sort.key}:${q.sort.dir}` : null,
180         limit: q.limit ?? null,
181         total: rallies.length,
182         selected: selectedIds.length,
183         selected_ids: selectedIds,
184         dropped_unavailable: q.unavailable.map((u) => `${u.kind}:${u.token}`),
185     });
186     if (selectedIds.length === 0) {
187         // Loud: a recognized query that matches nothing makes the grid look empty ? say
why.
188         log("warn", "query.empty_result", { cid, source, ...parseTrace(q) });
189     }
190     } catch (err) {
191         // Defensive: the pure parser/selector shouldn't throw, but never fail silently if
it does.
192         log("error", "query.apply_failed", { cid, source, raw: q.raw, error: String(err)
});
193     }
194 };
195
196 // Manual curation edits are traced too, so a journey (query ? hand-tune) reads as one
story.
197 const onToggle = (id: number) => {
198     log("debug", "rally.toggle", { id, action: sel.isSelected(id) ? "remove" : "add" });
199     sel.toggle(id);
200 };
201 const onBulk = (op: "select_all" | "clear" | "invert") => {
202     const resultCount = op === "select_all" ? rallies.length : op === "clear" ? 0 :
rallies.length - sel.count;
203     log("info", "selection.bulk", { cid: newCorrelationId(), op, result_count:
resultCount });
204     if (op === "select_all") sel.selectAll();
205     else if (op === "clear") sel.clearAll();
206     else sel.invert();
207 };
208
209 return (
210     <main className="min-h-screen bg-paper text-ink pb-24">
211         <header className="bg-ink text-white">
212             <div className="mx-auto flex max-w-5xl items-center justify-between gap-3 px-6
py-4">
213                 <span className="text-xl font-extrabold tracking-tight">
214                     Khel<span className="text-green">?</span>Sutra <span className="font-
semibold text-lime">Studio</span>
215                 </span>
216                 <LanguageSwitcher />
217             </div>
218         </header>
219
220         <section className="mx-auto max-w-5xl px-6 py-10">
221             <span className="inline-flex rounded-full bg-green/15 px-3 py-1 text-xs font-
semibold text-green">
222                 {t("app.badge")}
223             </span>
224             <h1 className="mt-4 text-3xl font-extrabold tracking-
tight">{t("app.title")}</h1>
225             <p className="mt-2 max-w-2xl text-ink/70">
226                 <Trans i18nKey="app.intro" components={{ b: <strong />, i: <em /> }} />
227             </p>
228
229             </* Front-half ingest (B-P2): when no video is loaded, point the tool at a
bucket URI / host

```

```

230         path ? process ? load. Once a video_id exists, the existing back-half takes
over. */}
231         {!videoId && (
232             <IngestPanel
233                 onLoad={({id}) => {
234                     setVideoId(id);
235                     window.history.replaceState(null, "", `?video=${encodeURIComponent(id)}`);
236                 }}
237             />
238         )}
239
240         <ModeBanner load={loadState} videoId={videoId} />
241
242         <div className="mt-6">
243             <QueryBar onApply={onApplyQuery} />
244         </div>
245
246         <div className="mt-6 flex flex-wrap gap-2 text-sm">
247             <button type="button" onClick={() => onBulk("select_all")} className="rounded-
full border border-black/15 px-3 py-1 hover:border-green">{t("bulk.selectAll")}</button>
248             <button type="button" onClick={() => onBulk("clear")} className="rounded-full
border border-black/15 px-3 py-1 hover:border-green">{t("bulk.clear")}</button>
249             <button type="button" onClick={() => onBulk("invert")} className="rounded-full
border border-black/15 px-3 py-1 hover:border-green">{t("bulk.invert")}</button>
250         </div>
251
252         <div className="mt-5">
253             <RallyGrid rallies={order} isSelected={sel.isSelected} onToggle={onToggle}
ordinalOf={ordinalOf} />
254         </div>
255
256         <CompileResult build={build} onDismiss={() => setBuild({ status: "idle" })} />
257     </section>
258
259     <SelectionFooter
260         count={sel.count}
261         totalSec={sel.totalSec}
262         reelName={reelName}
263         onReelNameChange={setReelName}
264         onBuild={onBuild}
265         building={build.status === "building"}
266         warning={warning}
267     />
268 </main>
269 );
270 }
271
272 function ModeBanner({ load, videoId }: { load: LoadState; videoId: string | null }) {
273     if (load.status === "demo") {
274         return (
275             <p className="mt-3 text-sm text-ink/50" data-testid="mode-banner">
276                 <Trans i18nKey="mode.demo" components={{ code: <code /> }} />
277             </p>
278         );
279     }
280     if (load.status === "loading") {
281         return (
282             <p className="mt-3 text-sm text-ink/60" data-testid="mode-banner">
283                 <Trans i18nKey="mode.loading" values={{ videoId }} components={{ code: <code /> }} />
284             </p>
285         );
286     }
287     if (load.status === "error") {
288         return (

```

```

289         <p className="mt-3 rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-sm
text-red-800" data-testid="mode-banner">
290             <Trans i18nKey="mode.error" values={{ videoId, error: load.error }}
components={{ code: <code /> }} />
291         </p>
292     );
293 }
294     return (
295         <p className="mt-3 text-sm text-ink/50" data-testid="mode-banner">
296             <Trans i18nKey="mode.loaded" values={{ count: load.count }} components={{ b:
<strong className="text-ink/70" /> }} />
297         </p>
298     );
299 }
300

```

12. user (2026-06-21T14:48:52.408Z)

```

1      // Error helpers shared by the ingest flow and the build flow. Kept i18n-FREE: callers
map an
2      // IngestErrorCode to a localized string (so hooks stay testable without a translation
context),
3      // while the engine's own `detail` text passes through verbatim (it's the most specific
message).
4      import { ApiError } from "../api/client";
5
6      /** Pull FastAPI's {"detail": "..."} message out of an error body, else return the raw
body. */
7      export function parseDetail(body: string): string {
8          try {
9              const j = JSON.parse(body) as { detail?: unknown };
10             if (j && typeof j.detail === "string") return j.detail;
11         } catch {
12             /* not JSON ? fall through to the raw body */
13         }
14         return body;
15     }
16
17     /** Stable, localizable failure categories surfaced by the ingest flow.
18     * `engine` carries the engine's own message in `detail`; the rest are localized by
code. */
19     export type IngestErrorCode = "invalidUri" | "networkError" | "emptyResult" | "timeout"
| "engine";
20
21     export interface IngestError {
22         code: IngestErrorCode;
23         /** Present for `engine` ? the verbatim FastAPI detail / status; rendered as-is, not
translated. */
24         detail?: string;
25     }
26
27     /** Classify a thrown client error into a stable code. A network throw (ApiError with no
`status`)
28     * is the common "engine unreachable" case ? its own friendly code; any HTTP error
surfaces the
29     * engine's `detail` (e.g. an unsupported-scheme 400, a not-found 404). */
30     export function classifyError(err: unknown): IngestError {
31         if (err instanceof ApiError) {
32             if (err.status === undefined) return { code: "networkError" }; // fetch threw ?
engine truly unreachable
33             if (err.body) {
34                 const detail = parseDetail(err.body);
35                 if (detail) return { code: "engine", detail }; // a real engine message (e.g. a
400 unsupported-scheme)
36             }

```

```

37      // A bare 5xx with no body is almost always the engine being down / a gateway that
can't reach it
38      // (e.g. the dev proxy when :8000 is off) ? for a non-technical user a friendly "is
it running?"
39      // beats a cryptic "HTTP 500". A 4xx with no body keeps the status (it's a client-
side mistake).
40      if (err.status >= 500) return { code: "networkError" };
41      return { code: "engine", detail: `HTTP ${err.status}` };
42  }
43  return { code: "engine", detail: String(err) };
44  }
45

```

13. user (2026-06-21T14:48:52.745Z)

```

1      // The compiled-reel result (PER_RALLY_SELECTION.md P5): once Build ? POST /api/compile
succeeds,
2      // preview the reel inline (<video> over GET /api/highlights/...) and offer a download.
The engine
3      // returns a server-local filepath, NOT a URL (main.py:394), so the SPA builds the URL
itself. On a
4      // failure (e.g. the min_shot_count 400) we show the engine's reason ? loud, never
swallowed.
5
6      import { useTranslation } from "react-i18next";
7
8      export type BuildState =
9      | { status: "idle" }
10     | { status: "building" }
11     | { status: "done"; url: string; filename: string }
12     | { status: "error"; error: string };
13
14     interface Props {
15         build: BuildState;
16         onDismiss: () => void;
17     }
18
19     export function CompileResult({ build, onDismiss }: Props) {
20         const { t } = useTranslation();
21         if (build.status === "idle" || build.status === "building") return null;
22
23         return (
24             <section
25                 data-testid="compile-result"
26                 className={
27                     "mt-6 rounded-xl border p-4 " +
28                     (build.status === "error" ? "border-red-200 bg-red-50" : "border-green/30 bg-
green/5")
29             >
30
31                 <div className="flex items-start justify-between gap-3">
32                     <h2 className="font-semibold text-ink">
33                         {build.status === "done" ? t("result.ready") : t("result.failed")}
34                     </h2>
35                     <button
36                         type="button"
37                         onClick={onDismiss}
38                         aria-label={t("result.dismiss")}
39                         className="rounded-full px-2 text-ink/50 hover:text-ink"
40                     >
41                         ?
42                     </button>
43                 </div>
44
45                 {build.status === "done" ? (

```



```

46         <div className="mt-3">
47             {/* eslint-disable-next-line jsx-a11y/media-has-caption ? a stitched rally
reel has no captions */}
48             <video
49                 data-testid="reel-video"
50                 src={build.url}
51                 controls
52                 playsInline
53                 className="w-full max-w-xl rounded-lg bg-black"
54             />
55             <a
56                 href={build.url}
57                 download={build.filename}
58                 className="mt-3 inline-block rounded-full bg-green px-4 py-2 text-sm font-
semibold text-[#04140D]"
59             >
60                 {t("result.download", { filename: build.filename })}
61             </a>
62         </div>
63     ) : (
64         <p className="mt-2 text-sm text-red-800" data-testid="compile-error">
65             {build.error}
66         </p>
67     )}
68 </section>
69 );
70 }
71

```

14. assistant (2026-06-21T14:49:01.352Z)

Now let me read the remaining components and the CSS + en catalog.

15. user (2026-06-21T14:49:02.260Z)

```

1      // The fast-entry query bar (PER_RALLY_SELECTION.md P3). A deterministic, OFFLINE parser
turns
2      // plain text ("top 15 longest", "over 10s") into a selection over the SAME shared set
the
3      // checkboxes use. It is honest by construction: a live "parsed-pill" shows exactly how
the
4      // text was understood, and concepts with no data behind them (shot-type / player /
score) are
5      // greyed out as "not available yet" ? never silently faked.
6      import { useMemo, useState } from "react";
7      import type { FormEvent } from "react";
8      import { useTranslation, Trans } from "react-i18next";
9      import { parseQuery, summarize } from "../lib/query";
10     import type { ParsedQuery } from "../lib/query";
11
12     interface Props {
13         /** Apply a parsed query to the rally set (App runs runQuery + writes the shared
selection).
14         * `source` distinguishes a typed-and-submitted query from an example-chip tap (for
the trace). */
15         onApply: (q: ParsedQuery, source: "typed" | "example") => void;
16     }
17
18     // Each example is a real, parseable query ? tapping one fills the box AND applies it.
Led by rally
19     // LENGTH (the trusted axis); shot-count filtering exists but is experimental, so it's
not featured
20     // here (a test pins that every example parses to a recognized, fully-available query).
21     export const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "first 10"];
22

```

```

23     const CHIP = "rounded-full px-2.5 py-0.5 text-xs font-medium";
24
25     export function QueryBar({ onApply }: Props) {
26         const { t } = useTranslation();
27         const [value, setValue] = useState("");
28         const parsed = useMemo(() => parseQuery(value), [value]);
29         const clauses = summarize(parsed);
30         const typed = value.trim().length > 0;
31
32         const applyText = (text: string) => {
33             setValue(text);
34             onApply(parseQuery(text), "example");
35         };
36         const submit = (e: FormEvent) => {
37             e.preventDefault();
38             if (parsed.recognized) onApply(parsed, "typed");
39         };
40
41         return (
42             <div>
43                 <form onSubmit={submit} className="flex flex-wrap items-center gap-2">
44                     <input
45                         type="text"
46                         value={value}
47                         onChange={(e) => setValue(e.target.value)}
48                         placeholder={t("query.placeholder")}
49                         aria-label={t("query.ariaLabel")}
50                         className="min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green"
51                     />
52                     <button
53                         type="submit"
54                         disabled={!parsed.recognized}
55                         className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
56                     >
57                         {t("query.apply")}
58                     </button>
59                 </form>
60
61                 {/* Live interpretation ? transparent + hand-correctable (no hidden NL guessing).
*/}
62                 <div aria-live="polite" data-testid="query-pill" className="mt-2 flex flex-wrap
items-center gap-1.5">
63                     {clauses.map((c) => (
64                         <span key={c} className={CHIP + " bg-green/15 text-green"}>
65                             {c}
66                         </span>
67                     ))}
68                     {parsed.unavailable.map((u) => (
69                         <span
70                             key={u.token}
71                             title={t("query.notAvailableTitle", { token: u.token, kind: u.kind })}
72                             className={CHIP + " bg-black/5 text-ink/45"}
73                         >
74                             <span className="line-through">{u.token}</span> · {t("query.notAvailable")}
75                         </span>
76                     ))}
77                     {typed && !parsed.recognized && parsed.unavailable.length === 0 && (
78                         <span className="text-xs text-ink/50">{t("query.unreadable")}</span>
79                     )}
80                     {!typed && <span className="text-xs text-ink/50">{t("query.hint")}</span>}
81                 </div>
82
83                 <div className="mt-3 flex flex-wrap gap-2 text-sm">

```



```

37         aria-label={t(selected ? "grid.inReel" : "grid.notInReel", { n })}
38         className={
39             "w-full text-left rounded-xl border p-3 transition " +
40             (selected
41                 ? "border-green bg-green/10"
42                 : "border-black/10 bg-white hover:border-green/60")
43         }
44     >
45         <div className="flex items-center justify-between">
46             <span className="font-semibold text-ink">{t("grid.rally", { n })}</span>
47             <span
48                 aria-hidden="true"
49                 className={
50                     "inline-flex h-5 w-5 items-center justify-center rounded-full text-
xs " +
51                     (selected ? "bg-green text-[#04140D]" : "border border-black/20
text-transparent")
52                 }
53             >
54                 ?
55             </span>
56         </div>
57         <div className="mt-1 text-sm text-ink/70">
58             {mmss(r.start_time)} <span className="text-
ink/40">{t("grid.start")}</span> · <strong className="text-ink/90">{mmss(r.duration)}</strong>
<span className="text-ink/40">{t("grid.long")}</span>
59         </div>
60         {typeof shot === "number" && (
61             <div
62                 title={t("grid.shotsTitle", {
63                     conf: conf && conf !== "Unknown" ? t("grid.shotsConfidence", { conf
64                 }) : "",
65                 className="mt-2 inline-block rounded-full bg-amber-50 px-2 py-0.5
text-xs text-amber-700"
66             >
67                 {t("grid.shots", { count: shot })}
68             </div>
69         )}
70     </button>
71 </li>
72 );
73 }}}
74 </ul>
75 );
76 }
77

```

17. user (2026-06-21T14:49:03.082Z)

```

1      // Sticky compile footer (PER_RALLY_SELECTION.md P4): live selection summary, a reel-
name input,
2      // the Build button, and ? above all ? an HONEST min_shot_count warning. The engine
silently drops
3      // selected rallies below stitching.min_shot_count; we surface that BEFORE Build so a
rally never
4      // vanishes without a reason (D7). We warn, we do NOT override the floor (D11).
5      import { useTranslation, Trans } from "react-i18next";
6      import { mmss } from "../lib/format";
7      import type { FloorRisk } from "../lib/floor";
8
9      interface Props {
10         count: number;
11         totalSec: number;
12         reelName: string;

```

```

13     onReelNameChange: (v: string) => void;
14     onBuild: () => void;
15     /** A compile is in flight (Build wired in P5). */
16     building?: boolean;
17     /** Non-null when some selected rallies sit below the engine floor. */
18     warning: FloorRisk | null;
19 }
20
21 export function SelectionFooter({ count, totalSec, reelName, onReelNameChange, onBuild,
building, warning }: Props) {
22     const { t } = useTranslation();
23     const buildDisabled = count === 0 || building || warning?.allDropped === true;
24
25     return (
26         <footer className="fixed inset-x-0 bottom-0 border-t border-black/10 bg-white/95
backdrop-blur">
27             {warning && (
28                 <div
29                     role="status"
30                     data-testid="floor-warning"
31                     className={
32                         "border-b px-6 py-2 text-sm " +
33                         (warning.allDropped
34                             ? "border-red-200 bg-red-50 text-red-800"
35                             : "border-amber-200 bg-amber-50 text-amber-900")
36                     }
37                 >
38                     {warning.allDropped ? (
39                         count === 1 ? (
40                             <Trans i18nKey="footer.floorOne" values={{ min: warning.minShotCount }}
components={{ b: <strong /> }} />
41                         ) : (
42                             <Trans i18nKey="footer.floorAll" values={{ count, min:
warning.minShotCount }} components={{ b: <strong /> }} />
43                         )
44                     ) : (
45                         <>
46                             <strong>{t("footer.floorSomeLead", { count: warning.atRisk.length
})}</strong>{" "}
47                             <Trans i18nKey="footer.floorSomeRest" values={{ min: warning.minShotCount
}} components={{ code: <code /> }} />
48                             </>
49                         )}
50                     </div>
51                 )}
52
53                 <div className="mx-auto flex max-w-5xl flex-wrap items-center gap-3 px-6 py-3">
54                     <span className="text-sm text-ink/80" data-testid="selection-summary">
55                         <strong className="text-ink">{t("footer.count", { count })}</strong>
56                         {t("footer.summaryRest", { total: mmss(totalSec) })}
57                     </span>
58
59                     <label className="ml-auto flex items-center gap-2 text-sm text-ink/60">
60                         <span className="hidden sm:inline">{t("footer.reelName")}</span>
61                         <input
62                             type="text"
63                             value={reelName}
64                             onChange={(e) => onReelNameChange(e.target.value)}
65                             placeholder={t("footer.reelNamePlaceholder")}
66                             aria-label={t("footer.reelName")}
67                             className="w-40 rounded-lg border border-black/15 bg-white px-3 py-1.5 text-
ink outline-none focus:border-green"
68                         />
69                     </label>

```

```

70         <button
71             type="button"
72             onClick={onBuild}
73             disabled={buildDisabled}
74             className="rounded-full bg-green px-5 py-2 text-sm font-semibold
text-[#04140D] disabled:opacity-40"
75         >
76             {building ? t("footer.building") : t("footer.build", { count })}
77         </button>
78     </div>
79 </footer>
80 );
81 }
82

```

18. user (2026-06-21T14:49:07.664Z)

```

1      // The front-half ingest screen (appliance S1/S2, tracker B-P2). Point the tool at a
video ? a
2      // `gs://` bucket URI or a path on the engine host ? and it submits to POST
/api/process, shows
3      // live progress while polling GET /api/jobs/{id}, and hands the resulting video_id to
the existing
4      // rally-selection back-half (App lifts ?video=<id>). Honest by construction: the engine
reports
5      // coarse phase WORDS (not a %), and a success-shaped failure (done but no rallies) is
shown, never
6      // silently treated as a load.
7      import { useState } from "react";
8      import type { FormEvent } from "react";
9      import { useTranslation } from "react-i18next";
10     import { useIngestJob } from "../hooks/useIngestJob";
11
12     interface Props {
13         /** Called with the engine's video_id once a submitted job finishes successfully. */
14         onLoaded: (videoId: string) => void;
15     }
16
17     export function IngestPanel({ onLoaded }: Props) {
18         const { t } = useTranslation();
19         const [uri, setUri] = useState("");
20         const { phase, submit, cancel, reset, busy } = useIngestJob(onLoaded);
21
22         const onSubmit = (e: FormEvent) => {
23             e.preventDefault();
24             submit(uri);
25         };
26
27         // `engine` failures carry the engine's own message (a 400 scheme/path detail, a
worker error);
28         // every other code maps to a friendly localized line ? the network case especially,
since this
29         // is the first screen a fresh user hits and "is the engine running?" must read
plainly.
30         const errorMsg =
31             phase.status === "error"
32             ? phase.error.code === "engine"
33               ? (phase.error.detail ?? t("ingest.failed", { error: "" })))
34               : t(`ingest.${phase.error.code}`)
35             : null;
36
37         return (
38             <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
testid="ingest-panel">
39                 <h2 className="text-lg font-bold">{t("ingest.title")}</h2>

```

```

40     <p className="mt-1 max-w-2xl text-sm text-ink/60">{t("ingest.intro")}</p>
41
42     <form onSubmit={onSubmit} className="mt-3 flex flex-wrap items-center gap-2">
43         <input
44             type="text"
45             value={uri}
46             onChange={(e) => setUri(e.target.value)}
47             placeholder={t("ingest.uriPlaceholder")}
48             aria-label={t("ingest.uriAriaLabel")}
49             disabled={busy}
50             className="min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
51         />
52         <button
53             type="submit"
54             disabled={busy}
55             className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
56         >
57             {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}
58         </button>
59         {busy && (
60             <button
61                 type="button"
62                 onClick={cancel}
63                 className="rounded-xl border border-black/15 px-4 py-2 text-sm hover:border-
green"
64             >
65                 {t("ingest.cancel")}
66             </button>
67         )}
68     </form>
69
70     <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>
71
72     {/* Live status (aria-live so screen readers hear progress). Indeterminate: the
engine reports
73         phase words ("hashing", "segmenting"), not a percentage ? so a spinner + the
phase word. */}
74     <div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
75         {busy && (
76             <p className="flex items-center gap-2 text-ink/70">
77                 <Spinner />
78                 <span>
79                     {t("ingest.working")}
80                     {phase.status === "polling" && phase.progress
81                         ? ` · ${t("ingest.progress", { progress: phase.progress })}`
82                         : ""}
83                 </span>
84             </p>
85         )}
86         {phase.status === "error" && (
87             <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-
red-800" data-testid="ingest-error">
88                 <p>{errorMsg}</p>
89                 <button
90                     type="button"
91                     onClick={reset}
92                     className="mt-2 rounded-lg border border-red-300 px-3 py-1 text-xs
hover:bg-red-100"
93                 >
94                     {t("ingest.retry")}
95                 </button>
96             </div>
97         )}

```

```

98         </div>
99     </section>
100 );
101 }
102
103 function Spinner() {
104     return (
105         <span
106             className="inline-block h-3.5 w-3.5 animate-spin rounded-full border-2 border-
ink/20 border-t-ink/70"
107             aria-hidden="true"
108         />
109     );
110 }
111

```

19. user (2026-06-21T14:49:08.147Z)

```

1     import { useTranslation } from "react-i18next";
2     import { SUPPORTED_LOCALES, DEFAULT_LOCALE, type Locale } from "../i18n";
3
4     // Each locale's label is its own autonym, shown in its own script. Kannada renders
crisply once the
5     // bundled Noto Sans Kannada font lands (tracker B4); most devices already ship a system
Kannada font.
6     const LANG_LABEL_KEY: Record<Locale, string> = {
7         en: "lang.en",
8         kn: "lang.kn",
9         hi: "lang.hi",
10    };
11
12    /**
13     * A persistent language switcher. Selecting a locale calls i18next's changeLanguage,
which the
14     * detector caches to localStorage (LANG_STORAGE_KEY) ? so the choice is the top-
priority signal on
15     * the next visit (negotiation: persisted pref wins). Icon-free + non-color active state
via
16     * aria-pressed keeps it usable for non-tech-savvy users (FRIENDLY_AND_MULTILINGUAL §4).
17     */
18    export function LanguageSwitcher() {
19        const { t, i18n } = useTranslation();
20        // Highlight the user's CHOSEN locale (i18n.language), not the resolved-for-content
one:
21        // resolvedLanguage falls back to `en` when a catalog is missing, so picking Kannada
(content
22        // still English until the kn catalog lands, B5) must still show Kannada as selected.
Compare on
23        // the base subtag so a detected "en-IN" highlights "en".
24        const active = (i18n.language || DEFAULT_LOCALE).split("-")[0];
25
26        return (
27            <nav aria-label={t("lang.label")} className="flex items-center gap-1">
28                {SUPPORTED_LOCALES.map((loc) => {
29                    const isActive = active === loc;
30                    return (
31                        <button
32                            key={loc}
33                            type="button"
34                            lang={loc}
35                            aria-pressed={isActive}
36                            onClick={() => void i18n.changeLanguage(loc)}
37                            className=[
38                                "rounded-full px-3 py-1.5 text-sm font-semibold transition",
39                                isActive ? "bg-white text-ink" : "text-white/70 hover:text-white",

```



```

40         ].join(" ")
41     >
42     {t(LANG_LABEL_KEY[loc])}
43 </button>
44 );
45 }}
46 </nav>
47 );
48 }
49

```

20. user (2026-06-21T14:49:08.547Z)

```

1      {
2      "app": {
3          "badge": "pick your rallies · alpha",
4          "title": "Pick the rallies for your reel",
5          "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-
6      tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want."
7      },
8      "lang": {
9          "label": "Language",
10         "en": "English",
11         "kn": "?????",
12         "hi": "?????"
13     },
14     "bulk": {
15         "selectAll": "Select all",
16         "clear": "Clear",
17         "invert": "Invert"
18     },
19     "mode": {
20         "demo": "These are sample rallies ? process a video above to work on a real match.",
21         "loading": "Finding the rallies in your video?",
22         "error": "Couldn't load this video's rallies: {error}",
23         "loaded": "Found <b>{count}</b> rallies in your video."
24     },
25     "query": {
26         "placeholder": "e.g. over 10s · top 15 longest · shortest first",
27         "ariaLabel": "Filter rallies by length, count or order",
28         "apply": "Apply",
29         "notAvailable": "not available yet",
30         "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
31         "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
32         "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
33         "try": "Sample queries:",
34         "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
35         <x>experimental</x> (under development)."
36     },
37     "grid": {
38         "empty": "No rallies to show yet.",
39         "rally": "Rally {n}",
40         "inReel": "Rally {n}, in reel",
41         "notInReel": "Rally {n}, not in reel",
42         "start": "start",
43         "long": "long",
44         "shots": "~{count} shots · experimental",
45         "shotsTitle": "Shot count is experimental (under development) and may be
46         inaccurate{conf}. Filter by rally length instead.",
47         "shotsConfidence": " ? confidence: {conf}"
48     },
49     "footer": {
50         "count": "{count, plural, one {# rally} other {# rallies}}",
51         "summaryRest": "selected · {total} total",
52         "reelName": "Reel name",

```

```

50     "reelNamePlaceholder": "my-highlights",
51     "build": "Build reel ({count})",
52     "building": "Building?",
53     "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
be skipped, so the build would fail. Pick a longer rally.",
54     "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
they'd all be skipped, so the build would fail. Pick longer rallies.",
55     "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",
56     "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
57 },
58     "result": {
59         "ready": "Your reel is ready",
60         "failed": "Build failed",
61         "dismiss": "Dismiss",
62         "download": "Download {filename}"
63     },
64     "build": {
65         "noVideo": "These are sample rallies ? process a real video first to build a reel."
66     },
67     "ingest": {
68         "title": "Process a video",
69         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
70         "uriPlaceholder": "gs://your-bucket/match.mp4",
71         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
72         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
73         "submit": "Process video",
74         "submitting": "Submitting?",
75         "cancel": "Cancel",
76         "working": "Processing your video?",
77         "progress": "{progress}",
78         "retry": "Try again",
79         "failed": "Couldn't process the video: {error}",
80         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
81         "networkError": "Can't reach KhelSutra. Is it running?",
82         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
83         "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again."
84     },
85     "selection": {
86         "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
87     }
88 }
89

```

21. assistant (2026-06-21T14:49:20.544Z)

Now the CSS, i18n index, and the hygiene/key-parity tests (to understand the CI guards I must keep green).

22. user (2026-06-21T14:49:21.362Z)

```

1     @import "tailwindcss";
2
3     /* Brand tokens (mirror the marketing site palette). Tailwind v4 generates utilities
4        from these ? e.g. bg-paper, text-ink, bg-ink, text-lime, text-green. */
5     @theme {
6         --color-ink: #0c261f;
7         --color-ink2: #123a2e;
8         --color-green: #19b36b;
9         --color-lime: #c7f2b0;

```

```

10      --color-paper: #f6f8f4;
11    }
12
13    /* Bundled OFL Noto fonts (B4 / D7): Latin uses the system stack; Kannada & Devanagari
codepoints
14      resolve to the self-hosted Noto faces (unicode-range-scoped), so kn/hi render crisply
with no
15      Google Fonts runtime dependency. Order matters ? the Latin stack is matched first for
Latin. */
16    body {
17      font-family:
18        ui-sans-serif, system-ui, -apple-system, "Segoe UI", Roboto, Helvetica, Arial,
19        "Noto Sans Kannada Variable", "Noto Sans Devanagari Variable", sans-serif;
20    }
21

```

23. user (2026-06-21T14:49:21.800Z)

```

1      // i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
2      //
3      // Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4      //   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5      //   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in
the catalog,
6      //     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7      //   - one negotiation order shared with the marketing site (B3);
8      //   - always-fallback to `en` so a missing translation degrades to English, never a raw
key.
9      import i18n from "i18next";
10     import { initReactI18next } from "react-i18next";
11     import LanguageDetector from "i18next-browser-languagedetector";
12     import ICU from "i18next-icu";
13     import enCommon from "../locales/en/common.json";
14     import knCommon from "../locales/kn/common.json";
15     import hiCommon from "../locales/hi/common.json";
16
17     // Supported locales (D6): `en` + `kn` + `hi`. Anything else falls back to `en`.
18     export const SUPPORTED_LOCALES = ["en", "kn", "hi"] as const;
19     export type Locale = (typeof SUPPORTED_LOCALES)[number];
20     export const DEFAULT_LOCALE: Locale = "en";
21
22     // ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker
B3), so a
23     // visitor's language choice carries across both surfaces.
24     export const LANG_STORAGE_KEY = "khelsutra.lang";
25
26     // Catalogs are co-located here (D9). `kn` + `hi` shipped (B5/B6, AI-drafted ? native
review
27     // pending). A missing key in any locale still falls back to `en` ? the by-design
invariant.
28     const resources = {
29       en: { common: enCommon },
30       kn: { common: knCommon },
31       hi: { common: hiCommon },
32     } as const;
33
34     void i18n
35       .use(ICU)
36       .use(LanguageDetector)
37       .use(initReactI18next)
38       .init({
39         resources,
40         fallbackLng: DEFAULT_LOCALE,
41         supportedLngs: [...SUPPORTED_LOCALES],
42         nonExplicitSupportedLngs: true, // en-IN -> en

```

```

43     defaultNS: "common",
44     ns: ["common"],
45     interpolation: { escapeValue: false }, // React already escapes
46     returnNull: false,
47     // Negotiation order (I18N_PLAN §2.3): persisted pref -> ?lang= -> browser -> en.
48     detection: {
49         order: ["localStorage", "querystring", "navigator"],
50         lookupLocalStorage: LANG_STORAGE_KEY,
51         lookupQuerystring: "lang",
52         caches: ["localStorage"],
53     },
54     react: { useSuspense: false },
55 });
56
57 // Keep <html lang> in sync with the active locale (screen readers + SEO use it).
Reflects the
58 // resolved content language, so an `en` fallback for an absent locale still reads as
`en`.
59 function syncDocumentLang(lng: string) {
60     if (typeof document !== "undefined") {
61         document.documentElement.lang = (i18n.resolvedLanguage || lng ||
DEFAULT_LOCALE).split("-")[0];
62     }
63 }
64 i18n.on("languageChanged", syncDocumentLang);
65 syncDocumentLang(i18n.language ?? DEFAULT_LOCALE);
66
67 export default i18n;
68

```

24. user (2026-06-21T14:49:22.391Z)

```

1 // CI guardrails that keep i18n "by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
2 // 1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
3 // drop a stub locale and this lists every gap). Trivially green while only `en`
exists; it
4 // starts enforcing the moment a kn/hi catalog lands (B5/B6).
5 // 2. NO-BARE-STRINGS (attribute level, v1) ? user-facing component attributes
(placeholder /
6 // aria-label / title) must route through t(), never a hardcoded literal. A curated
start per
7 // the doc; an AST-level sweep of JSX text can extend it later.
8 import { describe, it, expect } from "vitest";
9 import { readdirSync, readFileSync } from "node:fs";
10 import { join } from "node:path";
11
12 const LOCALES_DIR = join(import.meta.dirname, "locales");
13 const SRC_DIR = join(import.meta.dirname, "..");
14
15 function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
16     const keys: string[] = [];
17     for (const [k, v] of Object.entries(obj)) {
18         const key = prefix ? `${prefix}.${k}` : k;
19         if (v && typeof v === "object" && !Array.isArray(v)) keys.push(...flatten(v as
Record<string, unknown>, key));
20         else keys.push(key);
21     }
22     return keys.sort();
23 }
24
25 const loadKeys = (locale: string): string[] =>
26     flatten(JSON.parse(readFileSync(join(LOCALES_DIR, locale, "common.json"), "utf8")) as
Record<string, unknown>);
27

```

```

28 describe("i18n key-parity ? every locale has EXACTLY the en keys", () => {
29     const enKeys = loadKeys("en");
30     const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
31         .filter((d) => d.isDirectory() && d.name !== "en")
32         .map((d) => d.name);
33
34     it("en is the non-empty source catalog", () => {
35         expect(enKeys.length).toBeGreaterThan(20);
36     });
37
38     for (const loc of others) {
39         it(`${loc} matches en exactly (no missing, no extra keys)`, () => {
40             const keys = loadKeys(loc);
41             const missing = enKeys.filter((k) => !keys.includes(k));
42             const extra = keys.filter((k) => !enKeys.includes(k));
43             expect({ locale: loc, missing, extra }).toEqual({ locale: loc, missing: [], extra:
44 [] });
45         });
46     });
47
48 describe("no-bare-strings ? user-facing component attributes go through t()", () => {
49     const FILES = [
50         "App.tsx",
51         "components/QueryBar.tsx",
52         "components/RallyGrid.tsx",
53         "components/SelectionFooter.tsx",
54         "components/CompileResult.tsx",
55         "components/LanguageSwitcher.tsx",
56         "components/IngestPanel.tsx",
57     ];
58     // A hardcoded placeholder / aria-label / title with letters is a bare-string
59     regression ? it
60     // must be an expression ({t(...)}), not a quoted literal.
61     const BARE_ATTR = /\b(?:placeholder|aria-label|title)\s*=\s*"[\^]*[A-Za-z]{2}[\^]*"/g;
62
63     for (const f of FILES) {
64         it(`${f}: no hardcoded placeholder/aria-label/title`, () => {
65             const src = readFileSync(join(SRC_DIR, f), "utf8");
66             expect(src.match(BARE_ATTR) ?? []).toEqual([]);
67         });
68     });
69
70 describe("Indic fonts (B4) ? self-hosted OFL Noto, no runtime CDN", () => {
71     it("main.tsx bundles the OFL Noto Kannada + Devanagari fonts (self-hosted, not Google
72 Fonts)", () => {
73         const main = readFileSync(join(SRC_DIR, "main.tsx"), "utf8");
74         expect(main).toMatch(/@fontsource-variable\/noto-sans-kannada/);
75         expect(main).toMatch(/@fontsource-variable\/noto-sans-devanagari/);
76     });
77     it("the font stack falls back to Noto for Kannada + Devanagari glyphs", () => {
78         const css = readFileSync(join(SRC_DIR, "index.css"), "utf8");
79         expect(css).toMatch(/Noto Sans Kannada Variable/);
80         expect(css).toMatch(/Noto Sans Devanagari Variable/);
81     });
82
83     // The Studio SPA must render correctly on an AIR-GAPPED appliance (GPU/CPU/RAM, no
84     internet) ?
85     // every asset (fonts, styles, scripts) is bundled local, nothing pulled from a
86     CDN/Google Fonts.
87     describe("offline / self-contained ? no external runtime assets", () => {
88         const CDN = /googleapis|gstatic|fonts\.google|cdnjs|unpkg|jsdelivr|\.cdn\.[a-z]/i;
89         const FILES = [

```

```

88     "../index.html", // web/index.html
89     "main.tsx",
90     "index.css",
91 ];
92 for (const rel of FILES) {
93     it(`${rel}: no external font/CDN reference`, () => {
94         expect(readFileSync(join(SRC_DIR, rel), "utf8")).not.toMatch(CDN);
95     });
96 }
97 it("web/index.html loads no absolute-URL <link>/<script src> (everything is
bundled/local)", () => {
98     const html = readFileSync(join(SRC_DIR, "..", "index.html"), "utf8");
99     expect(html).not.toMatch(/(?:href|src)\s*=\s*["']https?:\/\//i);
100 });
101 });
102

```

25. assistant (2026-06-21T14:51:03.952Z)

I now have complete context on the `web/` surface. Let me set up the work. First, mark the chapter and cut the A4 branch from `origin/master` (shared-checkout discipline), and load the task-tracking tools.

26. user (2026-06-21T14:51:05.395Z)

Chapter marked: "A4 ? mobile touch targets". Continue your current work.

27. user (2026-06-21T14:51:09.387Z)

```

branch 'feat/a4-mobile-touch-targets' set up to track 'origin/master'.
Switched to a new branch 'feat/a4-mobile-touch-targets'
--- HEAD ---
ccdcfd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon) (#60)
--- branch ---
feat/a4-mobile-touch-targets

```

28. assistant (2026-06-21T14:51:15.796Z)

Let me create the mission task list for visibility, then implement A4.

29. user (2026-06-21T14:51:18.597Z)

Task #1 created successfully: A4 ? SPA mobile touch targets + visible tooltips

30. user (2026-06-21T14:51:20.485Z)

Task #2 created successfully: A5 ? friendly engine-error mapping on the BUILD path

31. user (2026-06-21T14:51:23.431Z)

Task #3 created successfully: A8 ? background-processing reassurance + icon+text status chips

32. user (2026-06-21T14:51:24.268Z)

Task #4 created successfully: B3 ? site/ marketing trilingual via shared t() shim

33. user (2026-06-21T14:51:26.232Z)

Task #5 created successfully: T4 ? in-UI local file UPLOAD (North Star keystone)

34. user (2026-06-21T14:51:28.521Z)

Task #6 created successfully: T2 ? droplet appliance shell (hosted + shareable)

35. user (2026-06-21T14:51:29.462Z)

Task #7 created successfully: T11 ? retention sweep (output/ + uploads/)

36. user (2026-06-21T14:51:31.142Z)

Task #8 created successfully: MULTILINGUAL_EXPANSION Phase A (es/da/id) ? owner-paced

37. user (2026-06-21T14:52:03.268Z)

```
1      // Deterministic, dependency-free query compiler for the rally picker
(PER_RALLY_SELECTION.md
2      // D2/D5). NO LLM, NO network ? a tiny regex grammar over the ONLY honest, queryable
axes the
3      // engine returns today: rally LENGTH (duration), ORDER (start_time / duration /
shot_count),
4      // COUNT (top/first N), and SHOT COUNT (metadata.shot_count).
5      //
6      // Everything else a user might type ? shot TYPE (smash/clear/drop?), PLAYER, SCORE ?
has no
7      // detector and no column, so we FLAG it as "not available yet" and NEVER fabricate a
result.
8      // Parsing is pure and unit-tested; the QueryBar React component is a thin shell over
it.
9      import type { RallySegment } from "../api/types";
10
11     export type CompareOp = ">" | ">=" | "<" | "<=" | "=";
12     export type FilterField = "duration" | "shot_count";
13     /** One ANDed predicate over a rally field (e.g. duration > 10s). */
14     export interface Filter {
15         field: FilterField;
16         op: CompareOp;
17         value: number; // seconds for duration; a raw count for shot_count
18     }
19
20     export type SortKey = "duration" | "start_time" | "shot_count";
21     export interface Sort {
22         key: SortKey;
23         dir: "asc" | "desc";
24     }
25
26     /** A recognized-but-unsupported concept ? surfaced as a greyed "not available yet"
hint. */
27     export type UnavailableKind = "shot-type" | "player" | "score";
28     export interface Unavailable {
29         token: string;
30         kind: UnavailableKind;
31     }
32
33     export interface ParsedQuery {
34         raw: string;
35         /** ANDed together. */
36         filters: Filter[];
37         sort?: Sort;
38         /** "top N" / "first N" / "N longest". */
39         limit?: number;
40         /** Concepts we understood but cannot honour (shot-type / player / score). */
41         unavailable: Unavailable[];
42         /** True when at least one actionable clause (filter | sort | limit) was understood.
*/
43         recognized: boolean;
44     }
45
46     export interface QueryResult {
47         /** ALL rallies in display order (sorted if a sort was given, else input order). */
```

```

48     ordered: RallySegment[];
49     /** Ids matching the filters (then limited), in display order. */
50     selectedIds: number[];
51 }
52
53 // ?? grammar fragments ?????????????????????????????????????????????????????????????????
54 // `(?!\\d)` stops a greedy digit-run from backtracking and leaving stray trailing digits
55 // (so "over 10 smashes" can't degrade to "over 1" + "0 smashes").
56 const NUM = "(\\d+(?:\\.\\d+)?)(?!\\d)";
57 // Time / "shots" unit tokens. "shots?" is FIRST so it isn't eaten by the bare "s";
58 "mins?"
59 // already covers "min" (no redundant bare "min"); \\b stops "m" matching "minutes" etc.
60 const UNIT_INNER = "shots?|seconds?|secs?|minutes?|mins?|m|s";
61 const UNIT = `(?:\\s*(${UNIT_INNER})\\b)?`;
62
63 // Shot-TYPE / player / score nouns ? concepts with NO detector and NO column. A number
64 // trailing
65 // one of these must NEVER become a real filter (honesty: never reroute an unsupported
66 // concept
67 // onto the duration axis ? PER_RALLY_SELECTION.md §3/§4.3). These stems are shared with
68 the
69 // "not available yet" flagging below so the two can never drift apart.
70 const SHOT_TYPE = "smash(?:es)?|clears?|drops?|dropshots?|net
71 ?shots?|drives?|lifts?|serves?|kills?|taps?|pushes?|blocks?|slices?";
72 const PLAYER = "players?|opponents?|servers?|receivers?";
73 const SCORE = "points?|score|deuce|game point|set point|match point";
74 const UNAVAIL_WORD = `(?:${SHOT_TYPE}|${PLAYER}|${SCORE})`;
75 // Voids a comparator clause whose number is immediately followed by an unsupported
76 noun.
77 const NOT_UNAVAIL = `(?!\\s*${UNAVAIL_WORD}\\b)`;
78
79 interface OpPattern {
80     op: CompareOp;
81     re: RegExp;
82     /** Which capture group holds the number / the unit. */
83     numAt: number;
84     unitAt: number;
85 }
86
87 // Leading comparator ("over 10s"). The "no more than" / "at least" guards come BEFORE
88 their
89 // bare counterparts ("more than" / "less than") so the negated phrase is consumed
90 first.
91 function lead(alt: string, op: CompareOp): OpPattern {
92     return { op, re: new RegExp(`(?:${alt})\\s*${NUM}${UNIT}${NOT_UNAVAIL}`, "g"), numAt:
93 1, unitAt: 2 };
94 }
95
96 const LEADING: OpPattern[] = [
97     lead("no more than|at most|maximum(?: of)?|max|up to|<=", "<="),
98     lead("no less than|no fewer than|at least|minimum(?: of)?|min|>=", ">="),
99     lead("exactly|equal to|equals", "="),
100     lead("over|longer than|more than|greater than|above|bigger than|>", ">"),
101     lead("under|shorter than|less than|fewer than|below|smaller than|<", "<"),
102 ];
103
104 // Trailing comparator. The unit may sit BEFORE the operator ("10s+", "8 shots or more")
105 or the
106 // "shots" noun AFTER it ("10+ shots") ? capture both sides and use whichever is
107 present.
108 // NOT_UNAVAIL guards the same way ("5+ smashes" must not become duration ? 5).
109 interface TrailPattern {
110     op: CompareOp;
111     re: RegExp;
112 }
113
114 const POST_NOUN = `(?:\\s*(shots?)\\b)?`;

```



```

102     const TRAILING: TrailPattern[] = [
103         { op: ">=", re: new RegExp(`${NUM}${UNIT}\\s*(?:\\+|or
104         (? :more|longer|over|above|greater))`${POST_NOUN}${NOT_UNAVAIL}` , "g") },
105         { op: "<=", re: new RegExp(`${NUM}${UNIT}\\s*or
106         (? :less|fewer|shorter|under|below)` ${POST_NOUN}${NOT_UNAVAIL}` , "g") },
107     ];
108
109     function toSeconds(n: number, unit?: string): number {
110         return unit && /^m/.test(unit) ? n * 60 : n; // m/min/minute(s) ? seconds; else as-is
111     }
112
113     function makeFilter(numStr: string, unit: string | undefined, op: CompareOp): Filter {
114         const n = Number(numStr);
115         const isShots = !!unit && /^shots?$/ .test(unit);
116         return isShots
117             ? { field: "shot_count", op, value: n }
118             : { field: "duration", op, value: toSeconds(n, unit) };
119     }
120
121     const SORT_PATTERNS: Array<[RegExp, Sort]> = [
122         [/\\b(?:longest(?: first)?|longer first|by(?:duration|length)|duration desc)\\b/, {
123         key: "duration", dir: "desc" }],
124         [/\\b(?:shortest(?: first)?|shorter first|duration asc)\\b/, { key: "duration", dir:
125         "asc" }],
126         [/\\b(?:newest(?: first)?|latest|most recent|recent first)\\b/, { key: "start_time",
127         dir: "desc" }],
128         [/\\b(?:oldest(?: first)?|earliest|chronological|in order|by time)\\b/, { key:
129         "start_time", dir: "asc" }],
130         [/\\b(?:most shots(?: first)?|highest shots?|by shots?|by shot count|shot count
131         desc)\\b/, { key: "shot_count", dir: "desc" }],
132         [/\\b(?:fewest shots(?: first)?|least shots?|lowest shots?|shot count asc)\\b/, { key:
133         "shot_count", dir: "asc" }],
134     ];
135
136     // Order before kind so a token claimed by an earlier kind isn't double-counted. The
137     // stems are the
138     // same SHOT_TYPE/PLAYER/SCORE used by NOT_UNAVAIL, so "flag it" and "don't filter on
139     // it" stay in sync.
140     const UNAVAILABLE_PATTERNS: Array<[UnavailableKind, RegExp]> = [
141         ["shot-type", new RegExp(`\\b(${SHOT_TYPE})\\b` , "g")],
142         ["player", new RegExp(`\\b(${PLAYER})\\b` , "g")],
143         ["score", new RegExp(`\\b(${SCORE})\\b` , "g")],
144     ];
145
146     // A magnitude that carries a time/"shots" unit is NOT an ordinal count ("first 30
147     // seconds" ? the
148     // first 30 rallies). This blocks the limit regexes from misreading such a number as a
149     // count.
150     const NOT_UNIT = `(?!\\s*(?:${UNIT_INNER})\\b)`;
151
152     // ?? public API ?????????????????????????????????????????????????????????????????
153
154     export function parseQuery(raw: string): ParsedQuery {
155         const normalized = raw
156             .toLowerCase()
157             .replace(/>/g, ">=")
158             .replace(/</g, "<=")
159             .replace(/(\\d),(? =\\d{3}\\b)/g, "$1") // strip thousands separators ("1,000 shots" ?
160             "1000 shots")
161             .replace(/,/g, " ") // any remaining comma is a clause separator
162             .replace(/\\s+/g, " ")
163             .trim();
164
165         const filters: Filter[] = [];
166         let working = normalized;

```

```

154
155 // Extract comparator clauses, blanking each match so later passes can't re-read its
number.
156 for (const pat of LEADING) {
157     working = working.replace(pat.re, (full, ...g) => {
158         filters.push(makeFilter(g[pat.numAt - 1], g[pat.unitAt - 1], pat.op));
159         return " ".repeat(full.length);
160     });
161 }
162 for (const pat of TRAILING) {
163     working = working.replace(pat.re, (full, num, preUnit, postNoun) => {
164         filters.push(makeFilter(num, preUnit ?? postNoun, pat.op));
165         return " ".repeat(full.length);
166     });
167 }
168
169 // Explicit sort (runs before limit so "top 15 longest" keeps the longest?desc
intent).
170 let sort: Sort | undefined;
171 for (const [re, s] of SORT_PATTERNS) {
172     if (re.test(working)) {
173         sort = s;
174         break;
175     }
176 }
177
178 // Limit ("top/best N", "first N", "last N", "N longest/shortest", "longest/shortest
N"). A number
179 // carrying a unit (\b + NOT_UNIT) is NOT a count, so "first 30 seconds" / "longest 3
shots" don't
180 // become counts. `sortFromLimit` tracks a sort implied SOLELY by the limit, so if the
limit turns
181 // out invalid (e.g. "top 0") we drop that phantom sort too and the whole query reads
as a no-op.
182 let limit: number | undefined;
183 let sortFromLimit = false;
184 let m: RegExpMatchArray | null;
185 if (
186     (m = working.match(new RegExp(`\\b(\\d+)\\b${NOT_UNIT}\\s+(longest|shortest)\\b`)))
||
187     (m = working.match(new RegExp(`\\b(longest|shortest)\\s+(\\d+)\\b${NOT_UNIT}`)))
188 ) {
189     const num = /^\\d/.test(m[1]) ? m[1] : m[2];
190     const word = /^\\d/.test(m[1]) ? m[2] : m[1];
191     limit = parseInt(num, 10);
192     if (!sort) {
193         sort = { key: "duration", dir: word === "longest" ? "desc" : "asc" };
194         sortFromLimit = true;
195     }
196 } else if ((m = working.match(new RegExp(`\\b(?:top|best)\\s+(\\d+)\\b${NOT_UNIT}`))))
{
197     limit = parseInt(m[1], 10);
198     if (!sort) {
199         sort = { key: "duration", dir: "desc" }; // "top N" ? best = longest
200         sortFromLimit = true;
201     }
202 } else if ((m = working.match(new
RegExp(`\\b(?:first|earliest)\\s+(\\d+)\\b${NOT_UNIT}`)))) {
203     limit = parseInt(m[1], 10);
204     if (!sort) {
205         sort = { key: "start_time", dir: "asc" };
206         sortFromLimit = true;
207     }
208 } else if ((m = working.match(new RegExp(`\\b(?:last|latest|newest|most
recent)\\s+(\\d+)\\b${NOT_UNIT}`)))) {

```

```

209     limit = parseInt(m[1], 10);
210     if (!sort) {
211         sort = { key: "start_time", dir: "desc" };
212         sortFromLimit = true;
213     }
214 }
215
216 // A limit must be a positive integer. Reject "top 0" (which would otherwise slice to
an EMPTY
217 // selection and silently wipe the user's curation) and clamp absurd magnitudes so the
pill never
218 // renders scientific notation.
219 if (limit !== null) {
220     if (!Number.isInteger(limit) || limit < 1) {
221         limit = undefined;
222         if (sortFromLimit) sort = undefined;
223     } else if (limit > Number.MAX_SAFE_INTEGER) {
224         limit = Number.MAX_SAFE_INTEGER;
225     }
226 }
227
228 // Unavailable concepts (scanned on the normalized text; deduped, first kind wins).
229 const unavailable: Unavailable[] = [];
230 const seen = new Set<string>();
231 for (const [kind, re] of UNAVAILABLE_PATTERNS) {
232     for (const mm of normalized.matchAll(re)) {
233         const token = mm[1];
234         if (!seen.has(token)) {
235             seen.add(token);
236             unavailable.push({ token, kind });
237         }
238     }
239 }
240
241 return {
242     raw,
243     filters,
244     sort,
245     limit,
246     unavailable,
247     recognized: filters.length > 0 || sort !== null || limit !== null,
248 };
249 }
250
251 function rallyValue(r: RallySegment, key: SortKey): number | undefined {
252     if (key === "duration") return r.duration;
253     if (key === "start_time") return r.start_time;
254     return r.metadata?.shot_count;
255 }
256
257 /** Stable sort; rallies missing the sort field always sort LAST (unknown ? smallest).
*/
258 export function sortRallies(rallies: RallySegment[], sort: Sort): RallySegment[] {
259     return rallies
260         .map((r, i) => ({ r, i }))
261         .sort((a, b) => {
262             const av = rallyValue(a.r, sort.key);
263             const bv = rallyValue(b.r, sort.key);
264             if (av == null && bv == null) return a.i - b.i;
265             if (av == null) return 1;
266             if (bv == null) return -1;
267             if (av !== bv) return sort.dir === "asc" ? av - bv : bv - av;
268             return a.i - b.i; // tie ? preserve input order
269         })
270         .map((x) => x.r);

```

```

271     }
272
273     function matchesFilter(r: RallySegment, f: Filter): boolean {
274         const v = f.field === "duration" ? r.duration : r.metadata?.shot_count;
275         if (v == null) return false; // a rally without shot_count can't satisfy a shot filter
276         switch (f.op) {
277             case ">":
278                 return v > f.value;
279             case ">=":
280                 return v >= f.value;
281             case "<":
282                 return v < f.value;
283             case "<=":
284                 return v <= f.value;
285             case "=":
286                 return v === f.value;
287             default:
288                 return false;
289         }
290     }
291
292     /** Apply a parsed query to the rallies: ordered display list + the ids it selects.
Pure.
293     * An UNRECOGNIZED query (nothing understood) selects nothing and leaves order untouched
?
294     * so garbage input can never silently wipe a user's manual curation. The App also
guards on
295     * `q.recognized` before applying, so an empty box is a no-op end to end. */
296     export function runQuery(rallies: RallySegment[], q: ParsedQuery): QueryResult {
297         if (!q.recognized) return { ordered: rallies.slice(), selectedIds: [] };
298         const ordered = q.sort ? sortRallies(rallies, q.sort) : rallies.slice();
299         let matched = ordered.filter((r) => q.filters.every((f) => matchesFilter(r, f)));
300         if (q.limit != null) matched = matched.slice(0, q.limit);
301         return { ordered, selectedIds: matched.map((r) => r.id) };
302     }
303
304     // ?? human-readable labels (shared by the QueryBar pill and the tests) ?????????
305     const OP_SYMBOL: Record<CompareOp, string> = { ">": ">", ">=": ">=", "<": "<", "<=": "<=", "=": "=", ">=": ">=" };
306
307     export function filterLabel(f: Filter): string {
308         if (f.field === "duration") return `length ${OP_SYMBOL[f.op]} ${f.value}s`;
309         return `shots ${OP_SYMBOL[f.op]} ${f.value}`;
310     }
311
312     export function sortLabel(s: Sort): string {
313         if (s.key === "duration") return s.dir === "desc" ? "longest first" : "shortest
first";
314         if (s.key === "start_time") return s.dir === "desc" ? "newest first" : "oldest first";
315         return s.dir === "desc" ? "most shots first" : "fewest shots first";
316     }
317
318     /** The count label, derived from the limit's actual sort so the pill can't contradict
itself
319     * ("first 10", not "top 10", when the sort is oldest-first). */
320     export function limitLabel(limit: number, sort?: Sort): string {
321         if (sort?.key === "start_time") return sort.dir === "asc" ? `first ${limit}` : `last
${limit}`;
322         if (sort?.key === "duration" && sort.dir === "asc") return `shortest ${limit}`;
323         if (sort?.key === "shot_count") return sort.dir === "asc" ? `fewest ${limit}` : `top
${limit} by shots`;
324         return `top ${limit}`; // duration desc, or no sort
325     }
326
327     /** Human clause labels for the parsed-pill (e.g. ["length > 10s", "longest first", "top

```

```

15"])). */
328   export function summarize(q: ParsedQuery): string[] {
329     const parts: string[] = [];
330     for (const f of q.filters) parts.push(filterLabel(f));
331     if (q.sort) parts.push(sortLabel(q.sort));
332     if (q.limit !== null) parts.push(limitLabel(q.limit, q.sort));
333     return parts;
334   }
335

```

38. user (2026-06-21T14:52:03.593Z)

```

1      // @vitest-environment jsdom
2      //
3      // The SPA had NO render tests before this (verified) ? this file adds the jsdom safety
net for the
4      // i18n scaffold (tracker B1): real copy renders from the catalog, the switcher persists
the choice,
5      // missing-locale falls back to English, and ICU plurals format. It mounts the real <App
/>.
6      import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
7      import { render, screen, cleanup, fireEvent } from "@testing-library/react";
8      import i18n, { LANG_STORAGE_KEY } from "../index";
9      import App from "../App";
10
11     beforeEach(async () => {
12       // No engine in the test env: stub fetch so App's getConfig()/listRallies effects
reject quietly
13       // (App handles this gracefully ? cfg stays null) instead of hitting the network.
14       vi.stubGlobal("fetch", vi.fn(() => Promise.reject(new Error("no engine in test"))));
15       window.localStorage.clear();
16       await i18n.changeLanguage("en"); // also guarantees init completed before the first
render
17     });
18
19     afterEach(() => {
20       cleanup();
21       vi.unstubAllGlobals();
22     });
23
24     describe("i18n scaffold (B1)", () => {
25       it("renders user-facing copy from the en catalog (not raw keys)", () => {
26         render(<App />);
27         expect(screen.getByRole("heading", { level: 1 })).textContent.toBe("Pick the rallies
for your reel");
28         expect(screen.getByRole("button", { name: "Select all" })).toBeTruthy();
29       });
30
31       it("B2: the extracted component strings render (no leftover raw keys across the
page)", () => {
32         const { container } = render(<App />);
33         expect(screen.getByRole("button", { name: "Apply" })).toBeTruthy(); // QueryBar
34         expect(screen.getByRole("button", { name: /Build reel/ })).toBeTruthy(); //
SelectionFooter
35         expect(container.textContent).toContain("rally length"); // <Trans> hero intro +
query support
36         expect(container.textContent).toMatch(/\d+ rallies selected \cdot \d+:\d+ total/); //
ICU footer summary
37         expect(container.textContent).toMatch(/Rally \d+/); // RallyGrid card
38         // No untranslated catalog keys leaked into the DOM.
39         expect(container.textContent).not.toMatch(/\b(app|grid|footer|query|mode|result|buil
d)\.[a-zA-Z]+\b/);
40       });
41
42       it("offers a language switcher and persists the choice (persisted pref wins on next

```

```

visit)", () => {
43     render(<App />);
44     const knBtn = screen.getByRole("button", { name: "?????" });
45     fireEvent.click(knBtn);
46     expect(i18n.language).toBe("kn");
47     expect(window.localStorage.getItem(LANG_STORAGE_KEY)).toBe("kn");
48     expect(knBtn.getAttribute("aria-pressed")).toBe("true"); // highlights the chosen
locale
49     // Switching actually re-renders the page into Kannada (the kn catalog, B5).
50     expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("????? ?????????
????????????? ?????");
51     });
52
53     it("B5: switching to Kannada renders the kn catalog (Kannada copy, not English)",
async () => {
54         await i18n.changeLanguage("kn");
55         render(<App />);
56         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("????? ?????????
????????????? ?????");
57         expect(screen.getByRole("button", { name: "?????????" })).toBeTruthy(); // Apply ?
Kannada
58         expect(screen.getByRole("button", { name: "????????? ??????????" })).toBeTruthy(); //
Select all ? Kannada
59         expect(document.documentElement.lang).toBe("kn"); // <html lang> tracks the active
locale (a11y)
60     });
61
62     it("B6: switching to Hindi renders the hi catalog (extensibility proof ? just a
catalog)", async () => {
63         await i18n.changeLanguage("hi");
64         render(<App />);
65         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("???? ???? ?? ???
???????? ?????");
66         expect(screen.getByRole("button", { name: "???? ??????" })).toBeTruthy(); // Apply ?
Hindi
67         expect(document.documentElement.lang).toBe("hi");
68     });
69
70     it("a locale with no catalog falls back to English (never a raw key)", async () => {
71         await i18n.changeLanguage("ta"); // ta has no catalog
72         render(<App />);
73         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("Pick the rallies
for your reel");
74     });
75
76     it("formats ICU plurals from the catalog", () => {
77         expect(i18n.t("selection.count", { count: 1 })).toBe("1 rally selected");
78         expect(i18n.t("selection.count", { count: 3 })).toBe("3 rallies selected");
79     });
80 });
81
82 // The owner's bar (#41): a user whose BROWSER/OS language is Kannada/Hindi must auto-
get the
83 // respective version. These prove the negotiation NOW at the detection level (B1, en-
only); the
84 // kn/hi CONTENT assertions ride the catalogs in B5/B6. See FRIENDLY_AND_MULTILINGUAL.md
$6.5 (N1?N9).
85 describe("browser-language negotiation (B1: N1/N3?N7)", () => {
86     const detectBases = () => {
87         const d = i18n.services.languageDetector.detect();
88         return (Array.isArray(d) ? d : [d]).filter(Boolean).map((l) =>
String(l).split("-")[0]);
89     };
90
91     it("N1/N5: a Kannada browser (kn-IN) is auto-detected as kn for a first-time visitor",

```

```

() => {
92     window.localStorage.clear(); // no persisted preference yet
93     vi.stubGlobal("navigator", { language: "kn-IN", languages: ["kn-IN", "en-IN"] });
94     expect(detectBases()).toContain("kn"); // the kn-IN region subtag normalizes to base
kn
95     });
96
97     it("N2: a Hindi browser (hi-IN) is auto-detected as hi (now a supported locale)", ()
=> {
98         window.localStorage.clear();
99         vi.stubGlobal("navigator", { language: "hi-IN", languages: ["hi-IN", "en-IN"] });
100        expect(detectBases()).toContain("hi");
101    });
102
103    it("N4: a persisted preference beats the browser language (returning user keeps their
choice)", () => {
104        window.localStorage.setItem(LANG_STORAGE_KEY, "kn");
105        vi.stubGlobal("navigator", { language: "en-US", languages: ["en-US"] });
106        expect(detectBases()[0]).toBe("kn");
107    });
108
109    it("N3: persisted pref and ?lang are negotiated BEFORE the browser language", () => {
110        const order = i18n.options.detection?.order ?? [];
111        expect(order.indexOf("localStorage")).toBeGreaterThanOrEqual(0);
112        expect(order.indexOf("localStorage")).toBeLessThan(order.indexOf("navigator"));
113        expect(order.indexOf("querystring")).toBeLessThan(order.indexOf("navigator"));
114    });
115
116    it("N6: an unsupported browser language (Tamil) serves English content ? never a
locale we can't render", async () => {
117        window.localStorage.clear();
118        await i18n.changeLanguage("ta"); // ta is not in SUPPORTED_LOCALES
119        render(<App />);
120        expect(screen.getByRole("heading", { level: 1 })).textContent.toBe("Pick the rallies
for your reel");
121    });
122
123    it("N7: a key with no catalog entry falls back to English (no raw key)", async () => {
124        await i18n.changeLanguage("ta"); // ta has no catalog ? keys resolve via
fallbackLng=en
125        expect(i18n.t("app.title")).toBe("Pick the rallies for your reel");
126        expect(i18n.t("bulk.selectAll")).toBe("Select all");
127    });
128    });
129

```

39. assistant (2026-06-21T14:52:38.000Z)

I have the full picture now. The `unavailable` kinds are `shot-type`/`player`/`score`. Let me check the kn/hi catalogs so any new key I add matches their tone.

40. user (2026-06-21T14:52:39.195Z)

```

1      {
2      "app": {
3          "badge": "?????-????? ????? . ?????",
4          "title": "????? ?????????? ?????????????? ?????",
5          "intro": "<b>????? ????</b>? ?????????? ?????? ? ????. <i>????? ?????? ???
15?</i> ? ??? ? ?????????????? ?????? ??? ? ?????????????? ??????. ?????? <b>????????????</b>
?????????????????; ?????????????? ?????? ?????????????."
6      },
7      "lang": {
8          "label": "?????",
9          "en": "English",
10         "kn": "?????",

```

```
11     "hi": "?????"
12 },
13 "bulk": {
14     "selectAll": "????????? ??????????",
15     "clear": "????????????",
16     "invert": "?????????"
17 },
18 "mode": {
19     "demo": "???? ???? ? ?????? ????? ???? ?????? ?????????????? ??????????????
<code>?video=?video_id?</code> ???? ??????????",
20     "loading": "<code>{videoId}</code> ???? ?????????????? ???? ?????????????????",
21     "error": "<code>{videoId}</code> ???? ?????????????? ???? ??????????????: {error}",
22     "loaded": "? ? ?????????? <b>{count}</b> ?????????????? ???? ??????????".
23 },
24 "query": {
25     "placeholder": "???. over 10s · top 15 longest · shortest first",
26     "ariaLabel": "????, ????? ???? ????? ?????????? ?????????????? ??????? ?????",
27     "apply": "?????????",
28     "notAvailable": "????? ??????????",
29     "notAvailableTitle": "{token}? ?? {kind} ????? ???? ? ?????? ??????????",
30     "unreadable": "?????? ??????????? ? ?over 10s? ???? ?top 15 longest? ????????????",
31     "hint": "10 ?????????????? ?????? ?????????????????? over 10s ???? ???? ???? ? ???? ??????
????????????? ?????? ????",
32     "try": "????? ??????????????",
33     "support": "<b>?????? ????</b>? ?????????? ?????????? ?????????? ??????????????
????????????????? ????-????? <x>????????????</x> (?????????????????)."
34 },
35 "grid": {
36     "empty": "???????? ???? ???? ???? ??????????????",
37     "rally": "??????? {n}",
38     "inReel": "??????? {n}, ??????????????",
39     "notInReel": "??????? {n}, ??????????????????",
40     "start": "?????????",
41     "long": "?????",
42     "shots": "~{count} ?????????? · ??????????",
43     "shotsTitle": "???? ???? ???? ?????????????????? (?????????????????) ????
?????????????????{conf}. ?????? ?????? ?????? ?????????? ??????? ????",
44     "shotsConfidence": " ? ??????????: {conf}"
45 },
46 "footer": {
47     "count": "{count, plural, one {# ??????} other {# ??????????}}",
48     "summaryRest": "????????????? · ?????? {total}",
49     "reelName": "????? ??????",
50     "reelNamePlaceholder": "my-highlights",
51     "build": "???? ???? ({count})",
52     "building": "?????????????????",
53     "floorOne": "<b>????? ???? ?????????? ??????</b>{min} ?????? ?????? ??????????
? ?????? ?????? ??????????????????, ?????????? ???? ?????????????????? ?????? ?????????????? ??????",
54     "floorAll": "<b>????????????? ?????? {count} ??????????????</b> {min} ?????? ??????
????????????? ? ?????? ?????????????????? ??????????????????, ?????????? ???? ?????????????????? ??????
????????????? ??????",
55     "floorSomeLead": "{count, plural, one {# ??????} other {# ??????????}}",
56     "floorSomeRest": "{min} ?????? ?????? ?????????????????? ?????????? ??????????????????????
(????????? <code>min_shot_count</code> ????)."
57 },
58 "result": {
59     "ready": "????? ???? ??????????????",
60     "failed": "???? ??????????????",
61     "dismiss": "?????????????",
62     "download": "{filename} ?????????? ?????"
63 },
64 "build": {
65     "noVideo": "???? ?????? ?????????????????? ?????????????????? ?video=<video_id> ???? ??????????
? ???? ?????????? ?????? ??????????".
66 },
```



```
67     "ingest": {
68         "title": "????? ??????????????",
69         "intro": "????????????????? ???? ??????? ?????? ? ????? ?????? ???? ?????????????????
???? ? ??? ?????????????? ??????????????. ?????? ?????? ?????????? ?????????????.",
70         "uriPlaceholder": "gs://your-bucket/match.mp4",
71         "uriAriaLabel": "?????? ???? ? gs:// ????? URL ???? ?????? ?????????????????? ??",
72         "hint": "gs:// ????? ?????, ???? ?????? ?????????????????? ?????? ?????? ??????
??????.",
73         "submit": "?????? ??????????????????",
74         "submitting": "????????????????????",
75         "cancel": "?????????????",
76         "working": "????? ?????? ??????????????????????????",
77         "progress": "{progress}",
78         "retry": "????? ??????????",
79         "failed": "?????? ??????????????????????????: {error}",
80         "invalidUri": "????? ?????? ?????????? ??????? ? gs:// ????? ???? ?????????????????
??.",
81         "networkError": "?????? ??????????????????. ??? ??????????????????",
82         "emptyResult": "?????????? ?????????? ???? ? ????????????? ?????? ?????????? ?????????
????????? ?????? ?????????????? ?????????????.",
83         "timeout": "????????????????? ?????? ??? ??????????????????????. ???? ?????? ?????????????????
? ?????? ?????????????????? ??????? ???? , ???? ?????? ?????????????."
84     },
85     "selection": {
86         "count": "{count, plural, one {# ?????? ?????????????} other {# ??????????
?????????????}}}"
87     }
88 }
89
```

41. user (2026-06-21T14:52:39.623Z)

```
1     {
2         "app": {
3             "badge": "?????-???? ??? . ??????",
4             "title": "???? ???? ?? ??? ??????? ??????",
5             "intro": "<b>???? ? ?????</b> ?? ???? ? ??????? ???? ? ???? <i>????? ???? ????
15?</i> ? ??? ????? ???? ???? ?????? ? ????????? ???? ? ???? <b>?????</b> ???? ???? ?; ?? ?
???? ?????? ?????? ??????"
6         },
7         "lang": {
8             "label": "????",
9             "en": "English",
10            "kn": "?????",
11            "hi": "?????"
12        },
13        "bulk": {
14            "selectAll": "??? ?????",
15            "clear": "???? ?????",
16            "invert": "?????"
17        },
18        "mode": {
19            "demo": "???? ???? ? ???? ???? ???? ???? ? ???? ???? ???? ? ????
<code>?video=?video_id?</code> ?? ??????",
20            "loading": "<code>{videoId}</code> ?? ??? ??????? ???? ? ???? ?????",
21            "error": "<code>{videoId}</code> ?? ??? ??????? ???? ???? ? ?????: {error}",
22            "loaded": "? ???? ? ? <b>{count}</b> ??????? ???? ??????"
23        },
24        "query": {
25            "placeholder": "???. over 10s . top 15 longest . shortest first",
26            "ariaLabel": "????, ?????? ? ???? ? ???? ? ? ?????? ??????? ?????",
27            "apply": "???? ?????",
28            "notAvailable": "??? ?????? ?????",
29            "notAvailableTitle": "?{token}? ? ???? {kind} ?????? ?????? ? ???? ?????? ?????",
30            "unreadable": "? ???? ???? ? ? ?over 10s? ? ?top 15 longest? ?????????",

```

[illegible]

```
86         "count": "{count, plural, one {# ??? ????} other {# ?????? ?????}}"  
87     }  
88 }  
89
```

42. assistant (2026-06-21T14:53:34.060Z)

I have full context, including a useful catch: the `kn/hi`mode.*`/`build.noVideo`` values are **\*\*stale relative to A1's en copy\*\*** (they still say ``?video=<id>`` while en now says "process a video above"). Key-parity passes (keys match), so it's a translation-drift issue flagged under "native review pending" ? out of A4 scope, but I'll flag it at the end.

Now implementing A4. Mark task in-progress and make the component edits.

43. user (2026-06-21T14:53:34.228Z)

Updated task #1 status

44. assistant (2026-06-21T14:53:39.011Z)

Now the QueryBar edits (input/apply ?44px, enlarge parsed-pill + sample chips, visible unavailable-help line):

45. user (2026-06-21T14:53:40.782Z)

The file `C:\Users\avidu\Projects\khelsutra\web\src\components\QueryBar.tsx` has been updated successfully. (file state is current in your context ? no need to Read it back)

46. user (2026-06-21T14:53:47.795Z)

The file `C:\Users\avidu\Projects\khelsutra\web\src\components\QueryBar.tsx` has been updated successfully. (file state is current in your context ? no need to Read it back)

47. assistant (2026-06-21T14:53:53.255Z)

Now add the visible unavailable-help line after the pill row, and enlarge the sample chips to ?44px:

48. user (2026-06-21T14:53:59.067Z)

The file `C:\Users\avidu\Projects\khelsutra\web\src\components\QueryBar.tsx` has been updated successfully. (file state is current in your context ? no need to Read it back)

49. assistant (2026-06-21T14:54:03.066Z)

Now App.tsx bulk buttons (?44px):

50. user (2026-06-21T14:54:07.917Z)

The file `C:\Users\avidu\Projects\khelsutra\web\src\App.tsx` has been updated successfully. (file state is current in your context ? no need to Read it back)

51. assistant (2026-06-21T14:54:11.357Z)

Now SelectionFooter (reel-name input + Build button ?44px):

52. user (2026-06-21T14:54:15.604Z)

The file `C:\Users\avidu\Projects\khelsutra\web\src\components\SelectionFooter.tsx` has been updated successfully. (file state is current in your context ? no need to Read it back)

53. assistant (2026-06-21T14:54:19.560Z)

Now IngestPanel (input, submit, cancel, retry ?44px):

54. user (2026-06-21T14:54:24.471Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

55. assistant (2026-06-21T14:54:27.767Z)

Now the IngestPanel retry button:

56. user (2026-06-21T14:54:29.957Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

57. assistant (2026-06-21T14:54:34.012Z)

Now LanguageSwitcher (?44px tap targets ? important for this audience):

58. user (2026-06-21T14:54:36.344Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\LanguageSwitcher.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

59. assistant (2026-06-21T14:54:39.939Z)

Now CompileResult (dismiss ? ? 44px square; download link ? ?44px):

60. user (2026-06-21T14:54:42.201Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\CompileResult.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

61. user (2026-06-21T14:54:47.425Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\CompileResult.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

62. assistant (2026-06-21T14:54:51.477Z)

Now add the `query.notAvailableHelp` key to all three catalogs (key-parity CI). en first:

63. user (2026-06-21T14:54:53.750Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

64. user (2026-06-21T14:55:05.306Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

65. user (2026-06-21T14:55:12.878Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

66. assistant (2026-06-21T14:55:20.965Z)

Now a focused A4 regression test. Let me check the test setup first.

67. user (2026-06-21T14:55:21.448Z)

```
1      // Vitest setup (runs before each test file's imports). DOM-env only: jsdom under Node
26 does not
2      // expose a Web Storage `localStorage`, which the i18n language detector and the
persistence test
3      // both need. Node-env test files (typeof window === "undefined") skip this entirely.
4      if (typeof window !== "undefined" && typeof globalThis.localStorage === "undefined") {
5          let store: Record<string, string> = {};
6          const mem: Storage = {
7              get length() {
8                  return Object.keys(store).length;
9              },
10             clear() {
11                 store = {};
12             },
13             getItem(key: string) {
14                 return Object.prototype.hasOwnProperty.call(store, key) ? store[key] : null;
15             },
16             key(index: number) {
17                 return Object.keys(store)[index] ?? null;
18             },
19             removeItem(key: string) {
20                 delete store[key];
21             },
22             setItem(key: string, value: string) {
23                 store[key] = String(value);
24             },
25         };
26         Object.defineProperty(window, "localStorage", { value: mem, configurable: true,
writable: true });
27         Object.defineProperty(globalThis, "localStorage", { value: mem, configurable: true,
writable: true });
28     }
29
```

68. user (2026-06-21T14:55:22.024Z)

```
1      // @vitest-environment jsdom
2      //
3      // The ingest screen end to end: type a URI ? submit ? (mocked engine) ? onLoaded gets
the video_id;
4      // and the two failure surfaces a non-technical user actually hits ? the engine's own
400 detail,
5      // and a friendly "is the engine running?" when it's unreachable. Mounts the real i18n
catalog.
6      import { describe, it, expect, vi, beforeEach, afterEach } from "vitest";
7      import { render, screen, fireEvent, cleanup, act } from "@testing-library/react";
8      import i18n from "../i18n/index";
9      import { IngestPanel } from "../IngestPanel";
10     import type { JobStatus } from "../api/types";
11
12     type FetchFn = typeof fetch;
13
14     function httpOk(status: number, json: unknown) {
15         return { ok: status >= 200 && status < 300, status, json: async () => json, text:
async () => JSON.stringify(json) };
16     }
17
18     function fetchSeq(process: unknown, jobs: JobStatus[]): FetchFn {
19         let i = 0;
20         return vi.fn(async (url: string | URL, init?: RequestInit) => {
21             const u = String(url);
22             if (u === "/api/process" && (init?.method ?? "GET") === "POST") return process;
23             if (u.startsWith("/api/jobs/")) {
```

```

24         const body = jobs[Math.min(i, jobs.length - 1)];
25         i += 1;
26         return httpOk(200, body);
27     }
28     throw new Error(`unexpected fetch ${u}`);
29 }) as unknown as FetchFn;
30 }
31
32 beforeEach(async () => {
33     window.localStorage.clear();
34     await i18n.changeLanguage("en"); // guarantees init completed + a known locale for the
assertions
35 });
36
37 afterEach(() => {
38     cleanup();
39     vi.restoreAllMocks();
40     vi.unstubAllGlobals();

```

69. assistant (2026-06-21T14:55:38.552Z)

Now the A4 regression test:

70. assistant (2026-06-21T14:55:53.781Z)

```

// @vitest-environment jsdom
//
// A4 ? non-tech-savvy mobile UX. Two guarantees a phone user depends on:
// 1. TOUCH TARGETS ? 44px (WCAG 2.5.5 / platform HIG) on every primary control ? pinned via
the
//     Tailwind min-h-11 (=2.75rem=44px) / h-11 class so a future "tighten the padding" can't
//     silently shrink a tap target below the floor.
// 2. The "not available yet" REASON is VISIBLE text, not a hover-only title ? a touch device
never
//     surfaces `title=`, so the explanation must render in the DOM for a phone user to read
it.
import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
import { render, screen, cleanup, fireEvent } from "@testing-library/react";
import i18n from "../i18n/index";
import App from "../App";
import { QueryBar } from "../QueryBar";

// 44px floor: min-h-11 (buttons/inputs) or an explicit h-11 square (the ? dismiss).
const TAP_44 = /\b(?:min-h-11|h-11)\b/;

beforeEach(async () => {
    vi.stubGlobal("fetch", vi.fn(() => Promise.reject(new Error("no engine in test"))));
    window.localStorage.clear();
    await i18n.changeLanguage("en");
});

afterEach(() => {
    cleanup();
    vi.unstubAllGlobals();
});

describe("A4: touch targets ? 44px on primary controls", () => {
    it("the always-visible buttons carry a ?44px tap class", () => {
        render(<App />);
        for (const name of [
            "Select all",
            "Clear",
            "Invert",
            "Apply", // QueryBar submit
            "Process video", // IngestPanel submit

```

```

    "English", // LanguageSwitcher
    "?????",
    "???????",
  ]) {
    const btn = screen.getByRole("button", { name });
    expect(btn.className, `${name} must be ?44px`).toMatch(TAP_44);
  }
  // The Build button label includes the live selection count ("Build reel (6)").
  expect(screen.getByRole("button", { name: /Build reel/ }).className).toMatch(TAP_44);
});

it("the text inputs carry a ?44px tap class", () => {
  render(<App />);
  expect(screen.getByRole("textbox", { name: "Filter rallies by length, count or order"
}).className).toMatch(TAP_44);
  expect(screen.getByRole("textbox", { name: "Reel name" }).className).toMatch(TAP_44);
  expect(
    screen.getByRole("textbox", { name: "Video location ? a gs:// bucket URL or a path on the
engine host" }).className,
  ).toMatch(TAP_44);
});

it("the sample-query chips are tappable (?44px)", () => {
  render(<App />);
  expect(screen.getByRole("button", { name: "over 10s" }).className).toMatch(TAP_44);
  expect(screen.getByRole("button", { name: "top 15 longest" }).className).toMatch(TAP_44);
});
});

describe("A4: the 'not available yet' reason is visible, not hover-only", () => {
  const HELP = "Shot type, players and score aren't available yet ? filter by rally length
instead.";

  it("hidden until an unsupported concept is typed, then shown as plain text", () => {
    render(<QueryBar onApply={() => {}} />);
    expect(screen.queryByText(HELP)).toBeNull(); // nothing typed ? no help line
    fireEvent.change(screen.getByRole("textbox", { name: "Filter rallies by length, count or
order" }), {
      target: { value: "smashes" }, // a shot-type token ? flagged "not available yet"
    });
    expect(screen.getByText(HELP)).toBeTruthy(); // the reason is now a visible DOM node
  });
});
});

```

71. user (2026-06-21T14:55:53.816Z)

File created successfully at:
C:\Users\avidu\Projects\kshelsutra\web\src\components\A4.touch.test.tsx (file state is current in
your context ? no need to Read it back)

72. assistant (2026-06-21T14:55:58.838Z)

Now run the web test suite + typecheck + build to verify A4:

73. user (2026-06-21T14:56:05.073Z)

```

=== test ===
{"ts":"2026-06-21T14:56:04.701Z","level":"error","event":"api.network_error","cid":"9fde149b-122a-43ba-9c4d-ee095d25c008","method":"GET","url":"/api/config","error":"Error: no engine in test"}

```

```

stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B5:
switching to Kannada renders the kn catalog (Kannada copy, not English)
{"ts":"2026-06-

```

```
21T14:56:04.701Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
```

```
stdout | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B6:  
switching to Hindi renders the hi catalog (extensibility proof ? just a catalog)  
{ "ts": "2026-06-21T14:56:04.717Z", "level": "info", "event": "api.request", "cid": "2ae0b903-ef26-4b3c-a67b-b01f07d11ce5", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B6:  
switching to Hindi renders the hi catalog (extensibility proof ? just a catalog)  
{ "ts": "2026-06-21T14:56:04.743Z", "level": "error", "event": "api.network_error", "cid": "2ae0b903-ef26-4b3c-a67b-b01f07d11ce5", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) > B6:  
switching to Hindi renders the hi catalog (extensibility proof ? just a catalog)  
{ "ts": "2026-06-21T14:56:04.743Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config" }
```

```
stdout | src/i18n/i18n.test.tsx > i18n scaffold (B1) > a  
locale with no catalog falls back to English (never a raw key)  
{ "ts": "2026-06-21T14:56:04.757Z", "level": "info", "event": "api.request", "cid": "d98643cf-6242-4fc3-b0e3-b24b9e67154c", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) > a  
locale with no catalog falls back to English (never a raw key)  
{ "ts": "2026-06-21T14:56:04.761Z", "level": "error", "event": "api.network_error", "cid": "d98643cf-6242-4fc3-b0e3-b24b9e67154c", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/i18n/i18n.test.tsx > i18n scaffold (B1) > a  
locale with no catalog falls back to English (never a raw key)  
{ "ts": "2026-06-21T14:56:04.761Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config" }
```

```
stdout | src/i18n/i18n.test.tsx > browser-language negotiation (B1:  
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?  
never a locale we can't render  
{ "ts": "2026-06-21T14:56:04.778Z", "level": "info", "event": "api.request", "cid": "ab7eed16-f5a4-403b-bde5-1fc272fa064b", "method": "GET", "url": "/api/config" }
```

```
stderr | src/i18n/i18n.test.tsx > browser-language negotiation (B1:  
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?  
never a locale we can't render  
{ "ts": "2026-06-21T14:56:04.780Z", "level": "error", "event": "api.network_error", "cid": "ab7eed16-f5a4-403b-bde5-1fc272fa064b", "method": "GET", "url": "/api/config", "error": "Error: no engine in test" }
```

```
stderr | src/i18n/i18n.test.tsx > browser-language negotiation (B1:  
N1/N3?N7) > N6: an unsupported browser language (Tamil) serves English content ?  
never a locale we can't render  
{ "ts": "2026-06-21T14:56:04.781Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config" }
```

```
? src/i18n/i18n.test.tsx (13 tests)  
586ms
```

```
? i18n scaffold (B1) > renders user-facing copy from the en  
catalog (not raw keys) 309ms
```

```
Test Files 12 passed (12)  
Tests     127 passed (127)  
Start at  20:26:01
```


Duration 3.74s (transform 628ms, setup 228ms, collect 2.87s, tests 1.51s, environment 7.80s, prepare 2.99s)

74. assistant (2026-06-21T14:56:11.636Z)

All 127 pass (123 + my 4 A4 tests). Now typecheck, lint, and build:

75. user (2026-06-21T14:56:21.679Z)

```
=== tsc ===
EXIT tsc: 0
=== lint ===
=== build ===
vite v6.4.3 building for production...
transforming...
? 88 modules transformed.
rendering chunks...
computing gzip size...
dist/index.html
  0.40 kB ? gzip: 0.27 kB
dist/assets/noto-sans-devanagari-latin-ext-wght-normal-CLkupaxV.woff2
 13.85 kB
dist/assets/noto-sans-kannada-latin-ext-wght-normal-MdBBF41x.woff2
 13.99 kB
dist/assets/noto-sans-devanagari-latin-wght-normal-Bxfr4UJH.woff2
 25.38 kB
dist/assets/noto-sans-kannada-latin-wght-normal-DeLZCgFT.woff2
 27.58 kB
dist/assets/noto-sans-kannada-kannada-wght-normal-DuwB-P8d.woff2
 90.80 kB
dist/assets/noto-sans-devanagari-devanagari-wght-normal-DWI_L5Cu.woff2
121.19 kB
dist/assets/index-CUYZ8r6F.css
 20.83 kB ? gzip: 4.84 kB
dist/assets/index-BQA7GRLW.js
347.66 kB ? gzip: 109.59 kB
? built in 1.21s
```

76. assistant (2026-06-21T14:56:28.463Z)

tsc/lint/build all clean. A4 is an observable mobile-UX change, so let me verify in the browser. Loading the preview tools.

77. user (2026-06-21T14:56:41.440Z)

```
=== khelsutra/.claude ===
.claude/launch.json

=== primary .claude/launch.json? ===
{
  "version": "0.0.1",
  "configurations": [
    {
      "name": "landing",
      "runtimeExecutable": "python",
      "runtimeArgs": ["-m", "http.server", "8099", "--directory", "artifacts/landing"],
      "port": 8099
    },
    {
      "name": "khelsutra-web",
      "runtimeExecutable": "npm",
      "runtimeArgs": ["--prefix", "C:/Users/avidu/Projects/khelsutra/web", "run", "dev", "--", "
--port", "5174", "--strictPort"],
      "port": 5174
    }
  ]
}
```

```

    },
    {
      "name": "khelsutra-site",
      "runtimeExecutable": "python",
      "runtimeArgs": ["-m", "http.server", "8123", "--directory",
"C:/Users/avidu/Projects/khelsutra/site/public"],
      "port": 8123
    },
    {
      "name": "khelsutra-node",
      "runtimeExecutable": "node",
      "runtimeArgs": ["C:/Users/avidu/Projects/khelsutra/site/server.js"],
      "port": 8080
    }
  ]
}

{
  "version": "0.0.1",
  "configurations": [
    {
      "name": "khelsutra-web",
      "runtimeExecutable": "npm",
      "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
      "port": 5173
    },
    {
      "name": "khelsutra-site",
      "runtimeExecutable": "node",
      "runtimeArgs": ["site/server.js"],
      "port": 8080
    }
  ]
}

```

78. assistant (2026-06-21T14:56:47.455Z)

The primary `.claude/launch.json` has a `khelsutra-web` config (absolute path, port 5174). Let me start it and verify A4 at mobile width.

79. user (2026-06-21T14:56:50.538Z)

```

{
  "serverId": "d4a4a2a4-7c2e-46e2-889e-f619477293b4",
  "port": 5174,
  "name": "khelsutra-web",
  "reused": false
}

```

Server started successfully on port 5174.

80. user (2026-06-21T14:56:54.879Z)

Viewport set to 375x812 (mobile).

81. assistant (2026-06-21T14:57:09.571Z)

Mobile layout looks clean ? taller language switcher, Process video, inputs, Build reel all comfortably tappable. Now let me verify the visible "not available" help line by typing an unsupported concept, then screenshot the query area.

82. user (2026-06-21T14:57:10.267Z)

Successfully filled: input[aria-label="Filter rallies by length, count or order"]

83. user (2026-06-21T14:57:15.643Z)

```
[1] RootWebArea: "KhelSutra Studio"
[5] main
[6] sectionheader
[7] none
[9] StaticText: "Khel"
[10] InlineTextBox: "Khel"
[11] StaticText: "?"
[12] InlineTextBox: "?"
[13] StaticText: "Sutra "
[14] InlineTextBox: "Sutra "
[15] StaticText: "Studio"
[16] InlineTextBox: "Studio"
[17] navigation: "Language"
[18] button: "English"
[19] StaticText: "English"
[20] InlineTextBox: "English"
[21] button: "?????"
[22] StaticText: "?????"
[23] InlineTextBox: "?????"
[24] button: "??????"
[25] StaticText: "??????"
[26] InlineTextBox: "??????"
[27] generic
[29] StaticText: "pick your rallies . alpha"
[30] InlineTextBox: "pick your rallies . alpha"
[31] heading: "Pick the rallies for your reel"
[32] StaticText: "Pick the rallies for your reel"
[33] InlineTextBox: "Pick the rallies for your "
[34] InlineTextBox: "reel"
[35] paragraph
[36] StaticText: "Filter by "
[37] InlineTextBox: "Filter by "
[38] strong
[39] StaticText: "rally length"
[40] InlineTextBox: "rally length"
[41] StaticText: " ? e.g. "
[42] InlineTextBox: " ? e.g. "
[43] emphasis
[44] StaticText: "?top 15 longest?"
[45] InlineTextBox: "?top 15 longest?"
[46] StaticText: " ? then fine-tune by tapping cards. Everything starts "
[47] InlineTextBox: "? then fine-tune by tapping cards. Everything "
[48] InlineTextBox: "starts "
[49] strong
[50] StaticText: "selected"
[51] InlineTextBox: "selected"
[52] StaticText: "; just drop the ones you don't want."
[53] InlineTextBox: "; just drop the ones you don't "
[54] InlineTextBox: "want."
[55] generic
[56] heading: "Process a video"
[57] StaticText: "Process a video"
[58] InlineTextBox: "Process a video"
[59] paragraph
[60] StaticText: "Point KhelSutra at a video and it finds the rallies for you ? this
can take a few minutes."
[61] InlineTextBox: "Point KhelSutra at a video and it finds the "
[62] InlineTextBox: "rallies for you ? this can take a few minutes."
[63] generic
[64] textbox: "Video location ? a gs:// bucket URL or a path on the engine host"
[67] button: "Process video"
[68] StaticText: "Process video"
[69] InlineTextBox: "Process video"
```

[70] paragraph

[71] StaticText: "Paste a cloud-storage link (gs://?), or a path to a video on the machine running KhelSutra."

[72] InlineTextBox: "Paste a cloud-storage link (gs://?), or a path to a "

[73] InlineTextBox: "video on the machine running KhelSutra."

[75] paragraph

[76] StaticText: "These are sample rallies ? process a video above to work on a real match."

[77] InlineTextBox: "These are sample rallies ? process a video above to "

[78] InlineTextBox: "work on a real match."

[80] none

[81] generic

[82] textbox: "Filter rallies by length, count or order" (value: "over 10s smashes by player")

[85] StaticText: "over 10s smashes by player"

[86] InlineTextBox: "over 10s smashes by player"

[87] button: "Apply"

[88] StaticText: "Apply"

[89] InlineTextBox: "Apply"

[92] StaticText: "length > 10s"

[93] InlineTextBox: "length > 10s"

[95] StaticText: "smashes"

[96] InlineTextBox: "smashes"

[97] StaticText: " . "

[98] InlineTextBox: " . "

[99] StaticText: "not available yet"

[100] InlineTextBox: "not available yet"

[102] StaticText: "player"

[103] InlineTextBox: "player"

[104] StaticText: " . "

[105] InlineTextBox: " . "

[106] StaticText: "not available yet"

[107] InlineTextBox: "not available yet"

[108] paragraph

[109] StaticText: "Shot type, players and score aren't available yet ? filter by rally length instead."

[110] InlineTextBox: "Shot type, players and score aren't available yet ? filter by "

[111] InlineTextBox: "rally length instead."

[112] none

[114] StaticText: "Sample queries:"

[115] InlineTextBox: "Sample queries:"

[116] button: "over 10s"

[117] StaticText: "over 10s"

[118] InlineTextBox: "over 10s"

[119] button: "top 15 longest"

[120] StaticText: "top 15 longest"

[121] InlineTextBox: "top 15 longest"

[122] button: "shortest first"

[123] StaticText: "shortest first"

[124] InlineTextBox: "shortest first"

[125] button: "first 10"

[126] StaticText: "first 10"

[127] InlineTextBox: "first 10"

[128] paragraph

[129] StaticText: "Filtering by "

[130] InlineTextBox: "Filtering by "

[131] strong

[132] StaticText: "rally length"

[133] InlineTextBox: "rally length"

[134] StaticText: " is fully supported. Shot-count is "

[135] InlineTextBox: " is fully supported. Shot-count is "

[136] StaticText: "experimental"

[137] InlineTextBox: "experimental"

[138] StaticText: " (under development)."

```
[139] InlineTextBox: " (under development)."  
[140] none  
[141] button: "Select all"  
[142] StaticText: "Select all"  
[143] InlineTextBox: "Select all"  
[144] button: "Clear"  
[145] StaticText: "Clear"  
[146] InlineTextBox: "Clear"  
[147] button: "Invert"  
[148] StaticText: "Invert"  
[149] InlineTextBox: "Invert"  
[151] list  
[152] listitem  
[153] button: "Rally 1, in reel"  
[156] StaticText: "Rally 1"  
[157] InlineTextBox: "Rally 1"  
[159] StaticText: "0:12"  
[160] InlineTextBox: "0:12"  
[161] StaticText: " "  
[162] InlineTextBox: " "  
[163] StaticText: "start"  
[164] InlineTextBox: "start"  
[165] StaticText: " . "  
[166] InlineTextBox: " . "  
[167] strong  
[168] StaticText: "0:08"  
[169] InlineTextBox: "0:08"  
[170] StaticText: " "  
[171] InlineTextBox: " "  
[172] StaticText: "long"  
[173] InlineTextBox: "long"  
[175] StaticText: "~9 shots . experimental"  
[176] InlineTextBox: "~9 shots . "  
[177] InlineTextBox: "experimental"  
[178] listitem  
[179] button: "Rally 2, in reel"  
[182] StaticText: "Rally 2"  
[183] InlineTextBox: "Rally 2"  
[185] StaticText: "0:41"  
[186] InlineTextBox: "0:41"  
[187] StaticText: " "  
[188] InlineTextBox: " "  
[189] StaticText: "start"  
[190] InlineTextBox: "start"  
[191] StaticText: " . "  
[192] InlineTextBox: " . "  
[193] strong  
[194] StaticText: "0:06"  
[195] InlineTextBox: "0:06"  
[196] StaticText: " "  
[197] InlineTextBox: " "  
[198] StaticText: "long"  
[199] InlineTextBox: "long"  
[201] StaticText: "~5 shots . experimental"  
[202] InlineTextBox: "~5 shots . "  
[203] InlineTextBox: "experimental"  
[204] listitem  
[205] button: "Rally 3, in reel"  
[208] StaticText: "Rally 3"  
[209] InlineTextBox: "Rally 3"  
[211] StaticText: "1:03"  
[212] InlineTextBox: "1:03"  
[213] StaticText: " "  
[214] InlineTextBox: " "  
[215] StaticText: "start"
```

[216] InlineTextBox: "start"
[217] StaticText: " . "
[218] InlineTextBox: " . "
[219] strong
[220] StaticText: "0:21"
[221] InlineTextBox: "0:21"
[222] StaticText: " "
[223] InlineTextBox: " "
[224] StaticText: "long"
[225] InlineTextBox: "long"
[227] StaticText: "~19 shots . experimental"
[228] InlineTextBox: "~19 shots . "
[229] InlineTextBox: "experimental"
[230] listitem
[231] button: "Rally 4, in reel"
[234] StaticText: "Rally 4"
[235] InlineTextBox: "Rally 4"
[237] StaticText: "1:35"
[238] InlineTextBox: "1:35"
[239] StaticText: " "
[240] InlineTextBox: " "
[241] StaticText: "start"
[242] InlineTextBox: "start"
[243] StaticText: " . "
[244] InlineTextBox: " . "
[245] strong
[246] StaticText: "0:06"
[247] InlineTextBox: "0:06"
[248] StaticText: " "
[249] InlineTextBox: " "
[250] StaticText: "long"
[251] InlineTextBox: "long"
[252] listitem
[253] button: "Rally 5, in reel"
[256] StaticText: "Rally 5"
[257] InlineTextBox: "Rally 5"
[259] StaticText: "2:10"
[260] InlineTextBox: "2:10"
[261] StaticText: " "
[262] InlineTextBox: " "
[263] StaticText: "start"
[264] InlineTextBox: "start"
[265] StaticText: " . "
[266] InlineTextBox: " . "
[267] strong
[268] StaticText: "0:12"
[269] InlineTextBox: "0:12"
[270] StaticText: " "
[271] InlineTextBox: " "
[272] StaticText: "long"
[273] InlineTextBox: "long"
[275] StaticText: "~11 shots . experimental"
[276] InlineTextBox: "~11 shots . "
[277] InlineTextBox: "experimental"
[278] listitem
[279] button: "Rally 6, in reel"
[282] StaticText: "Rally 6"
[283] InlineTextBox: "Rally 6"
[285] StaticText: "2:38"
[286] InlineTextBox: "2:38"
[287] StaticText: " "
[288] InlineTextBox: " "
[289] StaticText: "start"
[290] InlineTextBox: "start"
[291] StaticText: " . "

```

    [292] InlineTextBox: " . "
    [293] strong
    [294] StaticText: "0:29"
    [295] InlineTextBox: "0:29"
    [296] StaticText: " "
    [297] InlineTextBox: " "
    [298] StaticText: "long"
    [299] InlineTextBox: "long"
    [301] StaticText: "~24 shots . experimental"
    [302] InlineTextBox: "~24 shots . "
    [303] InlineTextBox: "experimental"
[304] sectionfooter
[305] none
    [307] strong
    [308] StaticText: "6 rallies"
    [309] InlineTextBox: "6 rallies"
    [310] StaticText: " "
    [311] InlineTextBox: " "
    [312] StaticText: "selected . 1:22 total"
    [313] InlineTextBox: "selected . 1:22 total"
    [314] LabelText
    [317] textbox: "Reel name" (value: "highlights")
    [320] StaticText: "highlights"
    [321] InlineTextBox: "highlights"
    [322] button: "Build reel (6)"
    [323] StaticText: "Build reel (6)"
    [324] InlineTextBox: "Build reel (6)"

```

84. assistant (2026-06-21T14:57:25.203Z)

The visible help line renders ([108?111]: `*"Shot type, players and score aren't available yet ? filter by rally length instead.*"`) right after the "not available yet" pills. Let me confirm no console errors, then I'm done verifying.

85. user (2026-06-21T14:57:26.157Z)

```

[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.505Z","level":"error","event":"api.http_error","cid":"2b69255a-938f-4471-9224-8ffbe2ee652a","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.509Z","level":"error","event":"api.http_error","cid":"2c4a37fb-6d1d-41f6-bc6c-e39e3c9640d1","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.509Z","level":"error","event":"api.http_error","cid":"2c4a37fb-6d1d-41f6-bc6c-e39e3c9640d1","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.509Z","level":"error","event":"api.http_error","cid":"2c4a37fb-6d1d-41f6-bc6c-e39e3c9640d1","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T14:56:50.509Z","level":"error","event":"api.http_error","cid":"2c4a37fb-6d1d-41f6-bc6c-e39e3c9640d1","method":"GET","url":"/api/config","status":500,"body":""}

```

```
e39e3c9640d1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.509Z", "level": "error", "event": "api.http_error", "cid": "2c4a37fb-6d1d-41f6-bc6c-
e39e3c9640d1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.509Z", "level": "error", "event": "api.http_error", "cid": "2c4a37fb-6d1d-41f6-bc6c-
e39e3c9640d1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.679Z", "level": "error", "event": "api.http_error", "cid": "a6d12cab-9428-430f-92be-
b1b7f106e7ac", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.679Z", "level": "error", "event": "api.http_error", "cid": "a6d12cab-9428-430f-92be-
b1b7f106e7ac", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.679Z", "level": "error", "event": "api.http_error", "cid": "a6d12cab-9428-430f-92be-
b1b7f106e7ac", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.679Z", "level": "error", "event": "api.http_error", "cid": "a6d12cab-9428-430f-92be-
b1b7f106e7ac", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.679Z", "level": "error", "event": "api.http_error", "cid": "a6d12cab-9428-430f-92be-
b1b7f106e7ac", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
[error] {"ts": "2026-06-
21T14:56:50.683Z", "level": "error", "event": "api.http_error", "cid": "040e10ec-56c9-48a9-b22f-
e04ab393b6a1", "method": "GET", "url": "/api/config", "status": 500, "body": ""}
```

86. assistant (2026-06-21T14:57:42.981Z)

A4 verified: ?44px targets visible in the screenshot, the help line renders for unsupported concepts, 127 tests + tsc + lint + build all green. The only console errors are expected `^/api/config` 500s (no engine on :8000 ? handled gracefully, unrelated to A4).

Per ultracode, let me run an adversarial review workflow over the A4 diff before merging ? to catch any missed interactive control or regression. First, capture the diff.

87. user (2026-06-21T14:57:44.276Z)

```
web/src/App.tsx | 6 +++--
web/src/components/CompileResult.tsx | 4 ++--
web/src/components/IngestPanel.tsx | 8 ++++----
web/src/components/LanguageSwitcher.tsx | 2 +-
web/src/components/QueryBar.tsx | 17 ++++++++-----
web/src/components/SelectionFooter.tsx | 4 ++--
web/src/i18n/locales/en/common.json | 1 +
web/src/i18n/locales/hi/common.json | 1 +
web/src/i18n/locales/kn/common.json | 1 +
9 files changed, 27 insertions(+), 17 deletions(-)
```


=====FULL DIFF=====

diff --git a/web/src/App.tsx b/web/src/App.tsx

index b43debd..85361d6 100644

--- a/web/src/App.tsx

+++ b/web/src/App.tsx

@@ -244,9 +244,9 @@ export default function App() {
 </div>

<div className="mt-6 flex flex-wrap gap-2 text-sm">
 - <button type="button" onClick={() => onBulk("select_all")} className="rounded-full
border border-black/15 px-3 py-1 hover:border-green">{t("bulk.selectAll")}</button>
 - <button type="button" onClick={() => onBulk("clear")} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">{t("bulk.clear")}</button>
 - <button type="button" onClick={() => onBulk("invert")} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">{t("bulk.invert")}</button>
 + <button type="button" onClick={() => onBulk("select_all")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.selectAll")}</button>
 + <button type="button" onClick={() => onBulk("clear")} className="inline-flex min-h-11
items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.clear")}</button>
 + <button type="button" onClick={() => onBulk("invert")} className="inline-flex
min-h-11 items-center rounded-full border border-black/15 px-4 hover:border-
green">{t("bulk.invert")}</button>
 </div>

<div className="mt-5">

diff --git a/web/src/components/CompileResult.tsx b/web/src/components/CompileResult.tsx

index 441c7d7..619d22b 100644

--- a/web/src/components/CompileResult.tsx

+++ b/web/src/components/CompileResult.tsx

@@ -36,7 +36,7 @@ export function CompileResult({ build, onDismiss }: Props) {

type="button"
 onClick={onDismiss}
 aria-label={t("result.dismiss")}
 - className="rounded-full px-2 text-ink/50 hover:text-ink"
 + className="flex h-11 w-11 shrink-0 items-center justify-center rounded-full text-
ink/50 hover:text-ink"

>

?

</button>

@@ -55,7 +55,7 @@ export function CompileResult({ build, onDismiss }: Props) {

<a
 href={build.url}
 download={build.filename}
 - className="mt-3 inline-block rounded-full bg-green px-4 py-2 text-sm font-semibold
text-[#04140D]"
 + className="mt-3 inline-flex min-h-11 items-center rounded-full bg-green px-4 py-2
text-sm font-semibold text-[#04140D]"
 >
 {t("result.download", { filename: build.filename })}

diff --git a/web/src/components/IngestPanel.tsx b/web/src/components/IngestPanel.tsx

index 8c6ffec..322ffb8 100644

--- a/web/src/components/IngestPanel.tsx

+++ b/web/src/components/IngestPanel.tsx

@@ -47,12 +47,12 @@ export function IngestPanel({ onLoaded }: Props) {

placeholder={t("ingest.uriPlaceholder")}
 aria-label={t("ingest.uriAriaLabel")}
 disabled={busy}
 - className="min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white px-4 py-2
text-sm text-ink outline-none focus:border-green disabled:opacity-50"
 + className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
 />

```

        <button
          type="submit"
          disabled={busy}
-         className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+         className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
        >
          {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}
        </button>
@@ -60,7 +60,7 @@ export function IngestPanel({ onLoad }: Props) {
    <button
      type="button"
      onClick={cancel}
-      className="rounded-xl border border-black/15 px-4 py-2 text-sm hover:border-green"
+      className="min-h-11 rounded-xl border border-black/15 px-4 py-2 text-sm
hover:border-green"
    >
      {t("ingest.cancel")}
    </button>
@@ -89,7 +89,7 @@ export function IngestPanel({ onLoad }: Props) {
    <button
      type="button"
      onClick={reset}
-      className="mt-2 rounded-lg border border-red-300 px-3 py-1 text-xs hover:bg-
red-100"
+      className="mt-2 inline-flex min-h-11 items-center rounded-lg border border-
red-300 px-3 text-sm hover:bg-red-100"
    >
      {t("ingest.retry")}
    </button>
diff --git a/web/src/components/LanguageSwitcher.tsx b/web/src/components/LanguageSwitcher.tsx
index 075a7c9..e1aead0 100644
--- a/web/src/components/LanguageSwitcher.tsx
+++ b/web/src/components/LanguageSwitcher.tsx
@@ -35,7 +35,7 @@ export function LanguageSwitcher() {
  aria-pressed={isActive}
  onClick={() => void i18n.changeLanguage(loc)}
  className={[
-    "rounded-full px-3 py-1.5 text-sm font-semibold transition",
+    "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold
transition",
    isActive ? "bg-white text-ink" : "text-white/70 hover:text-white",
  ].join(" ")}
  >
diff --git a/web/src/components/QueryBar.tsx b/web/src/components/QueryBar.tsx
index 3ebdad9..81697c2 100644
--- a/web/src/components/QueryBar.tsx
+++ b/web/src/components/QueryBar.tsx
@@ -20,7 +20,8 @@ interface Props {
  // here (a test pins that every example parses to a recognized, fully-available query).
  export const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "first 10"];

-const CHIP = "rounded-full px-2.5 py-0.5 text-xs font-medium";
+// Parsed-pill chips: legible on a phone (text-sm, not text-xs) ? A4.
+const CHIP = "rounded-full px-3 py-1 text-sm font-medium";

  export function QueryBar({ onApply }: Props) {
    const { t } = useTranslation();
@@ -47,12 +48,12 @@ export function QueryBar({ onApply }: Props) {
    onChange={e => setValue(e.target.value)}
    placeholder={t("query.placeholder")}
    aria-label={t("query.ariaLabel")}
-    className="min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white px-4 py-2
text-sm text-ink outline-none focus:border-green"

```

```

+         className="min-h-11 min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green"
+     />
+     <button
+         type="submit"
+         disabled={!parsed.recognized}
-         className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+         className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
+     >
+         {t("query.apply")}
+     </button>
@@ -80,14 +81,20 @@ export function QueryBar({ onApply }: Props) {
    {!typed && <span className="text-xs text-ink/50">{t("query.hint")}</span>}
  </div>

-   <div className="mt-3 flex flex-wrap gap-2 text-sm">
+   /* Surface the "not available yet" reason as VISIBLE text (the per-chip title is hover-
only,
+     so it never appears on a phone) ? A4. */
+   {parsed.unavailable.length > 0 && (
+     <p className="mt-1.5 text-xs text-ink/50">{t("query.notAvailableHelp")}</p>
+   )}
+
+   <div className="mt-3 flex flex-wrap items-center gap-2 text-sm">
+     <span className="text-ink/40">{t("query.try")}</span>
+     {EXAMPLES.map((ex) => (
+       <button
+         key={ex}
+         type="button"
+         onClick={() => applyText(ex)}
-         className="rounded-full border border-black/15 px-3 py-1 text-xs hover:border-
green"
+         className="inline-flex min-h-11 items-center rounded-full border border-black/15
px-4 text-sm hover:border-green"
+       >
+         {ex}
+       </button>
diff --git a/web/src/components/SelectionFooter.tsx b/web/src/components/SelectionFooter.tsx
index 9724c53..4590ab8 100644
--- a/web/src/components/SelectionFooter.tsx
+++ b/web/src/components/SelectionFooter.tsx
@@ -63,7 +63,7 @@ export function SelectionFooter({ count, totalSec, reelName, onReelNameChange,
0
    onChange={(e) => onReelNameChange(e.target.value)}
    placeholder={t("footer.reelNamePlaceholder")}
    aria-label={t("footer.reelName")}
-    className="w-40 rounded-lg border border-black/15 bg-white px-3 py-1.5 text-ink
outline-none focus:border-green"
+    className="min-h-11 w-40 rounded-lg border border-black/15 bg-white px-3 py-1.5
text-ink outline-none focus:border-green"
+  />
+  </label>

@@ -71,7 +71,7 @@ export function SelectionFooter({ count, totalSec, reelName, onReelNameChange,
0
    type="button"
    onClick={onBuild}
    disabled={buildDisabled}
-    className="rounded-full bg-green px-5 py-2 text-sm font-semibold text-[#04140D]
disabled:opacity-40"
+    className="min-h-11 rounded-full bg-green px-5 py-2 text-sm font-semibold
text-[#04140D] disabled:opacity-40"
+  >

```


wf_cd064e9b-e5c.js", resumeFromRunId: "wf_cd064e9b-e5c"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

90. assistant (2026-06-21T14:58:36.405Z)

The 3-lens review runs in the background. While it works, let me read the A5-relevant files (the build path already uses `parseDetail`; A5 will reuse `classifyError`). Reading the client, the ingest hook, and the errors test to prep.

91. user (2026-06-21T14:58:37.361Z)

```
1      // Typed client for the engine FastAPI. SAME-ORIGIN relative `/api/*` (the appliance
serves
2      // UI + engine behind one origin; in dev Vite proxies `/api` ? :8000). Every call
carries a
3      // correlation id (header + logs) so a journey is traceable end to end.
4      import { log, newCorrelationId } from "../lib/log";
5      import type { RallySegment, QueryResponse, CompileResponse, EngineConfig,
ProcessResponse, JobStatus } from "./types";
6
7      const BASE = "/api";
8
9      export class ApiError extends Error {
10         readonly cid?: string;
11         readonly status?: number;
12         readonly body?: string;
13         constructor(message: string, opts: { cid?: string; status?: number; body?: string;
cause?: unknown } = {}) {
14             super(message);
15             this.name = "ApiError";
16             this.cid = opts.cid;
17             this.status = opts.status;
18             this.body = opts.body;
19             if (opts.cause !== undefined) (this as { cause?: unknown }).cause = opts.cause;
20         }
21     }
22
23     interface RequestOpts {
24         method?: string;
25         body?: string;
26         headers?: Record<string, string>;
27         /** Correlation id to thread through this call; auto-generated if absent. */
28         cid?: string;
29     }
30
31     async function request<T>(path: string, opts: RequestOpts = {}): Promise<T> {
32         const cid = opts.cid ?? newCorrelationId();
33         const url = `${BASE}${path}`;
34         const method = opts.method ?? "GET";
35         log("info", "api.request", { cid, method, url });
36
37         let res: Response;
38         try {
39             res = await fetch(url, {
40                 method,
41                 body: opts.body,
42                 headers: { "content-type": "application/json", "x-correlation-id": cid,
...(opts.headers ?? {} ) },
43             });
44         } catch (err) {
45             // Loud failure, never silent (LOCAL_APPLIANCE_ARCHITECTURE.md §5).
46             log("error", "api.network_error", { cid, method, url, error: String(err) });
47             throw new ApiError(`Network error calling ${method} ${url}`, { cid, cause: err });
```

```

48     }
49
50     if (!res.ok) {
51         const body = await res.text().catch(() => "");
52         log("error", "api.http_error", { cid, method, url, status: res.status, body:
body.slice(0, 500) });
53         throw new ApiError(`${method} ${url} failed: ${res.status}`, { cid, status:
res.status, body });
54     }
55
56     const data = (await res.json()) as T;
57     log("info", "api.response", { cid, method, url, status: res.status });
58     return data;
59 }
60
61 /** Submit a video (a `gs://`/`gcs://`/`s3://` bucket URI, or a path on the engine host)
for
62 * processing. POST /api/process {video_path} ? 202 {job_id, ...} [main.py:260]. Fast-
fails 400
63 * (unsupported scheme / out-of-allowed-root) or 404 (missing LOCAL file) ? surfaced as
ApiError. */
64 export async function processVideo(videoPath: string, cid?: string):
Promise<ProcessResponse> {
65     return request<ProcessResponse>("/process", {
66         method: "POST",
67         body: JSON.stringify({ video_path: videoPath }),
68         cid,
69     });
70 }
71
72 /** Poll a submitted job. GET /api/jobs/{job_id} [main.py:303]. 404 ? unknown job_id. */
73 export async function getJob(jobId: string, cid?: string): Promise<JobStatus> {
74     return request<JobStatus>(`/jobs/${encodeURIComponent(jobId)}`, { method: "GET", cid
});
75 }
76
77 /** List a video's detected rallies. POST /api/query {video_id} ? {play_segments}
[main.py:331]. */
78 export async function listRallies(videoId: string, cid?: string):
Promise<RallySegment[]> {
79     const data = await request<QueryResponse>("/query", {
80         method: "POST",
81         body: JSON.stringify({ video_id: videoId }),
82         cid,
83     });
84     return data.play_segments ?? [];
85 }
86
87 /** Stitch selected rallies into one reel. POST /api/compile {video_id, segment_ids,
output_filename} [main.py:342]. */
88 export async function compileReel(
89     videoId: string,
90     segmentIds: number[],
91     outputFilename: string,
92     cid?: string,
93 ): Promise<CompileResponse> {
94     return request<CompileResponse>("/compile", {
95         method: "POST",
96         body: JSON.stringify({ video_id: videoId, segment_ids: segmentIds, output_filename:
outputFilename }),
97         cid,
98     });
99 }
100
101 /** The stream/download URL for a compiled reel. GET

```

```

/api/highlights/{video_id}/{filename} [main.py:307]. */
102     export function highlightUrl(videoId: string, filename: string): string {
103         return
104     }
105
106     /** Read engine config (for the stitching floor). GET /api/config [main.py:121]. */
107     export async function getConfig(cid?: string): Promise<EngineConfig> {
108         return request<EngineConfig>("/config", { method: "GET", cid });
109     }
110
111     /** The shot-count floor /api/compile silently enforces ? the UI must warn, not hide
[main.py:362]. */
112     export function minShotCount(cfg: EngineConfig): number | undefined {
113         return cfg.stitching?.min_shot_count;
114     }
115

```

92. user (2026-06-21T14:58:37.858Z)

```

1         // Drives the front-half ingest: submit a video to POST /api/process, then poll GET
/api/jobs/{id}
2         // until it finishes, and hand the resulting video_id to the existing rally-loading
back-half.
3         //
4         // Kept i18n-FREE (returns stable IngestErrorCodes, not prose) so it unit-tests without
a
5         // translation context ? IngestPanel maps codes to localized strings. The poll loop is a
RECURSIVE
6         // setTimeout (never setInterval): each tick waits for the prior getJob to resolve, so a
slow engine
7         // can't pile up overlapping requests. It backs off, gives up after a ceiling, and is
fully
8         // cancellable on unmount / user-cancel / a superseding submit.
9         import { useCallback, useEffect, useRef, useState } from "react";
10        import { getJob, processVideo } from "../api/client";
11        import { classifyError, type IngestError } from "../lib/errors";
12        import { log, newCorrelationId } from "../lib/log";
13        import type { JobStatus } from "../api/types";
14
15        const POLL_MIN_MS = 1000;
16        const POLL_MAX_MS = 5000;
17        const POLL_BACKOFF = 1.5;
18        const POLL_CEILING_MS = 10 * 60 * 1000; // a wedged 'running' job won't poll forever
19
20        export type IngestPhase =
21            | { status: "idle" }
22            | { status: "submitting" }
23            | { status: "polling"; progress: string | null }
24            | { status: "done"; videoId: string }
25            | { status: "error"; error: IngestError };
26
27        interface Run {
28            cancelled: boolean;
29            timer?: ReturnType<typeof setTimeout>;
30        }
31
32        export function useIngestJob(onLoaded?: (videoId: string) => void) {
33            const [phase, setPhase] = useState<IngestPhase>({ status: "idle" });
34            const runRef = useRef<Run | null>(null);
35            // Keep the latest onLoaded without making submit depend on it (a parent re-render
won't restart polls).
36            const onLoadedRef = useRef(onLoaded);
37            onLoadedRef.current = onLoaded;
38

```

```

39     const stop = useCallback(() => {
40         const run = runRef.current;
41         if (run) {
42             run.cancelled = true;
43             if (run.timer) clearTimeout(run.timer);
44         }
45         runRef.current = null;
46     }, []);
47
48     // Cancel any in-flight poll loop when the component unmounts (App.tsx:80-82 alive-
flag idiom).
49     useEffect(() => stop, [stop]);
50
51     const submit = useCallback(
52         (rawUri: string) => {
53             const uri = rawUri.trim();
54             if (!uri) {
55                 setPhase({ status: "error", error: { code: "invalidUri" } });
56                 return;
57             }
58
59             stop(); // supersede any prior run
60             const run: Run = { cancelled: false };
61             runRef.current = run;
62
63             const cid = newCorrelationId();
64             const startedAt = Date.now();
65             setPhase({ status: "submitting" });
66             log("info", "ingest.submit_start", { cid, uri });
67
68             const fail = (error: IngestError, event: string) => {
69                 if (run.cancelled) return;
70                 setPhase({ status: "error", error });
71                 const level = error.code === "timeout" || error.code === "emptyResult" ? "warn"
: "error";
72                 log(level, event, { cid, uri, code: error.code, detail: error.detail });
73             };
74
75             const poll = (jobId: string, delay: number) => {
76                 run.timer = setTimeout(() => {
77                     void (async () => {
78                         if (run.cancelled) return;
79                         let job: JobStatus;
80                         try {
81                             job = await getJob(jobId, cid);
82                         } catch (err) {
83                             fail(classifyError(err), "ingest.poll_error");
84                             return;
85                         }
86                         if (run.cancelled) return;
87
88                         if (job.status === "done") {
89                             const videoId = job.video_id ?? job.result?.video_id ?? null;
90                             // Two status layers: a `done` job with a `failed` pipeline verdict (or no
video_id) is
91                             // a success-shaped FAILURE ? never load it, never hang.
92                             if (job.result?.status === "failed" || !videoId) {
93                                 fail({ code: "emptyResult" }, "ingest.empty_result");
94                                 return;
95                             }
96                             setPhase({ status: "done", videoId });
97                             log("info", "ingest.done", { cid, uri, video_id: videoId });
98                             onLoadedRef.current?.(videoId);
99                             return;
100                         }

```



```

101         if (job.status === "failed") {
102             fail({ code: "engine", detail: job.error ?? "job failed" },
"ingest.job_failed");
103             return;
104         }
105         // queued | running ? reflect coarse progress (free-text phase) and keep
polling.
106         setPhase({ status: "polling", progress: job.progress ?? null });
107         if (Date.now() - startedAt > POLL_CEILING_MS) {
108             fail({ code: "timeout" }, "ingest.poll_timeout");
109             return;
110         }
111         poll(jobId, Math.min(delay * POLL_BACKOFF, POLL_MAX_MS));
112     }());
113 }, delay);
114 };
115
116 void (async () => {
117     let jobId: string;
118     try {
119         const resp = await processVideo(uri, cid);
120         jobId = resp.job_id;
121     } catch (err) {
122         fail(classifyError(err), "ingest.submit_error");
123         return;
124     }
125     if (run.cancelled) return;
126     log("info", "ingest.queued", { cid, uri, job_id: jobId });
127     setPhase({ status: "polling", progress: null });
128     poll(jobId, POLL_MIN_MS);
129 }());
130 },
131 [stop],
132 );
133
134 const cancel = useCallback(() => {
135     stop();
136     setPhase({ status: "idle" });
137     log("info", "ingest.cancel", {});
138 }, [stop]);
139
140 const reset = useCallback(() => {
141     stop();
142     setPhase({ status: "idle" });
143 }, [stop]);
144
145 const busy = phase.status === "submitting" || phase.status === "polling";
146 return { phase, submit, cancel, reset, busy };
147 }
148

```

93. user (2026-06-21T14:58:38.292Z)

```

1     import { describe, it, expect } from "vitest";
2     import { parseDetail, classifyError } from "../errors";
3     import { ApiError } from "../api/client";
4
5     describe("parseDetail", () => {
6         it("extracts FastAPI's {detail}", () => {
7             expect(parseDetail(JSON.stringify({ detail: "unsupported storage URI scheme"
}))).toBe(
8                 "unsupported storage URI scheme",
9             );
10         });
11         it("returns the raw body when it isn't JSON or has no string detail", () => {

```

```

12     expect(parseDetail("plain text")).toBe("plain text");
13     expect(parseDetail(JSON.stringify({ other: 1 }))).toBe(JSON.stringify({ other: 1
14     })));
15     expect(parseDetail(JSON.stringify({ detail: { nested: true }
16     }))).toBe(JSON.stringify({ detail: { nested: true } }));
17     });
18     });
19     describe("classifyError", () => {
20       it("a network throw (ApiError with no status) ? networkError", () => {
21         expect(classifyError(new ApiError("net", { cid: "c" }))).toEqual({ code:
22         "networkError" });
23       });
24       it("an HTTP error with a body ? engine + the FastAPI detail", () => {
25         const err = new ApiError("x", { status: 400, body: JSON.stringify({ detail:
26         "unsupported storage URI scheme" }) });
27         expect(classifyError(err)).toEqual({ code: "engine", detail: "unsupported storage
28         URI scheme" });
29       });
30       it("a bare 5xx with no body ? networkError (friendly 'is the engine running?', not
31       'HTTP 500')", () => {
32         expect(classifyError(new ApiError("x", { status: 500 }))).toEqual({ code:
33         "networkError" });
34         expect(classifyError(new ApiError("x", { status: 502 }))).toEqual({ code:
35         "networkError" });
36       });
37       it("a 5xx WITH a detail still surfaces the engine's message", () => {
38         const err = new ApiError("x", { status: 500, body: JSON.stringify({ detail: "failed
39         to persist job record" }) });
40         expect(classifyError(err)).toEqual({ code: "engine", detail: "failed to persist job
41         record" });
42       });
43       it("a 4xx with no body keeps the status (a client-side mistake, not unreachable)", ()
44       => {
45         expect(classifyError(new ApiError("x", { status: 404 }))).toEqual({ code: "engine",
46         detail: "HTTP 404" });
47       });
48       it("a non-ApiError ? engine + the stringified error", () => {
49         expect(classifyError(new Error("boom"))).toEqual({ code: "engine", detail: "Error:
50         boom" });
51       });
52     });
53   });

```

94. assistant (2026-06-21T14:59:30.301Z)

A5 is now well-scoped (build catch reuses `classifyError`; shared `errors.\*` namespace via a small `errorText(t, e)` helper; unify IngestPanel onto it). Let me read the rest of the IngestPanel test (so the A5 migration keeps it green) while the A4 review runs.

95. user (2026-06-21T14:59:30.928Z)

```

40     vi.unstubAllGlobals();
41     vi.useRealTimers();
42   });
43   const typeUri = (value: string) =>
44     fireEvent.change(screen.getByLabelText(/video location/i), { target: { value } });
45   const clickProcess = () => fireEvent.click(screen.getByRole("button", { name: /process
46   video/i }));
47   describe("IngestPanel", () => {
48     it("submits a URI, polls, and hands the video_id to onLoaded", async () => {
49       vi.useFakeTimers();
50       vi.stubGlobal(

```

```

52         "fetch",
53         fetchSeq(httpOk(202, { job_id: "j", status: "queued", poll: "/api/jobs/j" })), [
54             { job_id: "j", status: "running", progress: "segmenting" },
55             { job_id: "j", status: "done", video_id: "vidZ", result: { status: "success",
video_id: "vidZ" } },
56         ]),
57     );
58     const onLoaded = vi.fn();
59     render(<IngestPanel onLoaded={onLoaded} />);
60     typeUri("gs://bucket/match.mp4");
61     clickProcess();
62
63     await act(async () => {
64         await vi.advanceTimersByTimeAsync(0); // flush submit ? start polling
65     });
66     await act(async () => {
67         await vi.advanceTimersByTimeAsync(1000); // running tick
68     });
69     await act(async () => {
70         await vi.advanceTimersByTimeAsync(1500); // done tick
71     });
72     expect(onLoaded).toHaveBeenCalled("vidZ");
73 });
74
75 it("shows the engine's own 400 detail (e.g. an unsupported scheme)", async () => {
76     vi.stubGlobal("fetch", fetchSeq(httpOk(400, { detail: "unsupported storage URI
scheme: ftp://" })), []));
77     render(<IngestPanel onLoaded={vi.fn()} />);
78     typeUri("ftp://nope");
79     clickProcess();
80     expect(await screen.findByText(/unsupported storage URI scheme/i)).toBeTruthy();
81 });
82
83 it("shows a friendly, localized message when the engine is unreachable", async () => {
84     vi.stubGlobal("fetch", vi.fn(async () => {
85         throw new Error("offline");
86     }) as unknown as FetchFn);
87     render(<IngestPanel onLoaded={vi.fn()} />);
88     typeUri("gs://bucket/match.mp4");
89     clickProcess();
90     expect(await screen.findByText(/can't reach khelsutra/i)).toBeTruthy();
91 });
92
93 it("rejects an empty URI with a hint and never calls the engine", () => {
94     const f = vi.fn();
95     vi.stubGlobal("fetch", f);
96     render(<IngestPanel onLoaded={vi.fn()} />);
97     clickProcess();
98     expect(screen.getByTestId("ingest-error")).toBeTruthy();
99     expect(f).not.toHaveBeenCalled();
100 });
101 });
102

```

96. assistant (2026-06-21T14:59:49.544Z)

A5 migration is safe (tests assert rendered text, which I'll preserve). Now let me prep T4 (the keystone) by reading the engine's chunked-upload endpoints ? understanding the contract the SPA must call. This is read-only (I won't disturb the engine checkout, which a concurrent session owns).

97. user (2026-06-21T14:59:50.066Z)

```

1     """"Chunked upload (B2, PR-2) ? extracted from backend.main into its own router.
2

```

```

3     Browser uploads arrive in sequential parts ? security.max_part_mb (free-tier edge
4     proxies cap request bodies at ~100 MB ? HOSTING_PLAN $2), are assembled server-side
5     under security.upload_dir, then submitted to /api/process by the returned path.
6     Upload state is in-process by design (this is the single-box alpha): a server restart
7     aborts partial uploads and the client re-inits. Per-user partitioning of upload_dir
8     arrives with PR-3 identity scoping.
9
10    The startup config lives on ``backend.main.global_config`` (set ONLY in ``main()``).
11    ``_upload_cfg`` resolves it through the ``backend.main`` module object so it always
12    reads the live value the server set at startup (and so tests that monkeypatch
13    ``backend.main.global_config`` flow through unchanged).
14    """
15    import os
16    import threading
17    import uuid
18    from typing import Any, Dict, Optional
19
20    from fastapi import APIRouter, HTTPException, Request
21    from pydantic import BaseModel
22
23    from backend.utils.hashing import compute_video_id # canonical file-identity hashing
24    from backend.utils.paths import safe_output_filename
25
26    router = APIRouter()
27
28    _uploads: Dict[str, Dict[str, Any]] = {}
29    _uploads_lock = threading.Lock()
30
31
32    class UploadInitRequest(BaseModel):
33        filename: str
34        total_size_bytes: Optional[int] = None
35
36
37    class UploadCompleteRequest(BaseModel):
38        total_parts: int
39
40
41    def _upload_cfg():
42        # Resolved lazily (import inside the function) to read the LIVE startup config that
43        # main() sets on the module global, and to avoid a circular import at module load
44        # (main.py imports this router; this module must not import main at import time).
45        import backend.main as _main
46        sec = getattr(_main.global_config, "security", None)
47        upload_dir = getattr(sec, "upload_dir", None) or "output/uploads"
48        max_bytes = int(getattr(sec, "max_upload_mb", 4096) or 4096) * 1024 * 1024
49        part_bytes = int(getattr(sec, "max_part_mb", 95) or 95) * 1024 * 1024
50        exts = [e.lower().lstrip(".") for e in (getattr(sec, "allowed_upload_extensions",
51        None) or ["mp4", "mov"])]
52        return upload_dir, max_bytes, part_bytes, exts
53
54    def _abort_upload(upload_id: str) -> None:
55        with _uploads_lock:
56            st = _uploads.pop(upload_id, None)
57            if st:
58                try:
59                    os.remove(st["tmp_path"])
60                except OSError:
61                    pass
62
63
64    @router.post("/api/upload/init")
65    def upload_init(req: UploadInitRequest):
66        """Start a chunked upload. Returns upload_id; PUT sequential parts next."""

```

```

67     upload_dir, max_bytes, part_bytes, exts = _upload_cfg()
68     try:
69         name = safe_output_filename(req.filename)
70     except ValueError as e:
71         raise HTTPException(status_code=400, detail=str(e)) from e
72     ext = os.path.splitext(name)[1].lower().lstrip(".")
73     if ext not in exts:
74         raise HTTPException(status_code=400,
75                             detail=f"Extension '{ext}' not allowed. Allowed:
{sorted(exts)}")
76     if req.total_size_bytes is not None and req.total_size_bytes > max_bytes:
77         raise HTTPException(status_code=413,
78                             detail=f"File exceeds the {max_bytes // (1024 * 1024)} MB
upload limit.")
79     os.makedirs(upload_dir, exist_ok=True)
80     upload_id = uuid.uuid4().hex
81     tmp_path = os.path.join(upload_dir, f".partial-{upload_id}")
82     open(tmp_path, "wb").close()
83     with _uploads_lock:
84         _uploads[upload_id] = {"filename": name, "tmp_path": tmp_path, "parts": 0,
"bytes": 0}
85     return {"upload_id": upload_id, "max_part_mb": part_bytes // (1024 * 1024),
86           "next_part": f"/api/upload/{upload_id}/part/0"}
87
88
89 @router.put("/api/upload/{upload_id}/part/{index}")
90 async def upload_part(upload_id: str, index: int, request: Request):
91     """Append one part (raw bytes body). Parts are strictly sequential (0,1,2,...)."""
92     _, max_bytes, part_bytes, _ = _upload_cfg()
93     with _uploads_lock:
94         st = _uploads.get(upload_id)
95         if st is None:
96             raise HTTPException(status_code=404, detail=f"Unknown upload_id '{upload_id}'")
97         if index != st["parts"]:
98             raise HTTPException(status_code=409,
99                                 detail=f"Out-of-order part: expected {st['parts']}, got
{index} (parts are sequential)")
100
101         received = 0
102         overflow = None
103         with open(st["tmp_path"], "ab") as fh:
104             async for chunk in request.stream():
105                 received += len(chunk)
106                 if received > part_bytes:
107                     overflow = f"Part exceeds the {part_bytes // (1024 * 1024)} MB per-part
limit."
108                     break
109                 if st["bytes"] + received > max_bytes:
110                     overflow = f"Upload exceeds the {max_bytes // (1024 * 1024)} MB total
limit."
111                     break
112                 fh.write(chunk)
113         if overflow:
114             _abort_upload(upload_id)
115             raise HTTPException(status_code=413, detail=overflow + " Upload aborted ? re-
init to retry.")
116
117         with _uploads_lock:
118             st["parts"] += 1
119             st["bytes"] += received
120         return {"upload_id": upload_id, "received_parts": st["parts"], "received_bytes":
st["bytes"]}
121
122
123 @router.post("/api/upload/{upload_id}/complete")

```

```

124     def upload_complete(upload_id: str, req: UploadCompleteRequest):
125         """Finalize: verify part count, move into place, return {path, video_id} for
/api/process."""
126         upload_dir, _, _, _ = _upload_cfg()
127         with _uploads_lock:
128             st = _uploads.get(upload_id)
129             if st is None:
130                 raise HTTPException(status_code=404, detail=f"Unknown upload_id '{upload_id}'")
131             if st["parts"] == 0 or st["parts"] != req.total_parts:
132                 raise HTTPException(status_code=409,
133                                     detail=f"Expected {req.total_parts} part(s), received
{st['parts']}.")
134             final_path = os.path.join(upload_dir, st["filename"])
135             if os.path.exists(final_path): # never overwrite an earlier upload with the same
name
136                 stem, ext = os.path.splitext(st["filename"])
137                 final_path = os.path.join(upload_dir, f"{stem}-{upload_id[:8]}{ext}")
138             os.replace(st["tmp_path"], final_path)
139             with _uploads_lock:
140                 _uploads.pop(upload_id, None)
141             video_id = compute_video_id(final_path)
142             return {"path": os.path.abspath(final_path), "video_id": video_id,
143                     "size_bytes": os.path.getsize(final_path),
144                     "next": "POST /api/process with this path"}
145
146
147     @router.delete("/api/upload/{upload_id}")
148     def upload_abort(upload_id: str):
149         """Abort an in-flight upload and delete its partial file."""
150         with _uploads_lock:
151             known = upload_id in _uploads
152             if not known:
153                 raise HTTPException(status_code=404, detail=f"Unknown upload_id '{upload_id}'")
154             _abort_upload(upload_id)
155             return {"status": "aborted", "upload_id": upload_id}
156

```

98. assistant (2026-06-21T15:00:17.475Z)

T4 upload contract is now clear (init ? PUT sequential parts ? complete returns a server `path` ? feed to `/api/process`). Solid for later.

Let me read the `site/` negotiation + test harness for B3 prep while the A4 review finishes.

99. user (2026-06-21T15:00:18.396Z)

```

1     // Always-on VM host for the KhelSutra site ? dependency-free (Node 22+ only).
2     // Serves public/ and POST /api/request-access into SQLite (node:sqlite), using the
3     // SAME handler logic as the Cloudflare Worker (src/index.js). This is the portability
4     // fallback "if Cloudflare acts out" ? see docs/PORTABILITY.md.
5     //
6     //   PORT=8080 DB_PATH=/var/lib/khelsutra/access.db node server.js
7     //
8     import { createServer } from "node:http";
9     import { readFile } from "node:fs/promises";
10    import { join, extname, normalize } from "node:path";
11    import { DatabaseSync } from "node:sqlite";
12    import { handleRequest } from "../src/index.js";
13    import { sqliteStore } from "../src/store.js";
14    import { noopNotify } from "../src/notify.js";
15
16    const PORT = Number(process.env.PORT) || 8080;
17    const ROOT = import.meta.dirname;
18    const PUBLIC = join(ROOT, "public");
19    const DB_PATH = process.env.DB_PATH || join(ROOT, "access.db");

```

```

20
21     const db = new DatabaseSync(DB_PATH);
22     db.exec(await readFile(join(ROOT, "schema.sql"), "utf8")); // CREATE TABLE IF NOT EXISTS
? idempotent
23     const store = sqliteStore(db);
24     const notify = noopNotify(); // VM host: no email yet (add SMTP later ? see
docs/PORTABILITY.md)
25
26     const TYPES = {
27         ".html": "text/html; charset=utf-8", ".png": "image/png", ".svg": "image/svg+xml",
28         ".css": "text/css", ".js": "text/javascript", ".ico": "image/x-icon", ".txt":
"text/plain",
29         ".mp4": "video/mp4", ".webm": "video/webm", ".gif": "image/gif", ".jpg": "image/jpeg",
".jpeg": "image/jpeg",
30     };
31
32     async function toRequest(req) {
33         const url = `http://${req.headers.host || "localhost"}${req.url}`;
34         let body;
35         if (req.method !== "GET" && req.method !== "HEAD") {
36             const chunks = [];
37             for await (const c of req) chunks.push(c);
38             body = Buffer.concat(chunks);
39         }
40         return new Request(url, { method: req.method, headers: req.headers, body });
41     }
42
43     async function send(res, response) {
44         res.statusCode = response.status;
45         for (const [k, v] of response.headers) res.setHeader(k, v);
46         res.end(Buffer.from(await response.arrayBuffer()));
47     }
48
49     async function serveStatic(pathname, res) {
50         const rel = pathname === "/" ? "index.html"
51             : pathname === "/capture" ? "capture.html"
52             : pathname === "/own-model" ? "own-model.html"
53             : pathname === "/flyer" ? "flyer.html"
54             : pathname === "/flyer-kn" ? "flyer-kn.html"
55             : pathname === "/flyer-hi" ? "flyer-hi.html"
56             : pathname.replace(/^\/+/, "");
57         const file = normalize(join(PUBLIC, rel));
58         if (!file.startsWith(PUBLIC)) { res.statusCode = 403; return res.end("forbidden"); }
59         try {
60             const data = await readFile(file);
61             res.setHeader("content-type", TYPES[extname(file)] || "application/octet-stream");
62             res.end(data);
63         } catch {
64             res.statusCode = 404;
65             res.end("not found");
66         }
67     }
68
69     createServer(async (req, res) => {
70         try {
71             const pathname = decodeURIComponent(new URL(`http://x${req.url}`).pathname);
72             if (pathname === "/api/request-access") {
73                 if (req.method !== "POST") { res.statusCode = 405; return
res.end('{"ok":false,"error":"method not allowed"}'); }
74                 return await send(res, await handleRequest(await toRequest(req), store, notify));
75             }
76             return await serveStatic(pathname, res);
77         } catch (err) {
78             res.statusCode = 500;
79             res.end('{"ok":false,"error":"server error"}');

```

```

80         console.error(err);
81     }
82     }).listen(PORT, () => console.log(`khelsutra site listening on :${PORT} (sqlite:
${DB_PATH})`));
83

```

100. user (2026-06-21T15:00:18.587Z)

```

1      // Static-site integrity ? the landing page + capture checklist + OG image ARE the
public
2      // product. server.test.js proves the VM host *serves* "/", "/capture", "/og.png"; this
3      // guards the CONTENT contract so a broken edit (deleted asset, broken form wiring, dead
4      // capture link, missing/!absolute OG image) fails CI instead of shipping to the live
site.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync, statSync } from "node:fs";
8      import { join } from "node:path";
9
10     const PUBLIC = join(import.meta.dirname, "..", "public");
11     const read = (f) => readFileSync(join(PUBLIC, f), "utf8");
12     const size = (f) => statSync(join(PUBLIC, f)).size;
13
14     test("core public assets exist and are non-empty", () => {
15         for (const f of ["index.html", "capture.html", "og.png"]) {
16             assert.ok(size(f) > 0, `public/${f} is missing or empty`);
17         }
18     });
19
20     test("landing page wires the Request-Access form to the API", () => {
21         const html = read("index.html");
22         assert.match(html, /id="af"/, "the #af form is gone");
23         assert.match(html, /\api\/request-access/, "form no longer posts to /api/request-
access");
24         assert.match(html, /name="company"[^>]*tabindex="-1"/, "honeypot field removed (bots
will get through)");
25         for (const field of ["segment", "has_gpu", "storage"]) {
26             assert.match(html, new RegExp(`name="${field}"`), `form lost the '${field}' field (a
demand signal)`);
27         }
28     });
29
30     test("submitting the form shows an obvious in-flight state (no silent freeze)", () => {
31         const html = read("index.html");
32         assert.match(html, /Sending?/, "submit should swap to a 'Sending?' state while the
request is in flight");
33         assert.match(html, /aria-busy/, "submit should set aria-busy for assistive tech during
the request");
34         assert.match(html, /class="spin"/, "the in-flight spinner is gone");
35         assert.match(html, /\spin\{/, "the spinner style is gone");
36         // the button must be RE-ENABLED on failure so the user isn't stuck on a frozen
'Sending?'
37         assert.match(html, /btn\.disabled\s*=\s*false/, "submit button isn't restored on the
failure path");
38     });
39
40     test("OG + canonical meta point at the live https origin", () => {
41         const html = read("index.html");
42         assert.match(html,
/property="og:image"\s+content="https:\/\/khelsutra.guru\/og.png"/, "og:image must be the
absolute live URL");
43         assert.match(html, /property="og:url"\s+content="https:\/\/khelsutra.guru"/, "og:url
drift");
44     });
45

```



```

46     test("the sample reel is GATED behind sign-up + starts at a RANDOM point (not shown
openly)", () => {
47         const html = read("index.html");
48         assert.match(html, /ajTCZ7pJW_o/, "the sample-reel video id is gone");
49         assert.match(html, /youtube-nocookie\.com/, "reel should use the privacy nocookie
host");
50         assert.match(html, /id="reel-reveal"/, "the on-signup reveal host is gone");
51         assert.match(html, /see it in action/i, "the 'see it in action' sign-up teaser is
gone");
52         assert.match(html, /reel-count/, "the auto-close countdown is gone");
53         assert.match(html, /REEL_SECS = 30/, "the reel preview should be ~30s");
54         assert.match(html, /getDuration\(\)/, "random start should derive from the real video
duration");
55         assert.match(html, /Math\.random\(\)/, "the start point should be randomized");
56         assert.match(html, /seekTo\(/, "the player should seek to the random start");
57         // Must NOT be an openly-rendered public section ? it only appears after a successful
submit.
58         assert.doesNotMatch(html, /<section id="reel"/, "the reel must be sign-up-gated, not
an open public section");
59         assert.doesNotMatch(html, /id="reel-play"/, "the open click-to-play facade should be
removed");
60     });
61
62     test("the TOOL screencast is self-hosted, footage-free, and revealed only after sign-
up", () => {
63         const html = read("index.html");
64         assert.match(html, /\video\tool-cuj\.mp4/, "the tool-operation screencast reference
is gone");
65         assert.match(html, /function revealAfterSignup/, "the post-signup reveal function is
gone");
66         assert.match(html, /revealAfterSignup\(\)/, "the reveal must be wired to a successful
submit");
67         // GATED: the only reference to the tool screencast lives inside the reveal function
(injected on
68         // signup), not as an open autoplay element rendered for every visitor.
69         assert.ok(
70             html.indexOf("/video/tool-cuj.mp4") > html.indexOf("function revealAfterSignup"),
71             "the tool screencast must be inside the post-signup reveal, not shown openly",
72         );
73         // the self-hosted clip exists and is non-trivial (a real recording, not an empty
placeholder)
74         assert.ok(size("video/tool-cuj.mp4") > 50_000, "tool-cuj.mp4 is missing or too small
to be the real screencast");
75     });
76
77     test("the post-signup reveal keeps its watchability affordances (manual close + play-
gated auto-close)", () => {
78         // Content contract only ? the BEHAVIOUR (close works, auto-close holds while the reel
plays) is
79         // proven against the real page in ux.dom.test.js, so we don't pin brittle
implementation strings.
80         const html = read("index.html");
81         assert.match(html, /id="reel-close"/, "the manual ? close button is gone");
82         assert.match(html, /onStateChange/, "the reel's play-state must still gate the auto-
close");
83     });
84
85     test("the capture checklist is linked and is a real page", () => {
86         assert.match(read("index.html"), /href="\capture\(\.html)?"/, "footer capture-
checklist link is gone");
87         const cap = read("capture.html");
88         assert.match(cap, /<html/i, "capture.html is not HTML");
89         assert.match(cap, /capture checklist/i, "capture.html lost its checklist content");
90     });
91

```

```

92     test("the academy flyers (en/kn/hi) exist, are language-correct, and are linked from the
homepage", () => {
93         const html = read("index.html");
94         // All three are linked from the homepage footer (the owner ask: the flyers must be
findable).
95         assert.match(html, /href="\ flyer"/, "homepage doesn't link the English academy
flyer");
96         assert.match(html, /href="\ flyer-kn"/, "homepage doesn't link the Kannada academy
flyer");
97         assert.match(html, /href="\ flyer-hi"/, "homepage doesn't link the Hindi academy
flyer");
98
99         // The three flyer pages exist, are HTML, and carry the right language + script.
100        const en = read("flyer.html");
101        assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");
102        const kn = read("flyer-kn.html");
103        assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
104        assert.match(kn, /[? -?]/, "flyer-kn.html should contain Kannada text");
105        const hi = read("flyer-hi.html");
106        assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
107        assert.match(hi, /[? -?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
108    });
109
110    test("each flyer shows a screenshot of the tool rendered in that language", () => {
111        for (const [flyer, img] of [
["flyer.html", "studio-en.png"],
["flyer-kn.html", "studio-kn.png"],
["flyer-hi.html", "studio-hi.png"]
]) {
112            assert.ok(size(`img/${img}`) > 0, `public/img/${img} (the localized UI shot) is
missing or empty`);
113            assert.match(read(flyer), new RegExp(`/img/${img}`), `${flyer} should embed its
localized UI screenshot /img/${img}`);
114        }
115    });
116
117    test("the academy flyers are also linked from the top nav and the own-model page", () =>
{
118        const html = read("index.html");
119        // Desktop top nav carries a Flyer entry (alongside Own your model).
120        const nav = html.match(/<nav class="nav-links"[ \S]*?<\nav>/);
121        assert.ok(nav, "the primary nav block is gone");
122        assert.match(nav[0], /href="\ flyer"/, "the top nav doesn't link the Flyer");
123        // own-model surfaces all three languages.
124        const om = read("own-model.html");
125        assert.match(om, /href="\ flyer"/, "own-model doesn't link the English flyer");
126        assert.match(om, /href="\ flyer-kn"/, "own-model doesn't link the Kannada flyer");
127        assert.match(om, /href="\ flyer-hi"/, "own-model doesn't link the Hindi flyer");
128    });
129
130    test("the landing page surfaces how to record reliably (so users can set up with
confidence)", () => {
131        const html = read("index.html");
132        assert.match(html, /id="record"/, "the 'record it right' section is gone");
133        assert.match(html, /one match, one court/i, "the #1 single-court capture rule should
be on the homepage");
134        // the gist must carry the load-bearing capture cues + a prominent link to the full
checklist
135        for (const cue of [
"/1080p/",
"/30 fps/i,
"/[Aa]udio ON/",
"/baseline/",
"/[Nn]o panning/
]) {
136            assert.match(html, cue, `the recording gist is missing a key cue: ${cue}`);
137        }
138        assert.match(html, /href="\ capture"[^>]*>Full 1-page capture checklist/i, "a
prominent link to the full checklist is gone");
139    });
140
141    test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
142        const html = read("index.html");
143        const m = html.match(/How do I join?<\summary>(<p[ \S]*?<\p>)/);

```

```

144     assert.ok(m, "the 'How do I join?' FAQ is gone");
145     assert.match(m[1], /request access/i, "the join FAQ should send people to the request-
access form");
146     assert.match(m[1], /href="#join"/, "the join FAQ should link to the #join form");
147     assert.doesNotMatch(m[1], /mailto/, "the join FAQ should NOT tell people to email (use
the form)");
148     });
149
150     test("the own-model page exists, is honestly scoped, and is linked from the landing
page", () => {
151         const om = read("own-model.html");
152         assert.ok(om.length > 0, "own-model.html is missing or empty");
153         for (const id of ["annotate", "train", "setup"]) {
154             assert.match(om, new RegExp(`id="${id}"`), `own-model is missing the #${id}
section`);
155         }
156         assert.match(om, /github\.com\/Khelsutra\/rally-annotator/, "the GitHub link to the
annotator is gone");
157         assert.match(om, /Read this honestly/i, "the honest framing fence is gone");
158         assert.match(om, /open pipeline|in build/i, "training must be honestly scoped as in-
build, not one-click");
159         assert.match(om, /name="robots" content="noindex"/, "own-model should be noindex");
160         assert.match(read("index.html"), /href="\own-model"/, "the landing page should link
to /own-model");
161         assert.match(om, /<a href="\>"? KhelSutra home<\a>/, "own-model needs an obvious
back-to-home link (not just browser-back)");
162
163         // a ready-made default works without training (keeps non-tech users engaged); BYO-
training is optional
164         assert.match(om, /ready-made default|out of the box|don't have to train/i, "must
reassure a default works without training");
165         assert.match(om, /optional/i, "training your own should be framed as optional");
166
167         // own-model shows the annotation TOOL screenshots (no people) ? real captures, files
present
168         for (const img of ["annotate-enable.png", "annotate-tool.png"]) {
169             assert.match(om, new RegExp(`img/${img}`), `own-model should embed /img/${img}`);
170             assert.ok(size(`img/${img}`) > 0, `public/img/${img} is missing or empty`);
171         }
172         assert.match(om, /<img[^>]+alt="/i, "screenshots must have alt text");
173
174         // the sample REEL stays gated behind request-access ? NOT embedded/playable here, no
footage shown
175         assert.doesNotMatch(om, /<iframe/i, "the reel must NOT be embedded here ? it's gated
behind request-access");
176         assert.doesNotMatch(om, /youtube/i, "no YouTube embed on own-model; the reel is shown
only after request-access");
177         assert.doesNotMatch(om, /i\.yting\.com/, "don't show the video thumbnail (players)
openly");
178         assert.match(om, /sample[\s\S]{0,80}request access|request access[\s\S]{0,80}sample/i,
"point users to request access for a sample output");
179     });
180

```

101. assistant (2026-06-21T15:00:34.357Z)

I now understand the `site/` surface for B3 (vanilla, dependency-free, clean routes). Good prep banked.

The A4 review should be near done. Let me check its status.

102. user (2026-06-21T15:01:17.027Z)

<retrieval_status>success</retrieval_status>

<task_id>wqh6khdbw</task_id>

<task_type>local_workflow</task_type>

<status>completed</status>

<output>

```
{
  "summary": "Adversarial 3-lens review of the A4 mobile-touch-targets diff",
  "agentCount": 3,
  "logs": [],
  "result": [
    {
      "lens": "touch-completeness",
      "summary": "All interactive controls meet the WCAG 2.5.5 44px floor; no violations found.",
      "findings": [
        {
          "severity": "nit",
          "file": "web/src/components/RallyGrid.tsx",
          "title": "All-clear",
          "detail": "No touch-target violations. Every control uses min-h-11 or h-11/w-11; RallyGrid card is p-3 plus multi-line content over 44px."
        }
      ]
    },
    {
      "lens": "correctness",
      "summary": "Reviewed the feat/a4-mobile-touch-targets diff (8 changed files under web/src + a new test). The change is a clean WCAG 2.5.5 touch-target pass: it bumps primary controls to a 44px floor via Tailwind min-h-11/h-11, makes the QueryBar \"not available yet\" reason visible as DOM text (not hover-only title), and adds the query.notAvailableHelp key. I verified all five requested concerns and ran the gate locally.\n\nVERIFIED LOCALLY (web/ package):\n- typecheck: `npm run typecheck` (tsc --noEmit) ? clean, no errors.\n- tests: `npm run test` (vitest) ? 12 files, 127 tests, all green, including the new components/a4.touch.test.tsx (4 tests), the i18n key-parity hygiene test, and the no-bare-strings (BARE_ATTR) test. The error log lines in output are expected (the suite stubs fetch to reject and asserts the config-unavailable fallback).\n- No lint step exists in this package (no eslint/biome config, no lint script); CI relies on typecheck + vitest, both green.\n\nConcern-by-concern:\n1. SelectionFooter (lib 53 row is flex flex-wrap items-center gap-3): min-h-11 on the reel-name input (line 66) and Build button (line 74) only raises min height; items-center keeps them centered. No alignment/wrap/sticky-footer regression ? the fixed footer container is untouched.\n2. CompileResult header (line 31 parent is flex items-start justify-between gap-3): the dismiss button is now h-11 w-11 with internal items-center justify-center. With items-start the button's TOP still aligns to the h2 top; the larger 44px tap target extends downward and the glyph centers within it. This is a minor, intentional cosmetic shift (standard top-aligned close-button-as-tap-target pattern), not a break ? header does not wrap or overflow. Same applies to the download anchor at line 58 (inline-flex min-h-11 items-center is correct for a link turned into a tap target).\n3. query.notAvailableHelp is present in ALL THREE catalogs (en/kn/hi) at the same path under \"query\", so key-parity stays green (confirmed by the passing hygiene test). The string contains no ICU placeholders ({token}/{kind}), so no i18next-icu interpolation risk.\n4. no-bare-strings: ran the test's exact BARE_ATTR regex over all 7 watched files ? zero matches. notAvailableHelp is rendered as {t(...)} in a <p> body, not an attribute. No new bare attribute introduced.\n5. TypeScript/React: clean. The notAvailableHelp <p> is correctly gated on parsed.unavailable.length > 0, mutually exclusive with the unreadable line (gated on length === 0), so no double-messaging.\n\nNo correctness or regression issues found.",
      "findings": []
    },
    {
      "lens": "faithfulness",
      "findings": [
        {
          "severity": "minor",
          "file": "C:/Users/avidu/Projects/khelsutra/web/src/components/RallyGrid.tsx",
          "location": "lines 60-69 shot-count chip; grid.shotsConfidence in common.json line
```

```

45",
    "title": "Per-card shot-count confidence is hover-only",
    "detail": "The shot chip title at line 62 is the only place per-card
shot_count_confidence renders, and title= never surfaces on touch devices. Everything else in
the title is already visible elsewhere so is not lost on phones: experimental/under-development
is on the chip (grid.shots) and in query.support (QueryBar line 105); may-be-inaccurate is
conveyed by the visible word experimental; filter-by-rally-length is visible in query.support
and app.intro. The only uniquely-per-card piece appearing nowhere visible is the confidence
string. Minor not blocker because api/types.ts line 8 says it is often Unknown, RallyGrid
already suppresses Unknown/empty (lines 62-64) so it shows on only a minority of cards, and it
is a coarse label not a meter on a deliberately de-emphasized chip. The A4 core promise to
surface the essential warning visibly is met.",
    "suggestion": "When a non-Unknown confidence exists, append it to the VISIBLE chip
text (e.g. ~N shots experimental conf: High) reusing the line-63 guard, and drop or keep the
title as redundant. This mirrors the QueryBar visible-help pattern (lines 86-88). Alternatively
document in PER_RALLY_SELECTION.md that confidence is intentionally not surfaced on mobile."
  }
],
  "summary": "Verdict: leaving RallyGrid's shotsTitle hover-only is an ACCEPTABLE A4 gap,
with one minor caveat worth flagging rather than blocking on. The essential, decision-relevant
content of the title is already visible elsewhere: experimental is on the chip itself
(grid.shots = '~N shots experimental'), and under-development plus filter-by-rally-length-
instead are visible text in query.support (QueryBar line 105) and app.intro. The may-be-
inaccurate warning is conveyed by the visible word experimental. The ONLY information that is
unique-per-card and appears nowhere visible is the confidence value (shot_count_confidence via
grid.shotsConfidence) ? the single thing a phone user genuinely loses. It is low-stakes:
api/types.ts line 8 documents it is often Unknown, the code already suppresses it when
Unknown/empty (RallyGrid lines 62-64), and even when shown it is a coarse string label, not a
precise meter, on a chip the product intentionally de-emphasizes. So this is minor, not a
blocker, and the A4 core promise (surface the essential warning visibly) is met. I confirmed
there are exactly two title= attributes in the changed component surfaces (RallyGrid line 62,
QueryBar line 72); the QueryBar one is now redundant because the diff added the visible
notAvailableHelp line (lines 86-88), which the A4 test pins. No other hover-only title= exists
in the changed surfaces.</parameter>\n</invoke>\n"
}
]
}
</output>

```

103. assistant (2026-06-21T15:01:50.400Z)

The 3-lens review came back essentially clean:

- **touch-completeness**: no violations ? all controls meet 44px.
- **correctness**: no issues; independently re-ran typecheck + 127 tests + the key-parity/no-bare-strings guards, all green.
- **faithfulness**: one **minor** (not blocker) ? the per-card shot-count **confidence** is the one datum still hover-only (in `grid.shotsTitle`), invisible on phones. The reviewer's suggested fix: surface it in the visible chip.

That's a legitimate, cheap win that fully honors A4's "tooltip-text ? visible." Let me apply it ? append the confidence to the visible chip when present (keeping the title as redundant desktop detail).

104. user (2026-06-21T15:01:54.609Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\RallyGrid.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

105. assistant (2026-06-21T15:01:58.326Z)

Now add a coverage assertion for the visible confidence to the A4 test:

106. user (2026-06-21T15:02:01.304Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\a4.touch.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

107. assistant (2026-06-21T15:02:06.633Z)

Now re-run the suite + typecheck + build, and reload the preview to confirm the visible confidence.

108. user (2026-06-21T15:02:19.867Z)

```
Test Files  12 passed (12)
  Tests     128 passed (128)
=== tsc ===
tsc OK
=== build ===
dist/assets/index-CUYZ8r6F.css
  20.83 kB ? gzip:  4.84 kB
dist/assets/index-BBxB3my1.js
347.72 kB ? gzip: 109.60 kB
? built in 1.21s
```

109. assistant (2026-06-21T15:02:36.741Z)

128 tests pass (+1 confidence test), tsc clean, build green. The A4 test pins the visible `confidence: High` text. Let me grab a quick desktop screenshot as visual proof of the confidence on the chip, then commit.

110. user (2026-06-21T15:02:37.521Z)

Viewport reset to native size (desktop).

111. assistant (2026-06-21T15:02:49.890Z)

Confirmed: Rally cards now show `~9 shots · experimental ? confidence: High` (and Medium on Rally 3) visibly ? no longer hover-only. The full A4 change is verified (touch targets, visible help line, visible confidence).

Let me commit A4 (re-verifying branch/HEAD and staging explicit paths per shared-checkout discipline).

112. user (2026-06-21T15:02:54.180Z)

```
branch: feat/a4-mobile-touch-targets
HEAD (mine): ccdfcd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon)
(#60)
--- staging A4 paths ---
--- staged ---
web/src/App.tsx
web/src/components/CompileResult.tsx
web/src/components/IngestPanel.tsx
web/src/components/LanguageSwitcher.tsx
web/src/components/QueryBar.tsx
web/src/components/RallyGrid.tsx
web/src/components/SelectionFooter.tsx
web/src/components/a4.touch.test.tsx
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
```

113. assistant (2026-06-21T15:03:22.485Z)

Staged exactly the 11 A4 paths (not the untracked `site/access.db` or `.claude/`). HEAD is the clean A1 base. Committing:

114. user (2026-06-21T15:03:27.578Z)

```
--- committed ---
981e254 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text
--- vs origin/master (must be ONLY my commit) ---
981e254 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text
```

115. assistant (2026-06-21T15:03:33.463Z)

Clean ? only my commit on the branch. Push and open the PR:

116. user (2026-06-21T15:03:36.563Z)

```
remote:      https://github.com/avidullu/khelsutra/pull/new/feat/a4-mobile-touch-targets
remote:
branch 'feat/a4-mobile-touch-targets' set up to track 'origin/feat/a4-mobile-touch-targets'.
To https://github.com/avidullu/khelsutra.git
 * [new branch]      feat/a4-mobile-touch-targets -> feat/a4-mobile-touch-targets
```

117. user (2026-06-21T15:03:55.017Z)

<https://github.com/avidullu/khelsutra/pull/61>

118. assistant (2026-06-21T15:04:07.441Z)

PR [#61](<https://github.com/avidullu/khelsutra/pull/61>) created. Now update the \$7 tracker to mark A4 ? (and fix A1's stale ? ? it merged in #60), plus a changelog note, on the same branch.

119. user (2026-06-21T15:04:09.295Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

120. user (2026-06-21T15:04:15.615Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

121. user (2026-06-21T15:04:27.037Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

122. user (2026-06-21T15:04:36.376Z)

```
pushed
5dfb91f docs(a4): mark A1 (#60) + A4 (#61) done in the $7 tracker + changelog
981e254 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text
```

123. assistant (2026-06-21T15:04:43.070Z)

Both commits on the branch are mine. Now let me check CI on PR #61 before merging.

124. user (2026-06-21T15:05:05.295Z)

```
Workers Builds: hidden-king-khelsutra   pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8e9fd510-94c9-4340-8f6d-629b0a654473
site      pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27908339306/job/82580947234
web       pending 0
https://github.com/avidullu/khelsutra/actions/runs/27908339306/job/82580947225
```

125. assistant (2026-06-21T15:05:13.492Z)

site + CF build pass; web is still running. Let me wait for it.

126. user (2026-06-21T15:05:18.144Z)

```
poll 1: web=pass
=== final ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8e9fd510-94c9-4340-8f6d-629b0a654473
site pass 11s
https://github.com/avidullu/khelsutra/actions/runs/27908339306/job/82580947234
web pass 25s
https://github.com/avidullu/khelsutra/actions/runs/27908339306/job/82580947225
```

127. assistant (2026-06-21T15:05:23.573Z)

All green (web, site, Cloudflare build). Merging A4 per my merge authorization for green UX PRs.

128. user (2026-06-21T15:05:32.946Z)

```
web/src/i18n/locales/en/common.json | 1 +
web/src/i18n/locales/hi/common.json | 1 +
web/src/i18n/locales/kn/common.json | 1 +
12 files changed, 116 insertions(+), 19 deletions(-)
create mode 100644 web/src/components/a4.touch.test.tsx
--- sync local master ---
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
ccdcfcd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon) (#60)
a20002f docs: propose Multilingual Expansion ? 7 new locales (th/id/da/es/zh-Hans/ja/ko) (#58)
```

129. assistant (2026-06-21T15:05:39.817Z)

A4 merged (#61 ? `95195a5`) and local master synced. Marking A4 done and starting **A5 ? friendly engine-error mapping on the build path**.

130. user (2026-06-21T15:05:40.253Z)

Updated task #1 status

131. user (2026-06-21T15:05:41.205Z)

Updated task #2 status

132. user (2026-06-21T15:05:42.154Z)

Chapter marked: "A5 ? friendly build errors". Continue your current work.

133. user (2026-06-21T15:05:45.094Z)

```
branch 'feat/a5-friendly-build-errors' set up to track 'origin/master'.
Switched to a new branch 'feat/a5-friendly-build-errors'
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
```

134. assistant (2026-06-21T15:07:59.849Z)

A5 branch cut (includes A4). Now implementing A5: a shared `errors.\*` namespace + an `errorText(t, e)` helper, wiring `classifyError` into the build path and unifying IngestPanel onto it.

First, the catalogs ? move the ingest code-messages into a shared `errors` namespace (+ a new `engineGeneric` fallback). en:

135. user (2026-06-21T15:08:03.626Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

136. user (2026-06-21T15:08:32.354Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

137. user (2026-06-21T15:08:44.518Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

138. assistant (2026-06-21T15:08:48.603Z)

Now the `errorText` helper:

139. assistant (2026-06-21T15:08:53.111Z)

```
// The ONE place a classified error (lib/errors.ts) becomes user-facing text. Both surfaces use
it:
// the ingest flow (IngestPanel) and the build flow (App.onBuild ? CompileResult), so a 5xx /
engine-
// down failure reads the same friendly way everywhere instead of a raw "HTTP 500" / fetch
message.
//
// `engine` carries the engine's OWN message (the most specific) ? shown verbatim, never
translated.
// Every other code maps to a friendly localized line in the shared `errors.*` namespace. Kept
out of
// errors.ts so that module stays i18n-free and unit-testable without a translation context.
import type { TFunction } from "i18next";
import type { IngestError } from "../errors";

export function errorText(t: TFunction, e: IngestError): string {
  if (e.code === "engine") return e.detail ?? t("errors.engineGeneric");
  return t(`errors.${e.code}`);
}
```

140. user (2026-06-21T15:08:53.153Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra\web\src\lib\errorText.ts (file state is current in your context ? no need to Read it back)

141. assistant (2026-06-21T15:09:04.246Z)

Now wire the build path in App.tsx ? swap `parseDetail` for `classifyError` + `errorText`:

142. user (2026-06-21T15:09:06.184Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

143. user (2026-06-21T15:09:17.242Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

144. assistant (2026-06-21T15:09:21.569Z)

Now unify IngestPanel onto `errorText`:

145. user (2026-06-21T15:09:23.580Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

146. user (2026-06-21T15:09:34.605Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

147. assistant (2026-06-21T15:09:40.220Z)

Now the tests ? a unit test for `errorText` and an integration test proving the build path shows the friendly message:

148. assistant (2026-06-21T15:09:50.736Z)

```
// @vitest-environment jsdom
//
// errorText is the single mapping from a classified error ? user-facing text, shared by the
// ingest
// and build flows (A5). These pin: the engine message passes through verbatim, a detail-less
// engine
// error degrades to a friendly localized line (never a raw key), and every non-engine code
// resolves
// to a real catalog string in the shared `errors.*` namespace.
import { describe, it, expect, beforeAll } from "vitest";
import i18n from "../i18n";
import { errorText } from "../errorText";
import type { IngestErrorCode } from "../errors";

beforeAll(async () => {
  await i18n.changeLanguage("en");
});

describe("errorText", () => {
  it("an engine error shows the engine's own detail verbatim (most specific message)", () => {
    expect(errorText(i18n.t, { code: "engine", detail: "min_shot_count too low"
  })).toBe("min_shot_count too low");
  });

  it("an engine error with no detail degrades to a friendly localized line (not a raw key)", ()
=> {
    const s = errorText(i18n.t, { code: "engine" });
    expect(s).toBe(i18n.t("errors.engineGeneric"));
    expect(s).not.toMatch(/^errors\.\/);
    expect(s.length).toBeGreaterThan(0);
  });

  it("networkError maps to the friendly 'is it running?' line", () => {
    expect(errorText(i18n.t, { code: "networkError" })).toMatch(/is it running/i);
  });

  it("every non-engine code resolves to a real catalog string (never a raw key)", () => {
    for (const code of ["invalidUri", "networkError", "emptyResult", "timeout"] as
IngestErrorCode[]) {
      const s = errorText(i18n.t, { code });
      expect(s, code).not.toMatch(/^errors\.\/);
      expect(s.length, code).toBeGreaterThan(0);
    }
  });

  it("localizes per the active locale (Kannada network message)", async () => {
    await i18n.changeLanguage("kn");
```

```

    expect(errorText(i18n.t, { code: "networkError" })).toBe("????? ??????????????. ???
????????????????");
    await i18n.changeLanguage("en");
  });
});

```

149. user (2026-06-21T15:09:50.754Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra\web\src\lib\errorText.test.ts
(file state is current in your context ? no need to Read it back)

150. assistant (2026-06-21T15:10:34.597Z)

Now the build-path integration test (proves `App.onBuild` shows the friendly mapping):

151. assistant (2026-06-21T15:10:46.464Z)

```

// @vitest-environment jsdom
//
// A5 ? the BUILD path (App.onBuild ? CompileResult) now uses the SAME friendly mapping as
ingest
// (classifyError ? errorText), so a non-technical user never sees a raw "Network error calling
POST
// /api/compile" / "HTTP 500". A real engine 4xx still surfaces the engine's own detail (the
most
// specific, actionable message). Drives the real <App /> with a loaded video + a stubbed
engine.
import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
import { render, screen, cleanup, fireEvent } from "@testing-library/react";
import i18n from "../i18n";
import App from "../App";
import type { RallySegment } from "../api/types";

const RALLIES: RallySegment[] = [
  { id: 1, start_time: 10, end_time: 20, duration: 10, server: null, receiver: null, metadata: {
shot_count: 12 } },
  { id: 2, start_time: 30, end_time: 45, duration: 15, server: null, receiver: null, metadata: {
shot_count: 14 } },
];

const httpOk = (status: number, json: unknown) => ({
  ok: status >= 200 && status < 300, status, json: async () => json, text: async () =>
JSON.stringify(json),
});

const httpErr = (status: number, body: string) => ({
  ok: false, status, json: async () => JSON.parse(body), text: async () => body,
});

// /api/query ? rallies; /api/config ? 500 (cfg unavailable ? no floor warning); /api/compile ?
caller-supplied.
function mockFetch(compile: () => unknown) {
  return vi.fn(async (url: string | URL, init?: RequestInit) => {
    const u = String(url);
    const method = init?.method ?? "GET";
    if (u === "/api/query" && method === "POST") return httpOk(200, { play_segments: RALLIES });
    if (u === "/api/config") return httpErr(500, "");
    if (u === "/api/compile" && method === "POST") return compile();
    throw new Error(`unexpected fetch ${method} ${u}`);
  }) as unknown as typeof fetch;
}

beforeEach(async () => {
  window.history.pushState({}, "", "?video=vidX"); // job-tethered: load a real video's rallies
  window.localStorage.clear();

```

```

    await i18n.changeLanguage("en");
  });

afterEach(() => {
  cleanup();
  vi.unstubAllGlobals();
  window.history.pushState({}, "", "/");
});

// Rallies load all-selected (count 2) ? the Build button label proves the load completed.
const loadAndBuild = async () => {
  render(<App />);
  fireEvent.click(await screen.findByRole("button", { name: /build reel \(\2\)/i }));
};

describe("A5: friendly build-error mapping", () => {
  it("a network / engine-down compile failure shows the friendly 'is it running?' line", async
  () => {
    vi.stubGlobal("fetch", mockFetch(() => {
      throw new Error("offline");
    }));
    await loadAndBuild();
    expect(await screen.findByText(/can't reach khelsutra/i)).toBeTruthy();
    expect(screen.queryByText(/network error calling/i)).toBeNull(); // the raw client message
    is gone
  });

  it("a real engine 4xx surfaces the engine's own detail verbatim", async () => {
    vi.stubGlobal("fetch", mockFetch(async () => httpErr(400, JSON.stringify({ detail: "rally
    below min_shot_count" })))));
    await loadAndBuild();
    expect(await screen.findByText(/rally below min_shot_count/i)).toBeTruthy();
  });
});

```

152. user (2026-06-21T15:10:46.484Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra\web\src\components\build-error.test.tsx (file state is current in your context ? no need to Read it back)

153. assistant (2026-06-21T15:10:53.674Z)

Now run the suite + typecheck + build for A5:

154. user (2026-06-21T15:11:08.250Z)

```

{"ts":"2026-06-21T15:10:58.491Z","level":"error","event":"api.network_error","cid":"c209481f-6e05-4ea4-b2b4-9ff55e51391a","method":"GET","url":"/api/config","error":"Error: offline"}
{"ts":"2026-06-21T15:11:01.857Z","level":"error","event":"ingest.job_failed","cid":"5266ab2c-3ec4-4863-a3ee-2615b7ebddc2","uri":"gs://b/x.mp4","code":"engine","detail":"RuntimeError: boom"}
{"ts":"2026-06-21T15:11:00.864Z","level":"error","event":"api.network_error","cid":"ee7eb32b-47c1-4d22-a904-299da0fc1579","method":"POST","url":"/api/process","error":"Error: offline"}
{"ts":"2026-06-21T15:11:01.204Z","level":"error","event":"api.network_error","cid":"28cc7b77-6e61-40aa-abac-49c68c3ace00","method":"POST","url":"/api/process","error":"Error: offline"}
{"ts":"2026-06-21T15:11:01.271Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
{"ts":"2026-06-21T15:11:01.338Z","level":"error","event":"api.network_error","cid":"6d7cc958-5f94-45ed-89f5-2637d9e11fb1","method":"GET","url":"/api/config","error":"Error: no engine in test"}

```

```
{
  "ts": "2026-06-21T15:11:01.339Z",
  "level": "warn",
  "event": "config.unavailable",
  "error": "ApiError: Network error calling GET /api/config"
}
{"ts": "2026-06-21T15:11:01.352Z", "level": "error", "event": "api.network_error", "cid": "dc9658af-4520-428a-a7dc-6eba7d7078a4", "method": "POST", "url": "/api/compile", "error": "Error: offline"}
{"ts": "2026-06-21T15:11:01.358Z", "level": "error", "event": "build.failed", "cid": "dc9658af-4520-428a-a7dc-6eba7d7078a4", "video_id": "vidX", "filename": "highlights.mp4", "code": "networkError", "error": "ApiError: Network error calling POST /api/compile"}
{"ts": "2026-06-21T15:11:01.384Z", "level": "error", "event": "api.network_error", "cid": "f2a01c01-eaf5-4a5f-bc92-64438cb62a2a", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.384Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.415Z", "level": "error", "event": "api.network_error", "cid": "ea56608a-f652-4bd7-b568-b48f45f0f365", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.415Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.417Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: GET /api/config failed: 500"}
{"ts": "2026-06-21T15:11:01.430Z", "level": "error", "event": "api.network_error", "cid": "c9bf0794-14a3-42ae-b2f1-e8d4b2bd6041", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.430Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.488Z", "level": "error", "event": "build.failed", "cid": "4e3bfb21-b465-48f0-9804-3cfd45f8c34f", "video_id": "vidX", "filename": "highlights.mp4", "status": 400, "code": "engine", "detail": "rally below min_shot_count", "error": "ApiError: POST /api/compile failed: 400"}
{"ts": "2026-06-21T15:11:01.493Z", "level": "error", "event": "api.network_error", "cid": "b1c967ee-5dac-4813-bdf9-8727cddbc64a", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.494Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.512Z", "level": "error", "event": "api.network_error", "cid": "ffd4a5df-ba65-45ae-a588-821e075346f1", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.512Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.518Z", "level": "error", "event": "api.network_error", "cid": "22100c51-77a8-464d-b06a-e0c14b3a66d4", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.518Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.577Z", "level": "error", "event": "api.network_error", "cid": "768e29b2-d88d-4d28-bd7e-d46dd6853691", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.578Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error calling GET /api/config"}
{"ts": "2026-06-21T15:11:01.635Z", "level": "error", "event": "api.network_error", "cid": "5cc7feb0-e978-4ef2-a8c8-0a60d43df1b1", "method": "GET", "url": "/api/config", "error": "Error: no engine in test"}
{"ts": "2026-06-21T15:11:01.636Z", "level": "warn", "event": "config.unavailable", "error": "ApiError: Network error
```

```
calling GET /api/config"}
{"ts":"2026-06-
21T15:11:01.657Z","level":"error","event":"api.network_error","cid":"c1f4af09-a1cf-41d8-bd27-
31628c83a9b0","method":"GET","url":"/api/config","error":"Error: no engine in test"}
{"ts":"2026-06-
21T15:11:01.658Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error
calling GET /api/config"}
{"ts":"2026-06-
21T15:11:01.680Z","level":"error","event":"api.network_error","cid":"e0235890-0495-4870-b029-
59008793ef2f","method":"GET","url":"/api/config","error":"Error: no engine in test"}
=== tsc ===
tsc OK
=== build ===
dist/assets/index-DMN4rFdu.js
347.85 kB ? gzip: 109.68 kB
? built in 1.19s
```

155. assistant (2026-06-21T15:11:15.812Z)

The build logs confirm A5 working (`build.failed code:networkError` and `code:engine detail:"rally below min\_shot\_count"`). tsc + build clean. Let me get the clean test summary:

156. user (2026-06-21T15:11:23.171Z)

```
stdout | src/hooks/useIngestJob.test.ts > useIngestJob >
treats a done-but-failed pipeline verdict as emptyResult ? never a load
stdout | src/hooks/useIngestJob.test.ts > useIngestJob >
treats a done-but-failed pipeline verdict as emptyResult ? never a load
stdout | src/hooks/useIngestJob.test.ts > useIngestJob >
treats a done-but-failed pipeline verdict as emptyResult ? never a load
Test Files 14 passed (14)
Tests 135 passed (135)
```

157. assistant (2026-06-21T15:11:54.246Z)

135 tests pass (+5 errorText, +2 build-error), tsc + build clean. Let me browser-verify the shared `errorText` wiring via the ingest path (same helper the build path now uses) ? with no engine on :8000, a submit should show the friendly localized message.

158. user (2026-06-21T15:12:00.529Z)

"navigated to clean root"

159. user (2026-06-21T15:12:05.698Z)

Successfully filled: input[aria-label^="Video location"]

160. user (2026-06-21T15:12:10.114Z)

Successfully clicked: button[type="submit"]

161. user (2026-06-21T15:12:17.547Z)

"Can't reach KhelSutra. Is it running?Try again"

162. assistant (2026-06-21T15:12:27.677Z)

The shared `errorText` renders the friendly localized message in the browser (`"Can't reach KhelSutra. Is it running?"` + Try again) ? same helper the build path now uses. A5 verified: 135 tests, tsc, build all green; key-parity holds.

Let me capture the A5 diff and run an adversarial review before merging.

163. user (2026-06-21T15:12:30.042Z)

```
web/src/App.tsx | 11 ++++++----
web/src/components/IngestPanel.tsx | 15 ++++++-----
web/src/i18n/locales/en/common.json | 10 ++++++----
web/src/i18n/locales/hi/common.json | 10 ++++++----
web/src/i18n/locales/kn/common.json | 10 ++++++----
5 files changed, 31 insertions(+), 25 deletions(-)
=====DIFF=====
=====CATALOG (en only, kn/hi parallel)=====
```

164. assistant (2026-06-21T15:12:52.811Z)

Let me get a clean diff (the new files are untracked, so `git diff` skipped them) and run a focused 2-lens review:

165. user (2026-06-21T15:12:54.231Z)

```
Exit code 128
warning: could not open directory 'web/web/src/': No such file or directory
fatal: pathspec 'web/src/lib/errorText.ts' did not match any files
```

166. assistant (2026-06-21T15:13:01.530Z)

Working directory was still `khelsutra/web`. Let me run from the repo root:

167. user (2026-06-21T15:13:02.957Z)

```
diff --git a/web/src/App.tsx b/web/src/App.tsx
index 85361d6..4231ba3 100644
--- a/web/src/App.tsx
+++ b/web/src/App.tsx
@@ -10,7 +10,8 @@ import { IngestPanel } from "../components/IngestPanel";
import { runQuery, type ParsedQuery } from "../lib/query";
import { floorRisk } from "../lib/floor";
import { reelFilename } from "../lib/format";
-import { parseDetail } from "../lib/errors";
+import { classifyError } from "../lib/errors";
+import { errorText } from "../lib/errorText";
import { log, newCorrelationId } from "../lib/log";
import { ApiError, compileReel, getConfig, highlightUrl, listRallies, minShotCount } from
"./api/client";
import type { EngineConfig, RallySegment } from "../api/types";
@@ -143,10 +144,12 @@ export default function App() {
  setBuild({ status: "done", url, filename });
  log("info", "build.done", { cid, video_id: videoId, filename, filepath: res.filepath, url
});
} catch (err) {
+ // Same friendly mapping the ingest flow uses: a bare 5xx / network throw reads "is the
engine
+ // running?", a real engine 4xx surfaces its own detail ? never a raw "HTTP 500" (A5).
const status = err instanceof ApiError ? err.status : undefined;
- const detail = err instanceof ApiError && err.body ? parseDetail(err.body) : String(err);
- setBuild({ status: "error", error: detail });
- log("error", "build.failed", { cid, video_id: videoId, filename, status, error:
String(err) });
+ const e = classifyError(err);
+ setBuild({ status: "error", error: errorText(t, e) });
+ log("error", "build.failed", { cid, video_id: videoId, filename, status, code: e.code,
detail: e.detail, error: String(err) });
}
};
```

```
diff --git a/web/src/components/IngestPanel.tsx b/web/src/components/IngestPanel.tsx
```

```

index 322ffb8..87607f8 100644
--- a/web/src/components/IngestPanel.tsx
+++ b/web/src/components/IngestPanel.tsx
@@ -8,6 +8,7 @@ import { useState } from "react";
import type { FormEvent } from "react";
import { useTranslation } from "react-i18next";
import { useIngestJob } from "../hooks/useIngestJob";
+import { errorText } from "../lib/errorText";

interface Props {
  /** Called with the engine's video_id once a submitted job finishes successfully. */
@@ -24,15 +25,11 @@ export function IngestPanel({ onLoad }: Props) {
  submit(uri);
};

- // `engine` failures carry the engine's own message (a 400 scheme/path detail, a worker
error);
- // every other code maps to a friendly localized line ? the network case especially, since
this
- // is the first screen a fresh user hits and "is the engine running?" must read plainly.
- const errorMsg =
-   phase.status === "error"
-     ? phase.error.code === "engine"
-       ? (phase.error.detail ?? t("ingest.failed", { error: "" }))
-       : t(`ingest.${phase.error.code}`)
-     : null;
+ // Shared mapping with the build flow (lib/errorText): `engine` failures carry the engine's
own
+ // message (a 400 scheme/path detail, a worker error); every other code maps to a friendly
+ // localized line ? the network case especially, since this is the first screen a fresh user
hits
+ // and "is the engine running?" must read plainly.
+ const errorMsg = phase.status === "error" ? errorText(t, phase.error) : null;

return (
  <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
testid="ingest-panel">

```

168. assistant (2026-06-21T15:13:09.559Z)

Clean A5 diff. Now a focused 2-lens adversarial review (regression/orphan-keys + faithfulness/observability):

169. user (2026-06-21T15:13:32.418Z)

Workflow launched in background. Task ID: w8jaidc9f
Summary: Adversarial review of the A5 shared-error-mapping diff
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_d954e9ee-fd0
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\a5-review-wf_d954e9ee-fd0.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\a5-review-wf_d954e9ee-fd0.js"})
to iterate without resending the script.)
Run ID: wf_d954e9ee-fd0
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\a5-review-wf_d954e9ee-fd0.js", resumeFromRunId: "wf_d954e9ee-fd0"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

170. assistant (2026-06-21T15:14:14.637Z)

While the A5 review runs, I've scoped A8 (reassurance + icon+text status chips in IngestPanel progress and the build/CompileResult states). Let me wait for the A5 review to gate the merge.

171. user (2026-06-21T15:18:15.390Z)

<retrieval_status>timeout</retrieval_status>

<task_id>w8jaidc9f</task_id>

<task_type>local_workflow</task_type>

<status>running</status>

172. user (2026-06-21T15:18:21.895Z)

<retrieval_status>success</retrieval_status>

<task_id>w8jaidc9f</task_id>

<task_type>local_workflow</task_type>

<status>completed</status>

<output>

```
{
  "summary": "Adversarial review of the A5 shared-error-mapping diff",
  "agentCount": 2,
  "logs": [],
  "result": [
    {
      "lens": "regression-orphans",
      "summary": "clean",
      "findings": [
        {
          "severity": "nit",
          "file": "web/src/lib/errors.ts",
          "title": "parseDetail now internal-only",
          "detail": "After A5, parseDetail is only used inside errors.ts and its test; still
exported. Harmless."
        }
      ]
    },
    {
      "lens": "faithfulness-observability",
      "findings": [
        {
          "severity": "nit",
          "file": "web/src/App.tsx",
          "title": "Rally-load failure banner still shows raw String(err) (out of A5 scope)",
          "detail": "rallies.load_failed catch sets loadState.error=String(err), rendered by
ModeBanner mode.error (App.tsx 85-89, 290-296); a 500/network throw shows raw ApiError text. Out
of A5 scope (build path + ingest unification both done), not a spec violation; natural next
consolidation.",
          "location": "App.tsx 85-89, 290-296",
          "suggestion": "Map through errorText(t, classifyError(err)) and store in
loadState.error."
        }
      ],
      "summary": "A5 faithful; one out-of-scope nit. Build path uses classifyError->errorText
(friendly+localized, not raw String(err)/HTTP500), proven by build-error.test.tsx (network->'is
it running', 4xx->engine detail verbatim). errors.* namespace shared by IngestPanel+App via the
single errorText helper; the engine/non-engine branch lives ONLY in lib/errorText.ts (no
duplication; old inline ingest.${code} map and App parseDetail removed). errors.ts stays
i18n-free/testable. Observability: build.failed retains cid+status+raw error and ADDS
code+detail (nothing dropped). engineGeneric is a safe last-resort (only when code==engine AND
```

```
detail nullish; every producer sets a non-null detail). Catalogs:
ingest.{networkError,invalidUri,emptyResult,timeout} moved to errors.*, engineGeneric added,
ingest.failed removed, 11 ingest.* keys retained; identical en/kn/hi key sets with real
translations. Verified locally: web suite 135/135 green, tsc --noEmit clean (no eslint config
for web/, lint N/A there)."
    }
  ]
}
</output>
```

173. assistant (2026-06-21T15:18:58.262Z)

A5 review is clean ? two ****nits****, no blockers:

1. ``parseDetail`` is now internal-only but still exported (harmless ? it's used by ``classifyError`` and tested).
2. The rally-****load**** failure banner still shows raw ``String(err)`` ? "out of A5 scope but a natural next consolidation."

Nit #2 is the same raw-error class on the one remaining SPA surface (the load path), and it's a one-line application of the helper I just built. Leaving load showing ``ApiError: Network error...`` while build is friendly would be inconsistent and violates the DoD's "no raw engine jargon." I'll fold it in to fully complete "friendly errors everywhere."

174. user (2026-06-21T15:19:01.983Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

175. assistant (2026-06-21T15:19:19.856Z)

Now extend the test to cover the load path too:

176. user (2026-06-21T15:19:21.360Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\build-error.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

177. user (2026-06-21T15:19:31.027Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\build-error.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

178. user (2026-06-21T15:19:48.844Z)

```
Test Files  14 passed (14)
Tests      136 passed (136)
=== tsc ===
tsc OK
=== build ===
? built in 1.41s
```

179. assistant (2026-06-21T15:20:00.825Z)

136 tests pass (+1 load-failure test), tsc + build clean. A5 is complete (build + load paths + ingest unified). Committing ? verify branch/HEAD, stage explicit paths:

180. user (2026-06-21T15:20:03.548Z)

```
branch: feat/a5-friendly-build-errors
--- staged ---
web/src/App.tsx
web/src/components/IngestPanel.tsx
web/src/components/build-error.test.tsx
```

```
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
web/src/lib/errorText.test.ts
web/src/lib/errorText.ts
--- HEAD must be A4-merged master ---
```

181. user (2026-06-21T15:20:19.978Z)

```
1f28484 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/a5-friendly-build-errors -> feat/a5-friendly-build-errors
```

182. user (2026-06-21T15:20:43.610Z)

<https://github.com/avidullu/khelsutra/pull/62>

183. assistant (2026-06-21T15:20:49.377Z)

PR [#62](<https://github.com/avidullu/khelsutra/pull/62>) created. Now mark A5 ? in the tracker:

184. user (2026-06-21T15:20:51.868Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

185. user (2026-06-21T15:21:03.121Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

186. user (2026-06-21T15:21:37.928Z)

```
pushed; CI poll...
site    pass    16s
https://github.com/avidullu/khelsutra/actions/runs/27908758417/job/82582082654
Workers Builds: hidden-king-khelsutra    pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/78ca8f09-a900-4337-819b-5d57a21e3501
web      pending 0
https://github.com/avidullu/khelsutra/actions/runs/27908758417/job/82582082635
```

187. user (2026-06-21T15:22:05.712Z)

```
poll 1: web=pending cf=pass
poll 2: web=pass cf=pass
=== final ===
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/78ca8f09-a900-4337-819b-5d57a21e3501
site    pass    16s
https://github.com/avidullu/khelsutra/actions/runs/27908758417/job/82582082654
web      pass    30s
https://github.com/avidullu/khelsutra/actions/runs/27908758417/job/82582082635
```

188. assistant (2026-06-21T15:22:10.356Z)

All three checks green (web, site, Cloudflare). Merging A5:

189. user (2026-06-21T15:22:19.394Z)

```
create mode 100644 web/src/components/build-error.test.tsx
create mode 100644 web/src/lib/errorText.test.ts
```

```
create mode 100644 web/src/lib/errorText.ts
501c014 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
(#62)
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
```

190. assistant (2026-06-21T15:23:06.316Z)

A5 merged (#62 ? `501c014`). Now **A8 ? background-processing reassurance + icon+text status chips**.

191. user (2026-06-21T15:23:06.805Z)

Updated task #2 status

192. user (2026-06-21T15:23:07.269Z)

Updated task #3 status

193. user (2026-06-21T15:23:08.681Z)

Chapter marked: "A8 ? status chips + reassurance". Continue your current work.

194. user (2026-06-21T15:23:11.565Z)

```
branch 'feat/a8-status-chips' set up to track 'origin/master'.
Switched to a new branch 'feat/a8-status-chips'
501c014 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
(#62)
```

195. assistant (2026-06-21T15:23:17.185Z)

A8 branch cut. First, a small reusable `StatusChip` (always icon+text) + a shared `Spinner`:

196. assistant (2026-06-21T15:23:24.479Z)

```
// A status indicator that is ALWAYS icon + text ? never icon-only (HCI4D guidance for non-tech-
savvy
// users, FRIENDLY_AND_MULTILINGUAL §4: pair every icon with a word, don't rely on color alone).
Used
// for the ingest "working / couldn't process" states and the build "stitching / ready / failed"
states.
import type { ReactNode } from "react";

type Tone = "info" | "success" | "error";

const TONE: Record<Tone, string> = {
  info: "bg-ink/5 text-ink/70",
  success: "bg-green/15 text-green",
  error: "bg-red-100 text-red-800",
};

interface Props {
  /** A glyph or the <Spinner/> ? decorative; the label carries the meaning for screen readers.
  */
  icon: ReactNode;
  label: string;
  tone?: Tone;
}

export function StatusChip({ icon, label, tone = "info" }: Props) {
  return (
    <span className={`inline-flex items-center gap-1.5 rounded-full px-3 py-1 text-sm font-
medium ${TONE[tone]}`}>
      <span aria-hidden="true" className="inline-flex">
```

```

        {icon}
      </span>
    <span>{label}</span>
  </span>
);
}

/** Indeterminate spinner ? the engine reports coarse phase WORDS, not a percentage, so progress
is a
* spinner + the phase label rather than a misleading progress bar. */
export function Spinner() {
  return (
    <span
      className="inline-block h-3.5 w-3.5 animate-spin rounded-full border-2 border-current/30
border-t-current"
      aria-hidden="true"
    />
  );
}

```

197. user (2026-06-21T15:23:24.506Z)

File created successfully at:
C:\Users\avidu\Projects\khelsutra\web\src\components\StatusChip.tsx (file state is current in
your context ? no need to Read it back)

198. assistant (2026-06-21T15:23:46.135Z)

Let me use the proven spinner classes (matching the original) for robustness:

199. user (2026-06-21T15:23:49.220Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\StatusChip.tsx has been updated
successfully. (file state is current in your context ? no need to Read it back)

200. assistant (2026-06-21T15:23:54.287Z)

Now wire the IngestPanel ? import StatusChip/Spinner, use chips + reassurance, drop the local
Spinner:

201. user (2026-06-21T15:23:55.945Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated
successfully. (file state is current in your context ? no need to Read it back)

202. user (2026-06-21T15:24:09.728Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated
successfully. (file state is current in your context ? no need to Read it back)

203. assistant (2026-06-21T15:24:56.129Z)

Now wire `CompileResult` ? add a building reassurance card + status icons on the done/failed
headers:

204. user (2026-06-21T15:25:05.751Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\CompileResult.tsx has been updated
successfully. (file state is current in your context ? no need to Read it back)

205. assistant (2026-06-21T15:25:13.822Z)

Now the catalog keys (en/kn/hi) for `result.building`, `result.buildingReassure`,

`ingest.reassure`, `ingest.statusFailed`:

206. user (2026-06-21T15:25:16.397Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

207. user (2026-06-21T15:25:22.427Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

208. user (2026-06-21T15:25:38.012Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

209. user (2026-06-21T15:25:54.795Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

210. user (2026-06-21T15:26:02.464Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

211. user (2026-06-21T15:26:10.722Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

212. assistant (2026-06-21T15:26:48.725Z)

Now an A8 test (CompileResult building/done/error chips + IngestPanel reassurance/error chip):

213. assistant (2026-06-21T15:27:04.002Z)

```
// @vitest-environment jsdom
//
// A8 ? honest expectations for non-tech users on slow uplinks: background-processing
reassurance and
// status shown as icon+TEXT chips (never icon-only), on BOTH the ingest progress and the build
state.
import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
import { render, screen, cleanup, fireEvent, act } from "@testing-library/react";
import i18n from "../i18n";
import { CompileResult } from "../CompileResult";
import { IngestPanel } from "../IngestPanel";
import type { JobStatus } from "../api/types";

beforeEach(async () => {
  window.localStorage.clear();
  await i18n.changeLanguage("en");
});

afterEach(() => {
  cleanup();
  vi.restoreAllMocks();
  vi.unstubAllGlobals();
  vi.useRealTimers();
});
```

```

describe("A8: build state shows status + reassurance (CompileResult)", () => {
  it("building ? a 'stitching?' chip + a reassurance line (and nothing to dismiss yet)", () => {
    render(<CompileResult build={{ status: "building" }} onDismiss={() => {}} />);
    expect(screen.getByText("Stitching your reel?")).toBeTruthy();
    expect(screen.getByText(/usually takes under a minute/i)).toBeTruthy();
    expect(screen.queryByRole("button", { name: "Dismiss" })).toBeNull();
  });

  it("done ? a ? icon paired with the 'ready' text (icon+text, not icon-only)", () => {
    render(<CompileResult build={{ status: "done", url: "/x", filename: "r.mp4" }} onDismiss={() => {}} />);
    const h = screen.getByRole("heading", { level: 2 });
    expect(h.textContent).toContain("?");
    expect(h.textContent).toContain("Your reel is ready");
  });

  it("error ? a ? icon paired with 'failed' + the message", () => {
    render(<CompileResult build={{ status: "error", error: "boom" }} onDismiss={() => {}} />);
    const h = screen.getByRole("heading", { level: 2 });
    expect(h.textContent).toContain("?");
    expect(screen.getByText("boom")).toBeTruthy();
  });
});

describe("A8: ingest progress reassurance + status chips (IngestPanel)", () => {
  const httpOk = (s: number, j: unknown) => ({ ok: s >= 200 && s < 300, status: s, json: async () => j, text: async () => JSON.stringify(j) });
  function fetchSeq(process: unknown, jobs: JobStatus[]) {
    let i = 0;
    return vi.fn(async (url: string | URL, init?: RequestInit) => {
      const u = String(url);
      if (u === "/api/process" && (init?.method ?? "GET") === "POST") return process;
      if (u.startsWith("/api/jobs/")) {
        const b = jobs[Math.min(i, jobs.length - 1)];
        i += 1;
        return httpOk(200, b);
      }
      throw new Error(`unexpected fetch ${u}`);
    }) as unknown as typeof fetch;
  }

  it("while processing ? the working chip + 'safe to wait' reassurance", async () => {
    vi.useFakeTimers();
    vi.stubGlobal("fetch", fetchSeq(httpOk(202, { job_id: "j", status: "queued" })), [
      { job_id: "j", status: "running", progress: "segmenting" },
    ]);
    render(<IngestPanel onLoaded={vi.fn()} />);
    fireEvent.change(screen.getByLabelText(/video location/i), { target: { value: "gs://b/x.mp4" } });
    fireEvent.click(screen.getByRole("button", { name: /process video/i }));
    await act(async () => {
      await vi.advanceTimersByTimeAsync(0); // submit ? polling
    });
    await act(async () => {
      await vi.advanceTimersByTimeAsync(1000); // running tick ? progress word
    });
    expect(screen.getByText(/processing your video/i)).toBeTruthy();
    expect(screen.getByText(/safe to wait/i)).toBeTruthy();
  });

  it("on failure ? a ? 'Couldn't process' status chip alongside the friendly message", async () => {
    vi.stubGlobal("fetch", vi.fn(async () => {
      throw new Error("offline");
    }) as unknown as typeof fetch);
  });
});

```

```

    render(<IngestPanel onLoad={vi.fn()} />);
    fireEvent.change(screen.getByLabelText(/video location/i), { target: { value: "gs://b/x.mp4"
  } });
    fireEvent.click(screen.getByRole("button", { name: /process video/i }));
    expect(await screen.findByText("Couldn't process")).toBeTruthy();
    expect(await screen.findByText(/is it running/i)).toBeTruthy();
  });
});

```

214. user (2026-06-21T15:27:04.033Z)

File created successfully at:
 C:\Users\avidu\Projects\kheIsutra\web\src\components\A8.status.test.tsx (file state is current
 in your context ? no need to Read it back)

215. user (2026-06-21T15:27:22.901Z)

```

Test Files  15 passed (15)
  Tests     141 passed (141)
=== tsc ===
tsc OK
=== build ===
? built in 1.29s

```

216. assistant (2026-06-21T15:27:40.923Z)

141 tests pass (+5 A8 tests), tsc + build clean. Let me browser-verify the reachable A8 states
 (the ingest error chip is reachable with no engine; working/building are covered by tests).
 Reload and submit:

217. user (2026-06-21T15:27:42.415Z)

"ok"

218. user (2026-06-21T15:27:47.495Z)

Successfully filled: input[aria-label^="Video location"]

219. user (2026-06-21T15:27:53.655Z)

Successfully clicked: button[type="submit"]

220. user (2026-06-21T15:28:03.098Z)

"?Couldn't processCan't reach KheIsutra. Is it running?Try again"

221. assistant (2026-06-21T15:28:10.716Z)

The A8 error chip renders live: **?? Couldn't process** + the friendly message + Try again. Let
 me grab a screenshot for proof, then review.

222. assistant (2026-06-21T15:28:22.952Z)

A8 error chip renders cleanly (**?? Couldn't process** + message + Try again).
 Working/building/done states are covered by the 5 new tests. Let me capture the diff and run a
 lean adversarial review before committing.

223. user (2026-06-21T15:28:25.235Z)

```

diff --git a/web/src/components/CompileResult.tsx b/web/src/components/CompileResult.tsx
index 619d22b..04c40a5 100644
--- a/web/src/components/CompileResult.tsx
+++ b/web/src/components/CompileResult.tsx

```



```

@@ -4,6 +4,7 @@
// failure (e.g. the min_shot_count 400) we show the engine's reason ? loud, never swallowed.

import { useTranslation } from "react-i18next";
+import { StatusChip, Spinner } from "../StatusChip";

export type BuildState =
  | { status: "idle" }
@@ -18,18 +19,29 @@ interface Props {

export function CompileResult({ build, onDismiss }: Props) {
  const { t } = useTranslation();
- if (build.status === "idle" || build.status === "building") return null;
+ if (build.status === "idle") return null;

+ // Build state (A8): a visible "stitching?" card with an icon+text chip + reassurance, so the
+ user
+ // isn't staring at a frozen footer wondering whether anything is happening.
+ if (build.status === "building") {
+   return (
+     <section data-testid="compile-result" className="mt-6 rounded-xl border border-black/10
bg-paper p-4" aria-live="polite">
+       <StatusChip tone="info" icon={<Spinner />} label={t("result.building")} />
+       <p className="mt-2 text-sm text-ink/60">{t("result.buildingReassure")}</p>
+     </section>
+   );
+ }
+
+ const isError = build.status === "error";
  return (
    <section
      data-testid="compile-result"
-     className={
-       "mt-6 rounded-xl border p-4 " +
-       (build.status === "error" ? "border-red-200 bg-red-50" : "border-green/30 bg-green/5")
-     }
+     className={"mt-6 rounded-xl border p-4 " + (isError ? "border-red-200 bg-red-50" :
"border-green/30 bg-green/5")}
    >
      <div className="flex items-start justify-between gap-3">
-       <h2 className="font-semibold text-ink">
+       { /* Status as icon+text (never icon-only): ? ready / ? failed (A8). */ }
+       <h2 className="flex items-center gap-2 font-semibold text-ink">
+         <span aria-hidden="true" className={isError ? "text-red-700" : "text-green"}>{isError
? "?" : "?"}</span>
+         {build.status === "done" ? t("result.ready") : t("result.failed")}
+       </h2>
+       <button
diff --git a/web/src/components/IngestPanel.tsx b/web/src/components/IngestPanel.tsx
index 87607f8..6f0c37f 100644
--- a/web/src/components/IngestPanel.tsx
+++ b/web/src/components/IngestPanel.tsx
@@ -9,6 +9,7 @@ import type { FormEvent } from "react";
import { useTranslation } from "react-i18next";
import { useIngestJob } from "../hooks/useIngestJob";
import { errorText } from "../lib/errorText";
+import { StatusChip, Spinner } from "../StatusChip";

interface Props {
  /** Called with the engine's video_id once a submitted job finishes successfully. */
@@ -66,23 +67,29 @@ export function IngestPanel({ onLoaded }: Props) {

  <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>

-   { /* Live status (aria-live so screen readers hear progress). Indeterminate: the engine

```

```

reports
-   phase words ("hashing", "segmenting"), not a percentage ? so a spinner + the phase
word. */}
+   {/* Live status (aria-live so screen readers hear progress) as icon+text chips ? never
icon-only
+   (A8). Indeterminate: the engine reports phase words ("hashing", "segmenting"), not a
%. */}
    <div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
        {busy && (
-           <p className="flex items-center gap-2 text-ink/70">
-               <Spinner />
-               <span>
-                   {t("ingest.working")}
-                   {phase.status === "polling" && phase.progress
-                       ? ` ` . ${t("ingest.progress", { progress: phase.progress })}`
-                       : ""}
-               </span>
-           </p>
+           <div>
+               <StatusChip
+                   tone="info"
+                   icon={<Spinner />}
+                   label={
+                       t("ingest.working") +
+                       (phase.status === "polling" && phase.progress
+                           ? ` ` . ${t("ingest.progress", { progress: phase.progress })}`
+                           : "")
+                   }
+               />
+           <div>
+               {/* Reassurance for slow uplinks: the job runs on the server, so it's safe to wait.
*/}
+               <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
+           </div>
+       )}
        {phase.status === "error" && (
            <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-red-800"
data-testid="ingest-error">
-               <p>{errorMsg}</p>
+               <StatusChip tone="error" icon="?" label={t("ingest.statusFailed")} />
+               <p className="mt-2">{errorMsg}</p>
+               <button
+                   type="button"
+                   onClick={reset}
@@ -96,12 +103,3 @@ export function IngestPanel({ onLoaded }: Props) {
    </section>
  );
}
-
-function Spinner() {
-   return (
-       <span
-           className="inline-block h-3.5 w-3.5 animate-spin rounded-full border-2 border-ink/20
border-t-ink/70"
-           aria-hidden="true"
-       />
-   );
-}
diff --git a/web/src/components/StatusChip.tsx b/web/src/components/StatusChip.tsx
new file mode 100644
index 00000000..09718e0
--- /dev/null
+++ b/web/src/components/StatusChip.tsx
@@ -0,0 +1,41 @@
+// A status indicator that is ALWAYS icon + text ? never icon-only (HCI4D guidance for non-
tech-savvy

```

```

+// users, FRIENDLY_AND_MULTILINGUAL §4: pair every icon with a word, don't rely on color
alone). Used
+// for the ingest "working / couldn't process" states and the build "stitching / ready /
failed" states.
+import type { ReactNode } from "react";
+
+type Tone = "info" | "success" | "error";
+
+const TONE: Record<Tone, string> = {
+  info: "bg-ink/5 text-ink/70",
+  success: "bg-green/15 text-green",
+  error: "bg-red-100 text-red-800",
+};
+
+interface Props {
+  /** A glyph or the <Spinner/> ? decorative; the label carries the meaning for screen readers.
*/
+  icon: ReactNode;
+  label: string;
+  tone?: Tone;
+}
+
+export function StatusChip({ icon, label, tone = "info" }: Props) {
+  return (
+    <span className={`inline-flex items-center gap-1.5 rounded-full px-3 py-1 text-sm font-
medium ${TONE[tone]}`}>
+      <span aria-hidden="true" className="inline-flex">
+        {icon}
+      </span>
+      <span>{label}</span>
+    </span>
+  );
+}
+
+/** Indeterminate spinner ? the engine reports coarse phase WORDS, not a percentage, so
progress is a
+ * spinner + the phase label rather than a misleading progress bar. */
+export function Spinner() {
+  return (
+    <span
+      className="inline-block h-3.5 w-3.5 animate-spin rounded-full border-2 border-ink/20
border-t-ink/70"
+      aria-hidden="true"
+    />
+  );
+}

```

224. assistant (2026-06-21T15:28:40.612Z)

Clean diff. One tidy-up before review: the `success` tone in `StatusChip` is currently unused (the done header uses an inline ?). Let me drop it to avoid dead code (trivial to re-add):

225. user (2026-06-21T15:28:43.404Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\StatusChip.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

226. assistant (2026-06-21T15:28:49.158Z)

Now the A8 adversarial review (ally/correctness + faithfulness):

227. user (2026-06-21T15:29:10.435Z)

Workflow launched in background. Task ID: whphp65hw

Summary: Adversarial review of the A8 status-chips + reassurance diff
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_268ea95a-a09
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\sa8-review-wf_268ea95a-a09.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\sa8-review-wf_268ea95a-a09.js"} to iterate without resending the script.)
Run ID: wf_268ea95a-a09
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\sa8-review-wf_268ea95a-a09.js", resumeFromRunId: "wf_268ea95a-a09"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

228. assistant (2026-06-21T15:29:20.794Z)

While the A8 review runs, let me re-verify tests after the `success`-tone removal, and prep B3 by reading the `site/index.html` head/structure.

229. user (2026-06-21T15:29:31.996Z)

Test Files 15 passed (15)
Tests 141 passed (141)
tsc OK

230. user (2026-06-21T15:29:36.968Z)

```
1      <!doctype html>
2      <html lang="en">
3      <head>
4      <meta charset="utf-8" />
5      <meta name="viewport" content="width=device-width, initial-scale=1" />
6      <title>KhelSutra ? every rally indexed, the dead time gone</title>
7      <meta name="description" content="KhelSutra turns a full badminton match into a clean
index of rallies with the dead time stripped out ? a highlight reel you can watch and download.
Invite-only alpha, Bengaluru." />
8      <meta property="og:title" content="KhelSutra ? every rally indexed, the dead time gone"
/>
9      <meta property="og:description" content="A full match becomes a clean highlight reel ?
only the real play, no dead time. Invite-only alpha for academies and players in Bengaluru." />
10     <meta property="og:type" content="website" />
11     <meta property="og:url" content="https://khelsutra.guru" />
12     <meta property="og:image" content="https://khelsutra.guru/og.png" />
13     <meta property="og:image:width" content="1200" />
14     <meta property="og:image:height" content="630" />
15     <meta name="twitter:card" content="summary_large_image" />
16     <meta name="twitter:title" content="KhelSutra ? every rally indexed, the dead time gone"
/>
17     <meta name="twitter:description" content="A full match becomes a clean highlight reel ?
only the real play, no dead time. Invite-only alpha, Bengaluru." />
18     <meta name="twitter:image" content="https://khelsutra.guru/og.png" />
19     <meta name="theme-color" content="#0C261F" />
20     <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
21     <link rel="preconnect" href="https://fonts.googleapis.com" />
22     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
23     <link href="https://fonts.googleapis.com/css2?family=PlusJakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
24     <style>
25     :root{
```

```

26      --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
27      --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
28      --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
29      --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
30      --r:14px; --rs:10px; --maxw:1080px;
31      --font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,Helvetica,Arial,sans-serif;
32    }
33    *{box-sizing:border-box}
34    html{scroll-behavior:smooth}
35    body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.65;-webkit-font-smoothing:antialiased}
36    a{color:inherit}
37    .wrap{max-width:var(--maxw);margin:0 auto;padding:0 22px}
38    h1,h2,h3{line-height:1.15;margin:0;letter-spacing:-.02em}
39    h1{font-size:clamp(2rem,5vw,3.4rem);font-weight:800}
40    h2{font-size:clamp(1.5rem,3.2vw,2.2rem);font-weight:700}
41    h3{font-size:1.15rem;font-weight:700}
42    p{margin:.6rem 0}
43    .btn{display:inline-flex;align-items:center;gap:.5rem;font-weight:600;font-
size:1rem;border-radius:999px;padding:.78rem 1.4rem;text-decoration:none;border:1px solid
transparent;cursor:pointer;transition:.15s}
44    .btn-primary{background:var(--green);color:#04140D}
45    .btn-primary:hover{background:var(--green-d)}
46    .btn-ghost{background:transparent;border-color:rgba(255,255,255,.28);color:var(--on-
dark)}
47    .btn-ghost:hover{border-color:rgba(255,255,255,.6)}
48    .btn-dark{background:var(--ink);color:#fff}
49    .btn-dark:hover{background:var(--ink2)}
50    .btn[disabled]{opacity:.75;cursor:progress}
51    /* in-flight spinner for the request-access submit */
52    .spin{display:inline-block;width:1em;height:1em;border:2px solid currentColor;border-
right-color:transparent;border-radius:50%;animation:spin .6s linear infinite}
53    @keyframes spin{to{transform:rotate(360deg)}}
54    .eyebrow{display:inline-flex;align-items:center;gap:.5rem;font-size:.82rem;font-
weight:600;letter-spacing:.02em;
55      background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.3);padding:.3rem .8rem;border-radius:999px}
56
57    /* header */
58    header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
59    .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
60    .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-
size:1.18rem;letter-spacing:-.02em;text-decoration:none}
61    .brand .dot{color:var(--green)}
62    .nav-links{display:flex;align-items:center;gap:1.6rem}
63    .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
64    .nav-links a:hover{color:var(--tx)}
65    .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px
0 7px 12px;border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
66
67    /* hero */
68    .hero{background:linear-gradient(160deg,var(--ink) 0%,var(--ink2)
100%);color:var(--on-dark);position:relative;overflow:hidden}
69    .hero .wrap{padding-top:74px;padding-bottom:88px;position:relative;z-index:2}
70    .hero .eyebrow{background:rgba(199,242,176,.12);color:var(--lime);border-
color:rgba(199,242,176,.25)}

```

231. assistant (2026-06-21T15:30:20.646Z)

B3 is the next item but it carries an explicit open owner decision (the catalog-hoist approach) and is architecturally significant ? I'll surface that after A8 merges. Let me wait for the A8 review.

232. user (2026-06-21T15:33:53.214Z)

<retrieval_status>success</retrieval_status>

<task_id>whphp65hw</task_id>

<task_type>local_workflow</task_type>

<status>completed</status>

<output>

```
{
  "summary": "Adversarial review of the A8 status-chips + reassurance diff",
  "agentCount": 2,
  "logs": [],
  "result": [
    {
      "lens": "a11y-correctness",
      "summary": "A8 reviewed and verified clean.",
      "findings": [
        {
          "severity": "minor",
          "file": "web/src/components/CompileResult.tsx",
          "title": "aria-live on conditionally-mounted building section; done/error has none",
          "detail": "IngestPanel uses a stable always-mounted aria-live region. CompileResult puts aria-live on the building section only, and done/error has none, so SRs may not announce the terminal status. Tests assert text not announcement. Minor.",
          "location": "line 28 and lines 36-40",
          "suggestion": "Use one stable always-mounted aria-live wrapper, or add aria-live to the done/error section."
        }
      ]
    },
    {
      "lens": "faithfulness",
      "summary": "A8 faithful and verified locally.",
      "findings": [
        {
          "severity": "nit",
          "file": "web/src/i18n/locales/en/common.json",
          "location": "result.buildingReassure line 63",
          "title": "under a minute is the one timed promise",
          "detail": "Only line naming a time. Hedge usually is honest and stitch is fast concat. A slow box or long reel can exceed a minute. kn and hi share it.",
          "suggestion": "Optional. Drop the hard number to match ingest.reassure. As is is fine."
        }
      ]
    }
  ]
}
```

</output>

233. assistant (2026-06-21T15:34:18.930Z)

A8 review: faithful + clean, two small items worth folding (both improve a11y/honesty, which the owner's launch bar values):

1. **minor** ? the done/error CompileResult section lacks `aria-live` (only the building card has it), so a screen reader may not announce the terminal status.
2. **nit** ? `result.buildingReassure` is the one hard timed promise ("under a minute"); soften to a hedge.

Applying both:

234. user (2026-06-21T15:34:21.635Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\CompileResult.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

235. user (2026-06-21T15:34:27.309Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

236. user (2026-06-21T15:34:45.103Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

237. user (2026-06-21T15:34:51.391Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

238. assistant (2026-06-21T15:34:57.289Z)

The A8 test asserts the old reassurance copy ? update it to match:

239. user (2026-06-21T15:34:59.264Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\a8.status.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

240. user (2026-06-21T15:35:18.059Z)

```
Test Files   15 passed (15)
   Tests    141 passed (141)
tsc OK
? built in 1.28s
```

241. assistant (2026-06-21T15:35:26.184Z)

141 tests, tsc, build all green after folding the A8 findings. Committing A8:

242. user (2026-06-21T15:35:28.769Z)

```
branch: feat/a8-status-chips
web/src/components/CompileResult.tsx
web/src/components/IngestPanel.tsx
web/src/components/StatusChip.tsx
web/src/components/a8.status.test.tsx
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
--- base check (only my work) ---
```

243. user (2026-06-21T15:35:42.894Z)

```
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/a8-status-chips -> feat/a8-status-chips
```

244. user (2026-06-21T15:35:59.175Z)

<https://github.com/avidullu/khelsutra/pull/63>

245. assistant (2026-06-21T15:36:04.095Z)

PR [#63](<https://github.com/avidullu/khelsutra/pull/63>) created. Marking A8 ? in the tracker:

246. user (2026-06-21T15:36:06.211Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

247. user (2026-06-21T15:36:15.781Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

248. user (2026-06-21T15:36:51.352Z)

```
pushed
web    pending 0
https://github.com/avidullu/khelsutra/actions/runs/27909148385/job/82583116449
site   pass    15s
https://github.com/avidullu/khelsutra/actions/runs/27909148385/job/82583116448
Workers Builds: hidden-king-khelsutra    pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/33bb9960-d839-41d5-958c-57e77871035c
```

249. user (2026-06-21T15:37:19.678Z)

```
poll 1: web=pending cf=pass
poll 2: web=pass cf=pass
=== final ===
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/33bb9960-d839-41d5-958c-57e77871035c
site   pass    15s
https://github.com/avidullu/khelsutra/actions/runs/27909148385/job/82583116448
web    pass    32s
https://github.com/avidullu/khelsutra/actions/runs/27909148385/job/82583116449
```

250. assistant (2026-06-21T15:37:24.322Z)

All green. Merging A8:

251. user (2026-06-21T15:37:32.758Z)

```
create mode 100644 web/src/components/StatusChip.tsx
create mode 100644 web/src/components/a8.status.test.tsx
92a6c45 feat(web): A8 ? background-processing reassurance + icon+text status chips (#63)
501c014 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
(#62)
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
```

252. assistant (2026-06-21T15:38:13.703Z)

A8 merged (#63 ? `92a6c45`). **All three SPA UX A-items (A4, A5, A8) are done and on master.**

253. user (2026-06-21T15:38:14.786Z)

Updated task #3 status

254. user (2026-06-21T15:38:15.479Z)

Chapter marked: "B3 / North-Star decision point". Continue your current work.

255. assistant (2026-06-21T15:38:26.818Z)

Three clean PRs merged this session (A4 [#61](https://github.com/avidullu/khelsutra/pull/61), A5 [#62](https://github.com/avidullu/khelsutra/pull/62), A8

[#63](https://github.com/avidullu/khelsutra/pull/63)) ? each browser-verified, adversarially reviewed, CI-green, tracker updated.

The next items diverge, and two carry genuine calls that are yours. **B3** is flagged in your handoff S3 as an open decision ("confirm the catalog-hoist"), it's architecturally significant (adds a build step to the deliberately build-free `site/`), and it's a large translation-infra lift. **T4** (in-UI upload) is your stated North-Star #1 and is fully autonomous. So before I commit to the bigger work, let me confirm direction.

256. user (2026-06-21T16:18:49.053Z)

Your questions have been answered: "A4/A5/A8 are merged. Which should I build next?"="1 now but do record 4, 2 and 3 as immediate next or feel free to spin off a parallel session to complete them if thats reasonable", "For B3, where should the single source of truth for locale catalogs live? (Applies whenever B3 runs.)"="Hoist to repo-root /locales/". You can now continue with these answers in mind.

257. assistant (2026-06-21T16:20:46.874Z)

The owner confirmed: **build T4 (North Star) next**; keep B3, MULTILINGUAL Phase A, and T11 recorded as immediate-next (and I can spin them off as parallel sessions once T4 is in, to avoid catalog-file races); and **B3 will hoist catalogs to repo-root `locales/`** (decision locked).

Let me start T4. First, read the API types to slot in the upload helpers.

258. user (2026-06-21T16:20:47.323Z)

Updated task #5 status

259. user (2026-06-21T16:20:48.771Z)

```
1      // Types mirror the engine's verified contract (badminton-highlight-indexer).
2      // Anchors: backend/infrastructure/database.py:124-135 (play_segments),
3      // backend/main.py:331-396 (query/compile), :307-328 (highlights), :121 (config).
4
5      export interface RallyMetadata {
6          /** Gemini's shuttle_exchange_count (fallback max(3, dur/0.8)); absent on some
7          detectors. */
8          shot_count?: number;
9          /** Gemini confidence STRING (often "Unknown") ? not a numeric meter. */
10         shot_count_confidence?: string;
11         detector?: string;
12         [key: string]: unknown;
13     }
14
15     export interface RallySegment {
16         /** The integer the UI selects and passes to /api/compile as segment_ids. */
17         id: number;
18         start_time: number;
19         end_time: number;
20         duration: number;
21         /** motion-segmenter FABRICATION (random) ? DO NOT surface (see
22         PER_RALLY_SELECTION.md). */
23         server: string | null;
24         /** motion-segmenter FABRICATION (random) ? DO NOT surface. */
25         receiver: string | null;
26         metadata: RallyMetadata;
27         /** motion-only fabricated sub-events ? DO NOT surface. */
28         events?: unknown[];
29     }
30
31     export interface QueryResponse {
32         play_segments: RallySegment[];
33     }
```

```

32
33     export interface CompileResponse {
34         status: string;
35         /** server-local path (NOT a URL) ? build the download URL with highlightUrl(). */
36         filepath: string;
37     }
38
39     export interface EngineConfig {
40         stitching?: {
41             /** The shot-count floor /api/compile silently enforces ? surface it, don't hide it.
42             */
43             min_shot_count?: number;
44             [key: string]: unknown;
45         };
46         [key: string]: unknown;
47     }
48
49     /** POST /api/process ? 202 [backend/main.py:260]. The job is queued; poll GET
50     /api/jobs/{job_id}. */
51     export interface ProcessResponse {
52         job_id: string;
53         /** Always "queued" at submit. */
54         status: string;
55         /** Relative poll path, e.g. "/api/jobs/<id>". */
56         poll: string;
57     }
58
59     /** GET /api/jobs/{job_id} [backend/main.py:303]. Two status layers:
60     * `status` = the EXECUTION state; `result.status` = the pipeline VERDICT
61     (success|failed).
62     * A `done` job whose `result.status` === "failed" (or with no video_id) is a success-
63     shaped
64     * FAILURE ? the UI must not treat it as a load. */
65     export interface JobStatus {
66         job_id: string;
67         status: "queued" | "running" | "done" | "failed";
68         /** Free-text coarse phase ("hashing", "segmenting (gemini)", "finished") ? NOT a
69         percentage. */
70         progress?: string | null;
71         /** The canonical video_id, surfaced top-level on success (also in result.video_id).
72         */
73         video_id?: string | null;
74         /** Execution error (worker crash / unexpected) when status === "failed". */
75         error?: string | null;
76         result?: { status?: string; video_id?: string; message?: string } | null;
77     }
78
79

```

260. user (2026-06-21T16:20:49.467Z)

Chapter marked: "T4 ? in-UI file upload (North Star)". Continue your current work.

261. assistant (2026-06-21T16:20:55.713Z)

Now I have the full T4 contract. Let me add the upload types, then build the upload client, hook, and wire IngestPanel. First, types:

262. user (2026-06-21T16:21:00.668Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\types.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

263. assistant (2026-06-21T16:22:10.891Z)

Now build the chunked-upload client. Add the upload helpers + orchestrator to `client.ts`:

264. user (2026-06-21T16:22:13.820Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\client.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

265. user (2026-06-21T16:22:39.348Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\client.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

266. assistant (2026-06-21T16:22:44.337Z)

Now the `useUpload` hook:

267. assistant (2026-06-21T16:22:57.913Z)

```
// Drives the in-UI file UPLOAD half of ingest (tracker T4): chunk a local file up to the
engine's
// /api/upload/* endpoints, report byte progress, then hand the returned server PATH to the
existing
// processing back-half (useIngestJob.submit). Alpha users have a FILE, not a gs:// URI ? this
is the
// keystone that lets them point the tool at it from the browser.
//
// Kept i18n-FREE (returns stable IngestErrorCodes via classifyError, not prose) so it unit-
tests
// without a translation context ? IngestPanel maps codes to localized strings via errorText.
Abort
// is an AbortController: cancel/unmount/a superseding pick stops the in-flight upload and the
// orchestrator best-effort DELETes the server-side partial.
import { useCallback, useEffect, useRef, useState } from "react";
import { uploadFile } from "../api/client";
import { classifyError, type IngestError } from "../lib/errors";
import { log, newCorrelationId } from "../lib/log";

export type UploadPhase =
  | { status: "idle" }
  | { status: "uploading"; pct: number; filename: string }
  | { status: "error"; error: IngestError };

export function useUpload(onComplete: (path: string) => void) {
  const [phase, setPhase] = useState<UploadPhase>({ status: "idle" });
  const ctrlRef = useRef<AbortController | null>(null);
  // Keep the latest onComplete without making start depend on it (a parent re-render won't
restart).
  const onCompleteRef = useRef(onComplete);
  onCompleteRef.current = onComplete;

  const stop = useCallback(() => {
    ctrlRef.current?.abort();
    ctrlRef.current = null;
  }, []);

  // Abort any in-flight upload on unmount.
  useEffect(() => stop, [stop]);

  const start = useCallback(
    (file: File) => {
      // A 0-byte "video" is never valid ? reject before touching the network (reuse invalidUri
copy).
      if (!file || file.size === 0) {
        setPhase({ status: "error", error: { code: "invalidUri" } });
      }
    }
  );
}
```

```

    return;
}

stop(); // supersede any prior upload
const ctrl = new AbortController();
ctrlRef.current = ctrl;
const cid = newCorrelationId();
setPhase({ status: "uploading", pct: 0, filename: file.name });
log("info", "upload.submit_start", { cid, filename: file.name, size: file.size });

void (async () => {
  try {
    const res = await uploadFile(file, {
      cid,
      signal: ctrl.signal,
      onProgress: ({ sentBytes, totalBytes }) => {
        if (ctrl.signal.aborted) return;
        const pct = totalBytes > 0 ? Math.min(100, Math.round((sentBytes / totalBytes) *
100)) : 0;
        setPhase({ status: "uploading", pct, filename: file.name });
      },
    });
    if (ctrl.signal.aborted) return;
    setPhase({ status: "idle" }); // hand off ? the engine processing phase takes over
    onCompleteRef.current(res.path);
  } catch (err) {
    // User-cancelled (abort) is silent, not an error.
    if (ctrl.signal.aborted || (err instanceof DOMException && err.name === "AbortError"))
return;
    setPhase({ status: "error", error: classifyError(err) });
    log("error", "upload.failed", { cid, filename: file.name, error: String(err) });
  }
})();
},
[stop],
);

const cancel = useCallback(() => {
  stop();
  setPhase({ status: "idle" });
  log("info", "upload.cancel", {});
}, [stop]);

const reset = useCallback(() => {
  stop();
  setPhase({ status: "idle" });
}, [stop]);

const busy = phase.status === "uploading";
return { phase, start, cancel, reset, busy };
}

```

268. user (2026-06-21T16:22:57.928Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra\web\src\hooks\useUpload.ts (file state is current in your context ? no need to Read it back)

269. assistant (2026-06-21T16:23:03.219Z)

Now rewrite IngestPanel to add the upload mode. Let me read its current state after A8:

270. user (2026-06-21T16:23:03.646Z)

1 // The front-half ingest screen (appliance S1/S2, tracker B-P2). Point the tool at a

```

video ? a
2      // `gs://` bucket URI or a path on the engine host ? and it submits to POST
/api/process, shows
3      // live progress while polling GET /api/jobs/{id}, and hands the resulting video_id to
the existing
4      // rally-selection back-half (App lifts ?video=<id>). Honest by construction: the engine
reports
5      // coarse phase WORDS (not a %), and a success-shaped failure (done but no rallies) is
shown, never
6      // silently treated as a load.
7      import { useState } from "react";
8      import type { FormEvent } from "react";
9      import { useTranslation } from "react-i18next";
10     import { useIngestJob } from "../hooks/useIngestJob";
11     import { errorText } from "../lib/errorText";
12     import { StatusChip, Spinner } from "../StatusChip";
13
14     interface Props {
15       /** Called with the engine's video_id once a submitted job finishes successfully. */
16       onLoaded: (videoId: string) => void;
17     }
18
19     export function IngestPanel({ onLoaded }: Props) {
20       const { t } = useTranslation();
21       const [uri, setUri] = useState("");
22       const { phase, submit, cancel, reset, busy } = useIngestJob(onLoaded);
23
24       const onSubmit = (e: FormEvent) => {
25         e.preventDefault();
26         submit(uri);
27       };
28
29       // Shared mapping with the build flow (lib/errorText): `engine` failures carry the
engine's own
30       // message (a 400 scheme/path detail, a worker error); every other code maps to a
friendly
31       // localized line ? the network case especially, since this is the first screen a
fresh user hits
32       // and "is the engine running?" must read plainly.
33       const errorMsg = phase.status === "error" ? errorText(t, phase.error) : null;
34
35       return (
36         <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
testid="ingest-panel">
37           <h2 className="text-lg font-bold">{t("ingest.title")}</h2>
38           <p className="mt-1 max-w-2xl text-sm text-ink/60">{t("ingest.intro")}</p>
39
40           <form onSubmit={onSubmit} className="mt-3 flex flex-wrap items-center gap-2">
41             <input
42               type="text"
43               value={uri}
44               onChange={(e) => setUri(e.target.value)}
45               placeholder={t("ingest.uriPlaceholder")}
46               aria-label={t("ingest.uriAriaLabel")}
47               disabled={busy}
48               className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-
white px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
49             />
50             <button
51               type="submit"
52               disabled={busy}
53               className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-
white disabled:opacity-40"
54             >
55               {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}

```

```

56         </button>
57         {busy && (
58             <button
59                 type="button"
60                 onClick={cancel}
61                 className="min-h-11 rounded-xl border border-black/15 px-4 py-2 text-sm
hover:border-green"
62             >
63                 {t("ingest.cancel")}
64             </button>
65         )}
66     </form>
67
68     <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>
69
70     {/* Live status (aria-live so screen readers hear progress) as icon+text chips ?
never icon-only
71         (A8). Indeterminate: the engine reports phase words ("hashing", "segmenting"),
not a %. */}
72     <div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
73         {busy && (
74             <div>
75                 <StatusChip
76                     tone="info"
77                     icon={<Spinner />}
78                     label={
79                         t("ingest.working") +
80                         (phase.status === "polling" && phase.progress
81                             ? ` · ${t("ingest.progress", { progress: phase.progress })}`
82                             : "")
83                     }
84                 />
85                 {/* Reassurance for slow uplinks: the job runs on the server, so it's safe
to wait. */}
86                 <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
87             </div>
88         )}
89         {phase.status === "error" && (
90             <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-
red-800" data-testid="ingest-error">
91                 <StatusChip tone="error" icon="?" label={t("ingest.statusFailed")} />
92                 <p className="mt-2">{errorMsg}</p>
93                 <button
94                     type="button"
95                     onClick={reset}
96                     className="mt-2 inline-flex min-h-11 items-center rounded-lg border
border-red-300 px-3 text-sm hover:bg-red-100"
97                 >
98                     {t("ingest.retry")}
99                 </button>
100             </div>
101         )}
102     </div>
103 </section>
104 );
105 }
106

```

271. assistant (2026-06-21T16:24:35.414Z)

Now I'll rewrite IngestPanel with a **both-visible** design (file upload primary, cloud-link secondary) ? this adds the upload path while keeping the existing URI input present, so all existing IngestPanel/A8 tests still pass. Wiring `useUpload` ? on complete ? `submit(path)`:

272. assistant (2026-06-21T16:25:00.277Z)

```

// The front-half ingest screen (appliance S1/S2; tracker B-P2 + T4). Two ways to point the tool
at a
// video: UPLOAD a local file (primary ? alpha users have a file, not a URI; chunked to the
engine's
// /api/upload/* endpoints) or paste a `gs://` bucket URI / host path (secondary). Both converge
on
// the SAME back-half: POST /api/process ? poll GET /api/jobs/{id} ? hand the video_id to App.
Honest
// by construction: the engine reports coarse phase WORDS (not a %), and a success-shaped
failure
// (done but no rallies) is shown, never silently treated as a load.
import { useState } from "react";
import type { ChangeEvent, FormEvent } from "react";
import { useTranslation } from "react-i18next";
import { useIngestJob } from "../hooks/useIngestJob";
import { useUpload } from "../hooks/useUpload";
import { errorText } from "../lib/errorText";
import { StatusChip, Spinner } from "../StatusChip";

interface Props {
  /** Called with the engine's video_id once a submitted job finishes successfully. */
  onLoaded: (videoId: string) => void;
}

export function IngestPanel({ onLoaded }: Props) {
  const { t } = useTranslation();
  const [uri, setUri] = useState("");
  const { phase, submit, cancel: cancelIngest, reset: resetIngest, busy: ingestBusy } =
    useIngestJob(onLoaded);
  // On upload completion, feed the returned server PATH straight into the engine processing
  back-half.
  const upload = useUpload((path) => submit(path));
  const busy = ingestBusy || upload.busy;

  const onSubmitUri = (e: FormEvent) => {
    e.preventDefault();
    submit(uri);
  };

  const onFile = (e: ChangeEvent<HTMLInputElement>) => {
    const file = e.target.files?.[0];
    if (file) upload.start(file);
    e.target.value = ""; // let re-picking the same file fire change again
  };

  const cancelAll = () => {
    upload.cancel();
    cancelIngest();
  };

  const resetAll = () => {
    upload.reset();
    resetIngest();
  };

  // Shared mapping with the build flow (lib/errorText): an `engine` failure carries the
  engine's own
  // message (a 400 scheme/path/extension detail, a worker error); every other code maps to a
  friendly
  // localized line. Surface whichever half failed (upload or engine) ? they're mutually
  exclusive.
  const errorState = upload.phase.status === "error" ? upload.phase.error : phase.status ===
  "error" ? phase.error : null;
  const errorMsg = errorState ? errorText(t, errorState) : null;

  return (
    <section className="mt-6 rounded-2xl border border-black/10 bg-white p-5" data-
    testid="ingest-panel">

```

```

<h2 className="text-lg font-bold">{t("ingest.title")}</h2>
<p className="mt-1 max-w-2xl text-sm text-ink/60">{t("ingest.intro")}</p>

{/* PRIMARY: upload a local file (T4). A native file input, visually a button (?44px, A4).
*/}
<div className="mt-4">
  <label
    className={
      "inline-flex min-h-11 items-center rounded-xl bg-ink px-4 py-2 text-sm font-semibold
text-white hover:bg-ink2 " +
      (busy ? "pointer-events-none opacity-40" : "cursor-pointer")
    }
  >
    {t("ingest.chooseFile")}
    <input
      type="file"
      accept=".mp4, .mov, video/mp4, video/quicktime"
      aria-label={t("ingest.uploadAria")}
      disabled={busy}
      onChange={onFile}
      className="sr-only"
    />
  </label>
  <p className="mt-2 text-xs text-ink/40">{t("ingest.fileHint")}</p>
</div>

{/* SECONDARY: or point at a cloud bucket / host path. */}
<div className="mt-4 border-t border-black/5 pt-4">
  <p className="text-xs font-semibold uppercase tracking-wide text-
ink/40">{t("ingest.orLink")}</p>
  <form onSubmit={onSubmitUri} className="mt-2 flex flex-wrap items-center gap-2">
    <input
      type="text"
      value={uri}
      onChange={(e) => setUri(e.target.value)}
      placeholder={t("ingest.uriPlaceholder")}
      aria-label={t("ingest.uriAriaLabel")}
      disabled={busy}
      className="min-h-11 min-w-[18rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green disabled:opacity-50"
    />
    <button
      type="submit"
      disabled={busy}
      className="min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
    >
      {phase.status === "submitting" ? t("ingest.submitting") : t("ingest.submit")}
    </button>
  </form>
  <p className="mt-2 text-xs text-ink/40">{t("ingest.hint")}</p>
</div>

{/* Live status (aria-live so screen readers hear progress) as icon+text chips ? never
icon-only
(A8). Upload shows a determinate % bar; the engine phase is indeterminate (phase
words). */}
<div aria-live="polite" className="mt-3 text-sm" data-testid="ingest-status">
  {upload.phase.status === "uploading" && (
    <div data-testid="upload-progress">
      <StatusChip tone="info" icon={<Spinner />} label={t("ingest.uploading", { pct:
upload.phase.pct })} />
    </div>
    <div
      className="mt-2 h-1.5 w-full max-w-sm overflow-hidden rounded-full bg-black/10"
      role="progressbar"

```



```

        aria-valuenow={upload.phase.pct}
        aria-valuemin={0}
        aria-valuemax={100}
      >
        <div className="h-full bg-green transition-all" style={{ width:
`${upload.phase.pct}%` }} />
      </div>
      <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
      <button
        type="button"
        onClick={cancelAll}
        className="mt-2 inline-flex min-h-11 items-center rounded-xl border border-
black/15 px-4 text-sm hover:border-green"
      >
        {t("ingest.cancel")}
      </button>
    </div>
  )}
  {ingestBusy && (
    <div>
      <StatusChip
        tone="info"
        icon={<Spinner />}
        label={
          t("ingest.working") +
          (phase.status === "polling" && phase.progress
            ? ` . ${t("ingest.progress", { progress: phase.progress })}`
            : "")
        }
      />
      /* Reassurance for slow uplinks: the job runs on the server, so it's safe to wait.
    */
    <p className="mt-2 text-xs text-ink/50">{t("ingest.reassure")}</p>
    <button
      type="button"
      onClick={cancelAll}
      className="mt-2 inline-flex min-h-11 items-center rounded-xl border border-
black/15 px-4 text-sm hover:border-green"
    >
      {t("ingest.cancel")}
    </button>
    </div>
  )}
  {errorMsg && (
    <div className="rounded-lg border border-red-200 bg-red-50 px-3 py-2 text-red-800"
data-testid="ingest-error">
      <StatusChip tone="error" icon="?" label={t("ingest.statusFailed")} />
      <p className="mt-2">{errorMsg}</p>
      <button
        type="button"
        onClick={resetAll}
        className="mt-2 inline-flex min-h-11 items-center rounded-lg border border-red-300
px-3 text-sm hover:bg-red-100"
      >
        {t("ingest.retry")}
      </button>
    </div>
  )}
</div>
</section>
);
}

```

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

274. assistant (2026-06-21T16:25:08.923Z)

Now the 5 upload keys (en/kn/hi):

275. user (2026-06-21T16:25:12.088Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

276. user (2026-06-21T16:25:34.757Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

277. user (2026-06-21T16:25:45.146Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

278. assistant (2026-06-21T16:25:53.257Z)

Now T4 tests. Let me check the existing client test conventions first:

279. user (2026-06-21T16:25:53.716Z)

```
1      import { describe, it, expect, vi, afterEach } from "vitest";
2      import { listRallies, compileReel, highlightUrl, getConfig, minShotCount, ApiError }
from "./client";
3
4      type FetchFn = typeof fetch;
5
6      function mockFetch(status: number, json: unknown, text?: string): FetchFn {
7          return vi.fn(async () => ({
8              ok: status >= 200 && status < 300,
9              status,
10             json: async () => json,
11             text: async () => text ?? JSON.stringify(json),
12             })) as unknown as FetchFn;
13     }
14
15     function lastCall(f: FetchFn): [string, RequestInit] {
16         const calls = (f as unknown as { mock: { calls: [string, RequestInit][] } })
17         .mock.calls;
18         return calls[calls.length - 1];
19     }
20
21     afterEach(() => {
22         vi.restoreAllMocks();
23         vi.unstubAllGlobals();
24     });
25
26     describe("highlightUrl", () => {
27         it("builds an encoded same-origin path", () => {
28             expect(highlightUrl("abc123", "my
reel.mp4")).toBe("/api/highlights/abc123/my%20reel.mp4");
29         });
30     });
31
32     describe("listRallies", () => {
33         it("POSTs video_id to /api/query and returns play_segments", async () => {
34             const seg = { id: 1, start_time: 0, end_time: 5, duration: 5, server: null,
```

```

receiver: null, metadata: { shot_count: 7 } });
34     const f = mockFetch(200, { play_segments: [seg] });
35     vi.stubGlobal("fetch", f);
36
37     const rallies = await listRallies("vid");
38     expect(rallies).toHaveLength(1);
39     expect(rallies[0].id).toBe(1);
40
41     const [url, init] = lastCall(f);
42     expect(url).toBe("/api/query");
43     expect(init.method).toBe("POST");
44     expect(JSON.parse(init.body as string)).toEqual({ video_id: "vid" });
45     expect((init.headers as Record<string, string>)[ "x-correlation-id" ]).toBeTruthy();
46 });
47
48 it("returns [] when play_segments is missing", async () => {
49     vi.stubGlobal("fetch", mockFetch(200, {}));
50     expect(await listRallies("vid")).toEqual([]);
51 });
52 });
53
54 describe("compileReel", () => {
55     it("POSTs the selection to /api/compile", async () => {
56         const f = mockFetch(200, { status: "success", filepath: "/out/reel.mp4" });
57         vi.stubGlobal("fetch", f);
58
59         const res = await compileReel("vid", [1, 2, 3], "reel.mp4");
60         expect(res.status).toBe("success");
61
62         const [url, init] = lastCall(f);
63         expect(url).toBe("/api/compile");
64         expect(JSON.parse(init.body as string)).toEqual({
65             video_id: "vid",
66             segment_ids: [1, 2, 3],
67             output_filename: "reel.mp4",
68         });
69     });
70 });
71
72 describe("getConfig + minShotCount", () => {
73     it("reads the stitching floor", async () => {
74         vi.stubGlobal("fetch", mockFetch(200, { stitching: { min_shot_count: 4 } }));
75         const cfg = await getConfig();
76         expect(minShotCount(cfg)).toBe(4);
77     });
78
79     it("returns undefined when no floor is configured", async () => {
80         vi.stubGlobal("fetch", mockFetch(200, {}));
81         expect(minShotCount(await getConfig())).toBeUndefined();
82     });
83 });
84
85 describe("error handling (loud, never silent)", () => {
86     it("throws ApiError with status + correlation id on a non-ok response", async () => {
87         vi.stubGlobal("fetch", mockFetch(400, { detail: "bad" }, "bad request"));
88         await expect(listRallies("vid")).rejects.toMatchObject({ name: "ApiError", status:
400 });
89     });
90
91     it("throws ApiError on a network failure", async () => {
92         vi.stubGlobal("fetch", vi.fn(async () => { throw new Error("offline"); }) as unknown
as FetchFn);
93         await expect(getConfig()).rejects.toBeInstanceOf(ApiError);
94     });
95 });

```

280. assistant (2026-06-21T16:26:25.269Z)

Let me check how the existing hook test drives a hook (renderHook vs wrapper):

281. user (2026-06-21T16:26:26.606Z)

```

1      // @vitest-environment jsdom
2      //
3      // The ingest state machine: submit ? poll (queued/running) ? done | error. Drives the
recursive
4      // setTimeout poll loop with fake timers so each tick is deterministic, and pins the
load-bearing
5      // behaviours: the success-shaped-failure (done + no rallies ? emptyResult, never a
load), the
6      // two error surfaces (engine detail vs friendly network), and cancellation stopping the
loop.
7      import { describe, it, expect, vi, afterEach } from "vitest";
8      import { renderHook, act } from "@testing-library/react";
9      import { useIngestJob } from "../useIngestJob";
10     import type { JobStatus } from "../api/types";
11
12     type FetchFn = typeof fetch;
13
14     function httpOk(status: number, json: unknown) {
15       return { ok: status >= 200 && status < 300, status, json: async () => json, text:
async () => JSON.stringify(json) };
16     }
17
18     /** A fetch that answers POST /api/process with `process`, then walks `jobs` on each GET
/api/jobs/*. */
19     function fetchSeq(process: unknown, jobs: JobStatus[]): FetchFn {
20       let i = 0;
21       return vi.fn(async (url: string | URL, init?: RequestInit) => {
22         const u = String(url);
23         const method = init?.method ?? "GET";
24         if (u === "/api/process" && method === "POST") return process;
25         if (u.startsWith("/api/jobs/")) {
26           const body = jobs[Math.min(i, jobs.length - 1)];
27           i += 1;
28           return httpOk(200, body);
29         }
30         throw new Error(`unexpected fetch ${method} ${u}`);
31       }) as unknown as FetchFn;
32     }
33
34     /** Flush the submit microtasks, then walk the backoff ladder (1000 ? 1500 ? 2250 ? ?)
for n ticks. */
35     async function drain(ticks: number) {
36       await act(async () => {
37         await vi.advanceTimersByTimeAsync(0); // flush processVideo ? schedule the first
poll
38       });
39       let delay = 1000;
40       for (let k = 0; k < ticks; k += 1) {
41         await act(async () => {
42           await vi.advanceTimersByTimeAsync(delay);
43         });
44         delay = Math.min(delay * 1.5, 5000);
45       }
46     }
47
48     afterEach(() => {
49       vi.restoreAllMocks();

```

```

50     vi.unstubAllGlobals();
51     vi.useRealTimers();
52   });
53
54   describe("useIngestJob", () => {
55     it("rejects an empty URI before any network call", () => {

```

282. assistant (2026-06-21T16:26:35.299Z)

Now the T4 tests. First, the upload client (chunking + abort-cleanup + error):

283. assistant (2026-06-21T16:26:53.652Z)

```

// Chunked-upload client (T4): init ? sequential PUT parts (byte progress) ? complete, with a
// best-effort DELETE of the server-side partial on any failure. Pins the part slicing (sizes +
// strict 0,1,2 order), the progress callback, and that a mid-upload failure cleans up +
// rethrows.
import { describe, it, expect, vi, afterEach } from "vitest";
import { uploadFile, ApiError } from "../client";

type FetchFn = typeof fetch;
const MB = 1024 * 1024;
const ok = (j: unknown) => ({ ok: true, status: 200, json: async () => j, text: async () =>
JSON.stringify(j) });
const httpErr = (status: number, detail: string) => ({
  ok: false, status, json: async () => ({ detail }), text: async () => JSON.stringify({ detail
}),
});

afterEach(() => {
  vi.restoreAllMocks();
  vi.unstubAllGlobals();
});

/** A routing fetch over the /api/upload/* surface; records the order + sizes of the calls. */
function router(opts: { partFailsAt?: number; initStatus?: number } = {}) {
  const calls = { init: 0, parts: [] as number[], partSizes: [] as number[], complete: null as
number | null, deletes: 0 };
  const f = vi.fn(async (url: string | URL, init?: RequestInit) => {
    const u = String(url);
    const m = init?.method ?? "GET";
    if (u === "/api/upload/init" && m === "POST") {
      calls.init += 1;
      if (opts.initStatus) return httpErr(opts.initStatus, "Extension '.txt' not allowed");
      return ok({ upload_id: "up1", max_part_mb: 1, next_part: "/api/upload/up1/part/0" });
    }
    const part = u.match(/^\/api\/upload\/up1\/part\/(\d+)\$/);
    if (part && m === "PUT") {
      const idx = Number(part[1]);
      if (opts.partFailsAt === idx) return httpErr(413, "Part exceeds the per-part limit");
      const size = (init?.body as Blob).size;
      calls.parts.push(idx);
      calls.partSizes.push(size);
      return ok({ upload_id: "up1", received_parts: calls.parts.length, received_bytes: size });
    }
    if (u === "/api/upload/up1/complete" && m === "POST") {
      calls.complete = JSON.parse(init!.body as string).total_parts as number;
      return ok({ path: "/srv/uploads/match.mp4", video_id: "VID", size_bytes: 5 * MB });
    }
    if (u === "/api/upload/up1" && m === "DELETE") {
      calls.deletes += 1;
      return ok({ status: "aborted", upload_id: "up1" });
    }
    throw new Error(`unexpected fetch ${m} ${u}`);
  }) as unknown as FetchFn;

```

```

    return { f, calls };
}

const videoFile = (bytes: number, name = "match.mp4") =>
  new File([new Uint8Array(bytes)], name, { type: "video/mp4" });

describe("uploadFile", () => {
  it("slices into sequential parts ? max_part_mb, completes, and returns {path, video_id}",
  async () => {
    const { f, calls } = router();
    vi.stubGlobal("fetch", f);
    const progress: number[] = [];

    const res = await uploadFile(videoFile(2.5 * MB), { onProgress: (p) =>
    progress.push(p.sentBytes) });

    expect(calls.parts).toEqual([0, 1, 2]); // 2.5MB / 1MB = 3 strictly-sequential parts
    expect(calls.partSizes).toEqual([1 * MB, 1 * MB, 0.5 * MB]); // last part is the remainder
    expect(calls.complete).toBe(3); // total_parts handed to complete
    expect(progress[progress.length - 1]).toBe(2.5 * MB); // progress reaches 100%
    expect(res).toMatchObject({ path: "/srv/uploads/match.mp4", video_id: "VID" });
  });

  it("a single small file uploads as ONE part", async () => {
    const { f, calls } = router();
    vi.stubGlobal("fetch", f);
    await uploadFile(videoFile(0.3 * MB));
    expect(calls.parts).toEqual([0]);
    expect(calls.complete).toBe(1);
  });

  it("on a part failure it DELETES the server-side partial and rethrows the engine's reason",
  async () => {
    const { f, calls } = router({ partFailsAt: 1 });
    vi.stubGlobal("fetch", f);
    await expect(uploadFile(videoFile(2.5 * MB))).rejects.toMatchObject({ name: "ApiError",
    status: 413 });
    expect(calls.parts).toEqual([0]); // stopped at the failing part
    expect(calls.deletes).toBe(1); // partial cleaned up
  });

  it("an init rejection (bad extension) rethrows and never starts parts or a cleanup", async ()
  => {
    const { f, calls } = router({ initStatus: 400 });
    vi.stubGlobal("fetch", f);
    await expect(uploadFile(videoFile(1 * MB, "notes.txt"))).rejects.toBeInstanceOf(ApiError);
    expect(calls.parts).toEqual([]);
    expect(calls.deletes).toBe(0); // nothing to clean ? no upload_id yet
  });
});

```

284. user (2026-06-21T16:26:53.666Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra\web\src\api\upload.test.ts (file state is current in your context ? no need to Read it back)

285. assistant (2026-06-21T16:27:09.469Z)

Now the `useUpload` hook test:

286. assistant (2026-06-21T16:27:22.941Z)

```

// @vitest-environment jsdom
//

```

```

// The upload state machine (T4): start(file) ? uploading(%) ? hand the server PATH to
onComplete |
// error. Pins: an empty file is rejected before any network call, a happy upload calls
onComplete
// with the returned path and returns to idle, and an engine rejection surfaces a classified
error.
import { describe, it, expect, vi, afterEach } from "vitest";
import { renderHook, act, waitFor } from "@testing-library/react";
import { useUpload } from "../useUpload";

type FetchFn = typeof fetch;
const MB = 1024 * 1024;
const ok = (j: unknown) => ({ ok: true, status: 200, json: async () => j, text: async () =>
JSON.stringify(j) });
const httpErr = (status: number, detail: string) => ({
  ok: false, status, json: async () => ({ detail }), text: async () => JSON.stringify({ detail
}),
});

function uploadFetch(opts: { partFailsAt?: number } = {}): FetchFn {
  return vi.fn(async (url: string | URL, init?: RequestInit) => {
    const u = String(url);
    const m = init?.method ?? "GET";
    if (u === "/api/upload/init") return ok({ upload_id: "up1", max_part_mb: 1, next_part:
"/api/upload/up1/part/0" });
    const part = u.match(/\/part\/(\d+)\$/);
    if (part && m === "PUT") {
      if (opts.partFailsAt === Number(part[1])) return httpErr(413, "Part exceeds the per-part
limit");
      return ok({ upload_id: "up1", received_parts: 1, received_bytes: (init?.body as Blob).size
});
    }
    if (u.endsWith("/complete")) return ok({ path: "/srv/uploads/match.mp4", video_id: "VID",
size_bytes: 1 });
    if (m === "DELETE") return ok({ status: "aborted" });
    throw new Error(`unexpected ${m} ${u}`);
  }) as unknown as FetchFn;
}

const videoFile = (bytes: number, name = "match.mp4") => new File([new Uint8Array(bytes)], name,
{ type: "video/mp4" });

afterEach(() => {
  vi.restoreAllMocks();
  vi.unstubAllGlobals();
});

describe("useUpload", () => {
  it("rejects an empty file before any network call", () => {
    const f = vi.fn();
    vi.stubGlobal("fetch", f as unknown as FetchFn);
    const onComplete = vi.fn();
    const { result } = renderHook(() => useUpload(onComplete));

    act(() => result.current.start(videoFile(0)));

    expect(result.current.phase).toEqual({ status: "error", error: { code: "invalidUri" } });
    expect(f).not.toHaveBeenCalled();
    expect(onComplete).not.toHaveBeenCalled();
  });

  it("uploads a file and hands the returned server path to onComplete", async () => {
    vi.stubGlobal("fetch", uploadFetch());
    const onComplete = vi.fn();
    const { result } = renderHook(() => useUpload(onComplete));
  });
}

```

```

    act(() => result.current.start(videoFile(0.3 * MB)));
    await waitFor(() => expect(onComplete).toHaveBeenCalled("/srv/uploads/match.mp4"));
    expect(result.current.phase.status).toBe("idle"); // handed off ? the engine phase takes
over
  });

  it("surfaces a classified error when a part is rejected", async () => {
    vi.stubGlobal("fetch", uploadFetch({ partFailsAt: 0 }));
    const onComplete = vi.fn();
    const { result } = renderHook(() => useUpload(onComplete));

    act(() => result.current.start(videoFile(0.3 * MB)));
    await waitFor(() => expect(result.current.phase.status).toBe("error"));
    expect(onComplete).not.toHaveBeenCalled();
    // a 413 with a {detail} body classifies as an engine error (its message survives)
    expect(result.current.phase).toMatchObject({ status: "error", error: { code: "engine" } });
  });
});

```

287. user (2026-06-21T16:27:22.955Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra\web\src\hooks\useUpload.test.ts
(file state is current in your context ? no need to Read it back)

288. assistant (2026-06-21T16:28:09.232Z)

Now the IngestPanel upload?process?onLoaded integration test:

289. assistant (2026-06-21T16:28:23.244Z)

```

// @vitest-environment jsdom
//
// T4 end to end through IngestPanel: pick a local file ? it chunks up to /api/upload/* ? the
returned
// server PATH is fed to POST /api/process ? poll ? onLoaded(video_id). The keystone for alpha
users
// who have a FILE, not a gs:// URI. Also pins that the file picker is present + labelled
(a11y/A4).
import { describe, it, expect, vi, beforeEach, afterEach } from "vitest";
import { render, screen, cleanup, fireEvent, act, waitFor } from "@testing-library/react";
import i18n from "../i18n";
import { IngestPanel } from "../IngestPanel";

const MB = 1024 * 1024;
const ok = (j: unknown) => ({ ok: true, status: 200, json: async () => j, text: async () =>
JSON.stringify(j) });

let processBody: { video_path?: string } | null = null;

function uploadThenProcessFetch() {
  processBody = null;
  return vi.fn(async (url: string | URL, init?: RequestInit) => {
    const u = String(url);
    const m = init?.method ?? "GET";
    if (u === "/api/upload/init") return ok({ upload_id: "up1", max_part_mb: 1, next_part:
"/api/upload/up1/part/0" });
    if (u.includes("/api/upload/up1/part/")) return ok({ upload_id: "up1", received_parts: 1,
received_bytes: (init?.body as Blob).size });
    if (u.endsWith("/complete")) return ok({ path: "/srv/uploads/match.mp4", video_id: "PRE",
size_bytes: 1 });
    if (u === "/api/process" && m === "POST") {
      processBody = JSON.parse(init!.body as string);
      return ok({ job_id: "j", status: "queued", poll: "/api/jobs/j" });
    }
  })
}

```



```

    if (u.startsWith("/api/jobs/")) return ok({ job_id: "j", status: "done", video_id:
"VIDFINAL", result: { status: "success", video_id: "VIDFINAL" } });
    throw new Error(`unexpected fetch ${m} ${u}`);
  }) as unknown as typeof fetch;
}

const videoFile = (bytes: number) => new File([new Uint8Array(bytes)], "match.mp4", { type:
"video/mp4" });

const pickFile = (file: File) => {
  const input = screen.getByLabelText("Choose a video file to upload");
  Object.defineProperty(input, "files", { value: [file], configurable: true });
  fireEvent.change(input);
};

beforeEach(async () => {
  window.localStorage.clear();
  await i18n.changeLanguage("en");
});

afterEach(() => {
  cleanup();
  vi.restoreAllMocks();
  vi.unstubAllGlobals();
  vi.useRealTimers();
});

describe("T4: in-UI file upload", () => {
  it("offers a labelled file picker (present for a keyboard/SR user)", () => {
    vi.stubGlobal("fetch", vi.fn());
    render(<IngestPanel onLoaded={vi.fn()} />);
    expect(screen.getByLabelText("Choose a video file to upload")).toBeTruthy();
    expect(screen.getByText("Choose a video file")).toBeTruthy();
  });

  it("uploads the picked file, feeds the server path to /api/process, and loads the resulting
video_id", async () => {
    vi.useFakeTimers();
    vi.stubGlobal("fetch", uploadThenProcessFetch());
    const onLoaded = vi.fn();
    render(<IngestPanel onLoaded={onLoaded} />);

    pickFile(videoFile(0.3 * MB));

    // Flush the upload chain (init ? part ? complete) + the process submit ? schedules the
poll.
    await act(async () => {
      await vi.advanceTimersByTimeAsync(0);
      await vi.advanceTimersByTimeAsync(0);
    });
    // The uploaded server PATH (not the URI) is what gets processed.
    await waitFor(() => expect(processBody?.video_path).toBe("/srv/uploads/match.mp4"));

    // Poll tick ? done ? the job's canonical video_id is handed up.
    await act(async () => {
      await vi.advanceTimersByTimeAsync(1000);
    });
    expect(onLoaded).toHaveBeenCalledWith("VIDFINAL");
  });
});

```

290. user (2026-06-21T16:28:23.266Z)

File created successfully at:

C:\Users\avidu\Projects\khelsutra\web\src\components\upload.test.tsx (file state is current in

your context ? no need to Read it back)

291. user (2026-06-21T16:28:45.810Z)

```
? src/components/upload.test.tsx (2 tests | 1
failed) 5101ms
  × T4: in-UI file upload > uploads the picked file, feeds the server
path to /api/process, and loads the resulting video_id 5014ms
  Test Files  1 failed | 17 passed
(18)
    Tests  1 failed | 149 passed
(150)
=== tsc ===
tsc OK
=== build ===
? built in 1.14s
```

292. assistant (2026-06-21T16:29:18.905Z)

One integration test failed ? `waitFor` doesn't advance fake timers (a known gotcha). Let me switch it to the manual drain pattern (like `useIngestJob.test`):

293. user (2026-06-21T16:29:22.690Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\upload.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

294. user (2026-06-21T16:29:33.226Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\upload.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

295. user (2026-06-21T16:29:45.019Z)

```
Test Files  18 passed (18)
    Tests  150 passed (150)
```

296. assistant (2026-06-21T16:29:56.969Z)

All 150 tests pass (+8 T4 tests), tsc + build green. Let me browser-verify the new upload UI renders (the actual upload?process flow is test-covered; a live upload needs a running engine).

297. user (2026-06-21T16:29:58.077Z)

Server not found. No running servers for this workspace.

298. assistant (2026-06-21T16:30:03.219Z)

The preview server stopped. Let me restart it and verify the T4 UI:

299. user (2026-06-21T16:30:06.539Z)

```
{
  "serverId": "001260a2-3d4b-4722-8222-5e253669c429",
  "port": 5174,
  "name": "khelsutra-web",
  "reused": false
}
Server started successfully on port 5174.
```

300. user (2026-06-21T16:30:11.105Z)

```
[1] RootWebArea: "KhelSutra Studio"
```

```

[5] main
[6] sectionheader
[7] none
[9] StaticText: "Khel"
[10] InlineTextBox: "Khel"
[11] StaticText: "?"
[12] InlineTextBox: "?"
[13] StaticText: "Sutra "
[14] InlineTextBox: "Sutra "
[15] StaticText: "Studio"
[16] InlineTextBox: "Studio"
[17] navigation: "Language"
[18] button: "English"
[19] StaticText: "English"
[20] InlineTextBox: "English"
[21] button: "?????"
[22] StaticText: "?????"
[23] InlineTextBox: "?????"
[24] button: "??????"
[25] StaticText: "??????"
[26] InlineTextBox: "??????"
[27] generic
[29] StaticText: "pick your rallies . alpha"
[30] InlineTextBox: "pick your rallies . alpha"
[31] heading: "Pick the rallies for your reel"
[32] StaticText: "Pick the rallies for your reel"
[33] InlineTextBox: "Pick the rallies for your reel"
[34] paragraph
[35] StaticText: "Filter by "
[36] InlineTextBox: "Filter by "
[37] strong
[38] StaticText: "rally length"
[39] InlineTextBox: "rally length"
[40] StaticText: " ? e.g. "
[41] InlineTextBox: " ? e.g. "
[42] emphasis
[43] StaticText: "?top 15 longest?"
[44] InlineTextBox: "?top 15 longest?"
[45] StaticText: " ? then fine-tune by tapping cards. Everything starts "
[46] InlineTextBox: " ? then fine-tune by tapping cards. Everything "
[47] InlineTextBox: "starts "
[48] strong
[49] StaticText: "selected"
[50] InlineTextBox: "selected"
[51] StaticText: "; just drop the ones you don't want."
[52] InlineTextBox: "; just drop the ones you don't want."
[53] generic
[54] heading: "Process a video"
[55] StaticText: "Process a video"
[56] InlineTextBox: "Process a video"
[57] paragraph
[58] StaticText: "Point KhelSutra at a video and it finds the rallies for you ? this
can take a few minutes."
[59] InlineTextBox: "Point KhelSutra at a video and it finds the rallies for you ?
this can take a few minutes."
[60] none
[61] LabelText
[62] StaticText: "Choose a video file"
[63] InlineTextBox: "Choose a video file"
[64] button: "Choose a video file to upload" (value: "No file chosen")
[65] paragraph
[66] StaticText: "Pick an .mp4 or .mov from this device ? it uploads, then KhelSutra
finds the rallies."
[67] InlineTextBox: "Pick an .mp4 or .mov from this device ? it uploads, then
KhelSutra finds the rallies."

```

[68] none
[69] paragraph
[70] StaticText: "OR USE A CLOUD LINK"
[71] InlineTextBox: "OR USE A CLOUD LINK"
[72] generic
[73] textbox: "Video location ? a gs:// bucket URL or a path on the engine host"
[76] button: "Process video"
[77] StaticText: "Process video"
[78] InlineTextBox: "Process video"
[79] paragraph
[80] StaticText: "Paste a cloud-storage link (gs://?), or a path to a video on the machine running KhelSutra."
[81] InlineTextBox: "Paste a cloud-storage link (gs://?), or a path to a video on the machine running KhelSutra."
[83] paragraph
[84] StaticText: "These are sample rallies ? process a video above to work on a real match."
[85] InlineTextBox: "These are sample rallies ? process a video above to work on a real match."
[87] none
[88] generic
[89] textbox: "Filter rallies by length, count or order"
[92] button: "Apply"
[93] StaticText: "Apply"
[94] InlineTextBox: "Apply"
[97] StaticText: "Type over 10s for rallies longer than 10 seconds ? or tap a sample below."
[98] InlineTextBox: "Type over 10s for rallies longer than 10 seconds ? or tap a sample below."
[99] none
[101] StaticText: "Sample queries:"
[102] InlineTextBox: "Sample queries:"
[103] button: "over 10s"
[104] StaticText: "over 10s"
[105] InlineTextBox: "over 10s"
[106] button: "top 15 longest"
[107] StaticText: "top 15 longest"
[108] InlineTextBox: "top 15 longest"
[109] button: "shortest first"
[110] StaticText: "shortest first"
[111] InlineTextBox: "shortest first"
[112] button: "first 10"
[113] StaticText: "first 10"
[114] InlineTextBox: "first 10"
[115] paragraph
[116] StaticText: "Filtering by "
[117] InlineTextBox: "Filtering by "
[118] strong
[119] StaticText: "rally length"
[120] InlineTextBox: "rally length"
[121] StaticText: " is fully supported. Shot-count is "
[122] InlineTextBox: " is fully supported. Shot-count is "
[123] StaticText: "experimental"
[124] InlineTextBox: "experimental"
[125] StaticText: " (under development)."
[126] InlineTextBox: " (under development)."
[127] none
[128] button: "Select all"
[129] StaticText: "Select all"
[130] InlineTextBox: "Select all"
[131] button: "Clear"
[132] StaticText: "Clear"
[133] InlineTextBox: "Clear"
[134] button: "Invert"
[135] StaticText: "Invert"

```
[136] InlineTextBox: "Invert"
[138] list
[139] listitem
[140] button: "Rally 1, in reel"
[143] StaticText: "Rally 1"
[144] InlineTextBox: "Rally 1"
[146] StaticText: "0:12"
[147] InlineTextBox: "0:12"
[148] StaticText: " "
[149] InlineTextBox: " "
[150] StaticText: "start"
[151] InlineTextBox: "start"
[152] StaticText: " . "
[153] InlineTextBox: " . "
[154] strong
[155] StaticText: "0:08"
[156] InlineTextBox: "0:08"
[157] StaticText: " "
[158] InlineTextBox: " "
[159] StaticText: "long"
[160] InlineTextBox: "long"
[162] StaticText: "~9 shots . experimental"
[163] InlineTextBox: "~9 shots . "
[164] InlineTextBox: "experimental"
[165] StaticText: " ? confidence: High"
[166] InlineTextBox: " ? "
[167] InlineTextBox: "confidence: High"
[168] listitem
[169] button: "Rally 2, in reel"
[172] StaticText: "Rally 2"
[173] InlineTextBox: "Rally 2"
[175] StaticText: "0:41"
[176] InlineTextBox: "0:41"
[177] StaticText: " "
[178] InlineTextBox: " "
[179] StaticText: "start"
[180] InlineTextBox: "start"
[181] StaticText: " . "
[182] InlineTextBox: " . "
[183] strong
[184] StaticText: "0:06"
[185] InlineTextBox: "0:06"
[186] StaticText: " "
[187] InlineTextBox: " "
[188] StaticText: "long"
[189] InlineTextBox: "long"
[191] StaticText: "~5 shots . experimental"
[192] InlineTextBox: "~5 shots . "
[193] InlineTextBox: "experimental"
[194] listitem
[195] button: "Rally 3, in reel"
[198] StaticText: "Rally 3"
[199] InlineTextBox: "Rally 3"
[201] StaticText: "1:03"
[202] InlineTextBox: "1:03"
[203] StaticText: " "
[204] InlineTextBox: " "
[205] StaticText: "start"
[206] InlineTextBox: "start"
[207] StaticText: " . "
[208] InlineTextBox: " . "
[209] strong
[210] StaticText: "0:21"
[211] InlineTextBox: "0:21"
[212] StaticText: " "
```

[213] InlineTextBox: " "
[214] StaticText: "long"
[215] InlineTextBox: "long"
[217] StaticText: "~19 shots · experimental"
[218] InlineTextBox: "~19 shots · "
[219] InlineTextBox: "experimental"
[220] StaticText: " ? confidence: Medium"
[221] InlineTextBox: " ? "
[222] InlineTextBox: "confidence: Medium"
[223] listitem
[224] button: "Rally 4, in reel"
[227] StaticText: "Rally 4"
[228] InlineTextBox: "Rally 4"
[230] StaticText: "1:35"
[231] InlineTextBox: "1:35"
[232] StaticText: " "
[233] InlineTextBox: " "
[234] StaticText: "start"
[235] InlineTextBox: "start"
[236] StaticText: " · "
[237] InlineTextBox: " · "
[238] strong
[239] StaticText: "0:06"
[240] InlineTextBox: "0:06"
[241] StaticText: " "
[242] InlineTextBox: " "
[243] StaticText: "long"
[244] InlineTextBox: "long"
[245] listitem
[246] button: "Rally 5, in reel"
[249] StaticText: "Rally 5"
[250] InlineTextBox: "Rally 5"
[252] StaticText: "2:10"
[253] InlineTextBox: "2:10"
[254] StaticText: " "
[255] InlineTextBox: " "
[256] StaticText: "start"
[257] InlineTextBox: "start"
[258] StaticText: " · "
[259] InlineTextBox: " · "
[260] strong
[261] StaticText: "0:12"
[262] InlineTextBox: "0:12"
[263] StaticText: " "
[264] InlineTextBox: " "
[265] StaticText: "long"
[266] InlineTextBox: "long"
[268] StaticText: "~11 shots · experimental"
[269] InlineTextBox: "~11 shots · "
[270] InlineTextBox: "experimental"
[271] listitem
[272] button: "Rally 6, in reel"
[275] StaticText: "Rally 6"
[276] InlineTextBox: "Rally 6"
[278] StaticText: "2:38"
[279] InlineTextBox: "2:38"
[280] StaticText: " "
[281] InlineTextBox: " "
[282] StaticText: "start"
[283] InlineTextBox: "start"
[284] StaticText: " · "
[285] InlineTextBox: " · "
[286] strong
[287] StaticText: "0:29"
[288] InlineTextBox: "0:29"

```

[289] StaticText: " "
[290] InlineTextBox: " "
[291] StaticText: "long"
[292] InlineTextBox: "long"
[294] StaticText: "~24 shots · experimental"
[295] InlineTextBox: "~24 shots · "
[296] InlineTextBox: "experimental"
[297] StaticText: " ? confidence: High"
[298] InlineTextBox: " ? "
[299] InlineTextBox: "confidence: High"
[300] sectionfooter
[301] none
[303] strong
[304] StaticText: "6 rallies"
[305] InlineTextBox: "6 rallies"
[306] StaticText: " "
[307] InlineTextBox: " "
[308] StaticText: "selected · 1:22 total"
[309] InlineTextBox: "selected · 1:22 total"
[310] LabelText
[312] StaticText: "Reel name"
[313] InlineTextBox: "Reel name"
[314] textbox: "Reel name" (value: "highlights")
[317] StaticText: "highlights"
[318] InlineTextBox: "highlights"
[319] button: "Build reel (6)"
[320] StaticText: "Build reel (6)"
[321] InlineTextBox: "Build reel (6)"

```

301. assistant (2026-06-21T16:30:28.188Z)

The T4 UI renders correctly: a labelled *****Choose a video file***** picker ([60-67]) with hint, plus the *****OR USE A CLOUD LINK***** section ([68-81]). Let me trigger a real file pick via eval to verify the live upload wiring (engine down on :8000 ? expect the friendly error chip):

302. user (2026-06-21T16:30:31.870Z)

"?Couldn't processCan't reach KhelSutra. Is it running?Try again"

303. assistant (2026-06-21T16:30:49.358Z)

The live upload path works end-to-end: picking a file triggers the real upload (`.init` call ? friendly *****? Couldn't process / "Can't reach KhelSutra. Is it running?"***** chip, since no engine is on :8000). T4 verified: 150 tests, tsc, build green; file picker labelled + both paths visible.

This is the North-Star keystone ? let me run a thorough 3-lens adversarial review. Capturing the diff:

304. user (2026-06-21T16:30:52.016Z)

```

=== files ===
M web/src/api/client.ts
M web/src/api/types.ts
A web/src/api/upload.test.ts
M web/src/components/IngestPanel.tsx
A web/src/components/upload.test.tsx
A web/src/hooks/useUpload.test.ts
A web/src/hooks/useUpload.ts
M web/src/i18n/locales/en/common.json
M web/src/i18n/locales/hi/common.json
M web/src/i18n/locales/kn/common.json
=== client.ts upload additions ===
diff --git a/web/src/api/client.ts b/web/src/api/client.ts

```

```

Index f59884e..92cb9fb 100644
--- a/web/src/api/client.ts
+++ b/web/src/api/client.ts
@@ -2,7 +2,17 @@
 // UI + engine behind one origin; in dev Vite proxies `/api` ? :8000). Every call carries a
 // correlation id (header + logs) so a journey is traceable end to end.
 import { log, newCorrelationId } from "../lib/log";
-import type { RallySegment, QueryResponse, CompileResponse, EngineConfig, ProcessResponse,
+import type {
+  RallySegment,
+  QueryResponse,
+  CompileResponse,
+  EngineConfig,
+  ProcessResponse,
+  JobStatus,
+  UploadInitResponse,
+  UploadPartResponse,
+  UploadCompleteResponse,
+} from "../types";

const BASE = "/api";

@@ -112,3 +122,98 @@ export async function getConfig(cid?: string): Promise<EngineConfig> {
export function minShotCount(cfg: EngineConfig): number | undefined {
  return cfg.stitching?.min_shot_count;
}
+
+// ?? chunked upload (backend/api/uploads.py) ?????????????????????????????????????????????
+// A browser uploads a LOCAL file in sequential parts ? max_part_mb (free-tier edge proxies cap
+// bodies ~100 MB), then `complete` returns a server-host `path` to feed straight into
+/api/process.
+
+/** Start a chunked upload. 400 = bad extension; 413 = over the size limit [uploads.py:64]. */
+export async function uploadInit(filename: string, totalSizeBytes: number, cid?: string):
+Promise<UploadInitResponse> {
+  return request<UploadInitResponse>("/upload/init", {
+    method: "POST",
+    body: JSON.stringify({ filename, total_size_bytes: totalSizeBytes }),
+    cid,
+  });
+}
+
+/** Append ONE part (raw bytes ? not JSON). Parts are strictly sequential 0,1,2,?
+[uploads.py:89]. */
+export async function uploadPart(
+  uploadId: string,
+  index: number,
+  chunk: Blob,
+  cid?: string,
+  signal?: AbortSignal,
+): Promise<UploadPartResponse> {
+  const c = cid ?? newCorrelationId();
+  const url = `${BASE}/upload/${encodeURIComponent(uploadId)}/part/${index}`;
+  log("info", "api.request", { cid: c, method: "PUT", url });
+  let res: Response;
+  try {
+    res = await fetch(url, {
+      method: "PUT",
+      body: chunk,
+      headers: { "content-type": "application/octet-stream", "x-correlation-id": c },
+      signal,
+    });
+  } catch (err) {
+    log("error", "api.network_error", { cid: c, method: "PUT", url, error: String(err) });

```



```

+   throw new ApiError(`Network error calling PUT ${url}`, { cid: c, cause: err });
+ }
+ if (!res.ok) {
+   const body = await res.text().catch(() => "");
+   log("error", "api.http_error", { cid: c, method: "PUT", url, status: res.status, body:
body.slice(0, 500) });
+   throw new ApiError(`PUT ${url} failed: ${res.status}`, { cid: c, status: res.status, body
});
+ }
+ log("info", "api.response", { cid: c, method: "PUT", url, status: res.status });
+ return (await res.json()) as UploadPartResponse;
+}
+
+/** Finalize: returns {path, video_id} ? feed `path` to processVideo() [uploads.py:123]. */
+export async function uploadComplete(uploadId: string, totalParts: number, cid?: string):
Promise<UploadCompleteResponse> {
+   return request<UploadCompleteResponse>(`/upload/${encodeURIComponent(uploadId)}/complete`, {
+     method: "POST",
+     body: JSON.stringify({ total_parts: totalParts }),
+     cid,
+   });
+}
+
+/** Abort an in-flight upload (best-effort cleanup of the server-side partial)
[uploads.py:147]. */
+export async function uploadAbort(uploadId: string, cid?: string): Promise<void> {
+   await request<unknown>(`/upload/${encodeURIComponent(uploadId)}`, { method: "DELETE", cid });
+}
+
+export interface UploadProgress {
+   sentBytes: number;
+   totalBytes: number;
+}
+
+/** Upload a local File end to end: init ? sequential parts (byte progress, abortable) ?
complete.
+ * On ANY failure or abort it best-effort DELETes the server-side partial, then rethrows so
the
+ * caller can classify it (the engine's 400/413 detail survives). Returns {path, video_id}. */
+export async function uploadFile(
+   file: File,
+   opts: { cid?: string; signal?: AbortSignal; onProgress?: (p: UploadProgress) => void } = {},
+): Promise<UploadCompleteResponse> {
+   const cid = opts.cid ?? newCorrelationId();
+   const init = await uploadInit(file.name, file.size, cid);
+   const partBytes = Math.max(1, init.max_part_mb) * 1024 * 1024;
+   const totalParts = Math.max(1, Math.ceil(file.size / partBytes));
+   log("info", "upload.start", { cid, filename: file.name, size: file.size, parts: totalParts,
part_mb: init.max_part_mb });
+   let sent = 0;
+   try {
+     for (let i = 0; i < totalParts; i++) {
+       if (opts.signal?.aborted) throw new DOMException("Upload aborted", "AbortError");
+       const chunk = file.slice(i * partBytes, Math.min((i + 1) * partBytes, file.size));
+       await uploadPart(init.upload_id, i, chunk, cid, opts.signal);
+       sent += chunk.size;
+       opts.onProgress?.({ sentBytes: sent, totalBytes: file.size });
+     }
+     const done = await uploadComplete(init.upload_id, totalParts, cid);
+     log("info", "upload.done", { cid, video_id: done.video_id, path: done.path, size:
done.size_bytes });
+     return done;
+   } catch (err) {
+     log("warn", "upload.aborting_partial", { cid, upload_id: init.upload_id, error: String(err)
});
+   }

```

```

+   await uploadAbort(init.upload_id, cid).catch(() => {});
+   throw err;
+ }
+}
diff --git a/web/src/api/types.ts b/web/src/api/types.ts
index 3349567..4978d7d 100644
--- a/web/src/api/types.ts
+++ b/web/src/api/types.ts
@@ -54,6 +54,26 @@ export interface ProcessResponse {
   poll: string;
 }

+/** Chunked upload (backend/api/uploads.py). The browser uploads a local file in sequential
+parts
+ * ? max_part_mb, then `complete` returns a server-host `path` to feed straight into POST
+/api/process. */
+export interface UploadInitResponse {
+  upload_id: string;
+  /** Per-part ceiling in MB ? slice the file into parts this big. */
+  max_part_mb: number;
+  next_part: string;
+}
+export interface UploadPartResponse {
+  upload_id: string;
+  received_parts: number;
+  received_bytes: number;
+}
+export interface UploadCompleteResponse {
+  /** Absolute path on the engine host ? pass as video_path to POST /api/process. */
+  path: string;
+  video_id: string;
+  size_bytes: number;
+}
+
+/** GET /api/jobs/{job_id} [backend/main.py:303]. Two status layers:
+ * `status` = the EXECUTION state; `result.status` = the pipeline VERDICT (success|failed).
+ * A `done` job whose `result.status` == "failed" (or with no video_id) is a success-shaped

```

305. assistant (2026-06-21T16:31:02.076Z)

T4 diff is clean. Now the 3-lens adversarial review (correctness/chunking, a11y/UX faithfulness, engine-contract fidelity) ? agents read the SPA + the engine's `uploads.py`:

306. user (2026-06-21T16:31:36.765Z)

Workflow launched in background. Task ID: wrmvkuioo
Summary: Adversarial 3-lens review of the T4 in-UI upload
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_a48e6aa3-748
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\t4-review-wf_a48e6aa3-748.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\t4-review-wf_a48e6aa3-748.js"})
to iterate without resending the script.)
Run ID: wf_a48e6aa3-748
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\t4-review-wf_a48e6aa3-748.js", resumeFromRunId: "wf_a48e6aa3-748"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

307. assistant (2026-06-21T16:32:02.077Z)

While the T4 review runs, let me wait for it (it gates the merge). I'll do the memory checkpoint + spawn-offs after T4 lands to minimize edit churn.

308. user (2026-06-21T16:37:02.322Z)

<retrieval_status>timeout</retrieval_status>

<task_id>wrmvkuioo</task_id>

<task_type>local_workflow</task_type>

<status>running</status>

309. user (2026-06-21T16:40:03.882Z)

<retrieval_status>success</retrieval_status>

<task_id>wrmvkuioo</task_id>

<task_type>local_workflow</task_type>

<status>completed</status>

<output>

```
{
  "summary": "Adversarial 3-lens review of the T4 in-UI upload",
  "agentCount": 3,
  "logs": [],
  "result": [
    {
      "lens": "correctness",
      "summary": "T4 upload review",
      "findings": [
        {
          "severity": "nit",
          "file": "C:/Users/avidu/Projects/khelsutra/web/src/api/client.ts",
          "location": "199-200",
          "title": "max_part_mb guard catches 0 but not NaN/missing",
          "detail": "Math.max(1, init.max_part_mb) covers 0 but not undefined/NaN since Math.max(1, NaN) is NaN; partBytes and totalParts become NaN, the for-loop uploads zero parts, and uploadComplete(NaN) serializes to null and 422s as a silent zero-byte upload. Engine returns an int so defensive only, but it is the 0-or-missing gap the prompt asked about.",
          "suggestion": "Coerce with Number.isFinite (fallback 95) before scaling to bytes."
        },
        {
          "severity": "nit",
          "file": "C:/Users/avidu/Projects/khelsutra/web/src/api/client.ts",
          "location": "211",
          "title": "Per-part 413 is terminal; no retry without re-init",
          "detail": "Engine per-part overflow (uploads.py:113-115) aborts the whole upload, so a 413 part error is terminal for the upload_id; client part size is byte-exact vs engine so steady-state never hits it. Fine for the alpha; a documented edge.",
          "suggestion": "Note in the uploadFile docstring that a 413 part error needs re-init."
        }
      ]
    }
  ],
  {
    "lens": "a11y-ux",
    "summary": "T4 in-UI file upload is solid; nothing blocking. See findings.",
    "findings": [
      {
        "severity": "minor",
        "file": "C:/Users/avidu/Projects/khelsutra/web/src/components/IngestPanel.tsx",
        "location": "lines 59-74 (file-picker label/input)",
        "title": "Keyboard focus on the file picker is invisible (WCAG 2.4.7 Focus Visible)",
```

"detail": "The file input is sr-only (correct for staying focusable+labelled) inside a styled label, but the label has no focus-within style. A keyboard user who tabs to the picker gets no visible focus ring on the Choose-a-video-file button because focus lands on the hidden input. By contrast the gs:// input and the Process button both get a visible focus:border-green. The picker is reachable and SR-labelled but not focus-visible. Size is fine (min-h-11=44px); this is the focus indicator only.",

"suggestion": "Add a focus-within ring to the label so the visible button reflects the hidden input focus. Worth a one-line a4-style test asserting the label carries a focus-within class."

```
  },
  {
    "severity": "nit",
    "file": "C:/Users/avidu/Projects/khelsutra/web/src/components/IngestPanel.tsx",
    "location": "lines 108-114 (progressbar div)",
    "title": "Progressbar has no accessible name",
    "detail": "role=progressbar has aria-valuenow/min/max but no aria-label or aria-  
labelledby, so a screen reader announces a bare percent progressbar with no indication of what  
is progressing. The adjacent StatusChip under aria-live carries the meaning, so not a functional  
gap; a named bar is just more robust. The determinate-vs-indeterminate honesty itself is  
correct.",
```

"suggestion": "Add aria-label via t() to the progressbar div, or wire aria-labelledby to the chip text."

```
  },
  {
    "severity": "nit",
    "file": "C:/Users/avidu/Projects/khelsutra/web/src/components/IngestPanel.tsx",
    "location": "lines 104-149 (aria-live region with Cancel + the percent chip)",
    "title": "Interactive Cancel and a per-tick percent chip sit inside the aria-live  
region",
```

"detail": "Both busy blocks (each with a Cancel button) live inside the aria-live=polite wrapper. Nesting an interactive control plus a per-tick percent chip can make some screen readers re-announce on every tick, which is chatty during a long upload. Functionally fine; polish only.",

"suggestion": "Keep only the status text inside aria-live and move Cancel just outside it, or wrap only the changing label in its own aria-live span."

```
  }
]
},
{
  "lens": "contract",
  "summary": "T4 contract VERIFIED CLEAN. Two non-blocking notes below.",
  "findings": [
```

```
    {
      "severity": "minor",
      "file": "backend/config/models.py",
      "location": "models.py 287-293",
      "title": "HOSTED-mode caveat: allowed_video_root must contain upload_dir or process  
rejects every uploaded path",
```

"detail": "DEFAULT mode is correct and T4 is fine. In hosted mode with edge-auth ON, the path-jail rejects uploaded paths unless allowed_video_root contains upload_dir. T2 deployment note, not a T4 blocker.",

"suggestion": "In T2 set allowed_video_root to a parent of upload_dir."

```
  },
  {
    "severity": "nit",
    "file": "web/src/hooks/useUpload.ts",
    "location": "useUpload.ts 35-48",
    "title": "No client-side max-upload guard",
    "detail": "0-byte is guarded; oversize is caught by the init 413 before bytes flow.  
Functionally fine, just no proactive size hint since max_upload_mb is not exposed to the SPA.",
    "suggestion": "Optional: expose max_upload_mb and pre-check size for an immediate  
message."
```

```
  }
]
}
```

```
]
}
</output>
```

310. assistant (2026-06-21T16:41:51.728Z)

T4 review: ****contract verified clean, no blockers.**** Worth folding: one ****a11y MINOR**** (file-picker keyboard focus invisible ? WCAG 2.4.7), plus cheap robustness nits (NaN-safe `max\_part\_mb`, named progressbar, avoid chatty per-tick re-announcement). The hosted-mode `allowed\_video\_root` note is a T2 deployment item (I'll carry it into the T2 spawn-off). Folding the real ones:

311. user (2026-06-21T16:41:59.617Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\client.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

312. user (2026-06-21T16:42:08.359Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

313. user (2026-06-21T16:42:19.699Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

314. assistant (2026-06-21T16:42:25.775Z)

Now update the catalogs ? replace `uploading` with `uploadingStatus` + `uploadProgress` (all three):

315. user (2026-06-21T16:42:27.561Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

316. user (2026-06-21T16:42:37.360Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

317. user (2026-06-21T16:42:44.178Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

318. assistant (2026-06-21T16:42:59.626Z)

Now add a focus-visible regression assertion to the upload test, then re-run:

319. user (2026-06-21T16:43:03.925Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\upload.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

320. user (2026-06-21T16:43:24.107Z)

```
Test Files  18 passed (18)
Tests      150 passed (150)
=== tsc ===
tsc OK
=== build ===
```

? built in 1.14s

321. assistant (2026-06-21T16:43:38.797Z)

150 tests, tsc, build all green after folding the T4 findings. Let me confirm no orphaned `ingest.uploading` reference, then commit:

322. user (2026-06-21T16:43:39.672Z)

```
src\hooks\useUpload.ts:17:  | { status: "uploading"; pct: number; filename: string }
src\hooks\useUpload.ts:47:      setPhase({ status: "uploading", pct: 0, filename: file.name });
src\hooks\useUpload.ts:58:      setPhase({ status: "uploading", pct, filename: file.name
});
src\hooks\useUpload.ts:86:  const busy = phase.status === "uploading";
src\components\IngestPanel.tsx:107:      {upload.phase.status === "uploading" && (
```

323. assistant (2026-06-21T16:43:46.628Z)

All matches are the `"uploading"` phase-status string (state machine), not the removed i18n key ? clean. Committing T4:

324. user (2026-06-21T16:43:49.146Z)

```
branch: master
web/src/api/client.ts
web/src/api/types.ts
web/src/api/upload.test.ts
web/src/components/IngestPanel.tsx
web/src/components/upload.test.tsx
web/src/hooks/useUpload.test.ts
web/src/hooks/useUpload.ts
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
--- base (only my work) ---
```

325. assistant (2026-06-21T16:44:04.830Z)

I'm on `master` ? I skipped cutting the T4 branch. Caught before any commit. Let me move these staged changes onto a feature branch (`checkout -b` preserves the working tree):

326. user (2026-06-21T16:44:09.003Z)

```
origin/master: 4627830
local master: 92a6c45
Switched to a new branch 'feat/t4-in-ui-upload'
--- now on ---
feat/t4-in-ui-upload
--- staged still present ---
web/src/api/client.ts
web/src/api/types.ts
web/src/api/upload.test.ts
web/src/components/IngestPanel.tsx
web/src/components/upload.test.tsx
web/src/hooks/useUpload.test.ts
web/src/hooks/useUpload.ts
web/src/i18n/locales/en/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/kn/common.json
--- base vs origin/master (should be empty: nothing committed yet) ---
```

327. assistant (2026-06-21T16:44:29.922Z)

`origin/master` moved to `4627830` (a sibling merged after my A8) ? my branch is based on the

older `92a6c45`. Let me check what landed and rebase onto `origin/master` per branching discipline. First, commit T4, then rebase:

328. user (2026-06-21T16:44:30.365Z)

```
=== what is 4627830 ===
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*
tunnel + CF Access) (#65)
8bbc557 feat(web): VITE_API_BASE ? let the SPA target a split api.* origin (default same-origin
/api) (#64)
=== files it touched ===
README.md
deploy/DEPLOY_ALPHA.md
deploy/cloudflared.config.example.yml
docs/LOCAL_APPLIANCE_ARCHITECTURE.md
web/src/api/client.test.ts
web/src/api/client.ts
web/src/vite-env.d.ts
```

329. assistant (2026-06-21T16:44:42.164Z)

#64 modified `web/src/api/client.ts` (VITE_API_BASE) ? the same file I touched. I'll commit T4, then rebase onto `origin/master` and resolve. Committing:

330. user (2026-06-21T16:44:54.092Z)

```
committed: c06ee54 feat(web): T4 ? in-UI file upload (the runnable-tool keystone)
=== rebase onto origin/master ===
Rebasing (1/1)
```

Successfully rebased and updated refs/heads/feat/t4-in-ui-upload.

331. assistant (2026-06-21T16:45:04.869Z)

The rebase merged cleanly ? #64's `apiBase()`/`VITE\_API\_BASE` and my upload helpers coexist (my code uses `\${BASE}`, now resolved via `apiBase()`). Let me re-verify the full suite on the rebased base (which now includes #64's client changes):

332. user (2026-06-21T16:45:19.055Z)

```
Test Files  18 passed (18)
Tests       153 passed (153)
=== tsc ===
tsc OK
=== build ===
? built in 1.12s
=== branch base ===
a154121 feat(web): T4 ? in-UI file upload (the runnable-tool keystone)
```

333. assistant (2026-06-21T16:45:27.609Z)

Rebased cleanly ? **153 tests** pass (my 150 + #64's 3 new client tests), tsc + build green, and my T4 commit is the only one atop `origin/master`. Pushing + PR:

334. user (2026-06-21T16:45:30.301Z)

```
branch 'feat/t4-in-ui-upload' set up to track 'origin/feat/t4-in-ui-upload'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/t4-in-ui-upload -> feat/t4-in-ui-upload
```

335. user (2026-06-21T16:45:52.601Z)

<https://github.com/avidullu/khelsutra/pull/66>

336. assistant (2026-06-21T16:46:01.233Z)

PR [#66](https://github.com/avidullu/khelsutra/pull/66) created. Let me update T4's status in its tracker doc (`LOCAL\_APPLIANCE\_ARCHITECTURE.md` §9). First, find the T4 row:

337. user (2026-06-21T16:46:03.112Z)

```
41-## 3. Foundation ? what the engine gives us today `[verified this session unless noted]`
42:[Omitted long matching line]
43-- **In-process worker:** one module-global `ThreadPoolExecutor(max_workers=1)` `[verified
job_worker.py:37]` ? strictly **one job at a time**; the DB `jobs` table is the clock;
`fail_stale_jobs` sweeps queued/running on boot. Gemini chunk concurrency is a **separate** knob
`indexing.ai_max_workers` (**default 5** `[verified models.py:183]`; set to 1 to serialize) ? it
is **not** already 1.
--
68-?      control: jobs table + ThreadPoolExecutor(max_workers=1) drain      ?
69-?      data: uploads.py chunked upload · /api/compile · /api/highlights  ?
70-?      ?      ?      ?      ?
--
85-|---|---|---|
86-| **Local upload** | SPA chunks the file ? `max_part_mb` via the existing
`/api/upload/init\|part\|complete` `[verified uploads.py]` ? server path ? `POST /api/process`.
(Scale: also `StorageBackend.put` to `s3://`/`gs://`.) | **wire client only** (endpoints exist)
|
87-[Omitted long context line]
--
112-### 4.6 Reuse map
113:[Omitted long matching line]
114-
--
160-| T3 | L3 live posture test (raw `:8000`/`:900x` refused from outside) | T2 | no | ? | ? |
161-| T4 | S1 ingest (local upload wired) + segmenter picker | T1 | no | ? | ? |
162-| T5 | S2 progress (poll + one-job + restart-failure) | T4 | no | ? | ? |
163-| T6 | S3 embed **RallyPicker** + compile + download | T4 | no | ? | ? |
164-| T7 | *(engine)* `GET /api/capabilities` + `GET /api/health` + banner | T1 | coord | ? | ? |
|
--
166-| T9 | S5 Settings (config+capabilities; disabled compute/storage target) | T7,T8 | no | ? |
? |
167-| T10 | Observability pass: correlation id end-to-end + structured logs + metrics (§5) | T4
| no | ? | ? |
168-| T11 | Retention sweep for `output/+`uploads/` | ? | owner | ? | ? |
169-| T12 | Ingest from **bucket URI** (`s3://`/`gs://`) wiring ? engine accepts URIs
(M2/[#280]) ** SPA ingest screen shipped (B-P2, [#56])**; in-UI `gs://`?reel CUJ proven live
e2e (`DRY_RUN_CUJ.md` §9) | T4 | ? | ? | ? | engine #280 + SPA #56 |
170-| T13 | **GPU host stand-up** (provider-agnostic) + wire `detector_impl=native`; owner byte-
parity (P4) | branch | ? | owner | ? | ? |
--
191-## 12. References
192:[Omitted long matching line]
193-
```

338. assistant (2026-06-21T16:46:18.617Z)

T4's row bundles "local upload wired ** segmenter picker**" ? my PR delivers the upload keystone but not the picker. I'll mark it ? honestly (upload shipped, picker pending):

339. user (2026-06-21T16:46:22.067Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

340. user (2026-06-21T16:46:27.739Z)

158 | T1 | Mock engine + capability fixtures + browser-replay CUJ scripts (L1) | T0 | no | ?


```

| ? |
159 | T2 | Appliance shell: Caddyfile + systemd units; firewall; **edge auth**; rotate key
(P1) | ? | owner | ? | ? |
160 | T3 | L3 live posture test (raw `:8000`/`:900x` refused from outside) | T2 | no | ? | ? |
|
161 | T4 | S1 ingest (local upload wired) + segmenter picker | T1 | no | ? | ? |
162 | T5 | S2 progress (poll + one-job + restart-failure) | T4 | no | ? | ? |
163 | T6 | S3 embed **RallyPicker** + compile + download | T4 | no | ? | ? |
164 | T7 | *(engine)* `GET /api/capabilities` + `GET /api/health` + banner | T1 | coord | ? |
| ? |
165 | T8 | *(engine)* `GET /api/videos` + `GET /api/reels/{video_id}` (S4 reload-survival) |
? | coord | ? | ? |
166 | T9 | S5 Settings (config+capabilities; disabled compute/storage target) | T7,T8 | no |
? | ? |
167 | T10 | Observability pass: correlation id end-to-end + structured logs + metrics ($5) |
T4 | no | ? | ? |
168 | T11 | Retention sweep for `output/+`uploads/` | ? | owner | ? | ? |
169 | T12 | Ingest from **bucket URI** (`s3://`/`gs://`) wiring ? engine accepts URIs
(M2/[#280]) ** SPA ingest screen shipped (B-P2, [#56])**; in-UI `gs://`?reel CUJ proven live
e2e (`DRY_RUN_CUJ.md` $9) | T4 | ? | ? | engine #280 + SPA #56 |
170 | T13 | **GPU host stand-up** (provider-agnostic) + wire `detector_impl=native`; owner
byte-parity (P4) | branch | ? owner | ? | ? |
171 | T14 | *(reserved)* Bucket-worker bridge ? remote-GPU "compute as a setting" (P5) |
T8,T12 | ? owner | ? | ? |

```

341. user (2026-06-21T16:46:34.402Z)

The file C:\Users\avidu\Projects\khelsutra\docs\LOCAL_APPLIANCE_ARCHITECTURE.md has been updated successfully. (file state is current in your context ? no need to Read it back)

342. user (2026-06-21T16:47:15.703Z)

```

pushed
site    pass    13s
https://github.com/avidullu/khelsutra/actions/runs/27910960369/job/82587898644
Workers Builds: hidden-king-khelsutra    pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/b93606ec-542f-41ca-b341-cc54516bf214
web     pending 0
https://github.com/avidullu/khelsutra/actions/runs/27910960369/job/82587898656

```

343. user (2026-06-21T16:47:44.369Z)

```

poll 1: web=pending cf=pass
poll 2: web=pass cf=pass
=== final ===
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/b93606ec-542f-41ca-b341-cc54516bf214
site    pass    13s
https://github.com/avidullu/khelsutra/actions/runs/27910960369/job/82587898644
web     pass     30s
https://github.com/avidullu/khelsutra/actions/runs/27910960369/job/82587898656

```

344. assistant (2026-06-21T16:47:49.861Z)

All green. Merging T4 (the North-Star keystone):

345. user (2026-06-21T16:47:57.914Z)

```

create mode 100644 web/src/hooks/useUpload.ts
create mode 100644 web/src/vite-env.d.ts
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*

```

tunnel + CF Access) (#65)
8bbc557 feat(web): VITE_API_BASE ? let the SPA target a split api.* origin (default same-origin /api) (#64)

346. assistant (2026-06-21T16:49:08.128Z)

****T4 merged (#66 ? `ca619fb`) ? the North-Star keystone is in.**** Note: the sibling's #64/#65 already shipped a `VITE\_API\_BASE` split-origin mode + an ****alpha deploy kit**** (Cloudflare Pages + `api.\*` tunnel + CF Access) ? that's most of T2's plumbing.

That's ****4 merged PRs this session**** (A4/A5/A8/T4). Per your direction, let me record the remaining immediate-next items (B3, MULTILINGUAL Phase A, T11) as spawn-off chips you can launch as parallel sessions, each self-contained with the locked decisions + sequencing.

347. user (2026-06-21T16:49:08.648Z)

Updated task #5 status

348. user (2026-06-21T16:49:30.079Z)

Noted (position 1, task_id: task_b3060842). A chip is showing for the user ? they can start it in a fresh worktree with one click, or dismiss it. If this suggestion becomes stale or superseded, call dismiss_task with this task_id. Currently pending: task_b3060842 "B3 ? make site/ marketing trilingual (shared t() shim)". Continue your current work.

349. user (2026-06-21T16:49:42.454Z)

Noted (position 2, task_id: task_e15e9643). A chip is showing for the user ? they can start it in a fresh worktree with one click, or dismiss it. If this suggestion becomes stale or superseded, call dismiss_task with this task_id. Currently pending: task_b3060842 "B3 ? make site/ marketing trilingual (shared t() shim)", task_e15e9643 "MULTILINGUAL Phase A ? add es/da/id SPA catalogs". Continue your current work.

350. user (2026-06-21T16:49:51.954Z)

Noted (position 3, task_id: task_2480b9e2). A chip is showing for the user ? they can start it in a fresh worktree with one click, or dismiss it. If this suggestion becomes stale or superseded, call dismiss_task with this task_id. Currently pending: task_b3060842 "B3 ? make site/ marketing trilingual (shared t() shim)", task_e15e9643 "MULTILINGUAL Phase A ? add es/da/id SPA catalogs", task_2480b9e2 "T11 ? retention sweep for output/ + uploads/". Continue your current work.

351. assistant (2026-06-21T16:50:17.125Z)

All three immediate-next items are now spawn-off chips you can launch as parallel sessions. Let me refresh this track's handoff memory to capture the session's progress.

352. user (2026-06-21T16:50:37.785Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

353. user (2026-06-21T16:51:15.375Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

354. user (2026-06-21T16:51:29.189Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is

current in your context ? no need to Read it back)

355. assistant (2026-06-21T16:51:39.861Z)

Let me add a concise checkpoint to the shared `current-state.md`. Reading its current top first (it may have shifted via the concurrent session):

356. user (2026-06-21T16:51:40.680Z)

```
10      # Current state ? updated continuously (see [[working-agreement-checkpoints]])
11
12      > **Scope of this file = LIVE only:** the current handoff + *today's* checkpoints + open
PRs/decisions. Keep it read-first-short (?1 page). Older checkpoints are archived in [[current-
state-archive]] ? when today's checkpoints age out (next clean-slate day), move them there,
don't let them pile up here.
13
14      **Checkpoint:** 2026-06-21 (**ALPHA-SHAREABLE ? Claude's half DONE; 3 PRs merged**).
Owner's #1 = "highlights from a page I can share, no SSH." **KEY CORRECTION (anti-spiral
[[lesson-verify-engine-surface-before-scoping]]): **the icebreaker said do "B-P2 ingest screen +
M7 Cloud Run *service*" ? but a recon **workflow** (`wf_5de56b64`, 5 readers across both repos)
proved **B-P2 was ALREADY shipped** (khelsutra #56, live e2e `DRY_RUN_CUJ.md` §9) + CORS is
already env-driven ? **alpha-shareable is a DEPLOY/AUTH task, not an SPA build**. **Owner
decisions (2x AskUserQuestion): **topology **(i) Tunnel-to-a-box**, sub-topology **SPLIT** (SPA
on CF Pages + engine on `api.` cloudflared tunnel + CF Access; single-origin Caddy kept as the
alt). **3 PRs MERGED:** ? **engine [#294](https://github.com/Khelsutra/badminton-highlight-
indexer/pull/294)** (`0c0e064`) **exposure-safety boot posture** ? `startup.py` fails fast at
boot (server-only `include_exposure=True`) when `edge_auth_enabled` is ON but half-configured
(`EXPOSED_NO_VIDEO_ROOT`/`EXPOSED_EDGE_AUTH_INCOMPLETE` fatal, `EXPOSED_AUTH_EXTRA_MISSING`
warn); **default-OFF**; aligned `auth.resolve_tenant` whitespace; adversarial 3-lens review
(`wf_35b735a9`) ? no bypass; +16 tests; 1259 green cross-OS. ? **khelsutra
[#64](https://github.com/avidullu/khelsutra/pull/64)** (`8bbc557`) **SPA `VITE_API_BASE`** ?
`apiBase()` env-driven (default same-origin `/api`) + `vite-env.d.ts` + 3 tests; build-smoke
proved the override bakes in. ? **khelsutra
[#65](https://github.com/avidullu/khelsutra/pull/65)** (`4627830`) **deploy kit** ?
`deploy/DEPLOY_ALPHA.md` (split runbook + CORS-preflight gotcha + posture test) +
`cloudflared.config.example.yml` + tracker pointers. Each isolated/default-OFF/adversarial-
reviewed/CI-green/merged-on-green; khelsutra built in a dedicated **worktree** (main tree had
sibling A8 WIP, since merged #63; ? `rmdir` the `node_modules` junction BEFORE `git worktree
remove`). **? REMAINING for alpha = OWNER stand-up only** (cloudflared tunnel + CF Pages + CF
Access + key rotation per `khelsutra/deploy/DEPLOY_ALPHA.md`). **? NEXT engine code (Claude-
doable, batch-authorized): M12** (gdrive-api, clean, no DB migration) then **M11** (flywheel
skeleton, privacy-gated on v7 consent). [[ui-driven-cloud-serving-gap]] [[lesson-verify-engine-
surface-before-scoping]]
15
16      **?? NEXT SESSION FOCUS (2026-06-21, after the big localization+dry-run session) ? ?
SUPERSEDED by the checkpoint above (B-P2 confirmed DONE). **SPA is fully **en+kn+hi (DONE)**; a
real **UI?engine?reel?download CUJ ran (en+hi)**; a **critical engine bug fixed** (#281). **?
NEXT BUILD (owner-picked): (1) Path B ? point at a bucket video IN THE UI. ** ? **B-P1 VERIFIED
ALREADY DONE ? NO ENGINE CODE (do NOT re-scope it as a feature): **`POST /api/process` has
accepted `gs:///`gcs:///` URIs since **M2/#280** (submit resolves the URI + skips the local-
exists-404 for non-local backends `main.py:283`; the worker fetches to scratch
`acquire_local_input main.py:159` ? same hash?validate?segment?DB pipeline ? queryable API-DB
`video_id`); **TESTED**
(`tests/test_api_endpoints.py::test_process_nonlocal_uri_skips_exists_and_fetches` + hosted-
mode-reject / unknown-scheme-400 / CLI variants). Confirmed by a **3-skeptic verification
workflow (0 refuted, gaps:[])**. **Scope pin:** holds in DEFAULT single-user mode (hosted-mode
`allowed_video_root` correctly **400s** a bucket URI ? by design). Stale "local-path-only / net-
new" docs **CORRECTED ? khelsutra [#55]** (DRY_RUN_CUJ §1/2/4/6/8 + LOCAL_APPLIANCE + README).
**? So Path B = ONLY B-P2 = the SPA ingest/progress screen** (enter a `gs:///` URI ? `POST
/api/process` ? poll `/api/jobs` ? load `result.video_id`; back-half already works) ? **100%
khelsutra `web/` SPA + i18n (en/kn/hi), ZERO engine code.** Ready B-P2 sketch: `DRY_RUN_CUJ.md`
§2 (new `web/src/{api/types,api/client,hooks/useIngestJob,components/IngestPanel}.tsx` +
`App.tsx` `videoId?state` handoff + `ingest.` keys). See [[lesson-verify-engine-surface-before-
scoping]]. **(2) Droplet deploy (opt 3): **deploy the FIXED engine to `168.144.126.176` (un-
provisioned, 2-core/3.8GB) ? re-run CUJ on Linux. **STILL OPEN (localization DoD):** B3 (`site/`
```

marketing still English-only) + native-speaker review of the AI-drafted kn/hi. ****Ramp-up:****
`khelsutra/docs/DRY\_RUN\_CUJ.md` + `FRIENDLY\_AND\_MULTILINGUAL.md` §7 + the dry-run checkpoint
below. ****Clean slate (at session start):**** both repos on master, 0 open PRs, no worktrees/VMS.
khelsutra master `2421557` · engine master `2afd54f` (? origin/master `cee4baa`, #283 M4
squashed).
17

357. assistant (2026-06-21T16:52:03.775Z)

The concurrent session added the ALPHA-SHAREABLE checkpoint (#294/#64/#65) ? confirming #64/#65
are its T2 deploy-kit work. Let me insert my session checkpoint above it:

358. user (2026-06-21T16:52:14.949Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-
indexer\memory\current-state.md has been updated successfully. (file state is current in your
context ? no need to Read it back)

359. assistant (2026-06-21T16:52:33.366Z)

Let me verify the final clean git state and stop the dev server:

360. user (2026-06-21T16:52:38.288Z)

```
=== branch + sync ===
master
local master: ca619fb origin/master: ca619fb
=== uncommitted (should be only untracked .claude/ + site/access.db) ===
?? .claude/
?? site/access.db
=== my merged PRs this session ===
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*
tunnel + CF Access) (#65)
8bbc557 feat(web): VITE_API_BASE ? let the SPA target a split api.* origin (default same-origin
/api) (#64)
92a6c45 feat(web): A8 ? background-processing reassurance + icon+text status chips (#63)
501c014 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
(#62)
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
```

361. assistant (2026-06-21T16:52:48.082Z)

Clean wrap: on `master`, local ? `origin/master` (`ca619fb`); only the pre-existing untracked
`.claude/` + `site/access.db` remain (not mine); all feature branches deleted on merge. Stopping
the dev server:

362. user (2026-06-21T16:52:48.755Z)

Server 001260a2-3d4b-4722-8222-5e253669c429 stopped

363. assistant (2026-06-21T16:53:15.276Z)

Done. Here's the session summary.

Shipped this session ? 4 PRs merged (all green CI, browser-verified, each adversarially reviewed via a workf

```
| PR | What |
|----|-----|
| [#61](https://github.com/avidullu/khelsutra/pull/61) **A4** | ?44px mobile tap targets across
the SPA; enlarged parsed-pill + sample chips; **hover-only `title=` text made visible** (the
"not available yet" reason + per-card shot confidence ? phones never show `title=`). |
| [#62](https://github.com/avidullu/khelsutra/pull/62) **A5** | One shared
```

```
[`lib/errorText.ts`](web/src/lib/errorText.ts) + `errors.*` namespace maps build + load + ingest failures the same friendly, localized way ? no more raw `ApiError: ?`/`HTTP 500`. Logs gained `code`+`detail`. |  
| [#63](https://github.com/avidullu/khelsutra/pull/63) A8 | Background-processing reinsurance + icon+text [StatusChip](web/src/components/StatusChip.tsx) (never icon-only); a "Stitching your reel?" building card + `status icons` + `aria-live`. |  
| [#66](https://github.com/avidullu/khelsutra/pull/66) T4 ? North-Star keystone | In-UI file upload: a file picker ? chunked `/api/upload/` ([`api/client.ts`](web/src/api/client.ts) + [`hooks/useUpload.ts`](web/src/hooks/useUpload.ts)) ? server path ? `/api/process` ? the existing poll?load?compile?download. Alpha users can now point the tool at a file, not just a `gs://` URI. 153 web tests. |
```

Every item folded its review findings (e.g. A8's `aria-live` + honest copy; T4's WCAG focus-visible, NaN-safe chunking, named progressbar). Trackers in `FRIENDLY\_AND\_MULTILINGUAL.md` S7 and `LOCAL\_APPLIANCE\_ARCHITECTURE.md` S9 updated; memory handoff + current-state refreshed.

Decisions you made

- **Build T4 first** ?; **B3 catalogs hoist to repo-root** `/locales/` (locked, baked into the chip).

Recorded as spawn-off chips (one-click ? parallel session/worktree)

- **B3** ? `site/` trilingual via the shared shim (hoist approach baked in)
- **MULTILINGUAL Phase A** ? es/da/id catalogs (es 3-form plural noted)
- **T11** ? retention sweep (engine repo; you set the window)

? B3 + MULTILINGUAL both edit the catalogs ? don't run them at the same time.

Two things worth your attention

1. **T2** is nearly done by the concurrent session ? their #64 (`VITE\_API\_BASE`) + #65 (alpha deploy kit: CF Pages + `api.\*` tunnel + CF Access, see `deploy/DEPLOY\_ALPHA.md`) cover the plumbing. **Remaining is owner stand-up only:** set up Cloudflare Access, **rotate** `GEMINI\_API\_KEY`, run the deploy. One caveat surfaced by the T4 review: in hosted mode set the engine's `allowed\_video\_root` to a parent of `upload\_dir`, or `/api/process` will reject uploaded files.
2. **Process honesty:** I started the T4 edits on `master` by mistake and caught it **before any commit** ? moved them to a feature branch (`checkout -b` preserves the tree), then rebased onto `origin/master` after your sibling session's #64/#65 landed (clean merge). No master pollution.

Repo is clean: on `master` ? `origin/master` (`ca619fb`), no open PRs of mine, all branches deleted, dev server stopped. The two untracked files (`claude/`, `site/access.db`) pre-existed this session.

Next natural picks: launch the B3/MULTILINGUAL/T11 chips, do the T2 owner stand-up, and tackle A9/A3 + native review.

364. user (2026-06-21T16:53:18.790Z)

please keep merging the green CI PRs and ensure to keep improving the test coverage

365. assistant (2026-06-21T16:54:12.787Z)

On it ? I'll keep building the queued items myself, one PR each, merging on green and adding tests each time. Since I'm doing these here, I'll dismiss the corresponding spawn-off chips so they don't get double-launched. Starting with **MULTILINGUAL Phase A** (mechanical, high coverage value, owner-approved #58).

Let me read the expansion plan's specifics first, and dismiss its chip.

366. user (2026-06-21T16:54:13.790Z)

Task task_e15e9643 withdrawn ? the chip is no longer shown to the user. Continue your current work.

```

1      # Multilingual Expansion ? 7 new locales (th . id . da . es . zh-Hans . ja . ko)
2
3      > **Status:** `DRAFT` ? **owner-gated (approval needed to START this line)** .
**Owner:** Avi Dullu . **Created:** 2026-06-21 . **Last updated:** 2026-06-21
4      > **Lifecycle:** `DRAFT` ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when
DONE)
5      > **Tracking anchors:** §7 progress tracker is the source of truth; index in
`docs/README.md`; pointer in memory `current-state`; thread in `NEXT_STEPS.md` once work starts.
6      > **Relation to existing docs:** **PEER-OF / extends**
[ `FRIENDLY_AND_MULTILINGUAL.md` ] (FRIENDLY_AND_MULTILINGUAL.md) (the `en`/`kn`/`hi` foundation)
and the engine design `I18N_PLAN.md`. **Reuses that foundation verbatim** (react-i18next +
i18next-icu + browser detector + key-parity/no-bare-strings CI + self-hosted OFL Noto via
`@fontsource` + Gemini-draft?native-review). This is a **parallel** line: it adds locales, it
does **not** re-architect i18n.
7      > **Honesty note:** each claim tagged `[verified]` (checked vs the working tree this
session), `[researched]` (sourced, needs sign-off), or `[design]` (proposed). Not legal advice ?
the OFL-font carve-out is the owner's standing call (D7 in FRIENDLY).
8
9      ---
10
11     ## 0. TL;DR
12     Add **Thai, Indonesian, Danish, Spanish, Chinese (Simplified), Japanese, Korean** to the
Studio SPA with the **same rigor as en/kn/hi**. The good news `[verified]`: the i18n foundation
already scales ? **zero changes to the negotiation contract or the catalog format**; adding a
locale is "drop a reviewed `common.json` + (if non-Latin) bundle one OFL Noto font + keep CI
key-parity green." The work splits cleanly into **Phase A** (es/da/id ? *catalog-only, no
fonts*), **Phase B** (Thai ? *one small OFL font*), and **Phase C** (zh-Hans/ja/ko ? *large OFL
CJK fonts + lazy-load + an offline-bundle subsetting decision + the zh script-variant call*).
**The single most important caveats:** (1) **native-speaker review per language** is the real
cost and the public-launch gate (Gemini drafts are *inference-only*, never the source of truth ?
the standing guardrail); (2) **CJK fonts add tens of MB** to the otherwise-tiny air-gapped
bundle; (3) **Spanish now has a 3-form plural** (`one, many, other`) ? the one authoring
wrinkle.
13
14     ## 1. Problem & goal
15     **Why now.** en/kn/hi shipped and proved the foundation is locale-pluggable (a Kannada-
default browser auto-renders Kannada; the switcher walks kn?hi?en). The owner wants to broaden
reach beyond the India beachhead ? **SE Asia (th, id), Europe (da, es), and East Asia (zh, ja,
ko)**.
16     **Concrete outcome ("good"): a user whose browser is in any of the 7 languages lands
on the Studio (and, once `site/` is localized via FRIENDLY B3, the marketing pages too), and ?
without help ? understands the product, runs the tool, and gets a reel, **entirely in their
language**, with the fonts rendering crisply offline.
17     **Read to get current:** this doc §3?§4;
[ `FRIENDLY_AND_MULTILINGUAL.md` ] (FRIENDLY_AND_MULTILINGUAL.md) (the foundation this rides on,
esp. §4 design + §6.5 negotiation tests); `web/src/i18n/index.ts` (the detector/ICU/fallback
config) + `web/src/main.tsx` (the `@fontsource` font-load pattern) +
`web/src/i18n/hygiene.test.ts` (key-parity + no-bare-strings + offline guards).
18
19     ## 2. Decisions locked (inherited from FRIENDLY unless noted)
20     | # | Decision | Source / date | Implication |
21     |---|-----|-----|-----|
22     | ED1 | **Same framework, no re-architecture** ? react-i18next + i18next-icu + `i18next-
browser-languagedetector`; one `en` source catalog + per-locale siblings; **always fall back to
`en`** | FRIENDLY D-* / `i18n/index.ts` `[verified]` | Each new locale = add to
`SUPPORTED_LOCALES` + a `common.json`; negotiation/format unchanged |
23     | ED2 | **Self-host OFL Noto via `@fontsource`** (the D7 OFL-for-media carve-out) ?
**extend it to the 4 new Noto fonts** (Thai, SC, JP, KR) | FRIENDLY D7 (owner, 2026-06-21) | No
new licensing decision; same `main.tsx` import + `unicode-range`-scoped pattern as kn/hi |
24     | ED3 | **Gemini-draft ? native-speaker review** (inference only, never training; every
value flagged for review) | `CLAUDE.md` guardrail | Translation *quality* is human-gated +
owner-paced; CI proves parity, not quality |
25     | ED4 | **CI key-parity + no-bare-strings stay merge gates** for every locale |

```

```

`hygiene.test.ts` `[verified]` | A new catalog must match the `en` key set exactly or CI fails |
26 | ED5 | All 7 are LTR ? no RTL/bidi layout work in this batch | `[researched]`
CLDR/W3C | No `dir="rtl"`, no logical-property audit; RTL (ar/he/ur) would be a separate, larger
track |
27 | ED6 (proposed) | Chinese = `zh-Hans` (Simplified) for v1; zh-Hant`
(Traditional) is a separate catalog + font, added later only on demand | $8 Q2 [design] |
Key the catalog zh-Hans` (not bare zh`) so zh-Hant` slots in cleanly |
28
29 ## 3. Foundation ? research / prior art `[researched]`
30 Per-language diligence (Unicode CLDR plural-rules chart; SIL OFL; @fontsource; W3C
BCP-47 ? sources in $10):
31
32 | Lang | BCP-47 | CLDR cardinal plurals | Dir | Dedicated font (OFL) |
@fontsource(-variable) pkg | Font size / notes |
33 |---|---|---|---|---|---|---|
34 | Thai | th` | other` (1 form) | LTR | Noto Sans Thai | noto-sans-thai` |
small` (single script block) · no-space word-wrap gotcha |
35 | Indonesian | id` | other` (1 form) | LTR | ? (Latin) | ? | pure catalog add |
36 | Danish | da` | one, other` (2) | LTR | ? (Latin) | ? | same shape as English (æ
ø å` in Latin font) |
37 | Spanish | es` | one, many, other` (3) ? | LTR | ? (Latin) | ? | many` =
millions/compact only; ~15% string expansion |
38 | Chinese (Simpl.) | zh-Hans` | other` (1 form) | LTR | Noto Sans SC |
noto-sans-sc` | very large` (~7% MB/weight unsubset) · script-variant decision |
39 | Japanese | ja` | other` (1 form) | LTR | Noto Sans JP | noto-sans-jp` |
very large` (CJK) |
40 | Korean | ko` | other` (1 form) | LTR | Noto Sans KR | noto-sans-kr` |
very large` (Hangul + Han) |
41
42 Three findings that drive the design:
43 1. Spanish's 3-form plural is the only authoring change. Current CLDR es` cardinal
= {one, many, other}; many` fires only on large/compact numbers (e.g. millions), but every
es` ICU plural message must still carry a many {?} arm or intl-messageformat` falls back.
Flag it to the reviewer and extend the parity/lint check. (th/id/zh/ja/ko are single-form ?
trivial; da is 2-form like en.)
44 2. Fonts split the batch. es/da/id need no new font (Latin). th needs one
small` OFL font. zh-Hans/ja/ko need large OFL CJK fonts ? all OFL-1.1 (bundleable under
ED2), all on @fontsource-variable, but multi-MB each.
45 3. CJK + the offline guard collide. @fontsource` serves CJK as ~100+ unicode-
range` woff2` chunks, fetched on demand ? efficient online, but the SPA's air-
gapped/offline guarantee (hygiene.test.ts` "offline / self-contained") means we must ship
all` chunks so any glyph renders with no network ? tens of MB` added with 3 CJK languages.
Mitigations in $4.
46
47 ## 4. Design / architecture
48 Reuse map (what's reused vs new):
49 - Reused unchanged: the negotiation contract (persisted pref ? ?lang=` ? navigator ?
en`), the ICU catalog format, the @fontsource` unicode-range`-scoped self-host pattern
(main.tsx:7-8`), the key-parity + no-bare-strings + offline CI (hygiene.test.ts`), the
draft?review pipeline, the <html lang>` sync` (i18n/index.ts:59-65`).
50 - New: 7 common.json` catalogs; SUPPORTED_LOCALES` entries (i18n/index.ts:18`); 4
new Noto font imports; an es 3-form plural` allowance in the catalog + tooling; a CJK
lazy-load + offline-subset strategy (Phase C); Thai line-break CSS safety net.
51 - Catalog-home caveat `[verified]` catalogs today live at
web/src/i18n/locales/{en,kn,hi}/common.json` ? not` a shared top-level locales/` (the
I18N_PLAN "D-CATALOG-HOME" diagram). This expansion adds siblings there. If FRIENDLY B3` (the
shared site/` t()` shim) hoists them to a shared dir first, these new catalogs move with them
? sequence-aware, not a blocker.
52
53 Negotiation tests (per FRIENDLY $6.5): every new locale gets an N1/N2-style test ? a
browser set to that language auto-renders` it (e.g. navigator.languages=["ja-JP"]` ? `ja`),
region subtags normalize (zh-Hans-CN` ? zh-Hans`), and a missing key falls back to en`.
Auto-selection is the promise; it's proven by a test, never assumed.
54
55 Phasing (least new code/assets first):

```

56 - ****Phase A ? Latin trio (`es`, `da`, `id`): catalog-only, zero new assets.**** Highest ROI, proves the pipeline scales beyond Indic with no code. Only `es` needs the 3-form-plural touch.

57 - ****Phase B ? Thai (`th`): one small OFL font.**** Reuses the kn/hi font pattern exactly; add the no-space word-wrap CSS safety net. Self-contained, low-risk.

58 - ****Phase C ? CJK (`zh-Hans`, `ja`, `ko`): the heavy slice.**** Needs the zh-Hans/Hant decision, 3 large OFL fonts, ****per-locale lazy font-load**** (so non-CJK users never download CJK), and an ****offline-bundle subset strategy**** (ship-all-chunks vs a custom subset build step vs online-lazy-only). One PR per CJK language.

59

60 **## 5. Privacy / scope note**

61 i18n is ****presentation-only**** ? no new personal-data collection, no biometrics, minors-excluded posture unchanged (same as FRIENDLY \$5). Gemini-draft translation is inference, not training, with no user data in the loop. CJK/Thai font bundling is OFL media, not code/weights.

62

63 **## 6. Honest limits ? what this does NOT do**

64 - A green CI / DONE proves ****key-parity + render + no-bare-strings + auto-negotiation****, ****not**** translation ***quality*** (native-review-gated, ED3) or correct font rendering (owner-eyeball-gated, like kn/hi).

65 - ****`zh-Hant` (Traditional) is out of v1**** (separate catalog + font); only `zh-Hans` ships first.

66 - ****No RTL**** ? this batch is all LTR.

67 - The ****CJK offline bundle is large**** (tens of MB) unless a subset build is adopted ? a real size trade-off, not free.

68 - ****`site/` marketing localization for these 7 **depends on FRIENDLY B3** landing first (the shared shim); until then this is SPA-only.**

69

70 **## 7. Deliverables & progress tracker ? **source of truth****

71 Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. ****One small PR per row****, branched from `origin/master`, no stacking.

72

ID	Deliverable	Phase	Depends on	Gated?	Status	PR
E0	This proposal doc + inbound pointers (README/NEXT_STEPS/memory)					**Owner approval to start**
EA1	**Spanish (`es`)** catalog (Gemini-draft) + ICU **3-form `{one,many,other}`** handling + extend key-parity/no-bare-strings tooling for the **many` arm + negotiation test	A	E0	No		
EA2	**Danish (`da`)** catalog + negotiation test	A	E0	No		
EA3	**Indonesian (`id`)** catalog + negotiation test	A	E0	No		
EB1	**Noto Sans Thai** bundle (OFL, **`@fontsource-variable`) + Thai no-space word-wrap CSS safety net	B	E0	No (ED2 carve-out applies)		
EB2	**Thai (`th`)** catalog ? render + negotiation test	B	EB1	No		
EC0	**Decision + design:** `zh-Hans` vs `zh-Hant` (ED6) + CJK **lazy per-locale font-load** + **offline-bundle subset** strategy (ship-all-chunks vs custom subset vs online-lazy)	C	E0	**Owner (Q2/Q3)**		
EC1	**Noto Sans SC** + **`zh-Hans`** catalog + lazy-load + negotiation test	C	EC0	No (after EC0)		
EC2	**Noto Sans JP** + **`ja`** catalog + lazy-load + negotiation test	C	EC0	No		
EC3	**Noto Sans KR** + **`ko`** catalog + lazy-load + negotiation test	C	EC0	No		
EX1	**Native-speaker review** of each AI-drafted catalog (one tracked row; per-language sign-off)					**Owner (reviewer sourcing)**
EX2	**Owner-machine font eyeball** per new script (th, zh, ja, ko) ? cloud CI can't render fonts		EB*/EC*	**Owner (owner machine)**		
EX3	**`site/` marketing parity** for the 7 (rides FRIENDLY **B3** shared `t()` shim)		FRIENDLY B3	Blocked on B3		

88

89 **## 8. Open questions ? owner**

90 1. ****Approve starting this line**** (in parallel with the FRIENDLY UX/A-items), and the ****A ? B ? C phasing****? (E0 gate.)*

91 2. ****Chinese:**** ship ****`zh-Hans` only**** for v1 (recommended), or ****both Hans + Hant****? (EC0; Hant = a whole extra catalog + Noto Sans TC.)*

92 3. ****CJK offline strategy**** (EC0; the real size trade-off):* (a) ship ****all**** font

chunks ? simplest, ****tens of MB**** to the air-gapped bundle; (b) a ****custom subset build**** restricted to glyphs the reviewed catalogs use ? KB-scale but adds a build step that re-runs on catalog change; (c) ****online lazy-load only**** ? small bundle but ****breaks the offline guarantee for CJK****. *Recommend (b) if offline-for-CJK matters, else (a).*

93 4. ****Native-reviewer sourcing**** for 7 languages ? who/how/budget? (Vendor like the Roora labeling pilot? community? paid freelancers?) This is the launch-gate cost.

94 5. ****Priority order**** ? which markets first? (Default A-then-B-then-C is by *engineering cost*; if a market is urgent, e.g. `id` or `ja`, it can jump within its phase.)

95 6. ****Does `site/` localize for these too**** for v1, or SPA-only until FRIENDLY B3 lands? *(EX3.)*

96

97 ## 9. Definition of done

98 - [] All 7 catalogs (`es`, `da`, `id`, `th`, `zh-Hans`, `ja`, `ko`) live + ****rendering**** on the `web/` SPA; switcher + persistence + `en` fallback; ****no raw keys****.

99 - [] ****Auto-negotiation green**** ? a browser set to each language auto-renders it (N1/N2-style tests per locale); region subtags normalize; missing-key ? `en`.

100 - [] ****CI key-parity + no-bare-strings green**** (incl. the `es` 3-form plural) + the ****offline/self-contained guard**** still green after the CJK fonts land.

101 - [] ****Fonts render correctly**** ? owner eyeball per new script (th, zh-Hans, ja, ko).

102 - [] ****Native-speaker review**** complete + signed off per language (EX1).

103 - [] CJK ****offline/bundle-size**** strategy implemented per the EC0 decision; documented bundle-size impact.

104 - [] *(if in scope)* `site/` marketing renders the 7 via the shared shim (EX3, after FRIENDLY B3).

105 - [] \$7 all rows ? (or explicitly deferred) ? flip ****Status ? DONE**** + archive.

106

107 ## 10. References

108 ****Internal `[verified]`**** `web/src/i18n/{index.ts,hygiene.test.ts}`, `web/src/main.tsx` (font-load pattern), `web/src/i18n/locales/{en,kn,hi}/common.json`; [`FRIENDLY\_AND\_MULTILINGUAL.md`] (FRIENDLY_AND_MULTILINGUAL.md), engine `docs/I18N\_PLAN.md`, `docs/UI\_PROPOSAL.md`.

109 ****External `[researched]`**** Unicode CLDR v48 plural-rules chart (https://www.unicode.org/cldr/charts/48/supplemental/language_plural_rules.html) + plural-rules spec; W3C BCP-47 / Chinese script subtags (`zh-Hans`/`zh-Hant`); SIL Open Font License 1.1 + Noto CJK LICENSE (github.com/notofonts/noto-cjk); `@fontsource-variable/noto-sans-{thai,sc,jp,kr}`; W3C Thai line-breaking (`thai-gap`); react-i18next + i18next-icu.

110

111 ---

112

113 ### Changelog

114 - `2026-06-21` ? created. Owner ask: add Thai/Indonesian/Danish/Spanish/Chinese/Japanese/Korean with en/kn/hi-level diligence, as a parallel line for approval. Grounded in a per-language i18n research pass (CLDR plurals, OFL Noto fonts, BCP-47, offline-bundle sizing) + the verified working-tree foundation. Phasing A (Latin) ? B (Thai) ? C (CJK); decisions ED1?ED6; 6 owner questions surfaced (E0 = approval gate).

115

368. assistant (2026-06-21T16:54:31.919Z)

I have the Phase A specs: ****es**** = 3-form `{one, many, other}`, ****da**** = 2-form `{one, other}`, ****id**** = 1-form `{other}` only. Let me read the current complete en catalog to translate from:

369. user (2026-06-21T16:54:32.755Z)

```
1  {
2    "app": {
3      "badge": "pick your rallies · alpha",
4      "title": "Pick the rallies for your reel",
5      "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want."
6    },
7    "lang": {
8      "label": "Language",
9      "en": "English",
```

```

10     "kn": "?????",
11     "hi": "?????"
12 },
13 "bulk": {
14     "selectAll": "Select all",
15     "clear": "Clear",
16     "invert": "Invert"
17 },
18 "mode": {
19     "demo": "These are sample rallies ? process a video above to work on a real match.",
20     "loading": "Finding the rallies in your video?",
21     "error": "Couldn't load this video's rallies: {error}",
22     "loaded": "Found <b>{count}</b> rallies in your video."
23 },
24 "query": {
25     "placeholder": "e.g. over 10s · top 15 longest · shortest first",
26     "ariaLabel": "Filter rallies by length, count or order",
27     "apply": "Apply",
28     "notAvailable": "not available yet",
29     "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
30     "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by
rally length instead.",
31     "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
32     "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
33     "try": "Sample queries:",
34     "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
<x>experimental</x> (under development).",
35 },
36 "grid": {
37     "empty": "No rallies to show yet.",
38     "rally": "Rally {n}",
39     "inReel": "Rally {n}, in reel",
40     "notInReel": "Rally {n}, not in reel",
41     "start": "start",
42     "long": "long",
43     "shots": "~{count} shots · experimental",
44     "shotsTitle": "Shot count is experimental (under development) and may be
inaccurate{conf}. Filter by rally length instead.",
45     "shotsConfidence": " ? confidence: {conf}"
46 },
47 "footer": {
48     "count": "{count, plural, one {# rally} other {# rallies}}",
49     "summaryRest": "selected · {total} total",
50     "reelName": "Reel name",
51     "reelNamePlaceholder": "my-highlights",
52     "build": "Build reel ({count})",
53     "building": "Building?",
54     "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
be skipped, so the build would fail. Pick a longer rally.",
55     "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
they'd all be skipped, so the build would fail. Pick longer rallies.",
56     "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",
57     "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
58 },
59 "result": {
60     "ready": "Your reel is ready",
61     "failed": "Build failed",
62     "building": "Stitching your reel?",
63     "buildingReassure": "Joining your selected rallies into one video ? this usually
only takes a moment.",
64     "dismiss": "Dismiss",
65     "download": "Download {filename}"
66 },
67 "build": {

```

```

68         "noVideo": "These are sample rallies ? process a real video first to build a reel."
69     },
70     "ingest": {
71         "title": "Process a video",
72         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
73         "uriPlaceholder": "gs://your-bucket/match.mp4",
74         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
75         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
76         "submit": "Process video",
77         "submitting": "Submitting?",
78         "cancel": "Cancel",
79         "working": "Processing your video?",
80         "progress": "{progress}",
81         "retry": "Try again",
82         "reassure": "Safe to wait ? KhelSutra keeps working even if your connection is slow;
a long video can take several minutes.",
83         "statusFailed": "Couldn't process",
84         "chooseFile": "Choose a video file",
85         "uploadAria": "Choose a video file to upload",
86         "fileHint": "Pick an .mp4 or .mov from this device ? it uploads, then KhelSutra
finds the rallies.",
87         "orLink": "Or use a cloud link",
88         "uploadingStatus": "Uploading?",
89         "uploadProgress": "Upload progress"
90     },
91     "errors": {
92         "networkError": "Can't reach KhelSutra. Is it running?",
93         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
94         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
95         "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
96         "engineGeneric": "Something went wrong. Please try again."
97     },
98     "selection": {
99         "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
100     }
101 }
102

```

370. assistant (2026-06-21T16:54:39.652Z)

Now I have the complete en catalog. Let me set up the MULTILINGUAL Phase A branch and mark progress:

371. user (2026-06-21T16:54:40.234Z)

Updated task #8 status

372. user (2026-06-21T16:54:41.701Z)

Chapter marked: "MULTILINGUAL Phase A ? es/da/id". Continue your current work.

373. user (2026-06-21T16:54:44.844Z)

branch 'feat/mlx-phaseA-es-da-id' set up to track 'origin/master'.
Switched to a new branch 'feat/mlx-phaseA-es-da-id'
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)

374. assistant (2026-06-21T16:54:56.738Z)

Now add the `lang.es/da/id` autonyms to the existing en/kn/hi catalogs (key-parity needs them everywhere):

375. user (2026-06-21T16:54:58.860Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

376. user (2026-06-21T16:55:06.236Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

377. user (2026-06-21T16:55:12.793Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

378. assistant (2026-06-21T16:57:13.109Z)

Now create the three Phase A catalogs. Spanish first (with the 3-form `{one, many, other}` plural):

379. assistant (2026-06-21T16:57:33.973Z)

```
{
  "app": {
    "badge": "elige tus jugadas · alfa",
    "title": "Elige las jugadas para tu reel",
    "intro": "Filtra por <b>duración de la jugada</b> ? p. ej. <i>?las 15 más largas?</i> ? y luego ajusta tocando las tarjetas. Todo empieza <b>seleccionado</b>; solo quita las que no quieras."
  },
  "lang": {
    "label": "Idioma",
    "en": "English",
    "kn": "?????",
    "hi": "???????",
    "es": "Español",
    "da": "Dansk",
    "id": "Bahasa Indonesia"
  },
  "bulk": {
    "selectAll": "Seleccionar todo",
    "clear": "Borrar",
    "invert": "Invertir"
  },
  "mode": {
    "demo": "Estas son jugadas de ejemplo ? procesa un video arriba para trabajar con un partido real.",
    "loading": "Buscando las jugadas en tu video?",
    "error": "No se pudieron cargar las jugadas de este video: {error}",
    "loaded": "Se encontraron <b>{count}</b> jugadas en tu video."
  },
  "query": {
    "placeholder": "p. ej. over 10s · top 15 longest · shortest first",
    "ariaLabel": "Filtrar jugadas por duración, cantidad u orden",
    "apply": "Aplicar",
    "notAvailable": "aún no disponible",
    "notAvailableTitle": "?{token}? necesita detección de {kind} ? aún no disponible",
    "notAvailableHelp": "El tipo de golpe, los jugadores y el marcador aún no están disponibles ? filtra por duración de la jugada.",
    "unreadable": "No se entendió eso ? prueba con ?over 10s? o ?top 15 longest?.",
    "hint": "Escribe over 10s para jugadas de más de 10 segundos ? o toca un ejemplo abajo.",
```

```

    "try": "Consultas de ejemplo:",
    "support": "Filtrar por <b>duración de la jugada</b> es totalmente compatible. El conteo de golpes es <x>experimental</x> (en desarrollo).",
  },
  "grid": {
    "empty": "Aún no hay jugadas para mostrar.",
    "rally": "Jugada {n}",
    "inReel": "Jugada {n}, en el reel",
    "notInReel": "Jugada {n}, no está en el reel",
    "start": "inicio",
    "long": "de duración",
    "shots": "~{count} golpes · experimental",
    "shotsTitle": "El conteo de golpes es experimental (en desarrollo) y puede ser impreciso{conf}. Filtra por duración de la jugada.",
    "shotsConfidence": " ? confianza: {conf}"
  },
  "footer": {
    "count": "{count, plural, one {# jugada} many {# jugadas} other {# jugadas}}",
    "summaryRest": "seleccionadas · {total} en total",
    "reelName": "Nombre del reel",
    "reelNamePlaceholder": "mis-destacados",
    "build": "Crear reel ({count})",
    "building": "Creando?",
    "floorOne": "<b>Tu única jugada seleccionada</b> tiene menos de {min} golpes ? se omitiría, así que la creación fallaría. Elige una jugada más larga.",
    "floorAll": "<b>Las {count} jugadas seleccionadas</b> tienen menos de {min} golpes ? se omitirían todas, así que la creación fallaría. Elige jugadas más largas.",
    "floorSomeLead": "{count, plural, one {# jugada} many {# jugadas} other {# jugadas}}",
    "floorSomeRest": "con menos de {min} golpes se omitirán al crear (son demasiado cortas).",
  },
  "result": {
    "ready": "Tu reel está listo",
    "failed": "La creación falló",
    "building": "Uniando tu reel?",
    "buildingReassure": "Uniando las jugadas seleccionadas en un solo video ? normalmente solo toma un momento.",
    "dismiss": "Descartar",
    "download": "Descargar {filename}"
  },
  "build": {
    "noVideo": "Estas son jugadas de ejemplo ? procesa un video real primero para crear un reel."
  },
  "ingest": {
    "title": "Procesar un video",
    "intro": "Apunta KhelSutra a un video y encontrará las jugadas por ti ? esto puede tardar unos minutos.",
    "uriPlaceholder": "gs://tu-bucket/partido.mp4",
    "uriAriaLabel": "Ubicación del video ? una URL de bucket gs:// o una ruta en el servidor del motor",
    "hint": "Pega un enlace de almacenamiento en la nube (gs://?), o una ruta a un video en la máquina que ejecuta KhelSutra.",
    "submit": "Procesar video",
    "submitting": "Enviando?",
    "cancel": "Cancelar",
    "working": "Procesando tu video?",
    "progress": "{progress}",
    "retry": "Reintentar",
    "reassure": "Puedes esperar tranquilo ? KhelSutra sigue trabajando aunque tu conexión sea lenta; un video largo puede tardar varios minutos.",
    "statusFailed": "No se pudo procesar",
    "chooseFile": "Elegir un archivo de video",
    "uploadAria": "Elegir un archivo de video para subir",
    "fileHint": "Elige un .mp4 o .mov de este dispositivo ? se sube y luego KhelSutra encuentra las jugadas."
  }

```

```

    "orLink": "O usa un enlace en la nube",
    "uploadingStatus": "Subiendo?",
    "uploadProgress": "Progreso de la subida"
  },
  "errors": {
    "networkError": "No se puede conectar con KhelSutra. ¿Está en ejecución?",
    "invalidUri": "Primero indica la ubicación del video ? un enlace gs:// o una ruta en la máquina que ejecuta KhelSutra.",
    "emptyResult": "El procesamiento terminó pero no se encontraron jugadas en este video. Prueba con una grabación más clara del partido.",
    "timeout": "Esto está tardando más de lo esperado. El trabajo puede seguir en curso ? recarga con el enlace del video, o reintenta.",
    "engineGeneric": "Algo salió mal. Inténtalo de nuevo."
  },
  "selection": {
    "count": "{count, plural, one {# jugada seleccionada} many {# jugadas seleccionadas} other {# jugadas seleccionadas}}"
  }
}

```

380. user (2026-06-21T16:57:33.993Z)

File created successfully at:
 C:\Users\avidu\Projects\khelesutra\web\src\i18n\locales\es\common.json (file state is current in your context ? no need to Read it back)

381. assistant (2026-06-21T16:57:40.989Z)

Now Danish (2-form `{one, other}`):

382. assistant (2026-06-21T16:58:10.036Z)

```

{
  "app": {
    "badge": "vælg dine dueller · alfa",
    "title": "Vælg duellerne til din reel",
    "intro": "Filtrér efter <b>duellens længde</b> ? f.eks. <i>de 15 længste</i> ? og finjustér ved at trykke på kortene. Alt starter <b>valgt</b>; fjern blot dem, du ikke vil have."
  },
  "lang": {
    "label": "Sprog",
    "en": "English",
    "kn": "?????",
    "hi": "?????",
    "es": "Español",
    "da": "Dansk",
    "id": "Bahasa Indonesia"
  },
  "bulk": {
    "selectAll": "Vælg alle",
    "clear": "Ryd",
    "invert": "Vend om"
  },
  "mode": {
    "demo": "Dette er eksempeldueller ? behandl en video ovenfor for at arbejde med en rigtig kamp.",
    "loading": "Finder duellerne i din video?",
    "error": "Kunne ikke indlæse denne videos dueller: {error}",
    "loaded": "Fandt <b>{count}</b> dueller i din video."
  },
  "query": {
    "placeholder": "f.eks. over 10s · top 15 longest · shortest first",
    "ariaLabel": "Filtrér dueller efter længde, antal eller rækkefølge",
    "apply": "Anvend",

```

```

    "notAvailable": "ikke tilgængelig endnu",
    "notAvailableTitle": "?{token}? kræver {kind}-genkendelse ? ikke tilgængelig endnu",
    "notAvailableHelp": "Slagtype, spillere og stilling er ikke tilgængelige endnu ? filtrér
efter duellens længde i stedet.",
    "unreadable": "Kunne ikke læse det ? prøv ?over 10s? eller ?top 15 longest?.",
    "hint": "Skriv over 10s for dueller længere end 10 sekunder ? eller tryk på et eksempel
nedenfor.",
    "try": "Eksempelforespørgsler:",
    "support": "Filtrering efter <b>duellens længde</b> understøttes fuldt ud. Slagtælling er
<x>eksperimentel</x> (under udvikling).",
  },
  "grid": {
    "empty": "Ingen dueller at vise endnu.",
    "rally": "Duel {n}",
    "inReel": "Duel {n}, i reel",
    "notInReel": "Duel {n}, ikke i reel",
    "start": "start",
    "long": "lang",
    "shots": "~{count} slag · eksperimentel",
    "shotsTitle": "Slagtælling er eksperimentel (under udvikling) og kan være unøjagtig{conf}.
Filtrér efter duellens længde i stedet.",
    "shotsConfidence": " ? sikkerhed: {conf}"
  },
  "footer": {
    "count": "{count, plural, one {# duel} other {# dueller}}",
    "summaryRest": "valgt · {total} i alt",
    "reelName": "Reel-navn",
    "reelNamePlaceholder": "mine-højdepunkter",
    "build": "Lav reel ({count})",
    "building": "Laver?",
    "floorOne": "<b>Din eneste valgte duel</b> har færre end {min} slag ? den ville blive
sprunget over, så oprettelsen ville mislykkes. Vælg en længere duel.",
    "floorAll": "<b>Alle {count} valgte dueller</b> har færre end {min} slag ? de ville alle
blive sprunget over, så oprettelsen ville mislykkes. Vælg længere dueller.",
    "floorSomeLead": "{count, plural, one {# duel} other {# dueller}}",
    "floorSomeRest": "med færre end {min} slag springes over ved oprettelsen (de er for korte).",
  },
  "result": {
    "ready": "Din reel er klar",
    "failed": "Oprettelsen mislykkedes",
    "building": "Samler din reel?",
    "buildingReassure": "Samler dine valgte dueller til én video ? det tager normalt kun et
øjeblik.",
    "dismiss": "Afvis",
    "download": "Download {filename}"
  },
  "build": {
    "noVideo": "Dette er eksempeldueller ? behandl en rigtig video først for at lave en reel."
  },
  "ingest": {
    "title": "Behandl en video",
    "intro": "Peg KhelSutra mod en video, så finder den duellerne for dig ? det kan tage et par
minutter.",
    "uriPlaceholder": "gs://din-bucket/kamp.mp4",
    "uriAriaLabel": "Videoplacering ? en gs://-bucket-URL eller en sti på engine-værten",
    "hint": "Indsæt et cloud-lagringslink (gs://?), eller en sti til en video på maskinen, der
kører KhelSutra.",
    "submit": "Behandl video",
    "submitting": "Sender?",
    "cancel": "Annullér",
    "working": "Behandler din video?",
    "progress": "{progress}",
    "retry": "Prøv igen",
    "reassure": "Det er trygt at vente ? KhelSutra arbejder videre, selv hvis din forbindelse er
langsom; en lang video kan tage flere minutter.",
  }
}

```

```

    "statusFailed": "Kunne ikke behandle",
    "chooseFile": "Vælg en videofil",
    "uploadAria": "Vælg en videofil til upload",
    "fileHint": "Vælg en .mp4 eller .mov fra denne enhed ? den uploades, og så finder KhelSutra
duellerne.",
    "orLink": "Eller brug et cloud-link",
    "uploadingStatus": "Uploader?",
    "uploadProgress": "Upload-status"
  },
  "errors": {
    "networkError": "Kan ikke nå KhelSutra. Kører den?",
    "invalidUri": "Angiv først en videoplacering ? et gs://-link eller en sti på maskinen, der
kører KhelSutra.",
    "emptyResult": "Behandlingen er færdig, men der blev ikke fundet nogen dueller i denne
video. Prøv en tydeligere kampoptagelse.",
    "timeout": "Dette tager længere tid end forventet. Jobbet kører måske stadig ? genindlæs med
videolinket, eller prøv igen.",
    "engineGeneric": "Noget gik galt. Prøv igen."
  },
  "selection": {
    "count": "{count, plural, one {# duel valgt} other {# dueller valgt}}"
  }
}

```

383. user (2026-06-21T16:58:10.052Z)

File created successfully at:
C:\Users\avidu\Projects\kheLSutra\web\src\i18n\locales\da\common.json (file state is current in
your context ? no need to Read it back)

384. assistant (2026-06-21T16:58:16.879Z)

Now Indonesian (1-form `{other}` only ? CLDR `id` has no plural distinction):

385. assistant (2026-06-21T16:58:41.783Z)

```

{
  "app": {
    "badge": "pilih reli kamu · alfa",
    "title": "Pilih reli untuk reel kamu",
    "intro": "Filter berdasarkan <b>durasi reli</b> ? mis. <i>?15 terpanjang</i> ? lalu
sesuaikan dengan mengetuk kartu. Semua dimulai <b>terpilih</b>; cukup hapus yang tidak kamu
inginkan."
  },
  "lang": {
    "label": "Bahasa",
    "en": "English",
    "kn": "?????",
    "hi": "???????",
    "es": "Español",
    "da": "Dansk",
    "id": "Bahasa Indonesia"
  },
  "bulk": {
    "selectAll": "Pilih semua",
    "clear": "Hapus",
    "invert": "Balik"
  },
  "mode": {
    "demo": "Ini reli contoh ? proses video di atas untuk mengerjakan pertandingan nyata.",
    "loading": "Mencari reli di video kamu?",
    "error": "Tidak dapat memuat reli video ini: {error}",
    "loaded": "Ditemukan <b>{count}</b> reli di video kamu."
  }
},

```



```

"query": {
  "placeholder": "mis. over 10s · top 15 longest · shortest first",
  "ariaLabel": "Filter reli berdasarkan durasi, jumlah, atau urutan",
  "apply": "Terapkan",
  "notAvailable": "belum tersedia",
  "notAvailableTitle": "?{token}? memerlukan deteksi {kind} ? belum tersedia",
  "notAvailableHelp": "Jenis pukulan, pemain, dan skor belum tersedia ? filter berdasarkan durasi reli saja.",
  "unreadable": "Tidak terbaca ? coba ?over 10s? atau ?top 15 longest?.",
  "hint": "Ketik over 10s untuk reli lebih dari 10 detik ? atau ketuk contoh di bawah.",
  "try": "Contoh kueri:",
  "support": "Memfilter berdasarkan <b>durasi reli</b> sepenuhnya didukung. Hitungan pukulan masih <x>eksperimental</x> (dalam pengembangan).",
},
"grid": {
  "empty": "Belum ada reli untuk ditampilkan.",
  "rally": "Reli {n}",
  "inReel": "Reli {n}, ada di reel",
  "notInReel": "Reli {n}, tidak ada di reel",
  "start": "mulai",
  "long": "durasi",
  "shots": "~{count} pukulan · eksperimental",
  "shotsTitle": "Hitungan pukulan masih eksperimental (dalam pengembangan) dan mungkin tidak akurat{conf}. Filter berdasarkan durasi reli saja.",
  "shotsConfidence": " ? keyakinan: {conf}"
},
"footer": {
  "count": "{count, plural, other {# reli}}",
  "summaryRest": "dipilih · total {total}",
  "reelName": "Nama reel",
  "reelNamePlaceholder": "sorotan-saya",
  "build": "Buat reel ({count})",
  "building": "Membuat?",
  "floorOne": "<b>Satu-satunya reli yang kamu pilih</b> memiliki kurang dari {min} pukulan ? reli itu akan dilewati, jadi pembuatan akan gagal. Pilih reli yang lebih panjang.",
  "floorAll": "<b>Semua {count} reli yang dipilih</b> memiliki kurang dari {min} pukulan ? semuanya akan dilewati, jadi pembuatan akan gagal. Pilih reli yang lebih panjang.",
  "floorSomeLead": "{count, plural, other {# reli}}",
  "floorSomeRest": "dengan kurang dari {min} pukulan akan dilewati saat pembuatan (terlalu pendek).",
},
"result": {
  "ready": "Reel kamu siap",
  "failed": "Pembuatan gagal",
  "building": "Menggabungkan reel kamu?",
  "buildingReassure": "Menggabungkan reli yang kamu pilih menjadi satu video ? biasanya hanya sebentar.",
  "dismiss": "Tutup",
  "download": "Unduh {filename}"
},
"build": {
  "noVideo": "Ini reli contoh ? proses video nyata dulu untuk membuat reel."
},
"ingest": {
  "title": "Proses video",
  "intro": "Arahkan KhelSutra ke sebuah video dan ia akan menemukan reli untukmu ? ini bisa memakan beberapa menit.",
  "uriPlaceholder": "gs://bucket-kamu/pertandingan.mp4",
  "uriAriaLabel": "Lokasi video ? URL bucket gs:// atau path di host engine",
  "hint": "Tempel tautan penyimpanan cloud (gs://?), atau path ke video di mesin yang menjalankan KhelSutra.",
  "submit": "Proses video",
  "submitting": "Mengirim?",
  "cancel": "Batal",
  "working": "Memproses video kamu?",

```

```

    "progress": "{progress}",
    "retry": "Coba lagi",
    "reassure": "Aman untuk menunggu ? KhelSutra terus bekerja meski koneksimu lambat; video
panjang bisa memakan beberapa menit.",
    "statusFailed": "Tidak dapat memproses",
    "chooseFile": "Pilih file video",
    "uploadAria": "Pilih file video untuk diunggah",
    "fileHint": "Pilih .mp4 atau .mov dari perangkat ini ? file diunggah, lalu KhelSutra
menemukan reli.",
    "orLink": "Atau gunakan tautan cloud",
    "uploadingStatus": "Mengunggah?",
    "uploadProgress": "Progres unggahan"
  },
  "errors": {
    "networkError": "Tidak dapat menghubungi KhelSutra. Apakah sedang berjalan?",
    "invalidUri": "Masukkan lokasi video dulu ? tautan gs:// atau path di mesin yang menjalankan
KhelSutra.",
    "emptyResult": "Pemrosesan selesai tetapi tidak ada reli yang ditemukan di video ini. Coba
rekaman pertandingan yang lebih jelas.",
    "timeout": "Ini memakan waktu lebih lama dari perkiraan. Tugas mungkin masih berjalan ? muat
ulang dengan tautan video, atau coba lagi.",
    "engineGeneric": "Terjadi kesalahan. Silakan coba lagi."
  },
  "selection": {
    "count": "{count, plural, other {# reli dipilih}}"}
}

```

386. user (2026-06-21T16:58:41.803Z)

File created successfully at:
C:\Users\avidu\Projects\kheIsutra\web\src\i18n\locales\id\common.json (file state is current in
your context ? no need to Read it back)

387. assistant (2026-06-21T16:58:46.730Z)

Now wire the three locales into `i18n/index.ts`:

388. user (2026-06-21T16:58:50.865Z)

The file C:\Users\avidu\Projects\kheIsutra\web\src\i18n\index.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

389. user (2026-06-21T16:58:56.498Z)

The file C:\Users\avidu\Projects\kheIsutra\web\src\i18n\index.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

390. assistant (2026-06-21T16:59:44.736Z)

Now tests for es/da/id ? render, plural correctness, and negotiation. Appending to
`i18n.test.tsx`:

391. user (2026-06-21T16:59:55.383Z)

The file C:\Users\avidu\Projects\kheIsutra\web\src\i18n\i18n.test.tsx has been updated
successfully. (file state is current in your context ? no need to Read it back)

392. assistant (2026-06-21T17:00:01.918Z)

Now the structural 3-form check in `hygiene.test.ts` (the catalog-tooling test):

393. user (2026-06-21T17:00:07.034Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\hygiene.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

394. user (2026-06-21T17:00:22.700Z)

Exit code 2

Test Files 18 passed (18)
Tests 163 passed (163)

=== tsc ===

src/components/LanguageSwitcher.tsx(6,7): error TS2739: Type '{ en: string; kn: string; hi: string; }' is missing the following properties from type 'Record<"en" | "kn" | "hi" | "es" | "da" | "id", string>': es, da, id

395. assistant (2026-06-21T17:00:32.444Z)

163 tests pass (+10), but tsc caught `LanguageSwitcher`'s `LANG\_LABEL\_KEY` needs the new locales (the `Locale` type expanded). Fixing:

396. user (2026-06-21T17:00:34.584Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\LanguageSwitcher.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

397. user (2026-06-21T17:00:55.563Z)

tsc OK

Test Files 18 passed (18)
Tests 163 passed (163)

? built in 1.17s

398. assistant (2026-06-21T17:01:03.673Z)

tsc, 163 tests, build all green. Let me browser-verify the new locales render and the switcher shows all six. Starting the preview:

399. user (2026-06-21T17:01:06.731Z)

```
{
  "serverId": "b116717c-076f-463c-b562-6b4ea2cbaab3",
  "port": 5174,
  "name": "khelsutra-web",
  "reused": false
}
```

Server started successfully on port 5174.

400. user (2026-06-21T17:01:14.115Z)

Eval failed: Inspected target navigated or closed

401. user (2026-06-21T17:01:22.390Z)

```
{
  "footer": "6 jugadas seleccionadas · 1:22 en total",
  "h1": "Elige las jugadas para tu reel",
  "htmlLang": "es",
  "langs": [
    "English",
    "?????",
    "??????",
    "Español",
    "Dansk",
    "Bahasa Indonesia"
  ]
}
```

```
}
```

402. assistant (2026-06-21T17:01:32.360Z)

Spanish renders perfectly ? h1 in Spanish, the **3-form plural works** ("6 jugadas seleccionadas"), `<html lang="es">`, and the switcher shows all **6 languages**. Let me confirm Danish + Indonesian too:

403. user (2026-06-21T17:01:33.830Z)

undefined

404. user (2026-06-21T17:01:40.918Z)

```
{
  "da_footer": "6 dueller valgt · 1:22 i alt",
  "da_h1": "Vælg duellerne til din reel",
  "lang": "da"
}
```

405. assistant (2026-06-21T17:02:24.253Z)

Danish renders too ("Vælg duellerne til din reel", 2-form plural "6 dueller valgt"). es + da confirmed in-browser; id covered by tests.

Let me add one more durable guard that raises coverage across **all** locales ? a **placeholder-parity** test (catches a dropped `{count}/{error}`/etc. in any translation, which key-parity doesn't):

406. user (2026-06-21T17:02:33.435Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\hygiene.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

407. user (2026-06-21T17:02:45.273Z)

```
? placeholder parity ? every locale preserves en's {placeholders} > da
preserves every {placeholder} that en uses 1ms
? placeholder parity ? every locale preserves en's {placeholders} > es
preserves every {placeholder} that en uses 1ms
  × placeholder parity ? every locale preserves en's {placeholders} >
hi preserves every {placeholder} that en uses 15ms
? placeholder parity ? every locale preserves en's {placeholders} > id
preserves every {placeholder} that en uses 1ms
  × placeholder parity ? every locale preserves en's {placeholders} >
kn preserves every {placeholder} that en uses 2ms
? no-bare-strings ? user-facing component attributes go through t() >
App.tsx: no hardcoded placeholder/aria-label/title 1ms
? no-bare-strings ? user-facing component attributes go through t() >
components/QueryBar.tsx: no hardcoded placeholder/aria-label/title 0ms
? no-bare-strings ? user-facing component attributes go through t() >
components/RallyGrid.tsx: no hardcoded placeholder/aria-label/title 0ms
? no-bare-strings ? user-facing component attributes go through t() >
components/SelectionFooter.tsx: no hardcoded placeholder/aria-label/title
0ms
? no-bare-strings ? user-facing component attributes go through t() >
components/CompileResult.tsx: no hardcoded placeholder/aria-label/title
0ms
? no-bare-strings ? user-facing component attributes go through t() >
components/LanguageSwitcher.tsx: no hardcoded placeholder/aria-label/title
0ms
? no-bare-strings ? user-facing component attributes go through t() >
components/IngestPanel.tsx: no hardcoded placeholder/aria-label/title
1ms
```

Test Files 1 failed | 17 passed
(18)
Tests 2 failed | 166 passed
(168)

408. assistant (2026-06-21T17:02:54.321Z)

The new guard immediately caught **real** pre-existing placeholder bugs in the kn and hi catalogs** (es/da/id pass). Let me see exactly what drifted:

409. user (2026-06-21T17:02:59.233Z)

```
× placeholder parity ? every locale preserves en's {placeholders} >
hi preserves every {placeholder} that en uses 10ms
  ? expected [ { key: 'mode.loading', ?(2) }, ?(1) ] to deeply equal []
× placeholder parity ? every locale preserves en's {placeholders} >
kn preserves every {placeholder} that en uses 1ms
  ? expected [ { key: 'mode.loading', ?(2) }, ?(1) ] to deeply equal []
  ? offline / self-contained ? no external runtime assets > web/index.html
loads no absolute-URL <link>/<script src> (everything is bundled/local) 0ms
FAIL src/i18n/hygiene.test.ts > placeholder parity ? every locale
preserves en's {placeholders} > hi preserves every {placeholder} that en uses
FAIL src/i18n/hygiene.test.ts > placeholder parity ? every locale
preserves en's {placeholders} > kn preserves every {placeholder} that en uses
AssertionError: expected [ { key: 'mode.loading', ?(2) }, ?(1) ] to deeply equal
[]
- Expected
+ Received
+   "key": "mode.loading",
+   "key": "mode.error",
77|         if (a.join(",") !== b.join(",")) mismatches.push({ key, en: a,?
```

410. assistant (2026-06-21T17:04:20.854Z)

Excellent ? the guard immediately earned its keep: it caught a **real** pre-existing bug**. The drift is in `mode.loading` + `mode.error` for **kn** and **hi** ? they still carry a `{videoId}` placeholder that A1 (#60) removed from the en copy. This is exactly the A1 translation-drift I flagged at the start of the session; now it's caught by a test. Fixing it (re-draft the stale kn/hi `mode.\*` + `build.noVideo` to match A1's friendly en copy):

411. user (2026-06-21T17:04:29.400Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

412. user (2026-06-21T17:04:42.406Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

413. user (2026-06-21T17:04:57.943Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

414. user (2026-06-21T17:05:05.651Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

415. user (2026-06-21T17:05:24.966Z)

Test Files 18 passed (18)

Tests 168 passed (168)
=== tsc ===
tsc OK
=== build ===
? built in 1.05s

416. assistant (2026-06-21T17:05:39.474Z)

All **168 tests** green (placeholder guard now passes for every locale), tsc + build clean, and the kn/hi A1 drift is fixed. Committing MULTILINGUAL Phase A:

417. user (2026-06-21T17:05:42.084Z)

branch: feat/mlx-phaseA-es-da-id
web/src/components/LanguageSwitcher.tsx
web/src/i18n/hygiene.test.ts
web/src/i18n/i18n.test.tsx
web/src/i18n/index.ts
web/src/i18n/locales/da/common.json
web/src/i18n/locales/en/common.json
web/src/i18n/locales/es/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/id/common.json
web/src/i18n/locales/kn/common.json
--- base (only my work) ---

418. user (2026-06-21T17:05:59.465Z)

To <https://github.com/avidullu/khelsutra.git>
* [new branch] feat/mlx-phaseA-es-da-id -> feat/mlx-phaseA-es-da-id

419. user (2026-06-21T17:06:07.235Z)

Server b116717c-076f-463c-b562-6b4ea2cbaab3 stopped

420. user (2026-06-21T17:06:21.661Z)

<https://github.com/avidullu/khelsutra/pull/67>

421. assistant (2026-06-21T17:06:32.705Z)

PR [#67](<https://github.com/avidullu/khelsutra/pull/67>) created. Let me mark Phase A done in the `MULTILINGUAL\_EXPANSION.md` \$7 tracker:

422. user (2026-06-21T17:06:33.438Z)

73	ID Deliverable Phase Depends on Gated? Status PR
74	---- ----- ----- ----- ----- ----- ----
75	E0 This proposal doc + inbound pointers (README/NEXT_STEPS/memory) ? ? **Owner approval to start** ? ?
76	EA1 **Spanish (`es`)** catalog (Gemini-draft) + ICU **3-form `{one,many,other}`** handling + extend key-parity/no-bare-strings tooling for the `many` arm + negotiation test A
E0	No (after approval) ? ?
77	EA2 **Danish (`da`)** catalog + negotiation test A E0 No ? ?
78	EA3 **Indonesian (`id`)** catalog + negotiation test A E0 No ? ?
79	EB1 **Noto Sans Thai** bundle (OFL, `@fontsource-variable`) + Thai no-space word-wrap CSS safety net B E0 No (ED2 carve-out applies) ? ?
80	EB2 **Thai (`th`)** catalog ? render + negotiation test B EB1 No ? ?

423. user (2026-06-21T17:06:42.589Z)

The file C:\Users\avidu\Projects\khelsutra\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

424. user (2026-06-21T17:06:54.362Z)

The file C:\Users\avidu\Projects\khelsutra\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

425. user (2026-06-21T17:07:05.172Z)

The file C:\Users\avidu\Projects\khelsutra\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

426. user (2026-06-21T17:07:41.086Z)

```
pushed
site    pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27911498681/job/82589300488
Workers Builds: hidden-king-khelsutra    pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8f1a264a-845e-4ea1-818d-718b4b67deb8
web      pending 0
https://github.com/avidullu/khelsutra/actions/runs/27911498681/job/82589300499
```

427. user (2026-06-21T17:08:09.113Z)

```
poll 1: web=pending cf=pass
poll 2: web=pass cf=pass
=== final ===
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8f1a264a-845e-4ea1-818d-718b4b67deb8
site    pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27911498681/job/82589300488
web      pass    29s
https://github.com/avidullu/khelsutra/actions/runs/27911498681/job/82589300499
```

428. assistant (2026-06-21T17:08:15.506Z)

All green. Merging MULTILINGUAL Phase A:

429. user (2026-06-21T17:08:24.311Z)

```
create mode 100644 web/src/i18n/locales/es/common.json
create mode 100644 web/src/i18n/locales/id/common.json
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
```

430. assistant (2026-06-21T17:10:59.076Z)

MULTILINGUAL Phase A merged (#67 ? `a2292ef`) ? that's **5 PRs this session** plus a coverage win: the new placeholder-parity guard caught and fixed a real kn/hi A1-drift bug.

Continuing the cadence with **A9 ? tap-only filter controls** (the \$6.5 bridge for non-English-typing kn/hi users), a clean self-contained SPA feature with good coverage and no engine collision. Let me set it up.

431. user (2026-06-21T17:10:59.631Z)

Updated task #8 status

432. user (2026-06-21T17:11:01.552Z)

Task #9 created successfully: A9 ? tap-only localized filter controls (SPA)

433. user (2026-06-21T17:11:04.763Z)

branch 'feat/a9-tap-filters' set up to track 'origin/master'.
Switched to a new branch 'feat/a9-tap-filters'
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)

434. user (2026-06-21T17:11:42.389Z)

```
1      import { describe, it, expect } from "vitest";
2      import { EXAMPLES } from "../QueryBar";
3      import { parseQuery } from "../lib/query";
4
5      // The example chips apply on tap, so a broken example would silently do nothing (or
6      // show a // "couldn't read that"). Pin that EVERY shipped example is a recognized, fully-
7      // available query
8      // (no unsupported tokens) ? a regression guard for the duration-led example set.
9      describe("QueryBar examples", () => {
10         it("are all recognized, actionable, and fully available (no experimental/unsupported
11         tokens)", () => {
12             for (const ex of EXAMPLES) {
13                 const q = parseQuery(ex);
14                 expect(q.recognized, ex).toBe(true);
15                 expect(q.unavailable, ex).toEqual([]);
16                 // every example must actually constrain or order the set
17                 expect(q.filters.length > 0 || q.sort !== null || q.limit !== null, ex).toBe(true);
18             }
19         });
20     });
21     it("lead with rally length, not the experimental shot-count axis", () => {
22         const shotExamples = EXAMPLES.filter((ex) => parseQuery(ex).filters.some((f) =>
23         f.field === "shot_count"));
24         expect(shotExamples).toEqual([]);
25     });
26 });
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
```

435. user (2026-06-21T17:11:43.076Z)

Chapter marked: "A9 ? tap-only localized filters". Continue your current work.

436. assistant (2026-06-21T17:12:35.543Z)

The `EXAMPLES` test pins the English chips. I'll keep those (English "type-this" hints) and add a complementary **localized** `TapFilters` control set ? and pin that each tap builds the exact same query as typing its English equivalent (tap == type). Building the component:

437. assistant (2026-06-21T17:12:45.925Z)

```
// Localized tap-only filter controls (tracker A9). The query bar PARSES ENGLISH text (a
// documented
// limit) ? so a Kannada/Hindi/? user who can't type English needs to filter by TAPPING. Each
// control
// builds the SAME ParsedQuery the parser would for its English equivalent ? directly, no
// English
// round-trip ? and applies it through the shared onApply path. A test pins tap == type so a
// control
// can never silently drift from the parser. Length-led + fully-available only (never shot-
// count).
import { useTranslation } from "react-i18next";
import type { ParsedQuery } from "../lib/query";

interface TapFilter {
    /** i18n label key (localized) ? the user sees this, not the English query. */
    key: string;
    /** The equivalent typed query; the tap MUST select identically to typing this (pinned by a
```



```

test). */
  english: string;
  parts: Pick<ParsedQuery, "filters" | "sort" | "limit">;
}

export const TAP_FILTERS: TapFilter[] = [
  { key: "tap.longest", english: "longest first", parts: { filters: [], sort: { key: "duration",
dir: "desc" } } },
  { key: "tap.shortest", english: "shortest first", parts: { filters: [], sort: { key:
"duration", dir: "asc" } } },
  { key: "tap.over10", english: "over 10s", parts: { filters: [{ field: "duration", op: ">",
value: 10 } ] } },
  { key: "tap.over20", english: "over 20s", parts: { filters: [{ field: "duration", op: ">",
value: 20 } ] } },
  { key: "tap.top5", english: "top 5", parts: { filters: [], sort: { key: "duration", dir:
"desc" }, limit: 5 } },
  { key: "tap.top10", english: "top 10", parts: { filters: [], sort: { key: "duration", dir:
"desc" }, limit: 10 } },
];

interface Props {
  /** Same handler the QueryBar uses ? App runs runQuery + writes the shared selection. */
  onApply: (q: ParsedQuery, source: "typed" | "example") => void;
}

export function TapFilters({ onApply }: Props) {
  const { t } = useTranslation();
  // ?44px tap targets (A4) so the no-type path is comfortable on a phone.
  const BTN = "inline-flex min-h-11 items-center rounded-full border border-black/15 px-4 text-
sm hover:border-green";

  return (
    <div className="mt-3" data-testid="tap-filters">
      <span className="text-xs text-ink/40">{t("tap.title")}</span>
      <div className="mt-1.5 flex flex-wrap gap-2">
        {TAP_FILTERS.map((f) => (
          <button
            key={f.key}
            type="button"
            className={BTN}
            onClick={() =>
              onApply(
                { raw: `tap:${f.key}`, filters: f.parts.filters, sort: f.parts.sort, limit:
f.parts.limit, unavailable: [], recognized: true },
                "example",
              )
            }
          >
            {t(f.key)}
          </button>
        ))}
      </div>
    </div>
  );
}

```

438. user (2026-06-21T17:12:45.941Z)

File created successfully at:

C:\Users\avidu\Projects\khusutra\web\src\components\TapFilters.tsx (file state is current in
your context ? no need to Read it back)

439. assistant (2026-06-21T17:12:57.936Z)

Now the `tap.\*` keys in all six catalogs. en:

440. user (2026-06-21T17:13:00.755Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

441. user (2026-06-21T17:13:13.900Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

442. user (2026-06-21T17:13:23.764Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

443. user (2026-06-21T17:13:32.524Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\es\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

444. user (2026-06-21T17:13:40.881Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\da\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

445. user (2026-06-21T17:13:49.457Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\id\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

446. assistant (2026-06-21T17:13:55.433Z)

Now wire `TapFilters` into App (below the QueryBar) and add it to the no-bare-strings file list:

447. user (2026-06-21T17:13:57.213Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

448. user (2026-06-21T17:14:04.390Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

449. user (2026-06-21T17:14:11.079Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\hygiene.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

450. assistant (2026-06-21T17:14:42.613Z)

Now the TapFilters test (render, onApply, the tap==type invariant, localized labels, ?44px):

451. assistant (2026-06-21T17:14:51.302Z)

```
// @vitest-environment jsdom
//
// A9 ? localized tap-only filters. The load-bearing guarantee: each tap selects IDENTICALLY to
// typing its English equivalent (tap == type), so a Kannada/Hindi/? user who taps gets exactly
// what
// an English user who types gets ? the parser stays the single source of truth.
import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
import { render, screen, cleanup, fireEvent } from "@testing-library/react";
```

```

import i18n from "../i18n";
import { TapFilters, TAP_FILTERS } from "../TapFilters";
import { parseQuery } from "../lib/query";

beforeEach(async () => {
  await i18n.changeLanguage("en");
});
afterEach(() => cleanup());

describe("TapFilters (A9)", () => {
  it("each tap builds the SAME query as typing its English equivalent (tap == type)", () => {
    for (const f of TAP_FILTERS) {
      const typed = parseQuery(f.english);
      expect(typed.recognized, f.english).toBe(true);
      expect(typed.unavailable, f.english).toEqual([]); // length-led, fully available ? never
    }
    shot-count
    expect({ filters: typed.filters, sort: typed.sort, limit: typed.limit },
    f.english).toEqual({
      filters: f.parts.filters,
      sort: f.parts.sort,
      limit: f.parts.limit,
    });
  });
});

it("tapping a control applies a recognized query through onApply", () => {
  const onApply = vi.fn();
  render(<TapFilters onApply={onApply} />);
  fireEvent.click(screen.getByRole("button", { name: "Over 10 seconds" }));
  expect(onApply).toHaveBeenCalledTimes(1);
  const [q, source] = onApply.mock.calls[0];
  expect(source).toBe("example");
  expect(q.recognized).toBe(true);
  expect(q.filters).toEqual([{ field: "duration", op: ">", value: 10 }]);
  expect(q.unavailable).toEqual([]);
});

it("renders localized control labels (Kannada)", async () => {
  await i18n.changeLanguage("kn");
  render(<TapFilters onApply={() => {}} />);
  expect(screen.getByText("??? ?????? ??????")).toBeTruthy(); // tap.longest ? Kannada
  await i18n.changeLanguage("en");
});

it("every control is a 44px tap target (A4)", () => {
  render(<TapFilters onApply={() => {}} />);
  for (const f of TAP_FILTERS) {
    expect(screen.getByText(i18n.t(f.key)).className, f.key).toMatch(/min-h-11/);
  }
});
});

```

452. user (2026-06-21T17:14:51.330Z)

File created successfully at:

C:\Users\avidu\Projects\kheIsutra\web\src\components\TapFilters.test.tsx (file state is current in your context ? no need to Read it back)

453. user (2026-06-21T17:15:13.166Z)

```

Test Files 19 passed (19)
Tests 173 passed (173)
=== tsc ===
tsc OK
=== build ===

```

? built in 1.23s

454. assistant (2026-06-21T17:15:20.011Z)

173 tests (+5), tsc + build clean. Let me browser-verify A9 ? the tap controls render and actually filter:

455. user (2026-06-21T17:15:23.307Z)

```
{
  "serverId": "db54b1fa-72ce-4237-be96-32791b41b21d",
  "port": 5174,
  "name": "khelsutra-web",
  "reused": false
}
```

Server started successfully on port 5174.

456. user (2026-06-21T17:15:32.049Z)

```
{
  "labels": [
    "Længste først",
    "Korteste først",
    "Over 10 sekunder",
    "Over 20 sekunder",
    "De 5 længste",
    "De 10 længste"
  ],
  "lang": "da",
  "present": true,
  "title": "Eller tryk for at filtrere:"
}
```

457. assistant (2026-06-21T17:15:43.421Z)

TapFilters renders + localizes (showing Danish labels since the browser was still set to `da`). Let me reload to en, tap "Over 10 seconds", and confirm it actually filters the selection:

458. user (2026-06-21T17:15:44.434Z)

undefined

459. user (2026-06-21T17:15:50.354Z)

Successfully clicked: [data-testid="tap-filters"] button:nth-of-type(3)

460. user (2026-06-21T17:15:57.649Z)

```
{
  "clicked": "Over 10 seconds (3rd)",
  "enLabels": [
    "Longest first",
    "Shortest first",
    "Over 10 seconds",
    "Over 20 seconds",
    "Top 5 longest",
    "Top 10 longest"
  ],
  "lang": "en",
  "summary": "6 rallies selected · 1:22 total"
}
```

461. assistant (2026-06-21T17:16:13.756Z)

The click raced the reload. Page is stable now (en). Let me click "Over 10 seconds" and re-check the selection:

462. user (2026-06-21T17:16:14.357Z)

Successfully clicked: [data-testid="tap-filters"] button:nth-of-type(3)

463. user (2026-06-21T17:16:20.651Z)

"6 rallies selected · 1:22 total"

464. assistant (2026-06-21T17:16:30.736Z)

Still 6 ? the tap isn't filtering. Let me check the console logs to see what `onApply` did:

465. user (2026-06-21T17:16:31.249Z)

```
[error] {"ts":"2026-06-21T17:15:44.663Z","level":"error","event":"api.http_error","cid":"5bf6d848-d685-4b01-83f6-8741b84b7430","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T17:15:44.663Z","level":"error","event":"api.http_error","cid":"5bf6d848-d685-4b01-83f6-8741b84b7430","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T17:15:44.663Z","level":"error","event":"api.http_error","cid":"5bf6d848-d685-4b01-83f6-8741b84b7430","method":"GET","url":"/api/config","status":500,"body":""}
[warn] {"ts":"2026-06-21T17:15:44.663Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.663Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.663Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.663Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[error] {"ts":"2026-06-21T17:15:44.665Z","level":"error","event":"api.http_error","cid":"7c83df6a-94c5-4ca0-a8e3-6f71725a6700","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T17:15:44.665Z","level":"error","event":"api.http_error","cid":"7c83df6a-94c5-4ca0-a8e3-6f71725a6700","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T17:15:44.665Z","level":"error","event":"api.http_error","cid":"7c83df6a-94c5-4ca0-a8e3-6f71725a6700","method":"GET","url":"/api/config","status":500,"body":""}
[error] {"ts":"2026-06-21T17:15:44.665Z","level":"error","event":"api.http_error","cid":"7c83df6a-94c5-4ca0-a8e3-6f71725a6700","method":"GET","url":"/api/config","status":500,"body":""}
[warn] {"ts":"2026-06-21T17:15:44.665Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.665Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.665Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
[warn] {"ts":"2026-06-21T17:15:44.665Z","level":"warn","event":"config.unavailable","error":"ApiError: GET /api/config failed: 500"}
```

(Showing last 15 of 80 entries. Use 'lines' parameter (max 200) to see more.)

466. assistant (2026-06-21T17:16:51.647Z)

Let me trigger the tap via a native click in-page (more reliable for React delegation) and read the result:

467. user (2026-06-21T17:16:55.883Z)

```
{
  "clickedLabel": "Over 10 seconds",
  "selectedCards": 3,
  "summary": "3 rallies selected · 1:02 total"
}
```

468. assistant (2026-06-21T17:17:15.447Z)

A9 works in-browser: tapping "Over 10 seconds" filtered to **3 rallies (1:02)** ? tap == type confirmed, and labels localize (Danish earlier, English now). 173 tests, tsc, build green.

Let me run a focused adversarial review, then commit. Capturing the diff:

469. user (2026-06-21T17:17:17.221Z)

```
diff --git a/web/src/App.tsx b/web/src/App.tsx
index 4ab5002..34f546e 100644
--- a/web/src/App.tsx
+++ b/web/src/App.tsx
@@ -3,6 +3,7 @@ import { useTranslation, Trans } from "react-i18next";
import { useRallySelection } from "../hooks/useRallySelection";
import { RallyGrid } from "../components/RallyGrid";
import { QueryBar } from "../components/QueryBar";
+import { TapFilters } from "../components/TapFilters";
import { SelectionFooter } from "../components/SelectionFooter";
import { LanguageSwitcher } from "../components/LanguageSwitcher";
import { CompileResult, type BuildState } from "../components/CompileResult";
@@ -247,6 +248,8 @@ export default function App() {

    <div className="mt-6">
      <QueryBar onApply={onApplyQuery} />
+      /* A9: localized tap controls for users who can't type the English query syntax. */
+      <TapFilters onApply={onApplyQuery} />
    </div>

    <div className="mt-6 flex flex-wrap gap-2 text-sm">
diff --git a/web/src/components/TapFilters.tsx b/web/src/components/TapFilters.tsx
new file mode 100644
index 0000000..c0ed250
--- /dev/null
+++ b/web/src/components/TapFilters.tsx
@@ -0,0 +1,58 @@
+// Localized tap-only filter controls (tracker A9). The query bar PARSES ENGLISH text (a
+// documented
+// limit) ? so a Kannada/Hindi/? user who can't type English needs to filter by TAPPING. Each
+// control
+// builds the SAME ParsedQuery the parser would for its English equivalent ? directly, no
+// English
+// round-trip ? and applies it through the shared onApply path. A test pins tap == type so a
+// control
+// can never silently drift from the parser. Length-led + fully-available only (never shot-
+// count).
+import { useTranslation } from "react-i18next";
+import type { ParsedQuery } from "../lib/query";
+
+interface TapFilter {
+  /** i18n label key (localized) ? the user sees this, not the English query. */
```

```

+ key: string;
+ /** The equivalent typed query; the tap MUST select identically to typing this (pinned by a
test). */
+ english: string;
+ parts: Pick<ParsedQuery, "filters" | "sort" | "limit">;
+}
+
+export const TAP_FILTERS: TapFilter[] = [
+ { key: "tap.longest", english: "longest first", parts: { filters: [], sort: { key:
"duration", dir: "desc" } } },
+ { key: "tap.shortest", english: "shortest first", parts: { filters: [], sort: { key:
"duration", dir: "asc" } } },
+ { key: "tap.over10", english: "over 10s", parts: { filters: [{ field: "duration", op: ">",
value: 10 } ] } },
+ { key: "tap.over20", english: "over 20s", parts: { filters: [{ field: "duration", op: ">",
value: 20 } ] } },
+ { key: "tap.top5", english: "top 5", parts: { filters: [], sort: { key: "duration", dir:
"desc" }, limit: 5 } },
+ { key: "tap.top10", english: "top 10", parts: { filters: [], sort: { key: "duration", dir:
"desc" }, limit: 10 } },
+];
+
+interface Props {
+ /** Same handler the QueryBar uses ? App runs runQuery + writes the shared selection. */
+ onApply: (q: ParsedQuery, source: "typed" | "example") => void;
+}
+
+export function TapFilters({ onApply }: Props) {
+ const { t } = useTranslation();
+ // ?44px tap targets (A4) so the no-type path is comfortable on a phone.
+ const BTN = "inline-flex min-h-11 items-center rounded-full border border-black/15 px-4 text-
sm hover:border-green";
+
+ return (
+ <div className="mt-3" data-testid="tap-filters">
+ <span className="text-xs text-ink/40">{t("tap.title")}</span>
+ <div className="mt-1.5 flex flex-wrap gap-2">
+ {TAP_FILTERS.map((f) => (
+ <button
+ key={f.key}
+ type="button"
+ className={BTN}
+ onClick={() =>
+ onApply(
+ { raw: `tap:${f.key}`, filters: f.parts.filters, sort: f.parts.sort, limit:
f.parts.limit, unavailable: [], recognized: true },
+ "example",
+ )
+ )}
+ </div>
+ </div>
+ );
+}

```

470. assistant (2026-06-21T17:17:24.620Z)

Clean diff. Running a 2-lens adversarial review (correctness/tap-invariant + UX/faithfulness):

471. user (2026-06-21T17:17:44.202Z)

Workflow launched in background. Task ID: wg7x6iy0g

Summary: Adversarial review of the A9 tap-only localized filters
Transcript dir: C:\Users\avidu\claudel\projects\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\subagents\workflows\wf_5d655769-ba4
Script file: C:\Users\avidu\claudel\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\A9-review-wf_5d655769-ba4.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claudel\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\A9-review-wf_5d655769-ba4.js"} to iterate without resending the script.)
Run ID: wf_5d655769-ba4
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claudel\projects\C--Users-avidu-Projects-khelsutra\2ba49afa-99f4-41f2-86a2-27a289d432f3\workflows\scripts\A9-review-wf_5d655769-ba4.js", resumeFromRunId: "wf_5d655769-ba4"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

472. user (2026-06-21T17:17:51.830Z)

Server db54b1fa-72ce-4237-be96-32791b41b21d stopped

473. user (2026-06-21T17:20:16.981Z)

<retrieval_status>success</retrieval_status>

<task_id>wg7x6iy0g</task_id>

<task_type>local_workflow</task_type>

<status>completed</status>

<output>

```
{
  "summary": "Adversarial review of the A9 tap-only localized filters",
  "agentCount": 2,
  "logs": [],
  "result": [
    {
      "lens": "correctness",
      "summary": "A9 is CORRECT. The tap==type invariant holds for all six controls ? I manually traced each through parseQuery: \"longest first\" ? {sort:duration/desc}, \"shortest first\" ? {sort:duration/asc}, \"over 10s\"/\"over 20s\" ? {filters:[duration>10]/[duration>20]} with no sort and no limit, \"top 5\"/\"top 10\" ? {sort:duration/desc, limit:5/10} (the \"top N\" branch sets sortFromLimit=true ? duration desc, validation passes for positive integers). All match the hardcoded TAP_FILTERS.parts exactly. The pinning test deep-equals the full {filters,sort,limit} triple plus asserts unavailable==[], so it would catch any drift including a sort the parts omit (verified: over10/over20 produce sort:undefined on both sides, since no SORT_PATTERN matches and no limit triggers a phantom sort). The constructed ParsedQuery (recognized:true, unavailable:[], raw:\"tap:tap.longest\") flows through App.onApplyQuery identically to a typed query: it passes the !recognized guard, runs runQuery + sel.apply + setOrder, and logs query.parse/query.apply. The \"tap:...\" raw string is only ever echoed into log lines via parseTrace ? never re-parsed ? so it's safe. All controls are length-led (sort key + filter field are duration only; no shot_count, no unavailable tokens) per the doc. Full web suite green (173 tests, including TapFilters.test.tsx 4, hygiene 28, query 46), tsc --noEmit exits 0. tap.* block present in all six catalogs (en/kn/hi/es/da/id) with title + 6 control labels and key-parity enforced by the hygiene test. The diff is scoped cleanly to A9. No findings.",
      "findings": []
    },
    {
      "lens": "ux-faithfulness",
      "summary": "A9 is solid, well-tested work that faithfully meets the tracker intent. The TapFilters component builds a ParsedQuery directly (no English round-trip), routes through the shared onApply path, is pinned tap==type by a test, uses real ?44px <button>s with localized text labels, and ships localized tap.* blocks for all 6 locales. I reproduced the verification locally: 173 web tests pass, tsc --noEmit is clean. The no-bare-strings hygiene test DOES cover
```


TapFilters (added to its FILES list, line 107). Findings below are all minor/nit ? the main one is the genuine UX redundancy you flagged: two chip rows stacked directly on top of each other, one English-only and one localized, which is confusing clutter for the exact non-tech, non-English-typing user A9 targets. My concrete recommendation: differentiate the copy and, for non-English locales, suppress the English-only QueryBar examples row (it is the only English-only chip row left on the screen for a kn/hi user). FAITHFULNESS: A9 meets \$6.4 (\`kn/hi users rely on tap-only controls\`) and \$7 A9 (\`tap-only filter controls alongside the English query bar\`); nothing essential is missing ? reset is covered by the existing Select-all bulk control. No blockers.",

```

    "findings": [
      {
        "severity": "minor",
        "file": "web/src/components/QueryBar.tsx",
        "location": "QueryBar.tsx:90-102 (EXAMPLES row) + App.tsx:250-252 (TapFilters rendered
directly below)",
        "title": "Two stacked chip rows ? the English-only QueryBar examples row is dead
weight for the very user A9 targets",
        "detail": "On screen the user now sees, in order: 'Sample queries:' + HARDCODED
English chips ('over 10s', 'top 15 longest', 'shortest first', 'first 10') from
QueryBar.EXAMPLES, then a support note, then 'Or tap to filter:' + the localized A9 chips. The
EXAMPLES chips render literal English strings regardless of locale (QueryBar.tsx:99 renders
`{ex}` directly, not a t() key) ? so a Kannada/Hindi user gets a row of untappable-by-meaning
English text immediately above the localized tap row. For the non-English-typing user A9 exists
to serve, that first row is exactly the typing-syntax wall A9 is meant to route around, and
stacking it on top of the localized row is confusing clutter. Note the two rows are NOT pure
duplicates (EXAMPLES has 'top 15 longest'/'first 10'; A9 has 'Top 5'/'Top 10'/'Over 20s'), so a
straight 'merge' would drop functionality.",
        "suggestion": "Differentiate + de-clutter rather than keep both as-is. Cleanest: make
the QueryBar EXAMPLES row a teaching aid for the TYPED path (keep it, but only show it when
free-text typing is plausible) and let A9 own the tap path. A low-risk concrete step: in
QueryBar, hide the 'Sample queries:' row when i18n.language !== 'en' (it teaches English syntax
that a non-English user can't act on), so non-English locales see ONLY the localized tap row.
Alternatively, re-label the rows so they read as distinct affordances ('Type a query
(examples):' vs 'Or tap to filter:'). Either is a small follow-up; not a blocker."
      },
      {
        "severity": "nit",
        "file": "web/src/components/TapFilters.tsx",
        "location": "TapFilters.tsx:38 (t(`tap.title`)) + en common.json tap.title=`Or tap
to filter:`",
        "title": "tap.title copy ('Or tap to filter:') reads as a continuation of the row
above it",
        "detail": "The leading 'Or' makes the section copy depend on the English 'Sample
queries:' row sitting immediately above it. If the examples row is ever hidden/reordered (see
the redundancy finding) or on a narrow phone where the rows wrap apart, 'Or tap to filter:'
dangles with no antecedent. The localized sets faithfully copy the 'Or?' construction (kn
'????', es 'O toca?', da 'Eller?', id 'Atau?'), so the dependency is replicated across all 6
locales.",
        "suggestion": "Make the label self-contained, e.g. 'Tap to filter:' (drop the leading
'Or'), so the section stands on its own regardless of what precedes it. Re-translate the 6
tap.title values to match. Purely cosmetic."
      },
      {
        "severity": "nit",
        "file": "web/src/components/TapFilters.tsx",
        "location": "TapFilters.tsx:47",
        "title": "Synthetic raw `tap:${f.key}` is logged verbatim to the query trace",
        "detail": "Each tap calls onApply with raw=`tap:tap.longest` (the i18n key).
App.onApplyQuery (App.tsx:165) records `raw` into the query.parse trace via parseTrace(q). So
the observability trace shows raw=`tap:tap.longest` for tap-sourced queries vs the real typed
text for the bar. This is honest and arguably useful (source=`example` already distinguishes
them), but embedding the i18n key into the raw string is a slightly leaky representation ? if a
key is ever renamed the trace string silently changes meaning, and 'tap:tap.longest' double-
prefixes 'tap.'.",
        "suggestion": "Optional: set raw to the canonical English equivalent (f.english, e.g.

```

'longest first') so the trace mirrors what an equivalent typed query would log, keeping tap and type traces directly comparable; source='example' still flags it as a chip. Or drop the redundant 'tap.' (use f.english or a bare slug). No functional impact."

```
    },
    {
      "severity": "nit",
      "file": "web/src/components/TapFilters.test.tsx",
      "location": "TapFilters.test.tsx:18-29 (tap==type) vs TapFilters.tsx:47 (onClick
payload)",
      "title": "The tap==type test pins f.parts against the parser, but does NOT pin that
the onClick-built ParsedQuery equals f.parts",
      "detail": "The strong test (lines 18-29) proves parseQuery(f.english) deep-equals
f.parts for every filter ? excellent, the parser can't drift from the data table. But the
COMPONENT builds its own ParsedQuery inline at TapFilters.tsx:47 ({raw, filters:
f.parts.filters, sort: f.parts.sort, limit: f.parts.limit, unavailable: [], recognized: true}).
The 'tapping applies through onApply' test (lines 31-41) only asserts this for ONE control
(over10). So a hand-built field mistake on a different control (e.g. forgetting unavailable:[]
or mis-wiring limit for top5/top10) would not be caught by the table test ? only over10 is end-
to-end verified.",
      "suggestion": "Strengthen the applied-query test to loop over all TAP_FILTERS: render,
click each localized label, and assert the emitted ParsedQuery's
{filters,sort,limit,unavailable,recognized} matches the parser's parseQuery(f.english) output.
That closes the gap between 'the data table is correct' and 'the button emits the data table'.
Cheap, high-value."
    }
  ]
}
]
}
}
</output>
```

474. assistant (2026-06-21T17:21:15.860Z)

A9 review: ****correctness clean**** (tap==type traced for all 6 controls). One ****minor**** + 3 nits ? all genuinely good, so I'll fold them: (1) hide the English-only `EXAMPLES` row for non-English locales (it's clutter for the exact user A9 serves), (2) make `tap.title` self-contained ("Tap to filter:" ? needed once EXAMPLES is hidden), (3) log `raw` as the English equivalent (cleaner trace), (4) loop the applied-query test over all controls (closes the coverage gap).

Fix 1 ? QueryBar hides EXAMPLES for non-en:

475. user (2026-06-21T17:21:19.394Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\QueryBar.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

476. user (2026-06-21T17:21:29.430Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\QueryBar.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

477. assistant (2026-06-21T17:21:34.187Z)

Fix 3 ? log `raw` as the English equivalent:

478. user (2026-06-21T17:21:37.710Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\TapFilters.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

479. assistant (2026-06-21T17:21:49.633Z)

Fix 2 ? make `tap.title` self-contained across all six catalogs:

480. user (2026-06-21T17:21:51.780Z)

```
=== en tap.title ===
102:   "title": "Or tap to filter:",
=== kn tap.title ===
102:   "title": "???? ?????? ?????? ?????? ????:",
=== hi tap.title ===
102:   "title": "?? ??????? ????? ?? ??? ??? ?????:",
=== es tap.title ===
102:   "title": "O toca para filtrar:",
=== da tap.title ===
102:   "title": "Eller tryk for at filtrere:",
=== id tap.title ===
102:   "title": "Atau ketuk untuk memfilter:",
```

481. user (2026-06-21T17:21:57.351Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\en\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

482. user (2026-06-21T17:22:05.523Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\kn\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

483. user (2026-06-21T17:22:12.190Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\hi\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

484. user (2026-06-21T17:22:19.418Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\es\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

485. user (2026-06-21T17:22:25.647Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\da\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

486. user (2026-06-21T17:22:33.103Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\i18n\locales\id\common.json has been updated successfully. (file state is current in your context ? no need to Read it back)

487. assistant (2026-06-21T17:22:39.359Z)

Fix 4 ? strengthen the test to verify every control's emitted query equals the parser:

488. user (2026-06-21T17:22:46.014Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\TapFilters.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

489. user (2026-06-21T17:23:06.657Z)

```
Test Files   19 passed (19)
      Tests  173 passed (173)
=== tsc ===
tsc OK
=== build ===
? built in 1.36s
```

490. assistant (2026-06-21T17:23:18.467Z)

173 tests, tsc, build green. Let me quickly verify the key UX fix in-browser (kn hides the English EXAMPLES row, shows only localized TapFilters):

491. user (2026-06-21T17:23:21.533Z)

```
{
  "serverId": "98f833a4-2f35-49f7-9857-2efa97e11ae8",
  "port": 5174,
  "name": "khelsutra-web",
  "reused": false
}
```

Server started successfully on port 5174.

492. user (2026-06-21T17:23:27.365Z)

undefined

493. user (2026-06-21T17:23:35.868Z)

```
{
  "hasEnglishExamplesRow": false,
  "lang": "kn",
  "tapLabels": [
    "??? ?????? ??????",
    "??? ?????????? ??????",
    "10 ?????????????? ??????",
    "20 ?????????????? ??????",
    "??? ?????? 5",
    "??? ?????? 10"
  ],
  "tapTitle": "????????? ?????? ?????? ??????"
}
```

494. assistant (2026-06-21T17:23:45.099Z)

In Kannada: the English EXAMPLES row is ****hidden****, the self-contained "????????? ?????? ?????? ??????" title shows, and all 6 controls are localized ? exactly the declutter the review asked for. Let me confirm en still shows both rows (no regression):

495. user (2026-06-21T17:23:45.753Z)

undefined

496. user (2026-06-21T17:23:52.308Z)

```
{
  "hasEnglishChip": true,
  "hasSampleQueries": true,
  "hasTapTitle": true,
  "lang": "en"
}
```

497. assistant (2026-06-21T17:24:03.054Z)

en shows both rows (English type-hints + localized taps); kn shows only the localized taps. No regression. A9 fully verified. Stopping preview and committing:

498. user (2026-06-21T17:24:03.805Z)

Server 98f833a4-2f35-49f7-9857-2efa97e11ae8 stopped

499. user (2026-06-21T17:24:06.171Z)

```
branch: feat/a9-tap-filters
web/src/App.tsx
web/src/components/QueryBar.tsx
web/src/components/TapFilters.test.tsx
web/src/components/TapFilters.tsx
web/src/i18n/hygiene.test.ts
web/src/i18n/locales/da/common.json
web/src/i18n/locales/en/common.json
web/src/i18n/locales/es/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/id/common.json
web/src/i18n/locales/kn/common.json
--- base (only my work) ---
```

500. user (2026-06-21T17:24:22.537Z)

To <https://github.com/avidullu/khelsutra.git>
* [new branch] feat/a9-tap-filters -> feat/a9-tap-filters

501. user (2026-06-21T17:24:41.961Z)

<https://github.com/avidullu/khelsutra/pull/68>

502. assistant (2026-06-21T17:24:49.982Z)

PR [#68](<https://github.com/avidullu/khelsutra/pull/68>) created. Marking A9 ? in the tracker:

503. user (2026-06-21T17:24:52.246Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

504. user (2026-06-21T17:25:03.232Z)

The file C:\Users\avidu\Projects\khelsutra\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

505. user (2026-06-21T17:26:00.298Z)

```
pushed
poll 1: web=pending cf=pass
poll 2: web=pass cf=pass
=== final ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/8691e772-3870-4d18-bef2-37ced20868df
site pass 10s
https://github.com/avidullu/khelsutra/actions/runs/27911948093/job/82590475940
web pass 28s
https://github.com/avidullu/khelsutra/actions/runs/27911948093/job/82590475918
```

506. assistant (2026-06-21T17:26:07.916Z)

All green. Merging A9:

507. user (2026-06-21T17:26:16.207Z)

```
create mode 100644 web/src/components/TapFilters.test.tsx
create mode 100644 web/src/components/TapFilters.tsx
46e0244 feat(web): A9 ? localized tap-only filter controls (#68)
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
```

ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)

508. assistant (2026-06-21T17:27:19.886Z)

A9 merged (#68 ? `46e0244`) ? ****6 PRs this session**** (A4, A5, A8, T4, MULTILINGUAL Phase A, A9), web tests 103?173, plus 2 new invariant guards (placeholder-parity, tap==type) and a latent kn/hi bug fixed.

Let me update task state and refresh the handoff before deciding the next item.

509. user (2026-06-21T17:27:20.365Z)

Updated task #9 status

510. user (2026-06-21T17:27:26.746Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

511. user (2026-06-21T17:27:51.187Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

512. assistant (2026-06-21T17:28:21.718Z)

Now let me decide the next step thoughtfully. I'll update the current-state checkpoint to reflect all 6 PRs first.

513. user (2026-06-21T17:28:35.006Z)

<tool_use_error>File has been modified since read, either by the user or by a linter. Read it again before attempting to write it.</tool_use_error>

514. assistant (2026-06-21T17:28:41.875Z)

The concurrent session modified `current-state.md`. Let me re-read my checkpoint block and re-apply:

515. user (2026-06-21T17:28:44.111Z)

16:[Omitted long matching line]

516. user (2026-06-21T17:28:49.699Z)

14 ****Checkpoint:**** 2026-06-21 (****T11 retention sweep ? engine PR OPEN, all-green, coverage verified****). The owner-spun T11 chip (`task\_2480b9e2`) is now BUILT in the engine. ****Extended `tools/cleanup\_caches.py`**** (not hand-rolled, per **[[cache-hygiene-policy]]**) with a pre-alpha ****upload retention sweep****: a new **`"uploads"`** scan location + **`classify`** (**`uploaded source`** / **`partial upload`** for the orphaned **`partial-*<id>*`** files) over **`security.upload\_dir`** (default **`output/uploads`**); **`plan\_deletions`** gains an ****independent `uploads\_retention\_days` window**** (privacy) orthogonal to the cache **`--older-than`** (disk); **`scan\_windows`** now ****skips the nested uploads dir**** (was silently kept whole as "other dir" ? no retention); loud structured output (retention-window banner + per-category subtotals + per-item PURGED/FAILED + a **`--json`** plan for a cron/job wrapper). ****Dry-run by default; reels/DB/CSVs stay durable.**** ****Owner gate (AskUserQuestion): uploads 7d default; reels kept durable.**** ? ****engine** **[#299]**(<https://github.com/Khelsutra/badminton-highlight-indexer/pull/299>) OPEN, ALL 11 CI checks GREEN****** (ruff/mypy/full-suite/golden cross-OSx3/wheel-smoke/license-scan/syntax+import); +6 unit tests; ****coverage no-regression VERIFIED**** (branch ****85.30%**** vs **`origin/master`** baseline ****85.06%**** measured in an isolated worktree; same ****9748**** measured stmts, branch missed ****1433 ?**** baseline ****1456**** ? the +0.24% is obsreport reporting tests in my local lane, NOT my diff;

the diff touches **ONLY** tools/+tests/ and the tool imports **zero** backend/training). Branch `fix/t11-retention-sweep`, cut from `origin/master` in the shared checkout (serving session's branch untouched; explicit-path staging). **Awaiting owner merge decision** (feature-ish; not auto-merged despite green CI). The khelsutra-side §9 T11 doc lives in the sibling repo (not editable from this checkout). `cache-hygiene-policy` `ui-driven-cloud-serving-gap` `gotcha-shared-checkout-branch-collisions`

15

16 **Checkpoint:** 2026-06-21 (**UX A-items + North-Star UPLOAD ? 4 khelsutra PRs merged**). The UX/localization track (separate session from the serving/alpha-shareable one below). Shipped the SPA UX A-items + the runnable-tool keystone. **4 PRs merged ? all green CI, browser-verified, each adversarially reviewed via a workflow:**
[#61](https://github.com/avidullu/khelsutra/pull/61) **A4** (?44px mobile tap targets + tooltip-text?visible: the "not available yet" reason + per-card shot confidence) .
[#62](https://github.com/avidullu/khelsutra/pull/62) **A5** (ONE shared `lib/errorText.ts` + `errors.*` namespace across build+load+ingest ? no more raw `ApiError`/`HTTP 500`; logs gain code+detail) . [#63](https://github.com/avidullu/khelsutra/pull/63) **A8** (background-processing reassurance + icon+text `StatusChip`, a "Stitching your reel?" building card, ?? status icons, aria-live) . **[#66](https://github.com/avidullu/khelsutra/pull/66)** T4 ? in-UI file UPLOAD (NORTH-STAR keystone) (file picker ? chunked `/api/upload/` via new `api/client.ts` helpers + `hooks/useUpload.ts` ? server path ? `/api/process` ? existing poll?load?compile?download; **153 web tests**; rebased onto the sibling's #64/#65 ? `apiBase()` + upload coexist cleanly). **Owner decisions (AskUserQuestion):** build T4 first; **B3** catalog-home = hoist to repo-root `/locales/` (LOCKED); record/spin-off the rest. **Spun off as owner-launchable chips:** **B3** (`task_b3060842`), MULTILINGUAL Phase A es/da/id (`task_e15e9643`), T11 retention (`task_2480b9e2`) ? **B3+MULTILINGUAL** both edit catalogs, don't run together. **Remaining:** **A9** (tap-only filters), **A3** (recording-edu kn/hi), native review of AI-drafted kn/hi(+es/da/id); **T2** = owner stand-up only (sibling shipped the deploy kit #65) + the hosted-mode `allowed_video_root` ? `upload_dir` caveat (from the T4 review). ? Caught+fixed a slip: started T4 edits on `master`, moved to a feature branch BEFORE any commit. ? Track handoff = `next-session-ux-localization`. `working-agreement-merging` `gotcha-shared-checkout-branch-collisions`

17

18 **Checkpoint:** 2026-06-21 (**ALPHA-SHAREABLE ? Claude's half DONE; 3 PRs merged**). Owner's #1 = "highlights from a page I can share, no SSH." **KEY CORRECTION** (anti-spiral `lesson-verify-engine-surface-before-scoping`): **the icebreaker said do "B-P2 ingest screen + M7 Cloud Run *service" ? but a recon *workflow*** (`wf_5de56b64`, 5 readers across both repos) proved **B-P2 was ALREADY shipped** (khelsutra #56, live e2e `DRY_RUN_CUJ.md` §9) + CORS is already env-driven ? **alpha-shareable is a DEPLOY/AUTH task, not an SPA build**. **Owner decisions (2x AskUserQuestion):** topology **(i) Tunnel-to-a-box**, sub-topology **SPLIT** (SPA on CF Pages + engine on `api.` cloudflared tunnel + CF Access; single-origin Caddy kept as the alt). **3 PRs MERGED:** ? **engine** [#294](https://github.com/Khelsutra/badminton-highlight-indexer/pull/294) (`0c0e064`) **exposure-safety boot posture** ? `startup.py` fails fast at boot (server-only `include_exposure=True`) when `edge_auth_enabled` is ON but half-configured (`EXPOSED_NO_VIDEO_ROOT`/`EXPOSED_EDGE_AUTH_INCOMPLETE` fatal, `EXPOSED_AUTH_EXTRA_MISSING` warn); **default-OFF**; aligned `auth.resolve_tenant` whitespace; adversarial 3-lens review (`wf_35b735a9`) ? no bypass; +16 tests; 1259 green cross-OS. ? **khelsutra** [#64](https://github.com/avidullu/khelsutra/pull/64) **(8bbc557)** **SPA VITE_API_BASE** ? `apiBase()` env-driven (default same-origin `/api`) + `vite-env.d.ts` + 3 tests; build-smoke proved the override bakes in. ? **khelsutra** [#65](https://github.com/avidullu/khelsutra/pull/65) **(4627830)** **deploy kit** ? `deploy/DEPLOY_ALPHA.md` (split runbook + CORS-preflight gotcha + posture test) + `cloudflared.config.example.yml` + tracker pointers. Each isolated/default-OFF/adversarial-reviewed/CI-green/merged-on-green; khelsutra built in a dedicated **worktree** (main tree had sibling A8 WIP, since merged #63; ? `rmdir` the `node_modules` junction BEFORE `git worktree remove`). **REMAINING** for alpha = OWNER stand-up only (cloudflared tunnel + CF Pages + CF Access + key rotation per `khelsutra/deploy/DEPLOY_ALPHA.md`). **NEXT engine code** (Claude-doable, batch-authorized): **M12** (gdrive-api, clean, no DB migration) then **M11** (flywheel skeleton, privacy-gated on v7 consent). `ui-driven-cloud-serving-gap` `lesson-verify-engine-surface-before-scoping`

517. assistant (2026-06-21T17:29:04.815Z)

The concurrent session already built **T11** (engine [#299](https://github.com/Khelsutra/badminton-highlight-indexer/pull/299) open) from the chip I spawned ? so T11 is handled. Let me update my checkpoint block to reflect all 6 PRs + that

T11/MULTILINGUAL are resolved:

518. user (2026-06-21T17:29:28.484Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\current-state.md has been updated successfully. (file state is current in your context ? no need to Read it back)

519. assistant (2026-06-21T17:30:37.919Z)

The chips are converging nicely ? **T11** was picked up by the concurrent session² (engine [#299](https://github.com/Khelsutra/badminton-highlight-indexer/pull/299), open), and I did MULTILINGUAL myself (#67). Updating task state:

520. user (2026-06-21T17:30:38.000Z)

Updated task #7 status

521. assistant (2026-06-21T17:31:16.926Z)

Status: 6 PRs merged this session, all green CI, each browser-verified + adversarially reviewed.

PR	What	Coverage
[#61](https://github.com/avidullu/khelsutra/pull/61)	A4	?44px mobile tap targets + tooltip-text?visible +a4.touch
[#62](https://github.com/avidullu/khelsutra/pull/62)	A5	one shared `errorText`/`errors.` across build+load+ingest (no raw `ApiError`/`HTTP 500`) +errorText, +build-error
[#63](https://github.com/avidullu/khelsutra/pull/63)	A8	reassurance + icon+text `StatusChip` + building card + ?? + aria-live +a8.status
[#66](https://github.com/avidullu/khelsutra/pull/66)	T4 (North Star)	in-UI file upload ? chunked `/api/upload/*` ? `/api/process` ? existing back-half +upload, +useUpload
[#67](https://github.com/avidullu/khelsutra/pull/67)	MULTILINGUAL A	es/da/id ? 6 languages ; es 3-form plural; placeholder-parity guard (caught+fixed a latent kn/hi `{videoId}` bug) +5
[#68](https://github.com/avidullu/khelsutra/pull/68)	A9	localized tap-only filters; English chips now en-only; tap==type pinned +TapFilters

Web tests 103 ? 173², plus two new invariant guards (placeholder-parity across all 6 locales, tap==type). **Workstream A** is done² (A1/A4/A5/A8/A9 ?). I caught and fixed one process slip mid-stream (T4 edits started on `master` ? moved to a feature branch before any commit).

The queue has converged:

- **T11** ? picked up by the concurrent session ? engine [#299](https://github.com/Khelsutra/badminton-highlight-indexer/pull/299) (open, awaiting your merge).
- **T2** ? owner stand-up only (the sibling already shipped the deploy kit #65: CF Pages + `api.` tunnel + CF Access). Needs: CF Access setup + **rotate** `GEMINI\_API\_KEY`² + deploy. Caveat from the T4 review: set the engine's `allowed\_video\_root` to a parent of `upload\_dir`.

The one substantial item left is B3 (site/ trilingual), now **fully unblocked** (all 6 catalogs ready to hoist; approach locked = hoist to repo-root `/locales/`). It's architectural ? SPA import repoint + a new site build step + Vite out-of-root import config ? so I'd do it as **two clean PRs** (PR-1 catalog hoist + drift-guard; PR-2 vanilla shim + switcher + `data-i18n` annotation) rather than one risky change.

I'll start **B3 PR-1** (the hoist)² next on that basis ? say the word if you'd rather I hold B3 for a fresh focused session (the chip is ready) or prioritize something else.

522. user (2026-06-21T17:31:20.144Z)

when we store the video do we also record the locale in which the site was rendered in the database?

523. assistant (2026-06-21T17:31:50.515Z)

Good question ? and it's a factual one I should verify against the actual schema and API rather than answer from memory. Let me check the SPA's outgoing calls, the engine's ``/api/process`/upload endpoints`, and the DB schema.

524. user (2026-06-21T17:31:52.056Z)

Found 3 files
backend\reporting\spec.yaml
backend\assets\fonts\LICENSE-Apache-2.0.txt
backend\api\static\index.html

525. user (2026-06-21T17:31:53.242Z)

No matches found

526. assistant (2026-06-21T17:32:04.026Z)

The SPA's API client sends `**no**` locale, and in the engine ``backend/`` the only hits are an unrelated font license, the dead ``backend/api/static/index.html``, and ``backend/reporting/spec.yaml``. Let me confirm the DB schema (videos/jobs columns) and check what the ``spec.yaml`` hit is:

527. user (2026-06-21T17:32:06.067Z)

1-# Observability report spec for the badminton-highlight-indexer.
2-# The report ENGINE (config language, renderers) lives in the shared ``obsreport``
3-# library; this file is the indexer-specific layout + footgun rules. Every

528. user (2026-06-21T17:32:07.765Z)

```
65:         """Apply a bare ``ALTER TABLE ... ADD COLUMN`` migration step re-runnably.
69:         ``user_version`` stays un-bumped ? and the next open would re-run the same
82:         """Initializes tables for videos, play_segments, and events."""
88:         # Versioned migrations live here. PRAGMA user_version is the schema
91:         version = cursor.execute("PRAGMA user_version").fetchone()[0]
110:         # future: if version < 7: cursor.execute("ALTER TABLE ..."); PRAGMA user_version
= 7
115:         """Create the videos / play_segments / events base tables (idempotent)."""
118:         CREATE TABLE IF NOT EXISTS videos (
129:         CREATE TABLE IF NOT EXISTS play_segments (
138:             FOREIGN KEY (video_id) REFERENCES videos(id) ON DELETE CASCADE
144:         CREATE TABLE IF NOT EXISTS events (
157:         # Common fields are columns; detector-specific metrics go in `stats` JSON,
160:         CREATE TABLE IF NOT EXISTS candidate_segments (
175:             FOREIGN KEY (video_id) REFERENCES videos(id) ON DELETE CASCADE,
183:         cursor.execute("PRAGMA user_version = 1")
193:         CREATE TABLE IF NOT EXISTS jobs (
210:         cursor.execute("PRAGMA user_version = 2")
218:         # ADD COLUMNS are applied idempotently so an interrupted upgrade can re-run them.
219:         self._add_column_idempotent(cursor, "ALTER TABLE jobs ADD COLUMN policy TEXT")
220:         self._add_column_idempotent(cursor, "ALTER TABLE jobs ADD COLUMN next_poll_at
TIMESTAMP")
222:         cursor.execute("PRAGMA user_version = 3")
226:         # `user_id` to videos + candidate_segments so a future per-user / multi-tenant
230:         # the ADD COLUMNS are applied idempotently so an interrupted upgrade can re-run
them.
232:         self._add_column_idempotent(cursor, "ALTER TABLE videos ADD COLUMN user_id TEXT")
233:         self._add_column_idempotent(cursor, "ALTER TABLE candidate_segments ADD COLUMN
user_id TEXT")
237:         "CREATE INDEX IF NOT EXISTS idx_videos_user ON videos(user_id) "
242:         cursor.execute("PRAGMA user_version = 4")
259:         # n_videos_at_fit ? held-out-user corpus size when fit (min_n trust floor
```

```

input)
262:         CREATE TABLE IF NOT EXISTS user_models (
271:             n_videos_at_fit INTEGER NOT NULL DEFAULT 0,
280:             CREATE UNIQUE INDEX IF NOT EXISTS idx_user_models_user_version
290: cursor.execute("PRAGMA user_version = 5")
293: # v6: per-job COST LEDGER (COMPUTE_DECOUPLED_SERVING M8, D8). NULLABLE cost columns
on
297: # configurable FX rate. ALTER (not recreate) so v1-v5 job rows survive; ADD COLUMNS
are
311:         self._add_column_idempotent(cursor, f"ALTER TABLE jobs ADD COLUMN {col} {typ}")
318:         CREATE TABLE IF NOT EXISTS pricebook (
337: cursor.execute("PRAGMA user_version = 6")
350:         "INSERT INTO videos (id, filepath, status, validation_results) VALUES (?, ?, ?,
?) "
472:         row = conn.cursor().execute("SELECT * FROM videos WHERE id = ?",
(video_id,)).fetchone()
531:         conn.cursor().execute("DELETE FROM videos WHERE id = ?", (video_id,))
781: # JSON-serialised dicts; the rest are scalar columns.
789:         n_videos_at_fit: int = 0,
818:         n_videos_at_fit, is_active)
826:         n_videos_at_fit=excluded.n_videos_at_fit,
832:         n_videos_at_fit, 1 if is_active else 0))

```

529. user (2026-06-21T17:32:20.024Z)

```

115         """Create the videos / play_segments / events base tables (idempotent)."""
116 # Videos Table
117 cursor.execute("""
118     CREATE TABLE IF NOT EXISTS videos (
119         id TEXT PRIMARY KEY,
120         filepath TEXT NOT NULL,
121         processed_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
122         status TEXT NOT NULL,
123         validation_results TEXT
124     )
125 """)
126
127 # Play Segments Table (Extensible metadata JSON)
128 cursor.execute("""
129     CREATE TABLE IF NOT EXISTS play_segments (
130         id INTEGER PRIMARY KEY AUTOINCREMENT,
131         video_id TEXT NOT NULL,
132         start_time REAL NOT NULL,
133         end_time REAL NOT NULL,
134         duration REAL NOT NULL,
135         server TEXT,
136         receiver TEXT,
137         metadata TEXT,
138         FOREIGN KEY (video_id) REFERENCES videos(id) ON DELETE CASCADE
139     )
140 """)
141
142 # Events Table
143 cursor.execute("""
144     CREATE TABLE IF NOT EXISTS events (

```

530. user (2026-06-21T17:32:20.552Z)

```

186 # v2: async job model (DEFERRED_HARDENING_PLAN #16). One row per submitted
187 # /api/process request. `status` is the EXECUTION state of the job
188 # (queued|running|done|failed); the pipeline's own verdict (e.g. a video
189 # that failed validation) lives inside `result` JSON as result["status"].
190 # `result` is the full sync-era response dict (incl. report paths), so the
191 # observability report is the job's artifact, per the plan.
192 cursor.execute("""

```

```

193         CREATE TABLE IF NOT EXISTS jobs (
194             id TEXT PRIMARY KEY,
195             video_path TEXT NOT NULL,
196             video_id TEXT,
197             segmenter TEXT,
198             player_pool TEXT,
199             max_frames INTEGER,
200             status TEXT NOT NULL DEFAULT 'queued',
201             progress TEXT,
202             error TEXT,
203             result TEXT,
204             created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
205             started_at TIMESTAMP,
206             finished_at TIMESTAMP
207         )
208         """)
209     cursor.execute("CREATE INDEX IF NOT EXISTS idx_jobs_status ON jobs(status)")

```

531. assistant (2026-06-21T17:32:52.298Z)

Verified against the schema and the API ? answer is ****no****.

The site's rendered locale is ****purely a browser-side concern**** and never reaches the engine or the database:

****What actually gets stored when a video is processed:****

- `videos` table ([database.py:118](backend/infrastructure/database.py:118)): `id`, filepath, processed_at, status, validation_results` (+ `user_id` from the v4 migration). No locale.
- `jobs` table ([database.py:193](backend/infrastructure/database.py:193)), one row per `/api/process`: `id`, video_path, video_id, segmenter, player_pool, max_frames, status, progress, error, result, created_at/started_at/finished_at` (+ `policy`, `next_poll_at`, and the v6 cost columns). No locale.
- `play\_segments` / `events` / `candidate\_segments` ? no locale either.

****Where the locale lives instead:**** only in the browser ? the i18n detector persists the choice to `localStorage["khelsutra.lang"]` (web/src/i18n/index.ts:24). The SPA's outgoing calls don't carry it: `processVideo` sends only `{video\_path}` and `uploadInit` sends only `{filename, total\_size\_bytes}` (web/src/api/client.ts). The engine does no `Accept-Language` handling. (The only `language` hit in the backend is the `obsreport` config-DSL in `reporting/spec.yaml` ? unrelated, and the dead `backend/api/static/`.)

So today a Kannada-rendered session and an English-rendered session that process the same file produce identical DB rows.

****Whether that's a gap depends on what you want it for**** ? and there are two real reasons it might matter:

1. ****Localized output**** ? a Kannada/Hindi ****reel watermark**** or a localized report. The engine's `WatermarkConfig.font\_path` already takes a path (FRIENDLY §4 flagged this), but the engine would need to ***know*** the locale at process time to pick the language/font. Recording it is the natural way.
2. ****Analytics**** ? which language markets are actually using the tool (a PMF signal).

If you want it, it's a small, clean, additive change: add an optional `locale` to the `/api/process` (and upload-init) request, have the SPA pass `i18n.resolvedLanguage`, and store it as a nullable column on `videos` (or `jobs`) via a v7 migration ? additive-NULL, default-OFF behavior, no impact on existing rows.

Want me to spec/build that (it'd touch the engine, so I'd coordinate with the concurrent serving session and likely fold it into the same v7 migration they're planning), or were you just checking the current state?

532. user (2026-06-21T17:58:41.622Z)

yea you very rightly identified the top reasons (watermarking and PMF) for the locale inclusion.

Can you spec and build it and also do the work of localizing the watermarks in all the languages that we support? Would be good to also ensure that some basic analytics (how many spanish users etc.) are possible in the future

533. assistant (2026-06-21T18:00:42.098Z)

This is a meaty cross-repo feature, and the engine side has a real landmine: the concurrent serving session is **planning a v7 migration** (M9-consent + workspace_uri), so I must not blindly author a colliding `_migrate_to_v7`. Let me investigate the watermark/compile/migration surface against `origin/master` (read-only, not touching the concurrent session's working tree) before I spec anything.

534. user (2026-06-21T18:00:43.479Z)

Chapter marked: "Locale capture + localized watermarks". Continue your current work.

535. user (2026-06-21T18:00:47.770Z)

```
=== branch (concurrent session's) ===
serving/exposure-safety-preflight
origin/master: 4a06b8b

=== migration head on origin/master (database.py user_version) ===
89:         # contract ? bump it for every change and add an ordered `if version < N`
93:         if version < 1:
94:             self._migrate_to_v1(cursor)
96:         if version < 2:
97:             self._migrate_to_v2(cursor)
99:         if version < 3:
100:            self._migrate_to_v3(cursor)
102:         if version < 4:
103:            self._migrate_to_v4(cursor)
105:         if version < 5:
106:            self._migrate_to_v5(cursor)
108:         if version < 6:
109:            self._migrate_to_v6(cursor)
110:            # future: if version < 7: cursor.execute("ALTER TABLE ..."); PRAGMA user_version
= 7
155:     def _migrate_to_v1(self, cursor):
183:         cursor.execute("PRAGMA user_version = 1")
185:     def _migrate_to_v2(self, cursor):
210:         cursor.execute("PRAGMA user_version = 2")
212:     def _migrate_to_v3(self, cursor):
222:         cursor.execute("PRAGMA user_version = 3")
224:     def _migrate_to_v4(self, cursor):
242:         cursor.execute("PRAGMA user_version = 4")
244:     def _migrate_to_v5(self, cursor):
290:         cursor.execute("PRAGMA user_version = 5")
292:     def _migrate_to_v6(self, cursor):
337:         cursor.execute("PRAGMA user_version = 6")
```

536. assistant (2026-06-21T18:01:46.609Z)

v6 is the migration head on `origin/master`; v7 is free (the serving session's v7 is planned, not yet merged). The engine checkout is on the concurrent session's branch (`serving/exposure-safety-preflight`) ? I'll do any engine work in an isolated worktree.

Now let me map the watermark + compile + font surface (the core of the build):

537. user (2026-06-21T18:01:48.609Z)

Found 6 files
backend\main.py
backend\infrastructure\database.py

```
backend\config\models.py
backend\pipeline\stitcher\compiler.py
backend\assets\fonts\README.md
backend\tools\rally_slicer.py
```

538. user (2026-06-21T18:01:48.821Z)

```
backend\assets\fonts\LICENSE-Apache-2.0.txt
backend\assets\fonts\README.md
backend\assets\fonts\RobotoSlab-Regular.ttf
```

539. assistant (2026-06-21T18:02:03.744Z)

Critical finding: the engine bundles **only** `RobotoSlab-Regular.ttf` (Latin) ? so kn/hi watermarks will tofu without bundling the OFL Noto fonts. Let me read the watermark drawing code, the `WatermarkConfig`, and how the compile flow uses it:

540. user (2026-06-21T18:02:04.063Z)

```
1      import os
2      import subprocess
3      import tempfile
4      import logging
5      from pathlib import Path
6      from typing import Any, Dict, List, Optional, Tuple, Union
7
8      logger = logging.getLogger(__name__)
9
10     # Bundled, commercially-clean default watermark font (Apache-2.0). Shipped so the
overlay
11     # renders out-of-the-box without a system fontconfig setup (a common gap on Windows,
where
12     # `font='Sans` fails). Overridable via stitching.watermark.font_path. This module lives
at
13     # backend/pipeline/stitcher/, so parents[2] == backend/.
14     _BUNDLED_FONT = Path(__file__).resolve().parents[2] / "assets" / "fonts" / "RobotoSlab-
Regular.ttf"
15
16     class VideoCompiler:
17         def __init__(self, output_dir: str, end_padding: float = 1.0, begin_padding: float =
0.5,
18                     watermark: Optional[Any] = None):
19             self.output_dir = output_dir
20             self.end_padding = end_padding
21             self.begin_padding = begin_padding
22             # Optional branding overlay. Accepts a WatermarkConfig model or a plain dict;
23             # normalized to a dict (or None) so this module stays config-package-agnostic.
24             self.watermark = self._normalize_watermark(watermark)
25             os.makedirs(output_dir, exist_ok=True)
26
27         @staticmethod
28         def _normalize_watermark(watermark: Optional[Any]) -> Optional[Dict[str, Any]]:
29             if watermark is None:
30                 return None
31             if hasattr(watermark, "model_dump"):
32                 return watermark.model_dump()
33             if isinstance(watermark, dict):
34                 return dict(watermark)
35             return None
36
37         @staticmethod
38         def _ff_quote(path: str) -> str:
39             """Make a filesystem path safe to embed inside single quotes in an ffmpeg
40             filtergraph operand (drawtext fontfile/textfile, movie= source): forward
```

```

41         slashes (Windows-friendly), escaped single quotes, AND escaped colons.
42
43         The colon MUST be escaped even inside single quotes: ffmpeg's filtergraph
44         option parser treats ':' as the option separator, so a Windows drive-letter
45         path like ``C:/dir/font.ttf`` otherwise truncates the operand at ``C`` and
46         the encode fails with "Invalid argument". This silently disabled the
47         on-by-default bundled-font watermark (and absolute logo paths) on Windows.""
48         return path.replace("\\", "/").replace("'", r"\'").replace(":", r"\:")
49
50     @staticmethod
51     def _parse_time(val: Union[int, float, str]) -> float:
52         """Normalizes a timestamp value to float seconds.
53         Handles: float/int (pass-through), plain numeric strings ("12.4"),
54         and colon-separated strings ("MM:SS", "HH:MM:SS", "H:MM:SS.ms").
55         This mirrors the parse_time logic used in gemini.py to ensure
56         the stitcher can always consume whatever format the indexer produced.""
57         if isinstance(val, (int, float)):
58             return float(val)
59         if isinstance(val, str):
60             val = val.strip()
61             if ":" in val:
62                 # Handle MM:SS, HH:MM:SS, etc.
63                 parts = val.split(":")
64                 parts.reverse()
65                 total = 0.0
66                 for i, p in enumerate(parts):
67                     try:
68                         total += float(p) * (60 ** i)
69                     except ValueError:
70                         pass
71                 return total
72             try:
73                 return float(val)
74             except ValueError:
75                 logger.warning(f"Could not parse timestamp value '{val}' as a number.
Defaulting to 0.0.")
76                 return 0.0
77                 logger.warning(f"Unexpected timestamp type {type(val).__name__} for value
'{val}'. Defaulting to 0.0.")
78                 return 0.0
79
80     @staticmethod
81     def _merge_overlapping(segments: List[Tuple[float, float]]) -> List[Tuple[float,
float]]:
82         """Normalize, sort, and merge overlapping/duplicate (start, end) ranges.
83
84         A highlight reel must never replay the same footage. The same rally can land in
85         the segment list more than once ? e.g. two detector runs accumulated for one
86         video (add_video is an UPSERT, so re-running without a prune leaves both sets),
87         or
88         chunk-overlap duplicates near boundaries. Stitching those verbatim plays the
89         rally
90         twice. Merging any range that overlaps or abuts the previous one collapses true
91         duplicates/overlaps while preserving genuinely distinct (gapped) rallies.
92         Degenerate rows (end <= start) are dropped. Timestamps may be float/int/str.
93         """
94         parsed = []
95         for raw_s, raw_e in segments:
96             s = VideoCompiler._parse_time(raw_s)
97             e = VideoCompiler._parse_time(raw_e)
98             if e > s:
99                 parsed.append((s, e))
100         parsed.sort()
101         merged: List[Tuple[float, float]] = []
102         for s, e in parsed:

```

```

101         if merged and s <= merged[-1][1]: # overlaps/abuts previous -> extend it
102             merged[-1] = (merged[-1][0], max(merged[-1][1], e))
103         else:
104             merged.append((s, e))
105     return merged
106
107 def _get_video_duration(self, video_path: str) -> float:
108     """Probes the video file to get its total duration in seconds.
109     Returns 0.0 if it cannot be determined."""
110     try:
111         result = subprocess.run(
112             [
113                 "ffprobe", "-v", "error",
114                 "-show_entries", "format=duration",
115                 "-of", "default=noprint_wrappers=1:nokey=1",
116                 video_path
117             ],
118             capture_output=True, text=True, check=True
119         )
120         return float(result.stdout.strip())
121     except Exception as e:
122         logger.warning(f"Could not determine video duration via ffprobe: {e}")
123         return 0.0
124
125 def _watermark_filter(self, tmp_dir: str) -> Optional[str]:
126     """Build the ffmpeg -vf filtergraph that burns the configured watermark (text
127     and/or logo PNG) into a clip during the per-clip re-encode. Returns None when
128     watermarking is disabled or has nothing to draw. The concat stage stays -c copy
129     because the mark is already baked into every clip identically."""
130     wm = self.watermark
131     if not wm or not wm.get("enabled"):
132         return None
133
134     text = (wm.get("text") or "").strip()
135     logo_path = (wm.get("logo_path") or "").strip()
136     if logo_path and not os.path.exists(logo_path):
137         logger.warning(f"[watermark] logo not found: {logo_path} ? skipping logo
138         overlay.")
139         logo_path = ""
140     if not text and not logo_path:
141         return None
142
143     margin = int(wm.get("margin", 24))
144     opacity = float(wm.get("opacity", 0.85))
145     position = str(wm.get("position", "bottom-right"))
146     # drawtext uses lowercase w/h (main) + tw/th (text); overlay uses W/H (main) +
147     w/h (logo).
148     dt_xy = {
149         "bottom-right": f"x=w-tw-{margin}:y=h-th-{margin}",
150         "bottom-left": f"x={margin}:y=h-th-{margin}",
151         "top-right": f"x=w-tw-{margin}:y={margin}",
152         "top-left": f"x={margin}:y={margin}",
153     }.get(position, f"x=w-tw-{margin}:y=h-th-{margin}")
154     ov_xy = {
155         "bottom-right": f"W-w-{margin}:H-h-{margin}",
156         "bottom-left": f"{margin}:H-h-{margin}",
157         "top-right": f"W-w-{margin}:{margin}",
158         "top-left": f"{margin}:{margin}",
159     }.get(position, f"W-w-{margin}:H-h-{margin}")
160
161     drawtext = ""
162     if text:
163         ratio = float(wm.get("font_size_ratio") or 0.035)
164         divisor = max(1, round(1.0 / ratio))
165         # textfile= sidesteps the notorious drawtext text= escaping for arbitrary

```

```

strings.
164         tf_path = os.path.join(tmp_dir, "watermark.txt")
165         with open(tf_path, "w", encoding="utf-8") as fh:
166             fh.write(text)
167         # Font precedence: explicit font_path ? bundled Apache-2.0 default (renders
168         # without fontconfig) ? fontconfig family (last-resort, environment-
dependent).
169         font_path = (wm.get("font_path") or "").strip()
170         if not font_path and _BUNDLED_FONT.exists():
171             font_path = str(_BUNDLED_FONT)
172         if font_path:
173             font_opt = f"fontfile='{self._ff_quote(font_path)}'"
174         else:
175             font_opt = f"font='{wm.get('font', 'Sans')}'"
176         box = ""
177         if wm.get("box", True):
178             box = f"box=1:boxcolor=black@{min(opacity, 0.5):.2f}:boxborderw=10"
179         drawtext = (
180             f"drawtext=textfile='{self._ff_quote(tf_path)}':{font_opt}"
181             f"fontcolor=white@{opacity:.2f}:fontsize=h/{divisor}:{dt_xy}{box}"
182         )
183
184         if logo_path and drawtext:
185             return
186         f"movie='{self._ff_quote(logo_path)}'[wm];[in][wm]overlay={ov_xy},{drawtext}"
187         if logo_path:
188             return f"movie='{self._ff_quote(logo_path)}'[wm];[in][wm]overlay={ov_xy}"
189         return drawtext
190
191     def _trim_one_segment(
192         self,
193         idx: int,
194         raw_start: Union[int, float, str],
195         raw_end: Union[int, float, str],
196         segments: List[Tuple[float, float]],
197         video_duration: float,
198         tmp_dir: str,
199         raw_video_path: str,
200         watermark_filter: Optional[str],
201     ) -> Tuple[Optional[str], Optional[Tuple[int, float, float, str]]]:
202         """Trim a single segment into its own clip file (extracted verbatim from the
203         per-segment body of compile_highlights). Returns (clip_path, skip_record): on
204         success the clip path and None; on a skip (invalid/out-of-range/ffmpeg failure)
205         None and the (idx, start, end, reason) record to record in skipped_segments."""
206         # Normalize timestamps to float seconds ? handles float, int,
207         # plain numeric strings, and colon-separated formats like "MM:SS"
208         start = self._parse_time(raw_start)
209         end = self._parse_time(raw_end)
210         segment_label = f"Segment #{idx+1}/{len(segments)} [{start:.2f}s - {end:.2f}s]"
211
212         # Validate the segment times
213         if start < 0:
214             logger.warning(f"{segment_label}: start_time is negative ({start:.2f}s).
Clamping to 0.")
215             start = 0.0
216
217         if start >= end:
218             logger.error(f"{segment_label}: start_time ({start:.2f}s) >= end_time
({end:.2f}s). Skipping invalid segment.")
219             return None, (idx, start, end, "start >= end")
220
221         # Check if segment extends beyond video duration
222         if video_duration > 0:
223             if start >= video_duration:
224                 logger.error(f"{segment_label}: start_time ({start:.2f}s) is beyond the

```



```

video duration ({video_duration:.2f}s). "
224             f"This segment cannot be extracted ? the video ran out.
Skipping.")
225             return None, (idx, start, end, "start beyond video end")
226
227         if end > video_duration:
228             original_end = end
229             end = video_duration
230             logger.warning(f"{segment_label}: end_time ({original_end:.2f}s) exceeds
video duration ({video_duration:.2f}s). "
231             f"Clamping end_time to {video_duration:.2f}s. The segment
may be truncated.")
232
233         clip_path = os.path.join(tmp_dir, f"clip_{idx}.mp4")
234
235         # Precise sub-second trim using fast re-encoding to preserve stream headers
236         padded_start = max(0.0, start - self.begin_padding)
237         padded_end = end + self.end_padding
238
239         # Clamp padded_end to video duration if known
240         if video_duration > 0 and padded_end > video_duration:
241             padded_end = video_duration
242             logger.info(f"{segment_label}: Padded end ({end + self.end_padding:.2f}s)
exceeds video duration. "
243             f"Clamping to {video_duration:.2f}s (end padding partially
applied).")
244
245         trim_duration = padded_end - padded_start
246         logger.info(f"Trimming {segment_label} -> [{padded_start:.3f}s -
{padded_end:.3f}s] (duration: {trim_duration:.2f}s)")
247
248         base_cmd = [
249             "ffmpeg", "-y",
250             "-ss", str(round(padded_start, 3)),
251             "-to", str(round(padded_end, 3)),
252             "-i", raw_video_path,
253             "-c:v", "libx264",
254             "-preset", "superfast",
255             "-crf", "22",
256             "-c:a", "aac",
257             "-b:a", "128k",
258         ]
259         vf_args = ["-vf", watermark_filter] if watermark_filter else []
260
261         # Try with the watermark first; if that encode fails (e.g. a bad font/logo
262         # path), retry once WITHOUT it so a branding misconfig can never nuke the
263         # whole reel. Clips stay codec-identical either way, so concat -c copy holds.
264         attempts = [vf_args, []] if vf_args else [[]]
265         produced = False
266         last_exc: Optional[subprocess.CallProcessError] = None
267         cmd = base_cmd + [clip_path]
268         for attempt_vf in attempts:
269             cmd = base_cmd + attempt_vf + [clip_path]
270             try:
271                 subprocess.run(cmd, capture_output=True, check=True)
272             except subprocess.CallProcessError as e:
273                 last_exc = e
274                 if attempt_vf and vf_args:
275                     _err = (e.stderr.decode(errors="replace").strip()[-300:]
276                             if getattr(e, "stderr", None) else "")
277                     logger.warning(
278                         f"{segment_label}: watermark encode failed; retrying without it.
279
280                         f"ffmpeg: {_err or '(no stderr captured)'}"

```

```

281         continue
282     break
283     if os.path.exists(clip_path) and os.path.getsize(clip_path) > 0:
284         produced = True
285         if not attempt_vf and vf_args:
286             logger.warning(f"{segment_label}: encoded WITHOUT the watermark (the
watermark filter failed).")
287         break
288         last_exc = None # ffmpeg succeeded but produced nothing
289         break
290
291     if produced:
292         return clip_path, None
293     elif last_exc is not None:
294         stderr_msg = last_exc.stderr.decode(errors='replace').strip()
295         logger.error(f"{segment_label}: FFmpeg trim failed.")
296         print(f" Command: {' '.join(cmd)}")
297         print(f" FFmpeg stderr: {stderr_msg[-500:]}") # Last 500 chars to avoid
flooding
298         return None, (idx, start, end, f"ffmpeg error: {stderr_msg[-200:]}")
299     else:
300         logger.error(f"{segment_label}: FFmpeg exited successfully but output clip
is missing or empty. Skipping.")
301         return None, (idx, start, end, "empty output clip")
302
303     def compile_highlights(self, raw_video_path: str, segments: List[Tuple[float,
float]], output_filename: str) -> str:
304         """
305         Extracts selected segments from a raw video and stitches them together
306         into a seamless highlights file, applying end_padding to prevent abrupt endings.
307         """
308         if not segments:
309             raise ValueError("No highlight segments provided to compile.")
310
311         # Never stitch the same footage twice: collapse overlapping/duplicate ranges
312         # (e.g. accumulated re-run segments or chunk-overlap dupes) before trimming.
313         original_count = len(segments)
314         segments = self._merge_overlapping(segments)
315         if len(segments) < original_count:
316             logger.info("Merged %d overlapping/duplicate segment(s) before stitching: %d
-> %d.",
317                 original_count - len(segments), original_count, len(segments))
318         if not segments:
319             raise ValueError("No valid (start < end) highlight segments after merge.")
320
321         if not os.path.exists(raw_video_path):
322             raise FileNotFoundError(f"[COMPILER ERROR] Source video file not found:
{raw_video_path}")
323
324         # Defense-in-depth: never let the output name escape output_dir (the API also
325         # validates this at the request boundary).
326         output_path = os.path.join(self.output_dir, os.path.basename(output_filename))
327
328         # Probe video duration so we can detect out-of-range segments
329         video_duration = self._get_video_duration(raw_video_path)
330         if video_duration > 0:
331             logger.info(f"Source video duration: {video_duration:.2f}s")
332         else:
333             logger.warning("Video duration unknown. Cannot validate segment boundaries
against video length.")
334
335         # We will create temporary clips and stitch them using FFmpeg concat demuxer
336         temp_clips = []
337         skipped_segments = []
338

```

```

339         # Create a temp directory within output_dir
340         with tempfile.TemporaryDirectory(dir=self.output_dir) as tmp_dir:
341             logger.info(f"Trimming {len(segments)} segments
(begin_padding={self.begin_padding}s, end_padding={self.end_padding}s)...")
342             # Build the (optional) watermark filtergraph once; it is applied during
every
343             # per-clip re-encode so the mark is baked into each clip identically.
344             watermark_filter = self._watermark_filter(tmp_dir)
345             if watermark_filter:
346                 logger.info("[watermark] applying branding overlay to each clip.")
347             for idx, (raw_start, raw_end) in enumerate(segments):
348                 clip_path, skip_record = self._trim_one_segment(
349                     idx, raw_start, raw_end, segments, video_duration,
350                     tmp_dir, raw_video_path, watermark_filter,
351                 )
352                 if clip_path is not None:
353                     temp_clips.append(clip_path)
354                 if skip_record is not None:
355                     skipped_segments.append(skip_record)
356
357             # Report summary of skipped segments
358             if skipped_segments:
359                 logger.info(f"\n[SUMMARY] {len(skipped_segments)} out of {len(segments)}
segments were SKIPPED:")
360                 for seg_idx, seg_start, seg_end, reason in skipped_segments:
361                     logger.info(f" - Segment #{seg_idx+1} [{seg_start:.2f}s -
{seg_end:.2f}s]: {reason}")
362                 logger.info("")
363
364             if not temp_clips:
365                 raise RuntimeError(
366                     f"[COMPILER ERROR] Failed to generate ANY valid highlight clips. "
367                     f"All {len(segments)} segments were skipped. "
368                     f"Check the errors above for details. "
369                     f"Common causes: video file is corrupted, segments are out of range,
or ffmpeg is not installed."
370                 )
371
372             logger.info(f"Successfully trimmed {len(temp_clips)}/{len(segments)} clips.
Preparing to stitch...")
373
374             # Create a list file for FFmpeg concat demuxer
375             list_file_path = os.path.join(tmp_dir, "clips.txt")
376             # encoding pinned: a non-ASCII clip path would crash on Windows (cp1252
default);
377             # ffmpeg's concat demuxer reads the list as UTF-8 on every OS.
378             with open(list_file_path, "w", encoding="utf-8") as f:
379                 for clip in temp_clips:
380                     # Escape single quotes in path
381                     safe_path = clip.replace("'", "'\\'")
382                     f.write(f"file '{safe_path}'\n")
383
384             logger.info("Stitching clips together...")
385             # Stitch them together without re-encoding (since they were encoded with
identical settings)
386             concat_cmd = [
387                 "ffmpeg", "-y",
388                 "-f", "concat",
389                 "-safe", "0",
390                 "-i", list_file_path,
391                 "-c", "copy",
392                 output_path
393             ]
394
395             try:

```

```

396         subprocess.run(concat_cmd, capture_output=True, check=True)
397
398         # Final verification
399         if not os.path.exists(output_path) or os.path.getsize(output_path) == 0:
400             raise RuntimeError(
401                 f"[COMPILER ERROR] FFmpeg concatenation appeared to succeed, "
402                 f"but output file is missing or empty: {output_path}"
403             )
404
405         output_size_mb = os.path.getsize(output_path) / (1024 * 1024)
406         logger.info(f"Dynamic highlight reel saved: {output_path}
407 ({output_size_mb:.1f} MB)")
408         return output_path
409     except subprocess.CalledProcessError as e:
410         stderr_msg = e.stderr.decode(errors='replace').strip()
411         raise RuntimeError(
412             f"[COMPILER ERROR] FFmpeg concatenation failed.\n"
413             f"Command: {' '.join(concat_cmd)}\n"
414             f"FFmpeg stderr: {stderr_msg[-500:]}")
415     ) from e

```

541. assistant (2026-06-21T18:02:19.661Z)

Now I understand the watermark mechanism (ffmpeg `drawtext` with `text` + `font\_path`, defaulting to bundled RobotoSlab). To localize, I override `text` + `font\_path` per locale at compile time. Let me see `WatermarkConfig` and how `/api/compile` constructs the compiler:

542. user (2026-06-21T18:02:21.676Z)

```

237-
238: class WatermarkConfig(BaseModel):
239-     """Branding overlay burned into each highlight clip during the per-clip re-encode
240-     (backend\pipeline\stitcher\compiler.py). **On by default** ? set `enabled: false`
241-     (under `stitching.watermark` in config.json) to turn it off. The text is fully
242-     configurable. The concat stage stays stream-copy (-c copy)."""
243-     enabled: bool = True
244-     text: str = "Generated by Khelsutra.guru"
245-     logo_path: str = "" # optional transparent PNG overlay; "" = no logo
246-     font_path: str = "" # optional .ttf; "" = use the fontconfig `font` family below
247-     font: str = "Sans" # fontconfig family used when font_path is empty
248-     font_size_ratio: float = Field(default=0.035, gt=0.0, le=0.5) # text height as a
fraction of frame height
--
254-
255: class StitchingConfig(BaseModel):
256-     begin_padding: float = 0.5
257-
258-
259-     min_rally_duration: float = Field(default=0.0, ge=0.0)
260-     watermark: WatermarkConfig = Field(default_factory=WatermarkConfig)
261-
262-

```

543. user (2026-06-21T18:02:23.535Z)

```

35: from backend.pipeline.stitcher.compiler import VideoCompiler
127: class ProcessRequest(BaseModel):
140: class CompileRequest(BaseModel):
148:     On a non-empty run, drop the PRIOR rows (id <= the pre-run watermark) so only the
149:     fresh segments remain. On an empty run, drop the NEW partial rows (id > watermark) and
247:     play_wm, cand_wm = db_instance.segment_watermarks(video_id)
287:     db=db_instance, video_id=video_id, video_path=req.video_path,
config=global_config,
315:     validate_input_path(req.video_path, allowed_root=allowed_root)
442: def compile_highlights(req: CompileRequest):

```

```

487:     # Run compiler with the configured stitching paddings + optional branding watermark
489:     compiler = VideoCompiler(output_dir, begin_padding=stitching.begin_padding,
490:                             end_padding=stitching.end_padding,
watermark=stitching.watermark)
646:     # clip carries the same configured stitching paddings + watermark as a real
647:     # highlight (watermark default-on).
649:     compiler = VideoCompiler(out_dir, begin_padding=stitching.begin_padding,
650:                             end_padding=stitching.end_padding,
watermark=stitching.watermark)
740:         play_wm, cand_wm = db_instance.segment_watermarks(video_id)
757:         db=db_instance, video_id=video_id, video_path=args.video_path,
config=global_config,

```

544. assistant (2026-06-21T18:02:35.470Z)

Let me read the request models and the compile endpoint body to see exactly where to thread the locale:

545. user (2026-06-21T18:02:35.939Z)

```

127     class ProcessRequest(BaseModel):
128         video_path: str
129         player_pool: Optional[List[str]] = None
130         max_frames: Optional[int] = None
131         segmenter: Optional[str] = None
132
133     class QueryRequest(BaseModel):
134         video_id: str
135         server: Optional[str] = None
136         receiver: Optional[str] = None
137         duration_min: Optional[float] = None
138         event_type: Optional[str] = None
139
140     class CompileRequest(BaseModel):
141         video_id: str
142         segment_ids: List[int]
143         output_filename: str
144
145     def _finalize_reingest(video_id: str, segments, play_wm: int, cand_wm: int) -> None:
146         """Commit a (re)segmentation with destroy-AFTER-confirm semantics.
147
148         On a non-empty run, drop the PRIOR rows (id <= the pre-run watermark) so only the
149         fresh segments remain. On an empty run, drop the NEW partial rows (id > watermark)
150         and
151         keep the prior good results intact ? a failed/empty re-run never destroys prior
152         data.
153         """
154         if segments:
155             db_instance.prune_segments(video_id, play_upto=play_wm, cand_upto=cand_wm)
156         else:
157             db_instance.prune_segments(video_id, play_after=play_wm, cand_after=cand_wm)
158
159     # --- API Endpoints ---
160     @app.get("/api/config")
161     def get_config():
162         return global_config

```

546. user (2026-06-21T18:02:36.929Z)

```

442     def compile_highlights(req: CompileRequest):
443         video = db_instance.get_video(req.video_id)
444         if not video:
445             raise HTTPException(status_code=404, detail="Indexed video record not found.")

```

```

446
447 # Retrieve matching play segments from db
448 all_segments = db_instance.query_play_segments(req.video_id, {})
449 matched_segments = [s for s in all_segments if s["id"] in req.segment_ids]
450
451 if not matched_segments:
452     raise HTTPException(status_code=400, detail="No matching play segments found to
stitch.")
453
454 # Reject path traversal / absolute output names (os.path.join would otherwise let an
455 # absolute or '..'-laden output_filename write anywhere on disk).
456 try:
457     out_name = safe_output_filename(req.output_filename)
458 except ValueError as e:
459     raise HTTPException(status_code=400, detail=str(e)) from e
460
461 # The configured shot-count floor (stitching.min_shot_count) applies on the API
462 # path too ? parity with scripts/run_process_and_stitch.py. Segments WITHOUT
shot_count
463 # metadata are exempt: the floor filters known counts only, so explicitly
464 # requested manual/legacy segments can't silently vanish under the default floor.
465 stitching = getattr(global_config, "stitching", None) or StitchingConfig()
466 kept = []
467 for s in matched_segments:
468     meta = s.get("metadata") or {}
469     sc = meta.get("shot_count") if isinstance(meta, dict) else None
470     try:
471         if sc is not None and int(sc) < stitching.min_shot_count:
472             continue
473     except (TypeError, ValueError):
474         pass # unparseable count -> treat as unknown, keep
475     kept.append(s)
476 if len(kept) < len(matched_segments):
477     logger.info(f"[compile] stitching.min_shot_count={stitching.min_shot_count}:
dropped "
478               f"{len(matched_segments) - len(kept)}/{len(matched_segments)}
segments below the floor.")
479     if not kept:
480         raise HTTPException(status_code=400,
481                             detail=f"All {len(matched_segments)} matching segments fall
below "
482                             f"stitching.min_shot_count={stitching.min_shot_count}.")
483
484 # Extract start/end time pairs
485 time_pairs = [(s["start_time"], s["end_time"]) for s in kept]
486
487 # Run compiler with the configured stitching paddings + optional branding watermark
488 output_dir = getattr(getattr(global_config, "output", None), "output_dir", "output")
or "output"
489 compiler = VideoCompiler(output_dir, begin_padding=stitching.begin_padding,
490                             end_padding=stitching.end_padding,
watermark=stitching.watermark)
491 try:
492     # The stored `filepath` is the SOURCE ref ? a bucket/Drive URI (gs://, s3://,
gdrive://) for a
493     # video ingested via /api/process from a URI, or a plain local path. Resolve it
to a LOCAL file
494     # the stitcher can read: identity for a local path (byte-identical to before),
fetch-to-scratch
495     # for a bucket URI (the same seam the process path uses, _execute_processing
main.py:159).
496     # Without this, compiling a bucket-ingested video 500s ? ffmpeg can't open a
gs:// path.

```

547. assistant (2026-06-21T18:04:39.087Z)

I now have the complete engine picture. Key facts driving the design:

- **Watermark** = ffmpeg `drawtext` with `text` + `font\_path` (defaults to bundled **RobotoSlab**, Latin-only), built at `/api/compile` from `global\_config.stitching.watermark`.
- **CompileRequest** (video_id, segment_ids, output_filename) and **ProcessRequest** (video_path, ?) ? neither carries locale.
- **DB**: migration head **v6** on origin/master; v7 is free but the serving session plans its own v7 ? real collision risk.
- **Fonts**: only RobotoSlab is bundled ? es/da/id work as-is, but **kn/hi** need Noto Sans Kannada/Devanagari `.ttf` bundled.

The font availability decides the kn/hi approach. Let me check whether I can source the Noto `.ttf` (from `@fontsource` in `node_modules`, or a download):

548. user (2026-06-21T18:04:44.458Z)

```
=== @fontsource files (kannada) ===
```

```
noto-sans-kannada-kannada-standard-normal.woff2
noto-sans-kannada-kannada-width-normal.woff2
noto-sans-kannada-kannada-wght-normal.woff2
noto-sans-kannada-latin-ext-standard-normal.woff2
noto-sans-kannada-latin-ext-width-normal.woff2
noto-sans-kannada-latin-ext-wght-normal.woff2
noto-sans-kannada-latin-standard-normal.woff2
noto-sans-kannada-latin-width-normal.woff2
noto-sans-kannada-latin-wght-normal.woff2
```

```
=== any .ttf in @fontsource kannada/devanagari? ===
(end ttf search)
```

```
=== network test: can we fetch a Noto ttf? ===
-rw-r--r-- 1 avidu 197609 14 Jun 21 23:34 /tmp/notok.ttf
/tmp/notok.ttf: ASCII text, with no line terminators
```

549. assistant (2026-06-21T18:05:06.636Z)

`@fontsource` ships only `woff2` (no good for `ffmpeg`), and the first fetch 404'd (wrong path). Let me check that response and try the correct google/fonts variable-`.ttf` paths:

550. user (2026-06-21T18:05:11.215Z)

```
=== what was the 14-byte response ===
404: Not Found
=== try correct google/fonts variable ttf paths ===
size=641372 type=TrueType Font data, 21 tables, 1st "GDEF", 58 names, Macintosh, type 295
string, ThinNotoSansKannada-ThinExtraLightNotoSansKannada-ExtraLightLightNotoSansKannada-
LightRegularNot <- https://raw.githubusercontent.com/google/fonts/main/ofl/notosanskannada/Noto
SansKannada%5Bwidth%2Cwght%5D.ttf
size=641372 type=TrueType Font data, 21 tables, 1st "GDEF", 58 names, Macintosh, type 295
string, ThinNotoSansKannada-ThinExtraLightNotoSansKannada-ExtraLightLightNotoSansKannada-
LightRegularNot <-
https://github.com/google/fonts/raw/main/ofl/notosanskannada/NotoSansKannada%5Bwidth,wght%5D.ttf
```

551. assistant (2026-06-21T18:06:35.475Z)

The correct URL works ? I fetched a valid **641 KB** Noto Sans Kannada variable `.ttf` (OFL)**. So **kn/hi** watermarks are fully achievable (fetch Noto Kannada + Devanagari from `google/fonts`, bundle as OFL media per the locked D7 carve-out).

Here's the spec, then I'll build it.

Spec ? locale capture + localized watermarks

****Architecture (deliberately decoupled, to ship the watermark without waiting on a DB migration):****

```
| Concern | How | Repo | Migration? |
|---|---|---|---|
| **Localized watermark** | `CompileRequest.locale` ? a `localize_watermark(cfg, locale)` helper
overrides `text` + `font_path` per locale ? ffmpeg `drawtext`. en/es/da/id use RobotoSlab; kn/hi
use bundled Noto. | engine | **No** |
| **SPA sends locale** | pass `i18n.resolvedLanguage` to `/api/compile` (watermark) **and**
`/api/process` (analytics) | khelsutra | ? |
| **PMF analytics** | `ProcessRequest.locale` ? `jobs.locale` column ? `SELECT locale, COUNT(*)
FROM jobs GROUP BY locale` | engine | **v7 (the collision-risk piece)** |
```

****3 PRs, lowest-risk first:**** PR-1 watermark (engine, no migration) ? PR-2 SPA (no engine collision) ? PR-3 analytics v7 migration (engine, ****done last + in an isolated worktree + re-verified against `origin/master`**** so it can't collide with the serving session's planned v7 ? renumber to v8 if theirs lands first). Sending `locale` to `/api/process` before PR-3 is harmless (Pydantic ignores unknown fields).

****Watermark fallback (honest):**** unknown/missing locale ? the existing default text+font (en behavior unchanged). If a Noto font is somehow absent, the compiler already retries without the watermark rather than failing the reel.

Let me build. Setting up tasks + an isolated engine worktree for PR-1, and fetching the fonts:

552. user (2026-06-21T18:06:37.367Z)

Task #10 created successfully: LW1 ? engine: localized reel watermark (locale ? text+font) + Noto fonts

553. user (2026-06-21T18:06:39.248Z)

Task #11 created successfully: LW2 ? SPA: pass UI locale to /api/compile (+ /api/process)

554. user (2026-06-21T18:06:40.775Z)

Task #12 created successfully: LW3 ? engine: jobs.locale v7 migration + PMF analytics query

555. assistant (2026-06-21T18:06:49.288Z)

Now the isolated worktree for the engine watermark PR + fetch both Noto fonts:

556. user (2026-06-21T18:06:56.985Z)

```
Preparing worktree (new branch 'feat/localized-watermark')
branch 'feat/localized-watermark' set up to track 'origin/master'.
HEAD is now at 4a06b8b feat(pkg): P1b ? bundle the KhelSutra SPA single-origin into the engine
wheel (default-OFF) (#302)
--- worktree HEAD ---
4a06b8b feat(pkg): P1b ? bundle the KhelSutra SPA single-origin into the engine wheel (default-
OFF) (#302)
--- fetch Noto fonts (OFL) into the worktree ---
total 1528
drwxr-xr-x 1 avidu 197609      0 Jun 21 23:36 .
drwxr-xr-x 1 avidu 197609      0 Jun 21 23:36 ..
-rw-r--r-- 1 avidu 197609 11560 Jun 21 23:36 LICENSE-Apache-2.0.txt
-rw-r--r-- 1 avidu 197609 647144 Jun 21 23:36 NotoSansDevanagari-Variable.ttf
-rw-r--r-- 1 avidu 197609 641372 Jun 21 23:36 NotoSansKannada-Variable.ttf
-rw-r--r-- 1 avidu 197609 1099 Jun 21 23:36 README.md
-rw-r--r-- 1 avidu 197609 251880 Jun 21 23:36 RobotoSlab-Regular.ttf
--- verify both are valid TrueType ---
/c/Users/avidu/Projects/bhi-loc-watermark/backend/assets/fonts/NotoSansKannada-Variable.ttf:
TrueType Font data, 21 tables, 1st "GDEF", 58 names, Macintosh, type 295 string,
ThinNotoSansKannada-ThinExtraLightNotoSansKannada-ExtraLightLightNotoSansKannada-LightRegularNot
```


/c/Users/avidu/Projects/bhi-loc-watermark/backend/assets/fonts/NotoSansDevanagari-Variable.ttf:
TrueType Font data, 20 tables, 1st "GDEF", 44 names, Macintosh, type 299 string,
ThinExtraLightLightRegularMediumSemiBoldBoldExtraBoldBlack

557. assistant (2026-06-21T18:07:19.701Z)

Both Noto fonts fetched (valid TrueType, OFL) into the worktree (now on the latest
`origin/master` `4a06b8b`). Now the critical check ? does ffmpeg `drawtext` actually render
Kannada/Devanagari with these fonts?

558. user (2026-06-21T18:07:26.203Z)

```
=== Kannada render test ===  
[image2 @ 0000015c9df3ee00] Use a pattern such as %03d for an image sequence or use the -update  
option (with -frames:v 1 if needed) to write a single image.  
[out#0/image2 @ 0000015c9dec5bc0] video:13KiB audio:0KiB subtitle:0KiB other streams:0KiB global  
headers:0KiB muxing overhead: unknown  
frame=    1 fps=0.0 q=-0.0 Lsize=N/A time=00:00:00.04 bitrate=N/A speed=3.06x elapsed=0:00:00.01  
exit=0 size=13526  
=== Devanagari render test ===  
[image2 @ 000001fdd913e600] Use a pattern such as %03d for an image sequence or use the -update  
option (with -frames:v 1 if needed) to write a single image.  
[out#0/image2 @ 000001fdd90c5f00] video:8KiB audio:0KiB subtitle:0KiB other streams:0KiB global  
headers:0KiB muxing overhead: unknown  
frame=    1 fps=0.0 q=-0.0 Lsize=N/A time=00:00:00.04 bitrate=N/A speed=3.66x elapsed=0:00:00.01  
exit=0 size=8487  
=== Spanish via RobotoSlab (Latin diacritics) ===  
[out#0/image2 @ 000001b7dc125a00] video:10KiB audio:0KiB subtitle:0KiB other streams:0KiB global  
headers:0KiB muxing overhead: unknown  
frame=    1 fps=0.0 q=-0.0 Lsize=N/A time=00:00:00.04 bitrate=N/A speed=3.76x elapsed=0:00:00.01  
exit=0 size=9952  
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

559. assistant (2026-06-21T18:07:34.712Z)

All three render (exit 0, real output). Let me visually confirm the glyphs aren't tofu by
viewing the rendered frames:

560. user (2026-06-21T18:07:35.022Z)

File does not exist. Note: your current working directory is C:\Users\avidu\Projects\badminton-
highlight-indexer.

561. user (2026-06-21T18:07:44.903Z)

```
-rw-r--r-- 1 avidu 197609 9952 Jun 21 23:37 /c/Users/avidu/Projects/bhi-loc-watermark/wm_es.png  
-rw-r--r-- 1 avidu 197609 8487 Jun 21 23:37 /c/Users/avidu/Projects/bhi-loc-watermark/wm_hi.png  
-rw-r--r-- 1 avidu 197609 13526 Jun 21 23:37 /c/Users/avidu/Projects/bhi-loc-watermark/wm_kn.png
```

562. assistant (2026-06-21T18:07:59.018Z)

Kannada renders perfectly ? Latin brand + Kannada glyphs, no tofu. Let me confirm Devanagari:

563. assistant (2026-06-21T18:08:53.035Z)

Both render flawlessly ? Kannada and Devanagari glyphs (no tofu), with the Latin
"KheLSutra.guru" brand intact. The approach is proven end-to-end. Building LW1 now. First clean
up the test artifacts and read the fonts README + fetch the OFL license:

564. user (2026-06-21T18:08:53.515Z)

Updated task #10 status

565. user (2026-06-21T18:08:58.028Z)

removed test pngs
=== current fonts README ===

Bundled fonts

Fonts shipped with the highlight **watermark** (``stitching.watermark``). All bundled fonts are **Apache-2.0** ? commercial-clean per the project licensing guardrail (MIT/Apache/BSD only), so they can be redistributed with the tool and self-hosted derivatives.

```
| File | Font | License | Source |  
|-----|-----|-----|-----|  
| `RobotoSlab-Regular.ttf` | Roboto Slab | Apache-2.0 (see `LICENSE-Apache-2.0.txt`) |  
https://github.com/google/fonts/tree/main/apache/robotoslab |
```

``RobotoSlab-Regular.ttf`` is the **default** watermark font: ``stitching.watermark.font_path`` defaults to it so the overlay renders **without a system fontconfig setup** (a common gap on Windows, where ``font='Sans'`` fails). To use a different typeface ? your own, or another bundled one ? set ``stitching.watermark.font_path`` to its path in ``config.json``.

To add more bundled options, drop the `.ttf`` here, keep it **MIT/Apache/BSD-licensed**, and add a row to the table above (with its license file).

Roboto Slab is © Google, licensed under the Apache License, Version 2.0.

=== fetch OFL-1.1 license text ===
Copyright 2022 The Noto Project Authors (<https://github.com/notofonts/kannada>)

This Font Software is licensed under the SIL Open Font License, Version 1.1.
... (93 lines)

566. assistant (2026-06-21T18:09:09.860Z)

OFL license fetched (SIL OFL 1.1). Now build the engine pieces. First the localization helper:

567. assistant (2026-06-21T18:09:27.616Z)

"""Localized reel-watermark text + font selection.

The SPA passes the UI locale to ``POST /api/compile``; this maps it to a localized branding string and a script-appropriate bundled font, so a Kannada/Hindi/? user's reel carries the watermark in their language. The brand token (`"KheISutra.guru"`) stays Latin; only the surrounding phrase localizes.

Fonts (``backend/assets/fonts/``):

- en/es/da/id (Latin) ? the configured default (bundled RobotoSlab, Apache-2.0)
- kn ? Noto Sans Kannada · hi ? Noto Sans Devanagari (OFL-1.1, bundled ? the D7 OFL-for-media carve-out; FRIENDLY_AND_MULTILINGUAL §4 anticipated this).

Honest fallbacks: an unknown/missing locale (or a locale with no entry, incl. ``en``) returns the watermark UNCHANGED, so existing/default behavior is preserved. If a script font file is somehow absent, ``font_path`` is left at the default (RobotoSlab) rather than pointing at a missing file ? and the compiler already retries the encode without the watermark if `drawtext` can't render, so a font gap can never nuke the reel. Kept config-package-agnostic (operates on a dict).

```
from pathlib import Path  
from typing import Any, Dict, Optional
```

This module is backend/pipeline/stitcher/ ? parents[2] == backend/ (matches compiler

```
_FONTS_DIR = Path(__file__).resolve().parents[2] / "assets" / "fonts"
```

Localized watermark phrase per locale. AI-drafted ? native-speaker review pending (save the SPA catalogs). `en` is intentionally absent: it falls through to the configured default

```
WATERMARK_TEXT: Dict[str, str] = {
    "es": "Generado con KhelSutra.guru",
    "da": "Lavet med KhelSutra.guru",
    "id": "Dibuat dengan KhelSutra.guru",
    "kn": "KhelSutra.guru ????? ??????????",
    "hi": "KhelSutra.guru ?? ????? ???",
}
```

Script-specific bundled fonts ? only where the Latin default (RobotoSlab) can't render
Latin locales (es/da/id) localize the TEXT but keep the default font.

```
FONT_FILE_BY_LOCALE: Dict[str, str] = {
    "kn": "NotoSansKannada-Variable.ttf",
    "hi": "NotoSansDevanagari-Variable.ttf",
}
```

```
def _base_locale(locale: Optional[str]) -> str:
    """Normalize a BCP-47 tag to its base subtag: 'kn-IN'/'kn_IN'/'KN' ? 'kn'."""
    return (locale or "").strip().lower().replace("_", "-").split("-")[0]
```

```
def localize_watermark(watermark: Any, locale: Optional[str]) -> Any:
    """Return a watermark dict with ``text`` (and ``font_path`` for non-Latin scripts) localized
    for
    ``locale``. Returns the input UNCHANGED for ``en`` / unknown / missing locale (default
    behavior).
```

```
    Accepts a ``WatermarkConfig`` model or a plain dict; returns a dict when it localizes (the
    shape
    ``VideoCompiler`` already accepts), or the original object untouched when there's nothing to
    do.
```

```
    """
    base = _base_locale(locale)
    if base not in WATERMARK_TEXT:
        return watermark # en / unsupported / missing ? configured default, unchanged

    if hasattr(watermark, "model_dump"):
        wm: Dict[str, Any] = watermark.model_dump()
    elif isinstance(watermark, dict):
        wm = dict(watermark)
    else:
        return watermark # unknown shape ? don't risk mangling it

    wm["text"] = WATERMARK_TEXT[base]
    font_file = FONT_FILE_BY_LOCALE.get(base)
    if font_file:
        font_path = _FONTS_DIR / font_file
        if font_path.exists():
            wm["font_path"] = str(font_path)
        # else: leave the configured/default font_path (RobotoSlab) ? a graceful Latin fallback.
    return wm
```

568. user (2026-06-21T18:09:27.645Z)

File created successfully at: C:\Users\avidu\Projects\bhi-loc-watermark\backend\pipeline\stitcher\watermark_i18n.py (file state is current in your context ? no need to Read it back)

569. assistant (2026-06-21T18:09:33.573Z)

Now wire it into `/api/compile` ? add `locale` to `CompileRequest` and apply the helper:

570. user (2026-06-21T18:09:36.178Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

571. assistant (2026-06-21T18:09:47.566Z)

Right ? the worktree is off `origin/master`, which differs from the concurrent branch I read earlier. Let me read the worktree's actual `main.py` sections:

572. user (2026-06-21T18:09:49.138Z)

```
202:class ProcessRequest(BaseModel):
215:class CompileRequest(BaseModel):
642:def compile_highlights(req: CompileRequest):
689:    compiler = VideoCompiler(output_dir, begin_padding=stitching.begin_padding,
690:                             end_padding=stitching.end_padding,
watermark=stitching.watermark)
852:    compiler = VideoCompiler(out_dir, begin_padding=stitching.begin_padding,
853:                             end_padding=stitching.end_padding,
watermark=stitching.watermark)
```

573. user (2026-06-21T18:09:57.416Z)

```
202    class ProcessRequest(BaseModel):
203        video_path: str
204        player_pool: Optional[List[str]] = None
205        max_frames: Optional[int] = None
206        segmenter: Optional[str] = None
207
208    class QueryRequest(BaseModel):
209        video_id: str
210        server: Optional[str] = None
211        receiver: Optional[str] = None
212        duration_min: Optional[float] = None
213        event_type: Optional[str] = None
214
215    class CompileRequest(BaseModel):
216        video_id: str
217        segment_ids: List[int]
218        output_filename: str
219
220    def _finalize_reingest(video_id: str, segments, play_wm: int, cand_wm: int) -> None:
221        """Commit a (re)segmentation with destroy-AFTER-confirm semantics.
222
223        On a non-empty run, drop the PRIOR rows (id <= the pre-run watermark) so only the
```

574. user (2026-06-21T18:09:58.243Z)

```
684        # Extract start/end time pairs
685        time_pairs = [(s["start_time"], s["end_time"]) for s in kept]
686
687        # Run compiler with the configured stitching paddings + optional branding watermark
688        output_dir = getattr(getattr(global_config, "output", None), "output_dir", "output")
or "output"
689        compiler = VideoCompiler(output_dir, begin_padding=stitching.begin_padding,
690                                 end_padding=stitching.end_padding,
watermark=stitching.watermark)
691        try:
692            # The stored `filepath` is the SOURCE ref ? a bucket/Drive URI (gs://, s3://,
gdrive://) for a
693            # video ingested via /api/process from a URI, or a plain local path. Resolve it
to a LOCAL file
```

575. user (2026-06-21T18:10:09.758Z)

The file C:\Users\avidu\Projects\bhi-loc-watermark\backend\main.py has been updated successfully. (file state is current in your context ? no need to Read it back)

576. user (2026-06-21T18:10:29.404Z)

The file C:\Users\avidu\Projects\bhi-loc-watermark\backend\main.py has been updated successfully. (file state is current in your context ? no need to Read it back)

577. assistant (2026-06-21T18:10:37.962Z)

Now add the import. Let me find the `VideoCompiler` import line in the worktree:

578. user (2026-06-21T18:10:39.367Z)

```
39:from backend.pipeline.stitcher.compiler import VideoCompiler
```

579. user (2026-06-21T18:10:46.372Z)

The file C:\Users\avidu\Projects\bhi-loc-watermark\backend\main.py has been updated successfully. (file state is current in your context ? no need to Read it back)

580. assistant (2026-06-21T18:10:53.511Z)

Now update the fonts README to attribute the OFL Noto fonts + the D7 carve-out:

581. assistant (2026-06-21T18:11:04.681Z)

Bundled fonts

Fonts shipped with the highlight **watermark** (`stitching.watermark``), used by ffmpeg `drawtext`` during the per-clip re-encode (`backend/pipeline/stitcher/compiler.py``).

File	Font	License	Used for	Source
<code>RobotoSlab-Regular.ttf`</code>	Roboto Slab	Apache-2.0 (<code>LICENSE-Apache-2.0.txt`</code>)	default watermark; Latin locales (en/es/da/id)	https://github.com/google/fonts/tree/main/apache/robotoslab
<code>NotoSansKannada-Variable.ttf`</code>	Noto Sans Kannada	OFL-1.1 (<code>LICENSE-OFL-1.1.txt`</code>)	Kannada (<code>kn`</code>) watermark	https://github.com/google/fonts/tree/main/ofl/notosanskannada
<code>NotoSansDevanagari-Variable.ttf`</code>	Noto Sans Devanagari	OFL-1.1 (<code>LICENSE-OFL-1.1.txt`</code>)	Hindi (<code>hi`</code>) watermark	https://github.com/google/fonts/tree/main/ofl/notosansdevanagari

`RobotoSlab-Regular.ttf`` is the **default** watermark font: `stitching.watermark.font_path`` defaults to it so the overlay renders **without a system fontconfig setup** (a common gap on Windows, where `font='Sans`` fails). The **localized** watermark (`backend/pipeline/stitcher/watermark_i18n.py``, driven by the UI locale on `POST /api/compile``) keeps RobotoSlab for Latin locales and switches to the script-appropriate Noto font for `kn`/hi``. The Noto fonts also include basic Latin, so the Latin brand token (`"KheI Sutra.guru"`) renders correctly alongside the local script.

Licensing

Code/data/weights stay **MIT/Apache/BSD** per the project guardrail. **Fonts are media, not code** ? the **OFL-for-media carve-out (FRIENDLY_AND_MULTILINGUAL D7, owner-ratified 2026-06-21)** permits bundling/redistributing **SIL OFL-1.1** fonts (the same Noto faces the SPA self-hosts). To add another bundled font: drop the `.ttf`` here, keep it **MIT/Apache/BSD** *or* **OFL-1.1**, ship its license

file, and
add a row above.

Roboto Slab is © Google, licensed under the Apache License, Version 2.0. Noto Sans Kannada and Noto Sans Devanagari are © The Noto Project Authors, licensed under the SIL Open Font License, Version 1.1.

582. user (2026-06-21T18:11:04.683Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

583. user (2026-06-21T18:11:12.634Z)

```
1      # Bundled fonts
2
3      Fonts shipped with the highlight **watermark** (`stitching.watermark`). All bundled
fonts
4      are **Apache-2.0** ? commercial-clean per the project licensing guardrail
(MIT/Apache/BSD
5      only), so they can be redistributed with the tool and self-hosted derivatives.
6
7      | File | Font | License | Source |
8      |-----|-----|-----|-----|
9      | `RobotoSlab-Regular.ttf` | Roboto Slab | Apache-2.0 (see `LICENSE-Apache-2.0.txt`) |
https://github.com/google/fonts/tree/main/apache/robotoslab |
10
11      `RobotoSlab-Regular.ttf` is the **default** watermark font:
`stitching.watermark.font_path`
12      defaults to it so the overlay renders **without a system fontconfig setup** (a common
gap
13      on Windows, where `font='Sans'` fails). To use a different typeface ? your own, or
another
14      bundled one ? set `stitching.watermark.font_path` to its path in `config.json`.
15
16      To add more bundled options, drop the `.ttf` here, keep it **MIT/Apache/BSD-licensed**,
and
17      add a row to the table above (with its license file).
18
19      *Roboto Slab is © Google, licensed under the Apache License, Version 2.0.*
20
```

584. assistant (2026-06-21T18:11:27.122Z)

Bundled fonts

Fonts shipped with the highlight ****watermark**** (`stitching.watermark`), used by ffmpeg
`drawtext`
during the per-clip re-encode (`backend/pipeline/stitcher/compiler.py`).

```
| File | Font | License | Used for | Source |
|-----|-----|-----|-----|-----|
| `RobotoSlab-Regular.ttf` | Roboto Slab | Apache-2.0 (`LICENSE-Apache-2.0.txt`) | **default**
watermark; Latin locales (en/es/da/id) |
https://github.com/google/fonts/tree/main/apache/robotoslab |
| `NotoSansKannada-Variable.ttf` | Noto Sans Kannada | OFL-1.1 (`LICENSE-OFL-1.1.txt`) | Kannada
(`kn`) watermark | https://github.com/google/fonts/tree/main/ofl/notosanskannada |
| `NotoSansDevanagari-Variable.ttf` | Noto Sans Devanagari | OFL-1.1 (`LICENSE-OFL-1.1.txt`) |
Hindi (`hi`) watermark | https://github.com/google/fonts/tree/main/ofl/notosansdevanagari |
```

`RobotoSlab-Regular.ttf` is the ****default**** watermark font: `stitching.watermark.font\_path`
defaults to it so the overlay renders ****without a system fontconfig setup**** (a common gap on
Windows, where `font='Sans'` fails). The ****localized**** watermark (`backend/pipeline/stitcher/
watermark_i18n.py`, driven by the UI locale on `POST /api/compile`) keeps RobotoSlab for Latin

locales and switches to the script-appropriate Noto font for `kn`/`hi`. The Noto fonts also include basic Latin, so the Latin brand token ("KheI Sutra.guru") renders correctly alongside the local script.

Licensing

Code/data/weights stay **MIT/Apache/BSD** per the project guardrail. **Fonts are media, not code** ?
the **OFL-for-media** carve-out (FRIENDLY_AND_MULTILINGUAL D7, owner-ratified 2026-06-21)** permits bundling/redistributing **SIL OFL-1.1** fonts (the same Noto faces the SPA self-hosts). To add another bundled font: drop the `.ttf` here, keep it **MIT/Apache/BSD** *or* **OFL-1.1**, ship its license file, and add a row above.

Roboto Slab is © Google, licensed under the Apache License, Version 2.0. Noto Sans Kannada and Noto Sans Devanagari are © The Noto Project Authors, licensed under the SIL Open Font License, Version 1.1.

585. user (2026-06-21T18:11:27.166Z)

The file C:\Users\avidu\Projects\bhi-loc-watermark\backend\assets\fonts\README.md has been updated successfully. (file state is current in your context ? no need to Read it back)

586. assistant (2026-06-21T18:11:52.989Z)

Now the test for the helper. Let me check the engine test conventions, then write it:

587. user (2026-06-21T18:11:55.258Z)

```
test_api_endpoints.py
test_compiler.py
test_watermark.py
---
tests/test_api_endpoints.py
tests/test_compiler.py
tests/test_config.py
tests/test_generate_highlights.py
tests/test_import_smoke.py
tests/test_watermark.py
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

588. user (2026-06-21T18:12:04.555Z)

```
1      """Tests for the configurable highlight watermark (stitching.watermark).
2
3      Covers the config defaults, the filtergraph builder (text + logo, positions, font,
4      the configurable string), and the end-to-end wiring through compile_highlights with
5      ffmpeg/ffprobe mocked ? including the graceful fallback when the watermark encode fails.
6      """
7      import os
8      import subprocess
9      from pathlib import Path
10     from unittest.mock import MagicMock, patch
11
12     import pytest
13     from pydantic import ValidationError
14
15     from backend.config import AppConfig
16     from backend.config.models import WatermarkConfig
17     from backend.pipeline.stitcher.compiler import VideoCompiler
```

```

18
19
20 # --- config -----
21
22 def test_watermark_config_defaults_on_with_brand_text():
23     wm = AppConfig().stitching.watermark
24     assert wm.enabled is True # default-on, with an off switch
25     assert wm.text == "Generated by Khelsutra.guru"
26     assert wm.position == "bottom-right"
27
28
29 def test_watermark_can_be_disabled_via_config():
30     cfg = AppConfig.model_validate({"stitching": {"watermark": {"enabled": False}}})
31     assert cfg.stitching.watermark.enabled is False
32
33
34 def test_font_size_ratio_and_opacity_bounds_enforced():
35     with pytest.raises(ValidationError):
36         WatermarkConfig(opacity=1.5)
37     with pytest.raises(ValidationError):
38         WatermarkConfig(font_size_ratio=0.0)
39
40
41 # --- filtergraph builder -----
42
43 def test_disabled_or_none_builds_no_filter(tmp_path):
44     assert VideoCompiler(str(tmp_path / "a"),
45 watermark=None)._watermark_filter(str(tmp_path)) is None
46     off = VideoCompiler(str(tmp_path / "b"), watermark={"enabled": False})
47     assert off._watermark_filter(str(tmp_path)) is None
48
49
50 def test_text_filter_writes_configurable_string_and_builds_drawtext(tmp_path):
51     custom = "My Academy 2026 ? Khelsutra.guru"
52     comp = VideoCompiler(str(tmp_path / "o"), watermark={"enabled": True, "text":
53 custom})
54     graph = comp._watermark_filter(str(tmp_path))
55     assert graph is not None and graph.startswith("drawtext=")
56     # The arbitrary, configurable string is written verbatim to the textfile (no
57 escaping pain).
58     assert (tmp_path / "watermark.txt").read_text(encoding="utf-8") == custom
59     assert "textfile=" in graph
60     assert "fontcolor=white@0.85" in graph
61     assert "fontsize=h/29" in graph # round(1/0.035) == 29
62     assert "x=w-tw-24:y=h-th-24" in graph # bottom-right default, margin 24
63     assert "box=1" in graph
64
65
66 def test_position_and_margin_map_to_corner(tmp_path):
67     comp = VideoCompiler(str(tmp_path / "o"),
68 watermark={"enabled": True, "text": "X", "position": "top-
69 left", "margin": 12})
70     graph = comp._watermark_filter(str(tmp_path))
71     assert "x=12:y=12" in graph
72
73
74 def test_explicit_font_path_uses_fontfile(tmp_path):
75     comp = VideoCompiler(str(tmp_path / "o1"),
76 watermark={"enabled": True, "text": "X", "font_path":
77 "/fonts/Brand.ttf"})
78     g = comp._watermark_filter(str(tmp_path))
79     assert "fontfile='/fonts/Brand.ttf'" in g
80
81
82 def test_default_uses_bundled_apache_font(tmp_path):

```



```

78     # No font_path ? the bundled Apache-2.0 Roboto Slab (renders without fontconfig).
79     comp = VideoCompiler(str(tmp_path / "o2"), watermark={"enabled": True, "text": "X"})
80     g = comp._watermark_filter(str(tmp_path))
81     assert "fontfile=" in g and "RobotoSlab-Regular.ttf" in g
82     assert "font=" not in g # not the fontconfig path
83
84
85     def test_bundled_font_actually_ships_and_is_apache():
86         import backend.pipeline.stitcher.compiler as cmod
87         assert cmod._BUNDLED_FONT.exists(), "bundled default watermark font must ship in the
repo"
88         with open(cmod._BUNDLED_FONT, "rb") as fh:
89             assert fh.read(4) in (b"\x00\x01\x00\x00", b"OTTO", b"true", b"ttcf") # valid
sfnt
90         lic = cmod._BUNDLED_FONT.parent / "LICENSE-Apache-2.0.txt"
91         assert lic.exists() and "Apache License" in lic.read_text(encoding="utf-8",
errors="replace")
92
93
94     def test_fontconfig_fallback_when_bundled_missing(tmp_path, monkeypatch):
95         import backend.pipeline.stitcher.compiler as cmod
96         monkeypatch.setattr(cmod, "_BUNDLED_FONT", Path("/no/such/font.ttf"))
97         comp = VideoCompiler(str(tmp_path / "o3"),
98                             watermark={"enabled": True, "text": "X", "font": "DejaVu
Sans"})
99         g = comp._watermark_filter(str(tmp_path))
100         assert "font='DejaVu Sans'" in g and "fontfile=" not in g
101
102
103     # --- Windows drive-letter colon escaping (regression) -----
104     # A Windows absolute path's drive-letter colon (C:/...) must be escaped for the
105     # ffmpeg filtergraph, or drawtext/movie parse ':' as an option separator and the
106     # encode fails with "Invalid argument" ? which silently disabled the on-by-default
107     # bundled-font watermark (and absolute logo paths) on Windows. Verified end-to-end
108     # against real ffmpeg before this fix landed.
109
110     def test_ff_quote_escapes_drive_letter_colon():
111         assert VideoCompiler._ff_quote(r"C:\fonts\Brand.ttf") == r"C\:/fonts/Brand.ttf"
112         # no colon -> unchanged (POSIX paths and the Linux bundled font are unaffected)
113         assert VideoCompiler._ff_quote("/usr/share/fonts/font.ttf") ==
"/usr/share/fonts/font.ttf"
114         # colon + single-quote + backslash all handled
115         assert VideoCompiler._ff_quote(r"D:\a\b\f.ttf") == r"D\:/a\b/f.ttf"
116
117
118     def test_watermark_font_path_with_drive_colon_is_escaped(tmp_path):
119         # Explicit font_path (literal, existence not required) -> deterministic on any OS.
120         comp = VideoCompiler(str(tmp_path / "o"),
121                             watermark={"enabled": True, "text": "X", "font_path":
"C:/fonts/Brand.ttf"})
122         g = comp._watermark_filter(str(tmp_path))
123         assert r"fontfile='C\:/fonts/Brand.ttf'" in g
124         assert "fontfile='C:/fonts" not in g # the raw colon would break drawtext parsing
125
126
127     def test_logo_plus_text_overlays_then_draws(tmp_path):
128         logo = tmp_path / "logo.png"
129         logo.write_bytes(b"\x89PNG\r\n")
130         comp = VideoCompiler(str(tmp_path / "o"),
131                             watermark={"enabled": True, "text": "X", "logo_path":
str(logo)})
132         graph = comp._watermark_filter(str(tmp_path))
133         assert graph.startswith("movie=")
134         assert "overlay=W-w-24:H-h-24" in graph
135         assert "drawtext=" in graph

```

```

136
137
138     def test_missing_logo_is_skipped_gracefully(tmp_path):
139         comp = VideoCompiler(str(tmp_path / "o"),
140                               watermark={"enabled": True, "text": "X", "logo_path":
141 str(tmp_path / "nope.png")})
142         graph = comp._watermark_filter(str(tmp_path))
143         assert "movie=" not in graph and graph.startswith("drawtext=") # text still drawn
144
145     # --- end-to-end wiring (ffmpeg/ffprobe mocked) -----
146
147     def _fake_run_factory(calls, fail_on_vf=False):
148         def fake_run(cmd, *a, **k):
149             calls.append(cmd)
150             if cmd[0] == "ffprobe":
151                 return MagicMock(stdout="100.0\n", returncode=0)
152             if fail_on_vf and "-vf" in cmd:
153                 raise subprocess.CalledProcessError(1, cmd, output=b"", stderr=b"font not
154 found")
155             out = cmd[-1]
156             if isinstance(out, str) and out.endswith(".mp4"):
157                 open(out, "wb").write(b"clip")
158             return MagicMock(returncode=0, stdout=b"", stderr=b"")
159         return fake_run
160
161     def test_compile_applies_watermark_vf_to_each_clip_not_concat(tmp_path):
162         raw = tmp_path / "raw.mp4"
163         raw.write_bytes(b"x")
164         comp = VideoCompiler(str(tmp_path / "out"),
165                               watermark={"enabled": True, "text": "Generated by
166 Khelsutra.guru"})
167         calls = []
168         with patch.object(subprocess, "run", side_effect=_fake_run_factory(calls)):
169             comp.compile_highlights(str(raw), [(0.0, 5.0), (10.0, 15.0)], "reel.mp4")
170
171         trim_cmds = [c for c in calls if c[0] == "ffmpeg" and "-i" in c and "concat" not in
172 c]
173         assert trim_cmds, "expected per-clip trim invocations"
174         for c in trim_cmds:
175             assert "-vf" in c
176             assert "drawtext=" in c[c.index("-vf") + 1]
177         # The concat (-c copy) must NOT re-filter ? the mark is already baked into each
178 clip.
179         concat_cmds = [c for c in calls if "concat" in c]
180         assert concat_cmds and all("-vf" not in c for c in concat_cmds)
181
182     def test_compile_without_watermark_adds_no_vf(tmp_path):
183         raw = tmp_path / "raw.mp4"
184         raw.write_bytes(b"x")
185         comp = VideoCompiler(str(tmp_path / "out")) # no watermark passed
186         calls = []
187         with patch.object(subprocess, "run", side_effect=_fake_run_factory(calls)):
188             comp.compile_highlights(str(raw), [(0.0, 5.0)], "reel.mp4")
189         assert all("-vf" not in c for c in calls)
190
191     def test_watermark_failure_falls_back_to_unwatermarked_clip(tmp_path):
192         """A bad font/logo must not nuke the reel: the clip re-encodes without the
193 watermark."""
194         raw = tmp_path / "raw.mp4"
195         raw.write_bytes(b"x")
196         comp = VideoCompiler(str(tmp_path / "out"),

```

```

195                 watermark={"enabled": True, "text": "Generated by
Khelsutra.guru"})
196         calls = []
197         with patch.object(subprocess, "run", side_effect=_fake_run_factory(calls,
fail_on_vf=True)):
198             out_path = comp.compile_highlights(str(raw), [(0.0, 5.0)], "reel.mp4")
199
200         # Reel still produced despite the watermark encode failing.
201         assert out_path.endswith("reel.mp4")
202         assert os.path.exists(out_path)
203         # For the clip, both a watermarked attempt and a plain fallback attempt were made.
204         clip_cmds = [c for c in calls if c[0] == "ffmpeg" and "concat" not in c and "-i" in
c]
205         assert any("-vf" in c for c in clip_cmds)          # watermark attempt
206         assert any("-vf" not in c for c in clip_cmds)      # fallback attempt
207
208
209     def test_watermark_failure_logs_the_ffmpeg_reason(tmp_path, caplog):
210         """The fallback warning must surface ffmpeg's stderr (the *why*), not go silent ?
211         e.g. the 'Fontconfig error' that tells the user to set font_path."""
212         import logging as _logging
213         raw = tmp_path / "raw.mp4"
214         raw.write_bytes(b"x")
215         comp = VideoCompiler(str(tmp_path / "out"), watermark={"enabled": True, "text":
"Y"})
216
217         def fake_run(cmd, *a, **k):
218             if cmd[0] == "ffprobe":
219                 return MagicMock(stdout="100.0\n", returncode=0)
220             if "-vf" in cmd:
221                 raise subprocess.CalledProcessError(
222                     1, cmd, output=b"", stderr=b"Fontconfig error: Cannot load default
config file")
223             out = cmd[-1]
224             if isinstance(out, str) and out.endswith(".mp4"):
225                 open(out, "wb").write(b"clip")
226             return MagicMock(returncode=0, stdout=b"", stderr=b"")
227
228         with caplog.at_level(_logging.WARNING):
229             with patch.object(subprocess, "run", side_effect=fake_run):
230                 comp.compile_highlights(str(raw), [(0.0, 5.0)], "reel.mp4")
231         assert "Fontconfig error" in caplog.text
232

```

589. assistant (2026-06-21T18:12:19.993Z)

Good ? clear conventions. Now the test for the i18n helper (mirroring the style, including a filtergraph integration check):

590. assistant (2026-06-21T18:12:39.856Z)

```

"""Tests for the localized reel watermark (backend/pipeline/stitcher/watermark_i18n.py).

```

```

The SPA passes the UI locale to /api/compile; localize_watermark maps it to a localized branding
string + a script-appropriate bundled font. Covers: en/unknown/None pass-through (default
unchanged),
Latin locales (text-only override), kn/hi (text + the bundled Noto font), BCP-47 base-subtag
normalization, model-and-dict inputs without mutation, the bundled Noto fonts actually shipping
(OFI), and that a localized watermark flows correctly into the ffmpeg drawtext filtergraph.
"""

```

```

from pathlib import Path

```

```

from backend.config.models import WatermarkConfig
from backend.pipeline.stitcher.compiler import VideoCompiler
from backend.pipeline.stitcher.watermark_i18n import (

```

```

    FONT_FILE_BY_LOCALE,
    WATERMARK_TEXT,
    _FONTS_DIR,
    localize_watermark,
)

```

--- pass-through (default behavior preserved) -----

```

def test_en_unknown_none_pass_through_unchanged():
    cfg = WatermarkConfig()
    # en / unsupported / missing ? the SAME object back (configured default text + font
    untouched).
    assert localize_watermark(cfg, "en") is cfg
    assert localize_watermark(cfg, "en-US") is cfg
    assert localize_watermark(cfg, "fr") is cfg # supported by neither the watermark nor the
    SPA
    assert localize_watermark(cfg, None) is cfg
    assert localize_watermark(cfg, "") is cfg

```

--- Latin locales: text localized, font stays the default -----

```

def test_latin_locales_override_text_only():
    cfg = WatermarkConfig()
    for loc in ("es", "da", "id"):
        wm = localize_watermark(cfg, loc)
        assert isinstance(wm, dict)
        assert wm["text"] == WATERMARK_TEXT[loc]
        # No script font override ? keeps the configured default (empty ? RobotoSlab in the
        compiler).
        assert wm.get("font_path", "") == cfg.font_path
        assert "Noto" not in wm.get("font_path", "")

```

--- kn/hi: text localized + the bundled Noto font -----

```

def test_indic_locales_set_text_and_bundled_noto_font():
    cfg = WatermarkConfig()
    for loc, font_file in FONT_FILE_BY_LOCALE.items(): # kn, hi
        wm = localize_watermark(cfg, loc)
        assert wm["text"] == WATERMARK_TEXT[loc]
        assert wm["font_path"].endswith(font_file)
        assert Path(wm["font_path"]).exists(), f"{loc} watermark font must ship"

def test_base_subtag_normalization():
    cfg = WatermarkConfig()
    assert localize_watermark(cfg, "kn-IN")["text"] == WATERMARK_TEXT["kn"]
    assert localize_watermark(cfg, "hi-IN")["text"] == WATERMARK_TEXT["hi"]
    assert localize_watermark(cfg, "ES")["text"] == WATERMARK_TEXT["es"]
    assert localize_watermark(cfg, "es-419")["text"] == WATERMARK_TEXT["es"] # Latin-American
    Spanish

```

--- input handling: model + dict, no mutation -----

```

def test_accepts_dict_and_does_not_mutate_input():
    original = {"enabled": True, "text": "Generated by Khelsutra.guru", "font_path": ""}
    wm = localize_watermark(original, "kn")
    assert wm is not original
    assert original["text"] == "Generated by Khelsutra.guru" # input untouched

```

```
assert wm["text"] == WATERMARK_TEXT["kn"]
```

--- bundled assets ship + are valid sfnt + OFL-licensed -----

```
def test_bundled_noto_fonts_ship_and_are_valid_sfnt():
    for font_file in FONT_FILE_BY_LOCALE.values():
        fp = _FONTS_DIR / font_file
        assert fp.exists(), f"{font_file} must ship in backend/assets/fonts/"
        with open(fp, "rb") as fh:
            assert fh.read(4) in (b"\x00\x01\x00\x00", b"OTTO", b"true", b"ttcf") # valid sfnt
        ofl = _FONTS_DIR / "LICENSE-OFL-1.1.txt"
        assert ofl.exists() and "Open Font License" in ofl.read_text(encoding="utf-8",
errors="replace")
```

--- end-to-end: a localized watermark flows into the drawtext filtergraph -----

```
def test_localized_watermark_flows_into_drawtext_filtergraph(tmp_path):
    wm = localize_watermark(WatermarkConfig(enabled=True), "kn")
    graph = VideoCompiler(str(tmp_path / "o"), watermark=wm)._watermark_filter(str(tmp_path))
    assert graph is not None and "NotoSansKannada-Variable.ttf" in graph
    # The Kannada string is written verbatim to the drawtext textfile.
    assert (tmp_path / "watermark.txt").read_text(encoding="utf-8") == WATERMARK_TEXT["kn"]
```

591. user (2026-06-21T18:12:39.882Z)

File created successfully at: C:\Users\avidu\Projects\bhi-loc-watermark\tests\test_watermark_i18n.py (file state is current in your context ? no need to Read it back)

592. assistant (2026-06-21T18:12:46.989Z)

Now run the engine gate on the worktree ? the new test, related tests, ruff, mypy:

593. user (2026-06-21T18:12:50.537Z)

```
..... [100%]
31 passed in 0.59s
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

594. assistant (2026-06-21T18:13:01.110Z)

31 passed (incl. my 8 new tests). Now ruff + mypy on the changes + the API-endpoint tests:

595. user (2026-06-21T18:13:19.718Z)

```
=== ruff ===
All checks passed!
ruff done
=== mypy ===
Success: no issues found in 1 source file
=== api endpoints test (compile path) ===
..... [100%]
38 passed in 12.08s
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

596. assistant (2026-06-21T18:13:30.834Z)

ruff + mypy clean; API endpoints 38 pass. Now the full engine suite (the owner's pre-merge bar):

597. user (2026-06-21T18:15:12.460Z)

```

obsreport (optional reporting dep): available
=====
.....SS..... [ 5%]
..... [ 11%]
..... [ 16%]
..... [ 22%]
..... [ 27%]
..... [ 33%]
..... [ 38%]
..... [ 44%]
..... [ 49%]
..... [ 55%]
..... [ 60%]
..... [ 66%]
..... [ 71%]
.....SSSSS..... [ 77%]
..... [ 82%]
..... [ 88%]
..... [ 93%]
..... [ 99%]
..... [100%]
1302 passed, 7 skipped in 97.57s (0:01:37)
=====
RESULT: PASS - all tests green
=====
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

```

598. assistant (2026-06-21T18:15:27.637Z)

Full engine suite: **1302 passed, 7 skipped** ? green. ruff + mypy clean, ffmpeg renders kn/hi (visually verified). LW1 is complete. Committing in the worktree:

599. user (2026-06-21T18:15:32.401Z)

```

branch: feat/localized-watermark origin/master: ca34787
warning: in the working copy of 'backend/assets/fonts/README.md', LF will be replaced by CRLF
the next time Git touches it
warning: in the working copy of 'backend/assets/fonts/LICENSE-OFL-1.1.txt', LF will be replaced
by CRLF the next time Git touches it
warning: in the working copy of 'backend/pipeline/stitcher/watermark_i18n.py', LF will be
replaced by CRLF the next time Git touches it
warning: in the working copy of 'tests/test_watermark_i18n.py', LF will be replaced by CRLF the
next time Git touches it
--- staged ---
backend/assets/fonts/LICENSE-OFL-1.1.txt
backend/assets/fonts/NotoSansDevanagari-Variable.ttf
backend/assets/fonts/NotoSansKannada-Variable.ttf
backend/assets/fonts/README.md
backend/main.py
backend/pipeline/stitcher/watermark_i18n.py
tests/test_watermark_i18n.py
--- base (only my work) ---
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

```

600. assistant (2026-06-21T18:15:45.829Z)

`origin/master` advanced to `ca34787` (serving session merging fast) ? my branch is on `4a06b8b`. Let me commit, then rebase onto the new master and check for conflicts:

601. user (2026-06-21T18:15:56.766Z)

```

1f372cf feat(stitch): localize the reel watermark to the UI locale (+ OFL Noto fonts)
=== what did origin/master add since my base? ===
backend/main.py          | 96 ++++++

```

```
tests/test_app_launcher.py | 128 ++++++
2 files changed, 213 insertions(+), 11 deletions(-)
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

602. assistant (2026-06-21T18:16:05.206Z)

`origin/master` also changed `main.py` (+96, an app launcher) ? possible overlap with my `main.py` edits. Rebasing onto the new master:

603. user (2026-06-21T18:16:06.462Z)

Rebasing (1/1)

Successfully rebased and updated refs/heads/feat/localized-watermark.
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

604. assistant (2026-06-21T18:16:23.570Z)

Rebase merged cleanly ? my `localize\_watermark` import + `CompileRequest.locale` + the compile-endpoint change coexist with the serving session's new launcher. Let me re-verify on the rebased base (the new tests included) + ruff/mypy:

605. user (2026-06-21T18:17:02.743Z)

```
..... [ 96%]
... [100%]
75 passed in 33.10s
=== ruff main.py + new module ===
All checks passed!
=== mypy ===
Success: no issues found in 1 source file
=== compile endpoint intact? ===
43:from backend.pipeline.stitcher.watermark_i18n import localize_watermark
749:    localized_watermark = localize_watermark(stitching.watermark, req.locale)
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

606. assistant (2026-06-21T18:17:13.270Z)

Post-rebase: 75 tests pass (incl. the serving session's new launcher tests), ruff + mypy clean, wiring intact. Pushing LW1 + opening the PR:

607. user (2026-06-21T18:17:17.434Z)

```
5132e14 feat(stitch): localize the reel watermark to the UI locale (+ OFL Noto fonts)
--- remote ---
https://github.com/Khelsutra/badminton-highlight-indexer.git
remote:
branch 'feat/localized-watermark' set up to track 'origin/feat/localized-watermark'.
To https://github.com/Khelsutra/badminton-highlight-indexer.git
 * [new branch]      feat/localized-watermark -> feat/localized-watermark
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

608. user (2026-06-21T18:17:38.866Z)

<https://github.com/Khelsutra/badminton-highlight-indexer/pull/304>
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

609. assistant (2026-06-21T18:18:17.912Z)

LW1 PR **[#304](<https://github.com/Khelsutra/badminton-highlight-indexer/pull/304>)** is up. The OFL fonts could trip the engine's **license-scan** CI check (it may only allow MIT/Apache/BSD). Let me check CI status, and build LW2 (SPA passthrough) while it runs.

610. user (2026-06-21T18:18:40.573Z)

```
Golden fixtures cross-OS (windows-latest)      pass    52s
https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977777
Ruff lint          pass    10s    https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977849
Syntax sweep + import smoke (no GPU stack)      pass    20s
https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977825
Built wheel smoke (install + launch)           pending 0      https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977755
Mypy (lenient baseline) pass    31s    https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977808
Full test suite (offline, mocked)              pending 0      https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977761
Dependency license scan (no copyleft in runtime deps) pass    32s
https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977782
Golden fixtures cross-OS (macos-latest) pass    17s    https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977794
Golden fixtures cross-OS (ubuntu-latest)       pass    25s
https://github.com/Khelsutra/badminton-highlight-indexer/actions/runs/27913265375/job/82593977785
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

611. assistant (2026-06-21T18:18:56.826Z)

License-scan passed (it scans dependency licenses, not font media). Most checks green; wheel-smoke + full-suite pending. Let me verify the new fonts are included in the wheel package-data (else the packaged kn/hi watermark would break), then build LW2 while CI finishes:

612. user (2026-06-21T18:18:59.405Z)

```
=== package-data / font inclusion ===
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

613. user (2026-06-21T18:19:08.254Z)

```
=== pyproject build + package config ===
5:# reason), so the wheel target packages are listed EXPLICITLY below ? hatchling's
14:build-backend = "hatchling.build"
88:[tool.hatch.metadata]
93:[tool.hatch.build.targets.wheel]
94:# `backend` is a namespace package (no __init__.py); list both import roots
97:packages = ["backend", "training"]
```

```
=== is RobotoSlab tracked + how (other .ttf already shipped) ===
backend/assets/fonts/LICENSE-Apache-2.0.txt
backend/assets/fonts/LICENSE-OFL-1.1.txt
backend/assets/fonts/NotoSansDevanagari-Variable.ttf
backend/assets/fonts/NotoSansKannada-Variable.ttf
backend/assets/fonts/README.md
backend/assets/fonts/RobotoSlab-Regular.ttf
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

614. assistant (2026-06-21T18:19:26.016Z)

Hatchling packages all files under `backend/` by default (RobotoSlab already ships this way), so the new Noto `\*.ttf` are auto-included in the wheel ? no packaging change needed, and they're tracked. Let me let LW1 CI finish while I build **LW2** (the SPA passthrough). Cutting the khelsutra branch:

615. user (2026-06-21T18:19:26.507Z)

Updated task #11 status

616. user (2026-06-21T18:19:29.795Z)

```
branch 'feat/lw2-locale-passthrough' set up to track 'origin/master'.
Switched to a new branch 'feat/lw2-locale-passthrough'
1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) (#70)
=== current compileReel + processVideo signatures ===
84:export async function processVideo(videoPath: string, cid?: string): Promise<ProcessResponse>
{
108:export async function compileReel(
```

617. assistant (2026-06-21T18:19:46.261Z)

`origin/master` shows **B3 is already done** (#70 ? "trilingual marketing site via shared t()/data-i18n shim", the catalog hoist) ? the concurrent session/owner picked up that chip. Good, one less item. (My LW2 doesn't touch catalogs, so the hoist doesn't affect it.) Let me read the client functions to edit:

618. user (2026-06-21T18:19:47.544Z)

```
80
81      /** Submit a video (a `gs://`/`gcs://`/`s3://` bucket URI, or a path on the engine host)
for
82      * processing. POST /api/process {video_path} ? 202 {job_id,...} [main.py:260]. Fast-
fails 400
83      * (unsupported scheme / out-of-allowed-root) or 404 (missing LOCAL file) ? surfaced as
ApiError. */
84      export async function processVideo(videoPath: string, cid?: string):
Promise<ProcessResponse> {
85          return request<ProcessResponse>("/process", {
86              method: "POST",
87              body: JSON.stringify({ video_path: videoPath }),
88              cid,
89          });
90      }
91
92      /** Poll a submitted job. GET /api/jobs/{job_id} [main.py:303]. 404 ? unknown job_id. */
93      export async function getJob(jobId: string, cid?: string): Promise<JobStatus> {
94          return request<JobStatus>(`/jobs/${encodeURIComponent(jobId)}`, { method: "GET", cid
});
95      }
96
97      /** List a video's detected rallies. POST /api/query {video_id} ? {play_segments}
[main.py:331]. */
98      export async function listRallies(videoId: string, cid?: string):
Promise<RallySegment[]> {
99          const data = await request<QueryResponse>("/query", {
100              method: "POST",
101              body: JSON.stringify({ video_id: videoId }),
102              cid,
103          });
104          return data.play_segments ?? [];
105      }
106
107      /** Stitch selected rallies into one reel. POST /api/compile {video_id, segment_ids,
output_filename} [main.py:342]. */
108      export async function compileReel(
109          videoId: string,
110          segmentIds: number[],
111          outputFilename: string,
112          cid?: string,
113      ): Promise<CompileResponse> {
```

```

114     return request<CompileResponse>("/compile", {
115         method: "POST",
116         body: JSON.stringify({ video_id: videoId, segment_ids: segmentIds, output_filename:
outputFilename }),
117         cid,
118     });
119 }

```

619. assistant (2026-06-21T18:19:57.416Z)

LW2 ? thread locale through the client (optional, so existing callers are unaffected;
`JSON.stringify` drops `undefined`):

620. user (2026-06-21T18:20:01.024Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\client.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

621. user (2026-06-21T18:20:10.965Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\api\client.ts has been updated successfully.
(file state is current in your context ? no need to Read it back)

622. assistant (2026-06-21T18:20:22.714Z)

Now thread locale through the ingest hook and the components. Let me read the current
`useIngestJob.submit` + `IngestPanel` submit calls + `App.onBuild`:

623. user (2026-06-21T18:20:23.573Z)

```

51     const submit = useCallback(
52         (rawUri: string) => {
53             const uri = rawUri.trim();
54             if (!uri) {
55                 setPhase({ status: "error", error: { code: "invalidUri" } });
56                 return;
57             }
58
59             stop(); // supersede any prior run
60             const run: Run = { cancelled: false };
61             runRef.current = run;
62
63             const cid = newCorrelationId();
64             const startedAt = Date.now();
65             setPhase({ status: "submitting" });
66             log("info", "ingest.submit_start", { cid, uri });
67
68             const fail = (error: IngestError, event: string) => {
69                 if (run.cancelled) return;

```

624. user (2026-06-21T18:20:34.562Z)

```

116     void (async () => {
117         let jobId: string;
118         try {
119             const resp = await processVideo(uri, cid);
120             jobId = resp.job_id;
121         } catch (err) {
122             fail(classifyError(err), "ingest.submit_error");
123             return;
124         }
125         if (run.cancelled) return;
126         log("info", "ingest.queued", { cid, uri, job_id: jobId });
127         setPhase({ status: "polling", progress: null });

```

```
128         poll(jobId, POLL_MIN_MS);
129     }());
130 },
131 [stop],
```

625. user (2026-06-21T18:20:43.326Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\hooks\useIngestJob.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

626. user (2026-06-21T18:20:51.836Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\hooks\useIngestJob.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

627. assistant (2026-06-21T18:21:03.093Z)

Now `IngestPanel` ? pass the active locale on both submit paths. Let me read the current relevant lines:

628. user (2026-06-21T18:21:03.903Z)

```
19
20     export function IngestPanel({ onLoad }: Props) {
21         const { t } = useTranslation();
22         const [uri, setUri] = useState("");
23         const { phase, submit, cancel: cancelIngest, reset: resetIngest, busy: ingestBusy } =
useIngestJob(onLoad);
24         // On upload completion, feed the returned server PATH straight into the engine
processing back-half.
25         const upload = useUpload((path) => submit(path));
26         const busy = ingestBusy || upload.busy;
27
28         const onSubmitUri = (e: FormEvent) => {
29             e.preventDefault();
30             submit(uri);
31         };
32         const onFile = (e: ChangeEvent<HTMLInputElement>) => {
33             const file = e.target.files?.[0];
34             if (file) upload.start(file);
35             e.target.value = ""; // let re-picking the same file fire change again
36         };
37         const cancelAll = () => {
38             upload.cancel();
39             cancelIngest();
40         };
41         const resetAll = () => {
42             upload.reset();
43             resetIngest();
44         };
45
46         // Shared mapping with the build flow (lib/errorText): an `engine` failure carries the
engine's own
47         // message (a 400 scheme/path/extension detail, a worker error); every other code maps
to a friendly
48         // localized line. Surface whichever half failed (upload or engine) ? they're mutually
exclusive.
```

629. user (2026-06-21T18:21:18.285Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\IngestPanel.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

630. assistant (2026-06-21T18:21:28.780Z)

Now `App.onBuild` ? pass the locale to `compileReel`:

631. user (2026-06-21T18:21:29.832Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

632. user (2026-06-21T18:21:37.447Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\App.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

633. assistant (2026-06-21T18:21:54.093Z)

Now tests for the passthrough. A client-level test (locale included when present, omitted when absent) + an App-integration check. First the client test:

634. assistant (2026-06-21T18:22:03.100Z)

```
// LW2 ? the SPA records the UI locale on the two engine calls that need it: /api/compile
(localizes
// the reel watermark) and /api/process (PMF analytics). Optional + omitted when absent, so
existing
// callers/back-compat are untouched.
import { describe, it, expect, vi, afterEach } from "vitest";
import { compileReel, processVideo } from "../client";

type FetchFn = typeof fetch;
const ok = (json: unknown): FetchFn =>
  vi.fn(async () => ({ ok: true, status: 200, json: async () => json, text: async () =>
JSON.stringify(json) })) as unknown as FetchFn;
const bodyOf = (f: FetchFn) => {
  const calls = (f as unknown as { mock: { calls: [string, RequestInit][] } }).mock.calls;
  return JSON.parse(calls[calls.length - 1][1].body as string);
};

afterEach(() => {
  vi.restoreAllMocks();
  vi.unstubAllGlobals();
});

describe("LW2 locale passthrough", () => {
  it("compileReel includes the locale when given", async () => {
    const f = ok({ status: "success", filepath: "/o/r.mp4" });
    vi.stubGlobal("fetch", f);
    await compileReel("vid", [1, 2], "r.mp4", "cid", "kn");
    expect(bodyOf(f)).toEqual({ video_id: "vid", segment_ids: [1, 2], output_filename: "r.mp4",
locale: "kn" });
  });

  it("compileReel omits locale when absent (back-compat ? no null/undefined in the body)", async
() => {
    const f = ok({ status: "success", filepath: "/o/r.mp4" });
    vi.stubGlobal("fetch", f);
    await compileReel("vid", [1], "r.mp4");
    expect(bodyOf(f)).toEqual({ video_id: "vid", segment_ids: [1], output_filename: "r.mp4" });
    expect("locale" in bodyOf(f)).toBe(false);
  });

  it("processVideo includes the locale when given, omits it when absent", async () => {
    const f = ok({ job_id: "j", status: "queued", poll: "/api/jobs/j" });
    vi.stubGlobal("fetch", f);
    await processVideo("gs://b/x.mp4", "cid", "hi");
    expect(bodyOf(f)).toEqual({ video_path: "gs://b/x.mp4", locale: "hi" });
  });
});
```

```

    await processVideo("gs://b/y.mp4", "cid");
    expect(bodyOf(f)).toEqual({ video_path: "gs://b/y.mp4" });
  });
});

```

635. user (2026-06-21T18:22:03.127Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra\web\src\api\locale.test.ts (file state is current in your context ? no need to Read it back)

636. assistant (2026-06-21T18:22:40.010Z)

Now an App-integration test proving the active locale reaches `/api/compile`. Let me add it to the existing build-error harness:

637. user (2026-06-21T18:22:41.079Z)

```

73      const u = String(url);
74      const method = init?.method ?? "GET";
75      if (u === "/api/query" && method === "POST") throw new Error("offline"); // engine
down on load
76      if (u === "/api/config") return httpErr(500, "");
77      throw new Error(`unexpected fetch ${method} ${u}`);
78    }) as unknown as typeof fetch);
79    render(<App />);
80    const banner = await screen.findByTestId("mode-banner");
81    await waitFor(() => expect(banner.textContent).toMatch(/can't reach khelsutra/i));
82    expect(banner.textContent).not.toMatch(/ApiError|Network error calling/);
83  });
84  });
85

```

638. user (2026-06-21T18:22:52.862Z)

The file C:\Users\avidu\Projects\khelsutra\web\src\components\build-error.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

639. assistant (2026-06-21T18:23:08.431Z)

Now run the web suite + tsc + build for LW2:

640. user (2026-06-21T18:23:23.812Z)

```

Test Files  20 passed (20)
Tests      177 passed (177)
=== tsc ===
tsc OK
=== build ===
? built in 1.36s

```

641. assistant (2026-06-21T18:23:38.434Z)

177 tests (+4), tsc + build clean. LW2 has no visible UI change (data passthrough, fully test-covered). Committing:

642. user (2026-06-21T18:23:47.935Z)

```

branch: feat/lw2-locale-passthrough
web/src/App.tsx
web/src/api/client.ts
web/src/api/locale.test.ts
web/src/components/IngestPanel.tsx
web/src/components/build-error.test.tsx

```

```
web/src/hooks/useIngestJob.ts
--- base (only my work) ---
67a386c feat(web): LW2 ? send the UI locale to /api/compile (watermark) + /api/process
(analytics)
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/lw2-locale-passthrough -> feat/lw2-locale-passthrough
```

643. user (2026-06-21T18:24:05.668Z)

<https://github.com/avidullu/khelsutra/pull/73>

644. assistant (2026-06-21T18:24:13.434Z)

LW2 PR ****[#73](<https://github.com/avidullu/khelsutra/pull/73>)**** up. Let me check LW1 (#304) CI ? the full-suite + wheel-smoke were pending ? and LW2 CI:

645. user (2026-06-21T18:24:15.826Z)

```
=== LW1 #304 (engine) ===
Built    wheel
Dependency      license
Full      test
Golden  fixtures
Golden  fixtures
Golden  fixtures
Mypy    (lenient
Ruff    lint
Syntax  sweep
```

646. user (2026-06-21T18:24:32.072Z)

```
=== LW1 #304 ===
SUCCESS Ruff lint
SUCCESS Syntax sweep + import smoke (no GPU stack)
SUCCESS Golden fixtures cross-OS (windows-latest)
SUCCESS Built wheel smoke (install + launch)
SUCCESS Mypy (lenient baseline)
SUCCESS Full test suite (offline, mocked)
SUCCESS Golden fixtures cross-OS (ubuntu-latest)
SUCCESS Golden fixtures cross-OS (macos-latest)
SUCCESS Dependency license scan (no copyleft in runtime deps)
```

```
=== LW2 #73 ===
SUCCESS Workers Builds: hidden-king-khelsutra
SUCCESS site
IN_PROGRESS      web
```

647. assistant (2026-06-21T18:24:54.777Z)

****LW1 #304: all 9 engine checks green**** (full suite cross-OS, wheel-smoke, license-scan included). LW2 web check still running. Per "keep merging green CI PRs" and my merge authority, merging LW1 (owner-requested, fully green, backward-compatible):

648. user (2026-06-21T18:24:59.235Z)

Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

649. user (2026-06-21T18:25:08.793Z)

```
state=MERGED merged=2026-06-21T18:24:57Z
--- clean up the worktree (merged) ---
worktree removed
C:/Users/avidu/Projects/badminton-highlight-indexer
6fdd1d4 [serving/exposure-safety-preflight]
```

```
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/agent-a771ff1d85e18f2ed
7e0881a [perf/wasb-fast-frames]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/bhi-execpolicy
5cb7bbf [bhi-execpolicy]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/boxhill17
8736e2d [run/boxhill17-highlights]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/gap-doc
f04f3f3 [docs/rally-gap-closure]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/hardchop
614325d [feat/w1-hard-cap-fallback]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/pr-stitch
a6adcc5 [fix/runner-stitch-watermark]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/recdoc
9fd4215 [docs/recording-single-match]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/resweep
fe34013 [docs/lovo-resweep-n13]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/tier1-windowing
a3b209a [master]
C:/Users/avidu/Projects/badminton-highlight-indexer/.claude/worktrees/w2-safeguard
5ba6955 [feat/w2-never-empty-safeguard]
C:/Users/avidu/Projects/bhi-wt-p2a
ca34787 [feat/packaging-p2a-ffmpeg]
```

650. assistant (2026-06-21T18:25:19.190Z)

LW1 merged (engine PR #304) + worktree cleaned up. Marking it done; checking LW2 CI:

651. user (2026-06-21T18:25:19.700Z)

Updated task #10 status

652. user (2026-06-21T18:25:24.518Z)

```
poll 1: web=SUCCESS
SUCCESS Workers Builds: hidden-king-khelsutra
SUCCESS site
SUCCESS web
```

653. assistant (2026-06-21T18:25:30.320Z)

LW2 all green. Merging:

654. user (2026-06-21T18:25:58.850Z)

```
fatal: unable to access 'https://github.com/avidullu/khelsutra.git/': Failed to connect to
github.com port 443 after 21053 ms: Couldn't connect to server
! warning: not possible to fast-forward to: "master"
c1848df feat(web): LW2 ? send the UI locale to /api/compile (watermark) + /api/process
(analytics) (#73)
```

655. assistant (2026-06-21T18:26:14.689Z)

The merge went through on GitHub, but a transient network blip hit the follow-up `git pull`. Let me retry and verify state:

656. user (2026-06-21T18:26:25.529Z)

```
fetch ok
local master: c1848df origin/master: c1848df
after pull: local master = c1848df
c1848df feat(web): LW2 ? send the UI locale to /api/compile (watermark) + /api/process
(analytics) (#73)
1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-
HOME) (#70)
```

657. assistant (2026-06-21T18:26:44.426Z)

LW2 merged (#73 ? `c1848df`), khelsutra master synced. **LW1 + LW2 done.** Now **LW3** ? the analytics v7 migration, the collision-risk piece. First re-check the engine's current migration head (the serving session may have taken v7):

658. user (2026-06-21T18:26:44.912Z)

Updated task #11 status

659. user (2026-06-21T18:26:49.342Z)

```
engine origin/master: e99d0c3
=== migration head on origin/master ===
155:   def _migrate_to_v1(self, cursor):
183:       cursor.execute("PRAGMA user_version = 1")
185:   def _migrate_to_v2(self, cursor):
210:       cursor.execute("PRAGMA user_version = 2")
212:   def _migrate_to_v3(self, cursor):
222:       cursor.execute("PRAGMA user_version = 3")
224:   def _migrate_to_v4(self, cursor):
242:       cursor.execute("PRAGMA user_version = 4")
244:   def _migrate_to_v5(self, cursor):
290:       cursor.execute("PRAGMA user_version = 5")
292:   def _migrate_to_v6(self, cursor):
337:       cursor.execute("PRAGMA user_version = 6")
```

660. assistant (2026-06-21T18:27:10.302Z)

Migration head is **still v6** on `origin/master` (`e99d0c3`) ? v7 is still free (the serving session hasn't merged theirs). I'll take v7 for `jobs.locale`, in an isolated worktree, and re-verify before merge. Setting up + reading the relevant code:

661. user (2026-06-21T18:27:13.594Z)

```
branch 'feat/locale-analytics' set up to track 'origin/master'.
HEAD is now at e99d0c3 feat(stitch): localize the reel watermark to the UI locale (+ OFL Noto
fonts) (#304)
--- create_job signature + jobs insert ---
64:   def _add_column_idempotent(cursor: sqlite3.Cursor, ddl: str) -> None:
557:   def create_job(self, job_id: str, video_path: str, segmenter: Optional[str] = None,
566:       "INSERT INTO jobs (id, video_path, segmenter, player_pool, max_frames, status,
policy, "
```

662. user (2026-06-21T18:27:25.027Z)

```
86         self._create_base_tables(cursor)
87
88         # Versioned migrations live here. PRAGMA user_version is the schema
89         # contract ? bump it for every change and add an ordered `if version < N`
90         # block below. Tests assert the expected version, so accidental drift fails
91         CI.
92         version = cursor.execute("PRAGMA user_version").fetchone()[0]
93
94         if version < 1:
95             self._migrate_to_v1(cursor)
96
97         if version < 2:
98             self._migrate_to_v2(cursor)
99
100        if version < 3:
101            self._migrate_to_v3(cursor)
102
103        if version < 4:
```



```

103             self._migrate_to_v4(cursor)
104
105         if version < 5:
106             self._migrate_to_v5(cursor)
107
108         if version < 6:
109             self._migrate_to_v6(cursor)
110         # future: if version < 7: cursor.execute("ALTER TABLE ..."); PRAGMA
user_version = 7
111

```

663. user (2026-06-21T18:27:26.131Z)

<tool_use_error>InputValidationError: Read was called with input that could not be parsed as JSON.
You sent (first 130 of 130 bytes): {"file_path": "C:\\Users\\avidu\\Projects\\bhi-loc-analytics\\backend\\infrastructure\\database.py", "offset": 557, , "limit": 28}
Common causes: unescaped backslashes in file paths (use / or \\), unescaped control characters, or truncated output. Retry with valid JSON.</tool_use_error>

664. user (2026-06-21T18:27:33.168Z)

```

557     def create_job(self, job_id: str, video_path: str, segmenter: Optional[str] = None,
558                    player_pool: Optional[List[str]] = None,
559                    max_frames: Optional[int] = None,
560                    policy: Optional[Dict[str, Any]] = None,
561                    owner_id: Optional[str] = None) -> bool:
562         """Insert a new job in state 'queued'. ``policy`` is an optional JSON
ExecutionPolicy
563         (EXECUTION_POLICY.md) the worker honours; None ? the worker's default policy.
``owner_id``
564         (M9, D9) is the verified tenant from edge auth ? NULL for the local single-user
(default)."""
565         return self._execute_write(
566             "INSERT INTO jobs (id, video_path, segmenter, player_pool, max_frames,
status, policy, "
567             "owner_id) VALUES (?, ?, ?, ?, ?, 'queued', ?, ?)",
568             (job_id, video_path, segmenter,
569              json.dumps(player_pool) if player_pool is not None else None,
570              max_frames, json.dumps(policy) if policy is not None else None, owner_id),
571             f"Failed to create job {job_id}",
572         )
573
574     def mark_job_running(self, job_id: str) -> bool:
575         return self._execute_write(
576             "UPDATE jobs SET status='running', started_at=CURRENT_TIMESTAMP, "
577             "progress='starting' WHERE id = ?", (job_id,),
578             f"Failed to mark job {job_id} running",
579         )
580
581     def set_job_progress(self, job_id: str, progress: str) -> bool:
582         return self._execute_write(
583             "UPDATE jobs SET progress=? WHERE id = ?", (progress, job_id),
584             f"Failed to set progress for job {job_id}",
585         )
586

```

665. user (2026-06-21T18:27:43.976Z)

```

64     def _add_column_idempotent(cursor: sqlite3.Cursor, ddl: str) -> None:
65         """Apply a bare ``ALTER TABLE ... ADD COLUMN`` migration step re-runably.
66
67         A DDL ``ALTER`` auto-commits independently of the surrounding ``with conn``
68         transaction, so an interrupted v3/v4 block can leave the column added while

```

```

69         ``user_version`` stays un-bumped ? and the next open would re-run the same
70         ``ALTER`` and raise ``OperationalError: duplicate column name``, bricking every
71         future ``Database(...)`` construction (``_init_db`` runs in ``__init__``).
Swallow
72         ONLY that specific error so the ladder stays crash-safe, matching the re-
runnable
73         ``CREATE ... IF NOT EXISTS`` v1/v2/v5 blocks.
74         ""
75         try:
76             cursor.execute(ddl)
77         except sqlite3.OperationalError as exc:
78             if "duplicate column name" not in str(exc).lower():
79                 raise
80
81     def _init_db(self):
82         """Initializes tables for videos, play_segments, and events."""
83         with self._connect() as conn:
84             cursor = conn.cursor()
85

```

666. user (2026-06-21T18:27:44.788Z)

```

292     def _migrate_to_v6(self, cursor):
293         # v6: per-job COST LEDGER (COMPUTE_DECOUPLED_SERVING M8, D8). NULLABLE cost
columns on
294         # `jobs` (NULL = no cost recorded = byte-identical to today; nothing records
until
295         # billing.enabled + a real pricebook) + a VERSIONED `pricebook` table. Cost is
stored in
296         # USD (matches GCP billing = one source of truth); INR is a display conversion
at a
297         # configurable FX rate. ALTER (not recreate) so v1-v5 job rows survive; ADD
COLUMNS are
298         # idempotent so an interrupted upgrade can re-run them. Additive ONLY ? no
served change.
299         for col, typ in (
300             ("owner_id", "TEXT"),           # who pays (the non-owner user / tenant)
301             ("compute_backend", "TEXT"),    # local_gpu | cloud_run | ...
302             ("gpu_type", "TEXT"),           # L4 | T4 | ... (selects the per-second
GPU rate)
303             ("gpu_active_seconds", "REAL"),
304             ("wall_seconds", "REAL"),
305             ("bytes_out", "INTEGER"),       # egress
306             ("gemini_cost_usd", "REAL"),    # provider-reported, already USD
307             ("pricebook_version", "TEXT"),
308             ("cost_usd", "REAL"),           # computed total (USD = source of truth)
309             ("cost_breakdown_json", "TEXT"), # {gpu_seconds: .., egress_gb: ..,
gemini_usd: ..}
310         ):
311             self._add_column_idempotent(cursor, f"ALTER TABLE jobs ADD COLUMN {col}
{typ}")
312             # Partial index keeps the NULL=no-cost fast path churn-free while making per-
owner billing cheap.
313             cursor.execute("CREATE INDEX IF NOT EXISTS idx_jobs_owner ON jobs(owner_id) "
314                             "WHERE owner_id IS NOT NULL")
315             # Versioned pricebook: one row per (version, resource, gpu_type). Rates change +
differ by
316             # gpu_type ? re-version (never mutate a shipped version, so a recorded cost
stays auditable).
317             cursor.execute("""
318                 CREATE TABLE IF NOT EXISTS pricebook (
319                     version TEXT NOT NULL,
320                     resource TEXT NOT NULL,
321                     gpu_type TEXT NOT NULL DEFAULT '',
322                     unit_price_usd REAL NOT NULL DEFAULT 0.0,

```

```

323             currency TEXT NOT NULL DEFAULT 'USD',
324             effective_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
325         )
326     """)
327     cursor.execute("CREATE UNIQUE INDEX IF NOT EXISTS idx_pricebook_key "
328                   "ON pricebook(version, resource, gpu_type)")
329     # Seed a PLACEHOLDER version with every rate 0.0 ? cost_usd computes to 0
330     (nothing
331     # user-facing changes). The owner INSERTs a real, calibrated version (real GCP
332     $/GPU-s,
333     # egress $/GB) and flips billing.pricebook_version to it ? never overwrite this
334     seed.
335     for resource, gpu_type in (("gpu_seconds", "L4"), ("gpu_seconds", "T4"),
336                               ("wall_seconds", ""), ("egress_gb", "")):
337         cursor.execute(
338             "INSERT OR IGNORE INTO pricebook (version, resource, gpu_type,
339             unit_price_usd, "
340             "currency) VALUES ('placeholder-v0', ?, ?, 0.0, 'USD')", (resource,
341             gpu_type))
342     cursor.execute("PRAGMA user_version = 6")

```

667. assistant (2026-06-21T18:28:02.831Z)

Migration pattern is clear. Let me find where `/api/process` calls `create\_job` and the test that pins the schema version:

668. user (2026-06-21T18:28:03.829Z)

```

=== create_job caller in main.py ===
595:     if not db_instance.create_job(job_id, req.video_path, req.segmenter,
=== schema-version assertions in tests ===
tests/test_async_jobs.py:10:- migration: fresh DB lands at user_version 2 with a jobs table; v1
DBs upgrade in place
tests/test_async_jobs.py:83:         assert conn.execute("PRAGMA user_version").fetchone()[0] ==
6
tests/test_async_jobs.py:101:     conn.execute("PRAGMA user_version = 1")
tests/test_async_jobs.py:107:         assert c.execute("PRAGMA user_version").fetchone()[0] == 6
tests/test_billing.py:39:         ver = conn.execute("PRAGMA user_version").fetchone()[0]
tests/test_billing.py:50:     """"Re-opening the DB re-runs the ladder guard (version already 6 ?
no-op, no duplicate seed).""""
tests/test_database.py:86:     version = conn.execute("PRAGMA user_version").fetchone()[0]
tests/test_database.py:89:     assert version == 6
tests/test_database.py:108:     version = conn.execute("PRAGMA user_version").fetchone()[0]
tests/test_database.py:114:     assert version == 6          # v6 = per-job cost ledger
(COMPUTE_DECOUPLED_SERVING M8)
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

```

669. assistant (2026-06-21T18:28:19.528Z)

The schema-version is pinned to `== 6` in `test\_async\_jobs.py` + `test\_database.py` (the intentional-drift guard) ? I'll bump those to 7. Now building LW3. Marking in-progress and adding the v7 migration:

670. user (2026-06-21T18:28:20.058Z)

Updated task #12 status

671. user (2026-06-21T18:28:22.628Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\backend\infrastructure\database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

672. assistant (2026-06-21T18:28:29.362Z)

Now add the `\_migrate\_to\_v7` method after `\_migrate\_to\_v6`:

673. user (2026-06-21T18:28:33.959Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\backend\infrastructure\database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

674. assistant (2026-06-21T18:28:39.294Z)

Now add `locale` to `create\_job` + a `count\_jobs\_by\_locale` analytics helper:

675. user (2026-06-21T18:28:49.942Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\backend\infrastructure\database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

676. assistant (2026-06-21T18:28:56.563Z)

Now `ProcessRequest.locale` + pass it to `create\_job` in the worktree's main.py:

677. user (2026-06-21T18:28:57.219Z)

```
592         )
593
594         job_id = uuid.uuid4().hex
595         if not db_instance.create_job(job_id, req.video_path, req.segmenter,
596                                     req.player_pool, req.max_frames, owner_id=owner_id):
597             raise HTTPException(status_code=500, detail="Failed to persist job record.")
598         _get_executor().submit(_drain_due_jobs)
599         return JSONResponse(
```

678. user (2026-06-21T18:29:06.873Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\backend\main.py has been updated successfully. (file state is current in your context ? no need to Read it back)

679. user (2026-06-21T18:29:16.101Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\backend\main.py has been updated successfully. (file state is current in your context ? no need to Read it back)

680. assistant (2026-06-21T18:29:25.097Z)

Now fix the schema-version assertions (the intentional-drift guard). Let me find every one:

681. user (2026-06-21T18:29:27.534Z)

```
tests/test_async_jobs.py:83:         assert conn.execute("PRAGMA user_version").fetchone()[0] ==
6
tests/test_async_jobs.py:107:        assert c.execute("PRAGMA user_version").fetchone()[0] == 6
tests/test_database.py:237:        assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
tests/test_database.py:275:        assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
tests/test_job_worker_loop.py:275:        assert conn.execute("PRAGMA
user_version").fetchone()[0] == 6
tests/test_job_worker_loop.py:292:        assert c.execute("PRAGMA user_version").fetchone()[0]
== 6
--- billing line 39 context ---
def test_v6_migration_adds_cost_columns_and_seeds_placeholder(tmp_path):
    db = Database(str(tmp_path / "m.db"))
    with db._connect() as conn:
        ver = conn.execute("PRAGMA user_version").fetchone()[0]
        cols = {r[1] for r in conn.execute("PRAGMA table_info(jobs)").fetchall()}
        seeded = conn.execute(
```

```

        "SELECT unit_price_usd FROM pricebook WHERE version='placeholder-v0']").fetchall()
assert ver >= 6
assert {"cost_usd", "gpu_active_seconds", "wall_seconds", "bytes_out", "owner_id",
        "pricebook_version", "cost_breakdown_json", "compute_backend", "gpu_type"} <= cols
assert len(seeded) >= 4 and all(r[0] == 0.0 for r in seeded) # placeholder = every rate $0

def test_v6_migration_is_idempotent(tmp_path):
    """Re-opening the DB re-runs the ladder guard (version already 6 ? no-op, no duplicate
seed)."""
    path = str(tmp_path / "m.db")
    Database(path)
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

```

682. assistant (2026-06-21T18:29:51.949Z)

`test\_billing.py` uses `>= 6` (stays valid). Six `== 6` assertions across 3 files need bumping. Let me read their context (to fix any adjacent "v6 = ..." comments too):

683. user (2026-06-21T18:29:54.204Z)

```

===== tests/test_async_jobs.py =====
10:- migration: fresh DB lands at user_version 2 with a jobs table; v1 DBs upgrade in place
79: def test_migration_fresh_db_is_v3_with_jobs_table(tmp_path):
80:     db = Database(str(tmp_path / "fresh.db"))
82:     # v6 = per-job cost ledger (M8); the jobs table arrived at v2/v3, user_models at v5.
83:     assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
107:     assert c.execute("PRAGMA user_version").fetchone()[0] == 6
===== tests/test_database.py =====
88:     # v6 = per-job cost ledger (COMPUTE_DECOUPLED_SERVING M8). Bump with each migration.
113:     assert "pricebook" in tables # v6 (per-job cost ledger, M8)
114:     assert version == 6 # v6 = per-job cost ledger (COMPUTE_DECOUPLED_SERVING M8)
213: def test_migration_v3_db_upgrades_to_v6_preserving_rows(tmp_path):
214:     """A real v3 DB (jobs + candidates already populated) upgrades cleanly to v6: the new
217:     db = Database(str(db_path)) # fresh DB is born at the current version; simulate a v3
state
234:     # Re-open: the migration ladder must carry the v3 DB up to v6 without data loss.
237:     assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
241:     assert "pricebook" in tables # v6 (cost ledger)
244:     assert "cost_usd" in _table_cols(db_path, "jobs") # v6 cost columns back-filled (NULL)
===== tests/test_job_worker_loop.py =====
261:     db = Database(str(tmp_path / "fresh.db"))
271: def test_fresh_db_is_v6(tmp_path):
275:     assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
280:     # migration ladder up to the current head (v6) without error ? this exercises the v0?v6
292:     assert c.execute("PRAGMA user_version").fetchone()[0] == 6
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

```

684. assistant (2026-06-21T18:30:25.370Z)

Six `== 6` assertions (+ one `assert version == 6` in test_database.py:114) plus some "v6 = head" comments/names. Let me read all three test sections to bump them accurately:

685. user (2026-06-21T18:30:26.753Z)

```

79     def test_migration_fresh_db_is_v3_with_jobs_table(tmp_path):
80         db = Database(str(tmp_path / "fresh.db"))
81         with db._get_connection() as conn:
82             # v6 = per-job cost ledger (M8); the jobs table arrived at v2/v3, user_models at
v5.
83             assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
84             cols = {r["name"] for r in conn.execute("PRAGMA table_info(jobs)").fetchall()}
85             assert {"id", "video_path", "video_id", "status", "progress", "error", "result"} <=
cols

```

```

86         assert {"policy", "next_poll_at"} <= cols          # v3 self-scheduling columns
87
88
89     def test_migration_upgrades_v1_db_in_place(tmp_path):
90         path = str(tmp_path / "v1.db")
91         conn = sqlite3.connect(path)
92         conn.execute(
93             "CREATE TABLE videos (id TEXT PRIMARY KEY, filepath TEXT NOT NULL, "
94             "processed_at TIMESTAMP, status TEXT NOT NULL, validation_results TEXT)")
95         # A genuine v1 DB also has candidate_segments (created in the version<1 block);
include it
96         # so the v4 personalization ALTER (which adds user_id to that table) has a table to
alter.
97         conn.execute(
98             "CREATE TABLE candidate_segments (id INTEGER PRIMARY KEY AUTOINCREMENT, "
99             "video_id TEXT NOT NULL, detector TEXT NOT NULL, start_time REAL NOT NULL, "
100             "end_time REAL NOT NULL, duration REAL NOT NULL, stats TEXT)")
101         conn.execute("PRAGMA user_version = 1")
102         conn.commit()
103         conn.close()
104
105         db = Database(path) # ladder should take it 1 ? 6
106         with db._get_connection() as c:
107             assert c.execute("PRAGMA user_version").fetchone()[0] == 6
108             assert c.execute(

```

686. user (2026-06-21T18:30:27.390Z)

```

84         Database(str(db_path))
85         conn = sqlite3.connect(str(db_path))
86         version = conn.execute("PRAGMA user_version").fetchone()[0]
87         conn.close()
88         # v6 = per-job cost ledger (COMPUTE_DECOUPLED_SERVING M8). Bump with each migration.
89         assert version == 6
90
91
92     def test_init_db_idempotent_and_upgrades_old_db(tmp_path):
93         db_path = tmp_path / "legacy.db"
94         # Simulate a pre-v1 database that only has the old tables and no version.
95         conn = sqlite3.connect(str(db_path))
96         conn.execute("CREATE TABLE videos (id TEXT PRIMARY KEY, filepath TEXT, status
TEXT)")
97         conn.commit()
98         conn.close()
99
100         # Opening with the new Database should add candidate_segments without error...
101         Database(str(db_path))
102         # ...and running init again must be a no-op (idempotent).
103         Database(str(db_path))
104
105         conn = sqlite3.connect(str(db_path))
106         tables = [r[0] for r in conn.execute(
107             "SELECT name FROM sqlite_master WHERE type='table'").fetchall()]
108         version = conn.execute("PRAGMA user_version").fetchone()[0]
109         conn.close()
110         assert "candidate_segments" in tables
111         assert "jobs" in tables # v2 (async job model, #16)
112         assert "user_models" in tables # v5 (per-user model store)
113         assert "pricebook" in tables # v6 (per-job cost ledger, M8)
114         assert version == 6 # v6 = per-job cost ledger (COMPUTE_DECOUPLED_SERVING M8)
115

```

687. assistant (2026-06-21T18:30:42.423Z)

Now bump the assertions (+ note v7 in the comments). test_async_jobs.py:

688. user (2026-06-21T18:30:44.950Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_async_jobs.py has been updated successfully. (file state is current in your context ? no need to Read it back)

689. user (2026-06-21T18:30:54.147Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_async_jobs.py has been updated successfully. (file state is current in your context ? no need to Read it back)

690. user (2026-06-21T18:31:01.391Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

691. user (2026-06-21T18:31:08.820Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

692. assistant (2026-06-21T18:31:17.865Z)

Now the v3-upgrade test + the worker-loop test. Reading their context:

693. user (2026-06-21T18:31:18.824Z)

```
210         assert len(db.query_candidate_segments("vid1")) == 1
211
212
213     def test_migration_v3_db_upgrades_to_v6_preserving_rows(tmp_path):
214         """A real v3 DB (jobs + candidates already populated) upgrades cleanly to v6: the
new
215         columns/tables appear, user_id back-fills to NULL, and prior rows survive the
ALTERs."""
216         db_path = tmp_path / "legacy_v3.db"
217         db = Database(str(db_path)) # fresh DB is born at the current version; simulate a
v3 state
218         # Seed pre-upgrade data, then force the version back to 3 and re-open to run v4+v5.
219         db.add_video("vidA", "a.mp4", "processed", [{"v": 1}])
220         db.add_candidate_segment("vidA", "wasb_hybrid", 2.0, 9.0, stats={"net_crossings":
3})
221         conn = sqlite3.connect(str(db_path))
222         conn.execute("DROP INDEX IF EXISTS idx_videos_user")
223         conn.execute("DROP INDEX IF EXISTS idx_candidates_user")
224         conn.execute("DROP TABLE IF EXISTS user_models")
225         # Recreate v3-shaped tables WITHOUT user_id by rebuilding (simplest: just rewind
version
226         # and drop the v4/v5 artifacts that a true v3 DB wouldn't have).
227         conn.execute("ALTER TABLE videos DROP COLUMN user_id")
228         conn.execute("ALTER TABLE candidate_segments DROP COLUMN user_id")
229         conn.execute("PRAGMA user_version = 3")
230         conn.commit()
231         conn.close()
232         assert "user_id" not in _table_cols(db_path, "videos")
233
234         # Re-open: the migration ladder must carry the v3 DB up to v6 without data loss.
235         db2 = Database(str(db_path))
236         conn = sqlite3.connect(str(db_path))
237         assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
238         tables = {r[0] for r in conn.execute(
239             "SELECT name FROM sqlite_master WHERE type='table'").fetchall()}
240         assert "user_models" in tables # v5
241         assert "pricebook" in tables # v6 (cost ledger)
242         conn.close()
```

```
243         assert "user_id" in _table_cols(db_path, "videos")
244         assert "cost_usd" in _table_cols(db_path, "jobs") # v6 cost columns back-filled
(NULL)
245         assert "user_id" in _table_cols(db_path, "candidate_segments")
```

694. user (2026-06-21T18:31:19.572Z)

```
271     def test_fresh_db_is_v6(tmp_path):
272         db = Database(str(tmp_path / "v.db"))
273         with db._get_connection() as conn:
274             # Head of the migration ladder (bump when database.py adds a new `if version <
N`).
275             assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
276
277
278     def test_legacy_db_upgrades_to_head(tmp_path):
279         # A pre-migration legacy DB (only `videos`, user_version 0) must run the FULL
ordered
280         # migration ladder up to the current head (v6) without error ? this exercises the
v0?v6
281         # path including the v1 `candidate_segments` CREATE that the later v4 ALTER depends
on.
282         path = str(tmp_path / "legacy.db")
283         conn = sqlite3.connect(path)
284         conn.execute(
285             "CREATE TABLE videos (id TEXT PRIMARY KEY, filepath TEXT NOT NULL, "
286             "processed_at TIMESTAMP, status TEXT NOT NULL, validation_results TEXT)")
287         conn.execute("PRAGMA user_version = 0")
288         conn.commit()
289         conn.close()
290         db = Database(path)
291         with db._get_connection() as c:
292             assert c.execute("PRAGMA user_version").fetchone()[0] == 6
293
```

695. user (2026-06-21T18:31:44.374Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

696. user (2026-06-21T18:31:54.698Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

697. user (2026-06-21T18:32:04.554Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_job_worker_loop.py has been updated successfully. (file state is current in your context ? no need to Read it back)

698. user (2026-06-21T18:32:13.258Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_job_worker_loop.py has been updated successfully. (file state is current in your context ? no need to Read it back)

699. user (2026-06-21T18:32:20.708Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_job_worker_loop.py has been updated successfully. (file state is current in your context ? no need to Read it back)

700. assistant (2026-06-21T18:32:42.207Z)

Now the dedicated LW3 test. Let me check the existing `/api/process` test harness to mirror the API-level assertion:

701. user (2026-06-21T18:32:43.626Z)

```
1: """TestClient coverage for the FastAPI seam (previously zero ? the compiler SyntaxError
10: pytest.importorskip("httpx") # TestClient needs httpx; skip cleanly where absent
11: from fastapi.testclient import TestClient
31: monkeypatch.setattr(m, "db_instance", db)
34: client = TestClient(m.app)
155: def test_process_success_with_mocked_segmenter(env):
161:     r = client.post("/api/process", json={"video_path": str(vid_file), "segmenter": "x"})
169: def test_process_validation_failure_preserves_prior_segments(env):
176:     r = client.post("/api/process", json={"video_path": str(vid_file)})
185: def test_process_rejects_null_byte_path(env):
187:     r = client.post("/api/process", json={"video_path": "a\x00b.mp4"})
195: def test_process_uses_configured_output_dir_not_literal_output(env, tmp_path, monkeypatch):
218:     r = client.post("/api/process", json={"video_path": str(vid_file)})
250:     r = client.post("/api/process", json={"video_path": str(vid_file)})
262:     r2 = client.post("/api/process", json={"video_path": str(vid_file)})
275:     r = client.post("/api/query", json={"video_id": "vid"})
284:     r = client.post("/api/compile", json={
302:     r = client.post("/api/compile", json={
338:     r = client.post("/api/compile", json={
380:     r = client.post("/api/compile", json={
393:     r = client.post("/api/compile", json={
425:         r = client.post("/api/compile", json={
447:     rj = client.post("/api/process", json={"video_path": str(vid_file), "segmenter": "x"})
450:     rd = client.post("/api/process", json={"video_path": str(vid_file), "segmenter": "x"})
457:     rf = client.post("/api/process", json={"video_path": str(vid_file)})
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

702. user (2026-06-21T18:32:54.917Z)

```
20     """submit() runs the fn synchronously ? async jobs complete before the response
21     is inspected (full lifecycle coverage lives in test_async_jobs.py)."""
22
23     def submit(self, fn, *args, **kwargs):
24         fn(*args, **kwargs)
25
26
27     @pytest.fixture
28     def env(tmp_path, monkeypatch):
29         db = Database(str(tmp_path / "t.db"))
30         cfg = AppConfig()
31         monkeypatch.setattr(m, "db_instance", db)
32         monkeypatch.setattr(m, "global_config", cfg)
33         monkeypatch.setattr(m, "_get_executor", lambda: _InlineExecutor())
34         client = TestClient(m.app)
35         return client, db, tmp_path, monkeypatch
36
37
38     def _video(tmp_path, name="m.mp4"):
39         p = tmp_path / name
```

703. user (2026-06-21T18:32:55.426Z)

```
155     def test_process_success_with_mocked_segmenter(env):
156         """#16: submit returns 202 + job_id; the (inline) job carries the old response."""
157         client, db, tmp_path, mp = env
158         vid_file = _video(tmp_path)
159         mp.setattr(m.registry, "run_all_with_context", lambda *a, **k: (_pass(), {}))
160         mp.setattr(m.segmenter_registry, "get", lambda name: _FakeSeg)
161         r = client.post("/api/process", json={"video_path": str(vid_file), "segmenter":
"x"})
162         assert r.status_code == 202
163         job = client.get(f"/api/jobs/{r.json()['job_id']}").json()
164         assert job["status"] == "done"
```

```

165         assert job["result"]["status"] == "success"
166         assert len(job["result"]["play_segments"]) == 1
167
168

```

704. assistant (2026-06-21T18:33:20.450Z)

Now write the LW3 tests ? DB migration + create_job + analytics, plus an API-level check in the existing harness:

705. assistant (2026-06-21T18:33:33.549Z)

""v7 ? job UI-locale capture + PMF analytics (which language markets use the tool).

Covers: the v7 migration (fresh DB + a v6?v7 in-place upgrade that back-fills locale=NULL on prior rows), create_job storing the locale (NULL when absent), count_jobs_by_locale aggregation (incl. the '(unset)' bucket for NULL), and the ProcessRequest.locale field. The /api/process end-to-end capture lives in test_api_endpoints.py.

```

import sqlite3

from backend.infrastructure.database import Database
from backend.main import ProcessRequest

def _cols(path, table):
    conn = sqlite3.connect(path)
    try:
        return [r[1] for r in conn.execute(f"PRAGMA table_info({table})").fetchall()]
    finally:
        conn.close()

def _user_version(path):
    conn = sqlite3.connect(path)
    try:
        return conn.execute("PRAGMA user_version").fetchone()[0]
    finally:
        conn.close()

def test_fresh_db_v7_has_jobs_locale_column(tmp_path):
    path = str(tmp_path / "fresh.db")
    db = Database(path)
    assert _user_version(path) == 7
    assert "locale" in _cols(path, "jobs")

def test_v6_db_upgrades_to_v7_and_backfills_locale_null(tmp_path):
    path = str(tmp_path / "v6.db")
    db = Database(path) # born at v7
    db.create_job("j-old", "/v.mp4") # a prior row, no locale
    # Simulate a real v6 jobs table (no locale column, version pinned at 6).
    conn = sqlite3.connect(path)
    conn.execute("ALTER TABLE jobs DROP COLUMN locale")
    conn.execute("PRAGMA user_version = 6")
    conn.commit()
    conn.close()
    assert "locale" not in _cols(path, "jobs")

    Database(path) # re-open ? the ladder runs _migrate_to_v7
    assert _user_version(path) == 7

```

```

    assert "locale" in _cols(path, "jobs")
    # The prior row survived the ALTER and back-filled to NULL (not dropped, not defaulted to a
value).
    conn = sqlite3.connect(path)
    try:
        assert conn.execute("SELECT locale FROM jobs WHERE id='j-old']").fetchone()[0] is None
    finally:
        conn.close()

def test_create_job_stores_locale_and_defaults_null(tmp_path):
    db = Database(str(tmp_path / "j.db"))
    db.create_job("j-kn", "/a.mp4", locale="kn")
    db.create_job("j-none", "/b.mp4") # no locale ? NULL
    conn = sqlite3.connect(str(tmp_path / "j.db"))
    try:
        assert conn.execute("SELECT locale FROM jobs WHERE id='j-kn']").fetchone()[0] == "kn"
        assert conn.execute("SELECT locale FROM jobs WHERE id='j-none']").fetchone()[0] is None
    finally:
        conn.close()

def test_count_jobs_by_locale_aggregates_with_unset_bucket(tmp_path):
    db = Database(str(tmp_path / "c.db"))
    for jid, loc in [("a", "kn"), ("b", "kn"), ("c", "hi"), ("d", None), ("e", "es")]:
        db.create_job(jid, "/v.mp4", locale=loc)
    counts = db.count_jobs_by_locale()
    assert counts == {"kn": 2, "hi": 1, "es": 1, "(unset)": 1}
    # Busiest-first ordering (a dict preserves insertion order in py3.7+).
    assert list(counts.keys())[0] == "kn"

def test_process_request_accepts_optional_locale():
    assert ProcessRequest(video_path="x", locale="hi-IN").locale == "hi-IN"
    assert ProcessRequest(video_path="x").locale is None

```

706. user (2026-06-21T18:33:33.565Z)

File created successfully at: C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_locale_analytics.py (file state is current in your context ? no need to Read it back)

707. assistant (2026-06-21T18:33:41.578Z)

Now add the API-level capture test to the existing harness:

708. user (2026-06-21T18:33:45.733Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_api_endpoints.py has been updated successfully. (file state is current in your context ? no need to Read it back)

709. assistant (2026-06-21T18:33:53.567Z)

Now run the engine gate for LW3 ? the new test + all the migration/version tests + ruff/mypy:

710. user (2026-06-21T18:34:18.676Z)

```

    # Re-opening re-runs v3 (jobs.policy/next_poll_at), v4
(videos/candidate_segments.user_id),
    # v5 (user_models), and v6 (jobs cost columns + pricebook) over artifacts that ALREADY
exist ?
    # must NOT raise (re-runnable ALTERs / INSERT OR IGNORE), and must reach v6.
    Database(str(db_path))
    conn = sqlite3.connect(str(db_path))

```

```
>         assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
E         assert 7 == 6
```

```
tests\test_database.py:275: AssertionError
===== short test summary info =====
FAILED tests\test_database.py::test_migration_idempotent_on_interrupted_upgrade
1 failed, 114 passed in 18.93s
=== ruff ===
All checks passed!
=== mypy ===
Success: no issues found in 1 source file
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

711. assistant (2026-06-21T18:34:29.082Z)

One more `== 6` I missed (test_database.py:275, a different test). ruff + mypy clean. Let me fix it:

712. user (2026-06-21T18:34:30.377Z)

```
266         conn.execute("PRAGMA user_version = 2")
267         conn.commit()
268         conn.close()
269
270         # Re-opening re-runs v3 (jobs.policy/next_poll_at), v4
(videos/candidate_segments.user_id),
271         # v5 (user_models), and v6 (jobs cost columns + pricebook) over artifacts that
ALREADY exist ?
272         # must NOT raise (re-runnable ALTERs / INSERT OR IGNORE), and must reach v6.
273         Database(str(db_path))
274         conn = sqlite3.connect(str(db_path))
275         assert conn.execute("PRAGMA user_version").fetchone()[0] == 6
276         conn.close()
277         # Columns/tables are all present after the clean re-apply.
```

713. user (2026-06-21T18:34:40.049Z)

The file C:\Users\avidu\Projects\bhi-loc-analytics\tests\test_database.py has been updated successfully. (file state is current in your context ? no need to Read it back)

714. assistant (2026-06-21T18:34:48.505Z)

Now run the full engine suite to confirm everything green (catches any other version reference):

715. user (2026-06-21T18:36:50.137Z)

```
..... [ 87%]
..... [ 92%]
..... [ 98%]
..... [100%]
1315 passed, 7 skipped in 116.72s (0:01:56)
=====
RESULT: PASS - all tests green
=====
```

716. assistant (2026-06-21T18:37:01.328Z)

Full suite: **1315 passed, 7 skipped**, ruff + mypy clean. Before committing, re-verify `origin/master` hasn't gained a competing v7 (the serving session is active) ? renumber to v8 if so:

717. user (2026-06-21T18:37:05.455Z)

origin/master: fa7ee3f my base: e99d0c3

```
=== competing v7 on origin/master? ===
110:      # future: if version < 7: cursor.execute("ALTER TABLE ..."); PRAGMA user_version
= 7
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

718. assistant (2026-06-21T18:37:15.232Z)

`origin/master` advanced to `fa7ee3f` but ****still no v7**** (only the comment I'm replacing) ? v7 is mine to take. Committing LW3, then rebasing onto the new master:

719. user (2026-06-21T18:37:24.103Z)

```
branch: feat/locale-analytics
warning: in the working copy of 'tests/test_locale_analytics.py', LF will be replaced by CRLF
the next time Git touches it
backend/infrastructure/database.py
backend/main.py
tests/test_api_endpoints.py
tests/test_async_jobs.py
tests/test_database.py
tests/test_job_worker_loop.py
tests/test_locale_analytics.py
committed: e8ce25a feat(db): v7 ? record the UI locale per job (PMF analytics) +
count_jobs_by_locale
=== rebase onto origin/master ===
Rebasing (1/1)
```

Successfully rebased and updated refs/heads/feat/locale-analytics.
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

720. assistant (2026-06-21T18:37:35.857Z)

Rebased cleanly (the new master added a P2a ffmpeg-resolver import; my changes merged alongside). Re-verifying on the rebased base:

721. user (2026-06-21T18:38:02.721Z)

```
=== wiring intact ===
backend/main.py:264:      # analytics (count_jobs_by_locale). Optional ? NULL when unrecorded (CLI
/ older clients).
backend/main.py:265:      locale: Optional[str] = None
backend/main.py:280:      locale: Optional[str] = None
backend/main.py:601:                                     locale=req.locale):
backend/infrastructure/database.py:342:      def _migrate_to_v7(self, cursor):
backend/infrastructure/database.py:346:          # count_jobs_by_locale) and pairs with the
localized reel watermark (the SPA sends the same
backend/infrastructure/database.py:574:                                     locale: Optional[str] = None) -> bool:
backend/infrastructure/database.py:588:      def count_jobs_by_locale(self) -> Dict[str, int]:
=== targeted re-run ===
..... [ 62%]
..... [100%]
115 passed in 19.20s
=== ruff + mypy ===
All checks passed!
Success: no issues found in 1 source file
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer
```

722. assistant (2026-06-21T18:38:14.447Z)

All green post-rebase: 115 targeted tests, ruff + mypy clean, wiring intact
(`ProcessRequest.locale` + `\_migrate\_to\_v7` + `count\_jobs\_by\_locale`; the
`CompileRequest.locale` from the merged LW1 also present). Pushing + PR:

723. user (2026-06-21T18:38:17.907Z)

b6245ec feat(db): v7 ? record the UI locale per job (PMF analytics) + count_jobs_by_locale
branch 'feat/locale-analytics' set up to track 'origin/feat/locale-analytics'.
To <https://github.com/Khelsutra/badminton-highlight-indexer.git>
* [new branch] feat/locale-analytics -> feat/locale-analytics
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

724. user (2026-06-21T18:38:38.481Z)

<https://github.com/Khelsutra/badminton-highlight-indexer/pull/306>
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

725. assistant (2026-06-21T18:38:47.485Z)

LW3 PR ****[#306](<https://github.com/Khelsutra/badminton-highlight-indexer/pull/306>)**** up. Polling its CI:

726. user (2026-06-21T18:40:53.115Z)

Command running in background with ID: bc92pnhue. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-badminton-highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\tasks\bc92pnhue.output. You will be notified when it completes. To check interim output, use Read on that file path.

727. assistant (2026-06-21T18:41:23.871Z)

While LW3's engine CI runs (background), let me give a status ? the feature is essentially built and the first two PRs are already merged.

Locale capture + localized watermarks ? status

****Shipped end-to-end across 3 PRs (2 merged, 1 in CI):****

```
| PR | What | State |
|----|-----|-----|
| engine [#304](https://github.com/Khelsutra/badminton-highlight-indexer/pull/304) **LW1** | Localized reel **watermark** ? `localize_watermark(cfg, locale)` overrides text + font per locale; bundled **Noto Sans Kannada + Devanagari (OFL)**; `/api/compile` localizes it. Verified ffmpeg renders kn/hi (no tofu). | ? **merged** (1302 suite green) |
| khelsutra [#73](https://github.com/avidullu/khelsutra/pull/73) **LW2** | SPA sends `i18n.resolvedLanguage` to `/api/compile` (watermark) + `/api/process` (analytics). | ? **merged** (177 web tests) |
| engine [#306](https://github.com/Khelsutra/badminton-highlight-indexer/pull/306) **LW3** | **v7 migration**: `jobs.locale` column + `count_jobs_by_locale()` analytics; `/api/process` records it. | ? **CI running** (1315 suite green locally) |
```

Answering your three asks directly:

1. ****Watermarking**** ? done: a Kannada/Hindi/Spanish/? user's reel is now watermarked in their language (verified the actual ffmpeg render).
2. ****Locale in the DB**** ? yes now: `jobs.locale` (v7), captured at `/api/process`.
3. ****Basic analytics possible**** ? yes: `Database.count\_jobs\_by\_locale()` ? `{locale: count}` (e.g. how many Spanish submissions); SQL `GROUP BY locale` works.

Migration safety: I confirmed ****no competing v7**** before committing and after rebasing ? the serving session's planned consent migration can take v8. All engine work was done in ****isolated worktrees**** so the concurrent session's checkout was never touched.

I'll merge LW3 once CI is green (re-checking for a competing v7 at merge time), then refresh the memory handoff. Waiting on the CI poll now.

728. user (2026-06-21T18:41:24.802Z)

- 1 poll 1: 1/9 success, 0 failed
- 2 poll 2: 6/9 success, 0 failed
- 3 poll 3: 7/9 success, 0 failed

```
4      poll 4: 8/9 success, 0 failed
5      poll 5: 8/9 success, 0 failed
6      poll 6: 8/9 success, 0 failed
7      poll 7: 8/9 success, 0 failed
8
```

729. assistant (2026-06-21T18:41:46.213Z)

CI is at ****8/9 green, 0 failed**** ? the last check (full suite or wheel-smoke) is finishing. I'll merge LW3 as soon as the poll reports 9/9 (re-checking for a competing v7 at merge time), then refresh the handoff memory and give the final wrap. Waiting on the background poll to complete.

730. user (2026-06-21T18:41:48.366Z)

```
<task-notification>
<task-id>bc92pnhue</task-id>
<tool-use-id>toolu_01P4rGmRom2wACbnUDHgva7T</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-badminton-
highlight-indexer\2ba49afa-99f4-41f2-86a2-27a289d432f3\tasks\bc92pnhue.output</output-file>
<status>completed</status>
<summary>Background command "Poll LW3 engine CI" completed (exit code 0)</summary>
</task-notification>
```

731. user (2026-06-21T18:42:07.833Z)

```
1      poll 1: 1/9 success, 0 failed
2      poll 2: 6/9 success, 0 failed
3      poll 3: 7/9 success, 0 failed
4      poll 4: 8/9 success, 0 failed
5      poll 5: 8/9 success, 0 failed
6      poll 6: 8/9 success, 0 failed
7      poll 7: 8/9 success, 0 failed
8      poll 8: 9/9 success, 0 failed
9      === final ===
10     SUCCESS Ruff lint
11     SUCCESS Mypy (lenient baseline)
12     SUCCESS Syntax sweep + import smoke (no GPU stack)
13     SUCCESS Golden fixtures cross-OS (ubuntu-latest)
14     SUCCESS Golden fixtures cross-OS (windows-latest)
15     SUCCESS Golden fixtures cross-OS (macos-latest)
16     SUCCESS Dependency license scan (no copyleft in runtime deps)
17     SUCCESS Built wheel smoke (install + launch)
18     SUCCESS Full test suite (offline, mocked)
19
```

732. assistant (2026-06-21T18:42:50.868Z)

All 9 LW3 checks green ? but I'll hold the merge: the owner just directed me to ****verify the watermark via actual video generation for all locales first****. That's the right call ? my earlier test was a single ``drawtext`` frame, not a real reel through the compile pipeline. Let me do a true end-to-end render for all 6 locales.

733. user (2026-06-21T18:42:51.354Z)

Chapter marked: "Watermark video verification (all locales)". Continue your current work.

734. assistant (2026-06-21T18:43:07.230Z)

```
"""End-to-end watermark verification: generate a REAL highlight reel through the actual
VideoCompiler
(per-clip re-encode + ffmpeg drawtext) for EVERY supported locale, then dump a cropped frame of
the
bottom-right watermark for each so it can be eyeballed. Not committed (scratch)."""
import subprocess
```

```

import sys
from pathlib import Path

from backend.config.models import WatermarkConfig
from backend.pipeline.stitcher.compiler import VideoCompiler
from backend.pipeline.stitcher.watermark_i18n import WATERMARK_TEXT, localize_watermark

OUT = Path("scratch_wm_out")
OUT.mkdir(exist_ok=True)
SRC = OUT / "source.mp4"

```

A real 3s source with video + audio (the compile path re-encodes libx264 + aac).

```

subprocess.run([
    "ffmpeg", "-y",
    "-f", "lavfi", "-i", "testsrc=size=1280x720:rate=30:duration=3",
    "-f", "lavfi", "-i", "sine=frequency=440:duration=3",
    "-c:v", "libx264", "-pix_fmt", "yuv420p", "-c:a", "aac", "-shortest", str(SRC),
], check=True, capture_output=True)

locales = ["en", "kn", "hi", "es", "da", "id"]
results = []
for loc in locales:
    wm = localize_watermark(WatermarkConfig(enabled=True), loc)
    text = wm["text"] if isinstance(wm, dict) else wm.text
    comp = VideoCompiler(str(OUT), watermark=wm)
    reel = comp.compile_highlights(str(SRC), [(0.5, 2.5)], f"reel_{loc}.mp4")
    # Crop the bottom-right region where the watermark sits, so each locale is clearly legible.
    crop = OUT / f"wm_{loc}.png"
    subprocess.run([
        "ffmpeg", "-y", "-i", reel, "-ss", "0.8",
        "-vf", "crop=820:110:in_w-840:in_h-130",
        "-frames:v", "1", str(crop),
    ], check=True, capture_output=True)
    size = Path(reel).stat().st_size
    results.append((loc, text, Path(reel).name, size, crop.stat().st_size))
    print(f"[{loc}] reel={Path(reel).name} ({size} B) text={text!r} crop={crop.name} ({crop.stat().st_size} B)")

print("\nALL REELS GENERATED:", all(r[3] > 0 and r[4] > 0 for r in results))

```

735. user (2026-06-21T18:43:07.262Z)

File created successfully at: C:\Users\avidu\Projects\bhi-loc-analytics\scratch_wm_verify.py
(file state is current in your context ? no need to Read it back)

736. user (2026-06-21T18:43:18.700Z)

```

[en] reel=reel_en.mp4 (127585 B) text='Generated by Khelsutra.guru' crop=wm_en.png (24409 B)
[kn] reel=reel_kn.mp4 (128885 B) text='KheḷSutra.guru ??? ???? ????' crop=wm_kn.png (27423 B)
[hi] reel=reel_hi.mp4 (127376 B) text='KheḷSutra.guru ?? ???? ??' crop=wm_hi.png (22281 B)
[es] reel=reel_es.mp4 (127911 B) text='Generado con KheḷSutra.guru' crop=wm_es.png (24653 B)
[da] reel=reel_da.mp4 (127226 B) text='Lavet med KheḷSutra.guru' crop=wm_da.png (22697 B)
[id] reel=reel_id.mp4 (128029 B) text='Dibuat dengan KheḷSutra.guru' crop=wm_id.png (24878 B)

```

ALL REELS GENERATED: True

Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

737. assistant (2026-06-21T18:43:29.830Z)

All 6 reels generated through the **real** VideoCompiler pipeline (each ~127 KB, watermark baked in). Now let me view each cropped watermark to confirm correct rendering per locale:

738. assistant (2026-06-21T18:43:39.068Z)

en renders correctly ("Generated by Khelsutra.guru", with the box). Now the critical kn + hi (Noto fonts) through the real pipeline:

739. assistant (2026-06-21T18:43:57.710Z)

kn + hi render perfectly through the real reel pipeline (Latin brand + native script, no tofu). Now the three Latin locales (es/da/id via RobotoSlab):

740. assistant (2026-06-21T18:44:31.636Z)

****All 6 locales verified via real watermark video generation**** through the actual VideoCompiler pipeline ? every one renders correctly (no tofu), with the right localized text baked into a real reel:

- ****en**** "Generated by Khelsutra.guru" . ****es**** "Generado con KhelSutra.guru" . ****da**** "Lavet med KhelSutra.guru" . ****id**** "Dibuat dengan KhelSutra.guru" (RobotoSlab)
- ****kn**** "KhelSutra.guru ???? ????????" . ****hi**** "KhelSutra.guru ?? ????? ??" (Noto Kannada/Devanagari)

This also retroactively validates the already-merged LW1 (the test ran against master's code). Now clean up scratch, re-check for a competing v7, and merge LW3:

741. user (2026-06-21T18:44:36.231Z)

scratch cleaned
=== final competing-v7 check on origin/master ===
1
(0/absent comment = no competing v7) origin/master=fa7ee3f
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

742. assistant (2026-06-21T18:44:48.009Z)

Confirmed: the single match is just the `# future: if version < 7` comment (no real competing migration), `origin/master` unchanged at my rebase base ? mergeable. ****All the owner's conditions are met**** ? CI 9/9 green, all 6 locales verified via real watermark video. Merging LW3:

743. user (2026-06-21T18:44:56.816Z)

state=MERGED merged=2026-06-21T18:44:51Z
Shell cwd was reset to C:\Users\avidu\Projects\badminton-highlight-indexer

744. assistant (2026-06-21T18:45:04.882Z)

LW3 merged (#306). The full feature is complete ? all 3 PRs merged + verified. Cleaning up the worktree:

745. user (2026-06-21T18:45:09.028Z)

worktree removed
engine origin/master now: f01dc85
f01dc85 feat(db): v7 ? record the UI locale per job (PMF analytics) + count_jobs_by_locale (#306)
fa7ee3f feat(pkg): P2a ? single ffmpeg/ffprobe resolver (env-overridable; one fail-loud place) (default-OFF) (#305)
e99d0c3 feat(stitch): localize the reel watermark to the UI locale (+ OFL Noto fonts) (#304)

746. assistant (2026-06-21T18:45:29.558Z)

Worktree removed. Engine `origin/master` head is now my LW3 (#306), cleanly interleaved with the serving session's work. Let me mark LW3 done and refresh the handoff memory:

747. user (2026-06-21T18:45:30.061Z)

Updated task #12 status

748. user (2026-06-21T18:45:31.111Z)

```
10      # Handoff ? khelsutra UX / localization / runnable-tool (refreshed 2026-06-21)
11
12      > This is the **khelsutra (web/ SPA + site/)** product track. The **engine/serving**
track (Cloud-Run M5?M12, a CONCURRENT session) has its own `session-handoff.md` ? **don't touch
its files** (`COMPUTE_DECOUPLED_SERVING`, `backend/compute/`, engine `DOC_STATUS`/`NEXT_STEPS`).
13
14      ## 1. You are here *(refreshed 2026-06-21, end of the UX + North-Star session)*
15      The **SPA UX A-items are DONE** (A1/A4/A5/A8 merged), the **North-Star upload keystone
(T4) is SHIPPED**, the SPA is trilingual (en+kn+hi), and the bucket?reel CUJ is UI-driven +
proven. The North Star = make the tool runnable/shareable for alpha users from the UI; **a
sibling session shipped most of the T2 deploy plumbing**
([#64](https://github.com/avidullu/khelsutra/pull/64)) `VITE_API_BASE` split-origin +
[#65](https://github.com/avidullu/khelsutra/pull/65) **alpha deploy kit** = Cloudflare Pages +
`api.` tunnel + CF Access; see `deploy/DEPLOY_ALPHA.md`) ? so T2's remaining bits are owner-
gated (CF Access setup + **GEMINI_API_KEY rotation** + the actual deploy).
16
17      **Merged THIS session (all green CI, each browser-verified + adversarially reviewed via
a workflow):**
18      - [#61](https://github.com/avidullu/khelsutra/pull/61) **A4** ? 744px mobile tap targets
+ tooltip-text?visible (the "not available yet" reason + per-card shot confidence).
19      - [#62](https://github.com/avidullu/khelsutra/pull/62) **A5** ? friendly engine-error
mapping across build + load + ingest via one shared `lib/errorText.ts` + an `errors.` namespace
(no more raw `ApiError`/`HTTP 500`).
20      - [#63](https://github.com/avidullu/khelsutra/pull/63) **A8** ? background-processing
reassurance + icon+text status chips (`StatusChip`), a "Stitching your reel?" building card +
?? status icons.
21      - [#66](https://github.com/avidullu/khelsutra/pull/66) **T4 (North Star keystone)** ?
in-UI file UPLOAD: file picker ? chunked `api/upload/` (`api/client.ts` +
`hooks/useUpload.ts`) ? server path ? `/api/process` ? existing poll?load?compile?download. 153
web tests.
22
23      - [#67](https://github.com/avidullu/khelsutra/pull/67) **MULTILINGUAL Phase A** ?
es/da/id catalogs (SPA now speaks **6 languages**); es 3-form plural; a **placeholder-parity**
guard that caught + fixed a latent kn/hi A1-drift (`{videoId}`).
24      - [#68](https://github.com/avidullu/khelsutra/pull/68) **A9** ? localized tap-only
filter controls (`TapFilters`); English example chips now en-only; tap==type pinned.
25
26      **Workstream A is essentially DONE (A1/A4/A5/A8/A9 ?). SPA = en/kn/hi/es/da/id. Web
tests 103?173** + 2 new invariant guards (placeholder-parity, tap==type).
27
28      Prior session (context): engine #284/#289, khelsutra #55?#60, owner-merged #58.
Screencast: `gs://khelsutra-rally-corpus/promo/khelsutra-bucket-cuj-screencast.mp4`.
29
30      **Spun off as chips (owner-launchable parallel sessions, recorded 2026-06-21):** B3
(`task_b3060842`), MULTILINGUAL Phase A (`task_e15e9643`), T11 (`task_2480b9e2`). ? B3 +
MULTILINGUAL both edit the catalogs ? don't run them simultaneously.
31
32      ## 2. Next steps (one PR per item, off `origin/master`, merge on green + rising
coverage)
33      **DONE this session:** A1 (#60) · A4 (#61) · A5 (#62) · A8 (#63) · **T4 North-Star
upload (#66)** · **MULTILINGUAL Phase A es/da/id (#67)** · **A9 tap-filters (#68)** · (A2
DROPPED ? social/sharing is separate scope.)*
34
35      **? TOP NEXT ? B3 (`site/` trilingual), now FULLY UNBLOCKED.** All 6 catalogs
(en/kn/hi/es/da/id) exist to hoist. Chip `task_b3060842` is ready (still pending). **DECISION
LOCKED (owner): hoist catalogs to repo-root `/locales/` + re-point the SPA imports (or a Vite
`@locales` alias; note `web/src/i18n/index.ts` imports 6 catalogs now + `hygiene.test.ts`
`LOCALES_DIR`) + a tiny site prebuild copy + drift-guard. Vanilla `site/public/i18n.js` over
`index/capture/own-model.html` + switcher + `site/server.js` Accept-Language; en-only content
```

first. Negotiation must match the SPA exactly. ****Big/architectural** (SPA import repoint + a new site build step) ? best as a focused session, ideally split: PR-1 hoist+drift-guard, PR-2 shim+annotation.****** ? MULTILINGUAL already merged, so B3 hoists the full 6-catalog set.

749. assistant (2026-06-21T18:45:38.426Z)

Let me update the handoff to reflect the locale-watermark-analytics feature shipping and that B3 + T11 are done:

750. user (2026-06-21T18:45:54.167Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

751. user (2026-06-21T18:46:21.004Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

752. assistant (2026-06-21T18:46:30.453Z)

Now a concise checkpoint in the shared current-state. Let me read its current top (it's been moving):

753. user (2026-06-21T18:46:31.465Z)

12 > ****Scope of this file = LIVE only:**** the current handoff + **today's** checkpoints + open PRs/decisions. Keep it read-first-short (?1 page). Older checkpoints are archived in *[[current-state-archive]]* ? when today's checkpoints age out (next clean-slate day), move them there, don't let them pile up here.

13

14 ****Checkpoint:**** 2026-06-21 (****T11 retention sweep ? engine PR MERGED + both follow-ups done****). The owner-spun T11 chip (``task_2480b9e2``) is now BUILT in the engine. ****Extended `tools/cleanup\_caches.py`**** (not hand-rolled, per *[[cache-hygiene-policy]]*) with a pre-alpha ****upload retention sweep****: a new ``uploads`` scan location + ``classify`` (``uploaded source`` / ``partial upload`` for the orphaned ``partial-<id>`` files) over ``security.upload_dir`` (default ``output/uploads``); ``plan_deletions`` gains an ****independent `uploads\_retention\_days` window**** (privacy) orthogonal to the cache ``--older-than`` (disk); ``scan_windows`` now ****skips the nested uploads dir**** (was silently kept whole as "other dir" ? no retention); loud structured output (retention-window banner + per-category subtotals + per-item PURGED/FAILED + a ``--json`` plan for a cron/job wrapper). ****Dry-run by default; reels/DB/CSVs stay durable.**** ****Owner gate** (AskUserQuestion): uploads 7d default; reels kept durable.**** ? **engine** [#299](https://github.com/Khelsutra/badminton-highlight-indexer/pull/299) MERGED** (``cb7394b``, all 11 CI checks green: ruff/mypy/full-suite/golden cross-OSx3/wheel-smoke/license-scan/syntax+import); +6 unit tests; ****coverage no-regression VERIFIED**** (branch ****85.30%**** vs ``origin/master`` baseline ****85.06%**** measured in an isolated worktree; same ****9748**** measured stmts, branch missed ****1433 ?**** baseline ****1456**** ? the +0.24% is obsreport reporting tests in my local lane, NOT my diff; the diff touches ****ONLY tools/+tests/**** and the tool imports ****zero**** backend/training). Branch cut from ``origin/master`` in the shared checkout, explicit-path staging; after merge the checkout was ****restored to the serving session's branch**** + feature branches deleted. **** ? BOTH FOLLOW-UPS DONE** (owner-directed):**** (1) automation** (unattended scheduled-job wiring for hosted alpha) filed ? ****[engine** #301](https://github.com/Khelsutra/badminton-highlight-indexer/issues/301)****** (enhancement; the tool + ``--json`` hook is ready, needs a cron/Cloud-Scheduler wrapper + observability + default-OFF guard + in-flight/active-job safety). (2) ****khelsutra \$9 T11 doc flipped ??? ? [khelsutra #69](https://github.com/avidullu/khelsutra/pull/69) MERGED**** (``bea8a2a``; honest framing: sweep TOOL shipped #299, scheduling tracked #301; also updated the \$6 retention risk row + \$10 blocking-gate-#2 [window DECIDED] + \$11 DoD). Done in a dedicated worktree off ``origin/master``; the UX session's ``khelsutra-b3-wt`` worktree was untouched. *[[cache-hygiene-policy]]* *[[ui-driven-cloud-serving-gap]]* *[[gotcha-shared-checkout-branch-collisions]]* *[[doc-status-register]]*

15

754. assistant (2026-06-21T18:46:49.637Z)

The serving session updated the T11 checkpoint. Let me insert my locale-watermark checkpoint above it:

755. user (2026-06-21T18:46:59.436Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\current-state.md has been updated successfully. (file state is current in your context ? no need to Read it back)

756. assistant (2026-06-21T18:47:09.537Z)

All three PRs merged + verified, memory refreshed. Final sanity check on the workspace:

757. user (2026-06-21T18:47:12.982Z)

```
=== my engine worktrees gone? ===
(none of mine remain ?)
=== my open PRs across both repos ===
(end open PRs)
```

758. user (2026-06-21T18:47:20.948Z)

Updated task #4 status

759. assistant (2026-06-21T18:47:42.245Z)

Done ? and verified exactly as you asked. ?

Locale ? watermark + analytics: shipped & verified

All three PRs are **merged**, and I confirmed the watermark by **generating a real reel** through the actual ``VideoCompiler`` pipeline for every supported locale¹ and eyeballing the baked-in watermark:

Locale	Watermark on the real reel	Font	Render
en	Generated by Khelsutra.guru	RobotoSlab	?
es	Generado con KhelSutra.guru	RobotoSlab	?
da	Lavet med KhelSutra.guru	RobotoSlab	?
id	Dibuat dengan KhelSutra.guru	RobotoSlab	?
kn	KhelSutra.guru ???? ??????????	Noto Sans Kannada	? no tofu
hi	KhelSutra.guru ?? ????? ???	Noto Sans Devanagari	? no tofu

Not just a frame test ? each was a full ``compile_highlights`` ? per-clip re-encode + ffmpeg ``drawtext`` ? real ``mp4``, then I cropped and viewed the watermark region.

The PRs (merged on green CI + the video verification):

- [#304](https://github.com/Khelsutra/badminton-highlight-indexer/pull/304) **LW1** ? localized watermark + bundled OFL Noto fonts (engine, 1302 suite green)
- [#73](https://github.com/avidullu/khelsutra/pull/73) **LW2** ? SPA sends the UI locale to ``/api/compile`` + ``/api/process`` (177 web tests)
- [#306](https://github.com/Khelsutra/badminton-highlight-indexer/pull/306) **LW3** ? v7 ``jobs.locale`` + ``count_jobs_by_locale()`` (engine, 1315 suite green, all 9 CI checks)

Your three asks, delivered:

1. **Watermarking in every language** ? done & video-verified.
2. **Locale recorded in the DB** ? ``jobs.locale`` (v7), captured at ``/api/process``.
3. **Analytics possible** ? ``Database.count_jobs_by_locale()`` ? e.g. ``{"kn": 2, "hi": 1, "es": 1, "(unset)": 1}``; a read-only stats endpoint is a trivial follow-up if you want a dashboard.

Safety: all engine work in isolated worktrees (the serving session's checkout untouched); re-checked for a competing **v7** at commit, rebase, and merge ? none, so the engine head is now

v7 and the serving session's consent migration cleanly takes v8. Scratch render artifacts cleaned up; no worktrees or open PRs of mine remain.

****One honest caveat:**** the localized watermark strings (and the kn/hi/es/da/id catalog text) are AI-drafted ? ****native-speaker review**** is still the pre-public-launch gate. I recorded that, plus the remaining T2 owner stand-up, in the handoff.

Net for the session: ****9 PRs merged**** (A4/A5/A8/T4/MULTILINGUAL-A/A9 + LW1/LW2/LW3), web tests 103?177, engine suite green at 1315, and B3 + T11 landed via the chips. Want me to add the `GET /api/stats/locales` endpoint, or is the queryable column enough for now?

760. user (2026-06-21T19:03:23.304Z)

you are >80% context now, so can you get to a clean slate, update all teh documentation and give me a nie icebreaker to continue in the next session and complete the entire work. Amazing session!

761. assistant (2026-06-21T19:04:09.629Z)

Amazing session indeed ? thank you! Let me wrap to a clean slate, true up the docs, and leave you a crisp icebreaker. First, verify git state and check what the tracked docs currently say (the sibling's B3 #70 may have already updated some):

762. user (2026-06-21T19:04:16.419Z)

```
khelsutra: branch=master head=1cd84af origin=1cd84af
--- status (untracked-only expected) ---
?? .claude/
?? site/access.db
--- my branches still around? ---
  docs/multilingual-expansion-proposal
  feat/a3-recording-l10n
+ feat/a6-access-plain-language
+ fix/kn-hi-spa-console-native-review
```

763. assistant (2026-06-21T19:05:13.693Z)

khelsutra is on master, clean (only pre-existing untracked files). I can also see ****parallel sessions are already knocking out the remaining items**** ? there are live worktree branches `feat/a3-recording-l10n` (A3), `feat/a6-access-plain-language` (A6), and `fix/kn-hi-spa-console-native-review` (native review). So I'll leave the khelsutra tracked docs (FRIENDLY/MULTILINGUAL) to those sessions to avoid collision, and make the ****memory handoff**** the authoritative "continue here" record (no conflict ? separate files).

Let me add the icebreaker to the top of the track handoff and freshen the date:

764. user (2026-06-21T19:05:34.335Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

765. assistant (2026-06-21T19:05:42.045Z)

Let me fix a typo in that block ("018" slip):

766. user (2026-06-21T19:05:44.178Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\next-session-ux-localization.md has been updated successfully. (file state is current in your context ? no need to Read it back)

767. assistant (2026-06-21T19:05:57.032Z)

Now update the MEMORY.md index entry so the "? START HERE" pointer reflects the new reality (it still says "next: A4?A5?A8?B3"):

768. user (2026-06-21T19:05:57.948Z)

```
1      # Memory Index
2
3      ## ? Start here
4      - [? START HERE ? khelsutra UX/l10n/runnable-tool](next-session-ux-localization.md) ?
**refreshed 2026-06-21.** CUJ done + SPA trilingual + A1 copy merged + 7-lang expansion APPROVED
(#58). **Ordered next:** A4?A5?A8?B3 (SPA UX), then the **runnable-tool NORTH STAR** (T4 in-UI
upload ? T2 droplet+Cloudflare-Access+Gemini ? T11 retention; NOT GPU/NOT M12) + ramp-up + open
owner decisions. *(The engine/serving track has its OWN handoff in [session-handoff](session-
handoff.md) ? don't conflate.)*
5      - [Current state](current-state.md) ? **live micro-checkpoint** (updated every
checkpoint): open PRs, what just landed, next steps, open decisions. **Read this first.** Now
LIVE-only (handoff + today's checkpoints); kept read-first-short.
6      - [Current-state archive](current-state-archive.md) ? chronological checkpoint history
(2026-06-06 ? 06-18, 96 blocks) split out of current-state 2026-06-19. Deep history only; NOT
read each session.
7      - [Session handoff](session-handoff.md) ? current state · next steps · open decisions ·
ramp-up kit. AUTO-refreshed at meaningful checkpoints (PR merged, key decision, phase shift,
session wrap) ? see working-agreement-checkpoints staleness tripwire.
8      - [Code map artifact](code-map-artifact.md) ? for CODE/architecture ramp-up, read
`docs/CODE_MAP.md` FIRST (dense anchor-rich map; replaces a file crawl). How to regenerate it.
9      - [File-placement conventions](file-placement-conventions.md) ? **where new files go**
(scripts/ vs backend/eval/ vs tools/ vs scratch/ vs training/ vs artifacts/ ?); **read before
committing a new file.** Authoritative table = `docs/CODE_MAP.md` §0 (PR #138); scratch/
gitignored (#136).
10
```

769. user (2026-06-21T19:06:12.866Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\memory\MEMORY.md has been updated successfully. (file state is current in your context ? no need to Read it back)

770. assistant (2026-06-21T19:07:10.861Z)

Everything's tidy. Clean slate confirmed and docs trued up. Here's the wrap.

? Session wrap ? clean slate

****Git/workspace:**** khelsutra on `master` (clean; only pre-existing untracked `.claude/`, `site/access.db`). ****No branches, worktrees, or open PRs of mine remain**** ? all engine work was done in isolated worktrees (removed), nothing touched the serving session's checkout.

****Docs updated:****

- ****Memory handoff**** ([next-session-ux-localization.md](memory/next-session-ux-localization.md)) ? added a ****§0 icebreaker****, refreshed §1/§2, dated 2026-06-22.
- ****current-state.md**** ? checkpoint for the locale?watermark+analytics feature.
- ****MEMORY.md**** ? "? START HERE" pointer rewritten to the new reality.
- The khelsutra ****tracked docs**** (FRIENDLY/MULTILINGUAL §7) I deliberately ****left to the parallel sessions**** ? there are live worktrees for `feat/a3-recording-l10n`, `feat/a6-access-plain-language`, and `fix/kn-hi-spa-console-native-review`, so a doc PR from me would collide. The memory captures the full picture for safety.

What landed this session

****9 of my PRs merged**** + 2 via chips I spawned:

- ****SPA UX/i18n:**** A4 [#61](https://github.com/avidullu/khelsutra/pull/61) · A5 [#62](https://github.com/avidullu/khelsutra/pull/62) · A8 [#63](https://github.com/avidullu/khelsutra/pull/63) · ****T4 in-UI upload**** [#66](https://github.com/avidullu/khelsutra/pull/66) · MULTILINGUAL-A (es/da/id)

[#67](https://github.com/avidullu/khelsutra/pull/67) · A9 tap-filters
[#68](https://github.com/avidullu/khelsutra/pull/68)
- **Locale ? watermark + PMF analytics:** LW1 [#304](https://github.com/Khelsutra/badminton-highlight-indexer/pull/304) · LW2 [#73](https://github.com/avidullu/khelsutra/pull/73) · LW3 [#306](https://github.com/Khelsutra/badminton-highlight-indexer/pull/306) ? **verified via real watermark video for all 6 locales**
- **Via spawned chips:** B3 site-trilingual [#70](https://github.com/avidullu/khelsutra/pull/70)
· T11 retention [#299](https://github.com/Khelsutra/badminton-highlight-indexer/pull/299)

Web tests **103 ? 177**, engine suite green at **1315**, two new invariant guards (placeholder-parity, tap==type), one latent kn/hi bug caught+fixed. Every PR browser/video-verified + adversarially reviewed.

? Icebreaker for next session ? "make the alpha real"

> ? **The runnable tool is built and fully localized.** A non-tech Bangalore coach can, in **6 languages**, on a phone: upload a video ? watch it process with reassurance ? tap/type to pick rallies ? download a reel **watermarked in their own language** ? and we capture which language they used.

>
> **One thing stands between this and real alpha users: nothing is deployed yet.** So **start with T2** (~an afternoon, your call on the gated bits): Cloudflare Pages + a `cloudflared api.` tunnel + **Cloudflare Access** + **rotate `GEMINI\_API\_KEY`**, per `khelsutra/deploy/DEPLOY\_ALPHA.md`. ? set the engine's `allowed\_video\_root` to a parent of `upload\_dir` or uploads get rejected. Then run the in-UI upload?reel CUJ against the live URL and share it.

>
> **Then to finish:** native-speaker review of all AI-drafted strings (catalogs + watermark ? the public-launch gate) · A3/A6/A7 site polish (parallel sessions in flight) · MULTILINGUAL Phase B/C (Thai/CJK ? owner-gated).

Thank you ? this was a genuinely fun one. The tool's gone from "works on my machine in English" to "point-and-go in six languages with localized reels." See you next session to flip the switch. ?