

claude-windows / dca1ff63-3aec-42ab-897f-41970003f4e1

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1.jsonl`  
- SHA-256: `5bb1d71eeb349e201121298d83d4cbf0e9fbb0cf8badcf353554e36c4b5dbe7c`  
- Source modified: `2026-06-22T01:10:27+00:00`  
- Imported at: `2026-07-05T16:48:20+00:00`  
- project: `C--Users-avidu-Projects-khelsutra`  
- session_id: `dca1ff63-3aec-42ab-897f-41970003f4e1`
```

Transcript

1. user (2026-06-21T17:07:09.465Z)

Implement B3 in the khelsutra repo (C:\Users\avidu\Projects\khelsutra): make the marketing `site/` trilingual via a shared, dependency-free `t()/`data-i18n` shim, en-only content first (this proves the shared-catalog architecture across both surfaces; kn/hi marketing translation is a later effort).

LOCKED OWNER DECISION (D-CATALOG-HOME): hoist the locale catalogs to repo-root `./locales/{en,kn,hi}/common.json` as the single source of truth.

- Re-point the SPA's catalog imports (`web/src/i18n/index.ts` currently imports `./locales/{en,kn,hi}/common.json`) to the hoisted location, or add a Vite `@locales` alias. Keep `web/` tests green.
- Add a tiny `site` prebuild step that copies `./locales` ? `site/public/locales/` + a drift-guard test (the site is dependency-free/no-build today ? this copy is the only new build step).

Build:

- `site/public/i18n.js` ? a ~70-LOC vanilla `t(key, vars)` + a `data-i18n` attribute walker, with ICU-lite interpolation/plurals for the 2-form languages (mirror i18next behaviour for en/kn/hi).
- A persistent language switcher on `site/public/{index,capture,own-model}.html`.
- `site/server.js` Accept-Language negotiation.
- Negotiation MUST match the SPA EXACTLY: persisted `localStorage` key `khelsutra.lang` ? `?lang=` ? `navigator`/`Accept-Language` ? `en`; a missing key degrades to en, never a raw key.
- Tests: extend `site/src/{server,assets}.test.js` + a shim unit test + the §6.5 N8 negotiation test (`Accept-Language: kn` / `?lang=kn` ? kn-rendered).

Conventions (shared checkout ? multiple sessions): `git fetch origin` then `git checkout -b feat/b3-site-i18n origin/master`; re-verify HEAD before commit; stage EXPLICIT paths (never `git add -A`); ONE PR; merge on green CI (web + site + Cloudflare build). Update the tracker `docs/FRIENDLY\_AND\_MULTILINGUAL.md` §7 row B3 + the §8 D-CATALOG-HOME note + changelog.

? Catalog contention: if the MULTILINGUAL_EXPANSION PR (adds es/da/id catalogs) hasn't merged yet, just hoist en/kn/hi; if it HAS merged, hoist all locales. Do NOT run B3 and the MULTILINGUAL_EXPANSION task at the same time ? they both edit the catalogs.

Read first: `docs/FRIENDLY\_AND\_MULTILINGUAL.md` (§4 architecture, §6.5 negotiation matrix, §7 tracker), `web/src/i18n/index.ts`, `web/src/i18n/hygiene.test.ts`, `site/server.js`, `site/src/assets.test.js`.

2. assistant (2026-06-21T17:07:15.753Z)

I'll start by getting up to speed: pulling the latest, reading the tracker doc and the key files mentioned, and checking the state of the catalog contention warning.

3. user (2026-06-21T17:07:21.610Z)

On branch feat/mlx-phaseA-es-da-id

Your branch is up to date with 'origin/feat/mlx-phaseA-es-da-id'.

Untracked files:

(use "git add <file>..." to include in what will be committed)
 .claude/
 site/access.db

nothing added to commit but untracked files present (use "git add" to track)

---BRANCH---

feat/mlx-phaseA-es-da-id

---LOG---

4b8937d docs(mlx): mark Phase A (es/da/id) shipped (#67) in \$7 tracker + changelog
e873db3 feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#58)
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*
tunnel + CF Access) (#65)
8bbc557 feat(web): VITE_API_BASE ? let the SPA target a split api.* origin (default same-origin
/api) (#64)

4. user (2026-06-21T17:07:22.030Z)

```
1      # Friendly & Multilingual ? non-tech-savvy UX + Hindi/Kannada localization
2
3      > **Status:** `DRAFT` ? owner-gated (implementation starts only on explicit approval) .
**Owner:** Avi Dullu . **Created:** 2026-06-21 . **Last updated:** 2026-06-21
4      > **Lifecycle:** `DRAFT ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when
DONE).
5      > **Tracking anchors:** $7 progress tracker is the source of truth; indexed in
`docs/README.md`; thread in `NEXT_STEPS.md`; pointer in engine `docs/DOC_STATUS.md`; memory
`current-state` + `next-session-ux-localization`.
6      > **Relation to existing docs:** this is the **implementation project** for two engine
design docs ? it *adapts & supersedes-in-practice* `badminton-highlight-
indexer/docs/I18N_PLAN.md` (localization) and the UX half of `~/docs/UI_PROPOSAL.md` (non-tech-
savvy console). Those stay the canonical *design*; this doc carries the *tracked execution*
against today's surfaces.
7      > **Honesty note:** each claim tagged `[verified]` (checked against code this session),
`[researched]` (needs sign-off), or `[design]` (proposed). Not legal advice ? the OFL font
question (D-FONT) is owner/counsel-gated.
8
9      ---
10
11     ## 0. TL;DR
12     A coach or parent in Bangalore should land on KhelSutra, feel at home, set up their
camera with confidence, and get highlights ? **in Kannada or Hindi**, with **zero hand-
holding**. This project isolates that goal into one tracked workstream-pair: **(A)** make the UI
super friendly for non-tech-savvy users, and **(B)** localize to Hindi + Kannada. Both surfaces
(`web/` React SPA + `site/` vanilla marketing) have **zero i18n today** `[verified]`, so the
foundation ? shared `locales/{en,kn,hi}` catalogs + a negotiation contract + CI parity ? is the
real deliverable; translations follow. **The single most important caveat:** translations are
**human-reviewed** (Gemini drafts are *inference only, never training* ? the standing
guardrail), and Kannada/Hindi rendering is **blocked on the OFL font decision (D-FONT)**. The
cheapest unblocked high-impact first slice is the **SPA i18n scaffold + language switcher (en-
only)** ? it locks the shared catalog/negotiation contract and adds the render-test safety net
the SPA currently lacks.
13
14     ## 1. Problem & goal
15     **Why now.** The public site (kheLSutra.guru) is live, clean, honest, and tested. The
PMF beachhead is **Bangalore badminton academies** ; many coaches, parents, and players are far
more comfortable in **Kannada** than English, and most are **not highly tech-savvy** `[verified
? design intent]` (`UI_PROPOSAL.md:25,28`, `I18N_PLAN.md:10-13`, `PMF_MARKET_RESEARCH.md:116`,
`KHELSUTRA_PRODUCT_OVERVIEW.md:13/50/61`). An English-only, knob-heavy product adds friction at
the exact point of first contact.
16
17     **Concrete outcome ("good" looks like):** a Kannada/Hindi-comfortable, phone-first, non-
technical coach/parent can ? without help ? (1) understand what the product does and how to
```

record reliably, (2) request access / use the console, (3) pick rallies and get a reel, and (4) share it on WhatsApp, **entirely in their language**.

18
19 **Read to get current:** this doc's §3?§4; the engine design `I18N\_PLAN.md` (canonical i18n design) + `UI\_PROPOSAL.md` §2 (personas, the 6 alpha screens, "teach recording *before* upload"); `VIDEO\_RECORDING\_GUIDELINES.md`; this repo's `PER\_RALLY\_SELECTION.md` (the honest SPA scope) + `REQUEST\_ACCESS\_FORM.md`.

20
21 ## 2. Decisions locked (structural ? owner directive 2026-06-21)
22 | # | Decision | Source / date | Implication |
23 |---|-----|-----|-----|
24 | D1 | **Isolate as ONE tracked project** spanning both workstreams (A: UX, B: kn/hi l10n) | owner, 2026-06-21 | This doc; §7 = source of truth; archived on DoD |
25 | D2 | **Home = `khelsutra/docs/`** (the implementation repo) | owner-gated tracked-doc convention | `web/` + `site/` both live here; §7 tracks khelsutra PRs; engine P2 backend-l10n is a cross-repo deferred row |

26 | D3 | **Adapt `I18N\_PLAN.md` to today's surfaces:** P1 (vanilla `t()`) shim ? `site/`; P3 (react-i18next) ? `web/`; **drop the dead `backend/api/static` retrofit** | `[verified]` the doc targets `backend/api/static` (`I18N\_PLAN.md:25,30,156,191`) which exists only in the engine repo, not here | The doc's framework-agnostic *foundation* (catalog format + negotiation + ICU plurals + CI) survives unchanged; only the wiring re-points |

27 | D4 | **Engine P2 backend-localization stays owner-gated + cross-repo** (not in this DoD) | `CLAUDE.md` guardrails | Dynamic engine error/report text localizes later; tracked as a deferred row |

28 | D5 | **Archive trigger = en+kn+hi live on BOTH surfaces** (+ the non-tech UX baseline), then run the engine `DOC\_STATUS.md` §2` archival checklist | owner, 2026-06-21 | See §9 |

29 | D6 | **D-LOCALES: `en` + `kn` for v1, `hi` next; always-fallback to `en`** | owner, 2026-06-21 | Kannada-first beachhead; `hi` = catalog-only (both 2-form CLDR) |

30 | D7 | **D-FONT: OFL-for-media carve-out ? self-host Noto Sans Kannada/Devanagari** (counsel may still confirm) | owner, 2026-06-21 | Unblocks B4/B5/A3 + the kn/hi reel watermark; an explicit exception to the MIT/Apache/BSD code guardrail (fonts = media) |

31 | D8 | **D-SURFACE-FIRST: lead with the `web/` SPA scaffold; SKIP the dead static-UI retrofit** | owner, 2026-06-21 (via B1 go-ahead) | B1 is greenlit; site recording-education localized early |

32 | D9 | **D-CATALOG-HOME: co-locate `locales/` + CI in `khelsutra`** (shared, consumed by SPA + site) | owner, 2026-06-21 (via B1 go-ahead) | No cross-repo coupling |

33
34 *Only **D-BACKEND-DEPTH** (§8.3) remains open ? and it's a deferred, cross-repo engine concern (B7), not a v1 blocker.*

35
36 ## 3. Foundation ? research / prior art

37 **Current-state facts `[verified]` this session** (adversarially checked against the working tree):

38 - **`web/` SPA: zero i18n.** `web/package.json` deps are only `react`/`react-dom`; no `i18next`/`react-intl`/`formatjs`; no `locales/` dir; no `t()``useTranslation`/`data-i18n` anywhere. User-facing English is hardcoded in `tsx` (e.g. `QueryBar.tsx:46-47,56,72,76,78`; `App.tsx:115,211,224`) ? ~50 literals + ~16 derived labels.

39 - **`site/` marketing: vanilla, zero i18n.** Three `

40 - **Recording-education is *not* greenfield.** The homepage "Record it right" gist (`index.html:324-364`) + the `/capture` checklist (`capture.html`, routed `server.js:51`, guarded `assets.test.js:94`) already ship the user-facing best-practices surface. *Unshipped:* the empirical-threshold framing and the programmatic pre-flight validator (a code change, not a page).

41 - **Persona is design intent, not built.** kn/hi + zero-knobs are **proposed/owner-gated**; the app is English-only today (`KHELSUTRA\_PRODUCT\_OVERVIEW.md:61`). It's Kannada-**first**, Hindi-**next** ? not Kannada-only.

42
43 **Localization prior art `[researched]`:

44 - **CLDR plural categories:** Hindi = `{one, other}`; Kannada = `{one, other}`. Both are 2-form (same shape as English) ? once ICU MessageFormat is in the catalog, adding `hi`/`kn` plurals is **catalog-only**, no code. (ICU still required because English `count>1`'s:`` hand-

rolling ? present today in the SPA ? doesn't generalize.)

45 - **react-i18next** (web/): ``i18next` + `react-i18next` + `i18next-browser-languagedetector`` + an ICU/plural post-processor; lazy-load per-locale JSON; persist via ``localStorage``.

46 - **Shared catalog + tiny shim** (site/): the SAME i18next-flavored JSON consumed by a ~30-line ``t(key, vars)`` shim that walks ``data-i18n`` attributes ? no build step, no framework, mirrors i18next interpolation/plural rules for the 2-form languages.

47 - **Noto Sans Kannada / Noto Sans Devanagari** are **OFL-1.1**; OFL permits commercial bundling/redistribution (fonts = media, not code/weights). Self-host (e.g. ``@fontsource``) with ``font-display: swap`` + subsetting. **Gated on D-FONT.**

48 - **Non-tech-savvy / HCI4D patterns:** **icon** **++ text** (never icon-only), non-color selection indicators, large touch targets, mobile-first, WhatsApp as the share channel, a prominent persistent language switcher.

49

50 **## 4. Design / architecture**

51 **Two surfaces, one shared source of truth.**

52

53 `````

54 `locales/` # shared catalogs ? co-located in khelsutra (D-CATALOG-HOME, see §8)

55 `en/ common.json` # source of truth ? devs author keys here

56 `kn/ common.json` # Kannada (Gemini-draft ? human-review)

57 `hi/ common.json` # Hindi (next ? the extensibility proof)

58

59 `web/ ? react-i18next` # I18N_PLAN P3: provider in main.tsx; useTranslation in components

60 `site/ ? t(key,vars) shim` # I18N_PLAN P1 retargeted: data-i18n attrs over the static HTML

61 `````

62

63 - **Negotiation contract** (one order, both surfaces): **persisted pref** (localStorage) ? `switcher / ?lang=<code> ? navigator/Accept-Language ? "en"`. Supported locales in a single module; anything else falls back to ``en``; **a missing key degrades to English, never to a raw key.**

64 - **Keys, never prose** ? ``t("compile.button")``, with ICU for interpolation/plurals: ``"${count, plural, one {# rally} other {# rallies}}"``. This replaces the SPA's current hand-rolled ``Segment${count>1?'s':''}``.

65 - **Translation pipeline** (guardrail-clean): **dev authors** ``en`` keys ? ``scripts/i18n_draft.py``-style Gemini **draft** (inference only, never training; flags every value for review) ? **owner/native-speaker review** ? CI key-parity ? merge. Gemini never touches ``en``, never invents keys.

66 - **CI enforcement** (keeps it "by design"): (1) **key-parity** ? every locale has exactly the ``en`` key set (drop a stub ``ta.json`` ? CI lists every gap = the extensibility proof); (2) **no-bare-strings** ? flags user-facing literals not routed through ``t()`` (curated allowlist to start).

67 - **Fonts:** bundle Noto Sans Kannada + Devanagari **iff D-FONT = OFL carve-out**; this also unblocks a Kannada/Hindi **reel watermark** (engine ``WatermarkConfig.font_path`` already takes a path ? config, not code).

68

69 **Non-tech-savvy UX levers** (ranked impact × effort, grounded in personas; surface-tagged):

70

Lever	Surface	Impact	Effort	Note
Plain-language copy ? strip engine jargon, keep honest caveats	both	high	small	banners + footer carry backend vocabulary today
Localized WhatsApp share for the downloaded reel	both	high	small	WhatsApp is <i>the</i> channel for this audience
Language switcher persisted via a shared localStorage key	both	high	small	site promises kn/hi but ships no switcher
Localize recording-education (capture + gist)	kn?hi	site	high	medium gates input quality; the highest-leverage kn content
Mobile-first touch targets; tooltip-text ? visible	web	high	medium	tiny targets + desktop layout + invisible tooltips on phones
Icon ++ text + non-color selection indicator	web	medium	small	never icon-

```

only |
79 | Friendly engine-error mapping over raw FastAPI `detail` | web | medium | medium |
`CompileResult` passes engine text untranslated |
80 | Plain-language framing for the Request-Access GPU/storage Qs | site | medium | small |
"GPU"/"S3/GCS" are intimidating |
81 | Background-processing reassurance + status as icon chips | web | medium | small |
honest expectations on slow uplinks |
82 | Fix English-source recording gaps (a diagram) before translating | site | medium |
medium | the diagram is reusable across all 3 languages |
83 | Tap-only filter controls alongside the English query bar | web | medium | large | the
`parseQuery()` parser is English-grammar only |
84 | Keep the honest *today-vs-roadmap* split through translation | both | medium | small |
never soften "experimental"/"not available yet" |
85
86 **Reuse map (what's new vs reused):** *Reused* ? the i18next-flavored JSON + negotiation
contract + ICU plurals + key-parity/no-bare-strings CI + draft?review pipeline (all from
`I18N_PLAN.md`); the shipped recording pages; the SPA's `lib/format.ts`/`lib/query.ts`;
`site/src/assets.test.js` + the SPA's vitest harness. *New* ? `locales/` catalogs; the SPA
react-i18next provider + switcher; the site `t()` shim + `data-i18n` wiring; Noto font bundle
(gated); a jsdom render-test env for the SPA.
87
88 ## 5. Privacy / scope note
89 i18n touches **presentation only** ? no new personal-data collection, no biometrics,
minors-excluded posture unchanged. WhatsApp share opens the user's own client with a pre-filled
message; it sends nothing server-side. Gemini-draft translation is inference, not training (no
user data in the loop).
90
91 ## 6. Honest limits ? what this does NOT do
92 - A green CI / DONE status proves **key-parity + render + no-bare-strings**, **not**
translation *quality* ? that's human-gated and owner-paced.
93 - Kannada/Hindi will **not render** until the Noto fonts land (D-FONT); until then kn/hi
catalogs exist but display tofu/fallback.
94 - The SPA is **job-tethered**;; localizing **dynamic engine errors/report text** needs
engine P2 (owner-gated, cross-repo, D-BACKEND-DEPTH) ? out of this DoD.
95 - The query bar stays **English-grammar parsing**;; kn/hi users rely on tap-only controls
(a later, larger slice), not free-text Kannada queries.
96 - **Mobile-*perfect*** layout is an alpha non-goal (usable-on-phone is in scope; pixel-
perfect is not).
97
98 ## 6.5 Testing strategy ? automatic language negotiation (rigorous, owner-required)
99 **The bar (owner, #41):** a user whose **computer/browser language is Kannada or Hindi
must get the respective version automatically** ? that is the core promise and it is **proven by
tests at every layer, never assumed.** Auto-selection IS the negotiation order (persisted pref ?
`?lang=` ? browser/`Accept-Language` ? `en`); each step gets a test.
100
101 **Negotiation matrix ? every row is an automated test:**
102
103 | # | Signal under test | Setup | Expected | Proven in |
104 |---|---|---|---|---|
105 | N1 | **Browser/OS = Kannada** | no persisted pref, no `?lang`,
`navigator.languages=["kn-IN", ?]` | resolves to **kn** ? Kannada content (once the kn catalog
ships) | **B1** detection . **B5** content |
106 | N2 | **Browser/OS = Hindi** | `navigator.languages=["hi-IN", ?]` | resolves to **hi**
? Hindi content | **B6** (hi added to the supported set + catalog) |
107 | N3 | **`?lang=` override** | `?lang=kn`, browser = en | kn | B1 |
108 | N4 | **Persisted pref wins** | `localStorage=kn`, browser = en, no `?lang` | kn (a
returning user keeps their choice) | B1 |
109 | N5 | **Region subtag normalizes** | `navigator.language="kn-IN"` | base **kn** (not a
"kn-IN" miss) | B1 |
110 | N6 | **Unsupported language** | `navigator="ta-IN"` (Tamil, not yet supported) |
**en** fallback ? never a locale we can't serve | B1 |
111 | N7 | **Missing key in active locale** | kn active, a key absent from `kn/common.json`
| **en** fallback for that key (no raw key shown) | B1/B5 |
112 | N8 | **Static site (vanilla shim)** | `Accept-Language: kn` / `?lang=kn` on a `site/`
page | kn-rendered page (same order as the SPA) | B3 |

```

```

113 | N9 | **Backend (engine P2)** | `Accept-Language: kn` to the API | kn customer/report
text | B7 (owner-gated) |
114
115 **Levels & tooling:**
116 - **SPA (`web/`):** jsdom tests stub `navigator.language`/`navigator.languages`,
`localStorage`, and the `?lang` query ? assert `i18n.language`/`resolvedLanguage` + rendered
text per the matrix. *(B1 lands N1/N3?N7 at the **detection** level now ? `kn` is supported; the
kn/hi **content** assertions ride the catalogs in B5/B6.)*
117 - **Static site (B3):** the shared `t()` shim's negotiation is unit-tested the same way;
plus a server test that `Accept-Language: kn`/`?lang=kn` returns the kn-rendered page.
118 - **CI key-parity:** guarantees every locale has every key, so a correctly-negotiated
locale can never fall through to a raw key.
119 - **End-to-end (manual, owner machine ? per I18N_PLAN $6):** set the real OS/browser to
Kannada, then Hindi ? load both surfaces ? confirm the right language renders **and the Noto
fonts display** (the cloud CI container can't render fonts; the owner eyeball is the final
gate).
120 - **? Query parsing / semantic understanding (forward-looking, owner directive
2026-06-21) ? i18n testing is MANDATORY there.** The query bar is **English-grammar-only** today
(a documented limit, tracker A9): the user types English queries (`over 10s`, `top 15 longest`)
and a localized **sample-query prompt** shows them what to type in *every* locale (kn/hi
included). The **moment** the parser gains **semantic understanding** or accepts **Kannada/Hindi
query input** (e.g. typing a Kannada/Hindi phrase, or a conversational/NL builder ? I18N_PLAN
P4), i18n tests become a **merge gate**: a kn/hi query (typed or spoken) must parse to the
**correct selection**, the localized **parse-feedback** ("parsed-pill") must render in the
active locale, and the unsupported/empty-result messages must localize. **No query-NL /
semantic-parsing work merges without those tests.**
121
122 A locale that's reachable by the switcher but **not auto-selected from the browser
language is a bug, not a "later". ** This matrix is a DoD gate ($9).
123
124 ## 7. Deliverables & progress tracker ? **source of truth**
125 Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**,
branched from `origin/master`, no stacking.
126
127 | ID | Deliverable | Workstream | Depends on | Gated? | Status | PR |
128 |----|-----|-----|-----|-----|-----|----|
129 | P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |
[41](https://github.com/avidullu/khelsutra/pull/41) · engine
[275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275) |
130 | B1 | **SPA i18n scaffold + language switcher, en-only** (react-i18next + detector +
`en` catalog + switcher + persistence + **jsdom render tests** + **browser-language negotiation
tests** $6.5 N1/N3?N7) | B | P0 | No | ? | [42](https://github.com/avidullu/khelsutra/pull/42)
|
131 | B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys);
add **key-parity + no-bare-strings CI** | B | B1 | No | ? |
[45](https://github.com/avidullu/khelsutra/pull/45) |
132 | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color
selection) | A | B2 | No | ? | [60](https://github.com/avidullu/khelsutra/pull/60) |
133 | B3 | Tiny shared `t()` shim + `data-i18n` plumbing for `site/`, en-only (proves shared
catalogs across surfaces) | B | B2 | D-CATALOG-HOME | ? | ? |
134 | A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
135 | A6 | Plain-language framing for Request-Access GPU/storage questions | A | B3 | No | ?
| ? |
136 | A7 | Fix English-source recording gaps (add a placement diagram) before localizing | A
| ? | No | ? | ? |
137 | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? *SPA done; reel
watermark `font_path` = engine follow-up* | B | ? | D-FONT ? | ? |
[46](https://github.com/avidullu/khelsutra/pull/46) |
138 | B5 | **Kannada (`kn`) catalog** ? render ? *SPA done (AI-draft, native review
pending); `site/` rides B3* | B | B2/B4 | D-LOCALES ? | ? |
[47](https://github.com/avidullu/khelsutra/pull/47) |
139 | A3 | Localize **recording-education** (capture + homepage gist) to kn | A | B3/B5 |
D-LOCALES+D-FONT | ? | ? |
140 | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? |
[61](https://github.com/avidullu/khelsutra/pull/61) |

```

141 | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) |
A | B2 | No | ? | [#62](https://github.com/avidullu/khelsutra/pull/62) |

142 | B6 | ****Hindi (`hi`) catalog**** ? render (the extensibility proof ? just a catalog) ?
SPA done (AI-draft, native review pending) | B | B5 | D-LOCALES ? | ? |
[#48](https://github.com/avidullu/khelsutra/pull/48) |

143 | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 |
No | ? | [#63](https://github.com/avidullu/khelsutra/pull/63) |

144 | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ?
| ? |

145 | B7 | ***(deferred, cross-repo)* Engine **P2 backend customer-facing localization****
(report `customer\_` + rejection reasons) | B | engine | ****D-BACKEND-DEPTH, owner-gated**** | ? |
? |

146

147 ****? MILESTONE ? SPA fully trilingual (2026-06-21):**** the `web/` Studio SPA now speaks
****en + kn + hi**** end to end (B1?B2?B4?B5?B6, all merged). A ****Kannada-default browser auto-**
renders Kannada**, and the switcher walks kn ? hi ? en ? ****proven by a Playwright screencast****
with `locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + `
lang>` tracked). This meets the owner's success criterion ****on the SPA surface****. ****Still open**
for the full \$9 DoD:** ****B3**** (the `site/` marketing surface via the shared `t()` shim ? the
homepage/capture pages are still English-only), ****A3**** (recording-education in kn/hi), the
****non-tech UX A-items****, and a ****native-speaker review**** of the AI-drafted kn/hi catalogs before
a wide public launch. Do ****not**** archive until both surfaces are trilingual.

148

149 **## 8. Open questions ? owner (blocking gates) `[design]`**

150 ***Status (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see \$2 (D6?D9). Only**
D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

151 1. ****D-FONT ? ? LOCKED ? (a) OFL-for-media carve-out, self-host Noto Sans**
Kannada/Devanagari** (counsel may still confirm). An explicit exception to the MIT/Apache/BSD
code guardrail (fonts = media). Unblocks B4/B5/A3 + the kn/hi reel watermark.

152 2. ****D-LOCALES ? ? LOCKED ? `en` + `kn` for v1, `hi` next, always-fallback to `en`****
(both 2-form CLDR ? `hi` is catalog-only).

153 3. ****D-BACKEND-DEPTH ? ? OPEN (deferred, not a v1 blocker).**** Recommend ****customer**
verdict/report `customer\_` + validation-rejection reasons first; technical/operator text stays
English; phase two** (engine repo, owner-gated ? tracker row B7).

154 4. ****D-SURFACE-FIRST ? ? ADOPTED ? lead with the SPA scaffold (B1), localize site**
recording-education early, SKIP the dead static-UI retrofit.**

155 5. ****D-CATALOG-HOME ? ? ADOPTED ? co-locate `locales/` + CI in `khelsutra`**** (a shared
i18n dir consumed by both the SPA and the site). (The engine `I18N\_PLAN` assumed the indexer
repo; this is the adaptation.)

156

157 **## 9. Definition of done**

158 - [] ****Automatic language negotiation (\$6.5) is green**** ? a ****Kannada browser gets**
Kannada and a Hindi browser gets Hindi** (N1/N2); persisted-pref / `?lang` / region-subtag /
unsupported-fallback / missing-key-fallback all proven (N3?N7) on the SPA, and the static-site
shim honors `Accept-Language` + `?lang` (N8).

159 - [] ****Manual cross-check (owner machine):**** OS/browser set to Kannada and to Hindi
each render the respective language on BOTH surfaces, with Noto fonts displaying.

160 - [] **`en + kn + hi` catalogs live and ****rendering**** on BOTH `web/` SPA and `site/`**
marketing (switcher + persistence + `en` fallback; no raw keys shown).

161 - [] ****Noto Sans Kannada + Devanagari render correctly**** ? owner eyeball on a real
machine.

162 - [] CI ****key-parity + no-bare-strings**** green; a stub locale flags every gap.

163 - [] ****Recording-education**** (capture + homepage gist) available in `kn` + `hi`.

164 - [] ****Non-tech UX baseline:**** plain-language copy (no raw engine jargon in user-facing
strings), mobile-usable touch targets, icon+text, WhatsApp share, honest today-vs-roadmap
preserved through translation.

165 - [] \$7 all rows ? (or explicitly deferred with a reason) ? flip ****Status ? DONE**** +
completion note ? run engine `DOC\_STATUS.md \$2` archival checklist ? `git mv` to
`docs/archives/`.

166

167 **## 10. References**

168 ****Internal code anchors `[verified]`:**** `web/package.json`,
`web/src/{App.tsx,main.tsx,components/QueryBar.tsx,components/CompileResult.tsx,lib/query.ts}`;
`site/public/{index,capture,own-model}.html`, `site/server.js`, `site/src/assets.test.js`.
****This repo's docs:**** `docs/PER\_RALLY\_SELECTION.md`, `docs/REQUEST\_ACCESS\_FORM.md`,

```

`docs/README.md`, `NEXT_STEPS.md`. **Engine design docs (canonical):** `badminton-highlight-indexer/docs/{I18N_PLAN.md,UI_PROPOSAL.md,VIDEO_RECORDING_GUIDELINES.md,PMF_MARKET_RESEARCH.md,PMF_F
IELD_SIGNALS.md,KHELSUTRA_PRODUCT_OVERVIEW.md,DOC_STATUS.md}`. **External `[researched]`:**
Unicode CLDR plural rules (kn/hi = one/other); react-i18next + i18next-icu; SIL Open Font
License 1.1; Google Noto Sans Kannada/Devanagari.
169
170 ---
171
172 ### Changelog
173 - `2026-06-21` ? created. Isolated the UX + Hindi/Kannada work into one tracked project
(owner directive). Grounded in a multi-agent research+verification pass (web/+site/ string maps,
Indic-l10n prior art, 5 adversarial verdicts). Decisions D1?D5 locked; 5 product/licensing
decisions surfaced as open; §7 tracker seeded with B1 as the recommended first slice.
174 - `2026-06-21` ? owner locked **D6 (en+kn?hi)** + **D7 (OFL Noto carve-out)** and
adopted **D8 (SPA-first)** + **D9 (catalogs in khelsutra)**; only D-BACKEND-DEPTH remains open.
**B1 greenlit ? ? in progress.**
175 - `2026-06-21` ? **B1 opened ? [#42](https://github.com/avidullu/khelsutra/pull/42)**:
SPA i18n scaffold (react-i18next + ICU + detector) + `en` catalog + language switcher + the
SPA's first jsdom render tests. Verified typecheck/79-tests/build green + live in-browser
(switcher persists, en-fallback). Doc/pointer PRs opened: khelsutra
[#41](https://github.com/avidullu/khelsutra/pull/41), engine
[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275).
176 - `2026-06-21` ? **§6.5 Testing strategy added (owner ask, #41):** a rigorous
**automatic-negotiation matrix** (N1?N9) so a Kannada/Hindi **browser** auto-gets the respective
version ? proven at the detection level now (B1), at the content level with the catalogs
(B5/B6), on the static shim (B3), and by a manual font-render eyeball. Wired into the DoD (§9).
B1 (#42) gains the detection tests (N1/N3?N7).
177 - `2026-06-21` ? **A8 (#63) landed.** Background-processing reassurance + status as
icon+text chips (never icon-only): a new `StatusChip` + shared `Spinner`; IngestPanel processing
shows a working chip + "safe to wait ? runs on the server" line and a ? "Couldn't process" chip
on failure; CompileResult gains a "Stitching your reel?" building card + ?? status icons on the
terminal card (now `aria-live`). 141 web tests green; reviewed via a 2-lens adversarial workflow
(folded its aria-live + honest-copy findings). **Workstream A now: A1/A4/A5/A8 ?; remaining A9
(tap-only filters), A3 (recording-education kn/hi).**
178 - `2026-06-21` ? **A5 (#62) landed.** Friendly engine-error mapping unified across ALL
SPA surfaces (ingest + build + rally-load) via a single `lib/errorText.ts` helper + a shared
`errors.` catalog namespace: an `engine` failure shows the engine's own detail verbatim,
everything else a localized line (`engineGeneric` last resort). No more raw `ApiError`/`HTTP
500` text; `build.failed`/`rallies.load_failed` logs gain `code`+`detail`. 136 web tests green;
reviewed via a 2-lens adversarial workflow (folded its load-path consolidation nit).
179 - `2026-06-21` ? **A1 (#60) + A4 (#61) landed.** A1 = the plain-language `en` copy pass
(de-jargon). A4 = the non-tech / phone-first pass: ?44px tap targets across the SPA (Tailwind
`min-h-11`/`h-11`), enlarged parsed-pill + sample chips, and **hover-only `title=` text surfaced
as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence)
? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.
**Still open in workstream A:** A5 (friendly engine-error map on the build path), A8
(background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-
education kn/hi), B3 (site/ trilingual) + native review.
180 - `2026-06-21` ? **? SPA MILESTONE: fully trilingual (owner directive "take it to
completion + screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ?
B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all
merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity.
**Playwright screencast** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ?
switch hi ? switch en, each with `<html lang>` tracked (`khelsutra-i18n-screencast.mp4` + per-
locale frames). kn/hi are **AI-drafted ? native review pending**. **Remaining for full §9 DoD:**
B3 (the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.
181

```

5. assistant (2026-06-21T17:07:31.066Z)

Now let me check what's on `origin/master` (to resolve the catalog-contention question) and read the key implementation files.

6. user (2026-06-21T17:07:33.843Z)

```

=== origin/master log ===
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*
tunnel + CF Access) (#65)
8bbc557 feat(web): VITE_API_BASE ? let the SPA target a split api.* origin (default same-origin
/api) (#64)
92a6c45 feat(web): A8 ? background-processing reassurance + icon+text status chips (#63)
501c014 feat(web): A5 ? friendly engine-error mapping across build + load (shared errors.*)
(#62)
95195a5 feat(web): A4 ? mobile touch targets (?44px) + visible tooltip text (#61)
ccdcfcd feat(web): A1 ? plain-language copy pass on the en catalog (de-jargon) (#60)
a20002f docs: propose Multilingual Expansion ? 7 new locales (th/id/da/es/zh-Hans/ja/ko) (#58)

=== is es/da/id merged to origin/master? ===
a20002f docs: propose Multilingual Expansion ? 7 new locales (th/id/da/es/zh-Hans/ja/ko) (#58)
113587f docs: set the dry-run CUJ as a tracked goal (UI drives a bucket video -> reel download,
multilingual) (#53)
631c3aa docs(friendly-multilingual): SPA fully trilingual ? mark B1/B2/B4/B5/B6 done +
screencast milestone (#49)

=== diff current branch vs origin/master ===
4b8937d docs(mlx): mark Phase A (es/da/id) shipped (#67) in $7 tracker + changelog
e873db3 feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#58)

```

7. user (2026-06-21T17:07:34.098Z)

```

1      // i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
2      //
3      // Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4      //   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5      //   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in
the catalog,
6      //     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7      //   - one negotiation order shared with the marketing site (B3);
8      //   - always-fallback to `en` so a missing translation degrades to English, never a raw
key.
9      import i18n from "i18next";
10     import { initReactI18next } from "react-i18next";
11     import LanguageDetector from "i18next-browser-languagedetector";
12     import ICU from "i18next-icu";
13     import enCommon from "./locales/en/common.json";
14     import knCommon from "./locales/kn/common.json";
15     import hiCommon from "./locales/hi/common.json";
16     import esCommon from "./locales/es/common.json";
17     import daCommon from "./locales/da/common.json";
18     import idCommon from "./locales/id/common.json";
19
20     // Supported locales: en/kn/hi foundation (FRIENDLY D6) + MULTILINGUAL_EXPANSION Phase A
(es/da/id,
21     // Latin, catalog-only). Anything else falls back to `en`.
22     export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
23     export type Locale = (typeof SUPPORTED_LOCALES)[number];
24     export const DEFAULT_LOCALE: Locale = "en";
25
26     // ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker
B3), so a
27     // visitor's language choice carries across both surfaces.
28     export const LANG_STORAGE_KEY = "khelesutra.lang";
29
30     // Catalogs are co-located here (D9). `kn` + `hi` shipped (B5/B6, AI-drafted ? native
review
31     // pending). A missing key in any locale still falls back to `en` ? the by-design
invariant.
32     const resources = {
33       en: { common: enCommon },

```

```

34     kn: { common: knCommon },
35     hi: { common: hiCommon },
36     es: { common: esCommon },
37     da: { common: daCommon },
38     id: { common: idCommon },
39   } as const;
40
41   void i18n
42     .use(ICU)
43     .use(LanguageDetector)
44     .use(initReactI18next)
45     .init({
46       resources,
47       fallbackLng: DEFAULT_LOCALE,
48       supportedLngs: [...SUPPORTED_LOCALES],
49       nonExplicitSupportedLngs: true, // en-IN -> en
50       defaultNS: "common",
51       ns: ["common"],
52       interpolation: { escapeValue: false }, // React already escapes
53       returnNull: false,
54       // Negotiation order (I18N_PLAN §2.3): persisted pref -> ?lang= -> browser -> en.
55       detection: {
56         order: ["localStorage", "querystring", "navigator"],
57         lookupLocalStorage: LANG_STORAGE_KEY,
58         lookupQuerystring: "lang",
59         caches: ["localStorage"],
60       },
61       react: { useSuspense: false },
62     });
63
64   // Keep <html lang> in sync with the active locale (screen readers + SEO use it).
Reflects the
65   // resolved content language, so an `en` fallback for an absent locale still reads as
`en`.
66   function syncDocumentLang(lng: string) {
67     if (typeof document !== "undefined") {
68       document.documentElement.lang = (i18n.resolvedLanguage || lng ||
DEFAULT_LOCALE).split("-")[0];
69     }
70   }
71   i18n.on("languageChanged", syncDocumentLang);
72   syncDocumentLang(i18n.language ?? DEFAULT_LOCALE);
73
74   export default i18n;
75

```

8. assistant (2026-06-21T17:08:02.117Z)

Key finding on catalog contention: ****es/da/id have NOT merged to `origin/master`**** ?
`origin/master` HEAD is `ca619fb` (#66); the es/da/id catalogs only exist on this local branch
`feat/mlx-phaseA-es-da-id` (2 unmerged commits). Per the owner's instruction, since the
MULTILINGUAL_EXPANSION PR hasn't merged, B3 hoists ****only en/kn/hi****.

Let me read the remaining required files and inspect the locale + site structure (all from the
perspective of what's on master).

9. user (2026-06-21T17:08:02.271Z)

```

1   // CI guardrails that keep i18n "by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
2   //   1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
3   //     drop a stub locale and this lists every gap). Trivially green while only `en`
exists; it
4   //     starts enforcing the moment a kn/hi catalog lands (B5/B6).
5   //   2. NO-BARE-STRINGS (attribute level, v1) ? user-facing component attributes

```

```

(placeholder /
6      //      aria-label / title) must route through t(), never a hardcoded literal. A curated
start per
7      //      the doc; an AST-level sweep of JSX text can extend it later.
8      import { describe, it, expect } from "vitest";
9      import { readdirSync, readFileSync } from "node:fs";
10     import { join } from "node:path";
11
12     const LOCALES_DIR = join(import.meta.dirname, "locales");
13     const SRC_DIR = join(import.meta.dirname, "..");
14
15     function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
16         const keys: string[] = [];
17         for (const [k, v] of Object.entries(obj)) {
18             const key = prefix ? `${prefix}.${k}` : k;
19             if (v && typeof v === "object" && !Array.isArray(v)) keys.push(...flatten(v as
Record<string, unknown>, key));
20             else keys.push(key);
21         }
22         return keys.sort();
23     }
24
25     const loadKeys = (locale: string): string[] =>
26         flatten(JSON.parse(readFileSync(join(LOCALES_DIR, locale, "common.json"), "utf8")) as
Record<string, unknown>);
27
28     describe("i18n key-parity ? every locale has EXACTLY the en keys", () => {
29         const enKeys = loadKeys("en");
30         const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
31             .filter((d) => d.isDirectory() && d.name !== "en")
32             .map((d) => d.name);
33
34         it("en is the non-empty source catalog", () => {
35             expect(enKeys.length).toBeGreaterThan(20);
36         });
37
38         for (const loc of others) {
39             it(`${loc} matches en exactly (no missing, no extra keys)`, () => {
40                 const keys = loadKeys(loc);
41                 const missing = enKeys.filter((k) => !keys.includes(k));
42                 const extra = keys.filter((k) => !enKeys.includes(k));
43                 expect({ locale: loc, missing, extra }).toEqual({ locale: loc, missing: [], extra:
[] });
44             });
45         }
46     });
47
48     // Key-parity proves every locale has the same KEYS; this proves every locale's VALUE
keeps the same
49     // simple `{placeholder}` set as en ? so a translation can never silently drop a
{count}/{error}/{min}/
50     // {filename}/{n}/? and break interpolation. (ICU plural headers like `{count, plural,
?}` carry no
51     // simple {word} placeholder and match as empty on both sides, so they're correctly
ignored.)
52     describe("placeholder parity ? every locale preserves en's {placeholders}", () => {
53         function flatEntries(obj: Record<string, unknown>, prefix = ""): Record<string,
string> {
54             const out: Record<string, string> = {};
55             for (const [k, v] of Object.entries(obj)) {
56                 const key = prefix ? `${prefix}.${k}` : k;
57                 if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(out,
flatEntries(v as Record<string, unknown>, key));
58                 else out[key] = String(v);
59             }

```

```

60     return out;
61 }
62 const placeholders = (s: string) => (s.match(/\{(\w+)\}/g) ?? []).sort();
63 const load = (loc: string) => flatEntries(JSON.parse(readFileSync(join(LOCALES_DIR,
loc, "common.json"), "utf8")));
64 const enE = load("en");
65 const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
66   .filter((d) => d.isDirectory() && d.name !== "en")
67   .map((d) => d.name);
68
69 for (const loc of others) {
70   it(`${loc} preserves every {placeholder} that en uses`, () => {
71     const locE = load(loc);
72     const mismatches: Array<{ key: string; en: string[]; got: string[] }> = [];
73     for (const key of Object.keys(enE)) {
74       if (!(key in locE)) continue; // missing keys are the key-parity test's job
75       const a = placeholders(enE[key]);
76       const b = placeholders(locE[key]);
77       if (a.join(",") !== b.join(",")) mismatches.push({ key, en: a, got: b });
78     }
79     expect(mismatches).toEqual([]);
80   });
81 }
82 });
83
84 describe("es 3-form plural (CLDR one/many/other) ? MULTILINGUAL Phase A", () => {
85   // Spanish cardinal is {one, many, other}; every es ICU plural message MUST carry a
`many` {` arm
86   // (the `many` category fires on large/compact numbers) or intl-messageformat silently
falls back.
87   // These are the plural-bearing keys in the catalog.
88   const es = JSON.parse(readFileSync(join(LOCALES_DIR, "es", "common.json"), "utf8")) as
Record<string, Record<string, string>>;
89   const pluralKeys: Array<[string, string]> = [
90     ["footer", "count"],
91     ["footer", "floorSomeLead"],
92     ["selection", "count"],
93   ];
94   for (const [ns, key] of pluralKeys) {
95     it(`es ${ns}.${key} carries one/many/other arms`, () => {
96       const msg = es[ns][key];
97       expect(msg, `${ns}.${key}`).toMatch(/\\bone\\s*\\{/);
98       expect(msg, `${ns}.${key}`).toMatch(/\\bmany\\s*\\{/);
99       expect(msg, `${ns}.${key}`).toMatch(/\\bother\\s*\\{/);
100     });
101   }
102 });
103
104 describe("no-bare-strings ? user-facing component attributes go through t()", () => {
105   const FILES = [
106     "App.tsx",
107     "components/QueryBar.tsx",
108     "components/RallyGrid.tsx",
109     "components/SelectionFooter.tsx",
110     "components/CompileResult.tsx",
111     "components/LanguageSwitcher.tsx",
112     "components/IngestPanel.tsx",
113   ];
114   // A hardcoded placeholder / aria-label / title with letters is a bare-string
regression ? it
115   // must be an expression ({t(...)}), not a quoted literal.
116   const BARE_ATTR = /\\b(?:placeholder|aria-label|title)\\s*=\\s*"\\^"*[A-Za-z]{2}\\^"*"/g;
117
118   for (const f of FILES) {
119     it(`${f}: no hardcoded placeholder/aria-label/title`, () => {

```

```

120     const src = readFileSync(join(SRC_DIR, f), "utf8");
121     expect(src.match(BARE_ATTR) ?? []).toEqual([]);
122   });
123 }
124 });
125
126 describe("Indic fonts (B4) ? self-hosted OFL Noto, no runtime CDN", () => {
127   it("main.tsx bundles the OFL Noto Kannada + Devanagari fonts (self-hosted, not Google
Fonts)", () => {
128     const main = readFileSync(join(SRC_DIR, "main.tsx"), "utf8");
129     expect(main).toMatch(/@fontsource-variable\/noto-sans-kannada/);
130     expect(main).toMatch(/@fontsource-variable\/noto-sans-devanagari/);
131   });
132   it("the font stack falls back to Noto for Kannada + Devanagari glyphs", () => {
133     const css = readFileSync(join(SRC_DIR, "index.css"), "utf8");
134     expect(css).toMatch(/Noto Sans Kannada Variable/);
135     expect(css).toMatch(/Noto Sans Devanagari Variable/);
136   });
137 });
138
139 // The Studio SPA must render correctly on an AIR-GAPPED appliance (GPU/CPU/RAM, no
internet) ?
140 // every asset (fonts, styles, scripts) is bundled local, nothing pulled from a
CDN/Google Fonts.
141 describe("offline / self-contained ? no external runtime assets", () => {
142   const CDN = /googleapis|gstatic|fonts\.google|cdnjs|unpkg|jsdelivr|bcdn\.[a-z]/i;
143   const FILES = [
144     "../index.html", // web/index.html
145     "main.tsx",
146     "index.css",
147   ];
148   for (const rel of FILES) {
149     it(`${rel}: no external font/CDN reference`, () => {
150       expect(readFileSync(join(SRC_DIR, rel), "utf8")).not.toMatch(CDN);
151     });
152   }
153   it("web/index.html loads no absolute-URL <link>/<script src> (everything is
bundled/local)", () => {
154     const html = readFileSync(join(SRC_DIR, "..", "index.html"), "utf8");
155     expect(html).not.toMatch(/(?:href|src)\s*=\s*["']https?:\/\//i);
156   });
157 });
158

```

10. user (2026-06-21T17:08:03.234Z)

```

1 // Always-on VM host for the KhelSutra site ? dependency-free (Node 22+ only).
2 // Serves public/ and POST /api/request-access into SQLite (node:sqlite), using the
3 // SAME handler logic as the Cloudflare Worker (src/index.js). This is the portability
4 // fallback "if Cloudflare acts out" ? see docs/PORTABILITY.md.
5 //
6 // PORT=8080 DB_PATH=/var/lib/khelsutra/access.db node server.js
7 //
8 import { createServer } from "node:http";
9 import { readFile } from "node:fs/promises";
10 import { join, extname, normalize } from "node:path";
11 import { DatabaseSync } from "node:sqlite";
12 import { handleRequest } from "../src/index.js";
13 import { sqliteStore } from "../src/store.js";
14 import { noopNotify } from "../src/notify.js";
15
16 const PORT = Number(process.env.PORT) || 8080;
17 const ROOT = import.meta.dirname;
18 const PUBLIC = join(ROOT, "public");
19 const DB_PATH = process.env.DB_PATH || join(ROOT, "access.db");

```

```

20
21     const db = new DatabaseSync(DB_PATH);
22     db.exec(await readFile(join(ROOT, "schema.sql"), "utf8")); // CREATE TABLE IF NOT EXISTS
? idempotent
23     const store = sqliteStore(db);
24     const notify = noopNotify(); // VM host: no email yet (add SMTP later ? see
docs/PORTABILITY.md)
25
26     const TYPES = {
27         ".html": "text/html; charset=utf-8", ".png": "image/png", ".svg": "image/svg+xml",
28         ".css": "text/css", ".js": "text/javascript", ".ico": "image/x-icon", ".txt":
"text/plain",
29         ".mp4": "video/mp4", ".webm": "video/webm", ".gif": "image/gif", ".jpg": "image/jpeg",
".jpeg": "image/jpeg",
30     };
31
32     async function toRequest(req) {
33         const url = `http://${req.headers.host || "localhost"}${req.url}`;
34         let body;
35         if (req.method !== "GET" && req.method !== "HEAD") {
36             const chunks = [];
37             for await (const c of req) chunks.push(c);
38             body = Buffer.concat(chunks);
39         }
40         return new Request(url, { method: req.method, headers: req.headers, body });
41     }
42
43     async function send(res, response) {
44         res.statusCode = response.status;
45         for (const [k, v] of response.headers) res.setHeader(k, v);
46         res.end(Buffer.from(await response.arrayBuffer()));
47     }
48
49     async function serveStatic(pathname, res) {
50         const rel = pathname === "/" ? "index.html"
51             : pathname === "/capture" ? "capture.html"
52             : pathname === "/own-model" ? "own-model.html"
53             : pathname === "/flyer" ? "flyer.html"
54             : pathname === "/flyer-kn" ? "flyer-kn.html"
55             : pathname === "/flyer-hi" ? "flyer-hi.html"
56             : pathname.replace(/^\/+/, "");
57         const file = normalize(join(PUBLIC, rel));
58         if (!file.startsWith(PUBLIC)) { res.statusCode = 403; return res.end("forbidden"); }
59         try {
60             const data = await readFile(file);
61             res.setHeader("content-type", TYPES[extname(file)] || "application/octet-stream");
62             res.end(data);
63         } catch {
64             res.statusCode = 404;
65             res.end("not found");
66         }
67     }
68
69     createServer(async (req, res) => {
70         try {
71             const pathname = decodeURIComponent(new URL(`http://x${req.url}`).pathname);
72             if (pathname === "/api/request-access") {
73                 if (req.method !== "POST") { res.statusCode = 405; return
res.end('{"ok":false,"error":"method not allowed"}'); }
74                 return await send(res, await handleRequest(await toRequest(req), store, notify));
75             }
76             return await serveStatic(pathname, res);
77         } catch (err) {
78             res.statusCode = 500;
79             res.end('{"ok":false,"error":"server error"}');

```

```

80     console.error(err);
81   }
82   }).listen(PORT, () => console.log(`khelsutra site listening on :${PORT} (sqlite:
${DB_PATH})`));
83

```

11. user (2026-06-21T17:08:03.279Z)

```

1    // Static-site integrity ? the landing page + capture checklist + OG image ARE the
public
2    // product. server.test.js proves the VM host *serves* "/", "/capture", "/og.png"; this
3    // guards the CONTENT contract so a broken edit (deleted asset, broken form wiring, dead
4    // capture link, missing/!absolute OG image) fails CI instead of shipping to the live
site.
5    import { test } from "node:test";
6    import assert from "node:assert/strict";
7    import { readFileSync, statSync } from "node:fs";
8    import { join } from "node:path";
9
10   const PUBLIC = join(import.meta.dirname, "..", "public");
11   const read = (f) => readFileSync(join(PUBLIC, f), "utf8");
12   const size = (f) => statSync(join(PUBLIC, f)).size;
13
14   test("core public assets exist and are non-empty", () => {
15     for (const f of ["index.html", "capture.html", "og.png"]) {
16       assert.ok(size(f) > 0, `public/${f} is missing or empty`);
17     }
18   });
19
20   test("landing page wires the Request-Access form to the API", () => {
21     const html = read("index.html");
22     assert.match(html, /id="af"/, "the #af form is gone");
23     assert.match(html, /\api\/request-access/, "form no longer posts to /api/request-
access");
24     assert.match(html, /name="company"[^>]*tabindex="-1"/, "honeypot field removed (bots
will get through)");
25     for (const field of ["segment", "has_gpu", "storage"]) {
26       assert.match(html, new RegExp(`name="${field}"`), `form lost the '${field}' field (a
demand signal)`);
27     }
28   });
29
30   test("submitting the form shows an obvious in-flight state (no silent freeze)", () => {
31     const html = read("index.html");
32     assert.match(html, /Sending?/, "submit should swap to a 'Sending?' state while the
request is in flight");
33     assert.match(html, /aria-busy/, "submit should set aria-busy for assistive tech during
the request");
34     assert.match(html, /class="spin"/, "the in-flight spinner is gone");
35     assert.match(html, /\spin\{/, "the spinner style is gone");
36     // the button must be RE-ENABLED on failure so the user isn't stuck on a frozen
'Sending?'
37     assert.match(html, /btn\.disabled\s*=\s*false/, "submit button isn't restored on the
failure path");
38   });
39
40   test("OG + canonical meta point at the live https origin", () => {
41     const html = read("index.html");
42     assert.match(html,
/property="og:image"\s+content="https:\/\/khelsutra.guru\/og.png"/, "og:image must be the
absolute live URL");
43     assert.match(html, /property="og:url"\s+content="https:\/\/khelsutra.guru"/, "og:url
drift");
44   });
45

```

```

46     test("the sample reel is GATED behind sign-up + starts at a RANDOM point (not shown
openly)", () => {
47         const html = read("index.html");
48         assert.match(html, /ajTCZ7pJW_o/, "the sample-reel video id is gone");
49         assert.match(html, /youtube-nocookie\.com/, "reel should use the privacy nocookie
host");
50         assert.match(html, /id="reel-reveal"/, "the on-signup reveal host is gone");
51         assert.match(html, /see it in action/i, "the 'see it in action' sign-up teaser is
gone");
52         assert.match(html, /reel-count/, "the auto-close countdown is gone");
53         assert.match(html, /REEL_SECS = 30/, "the reel preview should be ~30s");
54         assert.match(html, /getDuration\(\)/, "random start should derive from the real video
duration");
55         assert.match(html, /Math\.random\(\)/, "the start point should be randomized");
56         assert.match(html, /seekTo\(/, "the player should seek to the random start");
57         // Must NOT be an openly-rendered public section ? it only appears after a successful
submit.
58         assert.doesNotMatch(html, /<section id="reel"/, "the reel must be sign-up-gated, not
an open public section");
59         assert.doesNotMatch(html, /id="reel-play"/, "the open click-to-play facade should be
removed");
60     });
61
62     test("the TOOL screencast is self-hosted, footage-free, and revealed only after sign-
up", () => {
63         const html = read("index.html");
64         assert.match(html, /\video\tool-cuj\.mp4/, "the tool-operation screencast reference
is gone");
65         assert.match(html, /function revealAfterSignup/, "the post-signup reveal function is
gone");
66         assert.match(html, /revealAfterSignup\(\)/, "the reveal must be wired to a successful
submit");
67         // GATED: the only reference to the tool screencast lives inside the reveal function
(injected on
68         // signup), not as an open autoplay element rendered for every visitor.
69         assert.ok(
70             html.indexOf("/video/tool-cuj.mp4") > html.indexOf("function revealAfterSignup"),
71             "the tool screencast must be inside the post-signup reveal, not shown openly",
72         );
73         // the self-hosted clip exists and is non-trivial (a real recording, not an empty
placeholder)
74         assert.ok(size("video/tool-cuj.mp4") > 50_000, "tool-cuj.mp4 is missing or too small
to be the real screencast");
75     });
76
77     test("the post-signup reveal keeps its watchability affordances (manual close + play-
gated auto-close)", () => {
78         // Content contract only ? the BEHAVIOUR (close works, auto-close holds while the reel
plays) is
79         // proven against the real page in ux.dom.test.js, so we don't pin brittle
implementation strings.
80         const html = read("index.html");
81         assert.match(html, /id="reel-close"/, "the manual ? close button is gone");
82         assert.match(html, /onStateChange/, "the reel's play-state must still gate the auto-
close");
83     });
84
85     test("the capture checklist is linked and is a real page", () => {
86         assert.match(read("index.html"), /href="\capture\(\.html)?"/, "footer capture-
checklist link is gone");
87         const cap = read("capture.html");
88         assert.match(cap, /<html/i, "capture.html is not HTML");
89         assert.match(cap, /capture checklist/i, "capture.html lost its checklist content");
90     });
91

```

```

92     test("the academy flyers (en/kn/hi) exist, are language-correct, and are linked from the
homepage", () => {
93         const html = read("index.html");
94         // All three are linked from the homepage footer (the owner ask: the flyers must be
findable).
95         assert.match(html, /href="\ flyer"/, "homepage doesn't link the English academy
flyer");
96         assert.match(html, /href="\ flyer-kn"/, "homepage doesn't link the Kannada academy
flyer");
97         assert.match(html, /href="\ flyer-hi"/, "homepage doesn't link the Hindi academy
flyer");
98
99         // The three flyer pages exist, are HTML, and carry the right language + script.
100        const en = read("flyer.html");
101        assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");
102        const kn = read("flyer-kn.html");
103        assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
104        assert.match(kn, /[? -?]/, "flyer-kn.html should contain Kannada text");
105        const hi = read("flyer-hi.html");
106        assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
107        assert.match(hi, /[? -?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
108    });
109
110    test("each flyer shows a screenshot of the tool rendered in that language", () => {
111        for (const [flyer, img] of [
["flyer.html", "studio-en.png"],
["flyer-kn.html", "studio-kn.png"],
["flyer-hi.html", "studio-hi.png"]
]) {
112            assert.ok(size(`img/${img}`) > 0, `public/img/${img} (the localized UI shot) is
missing or empty`);
113            assert.match(read(flyer), new RegExp(`/img/${img}`), `${flyer} should embed its
localized UI screenshot /img/${img}`);
114        }
115    });
116
117    test("the academy flyers are also linked from the top nav and the own-model page", () =>
{
118        const html = read("index.html");
119        // Desktop top nav carries a Flyer entry (alongside Own your model).
120        const nav = html.match(/<nav class="nav-links"[ \S]*?<\nav>/);
121        assert.ok(nav, "the primary nav block is gone");
122        assert.match(nav[0], /href="\ flyer"/, "the top nav doesn't link the Flyer");
123        // own-model surfaces all three languages.
124        const om = read("own-model.html");
125        assert.match(om, /href="\ flyer"/, "own-model doesn't link the English flyer");
126        assert.match(om, /href="\ flyer-kn"/, "own-model doesn't link the Kannada flyer");
127        assert.match(om, /href="\ flyer-hi"/, "own-model doesn't link the Hindi flyer");
128    });
129
130    test("the landing page surfaces how to record reliably (so users can set up with
confidence)", () => {
131        const html = read("index.html");
132        assert.match(html, /id="record"/, "the 'record it right' section is gone");
133        assert.match(html, /one match, one court/i, "the #1 single-court capture rule should
be on the homepage");
134        // the gist must carry the load-bearing capture cues + a prominent link to the full
checklist
135        for (const cue of [
"/1080p/",
"/30 fps/i,
"/[Aa]udio ON/",
"/baseline/",
"/[Nn]o panning/
]) {
136            assert.match(html, cue, `the recording gist is missing a key cue: ${cue}`);
137        }
138        assert.match(html, /href="\ capture"[^>]*>Full 1-page capture checklist/i, "a
prominent link to the full checklist is gone");
139    });
140
141    test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
142        const html = read("index.html");
143        const m = html.match(/How do I join?<\summary>(<p[ \S]*?<\p>)/);

```

```

144     assert.ok(m, "the 'How do I join?' FAQ is gone");
145     assert.match(m[1], /request access/i, "the join FAQ should send people to the request-
access form");
146     assert.match(m[1], /href="#join"/, "the join FAQ should link to the #join form");
147     assert.doesNotMatch(m[1], /mailto/, "the join FAQ should NOT tell people to email (use
the form)");
148     });
149
150     test("the own-model page exists, is honestly scoped, and is linked from the landing
page", () => {
151         const om = read("own-model.html");
152         assert.ok(om.length > 0, "own-model.html is missing or empty");
153         for (const id of ["annotate", "train", "setup"]) {
154             assert.match(om, new RegExp(`id="${id}"`), `own-model is missing the #${id}
section`);
155         }
156         assert.match(om, /github\.com\/Khelsutra\/rally-annotator/, "the GitHub link to the
annotator is gone");
157         assert.match(om, /Read this honestly/i, "the honest framing fence is gone");
158         assert.match(om, /open pipeline|in build/i, "training must be honestly scoped as in-
build, not one-click");
159         assert.match(om, /name="robots" content="noindex"/, "own-model should be noindex");
160         assert.match(read("index.html"), /href="\own-model"/, "the landing page should link
to /own-model");
161         assert.match(om, /<a href="\>? KhelSutra home<\a>/, "own-model needs an obvious
back-to-home link (not just browser-back)");
162
163         // a ready-made default works without training (keeps non-tech users engaged); BYO-
training is optional
164         assert.match(om, /ready-made default|out of the box|don't have to train/i, "must
reassure a default works without training");
165         assert.match(om, /optional/i, "training your own should be framed as optional");
166
167         // own-model shows the annotation TOOL screenshots (no people) ? real captures, files
present
168         for (const img of ["annotate-enable.png", "annotate-tool.png"]) {
169             assert.match(om, new RegExp(`img/${img}`), `own-model should embed /img/${img}`);
170             assert.ok(size(`img/${img}`) > 0, `public/img/${img} is missing or empty`);
171         }
172         assert.match(om, /<img[^>]+alt="/i, "screenshots must have alt text");
173
174         // the sample REEL stays gated behind request-access ? NOT embedded/playable here, no
footage shown
175         assert.doesNotMatch(om, /<iframe/i, "the reel must NOT be embedded here ? it's gated
behind request-access");
176         assert.doesNotMatch(om, /youtube/i, "no YouTube embed on own-model; the reel is shown
only after request-access");
177         assert.doesNotMatch(om, /i\.yting\.com/, "don't show the video thumbnail (players)
openly");
178         assert.match(om, /sample[\s\S]{0,80}request access|request access[\s\S]{0,80}sample/i,
"point users to request access for a sample output");
179     });
180

```

12. assistant (2026-06-21T17:08:08.934Z)

Let me explore the directory structures: the locales catalogs, the site/ layout, web build config, and existing test files.

13. user (2026-06-21T17:08:11.180Z)

```

=== web/src/i18n/locales ===
web/src/i18n/locales/:
da
en

```

es
hi
id
kn

web/src/i18n/locales/da:
common.json

web/src/i18n/locales/en:
common.json

web/src/i18n/locales/es:
common.json

web/src/i18n/locales/hi:
common.json

web/src/i18n/locales/id:
common.json

web/src/i18n/locales/kn:
common.json

=== repo-root /locales (if any) ===
(no repo-root /locales yet)

=== site/ tree ===
site/access.db
site/make_og.py
site/package-lock.json
site/package.json
site/public/capture.html
site/public/flyer-hi.html
site/public/flyer-kn.html
site/public/flyer.html
site/public/img/annotate-enable.png
site/public/img/annotate-tool.png
site/public/img/flyer-qr.svg
site/public/img/studio-en.png
site/public/img/studio-hi.png
site/public/img/studio-kn.png
site/public/index.html
site/public/og.png
site/public/own-model.html
site/public/video/tool-cuj.mp4
site/README.md
site/schema.sql
site/scripts/droplet-smoke.sh
site/scripts/parity-check.sh
site/scripts/provision-vm.sh
site/scripts/teardown-vm.sh
site/server.js
site/src/assets.test.js
site/src/deploy-config.test.js
site/src/index.js
site/src/index.test.js
site/src/notify.js
site/src/server.test.js
site/src/store.js
site/src/ux.dom.test.js
site/wrangler.toml

14. assistant (2026-06-21T17:08:16.810Z)

The working tree (on the unmerged es/da/id branch) has 6 locales, but I need to work from

`origin/master`. Let me confirm exactly what locales and i18n files exist on `origin/master`, and read the rest of the site test/build setup.

15. user (2026-06-21T17:08:31.275Z)

```
=== locales on origin/master ===
web/src/i18n/locales/da/common.json
web/src/i18n/locales/en/common.json
web/src/i18n/locales/es/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/id/common.json
web/src/i18n/locales/kn/common.json

=== web/src/i18n files on origin/master ===
web/src/i18n/hygiene.test.ts
web/src/i18n/i18n.test.tsx
web/src/i18n/index.ts
web/src/i18n/locales/da/common.json
web/src/i18n/locales/en/common.json
web/src/i18n/locales/es/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/id/common.json
web/src/i18n/locales/kn/common.json

=== index.ts on origin/master (imports) ===
9:import i18n from "i18next";
10:import { initReactI18next } from "react-i18next";
11:import LanguageDetector from "i18next-browser-languagedetector";
12:import ICU from "i18next-icu";
13:import enCommon from "../locales/en/common.json";
14:import knCommon from "../locales/kn/common.json";
15:import hiCommon from "../locales/hi/common.json";
16:import esCommon from "../locales/es/common.json";
17:import daCommon from "../locales/da/common.json";
18:import idCommon from "../locales/id/common.json";
22:export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
23:export type Locale = (typeof SUPPORTED_LOCALES)[number];
48:  supportedLngs: [...SUPPORTED_LOCALES],
```

16. user (2026-06-21T17:08:31.297Z)

```
1      // [VM/droplet host harness] Boots the REAL server.js (node:http + node:sqlite) and
2      // round-trips it over HTTP ? the same proof we run on the droplet, automated. Keeps the
3      // repo compatible with BOTH hosts: src/index.test.js covers the Cloudflare (Worker+D1)
4      // path; this covers the Node+SQLite path. Run: node --test src/ (or: npm run test:vm)
5      import { test, before, after } from "node:test";
6      import assert from "node:assert/strict";
7      import { spawn } from "node:child_process";
8      import { createServer } from "node:net";
9      import { mkdtempSync, rmSync } from "node:fs";
10     import { tmpdir } from "node:os";
11     import { join } from "node:path";
12     import { DatabaseSync } from "node:sqlite";
13
14     function freePort() {
15       return new Promise((res) => {
16         const s = createServer();
17         s.listen(0, "127.0.0.1", () => { const p = s.address().port; s.close(() => res(p));
18       });
19     }
20     async function waitUp(url, ms = 10000) {
21       const end = Date.now() + ms;
22       while (Date.now() < end) {
23         try { await fetch(url); return; } catch { await new Promise((r) => setTimeout(r,
```

```

150)); }
24     }
25     throw new Error("server.js did not start listening in time");
26 }
27
28 let proc, base, dbPath, dir;
29
30 before(async () => {
31     const port = await freePort();
32     dir = mkdtempSync(join(tmpdir(), "ks-vm-"));
33     dbPath = join(dir, "access.db");
34     base = `http://127.0.0.1:${port}`;
35     const serverPath = join(import.meta.dirname, "..", "server.js");
36     proc = spawn(process.execPath, [serverPath], {
37         env: { ...process.env, PORT: String(port), DB_PATH: dbPath },
38         stdio: "ignore",
39     });
40     await waitUp(`${base}/`);
41 });
42
43 after(() => {
44     proc?.kill();
45     try { rmSync(dir, { recursive: true, force: true }); } catch {}
46 });
47
48 test("[VM host] server.js serves the form", async () => {
49     const html = await (await fetch(`${base}/`)).text();
50     assert.match(html, /id="af"/);
51     assert.match(html, /Get into the KhelSutra alpha/);
52 });
53
54 test("[VM host] serves /capture and /og.png", async () => {
55     assert.equal((await fetch(`${base}/capture`)).status, 200);
56     assert.equal((await fetch(`${base}/og.png`)).status, 200);
57 });
58
59 test("[VM host] serves the tool screencast as video/mp4 (plays in the post-signup
reveal)", async () => {
60     const res = await fetch(`${base}/video/tool-cuj.mp4`);
61     assert.equal(res.status, 200);
62     assert.equal(res.headers.get("content-type"), "video/mp4"); // not octet-stream ?
63     <video> can play it
64 });
65
66 test("[VM host] serves /own-model", async () => {
67     const res = await fetch(`${base}/own-model`);
68     assert.equal(res.status, 200);
69     assert.match(await res.text(), /Train a model that's yours/);
70 });
71
72 test("[VM host] serves the academy flyers (/flyer, /flyer-kn, /flyer-hi) as clean URLs",
async () => {
73     // Cloudflare maps these via asset html-handling; the VM host needs explicit routes so
the
74     // footer links work on BOTH hosts (parity).
75     for (const path of ["/flyer", "/flyer-kn", "/flyer-hi"]) {
76         const res = await fetch(`${base}${path}`);
77         assert.equal(res.status, 200, `${path} should serve 200 on the VM host`);
78         assert.match(res.headers.get("content-type"), /text\/html/, `${path} should serve
HTML`);
79         assert.match(await res.text(), /<html/i, `${path} should be an HTML page`);
80     }
81 });
82
83 test("[VM host] POST /api/request-access persists to SQLite", async () => {

```

```

83     const res = await fetch(`${base}/api/request-access`, {
84       method: "POST",
85       headers: { "content-type": "application/json" },
86       body: JSON.stringify({ segment: "academy", email: "harness@khelsutra.guru", has_gpu:
"yes", storage: ["gdrive", "bucket"], consent: true }),
87     });
88     assert.equal(res.status, 200);
89     assert.deepEqual(await res.json(), { ok: true });
90
91     const db = new DatabaseSync(dbPath);
92     const row = db.prepare("SELECT email, segment, has_gpu, storage, consent FROM
access_requests").get();
93     assert.equal(row.email, "harness@khelsutra.guru");
94     assert.equal(row.segment, "academy");
95     assert.equal(row.has_gpu, "yes");
96     assert.equal(row.storage, "gdrive,bucket");
97     assert.equal(row.consent, 1);
98   });
99
100  test("[VM host] honeypot + bad email are rejected without persisting", async () => {
101    const bot = await fetch(`${base}/api/request-access`, {
102      method: "POST", headers: { "content-type": "application/json" },
103      body: JSON.stringify({ email: "x@y.co", company: "spam" }),
104    });
105    assert.equal(bot.status, 200); // dropped silently
106    const bad = await fetch(`${base}/api/request-access`, {
107      method: "POST", headers: { "content-type": "application/json" },
108      body: JSON.stringify({ email: "nope" }),
109    });
110    assert.equal(bad.status, 400);
111
112    const db = new DatabaseSync(dbPath);
113    const { n } = db.prepare("SELECT COUNT(*) AS n FROM access_requests").get();
114    assert.equal(n, 1); // only the valid submission above
115  });
116
117  test("[VM host] GET /api/request-access -> 405", async () => {
118    assert.equal((await fetch(`${base}/api/request-access`)).status, 405);
119  });
120

```

17. user (2026-06-21T17:08:31.303Z)

```

1    {
2      "name": "khelsutra-site",
3      "private": true,
4      "type": "module",
5      "scripts": {
6        "test": "node --test",
7        "test:cf": "node --test src/index.test.js",
8        "test:vm": "node --test src/server.test.js",
9        "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10       "deploy": "wrangler deploy",
11       "dev": "wrangler dev",
12       "og": "python make_og.py"
13     },
14     "devDependencies": {
15       "jsdom": "^29.1.1"
16     }
17   }
18

```

18. assistant (2026-06-21T17:08:53.868Z)

Wait ? there's a contradiction I must resolve before deciding what to hoist: `git log` says the

es/da/id feat commit is *ahead* of `origin/master`, yet `git ls-tree origin/master` *shows* es/da/id locale files. Let me pin this down exactly.

19. user (2026-06-21T17:09:11.915Z)

```
=== which commit introduced es/common.json (all branches) ===
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
e873db3 feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#58)

=== is es/common.json in origin/master tree? ===
YES - es exists on origin/master

=== origin/master HEAD sha ===
a2292ef08cd4ef602c5c5ec23a52825ece033707

=== does e873db3 ancestor of origin/master? ===
NO e873db3 NOT in origin/master

=== git log origin/master touching es locale ===
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
```

20. assistant (2026-06-21T17:09:38.191Z)

The picture just changed: `origin/master` HEAD is now **a2292ef** = "MULTILINGUAL Phase A ? es/da/id catalogs (#67)" ? **the expansion HAS merged to master** (my earlier read of `ca619fb` was stale; a fetch/sibling-merge advanced it). Per the owner's instruction, since it **has merged ? hoist all 6 locales**. The MLX task is now merged (not running concurrently), so B3 is safe to proceed.

Let me re-fetch to confirm the absolute latest state before branching (concurrency safety).

21. user (2026-06-21T17:09:41.938Z)

```
=== origin/master HEAD (re-confirmed) ===
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
ca619fb feat(web): T4 ? in-UI file upload (the runnable-tool keystone) (#66)
4627830 docs(deploy): alpha deploy kit ? make Studio a shareable page (split: Pages + api.*
tunnel + CF Access) (#65)

=== locales on origin/master (re-confirmed) ===
web/src/i18n/locales/da/common.json
web/src/i18n/locales/en/common.json
web/src/i18n/locales/es/common.json
web/src/i18n/locales/hi/common.json
web/src/i18n/locales/id/common.json
web/src/i18n/locales/kn/common.json

=== any open MLX-related remote branches? ===
origin/docs/friendly-multilingual-project
origin/docs/friendly-multilingual-spa-done
origin/docs/multilingual-expansion-proposal
origin/feat/mlx-phaseA-es-da-id
```

22. assistant (2026-06-21T17:10:17.395Z)

Confirmed and stable: `origin/master` = **a2292ef** with all 6 locales (en/kn/hi/es/da/id); MLX expansion #67 has merged. **Decision: hoist all 6 locales.** Now let me read the web build/test config and catalog structure to choose the cleanest re-pointing approach, and set up task tracking.

23. user (2026-06-21T17:10:21.072Z)

```
=== web/ config files ===
web/package-lock.json
```

```
web/package.json
web/tsconfig.json
web/vite.config.ts
(no root package.json/lockfile)
```

=== git tracked root-level ===

```
.gitattributes
.github
.gitignore
NEXT_STEPS.md
README.md
deploy
docs
site
web
```

24. user (2026-06-21T17:10:21.699Z)

```
1      import { defineConfig } from "vitest/config";
2      import react from "@vitejs/plugin-react";
3      import tailwindcss from "@tailwindcss/vite";
4
5      // The SPA makes SAME-ORIGIN relative `/api/*` calls. In the appliance (prod) a reverse
6      // proxy serves the SPA and proxies `/api` to the engine on 127.0.0.1:8000
7      // (docs/LOCAL_APPLIANCE_ARCHITECTURE.md). In dev, Vite proxies `/api` to the local
engine
8      // (`python -m backend.main --server`, :8000). Override with VITE_ENGINE_ORIGIN if
needed.
9      export default defineConfig({
10         plugins: [react(), tailwindcss()],
11         server: {
12             proxy: {
13                 "/api": { target: "http://localhost:8000", changeOrigin: true },
14             },
15         },
16         test: {
17             // Default env is node (the pure lib/parser tests); the i18n render test opts into
jsdom via a
18             // `/// @vitest-environment jsdom` docblock. Match .test.tsx too so render tests are
discovered.
19             environment: "node",
20             include: ["src/**/*.test.{ts,tsx}"],
21             // DOM-env localStorage polyfill (jsdom under Node 26 ships none); node-env files
no-op.
22             setupFiles: ["src/test/setup.ts"],
23         },
24     });
25
```

25. user (2026-06-21T17:10:21.968Z)

```
1      {
2          "name": "khelsutra-web",
3          "private": true,
4          "version": "0.0.0",
5          "type": "module",
6          "description": "KhelSutra Studio ? operator console SPA (drives the rally indexer
engine).",
7          "scripts": {
8              "dev": "vite",
9              "build": "vite build",
10             "preview": "vite preview",
11             "typecheck": "tsc --noEmit",
12             "test": "vitest run"
13         },
```

```

14     "dependencies": {
15       "@fontsource-variable/noto-sans-devanagari": "^5.2.8",
16       "@fontsource-variable/noto-sans-kannada": "^5.2.9",
17       "i18next": "^26.3.1",
18       "i18next-browser-languagedetector": "^8.2.1",
19       "i18next-icu": "^2.4.3",
20       "react": "^19.0.0",
21       "react-dom": "^19.0.0",
22       "react-i18next": "^17.0.8"
23     },
24     "devDependencies": {
25       "@tailwindcss/vite": "^4.0.0",
26       "@testing-library/dom": "^10.4.1",
27       "@testing-library/react": "^16.3.2",
28       "@types/node": "^26.0.0",
29       "@types/react": "^19.0.0",
30       "@types/react-dom": "^19.0.0",
31       "@vitejs/plugin-react": "^4.3.4",
32       "jsdom": "^29.1.1",
33       "tailwindcss": "^4.0.0",
34       "typescript": "^5.7.0",
35       "vite": "^6.0.0",
36       "vitest": "^3.0.0"
37     }
38   }
39

```

26. assistant (2026-06-21T17:13:03.805Z)

`origin/master` is stable at a2292ef (all 6 locales). No root workspace ? `web/` and `site/` are independent npm projects, and Vite's workspace-root detection will find `.git` at repo root (so importing `~/locales` from `web/` is permitted). Let me read the catalog, the SPA negotiation test, tsconfig, and the marketing HTML before finalizing the design.

27. user (2026-06-21T17:13:04.463Z)

```

1      // @vitest-environment jsdom
2      //
3      // The SPA had NO render tests before this (verified) ? this file adds the jsdom safety
net for the
4      // i18n scaffold (tracker B1): real copy renders from the catalog, the switcher persists
the choice,
5      // missing-locale falls back to English, and ICU plurals format. It mounts the real <App
/>.
6      import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
7      import { render, screen, cleanup, fireEvent } from "@testing-library/react";
8      import i18n, { LANG_STORAGE_KEY } from "../index";
9      import App from "../App";
10
11      beforeEach(async () => {
12        // No engine in the test env: stub fetch so App's getConfig()/listRallies effects
reject quietly
13        // (App handles this gracefully ? cfg stays null) instead of hitting the network.
14        vi.stubGlobal("fetch", vi.fn(() => Promise.reject(new Error("no engine in test"))));
15        window.localStorage.clear();
16        await i18n.changeLanguage("en"); // also guarantees init completed before the first
render
17      });
18
19      afterEach(() => {
20        cleanup();
21        vi.unstubAllGlobals();
22      });
23
24      describe("i18n scaffold (B1)", () => {

```

```

25     it("renders user-facing copy from the en catalog (not raw keys)", () => {
26         render(<App />);
27         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("Pick the rallies
for your reel");
28         expect(screen.getByRole("button", { name: "Select all" })).toBeTruthy();
29     });
30
31     it("B2: the extracted component strings render (no leftover raw keys across the
page)", () => {
32         const { container } = render(<App />);
33         expect(screen.getByRole("button", { name: "Apply" })).toBeTruthy(); // QueryBar
34         expect(screen.getByRole("button", { name: /Build reel/ })).toBeTruthy(); //
SelectionFooter
35         expect(container.textContent).toContain("rally length"); // <Trans> hero intro +
query support
36         expect(container.textContent).toMatch(/\\d+ rallies selected · \\d+:\\d+ total/); //
ICU footer summary
37         expect(container.textContent).toMatch(/Rally \\d+/); // RallyGrid card
38         // No untranslated catalog keys leaked into the DOM.
39         expect(container.textContent).not.toMatch(/\\b(app|grid|footer|query|mode|result|buil
d)\\. [a-zA-Z]+/);
40     });
41
42     it("offers a language switcher and persists the choice (persisted pref wins on next
visit)", () => {
43         render(<App />);
44         const knBtn = screen.getByRole("button", { name: "?????" });
45         fireEvent.click(knBtn);
46         expect(i18n.language).toBe("kn");
47         expect(window.localStorage.getItem(LANG_STORAGE_KEY)).toBe("kn");
48         expect(knBtn.getAttribute("aria-pressed")).toBe("true"); // highlights the chosen
locale
49         // Switching actually re-renders the page into Kannada (the kn catalog, B5).
50         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("????? ?????????
????????????? ?????");
51     });
52
53     it("B5: switching to Kannada renders the kn catalog (Kannada copy, not English)",
async () => {
54         await i18n.changeLanguage("kn");
55         render(<App />);
56         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("????? ?????????
????????????? ?????");
57         expect(screen.getByRole("button", { name: "?????????" })).toBeTruthy(); // Apply ?
Kannada
58         expect(screen.getByRole("button", { name: "????????? ??????????" })).toBeTruthy(); //
Select all ? Kannada
59         expect(document.documentElement.lang).toBe("kn"); // <html lang> tracks the active
locale (a11y)
60     });
61
62     it("B6: switching to Hindi renders the hi catalog (extensibility proof ? just a
catalog)", async () => {
63         await i18n.changeLanguage("hi");
64         render(<App />);
65         expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("???? ???? ?? ???
??????? ?????");
66         expect(screen.getByRole("button", { name: "???? ??????" })).toBeTruthy(); // Apply ?
Hindi
67         expect(document.documentElement.lang).toBe("hi");
68     });
69
70     it("a locale with no catalog falls back to English (never a raw key)", async () => {
71         await i18n.changeLanguage("ta"); // ta has no catalog
72         render(<App />);

```

```

73     expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("Pick the rallies
for your reel");
74   });
75
76   it("formats ICU plurals from the catalog", () => {
77     expect(i18n.t("selection.count", { count: 1 })).toBe("1 rally selected");
78     expect(i18n.t("selection.count", { count: 3 })).toBe("3 rallies selected");
79   });
80 });
81
82 // The owner's bar (#41): a user whose BROWSER/OS language is Kannada/Hindi must auto-
get the
83 // respective version. These prove the negotiation NOW at the detection level (B1, en-
only); the
84 // kn/hi CONTENT assertions ride the catalogs in B5/B6. See FRIENDLY_AND_MULTILINGUAL.md
$6.5 (N1?N9).
85 describe("browser-language negotiation (B1: N1/N3?N7)", () => {
86   const detectBases = () => {
87     const d = i18n.services.languageDetector.detect();
88     return (Array.isArray(d) ? d : [d]).filter(Boolean).map((l) =>
String(l).split("-")[0]);
89   };
90
91   it("N1/N5: a Kannada browser (kn-IN) is auto-detected as kn for a first-time visitor",
() => {
92     window.localStorage.clear(); // no persisted preference yet
93     vi.stubGlobal("navigator", { language: "kn-IN", languages: ["kn-IN", "en-IN"] });
94     expect(detectBases()).toContain("kn"); // the kn-IN region subtag normalizes to base
kn
95   });
96
97   it("N2: a Hindi browser (hi-IN) is auto-detected as hi (now a supported locale)", ()
=> {
98     window.localStorage.clear();
99     vi.stubGlobal("navigator", { language: "hi-IN", languages: ["hi-IN", "en-IN"] });
100    expect(detectBases()).toContain("hi");
101  });
102
103  it("N4: a persisted preference beats the browser language (returning user keeps their
choice)", () => {
104    window.localStorage.setItem(LANG_STORAGE_KEY, "kn");
105    vi.stubGlobal("navigator", { language: "en-US", languages: ["en-US"] });
106    expect(detectBases()[0]).toBe("kn");
107  });
108
109  it("N3: persisted pref and ?lang are negotiated BEFORE the browser language", () => {
110    const order = i18n.options.detection?.order ?? [];
111    expect(order.indexOf("localStorage")).toBeGreaterThanOrEqual(0);
112    expect(order.indexOf("localStorage")).toBeLessThan(order.indexOf("navigator"));
113    expect(order.indexOf("querystring")).toBeLessThan(order.indexOf("navigator"));
114  });
115
116  it("N6: an unsupported browser language (Tamil) serves English content ? never a
locale we can't render", async () => {
117    window.localStorage.clear();
118    await i18n.changeLanguage("ta"); // ta is not in SUPPORTED_LOCALES
119    render(<App />);
120    expect(screen.getByRole("heading", { level: 1 }).textContent).toBe("Pick the rallies
for your reel");
121  });
122
123  it("N7: a key with no catalog entry falls back to English (no raw key)", async () => {
124    await i18n.changeLanguage("ta"); // ta has no catalog ? keys resolve via
fallbackLng=en
125    expect(i18n.t("app.title")).toBe("Pick the rallies for your reel");

```

```

126         expect(i18n.t("bulk.selectAll")).toBe("Select all");
127     });
128 });
129
130 // MULTILINGUAL_EXPANSION Phase A ? es/da/id render + auto-negotiate, same rigor as
en/kn/hi.
131 // es is the only authoring wrinkle (CLDR 3-form {one, many, other}); da is 2-form; id
is single-form.
132 describe("MULTILINGUAL Phase A (es/da/id)", () => {
133     it("renders each new locale's catalog (real translations, not English / not raw
keys)", async () => {
134         const titles: Record<string, string> = {
135             es: "Elige las jugadas para tu reel",
136             da: "Vælg duellerne til din reel",
137             id: "Pilih reli untuk reel kamu",
138         };
139         for (const [loc, title] of Object.entries(titles)) {
140             await i18n.changeLanguage(loc);
141             cleanup();
142             const { container } = render(<App />);
143             expect(screen.getByRole("heading", { level: 1 }).textContent, loc).toBe(title);
144             expect(container.textContent,
loc).not.toMatch(/\b(app|grid|footer|query|ingest)\.[a-zA-Z]+/); // no raw keys
145         }
146         await i18n.changeLanguage("en");
147     });
148
149     it("es uses the 3-form plural (singular vs plural word forms)", async () => {
150         await i18n.changeLanguage("es");
151         expect(i18n.t("selection.count", { count: 1 })).toBe("1 jugada seleccionada"); //
one
152         expect(i18n.t("selection.count", { count: 2 })).toBe("2 jugadas seleccionadas"); //
other
153         await i18n.changeLanguage("en");
154     });
155
156     it("id is single-form (only an 'other' arm) and still interpolates the count", async
()) => {
157         await i18n.changeLanguage("id");
158         expect(i18n.t("selection.count", { count: 1 })).toBe("1 reli dipilih");
159         expect(i18n.t("selection.count", { count: 5 })).toBe("5 reli dipilih");
160         await i18n.changeLanguage("en");
161     });
162
163     it("auto-negotiates es/da/id from the browser language (region subtags normalize to
base)", () => {
164         for (const [lng, base] of [["es-ES", "es"], ["da-DK", "da"], ["id-ID", "id"]] as
const) {
165             window.localStorage.clear();
166             vi.stubGlobal("navigator", { language: lng, languages: [lng] });
167             const d = i18n.services.languageDetector.detect();
168             const bases = (Array.isArray(d) ? d : [d]).filter(Boolean).map((l) =>
String(l).split("-")[0]);
169             expect(bases, lng).toContain(base);
170         }
171     });
172 });
173

```

28. user (2026-06-21T17:13:05.225Z)

```

1      {
2          "compilerOptions": {
3              "target": "ES2022",
4              "useDefineForClassFields": true,

```

```

5      "lib": ["ES2022", "DOM", "DOM.Iterable"],
6      "module": "ESNext",
7      "skipLibCheck": true,
8
9      "moduleResolution": "bundler",
10     "allowImportingTsExtensions": true,
11     "resolveJsonModule": true,
12     "isolatedModules": true,
13     "moduleDetection": "force",
14     "noEmit": true,
15     "jsx": "react-jsx",
16
17     "strict": true,
18     "noUnusedLocals": true,
19     "noUnusedParameters": true,
20     "noFallthroughCasesInSwitch": true,
21
22     "types": ["vite/client", "node"]
23   },
24   "include": ["src", "vite.config.ts"]
25 }
26

```

29. user (2026-06-21T17:13:05.454Z)

```

1    {
2      "app": {
3        "badge": "pick your rallies · alpha",
4        "title": "Pick the rallies for your reel",
5        "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-
6          tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want."
7      },
8      "lang": {
9        "label": "Language",
10       "en": "English",
11       "kn": "?????",
12       "hi": "?????",
13       "es": "Español",
14       "da": "Dansk",
15       "id": "Bahasa Indonesia"
16     },
17     "bulk": {
18       "selectAll": "Select all",
19       "clear": "Clear",
20       "invert": "Invert"
21     },
22     "mode": {
23       "demo": "These are sample rallies ? process a video above to work on a real match.",
24       "loading": "Finding the rallies in your video?",
25       "error": "Couldn't load this video's rallies: {error}",
26       "loaded": "Found <b>{count}</b> rallies in your video."
27     },
28     "query": {
29       "placeholder": "e.g. over 10s · top 15 longest · shortest first",
30       "ariaLabel": "Filter rallies by length, count or order",
31       "apply": "Apply",
32       "notAvailable": "not available yet",
33       "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
34       "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by
35         rally length instead.",
36       "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
37       "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
38       "try": "Sample queries:",
39       "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
40         <x>experimental</x> (under development)."
41     }
42   }

```

```

38     },
39     "grid": {
40         "empty": "No rallies to show yet.",
41         "rally": "Rally {n}",
42         "inReel": "Rally {n}, in reel",
43         "notInReel": "Rally {n}, not in reel",
44         "start": "start",
45         "long": "long",
46         "shots": "~{count} shots · experimental",
47         "shotsTitle": "Shot count is experimental (under development) and may be
inaccurate{conf}. Filter by rally length instead.",
48         "shotsConfidence": " ? confidence: {conf}"
49     },
50     "footer": {
51         "count": "{count, plural, one {# rally} other {# rallies}}",
52         "summaryRest": "selected · {total} total",
53         "reelName": "Reel name",
54         "reelNamePlaceholder": "my-highlights",
55         "build": "Build reel ({count})",
56         "building": "Building?",
57         "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
be skipped, so the build would fail. Pick a longer rally.",
58         "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
they'd all be skipped, so the build would fail. Pick longer rallies.",
59         "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",
60         "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
61     },
62     "result": {
63         "ready": "Your reel is ready",
64         "failed": "Build failed",
65         "building": "Stitching your reel?",
66         "buildingReassure": "Joining your selected rallies into one video ? this usually
only takes a moment.",
67         "dismiss": "Dismiss",
68         "download": "Download {filename}"
69     },
70     "build": {
71         "noVideo": "These are sample rallies ? process a real video first to build a reel."
72     },
73     "ingest": {
74         "title": "Process a video",
75         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
76         "uriPlaceholder": "gs://your-bucket/match.mp4",
77         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
78         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
79         "submit": "Process video",
80         "submitting": "Submitting?",
81         "cancel": "Cancel",
82         "working": "Processing your video?",
83         "progress": "{progress}",
84         "retry": "Try again",
85         "reassure": "Safe to wait ? KhelSutra keeps working even if your connection is slow;
a long video can take several minutes.",
86         "statusFailed": "Couldn't process",
87         "chooseFile": "Choose a video file",
88         "uploadAria": "Choose a video file to upload",
89         "fileHint": "Pick an .mp4 or .mov from this device ? it uploads, then KhelSutra
finds the rallies.",
90         "orLink": "Or use a cloud link",
91         "uploadingStatus": "Uploading?",
92         "uploadProgress": "Upload progress"
93     },

```

```

94     "errors": {
95         "networkError": "Can't reach KhelSutra. Is it running?",
96         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
97         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
98         "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
99         "engineGeneric": "Something went wrong. Please try again."
100     },
101     "tap": {
102         "title": "Or tap to filter:",
103         "longest": "Longest first",
104         "shortest": "Shortest first",
105         "over10": "Over 10 seconds",
106         "over20": "Over 20 seconds",
107         "top5": "Top 5 longest",
108         "top10": "Top 10 longest"
109     },
110     "selection": {
111         "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
112     }
113 }
114

```

30. assistant (2026-06-21T17:16:13.685Z)

Now I have the full picture. The shared `common.json` is the SPA console catalog; the marketing site has its own copy. Let me read the marketing HTML structure (head, html tag, nav, footer) and the CF Worker to design the switcher + server negotiation correctly.

31. user (2026-06-21T17:16:15.835Z)

```

=== index.html: html tag + head + first nav + body start ===
<!doctype html>
<html lang="en">
<head>
<meta charset="utf-8" />
<meta name="viewport" content="width=device-width, initial-scale=1" />
<title>KhelSutra ? every rally indexed, the dead time gone</title>
<meta name="description" content="KhelSutra turns a full badminton match into a clean index of
rallies with the dead time stripped out ? a highlight reel you can watch and download. Invite-
only alpha, Bengaluru." />
<meta property="og:title" content="KhelSutra ? every rally indexed, the dead time gone" />
<meta property="og:description" content="A full match becomes a clean highlight reel ? only the
real play, no dead time. Invite-only alpha for academies and players in Bengaluru." />
<meta property="og:type" content="website" />
<meta property="og:url" content="https://kheLSutra.guru" />
<meta property="og:image" content="https://kheLSutra.guru/og.png" />
<meta property="og:image:width" content="1200" />
<meta property="og:image:height" content="630" />
<meta name="twitter:card" content="summary_large_image" />
<meta name="twitter:title" content="KhelSutra ? every rally indexed, the dead time gone" />
<meta name="twitter:description" content="A full match becomes a clean highlight reel ? only the
real play, no dead time. Invite-only alpha, Bengaluru." />
<meta name="twitter:image" content="https://kheLSutra.guru/og.png" />
<meta name="theme-color" content="#0C261F" />
<link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg' viewBox='0 0
32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13 10 L23 16 L13
22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
<link rel="preconnect" href="https://fonts.googleapis.com" />
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
<link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&
display=swap" rel="stylesheet" />
<style>

```

```

:root{
  --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
  --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
  --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
  --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
  --r:14px; --rs:10px; --maxw:1080px;
  --font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe UI,Roboto,Helvetica,Arial,sans-
serif;
}
*{box-sizing:border-box}
html{scroll-behavior:smooth}
body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.65;-webkit-font-smoothing:antialiased}
a{color:inherit}
.wrap{max-width:var(--maxw);margin:0 auto;padding:0 22px}
h1,h2,h3{line-height:1.15;margin:0;letter-spacing:-.02em}
h1{font-size:clamp(2rem,5vw,3.4rem);font-weight:800}
h2{font-size:clamp(1.5rem,3.2vw,2.2rem);font-weight:700}
h3{font-size:1.15rem;font-weight:700}
p{margin:.6rem 0}
.btn{display:inline-flex;align-items:center;gap:.5rem;font-weight:600;font-size:1rem;border-
radius:999px;padding:.78rem 1.4rem;text-decoration:none;border:1px solid
transparent;cursor:pointer;transition:.15s}
.btn-primary{background:var(--green);color:#04140D}
.btn-primary:hover{background:var(--green-d)}
.btn-ghost{background:transparent;border-color:rgba(255,255,255,.28);color:var(--on-dark)}
.btn-ghost:hover{border-color:rgba(255,255,255,.6)}
.btn-dark{background:var(--ink);color:#fff}
.btn-dark:hover{background:var(--ink2)}
.btn[disabled]{opacity:.75;cursor:progress}
/* in-flight spinner for the request-access submit */
.spin{display:inline-block;width:1em;height:1em;border:2px solid currentColor;border-right-
color:transparent;border-radius:50%;animation:spin .6s linear infinite}
@keyframes spin{to{transform:rotate(360deg)}}
.eyebrow{display:inline-flex;align-items:center;gap:.5rem;font-size:.82rem;font-
weight:600;letter-spacing:.02em;
background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.3);padding:.3rem .8rem;border-radius:999px}

/* header */
header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
.nav{display:flex;align-items:center;justify-content:space-between;height:66px}
.brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-size:1.18rem;letter-
spacing:-.02em;text-decoration:none}
...=== nav-links block ===
62: .nav-links{display:flex;align-items:center;gap:1.6rem}
63: .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
64: .nav-links a:hover{color:var(--tx)}
205: .nav-links{display:none}
231: <nav class="nav-links" aria-label="Primary">
238: </nav>
581:<footer>
593:</footer>
597:<script defer src="https://static.cloudflareinsights.com/beacon.min.js" data-cf-
beacon='{ "token": "REPLACE_WITH_CF_TOKEN" }'></script>
599:<script>
716:</body>

```

32. assistant (2026-06-21T17:16:26.441Z)

Note: the marketing site uses Google Fonts CDN (lines 21-23) ? that's fine, the airgap/no-CDN rule is SPA-only. Let me read the nav/header/footer regions and the other two pages' heads.

33. user (2026-06-21T17:16:28.311Z)

```

218     .reelwrap iframe{width:100%;height:100%;border:0;display:block}
219     .tool-vid{display:block;width:100%;max-width:680px;margin:.5rem auto 0;border-
radius:14px;border:1px solid var(--line);background:#0C261F}
220     .reveal-h{max-width:680px;margin:1.2rem auto .15rem;font-size:.74rem;font-
weight:700;letter-spacing:.06em;text-transform:uppercase;color:var(--green-d);text-align:left}
221     .reveal-bar{max-width:680px;margin:.2rem auto 0;display:flex;justify-content:flex-end}
222     .reveal-x{background:transparent;border:1px solid var(--line);color:var(--mut);font-
size:.78rem;font-weight:600;padding:.32rem .72rem;border-radius:999px;cursor:pointer}
223     .reveal-x:hover{color:var(--tx);border-color:var(--mut)}
224 </style>
225 </head>
226 <body>
227
228 <header>
229 <div class="wrap nav">
230 <a class="brand" href="#top">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
231 <nav class="nav-links" aria-label="Primary">
232 <a href="#how">How it works</a>
233 <a href="#diff">Why it's hard</a>
234 <a href="/own-model">Own your model</a>
235 <a href="/flyer">Flyer</a>
236 <a href="#roadmap">Roadmap</a>
237 <a href="#faq">FAQ</a>
238 </nav>
239 <a class="btn btn-dark" href="#join">Request access</a>
240 </div>
241 </header>
242
243 <a id="top"></a>
244 <section class="hero" style="padding:0">
245 <div class="wrap hero-grid">
246 <div class="hero-left">
247 <span class="eyebrow">Invite-only alpha . Bengaluru</span>

```

34. user (2026-06-21T17:16:28.783Z)

```

581 <footer>
582 <div class="wrap foot">
583 <div>
584 <div class="brand" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</div>
585 <div class="stamp" style="margin-top:.4rem">Automatic badminton highlights .
Bengaluru, India</div>
586 </div>
587 <div style="text-align:right">
588 <div><a href="/own-model">Own your model</a> . <a href="/capture">Capture
checklist</a> . <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> . <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
589 <div style="margin-top:.4rem">Academy flyer (print): <a href="/flyer"
hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn" lang="kn">?????</a> . <a
href="/flyer-hi" hreflang="hi" lang="hi">??????</a></div>
590 <div class="stamp" style="margin-top:.4rem">© 2026 KhelSutra . Invite-only alpha .
Reels carry a "Generated by Khelsutra.guru" mark</div>
591 </div>
592 </div>
593 </footer>
594
595 <!-- Cloudflare Web Analytics: paste your token from Cloudflare dashboard ? Analytics ?
Web Analytics ? Add a site.
596 (Or skip this snippet entirely and enable "Automatic setup" once the domain is
proxied through Cloudflare.) -->
597 <script defer src="https://static.cloudflareinsights.com/beacon.min.js" data-cf-
beacon="{\"token\": \"REPLACE_WITH_CF_TOKEN\"}"></script>
598

```

```

599     <script>
600     (function(){
601         var f = document.getElementById('af');
602         if(!f) return;
603
604         var REEL_VIDEO = 'ajTCZ7pJW_o', REEL_SECS = 30;
605         function loadYTApi(cb){
606             if(window.YT && window.YT.Player) return cb();
607             var prev = window.onYouTubeIframeAPIReady;
608             window.onYouTubeIframeAPIReady = function(){ if(typeof prev === 'function'){ prev();
        } cb(); };
609             if(!document.getElementById('yt-iframe-api')){
610                 var s = document.createElement('script');
611                 s.id = 'yt-iframe-api'; s.src = 'https://www.youtube.com/iframe_api';
612                 document.head.appendChild(s);
613             }
614         }
615         function revealAfterSignup(){
616             var host = document.getElementById('reel-reveal');
617             if(!host) return;
618             host.hidden = false;
619             // (1) the TOOL in action ? a self-hosted, FOOTAGE-FREE screencast (branded reel
        placeholder),
620             //      so it's safe to autoplay openly; (2) a real reel preview (gated nocookie
        YouTube). BOTH

```

35. assistant (2026-06-21T17:16:33.749Z)

Let me quickly check the heads/nav of capture.html and own-model.html, and the CF Worker (for parity understanding).

36. user (2026-06-21T17:16:36.986Z)

=== capture.html head + html tag + nav ===

```

<!doctype html>
<html lang="en">
<head>
<meta charset="utf-8" />
<meta name="viewport" content="width=device-width, initial-scale=1" />
<title>KhelSutra ? 1-page capture checklist</title>
<meta name="description" content="How to record a badminton session so KhelSutra gives you great
highlight reels: camera placement, settings, stability, lighting." />
<link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg' viewBox='0 0
32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13 10 L23 16 L13
22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
<link rel="preconnect" href="https://fonts.googleapis.com" />
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
<link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&
display=swap" rel="stylesheet" />
<style>
--- capture nav/header ---
2:<html lang="en">
55:<body>
131:</body>

```

=== own-model.html head + html tag ===

```

<!doctype html>
<html lang="en">
<head>
<meta charset="utf-8" />
<meta name="viewport" content="width=device-width, initial-scale=1" />
<title>KhelSutra ? Annotate your footage & train your own model</title>
<meta name="description" content="With KhelSutra you can annotate your own footage and grow a
rally model that's YOURS ? on an open, MIT-licensed stack you control. The free VLC rally-
annotator turns 'watch a match' into golden labels." />

```

```

<meta name="robots" content="noindex" />
<link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg' viewBox='0 0
32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13 10 L23 16 L13
22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
<link rel="preconnect" href="https://fonts.googleapis.com" />
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
<link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&
display=swap" rel="stylesheet" />
--- own-model nav/header ---
2:<html lang="en">
71:<body>
177:</body>

```

37. user (2026-06-21T17:16:37.171Z)

```

1      // Cloudflare Worker for khelsutra.guru ? serves the static site and handles the
2      // Request-Access form: POST /api/request-access -> validate -> insert into D1 (binding
DB).
3      // Pure helpers are exported so they can be unit-tested without a live Worker/D1.
4
5      import { d1Store } from "./store.js";
6      import { cfEmailNotify } from "./notify.js";
7
8      const SEGMENTS = ["academy", "individual"];
9      const GPU = ["yes", "unsure", "no", "prefer-cloud"];
10     const COURTS = ["1", "2-4", "5+"];
11     const STORAGE = ["gdrive", "onedrive", "dropbox", "bucket", "local", "unsure"];
12
13     function str(v, max) {
14         if (v == null) return null;
15         const s = String(v).trim();
16         return s ? s.slice(0, max) : null;
17     }
18
19     // Honeypot: humans never fill the hidden "company" field.
20     export function isBot(p) {
21         return !(p && typeof p.company === "string" && p.company.trim() !== "");
22     }
23
24     export function validate(p) {
25         if (!p || typeof p !== "object") return { ok: false, error: "bad payload" };
26         const email = String(p.email || "").trim();
27         if (!/^^[^@\\s]+@[^@\\s]+\\.^[^@\\s]+$/\\.test(email)) return { ok: false, error: "valid email
required" };
28         return { ok: true };
29     }
30
31     export function toRow(p, meta = {}) {
32         const storage = Array.isArray(p.storage)
33             ? p.storage.filter((s) => STORAGE.includes(s)).join(",")
34             : "";
35         return {
36             segment: SEGMENTS.includes(p.segment) ? p.segment : null,
37             name: str(p.name, 200),
38             email: str(p.email, 320),
39             city: str(p.city, 200),
40             org_name: str(p.org_name, 200),
41             courts: COURTS.includes(p.courts) ? p.courts : null,
42             has_gpu: GPU.includes(p.has_gpu) ? p.has_gpu : null,
43             storage,
44             message: str(p.message, 4000),
45             consent: p.consent ? 1 : 0,
46             country: str(meta.country, 8),
47             user_agent: str(meta.userAgent, 400),
48         };

```

```

49     }
50
51     function json(obj, status = 200) {
52         return new Response(JSON.stringify(obj), { status, headers: { "content-type":
53             "application/json" } });
54     }
55
56     export async function handleRequest(request, store, notify) {
57         let body;
58         try {
59             body = await request.json();
60         } catch {
61             return json({ ok: false, error: "invalid json" }, 400);
62         }
63         if (isBot(body)) return json({ ok: true }); // silently drop bots
64         const v = validate(body);
65         if (!v.ok) return json({ ok: false, error: v.error }, 400);
66
67         const r = toRow(body, {
68             country: request.headers.get("cf-ipcountry"),
69             userAgent: request.headers.get("user-agent"),
70         });
71
72         await store.insertAccessRequest(r);
73         try { await notify?.notify(r); } catch { /* email is best-effort; never fail the
74             request */ }
75
76         return json({ ok: true });
77     }
78
79     export default {
80         async fetch(request, env) {
81             const url = new URL(request.url);
82             if (url.pathname === "/api/request-access") {
83                 if (request.method !== "POST") return json({ ok: false, error: "method not
84                     allowed" }, 405);
85                 return handleRequest(request, d1Store(env.DB), cfEmailNotify(env.NOTIFY,
86                     env.NOTIFY_FROM, env.NOTIFY_TO));
87             }
88             return env.ASSETS.fetch(request); // everything else: static assets
89         },
90     };
91 }

```

38. assistant (2026-06-21T17:17:12.748Z)

I now have everything I need. Key architecture confirmed:

- CF Worker delegates static serving to `env.ASSETS` (no server-side injection on CF) ? so ****server.js (VM host) is where server-side negotiation lives****, and N8 targets it. Client-side shim works on both hosts.
- Marketing pages are en-only-content; the shared `common.json` will gain a `site.\*` namespace (en authored; non-en seeded = en, pending translation) to keep key-parity green.

Let me set up task tracking and create the branch from `origin/master` (branching-safety protocol).

39. user (2026-06-21T17:17:14.192Z)

Task #1 created successfully: Branch feat/b3-site-i18n from origin/master

40. user (2026-06-21T17:17:16.606Z)

Task #2 created successfully: Hoist /locales (all 6) + re-point SPA, keep web tests green

41. user (2026-06-21T17:17:17.944Z)

Task #3 created successfully: Add site.* marketing keys to shared catalogs (en authored, non-en seeded)

42. user (2026-06-21T17:17:20.369Z)

Task #4 created successfully: Add site prebuild copy step + drift-guard test

43. user (2026-06-21T17:17:22.214Z)

Task #5 created successfully: Write site/public/i18n.js shim (t + data-i18n walker + ICU-lite)

44. user (2026-06-21T17:17:24.063Z)

Task #6 created successfully: Add persistent language switcher + data-i18n to index/capture/own-model.html

45. user (2026-06-21T17:17:26.004Z)

Task #7 created successfully: Add server.js Accept-Language negotiation + lang injection

46. user (2026-06-21T17:17:27.890Z)

Task #8 created successfully: Tests: extend assets/server tests + shim unit test + N8 negotiation

47. user (2026-06-21T17:17:29.410Z)

Task #9 created successfully: Update tracker doc, commit, push, open PR

48. assistant (2026-06-21T17:17:35.023Z)

Now let me create the branch and verify HEAD per the branching-safety protocol.

49. user (2026-06-21T17:17:37.162Z)

```
M      web/src/App.tsx
A      web/src/components/TapFilters.test.tsx
A      web/src/components/TapFilters.tsx
M      web/src/i18n/hygiene.test.ts
M      web/src/i18n/locales/da/common.json
M      web/src/i18n/locales/en/common.json
M      web/src/i18n/locales/es/common.json
M      web/src/i18n/locales/hi/common.json
M      web/src/i18n/locales/id/common.json
M      web/src/i18n/locales/kn/common.json
branch 'feat/b3-site-i18n' set up to track 'origin/master'.
Switched to a new branch 'feat/b3-site-i18n'
---
BRANCH: feat/b3-site-i18n
HEAD: a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
--- only-my-commits check (should be empty now) ---
--- locales now in tree (should be the 6 from master, still under web/) ---
da
en
es
hi
id
kn
```

50. assistant (2026-06-21T17:17:54.426Z)

The checkout printed `M`/`A` lines ? I need to verify whether the working tree is clean (matching `origin/master`) or carries uncommitted changes that must not be clobbered.

51. user (2026-06-21T17:17:55.678Z)

```
=== git status ===
```

```
On branch feat/b3-site-i18n
```

```
Your branch is up to date with 'origin/master'.
```

```
Changes not staged for commit:
```

```
(use "git add <file>..." to update what will be committed)
```

```
(use "git restore <file>..." to discard changes in working directory)
```

```
modified:   web/src/App.tsx
new file:   web/src/components/TapFilters.test.tsx
new file:   web/src/components/TapFilters.tsx
modified:   web/src/i18n/hygiene.test.ts
modified:   web/src/i18n/locales/da/common.json
modified:   web/src/i18n/locales/en/common.json
modified:   web/src/i18n/locales/es/common.json
modified:   web/src/i18n/locales/hi/common.json
modified:   web/src/i18n/locales/id/common.json
modified:   web/src/i18n/locales/kn/common.json
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
.claude/
site/access.db
```

```
no changes added to commit (use "git add" and/or "git commit -a")
```

```
=== diff stat vs HEAD (should be empty if clean) ===
```

```
web/src/App.tsx | 3 ++
web/src/components/TapFilters.test.tsx | 56 ++++++
web/src/components/TapFilters.tsx | 58 ++++++
web/src/i18n/hygiene.test.ts | 1 +
web/src/i18n/locales/da/common.json | 9 +++++
web/src/i18n/locales/en/common.json | 9 +++++
web/src/i18n/locales/es/common.json | 9 +++++
web/src/i18n/locales/hi/common.json | 9 +++++
web/src/i18n/locales/id/common.json | 9 +++++
web/src/i18n/locales/kn/common.json | 9 +++++
10 files changed, 172 insertions(+)
```

52. assistant (2026-06-21T17:19:20.521Z)

This is the exact concurrency hazard my global instructions warn about. **Uncommitted changes** appeared in the working tree *during* my session (they weren't there at session start) ? a sibling session is actively working, and its WIP is on the very files B3 must move/edit (`TapFilters.tsx` + `tap.\*`-looking catalog additions = tracker item **A9**, "tap-only filter controls"). My branch checkout carried that WIP along. Let me gather the precise facts (read-only) before deciding anything.

53. user (2026-06-21T17:19:23.396Z)

```
=== local + remote branches (any A9/tap branch?) ===
```

```
feat/a9-tap-filters
* feat/b3-site-i18n
```

```
=== App.tsx uncommitted diff ===
```

```
diff --git a/web/src/App.tsx b/web/src/App.tsx
index 4ab5002..34f546e 100644
```

```
--- a/web/src/App.tsx
```

```
+++ b/web/src/App.tsx
```

```
@@ -3,6 +3,7 @@ import { useTranslation, Trans } from "react-i18next";
```

```

import { useRallySelection } from "../hooks/useRallySelection";
import { RallyGrid } from "../components/RallyGrid";
import { QueryBar } from "../components/QueryBar";
+import { TapFilters } from "../components/TapFilters";
import { SelectionFooter } from "../components/SelectionFooter";
import { LanguageSwitcher } from "../components/LanguageSwitcher";
import { CompileResult, type BuildState } from "../components/CompileResult";
@@ -247,6 +248,8 @@ export default function App() {

    <div className="mt-6">
      <QueryBar onApply={onApplyQuery} />
+      { /* A9: localized tap controls for users who can't type the English query syntax. */ }
+      <TapFilters onApply={onApplyQuery} />
    </div>

    <div className="mt-6 flex flex-wrap gap-2 text-sm">

=== en/common.json uncommitted diff (what keys were added) ===
diff --git a/web/src/i18n/locales/en/common.json b/web/src/i18n/locales/en/common.json
index ee2b1e2..82512b2 100644
--- a/web/src/i18n/locales/en/common.json
+++ b/web/src/i18n/locales/en/common.json
@@ -98,6 +98,15 @@
    "timeout": "This is taking longer than expected. The job may still be running ? reload with
the video link, or try again.",
    "engineGeneric": "Something went wrong. Please try again."
  },
+  "tap": {
+    "title": "Or tap to filter:",
+    "longest": "Longest first",
+    "shortest": "Shortest first",
+    "over10": "Over 10 seconds",
+    "over20": "Over 20 seconds",
+    "top5": "Top 5 longest",
+    "top10": "Top 10 longest"
+  },
  "selection": {
    "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
  }
}

=== hygiene.test.ts uncommitted diff ===
diff --git a/web/src/i18n/hygiene.test.ts b/web/src/i18n/hygiene.test.ts
index 109d550..2ce586f 100644
--- a/web/src/i18n/hygiene.test.ts
+++ b/web/src/i18n/hygiene.test.ts
@@ -105,6 +105,7 @@ describe("no-bare-strings ? user-facing component attributes go through
t()",
  const FILES = [
    "App.tsx",
    "components/QueryBar.tsx",
+  "components/TapFilters.tsx",
    "components/RallyGrid.tsx",
    "components/SelectionFooter.tsx",
    "components/CompileResult.tsx",

```

54. assistant (2026-06-21T17:20:18.570Z)

The picture is now precise: a sibling session is working on ****A9 (tap-only filters)**** ? there's a local branch ``feat/a9-tap-filters`` plus uncommitted WIP (TapFilters component + ``tap.*`` keys in all 6 catalogs + test wiring) that carried into my checkout. This WIP touches the exact catalog files B3 must hoist/edit. Let me check whether that WIP is already committed on the A9 branch before deciding how to proceed (read-only).

55. user (2026-06-21T17:20:28.579Z)

=== feat/a9-tap-filters vs origin/master ===

=== does feat/a9-tap-filters already contain TapFilters.tsx? ===

NO - not committed on a9 branch (so the WIP is uncommitted-only)

=== is the working-tree WIP identical to what's on feat/a9-tap-filters? ===

diff --git a/web/src/components/TapFilters.tsx b/web/src/components/TapFilters.tsx

new file mode 100644

index 0000000..c0ed250

--- /dev/null

+++ b/web/src/components/TapFilters.tsx

(empty above = WIP matches a9 branch)

56. assistant (2026-06-21T17:21:03.464Z)

Critical finding: the A9 WIP is **uncommitted-only** ? it lives **only** in the shared working tree (the `feat/a9-tap-filters` branch is still empty at `origin/master`, and nothing is committed). It's live, unsaved work on the exact catalog files B3 must hoist and edit. My branch checkout already moved the shared checkout's HEAD onto `feat/b3-site-i18n` (carrying that WIP along).

Per my global instructions ("never clobber a sibling session's WIP; serialize repo writes") and your own B3 warning about concurrent catalog edits, I won't touch those files until you decide how to coordinate ? this is genuinely your call, since only you know whether that A9 session is live or abandoned scratch.

57. user (2026-06-21T17:21:11.550Z)

The user did not answer the questions.

58. assistant (2026-06-21T17:22:04.863Z)

You didn't pick an option, so I'll proceed with the **safe default** I recommended ? isolate B3 in a separate git worktree². This touches none of the A9 WIP: it stays exactly where it is in the main checkout, and I do all B3 work in a parallel directory. I'll also restore the main checkout's HEAD to `feat/a9-tap-filters` (where that WIP belongs) since my branch creation moved it ? this is a zero-content relabel because both branches sit at `origin/master`.

59. user (2026-06-21T17:22:07.934Z)

=== confirm both branches point at the same commit (relabel is a no-op for tracked files) ===

a9: a2292ef08cd4ef602c5c5ec23a52825ece033707

b3: a2292ef08cd4ef602c5c5ec23a52825ece033707

mst: a2292ef08cd4ef602c5c5ec23a52825ece033707

=== restore main checkout HEAD to feat/a9-tap-filters (carries the WIP back to its branch) ===

M web/src/App.tsx

M web/src/components/QueryBar.tsx

A web/src/components/TapFilters.test.tsx

A web/src/components/TapFilters.tsx

M web/src/i18n/hygiene.test.ts

M web/src/i18n/locales/da/common.json

M web/src/i18n/locales/en/common.json

M web/src/i18n/locales/es/common.json

M web/src/i18n/locales/hi/common.json

M web/src/i18n/locales/id/common.json

M web/src/i18n/locales/kn/common.json

Your branch is up to date with 'origin/master'.

Switched to branch 'feat/a9-tap-filters'

=== confirm A9 WIP intact on its branch ===

M web/src/App.tsx

M web/src/components/QueryBar.tsx

A web/src/components/TapFilters.test.tsx

```
A web/src/components/TapFilters.tsx
M web/src/i18n/hygiene.test.ts
M web/src/i18n/locales/da/common.json
M web/src/i18n/locales/en/common.json
M web/src/i18n/locales/es/common.json
M web/src/i18n/locales/hi/common.json
M web/src/i18n/locales/id/common.json
M web/src/i18n/locales/kn/common.json
?? .claude/
?? site/access.db
```

60. assistant (2026-06-21T17:22:16.010Z)

Main checkout is restored to `feat/a9-tap-filters` with all A9 WIP intact (I even see QueryBar.tsx now modified too ? the sibling is actively adding more, confirming a live session). Now let me create the isolated worktree for B3.

61. user (2026-06-21T17:22:18.551Z)

Preparing worktree (checking out 'feat/b3-site-i18n')
HEAD is now at a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)

```
=== worktree list ===
C:/Users/avidu/Projects/khelsutra      a2292ef [feat/a9-tap-filters]
C:/Users/avidu/Projects/khelsutra-b3-wt a2292ef [feat/b3-site-i18n]

=== B3 worktree is CLEAN (no A9 WIP) ===
(empty above = clean)
HEAD: a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
```

62. assistant (2026-06-21T17:22:35.485Z)

The worktree is clean and isolated ? A9 WIP is safe in the main checkout, B3 proceeds in `C:/Users/avidu/Projects/khelsutra-b3-wt`. Let me update tasks and start the hoist.

63. user (2026-06-21T17:22:36.022Z)

Updated task #1 status

64. user (2026-06-21T17:22:36.289Z)

Updated task #2 status

65. user (2026-06-21T17:22:42.764Z)

```
=== after move: /locales ===
locales/:
da
en
es
hi
id
kn

locales/da:
common.json

locales/en:
common.json

locales/es:
common.json
```

```
locales/hi:
common.json
```

```
locales/id:
common.json
```

```
locales/kn:
common.json
```

```
=== web/src/i18n/locales should be gone ===
```

```
=== git status (renames staged) ===
```

```
R web/src/i18n/locales/da/common.json -> locales/da/common.json
R web/src/i18n/locales/en/common.json -> locales/en/common.json
R web/src/i18n/locales/es/common.json -> locales/es/common.json
R web/src/i18n/locales/hi/common.json -> locales/hi/common.json
R web/src/i18n/locales/id/common.json -> locales/id/common.json
R web/src/i18n/locales/kn/common.json -> locales/kn/common.json
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

66. assistant (2026-06-21T17:22:59.025Z)

Renames staged cleanly, `web/src/i18n/locales` is gone. Now re-point the SPA imports and the hygiene test path. I'll use relative imports (no extra config; Vite's workspace root resolves to the repo `.git` root so importing `/locales` from `web/` works in dev/build/test).

67. user (2026-06-21T17:23:00.296Z)

```
1      // i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
2      //
3      // Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4      //   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5      //   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in
the catalog,
6      //     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7      //   - one negotiation order shared with the marketing site (B3);
8      //   - always-fallback to `en` so a missing translation degrades to English, never a raw
key.
9      import i18n from "i18next";
10     import { initReactI18next } from "react-i18next";
11     import LanguageDetector from "i18next-browser-languagedetector";
12     import ICU from "i18next-icu";
13     import enCommon from "../locales/en/common.json";
14     import knCommon from "../locales/kn/common.json";
15     import hiCommon from "../locales/hi/common.json";
16     import esCommon from "../locales/es/common.json";
17     import daCommon from "../locales/da/common.json";
18     import idCommon from "../locales/id/common.json";
19
20     // Supported locales: en/kn/hi foundation (FRIENDLY D6) + MULTILINGUAL_EXPANSION Phase A
(es/da/id,
21     // Latin, catalog-only). Anything else falls back to `en`.
22     export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
23     export type Locale = (typeof SUPPORTED_LOCALES)[number];
24     export const DEFAULT_LOCALE: Locale = "en";
25
26     // ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker
B3), so a
27     // visitor's language choice carries across both surfaces.
28     export const LANG_STORAGE_KEY = "khelsutra.lang";
29
30     // Catalogs are co-located here (D9). `kn` + `hi` shipped (B5/B6, AI-drafted ? native
review
31     // pending). A missing key in any locale still falls back to `en` ? the by-design
invariant.
```

```
32     const resources = {
33       en: { common: enCommon },
34       kn: { common: knCommon },
35       hi: { common: hiCommon },
36       es: { common: esCommon },
37       da: { common: daCommon },
38       id: { common: idCommon },
39     } as const;
40
```

68. user (2026-06-21T17:23:08.667Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

69. assistant (2026-06-21T17:23:16.037Z)

Now update the stale "co-located here" comment to reflect the hoist.

70. user (2026-06-21T17:23:18.244Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

71. assistant (2026-06-21T17:23:21.505Z)

Now update the hygiene test's `LOCALES\_DIR` to the hoisted path:

72. user (2026-06-21T17:23:24.026Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

73. assistant (2026-06-21T17:23:29.876Z)

The worktree's copy is the clean origin/master version (no A9 WIP). Let me read it first.

74. user (2026-06-21T17:23:30.993Z)

```
8     import { describe, it, expect } from "vitest";
9     import { readdirSync, readFileSync } from "node:fs";
10    import { join } from "node:path";
11
12    const LOCALES_DIR = join(import.meta.dirname, "locales");
13    const SRC_DIR = join(import.meta.dirname, "..");
14
15    function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
```

75. user (2026-06-21T17:23:36.135Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\hygiene.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

76. assistant (2026-06-21T17:23:40.896Z)

Let me check for any other references to the old `i18n/locales` path in the worktree (scripts, configs, other tests), then install deps and run the web suite to confirm the hoist keeps tests green.

77. user (2026-06-21T17:23:42.880Z)

C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\hygiene.test.ts:12:// Catalogs are hoisted to repo-root /locales (D-CATALOG-HOME): web/src/i18n -> ../../../../locales.
C:\Users\avidu\Projects\khelsutra-b3-wt\docs\MULTILINGUAL_EXPANSION.md:51:- **? Catalog-home

```
caveat `[verified]`:** catalogs today live at `web/src/i18n/locales/{en,kn,hi}/common.json` ?
**not** a shared top-level `locales/` (the I18N_PLAN "D-CATALOG-HOME" diagram). This expansion
adds siblings there. If FRIENDLY **B3** (the shared `site/` `t()` shim) hoists them to a shared
dir first, these new catalogs move with them ? sequence-aware, not a blocker.
C:\Users\avidu\Projects\khelsutra-b3-wt\docs\MULTILINGUAL_EXPANSION.md:108:**Internal
`[verified]`:** `web/src/i18n/{index.ts,hygiene.test.ts}`, `web/src/main.tsx` (font-load
pattern), `web/src/i18n/locales/{en,kn,hi}/common.json`;
[`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md), engine `docs/I18N_PLAN.md`,
`docs/UI_PROPOSAL.md`.
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:16:import enCommon from
"../../../../locales/en/common.json";
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:17:import knCommon from
"../../../../locales/kn/common.json";
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:18:import hiCommon from
"../../../../locales/hi/common.json";
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:19:import esCommon from
"../../../../locales/es/common.json";
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:20:import daCommon from
"../../../../locales/da/common.json";
C:\Users\avidu\Projects\khelsutra-b3-wt\web\src\i18n\index.ts:21:import idCommon from
"../../../../locales/id/common.json";
```

78. assistant (2026-06-21T17:23:58.656Z)

Only the intended code references remain (the two stale `MULTILINGUAL\_EXPANSION.md` doc lines I'll fix during the doc update). Now I need `node\_modules` in the worktree to run the web suite. Let me install web deps (npm ci).

79. user (2026-06-21T17:24:06.860Z)

added 180 packages, and audited 181 packages in 6s

34 packages are looking for funding
run `npm fund` for details

found 0 vulnerabilities
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

80. assistant (2026-06-21T17:24:13.225Z)

Now run the web suite (typecheck + tests + build) to confirm the hoist keeps everything green:

81. user (2026-06-21T17:24:28.978Z)

=== TYPECHECK ===

```
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
```

=== VITEST ===

```
stderr | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.594Z","level":"error","event":"api.network_error","cid":"53ccd903-8053-46cd-94bd-ea5c54118887","method":"GET","url":"/api/config","error":"Error: no engine in test"}
```

```
stdout | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.612Z","level":"info","event":"api.request","cid":"585eec7f-fa99-46ad-9a3a-3a0691a65f9d","method":"GET","url":"/api/config"}
```

```
stderr | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
```

```

{"ts":"2026-06-21T17:24:28.626Z","level":"error","event":"api.network_error","cid":"585eec7f-fa99-46ad-9a3a-3a0691a65f9d","method":"GET","url":"/api/config","error":"Error: no engine in test"}

stdout | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.642Z","level":"info","event":"api.request","cid":"d9b5ebdf-34c2-45bd-b55d-0728ea76daa6","method":"GET","url":"/api/config"}

stderr | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.657Z","level":"error","event":"api.network_error","cid":"d9b5ebdf-34c2-45bd-b55d-0728ea76daa6","method":"GET","url":"/api/config","error":"Error: no engine in test"}
{"ts":"2026-06-21T17:24:28.657Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error calling GET /api/config"}

stderr | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.657Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error calling GET /api/config"}

stderr | src/i18n/i18n.test.tsx > MULTILINGUAL Phase A (es/da/id) >
renders each new locale's catalog (real translations, not English / not raw keys)
{"ts":"2026-06-21T17:24:28.657Z","level":"warn","event":"config.unavailable","error":"ApiError: Network error calling GET /api/config"}

? src/i18n/i18n.test.tsx (17 tests)
1045ms
? i18n scaffold (B1) > renders user-facing copy from the en
catalog (not raw keys) 482ms

Test Files 18 passed (18)
Tests 168 passed (168)
Start at 22:54:21
Duration 6.84s (transform 1.72s, setup 738ms, collect 10.20s, tests 4.41s,
environment 29.26s, prepare 6.81s)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

82. assistant (2026-06-21T17:24:35.307Z)

Typecheck clean, **168/168 web tests pass** (the stderr lines are expected "no engine in test" warnings). Now confirm the Vite production build resolves the parent-dir JSON imports:

83. user (2026-06-21T17:24:39.663Z)

```

> khelsutra-web@0.0.0 build
> vite build

vite v6.4.3 building for production...
transforming...
? 94 modules transformed.
rendering chunks...
computing gzip size...
dist/index.html
  0.40 kB ? gzip: 0.27 kB
dist/assets/noto-sans-devanagari-latin-ext-wght-normal-CLkupaxV.woff2
 13.85 kB
dist/assets/noto-sans-kannada-latin-ext-wght-normal-MdBBF41x.woff2
 13.99 kB
dist/assets/noto-sans-devanagari-latin-wght-normal-Bxfr4UJH.woff2
 25.38 kB
dist/assets/noto-sans-kannada-latin-wght-normal-DeLZCgFT.woff2

```

```
27.58 kB
dist/assets/noto-sans-kannada-kannada-wght-normal-DuwB-P8d.woff2
90.80 kB
dist/assets/noto-sans-devanagari-devanagari-wght-normal-DWI_L5Cu.woff2
121.19 kB
dist/assets/index-4RWwkpK.css
24.81 kB ? gzip: 5.42 kB
dist/assets/index-DJrwS9Xl.js
370.95 kB ? gzip: 116.62 kB
? built in 1.46s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

84. assistant (2026-06-21T17:24:59.177Z)

The hoist is fully verified ? **typecheck clean, 168/168 tests, production build green** with the parent-dir `./locales` imports. Let me mark task 2 done and read the marketing page bodies to choose the `site.\*` keys.

85. user (2026-06-21T17:24:59.640Z)

Updated task #2 status

86. user (2026-06-21T17:25:00.117Z)

Updated task #3 status

87. user (2026-06-21T17:25:01.040Z)

```
243     <a id="top"></a>
244     <section class="hero" style="padding:0">
245       <div class="wrap hero-grid">
246         <div class="hero-left">
247           <span class="eyebrow">Invite-only alpha · Bengaluru</span>
248           <h1>Every rally, indexed. <span class="hl">The dead time, gone.</span></h1>
249           <p class="lead">KhelSutra finds every rally in your session and strips out the
knock-ups, walks and gaps ? so a full match becomes a clean highlight reel you can watch and
download. No editing, no scrubbing.</p>
250           <div class="hero-cta">
251             <a class="btn btn-primary" href="#join">Request alpha access</a>
252             <a class="btn btn-ghost" href="#how">See how it works</a>
253             <a class="btn btn-ghost" href="#join">See it in action + a real reel</a>
254           </div>
255           <p class="hero-note">A phone or GoPro on a tripod is all you need. No special
hardware.</p>
256           <div class="loop">
257             <span class="chip"><b>1.</b> Auto-index rallies</span>
258             <span class="arrow">?</span>
259             <span class="chip"><b>2.</b> Dead time removed</span>
260             <span class="arrow">?</span>
261             <span class="chip"><b>3.</b> Download your reel</span>
262           </div>
263         </div>
264         <div class="hero-visual">
265           <div class="reel-card">
266             <div class="reel-head">
267               <span class="dots"><i></i><i></i><i></i></span>
268               <span class="file">match_2026.mp4 · indexed</span>
269             </div>
270             <div class="reel-body">
271               <div class="lbl"><span>Rallies detected</span><span class="match">44
found</span></div>
272             <div class="reel-track">
273               <span class="on" style="left:2%;width:8%"></span>
274               <span class="on" style="left:13%;width:6%"></span>
```

```

275         <span class="on" style="left:22%;width:12%"></span>
276         <span class="on" style="left:37%;width:7%"></span>
277         <span class="on" style="left:47%;width:11%"></span>
278         <span class="on" style="left:61%;width:6%"></span>
279         <span class="on" style="left:70%;width:13%"></span>
280         <span class="on" style="left:86%;width:9%"></span>
281     </div>
282     <div class="result">
283         <span class="play" aria-hidden="true">?</span>
284         <span class="result-tx"><b>Highlight reel · 44 rallies · 18 min</b><em>dead
time removed · ready to download</em></span>
285         <span class="dl" aria-hidden="true">?</span>
286     </div>
287 </div>

```

88. user (2026-06-21T17:25:07.221Z)

=== capture.html body head (h1/intro/header) lines 55-90 ===

```

<body>
<div class="sheet">
  <div class="head">
    <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
    <h1>1-page capture checklist</h1>
  </div>
  <div class="body">
    <p class="intro">Great highlights start with a steady, full-court recording. Five minutes of
setup makes a big difference to your reels.</p>

    <div class="rule">
      <span class="star" aria-hidden="true">?</span>
      <div>
        <b>The golden rule: one match, one court, in full frame ? and don't move the camera.</b>
        <p>Multi-court footage is the hard case we're still sharpening; a single court in frame
gives the best results today.</p>
      </div>
    </div>

    <div class="grid">
      <div class="step">
        <h3><span class="n">1</span>Place the camera</h3>
        <ul>
          <li><b>Behind</b> <b>one baseline</b>, elevated ? a high tripod, a few metres up, or a
balcony.</li>
          <li>Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a little
margin and net headroom.</li>
          <li>Players should never leave the frame.</li>
        </ul>
      </div>
      <div class="step">
        <h3><span class="n">2</span>Settings</h3>
        <ul>
          <li><b>1080p or higher</b>, shot in <b>landscape</b>.</li>
          <li><b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table tennis.</li>
          <li><b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise reduction
off.</li>
        </ul>
      </div>
      <div class="step">
        <h3><span class="n">3</span>Keep it still</h3>
        <ul>
          <li>Fixed tripod or mount.</li>

```

=== own-model.html body head lines 71-110 ===

```

<body>
<div class="sheet">

```

```

<div class="head">
  <div class="top">
    <a class="brand" href="/">Khel<span class="play" aria-hidden="true"></span>Sutra</a>
    <a href="/#join" style="color:#C7F2B0;font-weight:600;text-decoration:none">Request access
?</a>
  </div>
  <h1>Annotate your footage. <span class="hl">Train a model that's yours.</span></h1>
  <p>You can't train Gemini or GPT on your court footage. KhelSutra's direction is the inverse
? a small, <b style="color:#EAF3EE">owned</b> rally model where the moat is your consented
dataset, on a commercially-clean, inspectable stack you control.</p>
  <div class="nav"><a href="/">? KhelSutra home</a><a href="#annotate">Annotate</a><a
href="#train">Train your own model</a><a href="#setup">Setup & use</a></div>
</div>

<div class="body">

  <p class="sample">? <b>Want to see what KhelSutra produces?</b> A real sample reel plays the
moment you <a href="/#join">request access</a>.</p>

  <section class="sec" id="annotate">
    <div class="kick">Step 1 · real and shipping today</div>
    <h2>Annotate your footage <span class="pill live">live today</span></h2>
    <p><b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b> that turns "watch
a match" into golden labels. While you watch your own video in VLC, you mark each rally's start
and end plus how the point ended; it writes one row per rally to a plain CSV next to your video.
<b>Your footage never leaves your machine.</b> It covers five net-separated racquet sports
(badminton, tennis, table tennis, pickleball, padel).</p>
    <a class="ghbtn" href="https://github.com/Khelsutra/rally-annotator"><svg width="16"
height="16" viewBox="0 0 16 16" fill="currentColor" aria-hidden="true"><path d="M8 0C3.58 0 0
3.58 0 8a8 8 0 0 5.47 7.59c.4.07.55-.17.55-.38 0-.19-.01-.82-.01-1.49-2.01.37-2.53-.49-2.69-
.94-.09-.23-.48-.94-.82-1.13-.28-.15-.68-.52-.01-.53.63-.01 1.08.58 1.23.82.72 1.21 1.87.87
2.33.66.07-.52.28-.87.51-1.07-1.78-.2-3.64-.89-3.64-3.95
0-.87.31-1.59.82-2.15-.08-.2-.36-1.02.08-2.12 0 0 .67-.21 2.2.82a7.4 7.4 0 0 1 2-.27c.68 0
1.36.09 2 .27 1.53-1.04 2.2-.82 2.2-.82.44 1.1.16 1.92.08 2.12.51.56.82 1.27.82 2.15 0 3.07-1.87
3.75-3.65 3.95.29.25.54.73.54 1.48 0 1.07-.01 1.93-.01 2.2 0 .21.15.46.55.38A8 8 0 0 16
8c0-4.42-3.58-8-8-8Z"/></svg> github.com/Khelsutra/rally-annotator</a>
    <div class="shots">
      <figure><figcaption>Enable it once: VLC ? View ? Rally
Annotator.</figcaption></figure>
      <figure><figcaption>Mark each rally's start/end +
ending reason, then Save Rally.</figcaption></figure>
    </div>
    <p style="margin-top:1rem"><b>The flow, per rally:</b></p>
    <ol>
      <li><b>Mark START</b> on the serve-contact frame (pause/scrub for accuracy).</li>
      <li><b>Mark END</b> when the shuttle is dead.</li>
      <li>Pick an <b>ending reason</b>, optionally a shot count, then <b>Save Rally</b> ? one
CSV row.</li>
      <li>Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video later to
continue.</li>
    </ol>
    <p style="font-size:.9rem;color:var(--mut)">It's a click-driven dialog (no marking hotkeys
yet), and targets <b>VLC 3.0.x</b>.</p>
  </section>

  <section class="sec" id="train">
    <div class="kick">Step 2 · the moat</div>
    <h2>Train your own model <span class="pill build">open pipeline · in build</span></h2>
    <div class="honest" style="border-left-color:var(--green);background:#EAF6EF;border-
color:#BfE6D2">
      <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">?</span>
      <div>
        <b>You don't have to train anything to start.</b>

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

89. assistant (2026-06-21T17:25:58.500Z)

Now I have real content to localize. Let me confirm the exact structure of the hoisted en catalog (the worktree is clean origin/master ? no A9 `tap.\*`), then add the `site.\*` namespace.

90. user (2026-06-21T17:25:59.313Z)

```
93     },
94     "errors": {
95       "networkError": "Can't reach KhelSutra. Is it running?",
96       "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
97       "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
98       "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
99       "engineGeneric": "Something went wrong. Please try again."
100    },
101    "selection": {
102      "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
103    }
104  }
105
```

91. assistant (2026-06-21T17:26:52.842Z)

Confirmed ? the worktree's catalog is clean origin/master (no A9 `tap.\*`). Now I'll add the `site.\*` namespace. To guarantee valid JSON and byte-identical insertion across all 6 catalogs (en authored; non-en seeded = en, pending translation), I'll use a one-shot script.

92. assistant (2026-06-21T17:27:01.533Z)

```
// One-shot: inject the `site.*` marketing namespace into every hoisted catalog.
// en is authored to match the marketing HTML defaults; the other locales are SEEDDED with the en
// values (B3 ships en-only marketing content ? kn/hi marketing translation is a later effort,
A3).
// Seeding (rather than omitting) keeps the web key-parity + placeholder-parity CI green.
import { readFileSync, writeFileSync, readdirSync } from "node:fs";
import { join } from "node:path";

const LOCALES = join(import.meta.dirname, "locales");

const site = {
  nav: {
    how: "How it works",
    why: "Why it's hard",
    ownModel: "Own your model",
    flyer: "Flyer",
    roadmap: "Roadmap",
    faq: "FAQ",
    requestAccess: "Request access",
  },
  hero: {
    eyebrow: "Invite-only alpha · Bengaluru",
    lead: "KhelSutra finds every rally in your session and strips out the knock-ups, walks and
gaps ? so a full match becomes a clean highlight reel you can watch and download. No editing, no
scrubbing.",
    ctaPrimary: "Request alpha access",
    ctaHow: "See how it works",
  },
  capture: {
    title: "1-page capture checklist",
  },
}
```

```

    intro: "Great highlights start with a steady, full-court recording. Five minutes of setup
makes a big difference to your reels.",
  },
  ownModel: {
    requestAccess: "Request access ?",
  },
};

// Build the insertion text, indented for a top-level key (file depth 1).
const lines = JSON.stringify(site, null, 2).split("\n");
const body = lines.map((l, i) => (i === 0 ? l : "  " + l)).join("\n");
const insertion = `  "site": ${body},\n`;

const ANCHOR = `  "selection": {`;

for (const loc of readdirSync(LOCALES)) {
  const file = join(LOCALES, loc, "common.json");
  let text = readFileSync(file, "utf8");
  if (text.includes(`"site":`)) {
    console.log(`${loc}: already has site.*, skipping`);
    continue;
  }
  if (!text.includes(ANCHOR)) throw new Error(`${loc}: anchor "selection" not found`);
  text = text.replace(ANCHOR, insertion + ANCHOR);
  JSON.parse(text); // validate before writing
  writeFileSync(file, text);
  console.log(`${loc}: site.* added (${loc === "en" ? "authored" : "en-seed"})`);
}

```

93. user (2026-06-21T17:27:01.552Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra-b3-wt_tmp_addsite.mjs (file state is current in your context ? no need to Read it back)

94. user (2026-06-21T17:27:09.221Z)

```

da: site.* added (en-seed)
en: site.* added (authored)
es: site.* added (en-seed)
hi: site.* added (en-seed)
id: site.* added (en-seed)
kn: site.* added (en-seed)

```

=== en site block ===

```

"site": {
  "nav": {
    "how": "How it works",
    "why": "Why it's hard",
    "ownModel": "Own your model",
    "flyer": "Flyer",
    "roadmap": "Roadmap",
    "faq": "FAQ",
    "requestAccess": "Request access"
  },
  "hero": {
    "eyebrow": "Invite-only alpha · Bengaluru",
    "lead": "KheIsutra finds every rally in your session and strips out the knock-ups, walks
and gaps ? so a full match becomes a clean highlight reel you can watch and download. No
editing, no scrubbing.",
    "ctaPrimary": "Request alpha access",
    "ctaHow": "See how it works"
  },
  "capture": {
    "title": "1-page capture checklist",
    "intro": "Great highlights start with a steady, full-court recording. Five minutes of

```

setup makes a big difference to your reels."

```
  },
  "ownModel": {
    "requestAccess": "Request access ?"
  }
},
```

=== verify all 6 valid JSON + have site ===

en: site keys = nav,hero,capture,ownModel

kn: site keys = nav,hero,capture,ownModel

hi: site keys = nav,hero,capture,ownModel

es: site keys = nav,hero,capture,ownModel

da: site keys = nav,hero,capture,ownModel

id: site keys = nav,hero,capture,ownModel

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

95. assistant (2026-06-21T17:27:13.460Z)

All 6 catalogs have the `site.\*` block. Let me re-run the web hygiene tests to confirm key-parity + placeholder-parity stay green with the new keys.

96. user (2026-06-21T17:27:17.862Z)

```
RUN v3.2.6 C:/Users/avidu/Projects/khelsutra-b3-wt/web
```

```
? src/i18n/hygiene.test.ts (27 tests)
```

```
14ms
```

```
Test Files 1 passed (1)
```

```
Tests 27 passed (27)
```

```
Start at 22:57:16
```

```
Duration 614ms (transform 52ms, setup 19ms, collect 37ms, tests 14ms,
```

```
environment 0ms, prepare 223ms)
```

```
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

97. assistant (2026-06-21T17:28:11.964Z)

Key-parity + placeholder-parity green (27/27). Task 3 done. Now let me look at how the site's existing tests use jsdom (to design the shim for testability), then build the copy step + shim together.

98. user (2026-06-21T17:28:12.445Z)

Updated task #3 status

99. user (2026-06-21T17:28:12.810Z)

```
1      // Behavioral regression tests for the two USER-FACING fixes on the landing page, run
against the
2      // REAL index.html in a jsdom DOM (the inline script actually executes). These guard
behaviour, not
3      // just markup: a refactor that breaks the submit feedback or the watchable reveal fails
CI.
4      // 1. submit ? an obvious 'Sending?' state (disabled + aria-busy); restored on
failure.
5      // 2. post-signup reveal ? both videos; a ? closes it; the auto-close HOLDS while the
reel plays.
6      // jsdom is a TEST-ONLY devDependency ? the Worker + VM host runtimes stay dependency-
free.
7      import { test } from "node:test";
8      import assert from "node:assert/strict";
9      import { readFileSync } from "node:fs";
10     import { join } from "node:path";
11     import { JSDOM, VirtualConsole } from "jsdom";
```

```

12
13     const HTML = readFileSync(join(import.meta.dirname, "..", "public", "index.html"),
"utf8");
14     const tick = () => new Promise((r) => setTimeout(r, 5)); // let the inline async handler
settle
15
16     // Boot the real page; `fetchImpl` decides how /api/request-access resolves.
window.setInterval is
17     // captured so the test drives the reveal countdown deterministically (no real 1s
timers). A fake
18     // YT.Player records its events so we can simulate the reel playing/pausing.
19     function boot(fetchImpl) {
20         const vc = new VirtualConsole(); // swallow jsdom "Not implemented: navigation" (the
mailto fallback)
21         const captured = {};
22         const dom = new JSDOM(HTML, {
23             runScripts: "dangerously",
24             url: "https://khelesutra.guru/",
25             virtualConsole: vc,
26             beforeParse(window) {
27                 window.fetch = fetchImpl;
28                 window.setInterval = (fn) => { captured.tick = fn; return 1; };
29                 window.clearInterval = () => { captured.cleared = true; };
30                 window.YT = {
31                     Player: function (_id, cfg) {
32                         captured.reel = cfg;
33                         if (cfg.events && cfg.events.onReady) {
34                             cfg.events.onReady({ target: { getDuration: () => 120, seekTo() {}},
playVideo() {} } });
35                         }
36                         return { destroy() { captured.destroyed = true; } };
37                     },
38                 };
39             },
40         });
41         const { document } = dom.window;
42         const form = document.getElementById("af");
43         // fill the minimum-valid form
44         form.querySelector('input[name="segment"][value="individual"]').checked = true;
45         document.getElementById("af-name").value = "Demo";
46         document.getElementById("af-email").value = "demo@example.com";
47         const consent = document.getElementById("af-consent");
48         if (consent) consent.checked = true;
49         const submit = () => form.dispatchEvent(new dom.window.Event("submit", { bubbles:
true, cancelable: true }));
50         const btn = () => form.querySelector('button[type="submit"]');
51         return { dom, document, form, submit, btn, captured };
52     }
53
54     test("submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?')",
async () => {
55         // a fetch that never resolves ? the button stays in the in-flight state we can
inspect
56         const { submit, btn } = boot(() => new Promise(() => {}));
57         submit();
58         await tick();
59         const b = btn();
60         assert.equal(b.disabled, true, "button must be disabled while submitting");
61         assert.equal(b.getAttribute("aria-busy"), "true", "aria-busy must be set for assistive
tech");
62         assert.match(b.textContent, /Sending?/, "button must read 'Sending?'");
63         assert.ok(b.querySelector(".spin"), "an in-flight spinner must be shown");
64     });
65
66     test("on failure the button is restored ? never stuck on a frozen 'Sending?'", async ()

```

```

=> {
67     const { submit, btn } = boot(async () => ({ ok: false })); // backend down ? mailto
fallback path
68     const before = btn().textContent;
69     submit();
70     await tick();
71     const b = btn();
72     assert.equal(b.disabled, false, "button must be re-enabled after a failed submit");
73     assert.equal(b.getAttribute("aria-busy"), null, "aria-busy must be cleared");
74     assert.equal(b.textContent.trim(), before.trim(), "button label must be restored");
75 });
76
77 test("after sign-up BOTH videos appear and a ? closes the reveal", async () => {
78     const { document, submit } = boot(async () => ({ ok: true }));
79     submit();
80     await tick();
81     const host = document.getElementById("reel-reveal");
82     assert.equal(host.hidden, false, "reveal should be visible after a successful
submit");
83     assert.ok(host.querySelector("video.tool-vid"), "the tool screencast video must be
present");
84     assert.ok(host.querySelector(".reelwrap #reel-player, .reelwrap iframe"), "the reel
player must be present");
85     const close = host.querySelector("#reel-close");
86     assert.ok(close, "a manual ? close must be present");
87     close.click();
88     assert.equal(host.hidden, true, "? must hide the reveal");
89     assert.equal(host.innerHTML, "", "? must clear the reveal");
90 });
91
92 test("the auto-close HOLDS while the reel is playing (no mid-watch cut-off)", async ()
=> {
93     const { document, submit, captured } = boot(async () => ({ ok: true }));
94     submit();
95     await tick();
96     const count = () => Number(document.getElementById("reel-count").textContent);
97     const start = count();
98     captured.tick();
99     assert.equal(count(), start - 1, "the countdown ticks down normally");
100    // reel starts PLAYING (YT state 1) ? the countdown must FREEZE
101    captured.reel.events.onStateChange({ data: 1 });
102    const held = count();
103    captured.tick();
104    captured.tick();
105    assert.equal(count(), held, "the countdown must NOT advance while the reel is
playing");
106    // reel PAUSES (state 2) ? the countdown resumes
107    captured.reel.events.onStateChange({ data: 2 });
108    captured.tick();
109    assert.equal(count(), held - 1, "the countdown resumes once the reel stops");
110 });
111

```

100. assistant (2026-06-21T17:30:15.171Z)

Now I understand the jsdom pattern. Let me build the copy step, the shim, and the drift test. The shim will be an ESM module exporting pure helpers (testable via `import` in node) that auto-boots only in a browser. First, the copy script and shim:

101. assistant (2026-06-21T17:30:19.816Z)

```

// Mirror the single-source-of-truth catalogs (repo-root /locales, D-CATALOG-HOME) into the
site's
// static public/ dir, so the dependency-free marketing site can fetch them at runtime via the
// t()/data-i18n shim (public/i18n.js). This copy is the ONLY build step the otherwise no-build

```

```

site
// has. Run on demand (`npm run copy:locales`) or automatically before deploy (`predeploy`).
//
// The committed copy under site/public/locales/ is what actually ships (static hosts serve it
with
// no build); the drift-guard test (src/locales-drift.test.js) fails CI if it goes stale vs
/locales.
import { cpSync, rmSync, mkdirSync, readdirSync } from "node:fs";
import { join } from "node:path";

const SRC = join(import.meta.dirname, "..", "..", "locales");
const DEST = join(import.meta.dirname, "..", "public", "locales");

rmSync(DEST, { recursive: true, force: true });
mkdirSync(DEST, { recursive: true });
cpSync(SRC, DEST, { recursive: true });

console.log(`copy-locales: ${readdirSync(DEST).join(", ")} -> site/public/locales/`);

```

102. user (2026-06-21T17:30:19.833Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-b3-wt\site\scripts\copy-
locales.mjs (file state is current in your context ? no need to Read it back)

103. assistant (2026-06-21T17:30:48.943Z)

```

// KhelSutra marketing-site i18n shim (tracker B3) ? vanilla, dependency-free, zero build.
//
// Mirrors the SPA's react-i18next contract (web/src/i18n/index.ts) for the static site:
// - the SAME shared catalogs (repo-root /locales, copied into /public/locales ? D-CATALOG-
HOME);
// - the SAME negotiation order: persisted (localStorage `khelsutra.lang`) -> ?lang= ->
navigator -> en;
// - ICU-lite interpolation `{name}` + plurals `{n, plural, one {?} other {?}}` via
Intl.PluralRules
// (CLDR-correct for en/kn/hi ? the 2-form site languages ? and any locale);
// - a missing key degrades to en, then leaves the HTML's English default ? NEVER a raw key.
//
// The pure helpers are exported for the unit test (src/i18n.shim.test.js); boot() runs only in
a browser.

export const SUPPORTED = ["en", "kn", "hi"]; // the trilingual marketing site (es/da/id are SPA-
only)
export const STORAGE_KEY = "khelsutra.lang"; // shared with the SPA, so a choice carries across
surfaces
export const DEFAULT = "en";

const base = (code) => (code ? String(code).toLowerCase().split("-")[0] : ""); // "kn-IN" ->
"kn"
const supported = (code) => (SUPPORTED.includes(base(code)) ? base(code) : null);

// Negotiation ? EXACTLY the SPA order. Anything unsupported is skipped; nothing matches -> en.
export function negotiate({ stored, query, nav } = {}) {
  const navList = Array.isArray(nav) ? nav : nav ? [nav] : [];
  for (const candidate of [stored, query, ...navList]) {
    const ok = supported(candidate);
    if (ok) return ok;
  }
  return DEFAULT;
}

const dig = (obj, key) => key.split(".").reduce((o, k) => (o && typeof o === "object" ? o[k] :
undefined), obj);

// Resolve one plural block "{var, plural, one {?} other {?}} (balanced braces, # = the

```

```

number).
// Returns the string unchanged when there's no parseable plural block (so interpolate()
terminates).
function plural(msg, vars, locale) {
  const m = msg.match(/\{(\w+),\s*plural,/);
  if (!m) return msg;
  let depth = 0, end = -1;
  for (let i = m.index; i < msg.length; i++) {
    if (msg[i] === "{") depth++;
    else if (msg[i] === "}" && --depth === 0) { end = i; break; }
  }
  if (end < 0) return msg;
  const inner = msg.slice(m.index + m[0].length, end);
  const n = Number(vars[m[1]] ?? 0);
  const cat = new Intl.PluralRules(locale).select(n);
  const arms = {};
  for (const a of inner.matchAll(/(\w+)\s*\{/g)) {
    let d = 1, j = a.index + a[0].length, e = -1;
    for (; j < inner.length; j++) { if (inner[j] === "{") d++; else if (inner[j] === "}" && --d
=== 0) { e = j; break; } }
    if (e < 0) break;
    arms[a[1]] = inner.slice(a.index + a[0].length, e);
  }
  const chosen = (arms[cat] ?? arms.other ?? "").replace(/#/g, String(n));
  return msg.slice(0, m.index) + chosen + msg.slice(end + 1);
}

// ICU-lite: resolve every plural block, then simple {name} interpolation.
export function interpolate(msg, vars = {}, locale = DEFAULT) {
  if (typeof msg !== "string") return msg;
  let out = msg;
  for (let i = 0; i < 20; i++) { const next = plural(out, vars, locale); if (next === out)
break; out = next; }
  return out.replace(/\{(\w+)\}/g, (_, k) => (k in vars ? String(vars[k]) : `${k}`));
}

// active locale -> en fallback. undefined when absent in both (caller keeps the DOM's English
default).
export function translate(catalogs, locale, key, vars) {
  let msg = dig(catalogs[locale], key);
  if (msg == null) msg = dig(catalogs[DEFAULT], key);
  return msg == null ? undefined : interpolate(msg, vars, locale);
}

// Walk [data-i18n] under `root`; set.textContent (or [data-i18n-attr] target). Missing key ->
skip.
export function applyDom(root, catalogs, locale) {
  for (const el of root.querySelectorAll("[data-i18n]")) {
    const val = translate(catalogs, locale, el.getAttribute("data-i18n"));
    if (val == null) continue;
    const attr = el.getAttribute("data-i18n-attr");
    if (attr) el.setAttribute(attr, val); else el.textContent = val;
  }
  for (const el of root.querySelectorAll("[data-lang]")) {
    const on = el.getAttribute("data-lang") === locale;
    el.setAttribute("aria-pressed", String(on));
    el.classList.toggle("is-active", on);
  }
}

// ---- browser glue (skipped under the plain-node unit test, which has no document) ----
const readCookie = (name) => {
  const m = (document.cookie || "").match(new RegExp("(?:^|; )" + name.replace(/\./g, "\\.") +
"=([^\;]*)"));
  return m ? decodeURIComponent(m[1]) : null;
}

```

```

};

function persist(locale) {
  try { localStorage.setItem(STORAGE_KEY, locale); } catch { /* private mode */ }
  // Mirror to a cookie so server.js (VM host) can honor the persisted pref server-side (no
FOUC).
  try { document.cookie = `${STORAGE_KEY}=${locale};path=/;max-age=31536000;samesite=lax`; }
catch { /* ignore */ }
}

async function loadCatalog(loc) {
  try { const r = await fetch(`/locales/${loc}/common.json`); return r.ok ? await r.json() : {}; }
} catch { return {}; }
}

async function render(locale) {
  const catalogs = { en: await loadCatalog("en") };
  if (locale !== "en") catalogs[locale] = await loadCatalog(locale);
  document.documentElement.lang = locale;
  applyDom(document, catalogs, locale);
}

async function boot() {
  let stored = null;
  try { stored = localStorage.getItem(STORAGE_KEY); } catch { /* ignore */ }
  if (!stored) stored = readCookie(STORAGE_KEY); // server-set or cross-store persisted pref
  const query = new URLSearchParams(location.search).get("lang");
  const nav = navigator.languages && navigator.languages.length ? [...navigator.languages] :
[navigator.language];
  const locale = negotiate({ stored, query, nav });
  await render(locale);
  document.addEventListener("click", (e) => {
    const btn = e.target.closest && e.target.closest("[data-lang]");
    if (!btn) return;
    e.preventDefault();
    const loc = supported(btn.getAttribute("data-lang")) || DEFAULT;
    persist(loc);
    render(loc);
  });
}

if (typeof document !== "undefined" && typeof window !== "undefined") {
  if (document.readyState === "loading") document.addEventListener("DOMContentLoaded", boot);
  else boot();
}

```

104. user (2026-06-21T17:30:48.969Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra-b3-wt\site\public\i18n.js (file state is current in your context ? no need to Read it back)

105. assistant (2026-06-21T17:31:03.115Z)

Now wire the npm scripts and generate the committed copy. Let me read the worktree's site/package.json and update it.

106. user (2026-06-21T17:31:03.483Z)

```

1      {
2        "name": "kheIsutra-site",
3        "private": true,
4        "type": "module",
5        "scripts": {
6          "test": "node --test",

```

```

7      "test:cf": "node --test src/index.test.js",
8      "test:vm": "node --test src/server.test.js",
9      "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10     "deploy": "wrangler deploy",
11     "dev": "wrangler dev",
12     "og": "python make_og.py"
13   },
14   "devDependencies": {
15     "jsdom": "^29.1.1"
16   }
17 }
18

```

107. user (2026-06-21T17:31:10.080Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\package.json has been updated successfully. (file state is current in your context ? no need to Read it back)

108. assistant (2026-06-21T17:31:13.795Z)

Now generate the committed copy and write the drift-guard test:

109. user (2026-06-21T17:31:16.920Z)

```

> copy:locales
> node scripts/copy-locales.mjs

copy-locales: da, en, es, hi, id, kn -> site/public/locales/

=== generated tree ===
public/locales/:
da
en
es
hi
id
kn

public/locales/da:
common.json

public/locales/en:
common.json

public/locales/es:
common.json

public/locales/hi:
common.json

public/locales/id:
common.json

public/locales/kn:
common.json

=== byte-equality spot check (en) ===
en: IDENTICAL
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

110. assistant (2026-06-21T17:31:28.575Z)

// DRIFT GUARD for the one build step the otherwise no-build site has (tracker B3 / D-CATALOG-HOME):

```

// the catalogs the marketing site ships (site/public/locales/) MUST be byte-identical to the
single
// source of truth (repo-root /locales/). If someone edits /locales without re-running the copy,
this
// fails CI with the exact fix. Run `npm run copy:locales` to resync.
import { test } from "node:test";
import assert from "node:assert/strict";
import { readFileSync, readdirSync } from "node:fs";
import { join } from "node:path";

const SRC = join(import.meta.dirname, "..", "..", "locales");
const PUB = join(import.meta.dirname, "..", "public", "locales");

test("site/public/locales mirrors repo-root /locales exactly (else: npm run copy:locales)", ()
=> {
  const locales = readdirSync(SRC, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name);
  assert.ok(locales.length >= 3, "expected at least en/kn/hi catalogs in /locales");

  const shipped = new Set(readdirSync(PUB, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name));
  for (const loc of locales) {
    const src = readFileSync(join(SRC, loc, "common.json"), "utf8");
    assert.ok(shipped.has(loc), `site/public/locales/${loc} is missing ? run npm run
copy:locales`);
    const pub = readFileSync(join(PUB, loc, "common.json"), "utf8");
    assert.equal(pub, src, `site/public/locales/${loc}/common.json drifted from /locales/${loc}
? run npm run copy:locales`);
  }
  // No stale extra locales shipped that aren't in the source of truth.
  for (const loc of shipped) {
    assert.ok(locales.includes(loc), `site/public/locales/${loc} has no source in /locales ? run
npm run copy:locales`);
  }
});

```

111. user (2026-06-21T17:31:28.590Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra-b3-wt\site\src\locales-drift.test.js (file state is current in your context ? no need to Read it back)

112. assistant (2026-06-21T17:31:53.685Z)

Now let me write the shim unit test and run it to verify the shim before wiring HTML. I'll test it against the **real shared catalogs** (doubling as a cross-surface proof).

113. assistant (2026-06-21T17:32:12.220Z)

```

// Unit tests for the marketing-site i18n shim (public/i18n.js, tracker B3). Proves the shim
mirrors
// the SPA's react-i18next contract: same negotiation order, ICU-lite interpolation/plurals, en
// fallback, and a data-i18n walker that NEVER leaves a raw key. Tested against the REAL shared
// catalogs (/locales) ? so this also proves both surfaces consume one source of truth.
import { test } from "node:test";
import assert from "node:assert/strict";
import { readFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";
import { negotiate, interpolate, translate, applyDom, SUPPORTED, DEFAULT } from
"../public/i18n.js";

const LOCALES = join(import.meta.dirname, "..", "..", "locales");
const load = (loc) => JSON.parse(readFileSync(join(LOCALES, loc, "common.json"), "utf8"));
const catalogs = { en: load("en"), kn: load("kn"), hi: load("hi") };

```

```

test("negotiation order matches the SPA: persisted -> ?lang -> navigator -> en", () => {
  assert.equal(negotiate({ stored: "kn", query: "hi", nav: ["en-US"] })), "kn", "persisted pref wins");
  assert.equal(negotiate({ query: "hi", nav: ["en-US"] })), "hi", "?lang beats navigator");
  assert.equal(negotiate({ nav: ["kn-IN", "en-IN"] })), "kn", "navigator picks the first supported");
  assert.equal(negotiate({}), "en", "nothing -> en");
});

test("region subtags normalize and unsupported degrades to en (never a locale we can't serve)", () => {
  assert.equal(negotiate({ nav: ["hi-IN"] })), "hi", "hi-IN -> hi");
  assert.equal(negotiate({ nav: ["ta-IN"] })), "en", "Tamil (unsupported) -> en");
  assert.equal(negotiate({ stored: "es" })), "en", "es is SPA-only ? the trilingual site degrades it to en");
  assert.deepEqual([...SUPPORTED], ["en", "kn", "hi"]);
  assert.equal(DEFAULT, "en");
});

test("ICU-lite interpolation: {name} substitution", () => {
  assert.equal(interpolate("over {n}s", { n: 10 }), "over 10s");
  assert.equal(interpolate("Couldn't load: {error}", { error: "boom" }), "Couldn't load: boom");
});

test("ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number", () => {
  const en = catalogs.en.selection.count; // "{count, plural, one {# rally selected} other {# rallies selected}}"
  assert.equal(interpolate(en, { count: 1 }, "en"), "1 rally selected");
  assert.equal(interpolate(en, { count: 5 }, "en"), "5 rallies selected");
  // Kannada is also one/other ? the shim picks the arm from the catalog, no hard-coded rules.
  assert.equal(translate(catalogs, "kn", "selection.count", { count: 1 }), catalogs.kn.selection.count.match(/one \{([^\}]*)\}/)[1].replace("#", "1"));
});

test("translate: active locale, then en fallback, then undefined (caller keeps the DOM default)", () => {
  assert.equal(translate(catalogs, "kn", "app.title"), catalogs.kn.app.title); // real Kannada
  assert.equal(translate(catalogs, "en", "lang.kn"), "????"); // shared catalog autonym
  // B3 ships en-only marketing content: site.* in kn is the en seed -> Kannada visitor sees English now.
  assert.equal(translate(catalogs, "kn", "site.capture.title"), catalogs.en.site.capture.title);
  assert.equal(translate(catalogs, "kn", "does.not.exist"), undefined, "missing everywhere -> undefined");
});

test("applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw key", () => {
  const { document } = new JSDOM(`<!doctype html><body>
    <span id="auto" data-i18n="lang.kn">PLACEHOLDER</span>
    <span id="keep" data-i18n="does.not.exist">KEEP ME</span>
    <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
    <button id="b-en" data-lang="en">English</button>
    <button id="b-kn" data-lang="kn">????</button>
  </body>`).window;

  applyDom(document, catalogs, "kn");

  assert.equal(document.getElementById("auto").textContent, "????", "data-i18n sets textContent from the shared catalog");
  assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key leaves the HTML default ? never a raw key");
  assert.equal(document.getElementById("ph").getAttribute("placeholder"), catalogs.en.site.capture.title, "data-i18n-attr targets an attribute");
  assert.equal(document.getElementById("b-kn").getAttribute("aria-pressed"), "true", "active locale button is pressed");

```

```
    assert.equal(document.getElementById("b-en").getAttribute("aria-pressed"), "false", "inactive  
locale button is not pressed");  
    assert.ok(document.getElementById("b-kn").classList.contains("is-active"), "active button gets  
a non-color selection class");  
});
```

114. user (2026-06-21T17:32:12.234Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-b3-wt\site\src\i18n.shim.test.js
(file state is current in your context ? no need to Read it back)

115. assistant (2026-06-21T17:32:17.785Z)

Now install site deps (jsdom) in the worktree and run the new shim + drift tests:

116. user (2026-06-21T17:32:24.185Z)

8 packages are looking for funding
 run `npm fund` for details

found 0 vulnerabilities

```
=== shim + drift tests ===  
? negotiation order matches the SPA: persisted -> ?lang -> navigator -> en (0.8631ms)  
? region subtags normalize and unsupported degrades to en (never a locale we can't serve)  
(1.9203ms)  
? ICU-lite interpolation: {name} substitution (0.4531ms)  
? ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number (1.6303ms)  
? translate: active locale, then en fallback, then undefined (caller keeps the DOM default)  
(0.4085ms)  
? applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw key  
(104.9447ms)  
? site/public/locales mirrors repo-root /locales exactly (else: npm run copy:locales) (11.071ms)  
? tests 7  
? suites 0  
? pass 7  
? fail 0  
? cancelled 0  
? skipped 0  
? todo 0  
? duration_ms 1634.409  
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

117. assistant (2026-06-21T17:33:04.201Z)

All 7 shim + drift tests pass. Now the HTML wiring. Let me check the header/`.head` CSS in the
two sheet pages to place the switcher cleanly.

118. user (2026-06-21T17:33:04.684Z)

Updated task #4 status

119. user (2026-06-21T17:33:05.154Z)

Updated task #5 status

120. user (2026-06-21T17:33:05.619Z)

Updated task #6 status

121. user (2026-06-21T17:33:07.520Z)

```
=== capture .head CSS ===
```

```

16: .sheet{max-width:820px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
17: .head{background:var(--ink);color:#EAF3EE;padding:22px 30px;display:flex;align-
items:center;justify-content:space-between;gap:1rem;flex-wrap:wrap}
18: .brand{display:flex;align-items:center;gap:.55rem;font-weight:800;font-size:1.2rem}
19: .brand .dot{color:var(--green)}
20: .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px 0
6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
21: .head h1{font-size:1.05rem;font-weight:600;margin:0;color:#C7F2B0}
49: .sheet{box-shadow:none;margin:0;max-width:none;border-radius:0}

=== own-model .head / .top CSS ===
19: .head{background:var(--ink);color:#EAF3EE;padding:24px 32px}
20: .head .top{display:flex;align-items:center;justify-content:space-between;gap:1rem;flex-
wrap:wrap}
21: .brand{display:flex;align-items:center;gap:.5rem;font-weight:800;font-
size:1.2rem;color:#fff;text-decoration:none}
22: .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px 0
6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
23: .head h1{font-size:clamp(1.5rem,3.5vw,2.1rem);font-weight:800;letter-
spacing:-.02em;margin:1rem 0 0;max-width:20ch}
24: .head h1 .hl{color:var(--lime)}
25: .head p{color:#A7C3B7;margin:.7rem 0 0;max-width:62ch}
26: .head .nav{display:flex;gap:1rem;font-size:.9rem;margin-top:1rem;flex-wrap:wrap}
27: .head .nav a{color:var(--lime);text-decoration:none}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

122. assistant (2026-06-21T17:33:53.296Z)

Both sheet pages have dark headers, so the switcher CSS must read on dark (I'll use opacity for inactive + green fill for active ? theme-agnostic). Let me wire index.html: nav `data-i18n`, the switcher, hero `data-i18n`, CSS, and the script.

123. user (2026-06-21T17:33:58.688Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

124. assistant (2026-06-21T17:34:02.598Z)

Now the hero strings in index.html:

125. user (2026-06-21T17:34:07.667Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

126. assistant (2026-06-21T17:34:11.430Z)

Now add the switcher CSS near the `.nav-links` rule, and the script before `</body>`:

127. user (2026-06-21T17:34:16.552Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

128. assistant (2026-06-21T17:34:27.938Z)

Now add the shim script tag. Let me place it right after `<body>`:

129. user (2026-06-21T17:34:28.904Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

130. assistant (2026-06-21T17:34:51.011Z)

Now capture.html ? add the switcher, `data-i18n` on the title/intro, CSS, and the script:

131. user (2026-06-21T17:34:54.284Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

132. assistant (2026-06-21T17:34:59.041Z)

I need to read the worktree's capture.html first. Let me read the relevant regions:

133. user (2026-06-21T17:35:00.472Z)

```
12     <style>
13       :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--paper:#F6F8F4;--tx:#14271F;--
mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,sans-serif}
14       *{box-sizing:border-box}
15       body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.5;-webkit-font-smoothing:antialiased}
16       .sheet{max-width:820px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
17       .head{background:var(--ink);color:#EAF3EE;padding:22px 30px;display:flex;align-
items:center;justify-content:space-between;gap:1rem;flex-wrap:wrap}
18       .brand{display:flex;align-items:center;gap:.55rem;font-weight:800;font-size:1.2rem}
19       .brand .dot{color:var(--green)}
20       .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
21       .head h1{font-size:1.05rem;font-weight:600;margin:0;color:#C7F2B0}
22       .body{padding:24px 30px 8px}
23       .intro{color:var(--mut);margin:0 0 16px;font-size:.98rem}
```

134. user (2026-06-21T17:35:01.410Z)

```
55     <body>
56     <div class="sheet">
57       <div class="head">
58         <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
59         <h1>1-page capture checklist</h1>
60       </div>
61       <div class="body">
62         <p class="intro">Great highlights start with a steady, full-court recording. Five
minutes of setup makes a big difference to your reels.</p>
63
64         <div class="rule">
```

135. user (2026-06-21T17:35:01.986Z)

```
124       <p class="consent">Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.</p>
125     </div>
126     <div class="foot">
127       <span>Questions? <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> . <a
href="https://khelsutra.guru">khelsutra.guru</a></span>
128       <span class="noprint">Tip: press Ctrl/Cmd + P to print or save as PDF.</span>
129     </div>
130   </div>
131 </body>
```

136. assistant (2026-06-21T17:35:06.232Z)

Now I have the exact context. Let me make the capture.html edits:

137. user (2026-06-21T17:35:10.926Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

138. user (2026-06-21T17:35:19.664Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

139. user (2026-06-21T17:35:24.654Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

140. assistant (2026-06-21T17:35:40.585Z)

Now own-model.html. Let me read its style and header regions:

141. user (2026-06-21T17:35:40.895Z)

```
17      a{color:var(--green-d)}
18      .sheet{max-width:880px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
19      .head{background:var(--ink);color:#EAF3EE;padding:24px 32px}
20      .head .top{display:flex;align-items:center;justify-content:space-
between;gap:1rem;flex-wrap:wrap}
21      .brand{display:flex;align-items:center;gap:.5rem;font-weight:800;font-
size:1.2rem;color:#fff;text-decoration:none}
22      .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
23      .head h1{font-size:clamp(1.5rem,3.5vw,2.1rem);font-weight:800;letter-
spacing:-.02em;margin:1rem 0 0;max-width:20ch}
24      .head h1 .hl{color:var(--lime)}
25      .head p{color:#A7C3B7;margin:.7rem 0 0;max-width:62ch}
26      .head .nav{display:flex;gap:1rem;font-size:.9rem;margin-top:1rem;flex-wrap:wrap}
27      .head .nav a{color:var(--lime);text-decoration:none}
28      .body{padding:26px 32px 8px}
```

142. user (2026-06-21T17:35:41.231Z)

```
71      <body>
72      <div class="sheet">
73      <div class="head">
74      <div class="top">
75      <a class="brand" href="/">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
76      <a href="/#join" style="color:#C7F2B0;font-weight:600;text-
decoration:none">Request access ?</a>
77      </div>
78      <h1>Annotate your footage. <span class="hl">Train a model that's yours.</span></h1>
79      <p>You can't train Gemini or GPT on your court footage. KhelSutra's direction is the
inverse ? a small, <b style="color:#EAF3EE">owned</b> rally model where the moat is your
consented dataset, on a commercially-clean, inspectable stack you control.</p>
80      <div class="nav"><a href="/">? KhelSutra home</a><a href="#annotate">Annotate</a><a
href="#train">Train your own model</a><a href="#setup">Setup & use</a></div>
```

143. user (2026-06-21T17:35:41.484Z)

```

172     <div class="foot">
173         <span><a href="/">khelsutra.guru</a> · <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> · Academy flyer: <a href="/flyer" hreflang="en">English</a>
· <a href="/flyer-kn" hreflang="kn" lang="kn">?????</a> · <a href="/flyer-hi" hreflang="hi"
lang="hi">?????</a></span>
174         <span>Reels carry a "Generated by Khelsutra.guru" mark.</span>
175     </div>
176 </div>
177 </body>
178 </html>
179

```

144. assistant (2026-06-21T17:35:45.734Z)

Now the own-model.html edits ? CSS, switcher (grouped right with the request link), `data-i18n`, and script:

145. user (2026-06-21T17:35:51.451Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

146. user (2026-06-21T17:36:00.539Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

147. user (2026-06-21T17:36:05.164Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

148. assistant (2026-06-21T17:36:38.769Z)

All 3 pages wired. Task 6 done. Now server.js negotiation. Let me read the worktree's server.js and add the negotiation + lang injection.

149. user (2026-06-21T17:36:39.217Z)

Updated task #6 status

150. user (2026-06-21T17:36:39.722Z)

Updated task #7 status

151. user (2026-06-21T17:36:40.588Z)

```

26     const TYPES = {
27         ".html": "text/html; charset=utf-8", ".png": "image/png", ".svg": "image/svg+xml",
28         ".css": "text/css", ".js": "text/javascript", ".ico": "image/x-icon", ".txt":
"text/plain",
29         ".mp4": "video/mp4", ".webm": "video/webm", ".gif": "image/gif", ".jpg": "image/jpeg",
".jpeg": "image/jpeg",
30     };
31
32     async function toRequest(req) {
33         const url = `http://${req.headers.host || "localhost"}${req.url}`;
34         let body;
35         if (req.method !== "GET" && req.method !== "HEAD") {
36             const chunks = [];
37             for await (const c of req) chunks.push(c);
38             body = Buffer.concat(chunks);
39         }

```

```

40     return new Request(url, { method: req.method, headers: req.headers, body });
41 }
42
43 async function send(res, response) {
44     res.statusCode = response.status;
45     for (const [k, v] of response.headers) res.setHeader(k, v);
46     res.end(Buffer.from(await response.arrayBuffer()));
47 }
48
49 async function serveStatic(pathname, res) {
50     const rel = pathname === "/" ? "index.html"
51       : pathname === "/capture" ? "capture.html"
52       : pathname === "/own-model" ? "own-model.html"
53       : pathname === "/flyer" ? "flyer.html"
54       : pathname === "/flyer-kn" ? "flyer-kn.html"
55       : pathname === "/flyer-hi" ? "flyer-hi.html"
56       : pathname.replace(/^\/+/, "");
57     const file = normalize(join(PUBLIC, rel));
58     if (!file.startsWith(PUBLIC)) { res.statusCode = 403; return res.end("forbidden"); }
59     try {
60         const data = await readFile(file);
61         res.setHeader("content-type", TYPES[extname(file)] || "application/octet-stream");
62         res.end(data);
63     } catch {
64         res.statusCode = 404;
65         res.end("not found");
66     }
67 }
68
69 createServer(async (req, res) => {
70     try {
71         const pathname = decodeURIComponent(new URL(`http://${req.url}`).pathname);
72         if (pathname === "/api/request-access") {
73             if (req.method !== "POST") { res.statusCode = 405; return
res.end('{"ok":false,"error":"method not allowed"}'); }
74             return await send(res, await handleRequest(await toRequest(req), store, notify));
75         }
76         return await serveStatic(pathname, res);
77     } catch (err) {
78         res.statusCode = 500;
79         res.end('{"ok":false,"error":"server error"}');
80         console.error(err);
81     }
82 }).listen(PORT, () => console.log(`khelsutra site listening on :${PORT} (sqlite:
${DB_PATH})`));

```

152. assistant (2026-06-21T17:36:46.743Z)

Now add the negotiation helpers and wire them into `serveStatic`:

153. user (2026-06-21T17:36:58.877Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\server.js has been updated successfully.
(file state is current in your context ? no need to Read it back)

154. user (2026-06-21T17:37:10.432Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\server.js has been updated successfully.
(file state is current in your context ? no need to Read it back)

155. assistant (2026-06-21T17:37:15.134Z)

Now update the call site to pass `req` and parsed query:

156. user (2026-06-21T17:37:19.005Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\server.js has been updated successfully.
(file state is current in your context ? no need to Read it back)

157. assistant (2026-06-21T17:37:45.562Z)

Server negotiation done. Now the tests ? let me extend `assets.test.js` (switcher + shim wiring) and `server.test.js` (N8 negotiation). First, append to assets.test.js:

158. user (2026-06-21T17:37:46.169Z)

```
1      // Static-site integrity ? the landing page + capture checklist + OG image ARE the
public
2      // product. server.test.js proves the VM host *serves* "/", "/capture", "/og.png"; this
3      // guards the CONTENT contract so a broken edit (deleted asset, broken form wiring, dead
4      // capture link, missing/!absolute OG image) fails CI instead of shipping to the live
site.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync, statSync } from "node:fs";
8      import { join } from "node:path";
9
10     const PUBLIC = join(import.meta.dirname, "..", "public");
11     const read = (f) => readFileSync(join(PUBLIC, f), "utf8");
12     const size = (f) => statSync(join(PUBLIC, f)).size;
```

159. user (2026-06-21T17:37:54.092Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

160. user (2026-06-21T17:37:59.189Z)

```
176     assert.doesNotMatch(om, /<iframe/i, "the reel must NOT be embedded here ? it's gated
behind request-access");
177     assert.doesNotMatch(om, /youtube/i, "no YouTube embed on own-model; the reel is shown
only after request-access");
178     assert.doesNotMatch(om, /i\.yting\.com/, "don't show the video thumbnail (players)
openly");
179     assert.match(om, /sample[\s\S]{0,80}request access|request access[\s\S]{0,80}sample/i,
"point users to request access for a sample output");
180     });
```

161. assistant (2026-06-21T17:38:03.388Z)

Now append the i18n wiring tests to assets.test.js:

162. user (2026-06-21T17:38:19.391Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

163. assistant (2026-06-21T17:38:42.666Z)

I need to add a `.json` MIME type so the shim's `fetch` of the catalogs serves correctly on the VM host. Let me add that, then write the N8 server tests.

164. user (2026-06-21T17:38:46.444Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\server.js has been updated successfully.
(file state is current in your context ? no need to Read it back)

165. assistant (2026-06-21T17:38:50.748Z)

Now append the N8 server negotiation tests:

166. user (2026-06-21T17:39:03.950Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

167. user (2026-06-21T17:39:09.852Z)

```
117     test("[VM host] GET /api/request-access -> 405", async () => {
118         assert.equal((await fetch(`${base}/api/request-access`)).status, 405);
119     });
```

168. user (2026-06-21T17:39:24.981Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\site\src\server.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

169. assistant (2026-06-21T17:39:35.523Z)

Now run the full site test suite:

170. user (2026-06-21T17:39:39.025Z)

```
v26.1.0
=== full site suite (node --test) ===
? ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number (0.9334ms)
? translate: active locale, then en fallback, then undefined (caller keeps the DOM default)
(0.1629ms)
? applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw key
(105.7614ms)
? validate requires a well-formed email (1.2408ms)
? isBot detects a filled honeypot only (0.1566ms)
? toRow maps + sanitizes a valid payload (0.2946ms)
? toRow rejects invalid enum values (0.1351ms)
? handleRequest inserts a valid submission via the store (29.2874ms)
? handleRequest drops a bot without inserting (0.6905ms)
? handleRequest rejects a bad email with 400 (0.495ms)
? handleRequest rejects invalid JSON with 400 (0.5304ms)
? d1Store issues the bound INSERT (Cloudflare path) (0.3747ms)
? sqliteStore persists a real row (node:sqlite round-trip ? the VM path) (9.5883ms)
? fetch routes: POST /api hits the handler, other paths delegate to ASSETS (2.8528ms)
? fetch rejects non-POST to the API with 405 (0.3631ms)
? buildSubmissionEmail summarizes the submission (0.4103ms)
? handleRequest notifies on a valid submission; a notify failure never breaks it (1.0446ms)
? handleRequest does NOT notify on a bot or a bad email (2.0427ms)
? site/public/locales mirrors repo-root /locales exactly (else: npm run copy:locales) (8.3289ms)
? [VM host] server.js serves the form (240.9821ms)
? [VM host] serves /capture and /og.png (4.8501ms)
? [VM host] serves the tool screencast as video/mp4 (plays in the post-signup reveal) (3.3878ms)
? [VM host] serves /own-model (5.5458ms)
? [VM host] serves the academy flyers (/flyer, /flyer-kn, /flyer-hi) as clean URLs (13.2715ms)
? [VM host] POST /api/request-access persists to SQLite (18.6943ms)
? [VM host] honeypot + bad email are rejected without persisting (8.9234ms)
? [VM host] GET /api/request-access -> 405 (1.6206ms)
? [VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page (4.1018ms)
? [VM host · N8] ?lang= overrides the browser language (2.1465ms)
? [VM host · N8] the persisted cookie beats Accept-Language (returning user keeps their choice)
(1.9584ms)
? [VM host · N8] unsupported/absent language falls back to en (never a locale we can't serve)
(2.4351ms)
? [VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages negotiate)
(1.0719ms)
```

```
? [VM host] serves the shared catalogs the shim fetches (/locales/*/common.json as JSON)
(1.3784ms)
? submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?') (336.1607ms)
? on failure the button is restored ? never stuck on a frozen 'Sending?' (63.2093ms)
? after sign-up BOTH videos appear and a ? closes the reveal (49.3741ms)
? the auto-close HOLDS while the reel is playing (no mid-watch cut-off) (51.0607ms)
? tests 62
? suites 0
? pass 62
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 2103.0146
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

171. assistant (2026-06-21T17:40:00.616Z)

All 62 site tests pass ? including the 5 N8 negotiation tests, the drift guard, the shim unit tests, and the catalog-serving test. Let me mark tasks complete and do a real-browser smoke check (the change is browser-observable: module load + catalog fetch + switcher click). I'll start the VM host and use the preview tools.

172. user (2026-06-21T17:40:01.055Z)

Updated task #7 status

173. user (2026-06-21T17:40:01.567Z)

Updated task #8 status

174. assistant (2026-06-21T17:40:40.646Z)

The preview tool needs a ``.claude/launch.json`` config. I'll point it at the worktree's `server.js`` (which serves its own `public/`` via `import.meta.dirname``, independent of cwd) so the preview reflects my B3 changes. Let me set that up and start it.

175. assistant (2026-06-21T17:40:42.093Z)

```
{
  "version": "0.0.1",
  "configurations": [
    {
      "name": "b3-site",
      "runtimeExecutable": "node",
      "runtimeArgs": ["C:/Users/avidu/Projects/khelsutra-b3-wt/site/server.js"],
      "port": 8099
    }
  ]
}
```

176. user (2026-06-21T17:40:42.096Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

177. user (2026-06-21T17:40:51.464Z)

```
1      {
2        "version": "0.0.1",
3        "configurations": [
4          {
5            "name": "khelsutra-web",
6            "runtimeExecutable": "npm",
7            "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--
```

```
strictPort"],
8         "port": 5173
9     },
10    {
11        "name": "khelsutra-site",
12        "runtimeExecutable": "node",
13        "runtimeArgs": ["site/server.js"],
14        "port": 8080
15    }
16 ]
17 }
18
```

178. assistant (2026-06-21T17:41:13.546Z)

There's an existing config. Let me add a `b3-site` entry pointing at the worktree server (it defaults to port 8080):

179. user (2026-06-21T17:41:16.225Z)

The file C:\Users\avidu\Projects\khelsutra\.claude\launch.json has been updated successfully. (file state is current in your context ? no need to Read it back)

180. user (2026-06-21T17:41:25.024Z)

```
{
  "serverId": "e1f6be34-35b2-4ca0-9299-2b32362baba7",
  "port": 8080,
  "name": "b3-site",
  "reused": false
}
```

Server started successfully on port 8080.

181. assistant (2026-06-21T17:41:35.301Z)

Server started. Let me load the homepage and verify the shim boots cleanly (no console errors) and the switcher renders:

182. user (2026-06-21T17:41:37.180Z)

Eval failed: Inspected target navigated or closed

183. assistant (2026-06-21T17:41:42.798Z)

Navigation interrupted the eval context (expected). Let me query the now-loaded page state:

184. user (2026-06-21T17:41:45.885Z)

```
{
  "buttons": [
    {
      "lang": "en",
      "pressed": "true",
      "text": "English"
    },
    {
      "lang": "kn",
      "pressed": "false",
      "text": "?????"
    },
    {
      "lang": "hi",
      "pressed": "false",
      "text": "?????"
    }
  ]
}
```

```

    }
  ],
  "heroLead": "KhelSutra finds every rally in your sess",
  "htmlLang": "en",
  "navHow": "How it works",
  "switcher": true,
  "url": "http://localhost:8080/"
}

```

185. assistant (2026-06-21T17:41:54.915Z)

Homepage boots cleanly ? switcher renders all 3 languages, English active. Now let me test the interactive switch to Kannada (click ? persist ? `` + catalog fetch) and check for console errors:

186. user (2026-06-21T17:41:58.887Z)

```

{
  "cookie": "khelsutra.lang=kn",
  "heroLeadStillEn": "KhelSutra finds every rally in",
  "htmlLang": "kn",
  "knLabel": "?????",
  "localStorage": "kn",
  "pressedEn": "false",
  "pressedKn": "true"
}

```

187. assistant (2026-06-21T17:42:10.258Z)

The interactive cycle works end-to-end in a real browser: click ? ``, `` + cookie persisted (shared key), `` toggled, `` label rendered from the fetched catalog. Hero text stays English ? correct for "en-only content first" (kn `

188. user (2026-06-21T17:42:11.210Z)

No console logs.

189. user (2026-06-21T17:42:12.077Z)

Eval failed: Inspected target navigated or closed

190. assistant (2026-06-21T17:42:18.495Z)

No console errors. Let me verify the reloaded page honors the persisted preference (N4 on the client ? `` with no `lang`):

191. user (2026-06-21T17:42:20.885Z)

```

{
  "htmlLang": "kn",
  "persisted": "kn",
  "pressedKn": "true",
  "url": "http://localhost:8080/"
}

```

192. assistant (2026-06-21T17:43:05.621Z)

Real-browser verification is complete and clean:

- ? Module shim loads, boots with **no console errors**
- ? Switcher renders all 3 languages (autonyms correct)
- ? Click ? `` change + `` + cookie persisted + `` toggled + catalog fetched/applied

- ? Persistence survives reload (persisted pref honored, no `?lang` needed)
- ? Hero stays English on kn ? correct "en-only content first" behavior

Let me stop the preview and update the tracker doc. First, load `preview\_stop` and read the doc regions:

193. user (2026-06-21T17:43:07.201Z)

```

124    ## 7. Deliverables & progress tracker    ? **source of truth**
125    Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**,
branched from `origin/master`, no stacking.
126
127    | ID | Deliverable | Workstream | Depends on | Gated? | Status | PR |
128    |----|-----|-----|-----|-----|-----|----|
129    | P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |
[#41](https://github.com/avidullu/khelsutra/pull/41) · engine
[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275) |
130    | B1 | **SPA i18n scaffold + language switcher, en-only** (react-i18next + detector +
`en` catalog + switcher + persistence + **jsdom render tests** + **browser-language negotiation
tests** $6.5 N1/N3?N7) | B | P0 | No | ? | [#42](https://github.com/avidullu/khelsutra/pull/42)
|
131    | B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys);
add **key-parity + no-bare-strings CI** | B | B1 | No | ? |
[#45](https://github.com/avidullu/khelsutra/pull/45) |
132    | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color
selection) | A | B2 | No | ? | [#60](https://github.com/avidullu/khelsutra/pull/60) |
133    | B3 | Tiny shared `t()` shim + `data-i18n` plumbing for `site/`, en-only (proves shared
catalogs across surfaces) | B | B2 | D-CATALOG-HOME | ? | ? |
134    | A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
135    | A6 | Plain-language framing for Request-Access GPU/storage questions | A | B3 | No | ?
| ? |
136    | A7 | Fix English-source recording gaps (add a placement diagram) before localizing | A
| ? | No | ? | ? |
137    | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? *SPA done; reel
watermark `font_path` = engine follow-up* | B | ? | D-FONT ? | ? |
[#46](https://github.com/avidullu/khelsutra/pull/46) |
138    | B5 | **Kannada (`kn`) catalog** ? render ? *SPA done (AI-draft, native review
pending); `site/` rides B3* | B | B2/B4 | D-LOCALES ? | ? |
[#47](https://github.com/avidullu/khelsutra/pull/47) |
139    | A3 | Localize **recording-education** (capture + homepage gist) to kn | A | B3/B5 |
D-LOCALES+D-FONT | ? | ? |
140    | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? |
[#61](https://github.com/avidullu/khelsutra/pull/61) |
141    | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) |
A | B2 | No | ? | [#62](https://github.com/avidullu/khelsutra/pull/62) |
142    | B6 | **Hindi (`hi`) catalog** ? render (the extensibility proof ? just a catalog) ?
*SPA done (AI-draft, native review pending)* | B | B5 | D-LOCALES ? | ? |
[#48](https://github.com/avidullu/khelsutra/pull/48) |
143    | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 |
No | ? | [#63](https://github.com/avidullu/khelsutra/pull/63) |
144    | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ?
| ? |
145    | B7 | *(deferred, cross-repo)* Engine **P2 backend customer-facing localization**
(report `customer_` + rejection reasons) | B | engine | **D-BACKEND-DEPTH, owner-gated** | ? |
? |
146
147    *** MILESTONE ? SPA fully trilingual (2026-06-21):** the `web/` Studio SPA now speaks
**en + kn + hi** end to end (B1?B2?B4?B5?B6, all merged). A **Kannada-default browser auto-
renders Kannada**, and the switcher walks kn ? hi ? en ? **proven by a Playwright screencast**
with `locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + `` tracked). This meets the owner's success criterion **on the SPA surface**. **Still open
for the full $9 DoD:** **B3** (the `site/` marketing surface via the shared `t()` shim ? the
homepage/capture pages are still English-only), **A3** (recording-education in kn/hi), the
**non-tech UX A-items**, and a **native-speaker review** of the AI-drafted kn/hi catalogs before
a wide public launch. Do **not** archive until both surfaces are trilingual.

```

194. assistant (2026-06-21T17:43:12.090Z)

Let me stop the preview server and make the doc edits. I'll mark task 9 in progress.

195. user (2026-06-21T17:43:13.156Z)

Server e1f6be34-35b2-4ca0-9299-2b32362baba7 stopped

196. user (2026-06-21T17:43:13.418Z)

Updated task #9 status

197. assistant (2026-06-21T17:43:26.768Z)

Now update the §7 B3 row and the milestone note:

198. user (2026-06-21T17:43:30.944Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

199. user (2026-06-21T17:43:40.977Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

200. assistant (2026-06-21T17:43:51.723Z)

Now the §8 D-CATALOG-HOME note:

201. user (2026-06-21T17:43:56.444Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

202. assistant (2026-06-21T17:44:00.972Z)

Now add a changelog entry at the end:

203. user (2026-06-21T17:44:01.963Z)

```
178      - `2026-06-21` ? **A5 (#62) landed.** Friendly engine-error mapping unified across ALL
SPA surfaces (ingest + build + rally-load) via a single `lib/errorText.ts` helper + a shared
`errors.*` catalog namespace: an `engine` failure shows the engine's own detail verbatim,
everything else a localized line (`engineGeneric` last resort). No more raw `ApiError`/`HTTP
500` text; `build.failed`/`rallies.load_failed` logs gain `code`+`detail`. 136 web tests green;
reviewed via a 2-lens adversarial workflow (folded its load-path consolidation nit).
179      - `2026-06-21` ? **A1 (#60) + A4 (#61) landed.** A1 = the plain-language `en` copy pass
(de-jargon). A4 = the non-tech / phone-first pass: 744px tap targets across the SPA (Tailwind
`min-h-11`/`h-11`), enlarged parsed-pill + sample chips, and **hover-only `title=` text surfaced
as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence)
? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.
**Still open in workstream A:** A5 (friendly engine-error map on the build path), A8
(background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-
education kn/hi), B3 (site/ trilingual) + native review.
180      - `2026-06-21` ? **? SPA MILESTONE: fully trilingual (owner directive "take it to
completion + screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ?
B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all
merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity.
**Playwright screencast** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ?
switch hi ? switch en, each with `<html lang>` tracked (`khelsutra-i18n-screencast.mp4` + per-
```

locale frames). kn/hi are ****AI-drafted ? native review pending****. ****Remaining for full \$9 DoD:****
B3 (the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.
181

204. user (2026-06-21T17:44:20.328Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

205. assistant (2026-06-21T17:44:29.362Z)

Now fix the two now-stale catalog-location references in `MULTILINGUAL\_EXPANSION.md` (the hoist this PR performed makes them factually wrong):

206. user (2026-06-21T17:44:30.357Z)

```
49      - *Reused unchanged:* the negotiation contract (persisted pref ? `?lang=` ? navigator ?  
`en`), the ICU catalog format, the `@fontsource` `unicode-range`-scoped self-host pattern  
(`main.tsx:7-8`), the key-parity + no-bare-strings + offline CI (`hygiene.test.ts`), the  
draft?review pipeline, the `<html lang>` sync (`i18n/index.ts:59-65`).  
50      - *New:* 7 `common.json` catalogs; `SUPPORTED_LOCALES` entries (`i18n/index.ts:18`); **4  
new Noto font imports**; an **es 3-form plural** allowance in the catalog + tooling; a **CJK  
lazy-load + offline-subset** strategy (Phase C); Thai line-break CSS safety net.  
51      - **? Catalog-home caveat `[verified]`:** catalogs today live at  
`web/src/i18n/locales/{en,kn,hi}/common.json` ? **not** a shared top-level `locales/` (the  
I18N_PLAN "D-CATALOG-HOME" diagram). This expansion adds siblings there. If FRIENDLY **B3** (the  
shared `site/` `t()` shim) hoists them to a shared dir first, these new catalogs move with them  
? sequence-aware, not a blocker.  
52
```

207. user (2026-06-21T17:44:39.263Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

208. user (2026-06-21T17:44:43.676Z)

```
107      ## 10. References  
108      **Internal `[verified]`:** `web/src/i18n/{index.ts,hygiene.test.ts}`, `web/src/main.tsx`  
(font-load pattern), `web/src/i18n/locales/{en,kn,hi}/common.json`;  
[`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md), engine `docs/I18N_PLAN.md`,  
`docs/UI_PROPOSAL.md`.  
109      **External `[researched]`:** Unicode CLDR v48 plural-rules chart  
(https://www.unicode.org/cldr/charts/48/supplemental/language\_plural\_rules.html) + plural-rules  
spec; W3C BCP-47 / Chinese script subtags (`zh-Hans`/`zh-Hant`); SIL Open Font License 1.1 +  
Noto CJK LICENSE (github.com/notofonts/noto-cjk); `@fontsource-variable/noto-  
sans-{thai,sc,jp,kr}`; W3C Thai line-breaking (`thai-gap`); react-i18next + i18next-icu.
```

209. user (2026-06-21T17:44:51.802Z)

The file C:\Users\avidu\Projects\khelsutra-b3-wt\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

210. assistant (2026-06-21T17:45:16.241Z)

Docs updated. Now the final pre-commit verification gate ? re-run the full web suite + build (the SPA now imports the `site.\*` keys too) and the full site suite, and review the complete worktree diff status:

211. user (2026-06-21T17:45:30.976Z)

```
=== WEB typecheck ===  
> khelsutra-web@0.0.0 typecheck
```

```
> tsc --noEmit

=== WEB tests ===
  Test Files  18 passed (18)
    Tests     168 passed (168)
=== WEB build ===
dist/assets/index-4RWwkpkY.css
  24.81 kB ? gzip:   5.42 kB
dist/assets/index-BeYb6DlG.js
375.05 kB ? gzip: 117.06 kB
? built in 1.38s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

212. assistant (2026-06-21T17:45:37.142Z)

Web fully green (typecheck, 168 tests, build). Let me review the worktree's full change set and clean up stray artifacts before staging:

213. user (2026-06-21T17:45:40.484Z)

```
=== untracked artifacts to clean ===
site/access.db
```

```
web/dist:
assets
index.html
(remove web/dist + site/access.db)
```

```
=== git status (porcelain) ===
 M docs/FRIENDLY_AND_MULTILINGUAL.md
 M docs/MULTILINGUAL_EXPANSION.md
RM web/src/i18n/locales/da/common.json -> locales/da/common.json
RM web/src/i18n/locales/en/common.json -> locales/en/common.json
RM web/src/i18n/locales/es/common.json -> locales/es/common.json
RM web/src/i18n/locales/hi/common.json -> locales/hi/common.json
RM web/src/i18n/locales/id/common.json -> locales/id/common.json
RM web/src/i18n/locales/kn/common.json -> locales/kn/common.json
 M site/package.json
 M site/public/capture.html
 M site/public/index.html
 M site/public/own-model.html
 M site/server.js
 M site/src/assets.test.js
 M site/src/server.test.js
 M web/src/i18n/hygiene.test.ts
 M web/src/i18n/index.ts
?? site/public/i18n.js
?? site/public/locales/
?? site/scripts/copy-locales.mjs
?? site/src/i18n.shim.test.js
?? site/src/locales-drift.test.js
```

```
=== rename detection (locales hoist) ===
RM web/src/i18n/locales/da/common.json -> locales/da/common.json
RM web/src/i18n/locales/en/common.json -> locales/en/common.json
RM web/src/i18n/locales/es/common.json -> locales/es/common.json
RM web/src/i18n/locales/hi/common.json -> locales/hi/common.json
RM web/src/i18n/locales/id/common.json -> locales/id/common.json
RM web/src/i18n/locales/kn/common.json -> locales/kn/common.json
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

214. assistant (2026-06-21T17:46:08.486Z)

The change set is exactly as intended (6 catalog renames + content, SPA re-point, site

shim/switcher/server/tests, docs). Let me run the site suite once more, then stage explicit paths and verify the staged set:

215. user (2026-06-21T17:46:13.144Z)

```
? tests 62
? pass 62
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

216. user (2026-06-21T17:46:21.230Z)

```
=== STAGED ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M docs/MULTILINGUAL_EXPANSION.md
R web/src/i18n/locales/da/common.json -> locales/da/common.json
R web/src/i18n/locales/en/common.json -> locales/en/common.json
R web/src/i18n/locales/es/common.json -> locales/es/common.json
R web/src/i18n/locales/hi/common.json -> locales/hi/common.json
R web/src/i18n/locales/id/common.json -> locales/id/common.json
R web/src/i18n/locales/kn/common.json -> locales/kn/common.json
M site/package.json
M site/public/capture.html
A site/public/i18n.js
M site/public/index.html
A site/public/locales/da/common.json
A site/public/locales/en/common.json
A site/public/locales/es/common.json
A site/public/locales/hi/common.json
A site/public/locales/id/common.json
A site/public/locales/kn/common.json
M site/public/own-model.html
A site/scripts/copy-locale.mjs
M site/server.js
M site/src/assets.test.js
A site/src/i18n.shim.test.js
A site/src/locales-drift.test.js
M site/src/server.test.js
M web/src/i18n/hygiene.test.ts
M web/src/i18n/index.ts
```

```
=== unstaged/untracked left (should be empty) ===
(none ? all intended changes staged)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

217. assistant (2026-06-21T17:46:30.749Z)

All intended changes staged, nothing stray, renames correctly detected. Let me re-verify the branch/HEAD per the branching-safety protocol, then commit:

218. user (2026-06-21T17:46:44.561Z)

```
BRANCH: feat/b3-site-i18n
base check ? commits ahead of origin/master (should be empty before commit):
--- committing ---
--- committed ---
dd6b505 feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME)

=== only-my-commit vs origin/master ===
dd6b505 feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

219. assistant (2026-06-21T17:46:52.640Z)

Clean ? only my commit `dd6b505` is ahead of `origin/master`. Now push and open the PR:

220. user (2026-06-21T17:46:55.588Z)

```
remote:
remote: Create a pull request for 'feat/b3-site-i18n' on GitHub by visiting:
remote:      https://github.com/avidullu/khelsutra/pull/new/feat/b3-site-i18n
remote:
branch 'feat/b3-site-i18n' set up to track 'origin/feat/b3-site-i18n'.
To https://github.com/avidullu/khelsutra.git
 * [new branch]      feat/b3-site-i18n -> feat/b3-site-i18n
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

221. user (2026-06-21T17:47:16.734Z)

```
https://github.com/avidullu/khelsutra/pull/70
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

222. assistant (2026-06-21T17:47:23.219Z)

PR opened: [khelsutra#70](https://github.com/avidullu/khelsutra/pull/70). Let me fill in the real PR number in the doc placeholders and push a follow-up commit:

223. user (2026-06-21T17:47:25.867Z)

```
=== verify replacements ===
133:| B3 | **Shared `t()`/`data-i18n` shim + persistent switcher for `site/`** ? hoist catalogs
to repo-root `/locales` (D-CATALOG-HOME), re-point the SPA, site copy-step + drift-guard,
`server.js` + shim negotiation ($6.5 **N8**); **en-only marketing content** (kn/hi rides A3) | B
| B2 | D-CATALOG-HOME ? | ? | [#70](https://github.com/avidullu/khelsutra/pull/70) |
181:- `2026-06-21` ? **B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)) landed ? the
marketing `site/` is now i18n-wired, en-only content.** Implements **D-CATALOG-HOME**: catalogs
hoisted to repo-root **`/locales`** (all 6 ? en/kn/hi + the merged es/da/id) as the single
source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ?
typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm
run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook) + a **drift-
guard test**. New **`site/public/i18n.js`** ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n`
walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the
2-form site languages); a **persistent en/kn/hi switcher** on `index`/`capture`/`own-model`; and
**`server.js` Accept-Language negotiation** matching the SPA EXACTLY (persisted cookie ?
`?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key). Tests: shim
unit test + drift guard + extended `assets`/`server` tests + the **$6.5 N8** negotiation suite ?
**62 site tests green**; real-browser smoke (switch ? persist ? reload). kn/hi *marketing*
translation is the next effort (**A3**). ? **Concurrency note:** built in an isolated `git
worktree` because a sibling **A9** session held uncommitted catalog WIP in the shared checkout ?
never clobbered.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

224. assistant (2026-06-21T17:47:33.941Z)

PR numbers filled in. Let me commit the doc update and push:

225. user (2026-06-21T17:47:38.756Z)

```
To https://github.com/avidullu/khelsutra.git
dd6b505..5ac1c63 feat/b3-site-i18n -> feat/b3-site-i18n
--- branch state ---
5ac1c63 docs(friendly-multilingual): fill PR #70 into the B3 tracker row + changelog
dd6b505 feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-
HOME)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

226. assistant (2026-06-21T17:47:46.560Z)

Both commits pushed. Per the instructions, I merge on green CI (web + site + Cloudflare build).
Let me check the CI status:

227. user (2026-06-21T17:47:55.090Z)

Workers Builds: hidden-king-khelsutra pending 0
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/bc02cd35-8c8a-4843-9150-9dcdd865706f>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

228. assistant (2026-06-21T17:48:02.132Z)

Only the Cloudflare Workers build shows so far (pending). Let me check what CI workflows exist (web + site tests) and re-poll:

229. user (2026-06-21T17:48:04.327Z)

=== workflows ===

parity.yml
test.yml

=== what they run (triggers + jobs) ===

.github/workflows/parity.yml:9:on:
.github/workflows/parity.yml:11: - cron: "17 6 * * *" # daily ~06:17 UTC
.github/workflows/parity.yml:21: runs-on: ubuntu-latest
.github/workflows/parity.yml:28: run: bash site/scripts/parity-check.sh
.github/workflows/test.yml:2:on:
.github/workflows/test.yml:3: push:
.github/workflows/test.yml:5: pull_request:
.github/workflows/test.yml:9: runs-on: ubuntu-latest
.github/workflows/test.yml:11: run:
.github/workflows/test.yml:17: node-version: "24" # node:sqlite is unflagged;
server.test.js boots the VM host
.github/workflows/test.yml:21: # script in a DOM); the Cloudflare Worker + VM-host RUNTIMES
stay dependency-free. `npm test`
.github/workflows/test.yml:24: - run: npm ci
.github/workflows/test.yml:25: - run: npm test
.github/workflows/test.yml:29: run: for f in scripts/*.sh; do echo "checking \$f"; bash -n "\$f"; done
.github/workflows/test.yml:33: runs-on: ubuntu-latest
.github/workflows/test.yml:35: run:
.github/workflows/test.yml:41: node-version: "24"
.github/workflows/test.yml:44: - run: npm ci
.github/workflows/test.yml:45: - run: npm run typecheck
.github/workflows/test.yml:46: - run: npm run test
.github/workflows/test.yml:47: - run: npm run build
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

230. assistant (2026-06-21T17:48:34.724Z)

CI is `test.yml` (web + site jobs on PR) + the Cloudflare Workers build. All map to what I verified locally. Let me wait for the checks to complete:

231. user (2026-06-21T17:49:21.969Z)

Workers Builds: hidden-king-khelsutra pass 0
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/bc02cd35-8c8a-4843-9150-9dcdd865706f>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

232. assistant (2026-06-21T17:49:30.258Z)

Cloudflare Workers build ****passed****. The GH Actions `test.yml` checks aren't appearing ? let me verify whether Actions actually run on this repo:

233. user (2026-06-21T17:49:33.875Z)

=== recent workflow runs (any?) ===

```
completed      success docs(appliance): flip T11 retention sweep to ? ? tool shipped (engine?
test master push 27912303083 34s 2026-06-21T17:39:23Z
completed      success docs(appliance): flip T11 retention sweep to ? (engine #299 shipped;
scheduling #301) test docs/t11-retention-done pull_request 27912275082 40s
2026-06-21T17:38:15Z
completed      success feat(web): A9 ? localized tap-only filter controls (#68) test
master push 27911969968 36s 2026-06-21T17:26:13Z
completed      success feat(web): A9 ? localized tap-only filter controls test
feat/a9-tap-filters pull_request 27911948093 31s 2026-06-21T17:25:18Z
completed      success feat(web): A9 ? localized tap-only filter controls test
feat/a9-tap-filters pull_request 27911932913 38s 2026-06-21T17:24:44Z
completed      success feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catal?
test master push 27911523266 38s 2026-06-21T17:08:21Z
completed      success feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs
test feat/mlx-phaseA-es-da-id pull_request 27911498681 33s
2026-06-21T17:07:18Z
completed      success feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs
test feat/mlx-phaseA-es-da-id pull_request 27911476443 42s
2026-06-21T17:06:23Z
```

=== runs for this branch ===

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

234. assistant (2026-06-21T17:50:17.299Z)

Two critical findings: ****(1)**** GitHub Actions DO run here, but ****no run triggered for my PR**** ? I must investigate. ****(2)**** Much more important: ****A9 (#68) has already merged to master**** (17:26) ? the sibling session committed and merged while I worked. My branch is based on the pre-A9 master, so merging B3 as-is would ****drop A9's `tap.` catalog keys**** (B3 moved the pre-A9 catalogs). This is exactly the silent-absorption hazard. Let me re-fetch and assess.

235. user (2026-06-21T17:50:21.491Z)

=== origin/master now ===

```
bea8a2a docs(appliance): flip T11 retention sweep to ? ? tool shipped (engine #299), scheduling
tracked (#301) (#69)
46e0244 feat(web): A9 ? localized tap-only filter controls (#68)
a2292ef feat(web): MULTILINGUAL Phase A ? Spanish/Danish/Indonesian SPA catalogs (#67)
```

=== my base vs current origin/master ===

```
my branch base: a2292ef08cd4ef602c5c5ec23a52825ece033707
origin/master: bea8a2ae329a270cbb7112e57d89138c472c4a6a
```

=== what A9 (#68) changed ===

```
docs/FRIENDLY_AND_MULTILINGUAL.md | 3 +-
docs/LOCAL_APPLIANCE_ARCHITECTURE.md | 8 ++---
web/src/App.tsx | 3 ++
web/src/components/QueryBar.tsx | 33 ++++++-----
web/src/components/TapFilters.test.tsx | 62 ++++++
web/src/components/TapFilters.tsx | 60 ++++++
web/src/i18n/hygiene.test.ts | 1 +
web/src/i18n/locales/da/common.json | 9 +++++
web/src/i18n/locales/en/common.json | 9 +++++
web/src/i18n/locales/es/common.json | 9 +++++
web/src/i18n/locales/hi/common.json | 9 +++++
web/src/i18n/locales/id/common.json | 9 +++++
web/src/i18n/locales/kn/common.json | 9 +++++
13 files changed, 205 insertions(+), 19 deletions(-)
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

236. assistant (2026-06-21T17:51:43.041Z)

This is the silent-absorption hazard materializing. `origin/master` advanced to **bea8a2a** ? A9 (#68) added `tap.\*` keys to all 6 catalogs (at `web/src/i18n/locales/`), which my B3 **moved** away. Merging B3 as-is would drop A9's tap-filter keys and break master. I must integrate the new master and carry A9's `tap.\*` into the hoisted `/locales`. Let me merge and see the exact conflicts:

237. user (2026-06-21T17:51:45.126Z)

```
Auto-merging docs/FRIENDLY_AND_MULTILINGUAL.md
Auto-merging site/public/locales/da/common.json
CONFLICT (content): Merge conflict in site/public/locales/da/common.json
Auto-merging site/public/locales/en/common.json
CONFLICT (content): Merge conflict in site/public/locales/en/common.json
Auto-merging site/public/locales/es/common.json
CONFLICT (content): Merge conflict in site/public/locales/es/common.json
Auto-merging site/public/locales/hi/common.json
CONFLICT (content): Merge conflict in site/public/locales/hi/common.json
Auto-merging site/public/locales/id/common.json
CONFLICT (content): Merge conflict in site/public/locales/id/common.json
Auto-merging site/public/locales/kn/common.json
CONFLICT (content): Merge conflict in site/public/locales/kn/common.json
Auto-merging web/src/i18n/hygiene.test.ts
Automatic merge failed; fix conflicts and then commit the result.
```

```
=== conflict status ===
UU site/public/locales/da/common.json
UU site/public/locales/en/common.json
UU site/public/locales/es/common.json
UU site/public/locales/hi/common.json
UU site/public/locales/id/common.json
UU site/public/locales/kn/common.json
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

238. assistant (2026-06-21T17:52:21.155Z)

The merge surfaced an interesting rename-detection ambiguity (only `site/public/locales/\*` conflicted, because I have two near-identical copies of the catalogs). Rather than interpret git's partial merge, I'll **deterministically rebuild** the catalogs from the authoritative source. Let me first inspect the actual post-merge state:

239. user (2026-06-21T17:52:21.970Z)

```
=== does /locales/en have BOTH tap.* and site.*? ===
tap: false | site: true | selection: true
```

```
=== web/src/i18n/locales still present? (should be gone ? hoisted) ===
STILL THERE
```

```
=== full conflict/merge status ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M docs/LOCAL_APPLIANCE_ARCHITECTURE.md
M site/README.md
UU site/public/locales/da/common.json
UU site/public/locales/en/common.json
UU site/public/locales/es/common.json
UU site/public/locales/hi/common.json
UU site/public/locales/id/common.json
UU site/public/locales/kn/common.json
A site/public/robots.txt
M web/src/App.tsx
```

```
M web/src/components/QueryBar.tsx
A web/src/components/TapFilters.test.tsx
A web/src/components/TapFilters.tsx
M web/src/i18n/hygiene.test.ts
```

=== is site/public/locales/en conflicted content (markers)? ===

2

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

240. assistant (2026-06-21T17:53:27.229Z)

Now I understand the tangle: git's rename detection got confused by my two near-identical catalog copies (`/locales/\*` + `site/public/locales/\*`), so `/locales/en` lost A9's `tap.\*`, the old `web/src/i18n/locales/` came back, and `site/public/locales/\*` conflicted. Rather than untangle git's heuristic output, I'll **deterministically rebuild** every catalog from the authoritative source (master's catalog with `tap.\*` + my `site.\*`). Let me write a resolution script:

241. assistant (2026-06-21T17:53:37.688Z)

```
// Merge-conflict resolution (B3 ? A9): deterministically rebuild the hoisted catalogs as the
UNION
// of master's catalog (incl. A9's tap.*) + B3's site.* namespace ? sidestepping git's rename-
detection
// ambiguity (two near-identical copies: /locales + site/public/locales). Authoritative source =
// origin/master's web/src/i18n/locales/*/common.json.
import { execSync } from "node:child_process";
import { writeFileSync, mkdirSync } from "node:fs";
import { join } from "node:path";

const root = import.meta.dirname;
const LOCALES = ["en", "kn", "hi", "es", "da", "id"];

const site = {
  nav: {
    how: "How it works",
    why: "Why it's hard",
    ownModel: "Own your model",
    flyer: "Flyer",
    roadmap: "Roadmap",
    faq: "FAQ",
    requestAccess: "Request access",
  },
  hero: {
    eyebrow: "Invite-only alpha · Bengaluru",
    lead: "KhelSutra finds every rally in your session and strips out the knock-ups, walks and
gaps ? so a full match becomes a clean highlight reel you can watch and download. No editing, no
scrubbing.",
    ctaPrimary: "Request alpha access",
    ctaHow: "See how it works",
  },
  capture: {
    title: "1-page capture checklist",
    intro: "Great highlights start with a steady, full-court recording. Five minutes of setup
makes a big difference to your reels.",
  },
  ownModel: {
    requestAccess: "Request access ?",
  },
};

const lines = JSON.stringify(site, null, 2).split("\n");
const body = lines.map((l, i) => (i === 0 ? l : " " + l)).join("\n");
const insertion = `  "site": ${body},\n`;
const ANCHOR = `  "selection": {`;
```

```

for (const loc of LOCALES) {
  const master = execSync(`git show origin/master:web/src/i18n/locales/${loc}/common.json`, {
    encoding: "utf8", cwd: root });
  if (master.includes('"site"')) throw new Error(`${loc}: master unexpectedly already has
site.*`);
  if (!master.includes('"tap"')) throw new Error(`${loc}: master is missing A9's tap.* ? wrong
source?`);
  if (!master.includes(ANCHOR)) throw new Error(`${loc}: anchor not found`);
  const out = master.replace(ANCHOR, insertion + ANCHOR);
  const parsed = JSON.parse(out);
  if (!parsed.tap || !parsed.site || !parsed.selection) throw new Error(`${loc}: union
incomplete`);
  mkdirSync(join(root, "locales", loc), { recursive: true });
  writeFileSync(join(root, "locales", loc, "common.json"), out);
  console.log(`${loc}: rebuilt (tap.* + site.* + selection) ?`);
}

```

242. user (2026-06-21T17:53:37.704Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-b3-wt_tmp_resolve.mjs (file state is current in your context ? no need to Read it back)

243. user (2026-06-21T17:53:47.176Z)

```

en: rebuilt (tap.* + site.* + selection) ?
kn: rebuilt (tap.* + site.* + selection) ?
hi: rebuilt (tap.* + site.* + selection) ?
es: rebuilt (tap.* + site.* + selection) ?
da: rebuilt (tap.* + site.* + selection) ?
id: rebuilt (tap.* + site.* + selection) ?

```

```

=== remove the re-introduced old catalog dir (hoist) ===
fatal: pathspec 'web/src/i18n/locales' did not match any files
removed web/src/i18n/locales

```

```

=== regenerate site/public/locales from rebuilt /locales (resolves UU + drift) ===
copy-locales: da, en, es, hi, id, kn -> site/public/locales/

```

```

=== verify union in /locales/en ===
tap: true site: true selection: true
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

244. assistant (2026-06-21T17:54:03.668Z)

`/locales/\*` now correctly holds the union (tap.* + site.* + selection); old dir removed; site copies regenerated. Let me stage the resolved catalogs, then verify the whole tree has no conflict markers and the docs auto-merged sanely:

245. user (2026-06-21T17:54:09.090Z)

```

=== remaining conflicts (should be none) ===
(no conflicts remain)

```

```

=== any conflict markers left in tracked files? ===

```

```

=== web/src/i18n/locales in index? (should be empty) ===

```

```

=== index.ts imports ===
16:import enCommon from "../../locales/en/common.json";

```

```

=== FRIENDLY doc: A9 + B3 rows + changelog ===

```

```

133:| B3 | **Shared `t()`\`data-i18n` shim + persistent switcher for `site/`** ? hoist catalogs
to repo-root `/locales` (D-CATALOG-HOME), re-point the SPA, site copy-step + drift-guard,
`server.js` + shim negotiation ($6.5 **N8**); **en-only marketing content** (kn/hi rides A3) | B

```

```
| B2 | D-CATALOG-HOME ? | ? | [#70](https://github.com/avidullu/khelsutra/pull/70) |
144:| A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ? |
[#68](https://github.com/avidullu/khelsutra/pull/68) |
177:- `2026-06-21` ? **A9 (#68) landed.** Localized tap-only filter controls (`TapFilters`:
Sort/Length/Count) so a non-English-typing kn/hi/? user can filter without typing the English
query syntax; each tap builds the same `ParsedQuery` the parser would (tap == type, test-
pinned). The English example chips now show only in English. 173 web tests; reviewed via a
2-lens adversarial workflow. **Workstream A: A1/A4/A5/A8/A9 ?; remaining A3 (recording-edu
kn/hi), A6/A7 (site), B3 (site trilingual).** *(Also note: MULTILINGUAL_EXPANSION Phase A ?
es/da/id ? shipped #67, so the SPA now speaks 6 languages.)*
182:- `2026-06-21` ? **B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)) landed ? the
marketing `site/` is now i18n-wired, en-only content.** Implements **D-CATALOG-HOME**: catalogs
hoisted to repo-root **`/locales`** (all 6 ? en/kn/hi + the merged es/da/id) as the single
source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ?
typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm
run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook) + a **drift-
guard test**. New **`site/public/i18n.js`** ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n`
walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the
2-form site languages); a **persistent en/kn/hi switcher** on `index`/`capture`/`own-model`; and
**`server.js` Accept-Language negotiation** matching the SPA EXACTLY (persisted cookie ?
`?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key). Tests: shim
unit test + drift guard + extended `assets`/`server` tests + the **$6.5 N8** negotiation suite ?
**62 site tests green**;; real-browser smoke (switch ? persist ? reload). kn/hi *marketing*
translation is the next effort (**A3**). ? **Concurrency note:** built in an isolated `git
worktree` because a sibling **A9** session held uncommitted catalog WIP in the shared checkout ?
never clobbered.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

246. assistant (2026-06-21T17:54:28.009Z)

Clean resolution ? no conflicts, no markers, hoist intact, and the FRIENDLY doc auto-merged perfectly (A9 row ?#68 + B3 row ?#70, both changelog entries). Now the critical step: re-run **both full suites against the merged tree** (A9's SPA changes + my B3 together) before committing the merge:

247. user (2026-06-21T17:54:43.353Z)

```
=== WEB typecheck ===
> khelsutra-web@0.0.0 typecheck
> tsc --noEmit

=== WEB tests ===
Test Files 19 passed (19)
Tests 173 passed (173)
=== WEB build ===
dist/assets/index-DhQCU3nG.js
377.90 kB ? gzip: 117.75 kB
? built in 1.68s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

248. assistant (2026-06-21T17:54:50.073Z)

Web merged tree fully green: typecheck, **173 tests** (my 168 + A9's 5 TapFilters tests, all passing together against the hoisted `/locales`), build succeeds. Now the site suite:

249. user (2026-06-21T17:54:54.388Z)

```
? the en catalog value matches the HTML default for representative data-i18n keys (no drift)
(1.0967ms)
? [VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page (2.4308ms)
? [VM host · N8] ?lang= overrides the browser language (2.15ms)
? [VM host · N8] the persisted cookie beats Accept-Language (returning user keeps their choice)
(1.9693ms)
? [VM host · N8] unsupported/absent language falls back to en (never a locale we can't serve)
```

```
(2.3979ms)
? [VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages negotiate)
(1.1345ms)
? tests 62
? pass 62
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

250. assistant (2026-06-21T17:55:02.615Z)

Both suites green against the merged tree (web 173, site 62 incl. all N8 + drift). Let me confirm the merge is fully staged and commit it:

251. user (2026-06-21T17:55:05.475Z)

```
=== unstaged changes (should be none meaningful) ===
(working tree clean re: unstaged)

=== merge state ===
All conflicts fixed but you are still merging.
Changes to be committed:
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

252. user (2026-06-21T17:55:14.825Z)

```
=== branch log ===
84e1f7c Merge origin/master into feat/b3-site-i18n ? integrate A9 (#68) tap-filters
5ac1c63 docs(friendly-multilingual): fill PR #70 into the B3 tracker row + changelog
dd6b505 feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME)

=== PR diff sanity: my branch vs master, top-level dirs touched ===
site/src/locales-drift.test.js      | 28 +++++
site/src/server.test.js             | 43 ++++++
web/src/i18n/hygiene.test.ts        | 3 +-
web/src/i18n/index.ts               | 20 ++--
27 files changed, 1442 insertions(+), 33 deletions(-)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

253. assistant (2026-06-21T17:55:26.954Z)

Merge committed. Let me verify the true PR diff (my branch vs current master) contains ****only B3 changes**** ? no A9 files absorbed:

254. user (2026-06-21T17:55:30.056Z)

```
=== PR diff = origin/master..HEAD (what B3 actually adds) ===
docs/FRIENDLY_AND_MULTILINGUAL.md | 7 +-
docs/MULTILINGUAL_EXPANSION.md    | 4 +-
{web/src/i18n/locales => locales}/da/common.json | 24 ++++
{web/src/i18n/locales => locales}/en/common.json | 24 ++++
{web/src/i18n/locales => locales}/es/common.json | 24 ++++
{web/src/i18n/locales => locales}/hi/common.json | 24 ++++
{web/src/i18n/locales => locales}/id/common.json | 24 ++++
{web/src/i18n/locales => locales}/kn/common.json | 24 ++++
site/package.json                  | 2 +
site/public/capture.html           | 15 ++-
site/public/i18n.js                | 130 ++++++
site/public/index.html             | 36 +----
site/public/locales/da/common.json | 137 ++++++
site/public/locales/en/common.json | 137 ++++++
site/public/locales/es/common.json | 137 ++++++
site/public/locales/hi/common.json | 137 ++++++
site/public/locales/id/common.json | 137 ++++++
```

```

site/public/locales/kn/common.json          | 137 ++++++
site/public/own-model.html                   | 16 +-
site/scripts/copy-locales.mjs                | 18 +++
site/server.js                              | 66 ++++++
site/src/assets.test.js                     | 52 ++++++
site/src/i18n.shim.test.js                  | 69 ++++++
site/src/locales-drift.test.js               | 28 +++++
site/src/server.test.js                     | 43 ++++++
web/src/i18n/hygiene.test.ts                 | 3 +-
web/src/i18n/index.ts                        | 20 +-
27 files changed, 1442 insertions(+), 33 deletions(-)

```

=== sanity: does the PR diff wrongly include A9-only files? ===
? no A9-only files ? PR diff is B3-only
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

255. assistant (2026-06-21T17:55:49.206Z)

PR diff is clean and B3-only ? the catalogs show as renames `{web/src/i18n/locales => locales}` carrying A9's `tap.\*` forward (+24 lines = my `site.\*`), and **no A9-only files** are absorbed. Let me push and check CI (and inspect why Actions didn't trigger before):

256. user (2026-06-21T17:55:52.507Z)

To <https://github.com/avidullu/khelsutra.git>
5ac1c63..84e1f7c feat/b3-site-i18n -> feat/b3-site-i18n

=== test.yml on: triggers ===

```

name: test
on:
  push:
    branches: [master]
  pull_request:

```

```

jobs:
  site:
    runs-on: ubuntu-latest
    defaults:
      run:
        working-directory: site

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

257. assistant (2026-06-21T17:56:03.453Z)

Now I see it: `test.yml` runs on `push` only for `master`, and on `pull\_request` events. The merge push should trigger a `pull\_request: synchronize` run. Let me poll CI:

258. user (2026-06-21T17:56:56.947Z)

=== runs for this branch ===

=== pr checks ===

Workers Builds: hidden-king-khelsutra pass 0
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/42c151ae-9be1-4628-951c-21f33eca72ad>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

259. assistant (2026-06-21T17:57:12.946Z)

Still only the Cloudflare check. The likely reason GH Actions didn't run initially: GitHub skips `pull\_request` workflows on PRs with **merge conflicts** (which #70 had, before my merge resolved them). Let me check the PR's mergeability now and whether Actions registered:

260. user (2026-06-21T17:57:16.599Z)

```
=== PR mergeability ===
{"mergeStateStatus":"DIRTY","mergeable":"CONFLICTING","state":"OPEN"}
```

```
=== all recent runs (last 6, any branch) ===
```

```
completed      success chore(site): add robots.txt + a "crawling / bot protection" runbook f?
test master    push    27912594399      38s      2026-06-21T17:50:57Z
completed      success chore(site): robots.txt + crawling/bot-protection runbook for
khelsutra.guru test    chore/site-crawl-hygiene      pull_request    27912565182      39s
2026-06-21T17:49:55Z
completed      success docs(appliance): flip T11 retention sweep to ? ? tool shipped (engine?
test master    push    27912303083      34s      2026-06-21T17:39:23Z
completed      success docs(appliance): flip T11 retention sweep to ? (engine #299 shipped;
scheduling #301) test    docs/t11-retention-done pull_request    27912275082      40s
2026-06-21T17:38:15Z
completed      success feat(web): A9 ? localized tap-only filter controls (#68)      test
master push    27911969968      36s      2026-06-21T17:26:13Z
completed      success feat(web): A9 ? localized tap-only filter controls      test
feat/a9-tap-filters pull_request    27911948093      31s      2026-06-21T17:25:18Z
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

261. assistant (2026-06-21T17:57:39.328Z)

The PR shows `CONFLICTING` because **master moved again** ? a "chore(site): robots.txt" PR merged at 17:50, **after** the master I merged from. GitHub recomputed against newer master. This is the shared-checkout churn in action. Let me re-fetch and see exactly what the new conflict is:

262. user (2026-06-21T17:57:44.267Z)

```
=== origin/master now ===
```

```
f7e2bd5 chore(site): add robots.txt + a "crawling / bot protection" runbook for khelsutra.guru
(#71)
bea8a2a docs(appliance): flip T11 retention sweep to ? ? tool shipped (engine #299), scheduling
tracked (#301) (#69)
46e0244 feat(web): A9 ? localized tap-only filter controls (#68)
```

```
=== my merge-base vs origin/master ===
```

```
merge-base: f7e2bd5d4d07511ec2f26c33c4fdab83cd7fba8e
master:      f7e2bd5d4d07511ec2f26c33c4fdab83cd7fba8e
```

```
=== what the newest master commit(s) changed (since my last merge) ===
```

```
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

263. assistant (2026-06-21T17:58:17.809Z)

`merge-base(HEAD, origin/master) == origin/master == f7e2bd5` ? meaning **my branch already contains all of master** (the robots #71 was included in my merge). So there's no real git conflict; GitHub's `CONFLICTING` is a stale async computation. Let me confirm ancestry and re-poll after giving GitHub time to recompute:

264. user (2026-06-21T17:59:03.710Z)

```
=== is origin/master fully contained in my branch? ===
```

```
YES ? master is an ancestor of HEAD; PR is a clean fast-forward, no real conflict
```

```
=== confirm my server.js has both negotiation + master is merged (robots present) ===
```

```
2
site/public/robots.txt
robots.txt present (from #71, merged in)
```

```
=== wait for GitHub to recompute, then re-poll ===
```

```
{"mergeStateStatus":"DIRTY","mergeable":"CONFLICTING"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

265. assistant (2026-06-21T17:59:45.545Z)

GitHub still reports stale `CONFLICTING` despite git confirming master is a clean ancestor (server.js has both my negotiation + the merged robots.txt). Let me verify the *remote* branch truly contains master, then force GitHub to recompute via the REST API (which returns `null` while computing):

266. user (2026-06-21T18:00:53.023Z)

```
remote branch HEAD: 84e1f7ca0a54474ba8ea1213f90c184faad24b91
local HEAD:         84e1f7ca0a54474ba8ea1213f90c184faad24b91
origin/master:      f7e2bd5d4d07511ec2f26c33c4fdab83cd7fba8e
? remote branch contains origin/master (no real conflict)
```

```
=== nudge GitHub recompute (REST mergeable; null=computing) ===
poll 1: dirty / mergeable=false
poll 2: dirty / mergeable=false
poll 3: dirty / mergeable=false
poll 4: dirty / mergeable=false
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

267. assistant (2026-06-21T18:01:06.987Z)

GitHub insists `mergeable=false` while git says my branch cleanly contains `origin/master` ? which is only possible if **master has moved again on the remote** since my last fetch (this is a very high-churn period ? #67/#68/#69/#71 all merged during my session). Let me re-fetch and check the real current master:

268. user (2026-06-21T18:01:11.809Z)

```
origin/master NOW: f7e2bd5d4d07511ec2f26c33c4fdab83cd7fba8e
my branch HEAD:    84e1f7ca0a54474ba8ea1213f90c184faad24b91
```

? still contains master

```
=== if behind, what changed in the new master commits vs files I touch ===
docs/FRIENDLY_AND_MULTILINGUAL.md
docs/MULTILINGUAL_EXPANSION.md
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/package.json
site/public/capture.html
site/public/i18n.js
site/public/index.html
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/own-model.html
site/scripts/copy-locales.mjs
site/server.js
site/src/assets.test.js
site/src/i18n.shim.test.js
site/src/locales-drift.test.js
site/src/server.test.js
web/src/i18n/hygiene.test.ts
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

269. assistant (2026-06-21T18:02:04.210Z)

Definitive: `origin/master` (f7e2bd5) is unchanged and **fully contained in my branch** ? merging is a clean fast-forward, so GitHub's `mergeable=false` is a stuck/stale computation (common during rapid base churn). The reliable fix: collapse my branch into one clean commit on top of the latest master and re-push ? this gives GitHub a fresh HEAD to evaluate (recompute

mergeability + trigger CI) and a clean linear PR. Let me do that:

270. user (2026-06-21T18:02:07.342Z)

=== staged set after soft-reset to master (should be the 27-file B3 diff) ===

```
web/src/i18n/hygiene.test.ts      |   3 +-
web/src/i18n/index.ts             |  20 ++-
27 files changed, 1442 insertions(+), 33 deletions(-)
```

=== sanity: no A9-only files staged ===

? B3-only

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

271. assistant (2026-06-21T18:02:13.330Z)

Clean B3-only staged set on top of the latest master. Let me commit as one clean commit and force-push (safe ? isolated PR branch):

272. user (2026-06-21T18:02:26.674Z)

=== new linear history ===

aff0a9a feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME)

To <https://github.com/avidullu/khelsutra.git>

+ 84e1f7c...aff0a9a feat/b3-site-i18n -> feat/b3-site-i18n (forced update)

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

273. assistant (2026-06-21T18:02:33.291Z)

Branch is now one clean commit (aff0a9a) on top of the latest master, force-pushed. This gives GitHub a fresh HEAD ? should recompute mergeability and trigger `test` CI. Let me poll:

274. user (2026-06-21T18:03:34.325Z)

=== mergeability ===

clean / mergeable=true

=== CI runs for this branch ===

completed success feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) test feat/b3-site-i18n pull_request 27912890934 36s
2026-06-21T18:02:31Z

=== pr checks ===

Workers Builds: hidden-king-khelsutra pass 0

<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/ff389419-3d43-4109-b9a5-60591b270aef>

site pass 17s

<https://github.com/avidullu/khelsutra/actions/runs/27912890934/job/82592973459>

web pass 32s

<https://github.com/avidullu/khelsutra/actions/runs/27912890934/job/82592973469>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

275. assistant (2026-06-21T18:03:52.528Z)

All CI green ? mergeable `clean`, and all three checks pass: **web** ?, **site** ?,

Cloudflare Workers build ?. Per the instruction (merge on green CI), let me squash-merge:

276. user (2026-06-21T18:03:57.838Z)

=== PR state ===

MERGED @ 2026-06-21T18:03:56Z

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

277. assistant (2026-06-21T18:04:21.284Z)

PR #70 is **MERGED** to master. Now let me clean up the worktree, branches, and the temporary launch.json entry, and confirm B3 landed on master:

278. user (2026-06-21T18:04:30.863Z)

```
f7e2bd5..1b1fa7b master -> origin/master
=== B3 on master? ===
1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) (#70)
f7e2bd5 chore(site): add robots.txt + a "crawling / bot protection" runbook for khelsutra.guru (#71)

=== remove worktree + branches ===
worktree removed
Deleted branch feat/b3-site-i18n (was aff0a9a).
To https://github.com/avidullu/khelsutra.git
- [deleted]          feat/b3-site-i18n

=== worktrees now ===
C:/Users/avidu/Projects/khelsutra 46e0244 [master]
```

279. assistant (2026-06-21T18:04:47.594Z)

B3 is confirmed on `origin/master` (1b1fa7b). Worktree and branches cleaned up. Let me revert the temporary launch.json entry I added (it points to the now-removed worktree):

280. user (2026-06-21T18:04:47.876Z)

```
1      {
2        "version": "0.0.1",
3        "configurations": [
4          {
5            "name": "khelsutra-web",
6            "runtimeExecutable": "npm",
7            "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
8            "port": 5173
9          },
10         {
11           "name": "khelsutra-site",
12           "runtimeExecutable": "node",
13           "runtimeArgs": ["site/server.js"],
14           "port": 8080
15         },
16         {
17           "name": "b3-site",
18           "runtimeExecutable": "node",
19           "runtimeArgs": ["C:/Users/avidu/Projects/khelsutra-b3-wt/site/server.js"],
20           "port": 8080
21         }
22       ]
23     }
24
```

281. user (2026-06-21T18:04:54.097Z)

The file C:\Users\avidu\Projects\khelsutra\claude\launch.json has been updated successfully. (file state is current in your context ? no need to Read it back)

282. assistant (2026-06-21T18:05:04.014Z)

Task #9 done ? let me mark it and check the project memory/handoff (B3 merging is a checkpoint

worth recording per the session-handoff convention):

283. user (2026-06-21T18:05:04.532Z)

Updated task #9 status

284. user (2026-06-21T18:05:06.318Z)

=== memory dir exists? ===
(no khelsutra memory dir)

=== MEMORY.md ===
(no MEMORY.md)

285. assistant (2026-06-21T18:05:24.636Z)

Let me check the actual projects directory structure to resolve the memory path:

286. user (2026-06-21T18:05:26.350Z)

```
C--Users-avidu-Projects-khelsutra
c--Users-avidu-Projects-Verifiers-khelsutra-badminton-highlight-indexer-badminton-highlight-indexer
---
C:/Users/avidu/.claude/projects/C--Users-avidu-Projects-khelsutra
C:/Users/avidu/.claude/projects/c--Users-avidu-Projects-Verifiers-khelsutra-badminton-highlight-indexer-badminton-highlight-indexer
```

287. assistant (2026-06-21T18:05:43.978Z)

The project dir exists but `memory/` doesn't yet ? this is a good moment to bootstrap the handoff/memory the conventions expect (B3 merge is a checkpoint, and this session surfaced a durable, non-obvious concurrency pattern). Let me create a lean set: a concurrency memory, a session handoff, and the index.

288. assistant (2026-06-21T18:05:54.621Z)

```
---
name: shared-checkout-concurrency
description: khelsutra is a shared single checkout with rapid concurrent master churn; isolate repo-writing work in a git worktree
metadata:
  type: project
---
```

The `khelsutra` repo is worked by **multiple concurrent sessions on ONE shared working checkout** (`C:/Users/avidu/Projects/khelsutra`). During the 2026-06-21 B3 session, master advanced **5+ times** (#67?#68?#69?#71?#70) within ~1 hour, and a sibling **A9** session had **uncommitted catalog WIP** sitting in the shared working tree that carried across a `git checkout`.

Why: the owner runs several parallel "slates"; the shared tree + current branch can shift under you between two commands, and sibling WIP must never be clobbered (a past incident had a squash-merge silently absorb sibling work).

How to apply (for any repo-writing task here):

- **Don't work in the shared checkout when a sibling may be active.** Create an isolated worktree: `git worktree add <path> -b <branch> origin/master` (or check out an existing branch). Run `npm ci` per package there (web/ + site/ each have their own `node\_modules`; not shared across worktrees). Clean up after merge: `git worktree remove <path> --force`.
- **Always branch from `origin/master`** and re-verify `git log origin/master..HEAD` shows **ONLY** your commits before opening a PR.
- **Stage explicit paths**, never `git add -A`.
- **Expect master to move mid-task.** If your PR shows `mergeable=false` but `git merge-base`

--is-ancestor origin/master HEAD` is true, GitHub's mergeability is just **stale** ? collapse to one clean commit on top of latest `origin/master` (`git reset --soft origin/master` + recommit) and `git push --force-with-lease` to force a fresh recompute (this also triggers the `test` workflow, which GitHub **skips** while a PR is CONFLICTING).

See [[catalog-home-and-i18n-layout]] for the i18n-specific contention (catalog files).

289. user (2026-06-21T18:05:54.634Z)

File created successfully at: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\shared-checkout-concurrency.md (file state is current in your context ? no need to Read it back)

290. assistant (2026-06-21T18:06:09.814Z)

```
---
name: catalog-home-and-i18n-layout
description: i18n catalogs live at repo-root /locales (D-CATALOG-HOME); SPA imports them, site mirrors them via a copy step
metadata:
  type: reference
---
```

After B3 (#70, 2026-06-21), the localization catalogs are the **single source of truth** at repo-root `/locales/{en,kn,hi,es,da,id}/common.json` (D-CATALOG-HOME). Both surfaces consume them:

- **SPA** (`web/`): `web/src/i18n/index.ts` imports `../../../../../locales/<lng>/common.json` directly. Vite resolves the workspace root via the repo .git` marker, so dev/build/vitest all read the parent-dir JSON. web/src/i18n/hygiene.test.ts` reads /locales` for key-parity + placeholder-parity (+ an es 3-form plural check). Adding a key to en means adding it to ALL locales or these tests fail.`
- **Marketing site** (`site/`, dependency-free): `site/scripts/copy-locales.mjs` mirrors /locales` ? site/public/locales/` (npm run copy:locales` ; predeploy` hook). The committed copy is what ships; site/src/locales-drift.test.js` fails CI if it drifts. The shim site/public/i18n.js` (vanilla t()`/data-i18n`, ICU-lite via Intl.PluralRules`) fetches those at runtime; server.js` does Accept-Language negotiation (cookie??lang?Accept-Language?en) and stamps <html lang>`.`

Negotiation contract (both surfaces, identical): **persisted** (`localStorage`/cookie key khelsutra.lang` ? ?lang=` ? navigator/Accept-Language ? `en` ; a missing key degrades to en, never a raw key.`

Marketing content is en-only so far (B3): the `site.*` namespace in the catalogs is authored in en; non-en site.*` values are en seeds pending translation (tracker A3). The SPA console strings (app/query/grid/footer/?) ARE translated for kn/hi/es/da/id. Because the SPA bundles the whole common.json`, it also ships the (unused) site.*` keys ? negligible.`

Catalog files are a **contention hotspot** across i18n PRs ? see [[shared-checkout-concurrency]].

291. user (2026-06-21T18:06:09.830Z)

File created successfully at: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\catalog-home-and-i18n-layout.md (file state is current in your context ? no need to Read it back)

292. assistant (2026-06-21T18:06:30.073Z)

Session handoff ? khelsutra (Friendly & Multilingual workstream)

Last updated: 2026-06-21, after B3 merged.

You are here

- **B3** just merged ([#70](https://github.com/avidullu/khelsutra/pull/70), squash `1b1fa7b` on master): the marketing `site/` is now i18n-wired (shared `t()`/`data-i18n` shim + persistent en/kn/hi switcher + `server.js` Accept-Language negotiation), and the catalogs are **hoisted** to repo-root `/locales` (D-CATALOG-HOME). **en-only** marketing content so far. Web 173 + site 62 tests green; merged on green CI (web + site + Cloudflare).
- The SPA (`web/`) was already fully trilingual+ (en/kn/hi + es/da/id) before this.
- Built in an isolated worktree to avoid a concurrent **A9** session's catalog WIP ? see `[[shared-checkout-concurrency]]`.

Next steps / open threads (tracker §7 of docs/FRIENDLY_AND_MULTILINGUAL.md)

- **A3** ? translate the marketing copy (`site.\*` namespace + recording-education) to kn/hi. Currently en-seeded. Gated on D-FONT for site (kn/hi glyphs need Noto on the marketing site too).
- **A2** WhatsApp share, **A6** plain-language Request-Access framing, **A7** recording diagram.
- **Native-speaker review** of the AI-drafted kn/hi catalogs before a wide public launch.
- Do NOT archive the project doc until BOTH surfaces render kn/hi *content* (not just en).

Ramp-up kit (read these to get current)

- `docs/FRIENDLY\_AND\_MULTILINGUAL.md` ? §7 tracker is the source of truth; §4 architecture; §6.5 negotiation matrix (N1?N9); §8 decisions.
- `/locales/en/common.json` ? the shared catalog (SPA console keys + the `site.\*` marketing namespace).
- `web/src/i18n/index.ts` + `web/src/i18n/hygiene.test.ts` ? SPA wiring + CI guards.
- `site/public/i18n.js` (shim), `site/server.js` (negotiation), `site/scripts/copy-locales.mjs` (the one build step), `site/src/{i18n.shim, locales-drift, assets, server}.test.js`.
- `[[catalog-home-and-i18n-layout]]` for the catalog layout + negotiation contract.

Key decisions (don't relitigate)

- **D-CATALOG-HOME**: catalogs at repo-root `/locales`; SPA imports them; site mirrors via `copy:locales` + drift guard.
- Marketing content is **en-only first** (prove the architecture); kn/hi marketing = A3.
- Negotiation order is identical across surfaces: persisted (`khelsutra.lang`) ? `?lang=` ? navigator/Accept-Language ? en; missing key ? en, never a raw key.
- Work in an **isolated git worktree** here (shared checkout, rapid master churn).

293. user (2026-06-21T18:06:30.086Z)

File created successfully at: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md (file state is current in your context ? no need to Read it back)

294. assistant (2026-06-21T18:06:39.375Z)

Memory index ? khelsutra

- **Start here**: `[session-handoff.md](session-handoff.md)` ? current state, next steps, ramp-up kit.
- `[Shared-checkout concurrency](shared-checkout-concurrency.md)` ? multiple sessions share ONE checkout + rapid master churn; isolate work in a git worktree.
- `[Catalog home & i18n layout](catalog-home-and-i18n-layout.md)` ? catalogs at repo-root `/locales` (D-CATALOG-HOME); SPA imports, site mirrors via copy step; negotiation contract.

295. user (2026-06-21T18:06:39.393Z)

File created successfully at: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\MEMORY.md (file state is current in your context ? no need to Read it back)

296. assistant (2026-06-21T18:07:07.683Z)

All done. Let me give a final summary.

B3 shipped ? marketing `site/` is now trilingual-wired ?

****Merged:**** [khelsutra#70](https://github.com/avidullu/khelsutra/pull/70) (squash `1b1fa7b` on master), on green CI ? ****web**** ?, ****site**** ?, ****Cloudflare Workers build**** ?.

Catalog-contention call

The MULTILINGUAL_EXPANSION PR (es/da/id) ****had merged**** to `origin/master` by the time I started, so per your locked rule I ****hoisted all 6 locales**** (en/kn/hi/es/da/id), not just the original three.

What landed (D-CATALOG-HOME)

- ****Hoist:**** `git mv web/src/i18n/locales/{6}/common.json ? repo-root` `/locales/` ****as the single source of truth. SPA re-pointed to `../../../locales` (Vite resolves the `.git` workspace root ? dev/build/vitest all work). **Web stays green: typecheck + 173 tests + build.****
- ****Shared `site.` namespace**** added to the catalogs (en authored to match the HTML; non-en seeded = en, pending translation) so ****key-parity + placeholder-parity stay green****.
- ****`site/public/i18n.js` ? vanilla `t(key,vars)` + `data-i18n` walker, ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for en/kn/hi). Missing key ? en ? HTML default, **never a raw key**.**
- ****Persistent en/kn/hi switcher**** on `index/` `capture/` `own-model.html` (driven by the shared `lang.` keys).
- ****`server.js` Accept-Language negotiation**** matching the SPA EXACTLY: persisted cookie ? `?lang=` ? `Accept-Language` ? en.
- ****Site build step + drift guard:**** `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook); `locales-drift.test.js` fails CI on drift.
- ****Tests:**** shim unit test + drift guard + extended `assets/` `server` tests + the ****\$6.5 N8**** suite. ****62 site tests green.**** Verified in a ****real browser**** (switch ? persist ? reload, no console errors).
- ****Docs:**** `FRIENDLY\_AND\_MULTILINGUAL.md` \$7 B3 ?#70, \$8 D-CATALOG-HOME marked implemented, changelog; corrected the stale catalog-location notes in `MULTILINGUAL\_EXPANSION.md`.

? Concurrency ? the part worth flagging

A ****sibling A9 session was live in the shared checkout****, with uncommitted `tap.` catalog WIP on the exact files B3 moves. I asked how to proceed; you didn't answer, so I took the safe default: ****did all B3 work in an isolated `git worktree`****, never touching that WIP. A9 then ****merged (#68) mid-flight****, so I merged the new master and resolved the catalog conflict ****deterministically**** ? `/locales` is now the union of A9's `tap.` + B3's `site.`. The final PR diff is ****B3-only**** (no absorbed A9 work). Cleaned up the worktree, branches, and a temporary launch config afterward.

Follow-ups (tracker \$7)

- ****A3**** ? translate the `site.` marketing copy + recording-education to kn/hi (currently en-seeded).
- Native-speaker review of the AI-drafted kn/hi catalogs before public launch.

I also bootstrapped a project memory + session-handoff (the shared-checkout/worktree pattern and the catalog layout) since this repo clearly has heavy multi-session churn.

One note: the main shared checkout is on a slightly-behind local `master` (a sibling's context) ? a `git pull --ff-only` there will pick up B3.

297. user (2026-06-21T18:10:11.904Z)

Would be great if you can pickup the follow ups and follow the same diligence of improved test coverage and CI tests and merge the PRs

298. assistant (2026-06-21T18:11:48.976Z)

Ultracode is on, and you've asked me to take the follow-ups with the same diligence and merge them. Before I fan out, one genuinely-yours scoping decision ? the open tracker rows differ in how "ready" they are, and one (A3) touches the human-review translation guardrail and a site-font question:

299. user (2026-06-21T18:16:16.076Z)

Your questions have been answered: "Which follow-up rows should I implement now? (one small PR each, strong tests + CI, merged on green ? isolated worktrees per the shared-checkout convention)"="A3 followed by A6 followed by A7". You can now continue with these answers in mind.

300. assistant (2026-06-21T18:17:43.328Z)

Got it ? **A3 ? A6 ? A7**, in that order (A2/WhatsApp deferred). I'll do each as its own PR with the same diligence: isolated worktree, strong tests + CI, adversarial multi-agent review before merge (ultracode), merged on green CI. Let me reset the task list and set up the shared worktree.

301. user (2026-06-21T18:17:46.242Z)

Task #10 created successfully: A3 ? kn/hi recording-education + marketing translation (site)

302. user (2026-06-21T18:17:47.629Z)

Task #11 created successfully: A6 ? plain-language Request-Access GPU/storage framing (site)

303. user (2026-06-21T18:17:49.045Z)

Task #12 created successfully: A7 ? camera-placement diagram on the capture page (site)

304. user (2026-06-21T18:18:04.210Z)

origin/master: 1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) (#70)

```
=== create shared follow-ups worktree on a3 branch from origin/master ===
Preparing worktree (new branch 'feat/a3-recording-l10n')
branch 'feat/a3-recording-l10n' set up to track 'origin/master'.
HEAD is now at 1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) (#70)
```

1b1fa7b feat(web+site): B3 ? trilingual marketing site via shared t()/data-i18n shim (D-CATALOG-HOME) (#70)

305. assistant (2026-06-21T18:18:17.235Z)

Worktree ready at B3 (1b1fa7b). Let me install deps and explore the A3 surface area in parallel ? the capture page, the homepage recording gist, and the current catalog state.

306. user (2026-06-21T18:18:24.923Z)

site deps ?
web deps ?

307. user (2026-06-21T18:18:24.976Z)

```
1      <!doctype html>
2      <html lang="en">
3      <head>
4      <meta charset="utf-8" />
5      <meta name="viewport" content="width=device-width, initial-scale=1" />
6      <title>KhelSutra ? 1-page capture checklist</title>
7      <meta name="description" content="How to record a badminton session so KhelSutra gives
you great highlight reels: camera placement, settings, stability, lighting." />
8      <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'%3E%3C/svg%3E" />
```

```

9      <link rel="preconnect" href="https://fonts.googleapis.com" />
10     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
11     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
12     <style>
13         :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--paper:#F6F8F4;--tx:#14271F;--
mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,sans-serif}
14         *{box-sizing:border-box}
15         body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.5;-webkit-font-smoothing:antialiased}
16         .sheet{max-width:820px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
17         .head{background:var(--ink);color:#EAF3EE;padding:22px 30px;display:flex;align-
items:center;justify-content:space-between;gap:1rem;flex-wrap:wrap}
18         .brand{display:flex;align-items:center;gap:.55rem;font-weight:800;font-size:1.2rem}
19         .brand .dot{color:var(--green)}
20         .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
21         .head h1{font-size:1.05rem;font-weight:600;margin:0;color:#C7F2B0}
22         /* persistent language switcher (B3) ? inherits header text colour, green fill =
active */
23         .langsw{display:inline-flex;gap:2px;border:1px solid rgba(255,255,255,.28);border-
radius:999px;padding:2px}
24         .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.7;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
25         .langsw button:hover{opacity:1}
26         .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
27         .body{padding:24px 30px 8px}
28         .intro{color:var(--mut);margin:0 0 16px;font-size:.98rem}
29         .rule{display:flex;gap:.7rem;background:#EAF6EF;border:1px solid #BfE6D2;border-
radius:12px;padding:14px 16px;margin-bottom:20px}
30         .rule .star{color:var(--green-d);font-size:1.3rem;line-height:1}
31         .rule b{color:var(--tx)}
32         .rule p{margin:.25rem 0 0;color:var(--mut);font-size:.92rem}
33         .grid{display:grid;grid-template-columns:1fr 1fr;gap:16px 26px}
34         .step h3{display:flex;align-items:center;gap:.5rem;font-size:1rem;font-
weight:700;margin:0 0 .4rem}
35         .step h3 .n{width:24px;height:24px;border-
radius:7px;background:var(--green);color:#04140D;display:flex;align-items:center;justify-
content:center;font-size:.85rem;flex:none}
36         .step ul{margin:0;padding-left:1.1rem}
37         .step li{margin:.18rem 0;font-size:.92rem;color:#34453d}
38         .step li b{color:var(--tx)}
39         .cols{display:grid;grid-template-columns:1fr 1fr;gap:0;border:1px solid
var(--line);border-radius:12px;overflow:hidden;margin:22px 0 8px}
40         .cols div{padding:14px 16px}
41         .cols .do{background:#EAF6EF}
42         .cols .dont{background:#Fbeeb;border-left:1px solid var(--line)}
43         .cols h4{margin:0 0 .5rem;font-size:.92rem}
44         .cols .do h4{color:var(--green-d)}
45         .cols .dont h4{color:#9a3b22}
46         .cols ul{margin:0;padding-left:1.1rem}
47         .cols li{font-size:.88rem;margin:.16rem 0;color:#3a4b43}
48         .consent{font-size:.86rem;color:var(--mut);border-top:1px solid var(--line);margin-
top:6px;padding:14px 0 4px}
49         .foot{display:flex;justify-content:space-between;flex-wrap:wrap;gap:.5rem;padding:14px
30px 24px;color:var(--mut);font-size:.85rem}
50         .foot a{color:var(--green-d);text-decoration:none}
51         @media (max-width:680px){.grid,.cols{grid-template-columns:1fr}.cols .dont{border-
left:0;border-top:1px solid var(--line)}}
52         @media print{
53             body{background:#fff}

```

```

54     .sheet{box-shadow:none;margin:0;max-width:none;border-radius:0}
55     @page{margin:12mm}
56     .noprint{display:none}
57 }
58 </style>
59 </head>
60 <body>
61 <script type="module" src="/i18n.js"></script>
62 <div class="sheet">
63     <div class="head">
64         <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
65         <h1 data-i18n="site.capture.title">1-page capture checklist</h1>
66         <div class="langsw" role="group" aria-label="Language">
67             <button type="button" data-lang="en" data-i18n="lang.en"
lang="en">English</button>
68             <button type="button" data-lang="kn" data-i18n="lang.kn" lang="kn">????</button>
69             <button type="button" data-lang="hi" data-i18n="lang.hi" lang="hi">?????</button>
70         </div>
71     </div>
72     <div class="body">
73         <p class="intro" data-i18n="site.capture.intro">Great highlights start with a
steady, full-court recording. Five minutes of setup makes a big difference to your reels.</p>
74
75         <div class="rule">
76             <span class="star" aria-hidden="true">?</span>
77             <div>
78                 <b>The golden rule: one match, one court, in full frame ? and don't move the
camera.</b>
79                 <p>Multi-court footage is the hard case we're still sharpening; a single court
in frame gives the best results today.</p>
80             </div>
81         </div>
82
83         <div class="grid">
84             <div class="step">
85                 <h3><span class="n">1</span>Place the camera</h3>
86                 <ul>
87                     <li>Behind <b>one baseline</b>, elevated ? a high tripod, a few metres up, or
a balcony.</li>
88                     <li>Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a
little margin and net headroom.</li>
89                     <li>Players should never leave the frame.</li>
90                 </ul>
91             </div>
92             <div class="step">
93                 <h3><span class="n">2</span>Settings</h3>
94                 <ul>
95                     <li><b>1080p or higher</b>, shot in <b>landscape</b>.</li>
96                     <li><b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table
tennis.</li>
97                     <li><b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise
reduction off.</li>
98                 </ul>
99             </div>
100             <div class="step">
101                 <h3><span class="n">3</span>Keep it still</h3>
102                 <ul>
103                     <li>Fixed tripod or mount.</li>
104                     <li><b>No panning, no zooming</b> during play.</li>
105                 </ul>
106             </div>
107             <div class="step">
108                 <h3><span class="n">4</span>Light & record</h3>
109                 <ul>
110                     <li>Even indoor lighting; avoid backlight, glare and very dark halls.</li>

```

```

111         <li>Record the <b>whole session</b> and upload it as-is ? KhelSutra does the
cutting.</li>
112     </ul>
113 </div>
114 </div>
115
116 <div class="cols">
117     <div class="do">
118         <h4>Do</h4>
119         <ul>
120             <li>Fixed camera, full court, behind the baseline</li>
121             <li>1080p+, landscape, audio on</li>
122             <li>One match on one court</li>
123         </ul>
124     </div>
125     <div class="dont">
126         <h4>Avoid</h4>
127         <ul>
128             <li>Handheld or phone-in-hand</li>
129             <li>Broadcast-style pans & zooming</li>
130             <li>Several courts in one frame; very dark halls</li>
131         </ul>
132     </div>
133 </div>
134
135     <p class="consent">Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.</p>
136 </div>
137 <div class="foot">
138     <span>Questions? <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></span>
139     <span class="noprint">Tip: press Ctrl/Cmd + P to print or save as PDF.</span>
140 </div>
141 </div>
142 </body>
143 </html>
144

```

308. assistant (2026-06-21T18:18:56.220Z)

Full capture page captured ? it's substantial recording-education content (rule, 4 steps, Do/Avoid, consent), much with inline `**` markup (so the shim needs a `data-i18n-html` variant). Let me read the homepage recording gist and confirm the catalog/font state.**

309. user (2026-06-21T18:18:58.396Z)

```

=== index.html #record section ===
339: <section id="record" style="background:#EFF4EC">
340:   <div class="wrap">
341:     <div class="sec-head">
342:       <div class="kicker">Record it right</div>
343:       <h2>Five minutes of setup ? reliably great reels</h2>
344:       <p>Highlight quality starts with the recording. Set the camera up once like this and
KhelSutra has everything it needs to find the rallies.</p>
345:     </div>
346:
347:     <div style="max-width:780px;margin:0 auto 1.6rem;display:flex;gap:.8rem;align-
items:flex-start;background:#fff;border:1px solid var(--line);border-left:4px solid
var(--green);border-radius:14px;padding:1rem 1.2rem">
348:       <span aria-hidden="true" style="color:var(--green-d);font-size:1.4rem;line-
height:1">?</span>
349:       <p style="margin:0;color:var(--tx)"><b>The golden rule: one match, one court, in full
frame ? and don't move the camera.</b> <span style="color:var(--mut)">A single court in frame
gives the best results today; busy multi-court footage is the hard case we're still
sharpening.</span></p>

```

```

350:     </div>
351:
352:     <div class="grid g4">
353:         <div class="card">
354:             <div class="ic" aria-hidden="true">?</div>
355:             <h3>Place the camera</h3>
356:             <p>Behind <b>one baseline</b>, elevated (a high tripod or a balcony), tilted down
~30° ? the <b>whole court</b> in frame, players never cropped.</p>
357:         </div>
358:         <div class="card">
359:             <div class="ic" aria-hidden="true">?</div>
360:             <h3>Settings</h3>
361:             <p><b>1080p</b>, landscape, <b>30 fps</b> for badminton (60 fps for table tennis).
<b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies.</p>
362:         </div>
363:         <div class="card">
364:             <div class="ic" aria-hidden="true">?</div>
365:             <h3>Keep it still</h3>
366:             <p>Fixed tripod or mount. <b>No panning, no zooming</b> during play ? a steady,
full-court view is what the tool is tuned for.</p>
367:         </div>
368:         <div class="card">
369:             <div class="ic" aria-hidden="true">?</div>
370:             <h3>Record & upload</h3>
371:             <p>Even lighting, then record the <b>whole session</b> and upload it as-is ?
KhelSutra finds the rallies and does the cutting.</p>
372:         </div>
373:     </div>
374:
375:     <div style="text-align:center;margin-top:1.6rem">
376:         <a class="btn btn-dark" href="/capture">Full 1-page capture checklist ?</a>
377:     </div>
378: </div>
379: </section>
---END---
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

310. assistant (2026-06-21T18:20:17.243Z)

I have both recording-education surfaces (homepage `#record` + the capture page), much with inline `**` markup. My plan for A3: add a `data-i18n-html` variant to the shim, bundle Noto via Google Fonts CDN, author the en recording-education keys + wire data-i18n, then draft & **adversarially verify** kn/hi translations via a workflow. Let me read the shim's `applyDom` and the font setup to start the infra changes.**

311. user (2026-06-21T18:20:18.426Z)

```

82     el.classList.toggle("is-active", on);
83 }
84 }
85
86 // ---- browser glue (skipped under the plain-node unit test, which has no document)
----
87 const readCookie = (name) => {
88     const m = (document.cookie || "").match(new RegExp("(?:^|; )" + name.replace(/\./g,
"\\.") + "=[^;]*"));
89     return m ? decodeURIComponent(m[1]) : null;
90 };
91
92 function persist(locale) {
93     try { localStorage.setItem(STORAGE_KEY, locale); } catch { /* private mode */ }
94     // Mirror to a cookie so server.js (VM host) can honor the persisted pref server-side
(no FOUC).
95     try { document.cookie = `${STORAGE_KEY}=${locale};path=/;max-
age=31536000;samesite=lax`; } catch { /* ignore */ }

```

```

96     }
97
98     async function loadCatalog(loc) {
99         try { const r = await fetch(`/locales/${loc}/common.json`); return r.ok ? await
r.json() : {}; } catch { return {}; }
100     }
101
102     async function render(locale) {
103         const catalogs = { en: await loadCatalog("en") };

```

312. user (2026-06-21T18:20:19.244Z)

```

9         <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
10         <link rel="preconnect" href="https://fonts.googleapis.com" />
11         <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
12         <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
13         <style>
14             :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--lime:#C7F2B0;--paper:#F6F8F4;-
-tx:#14271F;--mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans',system-ui,-apple-
system,Segoe UI,Roboto,sans-serif}
15             *{box-sizing:border-box}
16             body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.6;-webkit-font-smoothing:antialiased}

```

313. user (2026-06-21T18:20:26.261Z)

```

70
71     // Walk [data-i18n] under `root`; set textContent (or [data-i18n-attr] target). Missing
key -> skip.
72     export function applyDom(root, catalogs, locale) {
73         for (const el of root.querySelectorAll("[data-i18n]")) {
74             const val = translate(catalogs, locale, el.getAttribute("data-i18n"));
75             if (val == null) continue;
76             const attr = el.getAttribute("data-i18n-attr");
77             if (attr) el.setAttribute(attr, val); else el.textContent = val;
78         }
79         for (const el of root.querySelectorAll("[data-lang]")) {
80             const on = el.getAttribute("data-lang") === locale;
81             el.setAttribute("aria-pressed", String(on));
82             el.classList.toggle("is-active", on);
83         }
84     }

```

314. assistant (2026-06-21T18:20:31.537Z)

Let me mark A3 in progress and update the shim to support `data-i18n-html` (for the `**`-rich recording content):**

315. user (2026-06-21T18:20:32.021Z)

Updated task #10 status

316. user (2026-06-21T18:20:37.977Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

317. assistant (2026-06-21T18:21:01.412Z)

Now bundle Noto (Kannada + Devanagari) via Google Fonts CDN on all 3 marketing pages so kn/hi render cleanly. First the font `[link](#)` on each page:

318. user (2026-06-21T18:21:03.741Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

319. user (2026-06-21T18:21:06.284Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

320. user (2026-06-21T18:21:07.889Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

321. assistant (2026-06-21T18:21:18.712Z)

index.html in this worktree needs reading first. Let me read its head + `:root` region:

322. user (2026-06-21T18:21:19.465Z)

```
21     <link rel="preconnect" href="https://fonts.googleapis.com" />
22     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
23     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&display=swap" rel="stylesheet" />
24     <style>
25         :root{
26             --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
27             --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
28             --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
29             --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
30             --r:14px; --rs:10px; --maxw:1080px;
31             --font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe
UI,Roboto,Helvetica,Arial,sans-serif;
32         }
```

323. user (2026-06-21T18:21:29.664Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

324. assistant (2026-06-21T18:21:35.471Z)

Now extend the `--font` stack on all 3 pages so Indic glyphs fall back to Noto:

325. user (2026-06-21T18:21:37.410Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

326. user (2026-06-21T18:21:39.932Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

327. user (2026-06-21T18:21:41.327Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

328. assistant (2026-06-21T18:23:24.180Z)

Fonts wired (Noto via Google Fonts CDN, with `--font` fallback). Now I'll wire `data-i18n` into the recording-education content. Starting with the homepage `#record` section ? plain leaves get

`data-i18n`, inline-`<b>` sentences get `data-i18n-html`:

329. user (2026-06-21T18:23:41.187Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

330. assistant (2026-06-21T18:23:50.663Z)

Now the capture page content. The golden rule first:

331. user (2026-06-21T18:23:53.431Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

332. assistant (2026-06-21T18:23:58.183Z)

Now the 4 steps grid:

333. user (2026-06-21T18:24:09.805Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

334. assistant (2026-06-21T18:24:15.340Z)

Now the Do/Avoid columns and consent + print tip:

335. user (2026-06-21T18:24:23.739Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

336. assistant (2026-06-21T18:25:23.065Z)

All HTML wired. Now I'll define the full en `site` object (existing + new recording-education keys, matching the HTML exactly), then drive translation via a workflow. Let me author the en source:

337. assistant (2026-06-21T18:25:40.045Z)

```
// A3: the full en `site` namespace (existing B3 marketing keys + new recording-education keys),
// authored to EXACTLY match the marketing HTML defaults. Emits the nested object + a flat map.
import { writeFileSync } from "node:fs";
import { join } from "node:path";

export const siteEn = {
  nav: {
    how: "How it works",
    why: "Why it's hard",
    ownModel: "Own your model",
    flyer: "Flyer",
    roadmap: "Roadmap",
    faq: "FAQ",
    requestAccess: "Request access",
  },
  hero: {
    eyebrow: "Invite-only alpha · Bengaluru",
    lead: "KhelSutra finds every rally in your session and strips out the knock-ups, walks and
gaps ? so a full match becomes a clean highlight reel you can watch and download. No editing, no
scrubbing.",
    ctaPrimary: "Request alpha access",
```

```

ctaHow: "See how it works",
},
// Homepage "Record it right" gist (index.html #record).
record: {
  kicker: "Record it right",
  title: "Five minutes of setup ? reliably great reels",
  intro: "Highlight quality starts with the recording. Set the camera up once like this and
KhelSutra has everything it needs to find the rallies.",
  goldenRuleLead: "The golden rule: one match, one court, in full frame ? and don't move the
camera.",
  goldenRuleRest: "A single court in frame gives the best results today; busy multi-court
footage is the hard case we're still sharpening.",
  place: {
    title: "Place the camera",
    body: "Behind <b>one baseline</b>, elevated (a high tripod or a balcony), tilted down ~30°
? the <b>whole court</b> in frame, players never cropped.",
  },
  settings: {
    title: "Settings",
    body: "<b>1080p+</b>, landscape, <b>30 fps</b> for badminton (60 fps for table tennis).
<b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies.",
  },
  still: {
    title: "Keep it still",
    body: "Fixed tripod or mount. <b>No panning, no zooming</b> during play ? a steady, full-
court view is what the tool is tuned for.",
  },
  upload: {
    title: "Record & upload",
    body: "Even lighting, then record the <b>whole session</b> and upload it as-is ? KhelSutra
finds the rallies and does the cutting.",
  },
  checklistCta: "Full 1-page capture checklist ?",
},
// Full capture checklist (capture.html).
capture: {
  title: "1-page capture checklist",
  intro: "Great highlights start with a steady, full-court recording. Five minutes of setup
makes a big difference to your reels.",
  ruleLead: "The golden rule: one match, one court, in full frame ? and don't move the
camera.",
  ruleRest: "Multi-court footage is the hard case we're still sharpening; a single court in
frame gives the best results today.",
  step1: {
    title: "Place the camera",
    b1: "Behind <b>one baseline</b>, elevated ? a high tripod, a few metres up, or a
balcony.",
    b2: "Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a little margin
and net headroom.",
    b3: "Players should never leave the frame.",
  },
  step2: {
    title: "Settings",
    b1: "<b>1080p or higher</b>, shot in <b>landscape</b>.",
    b2: "<b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table tennis.",
    b3: "<b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise reduction off.",
  },
  step3: {
    title: "Keep it still",
    b1: "Fixed tripod or mount.",
    b2: "<b>No panning, no zooming</b> during play.",
  },
  step4: {
    title: "Light & record",
    b1: "Even indoor lighting; avoid backlight, glare and very dark halls.",
  },

```

```

    b2: "Record the <b>whole session</b> and upload it as-is ? KhelSutra does the cutting.",
  },
  doTitle: "Do",
  do1: "Fixed camera, full court, behind the baseline",
  do2: "1080p+, landscape, audio on",
  do3: "One match on one court",
  dontTitle: "Avoid",
  dont1: "Handheld or phone-in-hand",
  dont2: "Broadcast-style pans & zooming",
  dont3: "Several courts in one frame; very dark halls",
  consent: "Please record adults with their okay. Footage involving minors is never used to
improve the tool and is never published.",
  questions: "Questions?",
  printTip: "Tip: press Ctrl/Cmd + P to print or save as PDF.",
},
ownModel: {
  requestAccess: "Request access ?",
},
};

```

```

function flatten(obj, prefix = "") {
  const out = {};
  for (const [k, v] of Object.entries(obj)) {
    const key = prefix ? `${prefix}.${k}` : k;
    if (v && typeof v === "object") Object.assign(out, flatten(v, key));
    else out[key] = v;
  }
  return out;
}

```

```

const root = import.meta.dirname;
const flat = flatten(siteEn);
writeFileSync(join(root, "_tmp_site_en.json"), JSON.stringify(siteEn, null, 2));
writeFileSync(join(root, "_tmp_site_en_flat.json"), JSON.stringify(flat, null, 2));
console.log(`en site keys: ${Object.keys(flat).length}`);
console.log(JSON.stringify(flat, null, 2));

```

338. user (2026-06-21T18:25:40.077Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-fu-wt_tmp_a3_en.mjs (file state is current in your context ? no need to Read it back)

339. user (2026-06-21T18:25:52.942Z)

```

en site keys: 55
{
  "nav.how": "How it works",
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

340. assistant (2026-06-21T18:26:20.429Z)

55 keys. Now I'll drive the kn/hi translation through a workflow (ultracode): independent drafters ? per-key judge ? adversarial back-translation verify ? repair. Let me read the flat en map to feed it as input:

341. user (2026-06-21T18:26:20.624Z)

```

1      {
2        "nav.how": "How it works",
3        "nav.why": "Why it's hard",
4        "nav.ownModel": "Own your model",
5        "nav.flyer": "Flyer",
6        "nav.roadmap": "Roadmap",
7        "nav.faq": "FAQ",

```

```

8      "nav.requestAccess": "Request access",
9      "hero.eyebrow": "Invite-only alpha · Bengaluru",
10     "hero.lead": "KheISutra finds every rally in your session and strips out the knock-
ups, walks and gaps ? so a full match becomes a clean highlight reel you can watch and download.
No editing, no scrubbing.",
11     "hero.ctaPrimary": "Request alpha access",
12     "hero.ctaHow": "See how it works",
13     "record.kicker": "Record it right",
14     "record.title": "Five minutes of setup ? reliably great reels",
15     "record.intro": "Highlight quality starts with the recording. Set the camera up once
like this and KheISutra has everything it needs to find the rallies.",
16     "record.goldenRuleLead": "The golden rule: one match, one court, in full frame ? and
don't move the camera.",
17     "record.goldenRuleRest": "A single court in frame gives the best results today; busy
multi-court footage is the hard case we're still sharpening.",
18     "record.place.title": "Place the camera",
19     "record.place.body": "Behind <b>one baseline</b>, elevated (a high tripod or a
balcony), tilted down ~30° ? the <b>whole court</b> in frame, players never cropped.",
20     "record.settings.title": "Settings",
21     "record.settings.body": "<b>1080p+</b>, landscape, <b>30 fps</b> for badminton (60 fps
for table tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies.",
22     "record.still.title": "Keep it still",
23     "record.still.body": "Fixed tripod or mount. <b>No panning, no zooming</b> during play
? a steady, full-court view is what the tool is tuned for.",
24     "record.upload.title": "Record & upload",
25     "record.upload.body": "Even lighting, then record the <b>whole session</b> and upload
it as-is ? KheISutra finds the rallies and does the cutting.",
26     "record.checklistCta": "Full 1-page capture checklist ?",
27     "capture.title": "1-page capture checklist",
28     "capture.intro": "Great highlights start with a steady, full-court recording. Five
minutes of setup makes a big difference to your reels.",
29     "capture.ruleLead": "The golden rule: one match, one court, in full frame ? and don't
move the camera.",
30     "capture.ruleRest": "Multi-court footage is the hard case we're still sharpening; a
single court in frame gives the best results today.",
31     "capture.step1.title": "Place the camera",
32     "capture.step1.b1": "Behind <b>one baseline</b>, elevated ? a high tripod, a few
metres up, or a balcony.",
33     "capture.step1.b2": "Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame
with a little margin and net headroom.",
34     "capture.step1.b3": "Players should never leave the frame.",
35     "capture.step2.title": "Settings",
36     "capture.step2.b1": "<b>1080p or higher</b>, shot in <b>landscape</b>.",
37     "capture.step2.b2": "<b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table
tennis.",
38     "capture.step2.b3": "<b>Audio ON</b> (don't mute) ? keep the mic unobstructed,
wind/noise reduction off.",
39     "capture.step3.title": "Keep it still",
40     "capture.step3.b1": "Fixed tripod or mount.",
41     "capture.step3.b2": "<b>No panning, no zooming</b> during play.",
42     "capture.step4.title": "Light & record",
43     "capture.step4.b1": "Even indoor lighting; avoid backlight, glare and very dark
halls.",
44     "capture.step4.b2": "Record the <b>whole session</b> and upload it as-is ? KheISutra
does the cutting.",
45     "capture.doTitle": "Do",
46     "capture.do1": "Fixed camera, full court, behind the baseline",
47     "capture.do2": "1080p+, landscape, audio on",
48     "capture.do3": "One match on one court",
49     "capture.dontTitle": "Avoid",
50     "capture.dont1": "Handheld or phone-in-hand",
51     "capture.dont2": "Broadcast-style pans & zooming",
52     "capture.dont3": "Several courts in one frame; very dark halls",
53     "capture.consent": "Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.",

```

```
54     "capture.questions": "Questions?",
55     "capture.printTip": "Tip: press Ctrl/Cmd + P to print or save as PDF.",
56     "ownModel.requestAccess": "Request access ?"
57 }
```

342. assistant (2026-06-21T18:30:18.168Z)

Now I'll draft the kn/hi translations (preserving `**` tags, brand names, and technical tokens), then run an adversarial verification workflow. Let me write the drafts:**

343. assistant (2026-06-21T18:32:26.873Z)

```
// A3 kn/hi DRAFT translations of the site.* namespace (marketing + recording-education).
// AI-drafted (native review pending, same practice as B5/B6). Adversarially verified by the
// a3-verify workflow; flagged issues folded back here before writing to the catalogs.
// Rules honored: <b> tags preserved, brand "KheISutra" untranslated, technical tokens kept
// (1080p, 30 fps, 60 fps, 30°, Audio ON, PDF, Ctrl/Cmd + P), "?"/"." kept.
import { writeFileSync } from "node:fs";
import { join } from "node:path";

export const kn = {
  "nav.how": "??? ??? ???? ?????????",
  "nav.why": "??? ??? ????",
  "nav.ownModel": "??????? ??????",
  "nav.flyer": "????????",
  "nav.roadmap": "????????",
  "nav.faq": "????????????",
  "nav.requestAccess": "??????? ????",
  "hero.eyebrow": "???????-????? ????? . ?????????",
  "hero.lead": "KheISutra ????? ????????????? ?????????? ?????????? ??????, ???-????????, ?????
  ????? ?????????? ????????????????? ? ?????? ?????? ?????????? ??? ?????? ?????????? ?????????? ?????
  ?????? ??? ??????????. ?????? ?????????? ????, ?????????????? ????",
  "hero.ctaPrimary": "????? ?????? ????",
  "hero.ctaHow": "??? ??? ???? ?????????? ????",
  "record.kicker": "????????? ?????????? ????",
  "record.title": "??? ?????? ?????? ? ?????????? ?????????? ??????????",
  "record.intro": "??????? ???????? ?????????????????????? ??????????????????. ?????????????? ?????? ???
  ?????????? ??? ? ?????????????? ???????? KheISutra ?? ?????? ?????? ??????????",
  "record.goldenRuleLead": "??????? ????: ??? ??????, ??? ??????, ????? ?????????????? ? ?????
  ?????????????? ??????????????",
  "record.goldenRuleRest": "????? ?????? ?????????????? ?????? ??? ?????????? ???????? ??????????;
  ??? ?????????? ?????? ?????? ??? ?????? ?????????????????? ??? ??????",
  "record.place.title": "????????? ??????",
  "record.place.body": "<b>????? ??????????</b> ?????, ?????????? (????? ?????????? ??? ??????),
  ~30° ?????? ?????? ? <b>??? ??????</b> ??????????????, ?????? ?????? ??????????????????",
  "record.settings.title": "?????????????????",
  "record.settings.body": "<b>1080p+</b>, ?????????????????, ?????????????????? <b>30 fps</b> (?????
  ?????????? 60 fps). <b>Audio ON</b> ? ?????? ?????? ??? ?????????????? ?????? ??????????????",
  "record.still.title": "????????? ??????",
  "record.still.body": "????? ?????????? ??? ??????. ??? ?????????? <b>??????? ???, ??? ?????</b> ?
  ?????????, ???-????? ?????????? ? ?????????? ??????????????",
  "record.upload.title": "????????? ??? ?????? ?????????? ????",
  "record.upload.body": "????? ?????, ??? <b>??? ?????</b> ?????? ?????????? ??? ??????????
  ?????????? ??? ? KheISutra ?????????????? ?????? ?????????? ??? ??????????",
  "record.checklistCta": "???????? 1-???? ?????????? ?????????? ????",
  "capture.title": "1-???? ?????????? ?????????? ????",
  "capture.intro": "????? ?????????? ?????????, ???-????? ?????????????????? ??????????????. ???
  ?????? ???????? ?????? ?????????????? ?????? ?????????? ??????????",
  "capture.ruleLead": "??????? ????: ??? ?????, ??? ?????, ????? ?????????????? ? ?????
  ?????????????? ??????????????",
  "capture.ruleRest": "????? ?????????? ?????? ??? ?????? ?????????????????? ??? ??????; ??? ??????
  ?????????????? ?????? ??? ?????????? ?????????? ??????????",
  "capture.step1.title": "????????? ??????",
  "capture.step1.b1": "<b>????? ??????????</b> ?????, ?????????? ? ?????? ?????????, ????? ?????
  ?????????, ??? ??????????",
```

```
"capture.step1.b2": "????? <b>30°</b> ?????? ?????; ?????? ???? ????? ???? ????????  
????????? <b>??? ??????</b> ????????????? ?????.",  
"capture.step1.b3": "??????? ?????? ???????????? ????????????",  
"capture.step2.title": "???????????????",  
"capture.step2.b1": "<b>1080p ???? ??????</b>, <b>????????????????</b>????? ?????????????.",  
"capture.step2.b2": "??????????????/??????????????? <b>30 fps</b>; ?????? ?????????? <b>60  
fps</b>.",  
"capture.step2.b3": "<b>Audio ON</b> (????? ??????) ? ???? ???????????????? ?????, ???/????  
????????? ?? ????.",  
"capture.step3.title": "????????? ?????",  
"capture.step3.b1": "????? ?????????? ??? ????.",  
"capture.step3.b2": "?? ? ?????? <b>????? ???, ??? ????</b>.",  
"capture.step4.title": "????? ????? ?????????",  
"capture.step4.b1": "????? ?????? ?????; ???????, ??????? ?????? ?????? ??????? ??????????  
????????.",  
"capture.step4.b2": "<b>??? ?????</b> ?????? ?????????? ?????? ?????????? ?????????? ???? ? ??????????  
????????? KhelSutra ??????????",  
"capture.doTitle": "????",  
"capture.do1": "????? ?????????, ?????? ?????, ?????????? ??????",  
"capture.do2": "1080p+, ?????????????????, ?????? ???",  
"capture.do3": "????? ?????????????? ??? ??????",  
"capture.dontTitle": "????????",  
"capture.dont1": "????????? ?????? ??? ???? ??????",  
"capture.dont2": "????????-????? ?????? ?????? ????",  
"capture.dont3": "????? ?????????????? ???? ?????????????; ?????? ?????????? ??????????",  
"capture.consent": "????????? ?????????? ?? ?????????????????? ?????????? ????. ?????????? ??????????  
????????????????? ?????????? ?????????? ??????? ?????????????? ?????? ?????? ??????????????????",  
"capture.questions": "?????????????????",  
"capture.printTip": "????: ?????????? ??? PDF ??? ?????? Ctrl/Cmd + P ?????.",  
"ownModel.requestAccess": "?????? ????",  
};
```

```
export const hi = {  
  "nav.how": "?? ???? ?? ???? ??",  
  "nav.why": "?? ???? ??????? ??",  
  "nav.ownModel": "???? ???? ??????",  
  "nav.flyer": "????????",  
  "nav.roadmap": "??????",  
  "nav.faq": "??????? ??????",  
  "nav.requestAccess": "?????? ?? ?????? ?????",  
  "hero.eyebrow": "????-???????? ?????? . ??????????",  
  "hero.lead": "KhelSutra ??? ???? ?? ?? ???? ?????? ?? ?? ???-??, ?????????? ?? ?????????? ???  
???? ?? ? ?????? ???? ?? ???? ?????????? ??? ?? ???? ?? ???? ?? ???? ?? ?????? ?? ???? ???? ????  
????????? ???, ?? ?????????? ??????",  
  "hero.ctaPrimary": "????? ?????? ?? ?????? ?????",  
  "hero.ctaHow": "????? ?? ???? ?? ???? ??",  
  "record.kicker": "??? ?????? ?? ????????? ?????",  
  "record.title": "???? ???? ?? ???? ? ?? ?? ? ?????? ???",  
  "record.intro": "????????? ?? ?????????? ?????????????? ?? ?? ???? ???? ?? ???? ?? ???? ?? ??  
??? ?? ?????????? ?????? ?? ??? KhelSutra ?? ??? ?? ???? ???? ????",  
  "record.goldenRuleLead": "?????? ???? : ?? ???, ?? ?????, ???? ??????? ??? ? ?? ?????? ?  
?????????",  
  "record.goldenRuleRest": "?? ?? ?????? ?????? ??? ?? ?? ?? ???? ?????? ?????? ?????? ???; ?? ??????  
????? ?????????? ???? ??????? ?? ?????????? ?????? ?? ???? ?? ???? ?????? ??? ???? ??????",  
  "record.place.title": "????? ??????",  
  "record.place.body": "<b>?? ??????</b> ?? ???? , ?????? ?? (???? ?????????? ?? ??????), ~30° ????  
?????? ? <b>????? ?????</b> ?????? ???, ?????????? ??? ???? ??????",  
  "record.settings.title": "?????????",  
  "record.settings.body": "<b>1080p+</b>, ??????????, ?????????? ?? ??? <b>30 fps</b> (???? ??????  
?? ??? 60 fps)? <b>Audio ON</b> ? ??? ?? ???? ?????? ?????????? ?????? ??? ??? ???? ???",  
  "record.still.title": "??? ?????? ?????",  
  "record.still.body": "????? ?????????? ?? ?????? ??? ?? ?????? <b>? ??? ???? , ? ???? ????</b> ?  
?????, ????-????? ???? ???? ?? ??? ?? ???? ???? ????",  
  "record.upload.title": "????????? ???? ?? ?????? ?????",  
  "record.upload.body": "??-???? ?????, ??? <b>????? ????</b> ?????????? ???? ?? ???? ?? ???? ??"
```


(ultracode): a workflow runs 2 languages × 3 independent lenses (meaning fidelity / natural fluency / technical integrity), each writing flagged issues to a file. Let me launch it:

347. user (2026-06-21T18:34:30.631Z)

Workflow launched in background. Task ID: wkmkorp3q
Summary: Adversarially verify kn/hi site translations (meaning, fluency, technical integrity); each lens writes its issues to a file
Transcript dir: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\subagents\workflows\wf_e3715462-63d
Script file: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-verify-translations-wf_e3715462-63d.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-verify-translations-wf_e3715462-63d.js"}) to iterate without resending the script.)
Run ID: wf_e3715462-63d
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-verify-translations-wf_e3715462-63d.js", resumeFromRunId: "wf_e3715462-63d"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

348. assistant (2026-06-21T18:35:07.960Z)

The verification workflow is running in the background. While it does, let me prepare the deterministic catalog-write script (it'll read the final flat maps and replace the `site` block in all 6 catalogs ? en/es/da/id ? en, kn ? kn, hi ? hi):

349. assistant (2026-06-21T18:35:17.867Z)

```
// A3 catalog writer: replaces the `site` block in all 6 hoisted catalogs with the full A3
namespace.
// en/es/da/id <- en source (site is trilingual; es/da/id are key-parity seeds, never shown on
the
// site); kn <- Kannada, hi <- Hindi translations. Targeted text replacement (no full reformat)
so
// the diff is just the site block. Reads the (post-verification) flat maps.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const root = import.meta.dirname;
const LOCALES = join(root, "locales");
const readJson = (p) => JSON.parse(readFileSync(p, "utf8"));

function unflatten(flat) {
  const out = {};
  for (const [k, v] of Object.entries(flat)) {
    const parts = k.split(".");
    let o = out;
    for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] ??= {};
    o[parts[parts.length - 1]] = v;
  }
  return out;
}

const enObj = readJson(join(root, "_tmp_site_en.json")); // nested
const knObj = unflatten(readJson(join(root, "_tmp_kn_flat.json")));
const hiObj = unflatten(readJson(join(root, "_tmp_hi_flat.json")));
const siteFor = { en: enObj, es: enObj, da: enObj, id: enObj, kn: knObj, hi: hiObj };

// Build a depth-1-indented "  "site": {...}," block from a site object.
```

```

function siteBlock(obj) {
  const lines = JSON.stringify(obj, null, 2).split("\n");
  const body = lines.map((l, i) => (i === 0 ? l : "  " + l)).join("\n");
  return `  "site": ${body},\n`;
}

for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const file = join(LOCALES, loc, "common.json");
  const text = readFileSync(file, "utf8");
  const start = text.indexOf('  "site": {');
  const selStart = text.indexOf('  "selection": {');
  if (start < 0 || selStart < 0 || selStart < start) throw new Error(`${loc}: cannot locate
site/selection anchors`);
  const next = text.slice(0, start) + siteBlock(siteFor[loc]) + text.slice(selStart);
  const parsed = JSON.parse(next); // validate
  if (!parsed.site || !parsed.site.record || !parsed.site.capture.step1) throw new
Error(`${loc}: site block incomplete`);
  writeFileSync(file, next);
  console.log(`${loc}: site block written (${loc === "kn" || loc === "hi" ? "translated" : "en-
source"})`);
}

```

350. user (2026-06-21T18:35:17.891Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-fu-wt_tmp_a3_write.mjs (file state is current in your context ? no need to Read it back)

351. assistant (2026-06-21T18:35:42.542Z)

The write script is ready. While the verification workflow runs, let me prepare the A3 test additions (independent of its output). Let me read the current site test files to extend them:

352. user (2026-06-21T18:35:43.271Z)

```

56      <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
57      <button id="b-en" data-lang="en">English</button>
58      <button id="b-kn" data-lang="kn">?????</button>
59    </body>` ).window;
60
61    applyDom(document, catalogs, "kn");
62
63    assert.equal(document.getElementById("auto").textContent, "?????", "data-i18n sets
textContent from the shared catalog");
64    assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key
leaves the HTML default ? never a raw key");
65    assert.equal(document.getElementById("ph").getAttribute("placeholder"),
catalogs.en.site.capture.title, "data-i18n-attr targets an attribute");
66    assert.equal(document.getElementById("b-kn").getAttribute("aria-pressed"), "true",
"active locale button is pressed");
67    assert.equal(document.getElementById("b-en").getAttribute("aria-pressed"), "false",
"inactive locale button is not pressed");
68    assert.ok(document.getElementById("b-kn").classList.contains("is-active"), "active
button gets a non-color selection class");
69  });

```

353. user (2026-06-21T18:36:03.366Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

354. assistant (2026-06-21T18:36:27.765Z)

I need to fix that test ? `record.intro` contains "KhelSutra", which would trip the `doesNotMatch` English-words check. The in-script `match` already disproves en-seeds, so let me

drop the brittle line:

355. user (2026-06-21T18:36:33.932Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

356. assistant (2026-06-21T18:36:47.828Z)

Now the assets test additions (fonts + recording-education wiring). Let me read the tail of the worktree's assets.test.js:

357. user (2026-06-21T18:36:48.854Z)

```
222     });
223
224     test("the en catalog value matches the HTML default for representative data-i18n keys
(no drift)", () => {
225         // The HTML carries the English default text (SEO/no-JS); the en catalog must mirror
it so an en
226         // visitor renders identically and a future kn/hi translation simply overrides the
same string.
227         assert.match(read("capture.html"), /<h1 data-i18n="site\.capture\.title">1-page
capture checklist<\/h1>/);
228         assert.equal(enCatalog.site.capture.title, "1-page capture checklist");
229         assert.match(read("index.html"), /data-i18n="site\.nav\.requestAccess">Request
access<\/);
230         assert.equal(enCatalog.site.nav.requestAccess, "Request access");
231     });
232
```

358. user (2026-06-21T18:37:05.329Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

359. assistant (2026-06-21T18:37:29.695Z)

Tests prepared. The verification workflow is still running, but I can validate the full mechanical pipeline now with the current drafts (they already pass key/markup parity) ? writing the catalogs, copying, and running both suites de-risks early. Fixes from verification fold in later. Let me run the write + copy + tests:

360. user (2026-06-21T18:37:35.662Z)

```
en: site block written (en-source)
kn: site block written (translated)
hi: site block written (translated)
es: site block written (en-source)
da: site block written (en-source)
id: site block written (en-source)
```

copy-locales: da, en, es, hi, id, kn -> site/public/locales/

=== web hygiene (key-parity + placeholder-parity with new site keys) ===

```
Test Files  1 passed (1)
  Tests     28 passed (28)
  Start at  00:07:34
  Duration  708ms (transform 56ms, setup 21ms, collect 37ms, tests 19ms,
environment 0ms, prepare 258ms)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

361. assistant (2026-06-21T18:37:41.998Z)

Web hygiene green (28 tests) with the expanded catalogs. Now the full site suite (includes the new shim + assets A3 tests):

362. user (2026-06-21T18:37:45.881Z)

```
? A3: every marketing page bundles Noto Kannada + Devanagari so kn/hi render (not tofu)
(1.0482ms)
? A3: the recording-education content is wired for translation (homepage gist + capture page)
(1.6876ms)
? src\i18n.shim.test.js (104.5852ms)
? handleRequest notifies on a valid submission; a notify failure never breaks it (0.7447ms)
? src\ux.dom.test.js (105.0504ms)
? tests 56
? pass 54
? fail 2
? failing tests:
? src\i18n.shim.test.js (104.5852ms)
  'test failed'
? src\ux.dom.test.js (105.0504ms)
  'test failed'
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

363. assistant (2026-06-21T18:37:54.018Z)

Two failures ? let me see the actual errors (one in my new shim test, one in the existing ux.dom test which my index.html edits may have affected):

364. user (2026-06-21T18:37:55.484Z)

```
=== shim test failures ===
? src\i18n.shim.test.js (109.7009ms)
? tests 1
? suites 0
? pass 0
? fail 1
? cancelled 0
? skipped 0
? todo 0
? duration_ms 118.1371

? failing tests:

test at src\i18n.shim.test.js:1:1
? src\i18n.shim.test.js (109.7009ms)
  'test failed'
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

365. assistant (2026-06-21T18:38:03.995Z)

The file fails to load (1 file-level failure, not assertions). Let me get the full error:

366. user (2026-06-21T18:38:05.906Z)

```
Error [ERR_MODULE_NOT_FOUND]: Cannot find package 'jsdom' imported from
C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js
    at Object.getPackageJSONURL (node:internal/modules/package_json_reader:301:9)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

367. assistant (2026-06-21T18:38:19.835Z)

jsdom is missing from the worktree's `site/node\_modules` (both jsdom-using tests fail to load) ? the parallel `npm ci` likely didn't complete cleanly. Let me verify and reinstall:

368. user (2026-06-21T18:38:25.202Z)

```
jsdom MISSING ? installing
  run `npm fund` for details
```

```
found 0 vulnerabilities
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

369. user (2026-06-21T18:38:35.535Z)

```
? tests 66
? pass 64
? fail 2
? failing tests:
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

370. assistant (2026-06-21T18:38:41.763Z)

jsdom installed ? now 66 tests, but 2 real assertion failures. Let me see them:

371. user (2026-06-21T18:38:45.432Z)

```
? translate: active locale, then en fallback, then undefined (caller keeps the DOM default)
(1.1214ms)
```

```
AssertionError [ERR_ASSERTION]: Expected values to be strictly equal:
+ actual - expected
```

```
+ '1-???? ?????????? ?????????? ??????'
- '1-page capture checklist'
  ^
```

```
    at TestContext.<anonymous> (file:///C:/Users/avidu/Projects/khelsutra-fu-
wt/site/src/i18n.shim.test.js:48:10)
    at Test.runInAsyncScope (node:async_hooks:226:14)
    at Test.run (node:internal/test_runner/test:1306:25)
    at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
    at Test.postRun (node:internal/test_runner/test:1447:19)
    at Test.run (node:internal/test_runner/test:1372:12)
    at async Test.processPendingSubtests (node:internal/test_runner/test:897:7) {
  generatedMessage: true,
  --
```

```
? applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw key
(115.9878ms)
```

```
AssertionError [ERR_ASSERTION]: data-i18n-attr targets an attribute
+ actual - expected
```

```
+ '1-???? ?????????? ?????????? ??????'
- '1-page capture checklist'
  ^
```

```
    at TestContext.<anonymous> (file:///C:/Users/avidu/Projects/khelsutra-fu-
wt/site/src/i18n.shim.test.js:65:10)
    at Test.runInAsyncScope (node:async_hooks:226:14)
    at Test.run (node:internal/test_runner/test:1306:25)
    at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
    at Test.postRun (node:internal/test_runner/test:1447:19)
    at Test.run (node:internal/test_runner/test:1372:12)
    at async Test.processPendingSubtests (node:internal/test_runner/test:897:7) {
  generatedMessage: false,
  --
```

```
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

372. assistant (2026-06-21T18:39:19.951Z)

Both failures are B3 shim assertions that hardcoded the old "kn site.* == en seed" assumption ? A3 deliberately translates `site.capture.title` to Kannada now, which is the intended change. (ux.dom passes once jsdom is present.) Let me update those two assertions to reflect A3:

373. user (2026-06-21T18:39:20.999Z)

```
44     test("translate: active locale, then en fallback, then undefined (caller keeps the DOM
default)", () => {
45         assert.equal(translate(catalogs, "kn", "app.title"), catalogs.kn.app.title); // real
Kannada
46         assert.equal(translate(catalogs, "en", "lang.kn"), "?????"); // shared catalog autonomy
47         // B3 ships en-only marketing content: site.* in kn is the en seed -> Kannada visitor
sees English now.
48         assert.equal(translate(catalogs, "kn", "site.capture.title"),
catalogs.en.site.capture.title);
49         assert.equal(translate(catalogs, "kn", "does.not.exist"), undefined, "missing
everywhere -> undefined");
50     });
51
52     test("applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw
key", () => {
53         const { document } = new JSDOM(`<!doctype html><body>
54             <span id="auto" data-i18n="lang.kn">PLACEHOLDER</span>
55             <span id="keep" data-i18n="does.not.exist">KEEP ME</span>
56             <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
57             <button id="b-en" data-lang="en">English</button>
58             <button id="b-kn" data-lang="kn">?????</button>
59         </body>`).window;
60
61         applyDom(document, catalogs, "kn");
62
63         assert.equal(document.getElementById("auto").textContent, "?????", "data-i18n sets
textContent from the shared catalog");
64         assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key
leaves the HTML default ? never a raw key");
65         assert.equal(document.getElementById("ph").getAttribute("placeholder"),
catalogs.en.site.capture.title, "data-i18n-attr targets an attribute");
66         assert.equal(document.getElementById("b-kn").getAttribute("aria-pressed"), "true",
"active locale button is pressed");
```

374. user (2026-06-21T18:39:32.705Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

375. assistant (2026-06-21T18:39:39.585Z)

The verification workflow finished ? issues flagged: kn (7 meaning, 8 fluency, 0 integrity), hi (2 meaning, 11 fluency, 4 integrity). Let me finish the second shim-test fix, then review all flagged issues:

376. user (2026-06-21T18:39:44.054Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

377. user (2026-06-21T18:39:50.748Z)

```
Exit code 1
=== KN MEANING (7) ===
cat: _tmp_issues_kn_meaning.json: No such file or directory
```

378. assistant (2026-06-21T18:40:01.346Z)

The issue files aren't where expected ? let me locate where the verifier agents actually wrote them:

379. user (2026-06-21T18:40:03.467Z)

C:/Users/avidu/Projects/khelsutra/undefined/_tmp_issues_hi_fluency.json
C:/Users/avidu/Projects/khelsutra/undefined/_tmp_issues_hi_integrity.json
C:/Users/avidu/Projects/khelsutra/undefined/_tmp_issues_hi_meaning.json
C:/Users/avidu/Projects/khelsutra/undefined/_tmp_issues_kn_fluency.json
C:/Users/avidu/Projects/khelsutra/undefined/_tmp_issues_kn_meaning.json
C:/Users/avidu/Projects/khelsutra-fu-wt/_tmp_issues_kn_integrity.json
---also check main root---
(not in main root)

380. assistant (2026-06-21T18:40:29.644Z)

The verifier agents wrote to a stray `khelsutra/undefined/` dir (an args-interpolation quirk) but the content is intact. Let me read all 6 issue files:

381. user (2026-06-21T18:40:31.382Z)

=== undefined/_tmp_issues_kn_meaning ===

```
[
  {
    "key": "bulk.invert",
    "severity": "critical",
    "problem": "\"\"????????\" means 'rotate / turn around', not 'invert the selection'. The intended sense ? flip selected to unselected and vice-versa ? is lost, so the meaning is wrong.",
    "suggestion": "????? ?????????????? ????",
  },
  {
    "key": "footer.floorOne",
    "severity": "critical",
    "problem": "Adds the concept '?????' (engine) that is absent from the English ('it would be skipped'). The English deliberately states the consequence without naming any engine; the translation introduces a new actor/meaning.",
    "suggestion": "\"<b>????? ?????????? ???? ??????</b>????? {min} ?????? ?????? ?????????? ? ?????? ??????????????????, ????????? ???? ??????????????. ?????? ?????????????? ??????\"",
  },
  {
    "key": "footer.floorAll",
    "severity": "critical",
    "problem": "Adds '?????' (engine) which is not in the English ('they'd all be skipped'). The translation introduces an actor/meaning the source intentionally omits.",
    "suggestion": "\"<b>????????? ?????? {count} ??????????????</b> {min} ?????? ?????? ?????????? ? ?????????? ??????????????????, ????????? ???? ??????????????. ?????? ?????????????? ??????\"",
  },
  {
    "key": "footer.floorSomeRest",
    "severity": "critical",
    "problem": "The parenthetical meaning is altered: English explains the reason '(they're too short)', but the Kannada replaces it with '(???????? min_shot_count ?????)' = '(the engine's min_shot_count limit)', a different, technical statement that changes the meaning and exposes an internal token.",
    "suggestion": "\"{min} ?????? ?????? ?????????????? ?????????? ????????????????????? (??? ?????? ??????????????)\"",
  },
  {
    "key": "ingest.intro",
    "severity": "minor",
    "problem": "Adds meaning not in the English ('Point KhelSutra at a video and it finds the rallies for you'): the inserted phrase '????? ?????? ???? ?????????????????? ????' ('a bucket link or a file on the engine') introduces concepts the source intro does not contain.",
    "suggestion": "\"????????????????? ???? ?????????? ?????? ? ??? ?????? ?????????????? ?????????????? ?????? ?????? ?????????? ??????????????\"",
  },
  {
    "key": "ingest.reassure",
    "severity": "minor",
  },
]
```

```

    "problem": "Adds '?????????' ('on the server') not present in the English ('KheISutra keeps working'), introducing meaning beyond the source.",
    "suggestion": "??????? ?????? ? ????? ?????? ?????????????? ?????????? ??? ??????????????; ????? ?????? ????? ?????? ??????????."
  },
  {
    "key": "errors.networkError",
    "severity": "minor",
    "problem": "Wrong referent: the English names the product ('Can't reach KheISutra'), but the Kannada says '????? ??????????????' ('Can't reach the engine'), changing what cannot be reached.",
    "suggestion": "????????? ???????????????. ??? ??????????????"
  }
]

```

```

=== undefined/_tmp_issues_kn_fluency ===

```

```

[
  {
    "key": "bulk.invert",
    "severity": "critical",
    "problem": "\"???????\" reads as 'rotate/turn around' ? it does not convey 'invert the selection'. A coach/parent will be confused about what this button does.",
    "suggestion": "????? ??????"
  },
  {
    "key": "result.dismiss",
    "severity": "minor",
    "problem": "\"???????\" is formal/legalistic (used for dismissing an employee or a case). For closing a result card it sounds stiff and odd.",
    "suggestion": "?????"
  },
  {
    "key": "footer.floorOne",
    "severity": "critical",
    "problem": "\"????? ?????? ??????????????\" leaks the internal jargon '?????' (engine), which the English deliberately avoids ('it would be skipped'). Non-technical parents won't know what 'engine' means.",
    "suggestion": "<b>????? ?????? ??? ??????</b>????? {min} ?????? ?????? ?????????? ? ?????? ??????????????????, ???????? ??? ?????? ??????????. ?????? ?????? ?????????????? ??????."
  },
  {
    "key": "footer.floorAll",
    "severity": "critical",
    "problem": "Again leaks '?????' (engine) jargon absent from the English ('they'd all be skipped'). Confusing for the non-technical audience.",
    "suggestion": "<b>????? ?????? ??? {count} ??????????????</b> {min} ?????? ?????? ?????????? ? ?????????????? ??????????????????, ???????? ??? ?????? ??????????. ?????? ?????? ?????????????? ??????."
  },
  {
    "key": "footer.floorSomeRest",
    "severity": "critical",
    "problem": "Exposes a raw code token (min_shot_count) and '?????' jargon inside a <code> tag, while the English simply says '(they're too short)'. This is machine-like and meaningless to a coach/parent.",
    "suggestion": "????? {min} ?????? ?????? ?????????????????? ???????? ?????????????????? (??? ?????? ??????????)."
  },
  {
    "key": "ingest.intro",
    "severity": "minor",
    "problem": "Adds '????? ?????? ??? ?????????????????? ????' (bucket link / file on engine) which is jargon not present in the English intro; sounds technical and off-putting for parents/coaches.",
    "suggestion": "????????????????? ??? ?????? ??? ? ??? ?????? ?????????????? ???????????. ?????? ?????? ?????????? ??????????."
  }
]

```

```

    },
    {
      "key": "ingest.reassure",
      "severity": "minor",
      "problem": "'????????? ?????????? ???? ??????????????' leaks '?????' jargon; the English just says 'KhelSutra keeps working'. Sounds techy for the audience.",
      "suggestion": "????????? ?????????? ? ?????? ?????? ?????????????? ?????????? ???? ??????????????; ?????? ?????????? ?????? ?????????? ??????????."
    },
    {
      "key": "errors.networkError",
      "severity": "minor",
      "problem": "'?????? ??????????????????' exposes '?????' to the user; the English says 'Can't reach KhelSutra'. The product name is warmer and clearer than the internal term.",
      "suggestion": "????????? ??????????????????. ??? ??????????????????"
    }
  ]

=== ../khelsutra-fu-wt/_tmp_issues_kn_integrity ===
[]

```

382. assistant (2026-06-21T18:41:29.937Z)

Important discovery: the `undefined/` path quirk made the verifiers review the **entire** kn/hi catalogs (not just my A3 site keys) ? and every kn issue they flagged (`bulk.invert`, `footer.floor\*`, `ingest.\*`, `errors.networkError`) is a **pre-existing** B5/B6 SPA-console translation** issue (notably "engine" jargon leaking, wrong terms), **not** my A3 site translations. So my A3 keys passed; the catalog has separate, out-of-scope issues. Let me read the hi issues to confirm the pattern:

383. user (2026-06-21T18:41:32.701Z)

```

=== HI MEANING ===
[
  {
    "key": "footer.floorSomeRest",
    "severity": "minor",
    "problem": "EN's plain-language reason '(they're too short)' is dropped and replaced with a technical token absent from the source: '(???? ?? min_shot_count ????)' = '(the engine's min_shot_count limit)'. Adds jargon and a code token the source never shows to non-tech coaches/parents, and drops the simple 'too short' explanation.",
    "suggestion": "?????? {min} ?? ?? ?????? ???, ?????? ??? ???? ???? ???? (?? ???? ???? ???)?"
  },
  {
    "key": "ingest.intro",
    "severity": "minor",
    "problem": "Adds meaning not in the EN source. EN: 'Point KhelSutra at a video and it finds the rallies for you ? this can take a few minutes.' HI inserts an extra clause '? ?? ???? ???? ?? ???? ???? ???? ?' (a bucket link or a file on the engine) that the source does not contain.",
    "suggestion": "????????? ?? ?? ?????? ?????? ?? ?? ???? ???? ?????? ?????? ???? ? ???? ???? ???? ?? ???? ?????"
  }
]

=== HI INTEGRITY ===
[
  {
    "key": "footer.floorSomeRest",
    "severity": "critical",
    "problem": "Adds a <code> tag and the English token min_shot_count that are absent in the English source (EN has plain '(they're too short)'); introduces a tag mismatch and leftover untranslated technical token.",
    "suggestion": "?????? {min} ?? ?? ?????? ???, ?????? ??? ???? ???? ???? ???? (?? ???? ????

```

```

???)"
  },
  {
    "key": "ingest.intro",
    "severity": "critical",
    "problem": "Brand 'KheISutra' transliterated to ????????; brand must stay in Latin script.",
    "suggestion": "KheISutra ?? ?? ?????? ?????? ? ?? ?????? ?????? ?? ?????? ?????? ? ?? ??
    ?????? ?????? ?????? ?????? ??? ?????? ?? ?????? ??????"
  },
  {
    "key": "ingest.reassure",
    "severity": "critical",
    "problem": "Brand 'KheISutra' transliterated to ????????; brand must stay in Latin script.",
    "suggestion": "??????? ?????? ???????? ?? ? ?????? ???????? ?????? ?????? ?? ?? KheISutra ?????? ??
    ??? ?????? ?????? ??; ?????? ?????? ??? ??? ?????? ?? ?????? ??????"
  },
  {
    "key": "ingest.fileHint",
    "severity": "critical",
    "problem": "Brand 'KheISutra' transliterated to ????????; brand must stay in Latin script.",
    "suggestion": "?? ?????? ?? ?? .mp4 ?? .mov ?????? ? ?? ?????? ?????, ??? KheISutra ??????
    ?????? ??????"
  }
]

```

=== HI FLUENCY (keys only) ===

minor app.badge: "?????-???? ??" is a stiff, machine-like compound noun (lit. 'per-rally selection'). EN '

minor app.intro: "?? ??? ?????? ?????? ??" is an awkward word-for-word calque of 'Everything starts selec

minor grid.shots: "?????????????" is an over-Sanskritized, bookish word for 'experimental'. A non-tech coach/p

minor grid.shotsTitle: Both "?????????????" (experimental) and "?????????????" (under development) are stiff officiales

minor grid.shotsConfidence: "?????????" (faith/trust) is an odd literal rendering of 'confidence' here; for a numeric co

minor query.support: "?????????????" (experimental) and "?????????????" (under development) are over-formal/Sanskriti

minor result.dismiss: "????? ??" is formal/legalistic (used for dismissing a petition or an employee). For clo

critical footer.floorOne: "???? ? ? ? ? ? ? ? ?" leaks the internal term '????' (engine), which the English deliberate

critical footer.floorAll: "???? ? ? ? ? ? ? ? ? ? ?" again leaks '????' (engine) absent from the English ('they'd

minor errors.networkError: "???? ? ? ? ? ? ? ? ? ? ?" exposes the internal term '????' (engine); the English says 'C

minor ingest.reassure: "????????? ?????? ? ? ? ? ? ? ? ? ? ?" leaks the jargon '?????' (server); the English simply

384. assistant (2026-06-21T18:42:44.764Z)

Confirmed: **every flagged issue is in the pre-existing B5/B6 SPA-console keys** (`app.\*`, `footer.\*`, `ingest.\*`, `errors.\*`, `grid.\*`) ? **zero** issues in my A3 `site.\*` translations. The path quirk turned the verification into a full-catalog audit, which usefully surfaced real pre-existing bugs (hi transliterates the brand "KheISutra"? "?????????" in `ingest.\*`; both leak "engine"/"server" jargon and a `min\_shot\_count` code token; hi over-Sanskritizes). These are **out of A3's scope** (SPA console, already-merged B5/B6) ? I'll flag them as a separate follow-up, not bloat A3.

385. user (2026-06-21T18:43:04.886Z)

Noted (position 1, task_id: task_c54519de). A chip is showing for the user ? they can start it in a fresh worktree with one click, or dismiss it. If this suggestion becomes stale or superseded, call dismiss_task with this task_id. Currently pending: task_c54519de "Fix kn/hi SPA-console translation bugs (native-review)". Continue your current work.

386. assistant (2026-06-21T18:43:24.444Z)

I've flagged the out-of-scope SPA-console issues as a separate task. Now let me clean up the stray `undefined/` dir the workflow created in the main checkout (so it doesn't pollute the sibling's tree), and re-run the full site suite with my shim-test fixes:

387. user (2026-06-21T18:43:29.975Z)

```
cleaned main-checkout undefined/ dir
```

```
? tests 66
? pass 66
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

388. assistant (2026-06-21T18:43:36.386Z)

All 66 site tests pass. Now confirm the full web suite + build stays green with A3's expanded catalogs:

389. user (2026-06-21T18:43:52.848Z)

```
=== typecheck ===
> tsc --noEmit

=== tests ===
  Test Files   19 passed (19)
    Tests     173 passed (173)
=== build ===
dist/assets/index-CrEVnwwN.js
404.25 kB ? gzip: 123.56 kB
? built in 1.38s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

390. assistant (2026-06-21T18:44:17.449Z)

Web fully green (173 tests, build). The SPA bundle grew ~27KB (it now carries the full recording-education translations x6 in the shared `common.json` ? unused by the SPA; a candidate future optimization is a site-only namespace). Now a real-browser proof that kn renders with Noto (the font-render is the owner's eyeball gate, but I'll capture a screenshot). Let me wire the preview to the worktree server:

391. user (2026-06-21T18:44:17.935Z)

```
1      {
2        "version": "0.0.1",
3        "configurations": [
4          {
5            "name": "khelsutra-web",
6            "runtimeExecutable": "npm",
7            "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
8            "port": 5173
9          },
10         {
11           "name": "khelsutra-site",
12           "runtimeExecutable": "node",
13           "runtimeArgs": ["site/server.js"],
14           "port": 8080
15         }
16       ]
17     }
18
```

392. user (2026-06-21T18:44:24.845Z)

The file C:\Users\avidu\Projects\khelsutra\.claude\launch.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

393. user (2026-06-21T18:44:32.751Z)

```
{
  "serverId": "f98a5bb3-aba7-4756-a7ef-b443e1cdf130",
  "port": 8080,
  "name": "fu-site",
  "reused": false
}
```

Server started successfully on port 8080.

394. user (2026-06-21T18:44:39.677Z)

Eval failed: Inspected target navigated or closed

395. user (2026-06-21T18:44:48.896Z)

```
{
  "doTitle": "????",
  "h1": "1-???? ?????????? ????????? ??????",
  "hasBoldEl": true,
  "htmlLang": "kn",
  "step1b1_html": "<b>???? ??????????</b> ?????, ?????????? ? ?????? ?????????, ????? ??????
????????????, ??? ?????????.",
  "step1title": "????????? ??????",
  "url": "http://localhost:8080/capture?lang=kn"
}
```

396. assistant (2026-06-21T18:45:01.610Z)

The kn capture page renders end-to-end ? Kannada title, translated steps, and `data-i18n-html` correctly preserving `**` as a real element. Let me check console errors and capture a screenshot as proof of font rendering:**

397. user (2026-06-21T18:45:02.060Z)

No console logs.

398. user (2026-06-21T18:45:32.462Z)

preview_screenshot timed out after 30s. The preview window may be stuck (modal dialog, navigation hang, or unresponsive renderer). Check preview_console_logs for errors.

399. assistant (2026-06-21T18:45:43.095Z)

No console errors. The screenshot timed out (likely the Noto CDN fetch in the headless renderer) ? the functional proof (Kannada content + `data-i18n-html` working) is already solid via the DOM eval, and true glyph rendering is the owner's manual eyeball gate. Let me retry once, then move on regardless:

400. user (2026-06-21T18:46:13.479Z)

preview_screenshot timed out after 30s. The preview window may be stuck (modal dialog, navigation hang, or unresponsive renderer). Check preview_console_logs for errors.

401. assistant (2026-06-21T18:46:29.163Z)

No console errors and the DOM proof is conclusive (Kannada content + working `data-i18n-html`); the screenshot hang is the headless renderer waiting on the Google-Fonts CDN, not a code issue,

and glyph rendering is the owner's manual gate regardless. Let me stop the preview, clean up temp files, and review the final A3 diff:

402. user (2026-06-21T18:46:29.674Z)

Server f98a5bb3-aba7-4756-a7ef-b443e1cdf130 stopped

403. user (2026-06-21T18:46:32.369Z)

cleaned worktree temp files

=== git status (only intended A3 changes?) ===

```
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/capture.html
M site/public/i18n.js
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/public/own-model.html
M site/src/assets.test.js
M site/src/i18n.shim.test.js
?? site/access.db
```

=== diff stat vs origin/master ===

```
locales/da/common.json      | 61 ++++++-----
locales/en/common.json      | 61 ++++++-----
locales/es/common.json      | 61 ++++++-----
locales/hi/common.json      | 87 ++++++-----
locales/id/common.json      | 61 ++++++-----
locales/kn/common.json      | 87 ++++++-----
site/public/capture.html    | 58 ++++++-----
site/public/i18n.js         | 15 +----
site/public/index.html      | 30 ++++++-----
site/public/locales/da/common.json | 61 ++++++-----
site/public/locales/en/common.json | 61 ++++++-----
site/public/locales/es/common.json | 61 ++++++-----
site/public/locales/hi/common.json | 87 ++++++-----
site/public/locales/id/common.json | 61 ++++++-----
site/public/locales/kn/common.json | 87 ++++++-----
site/public/own-model.html   | 4 +-
site/src/assets.test.js     | 32 ++++++
site/src/i18n.shim.test.js  | 46 ++++++-----
web/src/App.tsx             | 5 +-
web/src/api/client.ts       | 11 +-
web/src/api/locale.test.ts  | 45 -----
web/src/components/IngestPanel.tsx | 8 +-
web/src/components/build-error.test.tsx | 20 -----
web/src/hooks/useIngestJob.ts | 4 +-
24 files changed, 914 insertions(+), 200 deletions(-)
Shell cwd was reset to C:\Users\avidu\Projects\kheldutra
```

404. assistant (2026-06-21T18:47:03.761Z)

`origin/master` has moved again (the diff shows web/* files from a newly-merged PR ? API/ingest/locale changes my branch lacks). Those don't touch `/locales` or `site/`, so no

conflict with A3, but I must integrate to be current. Let me re-fetch and assess:

405. user (2026-06-21T18:47:06.232Z)

```
origin/master: c1848df feat(web): LW2 ? send the UI locale to /api/compile (watermark) +  
/api/process (analytics) (#73)  
my base:      1b1fa7b355b0dc758c0261e7bde0b1aa33efa0e6
```

```
=== new commits on master since my base ===  
c1848df feat(web): LW2 ? send the UI locale to /api/compile (watermark) + /api/process  
(analytics) (#73)
```

```
=== do the new master commits touch /locales or site/ (conflict risk)? ===  
(none ? no overlap with A3)  
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

406. assistant (2026-06-21T18:47:28.045Z)

`origin/master` is now c1848df (#73 LW2, web-only ? **no overlap with A3**). Clean integration ahead. Let me stage A3's explicit paths, commit, and rebase onto the new master:

407. user (2026-06-21T18:47:31.630Z)

```
=== staged ===  
M locales/da/common.json  
M locales/en/common.json  
M locales/es/common.json  
M locales/hi/common.json  
M locales/id/common.json  
M locales/kn/common.json  
M site/public/capture.html  
M site/public/i18n.js  
M site/public/index.html  
M site/public/locales/da/common.json  
M site/public/locales/en/common.json  
M site/public/locales/es/common.json  
M site/public/locales/hi/common.json  
M site/public/locales/id/common.json  
M site/public/locales/kn/common.json  
M site/public/own-model.html  
M site/src/assets.test.js  
M site/src/i18n.shim.test.js
```

```
=== nothing stray staged? ===  
? only A3 paths staged  
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

408. user (2026-06-21T18:47:49.999Z)

```
committed: a026299 feat(site): A3 ? localize recording-education + marketing to kn/hi (Noto on  
the site)
```

```
=== rebase onto origin/master (no overlap -> clean) ===  
Rebasing (1/1)
```

Successfully rebased and updated refs/heads/feat/a3-recording-l10n.

```
=== branch state (A3 atop c1848df) ===  
5166ec6 feat(site): A3 ? localize recording-education + marketing to kn/hi (Noto on the site)  
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

409. assistant (2026-06-21T18:48:16.564Z)

A3 committed (5166ec6) and cleanly rebased onto c1848df. Now an adversarial **code** review

(ultracode) on the A3 code changes before merge. Let me capture the code-only diff (excluding the already-verified translation bulk) to feed the review:

410. user (2026-06-21T18:48:19.463Z)

```
=== code diff size (excl. catalog JSON) ===
339
```

```
=== en catalog new keys (for reviewer context) ===
51
en site.* keys added/changed
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

411. assistant (2026-06-21T18:49:05.136Z)

339-line code diff. Let me run an adversarial code-review workflow (ultracode) over the A3 code changes ? four independent lenses (correctness/regression, a11y, i18n+innerHTML safety, test coverage). I'll hardcode the worktree path (with an args fallback) to avoid the earlier path quirk:

412. user (2026-06-21T18:49:28.103Z)

```
Workflow launched in background. Task ID: wzvhy78x3
Summary: Adversarial multi-lens review of the A3 site i18n code changes (shim/fonts/HTML/tests)
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\subagents\workflows\wf_f40bdb2b-ed3
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-code-review-
wf_f40bdb2b-ed3.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath:
"C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-code-review-
wf_f40bdb2b-ed3.js"} to iterate without resending the script.)
Run ID: wf_f40bdb2b-ed3
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--
Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\a3-code-
review-wf_f40bdb2b-ed3.js", resumeFromRunId: "wf_f40bdb2b-ed3"}) ? completed agents return
cached results.
```

You will be notified when it completes. Use /workflows to watch live progress.

413. assistant (2026-06-21T18:49:44.593Z)

The code-review workflow runs in the background. To parallelize, let me push A3 and open its PR now so CI runs concurrently ? I'll fold any review findings as a follow-up commit before merging. First verify the tree is clean, then push:

414. user (2026-06-21T18:49:48.315Z)

```
=== clean tree? (only untracked access.db ok) ===
?? site/access.db
```

```
remote:
branch 'feat/a3-recording-l10n' set up to track 'origin/feat/a3-recording-l10n'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/a3-recording-l10n -> feat/a3-recording-l10n
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

415. assistant (2026-06-21T18:49:57.304Z)

Pushed. Let me open the A3 PR (CI runs while the review workflow finishes):

416. user (2026-06-21T18:50:13.150Z)

<https://github.com/avidullu/khelsutra/pull/74>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

417. assistant (2026-06-21T18:50:24.586Z)

PR #74 opened (CI running). Now the tracker doc update (part of A3). Let me read the current A3 row and changelog tail in the worktree doc:

418. user (2026-06-21T18:50:26.852Z)

```
31:| D8 | **D-SURFACE-FIRST: lead with the `web/` SPA scaffold; SKIP the dead static-UI
retrofit** | owner, 2026-06-21 (via B1 go-ahead) | B1 is greenlit; site recording-education
localized early |
76:| Localize **recording-education** (capture + gist) kn?hi | site | high | medium | gates
input quality; the highest-leverage kn content |
134:| A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
139:| A3 | Localize **recording-education** (capture + homepage gist) to kn | A | B3/B5 |
D-LOCALES+D-FONT | ? | ? |
147:**? MILESTONE ? SPA fully trilingual (2026-06-21):** the `web/` Studio SPA now speaks **en +
kn + hi** end to end (B1?B2?B4?B5?B6, all merged). A **Kannada-default browser auto-renders
Kannada**, and the switcher walks kn ? hi ? en ? **proven by a Playwright screencast** with
`locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + ``
tracked). This meets the owner's success criterion **on the SPA surface**. **B3 has since
landed** ? the `site/` marketing surface now carries the shared `t()/`data-i18n` shim, a
persistent en/kn/hi switcher, and matching negotiation (client shim + `server.js`; $6.5 **N8**
green), with **en-only marketing content** for now (the shim/switcher/negotiation are the proof;
kn/hi *marketing* translation rides **A3**). **Still open for the full $9 DoD:** **A3**
(recording-education + the rest of the marketing copy in kn/hi), the remaining **non-tech UX
A-items** (A2/A6/A7/A9), and a **native-speaker review** of the AI-drafted kn/hi catalogs before
a wide public launch. Do **not** archive until both surfaces render kn/hi *content*.
154:4. **D-SURFACE-FIRST ? ? ADOPTED ? lead with the SPA scaffold (B1), localize site recording-
education early, SKIP the dead static-UI retrofit.**
178:- `2026-06-21` ? **A8 (#63) landed.** Background-processing reassurance + status as
icon+text chips (never icon-only): a new `StatusChip` + shared `Spinner`; IngestPanel processing
shows a working chip + "safe to wait ? runs on the server" line and a ? "Couldn't process" chip
on failure; CompileResult gains a "Stitching your reel?" building card + ?? status icons on the
terminal card (now `aria-live`). 141 web tests green; reviewed via a 2-lens adversarial workflow
(folded its aria-live + honest-copy findings). **Workstream A now: A1/A4/A5/A8 ?; remaining A9
(tap-only filters), A3 (recording-education kn/hi).**
180:- `2026-06-21` ? **A1 (#60) + A4 (#61) landed.** A1 = the plain-language `en` copy pass (de-
jargon). A4 = the non-tech / phone-first pass: 244px tap targets across the SPA (Tailwind
`min-h-11`/`h-11`), enlarged parsed-pill + sample chips, and **hover-only `title=` text surfaced
as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence)
? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.
**Still open in workstream A:** A5 (friendly engine-error map on the build path), A8
(background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-
education kn/hi), B3 (site/ trilingual) + native review.
=== changelog tail ===
- `2026-06-21` ? **A1 (#60) + A4 (#61) landed.** A1 = the plain-language `en` copy pass (de-
jargon). A4 = the non-tech / phone-first pass: 244px tap targets across the SPA (Tailwind
`min-h-11`/`h-11`), enlarged parsed-pill + sample chips, and **hover-only `title=` text surfaced
as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence)
? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.
**Still open in workstream A:** A5 (friendly engine-error map on the build path), A8
(background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-
education kn/hi), B3 (site/ trilingual) + native review.
- `2026-06-21` ? **? SPA MILESTONE: fully trilingual (owner directive "take it to completion +
screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ? B4 (#46,
self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all merged.
99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity. **Playwright
screencast** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ? switch hi ?
switch en, each with `` tracked (`khelsutra-i18n-screencast.mp4` + per-locale
frames). kn/hi are **AI-drafted ? native review pending**. **Remaining for full $9 DoD:** B3
(the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.
- `2026-06-21` ? **B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)) landed ? the
```

marketing `site/` is now i18n-wired, en-only content.** Implements **D-CATALOG-HOME**: catalogs hoisted to repo-root **`/locales`** (all 6 ? en/kn/hi + the merged es/da/id) as the single source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ? typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook) + a **drift-guard test**. New **`site/public/i18n.js`** ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n` walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the 2-form site languages); a **persistent en/kn/hi switcher** on `index/`/`capture/`/`own-model`; and **`server.js` Accept-Language negotiation** matching the SPA EXACTLY (persisted cookie ? `?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key). Tests: shim unit test + drift guard + extended `assets/`/`server` tests + the **\$6.5 N8** negotiation suite ? **62 site tests green** ; real-browser smoke (switch ? persist ? reload). kn/hi *marketing* translation is the next effort (**A3**). ? **Concurrency note:** built in an isolated `git worktree` because a sibling **A9** session held uncommitted catalog WIP in the shared checkout ? never clobbered.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

419. assistant (2026-06-21T18:50:34.742Z)

Let me update the A3 tracker row, the milestone note, and add a changelog entry:

420. user (2026-06-21T18:50:38.447Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

421. user (2026-06-21T18:50:45.267Z)

139 | A3 | Localize **recording-education** (capture + homepage gist) to kn | A | B3/B5 |
D-LOCALES+D-FONT | ? | ? |

422. user (2026-06-21T18:50:52.544Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

423. user (2026-06-21T18:51:03.092Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

424. assistant (2026-06-21T18:52:24.827Z)

The code review returned 5 legitimate findings (0 correctness, 0 i18n-safety, 2 a11y, 3 tests) ? all worth applying. Let me fold them all in. First the two a11y fixes (localize the switcher group `aria-label` via `lang.label`; author default `aria-pressed` for the no-JS baseline) across all 3 pages:

425. user (2026-06-21T18:52:26.750Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

426. user (2026-06-21T18:52:28.162Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

427. user (2026-06-21T18:52:29.565Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

428. user (2026-06-21T18:52:30.860Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

429. assistant (2026-06-21T18:52:37.032Z)

Now the same a11y fixes on capture.html and own-model.html:

430. user (2026-06-21T18:52:38.983Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

431. user (2026-06-21T18:52:40.350Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

432. user (2026-06-21T18:52:42.309Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

433. user (2026-06-21T18:52:43.709Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

434. user (2026-06-21T18:52:45.610Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

435. user (2026-06-21T18:52:47.003Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

436. user (2026-06-21T18:52:48.394Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

437. user (2026-06-21T18:52:49.947Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

438. assistant (2026-06-21T18:53:40.201Z)

All a11y fixes applied. Now the 3 test findings. Let me add the JSDOM import + a comprehensive drift test, and tighten the font-stack assertion in assets.test.js:

439. user (2026-06-21T18:53:42.078Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

440. user (2026-06-21T18:53:47.082Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

441. assistant (2026-06-21T18:53:58.694Z)

Now the comprehensive HTML-default-vs-en-catalog drift test (the major finding) ? appended to assets.test.js:

442. user (2026-06-21T18:54:08.011Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

443. assistant (2026-06-21T18:54:19.941Z)

Now the shim test finding ? add the `data-i18n-html` en-fallback case. Let me read the shim test tail and append:

444. user (2026-06-21T18:54:20.709Z)

```
73
74     test("data-i18n-html sets innerHTML and preserves inline <b> markup (A3 recording-
education)", () => {
75         const { document } = new JSDOM(`<!doctype html><body>
76             <p id="rich" data-i18n-html="site.record.place.body">Behind <b>one baseline</b>
?</p>
77             <li id="kept" data-i18n-html="does.not.exist">KEEP <b>this</b></li>
78         </body>`).window;
79
80         // en: innerHTML equals the catalog value verbatim (with its <b> tags), not escaped
text.
81         applyDom(document, catalogs, "en");
82         assert.equal(document.getElementById("rich").innerHTML,
catalogs.en.site.record.place.body);
83         assert.ok(document.getElementById("rich").querySelector("b"), "the <b> must be a real
element, not escaped text");
84         assert.equal(document.getElementById("kept").innerHTML, "KEEP <b>this</b>", "a missing
html key leaves the HTML default");
```

445. user (2026-06-21T18:54:28.408Z)

```
85
86         // kn: swaps to the Kannada value, still carrying its <b> tags.
87         applyDom(document, catalogs, "kn");
88         assert.equal(document.getElementById("rich").innerHTML,
catalogs.kn.site.record.place.body);
89         assert.match(document.getElementById("rich").innerHTML, /<b>.*<\b>/s, "kn rich value
keeps <b> markup");
90     });
91
92     test("A3: the kn/hi catalogs carry REAL recording-education translations (not English
seeds)", () => {
93         // Kannada script range U+0C80?U+0CFF; Devanagari U+0900?U+097F. A representative
spread of the
94         // recording keys must be in-script (proves A3 actually translated, not B3's en seed).
```

446. user (2026-06-21T18:54:38.968Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

447. assistant (2026-06-21T18:54:45.577Z)

All 5 review findings applied. Let me re-run the full site suite (the new comprehensive drift test will catch any HTML/catalog mismatch):

448. user (2026-06-21T18:54:49.312Z)

? tests 68

? pass 68
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

449. assistant (2026-06-21T18:55:05.314Z)

68 site tests pass ? the comprehensive drift test confirms my HTML defaults match the en catalog byte-for-byte across all 60+ tagged elements. Let me add the A3 changelog entry, then commit the review fixes + doc update:

450. user (2026-06-21T18:55:06.014Z)

181 - `2026-06-21` ? **SPA MILESTONE: fully trilingual (owner directive "take it to completion + screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ? B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity. ****Playwright screencast**** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ? switch hi ? switch en, each with `` tracked (`khelsutra-i18n-screencast.mp4` + per-locale frames). kn/hi are ****AI-drafted ? native review pending****. ****Remaining for full \$9 DoD:**** B3 (the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.
182 - `2026-06-21` ? **B3 ([#70](https://github.com/avidullu/khelsutra/pull/70))** landed ? the marketing `site/` is now i18n-wired, en-only content. ****Implements **D-CATALOG-HOME****: catalogs hoisted to repo-root ****`/locales`**** (all 6 ? en/kn/hi + the merged es/da/id) as the single source of truth; the SPA re-points its imports there (Vite resolves the **`.git`** workspace root ? typecheck/168 web tests/build green). The dependency-free site gains its one build step ? **`npm run copy:locales`** mirrors **`/locales`** ? **`site/public/locales/`** (**`predeploy`** hook) + a ****drift-guard test****. New ****`site/public/i18n.js`**** ? a ~110-LOC vanilla **`t(key,vars)`** + **`data-i18n`** walker with ICU-lite interpolation/plurals via **`Intl.PluralRules`** (mirrors i18next for the 2-form site languages); a ****persistent en/kn/hi switcher**** on **`index/`** **`capture/`** **`own-model`**; and ****`server.js`** **Accept-Language** negotiation ****matching the SPA EXACTLY (persisted cookie ? `?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key).** Tests: shim unit test + drift guard + extended **`assets/`** **`server`** tests + the ****\$6.5 N8**** negotiation suite ? ****62 site tests green****; real-browser smoke (switch ? persist ? reload). kn/hi ****marketing* translation is the next effort (**A3**).** ? ****Concurrency note:**** built in an isolated **`git worktree`** because a sibling ****A9**** session held uncommitted catalog WIP in the shared checkout ? never clobbered.

451. user (2026-06-21T18:55:23.830Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

452. assistant (2026-06-21T18:55:31.732Z)

Now commit the review fixes + doc update and push (re-triggers CI on #74):

453. user (2026-06-21T18:55:40.818Z)

```
=== staged ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M site/public/capture.html
M site/public/index.html
M site/public/own-model.html
M site/src/assets.test.js
M site/src/i18n.shim.test.js
?? site/access.db
To https://github.com/avidullu/khelsutra.git
 5166ec6..249007b feat/a3-recording-l10n -> feat/a3-recording-l10n
--- branch ---
249007b A3 review fixes: localize switcher aria-label, no-JS aria-pressed, drift/coverage tests + tracker
5166ec6 feat(site): A3 ? localize recording-education + marketing to kn/hi (Noto on the site)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

454. assistant (2026-06-21T18:55:47.718Z)

Pushed (2 commits on the A3 branch). Let me check CI + mergeability on PR #74 (and whether master churned again):

455. user (2026-06-21T18:56:41.078Z)

origin/master: c1848df | my base: c1848df27fd87e44bf7043f0ddd0b703186121d3
? branch contains master (no rebase needed)

```
=== PR #74 checks ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/1c32aa87-b240-4246-b963-7088373ac2b4
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27914217434/job/82596522057
web pass 33s
https://github.com/avidullu/khelsutra/actions/runs/27914217434/job/82596522029
=== mergeable ===
MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

456. assistant (2026-06-21T18:56:51.295Z)

All green on #74 ? **site ?, web ?, Cloudflare ?, MERGEABLE/CLEAN**, master stable. Let me squash-merge A3:

457. user (2026-06-21T18:56:56.840Z)

MERGED @ 2026-06-21T18:56:55Z
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

458. assistant (2026-06-21T18:57:10.443Z)

A3 merged (#74). Now A6. Let me update tasks, cut a fresh A6 branch in the worktree from the updated master, and read the Request-Access form:

459. user (2026-06-21T18:57:10.896Z)

Updated task #10 status

460. user (2026-06-21T18:57:11.392Z)

Updated task #11 status

461. user (2026-06-21T18:57:16.144Z)

```
c1848df..1cd84af master -> origin/master
origin/master: 1cd84af feat(site): A3 ? localize recording-education + marketing to kn/hi, Noto
on the site (#74)
branch 'feat/a6-access-plain-language' set up to track 'origin/master'.
Switched to a new branch 'feat/a6-access-plain-language'
```

```
=== Request-Access form (GPU/storage Qs) ===
507:<section id="join" style="padding-bottom:90px">
516:   <form id="af" class="af" novalidate>
520:     <label><input type="radio" name="segment" value="academy" required><span>Coaching
academy / club</span></label>
521:     <label><input type="radio" name="segment" value="individual"><span>Individual
player</span></label>
553:     <label>Do you have a GPU machine that could process video locally?</label>
555:     <label><input type="radio" name="has_gpu" value="yes">Yes ? a gaming / GPU PC or
laptop</label>
556:     <label><input type="radio" name="has_gpu" value="unsure">Not sure</label>
```

```

557:      <label><input type="radio" name="has_gpu" value="no">No</label>
558:      <label><input type="radio" name="has_gpu" value="prefer-cloud">I'd prefer it runs
in the cloud</label>
565:      <label><input type="checkbox" name="storage" value="gdrive">Google Drive</label>
566:      <label><input type="checkbox" name="storage" value="onedrive">OneDrive / MS
365</label>
567:      <label><input type="checkbox" name="storage" value="dropbox">Dropbox</label>
568:      <label><input type="checkbox" name="storage" value="bucket">Cloud bucket
(S3/GCS)</label>
569:      <label><input type="checkbox" name="storage" value="local">SD card / local
drive</label>
570:      <label><input type="checkbox" name="storage" value="unsure">Not sure</label>
687:      'GPU: ' + (p.has_gpu||''),
688:      'Storage: ' + ((p.storage||[]).join(', ')),
708:      has_gpu: fd.get('has_gpu'), storage: fd.getAll('storage'),
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

462. assistant (2026-06-21T18:57:22.142Z)

Let me read the full GPU/storage question block to plan the plain-language rewrite:

463. user (2026-06-21T18:57:23.426Z)

```

548      <option value="5+">5+ courts</option>
549      </select>
550      </div>
551
552      <div class="row">
553      <label>Do you have a GPU machine that could process video locally?</label>
554      <div class="opts">
555      <label><input type="radio" name="has_gpu" value="yes">Yes ? a gaming / GPU PC
or laptop</label>
556      <label><input type="radio" name="has_gpu" value="unsure">Not sure</label>
557      <label><input type="radio" name="has_gpu" value="no">No</label>
558      <label><input type="radio" name="has_gpu" value="prefer-cloud">I'd prefer it
runs in the cloud</label>
559      </div>
560      </div>
561
562      <div class="row">
563      <label>Where do your recordings live / how would you share them? <span
class="hint">(pick any)</span></label>
564      <div class="opts">
565      <label><input type="checkbox" name="storage" value="gdrive">Google
Drive</label>
566      <label><input type="checkbox" name="storage" value="onedrive">OneDrive / MS
365</label>
567      <label><input type="checkbox" name="storage" value="dropbox">Dropbox</label>
568      <label><input type="checkbox" name="storage" value="bucket">Cloud bucket
(S3/GCS)</label>
569      <label><input type="checkbox" name="storage" value="local">SD card / local
drive</label>
570      <label><input type="checkbox" name="storage" value="unsure">Not sure</label>
571      </div>
572      </div>
573
574      <div class="row">
575      <label for="af-msg">Anything else? <span class="hint">(how you record, what
you'd want?)</span></label>

```

464. assistant (2026-06-21T18:59:21.778Z)

A6 branch ready (off master with A3). Now I have the GPU/storage form. Let me check the `.hint` style to place the reassurance well, then rewrite the questions in plain language wired via

`data-i18n`:

465. user (2026-06-21T18:59:23.517Z)

```
182: .af .row{margin-bottom:1.05rem}
184: .af .hint{font-weight:400;color:var(--mut);font-size:.84rem}
193: .opts{display:flex;flex-wrap:wrap;gap:8px}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

466. user (2026-06-21T18:59:31.200Z)

```
182      .af .row{margin-bottom:1.05rem}
183      .af label{display:block;font-size:.9rem;font-weight:600;color:var(--tx);margin-
bottom:.4rem}
184      .af .hint{font-weight:400;color:var(--mut);font-size:.84rem}
185      .af input[type=text],.af input[type=email],.af select,.af
textarea{width:100%;font:inherit;font-
size:.95rem;color:var(--tx);background:var(--paper);border:1px solid var(--line);border-
radius:10px;padding:.6rem .75rem}
186      .af textarea{min-height:84px;resize:vertical}
187      .af input:focus,.af select:focus,.af textarea:focus{outline:none;border-
color:var(--green);box-shadow:0 0 3px rgba(25,179,107,.15)}
188      .seg{display:flex;gap:10px}
189      .seg label{flex:1;margin:0;border:1px solid var(--line);border-
radius:10px;padding:.7rem .8rem;cursor:pointer;font-weight:500;text-align:center}
190      .seg input{position:absolute;opacity:0}
191      .seg label:hover{border-color:var(--green)}
192      .seg label:has(input:checked){border-
color:var(--green);background:rgba(25,179,107,.07);color:var(--green-d);font-weight:700}
193      .opts{display:flex;flex-wrap:wrap;gap:8px}
194      .opts label{margin:0;display:inline-flex;align-items:center;gap:.4rem;border:1px solid
var(--line);border-radius:999px;padding:.4rem .8rem;font-weight:500;font-
size:.88rem;cursor:pointer}
```

467. assistant (2026-06-21T18:59:46.318Z)

`af label` is block, `.opts label` inline-flex (chips). My span-wrapping works. Let me confirm no test pins the old jargon label text, then rewrite the form:

468. user (2026-06-21T18:59:48.101Z)

```
site/src/index.test.js:148:  assert.match(text, /GPU:.*yes/);
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

469. assistant (2026-06-21T18:59:59.343Z)

`index.test.js:148` checks the internal email summary (`GPU: yes` ? the team-facing notification, not the user form), unaffected by relabeling. Safe to rewrite. Let me update the form:

470. user (2026-06-21T19:00:11.261Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

471. assistant (2026-06-21T19:00:29.914Z)

Now add the `site.join.\*` keys to all 6 catalogs (en authored everywhere ? the form stays English on all locales for now; key-parity green). Let me write the insertion script:

472. assistant (2026-06-21T19:00:38.197Z)

// A6: insert the plain-language Request-Access form copy (site.join.*) as the first key inside

```

the
// `site` object of every catalog. en content everywhere ? the access form is not yet translated
on
// any locale (a future increment); en-seeding keeps web key-parity green.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const root = import.meta.dirname;
const LOCALES = join(root, "locales");

const joinObj = {
  gpuLabel: "Do you have a powerful computer that could process videos on its own?",
  gpuHint: "A gaming PC or laptop with a graphics card. No worries if not ? we can run it in the
cloud for you.",
  gpuYes: "Yes ? a gaming PC or laptop with a graphics card",
  gpuUnsure: "Not sure",
  gpuNo: "No",
  gpuCloud: "No ? please run it in the cloud for me",
  storageLabel: "Where do your match videos live? How would you share them?",
  storageHint: "(pick any)",
  storageGdrive: "Google Drive",
  storageOnedrive: "OneDrive / Microsoft 365",
  storageDropbox: "Dropbox",
  storageBucket: "A cloud storage bucket ? advanced (e.g. Amazon S3, Google Cloud)",
  storageLocal: "SD card or the device itself",
  storageUnsure: "Not sure",
};

const lines = JSON.stringify(joinObj, null, 2).split("\n");
const body = lines.map((l, i) => (i === 0 ? l : "    " + l)).join("\n"); // +4 -> depth 2
const insertion = `      "join": ${body},\n`;
const ANCHOR = `  "site": {\n`;

for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const file = join(LOCALES, loc, "common.json");
  let text = readFileSync(file, "utf8");
  if (text.includes("join")) { console.log(`${loc}: already has join, skipping`); continue; }
  if (!text.includes(ANCHOR)) throw new Error(`${loc}: site anchor not found`);
  text = text.replace(ANCHOR, ANCHOR + insertion);
  const parsed = JSON.parse(text); // validate
  if (!parsed.site.join.gpuLabel || !parsed.site.record) throw new Error(`${loc}: join insert
broke site`);
  writeFileSync(file, text);
  console.log(`${loc}: site.join added (${Object.keys(parsed.site.join).length} keys)`);
}

```

473. user (2026-06-21T19:00:38.223Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra-fu-wt_tmp_a6.mjs (file state is current in your context ? no need to Read it back)

474. user (2026-06-21T19:00:49.277Z)

```

en: site.join added (14 keys)
kn: site.join added (14 keys)
hi: site.join added (14 keys)
es: site.join added (14 keys)
da: site.join added (14 keys)
id: site.join added (14 keys)

```

copy-locales: da, en, es, hi, id, kn -> site/public/locales/

```

=== web hygiene (key-parity with site.join) ===
  Tests  28 passed (28)
  Start at  00:30:48

```

Duration 643ms (transform 47ms, setup 16ms, collect 39ms, tests 22ms, environment 0ms, prepare 196ms)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

475. assistant (2026-06-21T19:01:11.312Z)

Web hygiene green with `site.join`. The A3 comprehensive drift test already auto-covers the new keys. Let me add an A6-specific test (de-jargoning + reassurance + backend-contract preservation):

476. user (2026-06-21T19:01:18.789Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

477. user (2026-06-21T19:01:28.674Z)

? A6: the GPU/storage questions are de-jargoned + reassuring, backend contract intact (0.9138ms)
? tests 69
? pass 69
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

478. assistant (2026-06-21T19:01:47.461Z)

69 site tests pass (A6 + the drift test auto-covering `site.join`). The change is en-label-only and the shim machinery was already browser-verified in A3, so tests suffice here. Let me update the tracker and commit. First the A6 row:

479. user (2026-06-21T19:01:48.458Z)

135:| A6 | Plain-language framing for Request-Access GPU/storage questions | A | B3 | No | ? | ?
|
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

480. user (2026-06-21T19:01:55.002Z)

135 | A6 | Plain-language framing for Request-Access GPU/storage questions | A | B3 | No | ?
| ? |

481. user (2026-06-21T19:02:03.384Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

482. assistant (2026-06-21T19:02:17.204Z)

Now the changelog entry. Let me read the tail and append:

483. user (2026-06-21T19:02:17.717Z)

- `2026-06-22` ? **A3 ([#74](https://github.com/avidullu/khelsutra/pull/74)) l
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

484. user (2026-06-21T19:02:23.334Z)

183 - `2026-06-22` ? **A3 ([#74](https://github.com/avidullu/khelsutra/pull/74)) landed ? the marketing `site/` recording-education + marketing copy now render in kn + hi.** Translated the homepage "Record it right" gist + the full 1-page capture checklist + the existing `site.\*` copy to **Kannada + Hindi** (~40 new `site.record.\*`/`site.capture.\*` keys; en-authored, kn/hi translated, es/da/id en-seeded ? key-parity green). The shim gains a ***`data-i18n-html`** form so inline `**` emphasis survives translation; **Noto Sans Kannada + Devanagari** bundled via Google Fonts on all 3 pages (+ `--font` fallback) so kn/hi render without tofu. Translations**

****AI-drafted ? adversarially verified**** by a 6-agent workflow (meaning/fluency/integrity × kn/hi; 0 issues in the A3 keys) and a 4-lens code review (folded its all findings ? switcher group `aria-label` now localized via `lang.label`, default `aria-pressed` for the no-JS baseline ? and 3 test-coverage findings incl. a byte-for-byte HTML?en-catalog drift test). ****Web 173 + site 68 green****; real-browser check (kn capture page renders Kannada, `**<b>**` preserved, no console errors). kn/hi remain ****native-review-pending**** (font glyphs = owner eyeball gate). The full-catalog audit also surfaced pre-existing ****B5/B6 SPA-console**** translation bugs (brand transliteration, "engine"/"server" jargon, a code-token leak, over-Sanskritized Hindi) ? flagged as a separate follow-up.

485. user (2026-06-21T19:02:37.065Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

486. assistant (2026-06-21T19:02:46.342Z)

Now stage A6's explicit paths, commit, push, and open the PR:

487. user (2026-06-21T19:02:55.040Z)

```
=== staged ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/src/assets.test.js
To https://github.com/avidullu/khelsutra.git
* [new branch] feat/a6-access-plain-language -> feat/a6-access-plain-language
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

488. user (2026-06-21T19:03:10.763Z)

<https://github.com/avidullu/khelsutra/pull/75>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

489. assistant (2026-06-21T19:03:16.428Z)

PR #75 opened (matches the doc reference). Let me check CI + mergeability:

490. user (2026-06-21T19:04:12.990Z)

```
? contains master
=== checks ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/36ed878d-d47c-43e2-9da0-67a2347d0920
site pass 13s
https://github.com/avidullu/khelsutra/actions/runs/27914413466/job/82597096540
web pass 35s
https://github.com/avidullu/khelsutra/actions/runs/27914413466/job/82597096549
=== mergeable ===
MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

491. assistant (2026-06-21T19:04:18.777Z)

All green on #75 (site ?, web ?, Cloudflare ?, CLEAN). Let me merge A6:

492. user (2026-06-21T19:04:23.644Z)

MERGED

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

493. assistant (2026-06-21T19:06:43.224Z)

A6 merged (#75). Now A7 ? a camera-placement diagram for the capture page. I'll build a clean side-view SVG (court, elevated camera, ~30° tilt, field-of-view cone covering the whole court) with a localized legend, consistent with the A3-localized page. Let me update tasks and write the diagram catalog keys (en + kn/hi, reusing A3 terms):

494. user (2026-06-21T19:06:43.710Z)

Updated task #11 status

495. user (2026-06-21T19:06:44.176Z)

Updated task #12 status

496. user (2026-06-21T19:06:48.390Z)

```
1cd84af..aa8d5e9 master -> origin/master
Switched to a new branch 'feat/a7-capture-diagram'
origin/master: aa8d5e9 feat(site): A6 ? plain-language Request-Access GPU/storage questions
(#75)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

497. assistant (2026-06-21T19:07:08.724Z)

```
// A7: insert site.capture.diagram (the camera-placement diagram's caption + legend) as the
first
// key of site.capture in each catalog. en/es/da/id <- en; kn <- Kannada; hi <- Hindi (reusing
the
// A3 capture terms for consistency). The capture page is already localized (A3), so the diagram
// labels are localized too.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const root = import.meta.dirname;
const LOCALES = join(root, "locales");

const diagram = {
  en: {
    title: "Side view: where the camera goes",
    camera: "Camera ? behind the baseline, elevated",
    angle: "Tilt ~30° down",
    frame: "Whole court in frame ? players never cropped",
    net: "Net",
  },
  kn: {
    title: "????? ???: ???????? ?????? ?????????",
    camera: "????????? ? ?????????? ??????, ?????????????",
    angle: "??????? 30° ???????? ??????",
    frame: "??? ?????? ?????????????? ? ???????? ?????? ?????????????????",
    net: "?????",
  },
  hi: {
    title: "????? ?????: ?????? ??? ?????",
    camera: "????? ? ???????? ?? ????, ?????? ??",
  }
}
```

```

    angle: "???? 30° ??? ????",
    frame: "???? ???? ???? ? ? ???? ? ? ? ??",
    net: "???",
  },
};
const pick = { en: "en", es: "en", da: "en", id: "en", kn: "kn", hi: "hi" };

const ANCHOR = `      "capture": {\n`;
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const file = join(LOCALES, loc, "common.json");
  let text = readFileSync(file, "utf8");
  if (text.includes('"diagram"')) { console.log(`${loc}: already has diagram, skipping`);
continue; }
  if (!text.includes(ANCHOR)) throw new Error(`${loc}: capture anchor not found`);
  const obj = diagram[pick[loc]];
  const lines = JSON.stringify(obj, null, 2).split("\n");
  const body = lines.map((l, i) => (i === 0 ? l : "      " + l)).join("\n"); // +6 -> depth 3
  const insertion = `      "diagram": ${body},\n`;
  text = text.replace(ANCHOR, ANCHOR + insertion);
  const parsed = JSON.parse(text);
  if (!parsed.site.capture.diagram.title || !parsed.site.capture.step1) throw new Error(`${loc}:
diagram insert broke capture`);
  writeFileSync(file, text);
  console.log(`${loc}: site.capture.diagram added (${pick[loc]})`);
}

```

498. user (2026-06-21T19:07:08.748Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-fu-wt_tmp_a7.mjs (file state is current in your context ? no need to Read it back)

499. user (2026-06-21T19:07:16.356Z)

```

en: site.capture.diagram added (en)
kn: site.capture.diagram added (kn)
hi: site.capture.diagram added (hi)
es: site.capture.diagram added (en)
da: site.capture.diagram added (en)
id: site.capture.diagram added (en)

```

copied
verify: ???????? ? ????????? ???? , ??????????
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

500. assistant (2026-06-21T19:08:04.990Z)

Diagram keys added (en/kn/hi). Now build the SVG diagram. First the CSS in capture.html:

501. user (2026-06-21T19:08:08.301Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

502. assistant (2026-06-21T19:08:15.138Z)

Now insert the diagram figure before the steps grid:

503. user (2026-06-21T19:08:29.340Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

504. assistant (2026-06-21T19:08:52.809Z)

Now the A7 test (diagram structure + localized legend), appended to assets.test.js:

505. user (2026-06-21T19:09:00.491Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

506. assistant (2026-06-21T19:09:06.627Z)

Now add the diagram to the shim test's "REAL translations" check (kn/hi in-script), then run the suite:

507. user (2026-06-21T19:09:09.091Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

508. user (2026-06-21T19:09:24.015Z)

? A7: the capture page shows an accessible, localized camera-placement diagram (0.5736ms)

? tests 70

? pass 70

? fail 0

=== web hygiene (key-parity w/ diagram) ===

Tests 28 passed (28)

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

509. assistant (2026-06-21T19:09:37.778Z)

70 site tests + web hygiene green. The diagram is a visual change, so let me render it in a real browser and capture it:

510. user (2026-06-21T19:09:40.857Z)

```
{
  "serverId": "e17acb41-aea9-4f7b-893a-b93a38e61751",
  "port": 8080,
  "name": "fu-site",
  "reused": false
}
Server started successfully on port 8080.
```

511. user (2026-06-21T19:09:46.530Z)

Eval failed: Inspected target navigated or closed

512. user (2026-06-21T19:09:56.927Z)

```
{
  "hasFigure": true,
  "legend": [
    "???????? ? ????????? ?????. ??",
    "?????? 30° ??????? ??????",
    "??? ?????? ????????????? ? ????"
  ],
  "netLabel": "????",
  "paths": 2,
  "svgH": 0,
  "svgW": 0,
  "texts": 5
}
```

513. assistant (2026-06-21T19:10:21.425Z)

The legend renders in Kannada (persistence from my earlier test carried `kn` over ? good sign), but the SVG measured 0x0. Let me investigate whether that's a layout-timing artifact or a real sizing bug:

514. user (2026-06-21T19:10:24.083Z)

```
{
  "client": [
    0,
    0
  ],
  "computed": [
    "0px",
    "0px",
    "inline"
  ],
  "figW": 0,
  "hasViewBox": "0 0 600 240",
  "svg_h": 0,
  "svg_w": 0
}
```

515. assistant (2026-06-21T19:10:48.523Z)

`figW: 0` and the SVG computes as `display:inline` with 0 size. Two things to check: SVG inline-display (a real bug ? inline SVG ignores `width:100%`) and whether the preview viewport itself has width. Let me check:

516. user (2026-06-21T19:10:50.760Z)

```
{
  "bodyDivW": 60,
  "bodyW": 0,
  "h1W": 78,
  "innerW": 0,
  "sheetW": 0
}
```

517. assistant (2026-06-21T19:11:06.128Z)

`innerW: 0` ? the preview **viewport itself has 0 width**, so all measurements are meaningless (an environment quirk, not my layout). But the SVG computing as `display:inline` is a real best-practice issue (inline SVG sizing is fragile). Let me fix that defensively, then resize the viewport and re-verify:

518. user (2026-06-21T19:11:08.194Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

519. assistant (2026-06-21T19:11:14.444Z)

Let me resize the preview viewport (it was 0-width), reload, and re-measure + screenshot the diagram:

520. user (2026-06-21T19:11:21.449Z)

Viewport reset to native size (desktop).

521. user (2026-06-21T19:11:27.507Z)

Eval failed: Inspected target navigated or closed

522. user (2026-06-21T19:11:34.657Z)

```
{
  "display": "block",
  "innerW": 0,
  "lang": "kn",
  "legendCount": 3,
  "svg_h": 0,
  "svg_w": 0
}
```

523. assistant (2026-06-21T19:11:56.060Z)

The viewport is stuck at 0-width in this preview environment (same reason A3's screenshot timed out) ? so I can't get a visual capture, but the SVG is now `display:block` (the real fix) and structurally sound; standard responsive SVG (`viewBox` + `width:100%` + `height:auto` + `display:block`) renders correctly at any real width. Note `lang:kn` despite `?lang=en` correctly reflects persisted-pref-wins. Let me clear storage to confirm the en default + diagram structure:

524. user (2026-06-21T19:11:57.714Z)

Eval failed: Inspected target navigated or closed

525. user (2026-06-21T19:12:03.951Z)

```
{
  "lang": "en",
  "legend": [
    "Camera ? behind the baseline, elevated",
    "Tilt ~30° down",
    "Whole court in frame ? players never cropped"
  ],
  "net": "Net",
  "svgParts": {
    "lines": 10,
    "paths": 2,
    "texts": 5
  }
}
```

526. assistant (2026-06-21T19:12:13.837Z)

The en default renders correctly (English legend, "Net", full SVG: 2 paths + 5 texts + 10 lines). Both en and kn confirmed end-to-end. Let me check console and stop the preview:

527. user (2026-06-21T19:12:14.200Z)

No console logs.

528. assistant (2026-06-21T19:12:23.860Z)

No console errors, CSS fix applied. Let me stop the preview and re-run the site suite to confirm the CSS edit is clean:

529. user (2026-06-21T19:12:24.371Z)

Server e17acb41-aea9-4f7b-893a-b93a38e61751 stopped

530. user (2026-06-21T19:12:28.693Z)

? tests 70
? pass 70

? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

531. assistant (2026-06-21T19:12:37.010Z)

70 site tests pass. Let me update the A7 tracker row + changelog, then commit/PR/merge:

532. user (2026-06-21T19:12:38.071Z)

136:| A7 | Fix English-source recording gaps (add a placement diagram) before localizing | A | ?
| No | ? | ? |
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

533. user (2026-06-21T19:12:47.566Z)

136 | A7 | Fix English-source recording gaps (add a placement diagram) before localizing | A
| ? | No | ? | ? |

534. user (2026-06-21T19:12:55.860Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

535. user (2026-06-21T19:13:01.232Z)

184 - `2026-06-22` ? **A6 ([#75](https://github.com/avidullu/khelsutra/pull/75)) landed ? plain-language Request-Access GPU/storage questions.** De-jargoned the intimidating form copy ("GPU machine that could process video locally" ? "a powerful computer that could process videos on its own"; dropped the bare "(S3/GCS)") and added a **GPU reassurance** ("No worries if not ? we can run it in the cloud for you"), so a non-technical coach/parent isn't scared off. Wired via the shim (`site.join.\*`, `data-i18n` spans that preserve the radio/checkbox ``s), translation-ready (en for now; the form's kn/hi is a later increment). The **backend enum contract is unchanged** (field names + every `has\_gpu`/`storage` value preserved ? server-validated). Tests: a de-jargon + reassurance + contract-intact assertion, and the A3 HTML?en-catalog drift test auto-covers the new keys. Site 69 + web 173 green.

536. user (2026-06-21T19:13:12.967Z)

The file C:\Users\avidu\Projects\khelsutra-fu-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

537. assistant (2026-06-21T19:13:21.308Z)

Now commit A7, push, and open the PR:

538. user (2026-06-21T19:13:29.954Z)

```
=== staged ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/capture.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/src/assets.test.js
```

```
M site/src/i18n.shim.test.js
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/a7-capture-diagram -> feat/a7-capture-diagram
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

539. user (2026-06-21T19:13:44.797Z)

<https://github.com/avidullu/khelsutra/pull/76>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

540. assistant (2026-06-21T19:13:50.508Z)

PR #76 opened (matches the doc). Let me check CI + mergeability:

541. user (2026-06-21T19:14:52.196Z)

```
? contains master
=== checks ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/179eff41-0179-4f0a-904b-255840203b8c
site pass 16s
https://github.com/avidullu/khelsutra/actions/runs/27914676823/job/82597803595
web pass 37s
https://github.com/avidullu/khelsutra/actions/runs/27914676823/job/82597803581
=== mergeable ===
MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

542. assistant (2026-06-21T19:14:58.496Z)

All green on #76 (site ?, web ?, Cloudflare ?, CLEAN). Let me merge A7:

543. user (2026-06-21T19:15:04.206Z)

MERGED
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

544. assistant (2026-06-21T19:15:15.868Z)

A7 merged (#76) ? all three follow-ups (A3, A6, A7) are done and merged. Let me mark the task complete and clean up (worktree, branches, launch.json), confirming all three landed on master:

545. user (2026-06-21T19:15:16.837Z)

Updated task #12 status

546. user (2026-06-21T19:15:30.806Z)

```
aa8d5e9..9a2d7d2 master -> origin/master
=== origin/master top (A3/A6/A7 present?) ===
9a2d7d2 feat(site): A7 ? camera-placement diagram on the capture page (#76)
aa8d5e9 feat(site): A6 ? plain-language Request-Access GPU/storage questions (#75)
1cd84af feat(site): A3 ? localize recording-education + marketing to kn/hi, Noto on the site
(#74)
c1848df feat(web): LW2 ? send the UI locale to /api/compile (watermark) + /api/process
(analytics) (#73)

=== remove worktree + local+remote A3/A6/A7 branches ===
worktree removed
Deleted branch feat/a3-recording-l10n (was 249007b).
- [deleted]      feat/a3-recording-l10n
Deleted branch feat/a6-access-plain-language (was 6ba7b1d).
```

```
- [deleted]          feat/a6-access-plain-language
Deleted branch feat/a7-capture-diagram (was 1c53118).
- [deleted]          feat/a7-capture-diagram
```

```
C:/Users/avidu/Projects/khelsutra          aa8d5e9 [master]
C:/Users/avidu/Projects/khelsutra-i18n-review  50ccbba [fix/kn-hi-spa-console-native-review]
```

547. assistant (2026-06-21T19:15:42.706Z)

All three follow-ups are on master (9a2d7d2). Worktree + branches cleaned. I also notice the spawned B5/B6 SPA-console fix is now running in its own worktree (`fix/kn-hi-spa-console-native-review`) ? being handled separately, untouched. Let me revert the temporary launch.json entry and refresh the handoff:

548. user (2026-06-21T19:15:42.900Z)

```
1      {
2      "version": "0.0.1",
3      "configurations": [
4      {
5      "name": "khelsutra-web",
6      "runtimeExecutable": "npm",
7      "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
8      "port": 5173
9      },
10     {
11     "name": "khelsutra-site",
12     "runtimeExecutable": "node",
13     "runtimeArgs": ["site/server.js"],
14     "port": 8080
15     },
16     {
17     "name": "fu-site",
18     "runtimeExecutable": "node",
19     "runtimeArgs": ["C:/Users/avidu/Projects/khelsutra-fu-wt/site/server.js"],
20     "port": 8080
21     }
22   ]
23 }
24
```

549. user (2026-06-21T19:15:50.543Z)

The file C:\Users\avidu\Projects\khelsutra\claude\launch.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

550. assistant (2026-06-21T19:15:57.506Z)

Now refresh the session handoff to reflect A3/A6/A7 landing:

551. assistant (2026-06-21T19:16:17.753Z)

Session handoff ? khelsutra (Friendly & Multilingual workstream)

Last updated: 2026-06-22, after A3/A6/A7 merged.

You are here

```
- The marketing `site/` is now trilingual end-to-end and non-tech-friendly:
- B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)): shared `t()/`data-i18n` shim
+ en/kn/hi switcher + `server.js` negotiation; catalogs hoisted to repo-root `/locales`
(D-CATALOG-HOME).
- A3 ([#74](https://github.com/avidullu/khelsutra/pull/74)): recording-education (homepage
```

gist + capture checklist) + `site.\*` marketing copy translated to **kn + hi**; Noto bundled on the site; shim gained `data-i18n-html`.

- **A6** ([#75](https://github.com/avidullu/khelsutra/pull/75)): plain-language Request-Access GPU/storage questions (de-jargoned + GPU reassurance), en, translation-ready.
- **A7** ([#76](https://github.com/avidullu/khelsutra/pull/76)): accessible camera-placement SVG diagram on the capture page, localized en/kn/hi legend.
- The SPA (`web/`) was already trilingual+ (en/kn/hi + es/da/id). All merged on green CI.
- kn/hi translations are **AI-drafted + adversarially verified** ? native review still pending **before a wide public launch**.

Next steps / open threads (tracker §7 of docs/FRIENDLY_AND_MULTILINGUAL.md)

- **B5/B6 SPA-console native-review pass** ? an adversarial audit during A3 found fixable kn/hi **console** translation bugs (brand transliteration "KhelSutra"????????, "engine"/"server" jargon leak, a `min\_shot\_count` code-token leak, over-Sanskritized Hindi). Spawned as a separate task (worktree `khelsutra-i18n-review`, branch `fix/kn-hi-spa-console-native-review`).
- **A2** ? localized WhatsApp share for the reel (SPA + site). Not yet started.
- **Access form kn/hi** ? A6 left the Request-Access form English on all locales (a small future increment; `site.join.\*` is en-seeded).
- **Native-speaker review** of ALL AI-drafted kn/hi catalogs (site + SPA) before public launch; owner font-glyph eyeball on a real device.

Ramp-up kit

- `docs/FRIENDLY\_AND\_MULTILINGUAL.md` ? §7 tracker (source of truth), §6.5 negotiation matrix, §8 decisions, changelog.
- `/locales/en/common.json` ? shared catalog: SPA console keys + `site.\*` (nav/hero/record/capture/join/ownModel).
- `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, negotiation), `site/server.js` (Accept-Language), `site/scripts/copy-locales.mjs` (the one build step), `site/src/{i18n.shim, locales-drift, assets, server}.test.js`.
- [[catalog-home-and-i18n-layout]], [[shared-checkout-concurrency]].

Key decisions (don't relitigate)

- **D-CATALOG-HOME**: catalogs at repo-root `/locales`; SPA imports; site mirrors via `copy:locales` + drift guard.
- Negotiation order (both surfaces): persisted (`khelsutra.lang`) ? `?lang=` ? navigator/Accept-Language ? en; missing key ? en, never a raw key.
- Marketing kn/hi translated; **access form is en for now**. es/da/id are SPA-only (site is trilingual; their `site.\*` is en-seeded for key-parity).
- Rich inline markup (`<b>`) localizes via `data-i18n-html` (innerHTML from project-authored catalog ? XSS-safe).
- **Process**: isolated `git worktree` per PR (shared checkout, rapid master churn); AI-draft translations ? adversarial verify workflow ? native review is a pre-launch (not pre-merge) gate.

552. user (2026-06-21T19:16:17.807Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

553. assistant (2026-06-21T19:16:42.556Z)

All three follow-ups are implemented, verified, and merged. Here's the wrap-up.

A3 ? A6 ? A7 shipped (all merged on green CI)

PR	What landed
A3 [#74](https://github.com/avidullu/khelsutra/pull/74)	Recording-education (homepage gist + full capture checklist) **kn + hi** marketing copy translated to Kannada + Hindi; Noto Kannada/Devanagari bundled on the site; shim gained a `data-i18n-html` form so inline `**` survives translation
A6 [#75](https://github.com/avidullu/khelsutra/pull/75)	**Plain-language Request-Access GPU/storage questions** ? de-jargoned ("GPU machine"? "powerful computer"; dropped bare "S3/GCS")**

+ a GPU reassurance, wired translation-ready, backend enum contract untouched |
| **A7** [#76](https://github.com/avidullu/khelsutra/pull/76) | **Accessible camera-placement SVG diagram** on the capture page (elevated camera behind baseline, ~30° tilt, full-court FOV cone) with a localized en/kn/hi legend |

`origin/master` is at `9a2d7d2` with all three.

Diligence applied (same bar as B3)

- **Adversarial translation verification** (A3): a 6-agent workflow (kn/hi × meaning/fluency/integrity lenses) ? **0** issues in my A3 keys. The full-catalog audit it accidentally ran surfaced **pre-existing** B5/B6 SPA-console bugs (brand transliteration, "engine"/"server" jargon, a code-token leak, over-Sanskritized Hindi) ? I flagged those as a **separate task**, now running in its own worktree (`fix/kn-hi-spa-console-native-review`), rather than bloating A3.
- **Adversarial code review** (A3): a 4-lens workflow (correctness/a11y/i18n-safety/tests) ? folded all 5 findings: localized the switcher group `aria-label`, authored no-JS `aria-pressed` defaults, and added a **byte-for-byte HTML?en-catalog drift test** (now auto-covers every data-i18n key across A3/A6/A7), an `data-i18n-html` en-fallback test, and an order-robust font-stack assertion.
- **Tests + CI**: site **70** + web **173** green throughout; every PR merged only on green **web + site + Cloudflare** CI. Real-browser DOM checks (kn/en render, persistence, `**b**` preserved, no console errors).
- **Concurrency-safe**: each PR done in an isolated `git worktree`, branched from the freshly-fetched `origin/master` (it churned ~6× during the work), rebased to integrate ? never clobbered a sibling.

Honest limits / what remains

- **kn/hi** are AI-drafted + machine-verified, native-review-pending ? the owner's font-glyph eyeball on a real device is the final gate (the headless preview viewport renders 0-width here, so I verified structure/DOM, not pixels).
- **A2** (WhatsApp share) wasn't selected, and the **Request-Access** form stays English on all locales (A6 left it translation-ready; `site.join.\*` is en-seeded) ? both noted as future increments.
- The spawned **B5/B6 SPA-console native-review** fix is in flight separately.
- Minor: the `site.\*` namespace now adds ~27KB to the SPA bundle (unused there) ? a candidate future split into a site-only catalog.

Tracker `docs/FRIENDLY\_AND\_MULTILINGUAL.md` S7 (A3/A6/A7 ? ?) + changelog updated; the session handoff/memory is refreshed.

554. user (2026-06-21T21:41:47.109Z)

what is left in the tracker an/or any prioritized next steps ?

555. assistant (2026-06-21T21:42:14.628Z)

Let me read the **current** tracker from `origin/master` (it's churned a lot, and other sessions have merged #77/#80) so I give you an accurate, up-to-date answer rather than relying on the handoff.

556. user (2026-06-21T21:42:19.741Z)

origin/master: 64076a5 test(web): add a coverage floor (CI-gated) + i18n regression tests for the #77 audit (#80)

=== S7 tracker rows ===

```
| P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |  
[#41](https://github.com/avidullu/khelsutra/pull/41) · engine  
[#275](https://github.com/khelsutra/badminton-highlight-indexer/pull/275) |  
| B1 | SPA i18n scaffold + language switcher, en-only (react-i18next + detector + `en`  
catalog + switcher + persistence + jsdom render tests + browser-language negotiation tests S6.5 N1/N3?N7) | B | P0 | No | ? | [#42](https://github.com/avidullu/khelsutra/pull/42)  
|
```

| B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys); add
 key-parity + no-bare-strings CI | B | B1 | No | ? |
 [#45](https://github.com/avidullu/khelsutra/pull/45) |
 | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color selection)
 | A | B2 | No | ? | [#60](https://github.com/avidullu/khelsutra/pull/60) |
 | B3 | **Shared `t()`/`data-i18n` shim + persistent switcher for `site/`** ? hoist catalogs to
 repo-root `/locales` (D-CATALOG-HOME), re-point the SPA, site copy-step + drift-guard,
 `server.js` + shim negotiation (\$6.5 **N8**); **en-only marketing content** (kn/hi rides A3) | B
 | B2 | D-CATALOG-HOME ? | ? | [#70](https://github.com/avidullu/khelsutra/pull/70) |
 | A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
 | A6 | Plain-language framing for Request-Access GPU/storage questions (de-jargoned + GPU
 reassurance; wired via `data-i18n`, en ? form kn/hi is a later increment) | A | B3 | No | ? |
 [#75](https://github.com/avidullu/khelsutra/pull/75) |
 | A7 | **Camera-placement diagram** on the capture page (accessible inline SVG: elevated camera
 behind the baseline, ~30° tilt, full-court field-of-view) with a localized en/kn/hi legend | A |
 ? | No | ? | [#76](https://github.com/avidullu/khelsutra/pull/76) |
 | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? *SPA done; reel watermark
 `font\_path` = engine follow-up* | B | ? | D-FONT ? | ? |
 [#46](https://github.com/avidullu/khelsutra/pull/46) |
 | B5 | **Kannada (`kn`) catalog** ? render ? *SPA done (AI-draft, native review pending);
 `site/` rides B3* | B | B2/B4 | D-LOCALES ? | ? |
 [#47](https://github.com/avidullu/khelsutra/pull/47) |
 | A3 | Localize **recording-education** (capture + homepage gist) + the `site.` marketing copy
 to **kn + hi** (Noto on the site; AI-draft, adversarially verified, native review pending) | A |
 B3/B5 | D-LOCALES ? + D-FONT ? (site: Google-Fonts Noto) | ? |
 [#74](https://github.com/avidullu/khelsutra/pull/74) |
 | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? |
 [#61](https://github.com/avidullu/khelsutra/pull/61) |
 | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) | A | B2 |
 No | ? | [#62](https://github.com/avidullu/khelsutra/pull/62) |
 | B6 | **Hindi (`hi`) catalog** ? render (the extensibility proof ? just a catalog) ? *SPA done
 (AI-draft, native review pending)* | B | B5 | D-LOCALES ? | ? |
 [#48](https://github.com/avidullu/khelsutra/pull/48) |
 | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 | No | ? |
 | [#63](https://github.com/avidullu/khelsutra/pull/63) |
 | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ? |
 [#68](https://github.com/avidullu/khelsutra/pull/68) |
 | B7 | *(deferred, cross-repo)* Engine **P2 backend customer-facing localization** (report
 `customer\_` + rejection reasons) | B | engine | **D-BACKEND-DEPTH, owner-gated** | ? | ? |

=== §9 Definition of Done ===

- [] **Automatic language negotiation (\$6.5) is green** ? a **Kannada browser gets Kannada and
 a Hindi browser gets Hindi** (N1/N2); persisted-pref / `?lang` / region-subtag / unsupported-
 fallback / missing-key-fallback all proven (N3?N7) on the SPA, and the static-site shim honors
 `Accept-Language` + `?lang` (N8).
- [] **Manual cross-check (owner machine):** OS/browser set to Kannada and to Hindi each render
 the respective language on BOTH surfaces, with Noto fonts displaying.
- [] `en + kn + hi` catalogs live and **rendering** on BOTH `web/` SPA and `site/` marketing
 (switcher + persistence + `en` fallback; no raw keys shown).
- [] **Noto Sans Kannada + Devanagari render correctly** ? owner eyeball on a real machine.
- [] CI **key-parity + no-bare-strings** green; a stub locale flags every gap.
- [] **Recording-education** (capture + homepage gist) available in `kn` + `hi`.
- [] **Non-tech UX baseline:** plain-language copy (no raw engine jargon in user-facing
 strings), mobile-usable touch targets, icon+text, WhatsApp share, honest today-vs-roadmap
 preserved through translation.
- [] §7 all rows ? (or explicitly deferred with a reason) ? flip **Status ? DONE** + completion
 note ? run engine `DOC\_STATUS.md §2` archival checklist ? `git mv` to `docs/archives/`.

557. assistant (2026-06-21T21:43:06.462Z)

Pulled the live tracker from `origin/master` (now at `64076a5`; sibling sessions also merged the
 #77 console-translation fix and #80 web-coverage floor since I last looked). Here's the accurate
 picture.

What's left in §7

Essentially **one open build row** ? everything else is ? or explicitly deferred:

```
| Row | Status | Note |
|---|---|---|
| A2 ? Localized WhatsApp share** (reel, SPA + site) | ? open | The only un-built deliverable. *You deferred it when we scoped A3/A6/A7.* |
| B7 ? Engine backend customer-facing l10n** | ? deferred | Cross-repo, owner-gated (D-BACKEND-DEPTH) ? out of this DoD by design |
| P0, B1?B6, A1, A3?A9 | ? | All merged |
```

What's left in §9 (Definition of Done)

The **code/CI gates** are all met** (negotiation N1?N8 green, en+kn+hi rendering both surfaces, key-parity/no-bare-strings green, recording-education in kn/hi) ? the checkboxes just haven't been flipped. The **genuinely remaining** items are:

1. **A2 (WhatsApp share)** ? the last piece of the "non-tech UX baseline" checkbox.
2. **Native-speaker review of the kn/hi catalogs** (site + SPA) ? they're AI-drafted + adversarially verified, but **human review** is the standing guardrail before a wide public launch*. *Human gate ? not codeable by me.*
3. **Owner font-glyph eyeball** on a real device (kn/hi render with Noto) ? DoD explicitly says the cloud CI can't verify glyphs. *Human gate.*
4. **Doc bookkeeping** ? flip the satisfied §9 boxes, then (once A2 + native review land) flip Status?DONE and run the archival checklist.

Prioritized next steps

1. **A2 ? WhatsApp share** *(highest-value codeable item; closes the last §7 row)*. Opens the user's own WhatsApp with a pre-filled localized message for the downloaded reel ? sends nothing server-side. ~1 small PR, same diligence. **You skipped it earlier, so I'd want your go-ahead before building it.**
2. **Queue the human gates** ? native-speaker review + owner font eyeball. These, not code, are what block public launch / archiving.
3. **Doc bookkeeping** ? I can flip the now-satisfied §9 checkboxes and add a "verified vs human-gated" completion note (small, safe).
4. **B7** stays deferred (owner-gated, cross-repo) unless you want to open it.

Minor/optional cleanups I noted along the way: the Request-Access **form labels** are still English** on kn/hi (A6 left them translation-ready); the ``site.*`` namespace adds ~27KB to the SPA bundle (could split to a site-only catalog); and #80's coverage thresholds can be ratcheted up as ``App.tsx`` gains tests.

Want me to **build A2** now, just do the **doc bookkeeping**, or both? (A2 is the only thing standing between the tracker and "all rows ? except the owner-gated B7.")

558. user (2026-06-21T21:54:33.885Z)

how much effort would be B7? If significant then drop it for now and run through all the work and cleanup items so you can close out the multilingual chapter. Also notice that rally-annotator sister repo is also localized in all these languages so the user sees a consistent view. BTW can you run a serious UI/UX eval of the website and maybe fix some clutter and misalignment in the headers as well as a follow up to all these? Make sure to make and merge PRs with the same due diligence as followed and everywhere possible do a screencast and put the video in my current local machine

559. assistant (2026-06-21T21:55:31.947Z)

Several things to assess before I commit to a plan. Let me do read-only reconnaissance in parallel: B7's real scope (cross-repo engine work), the rally-annotator sister repo's state, existing screencast tooling (the B1 milestone mentioned a Playwright screencast), and the current master.

560. user (2026-06-21T21:55:38.519Z)

```
=== sibling repos under Projects/ ===
C:/Users/avidu/Projects/badminton-highlight-indexer/
C:/Users/avidu/Projects/khelsutra-screencast/
C:/Users/avidu/Projects/khelsutra/
C:/Users/avidu/Projects/rally-annotator/
```

```
=== screencast/playwright tooling in khelsutra? ===
./site/node_modules/@exodus/bytes/package.json
./web/node_modules/@exodus/bytes/package.json
./web/node_modules/chai/package.json
./web/node_modules/loupe/package.json
./web/node_modules/tailwindcss/package.json
./web/node_modules/typescript/package.json
./site/public/video/tool-cuj.mp4
```

```
=== current origin/master ===
64076a5 test(web): add a coverage floor (CI-gated) + i18n regression tests for the #77 audit
(#80)
```

561. assistant (2026-06-21T21:55:49.824Z)

Useful ? there's a dedicated `khelsutra-screencast/` dir (likely the Playwright tooling from the B1 milestone), plus the `rally-annotator` and `badminton-highlight-indexer` (engine) sibling repos. Let me inspect the screencast tooling, rally-annotator's i18n, and B7's surface area:

562. user (2026-06-21T21:55:51.787Z)

```
=== khelsutra-screencast/ contents ===
total 58393
drwxr-xr-x 1 avidu 197609      0 Jun 21 18:57 .
drwxr-xr-x 1 avidu 197609      0 Jun 22 03:22 ..
-rw-r--r-- 1 avidu 197609  411510 Jun 21 18:56 b-205.png
-rw-r--r-- 1 avidu 197609  484558 Jun 21 18:56 b-218.png
-rw-r--r-- 1 avidu 197609  490788 Jun 21 18:56 b-228.png
-rw-r--r-- 1 avidu 197609   75790 Jun 21 18:47 cuj-1-ingest.png
-rw-r--r-- 1 avidu 197609   77670 Jun 21 18:47 cuj-2-uri.png
-rw-r--r-- 1 avidu 197609   79594 Jun 21 18:47 cuj-3-processing.png
-rw-r--r-- 1 avidu 197609   76136 Jun 21 18:51 cuj-4-rallies.png
-rw-r--r-- 1 avidu 197609  266133 Jun 21 18:51 cuj-5-reel-ready.png
-rw-r--r-- 1 avidu 197609 50604038 Jun 21 18:51 cuj-downloaded-reel.mp4
-rw-r--r-- 1 avidu 197609    3359 Jun 21 18:38 cuj-screencast.mjs
-rw-r--r-- 1 avidu 197609  471942 Jun 21 18:57 f-end.png
-rw-r--r-- 1 avidu 197609  377994 Jun 21 18:57 f-reveal.png
-rw-r--r-- 1 avidu 197609  495236 Jun 21 18:53 frame-ingest.png
-rw-r--r-- 1 avidu 197609  438734 Jun 21 18:53 frame-rallies.png
-rw-r--r-- 1 avidu 197609  401624 Jun 21 18:53 frame-reel.png
-rw-r--r-- 1 avidu 197609 1670821 Jun 21 18:57 khelsutra-bucket-cuj-screencast.mp4
-rw-r--r-- 1 avidu 197609  342162 Jun 21 12:45 khelsutra-i18n-screencast.mp4
drwxr-xr-x 1 avidu 197609      0 Jun 21 12:43 node_modules
-rw-r--r-- 1 avidu 197609    1714 Jun 21 12:43 package-lock.json
-rw-r--r-- 1 avidu 197609     309 Jun 21 12:43 package.json
-rw-r--r-- 1 avidu 197609  433109 Jun 21 18:54 raw-175.png
-rw-r--r-- 1 avidu 197609  435318 Jun 21 18:54 raw-188.png
--- package.json scripts ---
{
  "name": "khelsutra-screencast",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "keywords": [],
  "author": "",
  "license": "ISC",
```

```

    "type": "commonjs",
    "dependencies": {
      "playwright": "^1.61.0"
    }
  }
}

```

563. user (2026-06-21T21:55:54.592Z)

```

=== rally-annotator i18n state ===
d5d59f2 v1.6.4: guard unsaved rallies from silent loss + flag edit mode on Mark buttons (#13)
6653d89 v1.6.4: guard unsaved rallies from silent loss; flag edit mode on Mark buttons
0262ed5 v1.6.3: show the version next to the plugin in VLC's Active Extensions list (#12)
---locales?---
---i18n refs---
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

564. assistant (2026-06-21T21:56:28.147Z)

The screencast tooling exists (`khelsutra-screencast/` with Playwright + a `cuj-screencast.mjs` template + prior `.mp4`s) ? so headless video screencasts are feasible. But my grep found ****no i18n in rally-annotator**** ? contrary to "it's localized." Let me verify rally-annotator's actual state (it's a VLC Lua plugin, so I checked the wrong file types) and confirm B7's scope:

565. user (2026-06-21T21:56:33.525Z)

```

=== file types ===
  5 md
  2 lua
  1 yml
  1 snapshot
  1 gitignore
  1 gitattributes
  1 LICENSE

=== any Kannada/Hindi/Devanagari script anywhere? ===
CHANGELOG.md
README.md
docs/CSV_FORMAT.md
docs/ENDING_REASONS.md
test/README.md
test/dialog_test.lua
vlc/rally_annotator.lua

```

```

=== i18n/locale/lang mechanism? ===

```

```

=== README localization mentions? ===
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

566. assistant (2026-06-21T21:56:53.342Z)

rally-annotator ****does**** carry Kannada/Hindi/Devanagari across its plugin (`rally\_annotator.lua`), README, CHANGELOG, and docs ? so it's localized (my first grep checked the wrong file types). Let me confirm how, and check B7's engine scope to size it:

567. user (2026-06-21T21:57:01.612Z)

```

=== how the .lua is localized (sample Indic lines) ===
vlc/rally_annotator.lua:4:  (badminton · tennis · table tennis · pickleball · padel)
vlc/rally_annotator.lua:7:  reason, and append one CSV row per rally. Pause/scrub freely, then
click ? the
vlc/rally_annotator.lua:59:  description below DO show, but in a different place ? the "More
information"

=== README i18n framing ===

```

```
===== B7 / engine backend l10n scope =====
engine head: 6fdd1d4 feat(serving): exposure-safety boot posture ? fail fast on a half-
configured exposed engine (default-OFF)
--- backend i18n already present? ---
--- customer_* / rejection strings (B7 surface) ---
backend/main.py
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

568. assistant (2026-06-21T21:57:26.903Z)

Let me verify rally-annotator's Indic content properly (ripgrep handles Unicode correctly, unlike my byte-range `git grep` which likely false-matched on `.`/'/?`):

569. user (2026-06-21T21:57:28.018Z)

No files found

570. assistant (2026-06-21T21:58:24.513Z)

Definitive: ****rally-annotator has no Kannada/Hindi anywhere**** (proper Unicode search found nothing) ? it is ****not**** localized, contrary to "it's also localized in all these languages." Let me check if a localization branch exists before I raise this:

571. user (2026-06-21T21:58:30.503Z)

```
=== branches ===
* main
  remotes/origin/claude/intelligent-planck-fokdq2
  remotes/origin/feat/layout-snapshot-ci
  remotes/origin/feat/version-in-window-title
  remotes/origin/fix/gitattributes-eol-lf
  remotes/origin/main
=== any branch/tag mentioning i18n/locale/lang? ===
no localization branch on origin

=== README: what languages does the PLUGIN itself claim? ===
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

572. assistant (2026-06-21T21:58:57.629Z)

Verified three ways now: ****rally-annotator is English-only**** ? no kn/hi text, no i18n mechanism, no localization branch on `origin`. That contradicts "it's also localized in all these languages," so before I bake a "consistent multilingual journey" claim into anything (or silently skip it), I need your call. Everything else in your request I'll proceed on (drop B7 ? it's a significant, owner-gated cross-repo Python backend effort; do A2, the UI/UX eval + header fixes, screencasts, and the doc closeout).

573. user (2026-06-21T22:03:06.895Z)

Your questions have been answered: "rally-annotator is currently NOT localized (verified: no Kannada/Hindi text, no i18n mechanism, no localization branch on origin ? it's a single English VLC Lua plugin). You mentioned it's localized for a consistent view. How should I handle it?"="Can you sync that repo to remote head and reassess?". You can now continue with these answers in mind.

574. user (2026-06-21T22:03:20.938Z)

```
=== local vs remote main ===
local: d5d59f2
origin: ac245ce
ac245ce feat(vlc): complete localization ? status messages + HELP guide (v1.7.1) (#21)
245bf54 feat(vlc): localize dialog chrome into 7 languages (v1.7) (#20)
0a05ecf feat(web): localize panel into kn/hi/es/da/id/te + per-locale screencasts (#19)
5ec1831 feat(web): i18n infrastructure + English catalog (keys-not-prose) (#18)
```

75541ab docs: localization (i18n) design + locked decisions (#17)
7094d76 docs(readme): use verified Khelsutra site copy + add "About Khelsutra" (#16)
33a4348 docs: frame as Khelsutra sister repo; add design doc + CONTRIBUTING + PR template (#15)
ad6ac9c Add rally-annotator web extension (Chrome MV3) with proof-driven tests + CI (#14)

=== pull --ff-only ===

```
create mode 100644 web/tsconfig.json
create mode 100644 web/vitest.config.ts
create mode 100644 web/wxt.config.ts
```

=== reassess: Kannada/Devanagari present now? ===

```
.gitattributes
.github/pull_request_template.md
.github/workflows/ci.yml
.github/workflows/web-ci.yml
.gitignore
CHANGELOG.md
CONTRIBUTING.md
LICENSE
README.md
docs/CSV_FORMAT.md
---ripgrep proper unicode---
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

575. assistant (2026-06-21T22:03:40.128Z)

My local rally-annotator was stale ? you're right. After `git pull --ff-only` it fast-forwarded to `ac245ce`, which includes `**#18?#21: full i18n infrastructure + localization into kn/hi/es/da/id/te + per-locale screencasts**` (and a new Chrome `web/` extension). My earlier "not localized" was a stale-checkout error on my part (I should have pulled the sibling first ? my own convention). Let me confirm the actual kn/hi content with proper Unicode and see its locale layout:

576. user (2026-06-21T22:03:41.770Z)

Found 6 files

```
C:\Users\avidu\Projects\rally-annotator\web\src\i18n\locales\kn\common.json
C:\Users\avidu\Projects\rally-annotator\web\src\i18n\locales\hi\common.json
C:\Users\avidu\Projects\rally-annotator\web\src\i18n\index.ts
C:\Users\avidu\Projects\rally-annotator\web\extension.spec.ts
C:\Users\avidu\Projects\rally-annotator\vlc\rally_annotator.lua
C:\Users\avidu\Projects\rally-annotator\test\dialog_layout.snapshot
```

577. assistant (2026-06-21T22:04:28.304Z)

Confirmed ? rally-annotator `**is**` fully localized (kn/hi in both the new Chrome `web/` extension `web/src/i18n/locales/{kn,hi}/common.json` and the VLC Lua plugin). My miss was a stale sibling checkout (I didn't pull it first ? exactly my own convention). So the `**annotator ? site ? studio journey` is genuinely consistent in kn/hi`**`, which I'll reference in the closeout.

Now I'll execute the full batch: drop B7 (significant + owner-gated), build A2, run the UI/UX eval + header fixes, record screencasts to `khelsutra-screencast/`, and close out the chapter. Let me set up tasks and a fresh worktree.

578. user (2026-06-21T22:04:30.725Z)

Task #13 created successfully: A2 ? localized WhatsApp share for the reel (SPA + site)

579. user (2026-06-21T22:04:32.589Z)

Task #14 created successfully: UI/UX eval + fix header clutter/misalignment (site)

580. user (2026-06-21T22:04:34.472Z)

Task #15 created successfully: Record screencasts to khelsutra-screencast/ (local)

581. user (2026-06-21T22:04:36.361Z)

Task #16 created successfully: Close out the multilingual chapter (docs)

582. user (2026-06-21T22:04:47.349Z)

```
/usr/bin/bash: line 1: cd: C:/Users/avidu/Projects/khelsutra-fu2-wt/site: No such file or
directory
origin/master: 64076a5 test(web): add a coverage floor (CI-gated) + i18n regression tests for
the #77 audit (#80)
branch 'feat/a2-whatsapp-share' set up to track 'origin/master'.
HEAD is now at 64076a5 test(web): add a coverage floor (CI-gated) + i18n regression tests for
the #77 audit (#80)
--- deps ---
web ?
```

583. assistant (2026-06-21T22:04:59.334Z)

Site deps didn't install (a path race). Let me verify the worktree and install site deps:

584. user (2026-06-21T22:05:04.245Z)

```
site
web
--- site npm ci ---
  run `npm fund` for details

found 0 vulnerabilities
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

585. assistant (2026-06-21T22:05:11.970Z)

Worktree ready. Let me start A2 ? read the SPA `CompileResult` (the reel-ready surface), the `result.\*` catalog keys, and the site's post-signup reveal:

586. user (2026-06-21T22:05:12.963Z)

Updated task #13 status

587. user (2026-06-21T22:05:13.222Z)

```
1      // The compiled-reel result (PER_RALLY_SELECTION.md P5): once Build ? POST /api/compile
succeeds,
2      // preview the reel inline (<video> over GET /api/highlights/...) and offer a download.
The engine
3      // returns a server-local filepath, NOT a URL (main.py:394), so the SPA builds the URL
itself. On a
4      // failure (e.g. the min_shot_count 400) we show the engine's reason ? loud, never
swallowed.
5
6      import { useTranslation } from "react-i18next";
7      import { StatusChip, Spinner } from "../StatusChip";
8
9      export type BuildState =
10     | { status: "idle" }
11     | { status: "building" }
12     | { status: "done"; url: string; filename: string }
13     | { status: "error"; error: string };
14
15     interface Props {
16       build: BuildState;
17       onDismiss: () => void;
```

```

18     }
19
20     export function CompileResult({ build, onDismiss }: Props) {
21         const { t } = useTranslation();
22         if (build.status === "idle") return null;
23
24         // Build state (A8): a visible "stitching?" card with an icon+text chip + reassurance,
so the user
25         // isn't staring at a frozen footer wondering whether anything is happening.
26         if (build.status === "building") {
27             return (
28                 <section data-testid="compile-result" className="mt-6 rounded-xl border border-
black/10 bg-paper p-4" aria-live="polite">
29                     <StatusChip tone="info" icon={<Spinner />} label={t("result.building")} />
30                     <p className="mt-2 text-sm text-ink/60">{t("result.buildingReassure")}</p>
31                 </section>
32             );
33         }
34
35         const isError = build.status === "error";
36         return (
37             <section
38                 data-testid="compile-result"
39                 aria-live="polite"
40                 className={"mt-6 rounded-xl border p-4 " + (isError ? "border-red-200 bg-red-50" :
"border-green/30 bg-green/5")}>
41                 >
42                     <div className="flex items-start justify-between gap-3">
43                         {/* Status as icon+text (never icon-only): ? ready / ? failed (A8). */}
44                         <h2 className="flex items-center gap-2 font-semibold text-ink">
45                             <span aria-hidden="true" className={isError ? "text-red-700" : "text-
green"}>{isError ? "?" : "?"}</span>
46                             {build.status === "done" ? t("result.ready") : t("result.failed")}
47                         </h2>
48                         <button
49                             type="button"
50                             onClick={onDismiss}
51                             aria-label={t("result.dismiss")}
52                             className="flex h-11 w-11 shrink-0 items-center justify-center rounded-full
text-ink/50 hover:text-ink"
53                         >
54                             ?
55                         </button>
56                     </div>
57
58                     {build.status === "done" ? (
59                         <div className="mt-3">
60                             {/* eslint-disable-next-line jsx-a11y/media-has-caption ? a stitched rally
reel has no captions */}
61                             <video
62                                 data-testid="reel-video"
63                                 src={build.url}
64                                 controls
65                                 playsInline
66                                 className="w-full max-w-xl rounded-lg bg-black"
67                             />
68                             <a
69                                 href={build.url}
70                                 download={build.filename}
71                                 className="mt-3 inline-flex min-h-11 items-center rounded-full bg-green px-4
py-2 text-sm font-semibold text-[#04140D]"
72                             >
73                                 {t("result.download", { filename: build.filename })}
74                             </a>
75                         </div>

```

```

76         ) : (
77             <p className="mt-2 text-sm text-red-800" data-testid="compile-error">
78                 {build.error}
79             </p>
80         )}
81     </section>
82 );
83 }
84

```

588. assistant (2026-06-21T22:05:57.452Z)

Now let me see the site's post-signup reveal mechanism (where a site-side share would live) to scope the site half of A2:

589. user (2026-06-21T22:05:57.881Z)

```

622     var prev = window.onYouTubeIframeAPIReady;
623     window.onYouTubeIframeAPIReady = function(){ if(typeof prev === 'function'){ prev();
} cb(); };
624     if(!document.getElementById('yt-iframe-api')){
625         var s = document.createElement('script');
626         s.id = 'yt-iframe-api'; s.src = 'https://www.youtube.com/iframe_api';
627         document.head.appendChild(s);
628     }
629 }
630 function revealAfterSignup(){
631     var host = document.getElementById('reel-reveal');
632     if(!host) return;
633     host.hidden = false;
634     // (1) the TOOL in action ? a self-hosted, FOOTAGE-FREE screencast (branded reel
placeholder),
635     //      so it's safe to autoplay openly; (2) a real reel preview (gated nocookie
YouTube). BOTH
636     //      stay visible together; the auto-close PAUSES while the reel is playing (so a
viewer is
637     //      never cut off mid-watch) and a manual ? closes it on demand.
638     host.innerHTML =
639         '<div class="reveal-bar"><button type="button" id="reel-close" class="reveal-x"
aria-label="Close the videos">? Close</button></div>'
640         + '<p class="reveal-h">1 · The tool in action</p>'
641         + '<video class="tool-vid" src="/video/tool-cuj.mp4" autoplay muted loop
playsinline controls preload="metadata"></video>'
642         + '<p class="reveal-h">2 · A real reel it made</p>'
643         + '<div class="reelwrap"><div id="reel-player"></div></div>'
644         + '<p class="stamp" style="text-align:center;margin-top:.6rem">Generated by
Khelsutra.guru · auto-closes <span id="reel-count">' + REEL_SECS + '</span>s after the reel
stops ? or close it anytime</p>';
645     var n = REEL_SECS, el = document.getElementById('reel-count'), player = null, hold =
false, closed = false;
646     function close(){
647         if(closed) return; closed = true;
648         clearInterval(iv);
649         try{ if(player){ player.destroy(); } }catch(_){ }
650         host.innerHTML = ''; host.hidden = true;
651     }
652     var iv = setInterval(function(){
653         if(hold) return; // the reel is playing ? hold the timer (no
mid-watch cut-off)
654         n--; if(el){ el.textContent = n; }
655         if(n <= 0){ close(); }
656     }, 1000);
657     var x = document.getElementById('reel-close'); if(x){ x.addEventListener('click',
close); }
658     loadYTApi(function(){

```

```

659     player = new YT.Player('reel-player', {
660         width: '100%', height: '100%', videoId: REEL_VIDEO,
661         host: 'https://www.youtube-nocookie.com',
662         playerVars: { autoplay: 1, rel: 0, modestbranding: 1, playsinline: 1 },
663         events: {
664             onReady: function(e){
665                 var dur = Math.floor(e.target.getDuration() || 0);
666                 var maxStart = Math.max(0, dur - REEL_SECS);           // start so a full
~30s window plays before the end
667                 var start = maxStart > 0 ? Math.floor(Math.random() * (maxStart + 1)) : 0;
668                 host.setAttribute('data-reel-start', String(start)); // a different chunk
each sign-up
669                 e.target.seekTo(start, true);
670                 e.target.playVideo();
671             },
672             onStateChange: function(e){ hold = (e.data === 1); }      // 1 = PLAYING ? hold
the auto-close
673         }
674     });
675 });
676 }
677
678 f.addEventListener('change', function(e){
679     if(e.target.name === 'segment') f.classList.toggle('is-academy', e.target.value ===
'academy');
680 });
681 function mailtoFallback(p){

```

590. assistant (2026-06-21T22:07:14.981Z)

The reveal is dynamically injected, so the site-side share needs the shim to expose a small `t()` bridge for dynamic content. Plan for A2: **SPA** (share your reel) ? button in `CompileResult` done-state, `result.share`/`result.shareText` in all 6 SPA locales; **site** (share the product post-reveal) ? a `window`-exposed `t()` from the shim + a wa.me link in the reveal, `site.reveal.\*` (en/kn/hi real, es/da/id seeded). Let me write the catalog insertion script:

591. assistant (2026-06-21T22:07:27.244Z)

```

// A2 catalog keys:
// - result.share / result.shareText -> SPA "share YOUR reel" (all 6 SPA locales, real
translations)
// - site.reveal.share / .shareText -> site "share the product" post-reveal (en/kn/hi real;
es/da/id en-seed)
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const LOCALES = join(import.meta.dirname, "locales");

const result = {
    en: { share: "Share on WhatsApp", shareText: "I made my badminton highlights reel with
KhelSutra ? Try it: khelsutra.guru" },
    kn: { share: "WhatsApp ????? ??????????", shareText: "???? KhelSutra ???? ???? ?????????????
????? ???? ?????? ? ??????????: khelsutra.guru" },
    hi: { share: "WhatsApp ?? ???? ????", shareText: "????? KhelSutra ?? ???? ?????????
????? ? ? ??????: khelsutra.guru" },
    es: { share: "Compartir por WhatsApp", shareText: "Hice mi reel de jugadas de bádminton con
KhelSutra ? Pruébalo: khelsutra.guru" },
    da: { share: "Del på WhatsApp", shareText: "Jeg lavede min badminton-highlightreel med
KhelSutra ? Prøv det: khelsutra.guru" },
    id: { share: "Bagikan ke WhatsApp", shareText: "Saya membuat reel sorotan bulu tangkis dengan
KhelSutra ? Coba: khelsutra.guru" },
};

const revealEn = { share: "Share on WhatsApp", shareText: "Check out KhelSutra ? it turns a full

```

```

badminton match into a clean highlights reel ? khelsutra.guru" }];
const reveal = {
  en: revealEn,
  kn: { share: "WhatsApp ????? ??????????", shareText: "KhelSutra ???? ? ??? ????? ?????????????
????????? ????? ?????? ???? ???? ?????????? ? khelsutra.guru" },
  hi: { share: "WhatsApp ?? ???? ????", shareText: "KhelSutra ????? ? ?? ???? ?????????? ??? ?? ??
???? ?????? ??? ??? ???? ???? ? khelsutra.guru" },
  es: revealEn, da: revealEn, id: revealEn,
};

const RESULT_ANCHOR = ` "result": {\n`;
const SITE_ANCHOR = ` "site": {\n`;

for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const file = join(LOCALES, loc, "common.json");
  let text = readFileSync(file, "utf8");

  if (!text.includes('"share"')) {
    const r = result[loc];
    const ins = `      "share": ${JSON.stringify(r.share)},\n      "shareText":
${JSON.stringify(r.shareText)},\n`;
    text = text.replace(RESULT_ANCHOR, RESULT_ANCHOR + ins);
  }
  if (!text.includes('"reveal"')) {
    const rv = reveal[loc];
    const ins = `      "reveal": {\n        "share": ${JSON.stringify(rv.share)},\n
"shareText": ${JSON.stringify(rv.shareText)}\n      },\n`;
    text = text.replace(SITE_ANCHOR, SITE_ANCHOR + ins);
  }
  const parsed = JSON.parse(text);
  if (!parsed.result.share || !parsed.site.reveal.share) throw new Error(`${loc}: A2 insert
incomplete`);
  writeFileSync(file, text);
  console.log(`${loc}: result.share + site.reveal added`);
}

```

592. user (2026-06-21T22:07:27.280Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-fu2-wt_tmp_a2.mjs (file state is current in your context ? no need to Read it back)

593. user (2026-06-21T22:07:41.930Z)

```

en: result.share + site.reveal added
kn: result.share + site.reveal added
hi: result.share + site.reveal added
es: result.share + site.reveal added
da: result.share + site.reveal added
id: result.share + site.reveal added

copied
verify es result.share: Compartir por WhatsApp
verify kn reveal.shareText: KhelSutra ???? ? ???
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

594. assistant (2026-06-21T22:08:03.650Z)

Catalog keys added (all 6 locales). Now the SPA: add the "Share on WhatsApp" button to `CompileResult`'s done-state:

595. user (2026-06-21T22:08:09.178Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\web\src\components\CompileResult.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

596. assistant (2026-06-21T22:08:15.043Z)

Let me find where CompileResult is tested so I can add an A2 assertion:

597. user (2026-06-21T22:08:17.130Z)

```
src/components/a8.status.test.tsx
src/components/build-error.test.tsx
src/i18n/hygiene.test.ts
--- how build done-state is tested ---
src/components/IngestPanel.test.tsx:55:      { job_id: "j", status: "done", video_id: "vidZ",
result: { status: "success", video_id: "vidZ" } },
src/components/a8.status.test.tsx:33:    render(<CompileResult build={{ status: "done", url:
"/x", filename: "r.mp4" }} onDismiss={() => {}} />);
src/components/upload.test.tsx:37:    if (u.startsWith("/api/jobs/")) return ok({ job_id: "j",
status: "done", video_id: "VIDFINAL", result: { status: "success", video_id: "VIDFINAL" } });
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

598. assistant (2026-06-21T22:08:22.984Z)

`a8.status.test.tsx` tests the CompileResult done-state ? the natural home for the A2 share test. Let me read it:

599. user (2026-06-21T22:08:23.484Z)

```
1      // @vitest-environment jsdom
2      //
3      // A8 ? honest expectations for non-tech users on slow uplinks: background-processing
reassurance and
4      // status shown as icon+TEXT chips (never icon-only), on BOTH the ingest progress and
the build state.
5      import { describe, it, expect, beforeEach, afterEach, vi } from "vitest";
6      import { render, screen, cleanup, fireEvent, act } from "@testing-library/react";
7      import i18n from "../i18n";
8      import { CompileResult } from "../CompileResult";
9      import { IngestPanel } from "../IngestPanel";
10     import type { JobStatus } from "../api/types";
11
12     beforeEach(async () => {
13       window.localStorage.clear();
14       await i18n.changeLanguage("en");
15     });
16
17     afterEach(() => {
18       cleanup();
19       vi.restoreAllMocks();
20       vi.unstubAllGlobals();
21       vi.useRealTimers();
22     });
23
24     describe("A8: build state shows status + reassurance (CompileResult)", () => {
25       it("building ? a 'stitching?' chip + a reassurance line (and nothing to dismiss yet)",
() => {
26         render(<CompileResult build={{ status: "building" }} onDismiss={() => {}} />);
27         expect(screen.getByText("Stitching your reel?")).toBeTruthy();
28         expect(screen.getByText(/only takes a moment/i)).toBeTruthy();
29         expect(screen.queryByRole("button", { name: "Dismiss" })).toBeNull();
30       });
31
32       it("done ? a ? icon paired with the 'ready' text (icon+text, not icon-only)", () => {
33         render(<CompileResult build={{ status: "done", url: "/x", filename: "r.mp4" }}
onDismiss={() => {}} />);
34         const h = screen.getByRole("heading", { level: 2 });
35         expect(h.textContent).toContain("?");
```

```

36     expect(h.textContent).toContain("Your reel is ready");
37   });
38
39   it("error ? a ? icon paired with 'failed' + the message", () => {
40     render(<CompileResult build={{ status: "error", error: "boom" }} onDismiss={() =>
41     }} />);
42     const h = screen.getByRole("heading", { level: 2 });
43     expect(h.textContent).toContain("?");
44     expect(screen.getByText("boom")).toBeTruthy();
45   });
46
47   describe("A8: ingest progress reassurance + status chips (IngestPanel)", () => {
48     const httpOk = (s: number, j: unknown) => ({ ok: s >= 200 && s < 300, status: s, json:
49     async () => j, text: async () => JSON.stringify(j) });
50     function fetchSeq(process: unknown, jobs: JobStatus[]) {
51       let i = 0;
52       return vi.fn(async (url: string | URL, init?: RequestInit) => {
53         const u = String(url);
54         if (u === "/api/process" && (init?.method ?? "GET") === "POST") return process;
55         if (u.startsWith("/api/jobs/")) {
56           const b = jobs[Math.min(i, jobs.length - 1)];
57           i += 1;
58           return httpOk(200, b);
59         }
60         throw new Error(`unexpected fetch ${u}`);
61       }) as unknown as typeof fetch;
62     }
63
64     it("while processing ? the working chip + 'safe to wait' reassurance", async () => {
65       vi.useFakeTimers();
66       vi.stubGlobal("fetch", fetchSeq(httpOk(202, { job_id: "j", status: "queued" }), [
67         { job_id: "j", status: "running", progress: "segmenting" },
68       ]));
69       render(<IngestPanel onLoaded={vi.fn()} />);
70       fireEvent.change(screen.getByLabelText(/video location/i), { target: { value:
71       "gs://b/x.mp4" } });
72       fireEvent.click(screen.getByRole("button", { name: /process video/i }));
73       await act(async () => {
74         await vi.advanceTimersByTimeAsync(0); // submit ? polling
75       });
76       await act(async () => {
77         await vi.advanceTimersByTimeAsync(1000); // running tick ? progress word
78       });
79       expect(screen.getByText(/processing your video/i)).toBeTruthy();
80       expect(screen.getByText(/safe to wait/i)).toBeTruthy();
81     });
82
83     it("on failure ? a ? 'Couldn't process' status chip alongside the friendly message",
84     async () => {
85       vi.stubGlobal("fetch", vi.fn(async () => {
86         throw new Error("offline");
87       }) as unknown as typeof fetch);
88       render(<IngestPanel onLoaded={vi.fn()} />);
89       fireEvent.change(screen.getByLabelText(/video location/i), { target: { value:
90       "gs://b/x.mp4" } });
91       fireEvent.click(screen.getByRole("button", { name: /process video/i }));
92       expect(await screen.findByText("Couldn't process")).toBeTruthy();
93       expect(await screen.findByText(/is it running/i)).toBeTruthy();
94     });
95   });
96 }

```

Let me add the A2 share test to the build-state describe:

601. user (2026-06-21T22:08:46.139Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\web\src\components\a8.status.test.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

602. assistant (2026-06-21T22:08:52.928Z)

Now run the web suite to confirm the SPA A2 part (catalog keys all 6 + button + test):

603. user (2026-06-21T22:09:08.122Z)

```
=== typecheck ===
src/components/CompileResult.tsx(95,1): error TS1381: Unexpected token. Did you mean `{'}'` or `&rbrace;`?
src/components/CompileResult.tsx(96,1): error TS1005: '</' expected.
=== tests ===
  FAIL  src/components/a4.touch.test.tsx [
src/components/a4.touch.test.tsx ]
  FAIL  src/components/a8.status.test.tsx [
src/components/a8.status.test.tsx ]
  FAIL  src/components/build-error.test.tsx [ src/components/build-
error.test.tsx ]
  FAIL  src/i18n/i18n.test.tsx [ src/i18n/i18n.test.tsx ]
  Test Files  4 failed | 19 passed
(23)
    Tests  183 passed (183)
=== build ===
    at Readable.push (node:internal/streams/readable:399:5)
    at Pipe.onStreamRead (node:internal/stream_base_commons:189:23)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

604. assistant (2026-06-21T22:09:30.804Z)

The JSX broke ? my edit consumed the outer `

605. user (2026-06-21T22:09:31.735Z)

```
58      {build.status === "done" ? (
59        <div className="mt-3">
60          {/* eslint-disable-next-line jsx-a11y/media-has-caption ? a stitched rally
reel has no captions */}
61          <video
62            data-testid="reel-video"
63            src={build.url}
64            controls
65            playsInline
66            className="w-full max-w-xl rounded-lg bg-black"
67          />
68          <div className="mt-3 flex flex-wrap items-center gap-2">
69            <a
70              href={build.url}
71              download={build.filename}
72              className="inline-flex min-h-11 items-center rounded-full bg-green px-4
py-2 text-sm font-semibold text-[#04140D]"
73            >
74              {t("result.download", { filename: build.filename })}
75            </a>
76            {/* A2: localized WhatsApp share. Opens the user's own WhatsApp with a pre-
filled message
77              (wa.me can't attach the local file, so the user adds the just-
downloaded reel). */}
```

```

78         <a
79             href={`https://wa.me/?text=${encodeURIComponent(t("result.shareText"))}`}
80             target="_blank"
81             rel="noopener noreferrer"
82             data-testid="whatsapp-share"
83             className="inline-flex min-h-11 items-center gap-1.5 rounded-full border
border-green/50 px-4 py-2 text-sm font-semibold text-green hover:bg-green/5"
84         >
85             <span aria-hidden="true">?</span>{t("result.share")}
86         </a>
87     </div>
88     ) : (
89         <p className="mt-2 text-sm text-red-800" data-testid="compile-error">
90             {build.error}
91         </p>
92     )}
93 </section>
94 );
95 }

```

606. user (2026-06-21T22:09:40.052Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\web\src\components\CompileResult.tsx has been updated successfully. (file state is current in your context ? no need to Read it back)

607. user (2026-06-21T22:10:03.281Z)

```
> tsc --noEmit
```

```

=== tests ===
  Test Files   23 passed (23)
    Tests     215 passed (215)
=== build ===
dist/assets/index-C1fyBEZ0.js
412.48 kB ? gzip: 124.65 kB
? built in 1.31s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

608. assistant (2026-06-21T22:10:25.227Z)

Web A2 green (215 tests, typecheck, build). Now the site part. Let me read the shim's `render`/`boot` to add a small `window` bridge so the dynamically-injected reveal can localize:

609. user (2026-06-21T22:10:26.555Z)

```

100     try { localStorage.setItem(STORAGE_KEY, locale); } catch { /* private mode */ }
101     // Mirror to a cookie so server.js (VM host) can honor the persisted pref server-side
(no FOUC).
102     try { document.cookie = `${STORAGE_KEY}=${locale};path=/;max-
age=31536000;samesite=lax`; } catch { /* ignore */ }
103     }
104
105     async function loadCatalog(loc) {
106         try { const r = await fetch(`/locales/${loc}/common.json`); return r.ok ? await
r.json() : {}; } catch { return {}; }
107     }
108
109     async function render(locale) {
110         const catalogs = { en: await loadCatalog("en") };
111         if (locale !== "en") catalogs[locale] = await loadCatalog(locale);
112         document.documentElement.lang = locale;
113         applyDom(document, catalogs, locale);
114     }
115

```

```

116     async function boot() {
117         let stored = null;
118         try { stored = localStorage.getItem(STORAGE_KEY); } catch { /* ignore */ }
119         if (!stored) stored = readCookie(STORAGE_KEY); // server-set or cross-store persisted
pref
120         const query = new URLSearchParams(location.search).get("lang");
121         const nav = navigator.languages && navigator.languages.length ?
[...navigator.languages] : [navigator.language];
122         const locale = negotiate({ stored, query, nav });
123         await render(locale);
124         document.addEventListener("click", (e) => {
125             const btn = e.target.closest && e.target.closest("[data-lang]");
126             if (!btn) return;
127             e.preventDefault();
128             const loc = supported(btn.getAttribute("data-lang")) || DEFAULT;
129             persist(loc);
130             render(loc);
131         });
132     }
133
134     if (typeof document !== "undefined" && typeof window !== "undefined") {
135         if (document.readyState === "loading") document.addEventListener("DOMContentLoaded",
boot);
136         else boot();
137     }
138

```

610. assistant (2026-06-21T22:10:41.223Z)

Let me add the bridge to the shim's `render` (a `window.KhelSutra.t` for dynamically-injected content like the reveal):

611. user (2026-06-21T22:10:46.038Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

612. assistant (2026-06-21T22:11:12.025Z)

Now wire the WhatsApp share into the reveal IIFE using the bridge (with English fallback). Let me edit `revealAfterSignup`:

613. user (2026-06-21T22:11:16.312Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

614. assistant (2026-06-21T22:11:21.196Z)

Now add the share button to the reveal's injected HTML:

615. user (2026-06-21T22:11:25.523Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

616. assistant (2026-06-21T22:12:16.508Z)

Now the site A2 tests. Let me read the reveal tests in ux.dom.test.js to add a behavioral assertion:

617. user (2026-06-21T22:12:20.274Z)

```

77     test("after sign-up BOTH videos appear and a ? closes the reveal", async () => {
78         const { document, submit } = boot(async () => ({ ok: true }));
79         submit();
80         await tick();
81         const host = document.getElementById("reel-reveal");
82         assert.equal(host.hidden, false, "reveal should be visible after a successful
submit");
83         assert.ok(host.querySelector("video.tool-vid"), "the tool screencast video must be
present");
84         assert.ok(host.querySelector(".reelwrap #reel-player, .reelwrap iframe"), "the reel
player must be present");
85         const close = host.querySelector("#reel-close");
86         assert.ok(close, "a manual ? close must be present");
87         close.click();
88         assert.equal(host.hidden, true, "? must hide the reveal");
89         assert.equal(host.innerHTML, "", "? must clear the reveal");
90     });

```

618. user (2026-06-21T22:12:30.631Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\ux.dom.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

619. assistant (2026-06-21T22:12:35.457Z)

Now the static assets test for A2 site share:

620. user (2026-06-21T22:12:43.374Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

621. assistant (2026-06-21T22:12:52.127Z)

Right ? different worktree, need to read it first. Let me read the assets.test.js tail (the merged A7 test) in this worktree:

622. user (2026-06-21T22:12:53.143Z)

```

327: assert.match(cap, /data-i18n="site\.capture\.step1\.title"/, "the placement text step
should remain");
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

623. user (2026-06-21T22:12:58.485Z)

```

326     // The diagram complements the existing #1 "Place the camera" text step (doesn't
replace it).
327     assert.match(cap, /data-i18n="site\.capture\.step1\.title"/, "the placement text step
should remain");
328     });

```

624. user (2026-06-21T22:13:09.984Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

625. assistant (2026-06-21T22:13:20.789Z)

Now run the full site suite (ux.dom + assets A2 + drift/parity):

626. user (2026-06-21T22:13:25.303Z)

? A2: the post-signup reveal offers a localized, safe WhatsApp share of the reel (0.9445ms)
? A2: after sign-up the reveal offers a WhatsApp share of the reel (wa.me, safe, localizable)

```
(59.205ms)
? tests 72
? pass 72
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

627. assistant (2026-06-21T22:14:06.020Z)

72 site + 215 web tests green ? A2 is solid on both surfaces. The one integration the jsdom tests can't exercise is the ****shim bridge localizing the reveal in a real browser**** (jsdom only hits the en fallback). Let me verify that quickly via the preview. First add the fu2 server to launch.json:

628. user (2026-06-21T22:14:06.067Z)

```
1      {
2        "version": "0.0.1",
3        "configurations": [
4          {
5            "name": "khelsutra-web",
6            "runtimeExecutable": "npm",
7            "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
8            "port": 5173
9          },
10         {
11           "name": "khelsutra-site",
12           "runtimeExecutable": "node",
13           "runtimeArgs": ["site/server.js"],
14           "port": 8080
15         }
16       ]
17     }
18
```

629. user (2026-06-21T22:14:13.487Z)

The file C:\Users\avidu\Projects\khelsutra\.claude\launch.json has been updated successfully. (file state is current in your context ? no need to Read it back)

630. user (2026-06-21T22:14:22.684Z)

```
{
  "serverId": "6ef78ab2-9b2c-4b78-8d39-53086333bcda",
  "port": 8080,
  "name": "fu2-site",
  "reused": false
}
Server started successfully on port 8080.
```

631. assistant (2026-06-21T22:14:31.829Z)

Let me load the site in Kannada, submit the access form, and confirm the reveal injects a ****Kannada**** WhatsApp share (the real-browser bridge path):

632. user (2026-06-21T22:14:32.775Z)

Eval failed: Inspected target navigated or closed

633. user (2026-06-21T22:14:45.888Z)

```
{
  "bridge": true,
  "bridgeShareStart": "KhelSutra ???? ?",
}
```

```
"lang": "kn",
"shareHrefDecoded": null,
"shareLabel": null
}
```

634. assistant (2026-06-21T22:15:02.003Z)

The **bridge works** ? ``window.KhelSutra.t('site.reveal.shareText')`` returns Kannada ("KhelSutra ????? ?") and ``lang=kn``. The reveal didn't render (likely the form needs the name field / more time). Let me complete the submit properly and check the injected share:

635. user (2026-06-21T22:15:07.729Z)

```
{
  "rel": "noopener noreferrer",
  "revealHidden": false,
  "shareHref": "https://wa.me/?text=KhelSutra ????? ? ??? ????? ?????????",
  "shareLabel": "? WhatsApp ????? ?????????",
  "sharePresent": true
}
```

636. assistant (2026-06-21T22:15:20.752Z)

Site A2 verified end-to-end in a real browser ? the reveal share renders **""? WhatsApp ????? ????????????"** with a Kannada wa.me message and ``rel="noopener noreferrer"``. The bridge localizes dynamic content correctly. Let me check console and stop:

637. user (2026-06-21T22:15:21.150Z)

No console logs.

638. user (2026-06-21T22:15:25.593Z)

Server 6ef78ab2-9b2c-4b78-8d39-53086333bcda stopped

639. assistant (2026-06-21T22:15:41.893Z)

No console errors. A2 verified on both surfaces. Let me commit the A2 code, push, and open the PR (I'll add the tracker row + changelog with the real PR number after):

640. user (2026-06-21T22:15:55.140Z)

```
=== status (no temp files?) ===
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/i18n.js
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/src/assets.test.js
M site/src/ux.dom.test.js
M web/src/components/CompileResult.tsx
M web/src/components/a8.status.test.tsx
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/a2-whatsapp-share -> feat/a2-whatsapp-share
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

641. user (2026-06-21T22:16:10.075Z)

<https://github.com/avidullu/khelsutra/pull/82>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

642. assistant (2026-06-21T22:16:16.235Z)

PR #82 opened. Now the tracker A2 row + changelog with the real number:

643. user (2026-06-21T22:16:17.641Z)

134:| A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |
--- changelog tail ---
- `2026-06-22` ? **A7** ([#76](https://github.com/avidullu/khelsutra/p
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

644. user (2026-06-21T22:16:31.939Z)

134 | A2 | Localized **WhatsApp share** for the reel (SPA + site) | A | B1/B3 | No | ? | ? |

645. user (2026-06-21T22:16:40.038Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

646. user (2026-06-21T22:16:47.671Z)

185 - `2026-06-22` ? **A7** ([#76](https://github.com/avidullu/khelsutra/pull/76)) landed ?
camera-placement diagram on the capture page.** Added an **accessible inline SVG** (`role="img"`
+ localized `` side-view showing the load-bearing placement cues a coach can't get from
text alone: the elevated camera behind the baseline, the ~30° downward tilt, and the
full-court field-of-view cone (players within frame). A numbered ??? legend (HTML, so it
wraps) maps the markers to the rules and is localized en/kn/hi (`site.capture.diagram.\*`,
reusing the A3 capture terms) ? consistent with the now-trilingual capture page. The text "Place
the camera" step remains (the diagram complements it). Tests: a diagram-structure +
accessible-`<title>` + localized-legend assertion; kn/hi in-script check incl. `diagram.camera`;
the A3 drift test auto-covers the new keys; site 70 + web 173 green. Workstream A is now
A1/A3/A4/A5/A6/A7/A8/A9 ??? (remaining: A2 WhatsApp share; the B5/B6 SPA-console native-review
pass; full native review).
186</p></div><div data-bbox="64 625 327 639" data-label="Section-Header"><h4>647. user (2026-06-21T22:17:01.663Z)</h4></div><div data-bbox="64 653 792 681" data-label="Text"><p>The file C:\Users\avidu\Projects\khelsutra-fu2-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)</p></div><div data-bbox="64 696 327 711" data-label="Section-Header"><h4>648. user (2026-06-21T22:18:04.471Z)</h4></div><div data-bbox="64 725 610 753" data-label="Text"><p>To https://github.com/avidullu/khelsutra.git
f565f97..7763d88 feat/a2-whatsapp-share -> feat/a2-whatsapp-share</p></div><div data-bbox="64 767 813 919" data-label="Text"><p>=== CI (wait) ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/add45010-3a68-4c78-b5f2-efe1423e45b0
web pending 0
https://github.com/avidullu/khelsutra/actions/runs/27919219684/job/82609878284
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27919219684/job/82609878309
=== mergeable ===
MERGEABLE / UNSTABLE
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra</p></div>

649. assistant (2026-06-21T22:18:10.228Z)

Web CI is still running (the doc commit retriggered it). Let me wait for it to finish, then merge:

650. user (2026-06-21T22:18:54.585Z)

```
Workers Builds: hidden-king-khelsutra  pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/add45010-3a68-4c78-b5f2-efe1423e45b0
site  pass    15s
https://github.com/avidullu/khelsutra/actions/runs/27919219684/job/82609878309
web   pass    49s
https://github.com/avidullu/khelsutra/actions/runs/27919219684/job/82609878284
=== mergeable ===
MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

651. assistant (2026-06-21T22:19:01.463Z)

All green (site ?, web ?, Cloudflare ?, CLEAN). Let me merge A2 ? this closes the last open \$7 row:

652. user (2026-06-21T22:19:06.731Z)

```
MERGED
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

653. assistant (2026-06-21T22:19:43.538Z)

A2 merged (#82) ? **\$7 is now all ? except the owner-gated B7**. Now the UI/UX eval + header fixes. Let me mark A2 done, cut a fresh UI branch, and inspect the existing Playwright tooling (for both the eval screenshots and the screencasts):

654. user (2026-06-21T22:19:44.501Z)

Updated task #13 status

655. user (2026-06-21T22:19:44.973Z)

Updated task #14 status

656. user (2026-06-21T22:19:50.460Z)

```
1e52cfd..0fae364 master -> origin/master
Switched to a new branch 'feat/ui-header-cleanup'
master: 0fae364 feat(web+site): A2 ? localized WhatsApp share for the reel (SPA + site) (#82)

=== existing Playwright screencast script ===
// KhelSutra Studio ? FULL bucket?reel CUJ, driven entirely from the UI (B-P2).
// Point at a gs:// bucket video ? engine processes (real Gemini) ? review rallies ? build ?
download.
// Records the whole journey. Run against the SPA dev server (proxies /api ? the live engine on
:8000).
import { chromium } from "playwright";

const URL = process.env.URL || "http://localhost:5180";
const GS_URI = "gs://khelsutra-rally-corpus/videos/mahadevpura_smoke_180s.mp4";
const PROCESS_TIMEOUT = 300000; // up to 5 min for the real Gemini run + gs:// fetch
const HOLD = 1800;

const browser = await chromium.launch();
// Fresh context, English browser ? the SPA negotiates `en` (no persisted pref).
const ctx = await browser.newContext({
```

```

    locale: "en-US",
    viewport: { width: 1280, height: 900 },
    recordVideo: { dir: "video-cuj", size: { width: 1280, height: 900 } },
  });
const page = await ctx.newPage();
page.on("console", (m) => { if (m.type() === "error") console.log(" [page error]",
m.text().slice(0, 160)); });

await page.goto(URL, { waitUntil: "domcontentloaded" });

// 1) Land on the ingest screen (no ?video= ? the "Process a video" panel).
await page.getByText("Process a video", { exact: true }).waitFor({ timeout: 15000 });
console.log("ingest panel rendered; lang =", await page.evaluate(() =>
document.documentElement.lang));
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "cuj-1-ingest.png" });

// 2) Paste the bucket URI (typed for the camera) and submit.
const input = page.getByLabel(/video location/i);
await input.click();
await input.pressSequentially(GS_URI, { delay: 28 });
await page.waitForTimeout(700);
await page.screenshot({ path: "cuj-2-uri.png" });
await page.getByRole("button", { name: /process video/i }).click();

// 3) Live progress while the engine fetches the bucket video + runs Gemini.
await page.getByText(/Processing your video/i).waitFor({ timeout: 15000 }).catch(() => {});
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "cuj-3-processing.png" });

// 4) Rallies load into the existing back-half (the ingest panel hands off video_id ? ?video=).
await page.getByText(/rallies from this session/i).waitFor({ timeout: PROCESS_TIMEOUT });
const loaded = await page.getByText(/rallies from this session/i).textContent();
console.log("rallies loaded:", loaded?.trim());
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "cuj-4-rallies.png" });

// 5) Build the reel from the (default all-selected) rallies.
const buildBtn = page.getByRole("button", { name: /build reel/i });
await buildBtn.scrollIntoViewIfNeeded();
await buildBtn.click();

// 6) Reel ready ? preview + download.
await page.getByText("Your reel is ready", { exact: true }).waitFor({ timeout: 120000 });
await page.getByTestId("compile-result").scrollIntoViewIfNeeded();
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "cuj-5-reel-ready.png" });

// 7) Download to the local machine (the real end of the CUJ).
const [download] = await Promise.all([
  page.waitForEvent("download"),
  page.getByRole("link", { name: /download/i }).click(),
]);
await download.saveAs("cuj-downloaded-reel.mp4");
console.log("downloaded reel:", download.suggestedFilename());
await page.waitForTimeout(1200);

await ctx.close(); // flushes the video
await browser.close();
console.log("DONE");

=== playwright browsers installed? ===
chromium-1228
chromium_headless_shell-1228
ffmpeg-1011

```

winldd-1007

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

657. assistant (2026-06-21T22:20:19.860Z)

Playwright + chromium are installed and the `cuj-screencast.mjs` template shows the pattern. Let me start the worktree's site server and capture current-state screenshots to diagnose the headers (and reuse this for screencasts later). First the server:

658. user (2026-06-21T22:20:24.402Z)

site server on :8123 -> HTTP 200

659. assistant (2026-06-21T22:20:36.104Z)

```
// Capture above-the-fold screenshots of the marketing site (headers + hero) across pages,
// viewports and locales ? for the UI/UX header/clutter eval. Run with URL + OUT env.
import { chromium } from "playwright";
import { mkdirSync } from "node:fs";

const URL = process.env.URL || "http://localhost:8123";
const OUT = process.env.OUT || "eval-before";
mkdirSync(OUT, { recursive: true });

const pages = [
  ["home", "/"],
  ["capture", "/capture"],
  ["own-model", "/own-model"]
];
const views = [
  ["desktop", 1280, 900],
  ["mobile", 390, 844]
];
const locales = ["en", "kn"];

const browser = await chromium.launch();
for (const [vn, w, h] of views) {
  for (const loc of locales) {
    const ctx = await browser.newContext({
      viewport: { width: w, height: h },
      locale: loc === "kn" ? "kn-IN" : "en-US"
    });
    const page = await ctx.newPage();
    for (const [pn, path] of pages) {
      await page.goto(
        URL + path + "?lang=" + loc,
        { waitUntil: "domcontentloaded" }
      ).catch(() => {});
      await page.waitForTimeout(1000); // let fonts + the shim settle
      await page.screenshot({
        path: `${OUT}/${pn}-${vn}-${loc}.png`
      }); // above-the-fold (header + hero)
    }
    await ctx.close();
  }
}
await browser.close();
console.log("shots ->", OUT);
```

660. user (2026-06-21T22:20:36.128Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\eval-shots.mjs (file state is current in your context ? no need to Read it back)

661. user (2026-06-21T22:21:01.075Z)

```
shots -> eval-before
total 1872
drwxr-xr-x 1 avidu 197609      0 Jun 22 03:51 .
drwxr-xr-x 1 avidu 197609      0 Jun 22 03:50 ..
-rw-r--r-- 1 avidu 197609 111222 Jun 22 03:50 capture-desktop-en.png
-rw-r--r-- 1 avidu 197609 166734 Jun 22 03:50 capture-desktop-kn.png
-rw-r--r-- 1 avidu 197609  60336 Jun 22 03:50 capture-mobile-en.png
-rw-r--r-- 1 avidu 197609  89030 Jun 22 03:50 capture-mobile-kn.png
-rw-r--r-- 1 avidu 197609 336379 Jun 22 03:50 home-desktop-en.png
-rw-r--r-- 1 avidu 197609 369644 Jun 22 03:50 home-desktop-kn.png
```

```
-rw-r--r-- 1 avidu 197609 136387 Jun 22 03:50 home-mobile-en.png
-rw-r--r-- 1 avidu 197609 155938 Jun 22 03:50 home-mobile-kn.png
-rw-r--r-- 1 avidu 197609 143613 Jun 22 03:50 own-model-desktop-en.png
-rw-r--r-- 1 avidu 197609 144176 Jun 22 03:50 own-model-desktop-kn.png
-rw-r--r-- 1 avidu 197609 80689 Jun 22 03:50 own-model-mobile-en.png
-rw-r--r-- 1 avidu 197609 80809 Jun 22 03:51 own-model-mobile-kn.png
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

662. assistant (2026-06-21T22:21:08.969Z)

12 screenshots captured. Let me look at the headers across pages to diagnose the clutter/misalignment:

663. assistant (2026-06-21T22:21:20.861Z)

The home header is visibly **crowded**: brand + 6 nav links + the 3-pill switcher + "Request access" all jammed on one row, the switcher cramped between FAQ and the CTA. Let me check the other headers:

664. assistant (2026-06-21T22:21:31.643Z)

The capture page looks clean (the A7 diagram renders great), and its 3-item header is balanced. The **home** header is the crowded one. Let me check own-model and mobile:

665. assistant (2026-06-21T22:21:48.351Z)

The mobile home header is **broken** ? "Request access" overflows and is clipped at the right edge; brand + 3-pill switcher + CTA don't fit 390px. That's the core issue. Let me check the other two pages' mobile headers:

666. assistant (2026-06-21T22:22:42.537Z)

Diagnosis is clear: own-model wraps gracefully (fine), capture is balanced (fine), but the **home header overflows on mobile** (Request access clipped) and is **crowded on desktop**. Per ultracode, let me run a focused design-critique workflow over the screenshots + HTML to catch anything I'm missing before fixing:

667. user (2026-06-21T22:23:02.119Z)

Workflow launched in background. Task ID: w55aey5l9
Summary: Serious UI/UX critique of the marketing site headers + clutter/alignment across pages/viewports/locales
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\subagents\workflows\wf_7a9a5f0d-cb0
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\site-uiux-eval-wf_7a9a5f0d-cb0.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\site-uiux-eval-wf_7a9a5f0d-cb0.js"} to iterate without resending the script.)
Run ID: wf_7a9a5f0d-cb0
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\workflows\scripts\site-uiux-eval-wf_7a9a5f0d-cb0.js", resumeFromRunId: "wf_7a9a5f0d-cb0"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

668. assistant (2026-06-21T22:23:10.879Z)

The critique workflow runs in the background. Meanwhile let me read the home header CSS + the mobile breakpoint so I'm ready to fix:

669. user (2026-06-21T22:23:13.544Z)

```
=== .nav / nav-links / nav-right / langsw CSS ===
48: .btn-dark{background:var(--ink);color:#fff}
49: .btn-dark:hover{background:var(--ink2)}
59: .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
60: .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-size:1.18rem;letter-spacing:-.02em;text-decoration:none}
62: .nav-links{display:flex;align-items:center;gap:1.6rem}
63: .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
64: .nav-links a:hover{color:var(--tx)}
66: .nav-right{display:flex;align-items:center;gap:1rem}
67: .langsw{display:inline-flex;gap:2px;border:1px solid rgba(120,120,120,.3);border-radius:999px;padding:2px}
68: .langsw button{font:inherit;font-size:.8rem;font-weight:600;color:inherit;opacity:.62;background:transparent;border:0;border-radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}

=== mobile @media blocks ===
210: @media (max-width:860px){

=== nav-links display:none context ===

  footer{border-top:1px solid var(--line);padding:42px 0;color:var(--mut);font-size:.9rem}
  .foot{display:flex;flex-wrap:wrap;justify-content:space-between;gap:1.2rem;align-items:center}
  .foot a{color:var(--green-d);text-decoration:none}
  .foot a:hover{text-decoration:underline}
  .stamp{font-size:.82rem;color:var(--mut)}

  @media (max-width:860px){
    .nav-links{display:none}
    .g4{grid-template-columns:repeat(2,1fr)}
  }

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

670. assistant (2026-06-21T22:23:44.018Z)

I've prepped the header CSS (root cause: `.nav` is fixed-height + no-wrap, so on mobile the switcher + CTA overflow once `.nav-links` is hidden at 860px). The design-critique workflow is running in the background ? I'll fold its findings with my diagnosis once it completes, then fix the headers and re-screenshot to confirm before/after.

671. user (2026-06-21T22:23:46.117Z)

make sure to do a deep layout and rendering test for both desktop and mobile and ensure the rendering is good and if needed can remove the language switcher from the top panel to somewhere else? (recommendation, feel free to push back)

672. assistant (2026-06-21T22:25:34.163Z)

Good steer ? let me fold that in. The critique workflow is still running; here's my recommendation on the switcher (you invited pushback) and how I'll do the deep layout/render test.

****On moving the switcher out of the top panel ? partial pushback, with a better middle option:****

What the screenshots already proved is the real bug: the home header ****overflows on mobile**** ("Request access" is clipped) and is crowded on desktop ? because the switcher is ****3 always-visible pills**** ('English' '????' '????') competing with 6 nav links + the CTA. Capture and own-model headers are actually fine (own-model wraps; capture has room).

I'd ****keep the switcher in the header but collapse it to a compact dropdown**** ? a single control showing ? + the current language that reveals the three options on tap ? rather than moving it to the footer. Reasoning:

- For a non-tech kn/hi coach, a ****top, visible "?????" cue is a welcome signal**** ("this site

speaks your language")); burying it in the footer means they'd scroll a wall of English to find it.

- It's the **conventional, discoverable** spot ? and a single button fits mobile + desktop with room to spare, killing the overflow and the clutter.
- I'll build it no-JS-friendly (native `<details>` disclosure, keyboard/ARIA-correct), consistent across all three pages.
- (Auto Accept-Language negotiation already gives a Kannada phone Kannada automatically, so the switcher is mostly a manual override + signal ? which the compact dropdown preserves.)

If you'd still rather it leave the header entirely, say so and I'll move it (e.g., a slim full-width language bar directly under the header) ? but I think the compact dropdown is the cleaner win.

Deep layout + rendering test (desktop + mobile, en + kn): I'll drive Playwright across all 3 pages $\times \{1280, 390\} \times \{en, kn\}$ and assert **zero horizontal overflow** (`scrollWidth ? clientWidth`), check tap-target sizes, and eyeball every screenshot for Indic-glyph rendering (no tofu) and alignment ? before and after the fix ? and save the captures locally.

I'll implement the compact dropdown + fold the critique findings, then run that full test and report before/after. Proceeding on that basis unless you redirect.

673. user (2026-06-21T22:25:34.307Z)

```
<task-notification>
<task-id>w55aey5l9</task-id>
<tool-use-id>toolu_01WNJjShsy5bSnRcYeruPTxi</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\tasks\w55aey5l9.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "Serious UI/UX critique of the marketing site headers +
clutter/alignment across pages/viewports/locales" completed</summary>
<result>{"byLens":[{"lens":"headers","count":5}, {"lens":"hierarchy","count":5}, {"lens":"responsive",
"count":5}], "findings":[{"severity":"critical", "where":"home (index.html) / mobile 390px /
header ? brand + language switcher + \"Request access\" CTA", "problem":"CONFIRMED: the home
header overflows badly on mobile. Below 860px the nav links are hidden (.nav-links{display:none})
but the brand, the 3-button language switcher, and the dark \"Request access\" pill are all forced
into a single fixed-height row (.nav{display:flex;justify-content:space-between;height:66px}, no
wrap). There is not enough width for all three. In both en and kn screenshots the switcher
dominates the middle, the brand \"Khel?Sutra\" is squeezed against it, and the \"Request access\"
CTA is clipped off the right edge of the viewport ? it reads \"Requ / acce\" with the green/dark
pill bleeding past the screen edge (and in kn the same clip occurs). A coach/parent on a phone
literally cannot read or tap the primary CTA, and the header looks broken on the very first
screen.\"}, {"fix\":\"Add a mobile rule that lets the header wrap and removes the fixed height.
In the existing @media (max-width:860px) block (index.html ~line 210) add: \".nav{flex-wrap:wrap;
height:auto;row-gap:.5rem;padding-top:.55rem;padding-bottom:.55rem} .nav-right{flex-wrap:wrap;
gap:.6rem;justify-content:flex-end} .langsw button{padding:.28rem .5rem}\". Better still, at
&lt;=480px drop the brand to its own line and put switcher+CTA on a second line: @media (max-width:480px){.nav{flex-direction:column;align-items:stretch} .nav-right{justify-content:space-between;width:100%}}\". Also shorten the CTA on narrow screens (e.g. label it \"Request access\" -&gt; keep, but .btn-dark{white-space:nowrap}\" plus the wrap above prevents the clip).\", \"lens\":\"headers\"}, {"severity\":\"major\", \"where\":\"home (index.html) / desktop & mobile / header consistency vs capture + own-model\", \"problem\":\"The three page headers are structurally inconsistent. Home uses a light, sticky, full-width bar (rgba paper bg, height:66px, justify-content:space-between) while capture and own-model use a dark (var(--ink)) rounded card header inside a .sheet with flex-wrap:wrap. A coach moving home -&gt; capture -&gt; own-model sees three visually different headers (light vs dark, different brand sizing/colors, different switcher border color: home uses rgba(120,120,120,.3), the others rgba(255,255,255,.28)). This undermines the \"same product\" feel and is part of why the home header behaves differently (it's the only one that can't wrap).\", \"fix\":\"Make the home header wrap like the others (see critical fix) so behaviour matches. For visual consistency, align the switcher styling and brand treatment across the three files ? at minimum, give all three the same wrapping behaviour and the same switcher border token. Longer term, extract the header markup+CSS into one shared partial so the switcher/CTA layout can't drift between pages.\"}, {"lens\":\"headers\"}, {"severity\":\"major\", \"where\":\"home (index.html) / desktop / header ? nav links + switcher + CTA, especially kn\", \"problem\":\"On desktop the full nav (How it works /
```

Why it's hard / Own your model / Flyer / Roadmap / FAQ = 6 links) plus the 3-language switcher plus the "Request access" CTA crowd the bar. In Kannada the longer link labels push the cluster so the switcher's green active pill and the kn CTA ("????? ????") sit hard against the last nav link with almost no breathing room (nav-links gap:1.6rem, nav-right gap:1rem). It reads as cluttered rather than clipped, and is fragile ? one more link or a longer locale will overflow.", "fix": "Reduce crowding: trim the nav set (e.g. drop "Flyer" from the top nav since it already lives in the footer, leaving 5 links), and/or lower the breakpoint at which links collapse so kn/hi (wider scripts) collapse earlier than en ? e.g. hide .nav-links at <=1000px instead of 860px. Tighten spacing safety with .nav-right{gap:.75rem} and .nav-links{gap:1.2rem}. Ensure the langsw and CTA never wrap into the links: keep .nav-right as a non-shrinking group (flex:none).", "lens": "headers"}, {"severity": "minor", "where": "home (index.html) / mobile / header ? no way to reach nav sections", "problem": "On mobile the nav links are simply hidden (display:none) with no hamburger or alternative. A coach on a phone has no in-header path to How it works / Why it's hard / Own your model / Roadmap / FAQ ? they must scroll the long page blindly. This is secondary to the overflow but worsens the mobile header's usefulness.", "fix": "After fixing the overflow, consider a minimal disclosure: either a small "Menu" toggle that reveals the links, or (cheapest) keep links hidden but ensure the footer/section anchors are easy to reach. Not required to fix the clip, but recommended so the mobile header isn't just brand+switcher+CTA with no navigation.", "lens": "headers"}, {"severity": "nit", "where": "all three pages / header ? language switcher tap-target width on 390px", "problem": "The switcher buttons use padding:.3rem .55rem with min-height:32px. Height is fine, but on a 390px phone three buttons (English / ???? / ????) plus the brand and CTA make horizontal space tight; the en label "English" is the widest. Once wrapping is fixed this is acceptable, but the targets are near the low end for the stated non-tech-savvy, phone-first audience.", "fix": "Once the header wraps, bump tap comfort slightly: .langsw button{padding:.34rem .6rem;min-height:36px}. Optionally abbreviate the active-language label on the smallest screens (e.g. "EN" / "?" / "??") to save width, though full labels are clearer for first-time users.", "lens": "headers"}, {"severity": "critical", "where": "home (index.html) / mobile (~390px) / header .nav + .nav-right", "problem": "CONFIRMED overflow. The home header puts brand + 3-button language switcher + a solid 'Request access' pill into ONE flex row that is locked to height:66px with NO wrap and NO mobile collapse for .nav-right. At 860px the only mobile rule is .nav-links{display:none} ? the switcher and the CTA pill are never reflowed. Result on a phone: the 'Request access' pill is shoved off the right edge and clipped ('Requ / acce' in EN; the longer Kannada '????? ????' wraps to two lines and collides with the switcher in KN). The single most important conversion action is literally cut off-screen, and the header looks broken. This is the headline suspicion, and it is real and severe.", "fix": "In the @media (max-width:860px) block, let the bar wrap and drop the CTA pill on phones. Concretely: .nav{flex-wrap:wrap;height:auto;min-height:66px;row-gap:.5rem;padding-top:.5rem;padding-bottom:.5rem} and .nav-right .btn-dark{display:none} (the hero already has a prominent 'Request alpha access' primary button, and the sticky 'Request access' is redundant on mobile). If the CTA must stay, instead keep it and put brand on row 1 with .nav-right wrapping to row 2: .nav{flex-wrap:wrap;height:auto} + .brand{flex:1 1 100%} is heavy ? prefer hiding the pill. Either way add header .wrap.nav{flex-wrap:wrap} so nothing can clip.", "lens": "hierarchy"}, {"severity": "major", "where": "all three pages / header structure / .nav vs .head vs .head .top", "problem": "The three pages use three structurally different headers, so the persistent switcher behaves differently on each and there is no shared 'header rhythm'. Home: sticky bar, fixed 66px, space-between, no wrap (breaks ? see above). Capture: dark rounded sheet header, flex-wrap:wrap, brand LEFT / title CENTER / switcher RIGHT via space-between. Own-model: dark sheet header with a .top row (flex-wrap:wrap), brand + switcher + inline TEXT 'Request access ?' link (not a pill). A coach moving between pages sees the switcher jump position (right-of-center on capture, far-right on own-model, clipped on home) and sees 'Request access' rendered as a pill on home but as a plain text link on own-model and absent on capture. Inconsistent placement un ... (truncated 9283 chars, full result in C:\Users\avidu\AppData\Local\Temp\claudC--Users-avidu-Projects-khelsutra\dca1ff63-3aec-42ab-897f-41970003f4e1\tasks\w55aey5l9.output)</result><usage><agent_count>3</agent_count><subagent_tokens>211670</subagent_tokens><tool_uses>51</tool_uses><duration_ms>118163</duration_ms></usage></task-notification>

674. assistant (2026-06-21T22:25:49.218Z)

The critique strongly confirms my diagnosis (15 findings). Let me read the full output to capture all of them, then synthesize the fix:

```

1      {
2        "summary": "Serious UI/UX critique of the marketing site headers + clutter/alignment
across pages/viewports/locales",
3        "agentCount": 3,
4        "logs": [
5          "UI/UX critique: 15 findings (9 critical/major)"
6        ],
7        "result": {
8          "byLens": [
9            {
10              "lens": "headers",
11              "count": 5
12            },
13            {
14              "lens": "hierarchy",
15              "count": 5
16            },
17            {
18              "lens": "responsive",
19              "count": 5
20            }
21          ],
22          "findings": [
23            {
24              "severity": "critical",
25              "where": "home (index.html) / mobile 390px / header ? brand + language switcher
+ \"Request access\" CTA",
26              "problem": "CONFIRMED: the home header overflows badly on mobile. Below 860px
the nav links are hidden (.nav-links{display:none}) but the brand, the 3-button language
switcher, and the dark \"Request access\" pill are all forced into a single fixed-height row
(.nav{display:flex;justify-content:space-between;height:66px}, no wrap). There is not enough
width for all three. In both en and kn screenshots the switcher dominates the middle, the brand
\"Khel?Sutra\" is squeezed against it, and the \"Request access\" CTA is clipped off the right
edge of the viewport ? it reads \"Requ / acce\" with the green/dark pill bleeding past the
screen edge (and in kn the same clip occurs). A coach/parent on a phone literally cannot read or
tap the primary CTA, and the header looks broken on the very first screen.",
27              "fix": "Add a mobile rule that lets the header wrap and removes the fixed
height. In the existing @media (max-width:860px) block (index.html ~line 210) add: `.nav{flex-
wrap:wrap;height:auto;row-gap:.5rem;padding-top:.55rem;padding-bottom:.55rem} .nav-right{flex-
wrap:wrap;gap:.6rem;justify-content:flex-end} .langsw button{padding:.28rem .5rem}`. Better
still, at <=480px drop the brand to its own line and put switcher+CTA on a second line: `@media
(max-width:480px){.nav{flex-direction:column;align-items:stretch} .nav-right{justify-
content:space-between;width:100%}}`. Also shorten the CTA on narrow screens (e.g. label it
\"Request access\" -> keep, but `.btn-dark{white-space:nowrap}` plus the wrap above prevents the
clip).",
28              "lens": "headers"
29            },
30            {
31              "severity": "major",
32              "where": "home (index.html) / desktop & mobile / header consistency vs capture +
own-model",
33              "problem": "The three page headers are structurally inconsistent. Home uses a
light, sticky, full-width bar (rgba paper bg, height:66px, justify-content:space-between) while
capture and own-model use a dark (var(--ink)) rounded card header inside a .sheet with flex-
wrap:wrap. A coach moving home -> capture -> own-model sees three visually different headers
(light vs dark, different brand sizing/colors, different switcher border color: home uses
rgba(120,120,120,.3), the others rgba(255,255,255,.28)). This undermines the \"same product\"
feel and is part of why the home header behaves differently (it's the only one that can't
wrap).",
34              "fix": "Make the home header wrap like the others (see critical fix) so
behaviour matches. For visual consistency, align the switcher styling and brand treatment across
the three files ? at minimum, give all three the same wrapping behaviour and the same switcher
border token. Longer term, extract the header markup+CSS into one shared partial so the

```

```

switcher/CTA layout can't drift between pages.",
35         "lens": "headers"
36     },
37     {
38         "severity": "major",
39         "where": "home (index.html) / desktop / header ? nav links + switcher + CTA,
especially kn",
40         "problem": "On desktop the full nav (How it works / Why it's hard / Own your
model / Flyer / Roadmap / FAQ = 6 links) plus the 3-language switcher plus the \"Request
access\" CTA crowd the bar. In Kannada the longer link labels push the cluster so the switcher's
green active pill and the kn CTA (\"????? ??\") sit hard against the last nav link with
almost no breathing room (nav-links gap:1.6rem, nav-right gap:1rem). It reads as cluttered
rather than clipped, and is fragile ? one more link or a longer locale will overflow.",
41         "fix": "Reduce crowding: trim the nav set (e.g. drop \"Flyer\" from the top nav
since it already lives in the footer, leaving 5 links), and/or lower the breakpoint at which
links collapse so kn/hi (wider scripts) collapse earlier than en ? e.g. hide .nav-links at
<=1000px instead of 860px. Tighten spacing safety with .nav-right{gap:.75rem} and .nav-
links{gap:1.2rem}. Ensure the langsw and CTA never wrap into the links: keep .nav-right as a
non-shrinking group (flex:none).",
42         "lens": "headers"
43     },
44     {
45         "severity": "minor",
46         "where": "home (index.html) / mobile / header ? no way to reach nav sections",
47         "problem": "On mobile the nav links are simply hidden (display:none) with no
hamburger or alternative. A coach on a phone has no in-header path to How it works / Why it's
hard / Own your model / Roadmap / FAQ ? they must scroll the long page blindly. This is
secondary to the overflow but worsens the mobile header's usefulness.",
48         "fix": "After fixing the overflow, consider a minimal disclosure: either a small
\"Menu\" toggle that reveals the links, or (cheapest) keep links hidden but ensure the
footer/section anchors are easy to reach. Not required to fix the clip, but recommended so the
mobile header isn't just brand+switcher+CTA with no navigation.",
49         "lens": "headers"
50     },
51     {
52         "severity": "nit",
53         "where": "all three pages / header ? language switcher tap-target width on
390px",
54         "problem": "The switcher buttons use padding:.3rem .55rem with min-height:32px.
Height is fine, but on a 390px phone three buttons (English / ???? / ?????) plus the brand and
CTA make horizontal space tight; the en label \"English\" is the widest. Once wrapping is fixed
this is acceptable, but the targets are near the low end for the stated non-tech-savvy, phone-
first audience.",
55         "fix": "Once the header wraps, bump tap comfort slightly: .langsw
button{padding:.34rem .6rem;min-height:36px}. Optionally abbreviate the active-language label
on the smallest screens (e.g. \"EN\" / \"?\" / \"??\") to save width, though full labels are
clearer for first-time users.",
56         "lens": "headers"
57     },
58     {
59         "severity": "critical",
60         "where": "home (index.html) / mobile (~390px) / header .nav + .nav-right",
61         "problem": "CONFIRMED overflow. The home header puts brand + 3-button language
switcher + a solid 'Request access' pill into ONE flex row that is locked to height:66px with NO
wrap and NO mobile collapse for .nav-right. At 860px the only mobile rule is .nav-
links{display:none} ? the switcher and the CTA pill are never reflowed. Result on a phone: the
'Request access' pill is shoved off the right edge and clipped ('Requ / acce' in EN; the longer
Kannada '????? ????' wraps to two lines and collides with the switcher in KN). The single most
important conversion action is literally cut off-screen, and the header looks broken. This is
the headline suspicion, and it is real and severe.",
62         "fix": "In the @media (max-width:860px) block, let the bar wrap and drop the
CTA pill on phones. Concretely: .nav{flex-wrap:wrap;height:auto;min-height:66px;row-
gap:.5rem;padding-top:.5rem;padding-bottom:.5rem} and .nav-right .btn-dark{display:none} (the
hero already has a prominent 'Request alpha access' primary button, and the sticky 'Request
access' is redundant on mobile). If the CTA must stay, instead keep it and put brand on row 1

```

with ``.nav-right`` wrapping to row 2: ``.nav{flex-wrap:wrap;height:auto}`` + ``.brand{flex:1 1 100%}`` is heavy ? prefer hiding the pill. Either way add ``.header.wrap.nav{flex-wrap:wrap}`` so nothing can clip.",

```

63     "lens": "hierarchy"
64   },
65   {
66     "severity": "major",
67     "where": "all three pages / header structure / .nav vs .head vs .head .top",
68     "problem": "The three pages use three structurally different headers, so the
persistent switcher behaves differently on each and there is no shared 'header rhythm'. Home:
sticky bar, fixed 66px, space-between, no wrap (breaks ? see above). Capture: dark rounded sheet
header, `flex-wrap:wrap`, brand LEFT / title CENTER / switcher RIGHT via space-between. Own-
model: dark sheet header with a `top` row (`flex-wrap:wrap`), brand + switcher + inline TEXT
'Request access ?' link (not a pill). A coach moving between pages sees the switcher jump
position (right-of-center on capture, far-right on own-model, clipped on home) and sees 'Request
access' rendered as a pill on home but as a plain text link on own-model and absent on capture.
Inconsistent placement undermines the 'persistent' switcher's learnability.",
69     "fix": "Adopt one switcher placement convention: switcher always top-right of
the header, immediately followed (or not) by a single CTA treatment. Make the 'Request access'
affordance consistent ? use the SAME style on home and own-model (pick one: both ghost/text
link, or both pill). Easiest consistent fix: on home use the same inline text-link treatment
own-model uses for the sticky CTA on mobile, and standardize the switcher container (same
border/padding/gap values already match ? keep them) at top-right on every page. Add the same
`flex-wrap:wrap` safety to all three header rows.",
70     "lens": "hierarchy"
71   },
72   {
73     "severity": "major",
74     "where": "capture (capture.html) / mobile (~390px) / .head with title h1",
75     "problem": "Because `head` is space-between with `flex-wrap:wrap`, on a phone
the three items (brand, the centered h1 '1-page capture checklist' / '???? ????????? ?????????
?????', switcher) wrap into three stacked rows but the h1 keeps its desktop role as a centered
title squeezed between brand and switcher ? it ends up as a left-aligned full-width middle row
that reads like body text, not a page title, and the spacing between the three rows is uneven.
The page title (the user's main orientation cue) loses its visual weight and the rhythm looks
unbalanced versus the clean home/own-model stack.",
76     "fix": "Give the capture header an explicit mobile stack with order + spacing.
In a `@media (max-width:680px)` block (the file already has one): `.head{flex-
direction:column;align-items:flex-start;gap:.6rem}` and let h1 sit on its own row at full
prominence: `.head h1{font-size:1.15rem;order:3;width:100%}` with switcher last, brand first ?
or move the switcher to `.order:1` aligned right. The goal: brand row, then title row, then
switcher row, with one consistent gap (.6rem) ? matching the home/own-model header stacking
density.",
77     "lens": "hierarchy"
78   },
79   {
80     "severity": "minor",
81     "where": "home (index.html) / desktop + mobile / .langsw active state vs primary
CTA",
82     "problem": "The active language pill uses background:var(--green)` ? the exact
same green as the primary 'Request alpha access' / 'Request access' buttons. In the header the
green 'English' pill sits a few px from the green 'Request access' button (desktop) and is the
brightest thing in an otherwise muted bar, so the switcher draws more attention than its
importance warrants and competes chromatically with the real CTA. For a non-tech coach the eye
is pulled to a language toggle they rarely need rather than to the action.",
83     "fix": "Tone down the active switcher chip so it reads as 'selected' not 'call
to action': use a subtle fill instead of full brand green, e.g. `.langsw button[aria-
pressed=\\"true\\"]{background:rgba(25,179,107,.16);color:var(--green-d);opacity:1}` on the light
home header (and the analogous `.rgba(199,242,176,.18)` / lime text on the dark capture/own-model
headers). Reserve solid `.--green` fills for actual CTAs. This keeps the switcher legible while
restoring CTA primacy.",
84     "lens": "hierarchy"
85   },
86   {
87     "severity": "minor",

```

```

88         "where": "home (index.html) / desktop / header crowding before mobile
breakpoint",
89         "problem": "Even on desktop the home header is dense: 6 nav links + switcher +
CTA pill on one line. Between ~861px and ~1000px (small laptops, the common coach device after
phones) the nav links, the three-language switcher, and the pill crowd toward the edges with
tight gaps and the switcher can sit awkwardly close to the last nav link ('FAQ') and the CTA.
It's not clipped, but the spacing rhythm is uneven compared to the generous hero below.",
90         "fix": "Give the switcher breathing room and a clear separator from the links:
increase `.nav-right{gap:1rem}` is fine, but add a small left margin/divider before the
switcher, e.g. wrap nav-links and nav-right with `gap` and add `.nav-right{padding-
left:.25rem;border-left:1px solid var(--line);padding-left:1rem}` OR lower the mobile breakpoint
that hides nav-links to ~960px so the bar never reaches the crowded state. Verify the switcher's
32px-min-height buttons remain vertically centered within the 66px bar (they are, via align-
items:center ? keep).",
91         "lens": "hierarchy"
92     },
93     {
94         "severity": "critical",
95         "where": "home (index.html) / mobile 390px / header .nav .nav-right",
96         "problem": "CONFIRMED horizontal overflow. The header .nav is a single non-
wrapping flex row (display:flex; justify-content:space-between; height:66px) and the only mobile
rule, @media (max-width:860px){.nav-links{display:none}}, hides the center links but leaves
.nav-right intact: brand + 3-button language switcher + the 'Request access' .btn-dark pill. At
390px these three blocks exceed the viewport, so the dark button is clipped against the right
edge ('Reque... / acce...' cut off in EN) and the whole header bleeds past 390px, producing a
horizontal scrollbar / page shift. This is the headline issue a coach on a phone hits
immediately.",
97         "fix": "Make the home header wrap and shrink on mobile, mirroring what
capture/own-model already do. In the existing @media (max-width:860px) block add:\n .nav{flex-
wrap:wrap; height:auto; row-gap:.5rem; padding-top:.5rem; padding-bottom:.5rem}\n .nav-
right{gap:.5rem}\nAnd add a tighter rule for small phones:\n @media (max-width:430px){\n
.nav{justify-content:space-between}\n .brand{font-size:1.05rem}\n .nav-right .btn-
dark{padding:.55rem .9rem; font-size:.9rem}\n .langsw button{padding:.3rem .45rem}\n
}\nWrapping lets the language switcher + Request-access button drop to a second row instead of
overflowing. Also add `html,body{overflow-x:hidden}` (or better, `body{overflow-x:clip}`) as a
safety net against any residual bleed.",
98         "lens": "responsive"
99     },
100    {
101        "severity": "critical",
102        "where": "home (index.html) / mobile 390px Kannada (and Hindi) / header .nav-
right",
103        "problem": "The overflow is worse in KN: the active language pill (?????)
renders wider than 'English', and the localized 'Request access' label (?????? ?????) is longer,
so the .btn-dark wraps to two lines and the green pill is pushed off the right edge entirely.
Same root cause (no wrap, nav-right not collapsed) but it means the primary CTA is partially
unreachable in the non-English locales ? exactly the audience this i18n work targets.",
104        "fix": "Same wrap fix as above resolves it once .nav wraps. Additionally prevent
the CTA label from breaking: give the header CTA `white-space:nowrap` so '?????? ????' / Hindi
stays on one line:\n header .nav-right .btn-dark{white-space:nowrap}\nIf vertical space is a
concern after wrapping, consider hiding the header 'Request access' button on phones (the hero
already has a 'Request alpha access' primary CTA right below): @media (max-width:520px){header
.nav-right .btn-dark{display:none}} ? keeps the language switcher (the new, must-stay control)
and removes a redundant CTA.",
105        "lens": "responsive"
106    },
107    {
108        "severity": "major",
109        "where": "all three pages / mobile + desktop / language switcher .langsw
button",
110        "problem": "Tap targets are below the 44x44px a11y minimum. .langsw button has
min-height:32px with padding .3rem .55rem, giving ~36-38px tall and, for the 2-char 'hi'/short
labels, well under 44px wide. For non-tech-savvy users on phones (often older coaches/parents),
the en/kn/hi toggles are fiddly to hit accurately and easy to mis-tap, especially packed three-
in-a-row.",

```

```

111         "fix": "Bump the touch size on small viewports without enlarging the desktop
chrome:\n @media (max-width:680px){\n     .langsw button{min-height:40px; padding:.45rem .7rem;
font-size:.85rem}\n } \nThis is shared CSS-pattern across index/capture/own-model (all three
define .langsw identically), so apply to each. 40px+ with the padding meets a comfortable tap
target; pair with adequate spacing (the existing 2px gap is tight ? consider gap:4px).",
112         "lens": "responsive"
113     },
114     {
115         "severity": "minor",
116         "where": "home (index.html) / mobile / header vs capture+own-model headers
(consistency)",
117         "problem": "Inconsistent responsive behavior across the three headers.
capture.html (.head) and own-model.html (.head .top) both use flex-wrap:wrap and degrade
gracefully on phones and in KN/HI (verified in screenshots ? they stack into tidy rows, nothing
clipped). Only the home header lacks flex-wrap, so it's the lone broken one. Beyond the bug, the
divergence makes the site feel less coherent as users move home -> capture -> own-model.",
118         "fix": "Adopt the same flex-wrap:wrap pattern on the home .nav (covered by the
critical fix above). Going forward, factor the .langsw + header layout into one shared block so
the three pages don't drift again. No change needed to capture/own-model headers themselves.",
119         "lens": "responsive"
120     },
121     {
122         "severity": "nit",
123         "where": "home (index.html) / mobile / header .brand link tap target",
124         "problem": "The 'KheISutra' brand link in the header (and the bottom-aligned nav
anchors generally) is text-only with no padding, so its tappable area is just the glyph height
(~1.18rem line). Minor, but on a phone the home/brand link is a common escape hatch and is
smaller than ideal.",
125         "fix": "Give the brand a little vertical hit area on mobile: @media (max-
width:680px){.brand{padding:.25rem 0}} (it's already display:flex/align-items:center, so this
just grows the click target without visual change). Low priority relative to the overflow
fixes.",
126         "lens": "responsive"
127     }
128 ]
129 }
130 }

```

676. assistant (2026-06-21T22:28:32.393Z)

Full critique captured ? strong consensus: ***(1) critical*** home-header mobile overflow (CTA clipped, worse in kn), ***(2) major*** 3 inconsistent headers + the switcher jumping position/style, desktop crowding (fragile in kn), capture h1 losing prominence on mobile, and switcher **tap targets < 44px***, plus the active pill competing chromatically with the CTA.

The root cause across nearly all of these is the **3-always-visible pills***. So I'll do exactly what I recommended ? replace them with a **compact globe + `<select>`** (the robust, accessible, no-JS-correct form of a dropdown): it shows the current language (signal preserved), can't overflow, declutters desktop, is one comfortable tap target, and renders identically on every page. Plus defensive header fixes (wrap + `overflow-x` safety). Let me start with the shim:

677. user (2026-06-21T22:28:33.858Z)

```

71     // Walk i18n-tagged nodes under `root`. Three forms (missing key -> skip, leaving the
HTML default):
72     //   data-i18n="key"                                -> textContent
73     //   data-i18n="key" data-i18n-attr="x"              -> setAttribute(x, ?) (placeholder / aria-
label / alt ?)
74     //   data-i18n-html="key"                            -> innerHTML (for catalog-authored inline
markup like <b>;
75     //                                                     values are our own content, never user
input)
76     export function applyDom(root, catalogs, locale) {
77         for (const el of root.querySelectorAll("[data-i18n], [data-i18n-html]")) {
78             const htmlKey = el.getAttribute("data-i18n-html");

```

```

79     const val = translate(catalogs, locale, htmlKey || el.getAttribute("data-i18n"));
80     if (val == null) continue;
81     const attr = el.getAttribute("data-i18n-attr");
82     if (htmlKey) el.innerHTML = val;
83     else if (attr) el.setAttribute(attr, val);
84     else el.textContent = val;
85 }
86 for (const el of root.querySelectorAll("[data-lang]")) {
87     const on = el.getAttribute("data-lang") === locale;
88     el.setAttribute("aria-pressed", String(on));
89     el.classList.toggle("is-active", on);
90 }

```

678. user (2026-06-21T22:28:42.010Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

679. assistant (2026-06-21T22:28:48.248Z)

Now update boot's click handler to a `change` handler for the select:

680. user (2026-06-21T22:28:49.025Z)

```

122     }
123
124     async function boot() {
125         let stored = null;
126         try { stored = localStorage.getItem(STORAGE_KEY); } catch { /* ignore */ }
127         if (!stored) stored = readCookie(STORAGE_KEY); // server-set or cross-store persisted
128         const query = new URLSearchParams(location.search).get("lang");
129         const nav = navigator.languages && navigator.languages.length ?
130         [...navigator.languages] : [navigator.language];
131         const locale = negotiate({ stored, query, nav });
132         await render(locale);
133         document.addEventListener("click", (e) => {
134             const btn = e.target.closest && e.target.closest("[data-lang]");
135             if (!btn) return;
136             e.preventDefault();
137             const loc = supported(btn.getAttribute("data-lang")) || DEFAULT;
138             persist(loc);
139         });
140     }
141
142     if (typeof document !== "undefined" && typeof window !== "undefined") {
143         if (document.readyState === "loading") document.addEventListener("DOMContentLoaded",
144         boot);
145     }

```

681. user (2026-06-21T22:28:54.811Z)

```

132     document.addEventListener("click", (e) => {
133         const btn = e.target.closest && e.target.closest("[data-lang]");
134         if (!btn) return;
135         e.preventDefault();
136         const loc = supported(btn.getAttribute("data-lang")) || DEFAULT;
137         persist(loc);
138         render(loc);
139     });
140 }
141
142 if (typeof document !== "undefined" && typeof window !== "undefined") {
143     if (document.readyState === "loading") document.addEventListener("DOMContentLoaded",
144     boot);
145 }

```

682. user (2026-06-21T22:29:02.686Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

683. assistant (2026-06-21T22:29:43.842Z)

Shim updated (select-based). Now the 3 pages. Let me read the current switcher blocks + the `.langsw`` CSS across all three to replace them precisely:

684. user (2026-06-21T22:29:46.657Z)

```
=== index.html switcher markup ===
247:     <div class="langsw" role="group" aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
248-     <button type="button" data-lang="en" data-i18n="lang.en" lang="en" aria-
pressed="true">English</button>
249-     <button type="button" data-lang="kn" data-i18n="lang.kn" lang="kn" aria-
pressed="false">?????</button>
250-     <button type="button" data-lang="hi" data-i18n="lang.hi" lang="hi" aria-
pressed="false">?????</button>
251-     </div>
--- index.html .langsw CSS ---
67: .langsw{display:inline-flex;gap:2px;border:1px solid rgba(120,120,120,.3);border-
radius:999px;padding:2px}
68: .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.62;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
69: .langsw button:hover{opacity:1}
70: .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
=== capture.html switcher markup ===
73:     <div class="langsw" role="group" aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
74-     <button type="button" data-lang="en" data-i18n="lang.en" lang="en" aria-
pressed="true">English</button>
75-     <button type="button" data-lang="kn" data-i18n="lang.kn" lang="kn" aria-
pressed="false">?????</button>
76-     <button type="button" data-lang="hi" data-i18n="lang.hi" lang="hi" aria-
pressed="false">?????</button>
77-     </div>
--- capture.html .langsw CSS ---
23: .langsw{display:inline-flex;gap:2px;border:1px solid rgba(255,255,255,.28);border-
radius:999px;padding:2px}
24: .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.7;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
25: .langsw button:hover{opacity:1}
26: .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
=== own-model.html switcher markup ===
84:     <div class="langsw" role="group" aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
85-     <button type="button" data-lang="en" data-i18n="lang.en" lang="en" aria-
pressed="true">English</button>
86-     <button type="button" data-lang="kn" data-i18n="lang.kn" lang="kn" aria-
pressed="false">?????</button>
87-     <button type="button" data-lang="hi" data-i18n="lang.hi" lang="hi" aria-
pressed="false">?????</button>
88-     </div>
--- own-model.html .langsw CSS ---
30: .langsw{display:inline-flex;gap:2px;border:1px solid rgba(255,255,255,.28);border-
radius:999px;padding:2px}
31: .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.7;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
32: .langsw button:hover{opacity:1}
33: .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

685. assistant (2026-06-21T22:30:24.913Z)

I have the exact blocks. Let me read the regions I'll edit in capture.html and own-model.html (index.html is already tracked from A2):

686. user (2026-06-21T22:30:25.871Z)

```
22      /* persistent language switcher (B3) ? inherits header text colour, green fill =
active */
23      .langsw{display:inline-flex;gap:2px;border:1px solid rgba(255,255,255,.28);border-
radius:999px;padding:2px}
24      .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.7;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
25      .langsw button:hover{opacity:1}
26      .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
27      .body{padding:24px 30px 8px}
```

687. user (2026-06-21T22:30:26.610Z)

```
29      .nav-right{display:flex;align-items:center;gap:1rem}
30      .langsw{display:inline-flex;gap:2px;border:1px solid rgba(255,255,255,.28);border-
radius:999px;padding:2px}
31      .langsw button{font:inherit;font-size:.8rem;font-
weight:600;color:inherit;opacity:.7;background:transparent;border:0;border-
radius:999px;padding:.3rem .55rem;cursor:pointer;min-height:32px;line-height:1}
32      .langsw button:hover{opacity:1}
33      .langsw button[aria-pressed="true"]{background:var(--green);color:#04140D;opacity:1}
34      .body{padding:26px 32px 8px}
```

688. assistant (2026-06-21T22:30:43.874Z)

Now I'll convert all three switchers to the compact ``<select>`` and fix the headers. Starting with index.html ? CSS, then markup, then header-overflow safety:

689. user (2026-06-21T22:30:48.288Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

690. user (2026-06-21T22:30:57.374Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

691. assistant (2026-06-21T22:31:05.882Z)

Now the index.html header-overflow safety (body `overflow-x` + `.nav` wrap on mobile + CTA nowrap). Let me read the exact lines:

692. user (2026-06-21T22:31:07.226Z)

```
35:  body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.65;-webkit-font-smoothing:antialiased}
211: @media (max-width:860px){
      .split{grid-template-columns:1fr;gap:24px}
      .road{grid-template-columns:repeat(2,1fr)}
      .notes{grid-template-columns:1fr}
      .shuttle{opacity:.1}
      .hero-grid{grid-template-columns:1fr;gap:30px}
      .reel-card{max-width:460px}
    }
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

693. user (2026-06-21T22:31:13.724Z)

```
211     @media (max-width:860px){
212         .nav-links{display:none}
213         .g4{grid-template-columns:repeat(2,1fr)}
214         .g3, .g2{grid-template-columns:1fr}
```

694. user (2026-06-21T22:31:23.225Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

695. user (2026-06-21T22:31:33.297Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

696. assistant (2026-06-21T22:31:54.839Z)

Now capture.html ? CSS + switcher markup:

697. user (2026-06-21T22:31:58.962Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

698. user (2026-06-21T22:32:09.611Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

699. assistant (2026-06-21T22:32:15.313Z)

Now own-model.html ? CSS + switcher markup:

700. user (2026-06-21T22:32:20.207Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

701. user (2026-06-21T22:32:30.453Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

702. assistant (2026-06-21T22:32:41.223Z)

All three switchers converted to the compact `<select>`. Now update the tests that referenced the old pill markup. Let me find them:

703. user (2026-06-21T22:32:42.804Z)

```
src/assets.test.js:195:    assert.match(html, /class="langsw"[\^>]*role="group"[\^>]*aria-
label="Language"/, `${f} is missing the language switcher group`);
src/assets.test.js:197:    assert.match(html, new RegExp(`<button[\^>]+data-lang="${lang}"`),
`${f} switcher lacks the ${lang} button`);
src/assets.test.js:200:    assert.match(html, /data-
lang="kn"[\^>]*data-i18n="lang\.kn"|data-i18n="lang\.kn"[\^>]*data-lang="kn"/, `${f} switcher
isn't wired to the shared catalog (lang.kn)`);
src/i18n.shim.test.js:60:    <button id="b-en" data-lang="en">English</button>
src/i18n.shim.test.js:61:    <button id="b-kn" data-lang="kn">?????</button>
src/i18n.shim.test.js:69:    assert.equal(document.getElementById("b-kn").getAttribute("aria-
pressed"), "true", "active locale button is pressed");
src/i18n.shim.test.js:70:    assert.equal(document.getElementById("b-en").getAttribute("aria-
pressed"), "false", "inactive locale button is not pressed");
```

```
src/i18n.shim.test.js:71: assert.ok(document.getElementById("b-kn").classList.contains("is-
active"), "active button gets a non-color selection class");
src/server.test.js:130: assert.match(html, /data-lang="kn"/, "the switcher must be present on
the negotiated page");
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

704. assistant (2026-06-21T22:32:51.823Z)

Let me read the assets.test.js switcher-test block to rewrite it for the select:

705. user (2026-06-21T22:32:52.998Z)

```
192     test("every localizable page has a persistent en/kn/hi language switcher", () => {
193         for (const f of I18N_PAGES) {
194             const html = read(f);
195             assert.match(html, /class="langsw"[^>]*role="group"[^>]*aria-label="Language"/,
`{f} is missing the language switcher group`);
196             for (const lang of ["en", "kn", "hi"]) {
197                 assert.match(html, new RegExp(`<button[^>]+data-lang="${lang}"`), `{f} switcher
lacks the ${lang} button`);
198             }
199             // The switcher labels are driven by the SHARED catalog (lang.*) ? proves cross-
surface consumption.
200             assert.match(html, /data-
lang="kn"[^>]*data-i18n="lang\.kn"|data-i18n="lang\.kn"[^>]*data-lang="kn"/, `{f} switcher
isn't wired to the shared catalog (lang.kn)`);
201             // The Kannada/Hindi autonyms must be present in their own scripts (system-font
fallback renders them).
202             assert.match(html, /?????/, `{f} switcher lacks the Kannada autonym`);
203             assert.match(html, /?????/, `{f} switcher lacks the Hindi autonym`);
204         }
205     });
```

706. user (2026-06-21T22:33:08.879Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

707. assistant (2026-06-21T22:33:23.801Z)

Now the shim's applyDom test (uses old `data-lang` buttons). Let me read and rewrite it for the select:

708. user (2026-06-21T22:33:24.386Z)

```
52     assert.equal(translate(catalogs, "kn", "does.not.exist"), undefined, "missing
everywhere -> undefined");
53     });
54
55     test("applyDom walks data-i18n, sets attrs, marks the switcher, and never shows a raw
key", () => {
56         const { document } = new JSDOM(`<!doctype html><body>
57             <span id="auto" data-i18n="lang.kn">PLACEHOLDER</span>
58             <span id="keep" data-i18n="does.not.exist">KEEP ME</span>
59             <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
60             <button id="b-en" data-lang="en">English</button>
61             <button id="b-kn" data-lang="kn">?????</button>
62         </body>`).window;
63
64         applyDom(document, catalogs, "kn");
65
66         assert.equal(document.getElementById("auto").textContent, "?????", "data-i18n sets
textContent from the shared catalog");
67         assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key
```

```

leaves the HTML default ? never a raw key");
68     assert.equal(document.getElementById("ph").getAttribute("placeholder"),
catalogs.kn.site.capture.title, "data-i18n-attr targets an attribute (kn value for the kn
locale)");
69     assert.equal(document.getElementById("b-kn").getAttribute("aria-pressed"), "true",
"active locale button is pressed");
70     assert.equal(document.getElementById("b-en").getAttribute("aria-pressed"), "false",
"inactive locale button is not pressed");
71     assert.ok(document.getElementById("b-kn").classList.contains("is-active"), "active
button gets a non-color selection class");

```

709. user (2026-06-21T22:33:43.311Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

710. assistant (2026-06-21T22:33:51.819Z)

Now the server.test.js N8 switcher assertion:

711. user (2026-06-21T22:33:52.594Z)

```

126     assert.equal(res.headers.get("content-language"), "kn");
127     assert.match(res.headers.get("vary") || "", /accept-language/i, "must Vary on Accept-
Language for caches");
128     // The negotiated page still ships the client shim + switcher so the browser can
refine from here.
129     assert.match(html, /src="\/i18n\.js"/, "the negotiated page must still load the client
shim");
130     assert.match(html, /data-lang="kn"/, "the switcher must be present on the negotiated
page");
131     });

```

712. user (2026-06-21T22:34:00.981Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\server.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

713. assistant (2026-06-21T22:34:10.033Z)

Let me check for any remaining old-switcher references, then run the full site suite:

714. user (2026-06-21T22:34:15.477Z)

```

=== stragglers (old switcher refs in tests/src)? ===
(none ? all migrated)

=== full site suite ===
? every localizable page has a persistent, compact en/kn/hi language <select> switcher
(1.5434ms)
? tests 72
? pass 72
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

715. assistant (2026-06-21T22:34:34.875Z)

All 72 site tests pass, switcher fully migrated. Now the **deep layout + rendering test** you asked for ? Playwright across all 3 pages × {desktop, mobile} × {en, kn}, asserting zero horizontal overflow + capturing after-shots:

716. assistant (2026-06-21T22:34:42.271Z)

```

// Deep layout + rendering test: every page × {desktop,mobile} × {en,kn}. Asserts NO horizontal
// overflow (scrollWidth ≤ innerWidth), the compact <select> switcher reflects the locale, and
// captures an "after" screenshot for each combo.
import { chromium } from "playwright";
import { mkdirSync } from "node:fs";

const URL = process.env.URL || "http://localhost:8123";
const OUT = process.env.OUT || "eval-after";
mkdirSync(OUT, { recursive: true });

const pages = [["home", "/"], ["capture", "/capture"], ["own-model", "/own-model"]];
const views = [["desktop", 1280, 900], ["mobile", 390, 844]];
const locales = ["en", "kn"];

const browser = await chromium.launch();
const results = [];
for (const [vn, w, h] of views) {
  for (const loc of locales) {
    const ctx = await browser.newContext({ viewport: { width: w, height: h }, locale: loc ===
    "kn" ? "kn-IN" : "en-US" });
    const page = await ctx.newPage();
    for (const [pn, path] of pages) {
      await page.goto(URL + path + "?lang=" + loc, { waitUntil: "domcontentloaded" }).catch(()
      => {});
      await page.waitForTimeout(900);
      const m = await page.evaluate(() => ({
        sw: document.documentElement.scrollWidth,
        iw: window.innerWidth,
        lang: document.documentElement.lang,
        selVal: (document.querySelector("select[data-langsw]") || {}).value,
      }));
      const overflow = m.sw > m.iw + 1;
      results.push({ page: pn, view: vn, loc, ...m, overflow });
      await page.screenshot({ path: `${OUT}/${pn}-${vn}-${loc}.png` });
    }
    await ctx.close();
  }
}
await browser.close();

for (const r of results) console.log(`${r.overflow ? "OVERFLOW!" : "ok" }
${r.page}/${r.view}/${r.loc} lang=${r.lang} sel=${r.selVal} sw=${r.sw}/iw=${r.iw}`);
const bad = results.filter(r => r.overflow);
console.log(bad.length ? `FAIL: ${bad.length} overflow case(s)` : `PASS: no horizontal
overflow on any page/viewport/locale`);

```

717. user (2026-06-21T22:34:42.288Z)

File created successfully at: C:\Users\avidu\Projects\kheIsutra-screencast\deep-test.mjs (file state is current in your context ? no need to Read it back)

718. user (2026-06-21T22:35:04.907Z)

```

ok      home/desktop/en  lang=en sel=en sw=1280/iw=1280
ok      capture/desktop/en  lang=en sel=en sw=1280/iw=1280
ok      own-model/desktop/en  lang=en sel=en sw=1280/iw=1280
ok      home/desktop/kn  lang=kn sel=kn sw=1280/iw=1280
ok      capture/desktop/kn  lang=kn sel=kn sw=1280/iw=1280
ok      own-model/desktop/kn  lang=kn sel=kn sw=1280/iw=1280
ok      home/mobile/en  lang=en sel=en sw=390/iw=390
ok      capture/mobile/en  lang=en sel=en sw=390/iw=390
ok      own-model/mobile/en  lang=en sel=en sw=390/iw=390
ok      home/mobile/kn  lang=kn sel=kn sw=390/iw=390
ok      capture/mobile/kn  lang=kn sel=kn sw=390/iw=390
ok      own-model/mobile/kn  lang=kn sel=kn sw=390/iw=390

```

PASS: no horizontal overflow on any page/viewport/locale
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

719. assistant (2026-06-21T22:35:13.325Z)

****PASS ? zero horizontal overflow on all 12 combos****, and the `` reflects each locale. Let me visually confirm the previously-broken headers (home mobile was clipped, home desktop was crowded):

720. assistant (2026-06-21T22:35:23.256Z)

The mobile home header is now clean ? brand on row 1, then ****? English ?**** + a full, un-clipped "Request access" on row 2. Let me check desktop and the kn case (previously the worst):

721. assistant (2026-06-21T22:35:32.518Z)

Desktop home header is now tidy ? the single compact `? English ?` select frees up the space the 3 pills used to crowd. Let me confirm the kn mobile case (previously the worst ? clipped + 2-line CTA):

722. assistant (2026-06-21T22:37:08.400Z)

Headers are now clean across all 12 combos. One thing the kn home page reveals: the ****hero headline is still English**** (B3 left the `

723. user (2026-06-21T22:37:11.042Z)

```
266:      <h1>Every rally, indexed. <span class="hl">The dead time, gone.</span></h1>
--- hero object in en catalog ---
{
  "eyebrow": "Invite-only alpha · Bengaluru",
  "lead": "KhelSutra finds every rally in your session and strips out the knock-ups, walks and
gaps ? so a full match becomes a clean highlight reel you can watch and download. No editing, no
scrubbing.",
  "ctaPrimary": "Request alpha access",
  "ctaHow": "See how it works"
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

724. assistant (2026-06-21T22:37:35.855Z)

Let me add `site.hero.title` (en/kn/hi real; es/da/id seeded) and wire the h1 via `data-i18n-html`:

725. assistant (2026-06-21T22:37:42.070Z)

```
// Localize the home hero headline (the one big English string left on the kn/hi home page).
// Inserted as the first key of site.hero. en/kn/hi real; es/da/id en-seed (site is trilingual).
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
const LOCALES = join(import.meta.dirname, "locales");

const en = 'Every rally, indexed. <span class="hl">The dead time, gone.</span>';
const title = {
  en, es: en, da: en, id: en,
  kn: '????? ???????? ??????????. <span class="hl">?????????? ??, ???.</span>',
  hi: '?? ?????, ??? ?????. <span class="hl">????? ??, ?????.</span>',
};
const ANCHOR = `      "hero": {\n`;
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
```

```

const file = join(LOCALES, loc, "common.json");
let text = readFileSync(file, "utf8");
if (text.includes('"hero": {\n      "title"')) { console.log(`${loc}: already has
hero.title`); continue; }
text = text.replace(ANCHOR, ANCHOR + `      "title": ${JSON.stringify(title[loc])},\n`);
const p = JSON.parse(text);
if (!p.site.hero.title || !p.site.hero.lead) throw new Error(`${loc}: hero.title insert broke
hero`);
writeFileSync(file, text);
console.log(`${loc}: site.hero.title added`);
}

```

726. user (2026-06-21T22:37:42.089Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-fu2-wt_tmp_herotitle.mjs (file state is current in your context ? no need to Read it back)

727. user (2026-06-21T22:37:50.098Z)

```

en: site.hero.title added
kn: site.hero.title added
hi: site.hero.title added
es: site.hero.title added
da: site.hero.title added
id: site.hero.title added
copied
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

728. user (2026-06-21T22:37:57.248Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

729. assistant (2026-06-21T22:38:14.648Z)

Let me add `hero.title` to the "kn/hi carry REAL translations" check, then run the site + web suites and re-deep-test:

730. user (2026-06-21T22:38:16.547Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

731. user (2026-06-21T22:38:45.910Z)

```

=== site suite ===
? tests 72
? pass 72
? fail 0
=== web hygiene (key-parity w/ hero.title) ===
    Tests 28 passed (28)
=== deep layout/overflow re-test (after hero h1) ===
ok      own-model/mobile/kn  lang=kn sel=kn sw=390/iw=390

```

PASS: no horizontal overflow on any page/viewport/locale
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

732. assistant (2026-06-21T22:38:55.628Z)

All green (site 72, web hygiene 28, deep-test PASS). Let me confirm the kn hero now renders in Kannada (the after-shot):

733. assistant (2026-06-21T22:39:14.323Z)

The kn home hero now renders fully in Kannada (headline + everything), header clean. Let me quickly check the capture mobile header (the critique flagged the h1 prominence there):

734. assistant (2026-06-21T22:39:45.284Z)

Capture mobile header is now clean too ? the h1 ("1-page capture checklist") reads as a proper title beside the compact `? English ?`. The compact-select fix resolved every flagged header issue, and the hero now localizes. Let me review the change set and commit the UI/UX PR:

735. user (2026-06-21T22:39:49.413Z)

```
Exit code 1
=== status (no temp/eval files in repo?) ===
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/capture.html
M site/public/i18n.js
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/public/own-model.html
M site/src/assets.test.js
M site/src/i18n.shim.test.js
M site/src/server.test.js

=== staged file count ===
19
```

736. assistant (2026-06-21T22:39:58.009Z)

Clean ? 19 intended files staged (the exit code was just `grep` finding no stray files, which is what I want). Let me commit and open the UI/UX PR:

737. user (2026-06-22T00:54:35.231Z)

resume?

738. assistant (2026-06-22T00:55:00.635Z)

Resuming ? the UI/UX header-cleanup work is verified (compact `` switcher, zero overflow across all 12 desktop/mobile/en/kn combos, hero headline now localized). Let me confirm the staged set survived and commit it.

739. user (2026-06-22T00:55:04.680Z)

```
branch: feat/ui-header-cleanup
=== staged (cached) files ===
0
=== unstaged (should be none but access.db) ===
(nothing unstaged)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

740. assistant (2026-06-22T00:55:14.542Z)

0 staged AND nothing unstaged ? that's unexpected; my edits should be present. Let me investigate the full state before assuming anything:

741. user (2026-06-22T00:55:16.706Z)

=== full git status ===

On branch feat/ui-header-cleanup

Your branch is up to date with 'origin/feat/ui-header-cleanup'.

Untracked files:

(use "git add <file>..." to include in what will be committed)
site/access.db

nothing added to commit but untracked files present (use "git add" to track)

=== recent commits on this branch ===

8c6ca5e fix(site): UI/UX ? compact <select> language switcher + header overflow fix + localized hero headline

0fae364 feat(web+site): A2 ? localized WhatsApp share for the reel (SPA + site) (#82)

1e52cfd deploy(droplet): tailored alpha kit for the CPU droplet (engine api. side) (#81)

64076a5 test(web): add a coverage floor (CI-gated) + i18n regression tests for the #77 audit (#80)

8328721 docs(tracker): refresh the S7 milestone prose to merged reality (A6/A7/#77 landed) (#79)

=== are my UI/UX edits in the working tree? ===

1

0

742. assistant (2026-06-22T00:55:20.340Z)

API Error: Server is temporarily limiting requests (not your usage limit) · Rate limited

743. user (2026-06-22T00:56:47.670Z)

resume?

744. assistant (2026-06-22T00:57:17.973Z)

The work is safe ? it was committed as `8c6ca5e` and pushed (the "0" was just my bad grep: `site.hero.title` is nested JSON keys, not a literal string). Let me verify the commit is complete and check whether a PR exists yet:

745. user (2026-06-22T00:57:23.405Z)

=== commit 8c6ca5e file count + scope ===

locales/da/common.json	1 +
locales/en/common.json	1 +
locales/es/common.json	1 +
locales/hi/common.json	1 +
locales/id/common.json	1 +
locales/kn/common.json	1 +
site/public/capture.html	19 ++++++-----
site/public/i18n.js	16 +++++-----
site/public/index.html	26 ++++++-----
site/public/locales/da/common.json	1 +
site/public/locales/en/common.json	1 +
site/public/locales/es/common.json	1 +
site/public/locales/hi/common.json	1 +
site/public/locales/id/common.json	1 +
site/public/locales/kn/common.json	1 +
site/public/own-model.html	19 ++++++-----
site/src/assets.test.js	14 +++++-----
site/src/i18n.shim.test.js	18 ++++++-----
site/src/server.test.js	2 +-
19 files changed, 73 insertions(+), 53 deletions(-)	

=== hero.title present in committed catalogs? ===

en: Every rally, indexed. <span cl
kn: ????? ??????? ????????. <spa
hi: ?? ??, ??? ??. <span class

=== shim select handling present? ===
2

=== PR for this branch? ===
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

746. assistant (2026-06-22T00:57:37.344Z)

Commit `8c6ca5e` is complete (19 files; hero.title in en/kn/hi; shim select handling present), pushed, no PR yet. Let me run the full suites on the committed state (my pre-merge gate) and check master before opening the PR:

747. user (2026-06-22T00:58:01.017Z)

origin/master: 0fae364 feat(web+site): A2 ? localized WhatsApp share for the reel (SPA + site) (#82)
? branch contains master

=== WEB typecheck+test+build ===

Test Files 23 passed (23)
Tests 215 passed (215)
? built in 1.36s

=== SITE suite ===
? tests 72
? pass 72
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

748. assistant (2026-06-22T00:58:09.789Z)

All green (web 215, site 72), branch contains master. Let me open the UI/UX PR:

749. user (2026-06-22T00:58:25.529Z)

<https://github.com/avidullu/khelsutra/pull/83>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

750. assistant (2026-06-22T00:58:31.367Z)

PR #83 opened. Let me check CI + mergeability:

751. user (2026-06-22T00:59:25.323Z)

Workers Builds: hidden-king-khelsutra pass 0
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/b39a2121-49f7-4892-a17b-0675f2c8d2b8>
site pass 14s
<https://github.com/avidullu/khelsutra/actions/runs/27923225079/job/82620598573>
web pass 40s
<https://github.com/avidullu/khelsutra/actions/runs/27923225079/job/82620598628>
=== mergeable ===
MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

752. assistant (2026-06-22T00:59:33.813Z)

All green (site ?, web ?, Cloudflare ?, CLEAN). Let me merge the UI/UX PR:

753. user (2026-06-22T00:59:39.322Z)

MERGED

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

754. assistant (2026-06-22T01:00:18.913Z)

UI/UX merged (#83). Now the screencasts (task #15). Let me mark #14 done, restart the site server, and write a Playwright screencast of the multilingual journey + the clean compact switcher:

755. user (2026-06-22T01:00:19.473Z)

Updated task #14 status

756. user (2026-06-22T01:00:19.856Z)

Updated task #15 status

757. user (2026-06-22T01:00:22.367Z)

server already up on :8123

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

758. assistant (2026-06-22T01:00:47.870Z)

Server up. Let me write the screencast script (desktop multilingual journey + mobile header switch) using the Playwright recordVideo tooling:

759. assistant (2026-06-22T01:00:56.806Z)

```
// Records two screencasts of the localized + decluttered marketing site:
// 1) desktop multilingual journey: home (en) -> compact switcher -> Kannada home -> capture page
// 2) mobile header: the clean compact switcher reflowing en -> kn -> hi (no overflow)
// Run against the site server (URL env). Outputs .webm into ./ (Playwright records webm natively).
import { chromium } from "playwright";
import { rename } from "node:fs/promises";
import { mkdirSync } from "node:fs";

const URL = process.env.URL || "http://localhost:8123";
const HOLD = 1600;
mkdirSync("rec", { recursive: true });
const browser = await chromium.launch();

async function record(name, viewport, steps) {
  const ctx = await browser.newContext({ viewport, locale: "en-US", recordVideo: { dir: "rec",
size: viewport } });
  const page = await ctx.newPage();
  await steps(page);
  const v = page.video();
  await ctx.close(); // flush the video
  await rename(await v.path(), name);
  console.log("wrote", name);
}

// 1) Desktop: en home -> switch to Kannada -> recording gist -> capture page (kn persists)
await record("khelsutra-site-i18n-desktop.webm", { width: 1280, height: 800 }, async (page) => {
  await page.goto(URL + "/", { waitUntil: "domcontentloaded" });
  await page.waitForTimeout(HOLD);
  await page.selectOption("select[data-langsw]", "kn");
  await page.waitForTimeout(HOLD);
  await page.locator("#record").scrollIntoViewIfNeeded();
```

```

    await page.waitForTimeout(HOLD);
    await page.goto(URL + "/capture", { waitUntil: "domcontentloaded" });
    await page.waitForTimeout(HOLD);
    await page.locator(".diagram").scrollIntoViewIfNeeded();
    await page.waitForTimeout(HOLD);
  });

// 2) Mobile: the compact header switching en -> kn -> hi, never overflowing
await record("khelsutra-site-header-mobile.webm", { width: 390, height: 844 }, async (page) => {
  await page.goto(URL + "/", { waitUntil: "domcontentloaded" });
  await page.waitForTimeout(HOLD);
  await page.selectOption("select[data-langsw]", "kn");
  await page.waitForTimeout(HOLD);
  await page.selectOption("select[data-langsw]", "hi");
  await page.waitForTimeout(HOLD);
});

await browser.close();
console.log("DONE");

```

760. user (2026-06-22T01:00:56.837Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\site-screencast.mjs
(file state is current in your context ? no need to Read it back)

761. user (2026-06-22T01:01:23.730Z)

wrote khelsutra-site-i18n-desktop.webm
wrote khelsutra-site-header-mobile.webm
DONE

```

-rw-r--r-- 1 avidu 197609 261331 Jun 22 06:31 khelsutra-site-header-mobile.webm
-rw-r--r-- 1 avidu 197609 999454 Jun 22 06:31 khelsutra-site-i18n-desktop.webm
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

762. assistant (2026-06-22T01:01:33.412Z)

Two screencasts recorded (webm). The prior screencasts were mp4 ? let me convert for consistency (using ffmpeg; Playwright bundles one):

763. user (2026-06-22T01:01:39.714Z)

```

ffmpeg: /c/Users/avidu/AppData/Local/Microsoft/WinGet/Packages/Gyan.FFmpeg_Microsoft.Winget.Source_8wekyb3d8bbwe/ffmpeg-8.1.1-full_build/bin/ffmpeg
converted khelsutra-site-i18n-desktop.mp4
converted khelsutra-site-header-mobile.mp4
-rw-r--r-- 1 avidu 197609 209551 Jun 22 06:31 khelsutra-site-header-mobile.mp4
-rw-r--r-- 1 avidu 197609 482771 Jun 22 06:31 khelsutra-site-i18n-desktop.mp4
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

764. assistant (2026-06-22T01:01:51.864Z)

Both screencasts converted to mp4 and saved locally. Let me verify they're valid videos and tidy the intermediates:

765. user (2026-06-22T01:01:56.438Z)

```

khelsutra-site-i18n-desktop.mp4: 11.200000s
khelsutra-site-header-mobile.mp4: 5.000000s
--- cleanup intermediates ---
removed webm + rec/
--- final local deliverables in khelsutra-screencast/ ---
197609 50604038 Jun 21 18:51 cuj-downloaded-reel.mp4
197609 1670821 Jun 21 18:57 khelsutra-bucket-cuj-screencast.mp4

```

```
197609 342162 Jun 21 12:45 khelsutra-i18n-screencast.mp4
197609 209551 Jun 22 06:31 khelsutra-site-header-mobile.mp4
197609 482771 Jun 22 06:31 khelsutra-site-i18n-desktop.mp4
before/after eval shots:
eval-after:
(eval-before/ + eval-after/ screenshot sets present)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

766. assistant (2026-06-22T01:02:24.522Z)

Both screencasts saved locally in `khelsutra-screencast/` (desktop journey 11.2s, mobile header 5.0s), alongside before/after screenshot sets. Task #15 done. Now the doc closeout (#16). Let me cut a fresh branch and read the §9 DoD + changelog + B7 sections:

767. user (2026-06-22T01:02:25.011Z)

Updated task #15 status

768. user (2026-06-22T01:02:25.479Z)

Updated task #16 status

769. user (2026-06-22T01:02:30.424Z)

```
0fae364..4c0f35c master -> origin/master
Switched to a new branch 'feat/ml-closeout'
master: 4c0f35c fix(site): UI/UX ? compact language switcher + header overflow fix + localized
hero (#83)
```

=== §9 DoD ===

9. Definition of done

- [] **Automatic language negotiation** (§6.5) is green ? a **Kannada browser** gets Kannada and a **Hindi browser** gets Hindi (N1/N2); persisted-pref / `?lang` / region-subtag / unsupported-fallback / missing-key-fallback all proven (N3?N7) on the SPA, and the static-site shim honors `Accept-Language` + `?lang` (N8).
- [] **Manual cross-check** (owner machine): OS/browser set to Kannada and to Hindi each render the respective language on BOTH surfaces, with Noto fonts displaying.
- [] `en + kn + hi` catalogs live and **rendering** on BOTH `web/` SPA and `site/` marketing (switcher + persistence + `en` fallback; no raw keys shown).
- [] **Noto Sans Kannada + Devanagari** render correctly ? owner eyeball on a real machine.
- [] CI **key-parity + no-bare-strings** green; a stub locale flags every gap.
- [] **Recording-education** (capture + homepage gist) available in `kn` + `hi`.
- [] **Non-tech UX baseline**: plain-language copy (no raw engine jargon in user-facing strings), mobile-usable touch targets, icon+text, WhatsApp share, honest today-vs-roadmap preserved through translation.
- [] §7 all rows ? (or explicitly deferred with a reason) ? flip **Status ? DONE** + completion note ? run engine `DOC\_STATUS.md §2` archival checklist ? `git mv` to `docs/archives/`.

10. References

=== §8 B7 / D-BACKEND-DEPTH ===

34: **Only D-BACKEND-DEPTH** (§8.3) remains open ? and it's a deferred, cross-repo engine concern (B7), not a v1 blocker.*

94:- The SPA is **job-tethered**; localizing **dynamic engine errors/report text** needs engine P2 (owner-gated, cross-repo, D-BACKEND-DEPTH) ? out of this DoD.

113:| N9 | **Backend (engine P2)** | `Accept-Language: kn` to the API | kn customer/report text | B7 (owner-gated) |

145:| B7 | **(deferred, cross-repo) Engine P2 backend customer-facing localization** (report `customer\_` + rejection reasons) | B | engine | **D-BACKEND-DEPTH, owner-gated** | ? | ? |

150: **Status** (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see §2 (D6?D9). Only D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

153:3. **D-BACKEND-DEPTH** ? ? OPEN (deferred, not a v1 blocker). **Recommend customer verdict/report** `customer\_` + validation-rejection reasons first; technical/operator text stays English; phase two (engine repo, owner-gated ? tracker row B7).

174:- `2026-06-21` ? owner locked **D6 (en+kn?hi)** + **D7 (OFL Noto carve-out)** and adopted **D8 (SPA-first)** + **D9 (catalogs in khelsutra)**; only D-BACKEND-DEPTH remains open. **B1 greenlit ? ? in progress.**
186:- `2026-06-22` ? **A2 ([#82](https://github.com/avidullu/khelsutra/pull/82)) landed ? localized WhatsApp share (the last open \$7 row).** SPA `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`). SPA `result.share`/`result.shareText` translated in all 6 locales; the site reveal (injected after sign-up, outside the static `data-i18n` walk) localizes via a new **`window.KhelSutra.t` shim bridge** (`site.reveal.\*`, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????????" + a Kannada message. Web 215 + site 72 green. **\$7 is now all ? except the owner-gated, cross-repo B7** (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

770. assistant (2026-06-22T01:02:52.671Z)

Now I'll flip the \$9 DoD boxes that CI/tests prove, leave the human-gated ones honestly open, and update the rest. First \$9:

771. user (2026-06-22T01:03:06.216Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

772. assistant (2026-06-22T01:03:13.361Z)

Now the changelog ? UI/UX (#83) entry + a closeout note (B7 assessment, rally-annotator consistency, screencasts). Let me read the changelog tail:

773. user (2026-06-22T01:03:18.547Z)

186 - `2026-06-22` ? **A2 ([#82](https://github.com/avidullu/khelsutra/pull/82)) landed ? localized WhatsApp share (the last open \$7 row).** SPA `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`). SPA `result.share`/`result.shareText` translated in all 6 locales; the site reveal (injected after sign-up, outside the static `data-i18n` walk) localizes via a new **`window.KhelSutra.t` shim bridge** (`site.reveal.\*`, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????????" + a Kannada message. Web 215 + site 72 green. **\$7 is now all ? except the owner-gated, cross-repo B7** (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.
187

774. user (2026-06-22T01:03:36.242Z)

The file C:\Users\avidu\Projects\khelsutra-fu2-wt\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

775. assistant (2026-06-22T01:03:52.026Z)

Doc closeout edited (\$9 flipped honestly, changelog for #83 + the chapter-complete note with B7 assessment + rally-annotator consistency + remaining human gates). Let me commit and open the closeout PR:

776. user (2026-06-22T01:04:08.540Z)

To https://github.com/avidullu/khelsutra.git
* [new branch] feat/ml-closeout -> feat/ml-closeout
https://github.com/avidullu/khelsutra/pull/84
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

777. assistant (2026-06-22T01:04:13.583Z)

PR #84 opened. Let me check CI + merge (doc-only, should be quick):

778. user (2026-06-22T01:05:02.576Z)

```
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/916d144f-eded-4968-890b-bc6bfd219c39
site pass 14s
https://github.com/avidullu/khelsutra/actions/runs/27923377652/job/82621032705
web pass 41s
https://github.com/avidullu/khelsutra/actions/runs/27923377652/job/82621032624
mergeable: MERGEABLE / CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

779. assistant (2026-06-22T01:05:06.947Z)

All green. Let me merge the closeout PR and then do final cleanup:

780. user (2026-06-22T01:05:12.592Z)

```
MERGED
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

781. assistant (2026-06-22T01:05:24.887Z)

All four follow-up PRs are merged. Let me do final cleanup ? remove the worktree + branches, stop the background server, and revert the temporary launch.json entry:

782. user (2026-06-22T01:05:32.484Z)

```
Exit code 255
4c0f35c..5e5a2ac master -> origin/master
=== origin/master top (A2/UI-UX/closeout present?) ===
5e5a2ac docs(friendly-multilingual): close out the chapter ($9 DoD + UI/UX + B7 deferred) (#84)
4c0f35c fix(site): UI/UX ? compact language switcher + header overflow fix + localized hero
(#83)
0fae364 feat(web+site): A2 ? localized WhatsApp share for the reel (SPA + site) (#82)
1e52cfd deploy(droplet): tailored alpha kit for the CPU droplet (engine api. side) (#81)

=== stop background site server on :8123 ===
ERROR: The process with PID 50500 could not be terminated.

=== remove worktree + branches ===
error: failed to delete 'C:/Users/avidu/Projects/khelsutra-fu2-wt': Permission denied
```

783. assistant (2026-06-22T01:05:51.911Z)

The background server (cwd in the worktree) is locking the dir, blocking removal, and my PID parse missed. Let me find and kill the exact node process serving the fu2 worktree, then remove it:

784. user (2026-06-22T01:06:03.038Z)

```
no fu2-wt node process found
remaining :8123 listeners: 1
```

785. assistant (2026-06-22T01:06:11.012Z)

The listener's command line is just `node server.js` (the worktree path is its CWD, not in the args). Let me kill it by the port owner directly:

786. user (2026-06-22T01:06:18.284Z)

killing PID 50500 cmd:
remaining :8123 listeners: 0

787. assistant (2026-06-22T01:06:24.907Z)

Server killed (:8123 free). Now retry the worktree + branch cleanup:

788. user (2026-06-22T01:06:27.375Z)

fatal: 'C:/Users/avidu/Projects/khelsutra-fu2-wt' is not a working tree
--- worktrees now ---
C:/Users/avidu/Projects/khelsutra 1e52cfd [master]

789. assistant (2026-06-22T01:06:40.938Z)

The worktree is deregistered (list shows only main), but the `&&` chain stopped before the branch deletes. Let me delete the branches and confirm the dir is gone:

790. user (2026-06-22T01:06:51.328Z)

```
=== local branches (a2/ui/closeout still there?) ===
  feat/a2-whatsapp-share
  feat/ml-closeout
  feat/ui-header-cleanup
=== delete them (local + remote) ===
Deleted branch feat/ui-header-cleanup (was 8c6ca5e).
- [deleted]          feat/ui-header-cleanup
Deleted branch feat/a2-whatsapp-share (was 7763d88).
- [deleted]          feat/a2-whatsapp-share
Deleted branch feat/ml-closeout (was 8a8a83b).
- [deleted]          feat/ml-closeout

=== worktree dir physically gone? ===
C:/Users/avidu/Projects/khelsutra-fu2-wt
STILL EXISTS
remaining remote follow-up branches:
(none ? clean)
```

791. assistant (2026-06-22T01:07:00.367Z)

Branches gone (local + remote, none remaining). The worktree dir was deregistered but not deleted (the earlier locked-dir failure). Let me remove the leftover dir and revert the launch.json entry:

792. user (2026-06-22T01:07:04.993Z)

fu2-wt dir removed ?

```
=== worktrees (clean?) ===
C:/Users/avidu/Projects/khelsutra 1e52cfd [master]
```

793. assistant (2026-06-22T01:07:09.707Z)

Now revert the temporary launch.json entry:

794. user (2026-06-22T01:07:10.318Z)

```
1      {
2        "version": "0.0.1",
3        "configurations": [
4          {
5            "name": "khelsutra-web",
6            "runtimeExecutable": "npm",
```

```

7      "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--
strictPort"],
8      "port": 5173
9    },
10   {
11     "name": "khelsutra-site",
12     "runtimeExecutable": "node",
13     "runtimeArgs": ["site/server.js"],
14     "port": 8080
15   },
16   {
17     "name": "fu2-site",
18     "runtimeExecutable": "node",
19     "runtimeArgs": ["C:/Users/avidu/Projects/khelsutra-fu2-wt/site/server.js"],
20     "port": 8080
21   }
22 ]
23 }
24

```

795. user (2026-06-22T01:07:16.164Z)

The file C:\Users\avidu\Projects\khelsutra\.claude\launch.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

796. assistant (2026-06-22T01:07:28.261Z)

Cleanup complete. Let me mark task #16 done and refresh the session handoff to the final state:

797. user (2026-06-22T01:07:28.732Z)

Updated task #16 status

798. assistant (2026-06-22T01:07:49.444Z)

Session handoff ? khelsutra (Friendly & Multilingual workstream)

Last updated: 2026-06-22, after A2 (#82) + the UI/UX header pass (#83) + the chapter closeout (#84) merged.

You are here ? chapter effectively COMPLETE (pending human gates)

\$7 of `docs/FRIENDLY\_AND\_MULTILINGUAL.md` is ****all ? except the owner-gated, cross-repo B7**** (deferred). Both surfaces are trilingual end-to-end and non-tech-friendly:

- ****SPA (`web/`)****: en/kn/hi + es/da/id (B1?B6 + MLX). ****Site (`site/`)****: en/kn/hi ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy in kn/hi (Noto bundled), A6 plain-language access form, A7 camera-placement diagram, ****A2 WhatsApp share**** (#82), and the ****UI/UX header pass**** (#83): the 3 language pills ? a compact `` (fixed the mobile header overflow; zero horizontal overflow across all 12 page/viewport/locale combos) + the home hero headline localized.
- The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in ****#77****; web coverage floor added in ****#80****.
- Sister repo ****rally-annotator** is also localized (kn/hi/es/da/id/te) ? the journey annotator ? site ? Studio is consistent in the user's language.

What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)

1. ****Native-speaker review**** of the AI-drafted kn/hi catalogs (site + SPA) ? the standing guardrail before a wide public launch.
2. ****Owner font-glyph eyeball**** on a real Kannada/Hindi device (CI can't render fonts). Proxy screencasts: `C:/Users/avidu/Projects/khelsutra-screencast/khelsutra-site-i18n-desktop.mp4` + `khelsutra-i18n-screencast.mp4`.

Open engineering follow-ups (small)

- **own-model body content** is still English on kn/hi (only its switcher + request link are localized) ? a separate content-translation slice (like A3).
- **Access form kn/hi** ? A6 left it English (``site.join.*`` en-seeded), translation-ready.
- **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
- Minor: ``site.*`` adds ~27KB to the SPA bundle (could split to a site-only catalog); ratchet web coverage thresholds as ``App.tsx`` gains tests.

Ramp-up kit

- ``docs/FRIENDLY_AND_MULTILINGUAL.md`` ? \$7 tracker (source of truth, all ? except B7), \$6.5 N1?N9, \$9 DoD (boxes flipped; 2 human gates open), changelog.
- ``/locales/{en,kn,hi,es,da,id}/common.json`` ? shared catalog: SPA console keys + ``site.*`` (nav/hero/record/capture/join/ownModel/reveal).
- ``site/public/i18n.js`` (shim: ``t``, ``data-i18n``, ``data-i18n-html``, compact ``<select>`` switcher, ``window.KhelSutra.t`` bridge, negotiation), ``site/server.js``, ``site/scripts/copy-locales.mjs``, ``site/src/{i18n.shim,locales-drift,assets,server}.test.js``.
- Screenshot/Playwright tooling + before/after eval shots: ``C:/Users/avidu/Projects/khelsutra-screenshot/`` (``site-screenshot.mjs``, ``deep-test.mjs``, ``eval-shots.mjs``).
- `[[catalog-home-and-i18n-layout]]`, `[[shared-checkout-concurrency]]`.

Key decisions (don't relitigate)

- D-CATALOG-HOME: catalogs at repo-root ``/locales``; SPA imports; site mirrors via ``copy:locales`` + drift guard.
- Negotiation order (both surfaces): persisted (``khelsutra.lang``) ? ``?lang=`` ? navigator/Accept-Language ? en; missing key ? en, never a raw key.
- Switcher = compact ``<select>`` in the header (kept there for discoverability/signal; auto-negotiation covers kn-phones). Rich ``<b>`` markup localizes via ``data-i18n-html`` (XSS-safe; catalog-authored).
- Process: isolated ``git worktree`` per PR (shared checkout churns fast); AI-draft translations ? adversarial verify ? native review is a pre-launch (not pre-merge) gate.

799. user (2026-06-22T01:07:49.462Z)

The file `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md` has been updated successfully. (file state is current in your context ? no need to Read it back)

800. assistant (2026-06-22T01:08:17.336Z)

All done. Here's the wrap-up of this whole follow-up batch.

What shipped (all merged on green CI; ``origin/master`` = ``5e5a2ac``)

```
| PR | What |
|----|-----|
| **A2** [#82](https://github.com/avidullu/khelsutra/pull/82) | Localized WhatsApp share ? SPA reel + site post-signup reveal (via a new `window.KhelSutra.t` shim bridge). The last open $7 row. |
| **UI/UX** [#83](https://github.com/avidullu/khelsutra/pull/83) | Header declutter + the bug you suspected |
| **Closeout** [#84](https://github.com/avidullu/khelsutra/pull/84) | $9 DoD flipped to reality; B7 + consistency recorded |
```

Your specific asks

B7 ? assessed, then dropped. It's significant: cross-repo (the **engine**/Python repo), backend customer-facing i18n with **no existing infra** (Accept-Language negotiation + translating ``customer_*`/rejection text + native review), and still owner-gated (D-BACKEND-DEPTH). Kept deferred ? not a v1 blocker.

rally-annotator ? you were right, I was wrong (stale checkout). My first look said "not localized"; after ``git pull --ff-only`` it fast-forwarded and it **is** fully localized (kn/hi/es/da/id/te, in both the new Chrome ``web/`` extension and the VLC plugin ? #18?#21). So

the **annotator ? site ? Studio journey is consistent in the user's language**, now recorded in the doc. (My miss = not pulling the sibling first, my own convention ? fixed.)

Deep layout + rendering test + the switcher. A 3-lens design critique confirmed your suspicion: the home header **overflowed on mobile** ? the 3 always-visible language pills shoved "Request access" off-screen (worse in kn). I pushed back on moving it to the footer and instead made it a **compact `? <select>`** (kept in the header for the "we speak your language" signal; shows the current language; one tap target; accessible; consistent on all 3 pages) + wrap/**overflow-x`** safety, and localized the home hero headline (the one big English string left on the kn page). The deep Playwright test (every page × {1280, 390} × {en, kn}) now reports **zero horizontal overflow on all 12 combos**; web 215 + site 72 green.

Screenshots ? saved to your machine in `C:/Users/avidu/Projects/khelsutra-screenshot/`:
- `khelsutra-site-i18n-desktop.mp4` (11s ? en ? Kannada switch ? localized recording-education + capture diagram)
- `khelsutra-site-header-mobile.mp4` (5s ? the clean compact header reflowing en ? kn ? hi)
- plus before/after eval screenshot sets (`eval-before/`, `eval-after/`).

Honest status

\$7 is all ? except the owner-gated B7. What gates **archiving** the chapter is **not code** ? it's the two human gates I left open in \$9: a **native-speaker review** of the AI-drafted kn/hi, and your **font-glyph eyeball** on a real Kannada/Hindi device (CI can't render glyphs ? the screenshots are the closest proxy). One small engineering follow-up remains: **own-model's** body content is still English on kn/hi (a separate translation slice, flagged in the doc).

Cleanup done: worktree removed, all follow-up branches deleted (local + remote), background server stopped, temporary `launch.json` entry reverted, handoff refreshed.

801. user (2026-06-22T01:08:20.648Z)

your context is getting full so please wrap up to a clean slate, merge your pending PRs and give me a nice icebreaker prompt for the next session to pick up!

802. assistant (2026-06-22T01:08:44.452Z)

Let me verify the slate is actually clean ? any open PRs to merge, and the working-tree/worktree state:

803. user (2026-06-22T01:08:50.563Z)

=== open PRs (any pending to merge?) ===

=== main checkout status ===

master

(clean tree ? only untracked .claude/ + site/access.db)

=== worktrees ===

C:/Users/avidu/Projects/khelsutra 1e52cfd [master]

=== origin/master HEAD ===

5e5a2ac docs(friendly-multilingual): close out the chapter (\$9 DoD + UI/UX + B7 deferred) (#84)

804. assistant (2026-06-22T01:09:07.621Z)

No open PRs ? everything's merged. Clean tree, single worktree. Let me fast-forward the local `master` to the merged truth (safe ? tree is clean, `--ff-only`) so the checkout is a clean slate:

805. user (2026-06-22T01:09:12.105Z)

web/src/components/CompileResult.tsx | 27 ++++++

web/src/components/a8.status.test.tsx | 19 ++++++

23 files changed, 243 insertions(+), 69 deletions(-)

now at: 5e5a2ac docs(friendly-multilingual): close out the chapter (\$9 DoD + UI/UX + B7

deferred) (#84)

```
=== final slate ===
branch: master | clean: yes
local==origin/master: yes
```

806. assistant (2026-06-22T01:09:38.792Z)

Clean slate confirmed:

- **No open PRs** ? A2 (#82), UI/UX (#83), and the closeout (#84) are all merged.
- Local `master` fast-forwarded to `5e5a2ac` (= `origin/master`); working tree clean; single worktree; follow-up branches deleted (local + remote); background server stopped; temporary `launch.json` entry reverted.
- Handoff + memory refreshed; screencasts saved in `khelsutra-screencast/`.

The Friendly & Multilingual chapter is **code-complete** ? §7 all ? except the deferred, owner-gated B7. It's gated only on human review now.

Icebreaker for next session

...

Resume the khelsutra Friendly & Multilingual work. Read the session handoff first (`~/claude/projects/C--Users-avidu-Projects-khelsutra/memory/session-handoff.md`) and `git pull --ff-only` before reading anything else.

State: the chapter is code-complete ? §7 all ? except the deferred B7. Two human gates remain before archiving (native-speaker review of the AI-drafted kn/hi; my font-glyph eyeball on a real device ? see the screencasts in `../khelsutra-screencast/`), plus one small engineering gap: own-model's body content is still English on kn/hi.

Pick up own-model kn/hi localization with the same diligence as the rest: isolated git worktree off origin/master, data-i18n[-html] the body content, AI-draft ? adversarial verify the translations, extend the site tests (drift + render), record a screencast, and merge on green CI (web + site + Cloudflare). If instead I've cleared the two human gates, flip the §9 DoD to DONE and run the engine `DOC_STATUS.md` §2 archival checklist.

...

That prompt will drop the next session straight into the one remaining eng slice (own-model) or the archival path, with full ramp-up context.