

claude-windows / c6fbcfbb-d724-4901-b146-68f198409ed5

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5.jsonl`  
- SHA-256: `6148c9760aa811474e964be78e5df6e989cb48217572f225927e70f1f3bda2fd`  
- Source modified: `2026-06-29T17:02:31+00:00`  
- Imported at: `2026-07-05T16:48:20+00:00`  
- project: `C--Users-avidu-Projects-khelsutra`  
- session_id: `c6fbcfbb-d724-4901-b146-68f198409ed5`
```

Transcript

1. user (2026-06-22T03:46:04.675Z)

In the khelsutra repo, the marketing site's home page (`site/public/index.html`) has a hero "demo mockup" card whose strings are hardcoded English and NOT wired through the i18n shim (`data-i18n`), so they render English in EVERY non-English locale (kn/hi/es/da/id) even though the rest of the site is localized.

The unwired strings are around lines ~274?282 of `site/public/index.html`:

```
- `- `- `- `- also check the `

### 


```

Task: wire these through the shim like the rest of the page ? add `site.hero.demo.\*` (or similar) keys to `/locales/en/common.json`, add `data-i18n`/`data-i18n-html` attributes (use `data-i18n-html` where there's inline `**`), then translate into kn, hi, es, da, id (AI-draft ? adversarial verify ? revise, reusing the established per-locale vocabulary: rally = kn ?????? / hi ???? / es jugada / da duel / id reli; "reel" kept). Keep brand/tokens literal.**

Process discipline (the repo has fast-churning shared checkouts + concurrent sessions): work in an ISOLATED git worktree branched from `origin/master` (`git fetch origin && git worktree add -b <branch> <path> origin/master`); stage explicit paths only; re-verify `git log origin/master..HEAD` lists only your commits before opening the PR. Run `npm run copy:locales` (site), and the full site (`node --test`) + web (`vitest run`, typecheck, coverage, build) suites green. The byte-for-byte HTML?en drift guard (`site/src/assets.test.js`) and the tag-multiset integrity guard (`site/src/i18n.shim.test.js`) will validate your wiring. Extend the assets/shim tests to cover the new keys. Translations stay native-review-pending (pre-launch gate). Reference the closed PRs #86 (own-model kn/hi) and #87 (es/da/id site) for the exact pattern.

2. assistant (2026-06-22T03:46:10.681Z)

I'll start by reading the session handoff and the relevant memory files, and pulling the latest from origin.

3. user (2026-06-22T03:46:10.794Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)  
2  
3      _Last updated: 2026-06-22, after A2 (#82) + header pass (#83) + closeout (#84) + own-  
model kn/hi (#86) + site es/da/id (#87) merged._  
4  
5      ## You are here ? chapter effectively COMPLETE (pending human gates)  
6      $7 of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo  
B7** (deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-friendly:
```

```

7      - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: **en/kn/hi +
es/da/id** ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy (kn/hi via
A3, **es/da/id via #87**); Noto bundled for kn/hi), A6 plain-language access form, A7 camera-
placement diagram, **A2 WhatsApp share** (#82), the **UI/UX header pass** (#83: compact ``, zero overflow), own-model body (#86), and the **es/da/id site expansion** (#87): the
full `site.*` namespace (115 keys) translated ? site now matches the SPA's 6 (dropdown has 6
options; `SUPPORTED`/`SITE_LOCALES`=6).
8      - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77**; web
coverage floor added in **#80**.
9      - Sister repo **rally-annotator is also localized (kn/hi/es/da/id/te)** ? the journey
annotator ? site ? Studio is consistent in the user's language.
10     - **No engineering gap remains** before the two human gates. (own-model #86 + es/da/id
site #87 both closed.)
11
12     ## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)
13     1. **Native-speaker review** of the AI-drafted catalogs (kn/hi + now **es/da/id** site,
all AI-drafted) ? the standing guardrail before a wide public launch.
14     2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
Proxy screencasts in `C:/Users/avidu/Projects/khelsutra-screencast/`: `khelsutra-
site-i18n-desktop.mp4` (site home+capture, kn) + `khelsutra-i18n-screencast.mp4` (SPA, kn-IN) +
**`khelsutra-ownmodel-i18n-desktop.webm`** (#86, own-model en?kn?hi; stills
`ownmodel-{kn,hi}-{hero,full}.png`).
15
16     ## Open engineering follow-ups (small)
17     - ~~own-model body content English on kn/hi~~ ? **DONE (#86).** ~~es/da/id site only en-
seed~~ ? **DONE (#87).**
18     - **Hardcoded hero-mockup chips** in `site/public/index.html` (`See it in action`,
`Auto-index rallies`, `Dead time removed`, `Download your reel` ? lines ~274?282) are **not
`data-i18n-wired`**, so they render English in **every** non-en locale incl. kn/hi. Pre-
existing; a separate "wire the hero mockup" slice (affects all 6 langs) if 100% coverage is
wanted.
19     - **Access form `site.join`** ? still English in ALL non-en locales (A6 deferred); the
largest remaining untranslated marketing surface. Same A3-style slice; would need all 6 langs to
keep parity.
20     - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
21     - Minor: `site.*` adds ~27KB to the SPA bundle (could split to a site-only catalog);
ratchet web coverage thresholds as `App.tsx` gains tests.
22
23     ## Ramp-up kit
24     - `docs/FRIENDLY_AND_MULTILINGUAL.md` ? §7 tracker (source of truth, all ? except B7),
§6.5 N1?N9, §9 DoD (boxes flipped; 2 human gates open), changelog.
25     - `/locales/{en,kn,hi,es,da,id}/common.json` ? shared catalog: SPA console keys +
`site.*` (nav/hero/record/capture/join/ownModel/reveal).
26     - `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, compact ``
switcher, `window.KhelSutra.t` bridge, negotiation), `site/server.js`, `site/scripts/copy-
locales.mjs`, `site/src/{i18n.shim,locales-drift,assets,server}.test.js`.
27     - Screencast/Playwright tooling + before/after eval shots:
`C:/Users/avidu/Projects/khelsutra-screencast/` (`site-screencast.mjs`, `deep-test.mjs`, `eval-
shots.mjs`).
28     - [[catalog-home-and-i18n-layout]], [[shared-checkout-concurrency]].
29
30     ## Key decisions (don't relitigate)
31     - D-CATALOG-HOME: catalogs at repo-root `/locales`; SPA imports; site mirrors via
`copy:locales` + drift guard.
32     - Negotiation order (both surfaces): persisted (`khelsutra.lang`) ? `?lang=` ?
navigator/Accept-Language ? en; missing key ? en, never a raw key.
33     - Switcher = compact `` in the header (kept there for discoverability/signal;
auto-negotiation covers kn-phones). Rich `` markup localizes via `data-i18n-html` (XSS-safe;
catalog-authored).
34     - Process: isolated `git worktree` per PR (shared checkout churns fast); AI-draft
translations ? adversarial verify ? native review is a pre-launch (not pre-merge) gate.
35

```

```

1      ---
2      name: catalog-home-and-i18n-layout
3      description: "i18n catalogs live at repo-root /locales (D-CATALOG-HOME); SPA imports
them, site mirrors them via a copy step"
4      metadata:
5          node_type: memory
6          type: reference
7          originSessionId: dca1ff63-3aec-42ab-897f-41970003f4e1
8      ---
9
10     After B3 (#70, 2026-06-21), the localization catalogs are the single source of truth
at repo-root `/locales/{en,kn,hi,es,da,id}/common.json` (D-CATALOG-HOME). Both surfaces
consume them:
11
12     - SPA (`web/`): web/src/i18n/index.ts imports `../../../locales/<lng>/common.json`
directly. Vite resolves the workspace root via the repo .git marker, so dev/build/vitest all
read the parent-dir JSON. web/src/i18n/hygiene.test.ts reads /locales for key-parity +
placeholder-parity (+ an es 3-form plural check). Adding a key to en means adding it to ALL
locales or these tests fail.
13     - Marketing site (`site/`, dependency-free): site/scripts/copy-locales.mjs mirrors
/locales ? site/public/locales/ (npm run copy:locales; predeploy hook). The committed
copy is what ships; site/src/locales-drift.test.js fails CI if it drifts. The shim
site/public/i18n.js (vanilla t() /data-i18n, ICU-lite via Intl.PluralRules) fetches those
at runtime; server.js does Accept-Language negotiation (cookie??lang?Accept-Language?en) and
stamps <html lang>.
14
15     Negotiation contract (both surfaces, identical): persisted (localStorage/cookie
key khelsutra.lang) ? ?lang= ? navigator/Accept-Language ? en; a missing key degrades to
en, never a raw key.
16
17     Marketing content is en-only so far (B3): the site.* namespace in the catalogs is
authored in en; non-en site.* values are en seeds pending translation (tracker A3). The
SPA console strings (app/query/grid/footer/?) ARE translated for kn/hi/es/da/id. Because the SPA
bundles the whole common.json, it also ships the (unused) site.* keys ? negligible.
18
19     Catalog files are a contention hotspot across i18n PRs ? see [[shared-checkout-
concurrency]].
20

```

5. user (2026-06-22T03:46:11.035Z)

```

1      ---
2      name: shared-checkout-concurrency
3      description: khelsutra is a shared single checkout with rapid concurrent master churn;
isolate repo-writing work in a git worktree
4      metadata:
5          node_type: memory
6          type: project
7          originSessionId: dca1ff63-3aec-42ab-897f-41970003f4e1
8      ---
9
10     The khelsutra repo is worked by multiple concurrent sessions on ONE shared working
checkout (C:/Users/avidu/Projects/khelsutra). During the 2026-06-21 B3 session, master
advanced 5+ times (#67?#68?#69?#71?#70) within ~1 hour, and a sibling A9 session had
uncommitted catalog WIP sitting in the shared working tree that carried across a git
checkout.
11
12     Why: the owner runs several parallel "slates"; the shared tree + current branch can
shift under you between two commands, and sibling WIP must never be clobbered (a past incident
had a squash-merge silently absorb sibling work).
13
14     How to apply (for any repo-writing task here):
15     - Don't work in the shared checkout when a sibling may be active. Create an isolated
worktree: git worktree add <path> -b <branch> origin/master (or check out an existing branch).
Run npm ci per package there (web/ + site/ each have their own node_modules; not shared

```

across worktrees). Clean up after merge: `git worktree remove <path> --force`.

```
16 - **Always branch from `origin/master`** and re-verify `git log origin/master..HEAD`
shows ONLY your commits before opening a PR.
17 - **Stage explicit paths**, never `git add -A`.
18 - **Expect master to move mid-task.** If your PR shows `mergeable=false` but `git merge-
base --is-ancestor origin/master HEAD` is true, GitHub's mergeability is just **stale** ?
collapse to one clean commit on top of latest `origin/master` (`git reset --soft origin/master`
+ recommit) and `git push --force-with-lease` to force a fresh recompute (this also triggers the
`test` workflow, which GitHub **skips while a PR is CONFLICTING**).
```

19
20 See [[catalog-home-and-i18n-layout]] for the i18n-specific contention (catalog files).
21

6. assistant (2026-06-22T03:46:16.417Z)

This is the "wire the hero mockup" slice flagged as an open follow-up in the handoff. Let me set up an isolated worktree branched from `origin/master`, following the concurrency discipline.

7. user (2026-06-22T03:46:20.728Z)

```
cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages) (#87)
17242a9 feat(site): localize own-model body content to kn/hi (#86)
7b04f02 deploy(kit): align with the live-verified droplet deploy (+ the gemini-default fix)
(#85)
```

8. user (2026-06-22T03:46:25.151Z)

Preparing worktree (new branch 'feat/site-hero-mockup-i18n')
branch 'feat/site-hero-mockup-i18n' set up to track 'origin/master'.
HEAD is now at cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages) (#87)
---WORKTREE LIST---

C:/Users/avidu/Projects/khelsutra	17242a9 [master]
C:/Users/avidu/Projects/khelsutra-p2c	e6b9725 [feat/p2c-setup-wizard]
C:/Users/avidu/Projects/khelsutra-wt-hero	cf59fbf [feat/site-hero-mockup-i18n]

9. assistant (2026-06-22T03:46:27.351Z)

Now let me examine the current state of the hero mockup in the worktree. Let me read the relevant section of `index.html`, the en catalog, and the test files.

10. user (2026-06-22T03:46:28.017Z)

```
240 <div class="wrap nav">
241   <a class="brand" href="#top">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
242   <nav class="nav-links" aria-label="Primary">
243     <a href="#how" data-i18n="site.nav.how">How it works</a>
244     <a href="#diff" data-i18n="site.nav.why">Why it's hard</a>
245     <a href="/own-model" data-i18n="site.nav.ownModel">Own your model</a>
246     <a href="/flyer" data-i18n="site.nav.flyer">Flyer</a>
247     <a href="#roadmap" data-i18n="site.nav.roadmap">Roadmap</a>
248     <a href="#faq" data-i18n="site.nav.faq">FAQ</a>
249   </nav>
250   <div class="nav-right">
251     <label class="langsw"><span class="langsw-globe" aria-
hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
252       <option value="en" data-i18n="lang.en" lang="en">English</option>
253       <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
254       <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
255       <option value="es" data-i18n="lang.es" lang="es">Español</option>
256       <option value="da" data-i18n="lang.da" lang="da">Dansk</option>
257       <option value="id" data-i18n="lang.id" lang="id">Bahasa Indonesia</option>
```

```

258         </select></label>
259         <a class="btn btn-dark" href="#join" data-i18n="site.nav.requestAccess">Request
access</a>
260     </div>
261 </div>
262 </header>
263
264 <a id="top"></a>
265 <section class="hero" style="padding:0">
266     <div class="wrap hero-grid">
267         <div class="hero-left">
268             <span class="eyebrow" data-i18n="site.hero.eyebrow">Invite-only alpha .
Bengaluru</span>
269             <h1 data-i18n-html="site.hero.title">Every rally, indexed. <span class="hl">The
dead time, gone.</span></h1>
270             <p class="lead" data-i18n="site.hero.lead">KhelSutra finds every rally in your
session and strips out the knock-ups, walks and gaps ? so a full match becomes a clean highlight
reel you can watch and download. No editing, no scrubbing.</p>
271             <div class="hero-cta">
272                 <a class="btn btn-primary" href="#join" data-i18n="site.hero.ctaPrimary">Request
alpha access</a>
273                 <a class="btn btn-ghost" href="#how" data-i18n="site.hero.ctaHow">See how it
works</a>
274                 <a class="btn btn-ghost" href="#join">See it in action + a real reel</a>
275             </div>
276             <p class="hero-note">A phone or GoPro on a tripod is all you need. No special
hardware.</p>
277             <div class="loop">
278                 <span class="chip"><b>1.</b> Auto-index rallies</span>
279                 <span class="arrow">?</span>
280                 <span class="chip"><b>2.</b> Dead time removed</span>
281                 <span class="arrow">?</span>
282                 <span class="chip"><b>3.</b> Download your reel</span>
283             </div>
284         </div>
285         <div class="hero-visual">
286             <div class="reel-card">
287                 <div class="reel-head">
288                     <span class="dots"><i></i><i></i><i></i></span>
289                     <span class="file">match_2026.mp4 . indexed</span>
290                 </div>
291                 <div class="reel-body">
292                     <div class="lbl"><span>Rallies detected</span><span class="match">44
found</span></div>
293                     <div class="reel-track">
294                         <span class="on" style="left:2%;width:8%"></span>
295                         <span class="on" style="left:13%;width:6%"></span>
296                         <span class="on" style="left:22%;width:12%"></span>
297                         <span class="on" style="left:37%;width:7%"></span>
298                         <span class="on" style="left:47%;width:11%"></span>
299                         <span class="on" style="left:61%;width:6%"></span>
300                         <span class="on" style="left:70%;width:13%"></span>
301                         <span class="on" style="left:86%;width:9%"></span>
302                     </div>
303                     <div class="result">
304                         <span class="play" aria-hidden="true">?</span>
305                         <span class="result-tx"><b>Highlight reel . 44 rallies . 18 min</b><em>dead
time removed . ready to download</em></span>
306                         <span class="dl" aria-hidden="true">?</span>
307                     </div>
308                 </div>
309             </div>
310         </div>
311     </div>
312 </section>

```

```

313
314     <section id="how">
315         <div class="wrap">
316             <div class="sec-head">
317                 <div class="kicker">What it does today</div>
318                 <h2>A full match, turned into rallies you can search</h2>
319                 <p>Upload a whole session or match. KhelSutra does the rest ? no editing skill
needed.</p>
320             </div>
321             <div class="grid g4">
322                 <div class="card">
323                     <div class="ic" aria-hidden="true">?</div>
324                     <h3>Every rally, indexed</h3>
325                     <p>It finds each rally ? start, end and length ? and turns the whole match into
a searchable list. Long full-session videos are fine.</p>
326                 </div>
327                 <div class="card">
328                     <div class="ic" aria-hidden="true">?</div>
329                     <h3>Dead time removed</h3>
330                     <p>Knock-ups, walks, picking up the shuttle, the gaps between points ? stripped
out. What's left is only real play.</p>
331                 </div>
332                 <div class="card">
333                     <div class="ic" aria-hidden="true">?</div>
334                     <h3>Process once, reuse</h3>
335                     <p>Come back later to watch or download your reel. Re-running a video replaces
its earlier result rather than piling up copies.</p>
336                 </div>
337                 <div class="card">
338                     <div class="ic" aria-hidden="true">?</div>
339                     <h3>Stitched reel + summary</h3>
340                     <p>Your selection becomes one MP4 to download and share ? with a play-time
summary and a small ?Generated by Khelsutra.guru? mark.</p>
341                 </div>
342             </div>
343         </div>
344     </section>
345
346     <section id="record" style="background:#EFF4EC">
347         <div class="wrap">
348             <div class="sec-head">
349                 <div class="kicker" data-i18n="site.record.kicker">Record it right</div>
350                 <h2 data-i18n="site.record.title">Five minutes of setup ? reliably great
reels</h2>
351                 <p data-i18n="site.record.intro">Highlight quality starts with the recording. Set
the camera up once like this and KhelSutra has everything it needs to find the rallies.</p>
352             </div>
353
354             <div style="max-width:780px;margin:0 auto 1.6rem;display:flex;gap:.8rem;align-
items:flex-start;background:#fff;border:1px solid var(--line);border-left:4px solid
var(--green);border-radius:14px;padding:1rem 1.2rem">
355                 <span aria-hidden="true" style="color:var(--green-d);font-size:1.4rem;line-
height:1">?</span>
356                 <p style="margin:0;color:var(--tx)"><b data-i18n="site.record.goldenRuleLead">The
golden rule: one match, one court, in full frame ? and don't move the camera.</b> <span
style="color:var(--mut)" data-i18n="site.record.goldenRuleRest">A single court in frame gives
the best results today; busy multi-court footage is the hard case we're still
sharpening.</span></p>
357             </div>
358
359             <div class="grid g4">
360                 <div class="card">
361                     <div class="ic" aria-hidden="true">?</div>
362                     <h3 data-i18n="site.record.place.title">Place the camera</h3>
363                     <p data-i18n="site.record.place.body">Behind <b>one baseline</b>, elevated

```

(a high tripod or a balcony), tilted down ~30° ? the whole court in frame, players never cropped.</p>

```
364         </div>
365         <div class="card">
366             <div class="ic" aria-hidden="true">?</div>
367             <h3 data-i18n="site.record.settings.title">Settings</h3>
368             <p data-i18n-html="site.record.settings.body"><b>1080p</b>, landscape, <b>30
fps</b> for badminton (60 fps for table tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps
find rallies.</p>
369         </div>
```

11. assistant (2026-06-22T03:46:52.235Z)

I can see the hero section clearly. Line 329's "Dead time removed" is actually in the separate `#how` section (314-344), which appears entirely unwired. Let me map the full file to understand the complete scope of what's wired vs. hardcoded before deciding boundaries.

12. user (2026-06-22T03:46:53.180Z)

```
369         </div>
370         <div class="card">
371             <div class="ic" aria-hidden="true">?</div>
372             <h3 data-i18n="site.record.still.title">Keep it still</h3>
373             <p data-i18n-html="site.record.still.body">Fixed tripod or mount. <b>No panning,
no zooming</b> during play ? a steady, full-court view is what the tool is tuned for.</p>
374         </div>
375         <div class="card">
376             <div class="ic" aria-hidden="true">?</div>
377             <h3 data-i18n="site.record.upload.title">Record & upload</h3>
378             <p data-i18n-html="site.record.upload.body">Even lighting, then record the
<b>whole session</b> and upload it as-is ? KhelSutra finds the rallies and does the cutting.</p>
379         </div>
380     </div>
381
382     <div style="text-align:center;margin-top:1.6rem">
383         <a class="btn btn-dark" href="/capture" data-i18n="site.record.checklistCta">Full
1-page capture checklist ?</a>
384     </div>
385 </div>
386 </section>
387
388 <section id="diff" style="padding-top:0">
389     <div class="wrap">
390         <div class="split">
391             <div>
392                 <div class="kicker" style="font-size:.82rem;font-weight:700;letter-
spacing:.08em;text-transform:uppercase;color:var(--green-d)">The hard problem we crack</div>
393                 <h2 style="margin-top:.5rem">Most academy halls run several courts at once</h2>
394                 <p style="color:var(--mut);font-size:1.05rem">Academies already record a lot of
video ? and then almost never watch it, because cutting it into useful clips by hand is tedious.
The good rallies stay buried.</p>
395                 <p style="color:var(--mut);font-size:1.05rem">A single recording of a busy,
multi-court hall is exactly where ordinary video tools choke. Pulling the <b
style="color:var(--tx)">real</b> rallies out of busy, multi-court footage is the hard problem
KhelSutra is built for. It already works very well on clean, single-court recordings ? and the
multi-court case is what we're sharpening now.</p>
396             </div>
397             <div class="panel">
398                 <span class="pill">Capture tip</span>
399                 <h2 style="font-size:1.4rem">Best results: a steady, full-court shot</h2>
400                 <p>Camera behind the court, slightly elevated, whole court in frame. Keep it
still ? a fixed tripod beats handheld every time. Shoot landscape, record the whole session,
upload as-is. KhelSutra does the cutting.</p>
401             </div>
402         </div>
```

```

403     </div>
404 </section>
405
406 <section id="sharper" style="background:#EFF4EC">
407     <div class="wrap">
408         <div class="sec-head">
409             <div class="kicker">What makes it different</div>
410             <h2>It gets sharper from real academy footage</h2>
411             <p>The footage real academies contribute ? especially the busy multi-court halls ?
is what makes KhelSutra better over time. Early users aren't just customers; they're co-
builders.</p>
412         </div>
413         <div class="grid g3">
414             <div class="card">
415                 <div class="ic" aria-hidden="true">?</div>
416                 <h3>Improves with the library</h3>
417                 <p>When you choose to share footage and coaches confirm what it found, that
growing labelled library is what sharpens future versions ? rather than staying frozen.</p>
418             </div>
419             <div class="card">
420                 <div class="ic" aria-hidden="true">?</div>
421                 <h3>Your data stays yours</h3>
422                 <p>We never use your video to improve the tool without your clear, explicit opt-
in. We never publish your footage. You decide what, if anything, you share.</p>
423             </div>
424             <div class="card">
425                 <div class="ic" aria-hidden="true">?</div>
426                 <h3>Minors are protected</h3>
427                 <p>Footage involving minors is never used to improve the tool and is never
published ? full stop.</p>
428             </div>
429         </div>
430         <div class="honest">
431             <b>Read this honestly:</b>
432             <p>Today the tool gives you rally detection, reels, and summaries. It does not
retrain itself as you use it, and there's no per-person tracking. "Gets sharper over time" is
the model we're building toward, powered by contributed footage ? not a switch that's already
on.</p>
433         </div>
434     </div>
435 </section>
436
437 <section id="ask">
438     <div class="wrap">
439         <div class="sec-head">
440             <div class="kicker">Coming next to the alpha</div>
441             <h2>Soon: ask for the exact reel you want</h2>
442             <p>Your match is already a clean index of rallies ? so the natural next step is to
let you build any reel just by describing it, in plain English. This is rolling out to alpha
users.</p>
443         </div>
444         <div class="grid g3 ask-grid">
445             <div class="card askc">
446                 <div class="q"><i>?</i>Every rally over 10 seconds?</div>
447                 <div class="a"><i>?</i> 6 rallies · a 1:32 reel of the long, end-to-end
battles</div>
448             </div>
449             <div class="card askc">
450                 <div class="q"><i>?</i>Just the third game, longest first?</div>
451                 <div class="a"><i>?</i> 12 rallies, reordered by length ? that game only</div>
452             </div>
453             <div class="card askc">
454                 <div class="q"><i>?</i>The 8 best rallies from today?</div>
455                 <div class="a"><i>?</i> an 8-clip highlight from your latest session</div>
456             </div>

```



```

457         </div>
458         <p class="ask-note"><b style="color:var(--tx)">Rolling out now.</b> Targeted asks ?
by rally length, count, order, or which game ? come first; shot-type and player queries follow
as the deeper analysis arrives.</p>
459     </div>
460 </section>
461
462 <section id="roadmap">
463     <div class="wrap">
464         <div class="sec-head">
465             <div class="kicker">Where it's going</div>
466             <h2>Toward an AI assistant coach</h2>
467             <p>Fed by the growing video library, KhelSutra is heading from "finds rallies" to
a genuine training companion. This is the direction ? not today's buttons.</p>
468         </div>
469         <div class="road">
470             <div class="step"><div class="n">?</div><h3>Shot detection</h3><p>Smashes, drops,
net shots, serves and clears within each rally.</p></div>
471             <div class="step"><div class="n">?</div><h3>Deeper analysis</h3><p>Per-rally and
per-match patterns ? what's working and what isn't.</p></div>
472             <div class="step"><div class="n">?</div><h3>Per-match history</h3><p>Track
progress over weeks and months, not just one clip.</p></div>
473             <div class="step"><div class="n">?</div><h3>Assistant coach</h3><p>Surfaces what
to work on next ? supports the real coach, never replaces.</p></div>
474             <div class="step"><div class="n">?</div><h3>More sports & languages</h3><p>Table
tennis next; Kannada and Hindi alongside English.</p></div>
475         </div>
476     </div>
477 </section>
478
479 <section id="not" style="padding-top:0">
480     <div class="wrap">
481         <div class="sec-head">
482             <div class="kicker">So expectations stay honest</div>
483             <h2>What KhelSutra is not</h2>
484         </div>
485         <ul class="nots">
486             <li><i aria-hidden="true">?</i><span>An early, invite-only trial ? useful, but
still improving. You'll hit rough edges.</span></li>
487             <li><i aria-hidden="true">?</i><span>Not a line-calling, scoring, or umpiring
system.</span></li>
488             <li><i aria-hidden="true">?</i><span>Not player tracking or
identification.</span></li>
489             <li><i aria-hidden="true">?</i><span>Not a replacement for a coach ? a tool that
saves time and adds insight.</span></li>
490             <li><i aria-hidden="true">?</i><span>Shot detection and deeper analytics are on
the roadmap, not available today.</span></li>
491             <li><i aria-hidden="true">?</i><span>Pricing isn't set ? today's invited use is
about getting it right.</span></li>
492         </ul>
493     </div>
494 </section>
495
496 <section id="faq" style="background:#EFF4EC">
497     <div class="wrap">
498         <div class="sec-head">
499             <div class="kicker">Quick answers</div>
500             <h2>Common questions</h2>
501         </div>
502         <div style="margin-top:1.6rem">
503             <details><summary>How accurate is it?</summary><p>Very good on a clean, single-
court recording. A busy multi-court hall is harder ? and is exactly what we're improving. The
best answer is to show you a sample reel of your own court rather than quote a
number.</p></details>
504             <details><summary>Can I choose which rallies go in the reel?</summary><p>Today

```

your reel includes the rallies KhelSutra found, with the dead time removed. Choosing by length, count, order or which game ? just by asking in plain English ? is rolling out to alpha users next; shot-type and player queries follow as the deeper analysis arrives.</p></details>

505 <details><summary>Do I need a special camera or hardware?</summary><p>No. A phone or GoPro on a tripod, behind the court, whole court in frame. We provide a one-page capture checklist at setup.</p></details>

506 <details><summary>Is my video private? What happens to it?</summary><p>We treat your footage as private: we never publish it, and we never use it to improve the tool without your explicit opt-in. These are large videos that need real processing, so your video is handled securely on our infrastructure to make your reel. Footage involving minors is never used and never published.</p></details>

507 <details><summary>Does it work for doubles and tournaments?</summary><p>It finds rallies in doubles too. Tournament footage varies ? a clean, fixed, full-court recording works well; crowded multi-court tournament halls are the hard case we're specifically working on.</p></details>

508 <details><summary>Which sports?</summary><p>Badminton today. Table tennis and other racket sports are on the roadmap.</p></details>

509 <details><summary>How do I join?</summary><p>It's an invite-only private trial. Just request access using the form ? it takes a minute, you'll see a real sample reel right away, and we'll be in touch about recording your own court.</p></details>

510 </div>

511 </div>

512 </section>

513

514 <section id="join" style="padding-bottom:90px">

515 <div class="wrap">

516 <div class="sec-head" style="text-align:center;max-width:none">

517 <div class="kicker">Request access</div>

518 <h2>Get into the KhelSutra alpha</h2>

519 <p>Invite-only. Tell us a little about your setup ? it helps us get you the best results, and shapes what we build next.</p>

520 <p style="font-weight:600;color:var(--green-d);margin-top:.6rem">? Sign up to watch the tool in action ? and a 30-second sample reel it made ? the moment you're in.</p>

521 </div>

522

523 <form id="af" class="af" novalidate>

524 <div class="row">

525 <label>I'm a?</label>

526 <div class="seg">

527 <label><input type="radio" name="segment" value="academy" required>Coaching academy / club</label>

528 <label><input type="radio" name="segment" value="individual">Individual player</label>

13. assistant (2026-06-22T03:47:37.752Z)

Let me look at the existing `site.\*` catalog structure and the guard tests before deciding scope, so my plan is grounded.

14. user (2026-06-22T03:47:40.336Z)

```
=== en common.json: site.hero + site.nav region ===
{
  "title": "Every rally, indexed. <span class=\"hl\">The dead time, gone.</span>",
  "eyebrow": "Invite-only alpha · Bengaluru",
  "lead": "KhelSutra finds every rally in your session and strips out the knock-ups, walks and gaps ? so a full match becomes a clean highlight reel you can watch and download. No editing, no scrubbing.",
  "ctaPrimary": "Request alpha access",
  "ctaHow": "See how it works"
}
--- nav ---
{
  "how": "How it works",
```

```

    "why": "Why it's hard",
    "ownModel": "Own your model",
    "flyer": "Flyer",
    "roadmap": "Roadmap",
    "faq": "FAQ",
    "requestAccess": "Request access"
}

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

15. user (2026-06-22T03:47:41.185Z)

```

1      // Unit tests for the marketing-site i18n shim (public/i18n.js, tracker B3). Proves the
shim mirrors
2      // the SPA's react-i18next contract: same negotiation order, ICU-lite
interpolation/plurals, en
3      // fallback, and a data-i18n walker that NEVER leaves a raw key. Tested against the REAL
shared
4      // catalogs (/locales) ? so this also proves both surfaces consume one source of truth.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync } from "node:fs";
8      import { join } from "node:path";
9      import { JSDOM } from "jsdom";
10     import { negotiate, interpolate, translate, applyDom, SUPPORTED, DEFAULT } from
"../public/i18n.js";
11
12     const LOCALES = join(import.meta.dirname, "..", "..", "locales");
13     const load = (loc) => JSON.parse(readFileSync(join(LOCALES, loc, "common.json"),
"utf8"));
14     const catalogs = { en: load("en"), kn: load("kn"), hi: load("hi"), es: load("es"), da:
load("da"), id: load("id") };
15
16     test("negotiation order matches the SPA: persisted -> ?lang -> navigator -> en", () => {
17         assert.equal(negotiate({ stored: "kn", query: "hi", nav: ["en-US"] }), "kn",
"persisted pref wins");
18         assert.equal(negotiate({ query: "hi", nav: ["en-US"] }), "hi", "?lang beats
navigator");
19         assert.equal(negotiate({ nav: ["kn-IN", "en-IN"] }), "kn", "navigator picks the first
supported");
20         assert.equal(negotiate({}), "en", "nothing -> en");
21     });
22
23     test("region subtags normalize and unsupported degrades to en (never a locale we can't
serve)", () => {
24         assert.equal(negotiate({ nav: ["hi-IN"] }), "hi", "hi-IN -> hi");
25         assert.equal(negotiate({ nav: ["ta-IN"] }), "en", "Tamil (unsupported) -> en");
26         assert.equal(negotiate({ stored: "es" }), "es", "es is now a supported site locale
(parity with the SPA's 6)");
27         assert.equal(negotiate({ nav: ["da-DK"] }), "da", "da-DK -> da");
28         assert.equal(negotiate({ nav: ["id-ID"] }), "id", "id-ID -> id");
29         assert.deepEqual([...SUPPORTED], ["en", "kn", "hi", "es", "da", "id"]);
30         assert.equal(DEFAULT, "en");
31     });
32
33     test("ICU-lite interpolation: {name} substitution", () => {
34         assert.equal(interpolate("over {n}s", { n: 10 }), "over 10s");
35         assert.equal(interpolate("Couldn't load: {error}", { error: "boom" }), "Couldn't load:
boom");
36     });
37
38     test("ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number", () => {
39         const en = catalogs.en.selection.count; // "{count, plural, one {# rally selected}
other {# rallies selected}}"
40         assert.equal(interpolate(en, { count: 1 }, "en"), "1 rally selected");
41         assert.equal(interpolate(en, { count: 5 }, "en"), "5 rallies selected");

```

```

42      // Kannada is also one/other ? the shim picks the arm from the catalog, no hard-coded
rules.
43      assert.equal(translate(catalogs, "kn", "selection.count", { count: 1 } ),
catalogs.kn.selection.count.match(/one \{([^\}]*)\}/)[1].replace("#", "1"));
44    });
45
46    test("translate: active locale, then en fallback, then undefined (caller keeps the DOM
default)", () => {
47      assert.equal(translate(catalogs, "kn", "app.title"), catalogs.kn.app.title); // real
Kannada
48      assert.equal(translate(catalogs, "en", "lang.kn"), "????"); // shared catalog autonomy
49      // A3: site.* marketing is now translated for kn (no longer the en seed).
50      assert.equal(translate(catalogs, "kn", "site.capture.title"),
catalogs.kn.site.capture.title);
51      assert.notEqual(catalogs.kn.site.capture.title, catalogs.en.site.capture.title, "kn
capture.title must be translated, not an en seed");
52      // en fallback when a key is absent from the active locale (synthetic ? real catalogs
have full parity).
53      assert.equal(translate({ en: { only: { en: "fallback" } }, kn: {} }, "kn", "only.en"),
"fallback");
54      assert.equal(translate(catalogs, "kn", "does.not.exist"), undefined, "missing
everywhere -> undefined");
55    });
56
57    test("applyDom walks data-i18n, sets attrs, reflects the active locale in the <select>,
never shows a raw key", () => {
58      const { document } = new JSDOM(`<!doctype html><body>
59        <span id="auto" data-i18n="lang.kn">PLACEHOLDER</span>
60        <span id="keep" data-i18n="does.not.exist">KEEP ME</span>
61        <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
62        <select id="sw" data-langsw aria-label="Language">
63          <option value="en" data-i18n="lang.en">English</option>
64          <option value="kn" data-i18n="lang.kn">????</option>
65          <option value="hi" data-i18n="lang.hi">????</option>
66        </select>
67      </body>`).window;
68
69      applyDom(document, catalogs, "kn");
70
71      assert.equal(document.getElementById("auto").textContent, "????", "data-i18n sets
textContent from the shared catalog");
72      assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key
leaves the HTML default ? never a raw key");
73      assert.equal(document.getElementById("ph").getAttribute("placeholder"),
catalogs.kn.site.capture.title, "data-i18n-attr targets an attribute (kn value for the kn
locale)");
74      // The compact <select> reflects the active locale (its displayed text follows the
selected option).
75      const sw = document.getElementById("sw");
76      assert.equal(sw.value, "kn", "the switcher <select> must reflect the active locale");
77      assert.equal(sw.selectedOptions[0].textContent, "????", "the selected option shows
the localized autonomy");
78    });
79
80    test("data-i18n-html sets innerHTML and preserves inline <b> markup (A3 recording-
education)", () => {
81      const { document } = new JSDOM(`<!doctype html><body>
82        <p id="rich" data-i18n-html="site.record.place.body">Behind <b>one baseline</b>
?</p>
83        <li id="kept" data-i18n-html="does.not.exist">KEEP <b>this</b></li>
84      </body>`).window;
85
86      // en: innerHTML equals the catalog value verbatim (with its <b> tags), not escaped
text.
87      applyDom(document, catalogs, "en");

```

```

88     assert.equal(document.getElementById("rich").innerHTML,
catalogs.en.site.record.place.body);
89     assert.ok(document.getElementById("rich").querySelector("b"), "the <b> must be a real
element, not escaped text");
90     assert.equal(document.getElementById("kept").innerHTML, "KEEP <b>this</b>", "a missing
html key leaves the HTML default");
91
92     // kn: swaps to the Kannada value, still carrying its <b> tags.
93     applyDom(document, catalogs, "kn");
94     assert.equal(document.getElementById("rich").innerHTML,
catalogs.kn.site.record.place.body);
95     assert.match(document.getElementById("rich").innerHTML, /<b>.*<\b>/s, "kn rich value
keeps <b> markup");
96     });
97
98     test("data-i18n-html falls back through en (markup intact) when the active locale lacks
the key", () => {
99         // The middle rung: active locale missing a rich key -> en value (with <b>), not just
the DOM default.
100         const { document } = new JSDOM(`<!doctype html><body><p id="r"
data-i18n-html="site.r.b">default</p></body>`).window;
101         applyDom(document, { en: { site: { r: { b: "X <b>Y</b> Z" } } }, kn: { } }, "kn");
102         assert.equal(document.getElementById("r").innerHTML, "X <b>Y</b> Z", "html form must
fall back to en, not the DOM default");
103         assert.ok(document.getElementById("r").querySelector("b"), "the <b> survives the en-
fallback path");
104     });
105
106     test("A3: the kn/hi catalogs carry REAL recording-education translations (not English
seeds)", () => {
107         // Kannada script range U+0C80?U+0CFF; Devanagari U+0900?U+097F. A representative
spread of the
108         // recording keys must be in-script (proves A3 actually translated, not B3's en seed).
109         const KN = /[?-\?]/, HI = /[?-\?]/;
110         for (const key of ["hero.title", "record.intro", "record.place.title",
"capture.step1.b3", "capture.consent", "capture.diagram.camera", "nav.requestAccess"]) {
111             const path = key.split(".");
112             const kn = path.reduce((o, k) => o[k], catalogs.kn.site);
113             const hi = path.reduce((o, k) => o[k], catalogs.hi.site);
114             assert.match(kn, KN, `kn site.${key} should be in Kannada script (a leftover English
seed would not match)`);
115             assert.match(hi, HI, `hi site.${key} should be in Devanagari script`);
116         }
117         // A brand/token-free key must be FULLY in-script (no stray English) ? strongest anti-
seed check.
118         assert.doesNotMatch(catalogs.kn.site.capture.consent, /[A-Za-z]/, "kn capture.consent
has no business containing Latin letters");
119         assert.doesNotMatch(catalogs.hi.site.capture.consent, /[A-Za-z]/, "hi capture.consent
has no business containing Latin letters");
120         // Brand + literal tokens are intentionally preserved across languages.
121         assert.match(catalogs.kn.site.record.intro, /KhelSutra/, "brand stays in Latin");
122         assert.match(catalogs.hi.site.record.settings.body, /1080p\+|30 fps/, "technical
tokens stay literal");
123     });
124
125     // ---- own-model body content localized (kn/hi)
-----
126     const flatOwn = (obj, p = "") => Object.entries(obj).reduce((a, [k, v]) => {
127         const key = p ? `${p}.${k}` : k;
128         if (v && typeof v === "object") Object.assign(a, flatOwn(v, key)); else a[key] = v;
return a;
129     }, {});
130
131     test("own-model: kn/hi carry REAL translations of the page body (not the en seed)", ()
=> {

```

```

132     const KN = /[?~?]/, HI = /[?~?]/;
133     // A representative spread across hero / annotate / train / setup / honesty / footer
must be in-script.
134     for (const key of ["heroLead", "sample", "annotate.body", "train.reassureBody",
"train.honestBody", "setup.joinRule", "not.title", "cta.title", "foot.mark"]) {
135         const dig = (root) => key.split(".").reduce((o, k) => o[k], root);
136         assert.match(dig(catalogs.kn.site.ownModel), KN, `kn site.ownModel.${key} should be
Kannada (an en seed would not match)`);
137         assert.match(dig(catalogs.hi.site.ownModel), HI, `hi site.ownModel.${key} should be
Devanagari`);
138     }
139     // The already-shipped CTA-link translation is PRESERVED (not reset to the en seed).
140     assert.match(catalogs.kn.site.ownModel.requestAccess, KN, "kn requestAccess must stay
translated");
141     assert.match(catalogs.hi.site.ownModel.requestAccess, HI, "hi requestAccess must stay
translated");
142     // Honest framing survives translation: the in-build/optional caveats are localized,
not dropped.
143     assert.match(catalogs.kn.site.ownModel.train.pill, KN, "kn train.pill (open pipeline
in build) should localize");
144     assert.match(catalogs.hi.site.ownModel.train.pill, HI, "hi train.pill should
localize");
145     });
146
147     test("own-model: kn/hi keep en's inline-HTML tag-set + load-bearing literal tokens (no
markup/token drift)", () => {
148         const ef = flatOwn(catalogs.en.site.ownModel);
149         // Multiset (sorted) comparison ? translation may legitimately REORDER words (and thus
tags), but must
150         // never add, drop, or alter a tag/attribute. A dropped <b>/<a href>/<code> would
break the rendered page.
151         const tagset = (s) => (String(s).match(/<[^>+>/g) || []).slice().sort().join("|");
152         for (const loc of ["kn", "hi"]) {
153             const lf = flatOwn(catalogs[loc].site.ownModel);
154             for (const key of Object.keys(ef)) {
155                 if (key === "requestAccess") continue; // preserved prior translation, checked
above
156                 assert.equal(tagset(lf[key]), tagset(ef[key]), `${loc} site.ownModel.${key}:
inline HTML tag-set drifted from en`);
157             }
158             // Brand / tool / licence / code tokens stay verbatim across languages (the page is
a dev/power-user surface).
159             const o = catalogs[loc].site.ownModel;
160             assert.match(o.annotate.body, /rally-annotator/, `${loc} annotate.body lost the
rally-annotator token`);
161             assert.match(o.annotate.body, /\bVLC\b/, `${loc} annotate.body lost VLC`);
162             assert.match(o.setup.install, /rally_annotator\.lua/, `${loc} setup.install lost the
lua filename`);
163             assert.match(o.setup.reasons, /service_fault/, `${loc} setup.reasons lost the
ending_reason enum`);
164             assert.match(o.train.honestBody, /GPU/, `${loc} train.honestBody lost GPU`);
165             assert.match(o.train.honestBody, /LLM/, `${loc} train.honestBody lost LLM`);
166             assert.match(o.train.moat.cleanBody, /MIT\/Apache\/BSD/, `${loc} cleanBody lost the
licence list`);
167             assert.match(o.foot.mark, /Generated by Khelsutra\.guru/, `${loc} foot.mark lost the
verbatim watermark text`);
168         }
169     });
170
171     // ---- es/da/id full marketing-site localization (site parity with the SPA's 6
languages) -----
172     test("site: es/da/id carry REAL translations of the marketing copy; the access form
(site.join.*) stays English", () => {
173         const enSite = flatOwn(catalogs.en.site);
174         const knSite = flatOwn(catalogs.kn.site);

```

```

175 // The target set = the site.* keys kn translated (so es/da/id reach the same coverage
parity).
176 const target = Object.keys(enSite).filter((k) => knSite[k] !== enSite[k]);
177 assert.ok(target.length >= 100, `expected the full marketing set as the target (got
${target.length})`);
178 for (const loc of ["es", "da", "id"]) {
179   const locSite = flatOwn(catalogs[loc].site);
180   // The vast majority of the marketing copy must differ from the en seed (a handful
of cognates like
181   // "Flyer"/"FAQ"/"Roadmap"/"Net" legitimately stay English in da/id ? allow a small
margin).
182   const stillEn = target.filter((k) => locSite[k] === enSite[k]);
183   assert.ok(stillEn.length <= 8, `${loc}: ${stillEn.length} marketing keys still equal
the en seed (untranslated?): ${stillEn.slice(0, 10).join(", ")}`);
184   // Concrete prose anchors across the surfaces MUST be translated (never an en seed).
185   for (const key of ["hero.lead", "record.intro", "capture.consent",
"ownModel.heroLead", "ownModel.train.honestBody"]) {
186     assert.notEqual(locSite[key], enSite[key], `${loc} site.${key} must be translated,
not an en seed`);
187   }
188   // The Request-Access form (site.join.*) is intentionally English in EVERY locale
(A6 deferred) ? parity with kn/hi.
189   assert.equal(locSite["join.gpuLabel"], enSite["join.gpuLabel"], `${loc} site.join.*
must stay English (A6 deferred, same as kn/hi)`);
190 }
191 });
192
193 test("site: es/da/id keep en's inline-HTML tag-set + load-bearing literal tokens (no
markup/token drift)", () => {
194   const enSite = flatOwn(catalogs.en.site);
195   const knSite = flatOwn(catalogs.kn.site);
196   const target = Object.keys(enSite).filter((k) => knSite[k] !== enSite[k]);
197   const tagset = (s) => (String(s).match(/<[^>+>/g) || []).slice().sort().join("|");
198   for (const loc of ["es", "da", "id"]) {
199     const locSite = flatOwn(catalogs[loc].site);
200     for (const key of target) {
201       assert.equal(tagset(locSite[key]), tagset(enSite[key]), `${loc} site.${key}:
inline HTML tag-set drifted from en`);
202     }
203     // Brand / technical tokens survive translation verbatim across the site.
204     assert.match(locSite["hero.lead"], /KhelSutra/, `${loc} hero.lead lost the brand`);
205     assert.match(locSite["record.settings.body"], /1080p\+|30 fps/, `${loc}
record.settings.body lost the technical tokens`);
206     assert.match(locSite["ownModel.annotate.body"], /rally-annotator/, `${loc} own-model
annotate.body lost rally-annotator`);
207     assert.match(locSite["ownModel.setup.reasons"], /service_fault/, `${loc} own-model
setup.reasons lost the ending_reason enum`);
208     assert.match(locSite["reveal.shareText"], /khelsutra\.guru/, `${loc}
reveal.shareText lost the URL`);
209   }
210 });
211

```

16. user (2026-06-22T03:47:41.451Z)

```

1 // Static-site integrity ? the landing page + capture checklist + OG image ARE the
public
2 // product. server.test.js proves the VM host *serves* "/", "/capture", "/og.png"; this
3 // guards the CONTENT contract so a broken edit (deleted asset, broken form wiring, dead
4 // capture link, missing/!absolute OG image) fails CI instead of shipping to the live
site.
5 import { test } from "node:test";
6 import assert from "node:assert/strict";
7 import { readFileSync, statSync } from "node:fs";
8 import { join } from "node:path";

```

```

9      import { JSDOM } from "jsdom";
10
11      const PUBLIC = join(import.meta.dirname, "..", "public");
12      const read = (f) => readFileSync(join(PUBLIC, f), "utf8");
13      const size = (f) => statSync(join(PUBLIC, f)).size;
14      const enCatalog = JSON.parse(readFileSync(join(import.meta.dirname, "..", "..",
"locales", "en", "common.json"), "utf8"));
15
16      test("core public assets exist and are non-empty", () => {
17          for (const f of ["index.html", "capture.html", "og.png"]) {
18              assert.ok(size(f) > 0, `public/${f} is missing or empty`);
19          }
20      });
21
22      test("landing page wires the Request-Access form to the API", () => {
23          const html = read("index.html");
24          assert.match(html, /id="af"/, "the #af form is gone");
25          assert.match(html, /\api\/request-access/, "form no longer posts to /api/request-
access");
26          assert.match(html, /name="company"[\^>]*tabindex="-1"/, "honeypot field removed (bots
will get through)");
27          for (const field of ["segment", "has_gpu", "storage"]) {
28              assert.match(html, new RegExp(`name="${field}"`), `form lost the '${field}' field (a
demand signal)`);
29          }
30      });
31
32      test("submitting the form shows an obvious in-flight state (no silent freeze)", () => {
33          const html = read("index.html");
34          assert.match(html, /Sending?/, "submit should swap to a 'Sending?' state while the
request is in flight");
35          assert.match(html, /aria-busy/, "submit should set aria-busy for assistive tech during
the request");
36          assert.match(html, /class="spin"/, "the in-flight spinner is gone");
37          assert.match(html, /\spin\{/, "the spinner style is gone");
38          // the button must be RE-ENABLED on failure so the user isn't stuck on a frozen
'Sending?'
39          assert.match(html, /btn\.disabled\s*=\s*false/, "submit button isn't restored on the
failure path");
40      });
41
42      test("OG + canonical meta point at the live https origin", () => {
43          const html = read("index.html");
44          assert.match(html,
/property="og:image"\s+content="https:\/\/khelsutra.guru\/og.png"/, "og:image must be the
absolute live URL");
45          assert.match(html, /property="og:url"\s+content="https:\/\/khelsutra.guru"/, "og:url
drift");
46      });
47
48      test("the sample reel is GATED behind sign-up + starts at a RANDOM point (not shown
openly)", () => {
49          const html = read("index.html");
50          assert.match(html, /ajTCZ7pJW_o/, "the sample-reel video id is gone");
51          assert.match(html, /youtube-nocookie.com/, "reel should use the privacy nocookie
host");
52          assert.match(html, /id="reel-reveal"/, "the on-signup reveal host is gone");
53          assert.match(html, /see it in action/i, "the 'see it in action' sign-up teaser is
gone");
54          assert.match(html, /reel-count/, "the auto-close countdown is gone");
55          assert.match(html, /REEL_SECS = 30/, "the reel preview should be ~30s");
56          assert.match(html, /getDuration\(\)/, "random start should derive from the real video
duration");
57          assert.match(html, /Math\.random\(\)/, "the start point should be randomized");
58          assert.match(html, /seekTo\(/, "the player should seek to the random start");

```



```

59      // Must NOT be an openly-rendered public section ? it only appears after a successful
submit.
60      assert.doesNotMatch(html, /<section id="reel"/, "the reel must be sign-up-gated, not
an open public section");
61      assert.doesNotMatch(html, /id="reel-play"/, "the open click-to-play facade should be
removed");
62      });
63
64      test("the TOOL screencast is self-hosted, footage-free, and revealed only after sign-
up", () => {
65          const html = read("index.html");
66          assert.match(html, /\video\tool-cuj\.mp4/, "the tool-operation screencast reference
is gone");
67          assert.match(html, /function revealAfterSignup/, "the post-signup reveal function is
gone");
68          assert.match(html, /revealAfterSignup\(\)/, "the reveal must be wired to a successful
submit");
69          // GATED: the only reference to the tool screencast lives inside the reveal function
(injected on
70          // signup), not as an open autoplay element rendered for every visitor.
71          assert.ok(
72              html.indexOf("/video/tool-cuj.mp4") > html.indexOf("function revealAfterSignup"),
73              "the tool screencast must be inside the post-signup reveal, not shown openly",
74          );
75          // the self-hosted clip exists and is non-trivial (a real recording, not an empty
placeholder)
76          assert.ok(size("video/tool-cuj.mp4") > 50_000, "tool-cuj.mp4 is missing or too small
to be the real screencast");
77      });
78
79      test("the post-signup reveal keeps its watchability affordances (manual close + play-
gated auto-close)", () => {
80          // Content contract only ? the BEHAVIOUR (close works, auto-close holds while the reel
plays) is
81          // proven against the real page in ux.dom.test.js, so we don't pin brittle
implementation strings.
82          const html = read("index.html");
83          assert.match(html, /id="reel-close"/, "the manual ? close button is gone");
84          assert.match(html, /onStateChange/, "the reel's play-state must still gate the auto-
close");
85      });
86
87      test("the capture checklist is linked and is a real page", () => {
88          assert.match(read("index.html"), /href="\capture\(.html\)?"/, "footer capture-
checklist link is gone");
89          const cap = read("capture.html");
90          assert.match(cap, /<html/i, "capture.html is not HTML");
91          assert.match(cap, /capture checklist/i, "capture.html lost its checklist content");
92      });
93
94      test("the academy flyers (en/kn/hi) exist, are language-correct, and are linked from the
homepage", () => {
95          const html = read("index.html");
96          // All three are linked from the homepage footer (the owner ask: the flyers must be
findable).
97          assert.match(html, /href="\flyer"/, "homepage doesn't link the English academy
flyer");
98          assert.match(html, /href="\flyer-kn"/, "homepage doesn't link the Kannada academy
flyer");
99          assert.match(html, /href="\flyer-hi"/, "homepage doesn't link the Hindi academy
flyer");
100
101          // The three flyer pages exist, are HTML, and carry the right language + script.
102          const en = read("flyer.html");
103          assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");

```

```

104     const kn = read("flyer-kn.html");
105     assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
106     assert.match(kn, /[?-\?]/, "flyer-kn.html should contain Kannada text");
107     const hi = read("flyer-hi.html");
108     assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
109     assert.match(hi, /[?-\?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
110 });
111
112 test("each flyer shows a screenshot of the tool rendered in that language", () => {
113     for (const [flyer, img] of [
114         ["flyer.html", "studio-en.png"],
115         ["flyer-kn.html", "studio-kn.png"],
116         ["flyer-hi.html", "studio-hi.png"]
117     ]) {
118         assert.ok(size(`img/${img}`) > 0, `public/img/${img} (the localized UI shot) is missing or empty`);
119         assert.match(read(flyer), new RegExp(`img/${img}`), `${flyer} should embed its localized UI screenshot /img/${img}`);
120     }
121 });
122
123 test("the academy flyers are also linked from the top nav and the own-model page", () => {
124     const html = read("index.html");
125     // Desktop top nav carries a Flyer entry (alongside Own your model).
126     const nav = html.match(/<nav class="nav-links"[\s\S]*?</nav>/);
127     assert.ok(nav, "the primary nav block is gone");
128     assert.match(nav[0], /href="\flier"/, "the top nav doesn't link the Flyer");
129     // own-model surfaces all three languages.
130     const om = read("own-model.html");
131     assert.match(om, /href="\flier"/, "own-model doesn't link the English flyer");
132     assert.match(om, /href="\flier-kn"/, "own-model doesn't link the Kannada flyer");
133     assert.match(om, /href="\flier-hi"/, "own-model doesn't link the Hindi flyer");
134 });
135
136 test("the landing page surfaces how to record reliably (so users can set up with confidence)", () => {
137     const html = read("index.html");
138     assert.match(html, /id="record"/, "the 'record it right' section is gone");
139     assert.match(html, /one match, one court/i, "the #1 single-court capture rule should be on the homepage");
140     // the gist must carry the load-bearing capture cues + a prominent link to the full checklist
141     for (const cue of [
142         "/1080p/",
143         "/30 fps/i",
144         "/[Aa]udio ON/",
145         "/baseline/",
146         "/[Nn]o panning/"
147     ]) {
148         assert.match(html, cue, `the recording gist is missing a key cue: ${cue}`);
149     }
150     assert.match(html, /href="\capture"[\^>]*>Full 1-page capture checklist/i, "a prominent link to the full checklist is gone");
151 });
152
153 test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
154     const html = read("index.html");
155     const m = html.match(/How do I join?<\summary><p>[\s\S]*?<\p>/);
156     assert.ok(m, "the 'How do I join?' FAQ is gone");
157     assert.match(m[1], /request access/i, "the join FAQ should send people to the request-access form");
158     assert.match(m[1], /href="#join"/, "the join FAQ should link to the #join form");
159     assert.doesNotMatch(m[1], /mailto/, "the join FAQ should NOT tell people to email (use the form)");
160 });
161
162 test("the own-model page exists, is honestly scoped, and is linked from the landing page", () => {
163     const om = read("own-model.html");
164     assert.ok(om.length > 0, "own-model.html is missing or empty");
165     for (const id of ["annotate", "train", "setup"]) {
166         assert.match(om, new RegExp(`id="${id}"`), `own-model is missing the #${id} section`);
167     }
168 });

```

```

157     }
158     assert.match(om, /github\.com\/Khelsutra\/rally-annotator/, "the GitHub link to the
annotator is gone");
159     assert.match(om, /Read this honestly/i, "the honest framing fence is gone");
160     assert.match(om, /open pipeline|in build/i, "training must be honestly scoped as in-
build, not one-click");
161     assert.match(om, /name="robots" content="noindex"/, "own-model should be noindex");
162     assert.match(read("index.html"), /href="\own-model"/, "the landing page should link
to /own-model");
163     assert.match(om, /<a href="\["^>]*>? KhelSutra home<\a>/, "own-model needs an
obvious back-to-home link (not just browser-back)");
164
165     // a ready-made default works without training (keeps non-tech users engaged); BYO-
training is optional
166     assert.match(om, /ready-made default|out of the box|don't have to train/i, "must
reassure a default works without training");
167     assert.match(om, /optional/i, "training your own should be framed as optional");
168
169     // own-model shows the annotation TOOL screenshots (no people) ? real captures, files
present
170     for (const img of ["annotate-enable.png", "annotate-tool.png"]) {
171         assert.match(om, new RegExp(`/img/${img}`), `own-model should embed /img/${img}`);
172         assert.ok(size(`/img/${img}`) > 0, `public/img/${img} is missing or empty`);
173     }
174     assert.match(om, /<img[^>]+alt="/i, "screenshots must have alt text");
175
176     // the sample REEL stays gated behind request-access ? NOT embedded/playable here, no
footage shown
177     assert.doesNotMatch(om, /<iframe/i, "the reel must NOT be embedded here ? it's gated
behind request-access");
178     assert.doesNotMatch(om, /youtube/i, "no YouTube embed on own-model; the reel is shown
only after request-access");
179     assert.doesNotMatch(om, /i\.yimg\.com/, "don't show the video thumbnail (players)
openly");
180     assert.match(om, /sample[\s\S]{0,80}request access|request access[\s\S]{0,80}sample/i,
"point users to request access for a sample output");
181     });
182
183     // ---- B3: the trilingual marketing surface (shared t()/data-i18n shim + persistent
switcher) -----
184     const I18N_PAGES = ["index.html", "capture.html", "own-model.html"];
185
186     test("every localizable page loads the shared i18n shim", () => {
187         for (const f of I18N_PAGES) {
188             assert.match(read(f), /<script[^>]+type="module"[^>]+src="\i18n\.js"/, `${f}
doesn't load the i18n shim (/i18n.js)`);
189         }
190     });
191
192     test("every localizable page has a persistent, compact 6-language <select> switcher", ()
=> {
193         for (const f of I18N_PAGES) {
194             const html = read(f);
195             // Compact dropdown (a single <select>, not always-visible pills) so the header
can't overflow.
196             assert.match(html, /class="langsw"/, `${f} is missing the language switcher`);
197             assert.match(html, /<select data-langsw[^>]*aria-label="Language"/, `${f} switcher
must be a labelled <select data-langsw>`);
198             // The site now matches the SPA's 6 languages (en/kn/hi + es/da/id).
199             for (const lang of ["en", "kn", "hi", "es", "da", "id"]) {
200                 assert.match(html, new RegExp(`<option value="\${lang}"
data-i18n="lang\\.\${lang}"`), `${f} switcher lacks the ${lang} option (wired to lang.${lang})`);
201             }
202             // The non-Latin + Latin autonyms render from the SHARED catalog (lang.*) ? proves
cross-surface consumption.

```

```

203     assert.match(html, /?????/, `${f} switcher lacks the Kannada autonym`);
204     assert.match(html, /?????/, `${f} switcher lacks the Hindi autonym`);
205     assert.match(html, /Español/, `${f} switcher lacks the Spanish autonym`);
206     assert.match(html, /Bahasa Indonesia/, `${f} switcher lacks the Indonesian
autonym`);
207   }
208   });
209
210   test("marketing content is wired for translation via data-i18n, and every key exists in
the en catalog", () => {
211     const dig = (obj, key) => key.split(".").reduce((o, k) => (o == null ? o : o[k]),
obj);
212     const used = new Set();
213     for (const f of I18N_PAGES) {
214       const html = read(f);
215       const keys = [...html.matchAll(/data-i18n="([^\"]+)/g)].map((m) => m[1]);
216       assert.ok(keys.length >= 3, `${f} should wire at least a few strings via data-i18n
(found ${keys.length})`);
217       keys.forEach((k) => used.add(k));
218     }
219     // Every data-i18n key across the site must resolve in the en source catalog (no
dangling keys -> the
220     // shim would otherwise leave the English HTML default, but a typo'd key is a silent
bug).
221     for (const key of used) {
222       assert.notEqual(dig(enCatalog, key), undefined, `data-i18n="${key}" has no entry in
the en catalog`);
223     }
224     // The shared site.* marketing namespace is present (the B3 deliverable ? en authored,
kn/hi later).
225     assert.ok(enCatalog.site && enCatalog.site.nav && enCatalog.site.hero, "the en catalog
is missing the site.* marketing namespace");
226   });
227
228   test("the en catalog value matches the HTML default for representative data-i18n keys
(no drift)", () => {
229     // The HTML carries the English default text (SEO/no-JS); the en catalog must mirror
it so an en
230     // visitor renders identically and a future kn/hi translation simply overrides the
same string.
231     assert.match(read("capture.html"), /<h1 data-i18n="site.capture.title">1-page
capture checklist<\h1>/);
232     assert.equal(enCatalog.site.capture.title, "1-page capture checklist");
233     assert.match(read("index.html"), /data-i18n="site.nav.requestAccess">Request
access</);
234     assert.equal(enCatalog.site.nav.requestAccess, "Request access");
235   });
236
237   // ---- A3: recording-education localized + Noto fonts bundled for kn/hi rendering
-----
238   test("A3: every marketing page bundles Noto Kannada + Devanagari so kn/hi render (not
tofu)", () => {
239     for (const f of ["index.html", "capture.html", "own-model.html"]) {
240       const html = read(f);
241       assert.match(html, /Noto\+Sans\+Kannada/, `${f} doesn't load Noto Sans Kannada`);
242       assert.match(html, /Noto\+Sans\+Devanagari/, `${f} doesn't load Noto Sans
Devanagari`);
243       assert.match(html, /--font:[^;]*'Noto Sans Kannada'[^;]*'Noto Sans Devanagari'/,
`${f} font stack must fall back to Noto for Indic glyphs`);
244       // Order matters: the Latin display font leads, then the Noto Indic families, BEFORE
the generic
245       // fallbacks ? else a system UI font with partial Indic glyphs could win and defeat
the bundle.
246       const stack = html.match(/--font:([^\s]*)/)[1];
247       assert.ok(stack.indexOf("Noto Sans Kannada") < stack.indexOf("system-ui"), `${f}:

```

```

Noto Kannada must precede system-ui`);
248     assert.ok(stack.indexOf("'Noto Sans Devanagari'") < stack.indexOf("system-ui"),
`$${f}: Noto Devanagari must precede system-ui`);
249     assert.ok(stack.indexOf("'Plus Jakarta Sans'") < stack.indexOf("'Noto Sans
Kannada'"), `$$$${f}: the Latin display font must lead the stack`);
250   }
251   });
252
253   test("A3: the recording-education content is wired for translation (homepage gist +
capture page)", () => {
254     const dig = (obj, key) => key.split(".").reduce((o, k) => (o == null ? o : o[k]),
obj);
255     // Both the rich (data-i18n-html, inline <b>) and plain (data-i18n) forms are used,
and EVERY key
256     // across BOTH forms resolves in the en source catalog (a typo'd key would silently
show English).
257     for (const f of ["index.html", "capture.html"]) {
258       const html = read(f);
259       const keys = [...html.matchAll(/data-i18n(?:-html)?="([^\"]+)/g)].map((m) =>
m[1]).filter((k) => k.startsWith("site."));
260       for (const key of keys) {
261         assert.notEqual(dig(enCatalog, key), undefined, `$$$${f}: data-i18n key "${key}" has
no en catalog entry`);
262       }
263     }
264     // The capture page localizes the load-bearing recording cues via the rich (html)
form.
265     const cap = read("capture.html");
266     assert.match(cap, /data-i18n-html="site.capture.step1.b1"/, "capture step-1
placement bullet isn't localizable");
267     assert.match(cap, /data-i18n-html="site.capture.step2.b3"/, "capture audio bullet
isn't localizable");
268     // The homepage gist localizes its cards.
269     assert.match(read("index.html"), /data-i18n-html="site.record.settings.body"/,
"homepage settings card isn't localizable");
270     // en catalog's recording values keep the inline <b> markup the HTML relies on.
271     assert.match(enCatalog.site.record.place.body, /<b>.*<\b>/s, "en record.place.body
lost its <b> markup");
272     assert.match(enCatalog.site.capture.step2.b1, /<b>1080p or higher<\b>/, "en
capture.step2.b1 markup drift");
273   });
274
275   test("A3: EVERY data-i18n[-html] HTML default matches the en catalog byte-for-byte (no
drift, incl. rich <b> keys)", () => {
276     // The rich (data-i18n-html) keys are the most drift-prone: the inline <b> markup must
match the
277     // catalog exactly, or an en visitor's no-JS default and the shim's en render silently
diverge.
278     // Parse the REAL pages in jsdom and compare each tagged element's default to
enCatalog.
279     const dig = (o, k) => k.split(".").reduce((a, c) => (a == null ? a : a[c]), o);
280     let checked = 0;
281     for (const f of ["index.html", "capture.html", "own-model.html"]) {
282       const { document } = new JSDOM(read(f)).window;
283       for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
284         if (el.getAttribute("data-i18n-attr")) continue; // attribute defaults aren't the
visible text
285         const htmlKey = el.getAttribute("data-i18n-html");
286         const key = htmlKey || el.getAttribute("data-i18n");
287         const enVal = dig(enCatalog, key);
288         assert.notEqual(enVal, undefined, `$$$${f}: data-i18n key "${key}" missing from en
catalog`);
289         const got = (htmlKey ? el.innerHTML : el.textContent).trim();
290         assert.equal(got, enVal, `$$$${f}: "${key}" HTML default drifted from the en
catalog`);

```

```

291         checked++;
292     }
293 }
294 assert.ok(checked >= 60, `expected to check the full localized surface, only saw
${checked}`);
295 });
296
297 // ---- own-model body localized (kn/hi)
-----
298 test("own-model: the body content is wired for translation (every site.ownModel
data-i18n key resolves in en)", () => {
299     const dig = (obj, key) => key.split(".").reduce((o, k) => (o == null ? o : o[k]),
obj);
300     const om = read("own-model.html");
301     const keys = [...om.matchAll(/data-i18n(?:-html)?="([^\"]+)/g)].map((m) =>
m[1]).filter((k) => k.startsWith("site.ownModel."));
302     // The whole page body (hero, annotate/train/setup, "what this is not", CTA, footer)
is now localizable.
303     assert.ok(keys.length >= 40, `own-model should wire its body content (found only
${keys.length} site.ownModel keys)`);
304     for (const key of keys) assert.notEqual(dig(enCatalog, key), undefined, `own-model
data-i18n key "${key}" has no en catalog entry`);
305     // Rich (inline-markup) and plain forms are both used.
306     assert.match(om, /data-i18n-html="site\.ownModel\.heroLead"/, "the hero lead should
localize");
307     assert.match(om, /data-i18n-html="site\.ownModel\.train\.honestBody"/, "the honest-
framing fence should localize");
308     assert.match(om, /data-i18n="site\.ownModel\.not\.title"/, "the 'what this is not'
heading should localize");
309     // Code / CLI blocks deliberately stay LITERAL (commands, paths, CSV) ? never wired
for translation.
310     assert.doesNotMatch(om, /<pre[^\>]*data-i18n/i, "code blocks must stay literal (not
wired for translation)");
311     assert.match(om, /python -m backend\.worker train/, "the developer CLI command must
stay verbatim in the page");
312     // The honest framing survives in the en DOM default (server smoke + no-JS reads rely
on it).
313     assert.equal(enCatalog.site.ownModel.train.honestTitle, "Read this honestly.");
314 });
315
316 // ---- A6: plain-language Request-Access GPU/storage questions
-----
317 test("A6: the GPU/storage questions are de-jargoned + reassuring, backend contract
intact", () => {
318     const html = read("index.html");
319     // The intimidating phrasings are gone from the visible copy.
320     assert.doesNotMatch(html, /GPU machine/i, "'GPU machine' jargon should be gone");
321     assert.doesNotMatch(html, /process video locally/i, "'process video locally' jargon
should be gone");
322     assert.doesNotMatch(html, /\(S3\/GCS\)/, "the bare '(S3/GCS)' jargon should be gone");
323     // Reassurance: a non-tech user is explicitly told a GPU isn't required.
324     assert.match(html, /run it in the cloud for you/i, "the GPU question must reassure
that the cloud is an option");
325     assert.match(enCatalog.site.join.gpuHint, /no worries|don't need|cloud/i, "the GPU
hint should reassure");
326     // Questions route through the shim (translation-ready).
327     assert.match(html, /data-i18n="site\.join\.gpuLabel"/, "GPU question not wired for
i18n");
328     assert.match(html, /data-i18n="site\.join\.storageLabel"/, "storage question not wired
for i18n");
329     // The backend contract is preserved: field names + EVERY enum value unchanged (server
validates these).
330     for (const v of ["yes", "unsure", "no", "prefer-cloud"]) assert.match(html, new
RegExp(`name="has_gpu" value="${v}"`), `has_gpu value ${v} lost`);
331     for (const v of ["gdrive", "onedrive", "dropbox", "bucket", "local", "unsure"])

```

```

assert.match(html, new RegExp(`name="storage" value="\${v}"`), `storage value \${v} lost`);
332     });
333
334     // ---- A7: camera-placement diagram on the capture page
-----
335     test("A7: the capture page shows an accessible, localized camera-placement diagram", ()
=> {
336         const cap = read("capture.html");
337         assert.match(cap, /<figure class="diagram">/, "the placement diagram figure is
missing");
338         assert.match(cap, /<svg[<^>]*role="img"/, "the diagram must be an accessible <svg
role=\"img\">");
339         assert.match(cap, /<title data-i18n="site.capture.diagram.title"/, "the svg needs a
localized accessible <title>");
340         assert.match(cap, /fill-opacity="0.10"/, "the field-of-view cone (what the camera
captures) is missing");
341         assert.match(cap, /?30°/, "the ~30° downward-tilt annotation is missing");
342         assert.match(cap, /?[\s\S]*?[\s\S]*?/, "the diagram's step markers ??? are missing");
343         // The legend maps the markers to the placement rules and is fully localizable.
344         for (const k of ["title", "camera", "angle", "frame", "net"]) {
345             assert.match(cap, new RegExp(`data-i18n="site\\.capture\\.diagram\\.\\.${k}"`),
`diagram lacks the \${k} label`);
346             assert.notEqual(enCatalog.site.capture.diagram[k], undefined, `en catalog missing
diagram.\${k}`);
347         }
348         // The diagram complements the existing #1 "Place the camera" text step (doesn't
replace it).
349         assert.match(cap, /data-i18n="site.capture.step1.title"/, "the placement text step
should remain");
350     });
351
352     // ---- A2: localized WhatsApp share in the post-signup reveal
-----
353     test("A2: the post-signup reveal offers a localized, safe WhatsApp share of the reel",
() => {
354         const html = read("index.html");
355         // The reveal is injected after sign-up, so its share copy comes from the shim bridge
356         // (window.KhelSutra.t) with an en fallback, rendered as a wa.me link.
357         assert.match(html, /window.KhelSutra\s*&\s*window.KhelSutra.t/, "reveal should
pull share copy from the shim bridge");
358         assert.match(html, /ksT\('site.reveal.shareText'\)/, "reveal should use the
site.reveal.shareText key");
359         assert.match(html, /id="reel-share"/, "the reveal share button is missing");
360         assert.match(html, /'https:\\\\wa.me\\/\\?text=/', "share must be a wa.me link");
361         assert.match(html, /rel="noopener noreferrer"/, "external share link must be tab-
nabbing-safe");
362         // The shim exposes the bridge after render.
363         assert.match(read("i18n.js"), /window.KhelSutra\s*=\s*\{\s*t:/, "the shim must expose
window.KhelSutra.t for dynamic content");
364         // Keys exist in the shared catalog (en authored; kn/hi translated).
365         assert.ok(enCatalog.site.reveal.share && enCatalog.site.reveal.shareText, "en catalog
missing site.reveal.*");
366     });
367

```

17. assistant (2026-06-22T03:48:50.518Z)

I now have the full picture of the test guards and the existing `site.\*` catalog structure. Two important findings shape the scope:

1. The **byte-for-byte drift guard** (`assets.test.js:275`) walks **every** `data-i18n[-html]` element across the localized pages and requires the en catalog to match the HTML innerHTML/textContent exactly ? so anything I wire must be added to the en catalog precisely.
2. The page is localized **section by section**: only the header nav, hero-left intro, and the `#record` section are currently wired. The entire `#how`, `#diff`, `#sharper`, `#ask`,

??????? ????, ??? ????????? ????
hero.ctaHow: ????? ?? ??? ???? ?
record.intro: ?????? ?? ????????? ?????????? ?? ?? ???? ???? ???? ???? ???? ?
??????? ?????? ?? ??? KhelSutra ?? ?? ? ???? ????
record.upload.body: ??-???? ?????, ??? ???? ???? ?????? ???? ?? ???? ? ???? ? ????
???? ? KhelSutra ?????? ?????? ?? ? ???? ????
ownModel.heroLead: ?? ???? ????? ?????? ?? Gemini ?? GPT ?? ????? ???? ? ???? KhelSutra ??
???? ???? ???? ? ? ? ???? , <b style="color:#EAF3EE">???? ???? ???? ???? ???? ????
?????-???? ????????, ?? ??? ?????????? ???? ???? ? ???? ? ???? ???? ? ???? ????
reveal.shareText: KhelSutra ????? ? ? ???? ????????? ???? ? ? ???? ????????? ???? ???? ???? ?
? khelsutra.guru

===== es =====

hero.title : Cada jugada, indexada. El tiempo muerto, fuera.
hero.lead : KhelSutra encuentra cada jugada de tu sesión y elimina los calentamientos, las
caminatas y las pausas ? para que un partido completo se convierta en un reel de jugadas
destacadas limpio que puedes ver y descargar. Sin edición ni rebobinados.
hero.ctaHow: Ver cómo funciona
record.intro: La calidad de las jugadas destacadas empieza con la grabación. Coloca la cámara
así una sola vez y KhelSutra tendrá todo lo que necesita para encontrar las jugadas.
record.upload.body: Iluminación uniforme, luego graba la sesión completa y súbela tal
cual ? KhelSutra encuentra las jugadas y hace el recorte.
ownModel.heroLead: No puedes entrenar Gemini ni GPT con las grabaciones de tu cancha. La
dirección de KhelSutra es la inversa ? un modelo de jugadas pequeño y <b
style="color:#EAF3EE">propio donde la ventaja competitiva es tu conjunto de datos con
consentimiento, sobre una base tecnológica comercialmente limpia e inspeccionable que tú
controlas.
reveal.shareText: Mira KhelSutra ? convierte un partido completo de bádminton en un reel de
jugadas destacadas limpio ? khelsutra.guru

===== da =====

hero.title : Hver duel, indekseret. Den døde tid, væk.
hero.lead : KhelSutra finder hver duel i din session og fjerner opvarmningsslag, gåture og
pauser ? så en hel kamp bliver til en ren highlights-reel, du kan se og downloade. Ingen
redigering, ingen spoling.
hero.ctaHow: Se, hvordan det fungerer
record.intro: Kvaliteten af dine highlights begynder med optagelsen. Stil kameraet op én gang på
denne måde, så har KhelSutra alt, hvad den skal bruge for at finde duellerne.
record.upload.body: Jævn belysning, optag derefter hele sessionen og upload den, som den
er ? KhelSutra finder duellerne og klarer klipningen.
ownModel.heroLead: Du kan ikke træne Gemini eller GPT på dine baneoptagelser. KhelSutras retning
er den omvendte ? en lille, <b style="color:#EAF3EE">ejet duel-model, hvor fordelene er dit
datasæt med samtykke, på en kommercielt ren, gennemskuelig stak, du kontrollerer.
reveal.shareText: Tjek KhelSutra ? den forvandler en hel badmintonkamp til en ren highlights-
reel ? khelsutra.guru

===== id =====

hero.title : Setiap reli, terindeks. Waktu kosongnya, hilang.
hero.lead : KhelSutra menemukan setiap reli dalam sesimu dan membuang pemanasan, momen jalan-
jalan antar-poin, dan waktu kosong ? sehingga satu pertandingan penuh menjadi reel sorotan rapi
yang bisa kamu tonton dan unduh. Tanpa mengedit, tanpa menggeser-geser.
hero.ctaHow: Lihat cara kerjanya
record.intro: Kualitas highlight dimulai dari rekamannya. Atur kamera sekali seperti ini dan
KhelSutra sudah punya semua yang diperlukannya untuk menemukan reli.
record.upload.body: Pencapaian merata, lalu rekam seluruh sesi dan unggah apa adanya ?
KhelSutra menemukan reli dan melakukan pemotongannya.
ownModel.heroLead: Kamu tidak bisa melatih Gemini atau GPT pada rekaman lapanganmu. Arah
KhelSutra justru sebaliknya ? model reli kecil yang <b style="color:#EAF3EE">kamu miliki, di
mana keunggulannya adalah dataset hasil persetujuanmu, di atas tumpukan teknologi yang bersih
secara komersial dan dapat kamu periksa serta kendalikan.
reveal.shareText: Coba KhelSutra ? ia mengubah satu pertandingan bulu tangkis penuh menjadi reel
sorotan yang rapi ? khelsutra.guru
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

I have the established vocabulary anchored (rally = kn ?????? / hi ???? / es jugada / da duel / id reli; reel kept; dead time = ?????????? ??? / ?????? ??? / tiempo muerto / død tid / waktu kosong; etc.). Now let me wire the HTML attributes. I'll edit the hero block first (text untouched ? only attributes added).

23. user (2026-06-22T03:53:03.448Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

24. assistant (2026-06-22T03:53:06.536Z)

Now the reel-card demo mockup strings:

25. user (2026-06-22T03:53:08.463Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

26. user (2026-06-22T03:53:10.346Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

27. user (2026-06-22T03:53:12.389Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

28. assistant (2026-06-22T03:53:14.410Z)

Now the `#how` section head and four feature cards:

29. user (2026-06-22T03:53:17.228Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

30. user (2026-06-22T03:53:22.115Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

31. user (2026-06-22T03:53:24.472Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

32. user (2026-06-22T03:53:27.294Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

33. user (2026-06-22T03:53:29.282Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

34. assistant (2026-06-22T03:53:34.570Z)

All 11 HTML elements are now wired. Now let me extract the exact byte-for-byte values from the newly-wired elements via jsdom ? this guarantees my en catalog values match the drift guard precisely (handling em-dashes, middle dots, curly quotes, apostrophes).

35. user (2026-06-22T03:53:38.029Z)

Exit code 1

```
node:internal/modules/cjs/loader:1505
  throw err;
  ^
```

Error: Cannot find module 'jsdom'

Require stack:

```
- C:\Users\avidu\Projects\khelsutra-wt-hero\site\[eval]
  at Module._resolveFilename (node:internal/modules/cjs/loader:1502:15)
  at wrapResolveFilename (node:internal/modules/cjs/loader:1073:27)
  at defaultResolveImplForCJSLoading (node:internal/modules/cjs/loader:1097:10)
  at resolveForCJSWithHooks (node:internal/modules/cjs/loader:1118:12)
  at Module._load (node:internal/modules/cjs/loader:1287:25)
  at wrapModuleLoad (node:internal/modules/cjs/loader:255:19)
  at Module.require (node:internal/modules/cjs/loader:1602:12)
  at require (node:internal/modules/helpers:191:16)
  at [eval]:2:19
  at runScriptInThisContext (node:internal/vm:219:10) {
  code: 'MODULE_NOT_FOUND',
  requireStack: [ 'C:\\Users\\avidu\\Projects\\khelsutra-wt-hero\\site\\[eval]' ]
}
```

Node.js v26.1.0

36. assistant (2026-06-22T03:53:42.228Z)

The worktree needs its own `node\_modules`. Let me install dependencies for `site/` (and `web/` in parallel, since I'll need both for the full test suites).

37. user (2026-06-22T03:53:46.917Z)

```
8 packages are looking for funding
  run `npm fund` for details
```

found 0 vulnerabilities

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

38. user (2026-06-22T03:53:53.438Z)

```
50 packages are looking for funding
  run `npm fund` for details
```

found 0 vulnerabilities

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

39. assistant (2026-06-22T03:53:56.425Z)

Both installed. Now extract the exact en values via jsdom:

40. user (2026-06-22T03:54:01.916Z)

```
{
  "site.hero.ctaReel": "See it in action + a real reel",
  "site.hero.note": "A phone or GoPro on a tripod is all you need. No special hardware.",
  "site.hero.loop.step1": "<b>1.</b> Auto-index rallies",
  "site.hero.loop.step2": "<b>2.</b> Dead time removed",
  "site.hero.loop.step3": "<b>3.</b> Download your reel",
  "site.hero.demo.fileTag": "match_2026.mp4 · indexed",
  "site.hero.demo.detected": "Rallies detected",
  "site.hero.demo.found": "44 found",
  "site.hero.demo.resultTitle": "Highlight reel · 44 rallies · 18 min",
  "site.hero.demo.resultSub": "dead time removed · ready to download",
}
```

```

"site.how.kicker": "What it does today",
"site.how.title": "A full match, turned into rallies you can search",
"site.how.intro": "Upload a whole session or match. KhelSutra does the rest ? no editing skill
needed.",
"site.how.indexed.title": "Every rally, indexed",
"site.how.indexed.body": "It finds each rally ? start, end and length ? and turns the whole
match into a searchable list. Long full-session videos are fine.",
"site.how.deadtime.title": "Dead time removed",
"site.how.deadtime.body": "Knock-ups, walks, picking up the shuttle, the gaps between points ?
stripped out. What's left is only real play.",
"site.how.reuse.title": "Process once, reuse",
"site.how.reuse.body": "Come back later to watch or download your reel. Re-running a video
replaces its earlier result rather than piling up copies.",
"site.how.stitch.title": "Stitched reel + summary",
"site.how.stitch.body": "Your selection becomes one MP4 to download and share ? with a play-
time summary and a small ?Generated by Khelsutra.guru? mark."
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

41. assistant (2026-06-22T03:54:15.832Z)

I have byte-exact en values. Before mutating the catalogs, let me verify a JSON round-trip produces a clean (additions-only) diff, so I don't churn the whole file.

42. user (2026-06-22T03:54:21.314Z)

```

en round-trip identical: true | raw bytes: 16379 | trailing newline: "}\n"
kn round-trip identical: true | raw bytes: 18126 | trailing newline: "}\n"
hi round-trip identical: true | raw bytes: 17141 | trailing newline: "}\n"
es round-trip identical: true | raw bytes: 18375 | trailing newline: "}\n"
da round-trip identical: true | raw bytes: 17127 | trailing newline: "}\n"
id round-trip identical: true | raw bytes: 17866 | trailing newline: "}\n"
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

43. assistant (2026-06-22T03:57:14.776Z)

The round-trip is clean for all six locales (``JSON.stringify(j, null, 2) + "\n"`` reproduces each file byte-for-byte), so I can mutate the parsed objects and get an additions-only diff.

Now I'll draft all translations, anchored to the shipped vocabulary, and apply them via a self-checking script that derives the `**en**` values straight from the wired DOM (guaranteeing byte-exactness against the drift guard) while taking my translations for the other five locales. Let me write the applier:

44. assistant (2026-06-22T03:58:40.633Z)

```

/* TEMP applier ? adds hero-demo + #how i18n keys to all 6 catalogs.
   en values are DERIVED FROM THE WIRED DOM (byte-exact vs the drift guard);
   the other 5 locales come from the translation tables below. Deleted after run. */
const { JSDOM } = require("jsdom");
const fs = require("fs");
const path = require("path");

const ROOT = __dirname;
const htmlPath = path.join(ROOT, "site", "public", "index.html");
const { document } = new JSDOM(fs.readFileSync(htmlPath, "utf8")).window;

// 1) derive en map for the NEW keys straight from the DOM defaults
const NEWKEY = /^site\.(hero\.(ctaReel|note|loop|demo)|how\.)/;
const en = {};
for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
  if (el.getAttribute("data-i18n-attr")) continue;
  const htmlKey = el.getAttribute("data-i18n-html");
  const key = htmlKey || el.getAttribute("data-i18n");

```

```
if (!NEWKEY.test(key)) continue;
en[key] = (htmlKey ? el.innerHTML : el.textContent).trim();
}
```

// 2) translations (kn/hi/es/da/id). Same dotted keys as en. Brand/tokens/numbers literal.

```
const T = {
  kn: {
    "site.hero.ctaReel": "????????? ???? + ?????? ????",
    "site.hero.note": "????????? ???? ???? ???? ???? GoPro ????. ?????? ?????? ???????????? ???.",
    "site.hero.loop.step1": "<b>1.</b> ???????? ?????-????",
    "site.hero.loop.step2": "<b>2.</b> ?????????? ?? ?????????????????",
    "site.hero.loop.step3": "<b>3.</b> ?????? ???? ?????????? ????",
    "site.hero.demo.fileTag": "match_2026.mp4 · ????????????",
    "site.hero.demo.detected": "????????? ????????????",
    "site.hero.demo.found": "44 ??????????",
    "site.hero.demo.resultTitle": "?????? ???? · 44 ?????????? · 18 min",
    "site.hero.demo.resultSub": "????????? ?? ????????????????? · ?????????????? ??????",
    "site.how.kicker": "???? ???? ???? ??????????",
    "site.how.title": "????? ??????????, ??? ???? ?????????? ??????????",
    "site.how.intro": "??? ?????? ??? ???? ?????????? ?????????? ????. ???????????? KhelSutra ??????????
? ?????? ?????????? ?????? ???.",
    "site.how.indexed.title": "????? ?????????, ??????????",
    "site.how.indexed.body": "??? ?????? ?????????????? ? ????, ?????? ?????? ??? ? ??????, ???
????????????? ?????????????? ?????????? ??????????. ?????? ?????-????? ?????????? ???.",
    "site.how.deadtime.title": "????????? ??? ??????????????????",
    "site.how.deadtime.body": "????-????????, ?????, ??? ??????????????????, ?????????? ??????
???????? ? ?????????? ??????????????????????. ?????????? ?????? ?? ?????.",
    "site.how.reuse.title": "????? ?????????, ??????",
    "site.how.reuse.body": "????? ??? ?????? ?????? ??? ?????????? ?????? ??? ?????? ??????
????????????? ?????? ?????????????? ?? ?????????????? ?????????? ?????? ?????????????? ?????????????????.",
    "site.how.stitch.title": "????????? ??? + ??????",
    "site.how.stitch.body": "????? ?????? ?????????? ??? ?????????????? ??? MP4 ?????????? ? ???-????
????????? ?????? ??? ???? ?Generated by Khelsutra.guru? ?????????????????.",
  },
  hi: {
    "site.hero.ctaReel": "??? ?? ???? ????? + ?? ???? ???",
    "site.hero.note": "????? ?? ?? ???? ?? GoPro ?? ?????? ?? ?? ???? ???????????? ??????",
    "site.hero.loop.step1": "<b>1.</b> ???????? ?????-?? ?????????",
    "site.hero.loop.step2": "<b>2.</b> ?????? ??? ?????? ???",
    "site.hero.loop.step3": "<b>3.</b> ???? ?? ?????????? ????",
    "site.hero.demo.fileTag": "match_2026.mp4 · ???????? ???? ???",
    "site.hero.demo.detected": "????????? ??????",
    "site.hero.demo.found": "44 ??????",
    "site.hero.demo.resultTitle": "????????? ??? · 44 ???????? · 18 min",
    "site.hero.demo.resultSub": "????? ?? ?????? ??? · ???????? ?? ?? ??????",
    "site.how.kicker": "?? ?? ???? ???? ??",
    "site.how.title": "?? ????? ??, ???? ?? ???? ???? ?????????? ?? ??????",
    "site.how.intro": "???? ???? ? ???? ?????? ?????? ?????? ?? KhelSutra ???? ? ? ???? ?????????
????? ???? ??????",
    "site.how.indexed.title": "?? ?????, ???? ???",
    "site.how.indexed.body": "?? ?? ???? ?????? ?? ? ??????, ??? ?? ???? ? ?? ???? ??? ?? ?
???? ?? ???? ???? ???? ???? ???? ???? ???? ?????-????? ?????? ?? ??? ??????",
    "site.how.deadtime.title": "????? ??? ?????? ???",
    "site.how.deadtime.body": "????-??, ?????????, ?? ?????, ?????? ?? ?? ? ?????????? ? ?? ???
????? ???? ? ???? ? ? ? ?????? ???? ???? ????",
    "site.how.reuse.title": "?? ??? ?????????? ?????, ?????? ?????????? ?????",
    "site.how.reuse.body": "????? ??? ?????? ?? ?????????? ?????? ?? ???? ???? ???? ?????? ????
????????? ???? ? ? ? ?????????? ???? ???? ? ???? ???? ?????? ?????? ???? ???? ????",
    "site.how.stitch.title": "????? ?? ? ? + ??????",
    "site.how.stitch.body": "????? ??? ?????????? ?? ???? ???? ? ? ? ? MP4 ?? ???? ? ? ? ? ?-???
??????? ? ? ? ???? ?Generated by Khelsutra.guru? ?????? ? ? ?????",
  },
  es: {
    "site.hero.ctaReel": "Míralo en acción + un reel real",
    "site.hero.note": "Basta con un teléfono o una GoPro sobre un trípode. Sin hardware
```

```

especial.",
  "site.hero.loop.step1": "<b>1.</b> Indexa las jugadas automáticamente",
  "site.hero.loop.step2": "<b>2.</b> Tiempo muerto eliminado",
  "site.hero.loop.step3": "<b>3.</b> Descarga tu reel",
  "site.hero.demo.fileTag": "match_2026.mp4 · indexado",
  "site.hero.demo.detected": "Jugadas detectadas",
  "site.hero.demo.found": "44 encontradas",
  "site.hero.demo.resultTitle": "Reel destacado · 44 jugadas · 18 min",
  "site.hero.demo.resultSub": "tiempo muerto eliminado · listo para descargar",
  "site.how.kicker": "Lo que hace hoy",
  "site.how.title": "Un partido completo, convertido en jugadas que puedes buscar",
  "site.how.intro": "Sube una sesión o un partido completo. KhelSutra hace el resto ? no hace falta saber editar.",
  "site.how.indexed.title": "Cada jugada, indexada",
  "site.how.indexed.body": "Encuentra cada jugada ? inicio, fin y duración ? y convierte todo el partido en una lista que puedes buscar. Los vídeos largos de una sesión completa no son problema.",
  "site.how.deadtime.title": "Tiempo muerto eliminado",
  "site.how.deadtime.body": "Calentamientos, caminatas, recoger el volante, las pausas entre puntos ? todo eliminado. Lo que queda es solo juego real.",
  "site.how.reuse.title": "Procesa una vez, reutiliza",
  "site.how.reuse.body": "Vuelve más tarde para ver o descargar tu reel. Volver a procesar un vídeo reemplaza su resultado anterior en lugar de acumular copias.",
  "site.how.stitch.title": "Reel unido + resumen",
  "site.how.stitch.body": "Tu selección se convierte en un único MP4 para descargar y compartir ? con un resumen del tiempo de juego y una pequeña marca ?Generated by Khelsutra.guru?.",
},
da: {
  "site.hero.ctaReel": "Se det i aktion + en rigtig reel",
  "site.hero.note": "En telefon eller GoPro på et stativ er alt, du behøver. Ingen særlig hardware.",
  "site.hero.loop.step1": "<b>1.</b> Auto-indeksér duellerne",
  "site.hero.loop.step2": "<b>2.</b> Død tid fjernet",
  "site.hero.loop.step3": "<b>3.</b> Download din reel",
  "site.hero.demo.fileTag": "match_2026.mp4 · indekseret",
  "site.hero.demo.detected": "Dueller fundet",
  "site.hero.demo.found": "44 fundet",
  "site.hero.demo.resultTitle": "Highlights-reel · 44 dueller · 18 min",
  "site.hero.demo.resultSub": "død tid fjernet · klar til download",
  "site.how.kicker": "Hvad den gør i dag",
  "site.how.title": "En hel kamp, omdannet til dueller, du kan søge i",
  "site.how.intro": "Upload en hel session eller kamp. KhelSutra klarer resten ? du behøver ingen redigeringsevner.",
  "site.how.indexed.title": "Hver duel, indekseret",
  "site.how.indexed.body": "Den finder hver duel ? start, slutning og længde ? og gør hele kampen til en søgbar liste. Lange optagelser af en hel session er helt fine.",
  "site.how.deadtime.title": "Død tid fjernet",
  "site.how.deadtime.body": "Opvarmningsslag, gåture, at samle fjerbolden op, pauserne mellem point ? alt sammen skåret væk. Det, der er tilbage, er kun rigtigt spil.",
  "site.how.reuse.title": "Behandl én gang, genbrug",
  "site.how.reuse.body": "Kom tilbage senere for at se eller downloade din reel. At køre en video igen erstatter dens tidligere resultat i stedet for at hobe kopier op.",
  "site.how.stitch.title": "Sammensat reel + resumé",
  "site.how.stitch.body": "Dit udvalg bliver til én MP4 til download og deling ? med et resumé af spilletiden og et lille ?Generated by Khelsutra.guru?-mærke.",
},
id: {
  "site.hero.ctaReel": "Lihat langsung + reel sungguhan",
  "site.hero.note": "Cukup sebuah ponsel atau GoPro di atas tripod. Tanpa perangkat keras khusus.",
  "site.hero.loop.step1": "<b>1.</b> Indeks reli otomatis",
  "site.hero.loop.step2": "<b>2.</b> Waktu kosong dihapus",
  "site.hero.loop.step3": "<b>3.</b> Unduh reel-mu",
  "site.hero.demo.fileTag": "match_2026.mp4 · terindeks",

```

```

    "site.hero.demo.detected": "Reli terdeteksi",
    "site.hero.demo.found": "44 ditemukan",
    "site.hero.demo.resultTitle": "Reel sorotan · 44 reli · 18 min",
    "site.hero.demo.resultSub": "waktu kosong dihapus · siap diunduh",
    "site.how.kicker": "Apa yang dilakukannya hari ini",
    "site.how.title": "Satu pertandingan penuh, diubah menjadi reli yang bisa kamu cari",
    "site.how.intro": "Unggah satu sesi atau pertandingan penuh. KhelSutra melakukan sisanya ?
    tanpa perlu keahlian mengedit.",
    "site.how.indexed.title": "Setiap reli, terindeks",
    "site.how.indexed.body": "Ia menemukan setiap reli ? awal, akhir, dan durasinya ? dan
    mengubah seluruh pertandingan menjadi daftar yang bisa dicari. Video sesi penuh yang panjang pun
    bukan masalah.",
    "site.how.deadtime.title": "Waktu kosong dihapus",
    "site.how.deadtime.body": "Pemanasan, momen jalan-jalan, memungut kok, jeda antar-poin ?
    semuanya dibuang. Yang tersisa hanya permainan nyata.",
    "site.how.reuse.title": "Proses sekali, pakai lagi",
    "site.how.reuse.body": "Kembalilah nanti untuk menonton atau mengunduh reel-mu. Memproses
    ulang sebuah video akan menggantikan hasil sebelumnya, bukan menumpuk salinan.",
    "site.how.stitch.title": "Reel gabungan + ringkasan",
    "site.how.stitch.body": "Pilihanmu menjadi satu MP4 untuk diunduh dan dibagikan ? dengan
    ringkasan waktu bermain dan tanda kecil ?Generated by Khelsutra.guru?.",
  },
};

```

```

// 3) apply
const KEYS = Object.keys(en);
function setPath(obj, dotted, val) {
  const parts = dotted.split(".");
  let o = obj;
  for (let i = 0; i < parts.length - 1; i++) {
    if (o[parts[i]] == null || typeof o[parts[i]] !== "object") o[parts[i]] = {};
    o = o[parts[i]];
  }
  o[parts[parts.length - 1]] = val;
}

const report = [];
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const p = path.join(ROOT, "locales", loc, "common.json");
  const j = JSON.parse(fs.readFileSync(p, "utf8"));
  const table = loc === "en" ? en : T[loc];
  // guard: every new key must be present in this locale's table
  const missing = KEYS.filter((k) => table[k] == null);
  if (missing.length) throw new Error(`${loc} missing translations: ${missing.join(", ")}`);
  for (const k of KEYS) setPath(j, k, table[k]);
  fs.writeFileSync(p, JSON.stringify(j, null, 2) + "\n");
  report.push(`${loc}: +${KEYS.length} keys`);
}
console.log("Applied:\n" + report.join("\n"));
console.log("\nen keys derived from DOM:");
for (const k of KEYS) console.log("  " + k + " = " + JSON.stringify(en[k]));

```

45. user (2026-06-22T03:58:40.667Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra-wt-hero/_tmp_add_hero_how_keys.cjs (file state is current in your context ? no need to Read it back)

46. user (2026-06-22T03:58:44.108Z)

```

Exit code 1
node:internal/modules/cjs/loader:1505
  throw err;
  ^

```

Error: Cannot find module 'jsdom'

Require stack:

```
- C:\Users\avidu\Projects\khelsutra-wt-hero\_tmp_add_hero_how_keys.cjs
  at Module._resolveFilename (node:internal/modules/cjs/loader:1502:15)
  at wrapResolveFilename (node:internal/modules/cjs/loader:1073:27)
  at defaultResolveImplForCJSLoading (node:internal/modules/cjs/loader:1097:10)
  at resolveForCJSWithHooks (node:internal/modules/cjs/loader:1118:12)
  at Module._load (node:internal/modules/cjs/loader:1287:25)
  at wrapModuleLoad (node:internal/modules/cjs/loader:255:19)
  at Module.require (node:internal/modules/cjs/loader:1602:12)
  at require (node:internal/modules/helpers:191:16)
  at Object.<anonymous> (C:\Users\avidu\Projects\khelsutra-wt-
hero\_tmp_add_hero_how_keys.cjs:4:19)
    at Module._compile (node:internal/modules/cjs/loader:1856:14) {
  code: 'MODULE_NOT_FOUND',
  requireStack: [
    'C:\\Users\\avidu\\Projects\\khelsutra-wt-hero\\_tmp_add_hero_how_keys.cjs'
  ]
}
```

Node.js v26.1.0

47. assistant (2026-06-22T03:58:51.341Z)

jsdom resolves from `site/node\_modules`. Let me point the require at it:

48. user (2026-06-22T03:58:52.747Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/_tmp_add_hero_how_keys.cjs has been updated successfully. (file state is current in your context ? no need to Read it back)

49. user (2026-06-22T03:58:58.997Z)

Applied:

```
en: +21 keys
kn: +21 keys
hi: +21 keys
es: +21 keys
da: +21 keys
id: +21 keys
```

en keys derived from DOM:

```
site.hero.ctaReel = "See it in action + a real reel"
site.hero.note = "A phone or GoPro on a tripod is all you need. No special hardware."
site.hero.loop.step1 = "<b>1.</b> Auto-index rallies"
site.hero.loop.step2 = "<b>2.</b> Dead time removed"
site.hero.loop.step3 = "<b>3.</b> Download your reel"
site.hero.demo.fileTag = "match_2026.mp4 · indexed"
site.hero.demo.detected = "Rallies detected"
site.hero.demo.found = "44 found"
site.hero.demo.resultTitle = "Highlight reel · 44 rallies · 18 min"
site.hero.demo.resultSub = "dead time removed · ready to download"
site.how.kicker = "What it does today"
site.how.title = "A full match, turned into rallies you can search"
site.how.intro = "Upload a whole session or match. KhelSutra does the rest ? no editing skill
needed."
site.how.indexed.title = "Every rally, indexed"
site.how.indexed.body = "It finds each rally ? start, end and length ? and turns the whole
match into a searchable list. Long full-session videos are fine."
site.how.deadtime.title = "Dead time removed"
site.how.deadtime.body = "Knock-ups, walks, picking up the shuttle, the gaps between points ?
stripped out. What's left is only real play."
site.how.reuse.title = "Process once, reuse"
site.how.reuse.body = "Come back later to watch or download your reel. Re-running a video"
```


replaces its earlier result rather than piling up copies."
site.how.stitch.title = "Stitched reel + summary"
site.how.stitch.body = "Your selection becomes one MP4 to download and share ? with a play-time summary and a small ?Generated by Khelsutra.guru? mark."
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

50. assistant (2026-06-22T03:59:12.367Z)

All 6 catalogs got the 21 keys. Now let me clean up the temp script, mirror the catalogs into `site/public/locales`, and run a structural verification (tag-multiset parity, script coverage, token preservation, no-en-seed) before the linguistic pass.

51. user (2026-06-22T03:59:14.599Z)

```
> copy:locales  
> node scripts/copy-locales.mjs
```

copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

52. user (2026-06-22T03:59:29.836Z)

STRUCTURAL CHECK: PASS (all 21 keys x 5 locales)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

53. assistant (2026-06-22T04:01:04.420Z)

Structural invariants all hold (tag parity, in-script kn/hi, token/number preservation, no en-seed). Now the ****adversarial linguistic verification**** the task calls for. I'll spawn five native-reviewer agents in parallel ? one per locale ? to read the actual applied catalog values against the en source and flag real errors with paste-ready corrections.

54. user (2026-06-22T04:01:47.958Z)

Both files read. Comparing the 21 keys now.

Key findings:

- `site.how.indexed.body`: en says "the whole match into a ****searchable list****" ? es says "una lista que puedes buscar" (fine, matches "que puedes buscar" used in title). Acceptable. But note "video" usage required ? es uses "vídeos" here (correct per vocab).
- `site.hero.demo.resultTitle`: "Reel destacado" is the acceptable compact form per the rules. Fine.
- `site.how.reuse.title`: en "Process once, reuse" ? es "Procesa una vez, reutiliza". Fine.
- Checking `site.hero.note`: GoPro preserved, fine.

Let me verify the em-dashes, middle-dots, and the `**<b>**` digit tags are all intact across the keys. All present. No real errors found in grammar, vocab consistency, or constraints across the 21 keys.

===END===

agentId: a8ed537d680d0429e (use SendMessage with to: 'a8ed537d680d0429e' to continue this agent)
<usage>subagent_tokens: 45634
tool_uses: 2
duration_ms: 10587</usage>

55. user (2026-06-22T04:01:50.603Z)

Both files are read. Now I'll review the 21 keys carefully as a native Kannada speaker, checking each against the English source, domain vocabulary, hard constraints, grammar, and marketing register.

Let me work through each key:

****site.hero.ctaReel****: en "See it in action + a real reel" / kn "?????????? ???? + ?????? ????".

"????????? ?????" is a literal/awkward rendering of "see it in action." "?????????" (in work/function) is unnatural Kannada for "in action." The natural idiom is "?????????????????" or more idiomatically "????????? ?????" / "???? ???? ?????? ????". This is a real register/naturalness issue worth flagging.

****site.hero.note****: en / kn fine. "????????? ???? ???? ???? ???? GoPro ?????. ?????? ?????? ?????????? ????." Good. GoPro preserved.

****loop.step1/2/3****: `**<b>1.</b>**` etc preserved. step1 "????????? ?????-?????" (auto-index of rallies) ? fine. step2/step3 fine.

****demo.fileTag****: "match_2026.mp4 · ??????????" ? verbatim token + middle-dot preserved, "indexed" => ??????????. Good.

****demo.detected/found/resultTitle/resultSub****: resultTitle keeps "18 min" ? good. All fine.

****how.kicker****: "???? ???? ???? ??????????" for "What it does today" ? fine.

****how.title****: en "A full match, turned into rallies you can search" / kn fine.

****how.intro****, ****how.indexed****, ****how.deadtime****, ****how.reuse.body**** ("?????????" for process, but title uses ... let me check), ****how.stitch****: Let me scrutinize reuse and stitch.

****how.reuse.title****: en "Process once, reuse" / kn "????? ??????????, ??????". Note: elsewhere in the file "process" is consistently translated as ?????????????? (ingest.title, build.noVideo, mode.demo). Here reuse.title uses ?????????? ? a vocabulary inconsistency, but "process" isn't in my mandated domain-vocab list. This is borderline; the body also uses "?????????" (re-running). I'll be conservative ? it's a real internal inconsistency for "process," but not in the hard vocab list. I'll flag it lightly... Actually the instruction says flag vocabulary inconsistency. ?????????? vs the site-wide ?????????????? is a genuine inconsistency. I'll flag the title.

The dominant real error is ctaReel. Let me finalize.

site.hero.ctaReel ?????????? ???? + ?????? ???? "????????? ?????" is unnatural for "see it in action"; ?????????? is the idiomatic rendering
site.how.reuse.title ?????? ?????????????????, ??????? "process" is rendered ????????????????? everywhere else on the site (ingest/build/mode); ?????????? here is inconsistent
===END===
agentId: a66fcbcaa0ab0dce9 (use SendMessage with to: 'a66fcbcaa0ab0dce9' to continue this agent)
<usage>subagent_tokens: 63071
tool_uses: 2
duration_ms: 33933</usage>

56. user (2026-06-22T04:01:50.934Z)

I have both files. Now I'll review the 21 specified keys carefully, comparing each hi value against its en source for mistranslation, grammar/agreement, register, vocabulary consistency, and the hard constraints.

Let me work through them:

****site.hero.ctaReel****: en "See it in action + a real reel" / hi "??? ??? ???? ????? + ?? ????? ??" ? fine.

****site.hero.note****: en "A phone or GoPro on a tripod is all you need. No special hardware." / hi "????? ?? ?? ???? ?? GoPro ?? ?????? ??? ??? ???? ?????????? ??????" ? fine. Note: uses "?" danda (good). "?????" for tripod is fine.

****site.hero.loop.step1****: en "1. Auto-index rallies" / hi "1. ?????? ?????-?? ??????" ? preserved, fine.

****step2****: "2. ????? ??? ????? ??" ? fine. ****step3****: "3. ???? ??? ?????? ??????" ? fine.

****site.hero.demo.fileTag****: en "match_2026.mp4 · indexed" / hi "match_2026.mp4 · ?????? ????
 ??? ? verbatim token + middle dot preserved. Fine.

****site.hero.demo.detected****: en "Rallies detected" / hi "?????? ???? ? acceptable.

****site.hero.demo.found****: en "44 found" / hi "44 ????? ? digit preserved, fine.

****site.hero.demo.resultTitle****: en "Highlight reel · 44 rallies · 18 min" / hi "?????? ???? · 44
 ?????? · 18 min" ? middle dots, digits, "min" all preserved. Fine.

****site.hero.demo.resultSub****: en "dead time removed · ready to download" / hi "????? ??? ?????
 ??? · ?????? ?? ??? ????? ? fine.

****site.how.kicker****: en "What it does today" / hi "?? ?? ???? ???? ?" ? fine.

****site.how.title****: en "A full match, turned into rallies you can search" / hi "?? ???? ???,
 ???? ?? ???? ???? ?????? ??? ????? ? fine.

****site.how.intro****: en "Upload a whole session or match. KhelSutra does the rest ? no editing
 skill needed." / hi "???? ???? ?? ??? ????? ?????? ????? ??? KhelSutra ???? ?? ? ??? ?????? ????
 ???? ????? ? em-dash preserved, "????" consistent. Fine.

****site.how.indexed.title/body****, ****deadtime.title/body****, ****reuse.title/body****,
****stitch.title/body**** ? checking carefully now. Let me examine the two notable issues I see.

Now let me note the genuine errors I found:

1. ****site.hero.title**** is NOT in my review list ? skip.
2. ****site.how.reuse.body****: en "Come back later to watch or download your reel." / hi "???? ????
 ????? ? ? ?????? ???? ???? ???? ???? ???? ?" ? This has a grammar error: "?????? ???? ???? ?" is
 missing the postposition. It should be "?????? ???? ? ???? ???? ???? ???? ?" ? the "?? ??"
 (purpose) is dropped, making it ungrammatical/awkward. The parallel "???? ? ? ?????? ???? ?
 ??".

Let me verify the rest don't have issues and finalize. All hard constraints (verbatim tokens,
 digits, dots, dashes, tags, nukta forms, danda) appear intact across the reviewed keys. The
 only genuine error is the dropped postposition in reuse.body.

site.how.reuse.body ???? ???? ???? ? ? ?????? ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
 ?????? ???? ? ? ? ? ?????? ? ? ???? ? ? ???? ???? ???? ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
 postposition "?? ??" makes "???? ???? ??" ungrammatical; parallel purpose phrase needs "?? ??"
 ===END===
 agentId: a3d313305c1df0dd4 (use SendMessage with to: 'a3d313305c1df0dd4' to continue this agent)
 <usage>subagent_tokens: 49628
 tool_uses: 2
 duration_ms: 23908</usage>

57. user (2026-06-22T04:02:04.620Z)

Both files read. Reviewing the 21 keys against the domain vocabulary and hard constraints. Let
 me work through each.

Key findings:

****site.hero.loop.step1****: en is "Auto-index rallies" (imperative-ish process label, no definite
 article ? "rallies" generic). da has "Auto-indeksér duellerne" (definite "the rallies").
 step2/step3 don't use definite forms ("Død tid fjernet", "Download din reel"). The English step1
 is "rallies" (indefinite/generic), matching the chip-strip register of the other two steps. The
 definite "duellerne" is an over-specification inconsistent with the source's generic "rallies".
 This is a real mismatch ? should be "dueller" (generic), mirroring step2's generic "Død tid".

Let me verify the rest carefully ? checking the demo card and how.* section. Everything else:
 hero.note (GoPro verbatim kept, natural), demo.fileTag (match_2026.mp4 · indekseret ? verbatim +
 indeksér family correct, middle-dot kept), demo.detected/found/resultTitle/resultSub (44/18/min

digits kept, død tid + dueller + Highlights-reel + middle-dots all correct), how.* section (kicker/title/intro/cards all use duel/dueller, død tid, MP4, "Generated by Khelsutra.guru" verbatim, em-dashes and curly quotes preserved).

The only genuine error is step1's unwarranted definite form. Note step1 also has a verb ("Auto-indeksér" imperative) while en is a noun phrase, but step2 ("Død tid fjernet" = passive) and step3 ("Download din reel" = imperative) are already mixed, so the verb form is acceptable register; the definite-article over-translation is the one substantive inconsistency.

```
site.hero.loop.step1    <b>1.</b> Auto-indeksér dueller Definite "duellerne" over-specifies vs.
generic "rallies"; matches generic register of step2/step3
===END===
agentId: a48e59ce8ff220e8a (use SendMessage with to: 'a48e59ce8ff220e8a' to continue this agent)
<usage>subagent_tokens: 45718
tool_uses: 2
duration_ms: 17831</usage>
```

58. user (2026-06-22T04:02:16.484Z)

I have both files. Now let me carefully review each of the 21 keys, comparing the Indonesian draft against the English source and checking against the domain vocabulary and hard constraints.

Let me work through them systematically:

****site.hero.ctaReel**:** en "See it in action + a real reel" ? id "Lihat langsung + reel sungguhan". Natural, "reel" kept. Fine.

****site.hero.note**:** en "A phone or GoPro on a tripod is all you need. No special hardware." ? id "Cukup sebuah ponsel atau GoPro di atas tripod. Tanpa perangkat keras khusus." Fine, GoPro verbatim kept.

****site.hero.loop.step1/2/3**:** `<b>1.</b> Auto-index rallies` ? `<b>1.</b> Indeks reli otomatis`. Tags preserved, "reli". Fine. step2 "Waktu kosong dihapus", step3 "Unduh reel-mu". Fine.

****site.hero.demo.fileTag**:** "match_2026.mp4 · indexed" ? "match_2026.mp4 · terindeks". Verbatim token + middot kept. Fine.

****site.hero.demo.detected**:** "Rallies detected" ? "Reli terdeteksi". Fine.

****site.hero.demo.found**:** "44 found" ? "44 ditemukan". Number kept. Fine.

****site.hero.demo.resultTitle**:** "Highlight reel · 44 rallies · 18 min" ? "Reel sorotan · 44 reli · 18 min". Numbers, "min", middots all kept. "reel sorotan" matches. Fine.

****site.hero.demo.resultSub**:** "dead time removed · ready to download" ? "waktu kosong dihapus · siap diunduh". Fine.

****site.how.kicker**:** "What it does today" ? "Apa yang dilakukannya hari ini". Fine.

****site.how.title**:** "A full match, turned into rallies you can search" ? "Satu pertandingan penuh, diubah menjadi reli yang bisa kamu cari". Fine.

****site.how.intro**:** "Upload a whole session or match. KhelSutra does the rest ? no editing skill needed." ? "Unggah satu sesi atau pertandingan penuh. KhelSutra melakukan sisanya ? tanpa perlu keahlian mengedit." Fine.

****site.how.indexed.title/body**:** Fine.

****site.how.deadtime.title/body**:** "Knock-ups, walks, picking up the shuttle, the gaps between points" ? "Pemanasan, momen jalan-jalan, memungut kok, jeda antar-poin". "kok" used correctly. Fine.

****site.how.reuse.title/body**:** Fine.

```
**site.how.stitch.title/body**: "Stitched reel + summary" ? "Reel gabungan + ringkasan".  
Verbatim "Generated by Khelsutra.guru" + curly quotes kept. Fine.
```

All 21 keys check out against the constraints and vocabulary. The translations are consistent, natural, register-appropriate (informal "kamu"/"-mu"), tags/tokens/numbers/punctuation all preserved, and domain vocabulary matches (reli, reel, reel sorotan, waktu kosong, kok, terindeks, unduh, sesi, pertandingan, pemanasan).

No real errors found across the 21 reviewed keys.

===END===

```
agentId: a41d860d86c150944 (use SendMessage with to: 'a41d860d86c150944' to continue this agent)
<usage>subagent_tokens: 47104
tool_uses: 2
duration_ms: 19646</usage>
```

59. assistant (2026-06-22T04:02:57.661Z)

The adversarial pass returned ****4 conservative, well-grounded revisions**** (es and id came back clean):

```
- **kn** `hero.ctaReel` : ?????????? ? ???????????? ("in action" reads more idiomatically)
- **kn** `how.reuse.title` : ?????????? ? ????????????????? (matches how "process" is rendered elsewhere in the catalog)
- **hi** `how.reuse.body` : restore dropped postposition ?? ??? (grammar)
- **da** `hero.loop.step1` : duellerne ? dueller (generic, matching step2/3 register; `b` intact)
```

All four are legitimate. Let me apply them via a script (stable JSON round-trip), re-mirror, and re-run the structural check:

60. user (2026-06-22T04:03:05.788Z)

```
kn site.hero.ctaReel
- ?????????? ???? + ?????? ???
+ ??????????? ???? + ?????? ???

kn site.how.reuse.title
- ????? ??????????, ???????
+ ????? ?????????????????, ???????

hi site.how.reuse.body
- ???? ?? ????? ?? ??????? ???? ?? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ????
??? ???? ?? ???? ???? ????? ????? ???? ???? ??
+ ???? ?? ????? ?? ??????? ???? ?? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ???? ????
???????? ?? ???? ?? ???? ???? ???? ???? ???? ???? ???? ???? ????
da site.hero.loop.step1
- <b>1.</b> Auto-indeksér duellerne
+ <b>1.</b> Auto-indeksér dueller
```

```
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

61. assistant (2026-06-22T04:03:13.453Z)

Let me re-run the structural verification after the revisions, and confirm the kn "process" term now matches elsewhere in the catalog:

62. user (2026-06-22T04:03:23.146Z)

```
STRUCTURAL RE-CHECK: PASS
kn uses ?????????????? elsewhere: true | occurrences: 8
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

63. assistant (2026-06-22T04:04:20.718Z)

Structural re-check passes and the kn `????????????` consistency is confirmed (8 occurrences). Now let me **extend the guard tests** to explicitly cover the new keys, as the task requires. First the assets test (HTML?en wiring):

64. user (2026-06-22T04:04:34.801Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/src/assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

65. assistant (2026-06-22T04:04:36.918Z)

Now the shim test (real translations across locales):

66. user (2026-06-22T04:04:48.889Z)

The file C:/Users/avidu/Projects/khelsutra-wt-hero/site/src/i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

67. assistant (2026-06-22T04:04:53.236Z)

Now let me run the full **site** test suite (`node --test`) to validate the wiring, drift guards, and the new tests:

68. user (2026-06-22T04:04:56.776Z)

```
? toRow rejects invalid enum values (0.249ms)
? handleRequest inserts a valid submission via the store (51.3925ms)
? handleRequest drops a bot without inserting (1.5217ms)
? handleRequest rejects a bad email with 400 (1.271ms)
? handleRequest rejects invalid JSON with 400 (1.1907ms)
? d1Store issues the bound INSERT (Cloudflare path) (0.659ms)
? sqliteStore persists a real row (node:sqlite round-trip ? the VM path) (8.7394ms)
? fetch routes: POST /api hits the handler, other paths delegate to ASSETS (2.5018ms)
? fetch rejects non-POST to the API with 405 (1.1285ms)
? buildSubmissionEmail summarizes the submission (0.798ms)
? handleRequest notifies on a valid submission; a notify failure never breaks it (1.35ms)
? handleRequest does NOT notify on a bot or a bad email (0.8819ms)
? site/public/locales mirrors repo-root /locales exactly (else: npm run copy:locales)
(15.9108ms)
? [VM host] server.js serves the form (267.745ms)
? [VM host] serves /capture and /og.png (9.1868ms)
? [VM host] serves the tool screencast as video/mp4 (plays in the post-signup reveal) (4.7923ms)
? [VM host] serves /own-model (12.1236ms)
? [VM host] serves the academy flyers (/flyer, /flyer-kn, /flyer-hi) as clean URLs (13.705ms)
? [VM host] POST /api/request-access persists to SQLite (19.1356ms)
? [VM host] honeypot + bad email are rejected without persisting (5.8354ms)
? [VM host] GET /api/request-access -> 405 (1.8578ms)
? [VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page (3.2471ms)
? [VM host · N8] ?lang= overrides the browser language (2.8783ms)
? [VM host · N8] the persisted cookie beats Accept-Language (returning user keeps their choice)
(2.8579ms)
? [VM host · N8] unsupported/absent language falls back to en (never a locale we can't serve)
(3.5229ms)
? [VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages negotiate)
(1.8419ms)
? [VM host] serves the shared catalogs the shim fetches (/locales/*/common.json as JSON)
(3.3308ms)
? submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?') (429.5977ms)
? on failure the button is restored ? never stuck on a frozen 'Sending?' (92.7733ms)
? after sign-up BOTH videos appear and a ? closes the reveal (75.1085ms)
? A2: after sign-up the reveal offers a WhatsApp share of the reel (wa.me, safe, localizable)
(62.8604ms)
? the auto-close HOLDS while the reel is playing (no mid-watch cut-off) (52.6057ms)
? tests 81
```

```
? suites 0
? pass 81
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 2550.2917
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

69. assistant (2026-06-22T04:05:02.621Z)

All 81 site tests pass (drift guard, locales-mirror, and the new hero/#how tests included). Now the ****web**** suite ? the SPA bundles the same ``/locales`` catalogs, so its i18n hygiene tests (key/placeholder parity) must stay green. Let me check its scripts and run them:

70. user (2026-06-22T04:05:03.715Z)

```
{
  "dev": "vite",
  "build": "vite build",
  "preview": "vite preview",
  "typecheck": "tsc --noEmit",
  "test": "vitest run",
  "test:coverage": "vitest run --coverage"
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

71. user (2026-06-22T04:05:10.940Z)

```
===== TYPECHECK =====

> khelsutra-web@0.0.0 typecheck
> tsc --noEmit
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

72. assistant (2026-06-22T04:05:14.279Z)

Typecheck clean. Now the web test suite with coverage, plus the production build (independent ? run in parallel):

73. user (2026-06-22T04:05:27.067Z)

```
Test Files  23 passed (23)
   Tests    215 passed (215)
   Start at 09:35:17
   Duration 9.19s (transform 2.01s, setup 515ms, collect 13.97s, tests 9.41s,
environment 49.02s, prepare 8.90s)
```

% Coverage report from v8

File	% Stmts	% Branch	% Funcs	% Lines	Uncovered Line #s
All files	93.39	88.12	85.88	93.39	
src	74.89	78.04	25	74.89	
App.tsx	74.89	78.04	25	74.89	...10-215,242-244
src/api	98.1	89.36	100	98.1	
client.ts	98.1	89.36	100	98.1	174-176
src/components	98.47	90.72	86.36	98.47	
...ileResult.tsx	100	100	100	100	
IngestPanel.tsx	95.48	90.9	66.66	95.48	40-42,44-46
...eSwitcher.tsx	100	83.33	100	100	27
QueryBar.tsx	100	88.88	100	100	30
RallyGrid.tsx	98.11	73.33	50	98.11	42
...ionFooter.tsx	100	100	100	100	

StatusChip.tsx		100		100		100		100	
TapFilters.tsx		100		100		100		100	
src/hooks		92.89		76.92		100		92.89	
useIngestJob.ts		92.52		78.57		100		92.52	...08-110,141-142
...ySelection.ts		100		83.33		100		100	9
useUpload.ts		91.8		70.58		100		91.8	76-78,82-83
src/i18n		100		25		100		100	
index.ts		100		25		100		100	72-76
src/lib		97.22		94.61		100		97.22	
errorText.ts		100		100		100		100	
errors.ts		100		100		100		100	
floor.ts		100		100		100		100	
format.ts		100		100		100		100	
log.ts		81.81		87.5		100		81.81	13-14
query.ts		97.07		93.45		100		97.07	...95,284,286,288
selection.ts		100		92.3		100		100	30
----- ----- ----- ----- ----- ----- ----- ----- ----- -----									

==== Coverage summary =====

Statements : 93.39% (1286/1377)

Branches : 88.12% (371/421)

Functions : 85.88% (73/85)

Lines : 93.39% (1286/1377)

=====

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

74. user (2026-06-22T04:05:30.359Z)

vite v6.4.3 building for production...

transforming...

? 95 modules transformed.

rendering chunks...

computing gzip size...

dist/index.html

0.40 kB ? gzip: 0.27 kB

dist/assets/noto-sans-devanagari-latin-ext-wght-normal-CLkupaxV.woff2

13.85 kB

dist/assets/noto-sans-kannada-latin-ext-wght-normal-MdBBF41x.woff2

13.99 kB

dist/assets/noto-sans-devanagari-latin-wght-normal-Bxfr4UJH.woff2

25.38 kB

dist/assets/noto-sans-kannada-latin-wght-normal-DeLZCgFT.woff2

27.58 kB

dist/assets/noto-sans-kannada-kannada-wght-normal-DuwB-P8d.woff2

90.80 kB

dist/assets/noto-sans-devanagari-devanagari-wght-normal-DWI_L5Cu.woff2

121.19 kB

dist/assets/index-CVZz_zrZ.css

25.22 kB ? gzip: 5.47 kB

dist/assets/index-xzgkz5qK.js

474.21 kB ? gzip: 145.06 kB

? built in 1.44s

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

75. assistant (2026-06-22T04:05:46.277Z)

All green: **web 215 tests pass** (i18n hygiene/key-parity included), typecheck clean, coverage 93.39% stmts / 88.12% branch, and the production build succeeds. Since my change only adds catalog JSON (bundled data, not executed code), coverage is unaffected. Let me confirm the coverage floor and the CI gate so I've matched it exactly, and check for any lint step:

76. user (2026-06-22T04:05:48.938Z)

=== web vitest coverage thresholds ===

(no explicit thresholds in vitest config)

=== site package.json scripts ===

```
{
  "test": "node --test",
  "test:cf": "node --test src/index.test.js",
  "test:vm": "node --test src/server.test.js",
  "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
  "copy:locales": "node scripts/copy-locales.mjs",
  "predeploy": "node scripts/copy-locales.mjs",
  "deploy": "wrangler deploy",
  "dev": "wrangler dev",
  "og": "python make_og.py"
}
```

=== CI workflows ===

parity.yml

test.yml

Shell cwd was reset to C:\Users\avidu\Projects\kheldutra

77. user (2026-06-22T04:05:52.739Z)

```
1     name: test
2     on:
3       push:
4         branches: [master]
5       pull_request:
6
7     jobs:
8       site:
9         runs-on: ubuntu-latest
10        defaults:
11          run:
12            working-directory: site
13        steps:
14          - uses: actions/checkout@v4
15          - uses: actions/setup-node@v4
16          with:
17            node-version: "24" # node:sqlite is unflagged; server.test.js boots the VM
host
18            cache: "npm"
19            cache-dependency-path: site/package-lock.json
20            # jsdom is a TEST-ONLY devDep (the behavioral landing-page UX tests run the real
inline
21            # script in a DOM); the Cloudflare Worker + VM-host RUNTIMES stay dependency-free.
`npm test`
22            # runs ALL paths: Worker+D1 logic (index.test.js), the booted VM host
(server.test.js), the
23            # static content contract (assets.test.js), and the UX behaviour (ux.dom.test.js).
24            - run: npm ci
25            - run: npm test
26            # Syntax-check the ops shell scripts (provision/teardown/smoke/parity) so a broken
27            # script can't ship to the runbook. `bash -n` parses without executing.
28            - name: shell scripts parse-check
29              run: for f in scripts/*.sh; do echo "checking $f"; bash -n "$f"; done
30
31        web:
32          # Operator-console SPA (web/): typecheck + unit tests (with a coverage floor) +
production build
33          # gate the merge. `test:coverage` fails if coverage drops below the thresholds in
vite.config.ts,
34          # so a merge can't silently regress test coverage.
35          runs-on: ubuntu-latest
36          defaults:
37            run:
```

```

38         working-directory: web
39     steps:
40     - uses: actions/checkout@v4
41     - uses: actions/setup-node@v4
42       with:
43         node-version: "24"
44         cache: "npm"
45         cache-dependency-path: web/package-lock.json
46     - run: npm ci
47     - run: npm run typecheck
48     - run: npm run test:coverage
49     - run: npm run build
50

```

78. user (2026-06-22T04:05:52.950Z)

```

1      # Live-host parity ? the site runs on TWO hosts (Cloudflare Worker + the DO droplet's
2      # Node/SQLite twin) that must serve byte-identical pages. The unit suite proves the code
3      # works on each host; it CANNOT see that the two LIVE URLs have drifted (e.g. a merge
4      # auto-deployed Cloudflare but the droplet wasn't re-synced from git). This runs the
5      # existing scripts/parity-check.sh against both live URLs on a schedule ? NOT on PRs, so
6      # it never blocks development; a failure surfaces real production drift to the owner.
7      name: live-parity
8
9      on:
10         schedule:
11         - cron: "17 6 * * *" # daily ~06:17 UTC
12         workflow_dispatch: {} # and on demand
13
14      # Avoid overlapping runs if a manual dispatch races the cron.
15      concurrency:
16         group: live-parity
17         cancel-in-progress: false
18
19      jobs:
20         parity:
21             runs-on: ubuntu-latest
22             steps:
23             - uses: actions/checkout@v4
24             - name: Compare the two live hosts byte-for-byte
25               env:
26                 CF_URL: https://khelsutra.guru
27                 VM_URL: http://168.144.126.176:8787
28             run: bash site/scripts/parity-check.sh
29

```

79. assistant (2026-06-22T04:06:02.016Z)

The CI gate is exactly what I've run (site: `node --test` + shell parse-check; web: typecheck + test:coverage + build). Let me confirm the web coverage floor value to verify I'm at/above it per the pre-LGTM gate, and confirm no shell scripts were touched:

80. user (2026-06-22T04:06:04.688Z)

```

=== coverage thresholds (vite.config.ts) ===
23:    // Coverage floor (CI runs `npm run test:coverage`): a merge can't DROP coverage below
these
24:    // thresholds, so untested new code is caught. `all` counts every source file (not only
the ones a
27:    coverage: {
39:    // Floor set just below current (stmts/lines 93.3, branches 88.1, funcs 85.9) ? a real
ratchet
41:    // coverage grows. (functions stays a touch looser: App.tsx is the engine-orchestrating
shell,

```

```
43:     thresholds: {
44:         statements: 92,
45:         branches: 87,
46:         functions: 84,
47:         lines: 92,
```

=== changed files vs origin/master ===

```
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/src/assets.test.js
M site/src/i18n.shim.test.js
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

81. assistant (2026-06-22T04:06:31.438Z)

Coverage floor is statements 92 / branches 87 / functions 84 / lines 92 ? my run (93.39 / 88.12 / 85.88 / 93.39) clears all four, and adding catalog JSON + tests doesn't regress it. The diff is exactly the 15 expected files (6 catalogs, the mirrored 6, index.html, 2 test files); temp scripts cleaned up, no stray untracked files.

Now let me prove the localization renders end-to-end (not just that keys exist) by driving the **real** shim's `applyDom` over the **real** page for the `kn` locale:

82. user (2026-06-22T04:06:44.595Z)

===== rendered as kn =====

```
hero.ctaReel : ?????????? ??? + ?????? ???
loop.step1   : <b>1.</b> ???????? ?????-???
loop.step2   : <b>2.</b> ???????? ??? ??????????????
demo.fileTag : match_2026.mp4 · ??????????
demo.result  : ?????? ??? · 44 ?????????? · 18 min
how.title    : ????? ??????????, ??? ?????????? ??????????
how.deadtime : ?????????? ??? ??????????????
how.stitch   : ????? ?????? ?????????? ??? ?????????? ??? MP4 ???????? ? ???-??? ??????
????? ??? ???? ?Generated by Khelsutra.guru? ??????????????.
```

===== rendered as es =====

```
hero.ctaReel : Míralo en acción + un reel real
loop.step1   : <b>1.</b> Indexa las jugadas automáticamente
loop.step2   : <b>2.</b> Tiempo muerto eliminado
demo.fileTag : match_2026.mp4 · indexado
demo.result  : Reel destacado · 44 jugadas · 18 min
how.title    : Un partido completo, convertido en jugadas que puedes buscar
how.deadtime : Tiempo muerto eliminado
how.stitch   : Tu selección se convierte en un único MP4 para descargar y compartir ? con un resumen del tiempo de juego y una pequeña marca ?Generated by Khelsutra.guru?.
```

ASCII-only (untranslated?) wired keys under kn: none ?

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

83. assistant (2026-06-22T04:06:59.787Z)

End-to-end render confirmed: every hero + `#how` string renders in Kannada and Spanish with

`<b>` markers and literal tokens (match_2026.mp4, 18 min, MP4, the watermark) intact, and ****zero untranslated ASCII leaks**** among the wired keys. The shim swaps innerHTML for the rich chips and textContent for plain keys correctly.

All gates are green. Let me commit ? first re-verifying branch safety (fetch, confirm base, stage explicit paths only):

84. user (2026-06-22T04:07:04.798Z)

```
branch: feat/site-hero-mockup-i18n
HEAD:   cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6
languages) (#87)
origin/master: 7ae9cee feat(web): P2c first-run setup wizard (3 steps from /api/capabilities, 6
languages) (#88)
--- is origin/master an ancestor of HEAD? (expect: yes once committed; now base==HEAD) ---
ancestor: NO (HEAD has no commits yet ? expected)
```

85. assistant (2026-06-22T04:07:33.488Z)

origin/master moved to ****7ae9cee (#88, the P2c web setup wizard ? "6 languages")**** while I worked. Per the shared-checkout concurrency discipline, I must not let my branch (based on #87) silently clobber #88 ? especially since #88 touts "6 languages" and may have added keys to the ****shared catalogs**** I rewrote. Let me check exactly what #88 changed before committing:

86. user (2026-06-22T04:07:35.810Z)

```
=== #88 (cf59fbf..7ae9cee) changed files ===
locales/da/common.json          | 32 ++++++
locales/en/common.json          | 32 ++++++
locales/es/common.json          | 32 ++++++
locales/hi/common.json          | 32 ++++++
locales/id/common.json          | 32 ++++++
locales/kn/common.json          | 32 ++++++
site/public/locales/da/common.json | 32 ++++++
site/public/locales/en/common.json | 32 ++++++
site/public/locales/es/common.json | 32 ++++++
site/public/locales/hi/common.json | 32 ++++++
site/public/locales/id/common.json | 32 ++++++
site/public/locales/kn/common.json | 32 ++++++
web/src/App.tsx                 | 9 +-
web/src/api/client.ts           | 6 ++
web/src/api/types.ts            | 17 +++
web/src/components/SetupWizard.test.tsx | 127 ++++++
web/src/components/SetupWizard.tsx | 179 ++++++
web/src/components/a4.touch.test.tsx | 4 +
web/src/i18n/hygiene.test.ts    | 1 +
19 files changed, 726 insertions(+), 1 deletion(-)
```

=== did #88 touch my contention paths? ===

```
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
```

87. assistant (2026-06-22T04:08:42.339Z)

Confirmed the contention: ****#88 added 32 lines to every shared catalog**** (a setup-wizard namespace for the SPA) ? both ``/locales`` and the mirrored ``site/public/locales``. My branch is based on #87, so merging as-is risks the exact squash-clobber incident the concurrency rule warns about. I'll commit, then ****rebase onto origin/master****, regenerating the catalogs on top of #88's so both key sets survive.

First, commit my work (explicit paths only):

88. user (2026-06-22T04:08:45.489Z)

```
=== staged (must be exactly 15) ===
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/public/index.html
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
site/src/assets.test.js
site/src/i18n.shim.test.js
count: 15
```

89. assistant (2026-06-22T04:08:48.284Z)

Exactly 15 staged. Now commit:

90. user (2026-06-22T04:08:58.687Z)

db9d592 feat(site): localize the hero demo mockup + #how feature block (6 languages)

91. assistant (2026-06-22T04:09:02.098Z)

Committed (db9d592). Now rebase onto origin/master (7ae9cee, with #88). I expect the 12 catalog files to conflict:

92. user (2026-06-22T04:09:03.482Z)

Rebasing (1/1)

Successfully rebased and updated refs/heads/feat/site-hero-mockup-i18n.

--- rebase status ---

93. assistant (2026-06-22T04:09:15.394Z)

Rebase auto-merged without conflict ? but an auto-merged JSON can be subtly wrong, so I must ****verify**** both key sets survived intact and the files are valid. Let me check the rebased catalogs hold both #88's wizard keys and my hero/#how keys, and that the mirror is in sync:

94. user (2026-06-22T04:09:25.223Z)

```
=== commits on top of origin/master (must be ONLY mine) ===
317b245 feat(site): localize the hero demo mockup + #how feature block (6 languages)
```

```
=== what keys did #88 add? (top-level diff of en) ===
origin/master en top-level keys: app, lang, bulk, mode, query, grid, footer, result, build,
ingest, errors, tap, site, wizard, selection
```

```
=== validate rebased catalogs: valid JSON + my keys + #88 keys present ===
```

```
en: valid ? | mine ?:true | top-level keys:15
kn: valid ? | mine ?:true | top-level keys:15
hi: valid ? | mine ?:true | top-level keys:15
es: valid ? | mine ?:true | top-level keys:15
da: valid ? | mine ?:true | top-level keys:15
id: valid ? | mine ?:true | top-level keys:15
```

CATALOG MERGE: OK

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

95. assistant (2026-06-22T04:09:41.720Z)

Clean rebase: only my commit (317b245) sits on origin/master, #88's `wizard` namespace survived in all 6 catalogs, my keys are present, all valid JSON. The auto-merge worked because #88's `wizard` is a top-level key (between `site` and `selection`) while mine nest inside `site`.

Now I must re-verify the mirror is consistent and re-run the **full suites on the rebased tree** (which now includes #88's SetupWizard + the hygiene test). First confirm the mirror didn't drift in the merge:

96. user (2026-06-22T04:09:43.949Z)

=== git status after copy:locales (empty = mirror already consistent) ===

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

97. assistant (2026-06-22T04:09:50.572Z)

Mirror is consistent (clean working tree). Now re-run the **full gate on the rebased tree** (now including #88's SetupWizard + hygiene test). Site suite + web typecheck in parallel:

98. user (2026-06-22T04:09:54.071Z)

```
? tests 81
? suites 0
? pass 81
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 2326.9061
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

99. user (2026-06-22T04:09:57.463Z)

> khelsutra-web@0.0.0 typecheck

> tsc --noEmit

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

100. assistant (2026-06-22T04:10:00.169Z)

Site 81/81 pass, web typecheck clean on the rebased tree. Now web tests-with-coverage + build (includes #88's SetupWizard tests + the hygiene parity check against my new keys):

101. user (2026-06-22T04:10:12.532Z)

? src/i18n/hygiene.test.ts (29 tests)

80ms

Test Files 24 passed (24)

Tests 223 passed (223)

File	% Stmts	% Branch	% Funcs	% Lines	Uncovered Line #s
------	---------	----------	---------	---------	-------------------

===== Coverage summary =====

Statements	: 93.84% (1434/1528)
------------	------------------------

Branches	: 88.53% (417/471)
----------	----------------------

Functions	: 86.31% (82/95)
-----------	--------------------

Lines : 93.84% (1434/1528)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

102. user (2026-06-22T04:10:15.554Z)

```
dist/assets/index-BcE6Y0gS.css
26.09 kB ? gzip: 5.63 kB
dist/assets/index-C6Kg34ok.js
489.62 kB ? gzip: 149.60 kB
? built in 1.39s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

103. assistant (2026-06-22T04:10:26.454Z)

Full rebased gate is green: ****web 223 tests**** (24 files, includes #88's SetupWizard + the 29-test hygiene parity check validating all 6 locales hold both #88's wizard keys and my hero/#how keys), coverage 93.84/88.53/86.31/93.84 (all above the 92/87/84/92 floor), build succeeds, and site 81/81.

Let me do a final fetch (the repo churns fast) to confirm origin/master hasn't moved again, then push and open the PR:

104. user (2026-06-22T04:10:30.906Z)

```
origin/master now: 7ae9cee feat(web): P2c first-run setup wizard (3 steps from
/api/capabilities, 6 languages) (#88)
my HEAD: 317b245 feat(site): localize the hero demo mockup + #how feature block (6 languages)
--- only my commit on top of origin/master? ---
317b245 feat(site): localize the hero demo mockup + #how feature block (6 languages)
--- diff touches ONLY my 15 files? ---
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/public/index.html
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
site/src/assets.test.js
site/src/i18n.shim.test.js
```

105. assistant (2026-06-22T04:10:35.370Z)

origin/master is stable at #88, my branch is exactly one commit touching exactly my 15 files ?
no sibling work leaked in. Pushing and opening the PR:

106. user (2026-06-22T04:10:38.785Z)

```
remote:
remote: Create a pull request for 'feat/site-hero-mockup-i18n' on GitHub by visiting:
remote: https://github.com/avidullu/khelsutra/pull/new/feat/site-hero-mockup-i18n
remote:
branch 'feat/site-hero-mockup-i18n' set up to track 'origin/feat/site-hero-mockup-i18n'.
To https://github.com/avidullu/khelsutra.git
* [new branch] feat/site-hero-mockup-i18n -> feat/site-hero-mockup-i18n
```

107. user (2026-06-22T04:11:02.761Z)

<https://github.com/avidullu/khelsutra/pull/89>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

108. assistant (2026-06-22T04:11:13.307Z)

PR opened: ****[khelsutra#89](https://github.com/avidullu/khelsutra/pull/89)****. Let me confirm CI picked it up, and update the session handoff (a pushed PR is a meaningful checkpoint per the working agreement):

109. user (2026-06-22T04:11:22.112Z)

=== PR mergeability + checks ===

state=OPEN mergeable=MERGEABLE mergeState=UNSTABLE

web pending 0

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972638>

Workers Builds: hidden-king-khelsutra pass 0

<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/0d1a8b62-92c8-4f7c-80a3-6eea5ba4fd16>

site pass 12s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972620>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

110. assistant (2026-06-22T04:11:34.868Z)

PR is ****MERGEABLE****; CI shows ****site: pass****, ****Workers build: pass****, ****web: pending**** (running). Let me update the session handoff while web CI finishes:

111. user (2026-06-22T04:11:37.157Z)

The file C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

112. user (2026-06-22T04:11:46.315Z)

The file C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

113. assistant (2026-06-22T04:11:48.550Z)

Now let me confirm web CI finished green:

114. user (2026-06-22T04:12:03.808Z)

Workers Builds: hidden-king-khelsutra pass 0

<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/0d1a8b62-92c8-4f7c-80a3-6eea5ba4fd16>

site pass 12s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972620>

Workers Builds: hidden-king-khelsutra pass 0

<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/0d1a8b62-92c8-4f7c-80a3-6eea5ba4fd16>

site pass 12s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972620>

web pass 45s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972638>

Workers Builds: hidden-king-khelsutra pass 0

<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/0d1a8b62-92c8-4f7c-80a3-6eea5ba4fd16>

site pass 12s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972620>

web pass 45s

<https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972638>


```
--- final mergeability ---
mergeable=MERGEABLE mergeState=CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

115. assistant (2026-06-22T04:12:20.834Z)

All CI checks are green and the PR is **CLEAN / MERGEABLE**:

- **site** ? (12s) ? drift guards, mirror check, new hero/#how tests
- **web** ? (45s) ? 223 tests incl. 6-locale i18n hygiene parity, coverage above floor, build
- **Workers build** ?

Done ? PR [khelsutra#89](https://github.com/avidullu/khelsutra/pull/89)

What shipped. The home page hero **demo mockup** and the **#how** "What it does today" feature block were hardcoded English (rendering English in kn/hi/es/da/id). I wired both through the i18n shim:

- **Hero** ([index.html](site/public/index.html)): the "See it in action" CTA, the *phone/GoPro* note, the **3** process chips (``data-i18n-html``, ``<b>n.</b>`` preserved), and the **reel-card demo mockup** (file tag, "Rallies detected" + count, result title/sub).
- **#how**: section head (kicker/title/intro) + all **4** feature cards ? the scope you confirmed (line 329's "Dead time removed" lives here).
- **21 new keys** across all 6 catalogs. **en** derived byte-for-byte from the wired DOM (drift guard stays green); **kn/hi/es/da/id** translated on the shipped vocabulary (rally = `?????/????/jugada/duel/reli`; **reel** kept; brand/tokens/numbers literal; inline ``<b>`` preserved).

Process discipline followed.

- **Isolated worktree** branched from ``origin/master``; staged explicit paths only; ``git log origin/master..HEAD`` is exactly my one commit touching exactly 15 files.
- **AI-draft ? adversarial per-locale review ? revise**: 5 native-reviewer passes surfaced 4 conservative fixes (kn idiom + "process"-term consistency, hi dropped postposition, da generic plural) ? applied.
- **Concurrency save**: ``origin/master`` advanced to **#88** mid-task (which added a ``wizard.*`` catalog namespace to the same 6 shared catalogs). I rebased onto it and verified the merged catalogs hold **both** #88's keys and mine ? avoiding the squash-clobber the project's concurrency rule warns about.
- **Verified locally to match CI**, then confirmed green on the rebased tree: site 81/81, web 223/223 + typecheck + build, coverage 93.84/88.53/86.31/93.84 (floor 92/87/84/92), plus an end-to-end ``applyDom`` render check (kn & es render correctly, zero untranslated leaks).

Notes. Translations are **native-review-pending** (the standing pre-launch gate, same as #86/#87). The handoff is updated; the worktree at ``khelsutra-wt-hero`` is left in place until merge. I also flagged in the handoff that ``#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq`` remain hardcoded English ? the same incremental slice if you ever want 100% home-page coverage (none urgent).

Want me to clean up the worktree now, or leave it until the PR merges?

116. user (2026-06-22T04:33:00.593Z)

please make sure the tests and CI are green, the coverage is not regressed and merge the PRs then clean the worktree

117. assistant (2026-06-22T04:33:37.615Z)

Ultracode is on, but this turn is a mechanical merge-and-cleanup of an already-verified PR ? the right move is to execute it rigorously, not to fan out subagents to run ``gh``. I'll be exhaustive about the verification, though.

Let me gather the full state in one shot: re-fetch, list open PRs (the request said "PRs" ? I'll confirm whether there's more than mine), re-confirm CI + mergeability, and **prove coverage can't regress** by showing ``web/src`` is byte-identical to base:

118. user (2026-06-22T04:33:48.736Z)

```
=== open PRs ===
89 feat(site): localize the hero demo mockup + #how feature block (6 languages)
feat/site-hero-mockup-i18n OPEN 2026-06-22T04:11:01Z

=== #89 CI checks ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/0d1a8b62-92c8-4f7c-80a3-6eea5ba4fd16
site pass 12s
https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972620
web pass 45s
https://github.com/avidullu/khelsutra/actions/runs/27928980805/job/82636972638

=== #89 mergeability ===
state=OPEN mergeable=MERGEABLE mergeState=CLEAN

=== origin/master moved? ===
origin/master: 7ae9cee feat(web): P2c first-run setup wizard (3 steps from /api/capabilities, 6
languages) (#88)

=== COVERAGE-REGRESSION PROOF: does my branch change ANY web source vs base? (empty = web
coverage identical) ===
[web diff above ? empty means no web source touched]
```

119. assistant (2026-06-22T04:34:24.005Z)

```
All clear to merge:
- **Only one open PR** ? #89 (mine); nothing else to merge.
- **CI all green** (site, web, Workers build).
- **mergeable=MERGEABLE, mergeState=CLEAN**; origin/master still at #88.
- **Coverage cannot have regressed**: `git diff origin/master...HEAD -- web/` is **empty** ? my
branch touches zero web source, so web coverage is byte-identically the base's
93.84/88.53/86.31/93.84 (all above the 92/87/84/92 floor). The site suite has no coverage gate;
I only added tests there.

Merging #89 (squash, matching the repo's `?(#NN)` history), then deleting the remote branch:
```

120. user (2026-06-22T04:34:30.584Z)

```
--- PR state after merge ---
state=MERGED mergedAt=2026-06-22T04:34:28Z mergeCommit=26c9da15ccbc5c4ec04cebaee59db2a2d72f5e31
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

121. assistant (2026-06-22T04:34:35.351Z)

Merged ? squash commit **26c9da1**. Now let me verify it landed on master with my change intact, check the main checkout's state before touching it, then remove the worktree:

122. user (2026-06-22T04:34:42.590Z)

```
=== origin/master tip ===
26c9da1 feat(site): localize the hero demo mockup + #how feature block (6 languages) (#89)

=== merged squash contains my keys? ===
site.hero.demo present: true | site.how present: true | #88 wizard present: true

=== main checkout state (don't clobber a sibling session) ===
branch: master
HEAD: 17242a9 feat(site): localize own-model body content to kn/hi (#86)

=== worktrees ===
C:/Users/avidu/Projects/khelsutra 17242a9 [master]
```

123. assistant (2026-06-22T04:35:06.867Z)

Merge confirmed on `origin/master` (26c9da1, #89) with **both** my keys **and** #88's `wizard` namespace intact. The main checkout is on `master` but behind (at #86). Before cleanup, let me confirm the worktree has no un-committed work to lose and check the main checkout for any sibling WIP:

124. user (2026-06-22T04:35:10.919Z)

```
=== worktree: unmerged/uncommitted work? (expect only ignored node_modules/dist) ===
[worktree status above]
unpushed commits on the worktree branch vs merged: 1 (expect 0 ? it's merged)

=== main checkout: any tracked modifications (sibling WIP)? ===
[main tracked-changes above ? empty = safe to ff]
```

125. assistant (2026-06-22T04:35:21.024Z)

Both safe: the worktree is clean (the "1 unpushed commit" is just the expected squash-merge SHA divergence ? content is provably merged), and the main checkout has zero tracked modifications. Cleaning up ? remove worktree, delete the local branch, prune, and fast-forward the main checkout's master to land #89 (repo-freshness convention):

126. user (2026-06-22T04:35:27.963Z)

```
=== remove worktree ===
removed: C:/Users/avidu/Projects/khelsutra-wt-hero

=== delete merged local branch ===
Deleted branch feat/site-hero-mockup-i18n (was 317b245).

=== prune worktree metadata ===

=== fast-forward main checkout master -> #89 ===
Updating 17242a9..26c9da1
Fast-forward
 docs/FRIENDLY_AND_MULTILINGUAL.md      | 1 +
 locales/da/common.json                  | 291 ++++++-----
 locales/en/common.json                   | 69 ++++++
 locales/es/common.json                   | 297 ++++++-----
 locales/hi/common.json                   | 69 ++++++
 locales/id/common.json                   | 289 ++++++-----
 locales/kn/common.json                   | 69 ++++++
 site/public/capture.html                 | 3 +
 site/public/i18n.js                      | 2 +-
 site/public/index.html                   | 41 +++-
 site/public/locales/da/common.json       | 291 ++++++-----
 site/public/locales/en/common.json       | 69 ++++++
 site/public/locales/es/common.json       | 297 ++++++-----
 site/public/locales/hi/common.json       | 69 ++++++
 site/public/locales/id/common.json       | 289 ++++++-----
 site/public/locales/kn/common.json       | 69 ++++++
 site/public/own-model.html               | 3 +
 site/server.js                           | 2 +-
 site/src/assets.test.js                  | 58 +++++-
 site/src/i18n.shim.test.js               | 82 ++++++
 web/src/App.tsx                          | 9 +-
 web/src/api/client.ts                    | 6 +
 web/src/api/types.ts                     | 17 ++
 web/src/components/SetupWizard.test.tsx | 127 ++++++
 web/src/components/SetupWizard.tsx      | 179 ++++++
 web/src/components/a4.touch.test.tsx     | 4 +
```

```
web/src/i18n/hygiene.test.ts          | 1 +
27 files changed, 1989 insertions(+), 714 deletions(-)
create mode 100644 web/src/components/SetupWizard.test.tsx
create mode 100644 web/src/components/SetupWizard.tsx
```

=== final state ===

main worktrees:

C:/Users/avidu/Projects/khelsutra 26c9da1 [master]

main HEAD: 26c9da1 feat(site): localize the hero demo mockup + #how feature block (6 languages) (#89)

wt dir exists: NO

127. assistant (2026-06-22T04:35:50.025Z)

Cleanup complete and the main checkout fast-forwarded cleanly to **#89** (it was 3 PRs behind ? the FF also caught it up on #87/#88). Worktree dir gone, branch deleted, pruned, only the main worktree remains. Let me update the handoff to mark #89 merged:

128. user (2026-06-22T04:35:53.480Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

129. user (2026-06-22T04:35:58.288Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

130. assistant (2026-06-22T04:36:08.785Z)

All done. Summary of this turn:

? Verified, merged, and cleaned up

Pre-merge verification (all green):

- **CI** on [89](https://github.com/avidullu/khelsutra/pull/89): **site** ?, **web** ?, **Workers build** ? ? **mergeable=MERGEABLE**, **mergeState=CLEAN**.
- **Coverage not regressed ? proven, not just measured:** **git diff origin/master...HEAD -- web/** was **empty**, so my branch touches zero web source ? web coverage is byte-identically the base's **93.84% stmts / 88.53% br / 86.31% fn / 93.84% lines**, all above the **92/87/84/92** floor. (The site suite has no coverage gate; I only added tests there.)
- Confirmed **only one open PR** (89, mine) ? nothing else to merge.

Merged:

- Squash-merged 89 ? master as **26c9da1** (matching the repo's **?(#NN)** convention), remote branch deleted.
- Verified the merged **origin/master** catalog holds **both** my keys (**site.hero.demo**, **site.how**) **and** 88's **wizard** namespace ? the rebase-over-88 preserved everything, no clobber.

Cleaned up:

- Removed the isolated worktree (**khelsutra-wt-hero** ? gone), deleted the local **feat/site-hero-mockup-i18n** branch, pruned worktree metadata.
- Fast-forwarded the shared main checkout **master** ? **26c9da1** (it was 3 PRs behind; the FF also caught it up on #87/#88 cleanly, with no sibling WIP at risk).
- Updated the session handoff to mark 89 merged.

The hero demo mockup and **how** feature block now localize across all 6 languages on the live marketing site. Translations remain native-review-pending (the standing pre-launch gate). I left a note in the handoff that **diff**/**sharper**/**ask**/**roadmap**/**not**/**faq** are still hardcoded English ? the same incremental slice pattern if you ever want full home-page coverage.

131. user (2026-06-22T04:37:02.497Z)

can you take the incremental slice and implement it right away?

132. assistant (2026-06-22T04:38:39.168Z)

This is the larger slice ? six sections (`#diff`, `#sharper`, `#ask`, `#roadmap`, `#not`, `#faq`), roughly 60+ strings × 6 locales. Ultracode is on, so I'll be exhaustive: do the deterministic work (scoping, HTML wiring, byte-exact en derivation) myself, then **fan out a Workflow** for the per-locale translate ? adversarial-verify ? revise pipeline across all 5 target locales, then apply, test, and ship under the same worktree discipline. `#join` stays out (it's the separately-deferred A6 slice with a test pinning it to English).

Let me set up an isolated worktree from the fresh `origin/master` (#89) and read the exact section markup:

133. user (2026-06-22T04:38:43.793Z)

```
origin/master: 26c9da1 feat(site): localize the hero demo mockup + #how feature block (6
languages) (#89)
Preparing worktree (new branch 'feat/site-home-sections-i18n')
branch 'feat/site-home-sections-i18n' set up to track 'origin/master'.
HEAD is now at 26c9da1 feat(site): localize the hero demo mockup + #how feature block (6
languages) (#89)
--- worktrees ---
C:/Users/avidu/Projects/khelsutra          26c9da1 [master]
C:/Users/avidu/Projects/khelsutra-wt-home  26c9da1 [feat/site-home-sections-i18n]
```

134. user (2026-06-22T04:38:53.361Z)

```
site deps ok
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

135. user (2026-06-22T04:39:01.406Z)

```
web deps ok
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

136. user (2026-06-22T04:39:01.619Z)

```
388:<section id="diff" style="padding-top:0">
406:<section id="sharper" style="background:#EFF4EC">
437:<section id="ask">
462:<section id="roadmap">
479:<section id="not" style="padding-top:0">
496:<section id="faq" style="background:#EFF4EC">
514:<section id="join" style="padding-bottom:90px">
603:<footer>
745:</body>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

137. assistant (2026-06-22T04:39:05.537Z)

Sections are at the same lines. Let me read the exact markup for all six sections plus the footer (to judge whether it's in scope):

138. user (2026-06-22T04:39:06.285Z)

```
388      <section id="diff" style="padding-top:0">
389          <div class="wrap">
390              <div class="split">
391                  <div>
392                      <div class="kicker" style="font-size:.82rem;font-weight:700;letter-
spacing:.08em;text-transform:uppercase;color:var(--green-d)">The hard problem we crack</div>
```

```

393         <h2 style="margin-top:.5rem">Most academy halls run several courts at once</h2>
394         <p style="color:var(--mut);font-size:1.05rem">Academies already record a lot of
video ? and then almost never watch it, because cutting it into useful clips by hand is tedious.
The good rallies stay buried.</p>
395         <p style="color:var(--mut);font-size:1.05rem">A single recording of a busy,
multi-court hall is exactly where ordinary video tools choke. Pulling the <b
style="color:var(--tx)">real</b> rallies out of busy, multi-court footage is the hard problem
KhelSutra is built for. It already works very well on clean, single-court recordings ? and the
multi-court case is what we're sharpening now.</p>
396     </div>
397     <div class="panel">
398         <span class="pill">Capture tip</span>
399         <h2 style="font-size:1.4rem">Best results: a steady, full-court shot</h2>
400         <p>Camera behind the court, slightly elevated, whole court in frame. Keep it
still ? a fixed tripod beats handheld every time. Shoot landscape, record the whole session,
upload as-is. KhelSutra does the cutting.</p>
401     </div>
402 </div>
403 </div>
404 </section>
405
406 <section id="sharper" style="background:#EFF4EC">
407     <div class="wrap">
408         <div class="sec-head">
409             <div class="kicker">What makes it different</div>
410             <h2>It gets sharper from real academy footage</h2>
411             <p>The footage real academies contribute ? especially the busy multi-court halls ?
is what makes KhelSutra better over time. Early users aren't just customers; they're co-
builders.</p>
412         </div>
413         <div class="grid g3">
414             <div class="card">
415                 <div class="ic" aria-hidden="true">?</div>
416                 <h3>Improves with the library</h3>
417                 <p>When you choose to share footage and coaches confirm what it found, that
growing labelled library is what sharpens future versions ? rather than staying frozen.</p>
418             </div>
419             <div class="card">
420                 <div class="ic" aria-hidden="true">?</div>
421                 <h3>Your data stays yours</h3>
422                 <p>We never use your video to improve the tool without your clear, explicit opt-
in. We never publish your footage. You decide what, if anything, you share.</p>
423             </div>
424             <div class="card">
425                 <div class="ic" aria-hidden="true">?</div>
426                 <h3>Minors are protected</h3>
427                 <p>Footage involving minors is never used to improve the tool and is never
published ? full stop.</p>
428             </div>
429         </div>
430         <div class="honest">
431             <b>Read this honestly:</b>
432             <p>Today the tool gives you rally detection, reels, and summaries. It does not
retrain itself as you use it, and there's no per-person tracking. "Gets sharper over time" is
the model we're building toward, powered by contributed footage ? not a switch that's already
on.</p>
433         </div>
434     </div>
435 </section>
436
437 <section id="ask">
438     <div class="wrap">
439         <div class="sec-head">
440             <div class="kicker">Coming next to the alpha</div>
441             <h2>Soon: ask for the exact reel you want</h2>

```

```

442         <p>Your match is already a clean index of rallies ? so the natural next step is to
let you build any reel just by describing it, in plain English. This is rolling out to alpha
users.</p>
443     </div>
444     <div class="grid g3 ask-grid">
445         <div class="card ask">
446             <div class="q"><i>?</i>Every rally over 10 seconds?</div>
447             <div class="a"><i>?</i> 6 rallies · a 1:32 reel of the long, end-to-end
battles</div>
448         </div>
449         <div class="card ask">
450             <div class="q"><i>?</i>Just the third game, longest first?</div>
451             <div class="a"><i>?</i> 12 rallies, reordered by length ? that game only</div>
452         </div>
453         <div class="card ask">
454             <div class="q"><i>?</i>The 8 best rallies from today?</div>
455             <div class="a"><i>?</i> an 8-clip highlight from your latest session</div>
456         </div>
457     </div>
458     <p class="ask-note"><b style="color:var(--tx)">Rolling out now.</b> Targeted asks ?
by rally length, count, order, or which game ? come first; shot-type and player queries follow
as the deeper analysis arrives.</p>
459 </div>
460 </section>
461
462 <section id="roadmap">
463     <div class="wrap">
464         <div class="sec-head">
465             <div class="kicker">Where it's going</div>
466             <h2>Toward an AI assistant coach</h2>
467             <p>Fed by the growing video library, KhelSutra is heading from "finds rallies" to
a genuine training companion. This is the direction ? not today's buttons.</p>
468         </div>
469         <div class="road">
470             <div class="step"><div class="n">?</div><h3>Shot detection</h3><p>Smashes, drops,
net shots, serves and clears within each rally.</p></div>
471             <div class="step"><div class="n">?</div><h3>Deeper analysis</h3><p>Per-rally and
per-match patterns ? what's working and what isn't.</p></div>
472             <div class="step"><div class="n">?</div><h3>Per-match history</h3><p>Track
progress over weeks and months, not just one clip.</p></div>
473             <div class="step"><div class="n">?</div><h3>Assistant coach</h3><p>Surfaces what
to work on next ? supports the real coach, never replaces.</p></div>
474             <div class="step"><div class="n">?</div><h3>More sports & languages</h3><p>Table
tennis next; Kannada and Hindi alongside English.</p></div>
475         </div>
476     </div>
477 </section>
478
479 <section id="not" style="padding-top:0">
480     <div class="wrap">
481         <div class="sec-head">
482             <div class="kicker">So expectations stay honest</div>
483             <h2>What KhelSutra is not</h2>
484         </div>
485         <ul class="nots">
486             <li><i aria-hidden="true">?</i><span>An early, invite-only trial ? useful, but
still improving. You'll hit rough edges.</span></li>
487             <li><i aria-hidden="true">?</i><span>Not a line-calling, scoring, or umpiring
system.</span></li>
488             <li><i aria-hidden="true">?</i><span>Not player tracking or
identification.</span></li>
489             <li><i aria-hidden="true">?</i><span>Not a replacement for a coach ? a tool that
saves time and adds insight.</span></li>
490             <li><i aria-hidden="true">?</i><span>Shot detection and deeper analytics are on
the roadmap, not available today.</span></li>

```

```

491         <li><i aria-hidden="true">?</i><span>Pricing isn't set ? today's invited use is
about getting it right.</span></li>
492     </ul>
493 </div>
494 </section>
495
496 <section id="faq" style="background:#EFF4EC">
497     <div class="wrap">
498         <div class="sec-head">
499             <div class="kicker">Quick answers</div>
500             <h2>Common questions</h2>
501         </div>
502         <div style="margin-top:1.6rem">
503             <details><summary>How accurate is it?</summary><p>Very good on a clean, single-
court recording. A busy multi-court hall is harder ? and is exactly what we're improving. The
best answer is to show you a sample reel of your own court rather than quote a
number.</p></details>
504             <details><summary>Can I choose which rallies go in the reel?</summary><p>Today
your reel includes the rallies KhelSutra found, with the dead time removed. Choosing by length,
count, order or which game ? just by asking in plain English ? is rolling out to alpha users
next; shot-type and player queries follow as the deeper analysis arrives.</p></details>
505             <details><summary>Do I need a special camera or hardware?</summary><p>No. A phone
or GoPro on a tripod, behind the court, whole court in frame. We provide a one-page capture
checklist at setup.</p></details>
506             <details><summary>Is my video private? What happens to it?</summary><p>We treat
your footage as private: we never publish it, and we never use it to improve the tool without
your explicit opt-in. These are large videos that need real processing, so your video is handled
securely on our infrastructure to make your reel. Footage involving minors is never used and
never published.</p></details>
507             <details><summary>Does it work for doubles and tournaments?</summary><p>It finds
rallies in doubles too. Tournament footage varies ? a clean, fixed, full-court recording works
well; crowded multi-court tournament halls are the hard case we're specifically working
on.</p></details>
508             <details><summary>Which sports?</summary><p>Badminton today. Table tennis and
other racket sports are on the roadmap.</p></details>
509             <details><summary>How do I join?</summary><p>It's an invite-only private trial.
Just <a href="#join">request access</a> using the form ? it takes a minute, you'll see a real
sample reel right away, and we'll be in touch about recording your own court.</p></details>
510         </div>
511     </div>
512 </section>
513

```

139. assistant (2026-06-22T04:40:37.446Z)

I have all six sections. Let me also check the footer (the handoff named only the 6 sections, but I want to report its state accurately) before I start wiring:

140. user (2026-06-22T04:40:38.535Z)

```

603 <footer>
604     <div class="wrap foot">
605         <div>
606             <div class="brand" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</div>
607             <div class="stamp" style="margin-top:.4rem">Automatic badminton highlights .
Bengaluru, India</div>
608         </div>
609         <div style="text-align:right">
610             <div><a href="/own-model">Own your model</a> . <a href="/capture">Capture
checklist</a> . <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> . <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
611             <div style="margin-top:.4rem">Academy flyer (print): <a href="/flyer"
hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn" lang="kn">?????</a> . <a
href="/flyer-hi" hreflang="hi" lang="hi">?????</a></div>

```



```

612         <div class="stamp" style="margin-top:.4rem">© 2026 KhelSutra · Invite-only alpha ·
Reels carry a "Generated by Khelsutra.guru" mark</div>
613     </div>
614 </div>
615 </footer>
616
617 <!-- Cloudflare Web Analytics: paste your token from Cloudflare dashboard ? Analytics ?
Web Analytics ? Add a site.
618     (Or skip this snippet entirely and enable "Automatic setup" once the domain is
proxied through Cloudflare.) -->
619     <script defer src="https://static.cloudflareinsights.com/beacon.min.js" data-cf-
beacon="{\"token\": \"REPLACE_WITH_CF_TOKEN\"}'></script>
620
621     <script>
622     (function(){
623         var f = document.getElementById('af');
624         if(!f) return;
625
626         var REEL_VIDEO = 'ajTCZ7pJW_o', REEL_SECS = 30;
627         function loadYTApi(cb){
628             if(window.YT && window.YT.Player) return cb();
629             var prev = window.onYouTubeIframeAPIReady;
630             window.onYouTubeIframeAPIReady = function(){ if(typeof prev === 'function'){ prev();
} cb(); };
631             if(!document.getElementById('yt-iframe-api')){
632                 var s = document.createElement('script');
633                 s.id = 'yt-iframe-api'; s.src = 'https://www.youtube.com/iframe_api';
634                 document.head.appendChild(s);
635             }
636         }
637         function revealAfterSignup(){
638             var host = document.getElementById('reel-reveal');
639             if(!host) return;
640             host.hidden = false;
641             // A2: localized "Share on WhatsApp" CTA. The reveal is injected after sign-up
(outside the static
642             // data-i18n walk), so we pull copy from the shim bridge (window.KhelSutra.t) with
an en fallback.
643             var ksT = (window.KhelSutra && window.KhelSutra.t) || function(){ return undefined;
};
644             var shareText = ksT('site.reveal.shareText') || 'Check out KhelSutra ? it turns a
full badminton match into a clean highlights reel ? khelsutra.guru';
645             var shareLabel = ksT('site.reveal.share') || 'Share on WhatsApp';
646             var waHref = 'https://wa.me/?text=' + encodeURIComponent(shareText);
647             // (1) the TOOL in action ? a self-hosted, FOOTAGE-FREE screencast (branded reel
placeholder),

```

141. assistant (2026-06-22T04:44:09.628Z)

The footer also has hardcoded strings, but it's outside the named slice ? I'll wire the six content sections (the exact "incremental slice" from the handoff) and report the footer + `#join` as the remaining pieces.

Before wiring, let me find any existing test regexes that anchor on these sections' tags (so I don't silently break them ? e.g., the "How do I join?" FAQ test matches a literal `

`):

142. user (2026-06-22T04:44:13.056Z)

=== test regexes touching the 6 sections ===

```

src/assets.test.js:135: assert.match(html, /one match, one court/i, "the #1 single-court
capture rule should be on the homepage");
src/assets.test.js:143:test("the 'How do I join?' FAQ points at the request-access form, not
email", () => {
src/assets.test.js:145: const m = html.match(/How do I join\?<\summary>(<p>[\s\S]*?<\p>)/);
src/assets.test.js:146: assert.ok(m, "the 'How do I join?' FAQ is gone");

```

```

src/assets.test.js:147: assert.match(m[1], /request access/i, "the join FAQ should send people
to the request-access form");
src/assets.test.js:152:test("the own-model page exists, is honestly scoped, and is linked from
the landing page", () => {
src/assets.test.js:159: assert.match(om, /Read this honestly/i, "the honest framing fence is
gone");
src/assets.test.js:160: assert.match(om, /open pipeline|in build/i, "training must be honestly
scoped as in-build, not one-click");
src/assets.test.js:180: assert.match(om, /sample[\s\S]{0,80}request access|request
access[\s\S]{0,80}sample/i, "point users to request access for a sample output");
src/assets.test.js:307: assert.match(om, /data-i18n-html="site\.ownModel\.train\.honestBody"/,
"the honest-framing fence should localize");
src/assets.test.js:312: // The honest framing survives in the en DOM default (server smoke +
no-JS reads rely on it).
src/assets.test.js:313: assert.equal(enCatalog.site.ownModel.train.honestTitle, "Read this
honestly.");
src/i18n.shim.test.js:133: // A representative spread across hero / annotate / train / setup /
honesty / footer must be in-script.
src/i18n.shim.test.js:134: for (const key of ["heroLead", "sample", "annotate.body",
"train.reassureBody", "train.honestBody", "setup.joinRule", "not.title", "cta.title",
"foot.mark"]) {
src/i18n.shim.test.js:164:     assert.match(o.train.honestBody, /GPU/, `${loc} train.honestBody
lost GPU`);
src/i18n.shim.test.js:165:     assert.match(o.train.honestBody, /LLM/, `${loc} train.honestBody
lost LLM`);
src/i18n.shim.test.js:185:     for (const key of ["hero.lead", "record.intro", "capture.consent",
"ownModel.heroLead", "ownModel.train.honestBody"]) {
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

143. assistant (2026-06-22T04:44:19.537Z)

Only one existing test anchors on a literal tag in my sections ? `assets.test.js:145` matches
`How do I join?</summary><p>...` and will need `
that when extending tests. Now let me write the wiring script (literal anchored insertions with
assert-exactly-once, plus the `#ask` span-wrap):

144. assistant (2026-06-22T04:44:44.300Z)

```

/* TEMP: wire data-i18n into the 6 home-page sections. Pure string insertion (no DOM
round-trip) so the HTML stays byte-stable except the added attributes. Each insertion
asserts its anchor is globally unique. Deleted after run. */
const fs = require("fs");
const P = "site/public/index.html";
let html = fs.readFileSync(P, "utf8");
let n = 0;

// insert `attr="key"` at the end of the opening tag whose `>` immediately precedes `anchor`
function plain(anchor, key, attr = "data-i18n") {
    const find = ">" + anchor;
    const count = html.split(find).length - 1;
    if (count !== 1) throw new Error(`anchor not unique (${count}) for ${key}:
${JSON.stringify(find)}`);
    html = html.replace(find, ` ${attr}="${key}">` + anchor);
    n++;
}

// literal find->replace, assert once
function lit(find, replace, key) {
    const count = html.split(find).length - 1;
    if (count !== 1) throw new Error(`literal not unique (${count}) for ${key}:
${JSON.stringify(find)}`);
    html = html.replace(find, replace);
    n++;
}

// ---- #diff ----

```

```

plain("The hard problem we crack", "site.diff.kicker");
plain("Most academy halls run several courts at once", "site.diff.title");
plain("Academies already record a lot of video", "site.diff.p1");
plain("A single recording of a busy, multi-court hall", "site.diff.p2", "data-i18n-html");
plain("Capture tip", "site.diff.tipPill");
plain("Best results: a steady, full-court shot", "site.diff.tipTitle");
plain("Camera behind the court, slightly elevated", "site.diff.tipBody");

// ---- #sharper ----
plain("What makes it different", "site.sharper.kicker");
plain("It gets sharper from real academy footage", "site.sharper.title");
plain("The footage real academies contribute", "site.sharper.intro");
plain("Improves with the library", "site.sharper.improve.title");
plain("When you choose to share footage", "site.sharper.improve.body");
plain("Your data stays yours", "site.sharper.data.title");
plain("We never use your video to improve the tool without", "site.sharper.data.body");
plain("Minors are protected", "site.sharper.minors.title");
plain("Footage involving minors is never used", "site.sharper.minors.body");
plain("Read this honestly:", "site.sharper.honestLead");
plain("Today the tool gives you rally detection", "site.sharper.honestBody");

// ---- #ask ----
plain("Coming next to the alpha", "site.ask.kicker");
plain("Soon: ask for the exact reel you want", "site.ask.title");
plain("Your match is already a clean index of rallies", "site.ask.intro");
// q/a chips: wrap the text after the decorative icon in a localizable span (icon stays literal)
let qi = 0;
html = html.replace(/(<div class="q"><i>?</i>)([\\s\\S]*?)(</div>)/g, (m, a, t, c) => { qi++;
n++; return `${a}<span data-i18n="site.ask.q${qi}">${t}</span>${c}`; });
if (qi !== 3) throw new Error(`expected 3 .q chips, wrapped ${qi}`);
let ai = 0;
html = html.replace(/(<div class="a"><i>?</i> )([\\s\\S]*?)(</div>)/g, (m, a, t, c) => { ai++;
n++; return `${a}<span data-i18n="site.ask.a${ai}">${t}</span>${c}`; });
if (ai !== 3) throw new Error(`expected 3 .a chips, wrapped ${ai}`);
lit('<p class="ask-note">', '<p class="ask-note" data-i18n-html="site.ask.note">',
"site.ask.note");

// ---- #roadmap ----
plain("Where it", "site.roadmap.kicker");
plain("Toward an AI assistant coach", "site.roadmap.title");
plain("Fed by the growing video library", "site.roadmap.intro");
plain("Shot detection", "site.roadmap.shot.title");
plain("Smashes, drops, net shots", "site.roadmap.shot.body");
plain("Deeper analysis", "site.roadmap.deep.title");
plain("Per-rally and per-match patterns", "site.roadmap.deep.body");
plain("Per-match history", "site.roadmap.history.title");
plain("Track progress over weeks and months", "site.roadmap.history.body");
plain("Assistant coach", "site.roadmap.coach.title");
plain("Surfaces what to work on next", "site.roadmap.coach.body");
plain("More sports", "site.roadmap.more.title");
plain("Table tennis next", "site.roadmap.more.body");

// ---- #not ----
plain("So expectations stay honest", "site.not.kicker");
plain("What KhelSutra is not", "site.not.title");
plain("An early, invite-only trial", "site.not.li1");
plain("Not a line-calling, scoring", "site.not.li2");
plain("Not player tracking or identification", "site.not.li3");
plain("Not a replacement for a coach", "site.not.li4");
plain("Shot detection and deeper analytics", "site.not.li5");
plain("Pricing isn", "site.not.li6");

// ---- #faq ----
plain("Quick answers", "site.faq.kicker");
plain("Common questions", "site.faq.title");

```

```

lit("<summary>How accurate is it?", '<summary data-i18n="site.faq.q1.q">How accurate is it?',
"site.faq.q1.q");
lit("<summary>Can I choose which rallies go in the reel?", '<summary
data-i18n="site.faq.q2.q">Can I choose which rallies go in the reel?', "site.faq.q2.q");
lit("<summary>Do I need a special camera or hardware?", '<summary data-i18n="site.faq.q3.q">Do I
need a special camera or hardware?', "site.faq.q3.q");
lit("<summary>Is my video private? What happens to it?", '<summary data-i18n="site.faq.q4.q">Is
my video private? What happens to it?', "site.faq.q4.q");
lit("<summary>Does it work for doubles and tournaments?", '<summary
data-i18n="site.faq.q5.q">Does it work for doubles and tournaments?', "site.faq.q5.q");
lit("<summary>Which sports?", '<summary data-i18n="site.faq.q6.q">Which sports?',
"site.faq.q6.q");
lit("<summary>How do I join?", '<summary data-i18n="site.faq.q7.q">How do I join?',
"site.faq.q7.q");
plain("Very good on a clean", "site.faq.q1.a");
plain("Today your reel includes", "site.faq.q2.a");
plain("No. A phone or GoPro", "site.faq.q3.a");
plain("We treat your footage as private", "site.faq.q4.a");
plain("It finds rallies in doubles", "site.faq.q5.a");
plain("Badminton today.", "site.faq.q6.a");
lit("How do I join?</summary><p>", 'How do I join?</summary><p data-i18n-html="site.faq.q7.a">',
"site.faq.q7.a");

fs.writeFileSync(P, html);
console.log(`Inserted ${n} i18n attributes into ${P}`);

```

145. user (2026-06-22T04:44:44.327Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra-wt-home/_tmp_wire.cjs (file state is current in your context ? no need to Read it back)

146. user (2026-06-22T04:44:51.869Z)

Exit code 1

C:\Users\avidu\Projects\khelsutra-wt-home_tmp_wire.cjs:13

```

    if (count !== 1) throw new Error(`anchor not unique (${count}) for ${key}:
    ${JSON.stringify(find)}`);
    ^

```

```

Error: anchor not unique (2) for site.roadmap.shot.title: ">Shot detection"
    at plain (C:\Users\avidu\Projects\khelsutra-wt-home\_tmp_wire.cjs:13:26)
    at Object.<anonymous> (C:\Users\avidu\Projects\khelsutra-wt-home\_tmp_wire.cjs:64:1)
    at Module._compile (node:internal/modules/cjs/loader:1856:14)
    at Object..js (node:internal/modules/cjs/loader:1996:10)
    at Module.load (node:internal/modules/cjs/loader:1579:32)
    at Module._load (node:internal/modules/cjs/loader:1381:12)
    at wrapModuleLoad (node:internal/modules/cjs/loader:255:19)
    at Module.executeUserEntryPoint [as runMain] (node:internal/modules/run_main:154:5)
    at node:internal/main/run_main_module:33:47

```

Node.js v26.1.0

147. assistant (2026-06-22T04:45:32.216Z)

`>Shot detection` collides with `#not`'s "Shot detection and deeper analytics" prefix. The assert caught it before any write (file untouched). Let me anchor the roadmap h3 by its full tag instead:

148. user (2026-06-22T04:45:33.397Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/_tmp_wire.cjs has been updated successfully. (file state is current in your context ? no need to Read it back)

149. user (2026-06-22T04:45:38.086Z)

Inserted 65 i18n attributes into site/public/index.html
--- counts in #diff..#faq ---
data-i18n: 62
data-i18n-html: 3
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

150. assistant (2026-06-22T04:46:02.906Z)

65 attributes wired (62 plain + 3 rich-HTML). Now derive the **byte-exact en values** from the DOM and save them for the translation workflow:

151. user (2026-06-22T04:46:09.756Z)

extracted 65 new en keys -> _tmp_en_newkeys.json
site.diff.p2 = "A single recording of a busy, multi-court hall is exactly where ordinary video tools choke. Pulling the <b style=\"color:var(--tx)\">real rallies out of busy, multi-court footage is the hard problem KhelSutra is built for. It already works very well on clean, single-court recordings ? and the multi-court case is what we're sharpening now."
site.ask.note = "<b style=\"color:var(--tx)\">Rolling out now. Targeted asks ? by rally length, count, order, or which game ? come first; shot-type and player queries follow as the deeper analysis arrives."
site.faq.q7.a = "It's an invite-only private trial. Just request access using the form ? it takes a minute, you'll see a real sample reel right away, and we'll be in touch about recording your own court."
site.ask.q1 = "?Every rally over 10 seconds?"
site.ask.a1 = "6 rallies · a 1:32 reel of the long, end-to-end battles"
site.roadmap.more.title = "More sports & languages"
site.not.li6 = "Pricing isn't set ? today's invited use is about getting it right."
site.sharper.honestBody = "Today the tool gives you rally detection, reels, and summaries. It does not retrain itself as you use it, and there's no per-person tracking. \"Gets sharper over time\" is the model we're building toward, powered by contributed footage ? not a switch that's already on."
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

152. assistant (2026-06-22T04:48:09.552Z)

All 65 en values extracted byte-exact (rich HTML, curly quotes, `&`, apostrophes all intact). Now I'll fan out a **Workflow**: per locale (kn/hi/es/da/id, in parallel), a pipeline of **draft** ? 2-lens adversarial verify (accuracy+grammar / vocabulary+register) ? revise**, each agent grounded in that locale's existing catalog. Let me mark the chapter and launch it:

153. user (2026-06-22T04:48:10.481Z)

Chapter marked: "Localize remaining home sections". Continue your current work.

154. user (2026-06-22T04:48:47.951Z)

Workflow launched in background. Task ID: wkuo7ocoe
Summary: Translate 65 new KhelSutra home-page i18n keys into kn/hi/es/da/id (draft -> 2-lens adversarial verify -> revise)
Transcript dir: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\subagents\workflows\wf_2299f8ad-233
Script file: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_2299f8ad-233.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_2299f8ad-233.js"} to iterate without resending the script.)
Run ID: wf_2299f8ad-233
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_2299f8ad-233.js", resumeFromRunId: "wf_2299f8ad-233"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

155. assistant (2026-06-22T04:49:08.434Z)

The workflow failed at launch ? `args` didn't arrive as an object (the runtime got `locales` undefined). Rather than fight the args plumbing, I'll hardcode the config (the paths and locale list are fixed and known) and re-launch:

156. user (2026-06-22T04:49:35.080Z)

Workflow launched in background. Task ID: w4h01m1sj
Summary: Translate 65 new KhelSutra home-page i18n keys into kn/hi/es/da/id (draft -> 2-lens adversarial verify -> revise)
Transcript dir: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\subagents\workflows\wf_700faf42-eab
Script file: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_700faf42-eab.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_700faf42-eab.js"} to iterate without resending the script.)
Run ID: wf_700faf42-eab
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\c6fbcfbb-d724-4901-b146-68f198409ed5\workflows\scripts\translate-home-sections-wf_700faf42-eab.js", resumeFromRunId: "wf_700faf42-eab"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

157. assistant (2026-06-22T04:49:56.279Z)

The translation workflow (15 agents: 5 draft + 10 verify + 5 revise) is running in the background. While it works, let me do the independent prep: fix the FAQ test regex that will break, and write the test extensions + the applier. Let me read the current test files (fresh from #89, so they already include my hero/#how tests):

158. user (2026-06-22T04:49:56.946Z)

```
143     test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
144         const html = read("index.html");
145         const m = html.match(/How do I join\?<\summary>(<p>[\s\S]*?<\p>)/);
146         assert.ok(m, "the 'How do I join?' FAQ is gone");
147         assert.match(m[1], /request access/i, "the join FAQ should send people to the request-access form");
148         assert.match(m[1], /href="#join"/, "the join FAQ should link to the #join form");
149         assert.doesNotMatch(m[1], /mailto/, "the join FAQ should NOT tell people to email (use the form)");
150     });
151
152     test("the own-model page exists, is honestly scoped, and is linked from the landing page", () => {
```

159. assistant (2026-06-22T04:50:02.319Z)

Fixing the FAQ regex to tolerate the new attribute (the summary attr sits before "How do I join?", so that part still matches; only the `

` needs to allow attributes):

160. user (2026-06-22T04:50:03.603Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/site/src/assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

161. assistant (2026-06-22T04:50:06.745Z)

Let me read the tails of both test files to append the new home-section tests:

162. user (2026-06-22T04:50:08.157Z)

```
=== assets.test.js tail ===
});

test("#how: the 'what it does today' feature block (head + 4 cards) is wired for translation",
() => {
  const dig = (o, k) => k.split(".").reduce((a, c) => (a == null ? a : a[c]), o);
  const html = read("index.html");
  for (const k of ["kicker", "title", "intro"]) {
    assert.match(html, new RegExp(`data-i18n="site\\.how\\.\\${k}"`), `#how section head '${k}'
isn't wired`);
  }
  for (const card of ["indexed", "deadtime", "reuse", "stitch"]) {
    assert.match(html, new RegExp(`data-i18n="site\\.how\\.\\${card}\\.title"`), `#how card
'${card}' title isn't wired`);
    assert.match(html, new RegExp(`data-i18n="site\\.how\\.\\${card}\\.body"`), `#how card
'${card}' body isn't wired`);
  }
  // The watermark + MP4 literals stay verbatim in the en source.
  assert.match(enCatalog.site.how.stitch.body, /?Generated by Khelsutra\\.guru?/, "en
how.stitch.body lost the verbatim watermark");
  assert.match(enCatalog.site.how.stitch.body, /\bMP4\b/, "en how.stitch.body lost the MP4
token");
  // Every site.how.* key used in the HTML resolves in en.
  const keys = [...html.matchAll(/data-i18n="(site\\.how\\.\\[^\"]+)"\/g)].map((m) => m[1]);
  assert.ok(keys.length >= 11, `expected the full #how block wired (found ${keys.length})`);
  for (const key of keys) assert.notEqual(dig(enCatalog, key), undefined, `#how key "${key}"
missing from en catalog`);
});

=== i18n.shim.test.js tail ===
  assert.match(catalogs[loc].site.hero.loop[`step${n}`], new RegExp(`^<b>${n}\\.</b> `),
`${loc} loop.step${n} lost its <b>${n}</b> marker`);
}
}
});

test("hero+#how: es/da/id translate the new block (not en seeds) and keep the faux-UI literal
tokens", () => {
  const enSite = flatOwn(catalogs.en.site);
  for (const loc of ["es", "da", "id"]) {
    const locSite = flatOwn(catalogs[loc].site);
    for (const key of ["hero.ctaReel", "hero.demo.detected", "how.title", "how.deadtime.body",
"how.reuse.body", "how.stitch.title"]) {
      assert.notEqual(locSite[key], enSite[key], `${loc} site.${key} must be translated, not an
en seed`);
    }
    // Literal tokens survive translation in the faux-UI + feature copy.
    assert.match(locSite["hero.demo.fileTag"], /match_2026\\.mp4/, `${loc} hero.demo.fileTag lost
the filename`);
    assert.match(locSite["hero.demo.resultTitle"], /44\\.18 min/, `${loc} hero.demo.resultTitle
lost the 44/18 min tokens`);
    assert.match(locSite["how.intro"], /KhelSutra/, `${loc} how.intro lost the brand`);
    assert.match(locSite["how.stitch.body"], /?Generated by Khelsutra\\.guru?/, `${loc}
how.stitch.body lost the verbatim watermark`);
    assert.match(locSite["how.stitch.body"], /\bMP4\b/, `${loc} how.stitch.body lost MP4`);
  }
});
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

163. assistant (2026-06-22T04:50:44.178Z)

Both files end with my #89 tests. Let me append the home-section coverage tests to each:

164. user (2026-06-22T04:50:56.141Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/site/src/assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

165. user (2026-06-22T04:51:11.685Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

166. assistant (2026-06-22T04:51:19.132Z)

Need to Read the worktree file first. Let me read its tail and re-apply:

167. user (2026-06-22T04:51:20.496Z)

```
232         const locSite = flatOwn(catalogs[loc].site);
233         for (const key of ["hero.ctaReel", "hero.demo.detected", "how.title",
"how.deadtime.body", "how.reuse.body", "how.stitch.title"]) {
234             assert.notEqual(locSite[key], enSite[key], `${loc} site.${key} must be translated,
not an en seed`);
235         }
236         // Literal tokens survive translation in the faux-UI + feature copy.
237         assert.match(locSite["hero.demo.fileTag"], /match_2026\.mp4/, `${loc}
hero.demo.fileTag lost the filename`);
238         assert.match(locSite["hero.demo.resultTitle"], /44.*18 min/, `${loc}
hero.demo.resultTitle lost the 44/18 min tokens`);
239         assert.match(locSite["how.intro"], /KhelSutra/, `${loc} how.intro lost the brand`);
240         assert.match(locSite["how.stitch.body"], /?Generated by Khelsutra\.guru?/, `${loc}
how.stitch.body lost the verbatim watermark`);
241         assert.match(locSite["how.stitch.body"], /\bMP4\b/, `${loc} how.stitch.body lost
MP4`);
242     }
243 });
244
```

168. user (2026-06-22T04:51:35.408Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/site/src/i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

169. assistant (2026-06-22T04:51:42.050Z)

Tests extended and the FAQ regex fixed. Now let me pre-write the applier so it's ready the moment the workflow returns (it sets byte-exact en + per-locale translations into all 6 catalogs):

170. assistant (2026-06-22T04:51:49.853Z)

```
/* TEMP applier ? writes the 65 new home-section keys into all 6 catalogs.
   en values come from _tmp_en_newkeys.json (byte-exact from the wired DOM);
   kn/hi/es/da/id come from _tmp_translations.json ({loc:{key:val}}) produced by the workflow.
   Deleted after run. */
const fs = require("fs");
const path = require("path");
const ROOT = __dirname;

const en = JSON.parse(fs.readFileSync(path.join(ROOT, "_tmp_en_newkeys.json"), "utf8"));
const tx = JSON.parse(fs.readFileSync(path.join(ROOT, "_tmp_translations.json"), "utf8"));
const KEYS = Object.keys(en);

function setPath(obj, dotted, val) {
    const p = dotted.split(".");
```



```

let o = obj;
for (let i = 0; i < p.length - 1; i++) {
  if (o[p[i]] == null || typeof o[p[i]] !== "object") o[p[i]] = {};
  o = o[p[i]];
}
o[p[p.length - 1]] = val;
}

const report = [];
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const p = path.join(ROOT, "locales", loc, "common.json");
  const j = JSON.parse(fs.readFileSync(p, "utf8"));
  const table = loc === "en" ? en : tx[loc];
  if (!table) throw new Error(`no translation table for ${loc}`);
  const missing = KEYS.filter((k) => table[k] == null || table[k] === "");
  if (missing.length) throw new Error(`${loc} missing ${missing.length} keys: ${missing.slice(0, 8).join(", ")}${missing.length > 8 ? " ? " : ""}`);
  const extra = Object.keys(table).filter((k) => !en[k]);
  if (extra.length) throw new Error(`${loc} has ${extra.length} unexpected keys: ${extra.slice(0, 8).join(", ")}`);
  for (const k of KEYS) setPath(j, k, table[k]);
  fs.writeFileSync(p, JSON.stringify(j, null, 2) + "\n");
  report.push(`${loc}: +${KEYS.length}`);
}
console.log("Applied home-section keys -> " + report.join(" | "));

```

171. user (2026-06-22T04:51:49.870Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra-wt-home/_tmp_apply.cjs (file state is current in your context ? no need to Read it back)

172. assistant (2026-06-22T04:52:14.954Z)

The applier is ready. Let me also pre-write the structural verifier (it runs after applying ? checks tag-multiset parity, kn/hi in-script, token preservation, no en-seed, and the es/da/id cognate budget):

173. assistant (2026-06-22T04:52:28.728Z)

```

/* TEMP structural verifier for the 65 home-section keys across kn/hi/es/da/id. Deleted after run. */
const fs = require("fs"), path = require("path");
const ROOT = __dirname;
const L = ["en", "kn", "hi", "es", "da", "id"];
const load = (l) => JSON.parse(fs.readFileSync(path.join(ROOT, "locales", l, "common.json"), "utf8"));
const c = Object.fromEntries(L.map((l) => [l, load(l)]));
const en = JSON.parse(fs.readFileSync(path.join(ROOT, "_tmp_en_newkeys.json"), "utf8"));
const KEYS = Object.keys(en);
const dig = (o, k) => k.split(".").reduce((a, x) => (a == null ? a : a[x]), o);
const tagset = (s) => (String(s).match(/<[^\>]+>/g) || []).slice().sort().join("|");
const KN = /[?~?]/, HI = /[?~?]/;
let fail = 0;
const eq = []; // (loc,key) that equal the en seed
for (const k of KEYS) {
  const ev = dig(c.en, k);
  if (ev !== en[k]) { console.log("EN-DRIFT", k, "(catalog != extracted DOM value)"); fail++; }
  for (const l of L.slice(1)) {
    const v = dig(c[l], k);
    if (v == null) { console.log("MISSING", l, k); fail++; continue; }
    if (tagset(v) !== tagset(ev)) { console.log("TAG DRIFT", l, k, "| en:", tagset(ev), "|", l + ":", tagset(v)); fail++; }
    if (v === ev) eq.push(l + " " + k);
  }
}

```

```

    for (const [l, re] of [["kn", KN], ["hi", HI]]) {
      if (!re.test(dig(c[l], k))) { console.log("NOT-IN-SCRIPT", l, k, "=>", dig(c[l], k));
fail++; }
    }
  }
// token preservation
const need = [
  ["site.diff.p2", "KhelSutra"], ["site.sharper.intro", "KhelSutra"],
  ["site.faq.q7.a", 'href="#join"'],
  ["site.ask.a1", "1:32"], ["site.ask.q1", "10 seconds"],
];
for (const l of L) for (const [k, t] of need) { if (!String(dig(c[l], k)).includes(t)) {
console.log("TOKEN LOST", l, k, "missing:", t); fail++; } }
// es/da/id cognate budget vs en seed (existing guard allows <= 8 TOTAL across the whole site.*)
const flat = (o, p = "") => Object.entries(o).reduce((a, [k, v]) => { const key = p ? p + "." +
k : k; if (v && typeof v === "object") Object.assign(a, flat(v, key)); else a[key] = v; return
a; }, {});
const enSite = flat(c.en.site), knSite = flat(c.kn.site);
const target = Object.keys(enSite).filter((k) => knSite[k] !== enSite[k]);
for (const loc of ["es", "da", "id"]) {
  const locSite = flat(c[loc].site);
  const stillEn = target.filter((k) => locSite[k] === enSite[k]);
  console.log(`${loc}: stillEn(site-wide) = ${stillEn.length} (guard <= 8)` + (stillEn.length >
8 ? " !!! OVER" : ""), stillEn.length ? "-> " + stillEn.slice(0, 12).join(", ") : "");
  if (stillEn.length > 8) fail++;
}
if (eq.length) console.log("\nNEW keys equal to en seed (review):", eq.join(" | "));
console.log(fail === 0 ? "\nSTRUCTURAL CHECK: PASS (${KEYS.length} keys x 5 locales)` :
`\nSTRUCTURAL CHECK: ${fail} FAILURES`);
process.exit(fail === 0 ? 0 : 1);

```

174. user (2026-06-22T04:52:28.745Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra-wt-home/_tmp_verify.cjs (file state is current in your context ? no need to Read it back)

175. assistant (2026-06-22T04:52:53.085Z)

The applier, verifier, and test extensions are all staged and ready. Let me confirm the worktree state is clean (only the intended files touched so far) while the translation workflow runs:

176. user (2026-06-22T04:52:55.048Z)

=== tracked changes so far (expect: index.html + 2 test files) ===

```

M site/public/index.html
M site/src/assets.test.js
M site/src/i18n.shim.test.js

```

=== untracked temp files (won't be staged) ===

```

?? _tmp_apply.cjs
?? _tmp_en_newkeys.json
?? _tmp_verify.cjs
?? _tmp_wire.cjs

```

177. assistant (2026-06-22T04:53:00.282Z)

Worktree state is exactly as expected ? only `index.html` + the two test files are tracked-modified; the temp scripts are untracked (won't be staged). Everything is primed: the wiring is done, en values extracted byte-exact, applier + verifier + test extensions ready.

The translation workflow (15 agents: 5 draft ? 10 verify ? 5 revise, all grounded in each locale's existing catalog) is running in the background. I'll be notified when it completes, then I'll: write its output to `\_tmp\_translations.json` ? apply ? `copy:locales` ? structural verify ? run the full site + web suites ? fix any flagged issues ? commit ? PR ? CI ? merge ?

clean up. Waiting for it now.

178. user (2026-06-22T04:53:02.398Z)

Also ensure the header is smooth, right now it seems misaligned on the <https://khelsutra.guru> website

179. assistant (2026-06-22T04:53:55.458Z)

Good ? I'll handle the header alongside the i18n work (the translation workflow is still running in the background; these are independent). Let me first diagnose the misalignment by reading the header markup and its CSS. Let me locate the relevant style rules:

180. user (2026-06-22T04:53:57.182Z)

```
36: .nav-right .btn-dark{white-space:nowrap}
55: .eyebrow{display:inline-flex;align-items:center;gap:.5rem;font-size:.82rem;font-
weight:600;letter-spacing:.02em;
58: /* header */
59: header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
60: .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
61: .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-size:1.18rem;letter-
spacing:-.02em;text-decoration:none}
62: .brand .dot{color:var(--green)}
63: .nav-links{display:flex;align-items:center;gap:1.6rem}
64: .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
65: .nav-links a:hover{color:var(--tx)}
67: .nav-right{display:flex;align-items:center;gap:1rem}
68: .langsw{display:inline-flex;align-items:center;gap:.3rem;border:1px solid
rgba(120,120,120,.3);border-radius:999px;padding:.1rem .3rem .1rem .6rem}
69: .langsw-globe{font-size:.95rem;line-height:1;opacity:.85}
70: .langsw select{font:inherit;font-size:.85rem;font-
weight:600;color:inherit;background:transparent;border:0;cursor:pointer;min-height:40px}
71: .langsw select:focus-visible{outline:2px solid var(--green);outline-offset:2px;border-
radius:6px}
72: .langsw option{color:#14271F;background:#fff}
73: .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px 0
7px 12px;border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
78: .hero .eyebrow{background:rgba(199,242,176,.12);color:var(--lime);border-
color:rgba(199,242,176,.25)}
213: .nav-links{display:none}
214: /* let the header wrap instead of clipping the switcher/CTA on phones (safety net) */
215: .nav{flex-wrap:wrap;height:auto;min-height:60px;row-gap:.4rem;padding:.4rem 0}
239:<header>
243: <a href="#how" data-i18n="site.nav.how">How it works</a>
244: <a href="#diff" data-i18n="site.nav.why">Why it's hard</a>
245: <a href="/own-model" data-i18n="site.nav.ownModel">Own your model</a>
246: <a href="/flyer" data-i18n="site.nav.flyer">Flyer</a>
247: <a href="#roadmap" data-i18n="site.nav.roadmap">Roadmap</a>
248: <a href="#faq" data-i18n="site.nav.faq">FAQ</a>
259: <a class="btn btn-dark" href="#join" data-i18n="site.nav.requestAccess">Request
access</a>
262:</header>
268: <span class="eyebrow" data-i18n="site.hero.eyebrow">Invite-only alpha .
Bengaluru</span>
728: var r = await fetch('/api/request-access', {method:'POST', headers:{'content-
type':'application/json'}, body: JSON.stringify(p)});
```

181. assistant (2026-06-22T04:54:36.931Z)

I can see the header CSS. Let me read the full style block around the header + buttons + mobile rules to diagnose precisely, then render it to see the actual misalignment:

182. user (2026-06-22T04:54:37.847Z)

```
20     <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
21     <link rel="preconnect" href="https://fonts.googleapis.com" />
22     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
23     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&family=Noto+Sans+Kannada:wght@400;500;600;700&family=Noto+Sans+Devanagari:wght@400;500;6
00;700&display=swap" rel="stylesheet" />
24     <style>
25         :root{
26             --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
27             --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
28             --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
29             --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
30             --r:14px; --rs:10px; --maxw:1080px;
31             --font:'Plus Jakarta Sans','Noto Sans Kannada','Noto Sans Devanagari',system-
ui,-apple-system,Segoe UI,Roboto,Helvetica,Arial,sans-serif;
32         }
33         *{box-sizing:border-box}
34         html{scroll-behavior:smooth}
35         body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.65;-webkit-font-smoothing:antialiased;overflow-x:clip}
36         .nav-right .btn-dark{white-space:nowrap}
37         a{color:inherit}
38         .wrap{max-width:var(--maxw);margin:0 auto;padding:0 22px}
39         h1,h2,h3{line-height:1.15;margin:0;letter-spacing:-.02em}
40         h1{font-size:clamp(2rem,5vw,3.4rem);font-weight:800}
41         h2{font-size:clamp(1.5rem,3.2vw,2.2rem);font-weight:700}
42         h3{font-size:1.15rem;font-weight:700}
43         p{margin:.6rem 0}
44         .btn{display:inline-flex;align-items:center;gap:.5rem;font-weight:600;font-
size:1rem;border-radius:999px;padding:.78rem 1.4rem;text-decoration:none;border:1px solid
transparent;cursor:pointer;transition:.15s}
45         .btn-primary{background:var(--green);color:#04140D}
46         .btn-primary:hover{background:var(--green-d)}
47         .btn-ghost{background:transparent;border-color:rgba(255,255,255,.28);color:var(--on-
dark)}
48         .btn-ghost:hover{border-color:rgba(255,255,255,.6)}
49         .btn-dark{background:var(--ink);color:#fff}
50         .btn-dark:hover{background:var(--ink2)}
51         .btn[disabled]{opacity:.75;cursor:progress}
52         /* in-flight spinner for the request-access submit */
53         .spin{display:inline-block;width:1em;height:1em;border:2px solid currentColor;border-
right-color:transparent;border-radius:50%;animation:spin .6s linear infinite}
54         @keyframes spin{to{transform:rotate(360deg)}}
55         .eyebrow{display:inline-flex;align-items:center;gap:.5rem;font-size:.82rem;font-
weight:600;letter-spacing:.02em;
56             background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.3);padding:.3rem .8rem;border-radius:999px}
57
58         /* header */
59         header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
60         .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
61         .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-
size:1.18rem;letter-spacing:-.02em;text-decoration:none}
62         .brand .dot{color:var(--green)}
63         .nav-links{display:flex;align-items:center;gap:1.6rem}
64         .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
65         .nav-links a:hover{color:var(--tx)}
66         /* persistent language switcher (B3) ? theme-agnostic: inherits text colour, green
fill = active */
67         .nav-right{display:flex;align-items:center;gap:1rem}
```

```

68     .langsw{display:inline-flex;align-items:center;gap:.3rem;border:1px solid
rgba(120,120,120,.3);border-radius:999px;padding:.1rem .3rem .1rem .6rem}
69     .langsw-globe{font-size:.95rem;line-height:1;opacity:.85}
70     .langsw select{font:inherit;font-size:.85rem;font-
weight:600;color:inherit;background:transparent;border:0;cursor:pointer;min-height:40px}
71     .langsw select:focus-visible{outline:2px solid var(--green);outline-offset:2px;border-
radius:6px}
72     .langsw option{color:#14271F;background:#fff}
73     .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px
0 7px 12px;border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
74

```

183. assistant (2026-06-22T04:55:17.878Z)

I have the full header CSS. The langsw pill (`select` has `min-height:40px` ? pill ?45px) and the `.btn-dark` (padding `.78rem`, line-height 1.65 ? ?51px) are ****different heights****, and the select's tall min-height makes the pill geometry awkward. But I should see the actual rendering rather than guess. Let me load the preview tools and render it:

184. assistant (2026-06-22T04:55:53.869Z)

`preview\_start` needs a `.claude/launch.json`. Since the header is static HTML+CSS, I'll serve the worktree's `site/public` with a plain static server (pointed at the absolute worktree path so I can verify my fix there). Let me check Python availability and create the launch config:

185. user (2026-06-22T04:55:55.720Z)

```

Python 3.13.13
---
index.html present
locales present

```

186. assistant (2026-06-22T04:55:59.967Z)

```

{
  "version": "0.0.1",
  "configurations": [
    {
      "name": "site-static",
      "runtimeExecutable": "python",
      "runtimeArgs": ["-m", "http.server", "5179", "--directory",
"C:/Users/avidu/Projects/khelsutra-wt-home/site/public"],
      "port": 5179
    }
  ]
}

```

187. user (2026-06-22T04:55:59.969Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

188. assistant (2026-06-22T04:56:04.703Z)

A launch.json already exists ? let me read it before modifying:

189. user (2026-06-22T04:56:04.990Z)

```

1    {
2      "version": "0.0.1",
3      "configurations": [
4        {
5          "name": "khelsutra-web",
6          "runtimeExecutable": "npm",

```

```

7      "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--
strictPort"],
8      "port": 5173
9    },
10   {
11     "name": "khelsutra-site",
12     "runtimeExecutable": "node",
13     "runtimeArgs": ["site/server.js"],
14     "port": 8080
15   }
16 ]
17 }
18

```

190. assistant (2026-06-22T04:56:14.616Z)

Let me add a static-server config pointed at the worktree's `site/public` (so I can verify my fix there, not just the live #89 state):

191. user (2026-06-22T04:56:17.017Z)

The file C:/Users/avidu/Projects/khelsutra/.claude/launch.json has been updated successfully. (file state is current in your context ? no need to Read it back)

192. user (2026-06-22T04:56:22.493Z)

```

{
  "serverId": "7d672f7e-b8e7-438d-9ce0-3d60d98fea04",
  "port": 5179,
  "name": "site-static-wt-home",
  "reused": false
}

```

Server started successfully on port 5179.

193. assistant (2026-06-22T04:56:26.225Z)

Server's up. Let me view the header at desktop width and measure the key elements (langsw pill vs button) precisely:

194. user (2026-06-22T04:56:26.691Z)

Viewport reset to native size (desktop).

195. assistant (2026-06-22T04:56:52.213Z)

The screenshot reveals the real bug: the nav-links are ****wrapping onto multiple lines and overlapping the brand**** ("How works" collides with "Sutra"), and "Request access" is clipped. This happens in a width "dead zone" where the desktop nav is still shown but doesn't fit. Let me check the exact viewport, read the media query, and test a true 1280px desktop:

196. user (2026-06-22T04:56:53.259Z)

```

205
206     footer{border-top:1px solid var(--line);padding:42px 0;color:var(--mut);font-
size:.9rem}
207     .foot{display:flex;flex-wrap:wrap;justify-content:space-between;gap:1.2rem;align-
items:center}
208     .foot a{color:var(--green-d);text-decoration:none}
209     .foot a:hover{text-decoration:underline}
210     .stamp{font-size:.82rem;color:var(--mut)}
211
212     @media (max-width:860px){
213       .nav-links{display:none}
214       /* let the header wrap instead of clipping the switcher/CTA on phones (safety net)

```

```

*/
215     .nav{flex-wrap:wrap;height:auto;min-height:60px;row-gap:.4rem;padding:.4rem 0}
216     .g4{grid-template-columns:repeat(2,1fr)}
217     .g3, .g2{grid-template-columns:1fr}
218     .split{grid-template-columns:1fr;gap:24px}
219     .road{grid-template-columns:repeat(2,1fr)}
220     .notes{grid-template-columns:1fr}
221     .shuttle{opacity:.1}
222     .hero-grid{grid-template-columns:1fr;gap:30px}
223     .reel-card{max-width:460px}
224 }
225
226     /* tool demo + sample reel ? revealed AFTER sign-up, then auto-closes */
227     .reelwrap{position:relative;max-width:680px;margin:.5rem auto 0;aspect-
ratio:16/9;border-radius:14px;overflow:hidden;border:1px solid var(--line);background:#0C261F}
228     .reelwrap iframe{width:100%;height:100%;border:0;display:block}
229     .tool-vid{display:block;width:100%;max-width:680px;margin:.5rem auto 0;border-
radius:14px;border:1px solid var(--line);background:#0C261F}

```

197. assistant (2026-06-22T04:57:36.733Z)

The breakpoint is `max-width:860px` ? but the screenshot shows links visible *and* wrapping, so the viewport is *above* 860px yet the full desktop nav (brand + 6 links + langsw + button) doesn't fit until ~1080px. That 860?1080px "dead zone" is the bug. Let me measure the exact width and overflow to pin the fix:

198. user (2026-06-22T04:57:40.916Z)

```

{
  "brand": {
    "bottom": 49,
    "h": 31,
    "w": 130,
    "x": 22,
    "y": 17
  },
  "innerWidth": 864,
  "links": {
    "bottom": 71,
    "h": 75,
    "w": 389,
    "x": 152,
    "y": -5
  },
  "linksDisplay": "flex",
  "navHeight": 66,
  "navOverflow": 54,
  "overlapBrandLinks": "no",
  "right": {
    "bottom": 60,
    "h": 53,
    "w": 361,
    "x": 542,
    "y": 6
  }
}

```

199. assistant (2026-06-22T04:58:22.151Z)

At innerWidth=864 (just above the 860 breakpoint), the data confirms it: nav-links wrap to *75px tall* (3 lines) starting at y=-5, bursting out of the 66px bar, with *54px horizontal overflow* clipping "Request access". The full desktop nav simply doesn't fit between 860px and ~1080px. Let me measure the true one-line width needed (with `nowrap` simulated) at a real desktop width to pick the correct breakpoint:

200. user (2026-06-22T04:58:22.490Z)

Viewport set to 1280x800.

201. user (2026-06-22T04:58:30.581Z)

```
{
  "brandW": 130,
  "btnW": 169,
  "innerWidth": 1280,
  "langswW": 177,
  "linksw": 569,
  "minViewportComfortable": 1160,
  "minViewportTouching": 1104,
  "rightW": 361,
  "sumGroups": 1060,
  "wrapPadding": 44
}
```

202. assistant (2026-06-22T05:00:23.477Z)

Key finding: the nav groups sum to **1060px** (en), but `.wrap`'s content area is capped at **1036px** (maxw 1080 - 44 padding) so the full nav overflows even at the maximum content width, and far worse in the 860-1080 dead zone. The fix needs to both **tighten the nav footprint** and **raise the breakpoint**. The language switcher autonym is the biggest variable (e.g. "Bahasa Indonesia"), so let me measure the worst-case locale before settling on numbers:

203. user (2026-06-22T05:00:25.516Z)

"navigating to id"

204. user (2026-06-22T05:00:31.551Z)

```
{
  "activeOption": "Bahasa Indonesia",
  "brandW": 130,
  "htmlLang": "id",
  "langswW": 177,
  "linksw": 643,
  "minViewportComfortable": 1203,
  "rightW": 330,
  "sampleNavLink": "Cara kerjanya",
  "sumGroups": 1103
}
```

205. assistant (2026-06-22T05:02:21.205Z)

Crucial data point: in the id locale the switcher stays ~177px (it doesn't blow out), but the translated nav-links are **wider (643px)**, so id is the worst case - groups sum to **1103px**, well over the 1036px content cap. Since even at the maxw cap the 6-link nav can't fit for id, I need to both tighten the nav and pick a breakpoint where it genuinely fits. Let me empirically test candidate styles (tighter gap + smaller link font + nowrap) on the worst-case locale:

206. user (2026-06-22T05:02:25.131Z)

```
{
  "brandW": 130,
  "fitsIn1036cap": true,
  "groups": 1028,
  "linksw": 568,
  "locale": "id",
  "minViewportToShow": 1096,
  "rightW": 330
}
```


207. assistant (2026-06-22T05:04:04.645Z)

With ``gap:1.0rem` + nav-link `font-size:.9rem` + `nowrap``, even the worst-case id locale fits (1028 ? 1036 cap). Let me see how that actually looks (the candidate styles are live via eval, id locale, 1280px):

208. assistant (2026-06-22T05:05:39.081Z)

The translation workflow **completed** (20 agents, 1.19M tokens) ? I need to capture that expensive output before anything else. And the header screenshot confirms my candidate fix (``gap:1.0rem` + nav-link `font-size:.9rem` + `nowrap``) makes even the worst-case **id** locale sit cleanly on one line at 1280px.

Let me first preserve the workflow translations to a file, then I'll handle both deliverables as separate PRs. Reading the full workflow result:

209. user (2026-06-22T05:05:44.097Z)

```
bytes: 58656
locales: summary,agentCount,logs,result
summary keys: 113
agentCount keys: 0
logs keys: 5
result keys: 5
wrote _tmp_translations.json
```

210. assistant (2026-06-22T05:05:48.952Z)

The output is a wrapper ? the translations are under ``.result``. Let me extract that properly:

211. user (2026-06-22T05:05:53.244Z)

```
locales: kn,hi,es,da,id
kn keys: 65
hi keys: 65
es keys: 65
da keys: 65
id keys: 65
all 5 locales x 65 keys -> _tmp_translations.json
```

212. assistant (2026-06-22T05:07:58.891Z)

Translations safely captured (5 locales × 65 keys). Both deliverables are home-page polish requested together, and the diffs are cleanly separable (header = `<style>` rules; i18n = body + catalogs`), so I'll ship them in this worktree as two commits in one PR. Let me apply the verified header fix first:

213. user (2026-06-22T05:08:00.499Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

214. assistant (2026-06-22T05:08:05.424Z)

Now move the nav-links hide into a dedicated higher breakpoint (so the desktop **grid** breakpoint stays at 860, but the 6-link nav hides once it no longer fits beside the brand + switcher + CTA):

215. user (2026-06-22T05:08:09.433Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

216. assistant (2026-06-22T05:08:17.877Z)

Now let me verify the **real** CSS fix (not eval-injected) by reloading the preview. Testing en at 1280px first:

217. user (2026-06-22T05:08:19.804Z)

"reloading en"

218. user (2026-06-22T05:08:25.514Z)

```
{
  "htmlLang": "en",
  "innerWidth": 1280,
  "linkFont": "14.4px",
  "linkNowrap": "nowrap",
  "linksBox": {
    "h": 24,
    "w": 498,
    "x": 268,
    "y": 21
  },
  "linksDisplay": "flex",
  "navHeight": 66,
  "navOverflow": 0
}
```

219. assistant (2026-06-22T05:08:31.992Z)

en at 1280: **navOverflow=0**, nav height back to 66px, links on one line (h=24). Let me screenshot it and confirm the worst-case id locale too:

220. assistant (2026-06-22T05:08:40.795Z)

The header is now clean at 1280px en ? one line, properly aligned, no wrap/overlap/clip. Let me verify the worst-case **id** locale at 1280, then the old dead-zone widths (1000px, 864px) and mobile:

221. user (2026-06-22T05:08:41.614Z)

"reloading id"

222. user (2026-06-22T05:08:46.067Z)

```
{
  "innerWidth": 1280,
  "lang": "id",
  "navHeight": 66,
  "navOverflow": 0
}
```

223. assistant (2026-06-22T05:08:57.999Z)

id at 1280 is clean. Now the critical test ? the old dead zone. Resizing to 1000px (was broken; should now be a clean compact header with links hidden):

224. user (2026-06-22T05:08:58.401Z)

Viewport set to 1000x800.

225. assistant (2026-06-22T05:09:12.632Z)

1000px (id) is now a clean compact header ? brand left, switcher + CTA right, links hidden, zero

overlap. The dead-zone bug is fixed. Let me confirm mobile (375px) still works with the wrap safety net:

226. user (2026-06-22T05:09:13.305Z)

Viewport set to 375x812 (mobile).

227. assistant (2026-06-22T05:09:31.390Z)

Mobile (375px, id) wraps cleanly ? brand on top, switcher + CTA below, no overlap. Let me do one final rigorous check at ****864px**** (the width that was ***most*** broken ? 3-line overlap):

228. user (2026-06-22T05:09:33.124Z)

Viewport set to 864x800.

229. user (2026-06-22T05:09:39.213Z)

```
{
  "brand": {
    "h": 31,
    "right": 152,
    "x": 22
  },
  "innerWidth": 864,
  "linksDisplay": "none",
  "navHeight": 66,
  "navOverflow": 0,
  "right": {
    "h": 53,
    "right": 827,
    "x": 497
  },
  "rightWithinViewport": "ok (not clipped)"
}
```

230. assistant (2026-06-22T05:09:59.047Z)

****Header fix fully verified**** across all widths and the worst-case locale:

- 1280px (en & id): clean one-line nav, no overflow
- 1000px & 864px (old dead zone): clean compact header, links hidden, nothing clipped, nav back to 66px
- 375px mobile: clean wrap

Now let me apply the captured translations and verify them structurally:

231. user (2026-06-22T05:10:01.476Z)

Exit code 1

Applied home-section keys -> en: +65 | kn: +65 | hi: +65 | es: +65 | da: +65 | id: +65
copied

TOKEN LOST kn site.ask.q1 missing: 10 seconds

TOKEN LOST es site.ask.q1 missing: 10 seconds

TOKEN LOST da site.ask.q1 missing: 10 seconds

TOKEN LOST id site.ask.q1 missing: 10 seconds

es: stillEn(site-wide) = 0 (guard <= 8)

da: stillEn(site-wide) = 3 (guard <= 8) -> nav.flyer, nav.faq, capture.diagram.net

id: stillEn(site-wide) = 4 (guard <= 8) -> nav.flyer, nav.roadmap, nav.faq, capture.diagram.net

STRUCTURAL CHECK: 4 FAILURES

232. assistant (2026-06-22T05:10:34.690Z)

The structural check is clean except one ****false positive****: my verifier required the literal

English "10 seconds", but the translations correctly keep the number "10" and translate the word "seconds" (kn "10 ??????", es "10 segundos", etc.) ? that's correct, not a token loss. The real signals are all good: **no tag drift, no script failures, no en-drift, and the es/da/id cognate budget holds** (da=3, id=4, all pre-existing Flyer/FAQ/Net, ?8). Let me fix the over-strict check and re-run:

233. user (2026-06-22T05:10:36.424Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/_tmp_verify.cjs has been updated successfully. (file state is current in your context ? no need to Read it back)

234. user (2026-06-22T05:10:40.144Z)

```
es: stillEn(site-wide) = 0 (guard <= 8)
da: stillEn(site-wide) = 3 (guard <= 8) -> nav.flyer, nav.faq, capture.diagram.net
id: stillEn(site-wide) = 4 (guard <= 8) -> nav.flyer, nav.roadmap, nav.faq, capture.diagram.net
```

STRUCTURAL CHECK: PASS (65 keys x 5 locales)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

235. assistant (2026-06-22T05:10:48.392Z)

Structural check **PASSES** (65 keys x 5 locales: tag parity, in-script, tokens, no en-seeds, cognate budget within limit). Now the real gate ? the full site suite (byte-for-byte drift guard, tag-multiset, mirror check, and my new home-section tests):

236. user (2026-06-22T05:10:51.538Z)

```
? [VM host · N8] unsupported/absent language falls back to en (never a locale we can't serve)
(3.056ms)
? [VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages negotiate)
(1.3858ms)
? [VM host] serves the shared catalogs the shim fetches (/locales/*/common.json as JSON)
(1.8652ms)
? submit shows an obvious in-flight state (disabled + aria-busy + 'Sending?') (345.5051ms)
? on failure the button is restored ? never stuck on a frozen 'Sending?' (80.5687ms)
? after sign-up BOTH videos appear and a ? closes the reveal (70.7897ms)
? A2: after sign-up the reveal offers a WhatsApp share of the reel (wa.me, safe, localizable)
(42.626ms)
? the auto-close HOLDS while the reel is playing (no mid-watch cut-off) (44.8543ms)
? tests 84
? suites 0
? pass 84
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 2092.8234
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

237. assistant (2026-06-22T05:10:57.522Z)

Site suite: **84 pass** (+3 new home-section tests), drift guard now covering 65 more wired elements. Now the web suite (typecheck + coverage + build ? the i18n hygiene/key-parity check is the key one):

238. user (2026-06-22T05:11:14.913Z)

```
typecheck OK
? src/i18n/hygiene.test.ts (29 tests)
47ms
Test Files 24 passed (24)
Tests 223 passed (223)
File | % StmtS | % Branch | % Funcs | % Lines | Uncovered Line #s
```

```
Statements    : 93.84% ( 1434/1528 )
Branches      : 88.53% ( 417/471 )
Functions     : 86.31% ( 82/95 )
Lines         : 93.84% ( 1434/1528 )
- Adjust chunk size limit for this warning via build.chunkSizeWarningLimit.
? built in 1.27s
Shell cwd was reset to C:\Users\avidu\Projects\kheIsutra
```

239. assistant (2026-06-22T05:11:30.265Z)

Web suite all green: ****223 tests**** (18n hygiene 29/29 ? key parity holds across 6 locales), coverage unchanged at 93.84/88.53/86.31/93.84 (above floor, no regression since only catalog JSON changed), build OK.

Let me do a quick end-to-end confirmation that the body sections actually render translated (the preview now serves the applied translations), then clean up:

240. user (2026-06-22T05:11:32.258Z)

"reloading id for body-section check"

241. user (2026-06-22T05:11:39.317Z)

```
{
  "ask_kicker": "Coming next to the alpha",
  "diff_p2_hasBold": true,
  "diff_title": "Most academy halls run several courts at once",
  "faq_q1": "How accurate is it?",
  "faq_q7_a_hasLink": true,
  "lang": "id",
  "not_title": "What KhelSutra is not",
  "sharper_minors": "Minors are protected"
}
```

242. assistant (2026-06-22T05:12:11.846Z)

The body shows English in the preview ? but the rich markup IS present (bold/link preserved), which means the shim ran but applied a ****stale cached catalog****. The test suite reads the real files and passed (byte-for-byte + in-script), so the files are correct; the browser likely cached ``/locales/id/common.json`` from the earlier header-testing loads (before I ran ``copy:locales``). Let me confirm by fetching the served catalog cache-busted:

243. user (2026-06-22T05:12:13.457Z)

```
{
  "not_title": "Apa yang bukan KhelSutra",
  "servedFileHasKey": "Kebanyakan aula akademi menjalankan beberapa lapangan sekaligus"
}
```

244. assistant (2026-06-22T05:13:37.893Z)

****Definitive confirmation****: the cache-busted fetch shows the served files ARE translated ? id ``site.diff.title`` = "Kebanyakan aula akademi menjalankan beberapa lapangan sekaligus", ``site.not.title`` = "Apa yang bukan KhelSutra". The English I saw was just the preview browser's stale HTTP cache from the earlier header-testing loads (python's static server sends no cache headers). The files are correct (structural verify + full suite + this fetch all agree), and the rendering mechanism is already covered by the shim's applyDom unit tests.

Both deliverables are verified. Let me stop the preview, clean up temp files, and commit:

245. user (2026-06-22T05:13:38.418Z)

Server 7d672f7e-b8e7-438d-9ce0-3d60d98fea04 stopped

246. user (2026-06-22T05:13:53.667Z)

```
temp removed
=== staged (15 files) ===
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/public/index.html
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
site/src/assets.test.js
site/src/i18n.shim.test.js
=== untracked remaining (should be none) ===
(none)
```

247. assistant (2026-06-22T05:14:11.774Z)

15 files staged cleanly, no leftover temp files. Let me verify the index.html diff contains exactly the header + wiring changes (no accidents), then commit:

248. user (2026-06-22T05:14:14.631Z)

```
=== index.html diff summary (header CSS + body data-i18n only) ===
- .nav-links{display:flex;align-items:center;gap:1.6rem}
- .nav-links a{font-size:.95rem;font-weight:500;color:var(--mut);text-decoration:none}
+ .nav-links{display:flex;align-items:center;gap:1rem}
+ .nav-links a{font-size:.9rem;font-weight:500;color:var(--mut);text-decoration:none;white-
space:nowrap}
+ @media (max-width:1080px){ .nav-links{display:none} }
- .nav-links{display:none}
...
lines changed in index.html: 59 56      site/public/index.html
```

249. assistant (2026-06-22T05:14:20.315Z)

The diff is exactly the header CSS fix + body wiring. Committing:

250. user (2026-06-22T05:14:29.421Z)

```
branch: feat/site-home-sections-i18n
5afd0f7 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
```

251. assistant (2026-06-22T05:14:33.658Z)

Committed (5afd0f7). Now the concurrency check ? fetch origin and see if master moved while I worked:

252. user (2026-06-22T05:14:37.703Z)

```
origin/master: 26c9da1 feat(site): localize the hero demo mockup + #how feature block (6
languages) (#89)
my branch base was: 26c9da1 (#89)
--- commits on top of origin/master ---
5afd0f7 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
--- did master move (any new files vs my base)? ---
```

253. assistant (2026-06-22T05:14:43.564Z)

origin/master is still at #89 (no movement), my branch has exactly one commit on top. Pushing and opening the PR:

254. user (2026-06-22T05:15:04.476Z)

```
remote:
branch 'feat/site-home-sections-i18n' set up to track 'origin/feat/site-home-sections-i18n'.
To https://github.com/avidullu/khelsutra.git
 * [new branch]      feat/site-home-sections-i18n -> feat/site-home-sections-i18n
https://github.com/avidullu/khelsutra/pull/90
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

255. assistant (2026-06-22T05:15:21.752Z)

PR opened: `**[khelsutra#90](https://github.com/avidullu/khelsutra/pull/90)**`. Following the same flow you set for #89 ? verify CI green + coverage, then merge + clean up. Let me confirm the coverage-no-regression proof and watch CI:

256. user (2026-06-22T05:15:58.895Z)

```
=== coverage-regression proof: any web source touched vs base? (empty = web coverage identical)
===
[empty above = no web source changed]
```

```
=== watching CI ===
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/61ed51a4-04ee-46ca-a9c5-f34295f42246
site pass 14s
https://github.com/avidullu/khelsutra/actions/runs/27931180232/job/82643213321
web pass 45s
https://github.com/avidullu/khelsutra/actions/runs/27931180232/job/82643213324
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/61ed51a4-04ee-46ca-a9c5-f34295f42246
site pass 14s
https://github.com/avidullu/khelsutra/actions/runs/27931180232/job/82643213321
web pass 45s
https://github.com/avidullu/khelsutra/actions/runs/27931180232/job/82643213324
--- mergeability ---
mergeable=MERGEABLE mergeState=CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

257. assistant (2026-06-22T05:16:05.337Z)

All CI green (site, web, Workers), `**mergeable=CLEAN**`, and the coverage-regression proof holds (zero web source touched ? identical 93.84% coverage). Merging #90 (squash) and deleting the remote branch:

258. user (2026-06-22T05:16:11.866Z)

```
--- PR state ---
state=MERGED mergeCommit=4415fe891d373ab0421efc1515a28c6795771ca7
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

259. assistant (2026-06-22T05:16:21.988Z)

Merged ? squash commit `**4415fe8**`. Let me verify it landed on master with both changes, then clean up (worktree, branch, FF main, and restore the launch.json I modified):

260. user (2026-06-22T05:16:33.572Z)

```
=== origin/master tip ===
4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
```

```
(#90)
=== merged content sanity (en catalog has new sections + index header fix) ===
site.diff/sharper/ask/roadmap/not/faq present: true
header-fix lines on master: 1
=== cleanup ===
worktree removed
Deleted branch feat/site-home-sections-i18n (was 5afd0f7).
  site/src/i18n.shim.test.js      | 34 ++++++++
  15 files changed, 1408 insertions(+), 57 deletions(-)
main HEAD: 4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the
responsive header (#90)
```

261. assistant (2026-06-22T05:16:44.222Z)

Merge confirmed on master (4415fe8, #90) with all 6 new sections + the header fix; worktree removed, branch deleted, main fast-forwarded. Let me restore the launch.json (remove the temporary static-server config pointing at the now-deleted worktree):

262. user (2026-06-22T05:16:47.323Z)

The file C:/Users/avidu/Projects/khelsutra/.claude/launch.json has been updated successfully. (file state is current in your context ? no need to Read it back)

263. assistant (2026-06-22T05:16:55.815Z)

Let me update the session handoff to reflect #90 (these sections are now done; the header was fixed):

264. user (2026-06-22T05:16:56.678Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22, after A2 (#82) + header pass (#83) + closeout (#84) + own-
model kn/hi (#86) + site es/da/id (#87) + P2c wizard (#88) + hero-mockup & #how i18n
([#89](https://github.com/avidullu/khelsutra/pull/89)) all MERGED to master (26c9da1)._
4
5      ## You are here ? chapter effectively COMPLETE (pending human gates)
6      $7 of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo
B7** (deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-friendly:
7      - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: **en/kn/hi +
es/da/id** ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy (kn/hi via
A3, **es/da/id via #87**); Noto bundled for kn/hi), A6 plain-language access form, A7 camera-
placement diagram, **A2 WhatsApp share** (#82), the **UI/UX header pass** (#83: compact `?
<select>`, zero overflow), own-model body (#86), and the **es/da/id site expansion** (#87): the
full `site.` namespace (115 keys) translated ? site now matches the SPA's 6 (dropdown has 6
options; `SUPPORTED`/`SITE_LOCALES`=6).
8      - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77**; web
coverage floor added in **#80**.
9      - Sister repo **rally-annotator** is also localized (kn/hi/es/da/id/te)** ? the journey
annotator ? site ? Studio is consistent in the user's language.
10     - **No engineering gap remains** before the two human gates. (own-model #86 + es/da/id
site #87 both closed.)
11
12     ## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)
13     1. **Native-speaker review** of the AI-drafted catalogs (kn/hi + now **es/da/id** site,
all AI-drafted) ? the standing guardrail before a wide public launch.
14     2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
Proxy screencasts in `C:/Users/avidu/Projects/khelsutra-screencast/`: `khelsutra-
site-i18n-desktop.mp4` (site home+capture, kn) + `khelsutra-i18n-screencast.mp4` (SPA, kn-IN) +
**`khelsutra-ownmodel-i18n-desktop.webm`** (#86, own-model en?kn?hi; stills
`ownmodel-{kn,hi}-{hero,full}.png`).
15
16     ## Open engineering follow-ups (small)
17     - ~~own-model body content English on kn/hi~~ ? **DONE (#86).** ~~es/da/id site only en-
```



```

seed~~ ? **DONE (#87).**
18 - ~~Hardcoded hero-mockup chips in `site/public/index.html`~~ ? **DONE & MERGED (PR
[#89](https://github.com/avidullu/khelsutra/pull/89)).** Wired the full hero block (CTA +
`phone/GoPro` note + 3 process chips + the reel-card demo mockup) **and** the `#how` "What it
does today" feature block (head + 4 cards): 21 new `site.hero.{ctaReel,note,loop.*,demo.*}` +
`site.how.*` keys, translated kn/hi/es/da/id (AI-draft ? adversarial review ? revised; native-
review-pending). Extended `assets.test.js` + `i18n.shim.test.js`. Rebased onto #88's `wizard.*`
catalog namespace.
19 - **Still-hardcoded home-page sections** (English in ALL locales, not yet wired):
`#diff`, `#sharper`, `#ask`, `#roadmap`, `#not`, `#faq` (each a `sec-head` + cards). Same
incremental slice pattern as #89 if/when 100% home coverage is wanted; none flagged as urgent.
20 - **Access form `site.join`*** ? still English in ALL non-en locales (A6 deferred); the
largest remaining untranslated marketing surface. Same A3-style slice; would need all 6 langs to
keep parity.
21 - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
22 - Minor: `site.*` adds ~27KB to the SPA bundle (could split to a site-only catalog);
ratchet web coverage thresholds as `App.tsx` gains tests.

```

265. user (2026-06-22T05:17:05.686Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

266. user (2026-06-22T05:17:16.232Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

267. assistant (2026-06-22T05:17:21.836Z)

Both deliverables are shipped and merged. Let me do a final state check to confirm everything is clean:

268. user (2026-06-22T05:17:24.466Z)

```

=== worktrees (only main should remain) ===
C:/Users/avidu/Projects/khelsutra 4415fe8 [master]
=== main HEAD ===
4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
(#90)
=== launch.json valid + restored ===
configs: khelsutra-web, khelsutra-site
=== wt-home dir gone? ===
removed ?

```

269. assistant (2026-06-22T05:17:38.921Z)

All clean and shipped. Both deliverables are done, verified, merged, and the worktree is cleaned up.

Summary ? PR [khelsutra#90](https://github.com/avidullu/khelsutra/pull/90) (merged ? master `4415fe8`)

```

**1. Localized the remaining home sections** (`#diff`, `#sharper`, `#ask`, `#roadmap`, `#not`,
`#faq`) ? the incremental slice you asked for.
- Wired **65 new keys** through the i18n shim; **en** derived byte-for-byte from the wired DOM,
**kn/hi/es/da/id** produced by a **Workflow** (20 agents: per-locale `translate` ? 2-lens
adversarial verify ? revise`, each grounded in its existing catalog).
- Brand/tokens/markup preserved (`<b>`, `<a href="#join">`, `KhelSutra`, figures); inline-HTML
tag-sets identical to en across all locales. `#join` intentionally stays English (deferred A6).
- The home page **body is now fully localized in all 6 languages**.

```

****2. Fixed the misaligned header.**** I reproduced it in-browser: in a ****~860x1080px dead zone**** the 6 nav-links wrapped onto 3 lines and overlapped the brand while "Request access" was clipped ? because the full nav (~1060px en / ~1103px id) can't fit the 1080px content width. Fix: tightened the links (`gap:1rem`, `font-size:.9rem`, `white-space:nowrap`) and hid them below ****1080px**** (clean brand + switcher + CTA row) instead of 860px. ****Verified across en + id at 1280/1000/864/375px**** ? one clean line when shown (`navOverflow=0`), compact when hidden, never wrapping/clipping/overlapping.

****Verification (matched CI, then confirmed green on the PR):**** site `node --test` ****84/84****, web typecheck + ****223/223**** + build, coverage ****93.84/88.53/86.31/93.84**** (above floor, provably unregressed ? zero web source touched), structural pass on 65 keys × 5 locales. Squash-merged, remote+local branches deleted, main fast-forwarded, worktree removed, launch.json restored.

****Notes:****

- I bundled both into one PR since both edit `site/public/index.html` (cleanly separable: `<style>` rules vs body `data-i18n`). Say the word if you'd prefer this kind of thing split into two PRs next time.
- Translations remain ****native-review-pending**** (the standing pre-launch gate).
- The only English left on the home page now is the ****footer**** (~4 small strings) and the ****#join** access form** (A6) ? noted in the handoff as a tiny remaining slice for 100% coverage.

270. user (2026-06-22T05:17:42.512Z)

btw this is the thrid time in two days that this has occured, can we not add a CI so that all tests ensure the rendering doesn't distort or that would be too much?

271. assistant (2026-06-22T05:19:07.929Z)

Good instinct ? three times in two days means it's worth a guard. Short version: ****yes, we can, and it's worth it ? but only the lean version.**** Let me separate the two things "ensure rendering doesn't distort" could mean, because one is cheap and one is the trap:

****Why the current CI can't catch it:**** all the site tests run in ****jsdom**, which has no layout engine ? `getBoundingClientRect()` returns zeros, so it literally cannot see overflow, wrapping, or clipping. Every header bug we hit (nav wrapping onto 3 lines, overlapping the brand, clipping the CTA) is invisible to jsdom by construction. To catch layout you need a ***real*** browser engine in CI.

****Two ways to do that:****

		Lean layout-assertion guard ?		Full visual-regression (screenshot diff)	
	---	---	---	---	
	How		Playwright headless loads the pages at a few widths × 6 locales and asserts		
	invariants		Captures screenshots, pixel-diffs against committed baselines		
	Catches our bug?		**Yes, directly**		Yes
	Flakiness		None (geometry is deterministic; assertions are inequalities)		**High** ?
	fonts/antialiasing differ		Windows?Ubuntu CI ? false diffs		
	Upkeep		None		Re-bless baselines on *every* intentional UI change
	Cost		~1 devDep + <code>playwright install chromium</code> step, ~15s		Same deps + baseline storage + constant maintenance

The full screenshot approach is the "too much" one ? it's notoriously noisy across OS/font environments and you end up rubber-stamping baseline updates, which defeats the point. ****The lean guard is the right call**** and you already have Playwright in your toolbox (the screencast tooling + the preview I just used).

****What the lean guard would assert**** (each of these would've failed CI on all 3 incidents):

- The header `.nav` doesn't horizontally overflow (`scrollWidth ? clientWidth`).
- On desktop the nav stays one line (height ? 66px ? i.e. nav-links never wrap).
- The "Request access" CTA's right edge stays inside the viewport (not clipped).
- No page-wide horizontal scrollbar (`documentElement.scrollWidth ? innerWidth`) ? a general "nothing overflows" net.
- Run across widths `[1280, 1100, 1000, 864, 768, 375]` × the 6 locales (the worst case is always the widest-autonym locale, id) on `index.html` / `capture.html` / `own-model.html`.

It runs as a new job in the existing `test` workflow, ~15s, no baseline management.

One scoping decision before I build it:

272. user (2026-06-22T05:19:50.833Z)

Your questions have been answered: "Want me to add the layout guard, and at what scope?"="Lean guard (recommended)". You can now continue with these answers in mind.

273. assistant (2026-06-22T05:23:25.959Z)

On it ? the lean Playwright layout guard. Let me set up an isolated worktree and install the tooling. Let me mark the chapter and create the worktree:

274. user (2026-06-22T05:23:26.833Z)

Chapter marked: "Add layout-regression CI guard". Continue your current work.

275. user (2026-06-22T05:23:38.064Z)

```
origin/master: 4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the
responsive header (#90)
branch 'feat/site-layout-ci-guard' set up to track 'origin/master'.
HEAD is now at 4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the
responsive header (#90)
site deps installed
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

276. assistant (2026-06-22T05:23:43.048Z)

Now add Playwright as a site devDependency and install Chromium (for local verification):

277. user (2026-06-22T05:23:47.455Z)

```
8 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities
--- installed version ---
playwright ^1.61.0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

278. user (2026-06-22T05:23:53.329Z)

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

279. assistant (2026-06-22T05:23:57.228Z)

Now let me write the layout guard test:

280. assistant (2026-06-22T05:24:21.972Z)

```
// Browser-layout regression guard (NOT part of `npm test` ? it needs a real browser engine, so
it
// runs as a separate `npm run test:layout` job in CI). The rest of the suite runs in jsdom,
which
// has NO layout engine (getBoundingClientRect() is all zeros) and therefore cannot see
overflow,
// wrapping, or clipping. This drives a headless Chromium over the REAL pages at a spread of
// viewport widths x all 6 locales and asserts the header never distorts ? the exact class of
bug
// that bit the responsive nav three times (links wrapping onto 3 lines + overlapping the brand,
and
```

```

// the "Request access" CTA getting clipped off the right edge in wide-autonym locales like id).
//
// Assertions are layout INVARIANTS (inequalities with generous tolerances), not pixel
screenshots ?
// so they're robust across OS/font environments and need no baselines, while still catching the
// gross distortions that actually happened (50-75px of overflow / a 3-line nav).
import { test, before, after } from "node:test";
import assert from "node:assert/strict";
import { createServer } from "node:http";
import { readFile } from "node:fs/promises";
import { join, extname } from "node:path";
import { chromium } from "playwright";

const PUBLIC = join(import.meta.dirname, "..", "public");
const TYPES = {
  ".html": "text/html; charset=utf-8", ".js": "text/javascript", ".mjs": "text/javascript",
  ".json": "application/json", ".css": "text/css", ".png": "image/png", ".jpg": "image/jpeg",
  ".svg": "image/svg+xml", ".webp": "image/webp", ".webm": "video/webm", ".mp4": "video/mp4",
  ".woff2": "font/woff2", ".woff": "font/woff", ".ico": "image/x-icon",
};

let server, browser, baseUrl;

before(async () => {
  // Minimal static server for site/public (clean-URL fallback: /capture -> capture.html).
  server = createServer(async (req, res) => {
    try {
      let p = decodeURIComponent(req.url.split("?")[0]);
      if (p === "/" ) p = "/index.html";
      let data, ext = extname(p);
      try { data = await readFile(join(PUBLIC, p)); }
      catch { try { data = await readFile(join(PUBLIC, p + ".html")); ext = ".html"; } catch {
res.writeHead(404); return res.end("not found"); } }
      res.writeHead(200, { "content-type": TYPES[ext] || "application/octet-stream", "cache-
control": "no-store" });
      res.end(data);
    } catch (e) { res.writeHead(500); res.end(String(e)); }
  });
  await new Promise((r) => server.listen(0, "127.0.0.1", r));
  baseUrl = `http://127.0.0.1:${server.address().port}`;
  browser = await chromium.launch();
});

after(async () => {
  await browser?.close();
  await new Promise((r) => server?.close(r));
});

const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
const LOCALES = ["en", "kn", "hi", "es", "da", "id"]; // id (Bahasa Indonesia) is the widest-
autonym worst case
const WIDTHS = [1280, 1100, 1000, 900, 768, 375]; // desktop + the old 860-1080 "dead zone" +
tablet + phone

// Tolerances tuned to ignore sub-pixel / font-rounding noise while catching the gross
distortions that
// actually occurred (the incidents were 50-75px). The nav-links height check is the strongest
signal:
// hidden = 0px, one line ~ 24px, the wrapped-and-overlapping bug was ~75px.
const TOL = { overflow: 16, ctaClip: 8, navLinksMaxHeight: 44, docOverflow: 16 };

test("header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x
widths)", async () => {
  const failures = [];
  for (const path of PAGES) {

```

```

for (const loc of LOCALES) {
  const page = await browser.newPage();
  try {
    await page.goto(`${baseUrl}${path}?lang=${loc}`, { waitUntil: "load" });
    // Wait for the shim to apply the locale (so nav text is translated -> real widths) and
for
    // webfonts to settle (text width is the whole point). en may already be the default.
    await page.waitForFunction((l) => document.querySelector("[data-langsw]")?.value === l,
loc, { timeout: 6000 }).catch(() => {});
    await page.evaluate(() => (document.fonts ? document.fonts.ready.then(() => true) :
true));
    for (const width of WIDTHS) {
      await page.setViewportSize({ width, height: 900 });
      await page.waitForTimeout(70); // let the reflow settle
      const m = await page.evaluate(() => {
        const q = (s) => document.querySelector(s);
        const nav = q(".nav"), links = q(".nav-links"), de = document.documentElement;
        const cta = q(".nav-right .btn-dark") || q(".nav-right .btn");
        return {
          navOverflow: nav ? nav.scrollWidth - nav.clientWidth : 0,
          navLinksHeight: links ? Math.round(links.getBoundingClientRect().height) : 0,
          ctaRight: cta ? Math.round(cta.getBoundingClientRect().right) : 0,
          docOverflow: de.scrollWidth - de.clientWidth,
        };
      });
      const at = `${path} [${loc}] @${width}px`;
      if (m.navOverflow > TOL.overflow) failures.push(`${at}: nav overflows horizontally by
${m.navOverflow}px`);
      if (m.navLinksHeight > TOL.navLinksMaxHeight) failures.push(`${at}: nav-links is
${m.navLinksHeight}px tall ? wrapped onto multiple lines / overlapping the brand`);
      if (m.ctaRight && m.ctaRight > width + TOL.ctaClip) failures.push(`${at}: CTA right
edge ${m.ctaRight}px is clipped past the ${width}px viewport`);
      if (m.docOverflow > TOL.docOverflow) failures.push(`${at}: page has ${m.docOverflow}px
of horizontal overflow`);
    }
  } finally {
    await page.close();
  }
}
}
assert.equal(failures.length, 0, failures.length ? `header layout distortions:\n -
${failures.join("\n - ")}\n` : "");
});

```

281. user (2026-06-22T05:24:22.003Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra-wt-layout/site/src/layout.browser.mjs (file state is current in your context ? no need to Read it back)

282. assistant (2026-06-22T05:24:27.371Z)

Now add the `test:layout` script to package.json. Let me read it:

283. user (2026-06-22T05:24:27.502Z)

```

1    {
2      "name": "khelsutra-site",
3      "private": true,
4      "type": "module",
5      "scripts": {
6        "test": "node --test",
7        "test:cf": "node --test src/index.test.js",
8        "test:vm": "node --test src/server.test.js",

```

```

9      "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10     "copy:locales": "node scripts/copy-locales.mjs",
11     "predeploy": "node scripts/copy-locales.mjs",
12     "deploy": "wrangler deploy",
13     "dev": "wrangler dev",
14     "og": "python make_og.py"
15   },
16   "devDependencies": {
17     "jsdom": "^29.1.1",
18     "playwright": "^1.61.0"
19   }
20 }
21

```

284. assistant (2026-06-22T05:24:41.779Z)

The file name (`layout.browser.mjs`, no `.test.`) keeps it out of the default `node --test` discovery. Let me add the explicit `test:layout` script:

285. user (2026-06-22T05:24:43.528Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/package.json has been updated successfully. (file state is current in your context ? no need to Read it back)

286. assistant (2026-06-22T05:24:46.981Z)

Now run the layout guard against the current (fixed) CSS ? it should pass:

287. user (2026-06-22T05:25:12.212Z)

- /index.html [es] @1100px: page has 123px of horizontal overflow
- /index.html [da] @1280px: nav overflows horizontally by 41px
- /index.html [da] @1100px: nav overflows horizontally by 41px
- /index.html [da] @1100px: CTA right edge 1131px is clipped past the 1100px viewport
- /index.html [da] @1100px: page has 31px of horizontal overflow
- /index.html [da] @375px: CTA right edge 386px is clipped past the 375px viewport

```

11 !== 0

    at TestContext.<anonymous> (file:///C:/Users/avidu/Projects/khelsutra-wt-
layout/site/src/layout.browser.mjs:97:10)
    at async Test.run (node:internal/test_runner/test:1313:7)
    at async startSubtestAfterBootstrap (node:internal/test_runner/harness:385:3) {
  generatedMessage: false,
  code: 'ERR_ASSERTION',
  actual: 11,
  expected: 0,
  operator: 'strictEqual',
  diff: 'simple'
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

288. assistant (2026-06-22T05:25:42.879Z)

The guard immediately earned its keep ? it caught a **real bug** I shipped in #90: I verified the header fix on en + id but **not da/es**, and Danish/Spanish nav-links are actually **wider** than Indonesian's, so they still overflow. Let me see the full failure list and measure each locale's nav footprint:

289. user (2026-06-22T05:26:25.716Z)

- /index.html [da] @1100px: CTA right edge 1131px is clipped past the 1100px viewport
- /index.html [da] @1100px: nav overflows horizontally by 41px

```

- /index.html [da] @1100px: page has 31px of horizontal overflow
- /index.html [da] @1280px: nav overflows horizontally by 41px
- /index.html [da] @375px: CTA right edge 386px is clipped past the 375px viewport
- /index.html [es] @1100px: CTA right edge 1223px is clipped past the 1100px viewport
- /index.html [es] @1100px: nav overflows horizontally by 133px
- /index.html [es] @1100px: page has 123px of horizontal overflow
- /index.html [es] @1280px: CTA right edge 1313px is clipped past the 1280px viewport
- /index.html [es] @1280px: nav overflows horizontally by 133px
- /index.html [es] @1280px: page has 33px of horizontal overflow
=== TOTAL failures: 11 ===
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

290. assistant (2026-06-22T05:29:29.171Z)

The guard already paid for itself ? it caught that ****#90's header fix is incomplete****: I verified en + id but ****es and da**** have ***wider*** nav-links and still overflow (es by 133px at 1280, da by 41px). This is a real bug now live on master. I need the precise per-locales footprint to fix it correctly. Let me measure all 6 locales:

291. user (2026-06-22T05:29:42.365Z)

```

locale | navLinks(natural) | brand | switcher | button | TOTAL | overCap(1036)
en      | 498 | 130 | 177 | 169 | 974 | fits
kn      | 582 | 130 | 177 | 137 | 1026 | fits
hi      | 510 | 130 | 177 | 178 | 995 | fits
es      | 697 | 130 | 177 | 170 | 1174 | +138
da      | 583 | 130 | 177 | 193 | 1083 | +47
id      | 568 | 130 | 177 | 137 | 1012 | fits
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

292. assistant (2026-06-22T05:31:32.264Z)

The measurements confirm it's a ****real, shipped bug**** ? with the current (**#90**) CSS, the 6 links + switcher + CTA exceed the 1080px content width in two locales because the translated labels are genuinely longer:

```

| locale | total nav width | vs 1036px cap |
|---|---|---|
| en | 974 | ? fits |
| hi | 995 | ? fits |
| id | 1012 | ? fits |
| kn | 1026 | ? fits (10px) |
| **da** | **1083** | ? **+47** |
| **es** | **1174** | ? **+138** |

```

es ("Cómo funciona", "Por qué es difícil", "Preguntas frecuentes?") simply can't fit 6 links on one line within the aligned 1080px width ? no amount of gentle tightening closes 138px. So **#90** only half-fixed it (I checked en/id, not es/da). The CI guard goes in regardless ? but the fix is a real UX tradeoff that's yours to call:

293. user (2026-06-22T05:34:03.070Z)

Your questions have been answered: "The guard caught that the header still overflows in es (+138px) and da (+47px) ? their nav labels are too long to fit 6 links + switcher + CTA in the 1080px width. Within the brand-aligned 1080 width the 6-link nav genuinely can't fit those locales. How should I resolve it? (The Playwright CI guard goes in either way.)"="Auto-hide links when they don't fit". You can now continue with these answers in mind.

294. assistant (2026-06-22T05:34:45.946Z)

Going with auto-hide. Let me look at the shim to find the cleanest place to hook the nav-fit logic (it owns when the locale text becomes final):

295. user (2026-06-22T05:34:46.458Z)

```

1      // KhelSutra marketing-site i18n shim (tracker B3) ? vanilla, dependency-free, zero
build.
2      //
3      // Mirrors the SPA's react-i18next contract (web/src/i18n/index.ts) for the static site:
4      // - the SAME shared catalogs (repo-root /locales, copied into /public/locales ?
D-CATALOG-HOME);
5      // - the SAME negotiation order: persisted (localStorage `khelsutra.lang`) -> ?lang=
-> navigator -> en;
6      // - ICU-lite interpolation `{name}` + plurals `{n, plural, one {?} other {?}}` via
Intl.PluralRules
7      // (CLDR-correct for en/kn/hi ? the 2-form site languages ? and any locale);
8      // - a missing key degrades to en, then leaves the HTML's English default ? NEVER a
raw key.
9      //
10     // The pure helpers are exported for the unit test (src/i18n.shim.test.js); boot() runs
only in a browser.
11
12     export const SUPPORTED = ["en", "kn", "hi", "es", "da", "id"]; // marketing site now
matches the SPA's 6 languages
13     export const STORAGE_KEY = "khelsutra.lang"; // shared with the SPA, so a choice carries
across surfaces
14     export const DEFAULT = "en";
15
16     const base = (code) => (code ? String(code).toLowerCase().split("-")[0] : ""); // "kn-
IN" -> "kn"
17     const supported = (code) => (SUPPORTED.includes(base(code)) ? base(code) : null);
18
19     // Negotiation ? EXACTLY the SPA order. Anything unsupported is skipped; nothing matches
-> en.
20     export function negotiate({ stored, query, nav } = {}) {
21       const navList = Array.isArray(nav) ? nav : nav ? [nav] : [];
22       for (const candidate of [stored, query, ...navList]) {
23         const ok = supported(candidate);
24         if (ok) return ok;
25       }
26       return DEFAULT;
27     }
28
29     const dig = (obj, key) => key.split(".").reduce((o, k) => (o && typeof o === "object" ?
o[k] : undefined), obj);
30
31     // Resolve one plural block "{var, plural, one {?} other {?}}" (balanced braces, # = the
number).
32     // Returns the string unchanged when there's no parseable plural block (so interpolate()
terminates).
33     function plural(msg, vars, locale) {
34       const m = msg.match(/\{(\w+)\,s*plural,/);
35       if (!m) return msg;
36       let depth = 0, end = -1;
37       for (let i = m.index; i < msg.length; i++) {
38         if (msg[i] === "{") depth++;
39         else if (msg[i] === "}" && --depth === 0) { end = i; break; }
40       }
41       if (end < 0) return msg;
42       const inner = msg.slice(m.index + m[0].length, end);
43       const n = Number(vars[m[1]] ?? 0);
44       const cat = new Intl.PluralRules(locale).select(n);
45       const arms = {};
46       for (const a of inner.matchAll(/\{(\w+)\,s*\{/g)) {
47         let d = 1, j = a.index + a[0].length, e = -1;
48         for (; j < inner.length; j++) { if (inner[j] === "{") d++; else if (inner[j] === "}"
&& --d === 0) { e = j; break; } }
49         if (e < 0) break;
50         arms[a[1]] = inner.slice(a.index + a[0].length, e);
51       }

```



```

52     const chosen = (arms[cat] ?? arms.other ?? "").replace(/#/g, String(n));
53     return msg.slice(0, m.index) + chosen + msg.slice(end + 1);
54 }
55
56 // ICU-lite: resolve every plural block, then simple {name} interpolation.
57 export function interpolate(msg, vars = {}, locale = DEFAULT) {
58     if (typeof msg !== "string") return msg;
59     let out = msg;
60     for (let i = 0; i < 20; i++) { const next = plural(out, vars, locale); if (next ===
out) break; out = next; }
61     return out.replace(/\{(\w+)\}/g, (_, k) => (k in vars ? String(vars[k]) : `_${k}_`));
62 }
63
64 // active locale -> en fallback. undefined when absent in both (caller keeps the DOM's
English default).
65 export function translate(catalogs, locale, key, vars) {
66     let msg = dig(catalogs[locale], key);
67     if (msg == null) msg = dig(catalogs[DEFAULT], key);
68     return msg == null ? undefined : interpolate(msg, vars, locale);
69 }
70
71 // Walk i18n-tagged nodes under `root`. Three forms (missing key -> skip, leaving the
HTML default):
72 //   data-i18n="key"                                -> textContent
73 //   data-i18n="key" data-i18n-attr="x"              -> setAttribute(x, ?) (placeholder / aria-
label / alt ?)
74 //   data-i18n-html="key"                            -> innerHTML (for catalog-authored inline
markup like <b>;
75 //                                                    values are our own content, never user
input)
76 export function applyDom(root, catalogs, locale) {
77     for (const el of root.querySelectorAll("[data-i18n], [data-i18n-html]")) {
78         const htmlKey = el.getAttribute("data-i18n-html");
79         const val = translate(catalogs, locale, htmlKey || el.getAttribute("data-i18n"));
80         if (val == null) continue;
81         const attr = el.getAttribute("data-i18n-attr");
82         if (htmlKey) el.innerHTML = val;
83         else if (attr) el.setAttribute(attr, val);
84         else el.textContent = val;
85     }
86     // Reflect the active locale in the compact <select> language switcher(s).
87     for (const sel of root.querySelectorAll("select[data-langsw]")) sel.value = locale;
88 }
89
90 // ---- browser glue (skipped under the plain-node unit test, which has no document)
----
91 const readCookie = (name) => {
92     const m = (document.cookie || "").match(new RegExp("(?:^|; )" + name.replace(/\./g,
"\\" + ".") + "=[^;]*"));
93     return m ? decodeURIComponent(m[1]) : null;
94 };
95
96 function persist(locale) {
97     try { localStorage.setItem(STORAGE_KEY, locale); } catch { /* private mode */ }
98     // Mirror to a cookie so server.js (VM host) can honor the persisted pref server-side
(no FOCUS).
99     try { document.cookie = `${STORAGE_KEY}=${locale};path=/;max-
age=31536000;samesite=lax`; } catch { /* ignore */ }
100 }
101
102 async function loadCatalog(loc) {
103     try { const r = await fetch(`/locales/${loc}/common.json`); return r.ok ? await
r.json() : {}; } catch { return {}; }
104 }
105

```

```

106     let activeCatalogs = { en: {} };
107     let activeLocale = DEFAULT;
108
109     async function render(locale) {
110         const catalogs = { en: await loadCatalog("en") };
111         if (locale !== "en") catalogs[locale] = await loadCatalog(locale);
112         activeCatalogs = catalogs;
113         activeLocale = locale;
114         document.documentElement.lang = locale;
115         applyDom(document, catalogs, locale);
116         // Bridge for dynamically-injected content the static data-i18n walk can't reach (e.g.
the
117         // post-signup reel reveal): window.KheIaSutra.t(key, vars) -> active-locale string (en
fallback;
118         // undefined if absent everywhere, so callers can supply their own default).
119         if (typeof window !== "undefined") {
120             window.KheIaSutra = { t: (key, vars) => translate(activeCatalogs, activeLocale, key,
vars), lang: activeLocale };
121         }
122     }
123
124     async function boot() {
125         let stored = null;
126         try { stored = localStorage.getItem(STORAGE_KEY); } catch { /* ignore */ }
127         if (!stored) stored = readCookie(STORAGE_KEY); // server-set or cross-store persisted
pref
128         const query = new URLSearchParams(location.search).get("lang");
129         const nav = navigator.languages && navigator.languages.length ?
[...navigator.languages] : [navigator.language];
130         const locale = negotiate({ stored, query, nav });
131         await render(locale);
132         document.addEventListener("change", (e) => {
133             const sel = e.target.closest && e.target.closest("select[data-langsw]");
134             if (!sel) return;
135             const loc = supported(sel.value) || DEFAULT;
136             persist(loc);
137             render(loc);
138         });
139     }
140
141     if (typeof document !== "undefined" && typeof window !== "undefined") {
142         if (document.readyState === "loading") document.addEventListener("DOMContentLoaded",
boot);
143         else boot();
144     }
145

```

296. assistant (2026-06-22T05:36:19.799Z)

The shim's `render()` is the clean hook (nav text is final after `applyDom`). I'll add a `fitNav()` that hides the links when the row would overflow (per locale/width), driven by a class. Let me first check which pages carry the 6-link nav so I add the CSS rule in the right places:

297. user (2026-06-22T05:36:23.355Z)

```

=== index.html ===
nav-links blocks: 1
.nav-links CSS rules: 2
nav link items: 5
=== capture.html ===
nav-links blocks: 0
.nav-links CSS rules: 0
nav link items: 0
=== own-model.html ===

```

```
nav-links blocks: 0
.nav-links CSS rules: 0
nav link items: 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

298. assistant (2026-06-22T05:36:52.784Z)

Only `index.html` has the 6-link nav ? so the `.nav-crowded` CSS and the mobile fix go there; `fitNav()` goes in the shared shim (harmless no-op on the other pages). Let me read index.html's current nav CSS to edit precisely:

299. user (2026-06-22T05:36:53.892Z)

```
58      /* header */
59      header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
60      .nav{display:flex;align-items:center;justify-content:space-between;height:66px}
61      .brand{display:flex;align-items:center;gap:.6rem;font-weight:800;font-
size:1.18rem;letter-spacing:-.02em;text-decoration:none}
62      .brand .dot{color:var(--green)}
63      .nav-links{display:flex;align-items:center;gap:1rem}
64      .nav-links a{font-size:.9rem;font-weight:500;color:var(--mut);text-
decoration:none;white-space:nowrap}
65      .nav-links a:hover{color:var(--tx)}
66      /* persistent language switcher (B3) ? theme-agnostic: inherits text colour, green
fill = active */
67      .nav-right{display:flex;align-items:center;gap:1rem}
68      .langsw{display:inline-flex;align-items:center;gap:.3rem;border:1px solid
rgba(120,120,120,.3);border-radius:999px;padding:.1rem .3rem .1rem .6rem}
69      .langsw-globe{font-size:.95rem;line-height:1;opacity:.85}
70      .langsw select{font:inherit;font-size:.85rem;font-
weight:600;color:inherit;background:transparent;border:0;cursor:pointer;min-height:40px}
71      .langsw select:focus-visible{outline:2px solid var(--green);outline-offset:2px;border-
radius:6px}
72      .langsw option{color:#14271F;background:#fff}
73      .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px
0 7px 12px;border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
74
```

300. user (2026-06-22T05:37:03.027Z)

The file C:/Users/avidu/Projects/khelsutra-wt-home/../../khelsutra-wt-layout/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

301. assistant (2026-06-22T05:37:10.605Z)

Now the mobile fix ? let me read the breakpoint block and let the switcher+CTA wrap on narrow phones (da's long button clipped at 375px):

302. user (2026-06-22T05:37:11.559Z)

```
214      .stamp{font-size:.82rem;color:var(--mut)}
215
216      /* Hide the 6-link nav once it no longer fits beside the brand + switcher + CTA within
the 1080
217      content width (otherwise the links wrap onto multiple lines and overlap the brand).
Below this
218      the header stays a clean brand + switcher + CTA row ? no hamburger needed. */
219      @media (max-width:1080px){ .nav-links{display:none} }
220      @media (max-width:860px){
221      /* let the header wrap instead of clipping the switcher/CTA on phones (safety net)
*/
222      .nav{flex-wrap:wrap;height:auto;min-height:60px;row-gap:.4rem;padding:.4rem 0}
```

223 .g4{grid-template-columns:repeat(2,1fr)}

303. user (2026-06-22T05:37:22.116Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/public/index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

304. assistant (2026-06-22T05:37:42.474Z)

Now wire `fitNav()` into the shim ? add the function, call it after `applyDom`, and re-run it on resize and after webfonts settle:

305. user (2026-06-22T05:37:47.076Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/public/i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

306. user (2026-06-22T05:37:51.962Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/public/i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

307. user (2026-06-22T05:37:59.942Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/public/i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

308. assistant (2026-06-22T05:38:22.388Z)

The fix is in (CSS `.nav-crowded` rule + mobile wrap + shim `fitNav`). Now run the layout guard ? it should pass now that es/da auto-collapse:

309. user (2026-06-22T05:38:44.216Z)

```
> test:layout
> node --test src/layout.browser.mjs
```

```
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(18984.0758ms)
? tests 1
? suites 0
? pass 1
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 19558.213
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

310. assistant (2026-06-22T05:39:26.303Z)

Guard passes (19s). Let me add a small ****contract assertion**** so a future regression that hides the nav for ***everyone*** (which would pass the no-overflow check vacuously) still gets caught ? i.e. a locale that fits must keep its links:

311. user (2026-06-22T05:39:32.722Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/src/layout.browser.mjs has been updated successfully. (file state is current in your context ? no need to Read it back)

312. assistant (2026-06-22T05:39:46.169Z)

Let me add a tiny unit test for `fitNav`'s safe paths (jsdom has no layout, but it exercises the

export + the class-removal path). First the import line:

313. user (2026-06-22T05:39:47.397Z)

```
10      import { negotiate, interpolate, translate, applyDom, SUPPORTED, DEFAULT } from
"../public/i18n.js";
```

314. user (2026-06-22T05:39:54.079Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/src/i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

315. user (2026-06-22T05:40:01.230Z)

```
    }
    assert.match(locSite["diff.p2"], /KhelSutra/, `${loc} diff.p2 lost the brand`);
    assert.match(locSite["faq.q7.a"], /href="#join"/, `${loc} faq.q7.a lost the #join link`);
  }
});
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

316. user (2026-06-22T05:40:10.551Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/site/src/i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

317. assistant (2026-06-22T05:40:15.705Z)

Now run both the layout guard (both tests) and the site unit suite (confirming the new shim code is green and `layout.browser.mjs` isn't auto-discovered by the default `npm test`):

318. user (2026-06-22T05:40:42.633Z)

```
=== npm test (jsdom unit ? layout.browser.mjs must NOT be auto-run) ===
? tests 85
? pass 85
? fail 0
```

```
=== npm run test:layout (browser guard) ===
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(18969.3832ms)
? a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ? index.html [en]
(831.1555ms)
? tests 2
? pass 2
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

319. assistant (2026-06-22T05:40:53.644Z)

Both green: `npm test` is **85** (jsdom; the browser file is correctly *not* auto-discovered), and the layout guard is **2/2**. Now wire it into CI as its own job. Let me read the workflow and add it:

320. user (2026-06-22T05:40:53.940Z)

```
1      name: test
2      on:
3        push:
4          branches: [master]
5        pull_request:
6
7      jobs:
```

```

8      site:
9        runs-on: ubuntu-latest
10       defaults:
11         run:
12           working-directory: site
13       steps:
14         - uses: actions/checkout@v4
15         - uses: actions/setup-node@v4
16           with:
17             node-version: "24" # node:sqlite is unflagged; server.test.js boots the VM
host
18         cache: "npm"
19         cache-dependency-path: site/package-lock.json
20         # jsdom is a TEST-ONLY devDep (the behavioral landing-page UX tests run the real
inline
21         # script in a DOM); the Cloudflare Worker + VM-host RUNTIMES stay dependency-free.
`npm test`
22         # runs ALL paths: Worker+D1 logic (index.test.js), the booted VM host
(server.test.js), the
23         # static content contract (assets.test.js), and the UX behaviour (ux.dom.test.js).
24         - run: npm ci
25         - run: npm test
26         # Syntax-check the ops shell scripts (provision/teardown/smoke/parity) so a broken
27         # script can't ship to the runbook. `bash -n` parses without executing.
28         - name: shell scripts parse-check
29           run: for f in scripts/*.sh; do echo "checking $f"; bash -n "$f"; done
30
31       web:
32         # Operator-console SPA (web/): typecheck + unit tests (with a coverage floor) +
production build
33         # gate the merge. `test:coverage` fails if coverage drops below the thresholds in
vite.config.ts,
34         # so a merge can't silently regress test coverage.
35         runs-on: ubuntu-latest
36         defaults:
37           run:
38             working-directory: web
39         steps:
40           - uses: actions/checkout@v4
41           - uses: actions/setup-node@v4
42             with:
43               node-version: "24"
44               cache: "npm"
45               cache-dependency-path: web/package-lock.json
46           - run: npm ci
47           - run: npm run typecheck
48           - run: npm run test:coverage
49           - run: npm run build
50

```

321. user (2026-06-22T05:41:09.598Z)

The file C:/Users/avidu/Projects/khelsutra-wt-layout/.github/workflows/test.yml has been updated successfully. (file state is current in your context ? no need to Read it back)

322. assistant (2026-06-22T05:41:36.952Z)

The guard, measurements, and contract test all confirm the behavior ? but since es now shows a *compact* header on wide desktops, let me eyeball that one case (the potential "bare middle" concern) before shipping. Let me point the preview at this worktree:

323. user (2026-06-22T05:41:37.007Z)

```
1      {
```

```

2      "version": "0.0.1",
3      "configurations": [
4        {
5          "name": "khelsutra-web",
6          "runtimeExecutable": "npm",
7          "runtimeArgs": ["--prefix", "web", "run", "dev", "--", "--port", "5173", "--strictPort"],
8          "port": 5173
9        },
10       {
11         "name": "khelsutra-site",
12         "runtimeExecutable": "node",
13         "runtimeArgs": ["site/server.js"],
14         "port": 8080
15       }
16     ]
17   }
18

```

324. user (2026-06-22T05:41:42.543Z)

The file C:/Users/avidu/Projects/khelsutra/.claude/launch.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

325. user (2026-06-22T05:41:48.626Z)

```

{
  "serverId": "45185d5b-378b-4dd5-979c-f342d7b156bf",
  "port": 5181,
  "name": "site-static-wt-layout",
  "reused": false
}

```

Server started successfully on port 5181.

326. user (2026-06-22T05:41:54.570Z)

Viewport set to 1280x800.

327. user (2026-06-22T05:41:57.808Z)

"es"

328. assistant (2026-06-22T05:42:14.502Z)

es @1280 is **clean and intentional-looking** ? compact brand + switcher + CTA, no distortion, no clipping (the empty middle reads as a minimal header, not broken). Let me confirm en still shows its links at the same width:

329. user (2026-06-22T05:42:15.206Z)

"en"

330. assistant (2026-06-22T05:42:33.080Z)

The auto-hide works exactly as designed:

- **en (fits)**: full 6-link nav on one clean line.
- **es (doesn't fit)**: clean compact header, no overflow/clip.

Both smooth. Let me stop the preview, restore launch.json, and commit:

331. user (2026-06-22T05:42:33.441Z)

Server 45185d5b-378b-4dd5-979c-f342d7b156bf stopped

332. user (2026-06-22T05:42:39.871Z)

The file C:/Users/avidu/Projects/khelsutra/.claude/launch.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

333. user (2026-06-22T05:42:45.049Z)

```
=== all changes in worktree ===
M .github/workflows/test.yml
M site/package-lock.json
M site/package.json
M site/public/i18n.js
M site/public/index.html
M site/src/i18n.shim.test.js
?? site/src/layout.browser.mjs
```

334. assistant (2026-06-22T05:43:02.055Z)

Exactly the 7 expected files. Staging and committing:

335. user (2026-06-22T05:43:10.172Z)

```
staged: 7 files
.github/workflows/test.yml
site/package-lock.json
site/package.json
site/public/i18n.js
site/public/index.html
site/src/i18n.shim.test.js
site/src/layout.browser.mjs
1ce4427 test(site): browser layout-regression CI guard + auto-collapse the nav to fit every locale
```

336. assistant (2026-06-22T05:43:14.705Z)

Committed (1ce4427). Checking for master movement, then push + PR:

337. user (2026-06-22T05:43:18.748Z)

```
origin/master: 4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the responsive header (#90)
--- commits on top of origin/master ---
1ce4427 test(site): browser layout-regression CI guard + auto-collapse the nav to fit every locale
--- files vs base ---
.github/workflows/test.yml
site/package-lock.json
site/package.json
site/public/i18n.js
site/public/index.html
site/src/i18n.shim.test.js
site/src/layout.browser.mjs
```

338. assistant (2026-06-22T05:43:23.306Z)

Clean ? one commit, 7 files, master unchanged. Pushing and opening the PR:

339. user (2026-06-22T05:43:43.780Z)

```
branch 'feat/site-layout-ci-guard' set up to track 'origin/feat/site-layout-ci-guard'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/site-layout-ci-guard -> feat/site-layout-ci-guard
https://github.com/avidullu/khelsutra/pull/91
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```


340. assistant (2026-06-22T05:43:50.643Z)

PR opened: ****[khelsutra#91](https://github.com/avidullu/khelsutra/pull/91)****. The important validation now: does the new `layout` job pass in ****CI's Ubuntu environment**** (different fonts than my Windows ? the real test of whether the tolerances are environment-robust). Watching CI:

341. user (2026-06-22T05:44:57.193Z)

```
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9bcf1adc-9515-4f6b-88d2-b468be9fd62d
layout pass 53s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041154
site pass 17s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041137
web pass 41s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041236
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9bcf1adc-9515-4f6b-88d2-b468be9fd62d
layout pass 53s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041154
site pass 17s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041137
web pass 41s
https://github.com/avidullu/khelsutra/actions/runs/27932156163/job/82646041236
--- mergeability ---
mergeable=MERGEABLE mergeState=CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

342. assistant (2026-06-22T05:45:04.479Z)

All CI green ? and critically, the new ****`layout` job passes in CI's Ubuntu environment (53s)****, confirming the inequality-based assertions are robust across OS/fonts (exactly why I avoided screenshot diffing). mergeable=CLEAN. Merging and cleaning up:

343. user (2026-06-22T05:45:11.056Z)

```
--- state ---
state=MERGED mergeCommit=9f77ddc35f4332ba29ab48b72d417a1dcea89cc4
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

344. user (2026-06-22T05:45:21.255Z)

```
origin/master: 9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to
fit every locale (#91)
=== cleanup ===
worktree removed
Deleted branch feat/site-layout-ci-guard (was 1ce4427).
create mode 100644 site/src/layout.browser.mjs
main HEAD: 9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to fit
every locale (#91)
worktrees:
C:/Users/avidu/Projects/khelsutra 9f77ddc [master]
wt-layout gone? yes
launch.json configs: khelsutra-web, khelsutra-site
```

345. assistant (2026-06-22T05:45:31.879Z)

Clean: master at #91, worktree/branch removed, main fast-forwarded, launch.json restored. Let me update the handoff to record the new guard + the completed es/da fix:

346. user (2026-06-22T05:45:32.751Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22, after A2 (#82) + header pass (#83) + closeout (#84) + own-
model kn/hi (#86) + site es/da/id (#87) + P2c wizard (#88) + hero-mockup & #how i18n (#89) +
remaining home sections & responsive-header fix
([#90](https://github.com/avidullu/khelsutra/pull/90)) all MERGED to master (4415fe8). **The
home page body is now fully localized in all 6 languages except the #join access form (A6,
deferred).**_
4
```

347. user (2026-06-22T05:45:45.246Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

348. assistant (2026-06-22T05:46:06.238Z)

Done ? and the guard earned its keep on day one. Summary:

[khelsutra#91](https://github.com/avidullu/khelsutra/pull/91) ? merged to master ('9f77ddc')

****The CI guard you asked for**** ? a new `layout` job: headless Chromium (Playwright, a site test-only devDep) loads `index`/`capture`/`own-model` at ****widths [1280,1100,1000,900,768,375] × all 6 locales**** and asserts header ****invariants**** ? no nav overflow, links never wrap to multiple lines, CTA not clipped, no page-wide horizontal scroll. Inequality assertions, ****not screenshots**** ? robust across OS/fonts, no baselines, ~20s. (The reason the bug kept slipping through: every existing site test runs in jsdom, which has ***no layout engine*** ? `getBoundingClientRect()` is all zeros ? so it literally can't see overflow.)

****It immediately caught a bug I'd shipped.**** The guard failed on first run: ****#90's header fix was incomplete**** ? I'd verified en + id, but ****es (+138px)**** and ****da (+47px)**** still overflowed because their translated nav labels are much longer. So the "fixed" header was ***still broken*** on master for two locales. Exactly the kind of thing the guard exists to catch.

****The fix (auto-collapse, your pick):**** the shim now measures the header after applying a locale (and on resize / once webfonts load) and collapses the 6-link nav to a clean brand + switcher + CTA row when the links won't fit. Because it's ****measured live**, it self-adapts to any future translation length ? this class of bug can't silently come back.

****Verified:****

- The guard ****fails on the pre-fix CSS**** (11 failures) and ****passes after**** ? proven it actually catches the regression, not just rubber-stamps.
- ****Green in CI's Ubuntu env**** (53s) ? confirms the tolerances hold across OS/fonts (the whole point of inequalities over pixel-diffing).
- In-browser: ****en keeps all 6 links; es collapses cleanly**** (no bare/broken look).
- `npm test` 85/85 (jsdom unit, incl. a `fitNav` safe-path test; the browser file is `\*.browser.mjs` so it's not auto-run); web suite unaffected.

Merged, branches/worktree cleaned, main fast-forwarded, launch.json restored, handoff updated.

****Net:**** you now have a guard that catches header distortion ***and*** a header that genuinely fits all 6 locales. So to directly answer your question ? no, it wasn't too much; the ***lean*** version was right (full screenshot-diffing would've been the "too much" trap). Going forward, when you touch site CSS/markup, extend `site/src/layout.browser.mjs` rather than relying on a manual preview check.

349. user (2026-06-22T05:46:08.844Z)

please make sure to do a sweep of the relevant document which should be updated and merge the amazing regression gating PR (the rendering one) to mark an end to this great session!
make sure the shm added is also well tested and that we do land the CI gate you mentioned

350. assistant (2026-06-22T05:47:13.566Z)

Let me start by confirming where things stand ? the rendering PR's state ? and scoping which docs need the sweep. First, let me pull the latest and survey:

351. user (2026-06-22T05:47:19.799Z)

```
=== master tip ===
9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to fit every
locale (#91)
4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
(#90)
26c9da1 feat(site): localize the hero demo mockup + #how feature block (6 languages) (#89)

=== open PRs ===

=== is the layout CI gate + shim test on master? ===
fatal: ambiguous argument 'origin\master;github\workflows\test.yml': unknown revision or path
not in the working tree.
Use '--' to separate paths from revisions, like this:
'git <command> [<revision>...] -- [<file>...]'
test:layout in CI: 0
test:layout script: 1
100644 blob 83c735031663deb7919728564b48184c650f1ce4 i18n.shim.test.js
100644 blob 8b2e18d17fd5bcf07cdd26ef26981fe1dc4dc83c layout.browser.mjs
```

352. assistant (2026-06-22T05:47:50.734Z)

Confirmed: the rendering PR ****#91** is already merged** (last turn) ? master is at `9f77ddc`, the `layout` CI job ran green, the `test:layout` script + `layout.browser.mjs` + the `fitNav` shim test are all on master, and there are ****no open PRs****. So the CI gate is landed and the shim has tests.

What's left from your ask: (1) the ****doc sweep****, and (2) making the `fitNav` shim addition ****more thoroughly tested**** (right now its core "add `.nav-crowded` on overflow" branch is only covered indirectly). Let me scope the docs:

353. user (2026-06-22T05:47:53.457Z)

```
=== docs/ files ===
ANNOTATE_AND_TRAIN.md
DRY_RUN_CUJ.md
FRIENDLY_AND_MULTILINGUAL.md
LOCAL_APPLIANCE_ARCHITECTURE.md
MULTILINGUAL_EXPANSION.md
PER_RALLY_SELECTION.md
PORTABILITY.md
README.md
REQUEST_ACCESS_FORM.md

=== top-level docs ===
C:/Users/avidu/Projects/khelsutra/NEXT_STEPS.md
C:/Users/avidu/Projects/khelsutra/README.md

=== FRIENDLY doc: section headers + changelog ===
1:# Friendly & Multilingual ? non-tech-savvy UX + Hindi/Kannada localization
11:## 0. TL;DR
14:## 1. Problem & goal
21:## 2. Decisions locked (structural ? owner directive 2026-06-21)
36:## 3. Foundation ? research / prior art
50:## 4. Design / architecture
88:## 5. Privacy / scope note
91:## 6. Honest limits ? what this does NOT do
98:## 6.5 Testing strategy ? automatic language negotiation (rigorous, owner-required)
124:## 7. Deliverables & progress tracker ? **source of truth**
149:## 8. Open questions ? owner (blocking gates) `[design]`
```

157:## 9. Definition of done
167:## 10. References
172:### Changelog

354. assistant (2026-06-22T05:48:01.689Z)

`docs/FRIENDLY\_AND\_MULTILINGUAL.md` is the source-of-truth tracker. Let me read \$7 (tracker), \$9 (DoD), and the changelog to see what's stale:

355. user (2026-06-22T05:48:02.661Z)

```
124    ## 7. Deliverables & progress tracker    ? **source of truth**
125    Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**,
126    branched from `origin/master`, no stacking.
127    | ID | Deliverable | Workstream | Depends on | Gated? | Status | PR |
128    |----|-----|-----|-----|-----|-----|----|
129    | P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |
130    [#41](https://github.com/avidullu/khelsutra/pull/41) · engine
131    [#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275) |
132    | B1 | **SPA i18n scaffold + language switcher, en-only** (react-i18next + detector +
133    `en` catalog + switcher + persistence + **jsdom render tests** + **browser-language negotiation
134    tests** $6.5 N1/N3?N7) | B | P0 | No | ? | [#42](https://github.com/avidullu/khelsutra/pull/42)
135    |
136    | B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys);
137    add **key-parity + no-bare-strings CI** | B | B1 | No | ? |
138    [#45](https://github.com/avidullu/khelsutra/pull/45) |
139    | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color
140    selection) | A | B2 | No | ? | [#60](https://github.com/avidullu/khelsutra/pull/60) |
141    | B3 | **Shared `t()`/`data-i18n` shim + persistent switcher for `site/`** ? hoist
142    catalogs to repo-root `/locales` (D-CATALOG-HOME), re-point the SPA, site copy-step + drift-
143    guard, `server.js` + shim negotiation ($6.5 **N8**); **en-only marketing content** (kn/hi rides
144    A3) | B | B2 | D-CATALOG-HOME ? | ? | [#70](https://github.com/avidullu/khelsutra/pull/70) |
145    | A2 | Localized **WhatsApp share** for the reel ? SPA (CompileResult) + site (post-
146    signup reveal via a shim `window.Khelsutra.t` bridge); `wa.me`, client-only, `rel=noopener` | A
147    | B1/B3 | No | ? | [#82](https://github.com/avidullu/khelsutra/pull/82) |
148    | A6 | Plain-language framing for Request-Access GPU/storage questions (de-jargoned +
149    GPU reassurance; wired via `data-i18n`, en ? form kn/hi is a later increment) | A | B3 | No | ?
150    | [#75](https://github.com/avidullu/khelsutra/pull/75) |
151    | A7 | **Camera-placement diagram** on the capture page (accessible inline SVG: elevated
152    camera behind the baseline, ~30° tilt, full-court field-of-view) with a localized en/kn/hi
153    legend | A | ? | No | ? | [#76](https://github.com/avidullu/khelsutra/pull/76) |
154    | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? *SPA done; reel
155    watermark `font_path` = engine follow-up* | B | ? | D-FONT ? | ? |
156    [#46](https://github.com/avidullu/khelsutra/pull/46) |
157    | B5 | **Kannada (`kn`) catalog** ? render ? *SPA done (AI-draft, native review
158    pending); `site/` rides B3* | B | B2/B4 | D-LOCALES ? | ? |
159    [#47](https://github.com/avidullu/khelsutra/pull/47) |
160    | A3 | Localize **recording-education** (capture + homepage gist) + the `site.*`
161    marketing copy to **kn + hi** (Noto on the site; AI-draft, adversarially verified, native review
162    pending) | A | B3/B5 | D-LOCALES ? + D-FONT ? (site: Google-Fonts Noto) | ? |
163    [#74](https://github.com/avidullu/khelsutra/pull/74) |
164    | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? |
165    [#61](https://github.com/avidullu/khelsutra/pull/61) |
166    | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) |
167    A | B2 | No | ? | [#62](https://github.com/avidullu/khelsutra/pull/62) |
168    | B6 | **Hindi (`hi`) catalog** ? render (the extensibility proof ? just a catalog) ?
169    *SPA done (AI-draft, native review pending)* | B | B5 | D-LOCALES ? | ? |
170    [#48](https://github.com/avidullu/khelsutra/pull/48) |
171    | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 |
172    No | ? | [#63](https://github.com/avidullu/khelsutra/pull/63) |
173    | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ?
174    | [#68](https://github.com/avidullu/khelsutra/pull/68) |
175    | B7 | *(deferred, cross-repo)* Engine **P2 backend customer-facing localization**
176    (report `customer_` + rejection reasons) | B | engine | **D-BACKEND-DEPTH, owner-gated** | ? |
```

? |
146

147 **? MILESTONE ? SPA fully trilingual (2026-06-21):** the `web/` Studio SPA now speaks
 en + kn + hi end to end (B1?B2?B4?B5?B6, all merged). A **Kannada-default browser auto-
 renders Kannada**, and the switcher walks kn ? hi ? en ? **proven by a Playwright screencast**
 with `locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + `
 lang>` tracked). This meets the owner's success criterion **on the SPA surface**. **B3 has since
 landed** ? the `site/` marketing surface now carries the shared `t()/`data-i18n` shim, a
 persistent en/kn/hi switcher, and matching negotiation (client shim + `server.js`; \$6.5 **N8**
 green), with **en-only marketing content** for now (the shim/switcher/negotiation are the proof;
 kn/hi *marketing* translation rides **A3**). **A3 has since landed** ? the `site/` recording-
 education (homepage gist + capture checklist) and the `site.` marketing copy now render in **kn
 + hi** (Noto bundled on the site), so a Kannada/Hindi browser auto-gets localized recording
 instructions. **A6** (plain-language access form,
 [#75](https://github.com/avidullu/khelsutra/pull/75)) and **A7** (camera-placement diagram,
 [#76](https://github.com/avidullu/khelsutra/pull/76)) have since landed, and the **kn/hi SPA-
 console native-review pass** shipped ([#77](https://github.com/avidullu/khelsutra/pull/77)).
 Still open for the full \$9 DoD: a **native-speaker review** of the *remaining* AI-drafted
 catalogs (es/da/id + the reel-watermark strings; the kn/hi SPA console is done via #77) before a
 wide public launch. (**A2** WhatsApp/social share is **deferred out of v1 scope** ? not a DoD
 blocker.) Do **not** archive until both surfaces render kn/hi *content*. ? (both now do, pending
 the remaining native review).

148

149 ## 8. Open questions ? owner (blocking gates) `[design]`
 150 *Status (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see \$2 (D6?D9). Only
 D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

151 1. **D-FONT ? ? LOCKED ? (a) OFL-for-media carve-out, self-host Noto Sans
 Kannada/Devanagari** (counsel may still confirm). An explicit exception to the MIT/Apache/BSD
 code guardrail (fonts = media). Unblocks B4/B5/A3 + the kn/hi reel watermark.

152 2. **D-LOCALES ? ? LOCKED ? `en` + `kn` for v1, `hi` next, always-fallback to `en`**
 (both 2-form CLDR ? `hi` is catalog-only).

153 3. **D-BACKEND-DEPTH ? ? OPEN (deferred, not a v1 blocker).** Recommend **customer
 verdict/report `customer\_` + validation-rejection reasons first; technical/operator text stays
 English; phase two** (engine repo, owner-gated ? tracker row B7).

154 4. **D-SURFACE-FIRST ? ? ADOPTED ? lead with the SPA scaffold (B1), localize site
 recording-education early, SKIP the dead static-UI retrofit.**

155 5. **D-CATALOG-HOME ? ? ADOPTED & IMPLEMENTED (B3) ? repo-root
 `/locales/{en,kn,hi,es,da,id}/common.json` is the single source of truth.** The SPA imports it
 directly (re-pointed to `../../locales`; Vite resolves the workspace root via the repo `.git`
 marker, so dev/build/test all work). The dependency-free site consumes it through one tiny build
 step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (auto-runs
 `predeploy`), with a **drift-guard test** (`site/src/locales-drift.test.js`) failing CI if the
 shipped copy goes stale. (The engine `I18N\_PLAN` assumed the indexer repo; this is the
 adaptation.)

156

157 ## 9. Definition of done

158 - [x] **Automatic language negotiation (\$6.5) is green** ? N1/N3?N7 (SPA, jsdom) + N2
 (hi) + N8 (static-site shim honors `Accept-Language`/?lang`, `server.test.js`), all in CI.

159 - [] **Manual cross-check (owner machine):** OS/browser set to Kannada and to Hindi
 each render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner
 eyeball ? pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts
 in `khelsutra-screencast/` ? `khelsutra-site-i18n-desktop.mp4` (site, kn) +
 `khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`)).*

160 - [x] `en + kn + hi` catalogs live and **rendering** on BOTH `web/` SPA and `site/`
 marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3
 (site), proven by render tests + a real-browser pass.

161 - [] **Noto Sans Kannada + Devanagari render correctly** ? owner eyeball on a real
 machine. *(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the
 owner's device check.)*

162 - [x] CI **key-parity + no-bare-strings** green; a stub locale flags every gap ?
 `web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift`
 guard.

163 - [x] **Recording-education** (capture + homepage gist) available in `kn` + `hi` ? A3
 (#74), incl. a localized camera-placement diagram (A7, #76).

164 - [x] **Non-tech UX baseline** ? plain-language copy (A1/A6), mobile tap targets (A4) +

the decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only filters (A9), honest today-vs-roadmap preserved through translation.

165 - [] \$7 all rows ? (or explicitly deferred) ? flip **Status** ? **DONE** + run the engine ``DOC_STATUS.md $2` archival checklist ? `git mv` to `docs/archives/`. *($7 is all ? except the owner-gated, cross-repo B7 ? deferred. Holding the DONE flip on the two human gates above (native-speaker review of the AI-drafted kn/hi + the owner font eyeball). The prior engineering follow-up ? own-model body content English on kn/hi ? is now closed ([#86](https://github.com/avidullu/khelsutra/pull/86)): its full body is localized, so no engineering gap remains before the two human gates.)*`

166

167 **## 10. References**

168 **Internal code anchors** `[verified]:`web/package.json`,`web/src/{App.tsx,main.tsx,components/QueryBar.tsx,components/CompileResult.tsx,lib/query.ts}`;`site/public/{index,capture,own-model}.html`,`site/server.js`,`site/src/assets.test.js`.`

This repo's docs: ``docs/PER_RALLY_SELECTION.md`,`docs/REQUEST_ACCESS_FORM.md`,`docs/README.md`,`NEXT_STEPS.md`. Engine design docs (canonical): `badminton-highlight-indexer/docs/{I18N_PLAN.md,UI_PROPOSAL.md,VIDEO_RECORDING_GUIDELINES.md,PMF_MARKET_RESEARCH.md,PMF_FIELDED_SIGNALS.md,KHELSUTRA_PRODUCT_OVERVIEW.md,DOC_STATUS.md}`. External [researched]:`Unicode CLDR plural rules (kn/hi = one/other); react-i18next + i18next-icu; SIL Open Font License 1.1; Google Noto Sans Kannada/Devanagari`.`

169

170 ---

171

172 **### Changelog**

173 - `2026-06-21` ? created. Isolated the UX + Hindi/Kannada work into one tracked project (owner directive). Grounded in a multi-agent research+verification pass (web/+site/ string maps, Indic-l10n prior art, 5 adversarial verdicts). Decisions D1?D5 locked; 5 product/licensing decisions surfaced as open; \$7 tracker seeded with B1 as the recommended first slice.

174 - `2026-06-21` ? owner locked **D6** (en+kn?hi) + **D7** (OFL Noto carve-out) and adopted **D8** (SPA-first) + **D9** (catalogs in khelsutra); only D-BACKEND-DEPTH remains open. **B1 greenlit** ? ? in progress.

175 - `2026-06-21` ? **B1** opened ? [#42](https://github.com/avidullu/khelsutra/pull/42): SPA i18n scaffold (react-i18next + ICU + detector) + `en` catalog + language switcher + the SPA's first jsdom render tests. Verified typecheck/79-tests/build green + live in-browser (switcher persists, en-fallback). Doc/pointer PRs opened: khelsutra [#41](https://github.com/avidullu/khelsutra/pull/41), engine [#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275).

176 - `2026-06-21` ? **\$6.5 Testing strategy** added (owner ask, #41): **automatic-negotiation matrix** (N1?N9) so a Kannada/Hindi **browser** auto-gets the respective version ? proven at the detection level now (B1), at the content level with the catalogs (B5/B6), on the static shim (B3), and by a manual font-render eyeball. Wired into the DoD (\$9). B1 (#42) gains the detection tests (N1/N3?N7).

177 - `2026-06-21` ? **A9** (#68) landed. **Localized tap-only filter controls** (``TapFilters``: Sort/Length/Count) so a non-English-typing kn/hi/? user can filter without typing the English query syntax; each tap builds the same ``ParsedQuery`` the parser would (tap == type, test-pinned). The English example chips now show only in English. 173 web tests; reviewed via a 2-lens adversarial workflow. **Workstream A:** A1/A4/A5/A8/A9 ?; remaining A3 (recording-edu kn/hi), A6/A7 (site), B3 (site trilingual). **(Also note: MULTILINGUAL_EXPANSION Phase A ? es/da/id ? shipped #67, so the SPA now speaks 6 languages.)**

178 - `2026-06-21` ? **A8** (#63) landed. **Background-processing reassurance + status** as icon+text chips (never icon-only): a new ``StatusChip`` + shared ``Spinner``; IngestPanel processing shows a working chip + "safe to wait ? runs on the server" line and a ? "Couldn't process" chip on failure; ``CompileResult`` gains a "Stitching your reel?" building card + ??? status icons on the terminal card (now ``aria-live``). 141 web tests green; reviewed via a 2-lens adversarial workflow (folded its aria-live + honest-copy findings). **Workstream A** now: A1/A4/A5/A8 ?; remaining A9 (tap-only filters), A3 (recording-education kn/hi).

179 - `2026-06-21` ? **A5** (#62) landed. **Friendly engine-error mapping unified across ALL SPA surfaces** (ingest + build + rally-load) via a single ``lib/errorText.ts`` helper + a shared ``errors.`` catalog namespace: an ``engine`` failure shows the engine's own detail verbatim, everything else a localized line (``engineGeneric`` last resort). No more raw ``ApiError`/`HTTP 500`` text; ``build.failed`/`rallies.load_failed`` logs gain ``code`+`detail``. 136 web tests green; reviewed via a 2-lens adversarial workflow (folded its load-path consolidation nit).

180 - `2026-06-21` ? **A1** (#60) + **A4** (#61) landed. **A1** = the plain-language `en` copy pass (de-jargon). **A4** = the non-tech / phone-first pass: ?44px tap targets across the SPA (Tailwind ``min-h-11`/`h-11``), enlarged parsed-pill + sample chips, and **hover-only** ``title=`` text surfaced

as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence) ? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.

****Still open in workstream A:**** A5 (friendly engine-error map on the build path), A8 (background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-education kn/hi), B3 (site/ trilingual) + native review.

181 - `2026-06-21` ? ****? SPA MILESTONE:** fully trilingual (owner directive "take it to completion + screencast"). **** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ? B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity.**

****Playwright screencast**** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ? switch hi ? switch en, each with `` tracked (`khelsutra-i18n-screencast.mp4` + per-locale frames). kn/hi are ****AI-drafted ? native review pending****. ****Remaining for full \$9 DoD:**** B3 (the `site/` marketing surface), A3 + the UX A-items, native-speaker translation review.

182 - `2026-06-21` ? ****B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)) landed ? the marketing `site/` is now i18n-wired, en-only content.**** Implements ****D-CATALOG-HOME****: catalogs hoisted to repo-root ****/locales**** (all 6 ? en/kn/hi + the merged es/da/id) as the single source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ? typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook) + a ****drift-guard test****. New ****site/public/i18n.js**** ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n` walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the 2-form site languages); a ****persistent en/kn/hi switcher**** on `index/` capture/`own-model`; and ****server.js` Accept-Language negotiation\*\*** matching the SPA EXACTLY (persisted cookie ? `?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key). Tests: shim unit test + drift guard + extended `assets/`/`server` tests + the **\*\*\$6.5 N8\*\*** negotiation suite ? **\*\*62 site tests green\*\***; real-browser smoke (switch ? persist ? reload). kn/hi **\*\*marketing\* translation is the next effort (\*\*A3\*\*).** ? **\*\*Concurrency note:\*\*** built in an isolated `git worktree` because a sibling ****A9**** session held uncommitted catalog WIP in the shared checkout ? never clobbered.

183 - `2026-06-22` ? ****A3 ([#74](https://github.com/avidullu/khelsutra/pull/74)) landed ? the marketing `site/` recording-education + marketing copy now render in kn + hi.**** Translated the homepage "Record it right" gist + the full 1-page capture checklist + the existing `site.\*` copy to ****Kannada + Hindi**** (~40 new `site.record.\*`/`site.capture.\*` keys; en-authored, kn/hi translated, es/da/id en-seeded ? key-parity green). The shim gains a ****`data-i18n-html`**** form so inline `**<b>**` emphasis survives translation; ****Noto Sans Kannada + Devanagari**** bundled via Google Fonts on all 3 pages (+ `--font` fallback) so kn/hi render without tofu. Translations ****AI-drafted ? adversarially verified**** by a 6-agent workflow (meaning/fluency/integrity x kn/hi; 0 issues in the A3 keys) and a 4-lens code review (folded its ally findings ? switcher group `aria-label` now localized via `lang.label`, default `aria-pressed` for the no-JS baseline ? and 3 test-coverage findings incl. a byte-for-byte HTML?en-catalog drift test). ****Web 173 + site 68 green****; real-browser check (kn capture page renders Kannada, `**<b>**` preserved, no console errors). kn/hi remain ****native-review-pending**** (font glyphs = owner eyeball gate). The full-catalog audit also surfaced pre-existing ****B5/B6 SPA-console**** translation bugs (brand transliteration, "engine"/"server" jargon, a code-token leak, over-Sanskritized Hindi) ? flagged as a separate follow-up.

184 - `2026-06-22` ? ****A6 ([#75](https://github.com/avidullu/khelsutra/pull/75)) landed ? plain-language Request-Access GPU/storage questions.**** De-jargoned the intimidating form copy ("GPU machine that could process video locally" ? "a powerful computer that could process videos on its own"; dropped the bare "(S3/GCS)") and added a ****GPU reassurance**** ("No worries if not ? we can run it in the cloud for you"), so a non-technical coach/parent isn't scared off. Wired via the shim (`site.join.\*`, `data-i18n` spans that preserve the radio/checkbox ``s), translation-ready (en for now; the form's kn/hi is a later increment). The ****backend enum contract is unchanged**** (field names + every `has\_gpu`/`storage` value preserved ? server-validated). Tests: a de-jargon + reassurance + contract-intact assertion, and the A3 HTML?en-catalog drift test auto-covers the new keys. Site 69 + web 173 green.

185 - `2026-06-22` ? ****A7 ([#76](https://github.com/avidullu/khelsutra/pull/76)) landed ? camera-placement diagram on the capture page.**** Added an ****accessible inline SVG**** (`role="img"` + localized ``) side-view showing the load-bearing placement cues a coach can't get from text alone: the **elevated camera behind the baseline**, the **~30° downward tilt**, and the **full-court field-of-view cone** (players within frame). A numbered ??? legend (HTML, so it wraps) maps the markers to the rules and is localized **en/kn/hi** (`site.capture.diagram.\*`, reusing the A3 capture terms) ? consistent with the now-trilingual capture page. The text "Place the camera" step remains (the diagram complements it). Tests: a diagram-structure + accessible-`<title>` + localized-legend assertion; kn/hi in-script check incl. `diagram.camera`; the A3 drift test auto-covers the new keys; site 70 + web 173 green. **Workstream A is now</p>
</div>

A1/A3/A4/A5/A6/A7/A8/A9 ?** (remaining: A2 WhatsApp share; the B5/B6 SPA-console native-review pass; full native review).

186 - `2026-06-22` ? **A2 ([#82](https://github.com/avidullu/khelsutra/pull/82)) landed ? localized WhatsApp share (the last open \$7 row). ** SPA `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`). SPA `result.share`/`result.shareText` translated in all 6 locales; the site reveal (injected after sign-up, outside the static `data-i18n` walk) localizes via a new **`window.KhelSutra.t` shim bridge** (`site.reveal.\*`, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????????" + a Kannada message. Web 215 + site 72 green. **\$7 is now all ? except the owner-gated, cross-repo B7** (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.

187 - `2026-06-22` ? **UI/UX header pass ([#83](https://github.com/avidullu/khelsutra/pull/83)). ** A 3-lens design critique + a deep Playwright layout test (all pages x {1280, 390} x {en, hi/kn}) confirmed the home header **overflowed on mobile** ? the 3 always-visible language pills pushed the "Request access" CTA off-screen (worse in kn). Replaced the pills with a **compact` ? <select>` switcher** on all three pages (shows the current language, can't overflow, one tap target, accessible, consistent), added wrap/`overflow-x` safety, and localized the **home hero headline** (`site.hero.title`, the last big English string on the kn/hi home page) via `data-i18n-html`. Shim now reflects the locale in `select[data-langsw]` + listens for `change`. **Zero horizontal overflow on all 12 page/viewport/locale combos**; web 215 + site 72 green. Screencasts (desktop kn journey + mobile header) saved to `khelsutra-screencast/`.

188 - `2026-06-22` ? **? Multilingual chapter ? effectively complete (pending human gates). ** \$7 is **all ? except B7** (assessed: significant cross-repo **engine** backend-i18n in Python with no existing infra + owner-gated **D-BACKEND-DEPTH** ? kept deferred). Both surfaces are trilingual end-to-end (SPA en/kn/hi + es/da/id; site en/kn/hi), non-tech-friendly, and the **sister repo `rally-annotator` is also localized (kn/hi/es/da/id/te)** ? so the coach's journey **annotator ? site ? Studio** is consistent in their language. **What gates archival:** (1) a native-speaker review of the AI-drafted kn/hi catalogs (site + SPA), (2) the owner's font-glyph eyeball on a real Kannada/Hindi device, (3) a small remaining slice ? `own-model` body content is still English on kn/hi. Do not `git mv` to `docs/archives/` until (1)+(2) clear.

189 - `2026-06-22` ? **own-model body content localized to kn + hi ([#86](https://github.com/avidullu/khelsutra/pull/86)) ? closes engineering follow-up (3) above. ** The developer/power-user `own-model.html` was English-only on kn/hi (only its switcher + Request-access link were localized). Wired its **full body** ? hero, the annotate/train/setup steps, the moat grid, the honest-framing fences, "what this is not", CTA and footer ? through the shim (**52 new `site.ownModel.\*` keys**; `data-i18n` + `data-i18n-html` for inline `**<i>/<a>/<code>/<span>**`), keeping `

```
`/CLI blocks, file paths, the `ending_reason` enum, brand/tool tokens (KhelSutra/VLC/rally-annotator/MIT/GPU/LLM) and the VLC UI button labels **literal**, and every honest caveat intact (`<title>/meta` left English, consistent with A3). en authored **byte-for-byte** (jsdom-extracted ? the A3 drift guard validates it); es/da/id en-seeded; **kn/hi AI-drafted ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise** via a 10-agent workflow (16 kn + 10 hi findings folded), reusing the established kn/hi register; the shipped `requestAccess` translation preserved. New tests: own-model body-wiring assertion + kn/hi in-script render check + a **tag-multiset/literal-token integrity guard**; the web `catalog-invariants` ``-leak rule (#77) **scoped** to allow inline code only on `site.ownModel.*`. **Site 75 + web 215 green; web typecheck/coverage (93.4%, ? floor)/build green. ** Real-browser pass (kn + hi render, `<b>` preserved, code blocks literal, **zero console errors**); screencast `khelsutra-ownmodel-i18n-desktop.webm` + per-locale stills in `khelsutra-screencast/`. kn/hi remain **native-review-pending** (the two human gates are unchanged). Built in an isolated `git worktree` off `origin/master` (the shared checkout had churned to `deploy/kit-live-verified` mid-session ? concurrency convention vindicated).
```

190 - `2026-06-22` ? **marketing site reaches parity with the SPA's 6 languages ([#87](https://github.com/avidullu/khelsutra/pull/87)) ? es/da/id added to the site. ** The site dropdown was intentionally en/kn/hi because the other 3 catalogs (es=Spanish, da=Danish, id=Indonesian) had their `site.\*` marketing copy **100% English-seeded** (SPA-console only). Translated the **115 `site.\*` keys kn covers** (nav/hero/recording-education/capture+diagram/own-model/reveal) into es/da/id and added them to all 3 page switchers; the shim `SUPPORTED` + `server.js` `SITE\_LOCALES` now list all 6, so a browser in any of these auto-negotiates (`<html lang>` + `content-language`). **AI-drafted ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise** via a 15-agent workflow (11 es + 10 da + 14 id findings folded), reusing each locale's shipped SPA-console vocabulary (rally ? es `jugada`, da `duel`, id `reli`); inline HTML tags + literal tokens preserved (tag-multiset integrity test). The Request-Access form (`site.join.\*`, 14 keys) stays English in es/da/id too ? **parity with

kn/hi** (A6 deferred form l10n for all non-en). New/updated tests: 6-language switcher + es/da/id negotiation + real-translation + integrity guards. **Site 77 + web 215 green; web typecheck/coverage (93.4%)/build green.** Real-browser pass (es/da/id home heroes distinct & correct; Indonesian capture page + diagram render; only the pre-existing Cloudflare RUM beacon errors on localhost); screencast `khelsutra-site-esdaid-desktop.webm` + per-locale stills. es/da/id **native-review-pending** (same standing gate as kn/hi). *Note:* a few hardcoded hero-mockup chips in `index.html` (`See it in action`/`Auto-index rallies`/`Download your reel`, not `data-i18n`-wired) stay English in **every** non-en locale incl. kn/hi ? a pre-existing gap, out of scope.

191

356. assistant (2026-06-22T05:48:57.507Z)

The changelog stops at **87** ? it's missing #89/#90/#91, and the \$9 DoD + the "hero-mockup chips out of scope" note are now stale. That's the document to sweep. Let me also check `NEXT\_STEPS.md`, then do the work (doc sweep + strengthen the `fitNav` shim test) in a fresh worktree:

357. user (2026-06-22T05:49:01.371Z)

=== NEXT_STEPS.md head (check staleness) ===

Next steps (live) ? KhelSutra brand / site

Prioritized "what to do next" for the **`khelsutra` product repo**. Refresh at each checkpoint.

Where we are (2026-06-20): `khelsutra.guru` is **LIVE and fully shipped** ? landing page + `/capture` checklist + OG image + a **segmented Request-Access form** (academy/individual + GPU + storage + free text). On **Cloudflare** (Worker `hidden-king-khelsutra` + D1 `khelsutra-access`): the form persists to D1 **and emails a summary to the owner on every registration** (Email Routing send binding ? verified live). **Git auto-deploy is connected** (Workers Builds, root `site/`): merge to `master` ? deploys; **CI runs `npm test` (20 green) on every PR**. The same form also runs on a dependency-free **Node + SQLite** host (`site/server.js`), **live + browsable on the DO droplet ? http://168.144.126.176:8787** (systemd `khelsutra-site`). PRs #1?#8 merged. Docs: `docs/REQUEST\_ACCESS\_FORM.md`, `docs/PORTABILITY.md`.

Next product threads (owner ideas, 2026-06-20)

- **? ACTIVE FOCUS (owner directive 2026-06-21): Friendly & Multilingual** ? make the product **super user-friendly for non-tech-savvy** coaches/parents **and localize it in Hindi + Kannada**.
 - **? Tracked design + P-tracker (source of truth): `docs/FRIENDLY\_AND\_MULTILINGUAL.md` (DRAFT, owner-gated).** Both surfaces have zero i18n today; the foundation (shared `locales/{en,kn,hi}` catalogs + negotiation contract + CI parity) is the deliverable. **Recommended first slice = SPA i18n scaffold + language switcher (en-only), unblocked.** 5 open owner decisions in \$8 (font OFL carve-out · en+kn-then-hi · backend depth · surface-first · catalog home). Adapts the engine's `I18N\_PLAN.md` (P1?`site/` shim, P3?`web/` react-i18next) + the UX half of `UI\_PROPOSAL.md`.
- **Marketing video on the site** ? embed a short walkthrough of the record ? index ? reel process, themed for **serious enthusiasts**, on the landing page. ? **A real-UI CUJ screencast now exists** (Playwright recording of the per-rally SPA driven against real GPU-run data ? `promo\_cuj.mp4`/`.gif` in `gs://khelsutra-rally-corpus/promo/`). Decide: use it as the marketing clip (? shows real court

footage + a dev "P5" badge ? clean up before public embed), and/or produce a polished Grok/Gemini cut.

- **Interactive per-rally selection** (big product feature) ? ? **MVP / M0 COMPLETE** (the full pick ? query ? select ? compile ? download loop on existing engine endpoints). Lives in the alpha SPA
 - (`web/`). **Tracked design + P-tracker (source of truth):** `docs/PER\_RALLY\_SELECTION.md` (IN PROGRESS;

=== playwright browser cache (reused across worktrees?) ===
chromium-1228
chromium_headless_shell-1228
ffmpeg-1011
=== create worktree ===
HEAD is now at 9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to fit every locale (#91)

358. assistant (2026-06-22T05:50:07.110Z)

NEXT_STEPS.md points to the FRIENDLY tracker as the source of truth (so the tracker is the document to sweep), and Playwright's Chromium is cached globally (so `test:layout` will work after `npm ci`). Let me install deps and make the edits. First deps:

359. user (2026-06-22T05:50:12.183Z)

site deps installed
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

360. assistant (2026-06-22T05:50:27.227Z)

Now the doc sweep. First, the changelog ? adding entries for #89, #90, #91 (the missing ones):

361. user (2026-06-22T05:50:43.762Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

362. assistant (2026-06-22T05:50:49.565Z)

Need to read the worktree copy first:

363. user (2026-06-22T05:50:50.988Z)

186 - `2026-06-22` ? **A2** ([#82](https://github.com/avidullu/khelsutra/pull/82)) landed ? localized WhatsApp share (the last open \$7 row). **SPA** `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`). SPA `result.share`/`result.shareText` translated in all 6 locales; the site reveal (injected after sign-up, outside the static `data-i18n` walk) localizes via a new **window.KhelSutra.t` shim bridge** (`site.reveal.*`, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????????" + a Kannada message. Web 215 + site 72 green. **\$7** is now all ? except the owner-gated, cross-repo B7 (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.

187 - `2026-06-22` ? **UI/UX header pass** ([#83](https://github.com/avidullu/khelsutra/pull/83)). **A 3-lens design critique + a deep Playwright layout test** (all pages x {1280, 390} x {en, hi/kn}) confirmed the home header **overflowed on mobile** ? the 3 always-visible language pills pushed the "Request access" CTA off-screen (worse in kn). Replaced the pills with a **compact `? <select>` switcher** on all three pages (shows the current language, can't overflow, one tap target, accessible, consistent), added wrap/`overflow-x` safety, and localized the **home hero headline** (`site.hero.title`, the last big English string on the kn/hi home page) via `data-i18n-html`. Shim now reflects the locale in `select[data-langsw]` + listens for `change`. **Zero horizontal overflow on all 12 page/viewport/locale combos**; web 215 + site 72 green. Screenshots (desktop kn journey + mobile header) saved to `khelsutra-screenshot/`.

188 - `2026-06-22` ? **Tracked design + P-tracker** (source of truth): `docs/PER\_RALLY\_SELECTION.md` (IN PROGRESS;

Python with no existing infra + owner-gated ****D-BACKEND-DEPTH**** ? kept deferred). Both surfaces are trilingual end-to-end (SPA en/kn/hi + es/da/id; site en/kn/hi), non-tech-friendly, and the ****sister repo `rally-annotator`** is also localized (kn/hi/es/da/id/te) ****** ? so the coach's journey ****annotator ? site ? Studio**** is consistent in their language. ****What gates archival:**** (1) a native-speaker review of the AI-drafted kn/hi catalogs (site + SPA), (2) the owner's font-glyph eyeball on a real Kannada/Hindi device, (3) a small remaining slice ? **`own-model`** body content is still English on kn/hi. Do not **`git mv`** to **`docs/archives/`** until (1)+(2) clear.

189 - **`2026-06-22`** ? ****own-model** body content localized to kn + hi
([#86](https://github.com/avidullu/khelsutra/pull/86)) ? closes engineering follow-up (3) above. ****** The developer/power-user **`own-model.html`** was English-only on kn/hi (only its switcher + Request-access link were localized). Wired its ****full body**** ? hero, the annotate/train/setup steps, the moat grid, the honest-framing fences, "what this is not", CTA and footer ? through the shim (****52 new `site.ownModel.\*` keys****; **`data-i18n`** + **`data-i18n-html`** for inline **`<b>/<i>/<a>/<code>/<span>`**), keeping **`<pre>`**/CLI blocks, file paths, the **`ending\_reason`** enum, brand/tool tokens (KhelSutra/VLC/rally-annotator/MIT/GPU/LLM) and the VLC UI button labels ****literal****, and every honest caveat intact (**`<title>/meta`** left English, consistent with A3). en authored ****byte-for-byte**** (jsdom-extracted ? the A3 drift guard validates it); es/da/id en-seeded; ****kn/hi** AI-drafted ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise ****** via a 10-agent workflow (16 kn + 10 hi findings folded), reusing the established kn/hi register; the shipped **`requestAccess`** translation preserved. New tests: own-model body-wiring assertion + kn/hi in-script render check + a ****tag-multiset/literal-token integrity guard****; the web **`catalog-invariants`** **`<code>-leak`** rule (#77) ****scoped**** to allow inline code only on **`site.ownModel.\*`**. ****Site 75 + web 215 green; web typecheck/coverage (93.4%, ? floor)/build green.**** Real-browser pass (kn + hi render, **`<b>`** preserved, code blocks literal, ****zero console errors****); screencast **`khelsutra-ownmodel-i18n-desktop.webm`** + per-locale stills in **`khelsutra-screencast/`**. kn/hi remain ****native-review-pending**** (the two human gates are unchanged). Built in an isolated **`git worktree`** off **`origin/master`** (the shared checkout had churned to **`deploy/kit-live-verified`** mid-session ? concurrency convention vindicated).
190 - **`2026-06-22`** ? ****marketing site** reaches parity with the SPA's 6 languages
([#87](https://github.com/avidullu/khelsutra/pull/87)) ? es/da/id added to the site. ****** The site dropdown was intentionally en/kn/hi because the other 3 catalogs (es=Spanish, da=Danish, id=Indonesian) had their **`site.\*`** marketing copy ****100% English-seeded**** (SPA-console only). Translated the ****115 `site.\*` keys kn covers**** (nav/hero/recording-education/capture+diagram/own-model/reveal) into es/da/id and added them to all 3 page switchers; the shim **`SUPPORTED`** + **`server.js`** **`SITE\_LOCALES`** now list all 6, so a browser in any of these auto-negotiates (**`<html lang>`** + **`content-language`**). ****AI-drafted ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise**** via a 15-agent workflow (11 es + 10 da + 14 id findings folded), reusing each locale's shipped SPA-console vocabulary (rally ? es **`jugada`**, da **`duel`**, id **`reli`**); inline HTML tags + literal tokens preserved (tag-multiset integrity test). The Request-Access form (**`site.join.\*`**, 14 keys) stays English in es/da/id too ? ****parity with kn/hi**** (A6 deferred form l10n for all non-en). New/updated tests: 6-language switcher + es/da/id negotiation + real-translation + integrity guards. ****Site 77 + web 215 green; web typecheck/coverage (93.4%)/build green.**** Real-browser pass (es/da/id home heroes distinct & correct; Indonesian capture page + diagram render; only the pre-existing Cloudflare RUM beacon errors on localhost); screencast **`khelsutra-site-esdaid-desktop.webm`** + per-locale stills. es/da/id ****native-review-pending**** (same standing gate as kn/hi). ***Note:*** a few hardcoded hero-mockup chips in **`index.html`** (**`See it in action`/`Auto-index rallies`/`Download your reel`**, not **`data-i18n-wired`**) stay English in ****every**** non-en locale incl. kn/hi ? a pre-existing gap, out of scope.

191

364. assistant (2026-06-22T05:50:54.667Z)

Now I can apply the changelog additions:

365. user (2026-06-22T05:51:11.762Z)

The file C:/Users/avidu/Projects/khelsutra-wt-closeout/docs/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

366. assistant (2026-06-22T05:51:26.287Z)

Now update the \$9 DoD parenthetical to reflect the closed follow-ups + the new guard:

367. user (2026-06-22T05:51:31.201Z)

The file C:/Users/avidu/Projects/khelsutra-wt-closeout/docs/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

368. user (2026-06-22T05:51:37.868Z)

The file C:/Users/avidu/Projects/khelsutra-wt-closeout/docs/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

369. assistant (2026-06-22T05:51:51.362Z)

Now strengthen the `fitNav` shim test to cover its core add/remove branches deterministically. Let me read the current test in the worktree:

370. user (2026-06-22T05:51:52.271Z)

```
10:import { negotiate, interpolate, translate, applyDom, fitNav, SUPPORTED, DEFAULT } from
"../public/i18n.js";
279:// fitNav's real (geometry) behaviour is covered by the browser layout guard
(src/layout.browser.mjs);
282:test("fitNav: no-ops without a nav and clears .nav-crowded when nothing overflows", () => {
284:  assert.doesNotThrow(() => fitNav(empty), "fitNav must tolerate a page with no .nav");
286:  fitNav(withNav);
287:  assert.ok(!withNav.querySelector(".nav").classList.contains("nav-crowded"), "with no
overflow, fitNav should reveal the links (drop .nav-crowded)");
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

371. user (2026-06-22T05:52:01.290Z)

```
279    // fitNav's real (geometry) behaviour is covered by the browser layout guard
(src/layout.browser.mjs);
280    // jsdom has no layout engine (scrollWidth === clientWidth === 0), so here we only pin
its safe paths:
281    // it never throws without a nav, and with no measurable overflow it clears the collapse
class.
282    test("fitNav: no-ops without a nav and clears .nav-crowded when nothing overflows", ()
=> {
283      const { document: empty } = new JSDOM(`<!doctype html><body></body>`).window;
284      assert.doesNotThrow(() => fitNav(empty), "fitNav must tolerate a page with no .nav");
285      const { document: withNav } = new JSDOM(`<!doctype html><body><header><div class="nav
nav-crowded"><a class="brand">B</a><nav class="nav-
links"><a>x</a></nav></div></header></body>`).window;
286      fitNav(withNav);
287      assert.ok(!withNav.querySelector(".nav").classList.contains("nav-crowded"), "with no
overflow, fitNav should reveal the links (drop .nav-crowded)");
288    });
```

372. user (2026-06-22T05:52:16.833Z)

The file C:/Users/avidu/Projects/khelsutra-wt-closeout/site/src/i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

373. assistant (2026-06-22T05:52:25.679Z)

Test-only change ? no preview needed. Let me run the site suite (the strengthened `fitNav` test) and the layout guard to confirm everything's green:

374. user (2026-06-22T05:52:56.004Z)

```
=== npm test (jsdom unit, incl. strengthened fitNav) ===
? fitNav: no-ops without a nav (11.9427ms)
? fitNav: toggles .nav-crowded by whether the header row overflows (both branches + idempotent)
(11.8528ms)
```

```
? tests 86
? pass 86
? fail 0
```

```
=== npm run test:layout (sanity ? no CSS change here) ===
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(22343.7128ms)
? a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ? index.html [en]
(824.2483ms)
? tests 2
? pass 2
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

375. assistant (2026-06-22T05:53:21.633Z)

All green: ****86 unit tests**** (the strengthened `fitNav` now covers both branches ? collapse-on-overflow, reveal-on-fit, idempotency, re-collapse ? deterministically via mocked geometry), and the layout guard 2/2 (sanity). Let me commit the doc sweep + test strengthening:

376. user (2026-06-22T05:53:27.867Z)

```
=== changes ===
M docs/FRIENDLY_AND_MULTILINGUAL.md
M site/src/i18n.shim.test.js
staged: 2
docs/FRIENDLY_AND_MULTILINGUAL.md
site/src/i18n.shim.test.js
4419942 docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 + strengthen fitNav
tests
```

377. assistant (2026-06-22T05:53:34.010Z)

Committed (4419942). Checking master, then push + PR:

378. user (2026-06-22T05:53:52.531Z)

```
origin/master: 9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to
fit every locale (#91)
commits on top:
4419942 docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 + strengthen fitNav
tests
To https://github.com/avidullu/khelsutra.git
* [new branch] docs/multilingual-header-closeout -> docs/multilingual-header-closeout
https://github.com/avidullu/khelsutra/pull/92
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

379. assistant (2026-06-22T05:53:59.123Z)

PR #92 opened. Watching CI, then merging:

380. user (2026-06-22T05:55:05.489Z)

```
web      pass    28s
https://github.com/avidullu/khelsutra/actions/runs/27932516708/job/82647129537
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/9964464a-0c77-4eed-9502-8d1f2f591a79
layout   pass    54s
https://github.com/avidullu/khelsutra/actions/runs/27932516708/job/82647129565
site     pass    12s
https://github.com/avidullu/khelsutra/actions/runs/27932516708/job/82647129519
web      pass    28s
https://github.com/avidullu/khelsutra/actions/runs/27932516708/job/82647129537
```

```
--- mergeability ---
mergeable=MERGEABLE mergeState=CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

381. assistant (2026-06-22T05:55:13.602Z)

All green (incl. the `layout` job confirming it runs on every PR now), mergeable=CLEAN. Merging and cleaning up:

382. user (2026-06-22T05:55:26.227Z)

```
PR state: MERGED
=== cleanup ===
worktree removed
Deleted branch docs/multilingual-header-closeout (was 4419942).
 2 files changed, 36 insertions(+), 9 deletions(-)
main HEAD: 0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 +
strengthen fitNav tests (#92)
open PRs: 0
worktrees:
C:/Users/avidu/Projects/khelsutra 0bef61e [master]
```

383. assistant (2026-06-22T05:55:36.814Z)

Everything merged and clean ? master at ****#92**** (`0bef61e`), zero open PRs, only the main worktree remains. Let me give the session handoff a final touch to record the closeout:

384. user (2026-06-22T05:55:37.737Z)

```
3      _Last updated: 2026-06-22, after A2 (#82) ? hero-mockup & #how i18n (#89) + remaining
home sections & responsive-header fix (#90) + **browser layout-regression CI guard & full-locales
header fix ([#91](https://github.com/avidullu/khelsutra/pull/91))** all MERGED to master
(9f77ddc). **The home page body is fully localized in all 6 languages except the #join access
form (A6, deferred).**_
4
5      **Header is now robust across ALL 6 locales + guarded.** #90's fix only covered
en/kn/hi/id; the #91 layout guard caught that **es (+138px) / da (+47px)** still overflowed
(longer translated nav labels). Fixed in #91: the shim (`fitNav` in `site/public/i18n.js`)
measures the header after applying a locale (+ on resize / fonts.ready) and adds .nav-crowded`
to collapse the 6-link nav to a compact brand+switcher+CTA row when it won't fit ? **measured
live, so it self-adapts to any future translation length.** New CI: a `layout` job runs npm run
test:layout` = site/src/layout.browser.mjs` (headless Chromium/Playwright, a site test-only
devDep) asserting header invariants (no overflow / no link-wrap / CTA not clipped / no h-scroll)
across widths × 6 locales on index/capture/own-model. jsdom can't see layout, so this is the
only guard for rendering distortion ? extend it when touching site CSS/markup.
```

385. user (2026-06-22T05:55:44.936Z)

The file C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

386. assistant (2026-06-22T05:56:05.684Z)

Done ? the chapter is closed out. Here's the final state of the session:

? Session complete ? master at [#92](https://github.com/avidullu/khelsutra/pull/92) (`0bef61e`), 0 open PRs

Addressing each part of your ask:

```
***Merge the regression-gating PR (the rendering one)*** ?
**[#91](https://github.com/avidullu/khelsutra/pull/91) was already merged** last turn (the
`layout` CI job + the auto-collapse header fix). Confirmed it's on master and the gate is live.
```

Land the CI gate you mentioned ? ? **landed and verified running.** The `layout` job ran green on both subsequent PRs (#91, #92), so it now gates *every* PR: headless Chromium asserting header invariants across widths × 6 locales. jsdom-based suites can't see layout ? this is the only thing standing between you and a 4th header regression.

Make sure the shim added is well tested ? ? **strengthened in #92.** `fitNav` previously had only its safe paths unit-tested (jsdom has no layout engine). Now both branches are pinned deterministically by mocking the geometry it reads: *collapse-on-overflow* ? *reveal-on-fit* ? *idempotent* ? *re-collapse*. Real per-locale geometry stays covered end-to-end by the layout guard. Site suite: *86/86*.

Sweep the relevant document ? ? *docs/FRIENDLY_AND_MULTILINGUAL.md* (the source-of-truth tracker) is now current:

- Changelog: added the three missing entries (#89 hero/#how, #90 home sections + header, #91 layout guard).
- §9 DoD: updated to reflect that the home page body is fully localized in all 6 languages (except the deferred `#join` form) and the header is fixed *and* guarded ? leaving only the *two human gates* (native-speaker review + your font-glyph eyeball).
- §10 References: added the shim + the layout guard files.

The arc of this session, for the record: hero/#how localization (#89) ? remaining home sections + header smoothing (#90) ? the layout CI guard that *caught my own incomplete header fix* and the live-measured auto-collapse that fixed it for all 6 locales (#91) ? this closeout (#92). The home page now speaks all six languages end-to-end, the header can't silently break again, and the docs tell the whole story.

A genuinely great session ? thanks for pushing on the CI guard; it paid for itself within minutes. ?

387. user (2026-06-22T05:59:12.618Z)

lovely! Can you tell me what else is left from the *docs/FRIENDLY_AND_MULTILINGUAL.md* project and if we can move it to archived since its done?

388. assistant (2026-06-22T05:59:50.935Z)

Let me look at the current doc precisely ? the tracker (§7), the open owner gates (§8), and the Definition of Done (§9) ? plus whether an archives location exists, before advising on archival.

389. user (2026-06-22T05:59:51.846Z)

```
157    ## 9. Definition of done
158    - [x] Automatic language negotiation (§6.5) is green ? N1/N3?N7 (SPA, jsdom) + N2
(hi) + N8 (static-site shim honors `Accept-Language`/`?lang`, `server.test.js`), all in CI.
159    - [ ] Manual cross-check (owner machine): OS/browser set to Kannada and to Hindi
each render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner
eyeball ? pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts
in `khelsutra-screencast/` ? `khelsutra-site-i18n-desktop.mp4` (site, kn) +
`khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`.)*)
160    - [x] `en + kn + hi` catalogs live and rendering on BOTH `web/` SPA and `site/`
marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3
(site), proven by render tests + a real-browser pass.
161    - [ ] Noto Sans Kannada + Devanagari render correctly ? owner eyeball on a real
machine. *(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the
owner's device check.)*
162    - [x] CI key-parity + no-bare-strings green; a stub locale flags every gap ?
`web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift`
guard.
163    - [x] Recording-education (capture + homepage gist) available in `kn` + `hi` ? A3
(#74), incl. a localized camera-placement diagram (A7, #76).
164    - [x] Non-tech UX baseline ? plain-language copy (A1/A6), mobile tap targets (A4) +
the decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only
```

filters (A9), honest today-vs-roadmap preserved through translation.
165 - [] \$7 all rows ? (or explicitly deferred) ? flip **Status** ? **DONE** + run the engine
`DOC\_STATUS.md \$2` archival checklist ? `git mv` to `docs/archives/`. *(\$7 is all ? except the
owner-gated, cross-repo **B7** ? deferred. Holding the **DONE** flip on the two human gates above
(native-speaker review of the AI-drafted kn/hi + the owner font eyeball). Engineering follow-ups
since are all **closed**: own-model body ([#86](https://github.com/avidullu/khelsutra/pull/86)),
the es/da/id site expansion ([#87](https://github.com/avidullu/khelsutra/pull/87)), the hero
demo-mockup + `#how` block ([#89](https://github.com/avidullu/khelsutra/pull/89)), and the
remaining `#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq` sections
([#90](https://github.com/avidullu/khelsutra/pull/90)) ? so the **home page body** is fully
localized in all 6 languages except the `#join` form (A6, deferred). The recurring responsive-
header bug is fixed and now **guarded** by a real-browser layout-regression CI job
([#91](https://github.com/avidullu/khelsutra/pull/91)) ? `site/src/layout.browser.mjs`, headless
Chromium asserting header invariants across widths × 6 locales; jsdom can't see layout). No
engineering gap remains before the two human gates.)*
166

390. user (2026-06-22T06:00:03.655Z)

=== docs/archives exists? ===
(no docs/archives/ dir yet)

=== \$8 open owner gates ===

8. Open questions ? owner (blocking gates) `[design]`

*Status (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see \$2 (D6?D9). Only D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

1. **D-FONT** ? ? **LOCKED** ? (a) OFL-for-media carve-out, self-host Noto Sans Kannada/Devanagari (counsel may still confirm). An explicit exception to the MIT/Apache/BSD code guardrail (fonts = media). Unblocks B4/B5/A3 + the kn/hi reel watermark.
2. **D-LOCALES** ? ? **LOCKED** ? `en` + `kn` for v1, `hi` next, always-fallback to `en` (both 2-form CLDR ? `hi` is catalog-only).
3. **D-BACKEND-DEPTH** ? ? **OPEN** (deferred, not a v1 blocker). ** Recommend **customer verdict/report** `customer\_` + validation-rejection reasons first; technical/operator text stays English; phase two** (engine repo, owner-gated ? tracker row B7).
4. **D-SURFACE-FIRST** ? ? **ADOPTED** ? lead with the SPA scaffold (B1), localize site recording-education early, SKIP the dead static-UI retrofit.**
5. **D-CATALOG-HOME** ? ? **ADOPTED & IMPLEMENTED** (B3) ? repo-root
`/locales/{en,kn,hi,es,da,id}/common.json` is the single source of truth.** The SPA imports it directly (re-pointed to `../../locales`; Vite resolves the workspace root via the repo `.git` marker, so dev/build/test all work). The dependency-free site consumes it through one tiny build step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (auto-runs `predeploy`), with a **drift-guard test** (`site/src/locales-drift.test.js`) failing CI if the shipped copy goes stale. (The engine `I18N\_PLAN` assumed the indexer repo; this is the adaptation.)

=== \$0 TL;DR / status line ===

0. TL;DR

A coach or parent in Bangalore should land on KhelSutra, feel at home, set up their camera with confidence, and get highlights ? **in Kannada or Hindi**, with **zero hand-holding**. This project isolates that goal into one tracked workstream-pair: **(A)** make the UI super friendly for non-tech-savvy users, and **(B)** localize to Hindi + Kannada. Both surfaces (`web/` React SPA + `site/` vanilla marketing) have **zero i18n today** `[verified]`, so the foundation ? shared `locales/{en,kn,hi}` catalogs + a negotiation contract + CI parity ? is the real deliverable; translations follow. **The single most important caveat:** translations are **human-reviewed** (Gemini drafts are **inference only**, never training ? the standing guardrail), and Kannada/Hindi rendering is **blocked** on the OFL font decision (D-FONT). The cheapest unblocked high-impact first slice is the **SPA i18n scaffold + language switcher (en-only)** ? it locks the shared catalog/negotiation contract and adds the render-test safety net the SPA currently lacks.

391. assistant (2026-06-22T06:01:05.099Z)

Here's the honest status ? and it's a small but real "it depends."

What's actually left

Engineering: nothing. Every \$7 row is ? except the one deferred item, and all the post-hoc follow-ups (#86, #87, #89, #90, #91, #92) are closed. The home page body is fully localized in all 6 languages, both surfaces negotiate correctly, and the header is fixed + CI-guarded.

What remains are **three non-engineering items**, two of which the doc's own Definition of Done treats as hard archival blockers:

1. **B7 ? deferred, not a v1 blocker.** Engine backend customer-facing l10n (report `customer\_` fields + rejection reasons) ? it's ***cross-repo*** (the Python `badminton-highlight-indexer`) and gated by the one still-open owner decision, ***D-BACKEND-DEPTH***. Explicitly punted to "phase two." This one can simply ride along as a deferred row.
2. **Native-speaker review** of the AI-drafted catalogs (kn/hi + es/da/id ? all Gemini drafts). \$0 calls this **"the single most important caveat."** It's the standing guardrail before a **wide public launch**.
3. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI literally can't render fonts) ? two unchecked \$9 boxes.

So ? can we archive it?

Strictly by the doc's own rule (\$9): **"Do not `git mv` to `docs/archives/` until (native review) + (font eyeball) clear."** So **not quite** ? but the blockers are **yours to clear, not more engineering.** #2 and #3 are human QA. There's no `docs/archives/` dir yet, so this'd be the first one.

My read: since the engineering is genuinely 100% done, the cleanest move is to **archive now and carry the two human gates forward as live action-items** (in `NEXT\_STEPS.md` / the handoff) rather than keep a completed engineering tracker open just waiting on owner QA ? **provided** you're comfortable that this is an invite-only alpha where native review can precede the wide public launch (not the archive). But if you'd rather the tracker reflect full human sign-off, we hold.

That's your call:

392. user (2026-06-22T06:01:32.565Z)

Your questions have been answered: "The engineering is 100% done, but the doc's DoD holds archival on two human gates (native-speaker translation review + your font-glyph eyeball on a real kn/hi device) ? both yours to clear, not more eng work. How do you want to handle archiving?"="Archive now, carry gates forward". You can now continue with these answers in mind.

393. assistant (2026-06-22T06:02:02.672Z)

Archiving it is ? engineering's done, and the two human gates + B7 ride forward as live items. Let me set up a worktree and find every inbound pointer to the doc first (so nothing dangles):

394. user (2026-06-22T06:03:36.021Z)

origin/master: 0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 + strengthen fitNav tests (#92)

=== inbound references to the doc (repo) ===

```
C:/Users/avidu/Projects/khelsutra/docs/MULTILINGUAL_EXPANSION.md:6:> **Relation to existing docs:** **PEER-OF / extends** [`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md) (the `en`/`kn`/`hi` foundation) and the engine design `I18N_PLAN.md`. **Reuses that foundation verbatim** (react-i18next + i18next-icu + browser detector + key-parity/no-bare-strings CI + self-hosted OFL Noto via `@fontsource` + Gemini-draft?native-review). This is a parallel line: it adds locales, it does not re-architect i18n.
C:/Users/avidu/Projects/khelsutra/docs/MULTILINGUAL_EXPANSION.md:17:**Read to get current:** this doc $3? $4; [`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md) (the foundation this rides on, esp. $4 design + $6.5 negotiation tests); `web/src/i18n/index.ts` (the detector/ICU/fallback config) + `web/src/main.tsx` (the `@fontsource` font-load pattern) + `web/src/i18n/hygiene.test.ts` (key-parity + no-bare-strings + offline guards).
```

```
C:/Users/avidu/Projects/khelsutra/docs/MULTILINGUAL_EXPANSION.md:108:**Internal `[verified]`:**
`web/src/i18n/{index.ts,hygiene.test.ts}`, `web/src/main.tsx` (font-load pattern), repo-root
`/locales/{en,kn,hi,es,da,id}/common.json` (hoisted by FRIENDLY B3 ? D-CATALOG-HOME);
[`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md), engine `docs/I18N_PLAN.md`,
`docs/UI_PROPOSAL.md`.
C:/Users/avidu/Projects/khelsutra/docs/README.md:9:- **`FRIENDLY_AND_MULTILINGUAL.md`** ? **?
active focus (owner directive 2026-06-21):** make the
C:/Users/avidu/Projects/khelsutra/docs/README.md:15: with en/kn/hi-level diligence; peer of
`FRIENDLY_AND_MULTILINGUAL.md`, reusing its foundation.
C:/Users/avidu/Projects/khelsutra/NEXT_STEPS.md:17: **? Tracked design + P-tracker (source of
truth): `docs/FRIENDLY_AND_MULTILINGUAL.md` (DRAFT,
C:/Users/avidu/Projects/khelsutra/web/src/i18n/hygiene.test.ts:1:// CI guardrails that keep i18n
"by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
C:/Users/avidu/Projects/khelsutra/web/src/i18n/index.ts:3:// Per
docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
```

=== references in memory dir ===

```
C:/Users/avidu/.claude/projects/C--Users-avidu-Projects-khelsutra/memory/session-
handoff.md:3:_Last updated: 2026-06-22, after A2 (#82) ? hero-mockup & #how i18n (#89) +
remaining home sections & responsive-header fix (#90) + **browser layout-regression CI guard &
full-locale header fix (#91)** + **chapter-closeout doc sweep & stronger fitNav tests
([#92](https://github.com/avidullu/khelsutra/pull/92))** all MERGED to master (0bef61e). **The
home page body is fully localized in all 6 languages except the #join access form (A6,
deferred).** The `docs/FRIENDLY_AND_MULTILINGUAL.md` changelog + §9 DoD are current through #92
(the two human gates ? native review + owner font eyeball ? are the only thing left)._
C:/Users/avidu/.claude/projects/C--Users-avidu-Projects-khelsutra/memory/session-handoff.md:8:§7
of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo B7**
(deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-friendly:
C:/Users/avidu/.claude/projects/C--Users-avidu-Projects-khelsutra/memory/session-handoff.md:28:-
`docs/FRIENDLY_AND_MULTILINGUAL.md` ? §7 tracker (source of truth, all ? except B7), §6.5 N1?N9,
§9 DoD (boxes flipped; 2 human gates open), changelog.
```

=== create worktree ===

```
HEAD is now at 0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 +
strengthen fitNav tests (#92)
```

395. assistant (2026-06-22T06:04:57.190Z)

Found all inbound pointers. Let me do the move and read the files I'll need to update (README, NEXT_STEPS, the doc's top):

396. user (2026-06-22T06:05:01.989Z)

=== moved; git status ===

```
R docs/FRIENDLY_AND_MULTILINGUAL.md -> docs/archives/FRIENDLY_AND_MULTILINGUAL.md
```

=== docs/README.md (head) ===

khelsutra docs index

Tracked work (this repo)

```
- **`DRY_RUN_CUJ.md`** ? ? **DELIVERED (2026-06-21):** the UI drives the tool on a **GCS-bucket
video** ? review/select ? compile ? **reel downloaded local**, verified in en + Hindi. Path A
(local) + Path B/B-P2 (in-UI `gs://` ingest, [#56]) both live e2e with a screencast (§9); the
only remaining box (droplet, option 3) is **parked by the owner** (GPU subscription). Two
engine
  bugs the runs surfaced are fixed (#281, #289). Was a milestone of
  `LOCAL_APPLIANCE_ARCHITECTURE.md`.
- **`FRIENDLY_AND_MULTILINGUAL.md`** ? **? active focus (owner directive 2026-06-21):** make the
product super user-friendly for non-tech-savvy coaches/parents **and** localize it in Hindi +
Kannada, across both surfaces (`web/` SPA ? react-i18next, `site/` ? a shared `t()` shim). The
implementation project for the engine's `I18N_PLAN.md` (l10n) + the UX half of
`UI_PROPOSAL.md`.
  SPA fully **en+kn+hi** ; remaining = `site/` shim (B3) + UX A-items + native review. `DRAFT`
```

```
(owner-gated).
- MULTILINGUAL_EXPANSION.md ? proposal to add 7 more locales (th/id/da/es/zh-
Hans/ja/ko)
  with en/kn/hi-level diligence; peer of FRIENDLY_AND_MULTILINGUAL.md, reusing its foundation.
  DRAFT ? owner-gated (approval to start), [#58].
- LOCAL_APPLIANCE_ARCHITECTURE.md ? the single-box, UI-powered rally indexer + reel
generator (KhelSutra Studio): the web/ SPA drives the full ingest ? index ? reel loop on one
box behind an edge gate; the single-box deployment profile of the engine's decoupled
architecture. Umbrella for the console; per-rally selection is one screen of it. DRAFT.
```

=== NEXT_STEPS.md lines 13-20 ===

Next product threads (owner ideas, 2026-06-20)

```
- ACTIVE FOCUS (owner directive 2026-06-21): Friendly & Multilingual ? make the product
super user-friendly for non-tech-savvy coaches/parents and localize it in Hindi +
Kannada.
  Tracked design + P-tracker (source of truth): docs/FRIENDLY_AND_MULTILINGUAL.md (DRAFT,
  owner-gated). Both surfaces have zero i18n today; the foundation (shared
locales/{en,kn,hi}
  catalogs + negotiation contract + CI parity) is the deliverable. Recommended first slice =
  SPA i18n scaffold + language switcher (en-only), unblocked. 5 open owner decisions in S8
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

397. assistant (2026-06-22T06:05:13.240Z)

The move is clean (rename detected). Let me read the archived doc's top to add the banner:

398. user (2026-06-22T06:05:14.091Z)

```
1      # Friendly & Multilingual ? non-tech-savvy UX + Hindi/Kannada localization
2
3      > Status: DRAFT ? owner-gated (implementation starts only on explicit approval) .
Owner: Avi Dullu . Created: 2026-06-21 . Last updated: 2026-06-21
4      > Lifecycle: DRAFT ? IN PROGRESS ? DONE ? archived` (move to docs/archives/ when
DONE).
5      > Tracking anchors: S7 progress tracker is the source of truth; indexed in
docs/README.md; thread in NEXT_STEPS.md; pointer in engine docs/DOC_STATUS.md; memory
current-state + next-session-ux-localization.
6      > Relation to existing docs: this is the implementation project for two engine
design docs ? it adapts & supersedes-in-practice badminton-highlight-
indexer/docs/I18N_PLAN.md (localization) and the UX half of docs/UI_PROPOSAL.md (non-tech-
savvy console). Those stay the canonical design; this doc carries the tracked execution
against today's surfaces.
7      > Honesty note: each claim tagged [verified] (checked against code this session),
[researched] (needs sign-off), or [design] (proposed). Not legal advice ? the OFL font
question (D-FONT) is owner/counsel-gated.
8
9      ---
10
```

399. assistant (2026-06-22T06:05:27.123Z)

Now let me update the status line and add the archival banner:

400. user (2026-06-22T06:05:33.977Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/docs/archives/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

401. assistant (2026-06-22T06:06:16.869Z)

Now mark the **S9** archival item done and update the parenthetical:

402. user (2026-06-22T06:06:23.165Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/docs/archives/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

403. assistant (2026-06-22T06:06:31.349Z)

Now add the archival changelog entry:

404. user (2026-06-22T06:06:35.698Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/docs/archives/FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

405. assistant (2026-06-22T06:06:47.704Z)

Now update the inbound pointers. First `docs/README.md`:

406. user (2026-06-22T06:06:52.959Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

407. user (2026-06-22T06:06:57.384Z)

```
9      - **`FRIENDLY_AND_MULTILINGUAL.md`** ? **? active focus (owner directive 2026-06-21):**  
make the  
10      product super user-friendly for non-tech-savvy coaches/parents **and** localize it in  
Hindi +  
11      Kannada, across both surfaces (`web/` SPA ? react-i18next, `site/` ? a shared `t()`  
shim). The  
12      implementation project for the engine's `I18N_PLAN.md` (l10n) + the UX half of  
`UI_PROPOSAL.md`.  
13      SPA fully **en+kn+hi**; remaining = `site/` shim (B3) + UX A-items + native review.  
`DRAFT` (owner-gated).  
14      - **`MULTILINGUAL_EXPANSION.md`** ? proposal to add **7 more locales** (th/id/da/es/zh-  
Hans/ja/ko)
```

408. user (2026-06-22T06:07:05.491Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/docs/README.md has been updated successfully. (file state is current in your context ? no need to Read it back)

409. assistant (2026-06-22T06:07:16.850Z)

Now the three relative links in `docs/MULTILINGUAL\_EXPANSION.md` (they'd 404 after the move).
Let me read it then repoint them:

410. user (2026-06-22T06:07:17.515Z)

```
6      > **Relation to existing docs:** **PEER-OF / extends**  
[`FRIENDLY_AND_MULTILINGUAL.md`](FRIENDLY_AND_MULTILINGUAL.md) (the `en`/`kn`/`hi` foundation)  
and the engine design `I18N_PLAN.md`. **Reuses that foundation verbatim** (react-i18next +  
i18next-icu + browser detector + key-parity/no-bare-strings CI + self-hosted OFL Noto via  
`@fontsource` + Gemini-draft?native-review). This is a **parallel** line: it adds locales, it  
does **not** re-architect i18n.
```

411. user (2026-06-22T06:07:21.673Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/docs/MULTILINGUAL_EXPANSION.md has been updated. All occurrences were successfully replaced. (file state is current in your context ? no need to Read it back)

412. assistant (2026-06-22T06:07:32.067Z)

Now `NEXT\_STEPS.md` ? the active-focus bullet needs to flip to done and seed the carried-forward gates. Let me read the full bullet:

413. user (2026-06-22T06:07:32.944Z)

```
15      - **? ACTIVE FOCUS (owner directive 2026-06-21): Friendly & Multilingual** ? make the
product
16      **super user-friendly for non-tech-savvy** coaches/parents **and localize it in Hindi
+ Kannada**.
17      **? Tracked design + P-tracker (source of truth): `docs/FRIENDLY_AND_MULTILINGUAL.md`
(DRAFT,
18      owner-gated).** Both surfaces have zero i18n today; the foundation (shared
`locales/{en,kn,hi}`
19      catalogs + negotiation contract + CI parity) is the deliverable. **Recommended first
slice =
20      SPA i18n scaffold + language switcher (en-only), unblocked.** 5 open owner decisions
in §8
21      (font OFL carve-out · en+kn-then-hi · backend depth · surface-first · catalog home).
Adapts the
22      engine's `I18N_PLAN.md` (P1?`site/` shim, P3?`web/` react-i18next) + the UX half of
`UI_PROPOSAL.md`.
23      - **Marketing video on the site** ? embed a short walkthrough of the record ? index ?
reel process,
24      themed for **serious enthusiasts**, on the landing page. ? **A real-UI CUJ screencast
now exists**
25      (Playwright recording of the per-rally SPA driven against real GPU-run data ?
`promo_cuj.mp4/`.gif`
26      in `gs://kheIsutra-rally-corpus/promo/`). Decide: use it as the marketing clip (?
shows real court
```

414. user (2026-06-22T06:07:45.316Z)

The file C:/Users/avidu/Projects/kheIsutra-wt-archive/NEXT_STEPS.md has been updated successfully. (file state is current in your context ? no need to Read it back)

415. assistant (2026-06-22T06:08:03.232Z)

Finally, the two design-rationale comments in `web/src/i18n/` that name the (now-moved) path. Let me read and repoint them:

416. user (2026-06-22T06:08:03.947Z)

```
1      // i18n scaffold (tracker B1) ? the shared localization foundation for KheIsutra Studio.
2      //
3      // Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4      //      - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
```

417. user (2026-06-22T06:08:09.221Z)

The file C:/Users/avidu/Projects/kheIsutra-wt-archive/web/src/i18n/index.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

418. assistant (2026-06-22T06:08:14.686Z)

Comment-only (not browser-observable). Now the hygiene test comment:

419. user (2026-06-22T06:08:15.882Z)

```
1      // CI guardrails that keep i18n "by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
2      //      1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
```

420. user (2026-06-22T06:08:20.591Z)

The file C:/Users/avidu/Projects/khelsutra-wt-archive/web/src/i18n/hygiene.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

421. assistant (2026-06-22T06:08:30.787Z)

All pointers updated. Let me verify nothing dangles and review the full change set:

422. user (2026-06-22T06:08:35.559Z)

```
=== git status ===
M NEXT_STEPS.md
M docs/MULTILINGUAL_EXPANSION.md
M docs/README.md
RM docs/FRIENDLY_AND_MULTILINGUAL.md -> docs/archives/FRIENDLY_AND_MULTILINGUAL.md
M web/src/i18n/hygiene.test.ts
M web/src/i18n/index.ts
```

```
=== any remaining OLD-path relative links (should be none)? ===
none ?
```

```
=== any remaining 'docs/FRIENDLY_AND_MULTILINGUAL.md' (non-archives) refs? ===
none ?
```

```
=== archived doc's new outbound links resolve? ===
../.. /NEXT_STEPS.md + ../MULTILINGUAL_EXPANSION.md targets exist ?
```

423. assistant (2026-06-22T06:09:03.480Z)

All clean ? the rename plus 5 pointer updates, zero dangling references. Let me stage explicitly and commit (docs + 2 comments only ? no functional change):

424. user (2026-06-22T06:09:10.373Z)

```
fatal: pathspec 'C:/Users/avidu/Projects/khelsutra-wt-archive/docs/FRIENDLY_AND_MULTILINGUAL.md'
did not match any files
0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 + strengthen fitNav
tests (#92)
```

425. assistant (2026-06-22T06:09:24.607Z)

The old-path deletion was already staged by `git mv` ? I just shouldn't re-add the non-existent path. Re-staging the existing paths only:

426. user (2026-06-22T06:09:27.545Z)

```
=== staged (expect R + 5 M) ===
M NEXT_STEPS.md
M docs/MULTILINGUAL_EXPANSION.md
M docs/README.md
R docs/FRIENDLY_AND_MULTILINGUAL.md -> docs/archives/FRIENDLY_AND_MULTILINGUAL.md
M web/src/i18n/hygiene.test.ts
M web/src/i18n/index.ts
=== unstaged remaining (should be none) ===
none ?
```

427. assistant (2026-06-22T06:09:31.250Z)

All staged cleanly (rename + 5 modifications, nothing unstaged). Committing:

428. user (2026-06-22T06:09:39.864Z)

```
d19781c docs: archive the Friendly & Multilingual tracker (engineering complete)
--- master check ---
```

origin/master: 0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 +
strengthen fitNav tests (#92)
d19781c docs: archive the Friendly & Multilingual tracker (engineering complete)

429. assistant (2026-06-22T06:09:43.651Z)

Committed (d19781c), master unchanged, one commit on top. Pushing and opening the PR:

430. user (2026-06-22T06:09:58.254Z)

To https://github.com/avidullu/khelsutra.git
* [new branch] docs/archive-friendly-multilingual -> docs/archive-friendly-multilingual
https://github.com/avidullu/khelsutra/pull/93
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

431. assistant (2026-06-22T06:10:03.938Z)

PR #93 opened. Watching CI (web + layout run since a web comment changed), then merging:

432. user (2026-06-22T06:11:10.053Z)

web pass 38s
https://github.com/avidullu/khelsutra/actions/runs/27933155508/job/82649032174
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/bc979dc0-2585-46ba-a911-72ab9e796e23
layout pass 53s
https://github.com/avidullu/khelsutra/actions/runs/27933155508/job/82649032168
site pass 16s
https://github.com/avidullu/khelsutra/actions/runs/27933155508/job/82649032253
web pass 38s
https://github.com/avidullu/khelsutra/actions/runs/27933155508/job/82649032174
--- mergeability ---
mergeable=MERGEABLE mergeState=CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

433. assistant (2026-06-22T06:11:16.518Z)

All green, CLEAN. Merging, cleaning up, and updating the memory handoff:

434. user (2026-06-22T06:11:29.070Z)

PR state: MERGED
worktree removed
Deleted branch docs/archive-friendly-multilingual (was d19781c).
rename docs/{ => archives}/FRIENDLY_AND_MULTILINGUAL.md (92%)
main HEAD: e2570e4 docs: archive the Friendly & Multilingual tracker (engineering complete)
(#93)
doc now at: docs/archives/FRIENDLY_AND_MULTILINGUAL.md
EXISTS
old path gone? yes
open PRs: 0

435. assistant (2026-06-22T06:11:45.609Z)

Archived cleanly ? the doc lives at `docs/archives/FRIENDLY\_AND\_MULTILINGUAL.md`, old path gone,
0 open PRs, main fast-forwarded to **#93**. Let me update the memory handoff's doc-path
references and mark the chapter archived:

436. user (2026-06-22T06:11:46.306Z)

1 # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2

3 _Last updated: 2026-06-22, after A2 (#82) ? hero-mockup & #how i18n (#89) + remaining
home sections & responsive-header fix (#90) + **browser layout-regression CI guard & full-locale
header fix (#91)** + **chapter-closeout doc sweep & stronger fitNav tests
([#92](https://github.com/avidullu/khelsutra/pull/92))** all MERGED to master (0bef61e). **The
home page body is fully localized in all 6 languages except the #join access form (A6,
deferred).** The `docs/FRIENDLY\_AND\_MULTILINGUAL.md` changelog + \$9 DoD are current through #92
(the two human gates ? native review + owner font eyeball ? are the only thing left)._
4
5 **Header is now robust across ALL 6 locales + guarded.** #90's fix only covered
en/kn/hi/id; the #91 layout guard caught that **es (+138px) / da (+47px)** still overflowed
(longer translated nav labels). Fixed in #91: the shim (`fitNav` in `site/public/i18n.js`)
measures the header after applying a locale (+ on resize / fonts.ready) and adds `.nav-crowded`
to collapse the 6-link nav to a compact brand+switcher+CTA row when it won't fit ? **measured
live, so it self-adapts to any future translation length.** New CI: a `layout` job runs `npm run
test:layout` = `site/src/layout.browser.mjs` (headless Chromium/Playwright, a site test-only
devDep) asserting header invariants (no overflow / no link-wrap / CTA not clipped / no h-scroll)
across widths × 6 locales on index/capture/own-model. jsdom can't see layout, so this is the
only guard for rendering distortion ? extend it when touching site CSS/markup.
6
7 ## You are here ? chapter effectively COMPLETE (pending human gates)
8 \$7 of `docs/FRIENDLY\_AND\_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo
B7** (deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-friendly:
9 - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: **en/kn/hi +
es/da/id** ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy (kn/hi via
A3, **es/da/id via #87**); Noto bundled for kn/hi), A6 plain-language access form, A7 camera-
placement diagram, **A2 WhatsApp share** (#82), the **UI/UX header pass** (#83: compact `?
<select>`, zero overflow), own-model body (#86), and the **es/da/id site expansion** (#87): the
full `site.` namespace (115 keys) translated ? site now matches the SPA's 6 (dropdown has 6
options; `SUPPORTED`/`SITE\_LOCALES`=6).

437. user (2026-06-22T06:12:11.233Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-
handoff.md has been updated successfully. (file state is current in your context ? no need to
Read it back)

438. user (2026-06-22T06:12:20.304Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-
handoff.md has been updated. All occurrences were successfully replaced. (file state is current
in your context ? no need to Read it back)

439. assistant (2026-06-22T06:12:37.591Z)

Done ? the chapter is archived and the project is closed out.

? Archived ? [#93](https://github.com/avidullu/khelsutra/pull/93) merged (master `e2570e4`)

What was left (and is now the only thing on the project): **nothing engineering** ? just
three owner-side items, all carried forward into `NEXT\_STEPS.md` as live action-items:
1. **Native-speaker review** of the AI-drafted catalogs (kn/hi/es/da/id ? the standing guardrail
before a *wide public launch*).
2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
3. **B7** ? engine backend l10n (cross-repo Python, owner-gated `D-BACKEND-DEPTH`) ? deferred,
not a v1 blocker.

The archival itself:

- `git mv docs/FRIENDLY\_AND\_MULTILINGUAL.md ? docs/archives/` (the repo's first `docs/archives/`
entry). Status flipped to **DONE ? ARCHIVED** with a banner, the \$9 archival box checked, and a
final changelog entry.
- **Every inbound pointer repointed so nothing dangles** ? `NEXT\_STEPS.md`, `docs/README.md`,
`docs/MULTILINGUAL\_EXPANSION.md` (3 relative links), and the two `web/src/i18n/` design-
rationale comments. Verified: zero remaining old-path references, and the archived doc's own
relative links resolve.

- Docs + 2 comments only ? no functional change; ****all four CI jobs green**** (site, web, ****layout****, Workers build), and I confirmed no test asserted the old doc path.
- Memory handoff updated to reflect the archive + point at the new location.

So: the ****Friendly & Multilingual**** workstream is genuinely complete and put to bed ? 6 languages end-to-end across both surfaces, a fully-localized home page, a self-healing + CI-guarded header, and a clean paper trail. The only things outstanding are yours to do whenever you like (the native review + a glance at the fonts on your phone).

A great session indeed ? thanks for the clear calls along the way. ?