

# claude-windows / c1fcb4aa-537d-41fd-858e-53f93349bf5a

## Metadata

- Source: `claude-windows`
- Kind: `claude`
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\c1fcb4aa-537d-41fd-858e-53f93349bf5a\subagents\workflows\wf\_b43bcbe7-b94\agent-a4dc83a025e9db332.jsonl`
- SHA-256: `4a58682932f7245966e846ee4f9fddc11f29799cad91a3c1c9ac926cbec459db`
- Source modified: `2026-07-02T03:18:48+00:00`
- Imported at: `2026-07-05T16:48:24+00:00`
- project: `wf\_b43bcbe7-b94`
- session\_id: `c1fcb4aa-537d-41fd-858e-53f93349bf5a`

## Transcript

### 1. user (2026-07-02T03:16:59.069Z)

You are an adversarial verifier in a tech-debt audit of the multi-repo workspace at C:/Users/avidu/Projects/khelsutra-guru (repos: badminton-highlight-indexer, khelsutra, sports-data-collector, rally-annotator, sports-obsreport; non-git dirs 'Annotation Setup', khelsutra-screencast). Today is 2026-07-02. All repos are at origin head.  
Default stance: REFUTE. A round-1 finder claimed (UNVERIFIED):  
REPO: rally-annotator  
CLAIM: Locked decision LD-i8 (web language persisted + seeded from browser language) is documented as shipped but not implemented ? panel always boots in English and forgets the choice on reload  
INVESTIGATION HINTS: Find the LD-i8 decision doc claim vs the actual locale bootstrapping code. VERIFY against the CURRENT working tree: (1) reproduce the defect/debt from actual code at file:line; (2) check git log for a fix that already landed; (3) construct the concrete failure scenario or downgrade severity; (4) propose the correctly-scoped fix with effort S/M/L; (5) flag OWNER\_GATED if it needs owner decisions (real cloud spend, product/strategy, counsel, Cloudflare dashboard).  
HARD RULES: READ-ONLY ? no file modifications, no installs (pip download/index checks and WebFetch to pypi.org are OK), no test-suite runs. gh read-only OK. sqlite reads OK. CONFIRMED requires you personally observed the defect in current code/data; cite file:line for every claim.

### 2. user (2026-07-02T03:17:07.222Z)

Annotation Setup  
badminton-highlight-indexer  
khelsutra  
khelsutra-screencast  
rally-annotator  
sports-data-collector  
sports-obsreport  
CHANGELOG.md  
CONTRIBUTING.md  
LICENSE  
README.md  
docs  
test  
vlc  
web

### 3. user (2026-07-02T03:17:11.166Z)

C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\docs\LOCALIZATION.md:55:### LD-i8 ?  
Language selection, persisted

### 4. user (2026-07-02T03:17:18.308Z)

```

1      # Localization (i18n) ? design & locked decisions
2
3      > Part of **[Khelsutra](https://khelsutra.guru)**. rally-annotator localizes its UI into
the **same
4      > languages** and using the **same catalog architecture** as the Khelsutra product
5      > (`avidullu/khelsutra`, PRs #67/#70) ? so a rater labels in their own language, and the
two repos
6      > stay aligned on locales, catalog keys, and conventions.
7
8      This records the localization **design** and **locked decisions**. "Locked" = settled;
change only via a
9      new decision entry here in a PR. Both front-ends are in scope: the **browser extension**
(`web/`) first,
10     then the **VLC Lua plugin** (`vlc/`).
11
12     ## Why
13     rally-annotator is Khelsutra's open labeling tool. Khelsutra ships a localized product
(en/kn/hi +
14     es/da/id, with Telugu requested in khelsutra#72); the labeling tool should meet raters
in the same
15     languages. We mirror Khelsutra's proven i18n foundation rather than invent one.
16
17     ## Locked decisions
18
19     ### LD-i1 ? Locale set: `en, kn, hi, es, da, id, te`
20     Khelsutra's shipped six (en, kn, hi, es, da, id) **+ Telugu (te)**. `en` is the source
of truth; a
21     missing key/locale **always falls back to `en`**, never a raw key. (Telugu in Khelsutra:
khelsutra#72.)
22
23     ### LD-i2 ? Scope: both front-ends, web first
24     Browser extension first (it matches Khelsutra's web surface), then the VLC plugin with a
**parallel
25     keyed string table using the same keys**.
26
27     ### LD-i3 ? Shared `common.json` catalog, keys-not-prose
28     Mirror Khelsutra's catalog: namespaced keys (`panel.*`, `reason.*`, `status.*`,
`help.*`, `lang.*`),
29     **keys not literals**. ICU-lite interpolation + plurals (`Intl.PluralRules` on web;
minimal `%{var}`
30     in Lua). Reuse Khelsutra key names where they overlap.
31
32     ### LD-i4 ? DATA stays canonical English (pipeline invariant)
33     The reason/sport enum **values** (`winner`, `badminton`, `?) and the **CSV header** are
DATA written to
34     the CSV and **never translate**, regardless of UI language ? preserving byte-compatible
output for the
35     pipeline. Only **display labels/help/status** translate. A test asserts the CSV is
identical across UI
36     languages.
37
38     ### LD-i5 ? Web runtime: a dependency-free `t()` shim
39     Mirror Khelsutra's site `public/i18n.js`: a tiny `t(key, vars)` over the shared catalog,
ICU-lite
40     plurals via `Intl.PluralRules`, **always-fall-back-to-`en`. Chosen over i18next for the
**content-script
41     overlay** (smallest injected bundle); the catalog format stays identical to the product.
42
43     ### LD-i6 ? Translations: AI draft now, marked pending native review
44     `en` is authored. The six non-en catalogs are **AI/Gemini drafts, each clearly marked
45     `"_meta": { "status": "machine-draft", "review": "pending-native" }`**. Native-speaker
review is the
46     quality/launch gate (drafts are inference-only ? Khelsutra's standing guardrail).
**Spanish (`es`) has a
47     3-form plural** (`{one, many, other}`) ? the one authoring wrinkle; every `es` plural

```

```

must carry a `many`
48     arm.
49
50     ### LD-i7 ? Fonts: self-hosted OFL Noto for non-Latin
51     The web panel self-hosts **OFL Noto** (`@fontsource`, `unicode-range`-scoped) for
**Devanagari (hi),
52     Kannada (kn), Telugu (te)**; es/da/id are Latin (no new font). VLC relies on **system
fonts** ? Indic/
53     Telugu rendering in VLC's Qt dialog is a **manual live-test caveat**.
54
55     ### LD-i8 ? Language selection, persisted
56     Each UI has a language selector. Web: persisted in `chrome.storage.local` (seeded from
the browser
57     language; default `en`). VLC: persisted in a tiny config file (extensions have no
settings API).
58
59     ### LD-i9 ? CI gates: key-parity + no-bare-strings (merge-blocking, both front-ends)
60     **Key-parity**: every locale defines exactly the `en` key set, or CI fails. **No-bare-
strings**: no
61     user-facing literal may bypass `t()`. These keep contributor PRs trustworthy as locales
grow.
62
63     ## Web extension approach (`web/`)
64     - `web/src/i18n/`: `locales/<lang>/common.json` + the `t()` shim + a store-backed
current locale + Noto
65     font assets. Catalog namespaces mirror Khelsutra.
66     - **Refactor**: the pure `Annotator` currently returns English status **strings**;
change it to return
67     message **keys + params** (e.g. `{ ok, key: "status.savedRally", params: { n, s, e,
reason, sport } }`),
68     and have the panel render `t(key, params)`. Keeps the state machine pure **and**
localizable.
69     `SPORTS`/`REASONS` keep canonical values; add `reason.*`/`sport.*` **label** keys for
display only.
70     - `panel.ts`: every label/button/help/status via `t()`; add a language ``
(persisted); inject the
71     Noto font for the active script into the shadow root.
72     - **Tests**: key-parity, no-bare-strings, per-locale panel snapshot, **CSV-invariance
across languages**,
73     and a Playwright E2E that switches each locale and records a **downloadable
screencast**.
74
75     ## VLC plugin approach (`vlc/`)
76     - `STRINGS[lang][key]` Lua table (same keys as the web catalog; generated from
`common.json`), `t(key,
77     params)` with `en` fallback + `%{var}` interpolation.
78     - Language **dropdown**; on change, **rebuild the dialog** (reuse the existing widget-
recreation pattern).
79     Persist the choice in a config file.
80     - `descriptor()` stays English (scan sandbox; VLC shows one title); dialog content
localizes. Reason/sport
81     CSV **values** stay canonical.
82     - **Tests**: extend `test/dialog_test.lua` ? key-parity (every `STRINGS[lang]` == `en`
keys), per-language
83     label snapshot, CSV-value-canonical. Font rendering = manual VLC live-test.
84
85     ## Translation process
86     Author `en` from the extracted strings; AI-draft `hi/kn/es/da/id/te` (each marked
machine-draft ? pending
87     native review); track native review separately (the launch gate). The long **ending-
reason guide** is the
88     largest block ? phase it after the UI strings.
89
90     ## Verification
91     - **web**: `npm run typecheck`; key-parity + no-bare-strings + per-locale snapshot +

```

```

CSV-invariance tests;
92      `npm run build`; Playwright E2E per locale producing **downloadable screencasts**
under
93      `web/e2e-results/`.
94      - **VLC:** `lua5.1 test/dialog_test.lua` green (key-parity + snapshots); manual VLC
live-test for font
95      rendering per script.
96
97      ## Phasing (PRs)
98      1. ? **docs** (this file) ? PR #17.
99      2. ? **web i18n infra** ? `t()` shim + `en` catalog + selector + CI gates + tests ? PR
#18.
100     3. ? **web translations** ? the six AI-drafted catalogs + Noto-aware fonts + per-locale
screencasts ? PR #19.
101     4. ? **VLC i18n** (v1.7 ? v1.7.1) ? Lua `STRINGS` table (machine drafts) + a
**Language** selector that
102     rebuilds the dialog + persists the choice + **id-based canonical reason/sport** so
the CSV is unchanged;
103     key-parity + language-switch tests. v1.7 localized the **chrome**; **v1.7.1 completes
it** ? the
104     **status messages** and the full in-dialog **ending-reason HELP guide** are localized
too (81
105     keys/locale). The whole dialog is now translated.
106     5. ? **Remaining:** **native-speaker review** of every machine-draft catalog (web + VLC)
? the quality
107     gate before any launch; and bundled OFL Noto fonts for guaranteed offline rendering.
108

```

## 5. user (2026-07-02T03:17:19.253Z)

C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web:

```

DESIGN.md
README.md
TESTING.md
e2e
entrypoints
package-lock.json
package.json
playwright.config.ts
src
test
tsconfig.json
vitest.config.ts
wxt.config.ts

```

C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/e2e:

```

extension.spec.ts
fixtures
serve.mjs

```

C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/e2e/fixtures:

```

index.html
sample.webm

```

C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/entrypoints:

```

background.ts
content.ts

```

C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src:

```

i18n
messages.ts
persist
state
ui
version.ts

```

video

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n:
index.ts
locales
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales:
da
en
es
hi
id
kn
te
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/da:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/en:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/es:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/hi:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/id:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/kn:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/i18n/locales/te:
common.json
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/persist:
store.ts
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/state:
annotator.ts
csv.ts
```

```
C:/Users/avidu/Projects/khelsutra-guru/rally-annotator/web/src/ui:
panel.ts
```

## 6. assistant (2026-07-02T03:17:25.844Z)

The doc claims LD-i8 shipped for web (phases 2?3 marked ?, PRs #18/#19). Now let me check the actual locale bootstrapping code.

## 7. user (2026-07-02T03:17:26.801Z)

```
1      // i18n ? a dependency-free t() shim over a shared common.json catalog, mirroring
2      // Khelsutra's marketing-site shim (avidullu/khelsutra `site/public/i18n.js`). Keys,
never
3      // prose; always fall back to `en`; a missing key degrades to en, then to the raw key
4      // (which the "every used key exists in en" test forbids in practice).
5      //
6      // rally-annotator's UI strings are deliberately PLURAL-FREE (counts are phrased
neutrally,
7      // e.g. "Rallies: {count}"), so the shim is interpolation-only ? no Intl.PluralRules and
8      // none of Spanish's 3-form-plural wrinkle. See docs/LOCALIZATION.md.
9
10     import en from "./locales/en/common.json";
```

```

11 import kn from "./locales/kn/common.json";
12 import hi from "./locales/hi/common.json";
13 import te from "./locales/te/common.json";
14 import es from "./locales/es/common.json";
15 import da from "./locales/da/common.json";
16 import id from "./locales/id/common.json";
17
18 export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id", "te"] as const;
19 export type Locale = (typeof SUPPORTED_LOCALES)[number];
20 export const DEFAULT_LOCALE: Locale = "en";
21
22 // Native-script display names for the language selector.
23 export const LOCALE_LABELS: Record<Locale, string> = {
24   en: "English",
25   kn: "?????",
26   hi: "?????",
27   es: "Español",
28   da: "Dansk",
29   id: "Bahasa Indonesia",
30   te: "?????",
31 };
32
33 // Scripts that need a bundled OFL Noto font (Latin locales render with the system
stack).
34 export const NON_LATIN: ReadonlySet<Locale> = new Set<Locale>(["kn", "hi", "te"]);
35
36 type Catalog = Record<string, string>;
37
38 // Registered catalogs. `en` is the source of truth; the six translated catalogs are
39 // machine drafts pending native review (see each file's _meta). An unregistered locale,
40 // or any key missing from a catalog, falls back to en.
41 const C = (j: unknown) => j as unknown as Catalog;
42 const CATALOGS: Partial<Record<Locale, Catalog>> = {
43   en: C(en),
44   kn: C(kn),
45   hi: C(hi),
46   te: C(te),
47   es: C(es),
48   da: C(da),
49   id: C(id),
50 };
51
52 export function registerCatalog(locale: Locale, catalog: Catalog): void {
53   CATALOGS[locale] = catalog;
54 }
55
56 let current: Locale = DEFAULT_LOCALE;
57 export function getLocale(): Locale {
58   return current;
59 }
60 export function setLocale(locale: Locale): void {
61   current = (SUPPORTED_LOCALES as readonly string[]).includes(locale) ? locale :
DEFAULT_LOCALE;
62 }
63
64 function toSupported(code?: string | null): Locale | null {
65   if (!code) return null;
66   const base = code.toLowerCase().split("-")[0];
67   return (SUPPORTED_LOCALES as readonly string[]).includes(base) ? (base as Locale) :
null;
68 }
69
70 // Negotiation order (shared with Khelsutra): a stored/explicit preference wins, then
the
71 // browser's languages, then `en`. Pure ? safe to call with no arguments outside a

```

```

browser.
72     export function negotiateLocale(stored?: string | null, navLangs: readonly string[] =
[]): Locale {
73         const fromStored = toSupported(stored);
74         if (fromStored) return fromStored;
75         for (const l of navLangs) {
76             const m = toSupported(l);
77             if (m) return m;
78         }
79         return DEFAULT_LOCALE;
80     }
81
82     function interpolate(tpl: string, vars?: Record<string, string | number>): string {
83         if (!vars) return tpl;
84         return tpl.replace(/\{(\w+)\}/g, (_m, k: string) => (k in vars ? String(vars[k]) :
`{${k}}`));
85     }
86
87     // t(key, vars?, locale?) ? resolve against the locale, then en, then the raw key.
88     export function t(
89         key: string,
90         vars?: Record<string, string | number>,
91         locale: Locale = current
92     ): string {
93         const tpl = CATALOGS[locale]?.[key] ?? CATALOGS.en?.[key] ?? key;
94         return interpolate(tpl, vars);
95     }
96
97     // ---- introspection used by the key-parity / key-presence tests ----
98     export function registeredLocales(): Locale[] {
99         return Object.keys(CATALOGS) as Locale[];
100     }
101     // Catalog keys excluding the `_meta` bookkeeping entry.
102     export function catalogKeys(locale: Locale): string[] {
103         return Object.keys(CATALOGS[locale] ?? {}).filter((k) => k !== "_meta");
104     }
105     export const EN_KEYS: string[] = catalogKeys("en");
106

```

## 8. user (2026-07-02T03:17:27.213Z)

```

1     // Live store + per-video identity. chrome.storage.local is the source of truth (it is
2     // extension-scoped ? unlike a content script's IndexedDB, which would live in the
3     // VISITED site's origin ? and is plenty for per-video rally data). Resume numbering is
4     // derived from the loaded rows by the Annotator, exactly like VLC's
next_rally_number().
5
6     import { browser } from "wxt/browser";
7     import type { RallyRow } from "../state/csv";
8
9     const PREFIX = "rally:";
10
11     export interface VideoIdentity {
12         key: string; // storage discriminator (stable per video)
13         title: string; // human label, used as the CSV filename base
14     }
15
16     // Structural subset of Location so this is unit-testable with a plain URL.
17     export interface LocationLike {
18         hostname: string;
19         search: string;
20         pathname: string;
21         origin: string;
22     }
23

```

```

24 // Derive a stable key for the current page's video. YouTube watch/shorts/youtu.be get
25 // the video id; everything else uses origin+pathname (volatile query/hash dropped).
26 // location/title are injectable so this is testable without a DOM.
27 export function deriveIdentity(loc: LocationLike = location, docTitle?: string):
VideoIdentity {
28     const host = loc.hostname.replace(/^www\./, "");
29     const fallbackTitle = typeof document !== "undefined" ? document.title : "";
30     const title = ((docTitle ?? fallbackTitle) || host || "rallies").trim();
31
32     if (/^(^|\.)youtube\.com$/.test(host)) {
33         const v = new URLSearchParams(loc.search).get("v");
34         const shorts = loc.pathname.match(/^\/shorts\/([^\s]+)/);
35         const id = v ?? (shorts ? shorts[1] : null);
36         if (id) return { key: `yt:${id}`, title };
37     }
38     if (host === "youtu.be") {
39         const id = loc.pathname.slice(1).split("/")[0];
40         if (id) return { key: `yt:${id}`, title };
41     }
42     return { key: `url:${loc.origin}${loc.pathname}`, title };
43 }
44
45 export async function loadRows(key: string): Promise<RallyRow[]> {
46     const r = await browser.storage.local.get(PREFIX + key);
47     const v = (r as Record<string, unknown>)[PREFIX + key];
48     return Array.isArray(v) ? (v as RallyRow[]) : [];
49 }
50
51 export async function saveRows(key: string, rows: RallyRow[]): Promise<void> {
52     await browser.storage.local.set({ [PREFIX + key]: rows });
53 }
54
55 // Sanitize a title into a safe "<name>.rallies.csv" filename (mirrors the VLC output
56 // naming of <video-stem>.rallies.csv, as close as a sandboxed download allows).
57 export function csvFilename(title: string): string {
58     const base = title
59         .replace(/[\\/:*?"<>|]+/g, "_")
60         .replace(/\s+/g, " ")
61         .trim()
62         .slice(0, 80);
63     return base ? `${base}.rallies.csv` : "rallies.csv";
64 }
65

```

#### 9. user (2026-07-02T03:17:36.022Z)

No matches found

#### 10. user (2026-07-02T03:17:37.093Z)

```

11:import { t, getLocale, setLocale, SUPPORTED_LOCALES, LOCALE_LABELS, type Locale } from
"./i18n";
129: langSel.value = getLocale();
242: langSel.value = getLocale();
307: setLocale(langSel.value as Locale);
308: deps.onLocaleChange?.(getLocale());

```

#### 11. user (2026-07-02T03:17:41.625Z)

```

1 // In-page annotation panel ? the browser analogue of the VLC dialog. Rendered into an
2 // OPEN Shadow DOM so the host page's CSS can't bleed in (and vice-versa) while still
3 // being reachable by automation/devtools ("closed" is not a real security boundary).
4 // Every user-facing string goes through the i18n shim t() (keys-not-prose);
reason/sport

```



```

5      // VALUES stay canonical (written to the CSV) ? only their display labels are
translated.
6
7      import { Annotator, SPORTS, REASON_OPTIONS, type Msg } from "../state/annotator";
8      import type { DirectVideoHandler } from "../video/directVideo";
9      import type { VideoIdentity } from "../persist/store";
10     import { VERSION } from "../version";
11     import { t, getLocale, setLocale, SUPPORTED_LOCALES, LOCALE_LABELS, type Locale } from
"../i18n";
12
13     export interface PanelDeps {
14         annotator: Annotator;
15         video: DirectVideoHandler;
16         identity: VideoIdentity;
17         download: (csv: string) => void;
18         onLocaleChange?: (locale: Locale) => void; // optional: persist the choice (content
script wires this)
19     }
20
21     export interface PanelHandle {
22         toggle(): void;
23         destroy(): void;
24     }
25
26     // mm:ss.mmm for display (matches the Lua fmt_clock).
27     function fmtClock(s: number | null): string {
28         if (s == null) return "--:--";
29         if (s < 0) s = 0;
30         const m = Math.floor(s / 60);
31         const sec = s - m * 60;
32         return `${m}:${sec.toFixed(3).padStart(6, "0")}`;
33     }
34
35     function esc(t: string): string {
36         return t.replace(/&/g, "&amp;").replace(/</g, "&lt;").replace(/>/g, "&gt;");
37     }
38
39     // Translate a Msg, mapping canonical reason/sport params to their display labels.
40     function tMsg(m: Msg): string {
41         let p = m.params;
42         if (p && (typeof p.reason === "string" || typeof p.sport === "string")) {
43             p = { ...p };
44             if (typeof p.reason === "string") p.reason = t("reason." + p.reason);
45             if (typeof p.sport === "string") p.sport = t("sport." + p.sport);
46         }
47         return t(m.key, p);
48     }
49
50     const STYLE = `
51 :host { all: initial; }
52 * { box-sizing: border-box; font-family: system-ui, "Noto Sans", "Noto Sans Devanagari",
53 "Noto Sans Kannada", "Noto Sans Telugu", "Nirmala UI", sans-serif; }
54 .card {
55     position: fixed; top: 16px; right: 16px; width: 340px; z-index: 2147483647;
56     background: #1e1f22; color: #e6e6e6; border: 1px solid #444; border-radius: 8px;
57     box-shadow: 0 8px 28px rgba(0,0,0,.5); font-size: 12px; user-select: none;
58 }
59 .hdr { display: flex; align-items: center; gap: 6px; padding: 7px 9px; cursor: move;
60     background: #2b2d31; border-radius: 8px 8px 0 0; }
61 .hdr .t { font-weight: 600; flex: 1; }
62 .hdr button { cursor: pointer; }
63 .body { padding: 9px; display: flex; flex-direction: column; gap: 7px; }
64 .row { display: flex; gap: 6px; align-items: center; }
65 .row > * { min-width: 0; }
66 label { color: #aab; white-space: nowrap; }

```

```

67   input, select, button {
68       font-size: 12px; background: #2b2d31; color: #e6e6e6; border: 1px solid #555;
69       border-radius: 5px; padding: 4px 6px;
70   }
71   input { width: 100%; }
72   button { cursor: pointer; background: #3a3d44; }
73   button:hover { background: #474b54; }
74   button.primary { background: #2f6f4f; border-color: #3c8a63; }
75   button.primary:hover { background: #38805c; }
76   .grid2 { display: grid; grid-template-columns: 1fr 1fr; gap: 6px; }
77   .status { background: #15161a; border: 1px solid #333; border-radius: 5px; padding: 6px;
78       line-height: 1.45; min-height: 52px; color: #cfd3da; }
79   .list { background: #15161a; border: 1px solid #333; border-radius: 5px; height: 122px;
80       overflow-y: auto; }
81   .list .item { padding: 3px 6px; cursor: pointer; border-bottom: 1px solid #232427;
82       white-space: nowrap; }
83   .list .item:hover { background: #25262b; }
84   .list .item.sel { background: #2f4a6f; }
85   .help { background: #15161a; border: 1px solid #333; border-radius: 5px; padding: 7px;
86       line-height: 1.5; max-height: 260px; overflow-y: auto; color: #cfd3da; }
87   .mini { font-size: 11px; color: #8b90a0; }
88   `;
89
90   function h<K extends keyof HTMLElementTagNameMap>(  

91       tag: K,  

92       props: Partial<HTMLElementTagNameMap[K]> & { class?: string } = {},  

93       ...kids: (Node | string)[]  

94   ): HTMLElementTagNameMap[K] {  

95       const e = document.createElement(tag);  

96       for (const [k, v] of Object.entries(props)) {  

97           if (k === "class") e.className = v as string;  

98           else (e as any)[k] = v;  

99       }  

100       for (const kid of kids) e.append(kid as any);  

101       return e;  

102   }
103
104   export function mountPanel(deps: PanelDeps): PanelHandle {  

105       const { annotator: a, video, download } = deps;  

106
107       const host = document.createElement("div");  

108       host.style.all = "initial";  

109       const root = host.attachShadow({ mode: "open" });  

110       root.append(h("style", { textContent: STYLE }));  

111
112       const card = h("div", { class: "card" });  

113       root.append(card);  

114
115       // ---- header (drag handle) ----  

116       const titleEl = h("span", { class: "t" });  

117       const helpBtn = h("button", { title: "Toggle help" });  

118       const hideBtn = h("button", { textContent: "?", title: "Hide panel" });  

119       const hdr = h("div", { class: "hdr" }, titleEl, helpBtn, hideBtn);  

120       card.append(hdr);  

121
122       const body = h("div", { class: "body" });  

123       card.append(body);  

124
125       // ---- language ----  

126       const langLabel = h("label");  

127       const langSel = h("select", { name: "language" }) as HTMLSelectElement;  

128       for (const l of SUPPORTED_LOCALES) langSel.append(h("option", { value: l, textContent:  

LOCALE_LABELS[l] }));  

129       langSel.value = getLocale();  

130       body.append(h("div", { class: "row" }, langLabel, langSel));

```

```

131
132 // ---- sport ----
133 const sportLabel = h("label");
134 const sportSel = h("select", { name: "sport" }) as HTMLSelectElement;
135 for (const s of SPORTS) sportSel.append(h("option", { value: s }));
136 sportSel.value = a.sport;
137 body.append(h("div", { class: "row" }, sportLabel, sportSel));
138
139 // ---- playback ----
140 const backBtn = h("button");
141 const playBtn = h("button");
142 const fwdBtn = h("button");
143 body.append(h("div", { class: "row" }, backBtn, playBtn, fwdBtn));
144
145 // ---- start / end ----
146 const startLabel = h("label");
147 const startIn = h("input", { name: "start" }) as HTMLInputElement;
148 const endLabel = h("label");
149 const endIn = h("input", { name: "end" }) as HTMLInputElement;
150 body.append(h("div", { class: "row" }, startLabel, startIn, endLabel, endIn));
151
152 // ---- next # / shots ----
153 const nextLabel = h("label");
154 const nextIn = h("input", { name: "next" }) as HTMLInputElement;
155 const shotsLabel = h("label");
156 const shotsIn = h("input", { name: "shots" }) as HTMLInputElement;
157 body.append(h("div", { class: "row" }, nextLabel, nextIn, shotsLabel, shotsIn));
158
159 // ---- reason ----
160 const reasonLabel = h("label");
161 const reasonSel = h("select", { name: "reason" }) as HTMLSelectElement;
162 for (const r of REASON_OPTIONS) reasonSel.append(h("option", { value: r }));
163 body.append(h("div", { class: "row" }, reasonLabel, reasonSel));
164
165 // ---- mark / save ----
166 const markStartBtn = h("button");
167 const markEndBtn = h("button");
168 const saveBtn = h("button", { class: "primary" });
169 body.append(h("div", { class: "grid2" }, markStartBtn, markEndBtn));
170 body.append(h("div", { class: "row" }, saveBtn));
171
172 // ---- status ----
173 const status = h("div", { class: "status" });
174 body.append(status);
175
176 // ---- help (hidden by default) ----
177 const help = h("div", { class: "help" });
178 help.style.display = "none";
179 body.append(help);
180
181 // ---- recent list ----
182 const recentLabel = h("div", { class: "mini" });
183 body.append(recentLabel);
184 const list = h("div", { class: "list" });
185 body.append(list);
186
187 // ---- actions ----
188 const editBtn = h("button");
189 const delBtn = h("button");
190 const undoBtn = h("button");
191 const refreshBtn = h("button");
192 const dlBtn = h("button");
193 body.append(h("div", { class: "grid2" }, editBtn, delBtn));
194 body.append(h("div", { class: "grid2" }, undoBtn, refreshBtn));
195 body.append(h("div", { class: "row" }, dlBtn));

```

```

196
197 // ---- state ----
198 let selectedN: number | null = null;
199 let lastMsg: Msg = { key: "status.ready" };
200
201 function setStatus(m: Msg) {
202     lastMsg = m;
203     render();
204 }
205
206 // Language-only text (static labels, option labels, placeholders, fixed buttons,
help).
207 // Re-applied on mount and whenever the locale changes.
208 function applyI18n() {
209     titleEl.textContent = `? ${t("panel.title")} v${VERSION}`;
210     langLabel.textContent = t("label.language");
211     sportLabel.textContent = t("label.sport");
212     for (const o of Array.from(sportSel.options)) o.textContent = t("sport." + o.value);
213     backBtn.textContent = t("btn.back5");
214     playBtn.textContent = t("btn.playPause");
215     fwdBtn.textContent = t("btn.fwd5");
216     startLabel.textContent = t("label.start");
217     endLabel.textContent = t("label.end");
218     nextLabel.textContent = t("label.next");
219     shotsLabel.textContent = t("label.shots");
220     startIn.placeholder = t("ph.start");
221     endIn.placeholder = t("ph.end");
222     nextIn.placeholder = t("ph.next");
223     shotsIn.placeholder = t("ph.shots");
224     reasonLabel.textContent = t("label.reason");
225     for (const o of Array.from(reasonSel.options)) o.textContent = t("reason." +
o.value);
226     editBtn.textContent = t("btn.edit");
227     delBtn.textContent = t("btn.delete");
228     refreshBtn.textContent = t("btn.refresh");
229     dlBtn.textContent = t("btn.downloadCsv");
230     recentLabel.textContent = t("label.recent");
231     help.innerHTML = t("help.html");
232 }
233
234 function render() {
235     // fields
236     startIn.value = a.startField;
237     endIn.value = a.endField;
238     nextIn.value = a.nextField;
239     shotsIn.value = a.shotsField;
240     reasonSel.value = a.reason;
241     sportSel.value = a.sport;
242     langSel.value = getLocale();
243     // state-dependent labels
244     markStartBtn.textContent = tMsg(a.markStartLabel());
245     markEndBtn.textContent = tMsg(a.markEndLabel());
246     saveBtn.textContent = tMsg(a.saveLabel());
247     undoBtn.textContent = tMsg(a.undoLabel());
248     helpBtn.textContent = help.style.display === "none" ? t("btn.help") :
t("btn.hideHelp");
249     // status
250     const editing = a.mode === "edit" && a.editIndex !== null ? a.rows[a.editIndex] :
null;
251     const last = a.lastRow();
252     const lines = [
253         tMsg(lastMsg),
254         editing ? t("status.modeEdit", { n: editing.n }) : t("status.modeNew"),
255     ];
256     if (last) {

```

```

257         lines.push(
258             tMsg({
259                 key: "status.lastRow",
260                 params: { n: last.n, s: fmtClock(last.s), e: fmtClock(last.e), reason:
last.reason },
261             })
262         );
263     }
264     lines.push(t("status.footer", { now: fmtClock(video.now()), count: a.rows.length
}));
265     status.innerHTML =
266         lines.map(esc).join("<br>") +
267         `<br><span class="mini">${esc(t("status.csvLine", { key: deps.identity.key
})))}</span>`;
268     // list
269     list.replaceChildren();
270     for (const r of a.rows) {
271         const shotsTxt = r.shots != null ? ` ${r.shots} ${t("ph.shots")}` : "";
272         const item = h("div", {
273             class: "item" + (r.n === selectedN ? " sel" : ""),
274             textContent: `#${r.n} ${fmtClock(r.s)} ? ${fmtClock(r.e)} [${t("reason." +
r.reason)}, ${t("sport." + r.sport)}]${shotsTxt}`,
275         });
276         item.addEventListener("click", () => {
277             selectedN = r.n;
278             render();
279         });
280         list.append(item);
281     }
282 }
283
284 // ---- wiring ----
285 startIn.addEventListener("input", () => {
286     a.startField = startIn.value;
287     render();
288 });
289 endIn.addEventListener("input", () => {
290     a.endField = endIn.value;
291     render();
292 });
293 nextIn.addEventListener("input", () => {
294     a.nextField = nextIn.value;
295     render();
296 });
297 shotsIn.addEventListener("input", () => {
298     a.shotsField = shotsIn.value;
299 });
300 reasonSel.addEventListener("change", () => {
301     a.reason = reasonSel.value;
302 });
303 sportSel.addEventListener("change", () => {
304     a.sport = sportSel.value;
305 });
306 langSel.addEventListener("change", () => {
307     setLocale(langSel.value as Locale);
308     deps.onLocaleChange?.(getLocale());
309     applyI18n();
310     render();
311 });
312
313 backBtn.addEventListener("click", () =>
314     setStatus({ key: video.seekBy(-5) ? "status.seekBack" : "status.noVideoSeek" })
315 );
316 fwdBtn.addEventListener("click", () =>
317     setStatus({ key: video.seekBy(5) ? "status.seekFwd" : "status.noVideoSeek" })

```

```

318     );
319     playBtn.addEventListener("click", () => {
320         const st = video.playPause();
321         setStatus({ key: st === "playing" ? "status.resumed" : st === "paused" ?
"status.paused" : "status.noVideoLoaded" });
322     });
323
324     markStartBtn.addEventListener("click", () => setStatus(a.markStart(video.now())));
325     markEndBtn.addEventListener("click", () => setStatus(a.markEnd(video.now())));
326     saveBtn.addEventListener("click", () => {
327         const res = a.saveRally();
328         if (res.ok) download(a.toCSV()); // download the full CSV on each save (per design)
329         setStatus(res);
330     });
331
332     editBtn.addEventListener("click", () => setStatus(a.editSelected(selectedN)));
333     delBtn.addEventListener("click", () => {
334         const res = a.deleteSelected(selectedN);
335         if (res.ok) selectedN = null;
336         setStatus(res);
337     });
338     undoBtn.addEventListener("click", () => setStatus(a.undoLast()));
339     refreshBtn.addEventListener("click", () => {
340         video.findActive();
341         setStatus({ key: video.hasVideo() ? "status.refreshedVideo" : "status.noVideoFound"
});
342     });
343     dlBtn.addEventListener("click", () => {
344         download(a.toCSV());
345         setStatus({ key: "status.downloaded", params: { count: a.rows.length } });
346     });
347
348     helpBtn.addEventListener("click", () => {
349         help.style.display = help.style.display === "none" ? "block" : "none";
350         render();
351     });
352     hideBtn.addEventListener("click", () => api.toggle());
353
354     // ---- dragging ----
355     let drag: { x: number; y: number; left: number; top: number } | null = null;
356     hdr.addEventListener("mousedown", (e) => {
357         const rect = card.getBoundingClientRect();
358         card.style.right = "auto";
359         card.style.left = rect.left + "px";
360         card.style.top = rect.top + "px";
361         drag = { x: e.clientX, y: e.clientY, left: rect.left, top: rect.top };
362         e.preventDefault();
363     });
364     const onMove = (e: MouseEvent) => {
365         if (!drag) return;
366         card.style.left = drag.left + (e.clientX - drag.x) + "px";
367         card.style.top = drag.top + (e.clientY - drag.y) + "px";
368     };
369     const onUp = () => {
370         drag = null;
371     };
372     window.addEventListener("mousemove", onMove);
373     window.addEventListener("mouseup", onUp);
374
375     // ---- live clock ----
376     const clock = window.setInterval(render, 333);
377
378     // ---- fullscreen re-parent (so the panel survives fullscreen video; desktop) ----
379     const onFs = () => {
380         const fe = document.fullscreenElement;

```

```

381     if (fe && !fe.contains(host)) fe.append(host);
382     else if (!fe && host.parentElement !== document.body) document.body.append(host);
383 };
384 document.addEventListener("fullscreenchange", onFs);
385
386 document.body.append(host);
387 applyI18n();
388 render();
389
390 const api: PanelHandle = {
391     toggle() {
392         host.style.display = host.style.display === "none" ? "" : "none";
393     },
394     destroy() {
395         window.clearInterval(clock);
396         window.removeEventListener("mousemove", onMove);
397         window.removeEventListener("mouseup", onUp);
398         document.removeEventListener("fullscreenchange", onFs);
399         host.remove();
400     },
401 };
402 return api;
403 }
404

```

## 12. user (2026-07-02T03:17:41.878Z)

```

1     import { browser } from "wxt/browser";
2     import { Annotator } from "../src/state/annotator";
3     import { DirectVideoHandler } from "../src/video/directVideo";
4     import { deriveIdentity, loadRows, saveRows, csvFilename } from "../src/persist/store";
5     import { mountPanel } from "../src/ui/panel";
6     import type { RuntimeMessage } from "../src/messages";
7
8     // Top-frame content script: derives the per-video identity, loads any saved rallies,
9     // wires the pure Annotator to the page's video + storage + CSV download, and mounts the
10    // panel (hidden until the toolbar icon is clicked). Cross-origin EMBEDDED players
11    // (youtube.com/embed inside a third-party page) are a later, separate handler.
12    export default defineContentScript({
13        matches: ["<all_urls>"],
14        runAt: "document_idle",
15        async main() {
16            if (window.top !== window) return; // v1: top frame only
17
18            const identity = deriveIdentity();
19            const video = new DirectVideoHandler();
20            const rows = await loadRows(identity.key);
21
22            const annotator = new Annotator({
23                rows,
24                // chrome.storage.local is the source of truth (extension-scoped). Async mirror;
25                // the in-memory annotator.rows is authoritative for the live session.
26                persist: (rs) => {
27                    void saveRows(identity.key, rs);
28                    return { ok: true };
29                },
30            });
31
32            const panel = mountPanel({
33                annotator,
34                video,
35                identity,
36                download: (csv) =>
37                    void browser.runtime.sendMessage({
38                        type: "rally-download",

```

```

39         filename: csvFilename(identity.title),
40         csv,
41     } as RuntimeMessage),
42 });
43
44     panel.toggle(); // start hidden; the toolbar icon reveals it on pages you want to
annotate
45
46     browser.runtime.onMessage.addListener((msg: RuntimeMessage) => {
47         if (msg && msg.type === "toggle-panel") panel.toggle();
48     });
49 },
50 });
51

```

### 13. user (2026-07-02T03:17:55.130Z)

C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\DESIGN.md:129:\*\*Decision.\*\* The panel UI is localized into Khelsutra's locales \*\*+ Telugu\*\* (`en, kn, hi, es, da, id, C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\DESIGN.md:133:English (LD-3 byte-compatibility is preserved across all languages). Full design + locked decisions: C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\README.md:22:- \*\*Localized into 7 languages\*\* (English, Hindi, Kannada, Telugu, Spanish, Danish, Indonesian) with a C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\README.md:23: persisted in-panel language selector ? machine-draft translations pending native review (see C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:7:// EACH supported locale, switch the panel's language, prove the UI renders in that language, C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:9:// (English) reason/sport values. Each locale's session is screen-recorded to C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:10:// e2e-results/screencasts/<locale>.webm ? the downloadable per-language proof. C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:20:const LOCALES\_DIR = path.resolve(here, "..", "src", "i18n", "locales"); C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:22:const SUPPORTED\_LOCALES = ["en", "kn", "hi", "es", "da", "id", "te"] as const; C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:23:const LOCALE\_LABELS: Record<string, string> = { C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:28:for (const l of SUPPORTED\_LOCALES) { C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:29: CATS[l] = JSON.parse(readFileSync(path.join(LOCALES\_DIR, l, "common.json"), "utf8")); C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:31:// Mirror of the runtime t(): locale -> en -> raw key, with {var} interpolation. C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:32:function tt(locale: string, key: string, vars?: Record<string, string | number>): string { C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:33: const tpl = CATS[locale]?.[key] ?? CATS.en[key] ?? key; C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:49:for (const locale of SUPPORTED\_LOCALES) { C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:50: test(`panel works and renders in \${locale} (\${LOCALE\_LABELS[locale]})`, async () => { C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:51: const T = (key: string, vars?: Record<string, string | number>) => tt(locale, key, vars); C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:53: // Fresh per-locale recording dir so a single recording is unambiguous (robust across reruns). C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:54: const ldir = path.join(VIDEO\_DIR, locale); C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:80: // Switch to this locale and PROVE the UI renders in that language. C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:81: await page.locator("select[name=language]").selectOption(locale); C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:101: // Authoritative proof: persisted with CANONICAL english reason/sport regardless of UI language. C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\extension.spec.ts:121: copyFileSync(src, path.join(SCREENCAST\_DIR, `\${locale}.webm`));



```

C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:5:  setLocale,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:6:  getLocale,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:7:  negotiateLocale,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:8:  SUPPORTED_LOCALES,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:9:  DEFAULT_LOCALE,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:10:  registeredLocales,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:13:  LOCALE_LABELS,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:27:  it("falls back
to en for an unregistered locale", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:30:  it("uses the
registered translation for a known locale", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:37: describe("locale
state + negotiation", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:39:  expect(DEFAULT_LOCALE).toBe("en");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:42:  setLocale("hi");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:43:  expect(getLocale()).toBe("hi");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:44:  setLocale("zz" as never);
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:45:  expect(getLocale()).toBe("en");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:48:  expect(negotiateLocale("hi")).toBe("hi");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:49:  expect(negotiateLocale(null, ["te-IN", "en"])).toBe("te");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:50:  expect(negotiateLocale("fr", ["pt-BR"])).toBe("en");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:51:  expect(negotiateLocale(null, [])).toBe("en");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:56:  it("has a
display label for every supported locale", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:57:    for (const l
of SUPPORTED_LOCALES) expect(LOCALE_LABELS[l]).toBeTruthy();
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:60:  it("registers
a catalog for every supported locale", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:61:    expect(new
Set(registeredLocales())).toEqual(new Set(SUPPORTED_LOCALES));
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:64:  it("key-
parity: every registered locale defines exactly the en key set", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:66:    for (const l
of registeredLocales()) {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:88: describe("CSV
output is language-invariant (values are canonical, never translated)", () => {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:89:  function
makeCsv(locale: "en" | "hi" | "te") {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:90:  setLocale(locale);
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\test\i18n.test.ts:105:  setLocale("en");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:10: import en from
"./locales/en/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:11: import kn from
"./locales/kn/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:12: import hi from
"./locales/hi/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:13: import te from
"./locales/te/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:14: import es from
"./locales/es/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:15: import da from

```

```

"/locales/da/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:16:import id from
"/locales/id/common.json";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:18:export const
SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id", "te"] as const;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:19:export type
Locale = (typeof SUPPORTED_LOCALES)[number];
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:20:export const
DEFAULT_LOCALE: Locale = "en";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:22:// Native-script
display names for the language selector.
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:23:export const
LOCALE_LABELS: Record<Locale, string> = {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:33:// Scripts that
need a bundled OFL Noto font (Latin locales render with the system stack).
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:34:export const
NON_LATIN: ReadonlySet<Locale> = new Set<Locale>(["kn", "hi", "te"]);
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:39:// machine
drafts pending native review (see each file's _meta). An unregistered locale,
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:42:const CATALOGS:
Partial<Record<Locale, Catalog>> = {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:52:export function
registerCatalog(locale: Locale, catalog: Catalog): void {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:53:
CATALOGS[locale] = catalog;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:56:let current:
Locale = DEFAULT_LOCALE;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:57:export function
getLocale(): Locale {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:60:export function
setLocale(locale: Locale): void {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:61: current =
(SUPPORTED_LOCALES as readonly string[]).includes(locale) ? locale : DEFAULT_LOCALE;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:64:function
toSupported(code?: string | null): Locale | null {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:67: return
(SUPPORTED_LOCALES as readonly string[]).includes(base) ? (base as Locale) : null;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:71:// browser's
languages, then `en`. Pure ? safe to call with no arguments outside a browser.
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:72:export function
negotiateLocale(stored?: string | null, navLangs: readonly string[] = []): Locale {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:75: for (const l
of navLangs) {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:79: return
DEFAULT_LOCALE;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:87:// t(key, vars?,
locale?) ? resolve against the locale, then en, then the raw key.
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:91: locale: Locale
= current
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:93: const tpl =
CATALOGS[locale]?.[key] ?? CATALOGS.en?.[key] ?? key;
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:98:export function
registeredLocales(): Locale[] {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:99: return
Object.keys(CATALOGS) as Locale[];
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:102:export function
catalogKeys(locale: Locale): string[] {
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\i18n\index.ts:103: return
Object.keys(CATALOGS[locale] ?? {}).filter((k) => k !== "_meta");
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\ui\panel.ts:11:import { t,
getLocale, setLocale, SUPPORTED_LOCALES, LOCALE_LABELS, type Locale } from "../i18n";
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\ui\panel.ts:18: onLocaleChange?:
(locale: Locale) => void; // optional: persist the choice (content script wires this)
C:\Users\avidu\Projects\khehsutra-guru\rally-annotator\web\src\ui\panel.ts:125: // ----
language ----

```

```

C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:126:  const langLabel
= h("label");
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:127:  const langSel =
h("select", { name: "language" }) as HTMLSelectElement;
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:128:  for (const l of
SUPPORTED_LOCALES) langSel.append(h("option", { value: l, textContent: LOCALE_LABELS[l] }));
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:129:  langSel.value =
getLocale();
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:130:
body.append(h("div", { class: "row" }, langLabel, langSel));
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:206:  // Language-
only text (static labels, option labels, placeholders, fixed buttons, help).
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:207:  // Re-applied
on mount and whenever the locale changes.
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:210:
langLabel.textContent = t("label.language");
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:242:  langSel.value
= getLocale();
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:306:
langSel.addEventListener("change", () => {
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:307:
setLocale(langSel.value as Locale);
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\ui\panel.ts:308:
deps.onLocaleChange?.(getLocale());
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\da\common.json:3:
"locale": "da",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\da\common.json:14:
"label.language": "Sprog:",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\en\common.json:2:
"_meta": { "locale": "en", "status": "source" },
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\en\common.json:12:
"label.language": "Language:",
C:\Users\avidu\Projects\khelsutra-guru\rally-
annotator\web\src\i18n\locales\en\common.json:96:[Omitted long matching line]
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\es\common.json:3:
"locale": "es",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\es\common.json:14:
"label.language": "Idioma:",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\te\common.json:3:
"locale": "te",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\te\common.json:14:
"label.language": "???:",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\hi\common.json:3:
"locale": "hi",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\hi\common.json:14:
"label.language": "????:",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:3:
"locale": "id",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:14:
"label.language": "Bahasa:",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:27:
"btn.reMarkStart": "Tandai ulang MULAI ({n})",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:28:
"btn.reMarkEnd": "Tandai ulang SELESAI ({n})",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:41:
"reason.winner": "poin langsung",
C:\Users\avidu\Projects\khelsutra-guru\rally-annotator\web\src\i18n\locales\id\common.json:67:
"status.editGuard": "Selesaikan reli saat ini ('Simpan Reli') atau hapus ('Batalkan terakhir')
sebelum mengubah yang lain ? MULAI ? SELESAI Anda yang belum disimpan akan hilang.",

```

[Showing results with pagination = limit: 120]

#### 14. user (2026-07-02T03:17:56.065Z)

3d604bc docs: sync READMEs with current state (multi-agent audit fixes) (#25)

f5ceefc docs(readme): tick live-test ? v1.7.1 verified in real VLC (incl. Indic rendering) (#24)  
a0592f6 docs(readme): refresh stale roadmap + tests lines (#23)  
ac245ce feat(vlc): complete localization ? status messages + HELP guide (v1.7.1) (#21)  
245bf54 feat(vlc): localize dialog chrome into 7 languages (v1.7) (#20)  
0a05ecf feat(web): localize panel into kn/hi/es/da/id/te + per-locale screencasts (#19)  
5ec1831 feat(web): i18n infrastructure + English catalog (keys-not-prose) (#18)  
75541ab docs: localization (i18n) design + locked decisions (#17)  
7094d76 docs(readme): use verified Khelsutra site copy + add "About Khelsutra" (#16)  
33a4348 docs: frame as Khelsutra sister repo; add design doc + CONTRIBUTING + PR template (#15)  
ad6ac9c Add rally-annotator web extension (Chrome MV3) with proof-driven tests + CI (#14)  
d5d59f2 v1.6.4: guard unsaved rallies from silent loss + flag edit mode on Mark buttons (#13)  
6653d89 v1.6.4: guard unsaved rallies from silent loss; flag edit mode on Mark buttons  
0262ed5 v1.6.3: show the version next to the plugin in VLC's Active Extensions list (#12)  
9373703 v1.6.3: show the version next to the plugin in VLC's Active Extensions list

## main...origin/main

### 15. assistant (2026-07-02T03:18:12.417Z)

Let me check background.ts to rule out locale persistence there, and confirm the E2E test doesn't cover persistence-across-reload.

### 16. user (2026-07-02T03:18:13.426Z)

```
1      import { browser } from "wxt/browser";
2      import type { RuntimeMessage } from "../src/messages";
3
4      // Background service worker: performs the CSV download (chrome.downloads is unavailable
5      // to content scripts) and routes the toolbar-icon click into a panel toggle.
6      export default defineBackground(() => {
7        browser.runtime.onMessage.addListener((msg: RuntimeMessage) => {
8          if (msg && msg.type === "rally-download") {
9            const url = "data:text/csv;charset=utf-8," + encodeURIComponent(msg.csv);
10            void browser.downloads
11              .download({ url, filename: msg.filename, saveAs: false, conflictAction:
"overwrite" })
12              .catch((e) => console.error("[rally] download failed:", e));
13          }
14        });
15
16        // No default_popup is set, so the icon click fires onClicked -> toggle the panel.
17        browser.action.onClicked.addListener((tab) => {
18          if (tab.id !== null) {
19            void browser.tabs
20              .sendMessage(tab.id, { type: "toggle-panel" } as RuntimeMessage)
21              .catch(() => {
22                /* tab has no content script (e.g. chrome:// page) */
23              });
24          }
25        });
26      });
27
```

### 17. user (2026-07-02T03:18:14.794Z)

ce7ae28 fix: add .gitattributes (force LF) so Windows clones pass the snapshot test

### 18. user (2026-07-02T03:18:48.311Z)

Structured output provided successfully