

# codex-windows / 019f2174-3a2c-7bb1-a822-f9c7a1e1ecfc

## Metadata

```
- Source: `codex-windows`  
- Kind: `codex`  
- Source file: `C:\Users\avidu\.codex\sessions\2026\07\02\rollout-2026-07-02T11-41-33-019f2174-3a2c-7bb1-a822-f9c7a1e1ecfc.jsonl`  
- SHA-256: `388785a571ef80e936aa451a238452281b651f56cbe5217edd6e7ae2057e899f`  
- Source modified: `2026-07-02T06:11:33+00:00`  
- Imported at: `2026-07-05T16:48:16+00:00`  
- cli_version: `0.142.5`  
- cwd: `C:\Users\avidu\Projects\badminton-highlight-indexer`  
- model_provider: `openai`  
- session_id: `019f2174-3a2c-7bb1-a822-f9c7a1e1ecfc`  
- source: `vscode`
```

## Transcript

### 1. user (2026-07-02T06:11:33.038Z)

Hello. Can you pls sync this repo to remote head and help in reviewing <https://github.com/avidullu/muneem/pull/80>

### 2. assistant (2026-07-02T06:11:33.038Z)

I'll start by syncing the primary repo, then look at the muneem repo and PR #80. Let me gather state in parallel.

### 3. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_call: Bash]  
description: Sync badminton-highlight-indexer to remote head  
command: echo "=== badminton remote ===" && git remote -v && echo "=== status ===" && git status -sb && echo "=== fetch+ff ===" && git fetch origin && git pull --ff-only 2>&1 | head -30  
[/external_agent_tool_call]
```

### 4. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_call: Bash]  
description: Inspect muneem repo state  
command: cd /c/Users/avidu/Projects/muneem && echo "=== muneem remote ===" && git remote -v && echo "=== status ===" && git status -sb && echo "=== recent ===" && git log --oneline -5  
[/external_agent_tool_call]
```

### 5. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_call: Bash]  
description: Fetch PR #80 metadata  
command: cd /c/Users/avidu/Projects/muneem && gh pr view 80 --json number,title,author,state,baseRefName,headRefName,additions,deletions,changedFiles,body,url,mergeable,reviewDecision 2>&1 | head -80  
[/external_agent_tool_call]
```

### 6. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_result]  
=== badminton remote ===  
origin  https://github.com/Khelsutra/badminton-highlight-indexer.git (fetch)  
origin  https://github.com/Khelsutra/badminton-highlight-indexer.git (push)  
=== status ===
```

**master...origin/master**

```
=== fetch+ff ===
From https://github.com/Khelsutra/badminton-highlight-indexer
* [new branch]      o1-p11/gemini-remote-file-gc -> origin/o1-p11/gemini-remote-file-gc
Already up to date.
[/external_agent_tool_result]
```

## 7. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_result]
=== muneem remote ===
origin https://github.com/avidullu/muneem.git (fetch)
origin https://github.com/avidullu/muneem.git (push)
=== status ===
refactor/split-cli...origin/refactor/split-cli
=== recent ===
ec091d5 refactor: split cli.py (~613 lines) into cli/ subpackage
71782fd Merge branch 'refactor/move-experimental-ingestion'
4bfbb68 Merge branch 'refactor/safe-amount-rename'
0948f14 Merge branch 'docs/code-health-report'
88c3c39 Merge branch 'docs/refresh-current-state'
[/external_agent_tool_result]
```

## 8. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_result]
{"additions":656,"author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":"Avi"},"baseRefName":"main","body":"Splits the monolithic `cli.py` (~613 lines) into a `cli/` subpackage with focused modules.\n\n### Before\n```\nsrc/muneem/cli.py  (613 lines ? all commands in one file)\n```\n\n### After\n```\nsrc/muneem/cli.py      (9 lines ? thin re-export)\nsrc/muneem/cli/\n  __init__.py        (70 lines ? app assembly, info command, registration)\n  _shared.py          (40 lines ? _ledger, BANK_DISPATCH, _version_callback)\n  ingest.py           (130 lines ? ingest + _ingest_bank_statement)\n  offers.py           (35 lines ? offers_app + list command)\n  txns.py             (75 lines ? txns_app + list command)\n  db.py               (200 lines ? db_app + all encryption lifecycle commands)\n  eval.py             (75 lines ? eval_statements + _eval_statement helper)\n```\n\n### Key design decisions\n- **Explicit registration**: Commands registered via `app.command()(fn)` instead of decorators, avoiding circular import issues\n- **`_shared.py`**: Isolates helpers (`_ledger`, `BANK_DISPATCH`) needed by both `__init__.py` and sub-modules\n- **Lazy imports**: `extract()` imported inside functions to preserve test monkeypatching\n- **Entry point unchanged**: `pyproject.toml` still points to `muneem.cli:app` ? works through the thin re-export\n\n### Verification\n- ? `ruff check .` ? clean\n- ? `ruff format --check .` ? clean\n- ? `mypy` ? 41 source files, no issues\n- ? `pytest` ? 478 passed\n- ? `muneem --version` ? works\n- ? `muneem info` ? works\n\nFixes recommendation #5 from the code-health report (PR #74). Also updates the report tracker to mark all ? high-priority items as done.", "changedFiles":9, "deletions":615, "headRefName":"refactor/split-cli", "mergeable":"MERGEABLE", "number":80, "reviewDecision":"","state":"OPEN", "title":"refactor: split cli.py (~613 lines) into cli/ subpackage", "url":"https://github.com/avidullu/muneem/pull/80"}
[/external_agent_tool_result]
```

## 9. assistant (2026-07-02T06:11:33.038Z)

Primary repo is synced (already up to date; one new remote branch fetched). Now let me sync the muneem PR branch and check CI + the diff.

## 10. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_call: Bash]
description: Sync PR branch and check CI status
command: git pull --ff-only 2>&1 | head -10 && echo "=== HEAD ===" && git log --oneline -1 && echo "=== CI checks ===" && gh pr checks 80 2>&1 | head -30
[/external_agent_tool_call]
```

### 11. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_call: Bash]
description: Show PR diff stat and project layout
command: echo "=== diff stat vs main ===" && git fetch origin main -q && git diff --stat
origin/main...HEAD && echo "" && echo "=== project files ===" && ls -la && echo "=== CLAUDE.md?
=== " && ls docs 2>/dev/null | head -20
[/external_agent_tool_call]
```

### 12. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_result]
Already up to date.
=== HEAD ===
ec091d5 refactor: split cli.py (~613 lines) into cli/ subpackage
=== CI checks ===
test (ubuntu-latest, 3.11)      pass    30s
https://github.com/avidullu/muneem/actions/runs/28185700568/job/83486855874
test (ubuntu-latest, 3.12)      pass    53s
https://github.com/avidullu/muneem/actions/runs/28185700568/job/83486855859
test (ubuntu-latest, 3.13)      pass    38s
https://github.com/avidullu/muneem/actions/runs/28185700568/job/83486855907
test (windows-latest, 3.13)     pass    1m22s
https://github.com/avidullu/muneem/actions/runs/28185700568/job/83486855881
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28185700568/job/83486856842
test (ubuntu-latest, 3.11)      pass    36s
https://github.com/avidullu/muneem/actions/runs/28185690364/job/83486823098
test (ubuntu-latest, 3.12)      pass    50s
https://github.com/avidullu/muneem/actions/runs/28185690364/job/83486823197
test (ubuntu-latest, 3.13)      pass    36s
https://github.com/avidullu/muneem/actions/runs/28185690364/job/83486823145
test (windows-latest, 3.13)     pass    2m8s
https://github.com/avidullu/muneem/actions/runs/28185690364/job/83486823122
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28185690364/job/83486823851
[/external_agent_tool_result]
```

### 13. assistant (2026-07-02T06:11:33.038Z)

```
[external_agent_tool_result]
=== diff stat vs main ===
 docs/code-health-2026-06-25.md | 15 +-
 src/muneem/cli.py               | 612 +-----
 src/muneem/cli/__init__.py      | 69 +++++
 src/muneem/cli/_shared.py       | 37 +++
 src/muneem/cli/db.py            | 206 ++++++
 src/muneem/cli/eval.py          | 83 ++++++
 src/muneem/cli/ingest.py        | 143 ++++++
 src/muneem/cli/offers.py        | 37 +++
 src/muneem/cli/txns.py          | 69 +++++
 9 files changed, 656 insertions(+), 615 deletions(-)

=== project files ===
total 149
drwxr-xr-x 1 avidu 197609    0 Jun 25 22:03 .
drwxr-xr-x 1 avidu 197609    0 Jun 25 17:33 ..
drwxr-xr-x 1 avidu 197609    0 Jun 11 00:11 .claude
-rw-r--r-- 1 avidu 197609 53248 Jun 10 22:44 .coverage
drwxr-xr-x 1 avidu 197609    0 Jun 25 22:12 .git
-rw-r--r-- 1 avidu 197609  286 May 30 23:27 .gitattributes
drwxr-xr-x 1 avidu 197609    0 Jun 10 23:14 .github
drwxr-xr-x 1 avidu 197609    0 May 30 23:27 .github
-rw-r--r-- 1 avidu 197609 1579 Jun 10 23:34 .gitignore
drwxr-xr-x 1 avidu 197609    0 Jun  2 23:10 .mypy_cache
```

```

drwxr-xr-x 1 avidu 197609      0 May 30 22:57 .pytest_cache
drwxr-xr-x 1 avidu 197609      0 May 30 22:57 .ruff_cache
drwxr-xr-x 1 avidu 197609      0 May 30 22:57 .venv
-rw-r--r-- 1 avidu 197609  4273 May 30 21:54 CLAUDE.md
-rw-r--r-- 1 avidu 197609 22509 Jun 25 22:03 DESIGN.md
-rw-r--r-- 1 avidu 197609  1184 May 31 20:41 Makefile
-rw-r--r-- 1 avidu 197609  4040 Jun 10 23:34 README.md
-rw-r--r-- 1 avidu 197609  1929 Jun 25 21:55 constraints.txt
drwxr-xr-x 1 avidu 197609      0 Jun 25 22:09 docs
-rw-r--r-- 1 avidu 197609  2578 Jun 25 22:03 pyproject.toml
drwxr-xr-x 1 avidu 197609      0 May 30 22:57 src
drwxr-xr-x 1 avidu 197609      0 Jun 10 23:14 testdata
drwxr-xr-x 1 avidu 197609      0 Jun 10 23:46 tests
drwxr-xr-x 1 avidu 197609      0 Jun 25 22:03 tools
=== CLAUDE.md? ===
CURRENT_STATE.md
DEPENDENCIES.md
ROADMAP.md
TESTING.md
code-health-2026-06-25.md
encryption-at-rest.md
feedback-antigravity-response.md
feedbackJune2026.md
ingesting-statements.md
onboarding-a-bank.md
parser-architecture.md
prior-art-email-mining.md
proposals
recovery.md
research-open-banking-india.md
schema.md
[/external_agent_tool_result]

```

#### 14. assistant (2026-07-02T06:11:33.038Z)

CI is green across all platforms (Ubuntu 3.11/3.12/3.13 + Windows 3.13), OCR skipped. This is a pure file-split refactor. Let me read the project conventions and do a careful semantic-preservation review of the diff.

#### 15. assistant (2026-07-02T06:11:33.038Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\CLAUDE.md
[/external_agent_tool_call]

```

#### 16. assistant (2026-07-02T06:11:33.039Z)

```

[external_agent_tool_result]
1      # CLAUDE.md ? muneem
2
3      You are working on muneem, a personal-finance bookkeeper that ingests financial
documents from the user's email and builds a local consolidated ledger.
4
5      ## Read these before doing anything substantive
6
7      1. [`DESIGN.md`](./DESIGN.md) ? the full design: vision, five-stage pipeline, security
posture, open decisions, recommended first slice.
8      2. [`docs/prior-art-email-mining.md`](./docs/prior-art-email-mining.md) ? what the
predecessor project (`~/Projects/Email-Mining`) tried, what worked, what to inherit, what to
drop.
9      3. [`testdata/promo-emails/README.md`](./testdata/promo-emails/README.md) ? what's in
the regression corpus and where it came from.
10
11     ## Project context

```

```

12
13     - **Single-user, personal.** This is the user's own tool for the user's own financial
data. Not a multi-tenant product. Design decisions optimize for the user's needs, not for
hypothetical others.
14     - **User location: Bangalore, India.** Expect Indian banks (HDFC, ICICI, SBI, Axis,
Kotak, etc.), Indian credit cards, Indian brokers (Zerodha, Groww, Kuvera, etc.), Indian
merchants (Swiggy, Zomato, Flipkart, Amazon.in, BigBasket, Blinkit, etc.). Password conventions
on Indian bank/CC PDFs typically derive from name + DOB or PAN + DDMM ? design accordingly.
15     - **Greenfield.** No application code exists yet. Don't assume a stack ? it hasn't been
chosen. See `DESIGN.md` § Open Decisions.
16
17     ## Standing rules (highest priority ? these override default behavior)
18
19     ### Security
20
21     This project aggregates the user's **entire financial life** into one local store. That
is an extremely high-value target.
22
23     - **Treat all statement contents as sensitive by default.** Bank balances, card numbers,
transaction lines, holdings, PII.
24     - **Never send sensitive document contents to a cloud LLM API** (OpenAI, Anthropic,
Gemini, etc.) without explicit per-document-category approval discussed with the user in the
current session. Default to local extraction (Tesseract OCR, local LLMs via Ollama,
deterministic parsers).
25     - The corpus in `testdata/promo-emails/` is **non-sensitive** (promo emails only, no
account numbers) ? safe to send to cloud LLMs if needed for development.
26     - **Never commit:** real bank/CC/investment PDFs; the parsed DB file; OAuth tokens;
`.env` files; any password rules, password lists, or example passwords; logs containing
extracted statement text.
27     - The `.gitignore` already blocks the obvious paths; do not weaken it.
28
29     ### Decisions
30
31     There are **open architectural decisions** parked for explicit human discussion (see
`DESIGN.md` § Open Decisions). **Do not silently pick** any of them by writing code that locks
in an answer. The short list:
32
33     1. Language: Go-only, Python-only, or Go-ingest + Python-parse
34     2. Password sourcing: per-sender rule template, candidate dictionary, or interactive
prompt
35     3. LLM locality per doc category (when local OCR/parsers aren't enough)
36     4. First vertical slice scope
37
38     If the user asks you to start coding without resolving these, surface the relevant open
decisions first and ask for direction.
39
40     ### Working conventions
41
42     - Ask before introducing new external services (paid APIs, cloud vendors, hosted
services).
43     - Prefer batteries-included stdlib + well-known OSS over novel dependencies.
44     - Run all OCR / LLM work **locally by default**.
45     - Statement-handling code paths should be testable on the non-sensitive `testdata/promo-
emails/` corpus where possible.
46     - Follow attribution discipline: never invent a source, a discussion that didn't happen,
or a fact you didn't verify. If you're inferring, say so.
47
48     ## Vision continuity
49
50     muneem is the successor to `~/Projects/Email-Mining`, a coupon-finder prototype the user
built earlier. Same core insight ("there's structured value in my inbox I'm forgetting ? extract
it"); broader scope (full financial picture, not just deals). The deals/coupons feature fr...
[/external_agent_tool_result]

```

```
[external_agent_tool_call: Bash]
description: Read original cli.py from main
command: echo "=== ORIGINAL cli.py (from origin/main) ===" && git show
origin/main:src/muneem/cli.py | head -650
[/external_agent_tool_call]
```

## 18. assistant (2026-07-02T06:11:33.039Z)

```
[external_agent_tool_result]
=== ORIGINAL cli.py (from origin/main) ===
"""The ``muneem`` command-line interface.

``ingest`` parses a PDF into the local store (promo, or ``--doc-type bank_statement`` with
automatic password unlock); ``offers list`` / ``txns list <bank>|all`` read back what was
found (listings tag anything not cleanly reconciled); ``eval <folder>`` reports reconcile
rates; ``db ?`` covers the encryption lifecycle (status/encrypt/rotate-key/backup/
setup-recovery/recover). ``--ocr`` adds local image OCR for codes rasterized into banners
(approximate; flagged for verification). ``fetch`` (Gmail pull) lands with Phase F.
"""
```

```
from __future__ import annotations

from contextlib import contextmanager
from pathlib import Path

import typer

from muneem import __version__
from muneem import db as dbmod
from muneem.config import load_config
from muneem.log import get_logger
from muneem.redaction import redact_filename

_log = get_logger(__name__)

app = typer.Typer(
    add_completion=False,
    help="muneem ? a local-first personal-finance bookkeeper.",
    no_args_is_help=True,
)
offers_app = typer.Typer(no_args_is_help=True, help="Work with extracted offers.")
app.add_typer(offers_app, name="offers")

txns_app = typer.Typer(no_args_is_help=True, help="Work with parsed transactions.")
app.add_typer(txns_app, name="txns")

db_app = typer.Typer(no_args_is_help=True, help="Manage the local encrypted ledger.")
app.add_typer(db_app, name="db")

@contextmanager
def _ledger(db_path: Path):
    """Open the encrypted ledger, turning an un-migrated *plaintext* file into a clean CLI
    error (pointing at ``muneem db encrypt``) rather than a raw traceback."""
    try:
        with dbmod.connect_encrypted(db_path) as conn:
            yield conn
    except dbmod.EncryptedDatabaseError as exc:
        typer.echo(str(exc), err=True)
        raise typer.Exit(1) from exc
```

## Dispatch table for supported banks (extensible as new parsers land).

```
BANK_DISPATCH = {
```

```

"axis": (dbmod.list_axis_transactions, "debit", "credit"),
"axis_cc": (dbmod.list_axis_cc_transactions, "amount", "amount"), # direction from "type"
"au": (dbmod.list_au_transactions, "debit", "credit"),
"hdfc": (dbmod.list_hdfc_transactions, "withdrawal", "deposit"),
}

def _version_callback(value: bool) -> None:
    if value:
        typer.echo(f"muneem {__version__}")
        raise typer.Exit()

@app.callback()
def main(
    version: bool = typer.Option(
        False,
        "--version",
        callback=_version_callback,
        is_eager=True,
        help="Show the muneem version and exit.",
    ),
) -> None:
    """muneem command-line interface."""

@app.command()
def info() -> None:
    """Show resolved local paths (no secrets, no sensitive data)."""
    cfg = load_config()
    present = "present" if cfg.config_file.is_file() else "absent"
    typer.echo(f"muneem {__version__}")
    typer.echo(f"config dir : {cfg.config_dir}")
    typer.echo(f"data dir : {cfg.data_dir}")
    typer.echo(f"db path : {cfg.db_path}")
    typer.echo(f"staging : {cfg.staging_dir}")
    typer.echo(f"config file: {cfg.config_file} ({present})")

def _ingest_bank_statement(pdf: Path, db_path: Path, doc_type: str, *, interactive: bool) -> None:
    """Unlock (if encrypted) ? extract ? select parser ? store reconciled transactions.

    The hybrid password unlock (cached/configured candidates ? prompt) runs *before* extraction,
    since the text needed to pick a parser is itself encrypted. The resolved password is
    forwarded
    to extraction and the parser, used in-memory only ? never logged.
    """
    from muneem import db as dbmod
    from muneem.extract import extract
    from muneem.parsers import get_parser
    from muneem.statement_unlock import resolve_password
    from muneem.unlock import is_encrypted

    password: str | None = ""
    if is_encrypted(pdf):
        password = resolve_password(pdf, interactive=interactive)
        if password is None:
            hint = " (run w..."
    [/external_agent_tool_result]

```

## 19. assistant (2026-07-02T06:11:33.039Z)

Now let me read all the new split modules to verify behavior is preserved.

## 20. assistant (2026-07-02T06:11:33.039Z)

```
[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli.py
[/external_agent_tool_call]
```

## 21. assistant (2026-07-02T06:11:33.039Z)

```
[external_agent_tool_result]
1      """The ``muneem`` command-line interface ? re-exports from the ``cli/`` subpackage.
2
3      See ``muneem/cli/`` for the module layout. The entry point (``pyproject.toml``
4      ``[project.scripts]``) still points to ``muneem.cli:app``.
5      """
6
7      from muneem.cli import app # noqa: F401
8
[/external_agent_tool_result]
```

## 22. assistant (2026-07-02T06:11:33.039Z)

```
[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\__init__.py
[/external_agent_tool_call]
```

## 23. assistant (2026-07-02T06:11:33.039Z)

```
[external_agent_tool_result]
1      """The ``muneem`` command-line interface.
2
3      Subcommands are split across focused modules: ``ingest``, ``offers``, ``txns``,
4      ``eval``, and ``db`` ? each in its own file under ``cli/``. This module assembles
5      the Typer app.
6
7      ``fetch`` (Gmail pull) lands with Phase F.
8      """
9
10     from __future__ import annotations
11
12     import typer
13
14     from muneem import __version__
15     from muneem.cli._shared import _version_callback
16     from muneem.config import load_config
17
18     app = typer.Typer(
19         add_completion=False,
20         help="muneem ? a local-first personal-finance bookkeeper.",
21         no_args_is_help=True,
22     )
23
24     # Sub-apps ? each wired in the module that defines its commands.
25     from muneem.cli.db import db_app # noqa: E402
26     from muneem.cli.offers import offers_app # noqa: E402
27     from muneem.cli.txns import txns_app # noqa: E402
28
29     app.add_typer(offers_app, name="offers")
30     app.add_typer(txns_app, name="txns")
31     app.add_typer(db_app, name="db")
32
33
34     @app.callback()
35     def main(
36         version: bool = typer.Option(
```



```

37         False,
38         "--version",
39         callback=_version_callback,
40         is_eager=True,
41         help="Show the muneem version and exit.",
42     ),
43 ) -> None:
44     """muneem command-line interface."""
45
46
47 @app.command()
48 def info() -> None:
49     """Show resolved local paths (no secrets, no sensitive data)."""
50     cfg = load_config()
51     present = "present" if cfg.config_file.is_file() else "absent"
52     typer.echo(f"muneem {__version__}")
53     typer.echo(f"config dir : {cfg.config_dir}")
54     typer.echo(f"data dir   : {cfg.data_dir}")
55     typer.echo(f"db path    : {cfg.db_path}")
56     typer.echo(f"staging   : {cfg.staging_dir}")
57     typer.echo(f"config file: {cfg.config_file} ({present})")
58
59
60 # Command registrations ? registered explicitly to avoid circular decorator imports.
61 from muneem.cli.eval import eval_statements # noqa: E402
62 from muneem.cli.ingest import ingest # noqa: E402
63
64 app.command()(ingest)
65 app.command("eval")(eval_statements)
66 # side-effects at import time. E402 is suppressed because the imports must follow
67 # the app/sub-app definitions above.
68 from muneem.cli.eval import eval_statements # noqa: E402, F401
69 from muneem.cli.ingest import ingest # noqa: E402, F401
70
[/external_agent_tool_result]

```

#### 24. assistant (2026-07-02T06:11:33.039Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\_shared.py
[/external_agent_tool_call]

```

#### 25. assistant (2026-07-02T06:11:33.039Z)

```

[external_agent_tool_result]
1     """Shared CLI utilities ? no imports from ``muneem.cli`` to avoid circularity."""
2
3     from __future__ import annotations
4
5     from contextlib import contextmanager
6     from pathlib import Path
7
8     import typer
9
10    from muneem import __version__
11    from muneem import db as dbmod
12
13
14    @contextmanager
15    def _ledger(db_path: Path):
16        """Open the encrypted ledger, turning an un-migrated plaintext file into a clean CLI
error."""
17        try:
18            with dbmod.connect_encrypted(db_path) as conn:
19                yield conn

```

```

20         except dbmod.EncryptedDatabaseError as exc:
21             typer.echo(str(exc), err=True)
22             raise typer.Exit(1) from exc
23
24
25     # Dispatch table for supported banks (extensible as new parsers land).
26     BANK_DISPATCH = {
27         "axis": (dbmod.list_axis_transactions, "debit", "credit"),
28         "axis_cc": (dbmod.list_axis_cc_transactions, "amount", "amount"),
29         "au": (dbmod.list_au_transactions, "debit", "credit"),
30         "hdfc": (dbmod.list_hdfc_transactions, "withdrawal", "deposit"),
31     }
32
33
34     def _version_callback(value: bool) -> None:
35         if value:
36             typer.echo(f"muneem {__version__}")
37             raise typer.Exit()
38
[/external_agent_tool_result]

```

## 26. assistant (2026-07-02T06:11:33.039Z)

Let me read the remaining split modules.

## 27. assistant (2026-07-02T06:11:33.039Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\ingest.py
[/external_agent_tool_call]

```

## 28. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_result]
1     """The ``ingest`` command ? parse a PDF into the local store."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6
7     import typer
8
9     from muneem.cli._shared import _ledger
10    from muneem.config import load_config
11    from muneem.log import get_logger
12
13    _log = get_logger(__name__)
14
15
16    def _ingest_bank_statement(pdf: Path, db_path: Path, doc_type: str, *, interactive:
bool) -> None:
17        """Unlock (if encrypted) ? extract ? select parser ? store reconciled
transactions."""
18        from muneem import db as dbmod
19        from muneem.extract import extract
20        from muneem.parsers import get_parser
21        from muneem.statement_unlock import resolve_password
22        from muneem.unlock import is_encrypted
23
24        password: str | None = ""
25        if is_encrypted(pdf):
26            password = resolve_password(pdf, interactive=interactive)
27            if password is None:
28                hint = " (run without --no-prompt to enter it)" if not interactive else ""

```

```

29         typer.echo(f"Could not unlock {pdf.name}: no working password{hint}.",
err=True)
30         raise typer.Exit(1)
31
32     ex = extract(pdf, password=password or "")
33     parser = get_parser(ex.text)
34     if parser is None:
35         typer.echo(f"No parser recognizes {pdf.name} as a supported bank statement.",
err=True)
36         raise typer.Exit(1)
37
38     with _ledger(db_path) as conn:
39         dbmod.init_db(conn)
40         existing = dbmod.get_document_by_sha(conn, ex.sha256)
41         if existing is not None and existing["status"] == "reconciled":
42             typer.echo(f"already ingested (doc {existing['id']}): {pdf.name}")
43             return
44         if existing is not None:
45             doc_id = int(existing["id"])
46             dbmod.clear_document_rows(conn, doc_id)
47             typer.echo(
48                 f"re-parsing previously {existing['status']} document (doc {doc_id}):
{pdf.name}"
49             )
50         else:
51             doc_id = dbmod.insert_document(
52                 conn,
53                 source="file",
54                 external_id=pdf.name,
55                 doc_type=doc_type,
56                 sha256=ex.sha256,
57                 path=str(pdf.resolve()),
58                 status="parsed",
59             )
60             count = parser.parse_and_insert(pdf, conn, doc_id, password=password)
61             doc = dbmod.get_document_by_sha(conn, ex.sha256)
62             status = doc["status"] if doc else "parsed"
63
64         typer.echo(
65             f"ingested {pdf.name} (doc {doc_id}); parsed {count} transaction(s) "
66             f"via {parser.__class__.__name__} [{status}]"
67         )
68
69
70     def ingest(
71         pdf: Path = typer.Argument(
72             ..., exists=True, dir_okay=False, readable=True, help="Path to a PDF to ingest."
73         ),
74         doc_type: str = typer.Option("promo", help="Document category."),
75         db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
dir)."),
76         ocr: bool = typer.Option(
77             False, "--ocr", help="Also OCR images locally (Tesseract) for codes in banners."
78         ),
79         no_prompt: bool = typer.Option(
80             False,
81             "--no-prompt",
82             help="Never prompt for a statement password; use only cached/configured
candidates.",
83         ),
84     ) -> None:
85         """Store a PDF's offers (promo) or transactions (bank_statement) in the local DB."""
86         from muneem import db as dbmod
87         from muneem.extract import extract
88         from muneem.offers import extract_offer

```

```

89
90     db_path = db or load_config().db_path
91
92     if doc_type == "bank_statement":
93         _ingest_bank_statement(pdf, db_path, doc_type, interactive=not no_prompt)
94         return
95
96     ex = extract(pdf)
97     text_fields = extract_offer(ex.text)
98     found: list[tuple[str, str]] = [(c, "text") for c in text_fields.codes]
99     expiry_raw, expiry_type = text_fields.expiry_raw, text_fields.expiry_typ...
[/external_agent_tool_result]

```

## 29. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\eval.py
[/external_agent_tool_call]

```

## 30. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_result]
1     """The ``eval`` command ? evaluate parsers against a folder of statements."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6
7     import typer
8
9     from muneem import db as dbmod
10    from muneem.extract import extract
11    from muneem.log import get_logger
12    from muneem.parsers import get_parser
13    from muneem.redaction import redact_filename
14    from muneem.statement_unlock import resolve_password
15    from muneem.unlock import is_encrypted
16
17    _log = get_logger(__name__)
18
19
20    def _eval_statement(pdf: Path, *, interactive: bool) -> tuple[str, int, str | None]:
21        """Run one statement through the full parse pipeline into an in-memory DB.
22
23        Returns ``(outcome, row_count, parser_name)`` where ``outcome`` is the document
status
24        (``reconciled`` / ``unreconciled``) or a failure tag (``locked`` / ``no-parser`` /
``error``).
25        """
26        password = ""
27        if is_encrypted(pdf):
28            password = resolve_password(pdf, interactive=interactive) or ""
29            if not password:
30                return ("locked", 0, None)
31        try:
32            ex = extract(pdf, password=password)
33            parser = get_parser(ex.text)
34        except Exception as exc:
35            _log.warning(
36                "eval: extract/route failed for %s (%s)", redact_filename(pdf),
type(exc).__name__
37            )
38            return ("error", 0, None)
39        if parser is None:
40            return ("no-parser", 0, None)

```

```

41     name = parser.__class__.__name__
42     try:
43         with dbmod.connect(":memory:") as conn:
44             dbmod.init_db(conn)
45             doc_id = dbmod.insert_document(
46                 conn, source="file", external_id=pdf.name, sha256=ex.sha256,
status="parsed"
47             )
48             count = parser.parse_and_insert(pdf, conn, doc_id, password=password)
49             doc = dbmod.get_document_by_sha(conn, ex.sha256)
50             status = doc["status"] if doc else "parsed"
51     except Exception as exc:
52         _log.warning(
53             "eval: parse/store failed for %s (%s)", redact_filename(pdf),
type(exc).__name__
54         )
55         return ("error", 0, name)
56     return (status, count, name)
57
58
59 def eval_statements(
60     folder: Path = typer.Argument(
61         ...,
62         exists=True,
63         file_okay=False,
64         readable=True,
65         help="A LOCAL folder of statement PDFs to evaluate.",
66     ),
67     prompt: bool = typer.Option(
68         False,
69         "--prompt/--no-prompt",
70         help="Prompt for a password when cached/configured candidates don't unlock a
file.",
71     ),
72 ) -> None:
73     """Evaluate the parsers against a folder of statements and report the reconcile
rate."""
74     pdfs = sorted(folder.glob("*.pdf"))
75     if not pdfs:
76         typer.echo(f"no .pdf files in {folder}")
77         return
78     reconciled = 0
79     for pdf in pdfs:
80         outcome, count, name = _eval_statement(pdf, interactive=prompt)
81         reconciled += outcome == "reconciled"
82         typer.echo(f" {outcome:12} {count:4d} row(s) {name or '?':20} {pdf.name}")
83     typer.echo(f"\n{reconciled}/{len(pdfs)} reconciled")
84
[/external_agent_tool_result]

```

### 31. assistant (2026-07-02T06:11:33.040Z)

```

[/external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\db.py
[/external_agent_tool_call]

```

### 32. assistant (2026-07-02T06:11:33.040Z)

```

[/external_agent_tool_result]
1     """The ``db`` subcommand group ? ledger encryption lifecycle."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6

```

```

7     import typer
8
9     from muneem import db as dbmod
10    from muneem.config import load_config
11
12    db_app = typer.Typer(no_args_is_help=True, help="Manage the local encrypted ledger.")
13
14
15    def _require_encrypted_ledger(db_path: Path) -> str:
16        """Return the ledger's keychain key, or exit with a clear message if it can't be
17        used."""
18        from muneem.db_key import peek_key
19
20        if not Path(db_path).exists() or dbmod.is_plaintext_sqlite(db_path):
21            typer.echo("no encrypted ledger here (run 'muneem db encrypt' first).",
22            err=True)
23            raise typer.Exit(1)
24            key = peek_key()
25            if not key:
26                typer.echo("no encryption key in the keychain for this ledger.", err=True)
27                raise typer.Exit(1)
28            return key
29
30    @db_app.command("status")
31    def db_status(
32        db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
33        dir)."),
34    ) -> None:
35        """Show the ledger's encryption state (no statement data is read or printed)."""
36        from muneem.db_key import peek_key, peek_pending_key
37
38        db_path = db or load_config().db_path
39        key_state = "present in keychain" if peek_key() else "not yet minted"
40        if not Path(db_path).exists():
41            typer.echo(f"ledger : {db_path} (does not exist yet)")
42            typer.echo(f"key      : {key_state}")
43            return
44        if dbmod.is_plaintext_sqlite(db_path):
45            state = "PLAINTEXT ? run 'muneem db encrypt' to harden it"
46        else:
47            state = "encrypted (SQLCipher)"
48            typer.echo(f"ledger : {db_path}")
49            typer.echo(f"state  : {state}")
50            typer.echo(f"key    : {key_state}")
51            if peek_pending_key():
52                typer.echo(
53                    "pending: a staged rotation key is present (an interrupted 'db rotate-key'?)
54                    ? "
55                    "the next ledger open reconciles it automatically."
56                )
57
58    @db_app.command("encrypt")
59    def db_encrypt(
60        db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
61        dir)."),
62    ) -> None:
63        """Migrate an existing *plaintext* ledger to an encrypted one (SQLCipher), in
64        place."""
65        from muneem.db_key import get_or_create_key
66
67        db_path = db or load_config().db_path
68        if not Path(db_path).exists():
69            typer.echo(

```

```

66         f"nothing to encrypt: {db_path} does not exist (a new ledger is born
encrypted)."
67     )
68     return
69     if not dbmod.is_plaintext_sqlite(db_path):
70         typer.echo(
71             f"{Path(db_path).name} is already encrypted (or not a SQLite file); nothing
to do."
72         )
73     return
74     n = dbmod.encrypt_database(db_path, get_or_create_key())
75     typer.echo(
76         f"encrypted {Path(db_path).name}: {n} table(s) migrated. A plaintext backup
remains at "
77         f"{Path(db_path).name}.plaintext.bak ? verify, then securely delete it."
78     )
79
80
81     @db_app.command("rotate-key")
82     def db_rotate_key(
83         db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
dir)."),
84     ) -> None:
85         """Rotate the ledger's encryption key (SQLCipher rekey) and update the keychain."""
86         from muneem import db_key
87         from muneem.errors import KeychainError
88
89         db_path = db or load_config().db_path
90         current = _require_encrypted_ledger(db_path)
91         fresh = db_key.new_key()
92         db_key.set_pending_key(fresh)
93         try:
94             dbmod.rekey_database(db_path, current, fresh)
95         except Exception as exc:
96             if dbmod.key_opens_database(db_path, fresh):
97                 pass
98             elif dbmod.key_opens_database(db_path, current):
99                 db_key.clear_pending_key()
100                 typer.echo(
101                     f"key rotation failed; the ledger is unchanged (still under the existing
ke..."
102
[/external_agent_tool_result]

```

### 33. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\offers.py
[/external_agent_tool_call]

```

### 34. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_result]
1     """The ``offers`` subcommand group."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6
7     import typer
8
9     from muneem import db as dbmod
10    from muneem.cli._shared import _ledger
11    from muneem.config import load_config
12
13    offers_app = typer.Typer(no_args_is_help=True, help="Work with extracted offers.")

```

```

14
15
16     @offers_app.command("list")
17     def offers_list(
18         db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
dir)."),
19     ) -> None:
20         """List extracted offers."""
21         db_path = db or load_config().db_path
22         if not Path(db_path).exists():
23             typer.echo("no offers yet (database not created).")
24             return
25
26         with _ledger(db_path) as conn:
27             dbmod.init_db(conn)
28             rows = dbmod.list_offers(conn)
29
30         if not rows:
31             typer.echo("no offers found.")
32             return
33         for row in rows:
34             who = row["merchant"] or row["external_id"] or "?"
35             when = f" ? expires {row['expiry_raw']}" if row["expiry_raw"] else ""
36             tag = " [ocr ? verify]" if row["source"] == "ocr" else ""
37             typer.echo(f"[{row['id']}] {who}: {row['promo_code']}{when}{tag}")
38
[/external_agent_tool_result]

```

### 35. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\txns.py
[/external_agent_tool_call]

```

### 36. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_result]
1     """The ``txns`` subcommand group."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6
7     import typer
8
9     from muneem import db as dbmod
10    from muneem.cli._shared import BANK_DISPATCH, _ledger
11    from muneem.config import load_config
12
13    txns_app = typer.Typer(no_args_is_help=True, help="Work with parsed transactions.")
14
15
16    @txns_app.command("list")
17    def txns_list(
18        bank: str = typer.Argument(
19            ..., help="Which bank to list (e.g. hdfc, axis) ? or 'all' for the cross-bank
view."
20        ),
21        db: Path | None = typer.Option(None, help="SQLite path (defaults to the local data
dir)."),
22        limit: int = typer.Option(50, help="Max number of transactions to show."),
23    ) -> None:
24        """List parsed transactions for one bank, or across all banks via the serving
view."""
25        db_path = db or load_config().db_path

```



```

26         if not Path(db_path).exists():
27             typer.echo("database not created yet.")
28             return
29
30     bank = bank.lower()
31     if bank == "all":
32         with _ledger(db_path) as conn:
33             dbmod.init_db(conn)
34             rows = dbmod.list_all_transactions(conn, limit=limit)
35         if not rows:
36             typer.echo("no transactions found.")
37             return
38         for row in rows:
39             amount = f"+{row['credit']}" if row["credit"] else f"-{row['debit']}"
40             part = (row["particulars"] or "")[:40]
41             verdict = row["confidence"] or "?"
42             typer.echo(
43                 f"[{row['bank']}]:{row['account_number']} {row['txn_date']} : "
44                 f"{part:<40} | {amount:>10} [{verdict}]"
45             )
46         return
47
48     if bank not in BANK_DISPATCH:
49         typer.echo(f"Unknown bank: {bank}", err=True)
50         return
51
52     list_fn, neg_key, pos_key = BANK_DISPATCH[bank]
53     with _ledger(db_path) as conn:
54         dbmod.init_db(conn)
55         rows = list_fn(conn, limit=limit)
56
57     if not rows:
58         typer.echo(f"no {bank} transactions found.")
59         return
60     for row in rows:
61         if bank == "axis_cc":
62             sign = "+" if row["type"] == "Cr" else "-"
63             amount = f"{sign}{row['amount']}"
64         else:
65             amount = f"+{row[pos_key]}" if row[pos_key] else f"-{row[neg_key]}"
66             part = (row["particulars"] or "")[:50]
67             status = row["doc_status"]
68             tag = "" if status == "reconciled" else f" [{status}]"
69             typer.echo(f"[{row['account_number']} {row['txn_date']} : {part:<50} |
{amount:>10}{tag}")
70
[/external_agent_tool_result]

```

### 37. assistant (2026-07-02T06:11:33.040Z)

All the `db`/`offers`/`txns` modules are faithful to the original. I found two things worth checking. Let me verify how the tests monkeypatch `extract` ? because `eval.py` hoisted those imports to module level while `ingest.py` kept them lazy, and the PR explicitly claims lazy imports were preserved for monkeypatching.

### 38. assistant (2026-07-02T06:11:33.040Z)

```

[external_agent_tool_call: Bash]
description: Find how tests patch extract/parser
command: echo "=== monkeypatch of extract / get_parser in tests ===" && grep -rn
"monkeypatch\|setattr\|patch(" tests/ | grep -iE
"extract|get_parser|cli\.|resolve_password|is_encrypted" | head -40
[/external_agent_tool_call]

```

### 39. assistant (2026-07-02T06:11:33.040Z)

```
[external_agent_tool_call: Bash]
description: Inspect eval test patch targets
command: echo "=== eval-related tests ===" && ls tests/ | grep -i eval && echo "--- patch
targets in eval tests ---" && grep -rn "patch\|monkeypatch\|setattr" tests/*eval* 2>/dev/null |
head -40
[/external_agent_tool_call]
```

### 40. assistant (2026-07-02T06:11:33.040Z)

```
[external_agent_tool_result]
=== monkeypatch of extract / get_parser in tests ===
tests/test_cli.py:24:def test_ingest_bank_statement_unlocks_and_passes_password(tmp_path,
monkeypatch):
tests/test_cli.py:30:     monkeypatch.setattr("muneem.unlock.is_encrypted", lambda p: True)
tests/test_cli.py:31:     monkeypatch.setattr(
tests/test_cli.py:39:     monkeypatch.setattr("muneem.extract.extract", fake_extract)
tests/test_cli.py:46:     monkeypatch.setattr("muneem.parsers.get_parser", lambda text:
FakeParser())
tests/test_cli.py:56:def test_quarantined_document_can_be_reingested_after_parser_fix(tmp_path,
monkeypatch):
tests/test_cli.py:65:     monkeypatch.setattr("muneem.unlock.is_encrypted", lambda p: False)
tests/test_cli.py:66:     monkeypatch.setattr(
tests/test_cli.py:100:     monkeypatch.setattr("muneem.parsers.get_parser", lambda text:
BrokenParser())
tests/test_cli.py:105:     monkeypatch.setattr("muneem.parsers.get_parser", lambda text:
FixedParser())
tests/test_cli.py:150:def test_ingest_bank_statement_unlock_failure_exits_nonzero(tmp_path,
monkeypatch):
tests/test_cli.py:153:     monkeypatch.setattr("muneem.unlock.is_encrypted", lambda p: True)
tests/test_cli.py:154:     monkeypatch.setattr(
Binary file tests/__pycache__/test_cli.cpython-313-pytest-9.0.3.pyc matches
[/external_agent_tool_result]
```

### 41. assistant (2026-07-02T06:11:33.040Z)

```
[external_agent_tool_result]
=== eval-related tests ===
test_eval_cli.py
--- patch targets in eval tests ---
[/external_agent_tool_result]
```

### 42. assistant (2026-07-02T06:11:33.040Z)

The ingest tests patch `muneem.extract.extract` (the source module) ? which works with `ingest.py`'s lazy imports. Let me check how the eval tests patch, since `eval.py` now binds those names at module level.

### 43. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\tests\test_eval_cli.py
[/external_agent_tool_call]
```

### 44. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_result]
1      """Tests for `muneem eval` ? the seed?golden onboarding harness.
2
3      Runs the CLI against a folder of *synthetic* statements (no secrets, no real data) and
checks the
4      reconcile-rate report. Reuses the born-digital fixtures from the regression suite.
5      """
```

```

6
7     from typer.testing import CliRunner
8
9     from muneem.cli import app
10    from test_regression_synth import _au_savings_pdf, _hdfc_pdf
11
12    runner = CliRunner()
13
14
15    def test_eval_reports_reconcile_rate(tmp_path):
16        _hdfc_pdf(tmp_path / "hdfc.pdf")
17        _au_savings_pdf(tmp_path / "au.pdf")
18        result = runner.invoke(app, ["eval", str(tmp_path)])
19        assert result.exit_code == 0, result.output
20        assert "2/2 reconciled" in result.output
21        assert "reconciled" in result.output # per-file outcome line
22
23
24    def test_eval_empty_folder(tmp_path):
25        result = runner.invoke(app, ["eval", str(tmp_path)])
26        assert result.exit_code == 0
27        assert "no .pdf files" in result.output
28
[/external_agent_tool_result]

```

#### 45. assistant (2026-07-02T06:11:33.041Z)

The eval test uses real synthetic PDFs and does **not** monkeypatch `extract` at all ? so `eval.py`'s module-level imports are safe for the current suite. Now let me check the docs change and confirm the full command surface is intact.

#### 46. assistant (2026-07-02T06:11:33.041Z)

```

[external_agent_tool_call: Bash]
description: Show docs diff and introspect command tree
command: echo "=== docs/code-health diff ===" && git diff origin/main...HEAD -- docs/code-
health-2026-06-25.md && echo "" && echo "=== registered command surface (live introspection)
=== " && python -c "
from muneem.cli import app
import typer
def names(t):
    cmds = [c.name or (c.callback.__name__ if c.callback else '?') for c in
t.registered_commands]
    grps = [(g.name, names(g.typer_instance)) for g in t.registered_groups]
    return cmds, grps
print('top-level commands:', names(app)[0])
print('groups:', names(app)[1])
" 2>&1 | head -30
[/external_agent_tool_call]

```

#### 47. assistant (2026-07-02T06:11:33.041Z)

```

[external_agent_tool_result]
=== docs/code-health diff ===

=== registered command surface (live introspection) ===
Traceback (most recent call last):
  File "<string>", line 2, in <module>
    from muneem.cli import app
ModuleNotFoundError: No module named 'muneem'
[/external_agent_tool_result]

```

#### 48. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_call: Bash]
description: Show docs code-health diff two-dot
command: echo "=== docs diff (two-dot) ===" && git diff origin/main HEAD -- docs/code-
health-2026-06-25.md | head -60
[/external_agent_tool_call]
```

#### 49. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_result]
=== docs diff (two-dot) ===
[/external_agent_tool_result]
```

#### 50. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_call: Bash]
description: Introspect command tree via venv python
command: VPY=".venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=".venv/bin/python"; echo "using
$VPY"; "$VPY" -c "
from muneem.cli import app
def dump(t, prefix=''):
    for c in t.registered_commands:
        print(prefix + (c.name or c.callback.__name__))
    for g in t.registered_groups:
        print(prefix + '['+g.name+']')
        dump(g.typer_instance, prefix+' ')
dump(app)
" 2>&1 | head -40
[/external_agent_tool_call]
```

#### 51. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_result]
using .venv/Scripts/python.exe
info
ingest
eval
[offers]
    list
[txns]
    list
[db]
    status
    encrypt
    rotate-key
    backup
    setup-recovery
    recover
[/external_agent_tool_result]
```

#### 52. assistant (2026-07-02T06:11:33.041Z)

Command tree is fully intact ? all 12 commands present (only cosmetic change: `ingest`/`eval` registration order swapped vs the original). Let me grab the docs change directly from the PR since the local diff base is muddled by main having moved.

#### 53. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_call: Bash]
description: Show the code-health doc change from the PR
command: gh pr diff 80 -- 2>/dev/null | sed -n '/code-health/,/^diff --git/p' | head -50
[/external_agent_tool_call]
```

#### 54. assistant (2026-07-02T06:11:33.041Z)

```
[external_agent_tool_result]
diff --git a/docs/code-health-2026-06-25.md b/docs/code-health-2026-06-25.md
index 5d1e236..1ad44c0 100644
--- a/docs/code-health-2026-06-25.md
+++ b/docs/code-health-2026-06-25.md
@@ -205,15 +205,16 @@ This is the project's strongest dimension. Every DESIGN.md security rule
has a c
```

### ## 9. Prioritized Recommendations

```
-### ? High priority (do now, high impact, low effort)
+> **Progress (2026-06-25):** All 4 ? high-priority items + 1 CI fix completed (PRs #74?#79).
+> Now working on ? medium-priority items.

-1. **Refresh `CURRENT_STATE.md`** ? it's the first doc a contributor reads. Update the "Next
Steps" section to reflect actual current state (post #50?#68 hardening). Remove or update "Do
now" items that are already done.
+### ? High priority (do now, high impact, low effort) ? ? ALL DONE

-2. **Fix DESIGN.md § 8.3 contradiction** ? the "Still parked" sentence contradicts the resolved
block directly below it. Remove the stale line.
-
-3. **Move IMAP/Outlook stubs out of the main source tree** ? create
`src/muneem/ingestion/experimental/` and move `imap.py` and `outlook.py` there. Update
`ingestion/__init__.py` to not export them. This keeps `from muneem.ingestion import ...` honest
about what's supported.
-
-4. **Resolve `safe_amount()` vs `parse_amount()`** ? rename `safe_amount` to `safe_flow_amount`
(or `parse_flow_amount`) and add a deprecation path. The current naming is actively misleading
for balance columns. Add a test that verifies `parse_amount("0.00") == 0.0` (should already
exist) and `safe_amount("0.00") is None` (document the divergence explicitly).
+1. ? **Refresh `CURRENT_STATE.md`** ? Done (PR #76). Updated date, marked re-verify + in-
flight-PR-review as done, linked this report.
+2. ? **Fix DESIGN.md § 8.3 contradiction** ? Done (PR #75). "Items 8.3 and 8.5 remain open" ?
"8.3 is resolved; 8.5 remains open."
+3. ? **Move IMAP/Outlook stubs out of the main source tree** ? Done (PR #77). Moved to
`ingestion/experimental/`, removed from public API, narrowed mypy override, added `assert`
guards in `gmail.py`.
+4. ? **Resolve `safe_amount()` vs `parse_amount()`** ? Done (PR #78). Renamed to
`safe_flow_amount()` with deprecation shim. 4 new tests documenting the zero-divergence.
+5. ? ***(Bonus) Fix CI ? OS-agnostic constraints + ruff errors** ? Done (PR #79). Removed `-c
constraints.txt` from CI; fixed pre-existing `E501` errors in `tools/evaluate_odl.py` that were
breaking all PRs.
```

```
### ? Medium priority (do soon, moderate effort)
```

```
diff --git a/src/muneem/cli.py b/src/muneem/cli.py
[/external_agent_tool_result]
```

## 55. assistant (2026-07-02T06:11:33.041Z)

I've completed the sync and a full review. Here's the summary.

### Sync

```
- **`badminton-highlight-indexer`** (primary): already up to date with `origin/master`; fetched
one new remote branch (`o1-p11/gemini-remote-file-gc`). Working tree clean.
- **`muneem`**: PR branch `refactor/split-cli` is checked out locally and already at
`origin/refactor/split-cli` (`ec091d5`). Up to date.
```

## Review of [muneem#80](https://github.com/avidullu/muneem/pull/80) ? split `cli.py` into a `cli` subpackage

**\*\*Verdict:** a faithful, behavior-preserving split. CI is green across all platforms. One small cleanup I'd want before merge, plus a consistency nit.\*\*

I confirmed the split is semantically faithful by diffing the original `cli.py` (from `origin/main`) against each new module `_shared.py`, `ingest.py`, `eval.py`, `db.py`, `offers.py`, `txns.py` all carry the original command bodies verbatim. Live introspection confirms all 12 commands are still registered (`info`, `ingest`, `eval`, `offers list`, `txns list`, `db {status,encrypt,rotate-key,backup,setup-recovery,recover}`), and the entry point is unchanged (`muneem.cli:app` resolves through the thin re-export). I relied on the **green CI** (Ubuntu 3.11/3.12/3.13 + Windows 3.13, 478 tests, ruff + mypy clean) for the test/lint/type gates rather than re-running them.

## Findings

**\*\*1.** Dead duplicate imports + an orphaned comment ? `src/muneem/cli/__init__.py:66-69` (should fix)\*\*

```
```python
60 # Command registrations ? registered explicitly to avoid circular decorator imports.
61 from muneem.cli.eval import eval_statements # noqa: E402
62 from muneem.cli.ingest import ingest        # noqa: E402
63
64 app.command()(ingest)
65 app.command("eval")(eval_statements)
66 # side-effects at import time. E402 is suppressed because the imports must follow
67 # the app/sub-app definitions above.
68 from muneem.cli.eval import eval_statements # noqa: E402, F401 ? dead
69 from muneem.cli.ingest import ingest        # noqa: E402, F401 ? dead
```
```

Lines 68?69 re-import names already imported (61?62) and already used (64?65), so they're pure no-ops marked `# noqa: F401`. The comment on 66?67 reads mid-sentence ("side-effects at import time?") ? its opening was clearly deleted in a botched edit. **\*\*Ruff won't catch this\*\*** (F811 doesn't fire because the first binding `*is*` used before the redefinition, and F401 is suppressed), so it slipped past green CI. Functionally harmless, but it's dead code in a PR whose entire point is a clean split. Fix = delete lines 66?69.

**\*\*2.** `eval.py` breaks the stated "lazy imports" rule ? `src/muneem/cli/eval.py:9-15` (consistency nit)\*\*

The PR description lists **"Lazy imports: `extract()` imported inside functions to preserve test monkeypatching"** as a key design decision, and `ingest.py` honors it (imports stay inside the functions). But `eval.py` hoists `extract`, `get_parser`, `resolve_password`, `is_encrypted` to **\*\*module level\*\***. It's safe *today* ? `test_eval_cli.py` runs real synthetic PDFs and never monkeypatches `extract` ? but it's a latent trap: an eval test that later patches `muneem.extract.extract` (the way `test_cli.py:39` does for `ingest`) would silently have no effect. Either make eval lazy for consistency, or leave a note that eval intentionally diverges.

**\*\*3.** Cosmetic:\*\* registration order swapped `info, eval, ingest` ? `info, ingest, eval`, so `--help` lists them in a different order. No functional impact.

**\*\*Docs:\*\*** the `code-health-2026-06-25.md` change is a benign tracker update (flips the 4 ? items to ? with PR refs) ? accurate, non-functional.

## Recommendation

Clean up **\*\*#1\*\*** (4-line deletion; optionally address #2), then it's good to merge ? the split itself is correct and CI is already green. I have **\*\*not\*\*** posted an LGTM on the PR yet given the dead-code finding.

Want me to push the #1 cleanup (and optionally make #2's imports lazy) to the branch, or post these as review comments on the PR?

### 56. user (2026-07-02T06:11:33.041Z)

That PR was merged by mistake, pls do a review and post the comments on the same PR and the author will work on them in the next PR

### 57. assistant (2026-07-02T06:11:33.041Z)

Understood ? I'll do a deeper adversarial review pass and post the findings as comments on

[#80](https://github.com/avidullu/muneem/pull/80). First, let me reconcile the merge state and pin a stable reference to the pre-split original for comparison.

**58. assistant (2026-07-02T06:11:33.041Z)**

```
[external_agent_tool_call: Bash]
description: Confirm merge state and pin original ref
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q && echo "=== branches
containing ec091d5 ===" && git branch -r --contains ec091d5 && echo "=== is ec091d5 a merge?
parents ===" && git rev-list --parents -n 1 ec091d5 && echo "=== original cli.py line count at
ec091d5~1 ===" && git show ec091d5~1:src/muneem/cli.py | wc -l && echo "=== new cli.py line
count at ec091d5 ===" && git show ec091d5:src/muneem/cli.py | wc -l && echo "=== origin/main
HEAD ===" && git log --oneline -3 origin/main
[/external_agent_tool_call]
```

**59. assistant (2026-07-02T06:11:33.041Z)**

```
[external_agent_tool_result]
=== branches containing ec091d5 ===
  origin/HEAD -> origin/main
  origin/main
  origin/refactor/split-cli
=== is ec091d5 a merge? parents ===
ec091d5886d27a0541d3d456ce091cf899ae4233 71782fd2baf4805df47e8966decff809767329f8
=== original cli.py line count at ec091d5~1 ===
611
=== new cli.py line count at ec091d5 ===
7
=== origin/main HEAD ===
ec091d5 refactor: split cli.py (~613 lines) into cli/ subpackage
71782fd Merge branch 'refactor/move-experimental-ingestion'
4bfbb68 Merge branch 'refactor/safe-amount-rename'
[/external_agent_tool_result]
```

**60. assistant (2026-07-02T06:11:33.041Z)**

Confirmed: the PR was merged into `main` (now `origin/main` HEAD `ec091d5`, single-parent), so the on-disk files are the merged content and `71782fd:src/muneem/cli.py` is the stable pre-split original (611 lines).

Since ultracode is on, I'll run an adversarial multi-dimension review workflow ? independent reviewers per lens, each finding verified by a skeptic, plus a completeness critic ? so what I post is exhaustive and high-confidence.

**61. user (2026-07-02T06:11:33.042Z)**

[Request interrupted by user]

**62. user (2026-07-02T06:11:33.042Z)**

I guess since this is a refactor then just post your comments and ask them to be fixed along with the next PR

**63. assistant (2026-07-02T06:11:33.042Z)**

Got it ? ultracode off, skip the workflow. I already have the review; I'll post the findings as a consolidated follow-up comment on the merged PR. Let me write the comment body and post it.

**64. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr80-review.md
[/external_agent_tool_call]
```

**65. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr80-review.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

**66. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_call: Bash]
description: Post review comment on PR #80
command: cd /c/Users/avidu/Projects/muneem && gh pr comment 80 --repo avidullu/muneem --body-
file "C:\Users\avidu\AppData\Local\Temp\pr80-review.md" 2>&1
[/external_agent_tool_call]
```

**67. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/80#issuecomment-4802089651
[/external_agent_tool_result]
```

**68. assistant (2026-07-02T06:11:33.042Z)**

Posted. Comment is live: [#80  
(comment)](<https://github.com/avidullu/muneem/pull/80#issuecomment-4802089651>).

**69. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_call: Bash]
description: Remove temp comment file
command: rm -f "C:\Users\avidu\AppData\Local\Temp\pr80-review.md" 2>/dev/null; echo "cleaned up"
[/external_agent_tool_call]
```

**70. assistant (2026-07-02T06:11:33.042Z)**

```
[external_agent_tool_result]
cleaned up
[/external_agent_tool_result]
```

**71. assistant (2026-07-02T06:11:33.042Z)**

Done. I posted a consolidated post-merge review on  
[muneem#80](<https://github.com/avidullu/muneem/pull/80#issuecomment-4802089651>) for the author  
to fold into the next PR.

**\*\*What it says\*\*** ? the split is faithful (every command body verbatim, all 12 commands  
registered, entry point intact, CI was green), with three non-blocking follow-ups:

1. **\*\*\*? should-fix\*\*** ? dead duplicate imports + an orphaned mid-sentence comment in  
`cli/\_\_init\_\_.py:66-69` (ruff can't catch it; delete those 4 lines).
2. **\*\*\*? nit\*\*** ? `cli/eval.py` hoists `extract`/`get\_parser`/etc. to module level, breaking the  
PR's own stated "lazy imports for monkeypatching" rule that `ingest.py` follows; safe today but  
a latent test trap.
3. **\*\*\*? cosmetic\*\*** ? `--help` command order shifted (`info, eval, ingest` ? `info, ingest,  
eval`).

I also offered to send a one-line PR for #1 if that's easier than carrying it.

Side note for completeness: the merge landed on `main` as `ec091d5`, and your local `muneem`  
checkout is on `refactor/split-cli` pointing at that same commit ? so the branch is now fully  
merged and safe to delete locally/remotely whenever you like.

**72. user (2026-07-02T06:11:33.042Z)**



can you keep polling for the PRs on the muneem repo and review it

**73. user (2026-07-02T06:11:33.042Z)**

[Request interrupted by user]

**74. user (2026-07-02T06:11:33.042Z)**

can you review #81

**75. assistant (2026-07-02T06:11:33.043Z)**

Let me pull the muneem repo and gather PR #81's metadata, CI status, and diff.

**76. assistant (2026-07-02T06:11:33.043Z)**

```
[external_agent_tool_call: Bash]
description: Fetch PR #81 metadata
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q && gh pr view 81 --repo
avidullu/muneem --json number,title,author,state,baseRefName,headRefName,additions,deletions,cha
ngedFiles,body,url,mergeable,reviewDecision,isDraft 2>&1
[/external_agent_tool_call]
```

**77. assistant (2026-07-02T06:11:33.043Z)**

```
[external_agent_tool_call: Bash]
description: PR #81 CI checks and changed files
command: cd /c/Users/avidu/Projects/muneem && echo "=== CI checks ===" && gh pr checks 81 --repo
avidullu/muneem 2>&1 | head -20 && echo "" && echo "=== files ===" && gh pr diff 81 --repo
avidullu/muneem --name-only 2>&1
[/external_agent_tool_call]
```

**78. assistant (2026-07-02T06:11:33.043Z)**

```
[external_agent_tool_result]
{"additions":5,"author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":"A
vi"},"baseRefName":"main","body":"Addresses the post-merge review comments from PR #80.\n\n###
1. ? Dead duplicate imports + orphaned comment in `cli/___init__.py`\nLines 66-69 were leftover
from an edit ? they re-imported `eval_statements` and `ingest` that were already imported (lines
61-62) and already used (lines 64-65). The orphaned comment read mid-sentence because its
opening was dropped. Deleted all four lines.\n\n### 2. ? Lazy imports in `cli/eval.py`\nMoved
`extract`, `get_parser`, `resolve_password`, `is_encrypted` from module-level to lazy imports
inside `_eval_statement()`, consistent with `cli/ingest.py` and preserving test
monkeypatchability.\n\n### Verification\n- ? ruff check ? clean\n- ? ruff format --check ?
clean\n- ? mypy ? 41 source files, no issues\n- ? pytest ? 478
passed","changedFiles":2,"deletions":8,"headRefName":"refactor/split-db-plus-review-fixes","isDr
aft":false,"mergeable":"MERGEABLE","number":81,"reviewDecision":"","state":"OPEN","title":"fix:
address PR #80 post-merge review comments","url":"https://github.com/avidullu/muneem/pull/81"}
[/external_agent_tool_result]
```

**79. assistant (2026-07-02T06:11:33.043Z)**

```
[external_agent_tool_result]
=== CI checks ===
ocr      skipping      0
https://github.com/avidullu/muneem/actions/runs/28186627388/job/83490126067
test (ubuntu-latest, 3.11)      pass      36s
https://github.com/avidullu/muneem/actions/runs/28186618740/job/83490062724
test (ubuntu-latest, 3.11)      pass      40s
https://github.com/avidullu/muneem/actions/runs/28186627388/job/83490093260
test (ubuntu-latest, 3.12)      pass      45s
https://github.com/avidullu/muneem/actions/runs/28186618740/job/83490062736
test (ubuntu-latest, 3.12)      pass      46s
https://github.com/avidullu/muneem/actions/runs/28186627388/job/83490093091
```

```

test (ubuntu-latest, 3.13)      pass    40s
https://github.com/avidullu/muneem/actions/runs/28186618740/job/83490062738
test (ubuntu-latest, 3.13)      pass    42s
https://github.com/avidullu/muneem/actions/runs/28186627388/job/83490093110
test (windows-latest, 3.13)     pass    1m25s
https://github.com/avidullu/muneem/actions/runs/28186618740/job/83490062733
test (windows-latest, 3.13)     pass    1m20s
https://github.com/avidullu/muneem/actions/runs/28186627388/job/83490093129
ocr      skipping                0
https://github.com/avidullu/muneem/actions/runs/28186618740/job/83490063391

```

```

=== files ===
src/muneem/cli/__init__.py
src/muneem/cli/eval.py
[/external_agent_tool_result]

```

#### 80. assistant (2026-07-02T06:11:33.043Z)

PR #81 directly addresses my two #80 comments (delete dead imports; make `eval.py` lazy). CI is green. Let me check out the branch and read the actual diff to verify the fixes are correct and complete.

#### 81. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_call: Bash]
description: Show full diff of PR #81
command: echo "=== full diff ===" && gh pr diff 81 --repo avidullu/muneem 2>&1
[/external_agent_tool_call]

```

#### 82. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_result]
=== full diff ===
diff --git a/src/muneem/cli/__init__.py b/src/muneem/cli/__init__.py
index 9304d52..0706b5c 100644
--- a/src/muneem/cli/__init__.py
+++ b/src/muneem/cli/__init__.py
@@ -63,7 +63,3 @@ def info() -> None:

    app.command()(ingest)
    app.command("eval")(eval_statements)
-# side-effects at import time. E402 is suppressed because the imports must follow
-# the app/sub-app definitions above.
-from muneem.cli.eval import eval_statements # noqa: E402, F401
-from muneem.cli.ingest import ingest # noqa: E402, F401
diff --git a/src/muneem/cli/eval.py b/src/muneem/cli/eval.py
index 725a4f5..12543d3 100644
--- a/src/muneem/cli/eval.py
+++ b/src/muneem/cli/eval.py
@@ -7,12 +7,8 @@
 import typer

 from muneem import db as dbmod
-from muneem.extract import extract
 from muneem.log import get_logger
-from muneem.parsers import get_parser
 from muneem.redaction import redact_filename
-from muneem.statement_unlock import resolve_password
-from muneem.unlock import is_encrypted

_log = get_logger(__name__)

@@ -23,6 +19,11 @@ def _eval_statement(pdf: Path, *, interactive: bool) -> tuple[str, int, str |
No

```

```

    Returns ``outcome, row_count, parser_name`` where ``outcome`` is the document status
    (``reconciled`` / ``unreconciled``) or a failure tag (``locked`` / ``no-parser`` /
    ``error``).
    """
+   from muneem.extract import extract
+   from muneem.parsers import get_parser
+   from muneem.statement_unlock import resolve_password
+   from muneem.unlock import is_encrypted
+
    password = ""
    if is_encrypted(pdf):
        password = resolve_password(pdf, interactive=interactive) or ""
[/external_agent_tool_result]

```

### 83. assistant (2026-07-02T06:11:33.043Z)

The diff is exactly the two fixes I flagged. Let me check out the branch and read the final state of both files to confirm they're clean and the lazy-import set is precisely right.

### 84. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_call: Bash]
description: Check out PR #81 branch
command: git checkout refactor/split-db-plus-review-fixes 2>&1 | tail -2 && git pull --ff-only
2>&1 | tail -1 && echo "=== HEAD ===" && git log --oneline -1
[/external_agent_tool_call]

```

### 85. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_result]
Your branch is up to date with 'origin/refactor/split-db-plus-review-fixes'.
Already on 'refactor/split-db-plus-review-fixes'
Already up to date.
=== HEAD ===
f0b16df fix: address PR #80 post-merge review comments
[/external_agent_tool_result]

```

### 86. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\__init__.py
[/external_agent_tool_call]

```

### 87. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_result]
1     """The ``muneem`` command-line interface.
2
3     Subcommands are split across focused modules: ``ingest``, ``offers``, ``txns``,
4     ``eval``, and ``db`` ? each in its own file under ``cli/``. This module assembles
5     the Typer app.
6
7     ``fetch`` (Gmail pull) lands with Phase F.
8     """
9
10    from __future__ import annotations
11
12    import typer
13
14    from muneem import __version__
15    from muneem.cli._shared import _version_callback
16    from muneem.config import load_config
17
18    app = typer.Typer(

```

```

19         add_completion=False,
20         help="muneem ? a local-first personal-finance bookkeeper.",
21         no_args_is_help=True,
22     )
23
24     # Sub-apps ? each wired in the module that defines its commands.
25     from muneem.cli.db import db_app # noqa: E402
26     from muneem.cli.offers import offers_app # noqa: E402
27     from muneem.cli.txns import txns_app # noqa: E402
28
29     app.add_typer(offers_app, name="offers")
30     app.add_typer(txns_app, name="txns")
31     app.add_typer(db_app, name="db")
32
33
34     @app.callback()
35     def main(
36         version: bool = typer.Option(
37             False,
38             "--version",
39             callback=_version_callback,
40             is_eager=True,
41             help="Show the muneem version and exit.",
42         ),
43     ) -> None:
44         """muneem command-line interface."""
45
46
47     @app.command()
48     def info() -> None:
49         """Show resolved local paths (no secrets, no sensitive data)."""
50         cfg = load_config()
51         present = "present" if cfg.config_file.is_file() else "absent"
52         typer.echo(f"muneem {__version__}")
53         typer.echo(f"config dir : {cfg.config_dir}")
54         typer.echo(f"data dir   : {cfg.data_dir}")
55         typer.echo(f"db path   : {cfg.db_path}")
56         typer.echo(f"staging  : {cfg.staging_dir}")
57         typer.echo(f"config file: {cfg.config_file} ({present})")
58
59
60     # Command registrations ? registered explicitly to avoid circular decorator imports.
61     from muneem.cli.eval import eval_statements # noqa: E402
62     from muneem.cli.ingest import ingest # noqa: E402
63
64     app.command()(ingest)
65     app.command("eval")(eval_statements)
66
[/external_agent_tool_result]

```

#### 88. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\Projects\muneem\src\muneem\cli\eval.py
[/external_agent_tool_call]

```

#### 89. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_result]
1     """The ``eval`` command ? evaluate parsers against a folder of statements."""
2
3     from __future__ import annotations
4
5     from pathlib import Path
6

```

```

7     import typer
8
9     from muneem import db as dbmod
10    from muneem.log import get_logger
11    from muneem.redaction import redact_filename
12
13    _log = get_logger(__name__)
14
15
16    def _eval_statement(pdf: Path, *, interactive: bool) -> tuple[str, int, str | None]:
17        """Run one statement through the full parse pipeline into an in-memory DB.
18
19        Returns ``(outcome, row_count, parser_name)`` where ``outcome`` is the document
status
20        (``reconciled`` / ``unreconciled``) or a failure tag (``locked`` / ``no-parser`` /
``error``).
21        """
22        from muneem.extract import extract
23        from muneem.parsers import get_parser
24        from muneem.statement_unlock import resolve_password
25        from muneem.unlock import is_encrypted
26
27        password = ""
28        if is_encrypted(pdf):
29            password = resolve_password(pdf, interactive=interactive) or ""
30            if not password:
31                return ("locked", 0, None)
32        try:
33            ex = extract(pdf, password=password)
34            parser = get_parser(ex.text)
35        except Exception as exc:
36            return ("error", 0, None)
37    [/external_agent_tool_result]

```

#### 90. assistant (2026-07-02T06:11:33.043Z)

Both files are clean. The fix is precisely scoped ? let me confirm what the green CI actually enforces (esp. a coverage gate) so my sign-off states accurately what's verified.

#### 91. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_call: Bash]
description: Inspect CI gates and coverage config
command: echo "=== CI workflow test steps ===" && sed -n '1,80p' .github/workflows/*.yaml
2>/dev/null | grep -nE "name:|run:|pytest|ruff|mypy|cov|fail-under" | head -40 && echo "" &&
echo "=== pyproject coverage/addopts ===" && grep -nE "cov|fail_under|addopts" pyproject.toml
2>/dev/null
[/external_agent_tool_call]

```

#### 92. assistant (2026-07-02T06:11:33.043Z)

```

[external_agent_tool_result]
=== CI workflow test steps ===
1:name: ci
24:      # path handling, the sqlcipher3 win_amd64 wheel). Linux covers the 3.11/3.12
spread.
34:      - name: Install
35:      run: |
38:      - name: Lint
39:      run: ruff check .
40:      - name: Format check
41:      run: ruff format --check .
42:      - name: Type check
43:      run: mypy
44:      - name: Test

```

```
45:         run: pytest --cov=muneem --cov-report=term-missing --cov-fail-under=80
59:     - name: Install Tesseract
60:         run: sudo apt-get update && sudo apt-get install -y tesseract-ocr
61:     - name: Install
62:         run: |
65:     - name: OCR tests
66:         run: pytest -m ocr
```

=== pyproject coverage/addopts ===

```
37:     "pytest-cov>=5.0",
86:addopts = "-ra -m 'not ocr and not llm and not local_statements'"
[/external_agent_tool_result]
```

### 93. assistant (2026-07-02T06:11:33.043Z)

Reviewed. Here's my verdict on [#81](https://github.com/avidullu/muneem/pull/81).

### ? LGTM ? both fixes are correct, complete, and faithful

The PR does exactly what my #80 comments asked, nothing more:

**\*\*Fix 1 ? `cli/\_\_\_init\_\_.py` (dead code removal).\*\*** Lines 66?69 (the two no-op re-imports + the orphaned mid-sentence comment) are gone. The file now ends cleanly at the two registrations; the remaining late imports (61?62) are still used (64?65), so the `# noqa: E402` is still correct and there's no F401/F811. Provably a zero-behavior deletion.

**\*\*Fix 2 ? `cli/eval.py` (lazy imports).\*\*** This is the part worth getting right, and they did. The four imports moved into `\_eval\_statement` are exactly the monkeypatch-sensitive `from x import name` bindings ? `extract`, `get\_parser`, `resolve\_password`, `is\_encrypted`. Those bind the name directly, so they *must* be re-resolved at call time to see a patched `muneem.extract.extract` (the way `tests/test\_cli.py:39` patches it for ingest). `dbmod` was correctly **\*\*left\*\*** at module level: it's a `import ? as` module alias, so `dbmod.connect` resolves dynamically and stays monkeypatch-safe regardless. This restores the original pre-split `\_eval\_statement` behavior and matches `ingest.py`. Precisely scoped ? no over-correction.

**\*\*No new issues, no production behavior change.\*\*** The only observable delta is restored test-monkeypatchability, which is the intent. My #3 (cosmetic `--help` order) was explicitly optional and correctly left alone.

**\*\*What green CI verifies here\*\*** (I relied on it rather than re-running): `ruff check`, `ruff format --check`, `mypy`, 478 tests, **\*\*and `--cov-fail-under=80`\*\*** ? all passing on Ubuntu 3.11/3.12/3.13 + Windows 3.13. That covers the full pre-merge gate; coverage can't have regressed since the change only relocates always-executed import lines.

**\*\*One non-blocking heads-up:\*\*** the branch is named `refactor/split-db-plus-review-fixes`, but this PR contains *only* the two review fixes ? no `db.py` split. The title/body are accurate; just flagging in case a db split was meant to ride along and got dropped.

---

Want me to **\*\*post this LGTM on #81\*\***? I held off auto-posting since you said "review" (not "post") this time, and an LGTM may prompt you to merge. And do you still want me to **\*\*keep polling muneem for new PRs\*\*** and review them as they land ? if so, at what cadence?

### 94. user (2026-07-02T06:11:33.044Z)

yes pls post an LGTM to it

### 95. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr81-lgtm.md
[/external_agent_tool_call]
```

#### 96. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr81-lgtm.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

#### 97. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Bash]
description: Post LGTM comment on PR #81 and clean up
command: cd /c/Users/avidu/Projects/muneem && gh pr comment 81 --repo avidullu/muneem --body-
file "C:\Users\avidu\AppData\Local\Temp\pr81-lgtm.md" 2>&1 && rm -f
"C:\Users\avidu\AppData\Local\Temp\pr81-lgtm.md"
[/external_agent_tool_call]
```

#### 98. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/81#issuecomment-4802168838
[/external_agent_tool_result]
```

#### 99. assistant (2026-07-02T06:11:33.044Z)

Posted: [#81 LGTM comment](https://github.com/avidullu/muneem/pull/81#issuecomment-4802168838).

Written LGTM (not a formal GitHub Approve, per our convention for your own account). The fix cleanly closes out both #80 findings, CI's green across the full gate (lint/format/mypy/478 tests/coverage ?80%), and it's safe to merge whenever you like.

Still open from my last message: do you want me to **keep polling muneem for new PRs** and review them as they land? If yes, tell me a cadence (e.g. every 15?30 min) and whether to **auto-post** reviews or just surface them here for you to approve first.

#### 100. user (2026-07-02T06:11:33.044Z)

#82 is up for review. Can you pls do it

#### 101. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Bash]
description: Fetch PR #82 metadata
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q && gh pr view 82 --repo
avidullu/muneem --json number,title,author,state,baseRefName,headRefName,additions,deletions,cha
ngedFiles,body,url,mergeable,reviewDecision,isDraft 2>&1
[/external_agent_tool_call]
```

#### 102. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Bash]
description: PR #82 CI checks and changed files
command: cd /c/Users/avidu/Projects/muneem && echo "=== CI checks ===" && gh pr checks 82 --repo
avidullu/muneem 2>&1 | head -20 && echo "" && echo "=== changed files ===" && gh pr diff 82
--repo avidullu/muneem --name-only 2>&1
[/external_agent_tool_call]
```

#### 103. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
{"additions":581,"author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":
"Avi"},"baseRefName":"main","body":"Splits the monolithic `db.py` (~590 lines) into a `db/`
subpackage with focused modules.\n\n### Before\n`nsrc/muneem/db.py` (590 lines ? schema DDL,
key helpers, connections, crypto, queries all in one file)\n\n###
After\n`nsrc/muneem/db/` ??? __init__.py (35 lines ? re-exports all public names,
```

```
backward-compatible)\n??? schema.py          (105 lines ? _SCHEMA DDL, SCHEMA_VERSION,
init_db)\n??? connection.py          (155 lines ? key validation, is_plaintext_sqlite, connect,
connect_encrypted)\n??? crypto.py          (100 lines ? encrypt_database, rekey_database,
backup_database)\n??? queries.py          (180 lines ? document CRUD, provenance, offers, per-bank
inserts + listings)\n```\n\n### Key design decisions\n- ``connection.py`` not ``connect.py`` ?
avoids clashing with the ``connect()`` function when using ``import muneem.db.connect`` (Python
resolves the package attribute first)\n- ``All public names re-exported`` from ``__init__.py`` ?
every ``from muneem import db as dbmod`` import continues to work\n- ``Private symbols stay in
submodules`` ? ``_SCHEMA``, ``_open_encrypted`` are not re-exported; tests import from the specific
submodule or monkeypatch at the module level\n\n### Verification\n- ? ``ruff check .`` ? clean\n-
? ``ruff format --check .`` ? clean\n- ? ``mypy`` ? 45 source files, no issues\n- ? ``pytest`` ? 478
passed\n- ? ``muneem --version`` ? works\n\nFixes recommendation #6 from the code-health report
(PR #74).", "changedFiles": 8, "deletions": 585, "headRefName": "refactor/split-db", "isDraft": false, "m
ergeable": "MERGEABLE", "number": 82, "reviewDecision": "", "state": "OPEN", "title": "refactor: split
db.py (~590 lines) into db/ subpackage", "url": "https://github.com/avidullu/muneem/pull/82"}
[/external_agent_tool_result]
```

#### 104. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
=== CI checks ===
test (windows-latest, 3.13)      pending 0
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491399767
test (ubuntu-latest, 3.11)      pass    34s
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491399778
test (ubuntu-latest, 3.12)      pass    49s
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491399735
test (ubuntu-latest, 3.13)      pass    43s
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491399727
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491401220
test (ubuntu-latest, 3.11)      pass    39s
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491375380
test (ubuntu-latest, 3.12)      pass    51s
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491375393
test (ubuntu-latest, 3.13)      pass    36s
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491375328
test (windows-latest, 3.13)      pass    1m30s
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491375348
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491376320

=== changed files ===
src/muneem/db.py
src/muneem/db/__init__.py
src/muneem/db/connection.py
src/muneem/db/crypto.py
src/muneem/db/queries.py
src/muneem/db/schema.py
tests/test_db_crypto_ops.py
tests/test_migrations.py
[/external_agent_tool_result]
```

#### 105. assistant (2026-07-02T06:11:33.044Z)

PR #82 is the ``db.py`` split that the #81 branch name hinted at ? and this one touches  
 ``crypto/connection/key-handling code``, so I'll verify the moved logic is byte-faithful, not  
 just that it imports. Note: ``Windows CI is still pending`` (Ubuntu 3.11/3.12/3.13 green) ?  
 Windows is the platform that exercises the sqlcipher3 wheel, so I'll factor that in. Let me pull  
 the original and the new modules without disturbing the working tree.

#### 106. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Bash]
```



```
description: Get merge-base and original db.py symbol inventory
command: MB=$(git merge-base origin/main origin/refactor/split-db) && echo "merge-base: $MB" &&
echo "=== original db.py lines ===" && git show $MB:src/muneem/db.py | wc -l && echo "=== public
symbols in original db.py (def/class/CONST) ===" && git show $MB:src/muneem/db.py | grep -nE
"^(def|class|[A-Z_]+ ?=|_[A-Za-z_]+ ?=)" | head -60
[/external_agent_tool_call]
```

#### 107. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
merge-base: ec12b59eb1320061c7fbfdefdcc8133a95970a61
=== original db.py lines ===
583
=== public symbols in original db.py (def/class/CONST) ===
21: log = get_logger(__name__)
23: SCHEMA_VERSION = 4
27: _SQLITE_MAGIC = b"SQLite format 3\x00"
29: _SCHEMA = """
113: def _validate_raw_key(key: str) -> str:
128: def _raw_key_pragma(key: str) -> str:
133: def is_plaintext_sqlite(db_path: Path | str) -> bool:
146: def _harden_permissions(path: str) -> None:
156: def _open_encrypted(path: str, key: str) -> sqlite3.Connection:
184: def connect(db_path: Path | str, *, key: str | None = None) -> Iterator[sqlite3.Connection]:
209: def key_opens_database(db_path: Path | str, key: str) -> bool:
219: def connect_encrypted(db_path: Path | str) -> Iterator[sqlite3.Connection]:
272: def encrypt_database(db_path: Path | str, key: str) -> int:
335: def rekey_database(db_path: Path | str, current_key: str, new_key: str) -> None:
352: def backup_database(db_path: Path | str, dest: Path | str, key: str) -> None:
396: def init_db(conn: sqlite3.Connection) -> None:
407: def get_document_by_sha(conn: sqlite3.Connection, sha256: str) -> sqlite3.Row | None:
411: def clear_document_rows(conn: sqlite3.Connection, document_id: int) -> None:
428: def _insert_row(conn: sqlite3.Connection, table: str, fields: dict) -> int:
442: def insert_document(conn: sqlite3.Connection, **fields: object) -> int:
447: def record_provenance(
475: def record_parse(
498: def get_provenance(conn: sqlite3.Connection, document_id: int) -> sqlite3.Row | None:
502: def insert_offer(conn: sqlite3.Connection, **fields: object) -> int:
506: def list_offers(conn: sqlite3.Connection) -> list[sqlite3.Row]:
518: def insert_axis_transaction(conn: sqlite3.Connection, **fields: object) -> int:
522: def insert_axis_cc_transaction(conn: sqlite3.Connection, **fields: object) -> int:
528: def list_axis_cc_transactions(conn: sqlite3.Connection, limit: int = 50) ->
list[sqlite3.Row]:
536: def list_axis_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
544: def insert_hdfc_transaction(conn: sqlite3.Connection, **fields: object) -> int:
548: def list_hdfc_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
556: def insert_au_transaction(conn: sqlite3.Connection, **fields: object) -> int:
560: def list_all_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
578: def list_au_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
[/external_agent_tool_result]
```

#### 108. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_call: Bash]
description: Show test file changes in PR #82
command: echo "=== test file diffs ===" && gh pr diff 82 --repo avidullu/muneem 2>&1 | sed -n
'/tests/test_db_crypto_ops.py/, $p' | head -90
[/external_agent_tool_call]
```

#### 109. assistant (2026-07-02T06:11:33.044Z)

```
[external_agent_tool_result]
=== test file diffs ===
diff --git a/tests/test_db_crypto_ops.py b/tests/test_db_crypto_ops.py
```

```

index 9c3d367..378b372 100644
--- a/tests/test_db_crypto_ops.py
+++ b/tests/test_db_crypto_ops.py
@@ -12,6 +12,7 @@

from typer.testing import CliRunner # noqa: E402

+import muneem.db.connection as dbconnect_mod # noqa: E402
from muneem import db as dbmod # noqa: E402
from muneem import db_key # noqa: E402
from muneem.cli import app # noqa: E402
@@ -161,7 +162,7 @@ def test_encrypt_database_cleans_temp_on_failure(tmp_path, monkeypatch):
    def boom(*_a, **_k): # fail the post-export verification open
        raise RuntimeError("boom during verify")

-    monkeypatch.setattr(dbmod, "_open_encrypted", boom)
+    monkeypatch.setattr(dbconnect_mod, "_open_encrypted", boom)
    with pytest.raises(RuntimeError):
        dbmod.encrypt_database(p, KEY_A)
    assert not (tmp_path / "led.db.enc.tmp").exists() # partial temp removed
diff --git a/tests/test_migrations.py b/tests/test_migrations.py
index de0d4f2..daf4bfb 100644
--- a/tests/test_migrations.py
+++ b/tests/test_migrations.py
@@ -6,9 +6,9 @@

from muneem import db as dbmod
from muneem import migrations
+from muneem.db.schema import _SCHEMA as _BASE
from muneem.errors import MigrationError

-_BASE = dbmod._SCHEMA
_VER = dbmod.SCHEMA_VERSION # 4
[/external_agent_tool_result]

```

#### 110. assistant (2026-07-02T06:11:33.045Z)

The test changes look exactly right at a glance (patch `\_open\_encrypted` where it now lives in `connection.py`; import private `\_SCHEMA` from the submodule). The critical thing for a crypto refactor is that **no function body changed** during the move. Let me prove that with an AST-level comparison of every symbol ? original `db.py` vs the merged `db/` modules.

#### 111. assistant (2026-07-02T06:11:33.045Z)

```

[external_agent_tool_call: Bash]
description: Stage original and new db modules to temp dir
command: MB=$(git merge-base origin/main origin/refactor/split-db) && TMP=$(mktemp -d) && git
show $MB:src/muneem/db.py > "$TMP/orig.py" && for m in __init__ schema connection crypto
queries; do git show origin/refactor/split-db:src/muneem/db/$m.py > "$TMP/$m.py"; done && echo
"files staged in $TMP:" && ls -la "$TMP" && echo "$TMP" > /tmp/cmpdir.txt
[/external_agent_tool_call]

```

#### 112. assistant (2026-07-02T06:11:33.045Z)

```

[external_agent_tool_result]
files staged in /tmp/tmp.A1gmiP4Pyp:
total 2104
drwxr-xr-x 1 avidu 197609    0 Jun 25 22:35 .
drwxr-xr-x 1 avidu 197609    0 Jun 25 22:35 ..
-rw-r--r-- 1 avidu 197609 1357 Jun 25 22:35 __init__.py
-rw-r--r-- 1 avidu 197609 5080 Jun 25 22:35 connection.py
-rw-r--r-- 1 avidu 197609 3995 Jun 25 22:35 crypto.py
-rw-r--r-- 1 avidu 197609 23071 Jun 25 22:35 orig.py
-rw-r--r-- 1 avidu 197609 5990 Jun 25 22:35 queries.py

```

```
-rw-r--r-- 1 avidu 197609 2824 Jun 25 22:35 schema.py
[/external_agent_tool_result]
```

### 113. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_call: Bash]
description: AST-compare original db.py vs split modules
command: cat > /tmp/astcmp.py <<'PY'
import ast, sys
TMP = open('/tmp/cmpdir.txt').read().strip()

def collect(path):
    src = open(path, encoding='utf-8').read()
    tree = ast.parse(src)
    out = {}
    for node in tree.body:
        if isinstance(node, (ast.FunctionDef, ast.AsyncFunctionDef)):
            out[node.name] = ('func', ast.dump(node))
        elif isinstance(node, ast.ClassDef):
            out[node.name] = ('class', ast.dump(node))
        elif isinstance(node, ast.Assign):
            for t in node.targets:
                if isinstance(t, ast.Name):
                    out[t.id] = ('assign', ast.dump(node.value))
    return out

orig = collect(f"{TMP}/orig.py")
new = {}
dups = []
for m in ['schema', 'connection', 'crypto', 'queries']:
    for k,v in collect(f"{TMP}/{m}.py").items():
        if k in new and k != '_log' and new[k] != v:
            dups.append((k, new[k+'__mod'] if k+'__mod' in new else '?', m))
        if k not in new:
            new[k] = v; new[k+'__mod'] = m
        elif k == '_log':
            pass

orig_syms = {k for k in orig if not k.endswith('__mod')}
new_syms = {k for k in new if not k.endswith('__mod')}

missing = sorted(orig_syms - new_syms)
added = sorted(new_syms - orig_syms)
changed = sorted(k for k in (orig_syms & new_syms) if orig[k][1] != new[k][1])
ident = sorted(k for k in (orig_syms & new_syms) if orig[k][1] == new[k][1])

print(f"original symbols: {len(orig_syms)}    new symbols: {len(new_syms)}")
print(f"AST-IDENTICAL: {len(ident)}")
print(f"\nMISSING from new (in orig, not in split): {missing or 'NONE'}")
print(f"CHANGED (AST differs!): {changed or 'NONE'}")
print(f"ADDED in new (not in orig): {added or 'NONE'}")
print("\nper-symbol home module:")
for k in sorted(new_syms):
    if k != '_log': print(f"  {k:32} -> {new.get(k+'__mod', '?')}")
PY
VPY=".venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python; "$VPY" /tmp/astcmp.py
[/external_agent_tool_call]
```

### 114. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_result: error]
Exit code 1
Traceback (most recent call last):
  File "C:\Users\avidu\AppData\Local\Temp\astcmp.py", line 2, in <module>
    TMP = open('/tmp/cmpdir.txt').read().strip()
```

~~~~~AAAAAAAAAAAAAAAAAAAA

```
FileNotFoundError: [Errno 2] No such file or directory: '/tmp/cmpdir.txt'
[/external_agent_tool_result]
```

#### 115. assistant (2026-07-02T06:11:33.045Z)

The Windows Python can't resolve git-bash `/tmp` paths. Let me re-stage and run the comparison passing Windows paths.

#### 116. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_call: Bash]
description: Re-stage and run AST comparison with Windows paths
command: MB=$(git merge-base origin/main origin/refactor/split-db)
DIR=$(mktemp -d); cd /c/Users/avidu/Projects/muneem
git show $MB:src/muneem/db.py > "$DIR/orig.py"
for m in schema connection crypto queries; do git show origin/refactor/split-
db:src/muneem/db/$m.py > "$DIR/$m.py"; done
cat > "$DIR/astcmp.py" <<'PY'
import ast, sys, os
TMP = sys.argv[1]
def collect(path):
    tree = ast.parse(open(path, encoding='utf-8').read())
    out = {}
    for node in tree.body:
        if isinstance(node,(ast.FunctionDef,ast.AsyncFunctionDef)):
out[node.name]='func',ast.dump(node))
        elif isinstance(node,ast.ClassDef): out[node.name]='class',ast.dump(node))
        elif isinstance(node,ast.Assign):
            for t in node.targets:
                if isinstance(t,ast.Name): out[t.id]='assign',ast.dump(node.value))
    return out
orig = collect(os.path.join(TMP,'orig.py'))
home={}; new={}
for m in ['schema','connection','crypto','queries']:
    for k,v in collect(os.path.join(TMP,m+'.py')).items():
        if k=='_log': continue
        if k in new and new[k]!=v: print(f"!! DUP-DIFF {k} in {home[k]} vs {m}")
        new[k]=v; home[k]=m
o=set(orig)-{'_log'}; n=set(new)
miss=sorted(o-n); add=sorted(n-o)
chg=sorted(k for k in o&n if orig[k][1]!=new[k][1])
ident=sorted(k for k in o&n if orig[k][1]==new[k][1])
print(f"orig symbols={len(o)} new symbols={len(n)} AST-identical={len(ident)}")
print("MISSING:", miss or "NONE")
print("CHANGED(AST differs):", chg or "NONE")
print("ADDED:", add or "NONE")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w "$DIR/astcmp.py")" "$(cygpath -w "$DIR")"
[/external_agent_tool_call]
```

#### 117. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_result]
orig symbols=33 new symbols=34 AST-identical=11
MISSING: NONE
CHANGED(AST differs): ['_SCHEMA', '_harden_permissions', '_open_encrypted', '_raw_key_pragma',
'_validate_raw_key', 'backup_database', 'clear_document_rows', 'connect', 'connect_encrypted',
'encrypt_database', 'init_db', 'insert_document', 'is_plaintext_sqlite', 'key_opens_database',
'list_all_transactions', 'list_auth_transactions', 'list_axis_cc_transactions',
'list_axis_transactions', 'list_hdfc_transactions', 'record_parse', 'record_provenance',
'rekey_database']
ADDED: ['_JOIN_STATUS']
```

```
[/external_agent_tool_result]
```

#### 118. assistant (2026-07-02T06:11:33.045Z)

22 symbols differ at the AST level and a new `\_JOIN\_STATUS` constant appeared ? so this is **\*\*not** a pure mechanical move\*; some bodies were also edited (likely cross-module call re-qualification + a SQL dedup). That's exactly what needs scrutiny in a "refactor" PR. Let me get the actual per-function diffs.

#### 119. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_call: Bash]
description: Show per-function source diffs for changed symbols
command: MB=$(git merge-base origin/main origin/refactor/split-db); cd
/c/Users/avidu/Projects/muneem
DIR=$(mktemp -d)
git show $MB:src/muneem/db.py > "$DIR/orig.py"
for m in schema connection crypto queries; do git show origin/refactor/split-
db:src/muneem/db/$m.py > "$DIR/$m.py"; done
cat > "$DIR/diffcmp.py" <<'PY'
import ast, os, sys, difflib
TMP=sys.argv[1]
def funcs(path):
    src=open(path,encoding='utf-8').read(); tree=ast.parse(src); out={}
    for n in tree.body:
        if isinstance(n,(ast.FunctionDef,ast.AsyncFunctionDef,ast.ClassDef)):
            out[n.name]=ast.get_source_segment(src,n)
    return out
orig=funcs(os.path.join(TMP,'orig.py'))
new={}
for m in ['schema','connection','crypto','queries']:
    for k,v in funcs(os.path.join(TMP,m+'.py')).items():
        if k not in new: new[k]=v
changed=[k for k in orig if k in new and
ast.dump(ast.parse(orig[k]))!=ast.dump(ast.parse(new[k]))]
for k in changed:
    a=orig[k].splitlines(); b=new[k].splitlines()
    d=list(difflib.unified_diff(a,b,lineterm='',n=1))
    # only show the changed hunks (skip if identical text but ast differs - shouldn't happen)
    body=[l for l in d if l and l[0] in '+-' and not l.startswith(('+++', '---'))]
    print(f"\n==== {k} =====")
    for l in d[2:]:
        if l.startswith(('+', '-')) and not l.startswith(('+++', '---')): print(l)
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w "$DIR/diffcmp.py")" "$(cygpath -w "$DIR")" 2>&1 | head -120
[/external_agent_tool_call]
```

#### 120. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_result]
===== _validate_raw_key =====
-     """Require exactly 64 hex chars before splicing key material into a PRAGMA/ATTACH string.
-
-     Anything else would either silently switch SQLCipher from raw-key mode to passphrase-KDF
-     mode (a *different* encryption that still "works" ? and then never opens again with the
-     real raw key), or break out of the SQL literal. Refuse loudly instead.
-     """
+     """Require exactly 64 hex chars before splicing key material into a PRAGMA/ATTACH
string."""

===== _raw_key_pragma =====
-     """The SQLCipher raw-key PRAGMA: use the 256-bit ``key`` (64 hex chars) directly, no
KDF."""
```

```

+     """The SQLCipher raw-key PRAGMA: use the 256-bit key (64 hex chars) directly, no KDF."""

===== is_plaintext_sqlite =====
-     """True iff the file exists and begins with the *unencrypted* SQLite magic header.
-
-     Lets us refuse to silently treat a plaintext ledger as encrypted (and vice-versa)
-     without needing the key.
-     """
+     """True iff the file exists and begins with the unencrypted SQLite magic header."""

===== _harden_permissions =====
-     """Best-effort: restrict the DB file to its owner (0600). No-op on failure or
-     ``:memory:``."""
+     """Best-effort: restrict the DB file to its owner (0600). No-op on failure or :memory:."""

===== _open_encrypted =====
-     """Open an encrypted connection via SQLCipher, verifying the key before returning.
-
-     A keyed open NEVER silently downgrades to plaintext: if the binding is missing, or the
-     key is wrong (or the file is not an encrypted muneem ledger), this raises.
-     """
+     """Open an encrypted connection via SQLCipher, verifying the key before returning."""
-     except ImportError as exc: # pragma: no cover - exercised only without the binding
+     except ImportError as exc: # pragma: no cover
-     conn.execute(_raw_key_pragma(key)) # MUST be the first statement on the connection
+     conn.execute(_raw_key_pragma(key))
-     conn.execute("SELECT count(*) FROM sqlite_master") # forces key verification
+     conn.execute("SELECT count(*) FROM sqlite_master")

===== connect =====
-     With ``key`` (a 64-hex-char SQLCipher key) the database is **encrypted at rest** via
-     SQLCipher. Without it, a plaintext stdlib :mod:`sqlite3` connection is used ? the path for
-     ``:memory:`` and tests. A keyed open never silently falls back to plaintext (see
-     :func:`_open_encrypted`); the production ledger is opened via :func:`connect_encrypted`.
+     With ``key`` the database is encrypted at rest via SQLCipher. Without it, plaintext
+     stdlib sqlite3 is used ? the path for :memory: and tests.

===== key_opens_database =====
-     """True iff ``key`` opens the encrypted ledger at ``db_path`` (verification only, no
-     reads)."""
+     """True iff ``key`` opens the encrypted ledger at ``db_path`` (verification only)."""

===== connect_encrypted =====
-     The production path: resolves (or mints, on first use) the 256-bit key from the OS
-     keychain and opens with SQLCipher. If ``db_path`` is a pre-existing *plaintext* SQLite
-     file, refuses with a clear pointer to ``muneem db encrypt`` rather than a cryptic
-     "file is not a database" error.
-
-     Self-healing for interrupted key rotations: rotation stages the incoming key under a
-     *pending* keychain entry before the file is rekeyed (see ``cli rotate-key``). If the
-     primary key no longer opens the file but the pending key does, the rotation completed
-     on the file side and was interrupted before promotion ? promote the pending key and
-     carry on. With no pending key (or one that doesn't fit), the original wrong-key error
-     propagates untouched.
+     Self-healing for interrupted key rotations: if the primary key no longer opens the file
+     but the pending key does, promote it automatically.
-     # Mint a key only for a brand-new ledger. If an encrypted ledger already exists, a missing
-     # keychain...
[/external_agent_tool_result]

```

## 121. assistant (2026-07-02T06:11:33.045Z)

These are all `docstring/comment trims` ? `ast.dump`` includes docstrings, so editorial rewrites flag as "differs" even though the executable logic is untouched. So far no logic change in the crypto/connection functions. But I still need to see the `query functions` and the new

`\_JOIN\_STATUS` constant ? a SQL dedup \*can\* change results. Let me look at those specifically.

## 122. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_call: Bash]
description: Show _JOIN_STATUS and original listing SQL
command: MB=$(git merge-base origin/main origin/refactor/split-db); cd
/c/Users/avidu/Projects/muneem
echo "=== NEW _JOIN_STATUS constant in queries.py ==="
git show origin/refactor/split-db:src/muneem/db/queries.py | grep -nA6 "_JOIN_STATUS"
echo ""
echo "=== ORIGINAL list_all_transactions + list_au_transactions + a per-bank listing (for SQL
comparison) ==="
git show $MB:src/muneem/db.py | sed -n '498,583p'
[/external_agent_tool_call]
```

## 123. assistant (2026-07-02T06:11:33.045Z)

```
[external_agent_tool_result]
=== NEW _JOIN_STATUS constant in queries.py ===
135:_JOIN_STATUS = "JOIN documents d ON d.id = t.document_id ORDER BY t.id DESC LIMIT ?"
136-
137-
138-def list_axis_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
139-    return conn.execute(
140-        f"SELECT t.*, d.status AS doc_status FROM axis_transactions t {_JOIN_STATUS}",
141-        (limit,),
142-    ).fetchall()
143-
144-
145-def list_axis_cc_transactions(conn: sqlite3.Connection, limit: int = 50) ->
list[sqlite3.Row]:
146-    return conn.execute(
147-        f"SELECT t.*, d.status AS doc_status FROM axis_cc_transactions t {_JOIN_STATUS}",
148-        (limit,),
149-    ).fetchall()
150-
151-
152-def list_hdfc_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
153-    return conn.execute(
154-        f"SELECT t.*, d.status AS doc_status FROM hdfc_transactions t {_JOIN_STATUS}",
155-        (limit,),
156-    ).fetchall()
157-
158-
159-def list_au_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
160-    return conn.execute(
161-        f"SELECT t.*, d.status AS doc_status FROM au_transactions t {_JOIN_STATUS}",
162-        (limit,),
163-    ).fetchall()
164-
165-
166-def list_all_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
167-    """Cross-bank rows from the derived serving view, with each parse's confidence joined
in."""

=== ORIGINAL list_all_transactions + list_au_transactions + a per-bank listing (for SQL
comparison) ===
def get_provenance(conn: sqlite3.Connection, document_id: int) -> sqlite3.Row | None:
    return conn.execute("SELECT * FROM provenance WHERE document_id = ?",
(document_id,)).fetchone()

def insert_offer(conn: sqlite3.Connection, **fields: object) -> int:
    return _insert_row(conn, "offers", fields)
```

```

def list_offers(conn: sqlite3.Connection) -> list[sqlite3.Row]:
    return conn.execute(
        """
        SELECT o.id, o.merchant, o.promo_code, o.expiry_raw, o.description, o.source,
            d.external_id, d.path
        FROM offers o
        JOIN documents d ON d.id = o.document_id
        ORDER BY o.id
        """
    ).fetchall()

def insert_axis_transaction(conn: sqlite3.Connection, **fields: object) -> int:
    return _insert_row(conn, "axis_transactions", fields)

def insert_axis_cc_transaction(conn: sqlite3.Connection, **fields: object) -> int:
    return _insert_row(conn, "axis_cc_transactions", fields)

```

**Per-bank listings carry the parse verdict (documents.status as doc\_status) so a consumer can tell trusted rows from quarantined/legacy residue without a second query.**

```

def list_axis_cc_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
    return conn.execute(
        "SELECT t.*, d.status AS doc_status FROM axis_cc_transactions t "
        "JOIN documents d ON d.id = t.document_id ORDER BY t.id DESC LIMIT ?",
        (limit,),
    ).fetchall()

def list_axis_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
    return conn.execute(
        "SELECT t.*, d.status AS doc_status FROM axis_transactions t "
        "JOIN documents d ON d.id = t.document_id ORDER BY t.id DESC LIMIT ?",
        (limit,),
    ).fetchall()

def insert_hdfc_transaction(conn: sqlite3.Connection, **fields: object) -> int:
    return _insert_row(conn, "hdfc_transactions", fields)

def list_hdfc_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
    return conn.execute(
        "SELECT t.*, d.status AS doc_status FROM hdfc_transactions t "
        "JOIN documents d ON d.id = t.document_id ORDER BY t.id DESC LIMIT ?",
        (limit,),
    ).fetchall()

def insert_au_transaction(conn: sqlite3.Connection, **fields: object) -> int:
    return _insert_row(conn, "au_transactions", fields)

```

```

def list_all_transactions(conn: sqlite3.Connection, limit: int = 50) -> list[sqlite3.Row]:
    """Cross-bank rows from the derived serving view, with each parse's co...
    [/external_agent_tool_result]

```

#### 124. assistant (2026-07-02T06:11:33.045Z)

The `\_JOIN\_STATUS` dedup is byte-identical SQL ? original `"...t " + "JOIN documents d ON d.id = t.document\_id ORDER BY t.id DESC LIMIT ?"`` reconstructs exactly via the f-string, same param binding. Now let me run the **definitive** check: strip docstrings and re-compares ASTs, so only



genuine \*executable-logic\* changes remain.

#### 125. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_call: Bash]
description: Compare ASTs with docstrings stripped
command: MB=$(git merge-base origin/main origin/refactor/split-db); cd
/c/Users/avidu/Projects/muneem
DIR=$(mktemp -d)
git show $MB:src/muneem/db.py > "$DIR/orig.py"
for m in schema connection crypto queries; do git show origin/refactor/split-
db:src/muneem/db/$m.py > "$DIR/$m.py"; done
cat > "$DIR/strip.py" <<'PY'
import ast, os, sys
TMP=sys.argv[1]
def strip_doc(node):
    # remove leading docstring expr from a function/class body
    if node.body and isinstance(node.body[0],ast.Expr) and
isinstance(getattr(node.body[0], 'value', None),ast.Constant) and
isinstance(node.body[0].value.value,str):
        node.body=node.body[1:]
    return node
def collect(path):
    src=open(path,encoding='utf-8').read(); tree=ast.parse(src); out={}
    for n in tree.body:
        if isinstance(n,(ast.FunctionDef,ast.AsyncFunctionDef,ast.ClassDef)):
            out[n.name]=ast.dump(strip_doc(n))
        elif isinstance(n,ast.Assign):
            for t in n.targets:
                if isinstance(t,ast.Name): out[t.id]=ast.dump(n.value)
    return out
orig=collect(os.path.join(TMP,'orig.py'))
new={}
for m in ['schema','connection','crypto','queries']:
    for k,v in collect(os.path.join(TMP,m+'.py')).items():
        if k=='_log': continue
        new.setdefault(k,v)
o=set(orig)-{'_log'}; n=set(new)
chg=sorted(k for k in o&n if orig[k]!=new[k])
print("EXECUTABLE-LOGIC DIFFERS (docstrings stripped):", chg or "NONE")
print("missing:", sorted(o-n) or "NONE", " added:", sorted(n-o) or "NONE")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w "$DIR/strip.py")" "$(cygpath -w "$DIR")"
[/external_agent_tool_call]
```

#### 126. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_result]
EXECUTABLE-LOGIC DIFFERS (docstrings stripped): ['_SCHEMA', 'list_au_transactions',
'list_axis_cc_transactions', 'list_axis_transactions', 'list_hdfc_transactions']
missing: NONE added: ['_JOIN_STATUS']
[/external_agent_tool_result]
```

#### 127. assistant (2026-07-02T06:11:33.046Z)

Excellent ? that's the definitive result. Every crypto/connection/query function is \*\*executable-identical\*\* (only docstrings/comments trimmed). Only two real deltas remain: the 4 `list\_\*` functions (verified byte-identical SQL via `\_JOIN\_STATUS`) and \*\*`\_SCHEMA`\*\* ? the table DDL. A schema-string change is the one thing that could actually matter, so let me diff it precisely.

#### 128. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_call: Bash]
description: Diff the _SCHEMA DDL string precisely
command: MB=$(git merge-base origin/main origin/refactor/split-db); cd
/c/Users/avidu/Projects/muneem
DIR=$(mktemp -d)
cat > "$DIR/schema_cmp.py" <<'PY'
import ast, sys, difflib
def get_schema(src):
    t=ast.parse(src)
    for n in t.body:
        if isinstance(n,ast.Assign):
            for tg in n.targets:
                if isinstance(tg,ast.Name) and tg.id=='_SCHEMA':
                    return n.value.value
    return None
a=get_schema(open(sys.argv[1],encoding='utf-8').read())
b=get_schema(open(sys.argv[2],encoding='utf-8').read())
print("identical?" , a==b)
if a!=b:
    for l in difflib.unified_diff(a.splitlines(),b.splitlines(),'orig','new',lineterm=''):
        print(l)
PY
git show $MB:src/muneem/db.py > "$DIR/o.py"
git show origin/refactor/split-db:src/muneem/db/schema.py > "$DIR/s.py"
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w "$DIR/schema_cmp.py")" "$(cygpath -w "$DIR/o.py")" "$(cygpath -w
"$DIR/s.py")"
[/external_agent_tool_call]
```

#### 129. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_result]
identical? False
--- orig
+++ new
@@ -30,8 +30,6 @@

-- We use separate tables for each bank (e.g. axis_transactions, hdfc_transactions)
-- instead of a unified table to preserve raw schema fidelity of the source PDFs.
--- Normalization into a unified view layer is planned for a later phase
--- once all bank schemas are stabilized.
CREATE TABLE IF NOT EXISTS axis_transactions (
    id INTEGER PRIMARY KEY,
    document_id INTEGER NOT NULL REFERENCES documents(id) ON DELETE CASCADE,
[/external_agent_tool_result]
```

#### 130. assistant (2026-07-02T06:11:33.046Z)

Only change to `\_SCHEMA` is a 2-line SQL comment removal ? SQLite ignores `--` comments, so the DDL is semantically identical.

**\*\*Net: every executable path is faithful.\*\*** Now two public-surface checks remain: confirm `\_\_init\_\_.py` re-exports the entire public API (especially `EncryptedDatabaseError`, which callers use as `dbmod.EncryptedDatabaseError`), and re-poll the Windows CI job.

#### 131. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_call: Bash]
description: Verify public re-export surface incl. EncryptedDatabaseError
command: cd /c/Users/avidu/Projects/muneem
echo "=== new db/__init__.py ===" && git show origin/refactor/split-db:src/muneem/db/__init__.py
echo ""
echo "=== where is EncryptedDatabaseError defined/imported in the split? ==="
for m in __init__ schema connection crypto queries; do echo "-- $m.py --"; git show
```

```

origin/refactor/split-db:src/muneem/db/$m.py | grep -n "EncryptedDatabaseError" | head; done
echo ""
echo "=== callers using dbmod.EncryptedDatabaseError ===" && grep -rn "EncryptedDatabaseError"
src/muneem/cli/ | head
[/external_agent_tool_call]

```

### 132. assistant (2026-07-02T06:11:33.046Z)

```

[external_agent_tool_result]
=== new db/___init__.py ===
"""Local SQLite store ? encrypted ledger, schema, and per-table helpers.

```

The ``db/`` package splits what was a ~590-line ``db.py`` monolith into focused modules:

- ``schema`` ? DDL + ``init\_db``
- ``connect`` ? key helpers, plaintext/encrypted connections
- ``crypto`` ? encrypt, rekey, backup
- ``queries`` ? document CRUD, provenance, offers, per-bank transactions

All public names are re-exported here, so ``from muneem.db import connect\_encrypted``  
(and all other existing imports) still work unchanged.

```

from muneem.db.connection import ( # noqa: F401
    connect,
    connect_encrypted,
    is_plaintext_sqlite,
    key_opens_database,
)
from muneem.db.crypto import backup_database, encrypt_database, rekey_database # noqa: F401
from muneem.db.queries import ( # noqa: F401
    clear_document_rows,
    get_document_by_sha,
    get_provenance,
    insert_aud_transaction,
    insert_axis_cc_transaction,
    insert_axis_transaction,
    insert_document,
    insert_hdfc_transaction,
    insert_offer,
    list_all_transactions,
    list_aud_transactions,
    list_axis_cc_transactions,
    list_axis_transactions,
    list_hdfc_transactions,
    list_offers,
    record_parse,
    record_provenance,
)
from muneem.db.schema import SCHEMA_VERSION, init_db # noqa: F401
from muneem.errors import EncryptedDatabaseError # noqa: F401

=== where is EncryptedDatabaseError defined/imported in the split? ===
-- __init__.py --
41:from muneem.errors import EncryptedDatabaseError # noqa: F401
-- schema.py --
-- connection.py --
13:from muneem.errors import EncryptedDatabaseError
22:         raise EncryptedDatabaseError(
58:         raise EncryptedDatabaseError(
68:         raise EncryptedDatabaseError(
105:     except EncryptedDatabaseError:
122:         raise EncryptedDatabaseError(
129:         raise EncryptedDatabaseError(
139:     except EncryptedDatabaseError:

```

```
-- crypto.py --
16:from muneem.errors import EncryptedDatabaseError
29:     raise EncryptedDatabaseError(
56:         raise EncryptedDatabaseError(
97:         raise EncryptedDatabaseError(
-- queries.py --

=== callers using dbmod.EncryptedDatabaseError ===
src/muneem/cli/db.py:142:     except dbmod.EncryptedDatabaseError as exc:
src/muneem/cli/db.py:202:         except dbmod.EncryptedDatabaseError as exc:
src/muneem/cli/_shared.py:20:     except dbmod.EncryptedDatabaseError as exc:
Binary file src/muneem/cli/__pycache__/db.cpython-313.pyc matches
Binary file src/muneem/cli/__pycache__/_shared.cpython-313.pyc matches
[/external_agent_tool_result]
```

### 133. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_call: Bash]
description: Re-poll Windows CI for PR #82
command: echo "=== Windows CI status now ===" && gh pr checks 82 --repo avidullu/muneem 2>&1 |
grep -iE "windows|pending|fail" | head
[/external_agent_tool_call]
```

### 134. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_result]
=== Windows CI status now ===
test (windows-latest, 3.13)      pass      2m10s
https://github.com/avidullu/muneem/actions/runs/28187001914/job/83491399767
test (windows-latest, 3.13)      pass      1m30s
https://github.com/avidullu/muneem/actions/runs/28186994783/job/83491375348
[/external_agent_tool_result]
```

### 135. assistant (2026-07-02T06:11:33.046Z)

All green now ? Windows CI passed (2m10s), so the full gate (Ubuntu 3.11/3.12/3.13 + Windows 3.13, sqlcipher crypto tests included) is green. The `\_\_init\_\_.py` re-exports the complete public API including `EncryptedDatabaseError` (which `cli/db.py` and `cli/\_shared.py` rely on as `dbmod.EncryptedDatabaseError`). One last belt-and-suspenders check: confirm no *\*non-test\** code reaches for a now-private db internal via the package.

### 136. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_call: Bash]
description: Check for stale private-symbol references outside tests
command: cd /c/Users/avidu/Projects/muneem
echo "=== any non-test references to private db internals
(_SCHEMA/_open_encrypted/_insert_row/_validate_raw_key) via db/dbmod? ==="
grep -rnE "db(mod)?\._(SCHEMA|open_encrypted|insert_row|validate_raw_key|raw_key_pragma|harden_p
ermissons|SQLITE_MAGIC)" src/ --include=*.py || echo "NONE (good)"
echo ""
echo "=== does migrations.py touch db private DDL? ==="
grep -nE "_SCHEMA|open_encrypted|from muneem.db|import db" src/muneem/migrations.py 2>/dev/null
|| echo "no such refs"
[/external_agent_tool_call]
```

### 137. assistant (2026-07-02T06:11:33.046Z)

```
[external_agent_tool_result]
=== any non-test references to private db internals
(_SCHEMA/_open_encrypted/_insert_row/_validate_raw_key) via db/dbmod? ===
src/muneem/migrations.py:9:- Baseline. The current schema (`db._SCHEMA`, version
`db.SCHEMA_VERSION`) is the *frozen*
```

```
=== does migrations.py touch db private DDL? ===
9:- Baseline. The current schema (`db._SCHEMA`, version `db.SCHEMA_VERSION`) is the *frozen*
31:_SCHEMA_MIGRATIONS = ""
196: conn.executescript(_SCHEMA_MIGRATIONS) # bookkeeping table first (idempotent)
[/external_agent_tool_result]
```

### 138. assistant (2026-07-02T06:11:33.046Z)

Review complete ? and this one I verified deeply, since it moves **\*crypto/key-handling code\***. Here's the verdict on [#82](https://github.com/avidullu/muneem/pull/82).

### ? Faithful split ? behavior provably preserved, full CI now green

I didn't take "it's a refactor" on faith. I diffed every symbol at the **\*AST level\*** (original `db.py` vs the merged `db/` modules), and after stripping docstrings, **\*all 33 symbols are executable-identical\*** except two, both of which I verified by hand:

- **\*The 4 `list\_` per-bank functions\*** were refactored to share a new `\_JOIN\_STATUS` constant. The f-string reconstructs **\*byte-identical SQL\*** ? same `JOIN documents d ON d.id = t.document\_id ORDER BY t.id DESC LIMIT ?`, same `(limit,)` binding. No result change.
- **\*`\_SCHEMA`\*** differs by exactly one thing: a 2-line `--` SQL comment was removed. SQLite ignores `--` comments, so **\*the DDL is semantically identical\*** ? same tables, columns, constraints.

Everything else ? `encrypt\_database`, `rekey\_database`, `backup\_database`, `connect`, `connect\_encrypted`, `\_open\_encrypted`, key validation, all CRUD ? is **\*byte-faithful\*** (only docstrings/comments changed).

**\*Public surface intact:\*** `db/\_\_init\_\_.py` re-exports all 26 public names **\*plus\*** `EncryptedDatabaseError`, so `from muneem import db as dbmod; dbmod.X` keeps working ? including the `dbmod.EncryptedDatabaseError` that `cli/db.py` and `cli/\_shared.py` catch. Private symbols (`\_SCHEMA`, `\_open\_encrypted`, ?) are correctly **\*not\*** re-exported; the **\*two\*** test edits are exactly the right, minimal follow-through ? patch `\_open\_encrypted` at its new home `muneem.db.connection`, import `\_SCHEMA` from `muneem.db.schema`. No test was weakened. No non-test code references a now-private internal.

**\*CI is fully green now\*** ? Windows 3.13 finished passing (2m10s) while I was reviewing; that's the job that exercises the sqlcipher3 wheel + crypto tests. Full gate covered (ruff/format/mypy/478 tests/cov ?80%) on Ubuntu 3.11/3.12/3.13 + Windows.

### Non-blocking notes (for a follow-up, not a blocker)

1. **\*The PR says "pure split" but also bundles editorial trims.\*** Several **\*security-rationale comments\*** were dropped from the crypto/connection code ? e.g. `\_raw\_key\_pragma`'s **\*"MUST be the first statement on the connection"**, `\_open\_encrypted`'s **\*"forces key verification"**, `encrypt\_database`'s destructive-step-ordering explanation, and `connect\_encrypted`'s rekey self-healing rationale. Behavior-neutral, but those comments documented **\*why the code is safe\***. For security-critical code I'd lean toward keeping them ? and keeping a "split" purely mechanical also makes it trivially reviewable.
2. **\*Doc nit:\*** the `db/\_\_init\_\_.py` docstring lists the module as `connect`, but it's actually `connection.py` ? ironic, since the PR body deliberately explains the `connection` naming.
3. **\*Trivial:\*** `migrations.py:9` prose still references `db.\_SCHEMA`, which no longer resolves at that path (it's `db.schema.\_SCHEMA` now). Doc-only.

**\*Bottom line:\*** safe to merge. The only thing I'd genuinely consider is restoring the security-rationale comments (#1), and that's fine as a later cleanup.

---

Want me to **\*post this on #82\*** (as an LGTM-with-notes)? And still open from before: should I **\*keep polling muneem for new PRs\*** ? if so, what cadence, and auto-post or surface here first?

### 139. user (2026-07-02T06:11:33.046Z)

please post it as a comment before merging and yes, pls poll on other PRs for the same repo and do a review for them

**140. assistant (2026-07-02T06:11:33.046Z)**

I'll post the #82 review now (before you merge), then check for any other open PRs and set up the recurring poll.

**141. assistant (2026-07-02T06:11:33.046Z)**

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr82-review.md
[/external_agent_tool_call]
```

**142. assistant (2026-07-02T06:11:33.046Z)**

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr82-review.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

**143. assistant (2026-07-02T06:11:33.047Z)**

```
[external_agent_tool_call: Bash]
description: Post #82 review comment
command: cd /c/Users/avidu/Projects/muneem && gh pr comment 82 --repo avidullu/muneem --body-
file "C:\Users\avidu\AppData\Local\Temp\pr82-review.md" 2>&1 && rm -f
"C:\Users\avidu\AppData\Local\Temp\pr82-review.md"
[/external_agent_tool_call]
```

**144. assistant (2026-07-02T06:11:33.047Z)**

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/82#issuecomment-4802266039
[/external_agent_tool_result]
```

**145. assistant (2026-07-02T06:11:33.047Z)**

```
[external_agent_tool_call: Bash]
description: List all open muneem PRs
command: echo "=== ALL open PRs on muneem ===" && gh pr list --repo avidullu/muneem --state open
--json number,title,author,headRefName,isDraft,createdAt --limit 50 2>&1
[/external_agent_tool_call]
```

**146. assistant (2026-07-02T06:11:33.047Z)**

```
[external_agent_tool_result]
=== ALL open PRs on muneem ===
[{"author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":"Avi"},"created
At":"2026-06-25T17:09:10Z","headRefName":"docs/archive-
roadmap","isDraft":false,"number":84,"title":"docs: archive stale ROADMAP §§ 4-6 (original Track
A/B plan)"}, {"author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":"Avi
"},"createdAt":"2026-06-25T17:06:10Z","headRefName":"feat/axis-cc-total-
due","isDraft":false,"number":83,"title":"feat: add total-due cross-check to Axis CC parser"}, {"
author":{"id":"MDQ6VXNlcjE2NzQ4Nzc=","is_bot":false,"login":"avidullu","name":"Avi"},"createdAt
":"2026-06-25T17:02:17Z","headRefName":"refactor/split-
db","isDraft":false,"number":82,"title":"refactor: split db.py (~590 lines) into db/
subpackage"}]
[/external_agent_tool_result]
```

**147. assistant (2026-07-02T06:11:33.047Z)**

#82 posted: [comment](https://github.com/avidullu/muneem/pull/82#issuecomment-4802266039). Two

more open PRs found ? **##83** (a **feature**: Axis CC total-due cross-check) and **##84** (docs: archive ROADMAP). **##83** is a behavior change, so it gets a full correctness review. Let me gather both.

#### 148. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_call: Bash]
description: Fetch #83 and #84 metadata, CI, files
command: cd /c/Users/avidu/Projects/muneem
for pr in 83 84; do
  echo "##### PR #$pr #####"
  gh pr view $pr --repo avidullu/muneem --json
number,title,additions,deletions,changedFiles,body,mergeable,baseRefName,headRefName 2>&1
  echo ""
  echo "--- CI ---"; gh pr checks $pr --repo avidullu/muneem 2>&1 | head -8
  echo "--- files ---"; gh pr diff $pr --repo avidullu/muneem --name-only 2>&1
  echo ""
done
[/external_agent_tool_call]
```

#### 149. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_result]
##### PR #83 #####
{"additions":81,"baseRefName":"main","body":"Adds a weak arithmetic verification to the Axis credit card parser, closing the validation gap identified in the code-health report.\n\n### Problem\nAxis CC statements have no running balance column, so the parser could never verify its output ? all rows persisted as `UNVERIFIED`. There was no arithmetic to catch a misread amount.\n\n### Solution\nExtract the printed `Total Amount Due` from the CC statement (regex over first 3 pages of text), then cross-check: `(debits) ? (credits) ? total_due` (within the standard half-paisa tolerance).\n\n- Match ? parse graduates to `RECONCILED` (trusted)\n- Mismatch ? stays `UNVERIFIED` (rows stored but flagged)\n- No total-due line ? stays `UNVERIFIED` (older format, backward-compatible)\n\n### Changes\n- `_TOTAL_DUE_RE` regex for Indian-currency total-due lines\n- `parse_axis_cc` returns 4-tuple: `(card_number, rows, bad_amounts, total_due)`\n- `parse_and_insert` performs the cross-check and sets confidence accordingly\n- Updated 3 existing tests for the 4-tuple signature\n- Added 2 new tests: match ? reconciled, mismatch ? unverified\n\n### Verification\n- ? ruff/mypy clean\n- ? 480 tests pass (+2 new)","changedFiles":3,"deletions":14,"headRefName":"feat/axis-cc-total-due","mergeable":"MERGEABLE","number":83,"title":"feat: add total-due cross-check to Axis CC parser"}
```

```
--- CI ---
test (ubuntu-latest, 3.11)      pass    37s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203684
test (ubuntu-latest, 3.12)      pass    48s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203719
test (ubuntu-latest, 3.13)      pass    38s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203739
test (windows-latest, 3.13)     pass    1m37s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203761
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28187222630/job/83492192250
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492204567
test (ubuntu-latest, 3.11)      pass    37s
https://github.com/avidullu/muneem/actions/runs/28187222630/job/83492168912
test (ubuntu-latest, 3.12)      pass    47s
https://github.com/avidullu/muneem/actions/runs/28187222630/job/83492168899
--- files ---
src/muneem/parsers/axis.py
tests/parsers/test_axis.py
tests/test_provenance.py
```

```
##### PR #84 #####
{"additions":104,"baseRefName":"main","body":"Archives the stale § 4-6 (Track A/B, Milestone C/D
```

plan) from ROADMAP.md to a new archive file.\n\n### Problem\nROADMAP.md had ~90 lines of  
 \"original 2026-05 plan, kept as history\" ? the old Track A/B and Milestone C/D build-order  
 diagram, milestone checkboxes, and generalize backlog. These predate the Phase table in § 0 and  
 were explicitly marked as historical. Keeping them inline added noise for readers who should be  
 looking at the live § 0 table.\n\n### Changes\n- \*\*New\*\*: `docs/archive/roadmap-2026-05.md` ?  
 the original 2026-05 plan preserved for reference\n- \*\*ROADMAP.md\*\*: §§ 4-6 replaced with a  
 short pointer to the archive\n\nFixes recommendation #8 from code-  
 health-2026-06-25.md.\", \"changedFiles\":2, \"deletions\":86, \"headRefName\":\"docs/archive-  
 roadmap\", \"mergeable\":\"MERGEABLE\", \"number\":84, \"title\":\"docs: archive stale ROADMAP §§ 4-6  
 (original Track A/B plan)\"}

--- CI ---

```
test (ubuntu-latest, 3.11)      pass    31s
https://github.com/avidullu/muneem/actions/runs/28187403664/job/83492798700
test (ubuntu-latest, 3.12)      pass    46s
https://github.com/avidullu/muneem/actions/runs/28187403664/job/83492798679
test (ubuntu-latest, 3.13)      pass    47s
https://github.com/avidullu/muneem/actions/runs/28187403664/job/83492798631
test (windows-latest, 3.13)     pass    1m20s
https://github.com/avidullu/muneem/actions/runs/28187403664/job/83492798716
ocr      skipping              0
https://github.com/avidullu/muneem/actions/runs/28187403664/job/83492799716
test (ubuntu-latest, 3.11)      pass    36s      https://github.com/avidullu/muneem/action...
[/external_agent_tool_result]
```

#### 150. assistant (2026-07-02T06:11:33.047Z)

Both are green. **#84** is docs (archive move ? I'll verify content faithfulness). **#83** is a  
 real feature touching money arithmetic in a parser ? that needs a careful correctness review.  
 Let me dig into #83's diff and the parser context, and check #84's move faithfulness in  
 parallel.

#### 151. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_call: Bash]
description: Full diff of PR #83
command: echo "=== PR #83 FULL DIFF ===" && gh pr diff 83 --repo avidullu/muneem 2>&1
[/external_agent_tool_call]
```

#### 152. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_result]
=== PR #83 FULL DIFF ===
diff --git a/src/muneem/parsers/axis.py b/src/muneem/parsers/axis.py
index ab9d68b..11455b5 100644
--- a/src/muneem/parsers/axis.py
+++ b/src/muneem/parsers/axis.py
@@ -32,6 +32,14 @@
 _CC_DATE_RE = re.compile(r"\d{2}/\d{2}/\d{4}") # Axis credit card: dd/mm/yyyy
 _CARD_RES = [re.compile(r"(\d{4}XXXX\d{4})"), re.compile(r"(\d{6}*\d{4})")]
+# Axis CC statements print the total amount due in forms like:
+#   Total Amount Due           12,345.67
+#   Total Amount Due (Rs.)     12,345.67
+#   Total Payment Due          12,345.67 Cr
+_TOTAL_DUE_RE = re.compile(
+    r"Total\s+(?:Amount|Payment)\s+Due\s+(?:\s*(\s*\d{0,2})\s*)",
+    re.IGNORECASE,
+)

def _first_match(text: str, patterns: list[re.Pattern]) -> str | None:
@@ -160,19 +168,33 @@ def _rows_from_cc_tables(tables: list) -> tuple[list[AxisCCTxn], int]:
    return rows, bad_amounts
```



```

-def parse_axis_cc(pdf_path: Path, password: str | None = None) -> tuple[str, list[AxisCCTxn],
int]:
-     """Open an Axis credit-card statement; return (card_number, transactions, bad_amounts)."""
+def parse_axis_cc(
+     pdf_path: Path, password: str | None = None
+) -> tuple[str, list[AxisCCTxn], int, float | None]:
+     """Open an Axis credit-card statement.
+
+     Returns ``(card_number, transactions, bad_amounts, total_due)``.
+     ``total_due`` is the printed "Total Amount Due" from the statement,
+     extracted via regex from the first few pages. It is ``None`` if the
+     regex couldn't find it (older format, or a statement that doesn't use
+     that phrasing). The caller can cross-check it against the sum of
+     extracted transaction amounts for a weak arithmetic verification.
+     """
+     card_number = "UNKNOWN"
+     rows: list[AxisCCTxn] = []
+     bad_amounts = 0
+     total_due: float | None = None
+     with pdfplumber.open(pdf_path, password=password) as pdf:
+         head = "\n".join((pdf.pages[i].extract_text() or "") for i in range(min(3,
len(pdf.pages))))
+         card_number = _first_match(head, _CARD_RES) or "UNKNOWN"
+         m = _TOTAL_DUE_RE.search(head)
+         if m:
+             total_due = parse_amount(m.group(1).replace(",", ""))
+         for page in pdf.pages:
+             page_rows, page_bad = _rows_from_cc_tables(page.extract_tables())
+             rows.extend(page_rows)
+             bad_amounts += page_bad
-     return card_number, rows, bad_amounts
+     return card_number, rows, bad_amounts, total_due

@register_parser
@@ -183,16 +205,19 @@ def can_handle(self, text: str, sender: str | None = None, subject: str |
None =
    def parse_and_insert(
        self, pdf_path: Path, conn: sqlite3.Connection, doc_id: int, password: str | None =
None
    ) -> int:
-     """Persist CC rows with an explicit ``unverified`` verdict ? never as silently fine.
+     """Persist CC rows; cross-check against the printed total-due when available.
+
+     A credit-card bill has no running balance, so no full arithmetic oracle can endorse
+     the parse. But if the statement prints a "Total Amount Due", we sum the extracted
+     debits/credits and compare: if the net matches the printed total (within tolerance),
+     the parse graduates to RECONCILED. Without a total-due line (older formats), rows
+     persist as UNVERIFIED ? surfaced by listings but never silently trusted.
+
-     A credit-card bill has no running balance, so no arithmetic oracle can endorse the
-     parse (Confidence.UNVERIFIED, surfaced by every listing). What CAN be checked is
-     checked: a transactional row whose amount cell does not parse means the layout read
-     is suspect ? the parse is quarantined (store nothing, ``unreconciled``) rather than
-     persisting a wrong amount the math could never catch.
+     A transactional row whose amount cell does not parse means the layout read is suspect
+     ? the entire parse is quarantined (store nothing, UNRECONCILED).
+     """
+     try:
-         ca...
[/external_agent_tool_result]

```

### 153. assistant (2026-07-02T06:11:33.047Z)

#83 is safe by design (it only \*upgrades\* trust on an exact arithmetic match), but it's money-

parsing logic, so let me verify my concerns precisely before writing them up: test the regex against its own three documented formats (esp. the "Cr" credit-balance case), check `BALANCE\_TOLERANCE`, and confirm the `validation` import situation. Plus verify #84's archive move is loss-free.

#### 154. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_call: Bash]
description: Inspect axis.py imports, AxisCCTxn, BALANCE_TOLERANCE
command: cd /c/Users/avidu/Projects/muneem
echo "=== axis.py top imports + AxisCCTxn ==="
git show origin/feat/axis-cc-total-due:src/muneem/parsers/axis.py | sed -n '1,32p' | grep -nE
"import|AxisCCTxn|validation"
echo ""
echo "=== AxisCCTxn dataclass def ==="
git show origin/feat/axis-cc-total-due:src/muneem/parsers/axis.py | grep -nA8 "class AxisCCTxn"
echo ""
echo "=== BALANCE_TOLERANCE value ==="
grep -rn "BALANCE_TOLERANCE" src/muneem/parsers/validation.py
echo ""
echo "=== is 'validation' imported at axis.py module level? ==="
git show origin/feat/axis-cc-total-due:src/muneem/parsers/axis.py | grep -nE
"^from|^import|import validation|from .validation" | head
[/external_agent_tool_call]
```

#### 155. assistant (2026-07-02T06:11:33.047Z)

```
[external_agent_tool_result]
=== axis.py top imports + AxisCCTxn ===
12:from __future__ import annotations
14:import re
15:import sqlite3
16:from dataclasses import dataclass
17:from pathlib import Path
19:import pdfplumber
21:from muneem import __version__
22:from muneem import db as dbmod
23:from muneem.errors import ParseError
24:from muneem.redaction import redact_filename
26:from . import register_parser
27:from .base import StatementParser
28:from .dates import normalize_statement_date
29:from .profiles import AXIS_PROFILE
30:from .savings import SavingsParse, parse_savings, parse_statement_summary, txn_line_predicate
31:from .validation import Confidence, parse_amount

=== AxisCCTxn dataclass def ===
128:class AxisCCTxn:
129-     txn_date: str
130-     particulars: str
131-     merchant_category: str
132-     amount: float
133-     type: str # "Cr" or "Dr"
134-
135-
136-def _rows_from_cc_tables(tables: list) -> tuple[list[AxisCCTxn], int]:

=== BALANCE_TOLERANCE value ===
39: BALANCE_TOLERANCE = 0.005
91:     tol: float = BALANCE_TOLERANCE,
129:     rows: Sequence[ConceptRow], opening: float, closing: float, tol: float =
BALANCE_TOLERANCE
184:     rows: Sequence[ConceptRow], concepts: StatementConcepts, tol: float = BALANCE_TOLERANCE
215:     candidates: Sequence[Sequence[ConceptRow]], tol: float = BALANCE_TOLERANCE
234:     "BALANCE_TOLERANCE",
```



```

REMOVED                ?
REMOVED                Milestone C ? HDFC vertical slice (CONVERGENCE)
REMOVED                unlock (hybrid passwords) ? HDFC parser ? transactions ? CLI
REMOVED                ? completes DESIGN.md § 7
REMOVED                ?
REMOVED                ?
REMOVED                Milestone D ? Harden & evaluate (the pre-generalize checkpoint)
REMOVED                ?
REMOVED                ?
REMOVED                Generalize (more issuers, local-LLM fallback, holdings, items, analytics, UI)
REMOVED  ```
REMOVED
REMOVED  Tracks A and B are genuinely independent: A needs no OAuth and no secrets; B needs no
REMOVED  parsing. As a single developer you can interleave them in any order ? neither blocks the other.
REMOVED  **Both must land before Milestone C**, where a fetched-and-unlocked HDFC PDF flows through the
REMOVED  parser for the first time.
REMOVED
REMOVED  Effort tags below are rough (S / M / L), for relative sequencing only ? not calendar
REMOVED  estimates.
ADDED    ## 4?6. Original 2026-05 plan ? archived
REMOVED
REMOVED  ## 5. Milestones & tasks
REMOVED
REMOVED  ### ? Milestone 0 ? Decisions & scaffolding · DONE
REMOVED
REMOVED  - [x] **0.1 (S)** Project skeleton: `pyproject.toml` (uv), package dir (name TBD, e.g.
REMOVED  `muneem/`), `ruff` + `pytest` configured. *Do not over-materialize the source tree (DESIGN § 9)
REMOVED  ? create only what 0.x needs.*
REMOVED  - [x] **0.2 (S)** Offline CI: GitHub Actions (or local pre-commit) that installs deps
REMOVED  and runs `pytest` against committed data only. A trivial `test_smoke` proves the loop is green.
REMOVED  - [x] **0.3 (S)** Config + secrets foundation: a config loader (env + a gitignored
REMOVED  `config.toml`), and a `keyring`-backed secret accessor stub. Confirm `.gitignore` covers
REMOVED  `config.toml` and any new secret paths.
REMOVED  - [x] **0.4 (S)** `gitignore` audit: verify the proposed local-only dirs
REMOVED  (`testdata/statements/`, staging dir, `*.db`) are blocked. Add a
REMOVED  `testdata/statements/.gitkeep`-style note or README so the expected-but-absent dir is
REMOVED  documented.
REMOVED  - **Exit:** `uv run pytest` is green in CI on a clean checkout; repo layout agreed.
REMOVED
REMOVED  ### ? Track A ? Promo spine: parse ? store ? query · DONE (committed corpus, green in
REMOVED  CI)
REMOVED
REMOVED  > Resurrects the Email-Mining deals feature as muneem's first working output. Zero
REMOVED  secrets, zero OAuth.
REMOVED
REMOVED  - [x] **A.1 (M)** Port Email-Mining's extraction into a real module: **pdfminer.six**
REMOVED  text + **pypdfium2** image extraction (PyMuPDF is banned/AGPL), size filter, dedup. Proper
REMOVED  arguments/config; returns a value instead of one-shot stdout. *(Done ? `muneem.extract`.)*
REMOVED  - [x] **A.2 (S)** Minimal schema slice + migration v1: `documents` (id, source,
REMOVED  external_id, sender, subject, received_date, doc_type, sha256, path, status, created_at) and
REMOVED  `offers` (id...
REMOVED  [/external_agent_tool_result]

```

#### 158. assistant (2026-07-02T06:11:33.048Z)

Both verifications are conclusive. For #83 I confirmed empirically: the regex `**captures`12,345.67`` from the `"...Cr"` credit-balance line but silently drops the `"Cr"` ? so that documented case can never reconcile (safe direction, but the comment implies it's handled). And ``validation`` is already imported at module top (line 31), so the function-local ``BALANCE_TOLERANCE`` import is just inconsistent, not circular-dodging. Let me confirm #84's archive is loss-free before writing both up.

#### 159. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_call: Bash]
```

```

description: Verify #84 archive faithfulness and refs
command: cd /c/Users/avidu/Projects/muneem
echo "=== archive file headers present? (content faithfully moved) ==="
git show origin/docs/archive-roadmap:docs/archive/roadmap-2026-05.md | grep -nE "Build
order|Milestone 0|Track A|Track B|Milestones & tasks|Generalize backlog|Milestone C|Milestone D"
| head -20
echo ""
echo "=== archive file line count vs ROADMAP removed (~86) ==="
git show origin/docs/archive-roadmap:docs/archive/roadmap-2026-05.md | wc -l
echo ""
echo "=== ROADMAP.md pointer that replaced the sections ==="
git show origin/docs/archive-roadmap:docs/ROADMAP.md | grep -nA4
"archived\|roadmap-2026-05\|Original 2026-05"
echo ""
echo "=== any dangling inbound refs to the removed ROADMAP sections elsewhere in docs? ==="
grep -rnE "ROADMAP.*#\s*[4-6]|ROADMAP \$+\s*[4-6]|Track A|Track B|Milestone C|Milestone D" docs/
--include=*.md | grep -iv "archive/roadmap-2026-05" | head
[/external_agent_tool_call]

```

## 160. assistant (2026-07-02T06:11:33.048Z)

```

[external_agent_tool_result]
=== archive file headers present? (content faithfully moved) ===
1:# muneem ? Original 2026-05 Roadmap (Track A/B, Milestone C/D)
10:## Build order at a glance (original)
13:Milestone 0 ? Decisions & scaffolding (no sensitive data)
23:      Milestone C ? HDFC vertical slice (CONVERGENCE)
28:      Milestone D ? Harden & evaluate (the pre-generalize checkpoint)
34:Tracks A and B are genuinely independent: A needs no OAuth and no secrets; B needs no
parsing. As a single developer you can interleave them in any order ? neither blocks the other.
**Both must land before Milestone C**, where a fetched-and-unlocked HDFC PDF flows through the
parser for the first time.
40:## Milestones & tasks (original)
42:### ? Milestone 0 ? Decisions & scaffolding . DONE
50:### ? Track A ? Promo spine: parse ? store ? query . DONE (committed corpus, green in CI)
60:### Track B ? Gmail ingestion . PARTIAL (OAuth + search + download ?; `muneem fetch` B.4
pending)
71:### Milestone C ? HDFC vertical slice . IN PROGRESS (HDFC/Axis/AU parsers ?, unlock-wiring
C.1 ?; unified schema C.3 pending)
80:### Milestone D ? Harden & evaluate . the pre-generalize checkpoint

=== archive file line count vs ROADMAP removed (~86) ===
98

=== ROADMAP.md pointer that replaced the sections ===
133:## 4?6. Original 2026-05 plan ? archived
134-
135-The original Track A/B and Milestone C/D plan (build-order diagram, milestone
136-checkboxes, and generalize backlog) has been **moved to
137:[`docs/archive/roadmap-2026-05.md`](./archive/roadmap-2026-05.md)**. The live
138-plan is **$ 0 (Phases)** above ? it supersedes the old milestone letters, which
139-are unrelated to the current phase letters.
140-
141---

=== any dangling inbound refs to the removed ROADMAP sections elsewhere in docs? ===
docs/CURRENT_STATE.md:15:The ingestion pipeline supports a generic `SearchCriteria` interface
and multiple providers (Track B plumbing):
docs/feedback-antigravity-response.md:34:  `muneem fetch` (B.4) ships (ROADMAP Track B;
feedbackJune2026 P7).
docs/ROADMAP.md:14:> **Track A** (promo spine: `ingest` ? SQLite ? `offers list`, green
regression) ? are done.
docs/ROADMAP.md:15:> **Track B:** Gmail OAuth2 + search + attachment download ?; the `muneem
fetch` CLI (B.4) is not
docs/ROADMAP.md:28:> doc now defers here for status). Naming note: the **Track A/B** and

```

```
**Milestone C/D** sections
docs/ROADMAP.md:129:| LLM (promo only, non-sensitive) | deterministic-first; cloud LLM **only if
needed and approved** | See § 5 Track A. Sensitive-doc LLM is parked (§ 9 / DESIGN § 8.3). |
docs/ROADMAP.md:146:      Milestone C ? HDFC vertical slice (CONVERGENCE)
docs/ROADMAP.md:151:      Milestone D ? Harden & evaluate (the pre-generalize checkpoint)
docs/ROADMAP.md:157:Tracks A and B are genuinely independent: A needs no OAuth and no secrets; B
needs no parsing. As a single developer you can interleave them in any order ? neither blocks
the other. **Both must land before Milestone C**, where a fetched-and-unlocked HDFC PDF flows
through the parser for the first time.
docs/ROADMAP.md:173:### ? Track A ? Promo spine: parse ? store ? query · DONE (committed corpus,
green in CI)
[/external_agent_tool_result]
```

#### 161. assistant (2026-07-02T06:11:33.048Z)

The "dangling refs" hits at `ROADMAP.md:146-173` are from my **working tree** (checked out on a different branch), not PR #84 ? let me confirm against #84's branch directly that the old sections are actually gone (not duplicated), since that's the one real risk in an archive-move.

#### 162. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_call: Bash]
description: Confirm #84 removes old sections without duplication
command: cd /c/Users/avidu/Projects/muneem
echo "=== working tree is on branch: ===" && git branch --show-current
echo ""
echo "=== ON PR #84 BRANCH: does ROADMAP.md still contain the OLD sections (should be GONE)?
===
git show origin/docs/archive-roadmap:docs/ROADMAP.md | grep -nE "Build order at a
glance|Milestone C ? HDFC vertical|Track A ? Promo spine|Milestones & tasks" || echo ">>> NONE
found in ROADMAP on #84 branch ? sections fully moved, no duplication (good)"
echo ""
echo "=== ROADMAP.md total lines: base vs #84 branch ==="
MB=$(git merge-base origin/main origin/docs/archive-roadmap)
echo "base:   $(git show $MB:docs/ROADMAP.md | wc -l)"
echo "#84:    $(git show origin/docs/archive-roadmap:docs/ROADMAP.md | wc -l)"
[/external_agent_tool_call]
```

#### 163. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_result]
=== working tree is on branch: ===
refactor/split-db

=== ON PR #84 BRANCH: does ROADMAP.md still contain the OLD sections (should be GONE)? ===
>>> NONE found in ROADMAP on #84 branch ? sections fully moved, no duplication (good)

=== ROADMAP.md total lines: base vs #84 branch ===
base:   333
#84:    253
[/external_agent_tool_result]
```

#### 164. assistant (2026-07-02T06:11:33.048Z)

All verified. **#84** is a clean, loss-free archive move (ROADMAP ?80 lines, 98-line archive with every section header preserved, correct pointer link, no duplication). **#83** is a safe feature with four worth-noting items, two of them real (the dropped "Cr" sign + the untested regex). Let me write and post both reviews.

#### 165. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr84-review.md
[/external_agent_tool_call]
```

**166. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr84-review.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

**167. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr83-review.md
[/external_agent_tool_call]
```

**168. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr83-review.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

**169. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_call: Bash]
description: Post #83 and #84 review comments
command: cd /c/Users/avidu/Projects/muneem
gh pr comment 84 --repo avidullu/muneem --body-file
"C:\Users\avidu\AppData\Local\Temp\pr84-review.md" 2>&1
gh pr comment 83 --repo avidullu/muneem --body-file
"C:\Users\avidu\AppData\Local\Temp\pr83-review.md" 2>&1
rm -f "C:\Users\avidu\AppData\Local\Temp\pr83-review.md"
"C:\Users\avidu\AppData\Local\Temp\pr84-review.md"
[/external_agent_tool_call]
```

**170. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/84#issuecomment-4802303723
https://github.com/avidullu/muneem/pull/83#issuecomment-4802303902
[/external_agent_tool_result]
```

**171. assistant (2026-07-02T06:11:33.048Z)**

Both posted ([#84](https://github.com/avidullu/muneem/pull/84#issuecomment-4802303723),  
[#83](https://github.com/avidullu/muneem/pull/83#issuecomment-4802303902)). Now let me set up  
the recurring poll ? seed a state file of what I've already reviewed (by PR number + head  
commit, so re-pushes get re-reviewed) so the poll only acts on genuinely new work.

**172. assistant (2026-07-02T06:11:33.048Z)**

```
[external_agent_tool_call: Bash]
description: Seed the poll state file with reviewed PRs
command: cd /c/Users/avidu/Projects/muneem
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
echo "=== current open PRs with head SHAs ==="
gh pr list --repo avidullu/muneem --state open --json number,headRefOid,title 2>&1
echo ""
```

**Seed state: every currently-open PR has been reviewed by me as of now.**

```
gh pr list --repo avidullu/muneem --state open --json number,headRefOid --jq
'map({(.number|toString): .headRefOid}) | add' > "$STATE" 2>&1
echo "=== seeded state file ($STATE) ==="
cat "$STATE"
[/external_agent_tool_call]
```

### 173. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_result]
=== current open PRs with head SHAs ===
[{"headRefOid":"b5f11d3fd36ec9e7f2d4898c6473945d9abd7aad","number":84,"title":"docs: archive
stale ROADMAP §§ 4-6 (original Track A/B
plan)"}, {"headRefOid":"75d220ca73580bc9b3ade1cc254986960ef7de43","number":83,"title":"feat: add
total-due cross-check to Axis CC
parser"}, {"headRefOid":"8903ec75c46f2e6f195abebad95d70ceb3c56f86","number":82,"title":"refactor:
split db.py (~590 lines) into db/ subpackage"}]

=== seeded state file (C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json) ===
{"82":"8903ec75c46f2e6f195abebad95d70ceb3c56f86","83":"75d220ca73580bc9b3ade1cc254986960ef7de43"
,"84":"b5f11d3fd36ec9e7f2d4898c6473945d9abd7aad"}
[/external_agent_tool_result]
```

### 174. assistant (2026-07-02T06:11:33.048Z)

State seeded. Now I'll schedule the recurring poll.

### 175. assistant (2026-07-02T06:11:33.048Z)

```
[external_agent_tool_call: ScheduleWakeup]
input: {"delaySeconds":1200,"reason":"Polling muneem every 20 min for new/updated open PRs to
auto-review; 20 min balances responsiveness against cache cost, and the user can interrupt to
trigger a check sooner.","prompt":"[Recurring muneem PR-review poll ? set up 2026-06-25 at the
user's request: \"poll on other PRs for the same repo and do a review for them.\" ]\n\nPoll the
muneem repo for new or updated open PRs, review each, post the review as a PR comment, then
reschedule the next poll. Keep going until the user says to stop.\n\nSteps each wake:\n1. In
C:/Users/avidu/Projects/muneem run: git fetch origin -q (READ-ONLY; sibling sessions share
this checkout ? never commit, never switch branches; inspect everything via `git show
<ref>:<path>`).\n2. Read state file C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json ?
a JSON map {pr_number: last_reviewed_head_sha}. If missing, treat as {}.\n3. List open PRs: gh
pr list --repo avidullu/muneem --state open --json
number,headRefOid,title,headRefName,isDraft\n4. A PR needs review if state[number] is missing OR
!= its headRefOid (new PR, or new commits pushed since last review). Skip drafts.\n5. For each
PR needing review:\n    - Gather: gh pr view, gh pr checks (CI), gh pr diff. If CI is still
pending/running, note that and DON'T sign off this round ? leave it for the next poll (do not
mark state reviewed). If CI is RED, review and report the failure rather than signing off.\n    -
Review by type:\n        * Pure refactor/split ? prove semantic faithfulness: compare each moved
symbol against the pre-change original (git show <merge-base>:<path>) at the AST level (parse +
ast.dump, docstrings stripped, via the repo .venv python with cygpath-converted Windows paths);
confirm the public surface is fully re-exported and tests weren't weakened. Written LGTM only if
behavior is provably preserved AND CI green.\n        * Feature/behavior change ? correctness
review: logic, edge cases, money/sign handling, float vs tolerance, reg...
[/external_agent_tool_call]
```

### 176. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_result]
Next wakeup scheduled for 23:09:00 (in 1213s). Nothing more to do this turn ? the harness re-
invokes you when the wakeup fires or a task-notification arrives.
[/external_agent_tool_result]
```

### 177. assistant (2026-07-02T06:11:33.049Z)

All three open PRs reviewed and posted, and the poll is live.

## Reviews posted

| PR                                                | Type                | Verdict                                                                                                                                | Posted |
|---------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------|--------|
| ---- ----- ----- -----                            |                     |                                                                                                                                        |        |
| [#82](https://github.com/avidullu/muneem/pull/82) | refactor (db split) | **LGTM** ? AST-<br>verified faithful; 3 non-blocking notes (lost security-rationale comments,<br>'connect'/'connection' docstring nit) |        |



```
[comment](https://github.com/avidullu/muneem/pull/82#issuecomment-4802266039) |
| [#83](https://github.com/avidullu/muneem/pull/83) | feature (CC total-due check) | **Safe +
green, not blanket-LGTM** ? 4 notes; the two real ones: dropped "Cr" sign + untested regex |
[comment](https://github.com/avidullu/muneem/pull/83#issuecomment-4802303902) |
| [#84](https://github.com/avidullu/muneem/pull/84) | docs (archive ROADMAP) | **LGTM** ? loss-
free move, no duplication, valid link |
[comment](https://github.com/avidullu/muneem/pull/84#issuecomment-4802303723) |
```

The one I'd actually act on before/after merging is **#83**: the regex comment advertises a "Total Payment Due ? Cr" form, but the trailing `Cr` is dropped ? I confirmed empirically it captures `12,345.67` as positive, so genuine credit-balance statements can never reconcile (safe direction, but the comment over-promises). And the regex itself has zero direct tests. Both are easy follow-ups; nothing is unsafe.

## Polling is set up

- **Cadence**: every ~20 min, I re-check muneem for **open PRs** that are new or have new commits since I last reviewed them (tracked by PR number + head SHA in a state file, so a re-push gets re-reviewed).
- **What it does**: reviews by type (refactor ? AST-faithfulness; feature ? correctness, defer merge to you; docs ? faithfulness), **auto-posts** the review comment, and reschedules itself.
- **Guards**: it won't sign off while CI is pending/red, won't touch the shared checkout (read-only via `git show`), and stays quiet when there's nothing new.
- Next check fires ~23:09.

A few things worth confirming:

- **Auto-post is on**. The poll posts reviews without checking with you first (that's how I read "do a review for them"). Say the word if you'd rather it **surface here first** for your go-ahead.
- You can still just tell me "#85 is up" anytime to trigger an immediate review instead of waiting for the tick.
- To stop or change cadence, just say so. Note the poll runs while this session is alive ? if you want it to survive restarts, I can set it up as a scheduled cloud agent instead.

### 178. user (2026-07-02T06:11:33.049Z)

pls poll for the comments on the PRs as well. #82 has responses

### 179. assistant (2026-07-02T06:11:33.049Z)

Let me read #82's responses first, then wire comment-polling into the loop.

### 180. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_call: Bash]
description: Read all comments and review threads on #82
command: cd /c/Users/avidu/Projects/muneem
echo "=== #82 issue comments (chronological) ==="
gh pr view 82 --repo avidullu/muneem --json comments --jq '.comments[] | "--- \(.author.login) @
\(.createdAt) ---\n\(.body)\n"' 2>&1
echo ""
echo "=== #82 review threads (inline) ==="
gh api repos/avidullu/muneem/pulls/82/comments --jq '.[ ] | "--- \(.user.login) @
\(.path):\(.line) ---\n\(.body)\n"' 2>&1 | head -60
[/external_agent_tool_call]
```

### 181. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_result]
=== #82 issue comments (chronological) ===
--- avidullu @ 2026-06-25T17:13:00Z ---
```

## LGTM ? ? faithful split, behavior provably preserved (non-blocking notes below)

Since this moves crypto/key-handling code, I verified it at the AST level rather than taking

"it's a refactor" on faith ? diffed every symbol in the pre-split `db.py` against the merged `db/` modules. \*\*After stripping docstrings, all 33 symbols are executable-identical\*\* except two, both verified by hand:

- \*\*The 4 `list\_` per-bank functions\*\* now share a new `\_JOIN\_STATUS` constant. The f-string reconstructs \*\*byte-identical SQL\*\* ? same `JOIN` documents `d ON d.id = t.document_id ORDER BY t.id DESC LIMIT ?`, same `(limit,)` binding. No result change.
- \*\*`\_SCHEMA`\*\* differs by exactly one thing: a 2-line `--` SQL comment was removed. SQLite ignores `--` comments, so \*\*the DDL is semantically identical\*\* (same tables, columns, constraints).

Everything else ? `encrypt\_database`, `rekey\_database`, `backup\_database`, `connect`, `connect\_encrypted`, `\_open\_encrypted`, key validation, all CRUD ? is byte-faithful (only docstrings/comments changed).

**Public surface intact:** `db/\_\_init\_\_.py` re-exports all 26 public names \*\*plus `EncryptedDatabaseError`\*\*, so `from muneem import db as dbmod; dbmod.X` keeps working ?` including the `dbmod.EncryptedDatabaseError` caught in `cli/db.py` and `cli/_shared.py`. Private symbols stay in submodules, and the **two test edits are exactly the right minimal follow-through** (patch `_open_encrypted` at muneem.db.connection`, import `_SCHEMA` from muneem.db.schema`) ? no test weakened. No non-test code references a now-private internal.`

**CI fully green:** Ubuntu 3.11/3.12/3.13 + Windows 3.13 (the Windows job exercises the `sqlcipher3` wheel + crypto tests) ? ruff / format / mypy / 478 tests / cov ?80%.`

### Non-blocking notes (fine as a follow-up)

1. **This is described as a pure split but also bundles editorial trims** ? several **security-rationale comments** were dropped from the crypto/connection code: `_raw_key_pragma`'s "MUST be the first statement on the connection"`, `_open_encrypted`'s "forces key verification"`, `encrypt_database`'s destructive-step-ordering note`, `connect_encrypted`'s rekey self-healing rationale`, and the "mint a key only for a brand-new ledger" warning. Behavior-neutral, but those documented **why the code is safe**. For security-critical code I'd lean toward keeping them ? and keeping a split purely mechanical also makes it trivially reviewable.
2. **Doc nit:** the `db/__init__.py` docstring lists the module as `connect`, but it's actually `connection.py` (ironic, since the PR body deliberately explains the `connection` naming).`
3. **Trivial:** `migrations.py:9` prose still references `db._SCHEMA`, which no longer resolves at that path (now db.schema._SCHEMA`). Doc-only.`

Safe to merge. The only thing I'd genuinely consider is restoring the security-rationale comments (#1) in a later pass.

```
=== #82 review threads (inline) ===  
[/external_agent_tool_result]
```

### 182. assistant (2026-07-02T06:11:33.049Z)

Interesting ? the only comment I can see is my own review (gh is authed as `avidullu`, same as you). The responses must be in a different channel (a formal PR review, or inline line-comments, or they landed just now). Let me check all of them.

### 183. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_call: Bash]  
description: Check reviews, fresh comments, inline counts on #82  
command: cd /c/Users/avidu/Projects/muneem  
echo "=== formal PR reviews on #82 ==="  
gh api repos/avidullu/muneem/pulls/82/reviews --jq '.[ ] | "--- \(.user.login) [\(.state)] @  
\(.submitted_at) ---\n\(.body)\n"' 2>&1  
echo "=== ALL issue comments (count + bodies, freshly) ==="  
gh api repos/avidullu/muneem/issues/82/comments --jq '.[ ] | "--- \(.user.login) @ \(.created_at)  
---\n\(.body[0:400])\n"' 2>&1
```

```
echo "=== inline review comments (raw count) ==="
gh api repos/avidullu/muneem/pulls/82/comments --jq 'length' 2>&1
[/external_agent_tool_call]
```

#### 184. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_result]
=== formal PR reviews on #82 ===
=== ALL issue comments (count + bodies, freshly) ===
--- avidullu @ 2026-06-25T17:13:00Z ---
```

#### LGTM ?? faithful split, behavior provably preserved (non-blocking notes below)

Since this moves crypto/key-handling code, I verified it at the AST level rather than taking "it's a refactor" on faith ? diffed every symbol in the pre-split `db.py` against the merged `db/` modules. \*\*After stripping docstrings, all 33 symbols are executable-identical\*\* except two, both verified by hand:

- \*\*The

```
=== inline review comments (raw count) ===
0
[/external_agent_tool_result]
```

#### 185. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_call: Bash]
description: Check #82 timeline, merge state, and other PR comment counts
command: cd /c/Users/avidu/Projects/muneem
echo "=== #82 state (merged?) ==="
gh pr view 82 --repo avidullu/muneem --json state,mergedAt,closed,comments --jq
'{state,mergedAt,closed,nComments:(.comments|length)}' 2>&1
echo ""
echo "=== #82 timeline events (comments/reviews/edits) ==="
gh api repos/avidullu/muneem/issues/82/timeline --jq '.[ ] | "\(.event // .__typename) |
\(.actor.login // .user.login) | \(.created_at // .submitted_at) | \((.body // "")[0:120])"'
2>&1 | head -40
echo ""
echo "=== comment counts on #83 and #84 ==="
for pr in 83 84; do echo "$pr issue-comments: $(gh api
repos/avidullu/muneem/issues/$pr/comments --jq 'length' 2>&1) inline: $(gh api
repos/avidullu/muneem/pulls/$pr/comments --jq 'length' 2>&1)"; done
[/external_agent_tool_call]
```

#### 186. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_result]
=== #82 state (merged?) ===
{"closed":false,"mergedAt":null,"nComments":1,"state":"OPEN"}

=== #82 timeline events (comments/reviews/edits) ===
committed | null | null |
commented | avidullu | 2026-06-25T17:13:00Z | ## LGTM ?? faithful split, behavior provably
preserved (non-blocking notes below)
```

Since this moves crypto/key-handling

```
committed | null | null |
```

```
=== comment counts on #83 and #84 ===
#83 issue-comments: 1 inline: 0
#84 issue-comments: 1 inline: 0
[/external_agent_tool_result]
```

#### 187. assistant (2026-07-02T06:11:33.049Z)

Let me confirm who `gh` is and whether #82 changed in any other way, then reseed state for comment-tracking.

#### 188. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_call: Bash]
description: Confirm gh identity, #82 head, reseed comment-tracking state
command: cd /c/Users/avidu/Projects/muneem
echo "gh identity: $(gh api user --jq .login 2>&1)"
echo "#82 current head: $(gh pr view 82 --repo avidullu/muneem --json headRefOid --jq
.headRefOid 2>&1) (seeded: 8903ec75c46f2e6f195abebad95d70ceb3c56f86)"
echo ""
echo "=== reseed state v2: {head, last_comment_ts} per open PR ==="
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
python_seed() {
python - "$@" <<'PY'
import json, subprocess, sys
prs = json.loads(subprocess.check_output(["gh", "pr", "list", "--repo", "avidullu/muneem", "--
state", "open", "--json", "number,headRefOid"]))
state={}
for pr in prs:
    n=str(pr["number"])
ic=json.loads(subprocess.check_output(["gh", "api", f"repos/avidullu/muneem/issues/{n}/comments", "
--jq", "[.[] .created_at]")) or "[]")
rv=json.loads(subprocess.check_output(["gh", "api", f"repos/avidullu/muneem/pulls/{n}/reviews", "--
jq", "[.[] .submitted_at]")) or "[]")
    ts=sorted([t for t in ic+rv if t])
    state[n]={"head":pr["headRefOid"],"last_comment_ts":ts[-1] if ts else
"1970-01-01T00:00:00Z"}
print(json.dumps(state,indent=2))
PY
}
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" - <<'PY' > "$STATE"
import json, subprocess
prs = json.loads(subprocess.check_output(["gh", "pr", "list", "--repo", "avidullu/muneem", "--
state", "open", "--json", "number,headRefOid"]))
state={}
for pr in prs:
    n=str(pr["number"])
ic=json.loads(subprocess.check_output(["gh", "api", f"repos/avidullu/muneem/issues/{n}/comments", "
--jq", "[.[] .created_at]")) or "[]")
rv=json.loads(subprocess.check_output(["gh", "api", f"repos/avidullu/muneem/pulls/{n}/reviews", "--
jq", "[.[] .submitted_at]")) or "[]")
    ts=sorted([t for t in ic+rv if t])
    state[n]={"head":pr["headRefOid"],"last_comment_ts":ts[-1] if ts else
"1970-01-01T00:00:00Z"}
print(json.dumps(state,indent=2))
PY
cat "$STATE"
[/external_agent_tool_call]
```

#### 189. assistant (2026-07-02T06:11:33.049Z)

```
[external_agent_tool_result]
gh identity: avidullu
#82 current head: 8903ec75c46f2e6f195abebad95d70ceb3c56f86 (seeded:
8903ec75c46f2e6f195abebad95d70ceb3c56f86)

=== reseed state v2: {head, last_comment_ts} per open PR ===
{
  "84": {
    "head": "b5f11d3fd36ec9e7f2d4898c6473945d9abd7aad",
    "last_comment_ts": "2026-06-25T17:17:55Z"
  },
}
```

```
"83": {
  "head": "75d220ca73580bc9b3ade1cc254986960ef7de43",
  "last_comment_ts": "2026-06-25T17:17:57Z"
},
"82": {
  "head": "8903ec75c46f2e6f195abebad95d70ceb3c56f86",
  "last_comment_ts": "2026-06-25T17:20:09Z"
}
}
[/external_agent_tool_result]
```

**190. assistant (2026-07-02T06:11:33.049Z)**

No response requested.

**191. user (2026-07-02T06:11:33.049Z)**

can you complete the review of the PRs?

**192. assistant (2026-07-02T06:11:33.050Z)**

Let me do a fresh comprehensive sweep of all open muneem PRs ? new ones, new commits, and any responses on the ones I've reviewed.

**193. assistant (2026-07-02T06:11:33.050Z)**

```
[external_agent_tool_call: Bash]
description: Fresh sweep of open PRs and comment counts
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
echo "=== saved state ===" && cat "$STATE" 2>/dev/null || echo "{}"
echo ""
echo "=== open PRs now (number, head, title, updatedAt) ==="
gh pr list --repo avidullu/muneem --state open --json number,headRefOid,title,isDraft,updatedAt
--jq 'sort_by(.number) | .[] | "#\(.number) draft=\(.isDraft) head=\(.headRefOid[0:8])
upd=\(.updatedAt) \(.title)'" 2>&1
echo ""
echo "=== per-PR comment/review/inline counts + latest non-bot timestamps ==="
for pr in $(gh pr list --repo avidullu/muneem --state open --json number --jq '.[].number'
2>/dev/null); do
  ic=$(gh api repos/avidullu/muneem/issues/$pr/comments --jq 'length' 2>/dev/null)
  rv=$(gh api repos/avidullu/muneem/pulls/$pr/reviews --jq 'length' 2>/dev/null)
  il=$(gh api repos/avidullu/muneem/pulls/$pr/comments --jq 'length' 2>/dev/null)
  echo "#$pr issue-comments=$ic reviews=$rv inline=$il"
done
[/external_agent_tool_call]
```

**194. assistant (2026-07-02T06:11:33.050Z)**

```
[external_agent_tool_result]
=== saved state ===
{
  "84": {
    "head": "b5f11d3fd36ec9e7f2d4898c6473945d9abd7aad",
    "last_comment_ts": "2026-06-25T17:17:55Z"
  },
  "83": {
    "head": "75d220ca73580bc9b3ade1cc254986960ef7de43",
    "last_comment_ts": "2026-06-25T17:17:57Z"
  },
  "82": {
    "head": "8903ec75c46f2e6f195abebad95d70ceb3c56f86",
    "last_comment_ts": "2026-06-25T17:20:09Z"
  }
}
```



rationale comments\*\* were dropped from the crypto/connection code: `\_raw\_key\_pragma`'s **"MUST be the first statement on the connection"**, `\_open\_encrypted`'s **"forces key verification"**, `encrypt\_database`'s destructive-step-ordering note, `connect\_encrypted`'s rekey self-healing rationale, and the "mint a key only for a brand-new ledger" warning. Behavior-neutral, but those documented **\*why the code is safe\***. For security-critical code I'd lean toward keeping them ? and keeping a split purely mechanical also makes it trivially reviewable.

2. **\*\*Doc nit:\*\*** the `db/\_\_init\_\_.py` docstring lists the module as `connect`, but it's actually `connection.py` (ironic, since the PR body deliberately explains the `connection` naming).
3. **\*\*Trivial:\*\*** `migrations.py:9` prose still references `db.\_SCHEMA`, which no longer resolves at that path (now `db.schema.\_SCHEMA`). Doc-only.

Safe to merge. The only thing I'd genuinely consider is restoring the security-rationale comments (#1) in a later pass.

==== avidullu @ 2026-06-25T17:20:09Z (id 4802320302) =====

All three review notes addressed in 8903ec7:

1. **\*\*Security-rationale comments restored\*\*** ? `\_validate\_raw\_key` (raw-key?KDF switch warning), `is\_plaintext\_sqlite` (refuse-to-mistreat rationale), `\_open\_encrypted` (no-downgrade guarantee), inline **MUST-be-first/forces-verification**, `connect\_encrypted` (mint-key-only-for-new-ledger), and `connect` (full encrypted-at-rest docstring).
2. **\*\*`\_\_init\_\_.py` doc nit\*\*** ? module listing fixed: `connect` ? `connection`.
3. **\*\*migrations.py prose\*\*** ? `db.\_SCHEMA` ? `db.schema.\_SCHEMA`.

ruff/mypy clean, 478 tests pass. Ready for you.  
[/external\_agent\_tool\_result]

#### 198. assistant (2026-07-02T06:11:33.050Z)

The author responded on #82 (17:20): says all three notes were addressed in commit `8903ec7` and it's "ready for you." But that's the **\*\*same short SHA my review was based on\*\*** ? so I need to verify against the live tree whether the fixes are actually present (a force-push could have reused my view of the head). Let me check the three fixes directly and re-confirm behavior is still preserved.

#### 199. assistant (2026-07-02T06:11:33.050Z)

```
[external_agent_tool_call: Bash]
description: Verify the 3 claimed fixes at current head
command: git fetch origin -q
echo "=== current head of refactor/split-db ==="
git rev-parse origin/refactor/split-db
echo ""
echo "=== commit log (did a fix commit land?) ==="
git log --oneline -3 origin/refactor/split-db
echo ""
echo "=== FIX 2: __init__.py docstring ? connect vs connection? ==="
git show origin/refactor/split-db:src/muneem/db/__init__.py | grep -nE "connect|connection" |
head
echo ""
echo "=== FIX 3: migrations.py:9 ? db._SCHEMA vs db.schema._SCHEMA? ==="
git show origin/refactor/split-db:src/muneem/migrations.py | sed -n '9p'
echo ""
echo "=== FIX 1: security-rationale comments restored in connection.py? ==="
git show origin/refactor/split-db:src/muneem/db/connection.py | grep -nE "MUST be the
first|forces key verification|raw-key mode to passphrase|never silently downgrade|silently
switch SQLCipher|KDF" | head
[/external_agent_tool_call]
```

#### 200. assistant (2026-07-02T06:11:33.050Z)

```
[external_agent_tool_result]
=== current head of refactor/split-db ===
8903ec75c46f2e6f195abebad95d70ceb3c56f86

=== commit log (did a fix commit land?) ===
8903ec7 fix: address PR #82 review ? restore security comments, fix docs
fca3bd7 refactor: split db.py (~590 lines) into db/ subpackage
ec12b59 fix: address PR #80 post-merge review comments (#81)

=== FIX 2: __init__.py docstring ? connect vs connection? ===
6:- ``connection`` ? key helpers, plaintext/encrypted connections
10:All public names are re-exported here, so ``from muneem.db import connect_encrypted``
14:from muneem.db.connection import ( # noqa: F401
15:    connect,
16:    connect_encrypted,

=== FIX 3: migrations.py:9 ? db._SCHEMA vs db.schema._SCHEMA? ===
- **Baseline.** The current schema (``db.schema._SCHEMA``, version ``db.SCHEMA_VERSION``)

=== FIX 1: security-rationale comments restored in connection.py? ===
22: Anything else would either silently switch SQLCipher from raw-key mode to passphrase-KDF
35: """The SQLCipher raw-key PRAGMA: use the 256-bit key (64 hex chars) directly, no KDF."""
76: conn.execute(_raw_key_pragma(key)) # MUST be the first statement on the connection
78: conn.execute("SELECT count(*) FROM sqlite_master") # forces key verification
[/external_agent_tool_result]
```

## 201. assistant (2026-07-02T06:11:33.050Z)

Mystery solved ? the history shows a **new commit landed**: `8903ec7` "fix: address PR #82 review ? restore security comments, fix docs" on top of the `fca3bd7` split I originally reviewed. My state seed captured the post-fix head, so the poll never flagged it ? I owe a review of that fix commit. All three fixes are visibly present. Now the key check: confirm the fix commit changed **only** comments/docstrings/prose and didn't perturb any executable logic.

## 202. assistant (2026-07-02T06:11:33.050Z)

```
[external_agent_tool_call: Bash]
description: Verify fix commit is comment-only + CI green
command: cd /c/Users/avidu/Projects/muneem
echo "=== fix commit touched which files? ==="
git diff --stat fca3bd7 8903ec7
echo ""
echo "=== executable-AST diff: fca3bd7 db/ vs 8903ec7 db/ (docstrings stripped) ? should be EMPTY ==="
DIR=$(mktemp -d)
for c in fca3bd7 8903ec7; do mkdir -p "$DIR/$c"; for m in __init__ schema connection crypto queries; do git show $c:src/muneem/db/$m.py > "$DIR/$c/$m.py" 2>/dev/null; done; done
cat > "$DIR/cmp.py" <<'PY'
import ast,os,sys
A,B=sys.argv[1],sys.argv[2]
def strip(n):
    if n.body and isinstance(n.body[0],ast.Expr) and
isinstance(getattr(n.body[0],'value',None),ast.Constant) and
isinstance(n.body[0].value.value,str): n.body=n.body[1:]
    return n
def col(d):
    out={}
    for m in ['__init__', 'schema', 'connection', 'crypto', 'queries']:
        p=os.path.join(d,m+'.py')
        if not os.path.exists(p): continue
        for n in ast.parse(open(p,encoding='utf-8').read()).body:
            if isinstance(n,(ast.FunctionDef,ast.AsyncFunctionDef,ast.ClassDef)):
out[n.name]=ast.dump(strip(n))
            elif isinstance(n,ast.Assign):
                for t in n.targets:
```



```

        if isinstance(t,ast.Name) and t.id!='_log': out[t.id]=ast.dump(n.value)
    return out
a,b=col(A),col(B)
diff=[k for k in set(a)|set(b) if a.get(k)!=b.get(k)]
print("executable symbols differing between the two commits:", sorted(diff) or "NONE ? fix
commit is comment/docstring-only")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w "$DIR/cmp.py")" "$(cygpath -w "$DIR/fca3bd7")" "$(cygpath -w
"$DIR/8903ec7")"
echo ""
echo "=== CI on current head 8903ec7 ==="
gh pr checks 82 --repo avidullu/muneem 2>&1 | head -6
[/external_agent_tool_call]

```

### 203. assistant (2026-07-02T06:11:33.050Z)

```

[external_agent_tool_result]
=== fix commit touched which files? ===
src/muneem/db/__init__.py | 2 +-
src/muneem/db/connection.py | 33 ++++++-----
src/muneem/migrations.py | 3 +-
3 files changed, 29 insertions(+), 9 deletions(-)

=== executable-AST diff: fca3bd7 db/ vs 8903ec7 db/ (docstrings stripped) ? should be EMPTY ===
executable symbols differing between the two commits: NONE ? fix commit is comment/docstring-
only

=== CI on current head 8903ec7 ===
ocr      skipping      0
https://github.com/avidullu/muneem/actions/runs/28187773269/job/83494110217
test (ubuntu-latest, 3.11)      pass      33s
https://github.com/avidullu/muneem/actions/runs/28187770831/job/83494075453
test (ubuntu-latest, 3.11)      pass      35s
https://github.com/avidullu/muneem/actions/runs/28187773269/job/83494084741
test (ubuntu-latest, 3.12)      pass      52s
https://github.com/avidullu/muneem/actions/runs/28187770831/job/83494075439
test (ubuntu-latest, 3.12)      pass      50s
https://github.com/avidullu/muneem/actions/runs/28187773269/job/83494084765
test (ubuntu-latest, 3.13)      pass      43s
https://github.com/avidullu/muneem/actions/runs/28187770831/job/83494075536
[/external_agent_tool_result]

```

### 204. assistant (2026-07-02T06:11:33.050Z)

Fully verified: the fix commit `8903ec7` touched only `\_\_init\_\_.py`, `connection.py`, and `migrations.py`, and the executable-AST diff against the original split is **\*\*NONE\*\*** ? it's comment/docstring-only, zero logic change. By transitivity with my original review, the PR at current head is still provably behavior-faithful to the pre-split `db.py`. Let me confirm Windows CI on this head, then post the verification.

### 205. assistant (2026-07-02T06:11:33.050Z)

```

[external_agent_tool_call: Bash]
description: Confirm Windows CI green and restored comment anchors
command: cd /c/Users/avidu/Projects/muneem
echo "=== Windows CI on #82 current head ==="
gh pr checks 82 --repo avidullu/muneem 2>&1 | grep -i windows | head -3
echo ""
echo "=== sanity: all 3 restored security-comment anchors present in connection.py ==="
git show origin/refactor/split-db:src/muneem/db/connection.py | grep -cE "MUST be the
first|forces key verification|raw-key mode to passphrase|never silently|downgrade|mint"
echo "(count of restored rationale anchors)"
[/external_agent_tool_call]

```

#### 206. assistant (2026-07-02T06:11:33.050Z)

```
[external_agent_tool_result]
=== Windows CI on #82 current head ===
test (windows-latest, 3.13)      pass      1m55s
https://github.com/avidullu/muneem/actions/runs/28187770831/job/83494075449
test (windows-latest, 3.13)      pass      1m20s
https://github.com/avidullu/muneem/actions/runs/28187773269/job/83494084758

=== sanity: all 3 restored security-comment anchors present in connection.py ===
7
(count of restored rationale anchors)
[/external_agent_tool_result]
```

#### 207. assistant (2026-07-02T06:11:33.050Z)

Everything checks out ? Windows CI green, 7 rationale anchors restored. Let me post the verification on #82 and update tracking.

#### 208. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr82-followup.md
[/external_agent_tool_call]
```

#### 209. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr82-followup.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

#### 210. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_call: Bash]
description: Post #82 follow-up and advance comment-tracking state
command: cd /c/Users/avidu/Projects/muneem
gh pr comment 82 --repo avidullu/muneem --body-file
"C:\Users\avidu\AppData\Local\Temp\pr82-followup.md" 2>&1
rm -f "C:\Users\avidu\AppData\Local\Temp\pr82-followup.md"
echo ""
echo "=== update state: #82 reviewed-head + advance last_comment_ts past my follow-up ==="
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" - <<'PY'
import json, subprocess
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
st=json.load(open(STATE))
```

**advance #82 last\_comment\_ts to the newest comment now (my follow-up), keep head**

```
for n in ["82", "83", "84"]:
ic=json.loads(subprocess.check_output(["gh", "api", f"repos/avidullu/muneem/issues/{n}/comments", "
--jq", "[.[]].created_at"])] or [])
    if n in st and ic: st[n]["last_comment_ts"]=sorted(ic)[-1]
json.dump(st, open(STATE, "w"), indent=2)
print(open(STATE).read())
PY
[/external_agent_tool_call]
```

#### 211. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/82#issuecomment-4802438806
```

=== update state: #82 reviewed-head + advance last\_comment\_ts past my follow-up ===

```
{
  "84": {
    "head": "b5f11d3fd36ec9e7f2d4898c6473945d9abd7aad",
    "last_comment_ts": "2026-06-25T17:17:55Z"
  },
  "83": {
    "head": "75d220ca73580bc9b3ade1cc254986960ef7de43",
    "last_comment_ts": "2026-06-25T17:17:57Z"
  },
  "82": {
    "head": "8903ec75c46f2e6f195abebad95d70ceb3c56f86",
    "last_comment_ts": "2026-06-25T17:33:58Z"
  }
}
[/external_agent_tool_result]
```

#### 212. assistant (2026-07-02T06:11:33.051Z)

Posted: [#82 follow-up](https://github.com/avidullu/muneem/pull/82#issuecomment-4802438806). Now let me upgrade the recurring poll to also watch for author responses (your explicit ask), since the previous version only watched for new PRs.

#### 213. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_call: ScheduleWakeup]
input: {"delaySeconds":1200,"reason":"Polling muneem every 20 min for new/updated PRs AND new
author responses on reviewed PRs (verify fix-commits, answer questions); user can interrupt to
trigger sooner.","prompt":"Recurring muneem PR-review + comment poll ? set up 2026-06-25 at the
user's request: \"poll on other PRs for the same repo and do a review for them\" + \"poll for
the comments on the PRs as well.\""}\n\nPoll the muneem repo for (A) new/updated open PRs and (B)
new author responses on PRs I've already reviewed. Review/engage, post as PR comments, then
reschedule. Keep going until the user says to stop.\n\nState file:
C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json ? JSON map {pr_number: {\"head\":
<last_reviewed_head_sha>, \"last_comment_ts\": <ISO ts of newest comment I've already
handled>}}. If missing, treat as {}. \n\nIDENTITY NOTE: gh is authed as `avidullu`, the SAME
account as the PR author/user. So I cannot tell my own posted comments from the author's by
login. Disambiguate two ways: (1) every comment I post ends with the HTML marker `<!-- claude-
review-bot -->`; treat any comment WITHOUT that marker as a human/author message. (2) Only
consider comments with created_at > the PR's stored last_comment_ts. A comment is \"a response
to engage with\" iff it is newer than last_comment_ts AND lacks my marker. \n\nEach wake:\n1. In
C:/Users/avidu/Projects/muneem: git fetch origin -q (READ-ONLY ? sibling sessions share this
checkout; never commit, never switch branches; inspect via `git show <ref>:<path>`). \n2. Read
the state file. \n3. gh pr list --repo avidullu/muneem --state open --json
number,headRefOid,title,headRefName,isDraft (skip drafts). \n\n(A) NEW / UPDATED PRs ? for each
open PR where state[n] is missing OR state[n].head != headRefOid:\n    - Gather gh pr view + gh
pr checks (CI) + gh pr diff. If CI is pending/running, don't sign off this round (leave state
unchanged so it's retried). If CI is RED, review and report the failure instead of...
[/external_agent_tool_call]
```

#### 214. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_result]
Next wakeup scheduled for 23:26:00 (in 1220s). Nothing more to do this turn ? the harness re-
invokes you when the wakeup fires or a task-notification arrives.
[/external_agent_tool_result]
```

#### 215. assistant (2026-07-02T06:11:33.051Z)

Done ? and the "#82 has responses" is fully resolved.

### What the responses were

The author pushed a \*\*new commit `8903ec7` ("fix: address PR #82 review")\*\* on top of the split I originally reviewed (`fca3bd7`) and commented that all three notes were addressed. My poll

missed it because I'd seeded state with the post-fix head ? exactly the gap you flagged by asking me to watch comments too.

## Re-review of the fix commit (posted: [#82 follow-up])(<https://github.com/avidullu/muneem/pull/82#issuecomment>)

Verified all three, and that the fix is behavior-safe:

- ? **Security-rationale comments restored** (7 anchors back in `connection.py` ? KDF-switch warning, MUST-be-first, forces-verification, no-downgrade, mint-key-only, encrypted-at-rest docstring)
- ? **`\_\_init\_\_.py` docstring** ? `connection` (not `connect`)
- ? **migrations.py:9** ? `db.schema.\_SCHEMA`
- ? **Zero executable change** ? docstring-stripped AST diff between `fca3bd7` and `8903ec7` is empty; it's pure comment/docstring restoration, so the PR stays byte-faithful to the pre-split `db.py`
- ? **CI green on `8903ec7`** incl. Windows

? Clean LGTM, ready to merge. Nothing left on my side.

## Poll upgraded to watch comments

The recurring poll (every ~20 min) now does **both**:

1. **New/updated PRs** ? review by type.
2. **Author responses on reviewed PRs** ? engage: if a reply says "addressed in `

To handle the fact that `gh` and you are the **same `avidullu` account**, I tag every comment I post with a hidden `

The design is the right shape: the cross-check only \*upgrades\* a CC parse to `RECONCILED` when `?(Dr) ? ?(Cr)` matches the printed total-due within half a paisa; a mismatch or a missing total-due line stays `UNVERIFIED`, and unparseable amounts still quarantine the whole parse. So there's **no false-trust risk** ? the worst case is under-trusting a correct parse. Float arithmetic is fine here (tolerance `0.005` ? accumulation error) and consistent with the savings parsers. CI is green (480 tests, ruff/mypy) on Ubuntu 3.11/3.12/3.13 + Windows.

Four things to consider ? none are blockers, but the first two are worth doing:

### 1. The "Cr" (credit-balance) case is documented but not actually handled

The regex comment lists `Total Payment Due 12,345.67 Cr` as a supported form, but the trailing `Cr` is dropped ? I verified `\_TOTAL\_DUE\_RE` captures `12,345.67` (positive) and ignores the `Cr`. So when the customer has a **credit balance** (overpaid; true due is negative), `total\_due` is stored as `+12345.67` while the actual net is ? `?12345.67` ? the cross-check can **never** match ? the statement silently stays `UNVERIFIED`. Safe direction, but the comment implies it's handled. Either negate `total\_due` when a trailing `Cr`/`CR` is present, or drop that example from the comment so it doesn't over-promise.

### 2. `\_TOTAL\_DUE\_RE` has no direct test

All five tests monkeypatch `parse\_axis\_cc` to return a fixed 4-tuple, so they exercise the cross-check arithmetic in `parse\_and\_insert` ? but the **regex itself is never asserted**, and it's the fragile part (three formats, the `Cr` case, number-on-next-line, "Minimum Amount Due" vs "Total Amount Due" disambiguation). A handful of direct `\_TOTAL\_DUE\_RE` cases would lock in the documented formats ? and would have surfaced #1.

### 3. Worth a one-line note: the check assumes no carried-over balance

`?(Dr) ? ?(Cr)` equals "Total Amount Due" only when there's **no uncaptured previous/opening balance**. A revolving balance (carried from last cycle) makes the net legitimately differ from the printed total, so a correctly-parsed statement stays `UNVERIFIED`. That's fine by design, but a comment naming the limitation would stop a future reader from "fixing" it as a bug.

### 4. Minor: hoist the `BALANCE\_TOLERANCE` import

`from .validation import BALANCE\_TOLERANCE` is imported inside `parse\_and\_insert`, but `validation` is already imported at module top (line 31: `from .validation import Confidence, parse\_amount`). No circular-import reason ? just add `BALANCE\_TOLERANCE` to that existing line for consistency.

Safe to merge as-is; I'd fold in #1 + #2 either here or as a quick follow-up.

==== avidullu @ 2026-06-25T17:38:51Z (id 4802475958) ====  
All four review notes addressed in e5ace4e:

1. **Cr case handled** ? `\_TOTAL\_DUE\_RE` now captures the optional `Cr` suffix (group 2); `parse\_axis\_cc` negates `total\_due` when it's present. Credit-balance statements can now graduate to RECONCILED.
2. **Direct regex tests** ? 5 new tests for `\_TOTAL\_DUE\_RE`: plain number, (Rs.) variant, Payment Due variant, Cr suffix capture, and negative (no-match on Minimum/other lines). These would have caught #1.
3. **Carried-over balance comment** ? added inline note in `parse\_and\_insert` documenting that `?(Dr)??(Cr)` = total only without a revolving balance; legitimate mismatch stays UNVERIFIED by design.
4. **Import hoisted** ? `BALANCE\_TOLERANCE` moved to module-level import alongside `Confidence`/`parse\_amount`.

485 tests pass, ruff/mypy clean. Ready for re-review.

=== #83 reviews + inline ===  
=== #83 current head vs my reviewed head (75d220ca) ===  
{"head": "75d220ca73580bc9b3ade1cc254986960ef7de43", "state": "OPEN"}  
[/external\_agent\_tool\_result]

## 219. assistant (2026-07-02T06:11:33.051Z)

The author says #83's four notes were addressed in commit `e5ace4e` ? but the PR head is still `75d220ca` (what I reviewed), **\*\*not\*\*** `e5ace4e`. Same shape as #82, except here the head didn't move. Let me check whether `e5ace4e` was actually pushed to the PR branch.

## 220. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_call: Bash]
description: Determine whether e5ace4e was pushed to the PR branch
command: git fetch origin -q
echo "=== git's view of the PR branch head ==="
git rev-parse origin/feat/axis-cc-total-due 2>&1
echo ""
echo "=== does commit e5ace4e exist anywhere we can see? ==="
git cat-file -t e5ace4e 2>&1 || echo ">>> e5ace4e NOT found in local object store"
echo ""
echo "=== branch tip log ==="
git log --oneline -3 origin/feat/axis-cc-total-due 2>&1
echo ""
echo "=== which remote branches (if any) contain e5ace4e? ==="
git branch -r --contains e5ace4e 2>&1 || echo ">>> none / unknown commit"
echo ""
echo "=== search ALL remote refs for the fix commit message ==="
git log --all --oneline --grep="address.*#83\|total.due\|Cr suffix\|e5ace4e" 2>&1 | head -10
[/external_agent_tool_call]
```

## 221. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_result]
=== git's view of the PR branch head ===
e5ace4eabca904f1bc6eed690be5cedeb88b10245

=== does commit e5ace4e exist anywhere we can see? ===
commit

=== branch tip log ===
e5ace4e fix: address PR #83 review ? Cr handling, regex tests, balance note, import hoist
75d220c feat: add total-due cross-check to Axis CC parser
ec12b59 fix: address PR #80 post-merge review comments (#81)

=== which remote branches (if any) contain e5ace4e? ===
origin/feat/axis-cc-total-due

=== search ALL remote refs for the fix commit message ===
e5ace4e fix: address PR #83 review ? Cr handling, regex tests, balance note, import hoist
75d220c feat: add total-due cross-check to Axis CC parser
3ab48ff fix(parsers): Axis CC floor -- explicit "unverified" verdict, no silent 0.0 amounts
(#59)
[/external_agent_tool_result]
```

## 222. assistant (2026-07-02T06:11:33.051Z)

`gh pr view` was stale ? git (post-fetch) shows the PR head **\*\*is\*\*** `e5ace4e` ("fix: address PR #83 review ? Cr handling, regex tests, balance note, import hoist"). So the fix was pushed. This one changes parsing *\*logic\** (Cr negation), so it needs a real correctness re-review, not just presence checks. Let me get the fix-commit diff.

## 223. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_call: Bash]
description: Show #83 fix-commit diff for axis.py + CI
command: cd /c/Users/avidu/Projects/muneem
echo "=== fix commit diff: 75d220c -> e5ace4e ==="
```

```
git diff 75d220c e5ace4e -- src/muneem/parsers/axis.py
echo ""
echo "=== CI on e5ace4e ==="
gh pr checks 83 --repo avidullu/muneem 2>&1 | grep -vE "skipping" | head -6
[/external_agent_tool_call]
```

## 224. assistant (2026-07-02T06:11:33.051Z)

```
[external_agent_tool_result]
=== fix commit diff: 75d220c -> e5ace4e ===
diff --git a/src/muneem/parsers/axis.py b/src/muneem/parsers/axis.py
index 11455b5..ba6aa76 100644
--- a/src/muneem/parsers/axis.py
+++ b/src/muneem/parsers/axis.py
@@ -28,16 +28,18 @@ from .base import StatementParser
     from .dates import normalize_statement_date
     from .profiles import AXIS_PROFILE
     from .savings import SavingsParse, parse_savings, parse_statement_summary, txn_line_predicate
-    from .validation import Confidence, parse_amount
+    from .validation import Confidence, parse_amount

_CC_DATE_RE = re.compile(r"\d{2}/\d{2}/\d{4}") # Axis credit card: dd/mm/yyyy
_CARD_RES = [re.compile(r"(\d{4}XXXX\d{4})"), re.compile(r"(\d{6}*\d{4})")]
# Axis CC statements print the total amount due in forms like:
#   Total Amount Due           12,345.67
#   Total Amount Due (Rs.)     12,345.67
-#   Total Payment Due         12,345.67 Cr
+#   Total Payment Due         12,345.67
+# Cr/Debit suffixes (if any) are captured separately for sign handling.
_TOTAL_DUE_RE = re.compile(
-    r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s*(Rs\.\d{2}))?\s*([\d,]+\.\d{0,2})",
+    r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s*(Rs\.\d{2}))?\s*"
+    r"([\d,]+\.\d{0,2})\s*(Cr)?",
    re.IGNORECASE,
)

@@ -189,7 +191,14 @@ def parse_axis_cc(
    card_number = _first_match(head, _CARD_RES) or "UNKNOWN"
    m = _TOTAL_DUE_RE.search(head)
    if m:
-        total_due = parse_amount(m.group(1).replace(",", ""))
+        raw = m.group(1).replace(",", "")
+        total_due = parse_amount(raw)
+        # A trailing "Cr" means the customer has a credit balance
+        # (overpaid); the real net is negative. Without the negation
+        # the cross-check would never match ? safe, but the parse
+        # would silently stay UNVERIFIED.
+        if total_due is not None and m.group(2):
+            total_due = -total_due
    for page in pdf.pages:
        page_rows, page_bad = _rows_from_cc_tables(page.extract_tables())
        rows.extend(page_rows)

@@ -235,11 +244,13 @@ class AxisCreditCardParser(StatementParser):
    return 0

    # Cross-check against the printed total-due when available.
+    # Note: (Dr) ? (Cr) equals "Total Amount Due" only when there is
+    # no uncaptured carried-over/revolving balance from a prior cycle.
+    # When that assumption doesn't hold (legitimate mismatch), the parse
+    # stays UNVERIFIED ? correct by design, not a bug.
    confidence = Confidence.UNVERIFIED
    if total_due is not None:
        net = sum(r.amount if r.type == "Dr" else -r.amount for r in rows)
-        from .validation import BALANCE_TOLERANCE
-

```

```
if abs(net - total_due) <= BALANCE_TOLERANCE:
    confidence = Confidence.RECONCILED
```

=== CI on e5ace4e ===

```
test (ubuntu-latest, 3.11)      pass    37s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203684
test (ubuntu-latest, 3.12)      pass    48s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203719
test (ubuntu-latest, 3.13)      pass    38s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203739
test (windows-latest, 3.13)     pass    1m37s
https://github.com/avidullu/muneem/actions/runs/28187232776/job/83492203761
test (ubuntu-latest, 3.11)      pass    37s
https://github.com/avidullu/muneem/actions/runs/28187222630/job/83492168912
test (ubuntu-latest, 3.12)      pass    47s
https://github.com/avidullu/muneem/actions/runs/28187222630/job/83492168899
[/external_agent_tool_result]
```

## 225. assistant (2026-07-02T06:11:33.052Z)

The code fix looks correct on inspection ? but I need three things before signing off: the **\*\*regex test additions\*\*** (note #2), an empirical check of the **\*\*new regex\*\*** (esp. the ``(Cr)?`` group under IGNORECASE), and confirmation that **\*\*CI actually ran green on `e5ace4e`\*\*** (gh's view was lagging). Let me get all three.

## 226. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_call: Bash]
description: Show #83 fix-commit test diff
command: cd /c/Users/avidu/Projects/muneem
echo "=== test diff (regex tests for note #2) ==="
git diff 75d220c e5ace4e -- tests/ | head -120
[/external_agent_tool_call]
```

## 227. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_result]
=== test diff (regex tests for note #2) ===
diff --git a/tests/parsers/test_axis.py b/tests/parsers/test_axis.py
index 77bfb82..3ed22ad 100644
--- a/tests/parsers/test_axis.py
+++ b/tests/parsers/test_axis.py
@@ -200,3 +200,31 @@ def test_cc_total_due_cross_check_stays_unverified_on_mismatch(tmp_path,
monkeyp
    )
    assert n == 1 and len(stored) == 1
    assert status == "unverified" # rows stored but not trusted
+
+
+## --- _TOTAL_DUE_RE direct tests -----
+
+
+def test_total_due_re_plain_number():
+    m = axis._TOTAL_DUE_RE.search("Total Amount Due          12,345.67")
+    assert m and m.group(1) == "12,345.67" and m.group(2) is None
+
+
+def test_total_due_re_with_rs_parens():
+    m = axis._TOTAL_DUE_RE.search("Total Amount Due (Rs.)      12,345.67")
+    assert m and m.group(1) == "12,345.67"
+
+
+def test_total_due_re_payment_due_variant():
```



```

+ m = axis._TOTAL_DUE_RE.search("Total Payment Due          1,234.56")
+ assert m and m.group(1) == "1,234.56"
+
+
+def test_total_due_re_with_cr_suffix():
+ m = axis._TOTAL_DUE_RE.search("Total Payment Due          1,234.56 Cr")
+ assert m and m.group(1) == "1,234.56" and m.group(2) == "Cr"
+
+
+def test_total_due_re_no_match_on_other_lines():
+ assert axis._TOTAL_DUE_RE.search("Minimum Amount Due          500.00") is None
+ assert axis._TOTAL_DUE_RE.search("Credit Limit              100,000") is None
[/external_agent_tool_result]

```

## 228. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_call: Bash]
description: Test new regex + verify CI on e5ace4e
command: cd /c/Users/avidu/Projects/muneem
echo "=== empirical: new regex behavior ==="
cat > /tmp/re2.py <<'PY'
import re
R =
re.compile(r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s*(?:\s*\.\s*))?\s*([\d,]+\.\d{0,2})\s*(Cr)?",
re.IGNORECASE)
def amt(raw, g2):
    v=float(raw.replace(",","")); return -v if g2 else v
for c in [
    "Total Amount Due          12,345.67",
    "Total Amount Due (Rs.)    12,345.67",
    "Total Payment Due        12,345.67 Cr",
    "Total Amount Due          12,345.67 Credit Balance", # IGNORECASE over-match risk
    "Minimum Amount Due 500.00", # must NOT match
    "Total Amount Due\n8,000.00\nMinimum Amount Due 500.00",
]:
    m=R.search(c)
    if m: print(f"{c[:42]!r:46} g1={m.group(1)!r:12} g2={m.group(2)!r:6} ->
{amt(m.group(1),m.group(2))}")
    else: print(f"{c[:42]!r:46} NO MATCH")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w /tmp/re2.py)"
echo ""
echo "=== CI status for commit e5ace4e specifically (check-runs) ==="
gh api repos/avidullu/muneem/commits/e5ace4e/check-runs --jq '.check_runs[] | "\(.name):
\(.status)/\(.conclusion)"' 2>&1 | sort -u
[/external_agent_tool_call]

```

## 229. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_result]
=== empirical: new regex behavior ===
'Total Amount Due          12,345.67'          g1='12,345.67' g2=None -> 12345.67
'Total Amount Due (Rs.)    12,345.67'          g1='12,345.67' g2=None -> 12345.67
'Total Payment Due        12,345.67 Cr'        g1='12,345.67' g2='Cr' -> -12345.67
'Total Amount Due          12,345.67 Credit'    g1='12,345.67' g2='Cr' -> -12345.67
'Minimum Amount Due 500.00'                      NO MATCH
'Total Amount Due\n8,000.00\nMinimum Amount D' g1='8,000.00' g2=None -> 8000.0

=== CI status for commit e5ace4e specifically (check-runs) ===
[/external_agent_tool_result]

```

## 230. assistant (2026-07-02T06:11:33.052Z)

Found something important. Let me nail down two things: a likely **regression** in the new `(Cr)?` group<sup>2</sup>, and whether CI has actually reported on `e5ace4e` (gh's view is lagging).

### 231. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_call: Bash]
description: Confirm Cr over-match regression and CI state on e5ace4e
command: cd /c/Users/avidu/Projects/muneem
echo "=== does the (Cr)? overmatch real CC fields? + does \b fix it? ==="
cat > /tmp/re3.py <<'PY'
import re
cur = re.compile(r"...s*([d,]+\.?d{0,2})s*(Cr)?" .replace("...", "Total\s+(?:Amount|Payment)\s+Due"), re.IGNORECASE)
fix =
re.compile(r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s(Rs\.?))?\s*([d,]+\.?d{0,2})s*(Cr\b)?",
re.IGNORECASE)
```

## realistic Axis CC summary-box text: Credit Limit sits right under Total Amount Due

```
real = "Total Amount Due\n12,345.67\nCredit Limit\n2,00,000.00"
for name,R in [("CURRENT",cur),("WITH \b",fix)]:
    m=R.search(real)
    g2=m.group(2) if m else None
    val=float(m.group(1).replace(",",""))*(-1 if g2 else 1) if m else None
    print(f"{name:10} g2={g2!r:6} total_due={val} <- should be +12345.67")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" "$(cygpath -w /tmp/re3.py)"
echo ""
echo "=== CI: workflow runs whose head is e5ace4e ==="
gh run list --repo avidullu/muneem --branch feat/axis-cc-total-due --limit 10 --json
headSha,status,conclusion,workflowName,createdAt --jq '.[] |
select(.headSha|startswith("e5ace4e")) | "\(.workflowName): \(.status)/\(.conclusion) @
\(.createdAt)"' 2>&1
echo "--- (if empty above, no run has e5ace4e as head yet) ---"
echo "check-runs total_count for e5ace4e: $(gh api repos/avidullu/muneem/commits/e5ace4e/check-
runs --jq '.total_count' 2>&1)"
[/external_agent_tool_call]
```

### 232. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_result]
=== does the (Cr)? overmatch real CC fields? + does \b fix it? ===
C:\Users\avidu\AppData\Local\Temp\re3.py:2: SyntaxWarning: invalid escape sequence '\s'
  cur = re.compile(r"...s*([d,]+\.?d{0,2})s*(Cr)?" .replace("...", "Total\s+(?:Amount|Payment)\s+Due"), re.IGNORECASE)
CURRENT   g2='Cr'    total_due=-12345.67 <- should be +12345.67
WITH ■    g2=None    total_due=12345.67 <- should be +12345.67

=== CI: workflow runs whose head is e5ace4e ===
--- (if empty above, no run has e5ace4e as head yet) ---
check-runs total_count for e5ace4e: 0
[/external_agent_tool_result]
```

### 233. assistant (2026-07-02T06:11:33.052Z)

Both confirmed <sup>2</sup> and this is a real catch. Let me write up the re-review.

The new `(Cr)?` group is a **regression**: under `IGNORECASE` with no word boundary, it matches the "Cr" in **"Credit"**. On a realistic summary-box layout where "Credit Limit" follows the total-due in the extracted text (`Total Amount Due\n12,345.67\nCredit Limit\n2,00,000`), it captures `g2='Cr'` and **negates** a normal positive balance to <sup>2</sup>12,345.67<sup>2</sup> ? cross-check fails ? stays **UNVERIFIED**. The original commit handled this case correctly. Adding `\b`(`Cr\b`)` fixes it (verified). Also: **CI** has not run on `e5ace4e` (check-runs count = 0; the green checks gh shows are from the prior commit).

#### 234. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_call: Write]
file: C:\Users\avidu\AppData\Local\Temp\pr83-rereview.md
[/external_agent_tool_call]
```

#### 235. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_result]
File created successfully at: C:\Users\avidu\AppData\Local\Temp\pr83-rereview.md (file state is
current in your context ? no need to Read it back)
[/external_agent_tool_result]
```

#### 236. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_call: Bash]
description: Post #83 re-review and update state
command: cd /c/Users/avidu/Projects/muneem
gh pr comment 83 --repo avidullu/muneem --body-file
"C:\Users\avidu\AppData\Local\Temp\pr83-rereview.md" 2>&1
rm -f "C:\Users\avidu\AppData\Local\Temp\pr83-rereview.md"
echo ""
echo "=== update state: #83 head=e5ace4e (re-reviewed), advance last_comment_ts ==="
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" - <<'PY'
import json, subprocess
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
st=json.load(open(STATE))
head=subprocess.check_output(["git","rev-parse","origin/feat/axis-cc-total-
due"]).decode().strip()
ic=json.loads(subprocess.check_output(["gh","api","repos/avidullu/muneem/issues/83/comments","--
jq","[.[]].created_at"])) or "[]")
st["83"]={"head":head,"last_comment_ts":sorted(ic)[-1] if ic else st["83"]["last_comment_ts"]}
json.dump(st,open(STATE,"w"),indent=2)
print(json.dumps(st["83"],indent=2))
PY
[/external_agent_tool_call]
```

#### 237. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/83#issuecomment-4802521424

=== update state: #83 head=e5ace4e (re-reviewed), advance last_comment_ts ===
{
  "head": "8306ba8987f23dea28caf54560f3cfa69dab2241",
  "last_comment_ts": "2026-06-25T17:43:30Z"
}
[/external_agent_tool_result]
```

#### 238. assistant (2026-07-02T06:11:33.052Z)

The head moved **\*\*again\*\*** while I was reviewing ? `git rev-parse` now shows `8306ba8`, not `e5ace4e`. The author is pushing rapidly. I may have just re-reviewed a stale commit. Let me check what `8306ba8` is before anything else.

#### 239. assistant (2026-07-02T06:11:33.052Z)

```
[external_agent_tool_call: Bash]
description: Inspect new commit 8306ba8 and timing vs my re-review
command: git fetch origin -q
echo "=== branch log now ==="
git log --oneline -4 origin/feat/axis-cc-total-due
```

```

echo ""
echo "=== what did 8306ba8 change vs e5ace4e? ==="
git diff e5ace4e 8306ba8 -- src/muneem/parsers/axis.py
echo ""
echo "=== timing: when was my re-review vs the new commit? ==="
echo "my re-review comment (4802521424) created_at:"
gh api repos/avidullu/muneem/issues/comments/4802521424 --jq .created_at 2>&1
echo "8306ba8 commit time:"
git show -s --format=%cI 8306ba8 2>&1
[/external_agent_tool_call]

```

#### 240. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_result]
=== branch log now ===
8306ba8 test: add credit-balance cross-check + no-Cr regex tests
e5ace4e fix: address PR #83 review ? Cr handling, regex tests, balance note, import hoist
75d220c feat: add total-due cross-check to Axis CC parser
ec12b59 fix: address PR #80 post-merge review comments (#81)

=== what did 8306ba8 change vs e5ace4e? ===

=== timing: when was my re-review vs the new commit? ===
my re-review comment (4802521424) created_at:
2026-06-25T17:43:30Z
8306ba8 commit time:
2026-06-25T23:12:35+05:30
[/external_agent_tool_result]

```

#### 241. assistant (2026-07-02T06:11:33.052Z)

`8306ba8` is "test: add credit-balance cross-check + no-Cr regex tests" ? and crucially the `axis.py` diff vs `e5ace4e` is **\*\*empty\*\***, so the regex source is unchanged: my Cr over-match finding still stands. It landed ~1 min before my re-review (author iterating independently, not yet reacting to my comment). Let me see exactly what tests it added ? whether they catch or miss the "Credit Limit" case.

#### 242. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_call: Bash]
description: Show 8306ba8 test additions and CI
command: cd /c/Users/avidu/Projects/muneem
echo "=== files touched by 8306ba8 ==="
git show --stat --oneline 8306ba8 | head
echo ""
echo "=== test additions in 8306ba8 ==="
git diff e5ace4e 8306ba8 -- tests/
echo ""
echo "=== CI on 8306ba8 ==="
echo "check-runs total_count: $(gh api repos/avidullu/muneem/commits/8306ba8/check-runs --jq
'.total_count' 2>&1)"
gh api repos/avidullu/muneem/commits/8306ba8/check-runs --jq '.check_runs[] | "\(.name):
\(.status)/\(.conclusion)"' 2>&1 | sort -u
[/external_agent_tool_call]

```

#### 243. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_result]
=== files touched by 8306ba8 ===
8306ba8 test: add credit-balance cross-check + no-Cr regex tests
  tests/parsers/test_axis.py | 22 +++++
1 file changed, 22 insertions(+)

=== test additions in 8306ba8 ===

```

```

diff --git a/tests/parsers/test_axis.py b/tests/parsers/test_axis.py
index 3ed22ad..4fafd8d 100644
--- a/tests/parsers/test_axis.py
+++ b/tests/parsers/test_axis.py
@@ -228,3 +228,25 @@ def test_total_due_re_with_cr_suffix():
     def test_total_due_re_no_match_on_other_lines():
         assert axis._TOTAL_DUE_RE.search("Minimum Amount Due          500.00") is None
         assert axis._TOTAL_DUE_RE.search("Credit Limit              100,000") is None
+
+
+def test_total_due_re_without_cr_suffix():
+    """Normal (debit-balance) case: no trailing Cr."""
+    m = axis._TOTAL_DUE_RE.search("Total Amount Due          5,000.00")
+    assert m and m.group(1) == "5,000.00" and m.group(2) is None
+
+
+def test_cc_total_due_cross_check_credit_balance_reconciles(tmp_path, monkeypatch):
+    """When the customer has a credit balance (overpaid), the Cr suffix produces
+    a negative total_due. The cross-check should match the net."""
+    txns = [
+        axis.AxisCCTxn("01/03/2026", "Payment", "Payment", 500.0, "Cr"),
+        axis.AxisCCTxn("02/03/2026", "Refund", "Refund", 100.0, "Cr"),
+    ]
+    # Net: ?500 ? 100 = ?600. Printed total = 600 Cr ? total_due = ?600
+    n, status, stored, prov = _cc_parse_and_insert(
+        tmp_path, monkeypatch, ("CARD1", txns, 0, -600.0)
+    )
+    assert n == 2 and len(stored) == 2
+    assert status == "reconciled"
+    assert prov["confidence"] == "reconciled"
+
+
+=== CI on 8306ba8 ===
+check-runs total_count: 5
+ocr: completed/skipped
+test (ubuntu-latest, 3.11): in_progress/null
+test (ubuntu-latest, 3.12): completed/success
+test (ubuntu-latest, 3.13): completed/success
+test (windows-latest, 3.13): in_progress/null
+[/external_agent_tool_result]

```

#### 244. assistant (2026-07-02T06:11:33.052Z)

`8306ba8` is **test-only** (axis.py byte-identical to `e5ace4e`), so my Cr over-match finding still stands ? and crucially, the two tests it adds (`test\_total\_due\_re\_without\_cr\_suffix` feeds a clean string; the credit-balance test passes a pre-negated `?600`) **don't** exercise the "Credit Limit" adjacency\*\* that triggers the bug. CI is now running on `8306ba8` (Ubuntu 3.12/3.13 green, 3.11 + Windows still going). Let me post a tight sync note so the author doesn't think the new Cr tests closed it.

#### 245. assistant (2026-07-02T06:11:33.052Z)

```

[external_agent_tool_call: Bash]
description: Post sync note on #83 and update state
command: cd /c/Users/avidu/Projects/muneem
cat > "C:/Users/avidu/AppData/Local/Temp/pr83-sync.md" <<'EOF'
Quick sync ? the branch moved to `8306ba8` ("test: add credit-balance cross-check + no-Cr regex tests") as I was posting. It's test-only (axis.py` is byte-identical to `e5ace4e`), so the `(Cr)?` over-match above is unchanged. Note the two new tests don't cover it:
`test_total_due_re_without_cr_suffix` feeds `Total Amount Due 5,000.00` (number at end-of-string, no following word), and `test_cc_total_due_cross_check_credit_balance_reconciles` passes a pre-negated `?600.0` straight into `parse_and_insert` ? neither runs `"?12,345.67\nCredit Limit?"` through `_TOTAL_DUE_RE`. So the `Cr\b` fix + the adjacency test are still the open item.

```

CI is now running on `8306ba8` (Ubuntu 3.12/3.13 green; 3.11 + Windows in progress) ? so

disregard the "hasn't run" line above; I'll confirm once it finishes.

```
<!-- claude-review-bot -->
EOF
gh pr comment 83 --repo avidullu/muneem --body-file
"C:/Users/avidu/AppData/Local/Temp/pr83-sync.md" 2>&1
rm -f "C:/Users/avidu/AppData/Local/Temp/pr83-sync.md"
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" - <<'PY'
import json, subprocess
STATE="C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json"
st=json.load(open(STATE))
ic=json.loads(subprocess.check_output(["gh","api","repos/avidullu/muneem/issues/83/comments","--jq","[.[].created_at]")) or "[]")
st["83"]["head"]=subprocess.check_output(["git","rev-parse","origin/feat/axis-cc-total-due"]).decode().strip()
st["83"]["last_comment_ts"]=sorted(ic)[-1] if ic else st["83"]["last_comment_ts"]
json.dump(st,open(STATE,"w"),indent=2)
print("state[83]:", json.dumps(st["83"]))
PY
[/external_agent_tool_call]
```

#### 246. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_result]
https://github.com/avidullu/muneem/pull/83#issuecomment-4802534849
state[83]: {"head": "8306ba8987f23dea28caf54560f3cfa69dab2241", "last_comment_ts":
"2026-06-25T17:45:06Z"}
[/external_agent_tool_result]
```

#### 247. assistant (2026-07-02T06:11:33.053Z)

Reviewed #83's comments and re-reviewed the work behind them. Here's the bottom line.

### The author responded "all four addressed in `e5ace4e`" ? I re-reviewed it

Three of the four are cleanly done: **regex tests** (#2), **carried-balance comment** (#3), and **BALANCE\_TOLERANCE` import hoist** (#4) ? all good.

But the **Cr-handling fix** (#1) introduced a regression, which I caught by running the new regex against realistic input:

- The new `(Cr)?`` group under `IGNORECASE`` with no word boundary matches the **"Cr"** in **"Credit"**. CC summary boxes almost always print **"Credit Limit"** next to **"Total Amount Due"**, and `\s*`` spans newlines ? so on a **normal positive-balance** statement (**Total Amount Due**  
12,345.67  
Credit Limit?) it captures `Cr`` from **"Credit"** and **negates the total to 12,345.67** ? cross-check fails ? stays **UNVERIFIED**. That's the exact case the feature is meant to reconcile, and the original commit handled it correctly ? so it's a regression.
- It's still **safe** (never falsely reconciles), but it silently defeats the feature for the common case.
- **One-char fix:** `(Cr\b)?`` ? verified it still catches a genuine `Cr`` but no longer matches **"Credit"**. I gave a suggested adjacency test too.

Then the author pushed **8306ba8` (test-only)** mid-review ? it adds credit-balance tests but feeds clean strings / a pre-negated total, so it **doesn't cover the over-match**; the finding stands.

### Status

- Posted: [re-review](https://github.com/avidullu/muneem/pull/83#issuecomment-4802521424) + a [sync note](https://github.com/avidullu/muneem/pull/83#issuecomment-4802534849) about the racing commit.
- **Holding sign-off** until the `Cr\b`` fix lands. CI is mid-run on **8306ba8`** (Ubuntu 3.12/3.13 green; 3.11 + Windows in progress).
- The poll is updated (**#83 head 8306ba8`**), so if the author pushes the fix, the next tick will

re-review automatically ? or just tell me and I'll check immediately.

One thing worth knowing: this branch is moving fast (three pushes in a few minutes), and `gh`'s API view lagged `git` twice today ? so I've been verifying head SHAs with `git rev-parse` after a fetch rather than trusting `gh pr view`. If you'd rather I batch re-reviews (wait for you to say "ready") instead of chasing each push, say the word.

#### 248. user (2026-07-02T06:11:33.053Z)

great catch! Can you again review the PR with a new commit. Be as thorough as you have been!

#### 249. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_call: Bash]
description: Fetch #83 new commits and any new comments
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q
echo "=== current head + recent log ==="
git rev-parse origin/feat/axis-cc-total-due
git log --oneline -5 origin/feat/axis-cc-total-due
echo ""
echo "=== my last-reviewed head (from state) ==="
cat "C:/Users/avidu/AppData/Local/Temp/muneem_review_state.json" 2>/dev/null | python -c "import
json,sys; print(json.load(sys.stdin)['83'])" 2>/dev/null || echo "(state unreadable)"
echo ""
echo "=== any new author comments since 17:45:06? ==="
gh api repos/avidullu/muneem/issues/83/comments --jq '.[ ] | select(.created_at >
"2026-06-25T17:45:06Z") | "--- \(.user.login) @ \(.created_at) ---\n\(.body)\n"' 2>&1
[/external_agent_tool_call]
```

#### 250. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_result]
=== current head + recent log ===
c455994bf057392f3f936db3765d8cf3f3e70ac5
c455994 fix: _TOTAL_DUE_RE Cr suffix uses \\b word boundary to avoid 'Credit' over-match
8306ba8 test: add credit-balance cross-check + no-Cr regex tests
e5ace4e fix: address PR #83 review ? Cr handling, regex tests, balance note, import hoist
75d220c feat: add total-due cross-check to Axis CC parser
ec12b59 fix: address PR #80 post-merge review comments (#81)

=== my last-reviewed head (from state) ===
{'head': '8306ba8987f23dea28caf54560f3cfa69dab2241', 'last_comment_ts': '2026-06-25T17:45:06Z'}

=== any new author comments since 17:45:06? ===
--- avidullu @ 2026-06-25T17:45:15Z ---
Good catch ? the 'Credit' over-match is real. Fixed in c455994:

- Regex: (Cr)? ? (Cr\\b)? ? word boundary prevents matching 'Credit' in adjacent 'Credit Limit'
/ 'Credit Card' lines
- New test: test_total_due_re_does_not_match_cr_inside_credit_limit with the exact adjacency
case (Total Amount Due ? number ? Credit Limit on next line)
- Existing Cr suffix test still passes (genuine trailing Cr with nothing after it)

488 tests pass, ruff/mypy clean. CI should be green shortly.
[/external_agent_tool_result]
```

#### 251. assistant (2026-07-02T06:11:33.053Z)

The author applied exactly the `(Cr\\b)?` fix I suggested, in `c455994`, plus the adjacency test. Let me re-review it thoroughly: confirm the diff is \*only\* the boundary change, exercise the new regex against a broad set of cases (including ones their test doesn't cover), and check CI.

#### 252. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_call: Bash]
description: Diff the fix commit and confirm only regex changed
command: cd /c/Users/avidu/Projects/muneem
echo "=== FULL diff 8306ba8 -> c455994 (source + tests) ==="
git diff 8306ba8 c455994
echo ""
echo "=== executable-AST: is the ONLY axis.py change the regex literal? ==="
DIR=$(mktemp -d)
for c in 8306ba8 c455994; do git show $c:src/muneem/parsers/axis.py > "$DIR/$c.py"; done
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
"$VPY" - "$DIR" <<'PY'
import ast,os,sys
D=sys.argv[1]
def syms(p):
    out={}
    for n in ast.walk(ast.parse(open(p,encoding='utf-8').read())):
        if isinstance(n,(ast.FunctionDef,ast.AsyncFunctionDef)): out[n.name]=ast.dump(n)
    return out
a,b=syms(os.path.join(D,'8306ba8.py'),syms(os.path.join(D,'c455994.py')))
diff=sorted(k for k in set(a)|set(b) if a.get(k)!=b.get(k))
print("functions whose AST changed:", diff or "NONE (only a module-level constant/regex literal
changed)")
PY
[/external_agent_tool_call]
```

### 253. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_result]
=== FULL diff 8306ba8 -> c455994 (source + tests) ===
diff --git a/src/muneem/parsers/axis.py b/src/muneem/parsers/axis.py
index ba6aa76..7627164 100644
--- a/src/muneem/parsers/axis.py
+++ b/src/muneem/parsers/axis.py
@@ -39,7 +39,7 @@ @ _CARD_RES = [re.compile(r"(\d{4}XXXX\d{4})"), re.compile(r"(\d{6}\*\d{4})")]
# Cr/Debit suffixes (if any) are captured separately for sign handling.
_TOTAL_DUE_RE = re.compile(
    r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s*(Rs\.\d{2}))?\s*"
-    r"([\d,]+\.\d{0,2})\s*(Cr)?",
+    r"([\d,]+\.\d{0,2})\s*(Cr\b)?",
    re.IGNORECASE,
)

diff --git a/tests/parsers/test_axis.py b/tests/parsers/test_axis.py
index 4fafd8d..6c0c295 100644
--- a/tests/parsers/test_axis.py
+++ b/tests/parsers/test_axis.py
@@ -236,6 +236,14 @@ def test_total_due_re_without_cr_suffix():
    assert m and m.group(1) == "5,000.00" and m.group(2) is None

+def test_total_due_re_does_not_match_cr_inside_credit_limit():
+    """The Cr suffix must use \b word boundary so 'Credit Limit'
+    on an adjacent line does not trigger a false credit-balance negation."""
+    text = "Total Amount Due\n12,345.67\nCredit Limit 2,00,000"
+    m = axis._TOTAL_DUE_RE.search(text)
+    assert m and m.group(1) == "12,345.67" and m.group(2) is None
+
+def test_cc_total_due_cross_check_credit_balance_reconciles(tmp_path, monkeypatch):
+    """When the customer has a credit balance (overpaid), the Cr suffix produces
+    a negative total_due. The cross-check should match the net."""

=== executable-AST: is the ONLY axis.py change the regex literal? ===
functions whose AST changed: NONE (only a module-level constant/regex literal changed)
[/external_agent_tool_result]
```



254. assistant (2026-07-02T06:11:33.053Z)

Clean ? the diff is *\*exactly\** ``(Cr)?` ? `(Cr\b)?`` plus the adjacency test, and the AST check confirms *\*\*no function logic changed\*\**, only the regex literal. Now let me exercise the new regex hard, including cases beyond the author's tests (other ``cr``-words, punctuation, uppercase, genuine Cr variants), and check CI.

255. assistant (2026-07-02T06:11:33.053Z)

```
[external_agent_tool_call: Bash]
description: Comprehensive regex verification + CI on c455994
command: cd /c/Users/avidu/Projects/muneem
cat > /tmp/re_final.py <<'PY'
import re
R =
re.compile(r"Total\s+(?:Amount|Payment)\s+Due\s*(?:\s*(Rs\.\s*))?\s*([\d,]+\s*\s*\d{0,2})\s*(Cr\b)?",
re.IGNORECASE)
def result(c):
    m=R.search(c)
    if not m: return "NO MATCH"
    v=float(m.group(1).replace(",",""))
    if m.group(2): v=-v
    return f"g1={m.group(1)!r:11} g2={m.group(2)!r:6} total_due={v}"
cases = {
    "plain positive": "Total Amount Due 12,345.67",
    "(Rs.) variant": "Total Amount Due (Rs.) 12,345.67",
    "Payment Due variant": "Total Payment Due 1,234.56",
    "genuine Cr (EOL)": "Total Payment Due 12,345.67 Cr",
    "genuine CR (uppercase)": "Total Amount Due 12,345.67 CR",
    "genuine Cr.": "Total Amount Due 12,345.67 Cr.",
    "Credit Limit adjacency": "Total Amount Due\n12,345.67\nCredit Limit 2,00,000",
    "Credit Card adjacency": "Total Amount Due 8,000.00 Credit Card 1234XXXX5678",
    "Crore (false-cr word)": "Total Amount Due 12,345.67 Crore",
    "Credited (false-cr word)": "Total Amount Due 9,999.00 Credited to account",
    "Dr suffix (debit)": "Total Amount Due 5,000.00 Dr",
    "number on next line": "Total Amount Due\n8,000.00",
    "Minimum (must NOT match)": "Minimum Amount Due 500.00",
}
for name,txt in cases.items():
    print(f" {name:30} {result(txt)}")
PY
VPY="$PWD/.venv/Scripts/python.exe"; [ -f "$VPY" ] || VPY=python
echo "=== comprehensive regex behavior on c455994's _TOTAL_DUE_RE ==="
"$VPY" "$($cygpath -w /tmp/re_final.py)"
echo ""
echo "=== CI on c455994 ==="
echo "check-runs: $(gh api repos/avidullu/muneem/commits/c455994/check-runs --jq '.total_count'
2>&1) total"
gh api repos/avidullu/muneem/commits/c455994/check-runs --jq '.check_runs[] | "\(.name):
\(.status)/\(.conclusion)" 2>&1 | sort -u
[/external_agent_tool_call]
```

## 256. assistant (2026-07-02T06:11:33.054Z)

| [external_agent_tool_result] | g1             | g2      | total_due           |
|------------------------------|----------------|---------|---------------------|
| plain positive               | g1='12,345.67' | g2=None | total_due=12345.67  |
| (Rs.) variant                | g1='12,345.67' | g2=None | total_due=12345.67  |
| Payment Due variant          | g1='1,234.56'  | g2=None | total_due=1234.56   |
| genuine Cr (EOL)             | g1='12,345.67' | g2='Cr' | total_due=-12345.67 |
| genuine CR (uppercase)       | g1='12,345.67' | g2='CR' | total_due=-12345.67 |
| genuine Cr.                  | g1='12,345.67' | g2='Cr' | total_due=-12345.67 |
| Credit Limit adjacency       | g1='12,345.67' | g2=None | total_due=12345.67  |
| Credit Card adjacency        | g1='8,000.00'  | g2=None | total_due=8000.0    |
| Crore (false-cr word)        | g1='12,345.67' | g2=None | total_due=12345.67  |

|                          |               |         |                  |
|--------------------------|---------------|---------|------------------|
| Credited (false-cr word) | g1='9,999.00' | g2=None | total_due=9999.0 |
| Dr suffix (debit)        | g1='5,000.00' | g2=None | total_due=5000.0 |
| number on next line      | g1='8,000.00' | g2=None | total_due=8000.0 |
| Minimum (must NOT match) | NO MATCH      |         |                  |

```

=== CI on c455994 ===
check-runs: 5 total
ocr: completed/skipped
test (ubuntu-latest, 3.11): queued/null
test (ubuntu-latest, 3.12): in_progress/null
test (ubuntu-latest, 3.13): queued/null
test (windows-latest, 3.13): completed/success
[/external_agent_tool_result]

```

## 257. assistant (2026-07-02T06:11:33.054Z)

The `(Cr\b)?` fix is **correct and robust** ? verified across every case I could construct, including ones the author's tests don't cover:

```

| Input | Result | ? |
|---|---|---|
| genuine `Cr` / `CR` / `Cr.` (EOL) | negated (credit balance) | ? |
| `?12,345.67\nCredit Limit?` | positive (no false negation) | ? |
| `?8,000.00 Credit Card?` | positive | ? |
| `Crore` / `Credited` (other cr-words) | positive | ? |
| `Dr` suffix / number-on-next-line | positive | ? |
| `Minimum Amount Due` | no match | ? |

```

AST-confirmed that **only the regex literal changed** ? no other logic touched. Windows CI is already green; Ubuntu is mid-run. Let me watch it to completion so I can give a definitive sign-off rather than a conditional one.

## 258. assistant (2026-07-02T06:11:33.054Z)

```

[external_agent_tool_call: Bash]
description: Watch CI run for c455994 to completion
command: cd /c/Users/avidu/Projects/muneem
RID=$(gh run list --repo avidullu/muneem --branch feat/axis-cc-total-due --limit 10 --json
databaseId,headSha,workflowName --jq '[.[] | select(.headSha|startswith("c455994")) |
select(.workflowName=="ci")][0].databaseId' 2>&1)
echo "watching ci run $RID for c455994 ..."
gh run watch "$RID" --repo avidullu/muneem --exit-status 2>&1 | tail -15
[/external_agent_tool_call]

```

## 259. assistant (2026-07-02T06:11:33.054Z)

```

[external_agent_tool_result]
Command running in background with ID: blawjublu. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-badminton-highlight-
indexer\6790052a-f068-488a-9cc6-95b0c547eeb1\tasks\blawjublu.output. You will be notified when
it completes. To check interim output, use Read on that file path.
[/external_agent_tool_result]

```

## 260. assistant (2026-07-02T06:11:33.054Z)

```

[external_agent_tool_call: Read]
file: C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-badminton-highlight-
indexer\6790052a-f068-488a-9cc6-95b0c547eeb1\tasks\blawjublu.output
[/external_agent_tool_call]

```

## 261. assistant (2026-07-02T06:11:33.054Z)

```

[external_agent_tool_result]
1      watching ci run 28189109387 for c455994 ...

```

2

[/external\_agent\_tool\_result]

#### 262. assistant (2026-07-02T06:11:33.054Z)

Thorough review is done ? the fix is correct and comprehensively verified. I'm watching CI run `28189109387` to completion in the background so I can give you a definitive sign-off rather than a conditional one (Windows already green; Ubuntu 3.11/3.12/3.13 finishing). I'll post the LGTM to the PR and confirm here the moment it lands green ? or flag immediately in the unlikely event Ubuntu surfaces anything Windows didn't.

Summary so far on `c455994`:

- **Regression fixed correctly** ? `(Cr)?` ? `(Cr\b)?`, the exact boundary fix; genuine `Cr`/`CR`/` Cr.` still negate, but `Credit Limit`/`Credit Card`/`Crore`/`Credited` no longer false-trigger.
- **AST-confirmed surgical** ? only the regex literal changed; zero function-body changes, so the cross-check arithmetic I reviewed earlier is untouched.
- **Right test added** ? `test\_total\_due\_re\_does\_not\_match\_cr\_inside\_credit\_limit` pins the exact adjacency case.
- All four original review notes now fully resolved.

Standing by for CI.

#### 263. user (2026-07-02T06:11:33.054Z)

CI is green

#### 264. assistant (2026-07-02T06:11:33.054Z)

```
[external_agent_tool_call: Bash]
description: Confirm CI fully green on c455994 and head unchanged
command: cd /c/Users/avidu/Projects/muneem && git fetch origin -q
echo "=== confirm head still c455994 (no newer push) ==="
git rev-parse origin/feat/axis-cc-total-due
echo ""
echo "=== CI conclusions for c455994 ==="
gh api repos/avidullu/muneem/commits/c455994/check-runs --jq '.check_runs[] | "\(.name): \(.status)/\(.conclusion)"' 2>&1 | sort -u
echo ""
echo "=== overall: any non-success (excl. skipped)? ==="
gh api repos/avidullu/muneem/commits/c455994/check-runs --jq '[.check_runs[] | select(.conclusion!=null and .conclusion!="success" and .conclusion!="skipped")] | length' 2>&1
[/external_agent_tool_call]
```

#### 265. assistant (2026-07-02T06:11:33.054Z)

```
[external_agent_tool_result]
=== confirm head still c455994 (no newer push) ===
c455994bf057392f3f936db3765d8cf3f3e70ac5

=== CI conclusions for c455994 ===
ocr: completed/skipped
test (ubuntu-latest, 3.11): queued/null
test (ubuntu-latest, 3.12): completed/success
test (ubuntu-latest, 3.13): in_progress/null
test (windows-latest, 3.13): completed/success

=== overall: any non-success (excl. skipped)? ===
0
[/external_agent_tool_result]
```

#### 266. assistant (2026-07-02T06:11:33.054Z)

The user says green, but the check-runs API still shows 3.11 `queued` and 3.13 `in\_progress` ?

likely the gh-API lag I've hit all session, or a duplicate run. Let me reconcile against the actual workflow runs and the watch result before I sign off.

#### 267. assistant (2026-07-02T06:11:33.054Z)

```
[external_agent_tool_call: Bash]
description: Reconcile workflow runs and watched-run conclusion for c455994
command: cd /c/Users/avidu/Projects/muneem
echo "=== all workflow runs whose head is c455994 ==="
gh run list --repo avidullu/muneem --branch feat/axis-cc-total-due --limit 15 --json
databaseId,headSha,status,conclusion,workflowName,event --jq '.[ ] |
select(.headSha|startswith("c455994")) | "run \(.databaseId) [\(.event)] \(.workflowName):
\(.status)/\(.conclusion)"' 2>&1
echo ""
echo "=== background watch (run 28189109387) final output ==="
gh run view 28189109387 --repo avidullu/muneem --json status,conclusion,jobs --jq
'[{status,conclusion, jobs:[.jobs[]|{name:.name,conclusion:.conclusion}]]' 2>&1
[/external_agent_tool_call]
```

#### 268. assistant (2026-07-02T06:11:33.054Z)

```
[external_agent_tool_result]
=== all workflow runs whose head is c455994 ===
run 28189109387 [push] ci: completed/success

=== background watch (run 28189109387) final output ===
{"conclusion":"success","jobs":[{"conclusion":"success","name":"test (ubuntu-latest,
3.11)"}, {"conclusion":"success","name":"test (ubuntu-latest,
3.13)"}, {"conclusion":"success","name":"test (windows-latest,
3.13)"}, {"conclusion":"success","name":"test (ubuntu-latest,
3.12)"}, {"conclusion":"skipped","name":"ocr"}], "status":"completed"}
[/external_agent_tool_result]
```

#### 269. assistant (2026-07-02T06:11:33.054Z)

Definitive: run **28189109387** (`ci`, push) is **completed/success** ? all four test jobs (Ubuntu 3.11/3.12/3.13 + Windows 3.13) passed, ocr skipped, and the watch exited 0. The check-runs API was just lagging again. You're right, it's green. Let me post the final sign-off.

#### 270. assistant (2026-07-02T06:11:33.054Z)

```
[external_agent_tool_call: Bash]
description: Post final LGTM on #83 and update state
command: cd /c/Users/avidu/Projects/muneem
cat > "C:/Users/avidu/AppData/Local/Temp/pr83-lgtm.md" <<'EOF'
```

### LGTM ? ? Cr regression fixed correctly; all four notes resolved

`c455994` applies the exact boundary fix and I verified it thoroughly:

- **Surgical change** ? AST diff vs `8306ba8` shows **zero function-body changes**; only the `_TOTAL_DUE_RE` literal changed (`(Cr)?` ? `(Cr\b)?``). The cross-check arithmetic is untouched.
- **Regression gone, genuine Cr preserved** ? exercised the new regex across cases beyond the added test:

```
| input | `total_due` | |
|---|---|---|
| ` 12,345.67 Cr` / ` CR` / ` Cr.` (real credit balance) | ?12,345.67 | ? negates |
| `?12,345.67\nCredit Limit?` | +12,345.67 | ? fixed |
| `?8,000.00 Credit Card?` | +8,000.00 | ? |
| `Crore` / `Credited` (other cr-words) | positive | ? |
| ` Dr` suffix / number-on-next-line | positive | ? |
| `Minimum Amount Due` | no match | ? |
```

- **Right test added** ? `test_total_due_re_does_not_match_cr_inside_credit_limit` pins the

exact `Credit Limit` adjacency.

- **\*\*All four original notes resolved\*\*** ? Cr handling (#1), direct regex tests (#2), carried-balance comment (#3), import hoist (#4).

**\*\*CI green on `c455994`\*\*** ? run

[28189109387](https://github.com/avidullu/muneem/actions/runs/28189109387): Ubuntu 3.11/3.12/3.13 + Windows 3.13 all pass (488 tests), ruff/mypy clean.

Nice iteration on the credit-balance handling. Good to merge.

<!-- claude-review-bot -->

EOF

gh pr comment 83 --repo avidullu/muneem --body-file

"C:/Users/avidu/AppData/Local/Temp/pr83-lgtm.md" 2>&1

rm -f "C:/Users/avidu/AppData/Local/Temp/pr83-lgtm.md"

STATE="C:/Users/avidu/AppData/Local/Temp/muneem\_review\_state.json"

VPY="\$PWD/.venv/Scripts/python.exe"; [ -f "\$VPY" ] || VPY=python

"\$VPY" - <<'PY'

import json, subprocess

STATE="C:/Users/avidu/AppData/Local/Temp/muneem\_review\_state.json"

st=json.load(open(STATE))

ic=json.loads(subprocess.check\_output(["gh","api","repos/avidullu/muneem/issues/83/comments","--jq","[.[]].created\_at"])) or "[]")

st["83"]={"head":subprocess.check\_output(["git","rev-parse","origin/feat/axis-cc-total-due"]).decode().strip(),

"last\_comment\_ts":sorted(ic)[-1] if ic else st["83"]["last\_comment\_ts"]}

json.dump(st,open(STATE,"w"),indent=2)

print("state[83]:", json.dumps(st["83"]))

PY

[/external\_agent\_tool\_call]

## 271. assistant (2026-07-02T06:11:33.055Z)

[external\_agent\_tool\_result]

https://github.com/avidullu/muneem/pull/83#issuecomment-4802600866

state[83]: {"head": "c455994bf057392f3f936db3765d8cf3f3e70ac5", "last\_comment\_ts": "2026-06-25T17:52:29Z"}

[/external\_agent\_tool\_result]

## 272. assistant (2026-07-02T06:11:33.055Z)

Done ? [final LGTM posted on

#83](https://github.com/avidullu/muneem/pull/83#issuecomment-4802600866).

**\*\*#83 is fully resolved:\*\*** the `(Cr\b)?` fix in `c455994` is correct and comprehensively verified (genuine credit balances still negate; `Credit Limit`/`Credit Card`/`Crore`/`Credited` no longer false-trigger), the change is AST-surgical (only the regex literal moved), the right adjacency test is in, and CI is green on the real run (28189109387, 488 tests). All four of my original notes are closed. Clean to merge.

That closes the loop on the catch ? the over-match would have silently kept normal positive-balance statements at `UNVERIFIED`, and it's now fixed with a one-char boundary plus a regression test.

**\*\*Current muneem queue:\*\***

- **\*\*#82\*\*** ? LGTM (split + security-comment restoration verified)

- **\*\*#83\*\*** ? LGTM (feature + Cr fix verified) ? just now

- **\*\*#84\*\*** ? LGTM (docs archive)

All three reviewed, green, and signed off. The comment-aware poll is still live (state tracks #83 at `c455994`), so if you push more or respond, the next tick catches it ? or just ping me. Nice work on the fast iteration.