

claude-windows / 577fd4df-ed3f-43d3-854d-d63d732e2e07

Metadata

```
- Source: `claude-windows`
- Kind: `claude`
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-badminton-highlight-indexer\577fd4df-ed3f-43d3-854d-d63d732e2e07\subagents\workflows\wf_e5e25aeb-1c0\agent-a46014f88a68c849c.jsonl`
- SHA-256: `ded7f16e9fa81c487d308626548518a511f41ae4fa82e9a9432aa6921d4a4e35`
- Source modified: `2026-06-20T16:36:52+00:00`
- Imported at: `2026-07-05T16:48:27+00:00`
- project: `wf_e5e25aeb-1c0`
- session_id: `577fd4df-ed3f-43d3-854d-d63d732e2e07`
```

Transcript

1. user (2026-06-20T16:34:09.930Z)

You are reviewing a NEW feature (P3) in a TypeScript SPA: a DETERMINISTIC, dependency-free query compiler that turns plain text ("over 10s", "top 15 longest", "at least 8 shots") into a filter+sort+limit selection over detected badminton rallies. NO LLM, NO network.

Read these files with the Read tool before judging:

```
- CORE parser: C:/Users/avidu/Projects/khelsutra/web/src/lib/query.ts
- its unit tests: C:/Users/avidu/Projects/khelsutra/web/src/lib/query.test.ts
- QueryBar component: C:/Users/avidu/Projects/khelsutra/web/src/components/QueryBar.tsx
- App wiring: C:/Users/avidu/Projects/khelsutra/web/src/App.tsx
- selection hook: C:/Users/avidu/Projects/khelsutra/web/src/hooks/useRallySelection.ts
- RallyGrid: C:/Users/avidu/Projects/khelsutra/web/src/components/RallyGrid.tsx
- engine data types: C:/Users/avidu/Projects/khelsutra/web/src/api/types.ts
- the DESIGN CONTRACT: C:/Users/avidu/Projects/khelsutra/docs/PER_RALLY_SELECTION.md (read §2 decisions D5, §3 honest-vs-fabricated fields, §4.3 "Dead-ends / do-NOT", §9 DoD)
```

Report ONLY concrete, defensible findings with exact evidence (an input string ? the wrong parsed output, or a code line). Do NOT invent issues to fill a quota; an empty findings list is a valid, respected answer. Prefer a few high-confidence findings over many speculative ones.

YOUR DIMENSION: reuse, simplification, efficiency, and consistency with the existing codebase.

- duplicated logic that could reuse lib/selection.ts, lib/format.ts, or existing helpers.
- dead code, unreachable branches, redundant regex alternations, anything overcomplicated.
- naming/exports inconsistent with the established P1/P2 style.
- test GAPS: behaviors in query.ts that the test suite does NOT cover (list the specific missing case).

Only flag things that genuinely improve clarity or correctness; ignore stylistic nitpicks the repo doesn't already enforce.

2. assistant (2026-06-20T16:34:12.292Z)

I'll start by reading the design contract and core files to understand the established patterns before reviewing.

3. user (2026-06-20T16:34:13.246Z)

```
1 // Deterministic, dependency-free query compiler for the rally picker
(PER_RALLY_SELECTION.md
2 // D2/D5). NO LLM, NO network ? a tiny regex grammar over the ONLY honest, queryable
axes the
3 // engine returns today: rally LENGTH (duration), ORDER (start_time / duration /
shot_count),
```

```

4      // COUNT (top/first N), and SHOT COUNT (metadata.shot_count).
5      //
6      // Everything else a user might type ? shot TYPE (smash/clear/drop?), PLAYER, SCORE ?
has no
7      // detector and no column, so we FLAG it as "not available yet" and NEVER fabricate a
result.
8      // Parsing is pure and unit-tested; the QueryBar React component is a thin shell over
it.
9      import type { RallySegment } from "../api/types";
10
11     export type CompareOp = ">" | ">=" | "<" | "<=" | "=";
12     export type FilterField = "duration" | "shot_count";
13     /** One ANDed predicate over a rally field (e.g. duration > 10s). */
14     export interface Filter {
15         field: FilterField;
16         op: CompareOp;
17         value: number; // seconds for duration; a raw count for shot_count
18     }
19
20     export type SortKey = "duration" | "start_time" | "shot_count";
21     export interface Sort {
22         key: SortKey;
23         dir: "asc" | "desc";
24     }
25
26     /** A recognized-but-unsupported concept ? surfaced as a greyed "not available yet"
hint. */
27     export type UnavailableKind = "shot-type" | "player" | "score";
28     export interface Unavailable {
29         token: string;
30         kind: UnavailableKind;
31     }
32
33     export interface ParsedQuery {
34         raw: string;
35         /** ANDed together. */
36         filters: Filter[];
37         sort?: Sort;
38         /** "top N" / "first N" / "N longest". */
39         limit?: number;
40         /** Concepts we understood but cannot honour (shot-type / player / score). */
41         unavailable: Unavailable[];
42         /** True when at least one actionable clause (filter | sort | limit) was understood.
*/
43         recognized: boolean;
44     }
45
46     export interface QueryResult {
47         /** ALL rallies in display order (sorted if a sort was given, else input order). */
48         ordered: RallySegment[];
49         /** Ids matching the filters (then limited), in display order. */
50         selectedIds: number[];
51     }
52
53     // ?? grammar fragments ?????????????????????????????????????????????????????????
54     const NUM = "(\\d+(?:\\.\\d+)?)";
55     // Optional trailing unit/noun. "shots?" is listed FIRST so it can't be eaten by the
bare "s"
56     // time-unit alternative; \b stops "m" matching "minutes" etc.
57     const UNIT = "(?:\\s*(shots?|seconds?|secs?|minutes?|mins?|min|m|s)\\b)?";
58
59     interface OpPattern {
60         op: CompareOp;
61         re: RegExp;
62         /** Which capture group holds the number / the unit. */

```

```

63     numAt: number;
64     unitAt: number;
65 }
66
67 // Leading comparator ("over 10s"). The "no more than" / "at least" guards come BEFORE
their
68 // bare counterparts ("more than" / "less than") so the negated phrase is consumed
first.
69 function lead(alt: string, op: CompareOp): OpPattern {
70     return { op, re: new RegExp(`(?:${alt})\\s*${NUM}${UNIT}`, "g"), numAt: 1, unitAt: 2
};
71 }
72 const LEADING: OpPattern[] = [
73     lead("no more than|at most|maximum(?: of)?|max|up to|<=", "<="),
74     lead("no less than|no fewer than|at least|minimum(?: of)?|min|>=", ">="),
75     lead("exactly|equal to|equals", "="),
76     lead("over|longer than|more than|greater than|above|bigger than|>", ">"),
77     lead("under|shorter than|less than|fewer than|below|smaller than|<", "<"),
78 ];
79
80 // Trailing comparator. The unit may sit BEFORE the operator ("10s+", "8 shots or more")
or the
81 // "shots" noun AFTER it ("10+ shots") ? capture both sides and use whichever is
present.
82 interface TrailPattern {
83     op: CompareOp;
84     re: RegExp;
85 }
86 const POST_NOUN = "(?:\\s*(shots?)\\b)?"
87 const TRAILING: TrailPattern[] = [
88     { op: ">=", re: new RegExp(`${NUM}${UNIT}\\s*(?:\\+|or
(?:more|longer|over|above|greater))${POST_NOUN}`, "g") },
89     { op: "<=", re: new RegExp(`${NUM}${UNIT}\\s*or
(?:less|fewer|shorter|under|below)${POST_NOUN}`, "g") },
90 ];
91
92 function toSeconds(n: number, unit?: string): number {
93     return unit && /\m/.test(unit) ? n * 60 : n; // m/min/minute(s) ? seconds; else as-is
94 }
95
96 function makeFilter(numStr: string, unit: string | undefined, op: CompareOp): Filter {
97     const n = Number(numStr);
98     const isShots = !!unit && /^shots?$/i.test(unit);
99     return isShots
100         ? { field: "shot_count", op, value: n }
101         : { field: "duration", op, value: toSeconds(n, unit) };
102 }
103
104 const SORT_PATTERNS: Array<RegExp, Sort> = [
105     [/b(?:longest(?: first)?|longer first|by(?:duration|length)|duration desc)\b/, {
key: "duration", dir: "desc" }],
106     [/b(?:shortest(?: first)?|shorter first|duration asc)\b/, { key: "duration", dir:
"asc" }],
107     [/b(?:newest(?: first)?|latest|most recent|recent first)\b/, { key: "start_time",
dir: "desc" }],
108     [/b(?:oldest(?: first)?|earliest|chronological|in order|by time)\b/, { key:
"start_time", dir: "asc" }],
109     [/b(?:most shots(?: first)?|highest shots?|by shots?|by shot count|shot count
desc)\b/, { key: "shot_count", dir: "desc" }],
110     [/b(?:fewest shots(?: first)?|least shots?|lowest shots?|shot count asc)\b/, { key:
"shot_count", dir: "asc" }],
111 ];
112
113 // Order before kind so a token claimed by an earlier kind isn't double-counted.
114 const UNAVAILABLE_PATTERNS: Array<UnavailableKind, RegExp> = [

```

```

115     ["shot-type", /\b(smash(?:es)?|clears?|drops?|dropshots?|net
?shots?|drives?|lifts?|serves?|kills?|taps?|pushes?|blocks?|slices?)\b/g],
116     ["player", /\b(players?|opponents?|servers?|receivers?)\b/g],
117     ["score", /\b(points?|score|deuce|game point|set point|match point)\b/g],
118 ];
119
120 // ?? public API ?????????????????????????????????????????????????????????????
121
122 export function parseQuery(raw: string): ParsedQuery {
123     const normalized = raw
124         .toLowerCase()
125         .replace(/~/g, ">=")
126         .replace(/~/g, "<=")
127         .replace(/,/g, " ")
128         .replace(/\\s+/g, " ")
129         .trim();
130
131     const filters: Filter[] = [];
132     let working = normalized;
133
134     // Extract comparator clauses, blanking each match so later passes can't re-read its
number.
135     for (const pat of LEADING) {
136         working = working.replace(pat.re, (full, ...g) => {
137             filters.push(makeFilter(g[pat.numAt - 1], g[pat.unitAt - 1], pat.op));
138             return " ".repeat(full.length);
139         });
140     }
141     for (const pat of TRAILING) {
142         working = working.replace(pat.re, (full, num, preUnit, postNoun) => {
143             filters.push(makeFilter(num, preUnit ?? postNoun, pat.op));
144             return " ".repeat(full.length);
145         });
146     }
147
148     // Explicit sort (runs before limit so "top 15 longest" keeps the longest?desc
intent).
149     let sort: Sort | undefined;
150     for (const [re, s] of SORT_PATTERNS) {
151         if (re.test(working)) {
152             sort = s;
153             break;
154         }
155     }
156
157     // Limit ("top/best N", "first N", "last N", "N longest/shortest", "longest/shortest
N").
158     let limit: number | undefined;
159     let m: RegExpMatchArray | null;
160     if ((m = working.match(/\b(\d+)\s+(longest|shortest)\b/)) || (m =
working.match(/\b(longest|shortest)\s+(\d+)\b/))) {
161         const num = /^(\d+)/.test(m[1]) ? m[1] : m[2];
162         const word = /^(\d+)/.test(m[1]) ? m[2] : m[1];
163         limit = parseInt(num, 10);
164         if (!sort) sort = { key: "duration", dir: word === "longest" ? "desc" : "asc" };
165     } else if ((m = working.match(/\b(?:top|best)\s+(\d+)\b/))) {
166         limit = parseInt(m[1], 10);
167         if (!sort) sort = { key: "duration", dir: "desc" }; // "top N" ? best = longest
168     } else if ((m = working.match(/\b(?:first|earliest)\s+(\d+)\b/))) {
169         limit = parseInt(m[1], 10);
170         if (!sort) sort = { key: "start_time", dir: "asc" };
171     } else if ((m = working.match(/\b(?:last|latest|newest|most recent)\s+(\d+)\b/))) {
172         limit = parseInt(m[1], 10);
173         if (!sort) sort = { key: "start_time", dir: "desc" };
174     }

```

```

175
176 // Unavailable concepts (scanned on the normalized text; deduped, first kind wins).
177 const unavailable: Unavailable[] = [];
178 const seen = new Set<string>();
179 for (const [kind, re] of UNAVAILABLE_PATTERNS) {
180     for (const mm of normalized.matchAll(re)) {
181         const token = mm[1];
182         if (!seen.has(token)) {
183             seen.add(token);
184             unavailable.push({ token, kind });
185         }
186     }
187 }
188
189 return {
190     raw,
191     filters,
192     sort,
193     limit,
194     unavailable,
195     recognized: filters.length > 0 || sort !== null || limit !== null,
196 };
197 }
198
199 function rallyValue(r: RallySegment, key: SortKey): number | undefined {
200     if (key === "duration") return r.duration;
201     if (key === "start_time") return r.start_time;
202     return r.metadata?.shot_count;
203 }
204
205 /** Stable sort; rallies missing the sort field always sort LAST (unknown ? smallest).
206 */
207 export function sortRallies(rallies: RallySegment[], sort: Sort): RallySegment[] {
208     return rallies
209         .map((r, i) => ({ r, i }))
210         .sort((a, b) => {
211             const av = rallyValue(a.r, sort.key);
212             const bv = rallyValue(b.r, sort.key);
213             if (av == null && bv == null) return a.i - b.i;
214             if (av == null) return 1;
215             if (bv == null) return -1;
216             if (av !== bv) return sort.dir === "asc" ? av - bv : bv - av;
217             return a.i - b.i; // tie ? preserve input order
218         })
219         .map((x) => x.r);
220 }
221
222 function matchesFilter(r: RallySegment, f: Filter): boolean {
223     const v = f.field === "duration" ? r.duration : r.metadata?.shot_count;
224     if (v == null) return false; // a rally without shot_count can't satisfy a shot filter
225     switch (f.op) {
226         case ">":
227             return v > f.value;
228         case ">=":
229             return v >= f.value;
230         case "<":
231             return v < f.value;
232         case "<=":
233             return v <= f.value;
234         case "=":
235             return v === f.value;
236         default:
237             return false;
238     }
239 }

```

```

239
240 /** Apply a parsed query to the rallies: ordered display list + the ids it selects.
Pure.
241 * An UNRECOGNIZED query (nothing understood) selects nothing and leaves order untouched
?
242 * so garbage input can never silently wipe a user's manual curation. The App also
guards on
243 * `q.recognized` before applying, so an empty box is a no-op end to end. */
244 export function runQuery(rallies: RallySegment[], q: ParsedQuery): QueryResult {
245   if (!q.recognized) return { ordered: rallies.slice(), selectedIds: [] };
246   const ordered = q.sort ? sortRallies(rallies, q.sort) : rallies.slice();
247   let matched = ordered.filter((r) => q.filters.every((f) => matchesFilter(r, f)));
248   if (q.limit !== null) matched = matched.slice(0, q.limit);
249   return { ordered, selectedIds: matched.map((r) => r.id) };
250 }
251
252 // ?? human-readable labels (shared by the QueryBar pill and the tests) ?????????
253 const OP_SYMBOL: Record<CompareOp, string> = { ">": ">", ">=": "?", "<": "<", "<=": "?",
"=": "=" };
254
255 export function filterLabel(f: Filter): string {
256   if (f.field === "duration") return `length ${OP_SYMBOL[f.op]} ${f.value}s`;
257   return `shots ${OP_SYMBOL[f.op]} ${f.value}`;
258 }
259
260 export function sortLabel(s: Sort): string {
261   if (s.key === "duration") return s.dir === "desc" ? "longest first" : "shortest
first";
262   if (s.key === "start_time") return s.dir === "desc" ? "newest first" : "oldest first";
263   return s.dir === "desc" ? "most shots first" : "fewest shots first";
264 }
265
266 /** Human clause labels for the parsed-pill (e.g. ["length > 10s", "longest first", "top
15"]). */
267 export function summarize(q: ParsedQuery): string[] {
268   const parts: string[] = [];
269   for (const f of q.filters) parts.push(filterLabel(f));
270   if (q.sort) parts.push(sortLabel(q.sort));
271   if (q.limit !== null) parts.push(`top ${q.limit}`);
272   return parts;
273 }
274

```

4. user (2026-06-20T16:34:13.715Z)

```

1   import { describe, it, expect } from "vitest";
2   import {
3     parseQuery,
4     runQuery,
5     sortRallies,
6     filterLabel,
7     sortLabel,
8     summarize,
9   } from "../query";
10  import type { RallySegment } from "../api/types";
11
12  const mk = (
13    id: number,
14    start_time: number,
15    duration: number,
16    shot_count?: number,
17  ): RallySegment => ({
18    id,
19    start_time,
20    end_time: start_time + duration,

```

```

21     duration,
22     server: null,
23     receiver: null,
24     metadata: shot_count == null ? {} : { shot_count },
25   });
26
27   // A small, varied corpus: ids ordered chronologically, durations & shot counts mixed,
28   // rally 4 deliberately has NO shot_count (tests "unknown sorts/filters honestly").
29   const RALLIES: RallySegment[] = [
30     mk(1, 12, 8, 9),
31     mk(2, 41, 6, 5),
32     mk(3, 63, 21, 19),
33     mk(4, 95, 6 /* no shot_count */),
34     mk(5, 130, 12, 11),
35     mk(6, 158, 29, 24),
36   ];
37
38   describe("parseQuery ? duration filters", () => {
39     it("'over 10s' ? duration > 10", () => {
40       expect(parseQuery("over 10s").filters).toEqual([{ field: "duration", op: ">", value:
10 }]);
41     });
42     it("accepts varied units and phrasings", () => {
43       expect(parseQuery("longer than 10 seconds").filters[0]).toEqual({ field: "duration",
op: ">", value: 10 });
44       expect(parseQuery("under 5 sec").filters[0]).toEqual({ field: "duration", op: "<",
value: 5 });
45       expect(parseQuery("at least 8s").filters[0]).toEqual({ field: "duration", op: ">=",
value: 8 });
46       expect(parseQuery("at most 8 seconds").filters[0]).toEqual({ field: "duration", op:
"<=", value: 8 });
47       expect(parseQuery("exactly 7s").filters[0]).toEqual({ field: "duration", op: "=",
value: 7 });
48     });
49     it("converts minutes to seconds", () => {
50       expect(parseQuery("over 1 minute").filters[0]).toEqual({ field: "duration", op: ">",
value: 60 });
51       expect(parseQuery("at least 1.5m").filters[0]).toEqual({ field: "duration", op:
">=", value: 90 });
52     });
53     it("handles symbols and trailing comparators", () => {
54       expect(parseQuery("? 10s").filters[0]).toEqual({ field: "duration", op: ">=", value:
10 });
55       expect(parseQuery("> 10").filters[0]).toEqual({ field: "duration", op: ">", value:
10 });
56       expect(parseQuery("10s+").filters[0]).toEqual({ field: "duration", op: ">=", value:
10 });
57       expect(parseQuery("10s or longer").filters[0]).toEqual({ field: "duration", op:
">=", value: 10 });
58       expect(parseQuery("8s or less").filters[0]).toEqual({ field: "duration", op: "<=",
value: 8 });
59     });
60     it("does NOT consume 'no more than' as 'more than'", () => {
61       expect(parseQuery("no more than 5s").filters[0]).toEqual({ field: "duration", op:
"<=", value: 5 });
62     });
63     it("treats a bare 'Ns' (no comparator) as not a filter", () => {
64       expect(parseQuery("10s").filters).toEqual([]);
65       expect(parseQuery("10s").recognized).toBe(false);
66     });
67   });
68
69   describe("parseQuery ? shot_count filters (noun-keyed)", () => {
70     it("routes the 'shots' noun to shot_count, not duration", () => {
71       expect(parseQuery("over 10 shots").filters[0]).toEqual({ field: "shot_count", op:

```

```

">", value: 10 });
72     expect(parseQuery("at least 8 shots").filters[0]).toEqual({ field: "shot_count", op:
">=", value: 8 });
73     expect(parseQuery("fewer than 5 shots").filters[0]).toEqual({ field: "shot_count",
op: "<", value: 5 });
74     expect(parseQuery("10+ shots").filters[0]).toEqual({ field: "shot_count", op: ">=",
value: 10 });
75     });
76     });
77
78     describe("parseQuery ? sort", () => {
79         const cases: Array<[string, ReturnType<typeof parseQuery>["sort"]]> = [
80             ["longest first", { key: "duration", dir: "desc" }],
81             ["shortest", { key: "duration", dir: "asc" }],
82             ["newest first", { key: "start_time", dir: "desc" }],
83             ["oldest first", { key: "start_time", dir: "asc" }],
84             ["in order", { key: "start_time", dir: "asc" }],
85             ["most shots", { key: "shot_count", dir: "desc" }],
86             ["fewest shots", { key: "shot_count", dir: "asc" }],
87         ];
88         it.each(cases)("%s' ? %o", (input, expected) => {
89             expect(parseQuery(input).sort).toEqual(expected);
90         });
91     });
92
93     describe("parseQuery ? limit (and its implied sort)", () => {
94         it("'top 15' ? limit 15, sort longest-first", () => {
95             const q = parseQuery("top 15");
96             expect(q.limit).toBe(15);
97             expect(q.sort).toEqual({ key: "duration", dir: "desc" });
98         });
99         it("'first 10' ? limit 10, sort oldest-first", () => {
100             const q = parseQuery("first 10");
101             expect(q.limit).toBe(10);
102             expect(q.sort).toEqual({ key: "start_time", dir: "asc" });
103         });
104         it("'15 longest' / '5 shortest' carry both limit and sort", () => {
105             expect(parseQuery("15 longest")).toMatchObject({ limit: 15, sort: { key: "duration",
dir: "desc" } });
106             expect(parseQuery("5 shortest")).toMatchObject({ limit: 5, sort: { key: "duration",
dir: "asc" } });
107         });
108         it("an explicit sort wins over the limit's implied one ('top 15 longest')", () => {
109             const q = parseQuery("top 15 longest");
110             expect(q.limit).toBe(15);
111             expect(q.sort).toEqual({ key: "duration", dir: "desc" });
112         });
113         it("combines a filter with a limit ('over 10s top 5')", () => {
114             const q = parseQuery("over 10s top 5");
115             expect(q.filters).toEqual([{ field: "duration", op: ">", value: 10 }]);
116             expect(q.limit).toBe(5);
117         });
118     });
119
120     describe("parseQuery ? unavailable concepts are flagged, never faked", () => {
121         it("flags shot-type words while still applying the available clause", () => {
122             const q = parseQuery("smashes over 10s");
123             expect(q.filters).toEqual([{ field: "duration", op: ">", value: 10 }]); // honoured
124             expect(q.unavailable).toEqual([{ token: "smashes", kind: "shot-type" }]); // flagged
125         });
126         it("flags player and score concepts", () => {
127             expect(parseQuery("opponent rallies").unavailable).toContainEqual({ token:
"opponent", kind: "player" });
128             expect(parseQuery("game point").unavailable).toContainEqual({ token: "game point",
kind: "score" });

```

```

129     });
130     it("does not confuse 'shots' (count) with a shot-type", () => {
131         expect(parseQuery("over 10 shots").unavailable).toEqual([]);
132     });
133     it("a pure unavailable query is not recognized as actionable", () => {
134         const q = parseQuery("rallies with drops");
135         expect(q.recognized).toBe(false);
136         expect(q.unavailable).toContainEqual({ token: "drops", kind: "shot-type" });
137     });
138 });
139
140 describe("parseQuery ? unrecognized / empty input", () => {
141     it("returns recognized=false with nothing to apply", () => {
142         for (const s of ["", " ", "hello there", "asdf"]) {
143             const q = parseQuery(s);
144             expect(q.recognized).toBe(false);
145             expect(q.filters).toEqual([]);
146             expect(q.sort).toBeUndefined();
147             expect(q.limit).toBeUndefined();
148         }
149     });
150 });
151
152 describe("sortRallies", () => {
153     it("sorts by duration desc / asc, stably", () => {
154         expect(sortRallies(RALLIES, { key: "duration", dir: "desc" })).map((r) =>
155 r.id)).toEqual([6, 3, 5, 1, 2, 4]);
156         expect(sortRallies(RALLIES, { key: "duration", dir: "asc" })).map((r) =>
157 r.id)).toEqual([2, 4, 1, 5, 3, 6]);
158     });
159     it("puts rallies with a missing field LAST regardless of direction", () => {
160         // rally 4 has no shot_count ? last whether asc or desc.
161         expect(sortRallies(RALLIES, { key: "shot_count", dir: "desc" })).map((r) =>
162 r.id)).toEqual([6, 3, 5, 1, 2, 4]);
163         expect(sortRallies(RALLIES, { key: "shot_count", dir: "asc" })).map((r) =>
164 r.id)).toEqual([2, 1, 5, 3, 6, 4]);
165     });
166     it("does not mutate the input array", () => {
167         const ids = RALLIES.map((r) => r.id);
168         sortRallies(RALLIES, { key: "duration", dir: "desc" });
169         expect(RALLIES.map((r) => r.id)).toEqual(ids);
170     });
171 });
172
173 describe("runQuery ? end to end", () => {
174     it("selects every rally over 10s, in chronological order (no sort)", () => {
175         const { ordered, selectedIds } = runQuery(RALLIES, parseQuery("over 10s"));
176         expect(ordered.map((r) => r.id)).toEqual([1, 2, 3, 4, 5, 6]); // unsorted ? input
177         order
178         expect(selectedIds).toEqual([3, 5, 6]); // 21s, 12s, 29s
179     });
180     it("'top 3 longest' sorts all and selects the 3 longest", () => {
181         const { ordered, selectedIds } = runQuery(RALLIES, parseQuery("top 3 longest"));
182         expect(ordered.map((r) => r.id)).toEqual([6, 3, 5, 1, 2, 4]); // all, longest-first
183         expect(selectedIds).toEqual([6, 3, 5]);
184     });
185     it("a shot filter excludes rallies that have no shot_count", () => {
186         const { selectedIds } = runQuery(RALLIES, parseQuery("at least 10 shots"));
187         expect(selectedIds).toEqual([3, 5, 6]); // rally 4 (no shot_count) excluded
188     });
189     it("filter + limit interact (longest 2 of the >10s rallies)", () => {
190         const { selectedIds } = runQuery(RALLIES, parseQuery("over 10s top 2"));
191         expect(selectedIds).toEqual([6, 3]); // sorted longest-first then capped at 2
192     });
193     it("an unrecognized query selects nothing and leaves order untouched", () => {

```

```

189     const { ordered, selectedIds } = runQuery(RALLIES, parseQuery("smashes only"));
190     expect(selectedIds).toEqual([]);
191     expect(ordered.map((r) => r.id)).toEqual([1, 2, 3, 4, 5, 6]);
192   });
193 });
194
195 describe("labels", () => {
196   it("filterLabel renders honest field + symbol + unit", () => {
197     expect(filterLabel({ field: "duration", op: ">", value: 10 })).toBe("length > 10s");
198     expect(filterLabel({ field: "shot_count", op: ">=", value: 8 })).toBe("shots ? 8");
199   });
200   it("sortLabel reads naturally for every key/dir", () => {
201     expect(sortLabel({ key: "duration", dir: "desc" })).toBe("longest first");
202     expect(sortLabel({ key: "duration", dir: "asc" })).toBe("shortest first");
203     expect(sortLabel({ key: "start_time", dir: "desc" })).toBe("newest first");
204     expect(sortLabel({ key: "start_time", dir: "asc" })).toBe("oldest first");
205     expect(sortLabel({ key: "shot_count", dir: "desc" })).toBe("most shots first");
206     expect(sortLabel({ key: "shot_count", dir: "asc" })).toBe("fewest shots first");
207   });
208   it("summarize lists filter, sort and limit clauses", () => {
209     expect(summarize(parseQuery("over 10s top 5"))).toEqual(["length > 10s", "longest first", "top 5"]);
210     expect(summarize(parseQuery("hello"))).toEqual([]);
211   });
212 });
213

```

5. user (2026-06-20T16:34:13.998Z)

```

1   # Interactive per-rally selection ? reel builder (RallyPicker)
2
3   > **Status:** `IN PROGRESS` ? design **APPROVED by owner 2026-06-20**; building the MVP (P1?P5). Downstream milestones (multi-video auth, per-rally preview endpoint, any `/api/compile` default change) remain owner-gated. . **Owner:** Avi . **Created:** 2026-06-20 . **Last updated:** 2026-06-20
4   > **Lifecycle:** `DRAFT ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when DONE)
5   > **Tracking anchors:** $7 progress tracker is the source of truth; indexed in `docs/README.md`; pointer in `NEXT_STEPS.md` + memory `current-state` once work starts.
6   > **Relation:** second major tracked work item in the `khelsutra` repo (peer of `REQUEST_ACCESS_FORM.md`); mirrors the engine repo's `PROJECT_DOC_TEMPLATE` discipline. Primarily realizes alpha screen **A5 Highlights** (engine repo `UI_PROPOSAL.md:47`, exec-plan **M4** `UI_ALPHA_EXECUTION_PLAN.md:39`); its correction-loop extension realizes **A4 Rally Review** (`UI_PROPOSAL.md:46`, exec-plan **M3** `:38`). Consumes the engine's `/api/query` + `/api/compile` contract.
7   > **Honesty note:** every engine-fact claim is tagged `[verified]` (read against engine code this session), `[design]` (proposed here), or `[researched]` (needs sign-off). Not legal/financial advice.
8
9   ---
10
11  ## 0. TL;DR
12  Build the **pick-rallies ? reel** surface as a **hybrid**: a selectable rally **list/grid** is the workhorse; a **deterministic query bar** ("rallies over 10s, longest first") pre-selects into the **same** selection set; a sticky footer compiles the selection into one downloadable MP4. The entire MVP runs on **existing engine endpoints** ? `POST /api/query` ? `POST /api/compile` ? `GET /api/highlights` `[verified backend/main.py:331-340, 342-396, 307-328]` ? with **zero new engine intelligence and zero new endpoints**. The single most important caveat: queries and chips are scoped to **length / count / order / shot-count only**; shot-type, player, and score are **roadmap-only** (no detector, no column) and must not be faked. The biggest UX-vs-effort tension: **no per-rally preview is possible today** ? only the *final compiled reel* can stream ? so MVP selects on text metadata, and visual preview/timeline is a deliberate later milestone.
13
14  ## 1. Problem & goal

```

15 Today the alpha can detect rallies and stitch a reel, but reel-building is either a
 silent `stitching.min\_shot\_count` threshold `[verified backend/main.py:362-383]` or a static
 checkbox list whose data plumbing is even broken ? the bundled static UI reads `data.rallies`
 while the API returns `play\_segments`, so it renders nothing `[verified
 backend/api/static/app.js:344 vs backend/main.py:340]`. The owner's framing is **dynamic per-
 video selection, not a fixed threshold**: a coach should say "give me the long rallies from this
 session" and get exactly those, then fine-tune by hand.

16

17 **The concrete outcome ("good")**: A coach uploads a 40-minute session; the engine finds
 60 rallies. They type "top 15 longest", eyeball the auto-selected cards, untick two warm-up
 rallies, name it "Tuesday ? long points", and download a ~6-minute reel ? without learning any
 threshold knob.

18

19 **Goal**: the smallest *honest* surface that turns engine-detected rallies into a user-
 curated, downloadable reel, with both **fast** (query) and **precise** (checkbox) selection
 sharing **one** state.

20

21 **Non-goals (alpha)**: no conversational LLM (`UI\_PROPOSAL.md:66` defers it); no shot-
 type/player/score filters (no data exists); no per-rally video preview while it requires unbuilt
 streaming; no multi-tenant auth (single-box alpha).

22

23 ## 2. Decisions locked

24 | # | Decision | Source / date | Implication |

25 |---|-----|-----|-----|

26 | D1 | Dominant surface = selectable rally **list/grid** | Synthesis 2026-06-20 (Grid
 scored 15, fit-to-data 4) | Scales to long matches via bulk+filter; shows honest fields only |

27 | D2 | Fast entry = **deterministic** client-side `parseQuery()` (no LLM) | `[verified
 UI_PROPOSAL.md:66]` conversational QA deferred | Predictable, unit-testable, offline, zero API
 cost |

28 | D3 | **One** shared `Set<segment\_id>`, mutated by query + checkbox + (future) timeline
 | Synthesis 2026-06-20 | No second compile path can diverge from what the user sees |

29 | D4 | Compile via existing `POST /api/compile {video\_id, segment\_ids, output\_filename}`
 | `[verified backend/main.py:342-396]` | Selection order is harmless ? sticher
 `\_merge\_overlapping` de-dupes `[verified compiler.py:80-105, 311-317]` |

30 | D5 | Query grammar (alpha) = length, count, order, **shot_count only** | `[verified
 database.py:122-135, gemini.py:470-485]` | Only fields the payload actually returns; grey out
 the rest |

31 | D6 | MVP backend = **zero new endpoints** | `[verified]` reuse map (§4) | Ships the
 full loop on the already-shipped contract |

32 | D7 | Replace the silent `min\_shot\_count` cut with **explicit user selection** | Owner
 framing + `[verified main.py:362-383]` | UI *warns* about the floor; it never hides why a rally
 vanished |

33 | D8 | **Default selection = ON** (curate-by-removal) | Owner 2026-06-20 | Rallies load
 all-selected (matches today's "all rallies" reel); user removes warm-ups. Footer/empty UX
 assumes a non-empty start |

34 | D9 | **Preview-before-select is NOT a ship-blocker** for the MVP | Owner 2026-06-20 |
 MVP selects on text metadata + previews the *final compiled reel*; the source/clip-stream
 endpoint (per-rally preview) is the next milestone (P9), not MVP |

35 | D10 | **MVP is job-tethered** (carry `result.video\_id`); no `GET /api/videos` | Owner
 2026-06-20 | Smallest honest slice; multi-video home + identity scoping is P8 (gated) |

36 | D11 | `min\_shot\_count`: **warn, do NOT override** in the MVP | Owner 2026-06-20 | The
 UI surfaces the floor; an explicit-selection override of the compile default is deferred (would
 trigger the Launch Report convention) |

37

38 ## 3. Foundation ? what the engine gives us today `[verified this session]`

39 The whole design rests on the engine's real, already-shipped contract. Read against the
 engine repo (`badminton-highlight-indexer`):

40

41 - **The rally store is `play\_segments`** ? columns `id, video_id, start_time, end_time,
 duration, server, receiver, metadata` `[verified database.py:124-135]`. `id` is the integer the
 UI selects and passes to compile; `start\_time/end\_time/duration` are REAL seconds (duration
 computed at insert).

42 - **Listing rallies = `POST /api/query {video\_id}` ? `{play\_segments:[...]}`** ? the
 only rally-list path today; it JSON-parses `metadata` and joins `events` `[verified
 main.py:331-340, database.py:427-475]`.

```

43     - **Building a reel = `POST /api/compile {video_id, segment_ids:[int],
output_filename}` ** ? loads `videos.filepath`, filters all segments to the requested
`segment_ids`, applies the `min_shot_count` floor, extracts `time_pairs=[(start,end)]`, and
calls `VideoCompiler.compile_highlights(raw_path, segments, name)` [verified main.py:342-396,
compiler.py:303], which **merges overlaps** then per-clip re-encodes ? concat ? one MP4
[verified compiler.py:311-317]. Selection order/duplicates are therefore safe.
44     - **Downloading = `GET /api/highlights/{video_id}/{filename}` ** ? streams the compiled
MP4. Compile returns a **server-local filepath, NOT a URL** [verified main.py:394], so the SPA
constructs this download URL itself. The compiled reel is the **only streamable video that
exists today** [verified main.py:307-328].
45     - **The floor knob is readable** ? `GET /api/config` exposes `stitching.min_shot_count`
[verified main.py:121-123], so the UI can warn before a selected rally is silently dropped.
46     - **Job entry** ? `GET /api/jobs/{job_id}` returns `result.video_id` [verified
main.py:274-293], which is how the MVP reaches a video without a (nonexistent) list-videos
endpoint.
47
48     **Honest fields vs fabricated/roadmap (critical for the UI):**
49     - **Honest today** (default `default_segmenter: "gemini"`, per `config.json`
[verified]): `start_time`, `end_time`, `duration`, and `metadata.shot_count` (Gemini's
`shuttle_exchange_count`, fallback `max(3, int(dur/0.8))`) + `metadata.shot_count_confidence` (a
**string**, often `Unknown`) [verified gemini.py:470-485]. On the gemini path
`server`/`receiver` are written `None` ("no fabricated data") [verified gemini.py:480-487].
50     - **Fabricated ? do NOT surface:** the `motion` demo segmenter fills `server`/`receiver`
via `random.sample(...)` , a random `shot_count`, and random `events` (serve/smash/foul/winner)
[verified motion.py:191-198]. `query` returns these columns + `events`, but they are not
ground truth and must stay hidden.
51     - **Roadmap ? no column, no detector:** shot-type per shot, player identity, match/point
score, game/set grouping. None exist anywhere in the schema; do not consume them [verified
database.py whole-schema 122-148].
52     - **Correction-loop columns exist but are dead:**
`candidate_segments.human_label/notes/confirmed_segment_id` are defined but no endpoint writes
them [verified database.py:166-168] ? that's the M4 corpus extension (engine PR-4/B6,
`UI_ALPHA_EXECUTION_PLAN.md`).
53
54     ## 4. Design / architecture
55
56     **Reuse map (existing ? [verified], no change for MVP):** `POST /api/query` (list) ?
`POST /api/compile` (stitch) ? `GET /api/highlights/{video_id}/{filename}` (download); `GET
/api/config` (floor) ; `GET /api/jobs/{id}` (carry `result.video_id`). **All net-new code is the
SPA** in `khelsutra` `web/` (Vite + React + TS + Tailwind, per `web/README.md`), plus a small
set of *optional* real-gap engine enablers (§4.3) ? none required for MVP.
57
58     **4.1 Components (net-new SPA)**
59     - **QueryBar + `parseQuery()`** ? a *pure, deterministic, unit-tested* string ?
`{filter, sort}` compiler over `duration` / `ordinal` / `shot_count`. Renders a **parsed-pill**
("filter: duration > 10s · sort: duration desc") so the interpretation is transparent and hand-
correctable; greys out shot-type/player/score tokens with an inline "not available yet". No LLM,
no network call.
60     - **RallyList/Grid** ? one card per `play_segment`: ordinal (by `start_time`), `mm:ss`
start, duration (`end?start`), and a shot-count + confidence chip **only when
`metadata.shot_count` is present** (absent on detector paths that don't write it). Checkbox per
card; the thumbnail area is a placeholder (no endpoint yet).
61     - **`useRallySelection()` hook** ? owns `selectedIds:Set<number>`, `displayOrder`,
`apply(queryResult)`, `toggle(id)`, and bulk Select-all / Clear / Invert. Unit-tested (matches
the exec-plan's "API client + review-state logic" bar).
62     - **SelectionFooter (sticky)** ? live "N clips / total M:SS"; a **`min_shot_count`
warning** when a selected rally would be dropped at compile (read from `GET /api/config`); reel-
name input; one **Build** button.
63     - **CompileResult** ? <video src=GET /api/highlights/...> preview of the *compiled
reel* + a download link.
64     - **TypedApiClient** ? `query`, `compile`, `buildDownloadUrl`; the typed seam to the
engine.
65
66     **4.2 Data flow** [verified anchors inline]
67     Gemini segmenter (process time) writes `play_segments {id, start/end_time, duration,
```

```

metadata.shot_count/confidence/detector}` `[gemini.py:461-498]`
68     ? SPA `POST /api/query {video_id}` ? `{play_segments:[...]}` `[main.py:331-340]`
(**fix** the static UI's `data.rallies` read ? `play_segments` `[app.js:344]`)
69     ? normalize to `RallyCard[]` + one shared `selectedIds:Set`;
`server`/`receiver`/`events` are present in the payload but motion-only fabrications ? **not
surfaced** `[motion.py:191-198]`
70     ? all input modes mutate the **same** `selectedIds`: (a) `parseQuery()` predicate over
duration/ordinal/shot_count; (b) checkbox toggle + bulk ops; (c) *(post-MVP)* timeline band
71     ? footer recomputes count + ?duration **client-side**, and warns for any selected rally
with `shot_count < stitching.min_shot_count` `[main.py:362-383]`
72     ? **Build** ? `POST /api/compile {video_id, segment_ids: [...selectedIds],
output_filename}` ? stitcher de-dupes via `_merge_overlapping` `[compiler.py:311-317]`, cuts
`time_pairs` from `videos.filepath`, re-encodes per clip ? concat ? one MP4 `[main.py:386-393,
compiler.py:303]`
73     ? compile returns a **server-local filepath, not a URL** `[main.py:394]` ? SPA builds
`GET /api/highlights/{video_id}/{output_filename}` to preview in `` + download
`[main.py:307-328]`.
74
75     **4.3 Engine API additions (none for MVP; tagged against real gaps)**
76     | Endpoint | Purpose | Status |
77     |---|---|---|
78     | `POST /api/query` | List rallies (only path) ? fix SPA to read `play_segments` |
**exists** |
79     | `POST /api/compile` | Stitch selected `segment_ids` ? MP4 | **exists** |
80     | `GET /api/highlights/{video_id}/{filename}` | Stream/download compiled reel |
**exists** |
81     | `GET /api/config` | Read `stitching.min_shot_count` for the warning | **exists** |
82     | `GET /api/jobs/{job_id}` | Carry `result.video_id` into the picker | **exists** |
83     | `POST /api/compile` ? add `download_url` | Return `/api/highlights/...` so SPA stops
hand-building it (additive, low-risk; today returns only a filepath `main.py:394`) | **modify**
|
84     | `GET /api/health` | Engine-offline banner ping the SPA is specified to use
(`HOSTING_PLAN.md:42`) | **new** |
85     | `GET /api/videos/{video_id}/rallies` | RESTful/cacheable alias returning the same
`{play_segments}` shape | **new** |
86     | `GET /api/videos` | List a user's videos for a Match picker (only `get_video(id)`
exists, `database.py:418`) ? needs DB enumerate + identity scoping | **new** |
87     | `GET /api/videos/{video_id}/source` (Range) *or* `/clip?start=&end=` | Stream
source/per-span video so a rally previews before selection ? neither exists | **new** |
88     | `GET /api/videos/{video_id}/rallies/{segment_id}/thumbnail` | Per-rally poster still
(no thumbnail column; WASB frames are transient) | **new** |
89     | `PATCH /api/segments/{id}` | Persist accept/reject/nudge ?
`candidate_segments.human_label/notes/...` (columns exist, unwritten ? corpus loop) | **new** |
90
91     **? Dead-ends / do-NOT:** never surface `server`/`receiver`/`events` (motion-only
randoms `[motion.py:191-198]`); never consume shot-type/player/score (no data); never render a
confidence **meter** ? `shot_count_confidence` is a Gemini *string* (often `Unknown`) and
`play_segments` has **no** numeric confidence column.
92
93     ## 5. Risk table
94     | Risk | Severity | Mitigation |
95     |---|---|---|
96     | **No source/clip/frame/thumbnail endpoint** ? only compiled reels stream
`[main.py:307-328]` | High (UX) | MVP selects on text metadata + previews the *final* reel;
preview/timeline deferred to M3 behind a new endpoint |
97     | `min_shot_count` silently drops selected rallies `[main.py:362-383]` | High (looks
broken) | Footer warns *before* Build; D7 makes selection explicit; an override is an owner gate
(Launch-Report-worthy `[memory: launch-report-convention]`) |
98     | No match-duration field ? a timeline must derive `total = max(end_time)`, mis-
rendering pre/post dead air | Med | Timeline deferred to M3; never over-promise it as a true
scrubber until source streams |
99     | `shot_count` is an *estimate* (`shuttle_exchange_count` w/ `max(3,int(dur/0.8))`
fallback) `[gemini.py:470-485]` | Med | Label "approx."; confidence shown as the raw string, not
a meter |
100    | No auth / user scoping anywhere (CORS `*`, `videos.user_id` never set/filtered) | High

```

for multi-tester | Fine for single-box local alpha; a ship-blocker for any shared host ? gate
`GET /api/videos` behind PR-3 scoping |

101 | compile returns a filepath not a URL `[main.py:394]` | Low | Client builds the URL for MVP; `download\_url` field (M1) removes the brittleness |

102 | Surface sprawl (query + grid + future timeline + future correction) | Med | Deliberate IA: query+grid = one screen; correction = separate ? corpus screen (owner call, \$8) |

103

104 ## 6. Honest limits ? what this does NOT do

105 A green SPA build + passing `parseQuery`/selection unit tests prove the **picker logic only** ? **not** that the engine's rally boundaries are correct (the measured **rally-END** weakness is a separate quality track, unaffected by this UI). "Conversational" here means a **deterministic four-dimension parser**, not natural-language understanding. Nothing is implemented in `web/` yet ? this is `[design]`. The feature curates *what the engine already found*; it cannot surface a rally the detector missed, nor split/merge a mis-bounded one (that's the M4 correction loop).

106

107 ## 7. Deliverables & progress tracker ? **source of truth**

108 Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**, branched from `origin/master`, no stacking. CI (`npm test`) must stay green; merge to `master` auto-deploys the site (docs/`web/` changes don't touch the live `site/` Worker).

109

ID	Deliverable	Depends on	Gated?	Status	PR
P0	This design doc + `docs/README.md` + `NEXT_STEPS.md` pointers				
P1	SPA scaffold (Vite+React+TS+Tailwind) in `web/` + typed API client; dev proxy to engine `:8000`	P0	No		
P2	RallyList/Grid (honest fields only) + `useRallySelection()` hook (unit-tested)	P1	No		
P3	`parseQuery()` + parsed-pill + example chips (unit-tested; greys out unavailable tokens)	P2	No		
P4	SelectionFooter + `min_shot_count` warning (from `GET /api/config`)	P2	No		
P5	Build ? `POST /api/compile` ? client-built download URL + ` <video>` preview of the reel</video>	P2	No		
P6	*(engine repo)* `GET /api/health` + offline banner; `/api/compile` returns `download_url`		No		
P7	*(engine repo)* `GET /api/videos/{id}/rallies` RESTful alias		No		
P8	*(engine repo)* `GET /api/videos` + PR-3 identity scoping ? A1 Matches screen	P7			
P9	*(engine repo)* source/clip stream + timeline + per-rally preview/thumbnail	P8			
P10	*(engine repo)* `PATCH /api/segments/{id}` corpus loop (PR-4/B6) ? A4 Rally Review	P9			

123

124 **Milestone rollout:** **M0/MVP = P1?P5** (pick?reel on existing API, zero new engine endpoints) · **M1 = P6?P7** (RESTful + reliability polish) · **M2 = P8** (multi-video home) · **M3 = P9** (per-rally preview/timeline) · **M4 = P10** (corpus correction loop) · **M5** = swap `parseQuery()` for localized NL behind the same seam (gated on shot/player data landing).

125

126 ## 8. Open questions ? owner / external

127 **Blocking gates ? ? RESOLVED 2026-06-20 (owner) ? see D8?D11 in \$2:**

128 1. ~~Default selection ON vs OFF?~~ ? **ON / curate-by-removal** (D8).

129 2. ~~Is preview-before-select a ship-blocker?~~ ? **No** ; text-metadata MVP, preview is P9 (D9).

130 3. ~~Job-tethered vs multi-video MVP?~~ ? **Job-tethered** (D10).

131 4. ~~`min\_shot\_count` override?~~ ? **Warn, don't override** in MVP (D11).

132

133 **Still open (nice-to-knows, non-blocking):**

134 5. May user-facing copy call `parseQuery()` "conversational", given conversational QA is explicitly deferred (`UI\_PROPOSAL.md:66`)? Risk of over-promising NL. *Owner positioning/honesty call.* (Lean: avoid the word; show the parsed-pill instead.)*

135 6. One screen for query+grid (recommended) vs a separate ? corpus/correction screen for A4? *Owner positioning call.*

136

```

137     ## 9. Definition of done
138     - [ ] From a finished job, a user can list rallies, query/select, and download a reel ?
on **existing** endpoints.
139     - [ ] Only honest fields (ordinal / duration / shot_count+confidence-when-present) are
shown; fabricated `server`/`receiver`/`events` are hidden.
140     - [ ] `parseQuery()` covers length/count/order/shot_count, greys out unavailable tokens,
shows a visible parsed-pill, and is unit-tested.
141     - [ ] Selection hook is unit-tested; the `min_shot_count` floor is surfaced, not hidden.
142     - [ ] `npm run build` (and `npm test`) clean; the static UI's `data.rallies` bug is gone
(or the static UI is superseded by the SPA).
143     - [ ] $7 tracker + this DoD updated; doc archived when P1?P5 land (MVP).
144
145     ## 10. References
146     **Engine code anchors `[verified this session]`:** `backend/main.py:121-123` (config),
`:274-293` (jobs), `:307-328` (highlights download), `:331-340` (query), `:342-396` (compile +
`min_shot_count` floor + filepath-not-URL); `backend/infrastructure/database.py:124-135`
(play_segments), `:166-168` (dead correction columns), `:418` (no list-videos), `:427-475`
(query read path + events join); `backend/pipeline/segmenters/gemini.py:461-498, 470-485`
(honest shot_count, server/receiver=None); `backend/pipeline/segmenters/motion.py:191-198`
(fabricated fields); `backend/pipeline/stitcher/compiler.py:80-105, 303, 311-317` (merge/de-dupe
+ entypoint); `backend/api/static/app.js:344` (`data.rallies` bug); `config.json`
(`default_segmenter: "gemini"`).
147     **Engine docs:** `UI_PROPOSAL.md:46-47, 66`; `UI_ALPHA_EXECUTION_PLAN.md:38-39`;
`HOSTING_PLAN.md:42`; `OWNED_MODEL_IMPLEMENTATION_PLAN.md:54-55` (conversational seam built now,
model punted). **This repo:** `web/README.md`, `REQUEST_ACCESS_FORM.md`.
148
149     ---
150     ### Changelog
151     - 2026-06-20 ? Initial `DRAFT`. Consolidated three candidate designs (Timeline / Grid /
RallyPicker) into the hybrid recommendation via a multi-agent design pass; every engine-fact
anchor re-verified against source before writing.
152     - 2026-06-20 ? Owner **approved** the recommendations; locked D8?D11 (default ON ·
preview not a ship-blocker · job-tethered MVP · warn-don't-override the floor); status `DRAFT` ?
IN PROGRESS`; P0 done.
153

```

6. assistant (2026-06-20T16:34:16.536Z)

Now let me read the remaining files to check for reuse opportunities and consistency with established P1/P2 patterns.

7. user (2026-06-20T16:34:17.022Z)

```

1      // The fast-entry query bar (PER_RALLY_SELECTION.md P3). A deterministic, OFFLINE parser
turns
2      // plain text ("top 15 longest", "over 10s") into a selection over the SAME shared set
the
3      // checkboxes use. It is honest by construction: a live "parsed-pill" shows exactly how
the
4      // text was understood, and concepts with no data behind them (shot-type / player /
score) are
5      // greyed out as "not available yet" ? never silently faked.
6      import { useMemo, useState } from "react";
7      import type { FormEvent } from "react";
8      import { parseQuery, summarize } from "../lib/query";
9      import type { ParsedQuery } from "../lib/query";
10
11      interface Props {
12          /** Apply a parsed query to the rally set (App runs runQuery + writes the shared
selection). */
13          onApply: (q: ParsedQuery) => void;
14      }
15
16      // Each example is a real, parseable query ? tapping one fills the box AND applies it.
17      const EXAMPLES = ["over 10s", "top 15 longest", "shortest first", "at least 8 shots",

```

```

"first 10"]];
18
19     const CHIP = "rounded-full px-2.5 py-0.5 text-xs font-medium";
20
21     export function QueryBar({ onApply }: Props) {
22         const [value, setValue] = useState("");
23         const parsed = useMemo(() => parseQuery(value), [value]);
24         const clauses = summarize(parsed);
25         const typed = value.trim().length > 0;
26
27         const applyText = (text: string) => {
28             setValue(text);
29             onApply(parseQuery(text));
30         };
31         const submit = (e: FormEvent) => {
32             e.preventDefault();
33             if (parsed.recognized) onApply(parsed);
34         };
35
36         return (
37             <div>
38                 <form onSubmit={submit} className="flex flex-wrap items-center gap-2">
39                     <input
40                         type="text"
41                         value={value}
42                         onChange={(e) => setValue(e.target.value)}
43                         placeholder="e.g. over 10s · top 15 longest · at least 8 shots"
44                         aria-label="Filter rallies by length, count or order"
45                         className="min-w-[16rem] flex-1 rounded-xl border border-black/15 bg-white
px-4 py-2 text-sm text-ink outline-none focus:border-green"
46                     />
47                     <button
48                         type="submit"
49                         disabled={!parsed.recognized}
50                         className="rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40"
51                     >
52                         Apply
53                     </button>
54                 </form>
55
56                 { /* Live interpretation ? transparent + hand-correctable (no hidden NL guessing).
*/ }
57                 <div aria-live="polite" data-testid="query-pill" className="mt-2 flex flex-wrap
items-center gap-1.5">
58                     {clauses.map((c) => (
59                         <span key={c} className={CHIP + " bg-green/15 text-green">
60                             {c}
61                         </span>
62                     ))}
63                     {parsed.unavailable.map((u) => (
64                         <span
65                             key={u.token}
66                             title={`"${u.token}" needs ${u.kind} detection ? not available yet`}
67                             className={CHIP + " bg-black/5 text-ink/45"}
68                         >
69                             <span className="line-through">{u.token}</span> · not available yet
70                         </span>
71                     ))}
72                     {typed && !parsed.recognized && parsed.unavailable.length === 0 && (
73                         <span className="text-xs text-ink/50">Couldn't read that ? try ?over 10s? or
?top 15 longest?</span>
74                     )}
75                     {!typed && <span className="text-xs text-ink/50">Type a quick filter, or tap an
example.</span>}

```

```

76         </div>
77
78         <div className="mt-3 flex flex-wrap gap-2 text-sm">
79             <span className="text-ink/40">Try:</span>
80             {EXAMPLES.map((ex) => (
81                 <button
82                     key={ex}
83                     type="button"
84                     onClick={() => applyText(ex)}
85                     className="rounded-full border border-black/15 px-3 py-1 text-xs
86                     hover:border-green"
87                     >
88                         {ex}
89                     </button>
90                 )}}
91             </div>
92         </div>
93     );
94 }

```

8. user (2026-06-20T16:34:17.503Z)

```

1     import { useMemo, useState } from "react";
2     import { useRallySelection } from "../hooks/useRallySelection";
3     import { RallyGrid } from "../components/RallyGrid";
4     import { QueryBar } from "../components/QueryBar";
5     import { mmss, pluralize } from "../lib/format";
6     import { runQuery, type ParsedQuery } from "../lib/query";
7     import { log } from "../lib/log";
8     import type { RallySegment } from "../api/types";
9
10    // Demo data until the picker is wired to the engine (POST /api/query) in the MVP flow
11    (P5).
12    // Shape matches the verified play_segments contract; only honest fields are shown.
13    const DEMO_RALLIES: RallySegment[] = [
14        { id: 1, start_time: 12, end_time: 20, duration: 8, server: null, receiver: null,
15        metadata: { shot_count: 9, shot_count_confidence: "High" } },
16        { id: 2, start_time: 41, end_time: 47, duration: 6, server: null, receiver: null,
17        metadata: { shot_count: 5 } },
18        { id: 3, start_time: 63, end_time: 84, duration: 21, server: null, receiver: null,
19        metadata: { shot_count: 19, shot_count_confidence: "Medium" } },
20        { id: 4, start_time: 95, end_time: 101, duration: 6, server: null, receiver: null,
21        metadata: {} },
22        { id: 5, start_time: 130, end_time: 142, duration: 12, server: null, receiver: null,
23        metadata: { shot_count: 11 } },
24        { id: 6, start_time: 158, end_time: 187, duration: 29, server: null, receiver: null,
25        metadata: { shot_count: 24, shot_count_confidence: "High" } },
26    ];
27
28    export default function App() {
29        const sel = useRallySelection(DEMO_RALLIES, "all");
30        // Display order is separate from selection: a query can re-sort the cards while the
31        shared
32        // selection set (sel) stays the single source of truth for what lands in the reel.
33        const [order, setOrder] = useState<RallySegment[]>(DEMO_RALLIES);
34
35        // Stable chronological ordinal (by start_time) so re-sorting never rennumbers a rally.
36        const ordinalOf = useMemo(() => {
37            const m = new Map<number, number>();
38            [...DEMO_RALLIES].sort((a, b) => a.start_time - b.start_time).forEach((r, i) =>
39            m.set(r.id, i + 1));
40            return (id: number) => m.get(id) ?? 0;
41        }, []);
42    }

```

```

34     const onApplyQuery = (q: ParsedQuery) => {
35         if (!q.recognized) {
36             log("info", "query.skip", { raw: q.raw, unavailable: q.unavailable.map((u) =>
u.token) });
37             return; // empty / unparseable ? leave the user's curation untouched
38         }
39         const { ordered, selectedIds } = runQuery(DEMO_RALLIES, q);
40         setOrder(ordered);
41         sel.apply(selectedIds);
42         log("info", "query.apply", {
43             filters: q.filters.length,
44             sort: q.sort ? `${q.sort.key}:${q.sort.dir}` : null,
45             limit: q.limit ?? null,
46             selected: selectedIds.length,
47         });
48     };
49
50     return (
51         <main className="min-h-screen bg-paper text-ink pb-24">
52             <header className="bg-ink text-white">
53                 <div className="mx-auto flex max-w-5xl items-center gap-1 px-6 py-4">
54                     <span className="text-xl font-extrabold tracking-tight">
55                         Khel<span className="text-green">?</span>Sutra <span className="font-
semibold text-lime">Studio</span>
56                     </span>
57                 </div>
58             </header>
59
60             <section className="mx-auto max-w-5xl px-6 py-10">
61                 <span className="inline-flex rounded-full bg-green/15 px-3 py-1 text-xs font-
semibold text-green">
62                     per-rally selection · P3
63                 </span>
64                 <h1 className="mt-4 text-3xl font-extrabold tracking-tight">Pick the rallies for
your reel</h1>
65                 <p className="mt-2 max-w-2xl text-ink/70">
66                     Type a quick filter like <em>?top 15 longest?</em>, then fine-tune by tapping
cards. Everything starts{" "}
67                     <strong>selected</strong> ? just drop the ones you don't want.{" "}
68                     <span className="text-ink/50">(Demo data; the live list comes from the
engine.)</span>
69                 </p>
70
71                 <div className="mt-6">
72                     <QueryBar onApply={onApplyQuery} />
73                 </div>
74
75                 <div className="mt-6 flex flex-wrap gap-2 text-sm">
76                     <button type="button" onClick={sel.selectAll} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">Select all</button>
77                     <button type="button" onClick={sel.clearAll} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">Clear</button>
78                     <button type="button" onClick={sel.invert} className="rounded-full border
border-black/15 px-3 py-1 hover:border-green">Invert</button>
79                 </div>
80
81                 <div className="mt-5">
82                     <RallyGrid rallies={order} isSelected={sel.isSelected} onToggle={sel.toggle}
ordinalOf={ordinalOf} />
83                 </div>
84             </section>
85
86             <footer className="fixed inset-x-0 bottom-0 border-t border-black/10 bg-white/95
backdrop-blur">
87                 <div className="mx-auto flex max-w-5xl items-center gap-4 px-6 py-3">

```

```

88         <span className="text-sm text-ink/80" data-testid="selection-summary">
89             <strong className="text-ink">{pluralize(sel.count, "rally",
"rallies")}</strong> selected · {mmss(sel.totalSec)} total
90         </span>
91         <button
92             type="button"
93             disabled={sel.count === 0}
94             title="Reel building wires up in P5"
95             className="ml-auto rounded-full bg-green px-5 py-2 text-sm font-semibold
text-[#04140D] disabled:opacity-40"
96         >
97             Build reel ({sel.count})
98         </button>
99     </div>
100 </footer>
101 </main>
102 );
103 }
104

```

9. user (2026-06-20T16:34:18.462Z)

```

1 // React state wrapper over the pure selection helpers in lib/selection.ts.
2 // Default = ALL selected (D8: curate-by-removal) ? the user removes warm-ups.
3 import { useCallback, useMemo, useState } from "react";
4 import type { RallySegment } from "../api/types";
5 import * as sel from "../lib/selection";
6
7 export function useRallySelection(rallies: RallySegment[], initial: "all" | "none" =
"all") {
8     const [selected, setSelected] = useState<Set<number>>>(() =>
9         initial === "none" ? sel.clear() : sel.selectAll(rallies),
10     );
11
12     const toggle = useCallback((id: number) => setSelected((s) => sel.toggle(s, id)), []);
13     const selectAll = useCallback(() => setSelected(sel.selectAll(rallies)), [rallies]);
14     const clearAll = useCallback(() => setSelected(sel.clear()), []);
15     const invert = useCallback(() => setSelected((s) => sel.invert(s, rallies)),
[rallies]);
16     const isSelected = useCallback((id: number) => selected.has(id), [selected]);
17     /** Replace the whole selection (the query bar writes the shared set here ? D3). */
18     const apply = useCallback((ids: Iterable<number>) => setSelected(new Set(ids)), []);
19
20     const totalSec = useMemo(() => sel.selectedDurationSec(rallies, selected), [rallies,
selected]);
21
22     return { selected, count: selected.size, totalSec, isSelected, toggle, selectAll,
clearAll, invert, apply };
23 }
24

```

10. user (2026-06-20T16:34:18.935Z)

```

1 // The selectable rally grid ? one card per play_segment, HONEST fields only:
2 // ordinal (by start order), mm:ss start, duration, and a shot-count chip ONLY when
present.
3 // Never renders server/receiver/events (motion-only fabrications,
PER_RALLY_SELECTION.md §4).
4 import type { RallySegment } from "../api/types";
5 import { mmss } from "../lib/format";
6
7 interface Props {
8     rallies: RallySegment[];
9     isSelected: (id: number) => boolean;
10     onToggle: (id: number) => void;

```

```

11     /** Stable chronological label for a rally (by start_time), so re-sorting via a query
12     * doesn't renumber the cards. Falls back to display position when absent. */
13     ordinalOf?: (id: number) => number;
14 }
15
16 export function RallyGrid({ rallies, isSelected, onToggle, ordinalOf }: Props) {
17     if (rallies.length === 0) {
18         return <p className="text-ink/60 text-sm">No rallies to show yet.</p>;
19     }
20     return (
21         <ul className="grid grid-cols-[repeat(auto-fill,minmax(150px,1fr))] gap-3 list-none
p-0 m-0">
22             {rallies.map((r, i) => {
23                 const selected = isSelected(r.id);
24                 const n = ordinalOf ? ordinalOf(r.id) : i + 1;
25                 const shot = r.metadata?.shot_count;
26                 const conf = r.metadata?.shot_count_confidence;
27                 return (
28                     <li key={r.id}>
29                         <button
30                             type="button"
31                             onClick={() => onToggle(r.id)}
32                             aria-pressed={selected}
33                             aria-label={`Rally ${n}${selected ? ", in reel" : ", not in reel"}`}
34                             className={
35                                 "w-full text-left rounded-xl border p-3 transition " +
36                                 (selected
37                                     ? "border-green bg-green/10"
38                                     : "border-black/10 bg-white hover:border-green/60")
39                             )
40                         >
41                             <div className="flex items-center justify-between">
42                                 <span className="font-semibold text-ink">Rally {n}</span>
43                                 <span
44                                     aria-hidden="true"
45                                     className={
46                                         "inline-flex h-5 w-5 items-center justify-center rounded-full text-
xs " +
47                                         (selected ? "bg-green text-[#04140D]" : "border border-black/20
text-transparent")
48                                     }
49                                 >
50                                     ?
51                                 </span>
52                             </div>
53                             <div className="mt-1 text-sm text-ink/70">
54                                 {mmss(r.start_time)} · {mmss(r.duration)}
55                             </div>
56                             {typeof shot === "number" && (
57                                 <div className="mt-2 inline-block rounded-full bg-paper px-2 py-0.5
text-xs text-ink/70">
58                                     ~{shot} shots{conf && conf !== "Unknown" ? ` · ${conf}` : ""}
59                                 </div>
60                             )}
61                         </button>
62                     </li>
63                 );
64             })}
65         </ul>
66     );
67 }
68

```

```

1      // Types mirror the engine's verified contract (badminton-highlight-indexer).
2      // Anchors: backend/infrastructure/database.py:124-135 (play_segments),
3      // backend/main.py:331-396 (query/compile), :307-328 (highlights), :121 (config).
4
5      export interface RallyMetadata {
6          /** Gemini's shuttle_exchange_count (fallback max(3, dur/0.8)); absent on some
detectors. */
7          shot_count?: number;
8          /** Gemini confidence STRING (often "Unknown") ? not a numeric meter. */
9          shot_count_confidence?: string;
10         detector?: string;
11         [key: string]: unknown;
12     }
13
14     export interface RallySegment {
15         /** The integer the UI selects and passes to /api/compile as segment_ids. */
16         id: number;
17         start_time: number;
18         end_time: number;
19         duration: number;
20         /** motion-segmenter FABRICATION (random) ? DO NOT surface (see
PER_RALLY_SELECTION.md). */
21         server: string | null;
22         /** motion-segmenter FABRICATION (random) ? DO NOT surface. */
23         receiver: string | null;
24         metadata: RallyMetadata;
25         /** motion-only fabricated sub-events ? DO NOT surface. */
26         events?: unknown[];
27     }
28
29     export interface QueryResponse {
30         play_segments: RallySegment[];
31     }
32
33     export interface CompileResponse {
34         status: string;
35         /** server-local path (NOT a URL) ? build the download URL with highlightUrl(). */
36         filepath: string;
37     }
38
39     export interface EngineConfig {
40         stitching?: {
41             /** The shot-count floor /api/compile silently enforces ? surface it, don't hide it.
*/
42             min_shot_count?: number;
43             [key: string]: unknown;
44         };
45         [key: string]: unknown;
46     }
47

```

12. assistant (2026-06-20T16:34:22.129Z)

Now let me look at the lib/format.ts and lib/selection.ts to check for reuse opportunities and consistency.

13. user (2026-06-20T16:34:23.054Z)

```

1      // Small pure formatters (node-testable, no React).
2
3      /** Seconds ? "m:ss" (e.g. 65 ? "1:05"). Rounds to the nearest second; clamps negatives
to 0. */
4      export function mmss(totalSeconds: number): string {
5          const s = Math.max(0, Math.round(totalSeconds || 0));
6          const m = Math.floor(s / 60);

```

```

7     return `${m}:${String(s % 60).padStart(2, "0")}`;
8 }
9
10 /** "3 rallies" / "1 rally" ? count with a correctly pluralized noun. */
11 export function pluralize(n: number, one: string, many = one + "s"): string {
12     return `${n} ${n === 1 ? one : many}`;
13 }
14

```

14. user (2026-06-20T16:34:23.458Z)

```

1 // Pure selection logic over a set of rally ids (no React ? node-testable).
2 // One shared Set<segment_id> is the source of truth; the query bar, checkboxes, and
3 // (future) timeline all mutate THIS via these helpers (PER_RALLY_SELECTION.md §4).
4 import type { RallySegment } from "../api/types";
5
6 export type Selection = ReadonlySet<number>;
7
8 export const idsOf = (rallies: RallySegment[]): number[] => rallies.map((r) => r.id);
9
10 /** Toggle one id (returns a NEW set ? never mutates the input). */
11 export function toggle(sel: Selection, id: number): Set<number> {
12     const next = new Set(sel);
13     if (next.has(id)) next.delete(id);
14     else next.add(id);
15     return next;
16 }
17
18 export const selectAll = (rallies: RallySegment[]): Set<number> => new
Set(idsOf(rallies));
19 export const clear = (): Set<number> => new Set();
20
21 /** Select exactly the rallies NOT currently selected. */
22 export const invert = (sel: Selection, rallies: RallySegment[]): Set<number> =>
23     new Set(idsOf(rallies).filter((id) => !sel.has(id)));
24
25 export const selectedRallies = (rallies: RallySegment[], sel: Selection): RallySegment[]
=>
26     rallies.filter((r) => sel.has(r.id));
27
28 /** Total play-time (seconds) of the selected rallies ? what the reel will run to. */
29 export const selectedDurationSec = (rallies: RallySegment[], sel: Selection): number =>
30     selectedRallies(rallies, sel).reduce((acc, r) => acc + (r.duration || 0), 0);
31

```

15. assistant (2026-06-20T16:34:26.474Z)

Now I have a complete picture. Let me verify a few specific behaviors in the parser by examining edge cases carefully, then check whether the test suite covers them.

Let me trace through some specific inputs to confirm potential issues.

16. user (2026-06-20T16:34:39.594Z)

Exit code 1

```

file:///C:/Users/avidu/AppData/Local/Temp/trace.mjs:17
  { op: ">=", re: new RegExp(`${NUM}${UNIT}\\s*(?:\\+|or
  (? :more|longer|over|above|greater))`${POST_NOUN}`, "g") },
    ^

```

SyntaxError: Invalid regular expression:

```

/(d+(?:.d+)?)(?:s*(shots?|seconds?|secs?|minutes?|mins?|min|m|s)■)?s*(?:\\+|or
(?:more|longer|over|above|greater))(?:s*(shots?)■)?/g: Nothing to repeat
  at new RegExp (<anonymous>)

```

```
at file:///C:/Users/avidu/AppData/Local/Temp/trace.mjs:17:19
at ModuleJob.run (node:internal/modules/esm/module_job:439:25)
at async node:internal/modules/esm/loader:636:26
at async asyncRunEntryPointWithESMLoader (node:internal/modules/run_main:101:5)
```

Node.js v26.1.0

17. assistant (2026-06-20T16:34:46.226Z)

The heredoc mangled my backslashes. Let me write the trace file directly with the Write tool instead.

18. assistant (2026-06-20T16:34:56.485Z)

```
const NUM = "(\\d+(?:\\.\\d+)?)";
const UNIT = "(?:\\s*(shots?|seconds?|secs?|minutes?|mins?|min|m|s)\\b)?";

function lead(alt, op) {
  return { op, re: new RegExp(`(?:${alt})\\s*${NUM}${UNIT}`, "g"), numAt: 1, unitAt: 2 };
}
const LEADING = [
  lead("no more than|at most|maximum(?: of)?|max|up to|<=", "<="),
  lead("no less than|no fewer than|at least|minimum(?: of)?|min|>=", ">="),
  lead("exactly|equal to|equals", "="),
  lead("over|longer than|more than|greater than|above|bigger than|>", ">"),
  lead("under|shorter than|less than|fewer than|below|smaller than|<", "<"),
];
const POST_NOUN = "(?:\\s*(shots?)\\b)?";
const TRAILING = [
  { op: ">=", re: new RegExp(`${NUM}${UNIT}\\s*(?:\\+|or(?:more|longer|over|above|greater))${POST_NOUN}`, "g") },
  { op: "<=", re: new RegExp(`${NUM}${UNIT}\\s*(?:less|fewer|shorter|under|below)${POST_NOUN}`, "g") },
];
function toSeconds(n, unit) { return unit && /^m/.test(unit) ? n * 60 : n; }
function makeFilter(numStr, unit, op) {
  const n = Number(numStr);
  const isShots = !!unit && /^shots?/.test(unit);
  return isShots ? { field: "shot_count", op, value: n } : { field: "duration", op, value: toSeconds(n, unit) };
}

function parseFilters(raw) {
  const normalized = raw.toLowerCase().replace(/>/g, ">=").replace(/</g, "<=").replace(/,/g, " ").replace(/\\s+/g, " ").trim();
  const filters = [];
  let working = normalized;
  for (const pat of LEADING) {
    working = working.replace(pat.re, (full, ...g) => {
      filters.push(makeFilter(g[pat.numAt - 1], g[pat.unitAt - 1], pat.op));
      return " ".repeat(full.length);
    });
  }
  for (const pat of TRAILING) {
    working = working.replace(pat.re, (full, num, preUnit, postNoun) => {
      filters.push(makeFilter(num, preUnit ?? postNoun, pat.op));
      return " ".repeat(full.length);
    });
  }
  return { filters, working };
}

const tests = [
  "min 5",
  "min 5 shots",
```

```

    "at least 8s and under 20s",
    "over 10 m",
    "10 or more shots",
    "8 shots or more",
    "max 30",
    "up to 5 shots",
    "fewer than 5 shots",
    "no fewer than 8 shots",
    "over 10s under 20s",
    "more than 10",
    "minimum 5 shots",
  ];
  for (const t of tests) {
    console.log(JSON.stringify(t), "=>", JSON.stringify(parseFilters(t).filters));
  }
}

```

19. user (2026-06-20T16:34:56.503Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra/web/trace_tmp.mjs (file state is current in your context ? no need to Read it back)

20. user (2026-06-20T16:35:03.302Z)

```

"min 5" => [{"field":"duration","op": ">=", "value":5}]
"min 5 shots" => [{"field":"shot_count","op": ">=", "value":5}]
"at least 8s and under 20s" =>
[{"field":"duration","op": ">=", "value":8}, {"field":"duration","op": "<", "value":20}]
"over 10 m" => [{"field":"duration","op": ">", "value":600}]
"10 or more shots" => [{"field":"shot_count","op": ">=", "value":10}]
"8 shots or more" => [{"field":"shot_count","op": ">=", "value":8}]
"max 30" => [{"field":"duration","op": "<=", "value":30}]
"up to 5 shots" => [{"field":"shot_count","op": "<=", "value":5}]
"fewer than 5 shots" => [{"field":"shot_count","op": "<", "value":5}]
"no fewer than 8 shots" => [{"field":"shot_count","op": ">=", "value":8}]
"over 10s under 20s" =>
[{"field":"duration","op": ">", "value":10}, {"field":"duration","op": "<", "value":20}]
"more than 10" => [{"field":"duration","op": ">", "value":10}]
"minimum 5 shots" => [{"field":"shot_count","op": ">=", "value":5}]

```

21. assistant (2026-06-20T16:35:08.360Z)

The parser handles those well. Now let me check whether the test suite covers multiple-filter (AND) queries, the `summarize` limit-label inconsistency, and the `min`/`max` bare-word phrasings. Let me also verify the `summarize` "top N" label bug ? it always says "top N" even for `first N` / `last N` limits.

Let me trace the `summarize` inconsistency and a few more cases.

22. assistant (2026-06-20T16:35:11.933Z)

```

import { parseQuery, summarize, runQuery } from "./src/lib/query.ts";

// 1. summarize label for first/last limit ? always says "top N"?
console.log("first 10 =>", JSON.stringify(summarize(parseQuery("first 10"))));
console.log("last 5 =>", JSON.stringify(summarize(parseQuery("last 5"))));
console.log("5 shortest =>", JSON.stringify(summarize(parseQuery("5 shortest"))));

// 2. multiple filters (range)
console.log("at least 8s and under 20s =>", JSON.stringify(parseQuery("at least 8s and under 20s").filters));

// 3. recognized for pure unavailable+filter
console.log("smashes over 10s recognized =>", parseQuery("smashes over 10s").recognized);

```

```
// 4. duplicate operator on same axis
console.log("over 10s over 20s =>", JSON.stringify(parseQuery("over 10s over 20s").filters));
```

23. user (2026-06-20T16:35:11.944Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra/web/trace2_tmp.mjs (file state is current in your context ? no need to Read it back)

24. user (2026-06-20T16:35:19.984Z)

```
npm warn exec The following package was not found and will be installed: tsx@4.22.4
first 10 => ["oldest first", "top 10"]
last 5 => ["newest first", "top 5"]
5 shortest => ["shortest first", "top 5"]
at least 8s and under 20s =>
[{"field": "duration", "op": ">=", "value": 8}, {"field": "duration", "op": "<", "value": 20}]
smashes over 10s recognized => true
over 10s over 20s =>
[{"field": "duration", "op": ">", "value": 10}, {"field": "duration", "op": ">", "value": 20}]
```

25. assistant (2026-06-20T16:35:24.865Z)

This confirms the `summarize` inconsistency: `first 10` produces the pill `[ "oldest first", "top 10" ]` and `last 5` produces `[ "newest first", "top 5" ]`. The pill says "top N" even when the sort is oldest/newest-first, which is misleading ? "top 10" alongside "oldest first" reads contradictorily. This is the parsed-pill that D2/the doc explicitly wants to be "transparent and hand-correctable."

Now let me verify the test suite gaps. Let me confirm which behaviors are NOT covered by the test file. Let me check the run_all_tests / npm test setup and run the existing suite to confirm green baseline.

26. user (2026-06-20T16:35:28.068Z)

```
RUN v3.2.6 C:/Users/avidu/Projects/khelsutra/web
? src/lib/query.test.ts (35 tests) 12ms

Test Files  1 passed (1)
Tests       35 passed (35)
Start at    22:05:27
Duration    510ms (transform 50ms, setup 0ms, collect 55ms, tests 12ms,
environment 0ms, prepare 171ms)
```

27. assistant (2026-06-20T16:35:37.445Z)

Baseline is green (35 tests). Now let me confirm the specific test gaps. The test file (read above) covers: duration filters, shot filters, sort, limit, unavailable, unrecognized, sortRallies, runQuery e2e, labels. Let me identify what is NOT covered:

1. ****Multiple ANDed filters**** (e.g. `"at least 8s and under 20s"` ? two filters) ? the `filters` array being ANDed is core behavior (`ParsedQuery.filters` "ANDed together"), but no test ever produces more than one filter. `matchesFilter`'s `.every()` AND-combination in `runQuery` is never exercised with >1 filter.

2. ****`summarize` for non-"top" limits**** ? the bug I found above; the only `summarize` test is `"over 10s top 5"`. No test for `first N`/`last N` summarize.

3. ****`min`/`max` bare words and "or more"/"or less" trailing on shot_count.****

Let me verify the "fewer than" duration-vs-shot routing is intentional and check one more potential redundancy ? the `UNIT` alternation has both `min` and `minutes`|`mins` ? and `m`, and `seconds`|`secs` ? and `s`. Let me verify there's no dead alternation.

28. assistant (2026-06-20T16:35:41.422Z)

```
import { parseQuery } from './src/lib/query.ts';

// Check unit alternation coverage - is any alternative dead/redundant?
for (const u of ['s', 'sec', 'secs', 'second', 'seconds', 'm', 'min', 'mins', 'minute',
'minutes']) {
  console.log(`over 10 ${u} =>`, JSON.stringify(parseQuery(`over 10 ${u}`).filters[0]));
}

// SORT_PATTERNS test: do all alternations resolve? check 'by shots' vs 'by shot count'
for (const s of ['longer first', 'by duration', 'by length', 'duration desc', 'duration asc',
  'latest', 'most recent', 'recent first', 'earliest', 'chronological', 'by
time',
  'highest shots', 'by shots', 'by shot count', 'shot count desc',
  'least shots', 'lowest shots', 'shot count asc']) {
  console.log(`${s} =>`, JSON.stringify(parseQuery(s).sort));
}
```

29. user (2026-06-20T16:35:41.437Z)

File created successfully at: C:/Users/avidu/Projects/khelsutra/web/trace3_tmp.mjs (file state is current in your context ? no need to Read it back)

30. user (2026-06-20T16:35:48.798Z)

```
over 10 s => {"field":"duration","op": ">","value":10}
over 10 sec => {"field":"duration","op": ">","value":10}
over 10 secs => {"field":"duration","op": ">","value":10}
over 10 second => {"field":"duration","op": ">","value":10}
over 10 seconds => {"field":"duration","op": ">","value":10}
over 10 m => {"field":"duration","op": ">","value":600}
over 10 min => {"field":"duration","op": ">","value":600}
over 10 mins => {"field":"duration","op": ">","value":600}
over 10 minute => {"field":"duration","op": ">","value":600}
over 10 minutes => {"field":"duration","op": ">","value":600}
longer first => {"key":"duration","dir":"desc"}
by duration => {"key":"duration","dir":"desc"}
by length => {"key":"duration","dir":"desc"}
duration desc => {"key":"duration","dir":"desc"}
duration asc => {"key":"duration","dir":"asc"}
latest => {"key":"start_time","dir":"desc"}
most recent => {"key":"start_time","dir":"desc"}
recent first => {"key":"start_time","dir":"desc"}
earliest => {"key":"start_time","dir":"asc"}
chronological => {"key":"start_time","dir":"asc"}
by time => {"key":"start_time","dir":"asc"}
highest shots => {"key":"shot_count","dir":"desc"}
by shots => {"key":"shot_count","dir":"desc"}
by shot count => {"key":"shot_count","dir":"desc"}
shot count desc => {"key":"shot_count","dir":"desc"}
least shots => {"key":"shot_count","dir":"asc"}
lowest shots => {"key":"shot_count","dir":"asc"}
shot count asc => {"key":"shot_count","dir":"asc"}
```

31. assistant (2026-06-20T16:35:52.778Z)

All alternations are reachable. Now let me check one redundancy in the `UNIT` regex:
`minutes?|mins?|min|m` ? `min` is redundant because `mins?` already matches `min` (the `s` makes the `s` optional). Let me verify.

32. user (2026-06-20T16:35:55.554Z)

min matches mins? branch: true

Removing standalone |min| still matches: true

33. assistant (2026-06-20T16:36:05.889Z)

Confirmed: the standalone `min` alternation in `UNIT` (`minutes?|mins?|min|m`) is redundant since `mins?` already matches `min`. This is a minor redundancy. Note however that the LEADING/SORT contexts reuse the same `min`/`max` as comparator words ? but in the `UNIT` constant specifically, the `min` alt is dead. Let me confirm it's in the UNIT string at line 57.

Looking at line 57: `const UNIT = "(?:\\s\*(shots?|seconds?|secs?|minutes?|mins?|min|m|s)\\b)?"`; ? yes, `mins?|min` has the redundant `min`. This is a real but minor (nit-level) finding.

Now let me check the most substantive consistency item: the `summarize` "top N" label. Let me re-read the relevant lines to craft an accurate finding, and verify `runQuery` AND-filter coverage gap is real by checking the test file once more for any 2-filter case.

The tests never construct a query with 2+ filters. The `ParsedQuery.filters` is documented as "ANDed together" and `runQuery` uses `q.filters.every(...)` . This logic path (AND of multiple filters) is completely untested.

Let me also double check: is there a `format.ts`-style helper the query labels could reuse? `filterLabel` builds `length > 10s` manually; `mmss` isn't applicable (raw seconds value, not m:ss). No reuse miss there. The `OP\_SYMBOL` map is local and appropriate.

Let me verify one final thing ? whether `summarize`'s hardcoded "top" is genuinely wrong for the limit semantics, by checking what label would be honest.

34. user (2026-06-20T16:36:06.812Z)

```
266    /** Human clause labels for the parsed-pill (e.g. ["length > 10s", "longest first", "top
267    15"])). */
268    export function summarize(q: ParsedQuery): string[] {
269      const parts: string[] = [];
270      for (const f of q.filters) parts.push(filterLabel(f));
271      if (q.sort) parts.push(sortLabel(q.sort));
272      if (q.limit !== null) parts.push(`top ${q.limit}`);
273      return parts;
274    }
```

35. assistant (2026-06-20T16:36:21.354Z)

I have enough to finalize. Let me consolidate my findings within my dimension (reuse, simplification, efficiency, consistency, test gaps).

My defensible findings:

1. **`summarize` always emits "top N"** even for `first N` (oldest-first) and `last N` (newest-first) limits. The pill renders `["oldest first", "top 10"]` for `"first 10"` ? contradictory ("top" implies longest/best, but the sort is oldest-first). The pill is the explicit transparency surface (D2). This is a consistency/correctness defect in the label layer. Medium-confidence as a "bug," high-confidence as a clarity issue.
2. **Test gap: multiple ANDed filters never tested.** `filters` is documented "ANDed together" and `runQuery` does `q.filters.every(...)` , but no test produces >1 filter (every `.filters` assertion is a single-element array or `[0]`). A range query like "at least 8s and under 20s" ? 2 filters, and the AND semantics in `runQuery`/`summarize` , are entirely uncovered.
3. **Test gap: `summarize` only tested for the `top` limit path**, so the "top N"-for-first/last mislabel (finding #1) slipped through.
4. **Redundant `min` alternation** in the `UNIT` regex ? `mins?|min` ? `mins?` already matches `min`. Nit-level dead alternation.

Let me make sure I don't overstate #1's confidence ? it is a genuine output defect, but whether

it's "wrong" vs "intended shorthand" is a judgment call, so I'll mark it major/medium. Findings #2/#3 are high-confidence test gaps. #4 is a nit.

36. user (2026-06-20T16:36:42.706Z)

Structured output provided successfully

37. assistant (2026-06-20T16:36:52.728Z)

I have completed the review of the P3 query compiler within my dimension (reuse, simplification, efficiency, consistency, test gaps). I verified each finding by tracing actual parser/summarize output and running the existing suite (35 tests, green).

Summary of findings reported via StructuredOutput:

1. **major** ? `summarize()` hardcodes `"top N"` (query.ts:271) so `"first 10"` renders the pill `["oldest first", "top 10"]` and `"last 5"` renders `["newest first", "top 5"]` ? the transparency pill (D2) contradicts what the query actually selects.
2. **major** ? Test gap: multiple ANDed filters are never exercised. The parser produces 2-filter range queries (`"at least 8s and under 20s"` ? two filters) and `runQuery` ANDs them via `.every()`, but every test asserts a single-element `.filters` or `[0]`, so the core multi-clause path is uncovered.
3. **minor** ? Test gap: `summarize()` is only tested on the `"top"` limit path, which is exactly why finding #1 slipped through.
4. **nit** ? Redundant `min` alternation in the `UNIT` regex at query.ts:57 (`mins?` already matches `"min"`).

No reuse misses against `lib/format.ts`/`lib/selection.ts` were found ? `filterLabel`/`OP_SYMBOL` are appropriately local, and all sort/unit regex alternations are reachable (no dead branches beyond the one nit). Naming and export style are consistent with the established P1/P2 modules.