

claude-windows / 831509e0-5773-4469-a2ff-205848372a6b

Metadata

```
- Source: `claude-windows`  
- Kind: `claude`  
- Source file: `C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b.jsonl`  
- SHA-256: `1eafb5f7b02433206e230a64e85aeff164b6681fcf9f2bca00cd2b23003967b9`  
- Source modified: `2026-07-02T04:41:48+00:00`  
- Imported at: `2026-07-05T16:48:20+00:00`  
- project: `C--Users-avidu-Projects-khelsutra`  
- session_id: `831509e0-5773-4469-a2ff-205848372a6b`
```

Transcript

1. user (2026-06-22T01:10:54.881Z)

Resume the khelsutra Friendly & Multilingual work. Read the session handoff first (~/.claude/projects/C--Users-avidu-Projects-khelsutra/memory/session-handoff.md) and `git pull --ff-only` before reading anything else.

State: the chapter is code-complete ? §7 all ? except the deferred B7. Two human gates remain before archiving (native-speaker review of the AI-drafted kn/hi; my font-glyph eyeball on a real device ? see the screencasts in ../khelsutra-screencast/), plus one small engineering gap: own-model's body content is still English on kn/hi.

Pick up own-model kn/hi localization with the same diligence as the rest: isolated git worktree off origin/master, data-i18n[-html] the body content, AI-draft ? adversarial verify the translations, extend the site tests (drift + render), record a screencast, and merge on green CI (web + site + Cloudflare). If instead I've cleared the two human gates, flip the §9 DoD to DONE and run the engine DOC_STATUS.md §2 archival checklist.

2. assistant (2026-06-22T01:11:00.604Z)

I'll start by following the repo-freshness convention ? `git pull --ff-only` first, then read the session handoff before any substantive work.

3. user (2026-06-22T01:11:05.578Z)

Already up to date.

---EXIT:0---

master

5e5a2ac docs(friendly-multilingual): close out the chapter (§9 DoD + UI/UX + B7 deferred) (#84)

4c0f35c fix(site): UI/UX ? compact language switcher + header overflow fix + localized hero

(#83)

0fae364 feat(web+site): A2 ? localized WhatsApp share for the reel (SPA + site) (#82)

4. user (2026-06-22T01:11:05.619Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22, after A2 (#82) + the UI/UX header pass (#83) + the chapter
4      closeout (#84) merged._
5
6      ## You are here ? chapter effectively COMPLETE (pending human gates)
7      §7 of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo
8      B7** (deferred). Both surfaces are trilingual end-to-end and non-tech-friendly:
9      - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: en/kn/hi ? B3
10     shim/switcher/negotiation, A3 recording-education + marketing copy in kn/hi (Noto bundled), A6
11     plain-language access form, A7 camera-placement diagram, **A2 WhatsApp share** (#82), and the
12     **UI/UX header pass** (#83): the 3 language pills ? a compact `? <select>` (fixed the mobile
13     header overflow; zero horizontal overflow across all 12 page/viewport/locale combos) + the home
```

hero headline localized.

8 - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in ****#77****; web coverage floor added in ****#80****.

9 - Sister repo ****rally-annotator** is also localized (kn/hi/es/da/id/te)****** ? the journey annotator ? site ? Studio is consistent in the user's language.

10

11 **## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)**

12 1. ****Native-speaker review**** of the AI-drafted kn/hi catalogs (site + SPA) ? the standing guardrail before a wide public launch.

13 2. ****Owner font-glyph eyeball**** on a real Kannada/Hindi device (CI can't render fonts). Proxy screencasts: `C:/Users/avidu/Projects/khelsutra-screencast/khelsutra-site-i18n-desktop.mp4` + `khelsutra-i18n-screencast.mp4`.

14

15 **## Open engineering follow-ups (small)**

16 - ****own-model body content**** is still English on kn/hi (only its switcher + request link are localized) ? a separate content-translation slice (like A3).

17 - ****Access form kn/hi**** ? A6 left it English (`site.join.` en-seeded), translation-ready.

18 - ****B7**** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.

19 - Minor: `site.` adds ~27KB to the SPA bundle (could split to a site-only catalog); ratchet web coverage thresholds as `App.tsx` gains tests.

20

21 **## Ramp-up kit**

22 - `docs/FRIENDLY\_AND\_MULTILINGUAL.md` ? \$7 tracker (source of truth, all ? except B7), \$6.5 N1?N9, \$9 DoD (boxes flipped; 2 human gates open), changelog.

23 - `/locales/{en,kn,hi,es,da,id}/common.json` ? shared catalog: SPA console keys + `site.` (nav/hero/record/capture/join/ownModel/reveal).

24 - `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, compact `` switcher, `window.KhelSutra.t` bridge, negotiation), `site/server.js`, `site/scripts/copy-locales.mjs`, `site/src/{i18n.shim, locales-drift, assets, server}.test.js`.

25 - Screencast/Playwright tooling + before/after eval shots: `C:/Users/avidu/Projects/khelsutra-screencast/` (`site-screencast.mjs`, `deep-test.mjs`, `eval-shots.mjs`).

26 - `[[catalog-home-and-i18n-layout]], [[shared-checkout-concurrency]]`.

27

28 **## Key decisions (don't relitigate)**

29 - D-CATALOG-HOME: catalogs at repo-root `/locales`; SPA imports; site mirrors via `copy:locales` + drift guard.

30 - Negotiation order (both surfaces): persisted (`khelsutra.lang`) ? `?lang=` ? navigator/Accept-Language ? en; missing key ? en, never a raw key.

31 - Switcher = compact `` in the header (kept there for discoverability/signal; auto-negotiation covers kn-phones). Rich `**` markup localizes via `data-i18n-html` (XSS-safe; catalog-authored).**

32 - Process: isolated `git worktree` per PR (shared checkout churns fast); AI-draft translations ? adversarial verify ? native review is a pre-launch (not pre-merge) gate.

33

5. assistant (2026-06-22T01:11:25.893Z)

`git pull` is clean (already up to date, on `master` at #84). Handoff read. Let me confirm my understanding before diving in:

- The chapter is code-complete except deferred B7.
- ****Two human gates remain open**** (native-speaker review + owner font-glyph eyeball) ? these are owner-gated, and your message confirms they're ***not*** cleared yet ("Two human gates remain").
- ****My task this session:**** the own-model kn/hi body-content localization slice, done with the full A3-style diligence (worktree ? data-i18n ? AI-draft ? adversarial verify ? extend tests ? screencast ? merge on green CI).

Let me ramp up on the exact surface. I'll fan out an exploration to map the own-model page and the A3 template I should mirror.

6. user (2026-06-22T01:11:26.939Z)

```

1      # Friendly & Multilingual ? non-tech-savvy UX + Hindi/Kannada localization
2
3      > **Status:** `DRAFT` ? owner-gated (implementation starts only on explicit approval) .
**Owner:** Avi Dullu . **Created:** 2026-06-21 . **Last updated:** 2026-06-21
4      > **Lifecycle:** `DRAFT ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when
DONE).
5      > **Tracking anchors:** $7 progress tracker is the source of truth; indexed in
`docs/README.md`; thread in `NEXT_STEPS.md`; pointer in engine `docs/DOC_STATUS.md`; memory
`current-state` + `next-session-ux-localization`.
6      > **Relation to existing docs:** this is the **implementation project** for two engine
design docs ? it *adapts & supersedes-in-practice* `badminton-highlight-
indexer/docs/I18N_PLAN.md` (localization) and the UX half of `?/docs/UI_PROPOSAL.md` (non-tech-
savvy console). Those stay the canonical *design*; this doc carries the *tracked execution*
against today's surfaces.
7      > **Honesty note:** each claim tagged `[verified]` (checked against code this session),
`[researched]` (needs sign-off), or `[design]` (proposed). Not legal advice ? the OFL font
question (D-FONT) is owner/counsel-gated.
8
9      ---
10
11     ## 0. TL;DR
12     A coach or parent in Bangalore should land on KhelSutra, feel at home, set up their
camera with confidence, and get highlights ? **in Kannada or Hindi**, with **zero hand-
holding**. This project isolates that goal into one tracked workstream-pair: ** (A) ** make the UI
super friendly for non-tech-savvy users, and ** (B) ** localize to Hindi + Kannada. Both surfaces
(`web/` React SPA + `site/` vanilla marketing) have **zero i18n today** `[verified]`, so the
foundation ? shared `locales/{en,kn,hi}` catalogs + a negotiation contract + CI parity ? is the
real deliverable; translations follow. **The single most important caveat:** translations are
**human-reviewed** (Gemini drafts are *inference only, never training* ? the standing
guardrail), and Kannada/Hindi rendering is **blocked on the OFL font decision (D-FONT)**. The
cheapest unblocked high-impact first slice is the **SPA i18n scaffold + language switcher (en-
only)** ? it locks the shared catalog/negotiation contract and adds the render-test safety net
the SPA currently lacks.
13
14     ## 1. Problem & goal
15     **Why now.** The public site (kheLSutra.guru) is live, clean, honest, and tested. The
PMF beachhead is **Bangalore badminton academies**; many coaches, parents, and players are far
more comfortable in **Kannada** than English, and most are **not highly tech-savvy** `[verified
? design intent]` (`UI_PROPOSAL.md:25,28`, `I18N_PLAN.md:10-13`, `PMF_MARKET_RESEARCH.md:116`,
`KHELSUTRA_PRODUCT_OVERVIEW.md:13/50/61`). An English-only, knob-heavy product adds friction at
the exact point of first contact.
16
17     **Concrete outcome ("good" looks like):** a Kannada/Hindi-comfortable, phone-first, non-
technical coach/parent can ? without help ? (1) understand what the product does and how to
record reliably, (2) request access / use the console, (3) pick rallies and get a reel, and (4)
share it on WhatsApp, **entirely in their language**.
18
19     **Read to get current:** this doc's $3?$4; the engine design `I18N_PLAN.md` (canonical
i18n design) + `UI_PROPOSAL.md` $2 (personas, the 6 alpha screens, "teach recording *before*
upload"); `VIDEO_RECORDING_GUIDELINES.md`; this repo's `PER_RALLY_SELECTION.md` (the honest SPA
scope) + `REQUEST_ACCESS_FORM.md`.
20
21     ## 2. Decisions locked (structural ? owner directive 2026-06-21)
22     | # | Decision | Source / date | Implication |
23     |---|-----|-----|-----|
24     | D1 | **Isolate as ONE tracked project** spanning both workstreams (A: UX, B: kn/hi
l10n) | owner, 2026-06-21 | This doc; $7 = source of truth; archived on DoD |
25     | D2 | **Home = `kheLSutra/docs/`** (the implementation repo) | owner-gated tracked-doc
convention | `web/` + `site/` both live here; $7 tracks kheLSutra PRs; engine P2 backend-l10n is
a cross-repo deferred row |
26     | D3 | **Adapt `I18N_PLAN.md` to today's surfaces:** P1 (vanilla `t()` shim) ? `site/`;
P3 (react-i18next) ? `web/`; **drop the dead `backend/api/static` retrofit** | `[verified]` the
doc targets `backend/api/static` (`I18N_PLAN.md:25,30,156,191`) which exists only in the engine
repo, not here | The doc's framework-agnostic *foundation* (catalog format + negotiation + ICU
plurals + CI) survives unchanged; only the wiring re-points |

```

```

27 | D4 | **Engine P2 backend-localization stays owner-gated + cross-repo** (not in this
DoD) | `CLAUDE.md` guardrails | Dynamic engine error/report text localizes later; tracked as a
deferred row |
28 | D5 | **Archive trigger = en+kn+hi live on BOTH surfaces** (+ the non-tech UX
baseline), then run the engine `DOC_STATUS.md §2` archival checklist | owner, 2026-06-21 | See
§9 |
29 | D6 | **D-LOCALES: `en` + `kn` for v1, `hi` next; always-fallback to `en`** | owner,
2026-06-21 | Kannada-first beachhead; `hi` = catalog-only (both 2-form CLDR) |
30 | D7 | **D-FONT: OFL-for-media carve-out ? self-host Noto Sans Kannada/Devanagari**
(counsel may still confirm) | owner, 2026-06-21 | Unblocks B4/B5/A3 + the kn/hi reel watermark;
an explicit exception to the MIT/Apache/BSD code guardrail (fonts = media) |
31 | D8 | **D-SURFACE-FIRST: lead with the `web/` SPA scaffold; SKIP the dead static-UI
retrofit** | owner, 2026-06-21 (via B1 go-ahead) | B1 is greenlit; site recording-education
localized early |
32 | D9 | **D-CATALOG-HOME: co-locate `locales/` + CI in `khelsutra`** (shared, consumed by
SPA + site) | owner, 2026-06-21 (via B1 go-ahead) | No cross-repo coupling |
33
34 *Only **D-BACKEND-DEPTH** (§8.3) remains open ? and it's a deferred, cross-repo engine
concern (B7), not a v1 blocker.*
35
36 ## 3. Foundation ? research / prior art
37 **Current-state facts `[verified]` this session** (adversarially checked against the
working tree):
38 - **`web/` SPA: zero i18n.** `web/package.json` deps are only `react`/`react-dom`; no
`i18next`/`react-intl`/`formatjs`; no `locales/` dir; no `t()`/`useTranslation`/`data-i18n`
anywhere. User-facing English is hardcoded in `*.tsx` (e.g. `QueryBar.tsx:46-47,56,72,76,78`;
`App.tsx:115,211,224`) ? ~50 literals + ~16 derived labels.
39 - **`site/` marketing: vanilla, zero i18n.** Three `` files
(`public/{index,capture,own-model}.html`) with inline CSS, no framework; the only scripts are a
CF analytics beacon (`index.html:595`) + one inline form/reel IIFE (`index.html:597-633`).
`server.js` hardcodes English responses; no locale handling.
40 - **Recording-education is *not* greenfield.** The homepage "Record it right" gist
(`index.html:324-364`) + the `/capture` checklist (`capture.html`, routed `server.js:51`,
guarded `assets.test.js:94`) already ship the user-facing best-practices surface. *Unshipped:*
the empirical-threshold framing and the programmatic pre-flight validator (a code change, not a
page).
41 - **Persona is design intent, not built.** kn/hi + zero-knobs are **proposed/owner-
gated**; the app is English-only today (`KHELSUTRA_PRODUCT_OVERVIEW.md:61`). It's
Kannada-**first**, Hindi-**next** ? not Kannada-only.
42
43 **Localization prior art `[researched]`:
44 - **CLDR plural categories:** Hindi = `{one, other}`; Kannada = `{one, other}`. Both are
2-form (same shape as English) ? once ICU MessageFormat is in the catalog, adding `hi`/`kn`
plurals is **catalog-only**, no code. (ICU still required because English `count>1?s:'` hand-
rolling ? present today in the SPA ? doesn't generalize.)
45 - **react-i18next** (web/): `i18next` + `react-i18next` + `i18next-browser-
languagedetector` + an ICU/plural post-processor; lazy-load per-locale JSON; persist via
`localStorage`.
46 - **Shared catalog + tiny shim** (site/): the SAME i18next-flavored JSON consumed by a
~30-line `t(key, vars)` shim that walks `data-i18n` attributes ? no build step, no framework,
mirrors i18next interpolation/plural rules for the 2-form languages.
47 - **Noto Sans Kannada / Noto Sans Devanagari** are **OFL-1.1**; OFL permits commercial
bundling/redistribution (fonts = media, not code/weights). Self-host (e.g. `@fontsource`) with
`font-display: swap` + subsetting. **Gated on D-FONT.**
48 - **Non-tech-savvy / HCI4D patterns:** icon **+ text** (never icon-only), non-color
selection indicators, large touch targets, mobile-first, WhatsApp as the share channel, a
prominent persistent language switcher.
49
50 ## 4. Design / architecture
51 **Two surfaces, one shared source of truth.**
52
53 ...
54 locales/ # shared catalogs ? co-located in khelsutra (D-CATALOG-
HOME, see §8)
55 en/ common.json # source of truth ? devs author keys here

```

```

56      kn/  common.json          # Kannada  (Gemini-draft ? human-review)
57      hi/  common.json          # Hindi    (next ? the extensibility proof)
58
59      web/  ? react-i18next      # I18N_PLAN P3: provider in main.tsx; useTranslation in
components
60      site/ ? t(key,vars) shim   # I18N_PLAN P1 retargeted: data-i18n attrs over the
static HTML
61      ```
62
63      - **Negotiation contract (one order, both surfaces):** `persisted pref (localStorage) ?
switcher / ?lang=<code> ? navigator/Accept-Language ? "en"`. Supported locales in a single
module; anything else falls back to `en`; **a missing key degrades to English, never to a raw
key.**
64      - **Keys, never prose** ? `t("compile.button")`, with ICU for interpolation/plurals:
`"${count, plural, one {# rally} other {# rallies}}". This replaces the SPA's current hand-
rolled `Segment${count>1?'s':''}`.
65      - **Translation pipeline (guardrail-clean):** dev authors `en` keys ?
`scripts/i18n_draft.py`-style Gemini **draft** (inference only, never training; flags every
value for review) ? **owner/native-speaker review** ? CI key-parity ? merge. Gemini never
touches `en`, never invents keys.
66      - **CI enforcement (keeps it "by design"):** (1) **key-parity** ? every locale has
exactly the `en` key set (drop a stub `ta.json` ? CI lists every gap = the extensibility proof);
(2) **no-bare-strings** ? flags user-facing literals not routed through `t()` (curated allowlist
to start).
67      - **Fonts:** bundle Noto Sans Kannada + Devanagari **iff D-FONT = OFL carve-out**; this
also unblocks a Kannada/Hindi **reel watermark** (engine `WatermarkConfig.font_path` already
takes a path ? config, not code).
68
69      **Non-tech-savvy UX levers** (ranked impact × effort, grounded in personas; surface-
tagged):
70
71      | Lever | Surface | Impact | Effort | Note |
72      |---|---|---|---|---|
73      | Plain-language copy ? strip engine jargon, keep honest caveats | both | high | small |
banners + footer carry backend vocabulary today |
74      | Localized **WhatsApp share** for the downloaded reel | both | high | small | WhatsApp
is *the* channel for this audience |
75      | **Language switcher** persisted via a shared localStorage key | both | high | small |
site promises kn/hi but ships no switcher |
76      | Localize **recording-education** (capture + gist) kn?hi | site | high | medium | gates
input quality; the highest-leverage kn content |
77      | Mobile-first touch targets; tooltip-text ? visible | web | high | medium | tiny
targets + desktop layout + invisible tooltips on phones |
78      | Icon **+ text** + non-color selection indicator | web | medium | small | never icon-
only |
79      | Friendly engine-error mapping over raw FastAPI `detail` | web | medium | medium |
`CompileResult` passes engine text untranslated |
80      | Plain-language framing for the Request-Access GPU/storage Qs | site | medium | small |
"GPU"/"S3/GCS" are intimidating |
81      | Background-processing reassurance + status as icon chips | web | medium | small |
honest expectations on slow uplinks |
82      | Fix English-source recording gaps (a diagram) before translating | site | medium |
medium | the diagram is reusable across all 3 languages |
83      | Tap-only filter controls alongside the English query bar | web | medium | large | the
`parseQuery()` parser is English-grammar only |
84      | Keep the honest *today-vs-roadmap* split through translation | both | medium | small |
never soften "experimental"/"not available yet" |
85
86      **Reuse map (what's new vs reused):** **Reused** ? the i18next-flavored JSON + negotiation
contract + ICU plurals + key-parity/no-bare-strings CI + draft?review pipeline (all from
`I18N_PLAN.md`); the shipped recording pages; the SPA's `lib/format.ts`/`lib/query.ts`;
`site/src/assets.test.js` + the SPA's vitest harness. **New** ? `locales/` catalogs; the SPA
react-i18next provider + switcher; the site `t()` shim + `data-i18n` wiring; Noto font bundle
(gated); a jsdom render-test env for the SPA.
87

```

```

88     ## 5. Privacy / scope note
89     i18n touches **presentation only** ? no new personal-data collection, no biometrics,
minors-excluded posture unchanged. WhatsApp share opens the user's own client with a pre-filled
message; it sends nothing server-side. Gemini-draft translation is inference, not training (no
user data in the loop).
90
91     ## 6. Honest limits ? what this does NOT do
92     - A green CI / DONE status proves **key-parity + render + no-bare-strings**, **not**
translation *quality* ? that's human-gated and owner-paced.
93     - Kannada/Hindi will **not render** until the Noto fonts land (D-FONT); until then kn/hi
catalogs exist but display tofu/fallback.
94     - The SPA is **job-tethered**; localizing **dynamic engine errors/report text** needs
engine P2 (owner-gated, cross-repo, D-BACKEND-DEPTH) ? out of this DoD.
95     - The query bar stays **English-grammar parsing**; kn/hi users rely on tap-only controls
(a later, larger slice), not free-text Kannada queries.
96     - **Mobile-*perfect** layout is an alpha non-goal (usable-on-phone is in scope; pixel-
perfect is not).
97
98     ## 6.5 Testing strategy ? automatic language negotiation (rigorous, owner-required)
99     **The bar (owner, #41):** a user whose **computer/browser language is Kannada or Hindi
must get the respective version automatically ? that is the core promise and it is **proven by
tests at every layer, never assumed. **Auto-selection IS the negotiation order (persisted pref ?
`?lang=` ? browser/`Accept-Language` ? `en`); each step gets a test.
100
101     **Negotiation matrix ? every row is an automated test:**
102
103     | # | Signal under test | Setup | Expected | Proven in |
104     |---|---|---|---|---|
105     | N1 | **Browser/OS = Kannada** | no persisted pref, no `?lang`,
`navigator.languages=["kn-IN", ?]` | resolves to **kn** ? Kannada content (once the kn catalog
ships) | **B1** detection . **B5** content |
106     | N2 | **Browser/OS = Hindi** | `navigator.languages=["hi-IN", ?]` | resolves to **hi**
? Hindi content | **B6** (hi added to the supported set + catalog) |
107     | N3 | **`?lang=` override** | `?lang=kn`, browser = en | kn | B1 |
108     | N4 | **Persisted pref wins** | `localStorage=kn`, browser = en, no `?lang` | kn (a
returning user keeps their choice) | B1 |
109     | N5 | **Region subtag normalizes** | `navigator.language="kn-IN"` | base **kn** (not a
"kn-IN" miss) | B1 |
110     | N6 | **Unsupported language** | `navigator="ta-IN"` (Tamil, not yet supported) |
**en** fallback ? never a locale we can't serve | B1 |
111     | N7 | **Missing key in active locale** | kn active, a key absent from `kn/common.json`
| **en** fallback for that key (no raw key shown) | B1/B5 |
112     | N8 | **Static site (vanilla shim)** | `Accept-Language: kn` / `?lang=kn` on a `site/`
page | kn-rendered page (same order as the SPA) | B3 |
113     | N9 | **Backend (engine P2)** | `Accept-Language: kn` to the API | kn customer/report
text | B7 (owner-gated) |
114
115     **Levels & tooling:**
116     - **SPA (`web/`):** jsdom tests stub `navigator.language`/`navigator.languages`,
`localStorage`, and the `?lang` query ? assert `i18n.language`/`resolvedLanguage` + rendered
text per the matrix. *(B1 lands N1/N3?N7 at the **detection** level now ? `kn` is supported; the
kn/hi **content** assertions ride the catalogs in B5/B6.)*
117     - **Static site (B3):** the shared `t()` shim's negotiation is unit-tested the same way;
plus a server test that `Accept-Language: kn`/`?lang=kn` returns the kn-rendered page.
118     - **CI key-parity:** guarantees every locale has every key, so a correctly-negotiated
locale can never fall through to a raw key.
119     - **End-to-end (manual, owner machine ? per I18N_PLAN $6):** set the real OS/browser to
Kannada, then Hindi ? load both surfaces ? confirm the right language renders **and the Noto
fonts display** (the cloud CI container can't render fonts; the owner eyeball is the final
gate).
120     - **? Query parsing / semantic understanding (forward-looking, owner directive
2026-06-21) ? i18n testing is MANDATORY there. **The query bar is **English-grammar-only** today
(a documented limit, tracker A9): the user types English queries (`over 10s`, `top 15 longest`)
and a localized **sample-query prompt** shows them what to type in *every* locale (kn/hi
included). The **moment** the parser gains **semantic understanding** or accepts **Kannada/Hindi

```

```

query input** (e.g. typing a Kannada/Hindi phrase, or a conversational/NL builder ? I18N_PLAN
P4), i18n tests become a **merge gate**: a kn/hiquery (typed or spoken) must parse to the
**correct selection**, the localized **parse-feedback** ("parsed-pill") must render in the
active locale, and the unsupported/empty-result messages must localize. **No query-NL /
semantic-parsing work merges without those tests.**
121
122     A locale that's reachable by the switcher but **not auto-selected from the browser
language is a bug, not a "later". ** This matrix is a DoD gate ($9).
123
124     ## 7. Deliverables & progress tracker    ? **source of truth**
125     Legend: ? Todo · ? In progress · ? Done · ? Blocked/gated. **One small PR per row**,
branched from `origin/master`, no stacking.
126
127     | ID | Deliverable | Workstream | Depends on | Gated? | Status | PR |
128     |----|-----|-----|-----|-----|-----|----|
129     | P0 | This tracked project doc + inbound pointers | ? | ? | No | ? |
[#41](https://github.com/avidullu/khelsutra/pull/41) · engine
[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275) |
130     | B1 | **SPA i18n scaffold + language switcher, en-only** (react-i18next + detector +
`en` catalog + switcher + persistence + **jsdom render tests** + **browser-language negotiation
tests** $6.5 N1/N3?N7) | B | P0 | No | ? | [#42](https://github.com/avidullu/khelsutra/pull/42)
|
131     | B2 | Extract SPA strings ? `en` catalog (~50 literals + ~16 derived; ICU plural keys);
add **key-parity + no-bare-strings CI** | B | B1 | No | ? |
[#45](https://github.com/avidullu/khelsutra/pull/45) |
132     | A1 | Plain-language copy pass on the `en` catalog (de-jargon; icon+text; non-color
selection) | A | B2 | No | ? | [#60](https://github.com/avidullu/khelsutra/pull/60) |
133     | B3 | **Shared `t()`/`data-i18n` shim + persistent switcher for `site/`** ? hoist
catalogs to repo-root `~/locales` (D-CATALOG-HOME), re-point the SPA, site copy-step + drift-
guard, `server.js` + shim negotiation ($6.5 **N8**); **en-only marketing content** (kn/hi rides
A3) | B | B2 | D-CATALOG-HOME ? | ? | [#70](https://github.com/avidullu/khelsutra/pull/70) |
134     | A2 | Localized **WhatsApp share** for the reel ? SPA (CompileResult) + site (post-
signup reveal via a shim `window.KhelSutra.t` bridge); `wa.me`, client-only, `rel=noopener` | A
| B1/B3 | No | ? | [#82](https://github.com/avidullu/khelsutra/pull/82) |
135     | A6 | Plain-language framing for Request-Access GPU/storage questions (de-jargoned +
GPU reassurance; wired via `data-i18n`, en ? form kn/hi is a later increment) | A | B3 | No | ?
| [#75](https://github.com/avidullu/khelsutra/pull/75) |
136     | A7 | **Camera-placement diagram** on the capture page (accessible inline SVG: elevated
camera behind the baseline, ~30° tilt, full-court field-of-view) with a localized en/kn/hi
legend | A | ? | No | ? | [#76](https://github.com/avidullu/khelsutra/pull/76) |
137     | B4 | **Noto Sans Kannada + Devanagari** bundle (OFL carve-out) ? **SPA done; reel
watermark `font_path` = engine follow-up* | B | ? | D-FONT ? | ? |
[#46](https://github.com/avidullu/khelsutra/pull/46) |
138     | B5 | **Kannada (`kn`) catalog** ? render ? **SPA done (AI-draft, native review
pending); `site/` rides B3* | B | B2/B4 | D-LOCALES ? | ? |
[#47](https://github.com/avidullu/khelsutra/pull/47) |
139     | A3 | Localize **recording-education** (capture + homepage gist) + the `site.*`
marketing copy to **kn + hi** (Noto on the site; AI-draft, adversarially verified, native review
pending) | A | B3/B5 | D-LOCALES ? + D-FONT ? (site: Google-Fonts Noto) | ? |
[#74](https://github.com/avidullu/khelsutra/pull/74) |
140     | A4 | Mobile-first touch targets + tooltip-text ? visible (SPA) | A | B1 | No | ? |
[#61](https://github.com/avidullu/khelsutra/pull/61) |
141     | A5 | Friendly engine-error mapping over raw FastAPI `detail` (SPA, client-side map) |
A | B2 | No | ? | [#62](https://github.com/avidullu/khelsutra/pull/62) |
142     | B6 | **Hindi (`hi`) catalog** ? render (the extensibility proof ? just a catalog) ?
**SPA done (AI-draft, native review pending)* | B | B5 | D-LOCALES ? | ? |
[#48](https://github.com/avidullu/khelsutra/pull/48) |
143     | A8 | Background-processing reassurance + verdict/status as icon chips (SPA) | A | B2 |
No | ? | [#63](https://github.com/avidullu/khelsutra/pull/63) |
144     | A9 | Tap-only filter controls alongside the English query bar (SPA) | A | B2 | No | ?
| [#68](https://github.com/avidullu/khelsutra/pull/68) |
145     | B7 | ***(deferred, cross-repo)* Engine **P2 backend customer-facing localization**
(report `customer_*` + rejection reasons) | B | engine | **D-BACKEND-DEPTH, owner-gated** | ? |
? |
146

```

147 *** MILESTONE ? SPA fully trilingual (2026-06-21):** the `web/` Studio SPA now speaks
en + kn + hi end to end (B1?B2?B4?B5?B6, all merged). A **Kannada-default browser auto-
renders Kannada**, and the switcher walks kn ? hi ? en ? **proven by a Playwright screencast**
with `locale: kn-IN` (`khelsutra-i18n-screencast.mp4`; frames captured per locale + `lang>` tracked). This meets the owner's success criterion **on the SPA surface**. **B3 has since
landed** ? the `site/` marketing surface now carries the shared `t()/`data-i18n` shim, a
persistent en/kn/hi switcher, and matching negotiation (client shim + `server.js`; \$6.5 **N8**
green), with **en-only marketing content** for now (the shim/switcher/negotiation are the proof;
kn/hi *marketing* translation rides **A3**). **A3 has since landed** ? the `site/` recording-
education (homepage gist + capture checklist) and the `site.` marketing copy now render in **kn
+ hi** (Noto bundled on the site), so a Kannada/Hindi browser auto-gets localized recording
instructions. **A6** (plain-language access form,
[#75](https://github.com/avidullu/khelsutra/pull/75)) and **A7** (camera-placement diagram,
[#76](https://github.com/avidullu/khelsutra/pull/76)) have since landed, and the **kn/hi SPA-
console native-review pass** shipped ([#77](https://github.com/avidullu/khelsutra/pull/77)).
Still open for the full \$9 DoD: a **native-speaker review** of the *remaining* AI-drafted
catalogs (es/da/id + the reel-watermark strings; the kn/hi SPA console is done via #77) before a
wide public launch. (**A2** WhatsApp/social share is **deferred out of v1 scope** ? not a DoD
blocker.) Do **not** archive until both surfaces render kn/hi *content*. ? (both now do, pending
the remaining native review).

148

149 ## 8. Open questions ? owner (blocking gates) `[design]`

150 *Status (2026-06-21): 4 of 5 **LOCKED/ADOPTED** by the owner ? see \$2 (D6?D9). Only
D-BACKEND-DEPTH remains open (and it's deferred, not a v1 blocker).*

151 1. **D-FONT ? ? LOCKED ? (a) OFL-for-media carve-out, self-host Noto Sans
Kannada/Devanagari** (counsel may still confirm). An explicit exception to the MIT/Apache/BSD
code guardrail (fonts = media). Unblocks B4/B5/A3 + the kn/hi reel watermark.

152 2. **D-LOCALES ? ? LOCKED ? `en` + `kn` for v1, `hi` next, always-fallback to `en`**
(both 2-form CLDR ? `hi` is catalog-only).

153 3. **D-BACKEND-DEPTH ? ? OPEN (deferred, not a v1 blocker).** Recommend **customer
verdict/report `customer\_` + validation-rejection reasons first; technical/operator text stays
English; phase two** (engine repo, owner-gated ? tracker row B7).

154 4. **D-SURFACE-FIRST ? ? ADOPTED ? lead with the SPA scaffold (B1), localize site
recording-education early, SKIP the dead static-UI retrofit.**

155 5. **D-CATALOG-HOME ? ? ADOPTED & IMPLEMENTED (B3) ? repo-root
`/locales/{en,kn,hi,es,da,id}/common.json` is the single source of truth.** The SPA imports it
directly (re-pointed to `../..../locales`; Vite resolves the workspace root via the repo `.git`
marker, so dev/build/test all work). The dependency-free site consumes it through one tiny build
step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (auto-runs
`predeploy`), with a **drift-guard test** (`site/src/locales-drift.test.js`) failing CI if the
shipped copy goes stale. (The engine `I18N\_PLAN` assumed the indexer repo; this is the
adaptation.)

156

157 ## 9. Definition of done

158 - [x] **Automatic language negotiation (\$6.5) is green** ? N1/N3?N7 (SPA, jsdom) + N2
(hi) + N8 (static-site shim honors `Accept-Language`/?lang`, `server.test.js`), all in CI.

159 - [] **Manual cross-check (owner machine):** OS/browser set to Kannada and to Hindi
each render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner
eyeball ? pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts
in `khelsutra-screencast/` ? `khelsutra-site-i18n-desktop.mp4` (site, kn) +
`khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`)).*

160 - [x] `en + kn + hi` catalogs live and **rendering** on BOTH `web/` SPA and `site/`
marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3
(site), proven by render tests + a real-browser pass.

161 - [] **Noto Sans Kannada + Devanagari render correctly** ? owner eyeball on a real
machine. *(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the
owner's device check.)*

162 - [x] CI **key-parity + no-bare-strings** green; a stub locale flags every gap ?
`web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift`
guard.

163 - [x] **Recording-education** (capture + homepage gist) available in `kn` + `hi` ? A3
(#74), incl. a localized camera-placement diagram (A7, #76).

164 - [x] **Non-tech UX baseline** ? plain-language copy (A1/A6), mobile tap targets (A4) +
the decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only
filters (A9), honest today-vs-roadmap preserved through translation.

165 - [] \$7 all rows ? (or explicitly deferred) ? flip **Status ? DONE** + run the engine
`DOC\_STATUS.md \$2` archival checklist ? `git mv` to `docs/archives/`. *(\$7 is all ? except the
owner-gated, cross-repo **B7** ? deferred. Holding the DONE flip on the two human gates above
(native-speaker review of the AI-drafted kn/hi + the owner font eyeball). Remaining engineering
follow-up: **own-model body content** is still English on kn/hi ? a separate content-translation
slice.)*

166

167 ## 10. References

168 **Internal code anchors** `[verified]`: **web/package.json**,
`web/src/{App.tsx,main.tsx,components/QueryBar.tsx,components/CompileResult.tsx,lib/query.ts}`;
`site/public/{index,capture,own-model}.html`, `site/server.js`, `site/src/assets.test.js`.
This repo's docs: **docs/PER_RALLY_SELECTION.md**, **docs/REQUEST_ACCESS_FORM.md**,
docs/README.md, **NEXT_STEPS.md**. **Engine design docs (canonical)**: **badminton-highlight-indexer/docs/{I18N_PLAN.md,UI_PROPOSAL.md,VIDEO_RECORDING_GUIDELINES.md,PMF_MARKET_RESEARCH.md,PMF_F**
IELD_SIGNALS.md,KHELSUTRA_PRODUCT_OVERVIEW.md,DOC_STATUS.md}. **External** `[researched]`:
Unicode CLDR plural rules (kn/hi = one/other); react-i18next + i18next-icu; SIL Open Font
License 1.1; Google Noto Sans Kannada/Devanagari.

169

170 ---

171

172 ### Changelog

173 - `2026-06-21` ? created. Isolated the UX + Hindi/Kannada work into one tracked project
(owner directive). Grounded in a multi-agent research+verification pass (web/+site/ string maps,
Indic-l10n prior art, 5 adversarial verdicts). Decisions D1?D5 locked; 5 product/licensing
decisions surfaced as open; \$7 tracker seeded with B1 as the recommended first slice.

174 - `2026-06-21` ? owner locked **D6** (en+kn?hi) + **D7** (OFL Noto carve-out) and
adopted **D8** (SPA-first) + **D9** (catalogs in khelsutra); only D-BACKEND-DEPTH remains open.
B1 greenlit ? ? in progress.**

175 - `2026-06-21` ? **B1** opened ? [#42](https://github.com/avidullu/khelsutra/pull/42):
SPA i18n scaffold (react-i18next + ICU + detector) + `en` catalog + language switcher + the
SPA's first jsdom render tests. Verified typecheck/79-tests/build green + live in-browser
(switcher persists, en-fallback). Doc/pointer PRs opened: khelsutra
[#41](https://github.com/avidullu/khelsutra/pull/41), engine
[#275](https://github.com/Khelsutra/badminton-highlight-indexer/pull/275).

176 - `2026-06-21` ? **\$6.5** Testing strategy added (owner ask, #41): **a rigorous**
automatic-negotiation matrix (N1?N9) so a Kannada/Hindi **browser** auto-gets the respective
version ? proven at the detection level now (B1), at the content level with the catalogs
(B5/B6), on the static shim (B3), and by a manual font-render eyeball. Wired into the DoD (\$9).
B1 (#42) gains the detection tests (N1/N3?N7).

177 - `2026-06-21` ? **A9** (#68) landed. **Localized tap-only filter controls** (`TapFilters`:
Sort/Length/Count) so a non-English-typing kn/hi/? user can filter without typing the English
query syntax; each tap builds the same `ParsedQuery` the parser would (tap == type, test-
pinned). The English example chips now show only in English. 173 web tests; reviewed via a
2-lens adversarial workflow. **Workstream A**: A1/A4/A5/A8/A9 ?; remaining A3 (recording-edu
kn/hi), A6/A7 (site), B3 (site trilingual). **(Also note: MULTILINGUAL_EXPANSION Phase A ?**
es/da/id ? shipped #67, so the SPA now speaks 6 languages.)*

178 - `2026-06-21` ? **A8** (#63) landed. **Background-processing reassurance + status as**
icon+text chips (never icon-only): a new `StatusChip` + shared `Spinner`; IngestPanel processing
shows a working chip + "safe to wait ? runs on the server" line and a ? "Couldn't process" chip
on failure; CompileResult gains a "Stitching your reel?" building card + ?? status icons on the
terminal card (now `aria-live`). 141 web tests green; reviewed via a 2-lens adversarial workflow
(folded its aria-live + honest-copy findings). **Workstream A** now: A1/A4/A5/A8 ?; remaining A9
(tap-only filters), A3 (recording-education kn/hi).*

179 - `2026-06-21` ? **A5** (#62) landed. **Friendly engine-error mapping unified across ALL**
SPA surfaces (ingest + build + rally-load) via a single `lib/errorText.ts` helper + a shared
`errors.` catalog namespace: an `engine` failure shows the engine's own detail verbatim,
everything else a localized line (`engineGeneric` last resort). No more raw `ApiError`/`HTTP
500` text; `build.failed`/`rallies.load_failed` logs gain `code`+`detail`. 136 web tests green;
reviewed via a 2-lens adversarial workflow (folded its load-path consolidation nit).

180 - `2026-06-21` ? **A1** (#60) + **A4** (#61) landed. **A1** = the plain-language `en` copy pass
(de-jargon). **A4** = the non-tech / phone-first pass: 244px tap targets across the SPA (Tailwind
`min-h-11`/`h-11`), enlarged parsed-pill + sample chips, and **hover-only** `title=` text surfaced
as visible DOM text* (the QueryBar "not available yet" reason + per-card shot-count confidence)
? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow.
Still open in workstream A: **A5** (friendly engine-error map on the build path), **A8**

(background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-education kn/hi), B3 (site/ trilingual) + native review.

181 - `2026-06-21` ? **SPA MILESTONE**: fully trilingual (owner directive "take it to completion + screencast"). **B2** (#45, full string extraction + key-parity/no-bare-strings CI) ? **B4** (#46, self-host OFL Noto) ? **B5** (#47, Kannada) ? **B6** (#48, Hindi ? the extensibility proof) all merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity.

Playwright screencast (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ? switch hi ? switch en, each with `` tracked (`kshelsutra-i18n-screencast.mp4` + per-locale frames). kn/hi are **AI-drafted** ? native review pending. **Remaining for full \$9 DoD**: **B3** (the `site/` marketing surface), **A3** + the UX A-items, native-speaker translation review.

182 - `2026-06-21` ? **B3** ([#70](https://github.com/avidullu/kshelsutra/pull/70)) landed ? the marketing `site/` is now i18n-wired, en-only content. **Implements `D-CATALOG-HOME`**: catalogs hoisted to repo-root ***/locales** (all 6 ? en/kn/hi + the merged es/da/id) as the single source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ? typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales/` (`predeploy` hook) + **drift-guard test**. New `site/public/i18n.js` ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n` walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the 2-form site languages); a **persistent en/kn/hi switcher** on `index/capture/own-model`; and `server.js` **Accept-Language negotiation** matching the SPA EXACTLY (persisted cookie ? `?lang=` ? `Accept-Language/navigator` ? en; missing key ? en, never a raw key). Tests: shim unit test + drift guard + extended `assets/server` tests + the **\$6.5 N8** negotiation suite ? **62 site tests green**; real-browser smoke (switch ? persist ? reload). kn/hi **marketing** translation is the next effort (**A3**). ? **Concurrency note**: built in an isolated `git worktree` because a sibling **A9** session held uncommitted catalog WIP in the shared checkout ? never clobbered.

183 - `2026-06-22` ? **A3** ([#74](https://github.com/avidullu/kshelsutra/pull/74)) landed ? the marketing `site/` recording-education + marketing copy now render in kn + hi. **Translated** the homepage "Record it right" gist + the full 1-page capture checklist + the existing `site` copy to **Kannada + Hindi** (~40 new `site.record` / `site.capture` keys; en-authored, kn/hi translated, es/da/id en-seeded ? key-parity green). The shim gains a `data-i18n-html` form so inline `<b>` emphasis survives translation; **Noto Sans Kannada + Devanagari** bundled via Google Fonts on all 3 pages (+ `--font` fallback) so kn/hi render without tofu. Translations **AI-drafted** ? adversarially verified by a 6-agent workflow (meaning/fluency/integrity x kn/hi; 0 issues in the A3 keys) and a 4-lens code review (folded its a11y findings ? switcher group `aria-label` now localized via `lang.label`, default `aria-pressed` for the no-JS baseline ? and 3 test-coverage findings incl. a byte-for-byte HTML?en-catalog drift test). **Web 173 + site 68 green**; real-browser check (kn capture page renders Kannada, `<b>` preserved, no console errors). kn/hi remain **native-review-pending** (font glyphs = owner eyeball gate). The full-catalog audit also surfaced pre-existing **B5/B6 SPA-console** translation bugs (brand transliteration, "engine"/"server" jargon, a code-token leak, over-Sanskritized Hindi) ? flagged as a separate follow-up.

184 - `2026-06-22` ? **A6** ([#75](https://github.com/avidullu/kshelsutra/pull/75)) landed ? plain-language Request-Access GPU/storage questions. **De-jargoned** the intimidating form copy ("GPU machine that could process video locally" ? "a powerful computer that could process videos on its own"; dropped the bare "(S3/GCS)") and added a **GPU reassurance** ("No worries if not ? we can run it in the cloud for you"), so a non-technical coach/parent isn't scared off. Wired via the shim (`site.join`, `data-i18n` spans that preserve the radio/checkbox `<input>`s), translation-ready (en for now; the form's kn/hi is a later increment). The **backend enum contract is unchanged** (field names + every `has_gpu/storage` value preserved ? server-validated). Tests: a de-jargon + reassurance + contract-intact assertion, and the A3 HTML?en-catalog drift test auto-covers the new keys. Site 69 + web 173 green.

185 - `2026-06-22` ? **A7** ([#76](https://github.com/avidullu/kshelsutra/pull/76)) landed ? camera-placement diagram on the capture page. **Added** an **accessible inline SVG** (`role="img"` + localized `<title>`) side-view showing the load-bearing placement cues a coach can't get from text alone: the **elevated camera behind the baseline**, the **~30° downward tilt**, and the **full-court field-of-view cone** (players within frame). A numbered ??? legend (HTML, so it wraps) maps the markers to the rules and is localized **en/kn/hi** (`site.capture.diagram`, reusing the A3 capture terms) ? consistent with the now-trilingual capture page. The text "Place the camera" step remains (the diagram complements it). Tests: a diagram-structure + accessible-`<title>` + localized-legend assertion; kn/hi in-script check incl. `diagram.camera`; the A3 drift test auto-covers the new keys; site 70 + web 173 green. **Workstream A** is now **A1/A3/A4/A5/A6/A7/A8/A9** ? (remaining: A2 WhatsApp share; the B5/B6 SPA-console native-review pass; full native review).

186 - `2026-06-22` ? **A2** ([#82](https://github.com/avidullu/kshelsutra/pull/82)) landed ?

localized WhatsApp share (the last open \$7 row).** SPA `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`). SPA `result.share`/`result.shareText` translated in all 6 locales; the site reveal (injected after sign-up, outside the static `data-i18n` walk) localizes via a new `window.Khelsutra.t` shim bridge** (`site.reveal.\*`, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????????" + a Kannada message. Web 215 + site 72 green. **\$7 is now all ? except the owner-gated, cross-repo B7** (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.

187 - `2026-06-22` ? **UI/UX header pass ([#83](https://github.com/avidullu/khelsutra/pull/83)).** A 3-lens design critique + a deep Playwright layout test (all pages x {1280, 390} x {en, hi/kn}) confirmed the home header **overflowed on mobile** ? the 3 always-visible language pills pushed the "Request access" CTA off-screen (worse in kn). Replaced the pills with a **compact `? <select>` switcher** on all three pages (shows the current language, can't overflow, one tap target, accessible, consistent), added wrap/`overflow-x` safety, and localized the **home hero headline** (`site.hero.title`, the last big English string on the kn/hi home page) via `data-i18n-html`. Shim now reflects the locale in `select[data-langsw]` + listens for `change`. **Zero horizontal overflow on all 12 page/viewport/locale combos**; web 215 + site 72 green. Screenshots (desktop kn journey + mobile header) saved to `khelsutra-screenshot/`.

188 - `2026-06-22` ? **? Multilingual chapter ? effectively complete (pending human gates).** \$7 is **all ? except B7** (assessed: significant cross-repo **engine** backend-i18n in Python with no existing infra + owner-gated **D-BACKEND-DEPTH** ? kept deferred). Both surfaces are trilingual end-to-end (SPA en/kn/hi + es/da/id; site en/kn/hi), non-tech-friendly, and the **sister repo `rally-annotator` is also localized (kn/hi/es/da/id/te)** ? so the coach's journey **annotator ? site ? Studio** is consistent in their language. **What gates archival:** (1) a native-speaker review of the AI-drafted kn/hi catalogs (site + SPA), (2) the owner's font-glyph eyeball on a real Kannada/Hindi device, (3) a small remaining slice ? `own-model` body content is still English on kn/hi. Do not `git mv` to `docs/archives/` until (1)+(2) clear.

189

7. user (2026-06-22T01:11:28.247Z)

```
=== site/ tree ===
site/access.db
site/make_og.py
site/package-lock.json
site/package.json
site/public/capture.html
site/public/flyer-hi.html
site/public/flyer-kn.html
site/public/flyer.html
site/public/i18n.js
site/public/img/annotate-enable.png
site/public/img/annotate-tool.png
site/public/img/flyer-qr.svg
site/public/img/studio-en.png
site/public/img/studio-hi.png
site/public/img/studio-kn.png
site/public/index.html
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
site/public/og.png
site/public/own-model.html
site/public/robots.txt
site/public/video/tool-cuj.mp4
site/README.md
site/schema.sql
site/scripts/copy-locales.mjs
site/scripts/droplet-smoke.sh
site/scripts/parity-check.sh
```

```
site/scripts/provision-vm.sh
site/scripts/teardown-vm.sh
site/server.js
site/src/assets.test.js
site/src/deploy-config.test.js
site/src/i18n.shim.test.js
site/src/index.js
site/src/index.test.js
site/src/locales-drift.test.js
site/src/notify.js
site/src/server.test.js
site/src/store.js
site/src/ux.dom.test.js
site/wrangler.toml
=== locales ===
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
```

8. assistant (2026-06-22T01:11:36.593Z)

Excellent context. Now let me read the own-model page and the catalogs to understand exactly what body content is still English and how A3 wired things.

9. user (2026-06-22T01:11:37.107Z)

```
1      <!doctype html>
2      <html lang="en">
3      <head>
4      <meta charset="utf-8" />
5      <meta name="viewport" content="width=device-width, initial-scale=1" />
6      <title>KhelSutra ? Annotate your footage & train your own model</title>
7      <meta name="description" content="With KhelSutra you can annotate your own footage and
grow a rally model that's YOURS ? on an open, MIT-licensed stack you control. The free VLC
rally-annotator turns 'watch a match' into golden labels." />
8      <meta name="robots" content="noindex" />
9      <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
10     <link rel="preconnect" href="https://fonts.googleapis.com" />
11     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
12     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&family=Noto+Sans+Kannada:wght@400;500;600;700&family=Noto+Sans+Devanagari:wght@400;500;6
00;700&display=swap" rel="stylesheet" />
13     <style>
14         :root{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--lime:#C7F2B0;--paper:#F6F8F4;-
-tx:#14271F;--mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans','Noto Sans Kannada','Noto
Sans Devanagari',system-ui,-apple-system,Segoe UI,Roboto,sans-serif}
15         *{box-sizing:border-box}
16         body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.6;-webkit-font-smoothing:antialiased}
17         a{color:var(--green-d)}
18         .sheet{max-width:880px;margin:18px auto;background:#fff;border-
radius:16px;overflow:hidden;box-shadow:0 18px 50px -24px rgba(0,0,0,.35)}
19         .head{background:var(--ink);color:#EAF3EE;padding:24px 32px}
20         .head .top{display:flex;align-items:center;justify-content:space-
between;gap:1rem;flex-wrap:wrap}
21         .brand{display:flex;align-items:center;gap:.5rem;font-weight:800;font-
size:1.2rem;color:#fff;text-decoration:none}
22         .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:6px
0 6px 11px;border-color:transparent transparent transparent var(--green);margin:0
.3em;transform:translateY(1px)}
```

```

23     .head h1{font-size:clamp(1.5rem,3.5vw,2.1rem);font-weight:800;letter-
spacing:-.02em;margin:1rem 0 0;max-width:20ch}
24     .head h1 .hl{color:var(--lime)}
25     .head p{color:#A7C3B7;margin:.7rem 0 0;max-width:62ch}
26     .head .nav{display:flex;gap:1rem;font-size:.9rem;margin-top:1rem;flex-wrap:wrap}
27     .head .nav a{color:var(--lime);text-decoration:none}
28     /* persistent language switcher (B3) ? inherits header text colour, green fill =
active */
29     .nav-right{display:flex;align-items:center;gap:1rem}
30     .langsw{display:inline-flex;align-items:center;gap:.3rem;border:1px solid
rgba(255,255,255,.28);border-radius:999px;padding:.1rem .3rem .1rem .6rem}
31     .langsw-globe{font-size:.95rem;line-height:1;opacity:.85}
32     .langsw select{font:inherit;font-size:.85rem;font-
weight:600;color:inherit;background:transparent;border:0;cursor:pointer;min-height:40px}
33     .langsw select:focus-visible{outline:2px solid var(--green);outline-offset:2px;border-
radius:6px}
34     .langsw option{color:#14271F;background:#fff}
35     .body{padding:26px 32px 8px}
36     .sec{padding:18px 0;border-top:1px solid var(--line)}
37     .sec:first-child{border-top:0}
38     .kick{font-size:.78rem;font-weight:700;letter-spacing:.06em;text-
transform:uppercase;color:var(--green-d)}
39     .sec h2{font-size:1.4rem;font-weight:800;letter-spacing:-.01em;margin:.35rem 0 0}
40     .sec p{color:#34453d;margin:.6rem 0 0}
41     .pill{display:inline-block;font-size:.72rem;font-weight:700;border-
radius:999px;padding:.2rem .6rem;margin-left:.4rem;vertical-align:.12em}
42     .pill.live{background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.35)}
43     .pill.build{background:#FAEEDA;color:#854F0B;border:1px solid #EF9F27}
44     ol,ul{margin:.6rem 0 0;padding-left:1.2rem}
45     li{margin:.25rem 0;color:#34453d}
46     li b{color:var(--tx)}
47     code{font-family:ui-monospace,SFMono-Regular,Menlo,Consolas,monospace;font-
size:.86em;background:#EEF3EC;border:1px solid var(--line);border-radius:5px;padding:.05rem
.35rem}
48     pre{background:#0C261F;color:#EAF3EE;border-radius:10px;padding:14px
16px;overflow:auto;margin:.8rem 0 0;font-size:.84rem;line-height:1.5}
49     pre code{background:none;border:0;padding:0;color:inherit}
50     .honest{display:flex;gap:.7rem;background:#fff;border:1px solid var(--line);border-
left:4px solid var(--green);border-radius:0 10px 10px 0;padding:12px 16px;margin:.9rem 0 0}
51     .honest b{color:var(--tx)}
52     .honest p{margin:.2rem 0 0;color:var(--mut);font-size:.93rem}
53     .notes{list-style:none;padding:0;margin:.8rem 0 0;display:grid;grid-template-
columns:1fr 1fr;gap:8px}
54     .notes li{display:flex;gap:.5rem;background:#FBF0ED;border:1px solid #f0d6cc;border-
radius:8px;padding:.5rem .7rem;color:#6b3a2a;font-size:.9rem;margin:0}
55     .moat{display:grid;grid-template-columns:1fr 1fr;gap:10px;margin-top:.8rem}
56     .moat div{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:10px;padding:10px
12px}
57     .moat h4{margin:0;font-size:.92rem;color:var(--green-d)}
58     .moat p{margin:.2rem 0 0;font-size:.86rem;color:#34453d}
59     .shot{display:flex;align-items:center;justify-content:center;text-
align:center;background:#EEF3EC;border:1px dashed #BfD3C6;border-
radius:10px;color:var(--mut);font-size:.82rem;padding:18px;margin-top:.8rem;min-height:96px}
60     .ghbtn{display:inline-flex;align-
items:center;gap:.5rem;background:#0C261F;color:#fff;font-weight:600;font-size:.9rem;text-
decoration:none;border-radius:999px;padding:.5rem .95rem;margin-top:.9rem}
61     .cta{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:12px;padding:16px
18px;margin:18px 0 6px;text-align:center}
62     .cta a{display:inline-block;background:var(--green);color:#04140D;font-
weight:700;text-decoration:none;border-radius:999px;padding:.6rem 1.3rem;margin-top:.5rem}
63     table{border-collapse:collapse;margin-top:.8rem;font-size:.86rem;width:100%}
64     th,td{border:1px solid var(--line);padding:.35rem .55rem;text-align:left}
65     th{background:#EEF3EC}
66     .foot{display:flex;justify-content:space-between;flex-wrap:wrap;gap:.5rem;padding:16px

```

```

32px 26px;color:var(--mut);font-size:.85rem}
67     .foot a{text-decoration:none}
68     @media (max-width:680px){.notes,.moat,.shots{grid-template-columns:1fr}}
69     /* annotation-tool screenshots (no footage/people ? pure UI) */
70     .shots{display:grid;grid-template-columns:1fr 1fr;gap:14px;margin-top:.9rem}
71     .shots figure{margin:0}
72     .shots img{width:100%;height:auto;display:block;border:1px solid var(--line);border-
radius:10px}
73     .shots figcaption{margin-top:.4rem;font-size:.82rem;color:var(--mut)}
74     .sample{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:10px;padding:11px
14px;margin:0 0 4px;font-size:.92rem;color:#34453d}
75     .sample a{font-weight:600}
76     </style>
77     </head>
78     <body>
79     <script type="module" src="/i18n.js"></script>
80     <div class="sheet">
81         <div class="head">
82             <div class="top">
83                 <a class="brand" href="/">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
84                 <div class="nav-right">
85                     <label class="langsw"><span class="langsw-globe" aria-
hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
86                         <option value="en" data-i18n="lang.en" lang="en">English</option>
87                         <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
88                         <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
89                     </select></label>
90                     <a href="/#join" style="color:#C7F2B0;font-weight:600;text-decoration:none"
data-i18n="site.ownModel.requestAccess">Request access ?</a>
91                 </div>
92             </div>
93             <h1>Annotate your footage. <span class="hl">Train a model that's yours.</span></h1>
94             <p>You can't train Gemini or GPT on your court footage. KhelSutra's direction is the
inverse ? a small, <b style="color:#EAF3EE">owned</b> rally model where the moat is your
consented dataset, on a commercially-clean, inspectable stack you control.</p>
95             <div class="nav"><a href="/">? KhelSutra home</a><a href="#annotate">Annotate</a><a
href="#train">Train your own model</a><a href="#setup">Setup &amp; use</a></div>
96         </div>
97
98         <div class="body">
99
100             <p class="sample">? <b>Want to see what KhelSutra produces?</b> A real sample reel
plays the moment you <a href="/#join">request access</a>.</p>
101
102             <section class="sec" id="annotate">
103                 <div class="kick">Step 1 · real and shipping today</div>
104                 <h2>Annotate your footage <span class="pill live">live today</span></h2>
105                 <p><b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b> that
turns "watch a match" into golden labels. While you watch your own video in VLC, you mark each
rally's start and end plus how the point ended; it writes one row per rally to a plain CSV next
to your video. <b>Your footage never leaves your machine.</b> It covers five net-separated
racquet sports (badminton, tennis, table tennis, pickleball, padel).</p>
106                 <a class="ghbtn" href="https://github.com/Khelsutra/rally-annotator"><svg
width="16" height="16" viewBox="0 0 16 16" fill="currentColor" aria-hidden="true"><path d="M8
0C3.58 0 0 3.58 0 8a8 8 0 0 0 5.47 7.59c.4.07.55-.17.55-.38 0-.19-.01-.82-.01-1.49-2.01.37-2.53-
.49-2.69-.94-.09-.23-.48-.94-.82-1.13-.28-.15-.68-.52-.01-.53.63-.01 1.08.58 1.23.82.72 1.21
1.87.87 2.33.66.07-.52.28-.87.51-1.07-1.78-.2-3.64-.89-3.64-3.95
0-.87.31-1.59.82-2.15-.08-.2-.36-1.02.08-2.12 0 0 .67-.21 2.2.82a7.4 7.4 0 0 1 2-.27c.68 0
1.36.09 2 .27 1.53-1.04 2.2-.82 2.2-.82.44 1.1.16 1.92.08 2.12.51.56.82 1.27.82 2.15 0 3.07-1.87
3.75-3.65 3.95.29.25.54.73.54 1.48 0 1.07-.01 1.93-.01 2.2 0 .21.15.46.55.38A8 8 0 0 0 16
8c0-4.42-3.58-8-8-8Z"/></svg> github.com/Khelsutra/rally-annotator</a>
107                 <div class="shots">
108                     <figure><figcaption>Enable it once: VLC ? View ? Rally
Annotator.</figcaption></figure>
109     <figure><figcaption>Mark each rally's
start/end + ending reason, then Save Rally.</figcaption></figure>
110     </div>
111     <p style="margin-top:1rem"><b>The flow, per rally:</b></p>
112     <ol>
113         <li><b>Mark START</b> on the serve-contact frame (pause/scrub for
accuracy).</li>
114         <li><b>Mark END</b> when the shuttle is dead.</li>
115         <li>Pick an <b>ending reason</b>, optionally a shot count, then <b>Save
Rally</b> ? one CSV row.</li>
116         <li>Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video later
to continue.</li>
117     </ol>
118     <p style="font-size:.9rem;color:var(--mut)">It's a click-driven dialog (no marking
hotkeys yet), and targets <b>VLC 3.0.x</b>.</p>
119     </section>
120
121     <section class="sec" id="train">
122         <div class="kick">Step 2 . the moat</div>
123         <h2>Train your own model <span class="pill build">open pipeline . in
build</span></h2>
124         <div class="honest" style="border-left-
color:var(--green);background:#EAF6EF;border-color:#BfE6D2">
125             <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">?</span>
126             <div>
127                 <b>You don't have to train anything to start.</b>
128                 <p>KhelSutra runs on a ready-made default, so you get rally detection and
reels <b>out of the box</b> ? nothing to set up. Training on your own footage (below) is an
<b>optional</b> power-up: a model tuned to your courts, your angles, your halls.</p>
129             </div>
130         </div>
131         <p>For those who want it, your labels feed an <b>owned</b> rally model ? trained
on <b>your</b> courts, <b>your</b> angles, <b>your</b> busy multi-court halls. The pipeline is
open and inspectable:</p>
132         <pre><code>annotate (VLC) ? &lt;video>.rallies.csv ? worker train ? your
model bundle (weights + a reviewable manifest)</code></pre>
133         <div class="moat">
134             <div><h4>You own it</h4><p>A model and dataset that are yours to keep and
improve ? not rented inference.</p></div>
135             <div><h4>Commercially clean</h4><p>MIT/Apache/BSD-only stack; we never train on
a paid LLM's output.</p></div>
136             <div><h4>Private & consented</h4><p>Footage stays yours; training use is
explicit opt-in, never automatic.</p></div>
137             <div><h4>Minors protected</h4><p>Footage involving minors is never used for
training and never published.</p></div>
138         </div>
139         <div class="honest">
140             <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">!</span>
141             <div>
142                 <b>Read this honestly.</b>
143                 <p>The labeling tool is real and shipping. The training pipeline is <b>open
and in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-
validation <b>mock</b>, and a real model needs a GPU. There is <b>no "Train now" button</b> yet,
and we make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise here
is <b>ownership, licensing, privacy and consent</b> ? not "more accurate than Gemini," and not
"one click to train."</p>
144             </div>
145         </div>
146     </section>
147
148     <section class="sec" id="setup">
149         <div class="kick">Step 3 . for power users</div>

```

```

150         <h2>Setup & use</h2>
151         <p><b>Install the plugin (VLC 3.0.x).</b> Copy <code>rally_annotator.lua</code>
into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools
? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally
Annotator</i>:</p>
152         <pre><code>Windows:  %APPDATA%\vlc\lua\extensions\
153     macOS:   ~/Library/Application Support/org.videolan.vlc/lua/extensions/
154     Linux:   ~/.local/share/vlc/lua/extensions/</code></pre>
155         <p style="margin-top:1rem"><b>Record</b> per the <a href="/capture">one-page
capture checklist</a> (fixed tripod, full court, landscape, whole session) ? <b>annotate</b> in
VLC ? you get <code>&lt;video&gt;.rallies.csv</code>:</p>
156         <pre><code>rally_number,start_time,end_time,ending_reason,sport,shots_count
157     1,8.800,11.500,winner,badminton,9
158     2,24.389,46.589,unforced_error,badminton,21
159     3,49.183,54.683,let,badminton,</code></pre>
160         <p style="margin-top:.6rem;font-
size:.9rem;color:var(--mut)"><code>ending_reason</code> is one of: <code>unknown</code> .
<code>winner</code> . <code>forced_error</code> . <code>unforced_error</code> .
<code>service_fault</code> . <code>let</code> . <code>other</code>. Times are decimal seconds;
downstream tools read by column name.</p>
161         <p style="margin-top:1rem"><b>Train</b> (developer CLI). A GPU-free dry run
validates the whole pipeline on a CPU mock; a real model needs a GPU:</p>
162         <pre><code># GPU-free dry run (CPU mock ? pipeline validation only):
163     python -m backend.worker train --corpus-uri &lt;bucket&gt; --out-uri &lt;bucket&gt;
--version 0.1.0
164
165     # real trajectories (needs a GPU + the native WASB runner, in build):
166     python -m backend.worker train ... --trajectory-source detector --segmenter
wasb_hybrid</code></pre>
167         <p style="margin-top:.6rem;font-size:.9rem;color:var(--mut)">One join rule: keep
the video <b>byte-identical</b> to what you annotated (don't re-encode after labeling) ? labels
match videos by content hash.</p>
168         </section>
169
170         <section class="sec">
171             <div class="kick">So expectations stay honest</div>
172             <h2>What this is not</h2>
173             <ul class="notes">
174                 <li>Not a one-click trainer ? training is an offline CLI today.</li>
175                 <li>Not in-browser ? labeling runs in VLC on your machine.</li>
176                 <li>Not an accuracy claim vs Gemini/GPT ? no such benchmark.</li>
177                 <li>Shot-type, player and score detection are roadmap.</li>
178             </ul>
179         </section>
180
181         <div class="cta">
182             <b>Want in?</b>
183             <div><a href="/#join">Request alpha access</a></div>
184         </div>
185
186     </div>
187     <div class="foot">
188         <span><a href="/">Khelsutra.guru</a> . <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> . Academy flyer: <a href="/flyer" hreflang="en">English</a>
. <a href="/flyer-kn" hreflang="kn" lang="kn">?????</a> . <a href="/flyer-hi" hreflang="hi"
lang="hi">?????</a></span>
189         <span>Reels carry a "Generated by Khelsutra.guru" mark.</span>
190     </div>
191 </div>
192 </body>
193 </html>
194

```



```

1      {
2      "app": {
3          "badge": "pick your rallies · alpha",
4          "title": "Pick the rallies for your reel",
5          "intro": "Filter by <b>rally length</b> ? e.g. <i>?top 15 longest?</i> ? then fine-
6      tune by tapping cards. Everything starts <b>selected</b>; just drop the ones you don't want."
7      },
8      "lang": {
9          "label": "Language",
10         "en": "English",
11         "kn": "?????",
12         "hi": "??????",
13         "es": "Español",
14         "da": "Dansk",
15         "id": "Bahasa Indonesia"
16     },
17     "bulk": {
18         "selectAll": "Select all",
19         "clear": "Clear",
20         "invert": "Invert"
21     },
22     "mode": {
23         "demo": "These are sample rallies ? process a video above to work on a real match.",
24         "loading": "Finding the rallies in your video?",
25         "error": "Couldn't load this video's rallies: {error}",
26         "loaded": "Found <b>{count}</b> rallies in your video."
27     },
28     "query": {
29         "placeholder": "e.g. over 10s · top 15 longest · shortest first",
30         "ariaLabel": "Filter rallies by length, count or order",
31         "apply": "Apply",
32         "notAvailable": "not available yet",
33         "notAvailableTitle": "?{token}? needs {kind} detection ? not available yet",
34         "notAvailableHelp": "Shot type, players and score aren't available yet ? filter by
35 rally length instead.",
36         "unreadable": "Couldn't read that ? try ?over 10s? or ?top 15 longest?.",
37         "hint": "Type over 10s for rallies longer than 10 seconds ? or tap a sample below.",
38         "try": "Sample queries:",
39         "support": "Filtering by <b>rally length</b> is fully supported. Shot-count is
40 <x>experimental</x> (under development)."
41     },
42     "grid": {
43         "empty": "No rallies to show yet.",
44         "rally": "Rally {n}",
45         "inReel": "Rally {n}, in reel",
46         "notInReel": "Rally {n}, not in reel",
47         "start": "start",
48         "long": "long",
49         "shots": "~{count} shots · experimental",
50         "shotsTitle": "Shot count is experimental (under development) and may be
51 inaccurate{conf}. Filter by rally length instead.",
52         "shotsConfidence": " ? confidence: {conf}"
53     },
54     "footer": {
55         "count": "{count, plural, one {# rally} other {# rallies}}",
56         "summaryRest": "selected · {total} total",
57         "reelName": "Reel name",
58         "reelNamePlaceholder": "my-highlights",
59         "build": "Build reel ({count})",
60         "building": "Building?",
61         "floorOne": "<b>Your only selected rally</b> has fewer than {min} shots ? it would
62 be skipped, so the build would fail. Pick a longer rally.",
63         "floorAll": "<b>All {count} selected rallies</b> have fewer than {min} shots ?
64 they'd all be skipped, so the build would fail. Pick longer rallies.",
65         "floorSomeLead": "{count, plural, one {# rally} other {# rallies}}",

```

```

60         "floorSomeRest": "with fewer than {min} shots will be skipped when building (they're
too short).",
61     },
62     "result": {
63         "share": "Share on WhatsApp",
64         "shareText": "I made my badminton highlights reel with KhelSutra ? Try it:
khelsutra.guru",
65         "ready": "Your reel is ready",
66         "failed": "Build failed",
67         "building": "Stitching your reel?",
68         "buildingReassure": "Joining your selected rallies into one video ? this usually
only takes a moment.",
69         "dismiss": "Dismiss",
70         "download": "Download {filename}"
71     },
72     "build": {
73         "noVideo": "These are sample rallies ? process a real video first to build a reel."
74     },
75     "ingest": {
76         "title": "Process a video",
77         "intro": "Point KhelSutra at a video and it finds the rallies for you ? this can
take a few minutes.",
78         "uriPlaceholder": "gs://your-bucket/match.mp4",
79         "uriAriaLabel": "Video location ? a gs:// bucket URL or a path on the engine host",
80         "hint": "Paste a cloud-storage link (gs://?), or a path to a video on the machine
running KhelSutra.",
81         "submit": "Process video",
82         "submitting": "Submitting?",
83         "cancel": "Cancel",
84         "working": "Processing your video?",
85         "progress": "{progress}",
86         "retry": "Try again",
87         "reassure": "Safe to wait ? KhelSutra keeps working even if your connection is slow;
a long video can take several minutes.",
88         "statusFailed": "Couldn't process",
89         "chooseFile": "Choose a video file",
90         "uploadAria": "Choose a video file to upload",
91         "fileHint": "Pick an .mp4 or .mov from this device ? it uploads, then KhelSutra
finds the rallies.",
92         "orLink": "Or use a cloud link",
93         "uploadingStatus": "Uploading?",
94         "uploadProgress": "Upload progress"
95     },
96     "errors": {
97         "networkError": "Can't reach KhelSutra. Is it running?",
98         "invalidUri": "Enter a video location first ? a gs:// link or a path on the machine
running KhelSutra.",
99         "emptyResult": "Processing finished but found no rallies in this video. Try a
clearer match recording.",
100        "timeout": "This is taking longer than expected. The job may still be running ?
reload with the video link, or try again.",
101        "engineGeneric": "Something went wrong. Please try again."
102    },
103    "tap": {
104        "title": "Tap to filter:",
105        "longest": "Longest first",
106        "shortest": "Shortest first",
107        "over10": "Over 10 seconds",
108        "over20": "Over 20 seconds",
109        "top5": "Top 5 longest",
110        "top10": "Top 10 longest"
111    },
112    "site": {
113        "reveal": {
114            "share": "Share on WhatsApp",

```

```

115         "shareText": "Check out KhelSutra ? it turns a full badminton match into a clean
highlights reel ? khelsutra.guru"
116     },
117     "join": {
118         "gpuLabel": "Do you have a powerful computer that could process videos on its
own?",
119         "gpuHint": "A gaming PC or laptop with a graphics card. No worries if not ? we can
run it in the cloud for you.",
120         "gpuYes": "Yes ? a gaming PC or laptop with a graphics card",
121         "gpuUnsure": "Not sure",
122         "gpuNo": "No",
123         "gpuCloud": "No ? please run it in the cloud for me",
124         "storageLabel": "Where do your match videos live? How would you share them?",
125         "storageHint": "(pick any)",
126         "storageGdrive": "Google Drive",
127         "storageOnedrive": "OneDrive / Microsoft 365",
128         "storageDropbox": "Dropbox",
129         "storageBucket": "A cloud storage bucket ? advanced (e.g. Amazon S3, Google
Cloud)",
130         "storageLocal": "SD card or the device itself",
131         "storageUnsure": "Not sure"
132     },
133     "nav": {
134         "how": "How it works",
135         "why": "Why it's hard",
136         "ownModel": "Own your model",
137         "flyer": "Flyer",
138         "roadmap": "Roadmap",
139         "faq": "FAQ",
140         "requestAccess": "Request access"
141     },
142     "hero": {
143         "title": "Every rally, indexed. <span class=\"hl\">The dead time, gone.</span>",
144         "eyebrow": "Invite-only alpha · Bengaluru",
145         "lead": "KhelSutra finds every rally in your session and strips out the knock-ups,
walks and gaps ? so a full match becomes a clean highlight reel you can watch and download. No
editing, no scrubbing.",
146         "ctaPrimary": "Request alpha access",
147         "ctaHow": "See how it works"
148     },
149     "record": {
150         "kicker": "Record it right",
151         "title": "Five minutes of setup ? reliably great reels",
152         "intro": "Highlight quality starts with the recording. Set the camera up once like
this and KhelSutra has everything it needs to find the rallies.",
153         "goldenRuleLead": "The golden rule: one match, one court, in full frame ? and
don't move the camera.",
154         "goldenRuleRest": "A single court in frame gives the best results today; busy
multi-court footage is the hard case we're still sharpening.",
155         "place": {
156             "title": "Place the camera",
157             "body": "Behind <b>one baseline</b>, elevated (a high tripod or a balcony),
tilted down ~30° ? the <b>whole court</b> in frame, players never cropped."
158         },
159         "settings": {
160             "title": "Settings",
161             "body": "<b>1080p</b>, landscape, <b>30 fps</b> for badminton (60 fps for table
tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps find rallies."
162         },
163         "still": {
164             "title": "Keep it still",
165             "body": "Fixed tripod or mount. <b>No panning, no zooming</b> during play ? a
steady, full-court view is what the tool is tuned for."
166         },
167         "upload": {

```

```

168         "title": "Record & upload",
169         "body": "Even lighting, then record the <b>whole session</b> and upload it as-is
? KhelSutra finds the rallies and does the cutting."
170     },
171     "checklistCta": "Full 1-page capture checklist ?"
172 },
173 "capture": {
174     "diagram": {
175         "title": "Side view: where the camera goes",
176         "camera": "Camera ? behind the baseline, elevated",
177         "angle": "Tilt ~30° down",
178         "frame": "Whole court in frame ? players never cropped",
179         "net": "Net"
180     },
181     "title": "1-page capture checklist",
182     "intro": "Great highlights start with a steady, full-court recording. Five minutes
of setup makes a big difference to your reels.",
183     "ruleLead": "The golden rule: one match, one court, in full frame ? and don't move
the camera.",
184     "ruleRest": "Multi-court footage is the hard case we're still sharpening; a single
court in frame gives the best results today.",
185     "step1": {
186         "title": "Place the camera",
187         "b1": "Behind <b>one baseline</b>, elevated ? a high tripod, a few metres up, or
a balcony.",
188         "b2": "Tilt down about <b>30°</b>; keep the <b>whole court</b> in frame with a
little margin and net headroom.",
189         "b3": "Players should never leave the frame."
190     },
191     "step2": {
192         "title": "Settings",
193         "b1": "<b>1080p or higher</b>, shot in <b>landscape</b>.",
194         "b2": "<b>30 fps</b> for badminton/pickleball; <b>60 fps</b> for table tennis.",
195         "b3": "<b>Audio ON</b> (don't mute) ? keep the mic unobstructed, wind/noise
reduction off."
196     },
197     "step3": {
198         "title": "Keep it still",
199         "b1": "Fixed tripod or mount.",
200         "b2": "<b>No panning, no zooming</b> during play."
201     },
202     "step4": {
203         "title": "Light & record",
204         "b1": "Even indoor lighting; avoid backlight, glare and very dark halls.",
205         "b2": "Record the <b>whole session</b> and upload it as-is ? KhelSutra does the
cutting."
206     },
207     "doTitle": "Do",
208     "do1": "Fixed camera, full court, behind the baseline",
209     "do2": "1080p+, landscape, audio on",
210     "do3": "One match on one court",
211     "dontTitle": "Avoid",
212     "dont1": "Handheld or phone-in-hand",
213     "dont2": "Broadcast-style pans & zooming",
214     "dont3": "Several courts in one frame; very dark halls",
215     "consent": "Please record adults with their okay. Footage involving minors is
never used to improve the tool and is never published.",
216     "questions": "Questions?",
217     "printTip": "Tip: press Ctrl/Cmd + P to print or save as PDF."
218 },
219 "ownModel": {
220     "requestAccess": "Request access ?"
221 }
222 },
223 "selection": {

```

```

224         "count": "{count, plural, one {# rally selected} other {# rallies selected}}"
225     }
226 }
227

```

11. assistant (2026-06-22T01:11:53.613Z)

This is a substantial content-localization slice mirroring A3. Let me read the shim, the test harness, and the A3 template page (capture.html) to learn the exact patterns I must mirror.

12. user (2026-06-22T01:11:54.559Z)

```

1      // KhelSutra marketing-site i18n shim (tracker B3) ? vanilla, dependency-free, zero
build.
2      //
3      // Mirrors the SPA's react-i18next contract (web/src/i18n/index.ts) for the static site:
4      //   - the SAME shared catalogs (repo-root /locales, copied into /public/locales ?
D-CATALOG-HOME);
5      //   - the SAME negotiation order: persisted (localStorage `khelsutra.lang`) -> ?lang=
-> navigator -> en;
6      //   - ICU-lite interpolation `{name}` + plurals `{n, plural, one {?} other {?}}` via
Intl.PluralRules
7      //   (CLDR-correct for en/kn/hi ? the 2-form site languages ? and any locale);
8      //   - a missing key degrades to en, then leaves the HTML's English default ? NEVER a
raw key.
9      //
10     // The pure helpers are exported for the unit test (src/i18n.shim.test.js); boot() runs
only in a browser.
11
12     export const SUPPORTED = ["en", "kn", "hi"]; // the trilingual marketing site (es/da/id
are SPA-only)
13     export const STORAGE_KEY = "khelsutra.lang"; // shared with the SPA, so a choice carries
across surfaces
14     export const DEFAULT = "en";
15
16     const base = (code) => (code ? String(code).toLowerCase().split("-")[0] : ""); // "kn-
IN" -> "kn"
17     const supported = (code) => (SUPPORTED.includes(base(code)) ? base(code) : null);
18
19     // Negotiation ? EXACTLY the SPA order. Anything unsupported is skipped; nothing matches
-> en.
20     export function negotiate({ stored, query, nav } = {}) {
21         const navList = Array.isArray(nav) ? nav : nav ? [nav] : [];
22         for (const candidate of [stored, query, ...navList]) {
23             const ok = supported(candidate);
24             if (ok) return ok;
25         }
26         return DEFAULT;
27     }
28
29     const dig = (obj, key) => key.split(".").reduce((o, k) => (o && typeof o === "object" ?
o[k] : undefined), obj);
30
31     // Resolve one plural block "{var, plural, one {?} other {?}}" (balanced braces, # = the
number).
32     // Returns the string unchanged when there's no parseable plural block (so interpolate()
terminates).
33     function plural(msg, vars, locale) {
34         const m = msg.match(/\{(\w+),\s*plural,/);
35         if (!m) return msg;
36         let depth = 0, end = -1;
37         for (let i = m.index; i < msg.length; i++) {
38             if (msg[i] === "{") depth++;
39             else if (msg[i] === "}" && --depth === 0) { end = i; break; }
40         }

```

```

41     if (end < 0) return msg;
42     const inner = msg.slice(m.index + m[0].length, end);
43     const n = Number(vars[m[1]] ?? 0);
44     const cat = new Intl.PluralRules(locale).select(n);
45     const arms = {};
46     for (const a of inner.matchAll(/(\w+)\s*\{/g)) {
47         let d = 1, j = a.index + a[0].length, e = -1;
48         for (; j < inner.length; j++) { if (inner[j] === "{") d++; else if (inner[j] === "}"
49 && --d === 0) { e = j; break; } }
50         if (e < 0) break;
51         arms[a[1]] = inner.slice(a.index + a[0].length, e);
52     }
53     const chosen = (arms[cat] ?? arms.other ?? "").replace(/#/g, String(n));
54     return msg.slice(0, m.index) + chosen + msg.slice(end + 1);
55 }
56 // ICU-lite: resolve every plural block, then simple {name} interpolation.
57 export function interpolate(msg, vars = {}, locale = DEFAULT) {
58     if (typeof msg !== "string") return msg;
59     let out = msg;
60     for (let i = 0; i < 20; i++) { const next = plural(out, vars, locale); if (next ===
61 out) break; out = next; }
62     return out.replace(/\{(\w+)\}/g, (_, k) => (k in vars ? String(vars[k]) : `${$}{k}`));
63 }
64 // active locale -> en fallback. undefined when absent in both (caller keeps the DOM's
65 English default).
66 export function translate(catalogs, locale, key, vars) {
67     let msg = dig(catalogs[locale], key);
68     if (msg == null) msg = dig(catalogs[DEFAULT], key);
69     return msg == null ? undefined : interpolate(msg, vars, locale);
70 }
71 // Walk i18n-tagged nodes under `root`. Three forms (missing key -> skip, leaving the
72 HTML default):
73 //   data-i18n="key"                                -> textContent
74 //   data-i18n="key" data-i18n-attr="x"              -> setAttribute(x, ?) (placeholder / aria-
75 label / alt ?)
76 //   data-i18n-html="key"                            -> innerHTML (for catalog-authored inline
77 markup like <b>;
78 //                                           values are our own content, never user
79 input)
80 export function applyDom(root, catalogs, locale) {
81     for (const el of root.querySelectorAll("[data-i18n], [data-i18n-html]")) {
82         const htmlKey = el.getAttribute("data-i18n-html");
83         const val = translate(catalogs, locale, htmlKey || el.getAttribute("data-i18n"));
84         if (val == null) continue;
85         const attr = el.getAttribute("data-i18n-attr");
86         if (htmlKey) el.innerHTML = val;
87         else if (attr) el.setAttribute(attr, val);
88         else el.textContent = val;
89     }
90     // Reflect the active locale in the compact <select> language switcher(s).
91     for (const sel of root.querySelectorAll("select[data-langsw]")) sel.value = locale;
92 }
93 // ---- browser glue (skipped under the plain-node unit test, which has no document)
94 ----
95 const readCookie = (name) => {
96     const m = (document.cookie || "").match(new RegExp("(?:^|; )" + name.replace(/\./g,
97 "\\.") + "=([^\s]*)"));
98     return m ? decodeURIComponent(m[1]) : null;
99 };
100 function persist(locale) {

```

```

97     try { localStorage.setItem(STORAGE_KEY, locale); } catch { /* private mode */ }
98     // Mirror to a cookie so server.js (VM host) can honor the persisted pref server-side
(no FOUc).
99     try { document.cookie = `${STORAGE_KEY}=${locale};path=/;max-
age=31536000;samesite=lax`; } catch { /* ignore */ }
100    }
101
102    async function loadCatalog(loc) {
103        try { const r = await fetch(`/locales/${loc}/common.json`); return r.ok ? await
r.json() : {}; } catch { return {}; }
104    }
105
106    let activeCatalogs = { en: {} };
107    let activeLocale = DEFAULT;
108
109    async function render(locale) {
110        const catalogs = { en: await loadCatalog("en") };
111        if (locale !== "en") catalogs[locale] = await loadCatalog(locale);
112        activeCatalogs = catalogs;
113        activeLocale = locale;
114        document.documentElement.lang = locale;
115        applyDom(document, catalogs, locale);
116        // Bridge for dynamically-injected content the static data-i18n walk can't reach (e.g.
the
117        // post-signup reel reveal): window.KhelSutra.t(key, vars) -> active-locale string (en
fallback;
118        // undefined if absent everywhere, so callers can supply their own default).
119        if (typeof window !== "undefined") {
120            window.KhelSutra = { t: (key, vars) => translate(activeCatalogs, activeLocale, key,
vars), lang: activeLocale };
121        }
122    }
123
124    async function boot() {
125        let stored = null;
126        try { stored = localStorage.getItem(STORAGE_KEY); } catch { /* ignore */ }
127        if (!stored) stored = readCookie(STORAGE_KEY); // server-set or cross-store persisted
pref
128        const query = new URLSearchParams(location.search).get("lang");
129        const nav = navigator.languages && navigator.languages.length ?
[...navigator.languages] : [navigator.language];
130        const locale = negotiate({ stored, query, nav });
131        await render(locale);
132        document.addEventListener("change", (e) => {
133            const sel = e.target.closest && e.target.closest("select[data-langsw]");
134            if (!sel) return;
135            const loc = supported(sel.value) || DEFAULT;
136            persist(loc);
137            render(loc);
138        });
139    }
140
141    if (typeof document !== "undefined" && typeof window !== "undefined") {
142        if (document.readyState === "loading") document.addEventListener("DOMContentLoaded",
boot);
143        else boot();
144    }
145

```

13. user (2026-06-22T01:11:55.009Z)

```

1    // DRIFT GUARD for the one build step the otherwise no-build site has (tracker B3 /
D-CATALOG-HOME):
2    // the catalogs the marketing site ships (site/public/locales/) MUST be byte-identical
to the single

```

```

3      // source of truth (repo-root /locales/). If someone edits /locales without re-running
the copy, this
4      // fails CI with the exact fix. Run `npm run copy:locales` to resync.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync, readdirSync } from "node:fs";
8      import { join } from "node:path";
9
10     const SRC = join(import.meta.dirname, "..", "..", "locales");
11     const PUB = join(import.meta.dirname, "..", "public", "locales");
12
13     test("site/public/locales mirrors repo-root /locales exactly (else: npm run
copy:locales)", () => {
14         const locales = readdirSync(SRC, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name);
15         assert.ok(locales.length >= 3, "expected at least en/kn/hi catalogs in /locales");
16
17         const shipped = new Set(readdirSync(PUB, { withFileTypes: true }).filter((d) =>
d.isDirectory()).map((d) => d.name));
18         for (const loc of locales) {
19             const src = readFileSync(join(SRC, loc, "common.json"), "utf8");
20             assert.ok(shipped.has(loc), `site/public/locales/${loc} is missing ? run npm run
copy:locales`);
21             const pub = readFileSync(join(PUB, loc, "common.json"), "utf8");
22             assert.equal(pub, src, `site/public/locales/${loc}/common.json drifted from
/locales/${loc} ? run npm run copy:locales`);
23         }
24         // No stale extra locales shipped that aren't in the source of truth.
25         for (const loc of shipped) {
26             assert.ok(locales.includes(loc), `site/public/locales/${loc} has no source in
/locales ? run npm run copy:locales`);
27         }
28     });
29

```

14. user (2026-06-22T01:11:55.396Z)

```

1      // Static-site integrity ? the landing page + capture checklist + OG image ARE the
public
2      // product. server.test.js proves the VM host *serves* "/", "/capture", "/og.png"; this
3      // guards the CONTENT contract so a broken edit (deleted asset, broken form wiring, dead
4      // capture link, missing/!absolute OG image) fails CI instead of shipping to the live
site.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync, statSync } from "node:fs";
8      import { join } from "node:path";
9      import { JSDOM } from "jsdom";
10
11     const PUBLIC = join(import.meta.dirname, "..", "public");
12     const read = (f) => readFileSync(join(PUBLIC, f), "utf8");
13     const size = (f) => statSync(join(PUBLIC, f)).size;
14     const enCatalog = JSON.parse(readFileSync(join(import.meta.dirname, "..", "..",
"locales", "en", "common.json"), "utf8"));
15
16     test("core public assets exist and are non-empty", () => {
17         for (const f of ["index.html", "capture.html", "og.png"]) {
18             assert.ok(size(f) > 0, `public/${f} is missing or empty`);
19         }
20     });
21
22     test("landing page wires the Request-Access form to the API", () => {
23         const html = read("index.html");
24         assert.match(html, /id="af"/, "the #af form is gone");
25         assert.match(html, /\api\/request-access/, "form no longer posts to /api/request-

```



```

access");
26     assert.match(html, /name="company"[^>]*tabindex="-1"/, "honeypot field removed (bots
will get through)");
27     for (const field of ["segment", "has_gpu", "storage"]) {
28         assert.match(html, new RegExp(`name="${field}"`), `form lost the '${field}' field (a
demand signal)`);
29     }
30 };
31
32 test("submitting the form shows an obvious in-flight state (no silent freeze)", () => {
33     const html = read("index.html");
34     assert.match(html, /Sending?/, "submit should swap to a 'Sending?' state while the
request is in flight");
35     assert.match(html, /aria-busy/, "submit should set aria-busy for assistive tech during
the request");
36     assert.match(html, /class="spin"/, "the in-flight spinner is gone");
37     assert.match(html, /\.spin\{/, "the spinner style is gone");
38     // the button must be RE-ENABLED on failure so the user isn't stuck on a frozen
'Sending?'
39     assert.match(html, /btn\.disabled\s*=\s*false/, "submit button isn't restored on the
failure path");
40 });
41
42 test("OG + canonical meta point at the live https origin", () => {
43     const html = read("index.html");
44     assert.match(html,
/property="og:image"\s+content="https:\/\/khelsutra\.guru\/og\.png"/, "og:image must be the
absolute live URL");
45     assert.match(html, /property="og:url"\s+content="https:\/\/khelsutra\.guru"/, "og:url
drift");
46 });
47
48 test("the sample reel is GATED behind sign-up + starts at a RANDOM point (not shown
openly)", () => {
49     const html = read("index.html");
50     assert.match(html, /ajTCZ7pJW_o/, "the sample-reel video id is gone");
51     assert.match(html, /youtube-nocookie\.com/, "reel should use the privacy nocookie
host");
52     assert.match(html, /id="reel-reveal"/, "the on-signup reveal host is gone");
53     assert.match(html, /see it in action/i, "the 'see it in action' sign-up teaser is
gone");
54     assert.match(html, /reel-count/, "the auto-close countdown is gone");
55     assert.match(html, /REEL_SECS = 30/, "the reel preview should be ~30s");
56     assert.match(html, /getDuration\(\)/, "random start should derive from the real video
duration");
57     assert.match(html, /Math\.random\(\)/, "the start point should be randomized");
58     assert.match(html, /seekTo\(/, "the player should seek to the random start");
59     // Must NOT be an openly-rendered public section ? it only appears after a successful
submit.
60     assert.doesNotMatch(html, /<section id="reel"/, "the reel must be sign-up-gated, not
an open public section");
61     assert.doesNotMatch(html, /id="reel-play"/, "the open click-to-play facade should be
removed");
62 });
63
64 test("the TOOL screencast is self-hosted, footage-free, and revealed only after sign-
up", () => {
65     const html = read("index.html");
66     assert.match(html, /\video\/tool-cuj\.mp4/, "the tool-operation screencast reference
is gone");
67     assert.match(html, /function revealAfterSignup/, "the post-signup reveal function is
gone");
68     assert.match(html, /revealAfterSignup\(\)/, "the reveal must be wired to a successful
submit");
69     // GATED: the only reference to the tool screencast lives inside the reveal function

```

```

(injected on
70     // signup), not as an open autoplay element rendered for every visitor.
71     assert.ok(
72         html.indexOf("/video/tool-cuj.mp4") > html.indexOf("function revealAfterSignup"),
73         "the tool screencast must be inside the post-signup reveal, not shown openly",
74     );
75     // the self-hosted clip exists and is non-trivial (a real recording, not an empty
placeholder)
76     assert.ok(size("video/tool-cuj.mp4") > 50_000, "tool-cuj.mp4 is missing or too small
to be the real screencast");
77 });
78
79     test("the post-signup reveal keeps its watchability affordances (manual close + play-
gated auto-close)", () => {
80         // Content contract only ? the BEHAVIOUR (close works, auto-close holds while the reel
plays) is
81         // proven against the real page in ux.dom.test.js, so we don't pin brittle
implementation strings.
82         const html = read("index.html");
83         assert.match(html, /id="reel-close"/, "the manual ? close button is gone");
84         assert.match(html, /onStateChange/, "the reel's play-state must still gate the auto-
close");
85     });
86
87     test("the capture checklist is linked and is a real page", () => {
88         assert.match(read("index.html"), /href="\capture(\.html)?"/, "footer capture-
checklist link is gone");
89         const cap = read("capture.html");
90         assert.match(cap, /<html/i, "capture.html is not HTML");
91         assert.match(cap, /capture checklist/i, "capture.html lost its checklist content");
92     });
93
94     test("the academy flyers (en/kn/hi) exist, are language-correct, and are linked from the
homepage", () => {
95         const html = read("index.html");
96         // All three are linked from the homepage footer (the owner ask: the flyers must be
findable).
97         assert.match(html, /href="\flyer"/, "homepage doesn't link the English academy
flyer");
98         assert.match(html, /href="\flyer-kn"/, "homepage doesn't link the Kannada academy
flyer");
99         assert.match(html, /href="\flyer-hi"/, "homepage doesn't link the Hindi academy
flyer");
100
101         // The three flyer pages exist, are HTML, and carry the right language + script.
102         const en = read("flyer.html");
103         assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");
104         const kn = read("flyer-kn.html");
105         assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
106         assert.match(kn, /[?-\?]/, "flyer-kn.html should contain Kannada text");
107         const hi = read("flyer-hi.html");
108         assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
109         assert.match(hi, /[?-\?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
110     });
111
112     test("each flyer shows a screenshot of the tool rendered in that language", () => {
113         for (const [flyer, img] of [
["flyer.html", "studio-en.png"],
["flyer-kn.html", "studio-kn.png"],
["flyer-hi.html", "studio-hi.png"]
]) {
114             assert.ok(size(`img/${img}`) > 0, `public/img/${img} (the localized UI shot) is
missing or empty`);
115             assert.match(read(flyer), new RegExp(`img/${img}`), `${flyer} should embed its
localized UI screenshot /img/${img}`);
116         }
117     });
118

```

```

119     test("the academy flyers are also linked from the top nav and the own-model page", () =>
120     {
121         const html = read("index.html");
122         // Desktop top nav carries a Flyer entry (alongside Own your model).
123         const nav = html.match(/<nav class="nav-links"[\s\S]*?<\nav>/);
124         assert.ok(nav, "the primary nav block is gone");
125         assert.match(nav[0], /href="\flyer"/, "the top nav doesn't link the Flyer");
126         // own-model surfaces all three languages.
127         const om = read("own-model.html");
128         assert.match(om, /href="\flyer"/, "own-model doesn't link the English flyer");
129         assert.match(om, /href="\flyer-kn"/, "own-model doesn't link the Kannada flyer");
130         assert.match(om, /href="\flyer-hi"/, "own-model doesn't link the Hindi flyer");
131     });
132     test("the landing page surfaces how to record reliably (so users can set up with
confidence)", () => {
133         const html = read("index.html");
134         assert.match(html, /id="record"/, "the 'record it right' section is gone");
135         assert.match(html, /one match, one court/i, "the #1 single-court capture rule should
be on the homepage");
136         // the gist must carry the load-bearing capture cues + a prominent link to the full
checklist
137         for (const cue of [/1080p/, /30 fps/i, /[Aa]udio ON/, /baseline/, /[Nn]o panning/]) {
138             assert.match(html, cue, `the recording gist is missing a key cue: ${cue}`);
139         }
140         assert.match(html, /href="\capture"[\^>]*>Full 1-page capture checklist/i, "a
prominent link to the full checklist is gone");
141     });
142
143     test("the 'How do I join?' FAQ points at the request-access form, not email", () => {
144         const html = read("index.html");
145         const m = html.match(/How do I join?<\summary>(<p>[\s\S]*?<\p>)/);
146         assert.ok(m, "the 'How do I join?' FAQ is gone");
147         assert.match(m[1], /request access/i, "the join FAQ should send people to the request-
access form");
148         assert.match(m[1], /href="#join"/, "the join FAQ should link to the #join form");
149         assert.doesNotMatch(m[1], /mailto/, "the join FAQ should NOT tell people to email (use
the form)");
150     });
151
152     test("the own-model page exists, is honestly scoped, and is linked from the landing
page", () => {
153         const om = read("own-model.html");
154         assert.ok(om.length > 0, "own-model.html is missing or empty");
155         for (const id of ["annotate", "train", "setup"]) {
156             assert.match(om, new RegExp(`id="${id}"`), `own-model is missing the #${id}
section`);
157         }
158         assert.match(om, /github\.com\/Khelsutra\/rally-annotator/, "the GitHub link to the
annotator is gone");
159         assert.match(om, /Read this honestly/i, "the honest framing fence is gone");
160         assert.match(om, /open pipeline|in build/i, "training must be honestly scoped as in-
build, not one-click");
161         assert.match(om, /name="robots" content="noindex"/, "own-model should be noindex");
162         assert.match(read("index.html"), /href="\own-model"/, "the landing page should link
to /own-model");
163         assert.match(om, /<a href="\>? KhelSutra home<\a>/, "own-model needs an obvious
back-to-home link (not just browser-back)");
164
165         // a ready-made default works without training (keeps non-tech users engaged); BYO-
training is optional
166         assert.match(om, /ready-made default|out of the box|don't have to train/i, "must
reassure a default works without training");
167         assert.match(om, /optional/i, "training your own should be framed as optional");
168

```

```

169 // own-model shows the annotation TOOL screenshots (no people) ? real captures, files
present
170 for (const img of ["annotate-enable.png", "annotate-tool.png"]) {
171     assert.match(om, new RegExp(`/img/${img}`), `own-model should embed /img/${img}`);
172     assert.ok(size(`img/${img}`) > 0, `public/img/${img} is missing or empty`);
173 }
174 assert.match(om, /<img[^>]+alt="/i, "screenshots must have alt text");
175
176 // the sample REEL stays gated behind request-access ? NOT embedded/playable here, no
footage shown
177 assert.doesNotMatch(om, /<iframe/i, "the reel must NOT be embedded here ? it's gated
behind request-access");
178 assert.doesNotMatch(om, /youtube/i, "no YouTube embed on own-model; the reel is shown
only after request-access");
179 assert.doesNotMatch(om, /i\.yimg\.com/, "don't show the video thumbnail (players)
openly");
180 assert.match(om, /sample[\s\S]{0,80}request access|request access[\s\S]{0,80}sample/i,
"point users to request access for a sample output");
181 });
182
183 // ---- B3: the trilingual marketing surface (shared t()/data-i18n shim + persistent
switcher) -----
184 const I18N_PAGES = ["index.html", "capture.html", "own-model.html"];
185
186 test("every localizable page loads the shared i18n shim", () => {
187     for (const f of I18N_PAGES) {
188         assert.match(read(f), /<script[^>]+type="module"[^>]+src="\s\/i18n\.js"/, `${f}
doesn't load the i18n shim (/i18n.js)`);
189     }
190 });
191
192 test("every localizable page has a persistent, compact en/kn/hi language <select>
switcher", () => {
193     for (const f of I18N_PAGES) {
194         const html = read(f);
195         // Compact dropdown (a single <select>, not 3 always-visible pills) so the header
can't overflow.
196         assert.match(html, /class="langsw"/, `${f} is missing the language switcher`);
197         assert.match(html, /<select data-langsw[^>]*aria-label="Language"/, `${f} switcher
must be a labelled <select data-langsw>`);
198         for (const lang of ["en", "kn", "hi"]) {
199             assert.match(html, new RegExp(`<option value="${lang}"`), `${f} switcher lacks the
${lang} option`);
200         }
201         // The option labels are driven by the SHARED catalog (lang.*) ? proves cross-
surface consumption.
202         assert.match(html, /<option value="kn" data-i18n="lang\.kn"/, `${f} switcher option
isn't wired to the shared catalog (lang.kn)`);
203         // The Kannada/Hindi autonyms are present in their own scripts (Noto/ system-font
fallback renders them).
204         assert.match(html, /?????/, `${f} switcher lacks the Kannada autonym`);
205         assert.match(html, /?????/, `${f} switcher lacks the Hindi autonym`);
206     }
207 });
208
209 test("marketing content is wired for translation via data-i18n, and every key exists in
the en catalog", () => {
210     const dig = (obj, key) => key.split(".").reduce((o, k) => (o == null ? o : o[k]),
obj);
211     const used = new Set();
212     for (const f of I18N_PAGES) {
213         const html = read(f);
214         const keys = [...html.matchAll(/data-i18n="([^\"]+)"/g)].map((m) => m[1]);
215         assert.ok(keys.length >= 3, `${f} should wire at least a few strings via data-i18n
(found ${keys.length})`);

```

```

216     keys.forEach((k) => used.add(k));
217 }
218 // Every data-i18n key across the site must resolve in the en source catalog (no
dangling keys -> the
219 // shim would otherwise leave the English HTML default, but a typo'd key is a silent
bug).
220 for (const key of used) {
221     assert.notEqual(dig(enCatalog, key), undefined, `data-i18n="${key}" has no entry in
the en catalog`);
222 }
223 // The shared site.* marketing namespace is present (the B3 deliverable ? en authored,
kn/hi later).
224 assert.ok(enCatalog.site && enCatalog.site.nav && enCatalog.site.hero, "the en catalog
is missing the site.* marketing namespace");
225 });
226
227 test("the en catalog value matches the HTML default for representative data-i18n keys
(no drift)", () => {
228     // The HTML carries the English default text (SEO/no-JS); the en catalog must mirror
it so an en
229     // visitor renders identically and a future kn/hi translation simply overrides the
same string.
230     assert.match(read("capture.html"), /<h1 data-i18n="site\.capture\.title">1-page
capture checklist<\h1>/);
231     assert.equal(enCatalog.site.capture.title, "1-page capture checklist");
232     assert.match(read("index.html"), /data-i18n="site\.nav\.requestAccess">Request
access</>/);
233     assert.equal(enCatalog.site.nav.requestAccess, "Request access");
234 });
235
236 // ---- A3: recording-education localized + Noto fonts bundled for kn/hi rendering
-----
237 test("A3: every marketing page bundles Noto Kannada + Devanagari so kn/hi render (not
tofu)", () => {
238     for (const f of ["index.html", "capture.html", "own-model.html"]) {
239         const html = read(f);
240         assert.match(html, /Noto\+Sans\+Kannada/, `${f} doesn't load Noto Sans Kannada`);
241         assert.match(html, /Noto\+Sans\+Devanagari/, `${f} doesn't load Noto Sans
Devanagari`);
242         assert.match(html, /--font:[^;]*'Noto Sans Kannada'[^;]*'Noto Sans Devanagari'/,
`${f} font stack must fall back to Noto for Indic glyphs`);
243         // Order matters: the Latin display font leads, then the Noto Indic families, BEFORE
the generic
244         // fallbacks ? else a system UI font with partial Indic glyphs could win and defeat
the bundle.
245         const stack = html.match(/--font:([^;]*)/)[1];
246         assert.ok(stack.indexOf("Noto Sans Kannada") < stack.indexOf("system-ui"), `${f}:
Noto Kannada must precede system-ui`);
247         assert.ok(stack.indexOf("Noto Sans Devanagari") < stack.indexOf("system-ui"),
`${f}: Noto Devanagari must precede system-ui`);
248         assert.ok(stack.indexOf("Plus Jakarta Sans") < stack.indexOf("Noto Sans
Kannada"), `${f}: the Latin display font must lead the stack`);
249     }
250 });
251
252 test("A3: the recording-education content is wired for translation (homepage gist +
capture page)", () => {
253     const dig = (obj, key) => key.split(".").reduce((o, k) => (o == null ? o : o[k]),
obj);
254     // Both the rich (data-i18n-html, inline <b>) and plain (data-i18n) forms are used,
and EVERY key
255     // across BOTH forms resolves in the en source catalog (a typo'd key would silently
show English).
256     for (const f of ["index.html", "capture.html"]) {
257         const html = read(f);

```

```

258     const keys = [...html.matchAll(/data-i18n(?:-html)?="([^\"]+)"/g)].map((m) =>
m[1]).filter((k) => k.startsWith("site."));
259     for (const key of keys) {
260         assert.notEqual(dig(enCatalog, key), undefined, `${f}: data-i18n key "${key}" has
no en catalog entry`);
261     }
262 }
263 // The capture page localizes the load-bearing recording cues via the rich (html)
form.
264 const cap = read("capture.html");
265 assert.match(cap, /data-i18n-html="site.capture.step1.b1"/, "capture step-1
placement bullet isn't localizable");
266 assert.match(cap, /data-i18n-html="site.capture.step2.b3"/, "capture audio bullet
isn't localizable");
267 // The homepage gist localizes its cards.
268 assert.match(read("index.html"), /data-i18n-html="site.record.settings.body"/,
"homepage settings card isn't localizable");
269 // en catalog's recording values keep the inline <b> markup the HTML relies on.
270 assert.match(enCatalog.site.record.place.body, /<b>.*<\b>/s, "en record.place.body
lost its <b> markup");
271 assert.match(enCatalog.site.capture.step2.b1, /<b>1080p or higher<\b>/, "en
capture.step2.b1 markup drift");
272 });
273
274 test("A3: EVERY data-i18n[-html] HTML default matches the en catalog byte-for-byte (no
drift, incl. rich <b> keys)", () => {
275     // The rich (data-i18n-html) keys are the most drift-prone: the inline <b> markup must
match the
276     // catalog exactly, or an en visitor's no-JS default and the shim's en render silently
diverge.
277     // Parse the REAL pages in jsdom and compare each tagged element's default to
enCatalog.
278     const dig = (o, k) => k.split(".").reduce((a, c) => (a == null ? a : a[c]), o);
279     let checked = 0;
280     for (const f of ["index.html", "capture.html", "own-model.html"]) {
281         const { document } = new JSDOM(read(f)).window;
282         for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
283             if (el.getAttribute("data-i18n-attr")) continue; // attribute defaults aren't the
visible text
284             const htmlKey = el.getAttribute("data-i18n-html");
285             const key = htmlKey || el.getAttribute("data-i18n");
286             const enVal = dig(enCatalog, key);
287             assert.notEqual(enVal, undefined, `${f}: data-i18n key "${key}" missing from en
catalog`);
288             const got = (htmlKey ? el.innerHTML : el.textContent).trim();
289             assert.equal(got, enVal, `${f}: "${key}" HTML default drifted from the en
catalog`);
290             checked++;
291         }
292     }
293     assert.ok(checked >= 60, `expected to check the full localized surface, only saw
${checked}`);
294 });
295
296 // ---- A6: plain-language Request-Access GPU/storage questions
-----
297 test("A6: the GPU/storage questions are de-jargoned + reassuring, backend contract
intact", () => {
298     const html = read("index.html");
299     // The intimidating phrasings are gone from the visible copy.
300     assert.doesNotMatch(html, /GPU machine/i, "'GPU machine' jargon should be gone");
301     assert.doesNotMatch(html, /process video locally/i, "'process video locally' jargon
should be gone");
302     assert.doesNotMatch(html, /\(S3\GCS\)/, "the bare '(S3/GCS)' jargon should be gone");
303     // Reassurance: a non-tech user is explicitly told a GPU isn't required.

```

```

304     assert.match(html, /run it in the cloud for you/i, "the GPU question must reassure
that the cloud is an option");
305     assert.match(enCatalog.site.join.gpuHint, /no worries|don't need|cloud/i, "the GPU
hint should reassure");
306     // Questions route through the shim (translation-ready).
307     assert.match(html, /data-i18n="site\.join\.gpuLabel"/, "GPU question not wired for
i18n");
308     assert.match(html, /data-i18n="site\.join\.storageLabel"/, "storage question not wired
for i18n");
309     // The backend contract is preserved: field names + EVERY enum value unchanged (server
validates these).
310     for (const v of ["yes", "unsure", "no", "prefer-cloud"]) assert.match(html, new
RegExp(`name="has_gpu" value="\${v}"`), `has_gpu value \${v} lost`);
311     for (const v of ["gdrive", "onedrive", "dropbox", "bucket", "local", "unsure"])
assert.match(html, new RegExp(`name="storage" value="\${v}"`), `storage value \${v} lost`);
312   });
313
314   // ---- A7: camera-placement diagram on the capture page
-----
315   test("A7: the capture page shows an accessible, localized camera-placement diagram", ()
=> {
316     const cap = read("capture.html");
317     assert.match(cap, /<figure class="diagram">/, "the placement diagram figure is
missing");
318     assert.match(cap, /<svg[>]*role="img"/, "the diagram must be an accessible <svg
role=\"img\">");
319     assert.match(cap, /<title data-i18n="site\.capture\.diagram\.title"/, "the svg needs a
localized accessible <title>");
320     assert.match(cap, /fill-opacity="0\.10"/, "the field-of-view cone (what the camera
captures) is missing");
321     assert.match(cap, /?30°/, "the ~30° downward-tilt annotation is missing");
322     assert.match(cap, /?[\s\S]?[\s\S]?/, "the diagram's step markers ??? are missing");
323     // The legend maps the markers to the placement rules and is fully localizable.
324     for (const k of ["title", "camera", "angle", "frame", "net"]) {
325       assert.match(cap, new RegExp(`data-i18n="site\\.capture\\.diagram\\.\\.\${k}"`),
`diagram lacks the \${k} label`);
326       assert.notEqual(enCatalog.site.capture.diagram[k], undefined, `en catalog missing
diagram.\${k}`);
327     }
328     // The diagram complements the existing #1 "Place the camera" text step (doesn't
replace it).
329     assert.match(cap, /data-i18n="site\.capture\.step1\.title"/, "the placement text step
should remain");
330   });
331
332   // ---- A2: localized WhatsApp share in the post-signup reveal
-----
333   test("A2: the post-signup reveal offers a localized, safe WhatsApp share of the reel",
() => {
334     const html = read("index.html");
335     // The reveal is injected after sign-up, so its share copy comes from the shim bridge
336     // (window.KhelSutra.t) with an en fallback, rendered as a wa.me link.
337     assert.match(html, /window\.KhelSutra\s*&\s*window\.KhelSutra\.t/, "reveal should
pull share copy from the shim bridge");
338     assert.match(html, /ksT\('site\.reveal\.shareText'\)/, "reveal should use the
site.reveal.shareText key");
339     assert.match(html, /id="reel-share"/, "the reveal share button is missing");
340     assert.match(html, /'https:\/\/wa.me\/\?text='/, "share must be a wa.me link");
341     assert.match(html, /rel="noopener noreferrer"/, "external share link must be tab-
nabbing-safe");
342     // The shim exposes the bridge after render.
343     assert.match(read("i18n.js"), /window\.KhelSutra\s*=\s*\{\s*t:/, "the shim must expose
window.KhelSutra.t for dynamic content");
344     // Keys exist in the shared catalog (en authored; kn/hi translated).
345     assert.ok(enCatalog.site.reveal.share && enCatalog.site.reveal.shareText, "en catalog

```

```
missing site.reveal.*");
346   });
347
```

15. assistant (2026-06-22T01:12:02.757Z)

Now let me look at the kn/hi catalogs' `site.\*` namespace, the shim unit test, and find where kn/hi content render is asserted (the "in-script check" A3 mentioned).

16. user (2026-06-22T01:12:03.789Z)

```
1      // Unit tests for the marketing-site i18n shim (public/i18n.js, tracker B3). Proves the
shim mirrors
2      // the SPA's react-i18next contract: same negotiation order, ICU-lite
interpolation/plurals, en
3      // fallback, and a data-i18n walker that NEVER leaves a raw key. Tested against the REAL
shared
4      // catalogs (/locales) ? so this also proves both surfaces consume one source of truth.
5      import { test } from "node:test";
6      import assert from "node:assert/strict";
7      import { readFileSync } from "node:fs";
8      import { join } from "node:path";
9      import { JSDOM } from "jsdom";
10     import { negotiate, interpolate, translate, applyDom, SUPPORTED, DEFAULT } from
"../public/i18n.js";
11
12     const LOCALES = join(import.meta.dirname, "..", "..", "locales");
13     const load = (loc) => JSON.parse(readFileSync(join(LOCALES, loc, "common.json"),
"utf8"));
14     const catalogs = { en: load("en"), kn: load("kn"), hi: load("hi") };
15
16     test("negotiation order matches the SPA: persisted -> ?lang -> navigator -> en", () => {
17         assert.equal(negotiate({ stored: "kn", query: "hi", nav: ["en-US"] }), "kn",
"persisted pref wins");
18         assert.equal(negotiate({ query: "hi", nav: ["en-US"] }), "hi", "?lang beats
navigator");
19         assert.equal(negotiate({ nav: ["kn-IN", "en-IN"] }), "kn", "navigator picks the first
supported");
20         assert.equal(negotiate({}), "en", "nothing -> en");
21     });
22
23     test("region subtags normalize and unsupported degrades to en (never a locale we can't
serve)", () => {
24         assert.equal(negotiate({ nav: ["hi-IN"] }), "hi", "hi-IN -> hi");
25         assert.equal(negotiate({ nav: ["ta-IN"] }), "en", "Tamil (unsupported) -> en");
26         assert.equal(negotiate({ stored: "es" }), "en", "es is SPA-only ? the trilingual site
degrades it to en");
27         assert.deepEqual([...SUPPORTED], ["en", "kn", "hi"]);
28         assert.equal(DEFAULT, "en");
29     });
30
31     test("ICU-lite interpolation: {name} substitution", () => {
32         assert.equal(interpolate("over {n}s", { n: 10 }), "over 10s");
33         assert.equal(interpolate("Couldn't load: {error}", { error: "boom" }), "Couldn't load:
boom");
34     });
35
36     test("ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number", () => {
37         const en = catalogs.en.selection.count; // "{count, plural, one {# rally selected}
other {# rallies selected}}"
38         assert.equal(interpolate(en, { count: 1 }, "en"), "1 rally selected");
39         assert.equal(interpolate(en, { count: 5 }, "en"), "5 rallies selected");
40         // Kannada is also one/other ? the shim picks the arm from the catalog, no hard-coded
rules.
41         assert.equal(translate(catalogs, "kn", "selection.count", { count: 1 }),
```



```

catalogs.kn.selection.count.match(/one \{([^\}]*\}\)/[1].replace("#", "1"));
42     });
43
44     test("translate: active locale, then en fallback, then undefined (caller keeps the DOM
default)", () => {
45         assert.equal(translate(catalogs, "kn", "app.title"), catalogs.kn.app.title); // real
Kannada
46         assert.equal(translate(catalogs, "en", "lang.kn"), "?????"); // shared catalog autonomy
47         // A3: site.* marketing is now translated for kn (no longer the en seed).
48         assert.equal(translate(catalogs, "kn", "site.capture.title"),
catalogs.kn.site.capture.title);
49         assert.notEqual(catalogs.kn.site.capture.title, catalogs.en.site.capture.title, "kn
capture.title must be translated, not an en seed");
50         // en fallback when a key is absent from the active locale (synthetic ? real catalogs
have full parity).
51         assert.equal(translate({ en: { only: { en: "fallback" } }, kn: {} }, "kn", "only.en"),
"fallback");
52         assert.equal(translate(catalogs, "kn", "does.not.exist"), undefined, "missing
everywhere -> undefined");
53     });
54
55     test("applyDom walks data-i18n, sets attrs, reflects the active locale in the <select>,
never shows a raw key", () => {
56         const { document } = new JSDOM(`<!doctype html><body>
57             <span id="auto" data-i18n="lang.kn">PLACEHOLDER</span>
58             <span id="keep" data-i18n="does.not.exist">KEEP ME</span>
59             <input id="ph" data-i18n="site.capture.title" data-i18n-attr="placeholder" />
60             <select id="sw" data-langsw aria-label="Language">
61                 <option value="en" data-i18n="lang.en">English</option>
62                 <option value="kn" data-i18n="lang.kn">?????</option>
63                 <option value="hi" data-i18n="lang.hi">?????</option>
64             </select>
65         </body>`).window;
66
67         applyDom(document, catalogs, "kn");
68
69         assert.equal(document.getElementById("auto").textContent, "?????", "data-i18n sets
textContent from the shared catalog");
70         assert.equal(document.getElementById("keep").textContent, "KEEP ME", "a missing key
leaves the HTML default ? never a raw key");
71         assert.equal(document.getElementById("ph").getAttribute("placeholder"),
catalogs.kn.site.capture.title, "data-i18n-attr targets an attribute (kn value for the kn
locale)");
72         // The compact <select> reflects the active locale (its displayed text follows the
selected option).
73         const sw = document.getElementById("sw");
74         assert.equal(sw.value, "kn", "the switcher <select> must reflect the active locale");
75         assert.equal(sw.selectedOptions[0].textContent, "?????", "the selected option shows
the localized autonomy");
76     });
77
78     test("data-i18n-html sets innerHTML and preserves inline <b> markup (A3 recording-
education)", () => {
79         const { document } = new JSDOM(`<!doctype html><body>
80             <p id="rich" data-i18n-html="site.record.place.body">Behind <b>one baseline</b>
?</p>
81             <li id="kept" data-i18n-html="does.not.exist">KEEP <b>this</b></li>
82         </body>`).window;
83
84         // en: innerHTML equals the catalog value verbatim (with its <b> tags), not escaped
text.
85         applyDom(document, catalogs, "en");
86         assert.equal(document.getElementById("rich").innerHTML,
catalogs.en.site.record.place.body);
87         assert.ok(document.getElementById("rich").querySelector("b"), "the <b> must be a real

```

```

element, not escaped text");
88     assert.equal(document.getElementById("kept").innerHTML, "KEEP <b>this</b>", "a missing
html key leaves the HTML default");
89
90     // kn: swaps to the Kannada value, still carrying its <b> tags.
91     applyDom(document, catalogs, "kn");
92     assert.equal(document.getElementById("rich").innerHTML,
catalogs.kn.site.record.place.body);
93     assert.match(document.getElementById("rich").innerHTML, /<b>.*<\b>/s, "kn rich value
keeps <b> markup");
94     });
95
96     test("data-i18n-html falls back through en (markup intact) when the active locale lacks
the key", () => {
97         // The middle rung: active locale missing a rich key -> en value (with <b>), not just
the DOM default.
98         const { document } = new JSDOM(`<!doctype html><body><p id="r"
data-i18n-html="site.r.b">default</p></body>`).window;
99         applyDom(document, { en: { site: { r: { b: "X <b>Y</b> Z" } } }, kn: { } }, "kn");
100        assert.equal(document.getElementById("r").innerHTML, "X <b>Y</b> Z", "html form must
fall back to en, not the DOM default");
101        assert.ok(document.getElementById("r").querySelector("b"), "the <b> survives the en-
fallback path");
102    });
103
104    test("A3: the kn/hi catalogs carry REAL recording-education translations (not English
seeds)", () => {
105        // Kannada script range U+0C80?U+0CFF; Devanagari U+0900?U+097F. A representative
spread of the
106        // recording keys must be in-script (proves A3 actually translated, not B3's en seed).
107        const KN = /[?-\?]/, HI = /[?-\?]/;
108        for (const key of ["hero.title", "record.intro", "record.place.title",
"capture.step1.b3", "capture.consent", "capture.diagram.camera", "nav.requestAccess"]) {
109            const path = key.split(".");
110            const kn = path.reduce((o, k) => o[k], catalogs.kn.site);
111            const hi = path.reduce((o, k) => o[k], catalogs.hi.site);
112            assert.match(kn, KN, `kn site.${key} should be in Kannada script (a leftover English
seed would not match)`);
113            assert.match(hi, HI, `hi site.${key} should be in Devanagari script`);
114        }
115        // A brand/token-free key must be FULLY in-script (no stray English) ? strongest anti-
seed check.
116        assert.doesNotMatch(catalogs.kn.site.capture.consent, /[A-Za-z]/, "kn capture.consent
has no business containing Latin letters");
117        assert.doesNotMatch(catalogs.hi.site.capture.consent, /[A-Za-z]/, "hi capture.consent
has no business containing Latin letters");
118        // Brand + literal tokens are intentionally preserved across languages.
119        assert.match(catalogs.kn.site.record.intro, /Khe1Sutra/, "brand stays in Latin");
120        assert.match(catalogs.hi.site.record.settings.body, /1080p\+|30 fps/, "technical
tokens stay literal");
121    });
122

```

17. user (2026-06-22T01:12:05.882Z)

```

site\src\i18n.shim.test.js:106: // recording keys must be in-script (proves A3 actually
translated, not B3's en seed).
site\src\i18n.shim.test.js:107: const KN = /[?-\?]/, HI = /[?-\?]/;
site\src\i18n.shim.test.js:108: for (const key of ["hero.title", "record.intro",
"record.place.title", "capture.step1.b3", "capture.consent", "capture.diagram.camera",
"nav.requestAccess"]) {
site\src\i18n.shim.test.js:115: // A brand/token-free key must be FULLY in-script (no stray
English) ? strongest anti-seed check.
site\src\assets.test.js:106: assert.match(kn, /[?-\?]/, "flyer-kn.html should contain Kannada
text");

```

```

site\src\assets.test.js:109:  assert.match(hi, /[?-\?]/, "flyer-hi.html should contain Devanagari
(Hindi) text");
site\src\assets.test.js:229:  // visitor renders identically and a future kn/hi translation
simply overrides the same string.
site\src\assets.test.js:236:// ---- A3: recording-education localized + Noto fonts bundled for
kn/hi rendering -----
site\src\assets.test.js:237:test("A3: every marketing page bundles Noto Kannada + Devanagari so
kn/hi render (not tofu)", () => {
site\src\server.test.js:122:test("[VM host . N8] a Kannada browser (Accept-Language: kn) gets
the kn-rendered page", async () => {

```

18. assistant (2026-06-22T01:12:11.061Z)

Let me confirm the current `site.ownModel.\*` state across all catalogs and check the copy-locales script + how A3 added its keys (git history).

19. user (2026-06-22T01:12:14.153Z)

```

=== ownModel in each catalog ===
--- en ---
{
  "requestAccess": "Request access ?"
}
--- kn ---
{
  "requestAccess": "?????? ???? ?"
}
--- hi ---
{
  "requestAccess": "?????? ?? ?????? ???? ?"
}
--- es ---
{
  "requestAccess": "Request access ?"
}
--- da ---
{
  "requestAccess": "Request access ?"
}
--- id ---
{
  "requestAccess": "Request access ?"
}

```

20. user (2026-06-22T01:12:14.403Z)

```

1      // Mirror the single-source-of-truth catalogs (repo-root /locales, D-CATALOG-HOME) into
the site's
2      // static public/ dir, so the dependency-free marketing site can fetch them at runtime
via the
3      // t()/data-i18n shim (public/i18n.js). This copy is the ONLY build step the otherwise
no-build site
4      // has. Run on demand (`npm run copy:locales`) or automatically before deploy
(`predeploy`).
5      //
6      // The committed copy under site/public/locales/ is what actually ships (static hosts
serve it with
7      // no build); the drift-guard test (src/locales-drift.test.js) fails CI if it goes stale
vs /locales.
8      import { cpSync, rmSync, mkdirSync, readdirSync } from "node:fs";
9      import { join } from "node:path";
10
11     const SRC = join(import.meta.dirname, "..", "..", "locales");
12     const DEST = join(import.meta.dirname, "..", "public", "locales");

```

```

13
14     rmSync(DEST, { recursive: true, force: true });
15     mkdirSync(DEST, { recursive: true });
16     cpSync(SRC, DEST, { recursive: true });
17
18     console.log(`copy-locales: ${readdirSync(DEST).join(", ")} -> site/public/locales/`);
19

```

21. user (2026-06-22T01:12:14.565Z)

```

1     {
2       "name": "khelsutra-site",
3       "private": true,
4       "type": "module",
5       "scripts": {
6         "test": "node --test",
7         "test:cf": "node --test src/index.test.js",
8         "test:vm": "node --test src/server.test.js",
9         "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10        "copy:locales": "node scripts/copy-locales.mjs",
11        "predeploy": "node scripts/copy-locales.mjs",
12        "deploy": "wrangler deploy",
13        "dev": "wrangler dev",
14        "og": "python make_og.py"
15      },
16      "devDependencies": {
17        "jsdom": "^29.1.1"
18      }
19    }
20

```

22. assistant (2026-06-22T01:14:00.071Z)

I now understand the patterns fully. Let me finish ramp-up: the web key-parity expectations (adding keys to en forces all 6 locales), server routing for own-model, and the screencast tooling in the sibling repo.

23. user (2026-06-22T01:14:02.484Z)

```

=== web hygiene test ===
web/src/i18n/hygiene.test.ts
=== server.test own-model? ===
site/src/server.test.js:65:test(["VM host] serves /own-model", async () => {
site/src/server.test.js:66:  const res = await fetch(`${base}/own-model`);
site/src/server.test.js:146:  const none = await fetch(`${base}/own-model`);
site/server.js:41:const LOCALIZED_PAGES = new Set(["index.html", "capture.html", "own-
model.html"]);
site/server.js:99:      : pathname === "/own-model" ? "own-model.html"
=== screencast repo ===
total 59097
drwxr-xr-x 1 avidu 197609      0 Jun 22 06:31 .
drwxr-xr-x 1 avidu 197609      0 Jun 22 06:37 ..
-rw-r--r-- 1 avidu 197609 411510 Jun 21 18:56 b-205.png
-rw-r--r-- 1 avidu 197609 484558 Jun 21 18:56 b-218.png
-rw-r--r-- 1 avidu 197609 490788 Jun 21 18:56 b-228.png
-rw-r--r-- 1 avidu 197609  75790 Jun 21 18:47 cuj-1-ingest.png
-rw-r--r-- 1 avidu 197609  77670 Jun 21 18:47 cuj-2-uri.png
-rw-r--r-- 1 avidu 197609  79594 Jun 21 18:47 cuj-3-processing.png
-rw-r--r-- 1 avidu 197609  76136 Jun 21 18:51 cuj-4-rallies.png
-rw-r--r-- 1 avidu 197609 266133 Jun 21 18:51 cuj-5-reel-ready.png
-rw-r--r-- 1 avidu 197609 50604038 Jun 21 18:51 cuj-downloaded-reel.mp4
-rw-r--r-- 1 avidu 197609   3359 Jun 21 18:38 cuj-screencast.mjs
-rw-r--r-- 1 avidu 197609   1942 Jun 22 04:04 deep-test.mjs
drwxr-xr-x 1 avidu 197609      0 Jun 22 04:05 eval-after

```

```

drwxr-xr-x 1 avidu 197609      0 Jun 22 03:51 eval-before
-rw-r--r-- 1 avidu 197609    1246 Jun 22 03:50 eval-shots.mjs
-rw-r--r-- 1 avidu 197609   471942 Jun 21 18:57 f-end.png
-rw-r--r-- 1 avidu 197609   377994 Jun 21 18:57 f-reveal.png
-rw-r--r-- 1 avidu 197609   495236 Jun 21 18:53 frame-ingest.png
-rw-r--r-- 1 avidu 197609   438734 Jun 21 18:53 frame-rallies.png
-rw-r--r-- 1 avidu 197609   401624 Jun 21 18:53 frame-reel.png
-rw-r--r-- 1 avidu 197609  1670821 Jun 21 18:57 khelsutra-bucket-cuj-screencast.mp4
-rw-r--r-- 1 avidu 197609   342162 Jun 21 12:45 khelsutra-i18n-screencast.mp4
-rw-r--r-- 1 avidu 197609   209551 Jun 22 06:31 khelsutra-site-header-mobile.mp4
-rw-r--r-- 1 avidu 197609   482771 Jun 22 06:31 khelsutra-site-i18n-desktop.mp4
drwxr-xr-x 1 avidu 197609      0 Jun 21 12:43 node_modules
-rw-r--r-- 1 avidu 197609    1714 Jun 21 12:43 package-lock.json
-rw-r--r-- 1 avidu 197609     309 Jun 21 12:43 package.json
-rw-r--r-- 1 avidu 197609   433109 Jun 21 18:54 raw-175.png
-rw-r--r-- 1 avidu 197609   435318 Jun 21 18:54 raw-188.png
-rw-r--r-- 1 avidu 197609   515252 Jun 21 18:54 raw-241.png
-rw-r--r-- 1 avidu 197609    2090 Jun 21 12:44 screencast.mjs
-rw-r--r-- 1 avidu 197609   123371 Jun 21 12:44 shot-1-kn.png
-rw-r--r-- 1 avidu 197609   833368 Jun 21 12:44 shot-2-hi.png
-rw-r--r-- 1 avidu 197609   623302 Jun 21 12:44 shot-3-en.png
-rw-r--r-- 1 avidu 197609    2180 Jun 22 06:30 site-screencast.mjs
-rw-r--r-- 1 avidu 197609   478995 Jun 21 18:56 v2-climax.png
-rw-r--r-- 1 avidu 197609   440965 Jun 21 18:56 v2-end.png
-rw-r--r-- 1 avidu 197609   374232 Jun 21 18:55 v2-reveal.png

```

24. user (2026-06-22T01:14:08.349Z)

```

1      // CI guardrails that keep i18n "by design" (FRIENDLY_AND_MULTILINGUAL.md §4):
2      //   1. KEY-PARITY ? every locale catalog has EXACTLY the `en` key set (the
extensibility proof:
3      //       drop a stub locale and this lists every gap). Trivially green while only `en`
exists; it
4      //       starts enforcing the moment a kn/hi catalog lands (B5/B6).
5      //   2. NO-BARE-STRINGS (attribute level, v1) ? user-facing component attributes
(placeholder /
6      //       aria-label / title) must route through t(), never a hardcoded literal. A curated
start per
7      //       the doc; an AST-level sweep of JSX text can extend it later.
8      import { describe, it, expect } from "vitest";
9      import { readdirSync, readFileSync } from "node:fs";
10     import { join } from "node:path";
11
12     // Catalogs are hoisted to repo-root /locales (D-CATALOG-HOME): web/src/i18n ->
../.../locales.
13     const LOCALES_DIR = join(import.meta.dirname, "..", "..", "..", "locales");
14     const SRC_DIR = join(import.meta.dirname, "..");
15
16     function flatten(obj: Record<string, unknown>, prefix = ""): string[] {
17         const keys: string[] = [];
18         for (const [k, v] of Object.entries(obj)) {
19             const key = prefix ? `${prefix}.${k}` : k;
20             if (v && typeof v === "object" && !Array.isArray(v)) keys.push(...flatten(v as
Record<string, unknown>, key));
21             else keys.push(key);
22         }
23         return keys.sort();
24     }
25
26     const loadKeys = (locale: string): string[] =>
27         flatten(JSON.parse(readFileSync(join(LOCALES_DIR, locale, "common.json"), "utf8")) as
Record<string, unknown>);
28
29     describe("i18n key-parity ? every locale has EXACTLY the en keys", () => {
30         const enKeys = loadKeys("en");

```

```

31     const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
32       .filter((d) => d.isDirectory() && d.name !== "en")
33       .map((d) => d.name);
34
35     it("en is the non-empty source catalog", () => {
36       expect(enKeys.length).toBeGreaterThan(20);
37     });
38
39     for (const loc of others) {
40       it(`${loc} matches en exactly (no missing, no extra keys)`, () => {
41         const keys = loadKeys(loc);
42         const missing = enKeys.filter((k) => !keys.includes(k));
43         const extra = keys.filter((k) => !enKeys.includes(k));
44         expect({ locale: loc, missing, extra }).toEqual({ locale: loc, missing: [], extra:
[] });
45       });
46     }
47   });
48
49   // Key-parity proves every locale has the same KEYS; this proves every locale's VALUE
keeps the same
50   // simple `{placeholder}` set as en ? so a translation can never silently drop a
{count}/{error}/{min}/
51   // {filename}/{n}/? and break interpolation. (ICU plural headers like `{count, plural,
?}` carry no
52   // simple {word} placeholder and match as empty on both sides, so they're correctly
ignored.)
53   describe("placeholder parity ? every locale preserves en's {placeholders}", () => {
54     function flatEntries(obj: Record<string, unknown>, prefix = ""): Record<string,
string> {
55       const out: Record<string, string> = {};
56       for (const [k, v] of Object.entries(obj)) {
57         const key = prefix ? `${prefix}.${k}` : k;
58         if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(out,
flatEntries(v as Record<string, unknown>, key));
59         else out[key] = String(v);
60       }
61       return out;
62     }
63     const placeholders = (s: string) => (s.match(/\{(\w+)\}/g) ?? []).sort();
64     const load = (loc: string) => flatEntries(JSON.parse(readFileSync(join(LOCALES_DIR,
loc, "common.json"), "utf8")));
65     const enE = load("en");
66     const others = readdirSync(LOCALES_DIR, { withFileTypes: true })
67       .filter((d) => d.isDirectory() && d.name !== "en")
68       .map((d) => d.name);
69
70     for (const loc of others) {
71       it(`${loc} preserves every {placeholder} that en uses`, () => {
72         const locE = load(loc);
73         const mismatches: Array<{ key: string; en: string[]; got: string[] }> = [];
74         for (const key of Object.keys(enE)) {
75           if (!(key in locE)) continue; // missing keys are the key-parity test's job
76           const a = placeholders(enE[key]);
77           const b = placeholders(locE[key]);
78           if (a.join(",") !== b.join(",")) mismatches.push({ key, en: a, got: b });
79         }
80         expect(mismatches).toEqual([]);
81       });
82     }
83   });
84
85   describe("es 3-form plural (CLDR one/many/other) ? MULTILINGUAL Phase A", () => {
86     // Spanish cardinal is {one, many, other}; every es ICU plural message MUST carry a
`many` arm

```

```

87      // (the `many` category fires on large/compact numbers) or intl-messageformat silently
88      // falls back.
89      // These are the plural-bearing keys in the catalog.
90      const es = JSON.parse(readFileSync(join(LOCALES_DIR, "es", "common.json"), "utf8")) as
Record<string, Record<string, string>>;
91      const pluralKeys: Array<[string, string]> = [
92        ["footer", "count"],
93        ["footer", "floorSomeLead"],
94        ["selection", "count"],
95      ];
96      for (const [ns, key] of pluralKeys) {
97        it(`es ${ns}.${key} carries one/many/other arms`, () => {
98          const msg = es[ns][key];
99          expect(msg, `${ns}.${key}`).toMatch(/\\bone\\s*\\{/);
100          expect(msg, `${ns}.${key}`).toMatch(/\\bmany\\s*\\{/);
101          expect(msg, `${ns}.${key}`).toMatch(/\\bother\\s*\\{/);
102        });
103      }
104    });
105    describe("no-bare-strings ? user-facing component attributes go through t()", () => {
106      const FILES = [
107        "App.tsx",
108        "components/QueryBar.tsx",
109        "components/TapFilters.tsx",
110        "components/RallyGrid.tsx",
111        "components/SelectionFooter.tsx",
112        "components/CompileResult.tsx",
113        "components/LanguageSwitcher.tsx",
114        "components/IngestPanel.tsx",
115      ];
116      // A hardcoded placeholder / aria-label / title with letters is a bare-string
117      regression ? it
118      // must be an expression ({t(...)}), not a quoted literal.
119      const BARE_ATTR = /\\b(?:placeholder|aria-label|title)\\s*=\\s*"\\^[^"]*[A-Za-z]{2}\\^[^"]*"\\/g;
120      for (const f of FILES) {
121        it(`${f}: no hardcoded placeholder/aria-label/title`, () => {
122          const src = readFileSync(join(SRC_DIR, f), "utf8");
123          expect(src.match(BARE_ATTR) ?? []).toEqual([]);
124        });
125      }
126    });
127  });
128  describe("Indic fonts (B4) ? self-hosted OFL Noto, no runtime CDN", () => {
129    it("main.tsx bundles the OFL Noto Kannada + Devanagari fonts (self-hosted, not Google
Fonts)", () => {
130      const main = readFileSync(join(SRC_DIR, "main.tsx"), "utf8");
131      expect(main).toMatch(/@fontsource-variable\\n\\noto-sans-kannada\\/);
132      expect(main).toMatch(/@fontsource-variable\\n\\noto-sans-devanagari\\/);
133    });
134    it("the font stack falls back to Noto for Kannada + Devanagari glyphs", () => {
135      const css = readFileSync(join(SRC_DIR, "index.css"), "utf8");
136      expect(css).toMatch(/Noto Sans Kannada Variable\\/);
137      expect(css).toMatch(/Noto Sans Devanagari Variable\\/);
138    });
139  });
140
141  // The Studio SPA must render correctly on an AIR-GAPPED appliance (GPU/CPU/RAM, no
internet) ?
142  // every asset (fonts, styles, scripts) is bundled local, nothing pulled from a
CDN/Google Fonts.
143  describe("offline / self-contained ? no external runtime assets", () => {
144    const CDN = /googleapis|gstatic|fonts\\.google|cdnjs|unpkg|jsdelivr|\\bcdn\\.\\[a-z]\\/i;
145    const FILES = [

```

```

146     "../index.html", // web/index.html
147     "main.tsx",
148     "index.css",
149 ];
150 for (const rel of FILES) {
151     it(`${rel}: no external font/CDN reference`, () => {
152         expect(readFileSync(join(SRC_DIR, rel), "utf8")).not.toMatch(CDN);
153     });
154 }
155 it("web/index.html loads no absolute-URL <link>/<script src> (everything is
bundled/local)", () => {
156     const html = readFileSync(join(SRC_DIR, "..", "index.html"), "utf8");
157     expect(html).not.toMatch(/(?:href|src)\s*=\s*["']https?:\/\//i);
158 });
159 });
160

```

25. user (2026-06-22T01:14:08.823Z)

```

1     // Records two screencasts of the localized + decluttered marketing site:
2     //   1) desktop multilingual journey: home (en) -> compact switcher -> Kannada home ->
capture page
3     //   2) mobile header: the clean compact switcher reflowing en -> kn -> hi (no overflow)
4     // Run against the site server (URL env). Outputs .webm into ./ (Playwright records webm
natively).
5     import { chromium } from "playwright";
6     import { rename } from "node:fs/promises";
7     import { mkdirSync } from "node:fs";
8
9     const URL = process.env.URL || "http://localhost:8123";
10    const HOLD = 1600;
11    mkdirSync("rec", { recursive: true });
12    const browser = await chromium.launch();
13
14    async function record(name, viewport, steps) {
15        const ctx = await browser.newContext({ viewport, locale: "en-US", recordVideo: { dir:
"rec", size: viewport } });
16        const page = await ctx.newPage();
17        await steps(page);
18        const v = page.video();
19        await ctx.close(); // flush the video
20        await rename(await v.path(), name);
21        console.log("wrote", name);
22    }
23
24    // 1) Desktop: en home -> switch to Kannada -> recording gist -> capture page (kn
persists)
25    await record("khelsutra-site-i18n-desktop.webm", { width: 1280, height: 800 }, async
(page) => {
26        await page.goto(URL + "/", { waitUntil: "domcontentloaded" });
27        await page.waitForTimeout(HOLD);
28        await page.selectOption("select[data-langsw]", "kn");
29        await page.waitForTimeout(HOLD);
30        await page.locator("#record").scrollIntoViewIfNeeded();
31        await page.waitForTimeout(HOLD);
32        await page.goto(URL + "/capture", { waitUntil: "domcontentloaded" });
33        await page.waitForTimeout(HOLD);
34        await page.locator(".diagram").scrollIntoViewIfNeeded();
35        await page.waitForTimeout(HOLD);
36    });
37
38    // 2) Mobile: the compact header switching en -> kn -> hi, never overflowing
39    await record("khelsutra-site-header-mobile.webm", { width: 390, height: 844 }, async
(page) => {
40        await page.goto(URL + "/", { waitUntil: "domcontentloaded" });

```



```

41     await page.waitForTimeout(HOLD);
42     await page.selectOption("select[data-langsw]", "kn");
43     await page.waitForTimeout(HOLD);
44     await page.selectOption("select[data-langsw]", "hi");
45     await page.waitForTimeout(HOLD);
46   });
47
48   await browser.close();
49   console.log("DONE");
50

```

26. user (2026-06-22T01:14:09.299Z)

```

1    {
2      "name": "khelesutra-screencast",
3      "version": "1.0.0",
4      "description": "",
5      "main": "index.js",
6      "scripts": {
7        "test": "echo \"Error: no test specified\" && exit 1"
8      },
9      "keywords": [],
10     "author": "",
11     "license": "ISC",
12     "type": "commonjs",
13     "dependencies": {
14       "playwright": "^1.61.0"
15     }
16   }
17

```

27. user (2026-06-22T01:14:10.129Z)

```

55     assert.equal((await fetch(`${base}/capture`)).status, 200);
56     assert.equal((await fetch(`${base}/og.png`)).status, 200);
57   });
58
59   test("[VM host] serves the tool screencast as video/mp4 (plays in the post-signup
reveal)", async () => {
60     const res = await fetch(`${base}/video/tool-cuj.mp4`);
61     assert.equal(res.status, 200);
62     assert.equal(res.headers.get("content-type"), "video/mp4"); // not octet-stream ?
<video> can play it
63   });
64
65   test("[VM host] serves /own-model", async () => {
66     const res = await fetch(`${base}/own-model`);
67     assert.equal(res.status, 200);
68     assert.match(await res.text(), /Train a model that's yours/);
69   });
70
71   test("[VM host] serves the academy flyers (/flyer, /flyer-kn, /flyer-hi) as clean URLs",
async () => {
72     // Cloudflare maps these via asset html-handling; the VM host needs explicit routes so
the
73     // footer links work on BOTH hosts (parity).
74     for (const path of ["/flyer", "/flyer-kn", "/flyer-hi"]) {
75       const res = await fetch(`${base}${path}`);
76       assert.equal(res.status, 200, `${path} should serve 200 on the VM host`);
77       assert.match(res.headers.get("content-type"), /text\/html/, `${path} should serve
HTML`);
78       assert.match(await res.text(), /<html/i, `${path} should be an HTML page`);
79     }
80   });
81

```

```

82     test("[VM host] POST /api/request-access persists to SQLite", async () => {
83         const res = await fetch(`${base}/api/request-access`, {
84             method: "POST",
85             headers: { "content-type": "application/json" },
86             body: JSON.stringify({ segment: "academy", email: "harness@khelsutra.guru", has_gpu:
"yes", storage: ["gdrive", "bucket"], consent: true }),
87         });
88         assert.equal(res.status, 200);
89         assert.deepEqual(await res.json(), { ok: true });
90
91         const db = new DatabaseSync(dbPath);
92         const row = db.prepare("SELECT email, segment, has_gpu, storage, consent FROM
access_requests").get();
93         assert.equal(row.email, "harness@khelsutra.guru");
94         assert.equal(row.segment, "academy");
95         assert.equal(row.has_gpu, "yes");
96         assert.equal(row.storage, "gdrive,bucket");
97         assert.equal(row.consent, 1);
98     });
99
100    test("[VM host] honeypot + bad email are rejected without persisting", async () => {
101        const bot = await fetch(`${base}/api/request-access`, {
102            method: "POST", headers: { "content-type": "application/json" },
103            body: JSON.stringify({ email: "x@y.co", company: "spam" }),
104        });
105        assert.equal(bot.status, 200); // dropped silently
106        const bad = await fetch(`${base}/api/request-access`, {
107            method: "POST", headers: { "content-type": "application/json" },
108            body: JSON.stringify({ email: "nope" }),
109        });
110        assert.equal(bad.status, 400);
111
112        const db = new DatabaseSync(dbPath);
113        const { n } = db.prepare("SELECT COUNT(*) AS n FROM access_requests").get();
114        assert.equal(n, 1); // only the valid submission above
115    });
116
117    test("[VM host] GET /api/request-access -> 405", async () => {
118        assert.equal((await fetch(`${base}/api/request-access`)).status, 405);
119    });
120
121    // --- $6.5 N8: static-site language negotiation (same order as the SPA)
    -----
122    test("[VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page",
async () => {
123        const res = await fetch(`${base}/`, { headers: { "accept-language": "kn-
IN,kn;q=0.9,en;q=0.5" } });
124        const html = await res.text();
125        assert.match(html, /<html lang="kn"/, "a kn browser must auto-get <html
lang=\"kn\">");
126        assert.equal(res.headers.get("content-language"), "kn");
127        assert.match(res.headers.get("vary") || "", /accept-language/i, "must Vary on Accept-
Language for caches");
128        // The negotiated page still ships the client shim + switcher so the browser can
refine from here.
129        assert.match(html, /src="\i18n\.js"/, "the negotiated page must still load the client
shim");
130        assert.match(html, /<select data-langsw|<option value="kn"/, "the switcher must be
present on the negotiated page");
131    });
132
133    test("[VM host · N8] ?lang= overrides the browser language", async () => {
134        const res = await fetch(`${base}/?lang=hi`, { headers: { "accept-language": "en-US" }
});
135        assert.match(await res.text(), /<html lang="hi"/, "?lang=hi must win over an en

```

```

Accept-Language");
136     });
137
138     test("[VM host · N8] the persisted cookie beats Accept-Language (returning user keeps
their choice)", async () => {
139         const res = await fetch(`${base}/capture`, { headers: { "accept-language": "kn",
cookie: "khelsutra.lang=hi" } });
140         assert.match(await res.text(), /<html lang="hi"/, "the persisted-pref cookie must win
over Accept-Language");
141     });
142
143     test("[VM host · N8] unsupported/absent language falls back to en (never a locale we
can't serve)", async () => {
144         const ta = await fetch(`${base}/?lang=ta`, { headers: { "accept-language": "ta-IN" }
});
145         assert.match(await ta.text(), /<html lang="en"/, "Tamil (unsupported) must fall back
to en");
146         const none = await fetch(`${base}/own-model`);
147         assert.match(await none.text(), /<html lang="en"/, "no signal -> en default");
148     });
149
150     test("[VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages
negotiate)", async () => {
151         // The flyers are fixed-language pages ? negotiation must not touch them.
152         const res = await fetch(`${base}/flyer-kn`, { headers: { "accept-language": "hi" } });
153         assert.match(await res.text(), /<html lang="kn"/, "the Kannada flyer must stay kn
regardless of Accept-Language");
154     });

```

28. assistant (2026-06-22T01:14:41.296Z)

Let me read server.js to confirm the lang-rewrite mechanism (so my edits keep negotiation working), and check the toolchain.

29. user (2026-06-22T01:14:42.251Z)

```

1      // Always-on VM host for the KhelSutra site ? dependency-free (Node 22+ only).
2      // Serves public/ and POST /api/request-access into SQLite (node:sqlite), using the
3      // SAME handler logic as the Cloudflare Worker (src/index.js). This is the portability
4      // fallback "if Cloudflare acts out" ? see docs/PORTABILITY.md.
5      //
6      //   PORT=8080 DB_PATH=/var/lib/khelsutra/access.db node server.js
7      //
8      import { createServer } from "node:http";
9      import { readFile } from "node:fs/promises";
10     import { join, extname, normalize } from "node:path";
11     import { DatabaseSync } from "node:sqlite";
12     import { handleRequest } from "./src/index.js";
13     import { sqliteStore } from "./src/store.js";
14     import { noopNotify } from "./src/notify.js";
15
16     const PORT = Number(process.env.PORT) || 8080;
17     const ROOT = import.meta.dirname;
18     const PUBLIC = join(ROOT, "public");
19     const DB_PATH = process.env.DB_PATH || join(ROOT, "access.db");
20
21     const db = new DatabaseSync(DB_PATH);
22     db.exec(await readFile(join(ROOT, "schema.sql"), "utf8")); // CREATE TABLE IF NOT EXISTS
? idempotent
23     const store = sqliteStore(db);
24     const notify = noopNotify(); // VM host: no email yet (add SMTP later ? see
docs/PORTABILITY.md)
25
26     const TYPES = {
27         ".html": "text/html; charset=utf-8", ".png": "image/png", ".svg": "image/svg+xml",

```

```

28     ".css": "text/css", ".js": "text/javascript", ".json": "application/json;
charset=utf-8",
29     ".ico": "image/x-icon", ".txt": "text/plain",
30     ".mp4": "video/mp4", ".webm": "video/webm", ".gif": "image/gif", ".jpg": "image/jpeg",
".jpeg": "image/jpeg",
31     };
32
33     // --- Language negotiation (tracker B3 / S6.5 N8)
-----
34     // The trilingual marketing site. The client shim (public/i18n.js) does the full
negotiation in the
35     // browser; this VM host PRE-RESOLVES the locale server-side so the first paint (and any
no-JS read)
36     // already carries the right <html lang>. Same ORDER as the SPA + shim: persisted pref
-> ?lang= ->
37     // navigator/Accept-Language -> en. (On Cloudflare, assets are served directly and only
the client
38     // shim negotiates ? see src/index.js.)
39     const SITE_LOCALES = ["en", "kn", "hi"];
40     const LANG_COOKIE = "khelsutra.lang";
41     const LOCALIZED_PAGES = new Set(["index.html", "capture.html", "own-model.html"]);
42
43     const baseLang = (code) => (code ?
String(code).toLowerCase().split(";")[0].trim().split("-")[0] : "");
44
45     function cookieValue(header, name) {
46         const m = (header || "").match(new RegExp("(?:^|;\\s*)" + name.replace(/\./g, "\\.") +
"=([^\s;]*)"));
47         return m ? decodeURIComponent(m[1]) : null;
48     }
49
50     function parseAcceptLanguage(header) {
51         return (header || "")
52             .split(",")
53             .map((part) => {
54                 const [tag, ...params] = part.trim().split(";");
55                 const q = params.map((p) => p.trim()).find((p) => p.startsWith("q="));
56                 return { tag, q: q ? Number(q.slice(2)) : 1 };
57             })
58             .filter((x) => x.tag)
59             .sort((a, b) => b.q - a.q)
60             .map((x) => x.tag);
61     }
62
63     // persisted (cookie) -> ?lang= -> Accept-Language -> en. Anything unsupported is
skipped.
64     function negotiateLang(req, searchParams) {
65         const candidates = [
66             cookieValue(req.headers.cookie, LANG_COOKIE),
67             searchParams.get("lang"),
68             ...parseAcceptLanguage(req.headers["accept-language"]),
69         ];
70         for (const c of candidates) {
71             const b = baseLang(c);
72             if (b && SITE_LOCALES.includes(b)) return b;
73         }
74         return "en";
75     }
76
77     const setHtmlLang = (html, lang) => html.replace(/<html lang="[^"]*" /i, `<html
lang="${lang}"`);
78
79     async function toRequest(req) {
80         const url = `http://${req.headers.host || "localhost"}${req.url}`;
81         let body;

```

```

82     if (req.method !== "GET" && req.method !== "HEAD") {
83         const chunks = [];
84         for await (const c of req) chunks.push(c);
85         body = Buffer.concat(chunks);
86     }
87     return new Request(url, { method: req.method, headers: req.headers, body });
88 }
89
90 async function send(res, response) {
91     res.statusCode = response.status;
92     for (const [k, v] of response.headers) res.setHeader(k, v);
93     res.end(Buffer.from(await response.arrayBuffer()));
94 }
95
96 async function serveStatic(pathname, req, searchParams, res) {
97     const rel = pathname === "/" ? "index.html"
98       : pathname === "/capture" ? "capture.html"
99       : pathname === "/own-model" ? "own-model.html"
100       : pathname === "/flyer" ? "flyer.html"
101       : pathname === "/flyer-kn" ? "flyer-kn.html"
102       : pathname === "/flyer-hi" ? "flyer-hi.html"
103       : pathname.replace(/^\/+/, "");
104     const file = normalize(join(PUBLIC, rel));
105     if (!file.startsWith(PUBLIC)) { res.statusCode = 403; return res.end("forbidden"); }
106     try {
107         let data = await readFile(file);
108         res.setHeader("content-type", TYPES[extname(file)] || "application/octet-stream");
109         if (LOCALIZED_PAGES.has(rel)) {
110             // Pre-resolve the locale and stamp <html lang> so the first paint is correct (the
client shim
111             // refines it). Vary on Accept-Language so a shared cache keeps per-language
copies distinct.
112             const lang = negotiateLang(req, searchParams);
113             if (lang !== "en") data = Buffer.from(setHtmlLang(data.toString("utf8"), lang),
"utf8");
114             res.setHeader("content-language", lang);
115             res.setHeader("vary", "Accept-Language");
116         }
117         res.end(data);
118     } catch {
119         res.statusCode = 404;
120         res.end("not found");
121     }
122 }
123
124 createServer(async (req, res) => {
125     try {
126         const parsed = new URL(`http://${req.url}`);
127         const pathname = decodeURIComponent(parsed.pathname);
128         if (pathname === "/api/request-access") {
129             if (req.method !== "POST") { res.statusCode = 405; return
res.end('{"ok":false,"error":"method not allowed"}'); }
130             return await send(res, await handleRequest(await toRequest(req), store, notify));
131         }
132         return await serveStatic(pathname, req, parsed.searchParams, res);
133     } catch (err) {
134         res.statusCode = 500;
135         res.end('{"ok":false,"error":"server error"}');
136         console.error(err);
137     }
138 }).listen(PORT, () => console.log(`khelsutra site listening on :${PORT} (sqlite:
${DB_PATH})`));
139

```

```
v26.1.0
11.13.0
git version 2.45.2.windows.1
--- existing node_modules? ---
site/node_modules
web/node_modules
--- worktrees ---
C:/Users/avidu/Projects/khelsutra 5e5a2ac [master]
```

31. assistant (2026-06-22T01:15:17.604Z)

server.js only rewrites ``<html lang>`` (content translation is client-side via the shim) ? my edits keep the English DOM defaults and ``/i18n.js``, so negotiation and the ``/Train a model that's yours/`` server test keep passing. Toolchain is good.

Let me mark the chapter and set up the isolated worktree off ``origin/master`` (per the concurrency convention).

32. user (2026-06-22T01:15:19.030Z)

Chapter marked: "own-model kn/hi localization". Continue your current work.

33. user (2026-06-22T01:17:10.263Z)

```
--- origin/master vs HEAD ---
5e5a2ac21866136cabf5e904d5c0cfa4c6f3bc79
5e5a2ac21866136cabf5e904d5c0cfa4c6f3bc79
--- web node_modules size ---
132M    web/node_modules
25M     site/node_modules
```

34. assistant (2026-06-22T01:17:14.791Z)

`origin/master == HEAD (5e5a2ac)`, clean base. Let me create the isolated worktree and seed it with the (commit-identical) `node_modules` so I can run the full test suites locally.

35. user (2026-06-22T01:17:17.698Z)

```
Preparing worktree (new branch 'feat/own-model-kn-hi')
branch 'feat/own-model-kn-hi' set up to track 'origin/master'.
HEAD is now at 5e5a2ac docs(friendly-multilingual): close out the chapter (§9 DoD + UI/UX + B7 deferred) (#84)
--- worktree branch/head ---
fatal: cannot change to 'khelsutra-ownmodel-i18n': No such file or directory
fatal: cannot change to 'khelsutra-ownmodel-i18n': No such file or directory
fatal: cannot change to 'khelsutra-ownmodel-i18n': No such file or directory
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

36. user (2026-06-22T01:17:25.739Z)

```
--- worktree exists? ---
ls: cannot access '/c/Users/avidu/Projects/khelsutra-ownmodel-i18n': No such file or directory
fatal: cannot change to 'C:/Users/avidu/Projects/khelsutra-ownmodel-i18n': No such file or directory
fatal: cannot change to 'C:/Users/avidu/Projects/khelsutra-ownmodel-i18n': No such file or directory
--- verify branch rides ONLY on origin/master (no sibling commits) ---
fatal: cannot change to 'C:/Users/avidu/Projects/khelsutra-ownmodel-i18n': No such file or directory
--- worktree list ---
C:/Users/avidu/Projects/khelsutra          5e5a2ac [deploy/kit-live-verified]
C:/Users/avidu/Projects/khelsutra/khelsutra-ownmodel-i18n 5e5a2ac [feat/own-model-kn-hi]
```

37. assistant (2026-06-22T01:17:37.553Z)

Two important observations: (1) the worktree got created **inside** the repo (relative-path resolution), and (2) the main checkout has been switched to `deploy/kit-live-verified` by a concurrent session ? exactly the shared-checkout churn the convention warns about. My isolation is the right call. Let me move the worktree out to a clean sibling path.

38. user (2026-06-22T01:17:40.694Z)

```
Preparing worktree (checking out 'feat/own-model-kn-hi')
HEAD is now at 5e5a2ac docs(friendly-multilingual): close out the chapter ($9 DoD + UI/UX + B7 deferred) (#84)
--- list ---
C:/Users/avidu/Projects/khelsutra          5e5a2ac [deploy/kit-live-verified]
C:/Users/avidu/Projects/ks-ownmodel-i18n  5e5a2ac [feat/own-model-kn-hi]
```

39. assistant (2026-06-22T01:17:49.022Z)

Worktree is clean at `ks-ownmodel-i18n`, riding only on origin/master. Let me copy the (commit-identical) node_modules into it in the background while I start the implementation.

40. user (2026-06-22T01:17:52.760Z)

Command running in background with ID: bwzffufrrp. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bwzffufrrp.output. You will be notified when it completes. To check interim output, use Read on that file path.

41. assistant (2026-06-22T01:18:58.368Z)

Worktree ready. Now let me design the wiring. I'll read the worktree's own-model.html (to satisfy the edit precondition and confirm it's identical), then rewrite it with full `data-i18n`/'data-i18n-html` wiring ? keeping every English DOM default exactly intact (so server tests and no-JS reads are unaffected), leaving `

```
` code blocks and ``/meta literal (consistent with A3).</p></div><div data-bbox="64 525 320 540" data-label="Section-Header"><h3>42. user (2026-06-22T01:19:02.244Z)</h3></div><div data-bbox="64 555 823 942" data-label="Text"><pre>78     <body>
79     <script type="module" src="/i18n.js"></script>
80     <div class="sheet">
81         <div class="head">
82             <div class="top">
83                 <a class="brand" href="/">Khel<span class="play" aria-
84 hidden="true"></span>Sutra</a>
85                 <div class="nav-right">
86                     <label class="langsw"><span class="langsw-globe" aria-
87 hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
88 data-i18n-attr="aria-label">
89                         <option value="en" data-i18n="lang.en" lang="en">English</option>
90                         <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
91                         <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
92                     </select></label>
93                     <a href="/#join" style="color:#C7F2B0;font-weight:600;text-decoration:none"
94 data-i18n="site.ownModel.requestAccess">Request access ?</a>
95                 </div>
96             </div>
97             <h1>Annotate your footage. <span class="hl">Train a model that's yours.</span></h1>
98             <p>You can't train Gemini or GPT on your court footage. KhelSutra's direction is the
inverse ? a small, <b style="color:#EAF3EE">owned</b> rally model where the moat is your
consented dataset, on a commercially-clean, inspectable stack you control.</p>
99             <div class="nav"><a href="/">? KhelSutra home</a><a href="#annotate">Annotate</a><a
href="#train">Train your own model</a><a href="#setup">Setup &amp; use</a></div>
100         </div>
101     </div></pre></div>
```

99

100 `<p class="sample">? <b>Want to see what KhelSutra produces?</b> A real sample reel`
101 `plays the moment you <a href="/#join">request access</a>.</p>`

102

`<section class="sec" id="annotate">`

103 `<div class="kick">Step 1 · real and shipping today</div>`

104 `<h2>Annotate your footage <span class="pill live">live today</span></h2>`

105 `<p><b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b> that`
turns "watch a match" into golden labels. While you watch your own video in VLC, you mark each
rally's start and end plus how the point ended; it writes one row per rally to a plain CSV next
to your video. `<b>Your footage never leaves your machine.</b> It covers five net-separated`
racquet sports (badminton, tennis, table tennis, pickleball, padel).`</p>`

106 `<a class="ghbtn" href="https://github.com/Khelsutra/rally-annotator"><svg`
width="16" height="16" viewBox="0 0 16 16" fill="currentColor" aria-hidden="true"><path d="M8
0C3.58 0 0 3.58 0 8a8 8 0 0 0 5.47 7.59c.4.07.55-.17.55-.38 0-.19-.01-.82-.01-1.49-2.01.37-2.53-
.49-2.69-.94-.09-.23-.48-.94-.82-1.13-.28-.15-.68-.52-.01-.53.63-.01 1.08.58 1.23.82.72 1.21
1.87.87 2.33.66.07-.52.28-.87.51-1.07-1.78-.2-3.64-.89-3.64-3.95
0-.87.31-1.59.82-2.15-.08-.2-.36-1.02.08-2.12 0 0 .67-.21 2.2.82a7.4 7.4 0 0 1 2-.27c.68 0
1.36.09 2 .27 1.53-1.04 2.2-.82 2.2-.82.44 1.1.16 1.92.08 2.12.51.56.82 1.27.82 2.15 0 3.07-1.87
3.75-3.65 3.95.29.25.54.73.54 1.48 0 1.07-.01 1.93-.01 2.2 0 .21.15.46.55.38A8 8 0 0 0 16
8c0-4.42-3.58-8-8-8Z"/></svg> github.com/Khelsutra/rally-annotator

107 `<div class="shots">`

108 `<figure><figcaption>Enable it once: VLC ? View ? Rally
Annotator.</figcaption></figure>

109 `<figure><figcaption>Mark each rally's
start/end + ending reason, then Save Rally.</figcaption></figure>

110 `</div>`

111 `<p style="margin-top:1rem"><b>The flow, per rally:</b></p>`

112 `<ol>`

113 `<li><b>Mark START</b> on the serve-contact frame (pause/scrub for`
accuracy).

114 `<li><b>Mark END</b> when the shuttle is dead.</li>`

115 `<li>Pick an <b>ending reason</b>, optionally a shot count, then <b>Save`
Rally ? one CSV row.

116 `<li>Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video later`
to continue.

117 `</ol>`

118 `<p style="font-size:.9rem;color:var(--mut)">It's a click-driven dialog (no marking`
hotkeys yet), and targets VLC 3.0.x.</p>

119 `</section>`

120

`<section class="sec" id="train">`

122 `<div class="kick">Step 2 · the moat</div>`

123 `<h2>Train your own model <span class="pill build">open pipeline · in`
build</h2>

124 `<div class="honest" style="border-left-`
color:var(--green);background:#EAF6EF;border-color:#BfE6D2">

125 `<span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">?</span>`

126 `<div>`

127 `<b>You don't have to train anything to start.</b>`

128 `<p>KhelSutra runs on a ready-made default, so you get rally detection and`
reels out of the box ? nothing to set up. Training on your own footage (below) is an
optional power-up: a model tuned to your courts, your angles, your halls.</p>

129 `</div>`

130 `</div>`

131 `<p>For those who want it, your labels feed an <b>owned</b> rally model ? trained`
on your courts, your angles, your busy multi-court halls. The pipeline is
open and inspectable:</p>

132 `<pre><code>annotate (VLC) ? <video>;rallies.csv ? worker train ? your`
model bundle (weights + a reviewable manifest)</code></pre>

133 `<div class="moat">`

134 `<div><h4>You own it</h4><p>A model and dataset that are yours to keep and`
improve ? not rented inference.</p></div>


```

135         <div><h4>Commercially clean</h4><p>MIT/Apache/BSD-only stack; we never train on
a paid LLM's output.</p></div>
136         <div><h4>Private & consented</h4><p>Footage stays yours; training use is
explicit opt-in, never automatic.</p></div>
137         <div><h4>Minors protected</h4><p>Footage involving minors is never used for
training and never published.</p></div>
138     </div>
139     <div class="honest">
140         <span aria-hidden="true" style="color:var(--green-d);font-size:1.2rem">!</span>
141         <div>
142             <b>Read this honestly.</b>
143             <p>The labeling tool is real and shipping. The training pipeline is <b>open
and in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-
validation <b>mock</b>, and a real model needs a GPU. There is <b>no "Train now" button</b> yet,
and we make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise here
is <b>ownership, licensing, privacy and consent</b> ? not "more accurate than Gemini," and not
"one click to train."</p>
144         </div>
145     </div>
146 </section>
147
148 <section class="sec" id="setup">
149     <div class="kick">Step 3 · for power users</div>
150     <h2>Setup & use</h2>
151     <p><b>Install the plugin (VLC 3.0.x).</b> Copy <code>rally_annotator.lua</code>
into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools
? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally
Annotator</i>:</p>
152     <pre><code>Windows: %APPDATA%\vlc\lua\extensions\
153     macOS:  ~/Library/Application Support/org.videolan.vlc/lua/extensions/
154     Linux:   ~/.local/share/vlc/lua/extensions/</code></pre>
155     <p style="margin-top:1rem"><b>Record</b> per the <a href="/capture">one-page
capture checklist</a> (fixed tripod, full court, landscape, whole session) ? <b>annotate</b> in
VLC ? you get <code>&lt;video&gt;.rallies.csv</code>:</p>
156     <pre><code>rally_number,start_time,end_time,ending_reason,sport,shots_count
157     1,8.800,11.500,winner,badminton,9
158     2,24.389,46.589,unforced_error,badminton,21
159     3,49.183,54.683,let,badminton,</code></pre>
160     <p style="margin-top:.6rem;font-
size:.9rem;color:var(--mut)"><code>ending_reason</code> is one of: <code>unknown</code> ·
<code>winner</code> · <code>forced_error</code> · <code>unforced_error</code> ·
<code>service_fault</code> · <code>let</code> · <code>other</code>. Times are decimal seconds;
downstream tools read by column name.</p>
161     <p style="margin-top:1rem"><b>Train</b> (developer CLI). A GPU-free dry run
validates the whole pipeline on a CPU mock; a real model needs a GPU:</p>
162     <pre><code># GPU-free dry run (CPU mock ? pipeline validation only):
163     python -m backend.worker train --corpus-uri &lt;bucket&gt; --out-uri &lt;bucket&gt;
--version 0.1.0
164
165     # real trajectories (needs a GPU + the native WASB runner, in build):
166     python -m backend.worker train ... --trajectory-source detector --segmenter
wasb_hybrid</code></pre>
167     <p style="margin-top:.6rem;font-size:.9rem;color:var(--mut)">One join rule: keep
the video <b>byte-identical</b> to what you annotated (don't re-encode after labeling) ? labels
match videos by content hash.</p>
168 </section>
169
170 <section class="sec">
171     <div class="kick">So expectations stay honest</div>
172     <h2>What this is not</h2>
173     <ul class="nots">
174         <li>Not a one-click trainer ? training is an offline CLI today.</li>
175         <li>Not in-browser ? labeling runs in VLC on your machine.</li>
176         <li>Not an accuracy claim vs Gemini/GPT ? no such benchmark.</li>
177         <li>Shot-type, player and score detection are roadmap.</li>

```

```

178         </ul>
179     </section>
180
181     <div class="cta">
182         <b>Want in?</b>
183         <div><a href="/#join">Request alpha access</a></div>
184     </div>
185
186 </div>
187 <div class="foot">
188     <span><a href="/">khelsutra.guru</a> · <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> · Academy flyer: <a href="/flyer" hreflang="en">English</a>
· <a href="/flyer-kn" hreflang="kn" lang="kn">?????</a> · <a href="/flyer-hi" hreflang="hi"
lang="hi">??????</a></span>
189     <span>Reels carry a "Generated by Khelsutra.guru" mark.</span>
190 </div>
191 </div>
192 </body>
193 </html>

```

43. assistant (2026-06-22T01:19:10.831Z)

The robocopy "failure" is likely a false alarm ? robocopy returns exit code 1 on *successful* copies (0 = nothing copied). Let me verify the actual result.

44. user (2026-06-22T01:20:37.170Z)

```

jsdom: /c/Users/avidu/Projects/ks-ownmodel-i18n/site/node_modules/jsdom
OK
vite: /c/Users/avidu/Projects/ks-ownmodel-i18n/web/node_modules/vitest
OK
25M    /c/Users/avidu/Projects/ks-ownmodel-i18n/site/node_modules
132M   /c/Users/avidu/Projects/ks-ownmodel-i18n/web/node_modules

```

45. assistant (2026-06-22T01:21:24.684Z)

Both `node\_modules` copied fully. Now I'll wire the entire body of own-model.html in one precise edit ? adding `data-i18n`/`data-i18n-html` while keeping every English DOM default byte-identical, wrapping title+pill headings in spans, and leaving `

```
` blocks, the GitHub URL, autonym flyer links, and `` meta literal (A3 scope).
```

46. user (2026-06-22T01:21:34.715Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

47. user (2026-06-22T01:21:47.304Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

48. assistant (2026-06-22T01:21:49.853Z)

Now the #train section:

49. user (2026-06-22T01:22:08.725Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

50. assistant (2026-06-22T01:22:11.672Z)

Now the #setup section (prose paragraphs wired, `

```
` left literal):
```

51. user (2026-06-22T01:22:15.970Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

52. user (2026-06-22T01:22:22.011Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

53. user (2026-06-22T01:22:29.873Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

54. assistant (2026-06-22T01:22:33.320Z)

Now the join-rule note, "What this is not" section, CTA, and footer:

55. user (2026-06-22T01:22:45.329Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

56. assistant (2026-06-22T01:22:53.601Z)

All wiring is in place. Now I'll author the en catalog values by **extracting them from the wired HTML with jsdom** ? this guarantees the byte-for-byte drift test passes (no hand-copy drift). Let me write a one-off extraction script in the worktree.

57. assistant (2026-06-22T01:23:00.968Z)

```
// One-off authoring helper (NOT shipped): extract the en catalog values for the own-model page
// straight from the wired HTML so they match the drift guard byte-for-byte. Walks every
// data-i18n[-html] node under site.ownModel.* and prints the nested object as JSON.
import { readFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const html = readFileSync(join(import.meta.dirname, "..", "public", "own-model.html"), "utf8");
const { document } = new JSDOM(html).window;

const out = {};
const setDeep = (obj, path, val) => {
  const parts = path.split(".");
  let o = obj;
  for (let i = 0; i < parts.length - 1; i++) o = o[parts[i] ??= {}] ?? (o[parts[i]] = {});
  // rebuild because ??= above is wrong for nested ? do it explicitly:
};
function put(root, dotted, value) {
  const parts = dotted.split(".");
  let o = root;
  for (let i = 0; i < parts.length - 1; i++) {
    o[parts[i]] = o[parts[i]] || {};
    o = o[parts[i]];
  }
  o[parts[parts.length - 1]] = value;
}

let n = 0;
for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
  if (el.getAttribute("data-i18n-attr")) continue; // attribute defaults aren't the visible text
  const htmlKey = el.getAttribute("data-i18n-html");
  const key = htmlKey || el.getAttribute("data-i18n");
```

```

    if (!key.startsWith("site.ownModel.")) continue;
    const value = (htmlKey ? el.innerHTML : el.textContent).trim();
    put(out, key, value);
    n++;
}
console.error(`extracted ${n} site.ownModel.* keys`);
process.stdout.write(JSON.stringify(out.site.ownModel, null, 2) + "\n");

```

58. user (2026-06-22T01:23:00.996Z)

File created successfully at: C:\Users\avidu\Projects\ks-ownmodel-i18n\site\scripts\extract-ownmodel.mjs (file state is current in your context ? no need to Read it back)

59. user (2026-06-22T01:23:06.241Z)

```

extracted 53 site.ownModel.* keys
EXIT:0

```

```

{
  "requestAccess": "Request access ?",
  "heroTitle": "Annotate your footage. <span class=\\"hl\\">Train a model that's yours.</span>",
  "heroLead": "You can't train Gemini or GPT on your court footage. KhelSutra's direction is the inverse ? a small, <b style=\\"color:#EAF3EE\\">owned</b> rally model where the moat is your consented dataset, on a commercially-clean, inspectable stack you control.",
  "nav": {
    "home": "? KhelSutra home",
    "annotate": "Annotate",
    "train": "Train your own model",
    "setup": "Setup & use"
  },
  "sample": "? <b>Want to see what KhelSutra produces?</b> A real sample reel plays the moment you <a href=\\"/#join\\">request access</a>.",
  "annotate": {
    "kicker": "Step 1 · real and shipping today",
    "title": "Annotate your footage",
    "pill": "live today",
    "body": "<b>rally-annotator</b> is a free, open-source (MIT) <b>VLC plugin</b> that turns \\\"watch a match\\\" into golden labels. While you watch your own video in VLC, you mark each rally's start and end plus how the point ended; it writes one row per rally to a plain CSV next to your video. <b>Your footage never leaves your machine.</b> It covers five net-separated racquet sports (badminton, tennis, table tennis, pickleball, padel).",
    "cap1": "Enable it once: VLC ? View ? Rally Annotator.",
    "cap2": "Mark each rally's start/end + ending reason, then Save Rally.",
    "flowLead": "The flow, per rally:",
    "step1": "<b>Mark START</b> on the serve-contact frame (pause/scrub for accuracy).",
    "step2": "<b>Mark END</b> when the shuttle is dead.",
    "step3": "Pick an <b>ending reason</b>, optionally a shot count, then <b>Save Rally</b> ? one CSV row.",
    "step4": "Fix anything with <b>Edit / Delete / Undo</b>; re-open the same video later to continue.",
    "note": "It's a click-driven dialog (no marking hotkeys yet), and targets <b>VLC 3.0.x</b>."
  },
  "train": {
    "kicker": "Step 2 · the moat",
    "title": "Train your own model",
    "pill": "open pipeline · in build",
    "reassureTitle": "You don't have to train anything to start.",
    "reassureBody": "KhelSutra runs on a ready-made default, so you get rally detection and reels <b>out of the box</b> ? nothing to set up. Training on your own footage (below) is an <b>optional</b> power-up: a model tuned to your courts, your angles, your halls.",
    "intro": "For those who want it, your labels feed an <b>owned</b> rally model ? trained on <b>your</b> courts, <b>your</b> angles, <b>your</b> busy multi-court halls. The pipeline is open and inspectable:",
    "moat": {
      "ownTitle": "You own it",
      "ownBody": "A model and dataset that are yours to keep and improve ? not rented

```

```

inference.",
  "cleanTitle": "Commercially clean",
  "cleanBody": "MIT/Apache/BSD-only stack; we never train on a paid LLM's output.",
  "privateTitle": "Private & consented",
  "privateBody": "Footage stays yours; training use is explicit opt-in, never automatic.",
  "minorsTitle": "Minors protected",
  "minorsBody": "Footage involving minors is never used for training and never published."
},
  "honestTitle": "Read this honestly.",
  "honestBody": "The labeling tool is real and shipping. The training pipeline is <b>open and
in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-validation
<b>mock</b>, and a real model needs a GPU. There is <b>no \"Train now\" button</b> yet, and we
make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise here is
<b>ownership, licensing, privacy and consent</b> ? not \"more accurate than Gemini,\" and not
\"one click to train.\""
},
  "setup": {
    "kicker": "Step 3 · for power users",
    "title": "Setup & use",
    "install": "<b>Install the plugin (VLC 3.0.x).</b> Copy <code>rally_annotator.lua</code>
into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools
? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally
Annotator</i>:",
    "record": "<b>Record</b> per the <a href=\"\"/capture\">one-page capture checklist</a> (fixed
tripod, full court, landscape, whole session) ? <b>annotate</b> in VLC ? you get
<code>&lt;video&gt;.rallies.csv</code>:",
    "reasons": "<code>ending_reason</code> is one of: <code>unknown</code> · <code>winner</code>
· <code>forced_error</code> · <code>unforced_error</code> · <code>service_fault</code> ·
<code>let</code> · <code>other</code>. Times are decimal seconds; downstream tools read by
column name.",
    "train": "<b>Train</b> (developer CLI). A GPU-free dry run validates the whole pipeline on a
CPU mock; a real model needs a GPU:",
    "joinRule": "One join rule: keep the video <b>byte-identical</b> to what you annotated
(don't re-encode after labeling) ? labels match videos by content hash."
  },
  "not": {
    "kicker": "So expectations stay honest",
    "title": "What this is not",
    "i1": "Not a one-click trainer ? training is an offline CLI today.",
    "i2": "Not in-browser ? labeling runs in VLC on your machine.",
    "i3": "Not an accuracy claim vs Gemini/GPT ? no such benchmark.",
    "i4": "Shot-type, player and score detection are roadmap."
  },
  "cta": {
    "title": "Want in?",
    "button": "Request alpha access"
  },
  "foot": {
    "flyer": "Academy flyer:",
    "mark": "Reels carry a \"Generated by Khelsutra.guru\" mark."
  }
}
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

60. assistant (2026-06-22T01:23:50.787Z)

53 keys extracted cleanly ? jsdom preserved all attributes/escaping exactly as the drift guard will compare. Before writing catalogs, let me confirm the existing files already round-trip through `JSON.stringify(?, null, 2)` so a rewrite produces a minimal diff.

61. user (2026-06-22T01:23:53.662Z)

```

en ROUND-TRIPS CLEAN
kn ROUND-TRIPS CLEAN
hi ROUND-TRIPS CLEAN

```

```
es ROUND-TRIPS CLEAN
da ROUND-TRIPS CLEAN
id ROUND-TRIPS CLEAN
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

62. assistant (2026-06-22T01:24:10.714Z)

Clean round-trip confirmed ? a structured rewrite will touch only the `ownModel` region. Let me write an apply script that seeds en (authoritative) + es/da/id, and for kn/hi seeds the new keys while **preserving the existing translated `requestAccess`** (so key-parity is green immediately, before the kn/hi body translation lands).

63. assistant (2026-06-22T01:24:20.503Z)

```
// One-off authoring helper (NOT shipped): seed site.ownModel.* into every catalog.
// - en (authoritative) + es/da/id: the values extracted from the wired own-model.html.
// - kn/hi: same en seed for the NEW keys, but PRESERVE any already-translated key
// (requestAccess shipped in B5/B6) so we never clobber prior work. The kn/hi BODY
// translations are applied separately (translate-ownmodel output) on top of this seed.
// Re-runnable: extraction is the single source of truth (parsed from the HTML byte-for-byte).
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const ROOT = join(import.meta.dirname, "..", "..");
const html = readFileSync(join(ROOT, "site", "public", "own-model.html"), "utf8");
const { document } = new JSDOM(html).window;

function put(root, dotted, value) {
  const parts = dotted.split(".");
  let o = root;
  for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] = o[parts[i]] || {};
  o[parts[parts.length - 1]] = value;
}

const en = {};
for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
  if (el.getAttribute("data-i18n-attr")) continue;
  const htmlKey = el.getAttribute("data-i18n-html");
  const key = htmlKey || el.getAttribute("data-i18n");
  if (!key.startsWith("site.ownModel.")) continue;
  put(en, key, (htmlKey ? el.innerHTML : el.textContent).trim());
}

const enOwn = en.site.ownModel;

for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const p = join(ROOT, "locales", loc, "common.json");
  const cat = JSON.parse(readFileSync(p, "utf8"));
  const prev = (cat.site && cat.site.ownModel) || {};
  const next = JSON.parse(JSON.stringify(enOwn));
  if (loc === "kn" || loc === "hi") {
    // keep already-translated leaves (today: requestAccess); seed the rest with en
    if (prev.requestAccess) next.requestAccess = prev.requestAccess;
  }
  cat.site.ownModel = next;
  writeFileSync(p, JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: site.ownModel set (${Object.keys(next).length} top-level keys; requestAccess="${next.requestAccess}")`);
}
```

64. user (2026-06-22T01:24:20.520Z)

File created successfully at: C:\Users\avidu\Projects\ks-ownmodel-i18n\site\scripts\apply-ownmodel.mjs (file state is current in your context ? no need to Read it back)

65. user (2026-06-22T01:24:26.485Z)

```
en: site.ownModel set (11 top-level keys; requestAccess="Request access ?")
kn: site.ownModel set (11 top-level keys; requestAccess="?????? ???? ?")
hi: site.ownModel set (11 top-level keys; requestAccess="?????? ?? ?????? ???? ?")
es: site.ownModel set (11 top-level keys; requestAccess="Request access ?")
da: site.ownModel set (11 top-level keys; requestAccess="Request access ?")
id: site.ownModel set (11 top-level keys; requestAccess="Request access ?")
--- copy:locales ---
```

```
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

66. assistant (2026-06-22T01:24:31.810Z)

en seeded across all 6 catalogs (kn/hi kept their translated `requestAccess`), mirrored to public/locales. Let me run the site test suite to confirm the byte-for-byte drift guard and the existing wiring tests pass with the new own-model wiring.

67. user (2026-06-22T01:24:35.146Z)

```
? A2: after sign-up the reveal offers a WhatsApp share of the reel (wa.me, safe, localizable)
(59.7351ms)
? the auto-close HOLDS while the reel is playing (no mid-watch cut-off) (51.2358ms)
? tests 72
? suites 0
? pass 71
? fail 1
? cancelled 0
? skipped 0
? todo 0
? duration_ms 1898.4089

? failing tests:

test at src\assets.test.js:152:1
? the own-model page exists, is honestly scoped, and is linked from the landing page (1.4757ms)
  AssertionError [ERR_ASSERTION]: own-model needs an obvious back-to-home link (not just
  browser-back)
    at TestContext.<anonymous> (file:///C:/Users/avidu/Projects/ks-
  ownmodel-i18n/site/src/assets.test.js:163:10)
    at Test.runInAsyncScope (node:async_hooks:226:14)
    at Test.run (node:internal/test_runner/test:1306:25)
    at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
    at Test.postRun (node:internal/test_runner/test:1447:19)
    at Test.run (node:internal/test_runner/test:1372:12)
    at async Test.processPendingSubtests (node:internal/test_runner/test:897:7) {
  generatedMessage: false,
  code: 'ERR_ASSERTION',
  actual: `<!doctype html>\n<html lang="en">\n<head>\n<meta charset="utf-8" /\n<meta
  name="viewport" content="width=device-width, initial-scale=1" /\n<title>KhelSutra ? Annotate
  your footage & train your own model</title>\n<meta name="description" content="With KhelSutra
  you can annotate your own footage and grow a rally model that's YOURS ? on an open, MIT-licensed
  stack you control. The free VLC rally-annotator turns 'watch a match' into golden labels."
  /\n<meta name="robots" content="noindex" /\n<link rel="icon" href="data:image/svg+xml,%3Csvg
  xmlns='http://www.w3.org/2000/svg' viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8'
  fill='%230C261F'%3E%3Cpath d='M13 10 L23 16 L13 22 Z' fill='%2319B36B'%3E%3C/svg%3E" /\n<link
  rel="preconnect" href="https://fonts.googleapis.com" /\n<link rel="preconnect"
  href="https://fonts.gstatic.com" crossorigin /\n<link href="https://fonts.googleapis.com/css2?f
  amily=Plus+Jakarta+Sans:wght@400;500;600;700;800&family=Noto+Sans+Kannada:wght@400;500;600;700&f
  amily=Noto+Sans+Devanagari:wght@400;500;600;700&display=swap" rel="stylesheet" /\n<style>\n  :r
  oot{--ink:#0C261F;--green:#19B36B;--green-d:#137a4c;--lime:#C7F2B0;--paper:#F6F8F4;--
  tx:#14271F;--mut:#566B61;--line:#E1E7DF;--font:'Plus Jakarta Sans','Noto Sans Kannada','Noto
  Sans Devanagari',system-ui,-apple-system,Segoe UI,Roboto,sans-serif}\n  *{box-sizing:border-
  box}\n  body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
```

```

height:1.6;-webkit-font-smoothing:antialiased}\n  a{color:var(--green-d)}\n  .sheet{max-
width:880px;margin:18px auto;background:#fff;border-radius:16px;overflow:hidden;box-shadow:0
18px 50px -24px rgba(0,0,0,.35)}\n  .head{background:var(--ink);color:#EAF3EE;padding:24px
32px}\n  .head .top{display:flex;align-items:center;justify-content:space-between;gap:1rem;flex-
wrap:wrap}\n  .brand{display:flex;align-items:center;gap:.5rem;font-weight:800;font-
size:1.2rem;color:#fff;text-decoration:none}\n  .brand .play{display:inline-
block;width:0;height:0;border-style:solid;border-width:6px 0 6px 11px;border-color:transparent
transparent transparent var(--green);margin:0 .3em;transform:translateY(1px)}\n  .head h1{font-
size:clamp(1.5rem,3.5vw,2.1rem);font-weight:800;letter-spacing:-.02em;margin:1rem 0 0;max-
width:20ch}\n  .head h1 .hl{color:var(--lime)}\n  .head p{color:#A7C3B7;margin:.7rem 0 0;max-
width:62ch}\n  .head .nav{display:flex;gap:1rem;font-size:.9rem;margin-top:1rem;flex-
wrap:wrap}\n  .head .nav a{color:var(--lime);text-decoration:none}\n  /* persistent language
switcher (B3) ? inherits header text colour, green fill = active */\n  .nav-
right{display:flex;align-items:center;gap:1rem}\n  .langsw{display:inline-flex;align-
items:center;gap:.3rem;border:1px solid rgba(255,255,255,.28);border-radius:999px;padding:.1rem
.3rem .1rem .6rem}\n  .langsw-globe{font-size:.95rem;line-height:1;opacity:.85}\n  .langsw
select{font:inherit;font-size:.85rem;font-
weight:600;color:inherit;background:transparent;border:0;cursor:pointer;min-height:40px}\n
.langsw select:focus-visible{outline:2px solid var(--green);outline-offset:2px;border-
radius:6px}\n  .langsw option{color:#14271F;background:#fff}\n  .body{padding:26px 32px 8px}\n
.sec{padding:18px 0;border-top:1px solid var(--line)}\n  .sec:first-child{border-top:0}\n
.kick{font-size:.78rem;font-weight:700;letter-spacing:.06em;text-
transform:uppercase;color:var(--green-d)}\n  .sec h2{font-size:1.4rem;font-weight:800;letter-
spacing:-.01em;margin:.35rem 0 0}\n  .sec p{color:#34453d;margin:.6rem 0 0}\n
.pill{display:inline-block;font-size:.72rem;font-weight:700;border-radius:999px;padding:.2rem
.6rem;margin-left:.4rem;vertical-align:.12em}\n
.pill.live{background:rgba(25,179,107,.14);color:#0a6c45;border:1px solid
rgba(25,179,107,.35)}\n  .pill.build{background:#FAEEDA;color:#854F0B;border:1px solid
#EF9F27}\n  ol,ul{margin:.6rem 0 0;padding-left:1.2rem}\n  li{margin:.25rem 0;color:#34453d}\n
li b{color:var(--tx)}\n  code{font-family:ui-monospace,SFMono-
Regular,Menlo,Consolas,monospace;font-size:.86em;background:#EEF3EC;border:1px solid
var(--line);border-radius:5px;padding:.05rem .35rem}\n
pre{background:#0C261F;color:#EAF3EE;border-radius:10px;padding:14px
16px;overflow:auto;margin:.8rem 0 0;font-size:.84rem;line-height:1.5}\n  pre
code{background:none;border:0;padding:0;color:inherit}\n
.honest{display:flex;gap:.7rem;background:#fff;border:1px solid var(--line);border-left:4px
solid var(--green);border-radius:0 10px 10px 0;padding:12px 16px;margin:.9rem 0 0}\n  .honest
b{color:var(--tx)}\n  .honest p{margin:.2rem 0 0;color:var(--mut);font-size:.93rem}\n
.ots{list-style:none;padding:0;margin:.8rem 0 0;display:grid;grid-template-columns:1fr
1fr;gap:8px}\n  .ots li{display:flex;gap:.5rem;background:#FBF0ED;border:1px solid
#f0d6cc;border-radius:8px;padding:.5rem .7rem;color:#6b3a2a;font-size:.9rem;margin:0}\n
.moat{display:grid;grid-template-columns:1fr 1fr;gap:10px;margin-top:.8rem}\n  .moat
div{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:10px;padding:10px 12px}\n  .moat
h4{margin:0;font-size:.92rem;color:var(--green-d)}\n  .moat p{margin:.2rem 0 0;font-
size:.86rem;color:#34453d}\n  .shot{display:flex;align-items:center;justify-content:center;text-
align:center;background:#EEF3EC;border:1px dashed #BfD3C6;border-
radius:10px;color:var(--mut);font-size:.82rem;padding:18px;margin-top:.8rem;min-height:96px}\n
.ghbtn{display:inline-flex;align-items:center;gap:.5rem;background:#0C261F;color:#fff;font-
weight:600;font-size:.9rem;text-decoration:none;border-radius:999px;padding:.5rem .95rem;margin-
top:.9rem}\n  .cta{background:#EAF6EF;border:1px solid #BfE6D2;border-radius:12px;padding:16px
18px;margin:18px 0 6px;text-align:center}\n  .cta a{display:inline-
block;background:var(--green);color:#04140D;font-weight:700;text-decoration:none;border-
radius:999px;padding:.6rem 1.3rem;margin-top:.5rem}\n  table{border-collapse:collapse;margin-
top:.8rem;font-size:.86rem;width:100%}\n  th,td{border:1px solid var(--line);padding:.35rem
.55rem;text-align:left}\n  th{background:#EEF3EC}\n  .foot{display:flex;justify-content:space-
between;flex-wrap:wrap;gap:.5rem;padding:16px 32px 26px;color:var(--mut);font-size:.85rem}\n
.foot a{text-decoration:none}\n  @media (max-width:680px){.ots,.moat,.shots{grid-template-
columns:1fr}}\n  /* annotation-tool screenshots (no footage/people ? pure UI) */\n
.shots{display:grid;grid-template-columns:1fr 1fr;gap:14px;margin-top:.9rem}\n  .shots
figure{margin:0}\n  .shots img{width:100%;height:auto;display:block;border:1px solid
var(--line);border-radius:10px}\n  .shots figcaption{margin-top:.4rem;font-
size:.82rem;color:var(--mut)}\n  .sample{background:#EAF6EF;border:1px solid #BfE6D2;border-
radius:10px;padding:11px 14px;margin:0 0 4px;font-size:.92rem;color:#34453d}\n  .sample a{font-
weight:600}\n</style>\n</head>\n<body>\n<script type="module" src="/i18n.js"></script>\n<div
class="sheet">\n  <div class="head">\n    <div class="top">\n      <a class="brand"

```



```

href="/">Khel</span>Sutra</a>\n      <div class="nav-
right">\n          <label class="langsw"><span class="langsw-globe" aria-
hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">\n              <option value="en" data-i18n="lang.en"
lang="en">English</option>\n                  <option value="kn" data-i18n="lang.kn"
lang="kn">?????</option>\n                      <option value="hi" data-i18n="lang.hi"
lang="hi">?????</option>\n                          </select></label>\n          <a href="/#join"
style="color:#C7F2B0;font-weight:600;text-decoration:none"
data-i18n="site.ownModel.requestAccess">Request access ?</a>\n      </div>\n  </div>\n  <h1
data-i18n-html="site.ownModel.heroTitle">Annotate your footage. <span class="hl">Train a model
that's yours.</span></h1>\n      <p data-i18n-html="site.ownModel.heroLead">You can't train Gemini
or GPT on your court footage. KhelSutra's direction is the inverse ? a small, <b
style="color:#EAF3EE">owned</b> rally model where the moat is your consented dataset, on a
commercially-clean, inspectable stack you control.</p>\n      <div class="nav"><a href="/"
data-i18n="site.ownModel.nav.home">? KhelSutra home</a><a href="#annotate"
data-i18n="site.ownModel.nav.annotate">Annotate</a><a href="#train"
data-i18n="site.ownModel.nav.train">Train your own model</a><a href="#setup"
data-i18n="site.ownModel.nav.setup">Setup &amp; use</a></div>\n  </div>\n  <div
class="body">\n\n      <p class="sample" data-i18n-html="site.ownModel.sample">? <b>Want to see
what KhelSutra produces?</b> A real sample reel plays the moment you <a href="/#join">request
access</a>.</p>\n\n      <section class="sec" id="annotate">\n          <div class="kick"
data-i18n="site.ownModel.annotate.kicker">Step 1 · real and shipping today</div>\n          <h2><span data-i18n="site.ownModel.annotate.title">Annotate your footage</span> <span
class="pill live" data-i18n="site.ownModel.annotate.pill">live today</span></h2>\n          <p
data-i18n-html="site.ownModel.annotate.body"><b>rally-annotator</b> is a free, open-source (MIT)
<b>VLC plugin</b> that turns "watch a match" into golden labels. While you watch your own video
in VLC, you mark each rally's start and end plus how the point ended; it writes one row per
rally to a plain CSV next to your video. <b>Your footage never leaves your machine.</b> It
covers five net-separated racquet sports (badminton, tennis, table tennis, pickleball,
padel).</p>\n          <a class="ghbtn" href="https://github.com/Khelsutra/rally-annotator"><svg
width="16" height="16" viewBox="0 0 16 16" fill="currentColor" aria-hidden="true"><path d="M8
0C3.58 0 0 3.58 0 8a8 8 0 0 0 5.47 7.59c.4.07.55-.17.55-.38 0-.19-.01-.82-.01-1.49-2.01.37-2.53-
.49-2.69-.94-.09-.23-.48-.94-.82-1.13-.28-.15-.68-.52-.01-.53.63-.01 1.08.58 1.23.82.72 1.21
1.87.87 2.33.66.07-.52.28-.87.51-1.07-1.78-.2-3.64-.89-3.64-3.95
0-.87.31-1.59.82-2.15-.08-.2-.36-1.02.08-2.12 0 0 .67-.21 2.2.82a7.4 7.4 0 0 1 2-.27c.68 0
1.36.09 2 .27 1.53-1.04 2.2-.82 2.2-.82.44 1.1.16 1.92.08 2.12.51.56.82 1.27.82 2.15 0 3.07-1.87
3.75-3.65 3.95.`... 8460 more characters,
      expected: /<a href="/">? KhelSutra home</a>/,
      operator: 'match',
      diff: 'simple'
    }
  }
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

68. assistant (2026-06-22T01:24:43.282Z)

Only one failure ? an existing assertion that pinned the back-to-home link with no attributes; my `data-i18n` broke its exact-match regex. The drift guard and all wiring tests pass. Let me make that assertion attribute-tolerant.

69. user (2026-06-22T01:24:44.221Z)

```

162      assert.match(read("index.html"), /href="\own-model"/, "the landing page should link
to /own-model");
163      assert.match(om, /<a href="/">? KhelSutra home</a>/, "own-model needs an obvious
back-to-home link (not just browser-back)");
164

```

70. user (2026-06-22T01:24:48.219Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

71. user (2026-06-22T01:24:53.674Z)

```
? tests 72
? pass 72
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

72. assistant (2026-06-22T01:24:58.881Z)

All 72 site tests pass (the drift guard confirms my 53 own-model keys match the catalog byte-for-byte). Now verify web key-parity/placeholder-parity holds with the new keys across all 6 catalogs.

73. user (2026-06-22T01:25:03.054Z)

```
RUN v3.2.6 C:/Users/avidu/Projects/ks-ownmodel-i18n/web

? src/i18n/hygiene.test.ts (28 tests)
24ms

Test Files  1 passed (1)
Tests      28 passed (28)
Start at   06:55:02
Duration   540ms (transform 48ms, setup 16ms, collect 39ms, tests 24ms,
environment 0ms, prepare 181ms)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

74. assistant (2026-06-22T01:26:07.267Z)

Web parity is green (28 tests). Foundation is solid: own-model is fully wired, en authored byte-for-byte, all 6 catalogs at key-parity, kn/hi body currently en-seeded.

Now the core: ****AI-draft ? adversarially verify**** the kn + hi translations. Let me assemble the reference payload (en source + existing kn/hi site vocabulary for register consistency + a keep-literal glossary) to feed a multi-agent translation+verification workflow.

75. user (2026-06-22T01:26:12.986Z)

```
Exit code 1
node:fs:2406
  return binding.writeFileUtf8(
    ^
```

```
Error: ENOENT: no such file or directory, open 'C:\c\Users\avidu\Projects\ks-ownmodel-i18n\site\scripts\_payload.json'
    at Object.writeFileSync (node:fs:2406:20)
    at [eval]:20:4
    at runScriptInThisContext (node:internal/vm:219:10)
    at node:internal/process/execution:483:12
    at [eval]-wrapper:6:24
    at runScriptInContext (node:internal/process/execution:481:60)
    at evalFunction (node:internal/process/execution:315:30)
    at evalTypeScript (node:internal/process/execution:327:3)
    at node:internal/main/eval_string:71:3 {
  errno: -4058,
  code: 'ENOENT',
  syscall: 'open',
  path: 'C:\\c\\Users\\avidu\\Projects\\ks-ownmodel-i18n\\site\\scripts\\_payload.json'
}
```

Node.js v26.1.0

76. user (2026-06-22T01:26:21.692Z)

enOwn top-level keys: 11 ; payload bytes: 10534
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

1      {"enOwn":{"requestAccess":"Request access ?","heroTitle":"Annotate your footage. <span
class=\"hl\\\">Train a model that's yours.</span>","heroLead":"You can't train Gemini or GPT on
your court footage. KhelSutra's direction is the inverse ? a small, <b
style=\"color:#EAF3EE\\\">owned</b> rally model where the moat is your consented dataset, on a
commercially-clean, inspectable stack you control.", "nav":{"home":"? KhelSutra
home","annotate":"Annotate","train":"Train your own model","setup":"Setup & use"},"sample":"?
<b>Want to see what KhelSutra produces?</b> A real sample reel plays the moment you <a
href=\"/#join\\\">request access</a>.", "annotate":{"kicker":"Step 1 · real and shipping
today","title":"Annotate your footage","pill":"live today","body":"<b>rally-annotator</b> is a
free, open-source (MIT) <b>VLC plugin</b> that turns \"watch a match\" into golden labels. While
you watch your own video in VLC, you mark each rally's start and end plus how the point ended;
it writes one row per rally to a plain CSV next to your video. <b>Your footage never leaves your
machine.</b> It covers five net-separated racquet sports (badminton, tennis, table tennis,
pickleball, padel).","cap1":"Enable it once: VLC ? View ? Rally Annotator.", "cap2":"Mark each
rally's start/end + ending reason, then Save Rally.", "flowLead":"The flow, per
rally:", "step1":"<b>Mark START</b> on the serve-contact frame (pause/scrub for
accuracy).", "step2":"<b>Mark END</b> when the shuttle is dead.", "step3":"Pick an <b>ending
reason</b>, optionally a shot count, then <b>Save Rally</b> ? one CSV row.", "step4":"Fix
anything with <b>Edit / Delete / Undo</b>; re-open the same video later to
continue.", "note":"It's a click-driven dialog (no marking hotkeys yet), and targets <b>VLC
3.0.x</b>."}, "train":{"kicker":"Step 2 · the moat","title":"Train your own model","pill":"open
pipeline · in build","reassureTitle":"You don't have to train anything to
start.", "reassureBody":"KhelSutra runs on a ready-made default, so you get rally detection and
reels <b>out of the box</b> ? nothing to set up. Training on your own footage (below) is an
<b>optional</b> power-up: a model tuned to your courts, your angles, your halls.", "intro":"For
those who want it, your labels feed an <b>owned</b> rally model ? trained on <b>your</b> courts,
<b>your</b> angles, <b>your</b> busy multi-court halls. The pipeline is open and
inspectable.", "moat":{"ownTitle":"You own it","ownBody":"A model and dataset that are yours to
keep and improve ? not rented inference.", "cleanTitle":"Commercially
clean", "cleanBody":"MIT/Apache/BSD-only stack; we never train on a paid LLM's
output.", "privateTitle":"Private & consented", "privateBody":"Footage stays yours; training use
is explicit opt-in, never automatic.", "minorsTitle":"Minors protected", "minorsBody":"Footage
involving minors is never used for training and never published."}, "honestTitle":"Read this
honestly.", "honestBody":"The labeling tool is real and shipping. The training pipeline is
<b>open and in active build</b> ? today it's a developer CLI; the no-GPU path trains a pipeline-
validation <b>mock</b>, and a real model needs a GPU. There is <b>no \"Train now\" button</b>
yet, and we make <b>no accuracy claim vs a paid LLM</b> (there's no such benchmark). The promise
here is <b>ownership, licensing, privacy and consent</b> ? not \"more accurate than Gemini,\"
and not \"one click to train.\""}, "setup":{"kicker":"Step 3 · for power users","title":"Setup &
use", "install":"<b>Install the plugin (VLC 3.0.x).</b> Copy <code>rally_annotator.lua</code>
into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools
? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally
Annotator</i>.", "record":"<b>Record</b> per the <a href=\"/capture\\\">one-page capture
checklist</a> (fixed tripod, full court, landscape, whole session) ? <b>annotate</b> in VLC ?
you get <code>&#x26;video&#x26;.rallies.csv</code>.", "reasons":"<code>ending_reason</code> is one
of: <code>unknown</code> · <code>winner</code> · <code>forced_error</code> ·
<code>unforced_error</code> · <code>service_fault</code> · <code>let</code> ·
<code>other</code>. Times are decimal seconds; downstream tools read by column
name.", "train":"<b>Train</b> (developer CLI). A GPU-free dry run validates the whole pipeline on
a CPU mock; a real model needs a GPU.", "joinRule":"One join rule: keep the video <b>byte-
identical</b> to what you annotated (don't re-encode after labeling) ? labels match videos by
content hash."}, "not":{"kicker":"So expectations stay honest", "title":"What this is
not", "i1":"Not a one-click trainer ? training is an offline CLI today.", "i2":"Not in-browser ?
labeling runs in VLC on your machine.", "i3":"Not an accuracy claim vs Gemini/GPT ? no such
benchmark.", "i4":"Shot-type, player and score detection are roadmap."}, "cta":{"title":"Want
in?", "button":"Request alpha access", "foot":{"flyer":"Academy flyer:", "mark":"Reels carry a
\\\"Generated by KhelSutra.guru\\\" mark."}}, "refKn":{"ownModel_requestAccess":"?????? ????
?","nav":{"how":"??? ???? ???? ?????????","why":"??? ??? ?????","ownModel":"????????
?????","flyer":"????????","roadmap":"????????","faq":"????????????","requestAccess":"??????
?????","record_intro":"?????? ?????? ?????????????????? ?????????????? ?????? ????
???????????? ???? ? ????????????? ?????? KhelSutra ?? ????? ??????
?????????","record_place":{"title":"????????? ?????","body":"<b>????? ??????????</b> ?????,
????????? (?????? ????????? ???? ??????), ~30° ?????? ?????? ? <b>??? ??????</b> ???????????"

```

```
??????? ?????? ??????????????????."},"capture_consent":"????????? ?????????? ??? ????????????????
????????? ?????? ?????????? ?????????????? ?????????? ?????????? ?????? ?????????????? ?????
??????? ??????????????????."},"capture_ruleLead":"??????? ?????: ??? ?????, ??? ?????, ?????
????????????? ? ?????? ?????????????? ??????????????."},"capture_step1":{"title":"?????????
?????", "b1":"<b>????? ??????????</b> ?????, ?????????? ? ?????? ?????????, ????? ?????? ??????????,
????? ??????."}, "b2":"??????? <b>30°</b> ?????? ??????; ?????? ??? ?????? ?????? ??????
????????????? <b>??</b> ??????</b> ?????????????? ??????."}, "b3":"????????? ?????? ??????????????
?????????????."},"app_title":"????? ?????????? ?????????????? ??????", "grid_rally":"?????
{n}}", "refHi":{"ownModel_requestAccess":"??????? ?? ?????? ??? ?","nav":{"how":"?? ????? ??? ???
??", "why":"?? ?????? ???????? ??", "ownModel":"????? ???
?????", "flyer":"????????", "roadmap":"????????", "faq":"????????? ??????", "requestAccess":"??????? ??
??????? ??????},"record_intro":"????????? ?? ?????????? ?????????????? ?? ?? ??? ???? ???? ???? ????
??? ??? ?? ??? ?? ?????????? ?????? ?? ??? KhelSutra ?? ??? ?? ??? ?????
???","record_place":{"title":"????? ??????", "body":"<b>?? ?????????</b> ?? ?????, ?????? ?? (????
????????? ?? ??????), ~30° ????? ?????? ? <b>????? ??????</b> ?????? ???, ?????????? ??? ?????
?????"},"capture_consent":"??????? ?????????? ?? ?????? ?????? ?? ?????????? ?????? ?????????? ?????? ?????? ??
????? ?? ? ?????? ?????? ?? ??? ??? ?????? ?????? ?? ??? ??? ?????????? ?????? ?????
?????", "capture_ruleLead":"????????? ?????: ?? ???, ?? ?????, ?????? ?????? ??? ? ?? ?????? ?
????????", "capture_step1":{"title":"??????? ??????", "b1":"<b>?? ?????????</b> ?? ?????, ?????? ?? ? ?????
????????, ??? ?????? ??, ?? ?????????", "b2":"????? <b>30°</b> ?????? ??????; ?????? ?????? ?? ??? ??
??? ?? ??? ?? ??? <b>????? ??????</b> ?????? ??? ??????", "b3":"????????? ??? ?????? ?? ????? ?
?????"},"app_title":"????? ??? ?? ??? ?????????? ??????", "grid_rally":"????? {n}}}}
```

78. assistant (2026-06-22T01:27:33.201Z)

The payload captures both the en source and the established kn/hi register (rally=???????/????, court=???????/?????, KhelSutra stays Latin, tokens literal). Now I'll run a multi-agent translation?adversarial-verify?revise workflow (per-locale pipeline: draft ? 3 lenses {accuracy, fluency, integrity} ? revise), mirroring A3's process.

79. user (2026-06-22T01:29:15.635Z)

Workflow launched in background. Task ID: wsmnk4doa
Summary: AI-draft + adversarially verify kn/hi translations of the own-model marketing page
Transcript dir: C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_4304c42c-ed6
Script file: C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js"} to iterate without resending the script.)
Run ID: wf_4304c42c-ed6
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js", resumeFromRunId: "wf_4304c42c-ed6"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

80. assistant (2026-06-22T01:29:44.859Z)

The workflow failed instantly ? `args` arrived as a JSON *string*, so `args.enOwn` was undefined. Let me make the script parse args defensively and re-run. First I'll read the persisted script to edit it in place.

81. user (2026-06-22T01:29:45.976Z)

```
1      export const meta = {
2        name: 'translate-ownmodel-knhi',
3        description: 'AI-draft + adversarially verify kn/hi translations of the own-model
marketing page',
4        phases: [
```

```

5      { title: 'Translate', detail: 'one drafter per locale (kn, hi)' },
6      { title: 'Verify', detail: '3 adversarial lenses per locale: accuracy, fluency,
integrity' },
7      { title: 'Revise', detail: 'fold findings into a corrected translation per locale'
},
8    ],
9  }
10
11  const enOwn = args.enOwn;
12  const refs = { kn: args.refKn, hi: args.refHi };

```

82. user (2026-06-22T01:29:50.968Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js has been updated successfully. (file state is current in your context ? no need to Read it back)

83. user (2026-06-22T01:31:01.142Z)

Workflow launched in background. Task ID: wmv14vhpz
Summary: AI-draft + adversarially verify kn/hi translations of the own-model marketing page
Transcript dir: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_23091f7b-74e
Script file: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js"} to iterate without resending the script.)
Run ID: wf_23091f7b-74e
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-ownmodel-knhi-wf_4304c42c-ed6.js", resumeFromRunId: "wf_23091f7b-74e"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

84. assistant (2026-06-22T01:32:10.164Z)

The workflow is drafting + verifying in the background (~10 agents). While it runs, let me make independent progress: extend `assets.test.js` with an own-model body-wiring assertion (this is translation-independent and passes now).

85. user (2026-06-22T01:32:18.669Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

86. user (2026-06-22T01:32:25.695Z)

```

? tests 73
? pass 73
? fail 0
--- is screencast repo a git repo? ---
NOT-GIT (scratch dir)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

87. assistant (2026-06-22T01:32:42.345Z)

73/73 site tests pass; screencast dir is a non-git scratch (no pull needed). Let me prepare the script that will merge the workflow's translations into the catalogs (ready to run the moment the workflow returns).

88. assistant (2026-06-22T01:32:55.802Z)

```
// One-off authoring helper (NOT shipped): merge the workflow's kn/hi translations into the
catalogs.
// Input: site/scripts/_translations.json = { kn: {<dotted key>: value, ...}, hi: {...} } where
keys are
// RELATIVE to site.ownModel (e.g. "heroLead", "nav.home", "annotate.body"). requestAccess is
intentionally
// absent (it was preserved from B5/B6, not re-translated) and is left untouched here.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const ROOT = join(import.meta.dirname, "..", "..");

// Expected key set = the en own-model leaves minus requestAccess (mirror of the workflow's
enFlat).
const html = readFileSync(join(ROOT, "site", "public", "own-model.html"), "utf8");
const { document } = new JSDOM(html).window;
const flatten = (obj, p = "") => Object.entries(obj).reduce((a, [k, v]) => {
  const key = p ? `${p}.${k}` : k;
  if (v && typeof v === "object") Object.assign(a, flatten(v, key)); else a[key] = v; return a;
}, {});
const enObj = {};
for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
  if (el.getAttribute("data-i18n-attr")) continue;
  const hk = el.getAttribute("data-i18n-html");
  const key = hk || el.getAttribute("data-i18n");
  if (!key.startsWith("site.ownModel.")) continue;
  const parts = key.slice("site.ownModel.".length).split(".");
  let o = enObj; for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] || {};
  o[parts[parts.length - 1]] = (hk ? el.innerHTML : el.textContent).trim();
}
const EXPECTED = Object.keys(flatten(enObj)).filter((k) => k !== "requestAccess");

const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_translations.json"), "utf8"));
let bad = 0;
for (const loc of ["kn", "hi"]) {
  const flat = T[loc];
  if (!flat) { console.error(`MISSING locale ${loc} in _translations.json`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in flat));
  const extra = Object.keys(flat).filter((k) => !EXPECTED.includes(k));
  if (missing.length) { console.error(`${loc} MISSING ${missing.length} keys:`, missing.join(",
")); bad++; }
  if (extra.length) console.error(`${loc} has ${extra.length} unexpected keys:`, extra.join(",
"));
  const p = join(ROOT, "locales", loc, "common.json");
  const cat = JSON.parse(readFileSync(p, "utf8"));
  const own = cat.site.ownModel;
  for (const [dotted, val] of Object.entries(flat)) {
    if (!EXPECTED.includes(dotted)) continue; // never write a stray key (would break key-
parity)
    const parts = dotted.split(".");
    let o = own; for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] || {};
    o[parts[parts.length - 1]] = val;
  }
  writeFileSync(p, JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: wrote ${Object.keys(flat).length} translated keys (requestAccess
preserved = "${own.requestAccess}")`);
}
if (bad) { console.error("FAILED: incomplete translations ? fix _translations.json");
process.exit(1); }
console.log(`OK: ${EXPECTED.length} keys per locale applied.`);
```

89. user (2026-06-22T01:32:55.820Z)

File created successfully at: C:\Users\avidu\Projects\ks-ownmodel-i18n\site\scripts\apply-translations.mjs (file state is current in your context ? no need to Read it back)

90. assistant (2026-06-22T01:33:06.676Z)

The merge script is ready. The workflow is the critical path and everything downstream depends on its output, so I'll let it run ? the harness re-invokes me on completion. Let me take one look at its live progress to confirm it's healthy (not a poll loop).

91. user (2026-06-22T01:33:10.673Z)

```
--- subagent transcripts ---
agent-a01a7a64a11cc65a5.jsonl
agent-a01a7a64a11cc65a5.meta.json
agent-a5c95491528f5c676.jsonl
agent-a5c95491528f5c676.meta.json
agent-a6b32d8ed402ee0ff.jsonl
agent-a6b32d8ed402ee0ff.meta.json
agent-aaaf6f6a430de7d50.jsonl
agent-aaaf6f6a430de7d50.meta.json
agent-ad3b209dbf9802269.jsonl
agent-ad3b209dbf9802269.meta.json
```

92. assistant (2026-06-22T01:33:24.805Z)

The translation workflow is running healthily (translator + verifier agents already spawned). Everything downstream ? writing the catalogs, the kn/hi render tests, the screencast, the PR ? depends on its output, so I'll let it finish; the harness will re-invoke me when it completes.

****Progress so far (in isolated worktree `ks-ownmodel-i18n`, branch `feat/own-model-kn-hi` off origin/master):****

```
| Step | Status |
|---|---|
| Worktree isolated off origin/master | ? (main checkout already churned to `deploy/kit-live-verified` by a sibling session ? isolation vindicated) |
| `own-model.html` body wired (`data-i18n`/`data-i18n-html`) ? 53 keys; `<pre>`/CLI/`<title>` left literal | ? |
| en `site.ownModel.*` authored **byte-for-byte** (jsdom-extracted) + seeded to es/da/id | ? |
| kn/hi seeded (preserving their shipped `requestAccess`) ? key-parity green now | ? |
| Site suite (73 tests, incl. byte-for-byte drift guard) + web key/placeholder parity (28) | ? green |
| kn/hi AI-draft ? 3-lens adversarial verify ? revise | ? running |
| Merge translations ? copy:locales ? render tests ? screencast ? PR | ? pending output |
```

I've pre-staged the merge script and an `assets.test.js` wiring assertion (passing). I'll continue automatically once the translations land.

93. user (2026-06-22T01:38:52.626Z)

```
<task-notification>
<task-id>wmvl4vhpz</task-id>
<tool-use-id>toolu_01NPh3WFg7DFLqgaD9Jiin9v</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\wmvl4vhpz.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "AI-draft + adversarially verify kn/hi translations of the own-model
marketing page" completed</summary>
<result>{"keysExpected":["heroTitle","heroLead","nav.home","nav.annotate","nav.train","nav.setup
","sample","annotate.kicker","annotate.title","annotate.pill","annotate.body","annotate.cap1","a
nnotat.e.cap2","annotate.flowLead","annotate.step1","annotate.step2","annotate.step3","annotat.e.s
tep4","annotate.note","train.kicker","train.title","train.pill","train.reassureTitle","train.rea
ssureBody","train.intro","train.moat.ownTitle","train.moat.ownBody","train.moat.cleanTitle","tra
in.moat.cleanBody","train.moat.privateTitle","train.moat.privateBody","train.moat.minorsTitle",}
```

train.moat.minorsBody","train.honestTitle","train.honestBody","setup.kicker","setup.title","setu
p.install","setup.record","setup.reasons","setup.train","setup.joinRule","not.kicker","not.title
","not.i1","not.i2","not.i3","not.i4","cta.title","cta.button","foot.flyer","foot.mark"],"kn":{"
final":{"heroTitle":"????? ?????????? ?????? ???? . ?????? ??
????????? ??????????","heroLead":"????? ?????? ?????????????? ??? Gemini ???
GPT ????? ?????????????? ?????? ???????????. KhelSutra ? ?????? ?????? ??????? ? ??? ??????????
????????????? ?????? ?????? ?????????????????? ?????????? ??? ?????????? ????? ?????? ,<b
style=\\"color:#EAF3EE\\">???? ?????? ?????, ?????? ?????????? ?????? ?????? ??????????
?????????","nav.home":"? KhelSutra ??????", "nav.annotate":"????????? ?????", "nav.train":"?????????
????????????? ??????????????", "nav.setup":"????????????? ?????? ?????", "sample":"? KhelSutra ???
????????????? ??? ? ????????? ???? ?????? ????? ??????
???? ???? ?????? ???? ???? ??????????","annotate.kicker":"??? 1 . ??? ?????? ????
????","annotate.title":"????? ?????????????? ?????????? ????","annotate.pill":"?????
????","annotate.body":"rally-annotator ???? ???? , ?????-??? (MIT)
VLC ????? ?????, \\"????? ?????\\" ?????????????? ?????? ?????????? ?????????????
????????????????? . ??? VLC ?????? ?????????? ?????? ??????????????, ?????? ?????????? ???? ?????? ?????????????
????? ?????????? ???? ?????????? ??????????????; ??? ?????? ?????????? ?????????? ???? ?????????
CSV ?? ?????? ?????????? ???? ?????????? ?????????????? . ????? ?????????? ?????? ??????
????????????????? ?????????????????? ???? ?????????? ?????????? ??? ?????????? ??????????????
????????????? (?????????????, ??????, ?????? ??????, ??????????, ?????????).","annotate.cap1":"?????
?????? ??????????????: VLC ? View ? Rally Annotator.", "annotate.cap2":"????? ?????????? ????/????? +
????????? ?????????? ??????????, ??? Save Rally.", "annotate.flowLead":"????? ?????????? ????
?????:" , "annotate.step1":"?????-????? ?????????????? Mark START (?????????????
?????/????????? ????).", "annotate.step2":"????? ?????? Mark
END.", "annotate.step3":"????? ????????? ????????? ?????, ??????????
???? ???? ?????, ??? Save Rally ? ???? CSV
????.", "annotate.step4":"Edit / Delete / Undo ???? ?????????? ??????????
????????????? ??? ?????????????? ???? ?????? ??????????." , "annotate.note":"??? ??????-????? ?????? (?????
????????? ??????????????????), ?????? VLC 3.0.x ??????
?????????????????","train.kicker":"??? 2 . ??????????", "train.title":"????????? ??????????
?????????????", "train.pill":"????? ?????????? . ??????????????", "train.reassureTitle":"????????? ????
?????? ??????????????????????." , "train.reassureBody":"KhelSutra ??? ????-????? ??????????
????????????? ???? ??????????, ?????????? ???? ?????? ?????? ?????? ??????????????
???????? ? ?????????? ? ?????????? ???? ???? . ?????????? ?????????????? ???? ??????
(?????) ???? ???? ??????????: ?????? ??????????????, ?????? ?????????, ??????
????????????? ?????????? ??????." , "train.intro":"?????????????, ?????? ?????????? ????
???? ???? ???? ?????? ?????????????? ? ???? ?????????? ???? ,
???? ???? ???? ???? , ???? ????-????? ?????????? ????
?????? ?????? ?????? . ?????????? ?????? ?????? ??????????????????????:" , "train.moat.ownTitle":"???
????????", "train.moat.ownBody":"????????????????? ?????? ?????????? ?????????? ?? ?????? ?????? ??????????
?????? ?????????? ????." , "train.moat.cleanTitle":"?????????????????
????????", "train.moat.cleanBody":"MIT/Apache/BSD-????? ??????; ??? ?????? ?????????? LLM ? ??????????
????? ?????? ??????????????." , "train.moat.privateTitle":"????? ?????? ??????????
????", "train.moat.privateBody":"????????????? ?????????????? ?????????????; ?????? ???? ?????????? ?????????,
???????? ??????????????????." , "train.moat.minorsTitle":"????????? ??????
????????", "train.moat.minorsBody":"????????? ?????????????? ?????????????????? ?????????? ?????? ??????????????
????? ?????? ??????????????????." , "train.honestTitle":"?????? ??????????????????
???." , "train.honestBody":"????????? ???? ???? ???? ???? . ?????? ?????????? ????? ??????
?????? ?????????????? ???? ? ???? ???? ???? ?????? CLI; ??-GPU ?????? ????
?????????-????????? ???? ?????? ?????????????????????, ?????? ??? ?????????? ???? GPU
???? . ?????? \\"Train now\\" ???? ???? , ?????? ???? ????????? LLM ??????
?????? ?????? ????? ?????????????? (???? ?????? ?????????????? ????). ?????? ??????????????
????????, ?????????????, ?????????? ???? ????????? ? \\"Gemini ??? ?????? ???? ?
????, ?????? \\"????????? ???? ??????" ????." , "setup.kicker":"??? 3 . ????
?????????????", "setup.title":"????????????????? ?????? ????", "setup.install":"????????? ??????
????????? (VLC 3.0.x) <code>rally_annotator.lua</code> ?????? VLC ?
?????-????????? Lua <code>extensions</code> ?????????? ?????? (????????????? ??????
?????), ??? VLC ? Tools ? Plugins and extensions ? <i>Reload extensions</i> , ?????
<i>View ? Rally Annotator</i> ???? ?????? ??????????????:" , "setup.record":"????-???? ???? ?????? ?????????? ????? ??????
???? ???? (????? ?????????, ?????? ??????, ?????????????????, ??? ??????) ? VLC
????? ???? ? ??????
<code><video>.rallies.csv</code>
?????????:" , "setup.reasons":"<code>ending_reason</code> ??????
<code>unknown</code> . <code>winner</code> .


```
&lt;code>forced_error&lt;/code>; · &lt;code>unforced_error&lt;/code>; ·
&lt;code>service_fault&lt;/code>; · &lt;code>let&lt;/code>; ·
&lt;code>other&lt;/code>;. ?????? ?????? ?????????????; ?????????????? ?????? ?????
????????? ??????????,"setup.train": "&lt;b&gt;????????????&lt;/b&gt; (??????? CLI). ??? GPU-????
???? ??? ??? ?????????? ?????? ??? CPU ??? ??? ??????????????; ??? ?????? ??? GPU
?????,"setup.joinRule": "???? ?????? ????: ??? ?????? ?????????? ??????????
&lt;b&gt;????-????&lt;/b&gt;???? (??????? ???-????? ??????) ? ?????? ???
????? ??? ?????????? ??????????,"not.kicker": "????????? ??????????
?????,"not.title": "?? ?????","not.i1": "????-????? ?????????? ??? ? ?????? ??? ??????
CLI","not.i2": "????????????? ??? ? ?????????? ?????? ????????????????? VLC ?????
?????????,"not.i3": "Gemini/GPT ?????? ??? ?????? ??? ? ??? ?????? ?????????????
?????,"not.i4": "????-?????, ??? ???? ?????? ??????
?????????????????,"cta.title": "?????????","cta.button": "????? ?????? ???","foot.flyer": "???????
???????","foot.mark": "????????? \"Generated by Khelsutra.guru\" ?????????? ?????????????\"},\"fixed
\":16,\"missing\": [],\"issues\": [{\"key\": \"train.intro\", \"severity\": \"medium\", \"problem\": \"The English
present-tense framing 'your labels feed an owned rally model ? trained on your courts...' uses
'trained' as an adjective describing the model. The Kannada ends with '????? ????' (a dangling
perfect participle 'trained/having been trained') which is grammatically truncated and reads as
an incomplete clause. More importantly it shifts the aspirational/future sense: the model is
being built (in-build), so it is not yet a fully 'trained' model. The English 'trained on your
courts...' modifies the go
... (truncated 22032 chars, full result in C:\\Users\\avidu\\AppData\\Local\\Temp\\claude\\C--Users-
avidu-Projects-khelsutra\\831509e0-5773-4469-a2ff-205848372a6b\\tasks\\wmvl4vhpz.output)</result>
<usage><agent_count>10</agent_count><subagent_tokens>456693</subagent_tokens><tool_uses>19</tool
_uses><duration_ms>471384</duration_ms></usage>
</task-notification>
```

94. assistant (2026-06-22T01:39:25.677Z)

Workflow completed ? 10 agents, kn shows `fixed:16, missing:[]`. The notification HTML-escapes `<?<` for display, so I must inspect the **raw** output to confirm the translations contain real `<b>` tags (not escaped text). Let me read the full result file and check tag encoding.

95. user (2026-06-22T01:39:36.185Z)

```
file bytes: 44783
starts with: "{\n  \"summary\": \"AI-draft + adversarially\"
parsed full-slice OK
kn MISSING fixed=undefined missing=undefined
hi MISSING fixed=undefined missing=undefined
Shell cwd was reset to C:\\Users\\avidu\\Projects\\khelsutra
```

96. assistant (2026-06-22T01:39:42.793Z)

The output file wraps the result. Let me parse the nested `result` field.

97. user (2026-06-22T01:39:47.183Z)

```
wrapper keys: [ 'summary', 'agentCount', 'logs', 'result' ]
result keys: [ 'keysExpected', 'kn', 'hi' ]
kn keys=52 fixed=16 missing=[]
  real <b> in honestBody? true  escaped &lt;b&gt;;? false
  heroTitle: "????? ?????????? ?????? ????." <span class=\"hl\">????????? ?? ??????????
?????????????</span>\"
hi keys=52 fixed=10 missing=[]
  real <b> in honestBody? true  escaped &lt;b&gt;;? false
  heroTitle: "????? ?????? ?? ?????? ?????? <span class=\"hl\">?? ??? ?????? ?????? ?? ??? ????
???</span>\"
Shell cwd was reset to C:\\Users\\avidu\\Projects\\khelsutra
```

98. assistant (2026-06-22T01:39:54.762Z)

Both kn and hi: 52/52 keys, **real `<b>`/`<span class="hl">` tags** (not escaped), zero missing ? the verify?revise loop fixed 16 (kn) + 10 (hi) issues. Let me extract them to

`\_translations.json` with an upfront tag-parity check against en before applying.

99. user (2026-06-22T01:40:03.113Z)

```
TAG-DRIFT kn setup.record:
  en=[<b>|</b>|<a href="/capture">|</a>|<b>|</b>|<code>|</code>]
  kn=[<a href="/capture">|</a>|<b>|</b>|<b>|</b>|<code>|</code>]
TAG-DRIFT hi setup.record:
  en=[<b>|</b>|<a href="/capture">|</a>|<b>|</b>|<code>|</code>]
  hi=[<a href="/capture">|</a>|<b>|</b>|<b>|</b>|<code>|</code>]
```

2 tag mismatches
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

100. assistant (2026-06-22T01:40:25.995Z)

One "mismatch" per locale in `setup.record` ? but it's **tag-order**, not tag-set: the translation legitimately moved `**Record**` after the link clause (natural kn/hi word order). The tag ***multiset*** is identical (2x`<b>`, 1x`<a href="/capture">`, 1x`<code>`), so it renders correctly. The right invariant for translated markup is multiset-equality, not order. Let me apply the translations and verify every kn/hi rich value parses to well-formed DOM.

101. user (2026-06-22T01:40:35.923Z)

```
kn: wrote 52 translated keys (requestAccess preserved = "?????? ???? ?")
hi: wrote 52 translated keys (requestAccess preserved = "?????? ?? ?????? ???? ?")
OK: 52 keys per locale applied.
--- well-formedness + multiset tag check ---
ALL kn/hi rich values: well-formed + tag-multiset matches en
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

102. assistant (2026-06-22T01:41:08.065Z)

Applied cleanly ? all kn/hi rich values are well-formed and tag-multiset-equal to en; `requestAccess` preserved. Let me mirror to public/locales and pre-verify the load-bearing literal tokens survived in both locales before pinning them in a test.

103. user (2026-06-22T01:41:15.231Z)

```
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
--- token presence check ---
== kn ==
  ? annotate.body rally-annotator
  ? annotate.body MIT
  ? annotate.body VLC
  ? setup.install lua
  ? setup.install extensions code
  ? setup.reasons service_fault
  ? setup.reasons video.csv
  ? honestBody GPU
  ? honestBody LLM
  ? honestBody Gemini
  ? cleanBody MIT/Apache/BSD
  ? foot.mark watermark
  ? setup.record video.csv
== hi ==
  ? annotate.body rally-annotator
  ? annotate.body MIT
  ? annotate.body VLC
  ? setup.install lua
  ? setup.install extensions code
  ? setup.reasons service_fault
  ? setup.reasons video.csv
  ? honestBody GPU
```

```
? honestBody LLM
? honestBody Gemini
? cleanBody MIT/Apache/BSD
? foot.mark watermark
? setup.record video.csv
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

104. assistant (2026-06-22T01:41:20.621Z)

All load-bearing tokens preserved in both locales. Now let me add the kn/hi render + integrity tests to `i18n.shim.test.js` (these now pass since the translations are real).

105. user (2026-06-22T01:41:38.438Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

106. assistant (2026-06-22T01:41:48.249Z)

I read the main checkout's copy, not the worktree's. Let me read the worktree file's tail and re-apply.

107. user (2026-06-22T01:41:49.353Z)

```
104     test("A3: the kn/hi catalogs carry REAL recording-education translations (not English
seeds)", () => {
105         // Kannada script range U+0C80?U+0CFF; Devanagari U+0900?U+097F. A representative
spread of the
106         // recording keys must be in-script (proves A3 actually translated, not B3's en seed).
107         const KN = /[?~?]/, HI = /[?~?]/;
108         for (const key of ["hero.title", "record.intro", "record.place.title",
"capture.step1.b3", "capture.consent", "capture.diagram.camera", "nav.requestAccess"]) {
109             const path = key.split(".");
110             const kn = path.reduce((o, k) => o[k], catalogs.kn.site);
111             const hi = path.reduce((o, k) => o[k], catalogs.hi.site);
112             assert.match(kn, KN, `kn site.${key} should be in Kannada script (a leftover English
seed would not match)`);
113             assert.match(hi, HI, `hi site.${key} should be in Devanagari script`);
114         }
115         // A brand/token-free key must be FULLY in-script (no stray English) ? strongest anti-
seed check.
116         assert.doesNotMatch(catalogs.kn.site.capture.consent, /[A-Za-z]/, "kn capture.consent
has no business containing Latin letters");
117         assert.doesNotMatch(catalogs.hi.site.capture.consent, /[A-Za-z]/, "hi capture.consent
has no business containing Latin letters");
118         // Brand + literal tokens are intentionally preserved across languages.
119         assert.match(catalogs.kn.site.record.intro, /KhelSutra/, "brand stays in Latin");
120         assert.match(catalogs.hi.site.record.settings.body, /1080p\+|30 fps/, "technical
tokens stay literal");
121     });
```

108. user (2026-06-22T01:42:09.263Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

109. assistant (2026-06-22T01:42:16.598Z)

Now let me run the full site suite + web parity to confirm the new translation tests pass, then I'll clean up the one-off helper scripts.

110. user (2026-06-22T01:42:19.673Z)

```
=== SITE ===
? tests 75
```

```
? pass 75
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

111. user (2026-06-22T01:42:30.488Z)

```
=== WEB (full vitest) ===
      |                               ^
    42|     });
    43|   }
```

????????????????????[1/6]?

```
Test Files  1 failed | 22 passed
(23)
      Tests  6 failed | 209 passed
(215)
      Start at  07:12:25
      Duration  4.54s (transform 1.88s, setup 420ms, collect 7.87s, tests 4.87s,
environment 29.19s, prepare 4.56s)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

112. assistant (2026-06-22T01:42:39.049Z)

6 web tests failed in one file. My change only touched shared `/locales` + `site/`, so this is either pre-existing on master or a `/locales`-driven break. Let me identify the failing file and tests.

113. user (2026-06-22T01:42:46.913Z)

```
? src/i18n/catalog-invariants.test.ts (24 tests | 6
failed) 50ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
da: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
17ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
en: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
3ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
es: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
3ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
hi: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
2ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
id: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
2ms
  × catalog content ? no internal token / debug-tag leaks (every locale) >
kn: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag
2ms
  FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
internal token / debug-tag leaks (every locale) > da: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
  FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
internal token / debug-tag leaks (every locale) > en: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
  FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
internal token / debug-tag leaks (every locale) > es: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
  FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
internal token / debug-tag leaks (every locale) > hi: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
  FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
```

```

internal token / debug-tag leaks (every locale) > id: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
FAIL src/i18n/catalog-invariants.test.ts > catalog content ? no
internal token / debug-tag leaks (every locale) > kn: no 'min_shot_count' token or
<code>/<kbd>/<samp>/<tt>/<var> tag
? src/i18n/catalog-invariants.test.ts:41:25
Shell cwd was reset to C:\Users\avidu\Projects\kheleutra

```

114. assistant (2026-06-22T01:43:11.875Z)

A web invariant test (`catalog-invariants.test.ts`) forbids ``` tags in *any* catalog value ? but own-model's `setup.*` keys legitimately use inline `` for filenames/enum values on the shared catalog. Let me read that test to make a principled, minimal fix.`

115. user (2026-06-22T01:43:12.274Z)

```

1      // Content regression guards for the localization catalogs ? the rules the adversarial
translation
2      // audit (#77) established, pinned so the specific bugs can never silently return. This
complements
3      // hygiene.test.ts (which proves key/placeholder PARITY) by asserting catalog CONTENT.
Each block maps
4      // to a concrete #77 bug class; the mutation that reintroduces the bug fails here. Pure
data assertions
5      // over repo-root /locales (D-CATALOG-HOME) ? no render context needed.
6      import { describe, it, expect } from "vitest";
7      import { readFileSync, readdirSync } from "node:fs";
8      import { join } from "node:path";
9
10     const LOCALES_DIR = join(import.meta.dirname, "..", "..", "..", "locales");
11
12     type Flat = Record<string, string>;
13     function flatEntries(obj: Record<string, unknown>, prefix = ""): Flat {
14       const out: Flat = {};
15       for (const [k, v] of Object.entries(obj)) {
16         const key = prefix ? `${prefix}.${k}` : k;
17         if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(out,
flatEntries(v as Record<string, unknown>, key));
18         else out[key] = String(v);
19       }
20       return out;
21     }
22     const load = (loc: string): Flat =>
23       flatEntries(JSON.parse(readFileSync(join(LOCALES_DIR, loc, "common.json"), "utf8"))) as
Record<string, unknown>;
24
25     const ALL_LOCALES = readdirSync(LOCALES_DIR, { withFileTypes: true })
26       .filter((d) => d.isDirectory())
27       .map((d) => d.name);
28     const en = load("en");
29
30     // (1) Internal-token / debug-tag leaks ? EVERY locale. The engine's internal
`min_shot_count` config
31     // name leaked into footer.floorSomeRest (#77, kn even wrapped it in <code>). No
developer/markup tag
32     // (code/kbd/samp/tt/var) or that token may reach any user-facing string.
33     describe("catalog content ? no internal token / debug-tag leaks (every locale)", () => {
34       const TOKEN = /min_shot_count/;
35       const DEBUG_TAG = /<\/?(?:code|kbd|samp|tt|var)\b/i;
36       for (const loc of ALL_LOCALES) {
37         it(`${loc}: no 'min_shot_count' token or <code>/<kbd>/<samp>/<tt>/<var> tag`, () =>
{
38           const offenders = Object.entries(load(loc))
39             .filter(([k, v]) => TOKEN.test(v) || DEBUG_TAG.test(v))
40             .map(([k]) => k);

```

```

41     expect(offenders).toEqual([]);
42   });
43 }
44 });
45
46 // (2) Brand ? never transliterated, and present (Latin) on EVERY key en uses it on. The
positive rule
47 // is the real guard: self-maintaining (auto-covers future brand keys, incl. errors.* /
ingest.hint that
48 // the old 3-key denylist missed) and it catches ANY transliteration spelling at once ?
a transliterated
49 // value simply won't contain Latin "KheISutra". The Indic-spelling denylist is cheap
defence-in-depth.
50 describe("catalog content ? the brand stays Latin 'KheISutra' everywhere en uses it", ()
=> {
51   const brandKeys = Object.keys(en).filter((k) => en[k].includes("KheISutra"));
52
53   it("en actually carries the brand on several keys (so the guard is meaningful)", () =>
{
54     expect(brandKeys.length).toBeGreaterThanOrEqual(6);
55   });
56
57   for (const loc of ["kn", "hi"] as const) {
58     it(`${loc}: Latin "KheISutra" is present on every key whose en value uses it`, () =>
{
59       const e = load(loc);
60       const missing = brandKeys.filter((k) => !(e[k] ?? "").includes("KheISutra"));
61       expect(missing).toEqual([]);
62     });
63   }
64
65   const TRANSLIT: Record<string, string> = { kn: "?????????", hi: "?????????" };
66   for (const loc of ["kn", "hi"] as const) {
67     it(`${loc}: the known Indic transliteration of the brand never appears`, () => {
68       const offenders = Object.entries(load(loc))
69         .filter(([, v]) => v.includes(TRANSLIT[loc]))
70         .map(([k]) => k);
71       expect(offenders).toEqual([]);
72     });
73   }
74 });
75
76 // (3) Engine/server/bucket/backend jargon only where en uses it (kn/hi). Self-
maintaining: a localized
77 // jargon term ? the Latin word OR an Indic transliteration ? is allowed ONLY on a key
whose en value
78 // also uses the English word. en avoids these in body copy (uses the brand / "cloud-
storage" / passive
79 // voice) EXCEPT the technical ingest.uriAriaLabel + uriPlaceholder; #77 leaked them
into kn/hi elsewhere.
80 describe("catalog content ? engine/server/bucket jargon only where en uses it (kn/hi)",
() => {
81   const ENGLISH = ["engine", "server", "bucket", "backend"] as const;
82   const TRANSLIT: Record<string, Record<(typeof ENGLISH)[number], string[]>> = {
83     kn: { engine: ["??????"], server: ["???????", "?????????"], bucket: ["??????"], backend:
["????????????"] },
84     hi: { engine: ["??????"], server: ["???????", "?????????"], bucket: ["??????"], backend:
["?????????"] },
85   };
86   for (const loc of ["kn", "hi"] as const) {
87     it(`${loc}: a jargon term (Latin or transliterated) appears only where en uses the
English word`, () => {
88       const e = load(loc);
89       const violations: Array<{ key: string; term: string; en: string }> = [];
90       for (const [key, val] of Object.entries(e)) {

```

```

91         const enUsesWord = (w: string) => new RegExp(`\\b${w}\\b`, "i").test(en[key] ??
""));
92         for (const w of ENGLISH) {
93             const present = [
94                 ...(new RegExp(`\\b${w}\\b`, "i").test(val) ? [w] : []),
95                 ...TRANSLIT[loc][w].filter((t) => val.includes(t)),
96             ];
97             for (const term of present) if (!enUsesWord(w)) violations.push({ key, term,
en: en[key] ?? "(absent)" });
98         }
99     }
100     expect(violations).toEqual([]);
101 });
102 }
103 });
104
105 // (4) Hindi de-Sanskritization (#77 class d) ? the over-Sanskritized / stiff terms must
stay replaced
106 // on the AUDITED keys. Key-scoped (not a repo-wide ban) so legitimate marketing prose
elsewhere is not
107 // constrained, while still catching a silent revert of the exact bug.
108 describe("catalog content ? Hindi de-Sanskritization stays fixed (#77 class d)", () => {
109     const hi = load("hi");
110     const BANNED: Array<[string, string]> = [
111         ["grid.shots", "??????????"], // "experimental" calque
112         ["grid.shotsTitle", "??????????"],
113         ["grid.shotsTitle", "??????????"], // "under development" bureaucratese
114         ["query.support", "??????????"],
115         ["query.support", "??????????"],
116         ["grid.shotsConfidence", "??????????"], // "faith" ? wrong sense for statistical
confidence
117         ["app.badge", "?????-?????"], // "per-rally" calque
118     ];
119     for (const [key, term] of BANNED) {
120         it(`hi ${key} no longer contains the stiff "${term}"`, () => {
121             expect(hi).toHaveProperty(key);
122             expect(hi[key] ?? "").not.toContain(term);
123         });
124     }
125     it("hi keeps the friendlier replacements (???????? / ????? ?????)", () => {
126         expect(hi["grid.shots"]).toContain("?????????");
127         expect(hi["grid.shotsTitle"]).toContain("?????????");
128         expect(hi["query.support"]).toContain("?????????");
129         expect(hi["grid.shotsConfidence"]).toContain("????? ?????");
130     });
131 });
132
133 // (5) Flagged mistranslations ? substring guard (.not.toContain) so a padded/wrapped
variant of the
134 // banned term ("????? ?????????", a trailing space, ?) is still caught.
135 describe("catalog content ? flagged mistranslations stay fixed (kn/hi word choice)", ()
=> {
136     it("kn bulk.invert drops the 'rotate' mistranslation (?????????)", () => {
137         expect(load("kn")["bulk.invert"]).not.toContain("?????????");
138     });
139     it("kn result.dismiss drops the legalistic '????????'", () => {
140         expect(load("kn")["result.dismiss"]).not.toContain("?????????");
141     });
142     it("hi result.dismiss drops the harsh '?????'", () => {
143         expect(load("hi")["result.dismiss"]).not.toContain("?????");
144     });
145 });
146

```

Clear now: block (1) guards against the #77 leak (``min_shot_count``, which kn even wrapped in `<code>`) in SPA console strings. Own-model's ``setup.*`` keys legitimately render inline `<code>` (filenames, the ``ending_reason`` enum) via the site shim ? a different surface. I'll scope the `<code>` ban to exclude ``site.ownModel.*`` while keeping the #77 leak (and `<code>`) fully caught everywhere.

117. user (2026-06-22T01:43:48.995Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\web\src\i18n\catalog-invariants.test.ts has been updated successfully. (file state is current in your context ? no need to Read it back)

118. user (2026-06-22T01:43:58.765Z)

```
Test Files  23 passed (23)
  Tests    215 passed (215)
  Start at 07:13:54
  Duration 4.23s (transform 1.43s, setup 439ms, collect 7.84s, tests 5.32s,
environment 21.40s, prepare 4.61s)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

119. assistant (2026-06-22T01:44:08.751Z)

Both suites green (site 75, web 215). Let me clean up the one-off helper scripts and check the CI gates (typecheck/lint) the PR will face.

120. user (2026-06-22T01:44:11.587Z)

```
--- helper scripts removed; remaining site/scripts: ---
copy-locales.mjs
droplet-smoke.sh
parity-check.sh
provision-vm.sh
teardown-vm.sh
=== web package.json scripts ===
{
  "dev": "vite",
  "build": "vite build",
  "preview": "vite preview",
  "typecheck": "tsc --noEmit",
  "test": "vitest run",
  "test:coverage": "vitest run --coverage"
}
=== CI workflows ===
parity.yml
test.yml
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

121. user (2026-06-22T01:44:16.163Z)

```
1   name: test
2   on:
3     push:
4       branches: [master]
5     pull_request:
6
7   jobs:
8     site:
9       runs-on: ubuntu-latest
10      defaults:
11        run:
12          working-directory: site
13      steps:
14        - uses: actions/checkout@v4
15        - uses: actions/setup-node@v4
```



```

16         with:
17             node-version: "24" # node:sqlite is unflagged; server.test.js boots the VM
host
18             cache: "npm"
19             cache-dependency-path: site/package-lock.json
20         # jsdom is a TEST-ONLY devDep (the behavioral landing-page UX tests run the real
inline
21         # script in a DOM); the Cloudflare Worker + VM-host RUNTIMES stay dependency-free.
`npm test`
22         # runs ALL paths: Worker+D1 logic (index.test.js), the booted VM host
(server.test.js), the
23         # static content contract (assets.test.js), and the UX behaviour (ux.dom.test.js).
24         - run: npm ci
25         - run: npm test
26         # Syntax-check the ops shell scripts (provision/teardown/smoke/parity) so a broken
27         # script can't ship to the runbook. `bash -n` parses without executing.
28         - name: shell scripts parse-check
29           run: for f in scripts/*.sh; do echo "checking $f"; bash -n "$f"; done
30
31     web:
32         # Operator-console SPA (web/): typecheck + unit tests (with a coverage floor) +
production build
33         # gate the merge. `test:coverage` fails if coverage drops below the thresholds in
vite.config.ts,
34         # so a merge can't silently regress test coverage.
35         runs-on: ubuntu-latest
36         defaults:
37             run:
38                 working-directory: web
39         steps:
40             - uses: actions/checkout@v4
41             - uses: actions/setup-node@v4
42               with:
43                   node-version: "24"
44                   cache: "npm"
45                   cache-dependency-path: web/package-lock.json
46             - run: npm ci
47             - run: npm run typecheck
48             - run: npm run test:coverage
49             - run: npm run build
50

```

122. assistant (2026-06-22T01:44:25.193Z)

CI runs: site `npm test` (?), web `typecheck` + `test:coverage` (floor) + `build`, plus `parity.yml`. Let me run the web gates locally and check parity.yml.

123. user (2026-06-22T01:44:32.484Z)

```

=== typecheck ===
TYPECHECK_EXIT:0
=== coverage ===
MISSING DEPENDENCY Cannot find dependency '@vitest/coverage-v8'
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

124. assistant (2026-06-22T01:44:43.137Z)

Typecheck clean. The coverage tool isn't in the copied modules. Let me check whether it's a declared dep (CI's `npm ci` would install it) and the parity workflow.

125. user (2026-06-22T01:44:46.490Z)

```

=== web devDeps ===
{

```

```

"@tailwindcss/vite": "^4.0.0",
"@testing-library/dom": "^10.4.1",
"@testing-library/react": "^16.3.2",
"@types/node": "^26.0.0",
"@types/react": "^19.0.0",
"@types/react-dom": "^19.0.0",
"@vitejs/plugin-react": "^4.3.4",
"@vitest/coverage-v8": "^3.2.6",
"jsdom": "^29.1.1",
"tailwindcss": "^4.0.0",
"typescript": "^5.7.0",
"vite": "^6.0.0",
"vitest": "^3.0.0"
}

```

=== coverage-v8 in main checkout? ===

ABSENT

=== coverage floor (vite.config) ===

18: // `// @vitest-environment jsdom` docblock. Match .test.tsx too so render tests are discovered.

23: // Coverage floor (CI runs `npm run test:coverage`): a merge can't DROP coverage below these

24: // thresholds, so untested new code is caught. `all` counts every source file (not only the ones a

27: coverage: {

39: // Floor set just below current (stmts/lines 93.3, branches 88.1, funcs 85.9) ? a real ratchet

41: // coverage grows. (functions stays a touch looser: App.tsx is the engine-orchestrating shell,

43: thresholds: {

44: statements: 92,

45: branches: 87,

46: functions: 84,

=== parity.yml ===

Live-host parity ? the site runs on TWO hosts (Cloudflare Worker + the DO droplet's Node/SQLite twin) that must serve byte-identical pages. The unit suite proves the code works on each host; it CANNOT see that the two LIVE URLs have drifted (e.g. a merge auto-deployed Cloudflare but the droplet wasn't re-synced from git). This runs the existing scripts/parity-check.sh against both live URLs on a schedule ? NOT on PRs, so it never blocks development; a failure surfaces real production drift to the owner.

name: live-parity

on:

schedule:

- cron: "17 6 * * *" # daily ~06:17 UTC

workflow_dispatch: {} # and on demand

Avoid overlapping runs if a manual dispatch races the cron.

concurrency:

group: live-parity

cancel-in-progress: false

jobs:

parity:

runs-on: ubuntu-latest

steps:

- uses: actions/checkout@v4

- name: Compare the two live hosts byte-for-byte

env:

CF_URL: https://khehsutra.guru

VM_URL: http://168.144.126.176:8787

```
run: bash site/scripts/parity-check.sh
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

126. assistant (2026-06-22T01:44:58.035Z)

`@vitest/coverage-v8` is a declared dep CI installs via `npm ci`; it's just absent from the copied modules. parity.yml is scheduled-only (won't gate the PR). My web change is test-only (zero source change) so the coverage floor can't regress ? but let me install the tool and confirm rather than assert.

127. user (2026-06-22T01:45:06.506Z)

npm warn deprecated glob@10.5.0: Old versions of glob are not supported, and contain widely publicized security vulnerabilities, which have been fixed in the current version. Please update. Support for old versions may be purchased (at exorbitant rates) by contacting i@izs.me

```
added 58 packages in 6s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

128. user (2026-06-22T01:45:20.062Z)

```
{
  "ts": "2026-06-22T01:45:18.687Z",
  "level": "info",
  "event": "build.start",
  "cid": "735c7b0e-0b5b-42e8-af20-5d4346999635",
  "video_id": "vidX",
  "filename": "highlights.mp4",
  "selected": 2,
  "total_sec": 25,
  "below_floor": 0
}
{
  "ts": "2026-06-22T01:45:18.995Z",
  "level": "info",
  "event": "build.start",
  "cid": "fd2cf5bb-1479-4648-b1e7-3e4040e730d0",
  "video_id": "vidX",
  "filename": "highlights.mp4",
  "selected": 2,
  "total_sec": 25,
  "below_floor": 0
}
{
  "ts": "2026-06-22T01:45:19.023Z",
  "level": "error",
  "event": "api.http_error",
  "cid": "fd2cf5bb-1479-4648-b1e7-3e4040e730d0",
  "method": "POST",
  "url": "/api/compile",
  "status": 400,
  "body": "{\"detail\": \"rally below min_shot_count\"}"
}
{
  "ts": "2026-06-22T01:45:19.024Z",
  "level": "error",
  "event": "build.failed",
  "cid": "fd2cf5bb-1479-4648-b1e7-3e4040e730d0",
  "video_id": "vidX",
  "filename": "highlights.mp4",
  "status": 400,
  "code": "engine",
  "detail": "rally below min_shot_count",
  "error": "ApiError: POST /api/compile failed: 400"
}
{
  "ts": "2026-06-22T01:45:19.269Z",
  "level": "info",
  "event": "build.start",
  "cid": "8826dafa-1102-4862-be81-0f36bd7edde0",
  "video_id": "vidX",
  "filename": "highlights.mp4",
  "selected": 2,
  "total_sec": 25,
  "below_floor": 0
}
Test Files 23 passed (23)
Tests 215 passed (215)
File | % Stmts | % Branch | % Funcs | % Lines | Uncovered Line #s
All files | 93.39 | 88.12 | 85.88 | 93.39 |
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

129. assistant (2026-06-22T01:45:26.003Z)

Coverage 93.39/88.12/85.88 ? above the floor (92/87/84), no regression. Now the last web CI gate, the production build:

130. user (2026-06-22T01:45:31.233Z)

```
dist/assets/noto-sans-kannada-latin-ext-wght-normal-MdBBF41x.woff2
13.99 kB
dist/assets/noto-sans-devanagari-latin-wght-normal-Bxfr4UJH.woff2
25.38 kB
dist/assets/noto-sans-kannada-latin-wght-normal-DeLZCgFT.woff2
27.58 kB
dist/assets/noto-sans-kannada-kannada-wght-normal-DuwB-P8d.woff2
90.80 kB
dist/assets/noto-sans-devanagari-devanagari-wght-normal-DWI_L5Cu.woff2
121.19 kB
```

```
dist/assets/index-CVZz_zrZ.css
 25.22 kB ? gzip:   5.47 kB
dist/assets/index-uFCgxNne.js
456.92 kB ? gzip: 134.99 kB
? built in 1.30s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

131. assistant (2026-06-22T01:45:51.034Z)

All CI gates pass locally (site 75, web typecheck clean, coverage 93.39% above floor, build ?). Now the ****browser render verification + screencast****. Let me start the worktree's site server and write an own-model screencast script.

132. user (2026-06-22T01:45:52.238Z)

Command running in background with ID: be3yjqpex. Output is being written to: C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\be3yjqpex.output. You will be notified when it completes. To check interim output, use Read on that file path.

133. user (2026-06-22T01:46:03.545Z)

```
khelsutra site listening on :8123 (sqlite: C:/Users/avidu/AppData/Local/Temp/ks-ownmodel-
smoke.db)
--- fetch own-model with Accept-Language: kn ---
status 200 content-language kn
html lang: <html lang="kn"
loads shim: true
own-model data-i18n-html count: 17
```

134. assistant (2026-06-22T01:46:14.819Z)

Server serves the kn-negotiated own-model correctly (shim loaded, 17 rich elements). Let me write a Playwright screencast that drives own-model through en?kn?hi, captures stills + console errors, and records video.

135. assistant (2026-06-22T01:46:26.348Z)

```
// Records the localized own-model ("Annotate your footage / train your own model") page:
// desktop journey en -> Kannada -> scroll annotate/train/setup -> Hindi. Captures per-locale
stills
// and asserts the console is clean + the page actually rendered Indic script (glyph proxy for
the
// owner's real-device eyeball). Run against the worktree site server (URL env, default :8123).
import { chromium } from "playwright";
import { rename } from "node:fs/promises";
import { mkdirSync } from "node:fs";

const URL = process.env.URL || "http://localhost:8123";
const HOLD = 1500;
mkdirSync("rec", { recursive: true });
const browser = await chromium.launch();

const errors = [];
const ctx = await browser.newContext({
  viewport: { width: 1280, height: 900 },
  locale: "en-US",
  recordVideo: { dir: "rec", size: { width: 1280, height: 900 } },
});
const page = await ctx.newPage();
page.on("console", (m) => { if (m.type() === "error") errors.push(m.text()); });
page.on("pageerror", (e) => errors.push("pageerror: " + e.message));

await page.goto(URL + "/own-model", { waitUntil: "networkidle" });
```

```

await page.waitForTimeout(HOLD);
await page.screenshot({ path: "ownmodel-en.png", fullPage: true });

// Switch to Kannada via the compact header switcher, then walk the three sections.
await page.selectOption("select[data-langsw]", "kn");
await page.waitForTimeout(HOLD);
const knHero = await page.locator("h1").first().innerText();
await page.screenshot({ path: "ownmodel-kn-hero.png" });
for (const id of ["#annotate", "#train", "#setup"]) {
  await page.locator(id).scrollIntoViewIfNeeded();
  await page.waitForTimeout(HOLD);
}
await page.screenshot({ path: "ownmodel-kn-full.png", fullPage: true });

// Switch to Hindi.
await page.evaluate(() => window.scrollTo(0, 0));
await page.selectOption("select[data-langsw]", "hi");
await page.waitForTimeout(HOLD);
const hiHero = await page.locator("h1").first().innerText();
await page.screenshot({ path: "ownmodel-hi-hero.png" });
await page.locator("#train").scrollIntoViewIfNeeded();
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "ownmodel-hi-full.png", fullPage: true });

const v = page.video();
await ctx.close();
await rename(await v.path(), "khelsutra-ownmodel-i18n-desktop.webm");

const KN = /[?~]/, HI = /[?~]/;
console.log("kn hero:", JSON.stringify(knHero));
console.log("hi hero:", JSON.stringify(hiHero));
console.log("kn hero in Kannada script:", KN.test(knHero));
console.log("hi hero in Devanagari script:", HI.test(hiHero));
console.log("console errors:", errors.length ? errors : "NONE");
await browser.close();
console.log("wrote khelsutra-ownmodel-i18n-desktop.webm + ownmodel-{en,kn-hero,kn-full,hi-hero,hi-full}.png");

```

136. user (2026-06-22T01:46:26.392Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\ownmodel-screencast.mjs (file state is current in your context ? no need to Read it back)

137. user (2026-06-22T01:46:46.697Z)

```

kn hero: "????? ???????????? ??????? ?????? ?? ?????????? ??????????????"
hi hero: "????? ?????? ?? ?????? ?????? ?? ??? ??? ???? ? ???? ???? ??"
kn hero in Kannada script: true
hi hero in Devanagari script: true
console errors: NONE
wrote khelsutra-ownmodel-i18n-desktop.webm + ownmodel-{en,kn-hero,kn-full,hi-hero,hi-full}.png
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

138. assistant (2026-06-22T01:47:00.301Z)

Render verified: kn/hi heroes are in-script, **zero console errors**, `data-i18n-html` applied (innerText shows translated span content). Let me eyeball the captured stills to confirm glyphs, bolding, and that code blocks stayed literal.

139. assistant (2026-06-22T01:47:07.972Z)

Kannada renders cleanly ? Noto glyphs, switcher shows "? ?????", translated hero/lead/pill, Latin tokens (rally-annotator, VLC, MIT) preserved, code block literal, no overflow. Let me check the Hindi full page (train/setup sections, code blocks, honest boxes).

140. assistant (2026-06-22T01:47:36.195Z)

Hindi renders perfectly too ? Devanagari throughout, the 2x2 moat grid, honest boxes, **code blocks stayed literal** (VLC paths, CSV, python all English), CTA translated, flyer autonyms preserved, clean layout. Both locales verified, zero console errors.

Let me stop the server and update the tracking doc.

141. user (2026-06-22T01:47:40.384Z)

server on :8123 stopped

142. user (2026-06-22T01:47:40.427Z)

```
157     ## 9. Definition of done
158     - [x] Automatic language negotiation ($6.5) is green ? N1/N3?N7 (SPA, jsdom) + N2
(hi) + N8 (static-site shim honors `Accept-Language`/?lang`, `server.test.js`), all in CI.
159     - [ ] Manual cross-check (owner machine): OS/browser set to Kannada and to Hindi
each render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner
eyeball ? pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts
in `khelsutra-screencast`/? `khelsutra-site-i18n-desktop.mp4` (site, kn) +
`khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`.)*)
160     - [x] `en + kn + hi` catalogs live and rendering on BOTH `web`/`SPA` and `site`/
marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3
(site), proven by render tests + a real-browser pass.
161     - [ ] Noto Sans Kannada + Devanagari render correctly ? owner eyeball on a real
machine. *(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the
owner's device check.)*
162     - [x] CI key-parity + no-bare-strings green; a stub locale flags every gap ?
`web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift`
guard.
163     - [x] Recording-education (capture + homepage gist) available in `kn` + `hi` ? A3
(#74), incl. a localized camera-placement diagram (A7, #76).
164     - [x] Non-tech UX baseline ? plain-language copy (A1/A6), mobile tap targets (A4) +
the decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only
filters (A9), honest today-vs-roadmap preserved through translation.
165     - [ ] $7 all rows ? (or explicitly deferred) ? flip Status ? DONE + run the engine
`DOC_STATUS.md` $2` archival checklist ? `git mv` to `docs/archives/`. *($7 is all ? except the
owner-gated, cross-repo B7 ? deferred. Holding the DONE flip on the two human gates above
(native-speaker review of the AI-drafted kn/hi + the owner font eyeball). Remaining engineering
follow-up: own-model body content is still English on kn/hi ? a separate content-translation
slice.)*
166
167     ## 10. References
168     Internal code anchors `[verified]`: web/package.json,
`web/src/{App.tsx,main.tsx,components/QueryBar.tsx,components/CompileResult.tsx,lib/query.ts}`;
`site/public/{index,capture,own-model}.html`, `site/server.js`, `site/src/assets.test.js`.
This repo's docs: `docs/PER_RALLY_SELECTION.md`, `docs/REQUEST_ACCESS_FORM.md`,
`docs/README.md`, `NEXT_STEPS.md`. Engine design docs (canonical): `badminton-highlight-inde
xer/docs/{I18N_PLAN.md,UI_PROPOSAL.md,VIDEO_RECORDING_GUIDELINES.md,PMF_MARKET_RESEARCH.md,PMF_F
IELD_SIGNALS.md,KHELSUTRA_PRODUCT_OVERVIEW.md,DOC_STATUS.md}`. External `[researched]`:
Unicode CLDR plural rules (kn/hi = one/other); react-i18next + i18next-icu; SIL Open Font
License 1.1; Google Noto Sans Kannada/Devanagari.
169
170     ---
171
172     ### Changelog
173     - `2026-06-21` ? created. Isolated the UX + Hindi/Kannada work into one tracked project
(owner directive). Grounded in a multi-agent research+verification pass (web/+site/ string maps,
Indic-l10n prior art, 5 adversarial verdicts). Decisions D1?D5 locked; 5 product/licensing
decisions surfaced as open; $7 tracker seeded with B1 as the recommended first slice.
174     - `2026-06-21` ? owner locked D6 (en+kn?hi) + D7 (OFL Noto carve-out) and
adopted D8 (SPA-first) + D9 (catalogs in khelsutra); only D-BACKEND-DEPTH remains open.
B1 greenlit ? ? in progress.
175     - `2026-06-21` ? B1 opened ? [#42](https://github.com/avidullu/khelsutra/pull/42):
```

SPA i18n scaffold (react-i18next + ICU + detector) + `en` catalog + language switcher + the SPA's first jsdom render tests. Verified typecheck/79-tests/build green + live in-browser (switcher persists, en-fallback). Doc/pointer PRs opened: khelsutra [#41](https://github.com/avidullu/khelsutra/pull/41), engine [#275](https://github.com/khelsutra/badminton-highlight-indexer/pull/275).

176 - `2026-06-21` ? **\$6.5 Testing strategy added (owner ask, #41):** a rigorous **automatic-negotiation matrix** (N1?N9) so a Kannada/Hindi **browser** auto-gets the respective version ? proven at the detection level now (B1), at the content level with the catalogs (B5/B6), on the static shim (B3), and by a manual font-render eyeball. Wired into the DoD (\$9). B1 (#42) gains the detection tests (N1/N3?N7).

177 - `2026-06-21` ? **A9 (#68) landed.** Localized tap-only filter controls (`TapFilters`: Sort/Length/Count) so a non-English-typing kn/hi/? user can filter without typing the English query syntax; each tap builds the same `ParsedQuery` the parser would (tap == type, test-pinned). The English example chips now show only in English. 173 web tests; reviewed via a 2-lens adversarial workflow. **Workstream A: A1/A4/A5/A8/A9 ?; remaining A3 (recording-edu kn/hi), A6/A7 (site), B3 (site trilingual).** *(Also note: MULTILINGUAL_EXPANSION Phase A ? es/da/id ? shipped #67, so the SPA now speaks 6 languages.)*

178 - `2026-06-21` ? **A8 (#63) landed.** Background-processing reassurance + status as icon+text chips (never icon-only): a new `StatusChip` + shared `Spinner`; IngestPanel processing shows a working chip + "safe to wait ? runs on the server" line and a ? "Couldn't process" chip on failure; CompileResult gains a "Stitching your reel?" building card + ?? status icons on the terminal card (now `aria-live`). 141 web tests green; reviewed via a 2-lens adversarial workflow (folded its aria-live + honest-copy findings). **Workstream A now: A1/A4/A5/A8 ?; remaining A9 (tap-only filters), A3 (recording-education kn/hi).**

179 - `2026-06-21` ? **A5 (#62) landed.** Friendly engine-error mapping unified across ALL SPA surfaces (ingest + build + rally-load) via a single `lib/errorText.ts` helper + a shared `errors.\*` catalog namespace: an `engine` failure shows the engine's own detail verbatim, everything else a localized line (`engineGeneric` last resort). No more raw `ApiError`/'HTTP 500' text; `build.failed`/'rallies.load_failed' logs gain `code`+'detail'. 136 web tests green; reviewed via a 2-lens adversarial workflow (folded its load-path consolidation nit).

180 - `2026-06-21` ? **A1 (#60) + A4 (#61) landed.** A1 = the plain-language `en` copy pass (de-jargon). A4 = the non-tech / phone-first pass: ?44px tap targets across the SPA (Tailwind `min-h-11`/'h-11'), enlarged parsed-pill + sample chips, and **hover-only `title=` text surfaced as visible DOM text** (the QueryBar "not available yet" reason + per-card shot-count confidence) ? a phone never shows `title=`. 128 web tests green; reviewed via a 3-lens adversarial workflow. **Still open in workstream A:** A5 (friendly engine-error map on the build path), A8 (background-processing reassurance / status chips), A9 (tap-only filters), A3 (recording-education kn/hi), B3 (site/ trilingual) + native review.

181 - `2026-06-21` ? **? SPA MILESTONE: fully trilingual (owner directive "take it to completion + screencast").** B2 (#45, full string extraction + key-parity/no-bare-strings CI) ? B4 (#46, self-host OFL Noto) ? B5 (#47, Kannada) ? B6 (#48, Hindi ? the extensibility proof) all merged. 99 web tests green incl. N1/N2 browser-detection + B5/B6 render + key-parity. **Playwright screencast** (`locale: kn-IN`): a Kannada-default browser auto-renders Kannada ? switch hi ? switch en, each with `` tracked (`khelsutra-i18n-screencast.mp4` + per-locale frames). kn/hi are **AI-drafted ? native review pending**. **Remaining for full \$9 DoD:** B3 (the `site`/' marketing surface), A3 + the UX A-items, native-speaker translation review.

182 - `2026-06-21` ? **B3 ([#70](https://github.com/avidullu/khelsutra/pull/70)) landed ? the marketing `site`/' is now i18n-wired, en-only content.** Implements **D-CATALOG-HOME**: catalogs hoisted to repo-root **`/locales`** (all 6 ? en/kn/hi + the merged es/da/id) as the single source of truth; the SPA re-points its imports there (Vite resolves the `.git` workspace root ? typecheck/168 web tests/build green). The dependency-free site gains its one build step ? `npm run copy:locales` mirrors `/locales` ? `site/public/locales`/' (predeploy` hook) + a \*\*drift-guard test\*\*. New \*\*`site/public/i18n.js`\*\* ? a ~110-LOC vanilla `t(key,vars)` + `data-i18n` walker with ICU-lite interpolation/plurals via `Intl.PluralRules` (mirrors i18next for the 2-form site languages); a \*\*persistent en/kn/hi switcher\*\* on `index`/'capture`/'own-model`; and \*\*`server.js` Accept-Language negotiation\*\* matching the SPA EXACTLY (persisted cookie ? `?lang=` ? `Accept-Language`/navigator ? en; missing key ? en, never a raw key). Tests: shim unit test + drift guard + extended `assets`/'`server` tests + the \*\*\$6.5 N8\*\* negotiation suite ? \*\*62 site tests green\*\*; real-browser smoke (switch ? persist ? reload). kn/hi \*marketing\* translation is the next effort (\*\*A3\*\*). ? \*\*Concurrency note:\*\* built in an isolated `git worktree` because a sibling **A9** session held uncommitted catalog WIP in the shared checkout ? never clobbered.

183 - `2026-06-22` ? **A3 ([#74](https://github.com/avidullu/khelsutra/pull/74)) landed ? the marketing `site`/' recording-education + marketing copy now render in kn + hi.** Translated the homepage "Record it right" gist + the full 1-page capture checklist + the existing `site.\*`

copy to ****Kannada + Hindi**** (~40 new ``site.record.*`/`site.capture.*`` keys; en-authored, kn/hi translated, es/da/id en-seeded ? key-parity green). The shim gains a *****data-i18n-html***** form so inline ``<b>`` emphasis survives translation; ****Noto Sans Kannada + Devanagari**** bundled via Google Fonts on all 3 pages (+ ``--font`` fallback) so kn/hi render without tofu. Translations ****AI-drafted ? adversarially verified**** by a 6-agent workflow (meaning/fluency/integrity × kn/hi; 0 issues in the A3 keys) and a 4-lens code review (folded its a11y findings ? switcher group ``aria-label`` now localized via ``lang.label``, default ``aria-pressed`` for the no-JS baseline ? and 3 test-coverage findings incl. a byte-for-byte HTML?en-catalog drift test). ****Web 173 + site 68 green****; real-browser check (kn capture page renders Kannada, ``<b>`` preserved, no console errors). kn/hi remain ****native-review-pending**** (font glyphs = owner eyeball gate). The full-catalog audit also surfaced pre-existing ****B5/B6 SPA-console**** translation bugs (brand transliteration, "engine"/"server" jargon, a code-token leak, over-Sanskritized Hindi) ? flagged as a separate follow-up.

184 - `2026-06-22` ? ****A6 ([#75](https://github.com/avidullu/khelsutra/pull/75))** landed ? plain-language Request-Access GPU/storage questions. ****De-jargoned the intimidating form copy** ("GPU machine that could process video locally" ? "a powerful computer that could process videos on its own"; dropped the bare "(S3/GCS)") and added a ****GPU reassurance**** ("No worries if not ? we can run it in the cloud for you"), so a non-technical coach/parent isn't scared off. Wired via the shim (``site.join.*``, ``data-i18n`` spans that preserve the radio/checkbox ``<input>``s), translation-ready (en for now; the form's kn/hi is a later increment). The ****backend enum contract is unchanged**** (field names + every ``has_gpu`/`storage`` value preserved ? server-validated). Tests: a de-jargon + reassurance + contract-intact assertion, and the A3 HTML?en-catalog drift test auto-covers the new keys. Site 69 + web 173 green.

185 - `2026-06-22` ? ****A7 ([#76](https://github.com/avidullu/khelsutra/pull/76))** landed ? camera-placement diagram on the capture page. ****Added an accessible inline SVG**** (``role="img"`` + localized ``<title>``) side-view showing the load-bearing placement cues a coach can't get from text alone: the ****elevated camera behind the baseline****, the ****~30° downward tilt****, and the ****full-court field-of-view cone**** (players within frame). A numbered ??? legend (HTML, so it wraps) maps the markers to the rules and is localized ****en/kn/hi**** (``site.capture.diagram.*``, reusing the A3 capture terms) ? consistent with the now-trilingual capture page. The text "Place the camera" step remains (the diagram complements it). Tests: a diagram-structure + accessible-``<title>`` + localized-legend assertion; kn/hi in-script check incl. ``diagram.camera``; the A3 drift test auto-covers the new keys; site 70 + web 173 green. ****Workstream A is now A1/A3/A4/A5/A6/A7/A8/A9 ?**** (remaining: A2 WhatsApp share; the B5/B6 SPA-console native-review pass; full native review).

186 - `2026-06-22` ? ****A2 ([#82](https://github.com/avidullu/khelsutra/pull/82))** landed ? localized WhatsApp share (the last open \$7 row). ****SPA `CompileResult` done-state + the site's post-signup reveal each offer a localized "Share on WhatsApp" CTA that opens `wa.me` with a pre-filled message (client-only; `rel=noopener`).** SPA ``result.share`/`result.shareText`` translated in all 6 locales; the site reveal (injected after sign-up, outside the static ``data-i18n`` walk) localizes via a new ****`window.KhelSutra.t` shim bridge**** (``site.reveal.*``, en/kn/hi real + es/da/id seeded). Verified in-browser: the kn reveal renders "? WhatsApp ????? ??????" + a Kannada message. Web 215 + site 72 green. ****\$7 is now all ? except the owner-gated, cross-repo B7**** (engine backend l10n ? deferred). Remaining for the DoD: native-speaker review of the AI-drafted kn/hi + the owner's font-glyph eyeball.

187 - `2026-06-22` ? ****UI/UX header pass ([#83](https://github.com/avidullu/khelsutra/pull/83)).**** A 3-lens design critique + a deep Playwright layout test (all pages × {1280, 390} × {en, hi/kn}) confirmed the home header ****overflowed on mobile**** ? the 3 always-visible language pills pushed the "Request access" CTA off-screen (worse in kn). Replaced the pills with a ****compact `? <select>` switcher**** on all three pages (shows the current language, can't overflow, one tap target, accessible, consistent), added wrap/``overflow-x`` safety, and localized the ****home hero headline**** (``site.hero.title``, the last big English string on the kn/hi home page) via ``data-i18n-html``. Shim now reflects the locale in ``select[data-langsw]`` + listens for ``change``. ****Zero horizontal overflow on all 12 page/viewport/locale combos****; web 215 + site 72 green. Screenshots (desktop kn journey + mobile header) saved to ``khelsutra-screenshot/``.

188 - `2026-06-22` ? ****? Multilingual chapter ? effectively complete (pending human gates).**** \$7 is ****all ? except B7**** (assessed: significant cross-repo ****engine**** backend-i18n in Python with no existing infra + owner-gated ****D-BACKEND-DEPTH**** ? kept deferred). Both surfaces are trilingual end-to-end (SPA en/kn/hi + es/da/id; site en/kn/hi), non-tech-friendly, and the ****sister repo `rally-annotator` is also localized (kn/hi/es/da/id/te)**** ? so the coach's journey ****annotator ? site ? Studio**** is consistent in their language. ****What gates archival:**** (1) a native-speaker review of the AI-drafted kn/hi catalogs (site + SPA), (2) the owner's font-glyph eyeball on a real Kannada/Hindi device, (3) a small remaining slice ? ``own-model`` body content is still English on kn/hi. Do not ``git mv`` to ``docs/archives/`` until (1)+(2) clear.

143. assistant (2026-06-22T01:48:30.598Z)

Server stopped (exit 127 = the kill). Both locales render with zero console errors. Now let me verify the worktree git state before committing (explicit paths only, per the branching-safety convention).

144. user (2026-06-22T01:48:34.803Z)

```
=== branch + HEAD (must be mine) ===
feat/own-model-kn-hi
5e5a2ac docs(friendly-multilingual): close out the chapter (§9 DoD + UI/UX + B7 deferred) (#84)
=== commits on top of origin/master (should be NONE yet) ===
=== status (porcelain) ===
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/public/own-model.html
M site/src/assets.test.js
M site/src/i18n.shim.test.js
M web/src/i18n/catalog-invariants.test.ts
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

145. assistant (2026-06-22T01:48:55.333Z)

Clean ? exactly the 16 expected files (no helpers, no node_modules, package-lock untouched), branch rides only on origin/master. Let me stage explicit paths and make the implementation commit.

146. user (2026-06-22T01:49:03.714Z)

```
=== staged ===
locales/da/common.json
locales/en/common.json
locales/es/common.json
locales/hi/common.json
locales/id/common.json
locales/kn/common.json
site/public/locales/da/common.json
site/public/locales/en/common.json
site/public/locales/es/common.json
site/public/locales/hi/common.json
site/public/locales/id/common.json
site/public/locales/kn/common.json
site/public/own-model.html
site/src/assets.test.js
site/src/i18n.shim.test.js
web/src/i18n/catalog-invariants.test.ts
=== after commit ===
f7f6470 feat(site): localize own-model body content to kn/hi
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

147. assistant (2026-06-22T01:49:08.398Z)

Committed (f7f6470, rides only on origin/master). Let me push the branch and open the PR.

148. user (2026-06-22T01:49:11.653Z)

```
remote: Create a pull request for 'feat/own-model-kn-hi' on GitHub by visiting:
remote:      https://github.com/avidullu/khelsutra/pull/new/feat/own-model-kn-hi
remote:
branch 'feat/own-model-kn-hi' set up to track 'origin/feat/own-model-kn-hi'.
To https://github.com/avidullu/khelsutra.git
 * [new branch]      feat/own-model-kn-hi -> feat/own-model-kn-hi
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

149. user (2026-06-22T01:49:32.785Z)

```
https://github.com/avidullu/khelsutra/pull/86
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

150. assistant (2026-06-22T01:49:42.550Z)

PR opened: [#86](https://github.com/avidullu/khelsutra/pull/86). Now let me record it in the tracking doc (update the §9 follow-up note + append a changelog entry), then commit it to the PR.

151. user (2026-06-22T01:49:47.784Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

152. user (2026-06-22T01:50:05.969Z)

The file C:\Users\avidu\Projects\ks-ownmodel-i18n\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

153. user (2026-06-22T01:50:14.347Z)

```
To https://github.com/avidullu/khelsutra.git
 f7f6470..afc4c9a  feat/own-model-kn-hi -> feat/own-model-kn-hi
=== branch commits vs origin/master ===
afc4c9a docs(friendly-multilingual): record own-model kn/hi localization (#86)
f7f6470 feat(site): localize own-model body content to kn/hi
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

154. assistant (2026-06-22T01:50:20.333Z)

Both commits pushed (rides only on origin/master). PR #86 is complete. Now let me watch CI and merge on green. Let me check the initial check status.

155. user (2026-06-22T01:50:44.087Z)

```
site    pass    15s
https://github.com/avidullu/khelsutra/actions/runs/2792466597/job/82624686562
Workers Builds: hidden-king-khelsutra  pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/266ce409-8856-49c8-9338-9b80a4b8c1e2
web     pending 0
https://github.com/avidullu/khelsutra/actions/runs/2792466597/job/82624686593
---
{"mergeable":"MERGEABLE","state":"UNSTABLE"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

156. assistant (2026-06-22T01:51:05.781Z)

site ? already. web + Cloudflare Workers build pending. Let me watch the checks to completion.

157. user (2026-06-22T01:51:07.780Z)

```
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/266ce409-8856-49c8-9338-9b80a4b8c1e2
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27924665977/job/82624686562
web pass 41s
https://github.com/avidullu/khelsutra/actions/runs/27924665977/job/82624686593
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/266ce409-8856-49c8-9338-9b80a4b8c1e2
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27924665977/job/82624686562
web pass 41s
https://github.com/avidullu/khelsutra/actions/runs/27924665977/job/82624686593
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

158. assistant (2026-06-22T01:51:18.100Z)

All three checks green ? **site** ?, **web** ?, Cloudflare Workers build ?. Per the directive, merging on green CI. The repo uses squash-merge (PR-number-suffixed titles). My branch carries only my 2 commits.

159. user (2026-06-22T01:51:23.989Z)

```
=== pre-merge: only my commits on top of origin/master ===
afc4c9a docs(friendly-multilingual): record own-model kn/hi localization (#86)
f7f6470 feat(site): localize own-model body content to kn/hi
=== merge ===
failed to run git: fatal: 'master' is already used by worktree at
'C:/Users/avidu/Projects/khelsutra'
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

160. assistant (2026-06-22T01:51:31.133Z)

The squash-merge likely went through on GitHub ? the error is from `gh`'s **local** branch cleanup (it tried to switch this worktree to **master**, which is reserved by another worktree). Let me verify the PR actually merged.

161. user (2026-06-22T01:51:35.170Z)

```
{"mergeCommit":"17242a9937bd3b3083a6ef2461c311c5a44b3092","mergedAt":"2026-06-
22T01:51:22Z","state":"MERGED"}
--- origin/master now ---
17242a9 feat(site): localize own-model body content to kn/hi (#86)
7b04f02 deploy(kit): align with the live-verified droplet deploy (+ the gemini-default fix)
(#85)
5e5a2ac docs(friendly-multilingual): close out the chapter ($9 DoD + UI/UX + B7 deferred) (#84)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

162. assistant (2026-06-22T01:51:48.869Z)

PR #86 is **MERGED** (squash commit `17242a9`). Note origin/master also gained **#85** from a sibling session between my branch-point and merge ? but I verified pre-merge that my branch carried only my 2 commits, so GitHub squashed only mine; no sibling work was absorbed (the exact incident the convention guards against, avoided). Let me clean up the remote branch and worktree.

163. user (2026-06-22T01:51:57.500Z)

```
=== remote branch still there? ===
afc4c9a60e14f8e29557bae62dad3db734c6226c refs/heads/feat/own-model-kn-hi
```

```
To https://github.com/avidullu/khelsutra.git
- [deleted]          feat/own-model-kn-hi
=== remove worktree ===
=== worktrees now ===
C:/Users/avidu/Projects/khelsutra 7b04f02 [master]
```

164. assistant (2026-06-22T01:52:21.056Z)

Cleanup complete ? remote branch deleted, worktree removed, main checkout untouched (still the sibling's `master`; I left it read-only per convention). Now let me refresh the session handoff (a merged PR is a checkpoint).

165. user (2026-06-22T01:52:21.710Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22, after A2 (#82) + the UI/UX header pass (#83) + the chapter
closeout (#84) merged._
4
5      ## You are here ? chapter effectively COMPLETE (pending human gates)
6      $7 of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo
B7** (deferred). Both surfaces are trilingual end-to-end and non-tech-friendly:
7      - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: en/kn/hi ? B3
shim/switcher/negotiation, A3 recording-education + marketing copy in kn/hi (Noto bundled), A6
plain-language access form, A7 camera-placement diagram, **A2 WhatsApp share** (#82), and the
**UI/UX header pass** (#83): the 3 language pills ? a compact `<select>` (fixed the mobile
header overflow; zero horizontal overflow across all 12 page/viewport/locale combos) + the home
hero headline localized.
8      - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77** ; web
coverage floor added in **#80**.
9      - Sister repo **rally-annotator is also localized (kn/hi/es/da/id/te)** ? the journey
annotator ? site ? Studio is consistent in the user's language.
10
11     ## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)
12     1. **Native-speaker review** of the AI-drafted kn/hi catalogs (site + SPA) ? the
standing guardrail before a wide public launch.
13     2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
Proxy screencasts: `C:/Users/avidu/Projects/khelsutra-screencast/khelsutra-
site-i18n-desktop.mp4` + `khelsutra-i18n-screencast.mp4`.
14
15     ## Open engineering follow-ups (small)
16     - **own-model body content** is still English on kn/hi (only its switcher + request link
are localized) ? a separate content-translation slice (like A3).
17     - **Access form kn/hi** ? A6 left it English (`site.join.*` en-seeded), translation-
ready.
18     - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
19     - Minor: `site.*` adds ~27KB to the SPA bundle (could split to a site-only catalog);
ratchet web coverage thresholds as `App.tsx` gains tests.
20
```

166. user (2026-06-22T01:52:27.133Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

167. user (2026-06-22T01:52:34.159Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

168. user (2026-06-22T01:52:43.306Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

169. user (2026-06-22T01:52:54.263Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

170. assistant (2026-06-22T01:53:23.800Z)

Done. The own-model kn/hi localization is **merged to master** ([#86](https://github.com/avidullu/khelsutra/pull/86), squash `17242a9`) with full A3-style diligence.

What shipped

The developer "Annotate your footage / train your own model" page (`site/public/own-model.html`) ? previously English-only on kn/hi except its switcher + request link ? now renders **fully in-language**:

- **52 new `site.ownModel.\*` keys** wired via `data-i18n`/`data-i18n-html` (hero, annotate/train/setup steps, the moat grid, both honest-framing fences, "what this is not", CTA, footer; inline `**<i>/<a>/<code>/<span>**` preserved).
- **Deliberately literal:** `pre`/CLI blocks, file paths, the `ending\_reason` enum, brand/tool tokens (KhelSutra/VLC/rally-annotator/MIT/GPU/LLM), and the VLC UI button labels shown in the screenshots. Every honest caveat kept intact.
- **en authored byte-for-byte** (jsdom-extracted ? the A3 drift guard validates it); es/da/id en-seeded; **kn/hi AI-drafted** ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise via a 10-agent workflow (16 kn + 10 hi findings folded). The shipped `requestAccess` translation was preserved.

Verified (the pre-LGTM bar, run locally)

- **site `npm test`**: 75 ? (incl. the byte-for-byte drift guard) . **web**: 215 ? . typecheck clean . **coverage** 93.4/88.1/85.9% ? floor (92/87/84), no regression . build ?.
- New tests: own-model body-wiring assertion + kn/hi in-script render check + a tag-multiset/literal-token integrity guard.
- **Real-browser pass** (kn + hi render with Noto glyphs, `**<b>**` bold preserved, code blocks literal, **zero console errors**); screencast `khelsutra-ownmodel-i18n-desktop.webm` + per-locale stills in `../khelsutra-screencast/`.
- **CI green on the PR**: site ?, web ?, Cloudflare Workers build ?.

Notable

- Built in an isolated worktree off `origin/master` ? vindicated: the shared checkout churned to `deploy/kit-live-verified` *and* a sibling PR (#85) merged mid-session. I confirmed my branch carried only my 2 commits before the squash, so no sibling work was absorbed.
- One justified test-guard tweak: the web `catalog-invariants` ```-leak rule (from #77) is scoped to allow inline code only on `site.ownModel.*` (the SPA-console leak guard stays intact everywhere else).`

Still open (unchanged ? both human/owner gates)

The S9 DoD is **not** flipped to DONE and nothing is archived. The two standing gates remain: **native-speaker review** of the AI-drafted kn/hi, and your **font-glyph eyeball** on a real device. With #86, **no engineering gap remains** before those gates (access-form kn/hi is now the largest remaining English-on-kn/hi surface, but it's a separate, optional A3-style slice ? not a DoD blocker). Handoff + doc updated accordingly.

171. user (2026-06-22T01:55:51.786Z)

we should also add the new languages (dutch, thai etc.) to this drop down and make sure it works? Right now it only shows hi and kn

172. assistant (2026-06-22T01:56:50.195Z)

Before I touch anything, let me ground myself in the actual current state ? which locales exist, what each surface supports, and whether the "new languages" already have translated content or are English seeds. Master has moved (my #86 + a sibling's #85), so let me check the live state.

173. user (2026-06-22T01:56:53.476Z)

```
=== main checkout git state ===
?? .claude/
?? site/access.db
master
17242a9 feat(site): localize own-model body content to kn/hi (#86)
=== locales present (origin/master) ===
locales/da
locales/en
locales/es
locales/hi
locales/id
locales/kn
=== site shim SUPPORTED ===
12:export const SUPPORTED = ["en", "kn", "hi"]; // the trilingual marketing site (es/da/id are
SPA-only)
=== SPA supported langs ===
1:// i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
3:// Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4://   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5://   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in the
catalog,
6://     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7://   - one negotiation order shared with the marketing site (B3);
8://   - always-fallback to `en` so a missing translation degrades to English, never a raw key.
11:import LanguageDetector from "i18next-browser-languagedetector";
13:// Catalogs are HOISTED to repo-root /locales (D-CATALOG-HOME) ? the single source of truth
shared
14:// by this SPA and the marketing site's t() shim (tracker B3). Vite resolves the workspace
root via
15:// the repo `.git` marker, so importing the parent-dir /locales works in dev, build, and
vitest.
16:import enCommon from "../../locales/en/common.json";
17:import knCommon from "../../locales/kn/common.json";
18:import hiCommon from "../../locales/hi/common.json";
19:import esCommon from "../../locales/es/common.json";
20:import daCommon from "../../locales/da/common.json";
21:import idCommon from "../../locales/id/common.json";
23:// Supported locales: en/kn/hi foundation (FRIENDLY D6) + MULTILINGUAL_EXPANSION Phase A
(es/da/id,
24:// Latin, catalog-only). Anything else falls back to `en`.
25:export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
26:export type Locale = (typeof SUPPORTED_LOCALES)[number];
29:// ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker B3),
so a
30:// visitor's language choice carries across both surfaces.
33:// Catalogs live in repo-root /locales (D-CATALOG-HOME), consumed by both surfaces. `kn` +
`hi`
34:// shipped (B5/B6, AI-drafted ? native review pending). A missing key in any locale still
falls back
35:// to `en` ? the by-design invariant.
36:const resources = {
38:  kn: { common: knCommon },
39:  hi: { common: hiCommon },
40:  es: { common: esCommon },
```

174. assistant (2026-06-22T01:57:10.576Z)

Key finding before I do anything: there is **no Dutch or Thai** anywhere. Let me confirm exactly what each "extra" locale contains so I report this accurately.

175. user (2026-06-22T01:57:17.977Z)

```
=== are es/da/id site.* TRANSLATED or en-seeded? (compare to en) ===
es site.* keys: 129 | identical-to-en (en-seed): 129 | translated: 0
da site.* keys: 129 | identical-to-en (en-seed): 129 | translated: 0
id site.* keys: 129 | identical-to-en (en-seed): 129 | translated: 0
=== SPA app.title (proves es/da/id ARE translated in the console namespace) ===
es "Elige las jugadas para tu reel"
da "Vælg duellerne til din reel"
id "Pilih reli untuk reel kamu"
=== any nl/th/te anywhere? ===
(empty = none)
```

176. assistant (2026-06-22T01:58:09.644Z)

I dug into the actual state before doing anything, and the request rests on a mismatch worth surfacing:

What actually exists (``/locales``): ``en``, ``kn``, ``hi``, ``es`` (Spanish), ``da`` (**Danish**), ``id`` (Indonesian). There is **no Dutch** (``nl``) or Thai (``th``) anywhere ? I grepped the whole repo. ("Danish" and "Dutch" are easy to swap.)

Why the site dropdown is only en/kn/hi ? it's by design, not a bug:

- The **SPA console** strings *are* translated for es/da/id (e.g. es ``Elige las jugadas para tu reel``).

- But the **marketing-site namespace** (``site.*``, 129 keys ?

nav/hero/record/capture/join/ownModel/reveal) is **100% English-seeded** for es/da/id (0 of 129 translated). So if I just added them to the dropdown, picking "Español" would render the entire site in **English under a Spanish label** ? i.e. it wouldn't "work" in the sense you mean.

So "add them and make sure it works" really means: **translate the full marketing site into each added language** (the same A3/own-model-style AI-draft ? adversarial-verify pass), then wire the dropdown. That's a real, sizable slice ? and which languages to invest in is a product call, so I want to confirm rather than guess.

177. user (2026-06-22T03:16:56.396Z)

Your questions have been answered: "Which languages should the marketing-site dropdown offer? (Each added language needs its full site.* marketing copy translated ? 129 keys ? to render correctly, not just a dropdown entry.)"="Translate + add es/da/id". You can now continue with these answers in mind.

178. assistant (2026-06-22T03:17:56.704Z)

Got it ? translate the full marketing namespace into **es/da/id** and add them to the dropdown, bringing the site to parity with the SPA's 6 languages. No new locales, all Latin-script (no font work needed).

Let me set up a fresh isolated worktree off the updated origin/master and start node_modules copying.

179. user (2026-06-22T03:18:01.321Z)

```
Preparing worktree (new branch 'feat/site-es-da-id')
branch 'feat/site-es-da-id' set up to track 'origin/master'.
HEAD is now at 17242a9 feat(site): localize own-model body content to kn/hi (#86)
=== worktree state ===
17242a9 feat(site): localize own-model body content to kn/hi (#86)
(empty diff above = rides cleanly on origin/master)
```

180. assistant (2026-06-22T03:18:06.692Z)

Worktree ready at `ks-site-esdaid` (on 17242a9, includes the own-model merge). Let me copy node_modules in the background and compute the exact translation key set (the `site.\*` keys that kn actually translated ? so es/da/id reach the same coverage parity, leaving the intentionally-English `site.join` form as-is for all locales).

181. user (2026-06-22T03:18:10.280Z)

Command running in background with ID: bysslpf28. Output is being written to: C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bysslpf28.output. You will be notified when it completes. To check interim output, use Read on that file path.

182. user (2026-06-22T03:18:21.587Z)

```
total site.* keys: 129
kn-translated (=> translate for es/da/id): 115
kn-identical-to-en (leave en-seed for es/da/id too): 14

-- kn-identical keys (NOT translating these; parity with kn/hi) --
site.join.gpuLabel
site.join.gpuHint
site.join.gpuYes
site.join.gpuUnsure
site.join.gpuNo
site.join.gpuCloud
site.join.storageLabel
site.join.storageHint
site.join.storageGdrive
site.join.storageOnedrive
site.join.storageDropbox
site.join.storageBucket
site.join.storageLocal
site.join.storageUnsure
```

```
es already-translated among target set (should be 0): 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

183. assistant (2026-06-22T03:18:31.559Z)

The robocopy exit-1 is its success code again ? let me verify the modules landed. The key set is clear: ****115 `site.\*` keys to translate**** for each of es/da/id (the 14 `site.join` form keys stay English, matching kn/hi parity).

184. user (2026-06-22T03:20:01.138Z)

```
jsdom: /c/Users/avidu/Projects/ks-site-esdaid/site/node_modules/jsdom
OK
vitest: /c/Users/avidu/Projects/ks-site-esdaid/web/node_modules/vitest
OK
25M      /c/Users/avidu/Projects/ks-site-esdaid/site/node_modules
132M     /c/Users/avidu/Projects/ks-site-esdaid/web/node_modules
```

185. assistant (2026-06-22T03:20:16.937Z)

Modules ready. Let me build the translation payload ? the 115 en target keys plus each locale's existing SPA-console vocabulary as register reference (so "rally", "reel", "court" stay consistent with what's already shipped in es/da/id).

186. user (2026-06-22T03:20:23.991Z)

```
target keys: 115 | payload bytes: 14541
target keys with {placeholders}: 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```


187. assistant (2026-06-22T03:20:36.941Z)

115 keys, zero placeholders. Let me read the payload and launch the es/da/id translation workflow (same proven draft?3-lens-verify?revise pipeline, now per-locale across the three).

188. user (2026-06-22T03:20:37.531Z)

```
1      {"enSite":{"site.reveal.share":"Share on WhatsApp","site.reveal.shareText":"Check out
KhelSutra ? it turns a full badminton match into a clean highlights reel ?
kheIsutra.guru","site.nav.how":"How it works","site.nav.why":"Why it's
hard","site.nav.ownModel":"Own your model","site.nav.flyer":"Flyer","site.nav.roadmap":"Roadmap"
,"site.nav.faq":"FAQ","site.nav.requestAccess":"Request access","site.hero.title":"Every rally,
indexed. <span class=\\"hl\\">The dead time, gone.</span>","site.hero.eyebrow":"Invite-only alpha
· Bengaluru","site.hero.lead":"KhelSutra finds every rally in your session and strips out the
knock-ups, walks and gaps ? so a full match becomes a clean highlight reel you can watch and
download. No editing, no scrubbing.","site.hero.ctaPrimary":"Request alpha
access","site.hero.ctaHow":"See how it works","site.record.kicker":"Record it
right","site.record.title":"Five minutes of setup ? reliably great
reels","site.record.intro":"Highlight quality starts with the recording. Set the camera up once
like this and KhelSutra has everything it needs to find the
rallies.","site.record.goldenRuleLead":"The golden rule: one match, one court, in full frame ?
and don't move the camera.","site.record.goldenRuleRest":"A single court in frame gives the best
results today; busy multi-court footage is the hard case we're still
sharpening.","site.record.place.title":"Place the camera","site.record.place.body":"Behind
<b>one baseline</b>, elevated (a high tripod or a balcony), tilted down ~30° ? the <b>whole
court</b> in frame, players never
cropped.","site.record.settings.title":"Settings","site.record.settings.body":"<b>1080p+</b>,
landscape, <b>30 fps</b> for badminton (60 fps for table tennis). <b>Audio ON</b> ? the
shuttle's ?thwack? helps find rallies.","site.record.still.title":"Keep it
still","site.record.still.body":"Fixed tripod or mount. <b>No panning, no zooming</b> during
play ? a steady, full-court view is what the tool is tuned
for.","site.record.upload.title":"Record & upload","site.record.upload.body":"Even lighting,
then record the <b>whole session</b> and upload it as-is ? KhelSutra finds the rallies and does
the cutting.","site.record.checklistCta":"Full 1-page capture checklist
?","site.capture.diagram.title":"Side view: where the camera
goes","site.capture.diagram.camera":"Camera ? behind the baseline,
elevated","site.capture.diagram.angle":"Tilt ~30° down","site.capture.diagram.frame":"Whole
court in frame ? players never
cropped","site.capture.diagram.net":"Net","site.capture.title":"1-page capture
checklist","site.capture.intro":"Great highlights start with a steady, full-court recording.
Five minutes of setup makes a big difference to your reels.","site.capture.ruleLead":"The golden
rule: one match, one court, in full frame ? and don't move the
camera.","site.capture.ruleRest":"Multi-court footage is the hard case we're still sharpening; a
single court in frame gives the best results today.","site.capture.step1.title":"Place the
camera","site.capture.step1.b1":"Behind <b>one baseline</b>, elevated ? a high tripod, a few
metres up, or a balcony.","site.capture.step1.b2":"Tilt down about <b>30°</b>; keep the <b>whole
court</b> in frame with a little margin and net headroom.","site.capture.step1.b3":"Players
should never leave the
frame.","site.capture.step2.title":"Settings","site.capture.step2.b1":"<b>1080p or higher</b>,
shot in <b>landscape</b>.","site.capture.step2.b2":"<b>30 fps</b> for badminton/pickleball;
<b>60 fps</b> for table tennis.","site.capture.step2.b3":"<b>Audio ON</b> (don't mute) ? keep
the mic unobstructed, wind/noise reduction off.","site.capture.step3.title":"Keep it
still","site.capture.step3.b1":"Fixed tripod or mount.","site.capture.step3.b2":"<b>No panning,
no zooming</b> during play.","site.capture.step4.title":"Light &
record","site.capture.step4.b1":"Even indoor lighting; avoid backlight, glare and very dark
halls.","site.capture.step4.b2":"Record the <b>whole session</b> and upload it as-is ? KhelSutra
does the cutting.","site.capture.doTitle":"Do","site.capture.do1":"Fixed camera, full court,
behind the baseline","site.capture.do2":"1080p+, landscape, audio on","site.capture.do3":"One
match on one court","site.capture.dontTitle":"Avoid","site.capture.dont1":"Handheld or phone-in-
hand","site.capture.dont2":"Broadcast-style pans & zooming","site.capture.dont3":"Several courts
in one frame; very dark halls","site.capture.consent":"Please record adults with their okay.
Footage involving minors is never used to improve the tool and is never
published.","site.capture.questions":"Questions?","site.capture.printTip":"Tip: press Ctrl/Cmd +
P to print or save as PDF.","site.ownModel.requestAccess":"Request access
?","site.ownModel.heroTitle":"Annotate your footage. <span class=\\"hl\\">Train a model that's
```

yours.","site.ownModel.heroLead":"You can't train Gemini or GPT on your court footage. KhelSutra's direction is the inverse ? a small, <b style=\\"color:#EAF3EE\\">owned rally model where the moat is your consented dataset, on a commercially-clean, inspectable stack you control.", "site.ownModel.nav.home": "? KhelSutra home", "site.ownModel.nav.annotate": "Annotate", "site.ownModel.nav.train": "Train your own model", "site.ownModel.nav.setup": "Setup & use", "site.ownModel.sample": "? Want to see what KhelSutra produces? A real sample reel plays the moment you request access.", "site.ownModel.annotate.kicker": "Step 1 · real and shipping today", "site.ownModel.annotate.title": "Annotate your footage", "site.ownModel.annotate.pill": "live today", "site.ownModel.annotate.body": "rally-annotator is a free, open-source (MIT) VLC plugin that turns \\"watch a match\\" into golden labels. While you watch your own video in VLC, you mark each rally's start and end plus how the point ended; it writes one row per rally to a plain CSV next to your video. Your footage never leaves your machine. It covers five net-separated racquet sports (badminton, tennis, table tennis, pickleball, padel).", "site.ownModel.annotate.cap1": "Enable it once: VLC ? View ? Rally Annotator.", "site.ownModel.annotate.cap2": "Mark each rally's start/end + ending reason, then Save Rally.", "site.ownModel.annotate.flowLead": "The flow, per rally:", "site.ownModel.annotate.step1": "Mark START on the serve-contact frame (pause/scrub for accuracy).", "site.ownModel.annotate.step2": "Mark END when the shuttle is dead.", "site.ownModel.annotate.step3": "Pick an ending reason, optionally a shot count, then Save Rally ? one CSV row.", "site.ownModel.annotate.step4": "Fix anything with Edit / Delete / Undo; re-open the same video later to continue.", "site.ownModel.annotate.note": "It's a click-driven dialog (no marking hotkeys yet), and targets VLC 3.0.x.", "site.ownModel.train.kicker": "Step 2 · the moat", "site.ownModel.train.title": "Train your own model", "site.ownModel.train.pill": "open pipeline · in build", "site.ownModel.train.reassureTitle": "You don't have to train anything to start.", "site.ownModel.train.reassureBody": "KhelSutra runs on a ready-made default, so you get rally detection and reels out of the box ? nothing to set up. Training on your own footage (below) is an optional power-up: a model tuned to your courts, your angles, your halls.", "site.ownModel.train.intro": "For those who want it, your labels feed an owned rally model ? trained on your courts, your angles, your busy multi-court halls. The pipeline is open and inspectable:", "site.ownModel.train.moat.ownTitle": "You own it", "site.ownModel.train.moat.ownBody": "A model and dataset that are yours to keep and improve ? not rented inference.", "site.ownModel.train.moat.cleanTitle": "Commercially clean", "site.ownModel.train.moat.cleanBody": "MIT/Apache/BSD-only stack; we never train on a paid LLM's output.", "site.ownModel.train.moat.privateTitle": "Private & consented", "site.ownModel.train.moat.privateBody": "Footage stays yours; training use is explicit opt-in, never automatic.", "site.ownModel.train.moat.minorsTitle": "Minors protected", "site.ownModel.train.moat.minorsBody": "Footage involving minors is never used for training and never published.", "site.ownModel.train.honestTitle": "Read this honestly.", "site.ownModel.train.honestBody": "The labeling tool is real and shipping. The training pipeline is open and in active build ? today it's a developer CLI; the no-GPU path trains a pipeline-validation mock, and a real model needs a GPU. There is no \\"Train now\\" button yet, and we make no accuracy claim vs a paid LLM (there's no such benchmark). The promise here is ownership, licensing, privacy and consent ? not \\"more accurate than Gemini,\\" and not \\"one click to train.\\"", "site.ownModel.setup.kicker": "Step 3 · for power users", "site.ownModel.setup.title": "Setup & use", "site.ownModel.setup.install": "Install the plugin (VLC 3.0.x). Copy <code>rally_annotator.lua</code> into VLC's per-user Lua <code>extensions</code> folder (create it if missing), then VLC ? Tools ? Plugins and extensions ? <i>Reload extensions</i>, and enable it from <i>View ? Rally Annotator</i>:", "site.ownModel.setup.record": "Record per the one-page capture checklist (fixed tripod, full court, landscape, whole session) ? annotate in VLC ? you get <code><video>.rallies.csv</code>:", "site.ownModel.setup.reasons": "<code>ending_reason</code> is one of: <code>unknown</code> · <code>winner</code> · <code>forced_error</code> · <code>unforced_error</code> · <code>service_fault</code> · <code>let</code> · <code>other</code>. Times are decimal seconds; downstream tools read by column name.", "site.ownModel.setup.train": "Train (developer CLI). A GPU-free dry run validates the whole pipeline on a CPU mock; a real model needs a GPU:", "site.ownModel.setup.joinRule": "One join rule: keep the video byte-identical to what you annotated (don't re-encode after labeling) ? labels match videos by content hash.", "site.ownModel.not.kicker": "So expectations stay honest", "site.ownModel.not.title": "What this is not", "site.ownModel.not.i1": "Not a one-click trainer ? training is an offline CLI today.", "site.ownModel.not.i2": "Not in-browser ? labeling runs in VLC on your machine.", "site.ownModel.not.i3": "Not an accuracy claim vs Gemini/GPT ? no such

benchmark.", "site.ownModel.not.i4": "Shot-type, player and score detection are roadmap.", "site.ownModel.cta.title": "Want in?", "site.ownModel.cta.button": "Request alpha access", "site.ownModel.foot.flyer": "Academy flyer:", "site.ownModel.foot.mark": "Reels carry a \"Generated by Khelsutra.guru\" mark.\"}, \"ref\": {\"es\": {\"app\": {\"badge\": \"elige tus jugadas · alfa\", \"title\": \"Elige las jugadas para tu reel\", \"intro\": \"Filtra por duración de la jugada ? p. ej. <i>?las 15 más largas?</i> ? y luego ajusta tocando las tarjetas. Todo empieza seleccionado; solo quita las que no quieras.\"}, \"query_placeholder\": \"p. ej. over 10s · top 15 longest · shortest first\", \"query_support\": \"Filtrar por duración de la jugada es totalmente compatible. El conteo de golpes es <x>experimental</x> (en desarrollo).\", \"grid_rally\": \"Jugada {n}\", \"grid_long\": \"de duración\", \"grid_shots\": \"~{count} golpes · experimental\", \"ingest_title\": \"Procesar un video\", \"ingest_intro\": \"Apunta KhelSutra a un video y encontrará las jugadas por ti ? esto puede tardar unos minutos.\", \"result_ready\": \"Tu reel está listo\", \"footer_build\": \"Crear reel ({count})\", \"tap\": {\"title\": \"Toca para filtrar:\", \"longest\": \"Las más largas primero\", \"shortest\": \"Las más cortas primero\", \"over10\": \"Más de 10 segundos\", \"over20\": \"Más de 20 segundos\", \"top5\": \"Las 5 más largas\", \"top10\": \"Las 10 más largas\"}, \"mode_loaded\": \"Se encontraron {count} jugadas en tu video.\", \"lang\": {\"label\": \"Idioma\", \"en\": \"English\", \"kn\": \"????\", \"hi\": \"????\", \"es\": \"Español\", \"da\": \"Dansk\", \"id\": \"Bahasa Indonesia\"}}, \"da\": {\"app\": {\"badge\": \"vælg dine dueller · alfa\", \"title\": \"Vælg duellerne til din reel\", \"intro\": \"Filtrér efter duellens længde ? f.eks. <i>?de 15 længste?</i> ? og finjustér ved at trykke på kortene. Alt starter valgt; fjern blot dem, du ikke vil have.\"}, \"query_placeholder\": \"f.eks. over 10s · top 15 longest · shortest first\", \"query_support\": \"Filtrering efter duellens længde understøttes fuldt ud. Slagtælling er <x>eksperimentel</x> (under udvikling).\", \"grid_rally\": \"Duel {n}\", \"grid_long\": \"lang\", \"grid_shots\": \"~{count} slag · eksperimentel\", \"ingest_title\": \"Behandl en video\", \"ingest_intro\": \"Peg KhelSutra mod en video, så finder den duellerne for dig ? det kan tage et par minutter.\", \"result_ready\": \"Din reel er klar\", \"footer_build\": \"Lav reel ({count})\", \"tap\": {\"title\": \"Tryk for at filtrere:\", \"longest\": \"Længste først\", \"shortest\": \"Korteste først\", \"over10\": \"Over 10 sekunder\", \"over20\": \"Over 20 sekunder\", \"top5\": \"De 5 længste\", \"top10\": \"De 10 længste\"}, \"mode_loaded\": \"Fandt {count} dueller i din video.\", \"lang\": {\"label\": \"Sprog\", \"en\": \"English\", \"kn\": \"????\", \"hi\": \"????\", \"es\": \"Español\", \"da\": \"Dansk\", \"id\": \"Bahasa Indonesia\"}}, \"id\": {\"app\": {\"badge\": \"pilih reli kamu · alfa\", \"title\": \"Pilih reli untuk reel kamu\", \"intro\": \"Filter berdasarkan durasi reli ? mis. <i>?15 terpanjang?</i> ? lalu sesuaikan dengan mengetuk kartu. Semua dimulai terpilih; cukup hapus yang tidak kamu inginkan.\"}, \"query_placeholder\": \"mis. over 10s · top 15 longest · shortest first\", \"query_support\": \"Memfilter berdasarkan durasi reli sepenuhnya didukung. Hitungan pukulan masih <x>eksperimental</x> (dalam pengembangan).\", \"grid_rally\": \"Reli {n}\", \"grid_long\": \"durasi\", \"grid_shots\": \"~{count} pukulan · eksperimental\", \"ingest_title\": \"Proses video\", \"ingest_intro\": \"Arahkan KhelSutra ke sebuah video dan ia akan menemukan reli untukmu ? ini bisa memakan beberapa menit.\", \"result_ready\": \"Reel kamu siap\", \"footer_build\": \"Buat reel ({count})\", \"tap\": {\"title\": \"Ketuk untuk memfilter:\", \"longest\": \"Terpanjang dulu\", \"shortest\": \"Terpendek dulu\", \"over10\": \"Lebih dari 10 detik\", \"over20\": \"Lebih dari 20 detik\", \"top5\": \"5 terpanjang\", \"top10\": \"10 terpanjang\"}, \"mode_loaded\": \"Ditemukan {count} reli di video kamu.\", \"lang\": {\"label\": \"Bahasa\", \"en\": \"English\", \"kn\": \"????\", \"hi\": \"????\", \"es\": \"Español\", \"da\": \"Dansk\", \"id\": \"Bahasa Indonesia\"}}}}

189. assistant (2026-06-22T03:20:57.221Z)

The reference gives each language's established vocabulary (rally ? es \"jugada\", da \"duel\", id \"reli\"). Now let me launch the es/da/id translation workflow ? same draft?verify?revise pipeline, with the defensive args-parse built in this time.

190. user (2026-06-22T03:21:30.758Z)

Workflow launched in background. Task ID: wtc756or9
 Summary: AI-draft + adversarially verify es/da/id translations of the full marketing site (site.* namespace)
 Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_31ab4530-b3b
 Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js
 (Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: \"C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js\"} to iterate without resending the script.)

Run ID: wf_31ab4530-b3b

To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js", resumeFromRunId: "wf_31ab4530-b3b"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

191. assistant (2026-06-22T03:21:38.432Z)

I passed a placeholder instead of the real payload. The script's defensive arg-parse is correct; I just need to re-invoke with the actual payload. Let me re-run via scriptPath with the real args.

192. user (2026-06-22T03:22:36.928Z)

Workflow launched in background. Task ID: wf1rm0b34

Summary: AI-draft + adversarially verify es/da/id translations of the full marketing site (site.* namespace)

Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_4b0f398f-c8a

Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js

(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath:

"C:\Users\avidu\claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js"} to iterate without resending the script.)

Run ID: wf_4b0f398f-c8a

To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-site-esdaid-wf_31ab4530-b3b.js", resumeFromRunId: "wf_4b0f398f-c8a"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

193. assistant (2026-06-22T03:23:02.829Z)

Workflow running with the real payload now (3 drafters ? 9 verifiers ? revisers). While it translates, let me do the independent wiring ? the dropdown options, shim `SUPPORTED`, and `server.js` locales. Let me inspect the exact switcher markup across the three pages first.

194. user (2026-06-22T03:23:04.823Z)

=== index.html switcher ===

252: <option value="en" data-i18n="lang.en" lang="en">English</option>

253: <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>

254: <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>

=== capture.html switcher ===

75: <option value="en" data-i18n="lang.en" lang="en">English</option>

76: <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>

77: <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>

=== own-model.html switcher ===

86: <option value="en" data-i18n="lang.en" lang="en">English</option>

87: <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>

88: <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

195. assistant (2026-06-22T03:23:15.004Z)

Different indentation per page. Let me add the es/da/id options to each switcher (autonyms already exist as `lang.es/da/id` in the catalog).

196. user (2026-06-22T03:23:17.258Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

197. user (2026-06-22T03:23:19.567Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

198. user (2026-06-22T03:23:21.146Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

199. assistant (2026-06-22T03:23:24.747Z)

Need to read the new worktree's files first. Let me read the switcher regions of all three.

200. user (2026-06-22T03:23:25.691Z)

```
249         </nav>
250         <div class="nav-right">
251             <label class="langsw"><span class="langsw-globe" aria-
hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
252                 <option value="en" data-i18n="lang.en" lang="en">English</option>
253                 <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
254                 <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
255             </select></label>
256             <a class="btn btn-dark" href="#join" data-i18n="site.nav.requestAccess">Request
access</a>
```

201. user (2026-06-22T03:23:26.623Z)

```
72         <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
73         <h1 data-i18n="site.capture.title">1-page capture checklist</h1>
74         <label class="langsw"><span class="langsw-globe" aria-hidden="true">?</span><select
data-langsw aria-label="Language" data-i18n="lang.label" data-i18n-attr="aria-label">
75             <option value="en" data-i18n="lang.en" lang="en">English</option>
76             <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
77             <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
78         </select></label>
79     </div>
```

202. user (2026-06-22T03:23:27.334Z)

```
84         <div class="nav-right">
85             <label class="langsw"><span class="langsw-globe" aria-
hidden="true">?</span><select data-langsw aria-label="Language" data-i18n="lang.label"
data-i18n-attr="aria-label">
86                 <option value="en" data-i18n="lang.en" lang="en">English</option>
87                 <option value="kn" data-i18n="lang.kn" lang="kn">?????</option>
88                 <option value="hi" data-i18n="lang.hi" lang="hi">?????</option>
89             </select></label>
```

203. assistant (2026-06-22T03:23:31.260Z)

Now I have exact context. Let me add the es/da/id options to all three switchers:

204. user (2026-06-22T03:23:33.702Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

205. user (2026-06-22T03:23:36.027Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\public\capture.html has been updated

successfully. (file state is current in your context ? no need to Read it back)

206. user (2026-06-22T03:23:38.335Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

207. assistant (2026-06-22T03:23:44.626Z)

All three switchers wired. Now the shim `SUPPORTED` and `server.js` `SITE\_LOCALES`. Let me read and update both.

208. user (2026-06-22T03:23:45.627Z)

```
12     export const SUPPORTED = ["en", "kn", "hi"]; // the trilingual marketing site (es/da/id
are SPA-only)
```

209. user (2026-06-22T03:23:46.239Z)

```
39     const SITE_LOCALES = ["en", "kn", "hi"];
```

210. user (2026-06-22T03:23:51.428Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\public\i18n.js has been updated successfully. (file state is current in your context ? no need to Read it back)

211. user (2026-06-22T03:23:52.502Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\server.js has been updated successfully. (file state is current in your context ? no need to Read it back)

212. assistant (2026-06-22T03:24:13.673Z)

Shim + server updated. Now the structural tests that pin the 3-locale set need updating (these are translation-independent). Let me read the relevant test regions in the worktree.

213. user (2026-06-22T03:24:14.629Z)

```
23     test("region subtags normalize and unsupported degrades to en (never a locale we can't
serve)", () => {
24         assert.equal(negotiate({ nav: ["hi-IN"] }), "hi", "hi-IN -> hi");
25         assert.equal(negotiate({ nav: ["ta-IN"] }), "en", "Tamil (unsupported) -> en");
26         assert.equal(negotiate({ stored: "es" }), "en", "es is SPA-only ? the trilingual site
degrades it to en");
27         assert.deepEqual([...SUPPORTED], ["en", "kn", "hi"]);
28         assert.equal(DEFAULT, "en");
29     });
```

214. user (2026-06-22T03:24:15.320Z)

```
192     test("every localizable page has a persistent, compact en/kn/hi language <select>
switcher", () => {
193         for (const f of I18N_PAGES) {
194             const html = read(f);
195             // Compact dropdown (a single <select>, not 3 always-visible pills) so the header
can't overflow.
196             assert.match(html, /class="langsw"/, `${f} is missing the language switcher`);
197             assert.match(html, /<select data-langsw[^>]*aria-label="Language"/, `${f} switcher
must be a labelled <select data-langsw>`);
198             for (const lang of ["en", "kn", "hi"]) {
199                 assert.match(html, new RegExp(`<option value="${lang}"`), `${f} switcher lacks the
${lang} option`);
200             }
```

```

201      // The option labels are driven by the SHARED catalog (lang.*) ? proves cross-
surface consumption.
202      assert.match(html, /<option value="kn" data-i18n="lang\.kn"/, `${f} switcher option
isn't wired to the shared catalog (lang.kn)`);
203      // The Kannada/Hindi autonoms are present in their own scripts (Noto/ system-font
fallback renders them).
204      assert.match(html, /?????/, `${f} switcher lacks the Kannada autonym`);
205      assert.match(html, /?????/, `${f} switcher lacks the Hindi autonym`);
206    }
207  });

```

215. user (2026-06-22T03:24:21.469Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

216. user (2026-06-22T03:24:33.876Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

217. assistant (2026-06-22T03:24:39.968Z)

Let me run the site suite to confirm the wiring is structurally green and catch any other test that assumed 3 locales (translations not applied yet, so pages still render English under es/da/id ? structural tests should pass).

218. user (2026-06-22T03:24:42.854Z)

```

? tests 75
? pass 75
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

219. assistant (2026-06-22T03:24:58.951Z)

All 75 site tests green with the dropdown wiring (no other test assumed 3 locales). Now I'll wait for the translation workflow. Meanwhile, let me pre-stage the apply script for the es/da/id translations.

220. assistant (2026-06-22T03:25:09.236Z)

```

// One-off authoring helper (NOT shipped): merge the workflow's es/da/id translations into the
catalogs.
// Input: site/scripts/_esdaid_translations.json = { es:{"site.<dotted>":value,...}, da:{...},
id:{...} }.
// Target set = the site.* keys kn translated (so es/da/id reach the same coverage parity); the
14
// site.join.* form keys stay English in EVERY locale (A6 deferred) and are intentionally
untouched.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const flat = (o, p = "") => Object.entries(o).reduce((a, [k, v]) => {
  const key = p ? `${p}.${k}` : k;
  if (v && typeof v === "object" && !Array.isArray(v)) Object.assign(a, flat(v, key)); else
a[key] = String(v);
  return a;
}, {});

const en = load("en"), kn = load("kn");
const ef = flat(en.site, "site"), kf = flat(kn.site, "site");

```

```

const EXPECTED = Object.keys(ef).filter((k) => kf[k] !== ef[k]); // 115 keys kn translated

const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_esdaid_translations.json"),
"utf8"));
let bad = 0;
for (const loc of ["es", "da", "id"]) {
  const flatT = T[loc];
  if (!flatT) { console.error(`MISSING locale ${loc}`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in flatT));
  const extra = Object.keys(flatT).filter((k) => !EXPECTED.includes(k));
  if (missing.length) { console.error(`${loc} MISSING ${missing.length}:`, missing.join(", "));
bad++; }
  if (extra.length) console.error(`${loc} ${extra.length} unexpected keys (ignored):`,
extra.join(", "));
  const cat = load(loc);
  for (const dotted of EXPECTED) {
    if (!(dotted in flatT)) continue;
    const parts = dotted.split(".");
    let o = cat; for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] = o[parts[i]] || {};
    o[parts[parts.length - 1]] = flatT[dotted];
  }
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: applied ${EXPECTED.filter((k) => k in flatT).length}/${EXPECTED.length}
keys`);
}
if (bad) { console.error("FAILED: incomplete translations"); process.exit(1); }
console.log(`OK: ${EXPECTED.length} target keys per locale (site.join.* left English in all
locales).`);

```

221. user (2026-06-22T03:25:09.262Z)

File created successfully at: C:\Users\avidu\Projects\ks-site-esdaid\site\scripts\apply-esdaid.mjs (file state is current in your context ? no need to Read it back)

222. assistant (2026-06-22T03:25:13.686Z)

Apply script staged. The wiring is done and green; everything else waits on the translation workflow. Let me confirm it's running healthily, then yield until it completes.

223. user (2026-06-22T03:25:16.588Z)

agent transcripts so far: 15

224. assistant (2026-06-22T03:25:26.660Z)

The es/da/id translation workflow is running healthily (15 agents spawned ? 3 drafters ? 9 verifiers ? revisers). I'll let it finish; the harness re-invokes me on completion.

Progress (worktree `ks-site-esdaid`, branch `feat/site-es-da-id` off origin/master @17242a9):

```

| Step | Status |
|---|---|
| Worktree isolated; node_modules seeded | ? |
| Dropdown wired: es/da/id `option`s on all 3 pages + shim `SUPPORTED`=6 + `server.js`
`SITE_LOCALES`=6 | ? |
| Structural tests updated (negotiate es?es, da?da, id?id; 6-option switcher) | ? |
| Site suite green with wiring (75 ?) | ? |
| Translate full `site.*` (115 keys) ? es/da/id, AI-draft ? 3-lens verify ? revise | ? running |
| Apply translations ? copy:locales ? content tests ? screencast ? PR | ? pending output |

```

Scope note I locked in: I'm translating the ****115 keys kn already covers**** (so es/da/id reach the same content parity), leaving the 14 `site.join` access-form keys English in every locale ? consistent with kn/hi, since A6 deferred form translation universally. Apply script is pre-

staged. Continuing automatically when the translations land.

225. user (2026-06-22T03:27:02.669Z)

```
<task-notification>
<task-id>wf1rm0b34</task-id>
<tool-use-id>toolu_01MtVbr32az88tN3ecMSurcm</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users\avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\wf1rm0b34.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "AI-draft + adversarially verify es/da/id translations of the full
marketing site (site.* namespace)" completed</summary>
<result>{"keysExpected":["site.reveal.share","site.reveal.shareText","site.nav.how","site.nav.wh
y","site.nav.ownModel","site.nav.flyer","site.nav.roadmap","site.nav.faq","site.nav.requestAcces
s","site.hero.title","site.hero.eyebrow","site.hero.lead","site.hero.ctaPrimary","site.hero.ctaH
ow","site.record.kicker","site.record.title","site.record.intro","site.record.goldenRuleLead","s
ite.record.goldenRuleRest","site.record.place.title","site.record.place.body","site.record.setti
ngs.title","site.record.settings.body","site.record.still.title","site.record.still.body","site.
record.upload.title","site.record.upload.body","site.record.checklistCta","site.capture.diagram.
title","site.capture.diagram.camera","site.capture.diagram.angle","site.capture.diagram.frame","
site.capture.diagram.net","site.capture.title","site.capture.intro","site.capture.ruleLead","sit
e.capture.ruleRest","site.capture.step1.title","site.capture.step1.b1","site.capture.step1.b2","
site.capture.step1.b3","site.capture.step2.title","site.capture.step2.b1","site.capture.step2.b2
","site.capture.step2.b3","site.capture.step3.title","site.capture.step3.b1","site.capture.step3
.b2","site.capture.step4.title","site.capture.step4.b1","site.capture.step4.b2","site.capture.do
Title","site.capture.do1","site.capture.do2","site.capture.do3","site.capture.dontTitle","site.c
apture.dont1","site.capture.dont2","site.capture.dont3","site.capture.consent","site.capture.que
stions","site.capture.printTip","site.ownModel.requestAccess","site.ownModel.heroTitle","site.ow
nModel.heroLead","site.ownModel.nav.home","site.ownModel.nav.annotate","site.ownModel.nav.train
","site.ownModel.nav.setup","site.ownModel.sample","site.ownModel.annotate.kicker","site.ownModel
.annotate.title","site.ownModel.annotate.pill","site.ownModel.annotate.body","site.ownModel.anno
tate.cap1","site.ownModel.annotate.cap2","site.ownModel.annotate.flowLead","site.ownModel.annota
te.step1","site.ownModel.annotate.step2","site.ownModel.annotate.step3","site.ownModel.annotate.
step4","site.ownModel.annotate.note","site.ownModel.train.kicker","site.ownModel.train.title","s
ite.ownModel.train.pill","site.ownModel.train.reassureTitle","site.ownModel.train.reassureBody",
"site.ownModel.train.intro","site.ownModel.train.moat.ownTitle","site.ownModel.train.moat.ownBod
y","site.ownModel.train.moat.cleanTitle","site.ownModel.train.moat.cleanBody","site.ownModel.tra
in.moat.privateTitle","site.ownModel.train.moat.privateBody","site.ownModel.train.moat.minorsTit
le","site.ownModel.train.moat.minorsBody","site.ownModel.train.honestTitle","site.ownModel.train
.honestBody","site.ownModel.setup.kicker","site.ownModel.setup.title","site.ownModel.setup insta
ll","site.ownModel.setup.record","site.ownModel.setup.reasons","site.ownModel.setup.train","site
.ownModel.setup.joinRule","site.ownModel.not.kicker","site.ownModel.not.title","site.ownModel.no
t.i1","site.ownModel.not.i2","site.ownModel.not.i3","site.ownModel.not.i4","site.ownModel.cta.ti
tle","site.ownModel.cta.button","site.ownModel.foot.flyer","site.ownModel.foot.mark"],"es":{"fin
al":{"site.reveal.share":"Compartir por WhatsApp","site.reveal.shareText":"Mira KhelSutra ?
convierte un partido completo de bádminton en un reel de jugadas destacadas limpio ?
khelsutra.guru","site.nav.how":"Cómo funciona","site.nav.why":"Por qué es
difícil","site.nav.ownModel":"Tu propio
modelo","site.nav.flyer":"Folleto","site.nav.roadmap":"Hoja de ruta","site.nav.faq":"Preguntas
frecuentes","site.nav.requestAccess":"Solicitar acceso","site.hero.title":"Cada jugada,
indexada. <span class=\"hl\">El tiempo muerto,
fuera.</span>","site.hero.eyebrow":"Alfa solo por invitación .
Bengaluru","site.hero.lead":"KhelSutra encuentra cada jugada de tu sesión y elimina los
calentamientos, las caminatas y las pausas ? para que un partido completo se convierta en un
reel de jugadas destacadas limpio que puedes ver y descargar. Sin edición ni
rebobinados.","site.hero.ctaPrimary":"Solicitar acceso al alfa","site.hero.ctaHow":"Ver cómo
funciona","site.record.kicker":"Grábalo bien","site.record.title":"Cinco minutos de
configuración ? reels geniales de forma fiable","site.record.intro":"La calidad de las jugadas
destacadas empieza con la grabación. Coloca la cámara así una sola vez y KhelSutra tendrá todo
lo que necesita para encontrar las jugadas.","site.record.goldenRuleLead":"La regla de oro: un
partido, una cancha, en cuadro completo ? y no muevas la
cámara.","site.record.goldenRuleRest":"Una sola cancha en cuadro da los mejores resultados hoy;
las grabaciones con varias canchas son el caso difícil que aún estamos
puliendo.","site.record.place.title":"Coloca la cámara","site.record.place.body":"Detrás de
<b>una línea de fondo</b>;, en alto (un trípode alto o un balcón), inclinada hacia
```

abajo ~30° ? la cancha completa en cuadro, los jugadores nunca recortados.", "site.record.settings.title": "Ajustes", "site.record.settings.body": "1080p; horizontal, 30 fps para bádminton (60 fps para tenis de mesa). Audio ACTIVADO ? el sonido seco del golpe al volante ayuda a encontrar las jugadas.", "site.record.still.title": "Mantenla fija", "site.record.still.body": "Trípode o soporte fijo. Sin paneos, sin zoom durante el juego ? una vista estable y de cancha completa es para lo que está ajustada la herramienta.", "site.record.upload.title": "Graba y sube", "site.record.upload.body": "Iluminación uniforme, luego graba la sesión completa y súbela tal cual ? KhelSutra encuentra las jugadas y hace el recorte.", "site.record.checklistCta": "Lista de captura completa de 1 página ?", "site.capture.diagram.title": "Vista lateral: dónde va la cámara", "site.capture.diagram.camera": "Cámara ? detrás de la línea de fondo, en alto", "site.capture.diagram.angle": "Inclina ~30° hacia abajo", "site.capture.diagram.frame": "Cancha completa en cuadro ? los jugadores nunca recortados", "site.capture.diagram.net": "Red", "site.capture.title": "Lista de captura de 1 página", "site.capture.intro": "Las buenas jugadas destacadas empiezan con una grabación estable y de cancha completa. Cinco minutos de configuración marcan una gran diferencia en tus reels.", "site.capture.ruleLead": "La regla de oro: un partido, una cancha, en cuadro completo ? y no muevas la cámara.", "site.capture.ruleRest": "Las grabaciones con varias canchas son el caso difícil que aún estamos puliendo; una sola cancha en cuadro da los mejores resultados hoy.", "site.capture.step1.title": "Coloca la cámara", "site.capture.step1.b1": "Detrás de una línea de fondo, en alto ? un trípode alto, a unos metros de altura, o un balcón.", "site.capture.step1.b2": "Inclínala hacia abajo unos 30°; mantén la cancha completa en cuadro con un poco de margen y espacio sobre la red.", "site.capture.step1.b3": "Los jugadores nunca deberían salir del cuadro.", "site.capture.step2.title": "Ajustes", "site.capture.step2.b1": "1080p o superior; grabado en horizontal.", "site.capture.step2.b2": "30 fps para bádminton/pickleball; 60 fps para tenis de mesa.", "site.capture.step2.b3": "Audio ACTIVADO (no silencios) ? mantén el micrófono despejado, con la reducción de viento/ruido desactivada.", "site.capture.step3.title": "Mantenla fija", "site.capture.step3.b1": "Trípode o soporte fijo.", "site.capture.step3.b2": "Sin paneos, sin zoom durante el juego.", "site.capture.step4.title": "Ilumina y graba", "site.capture.step4.b1": "Iluminación interior uniforme; evita el contraluz, los reflejos y los pabellones muy oscuros.", "site.capture.step4.b2": "Graba la sesión completa y súbela tal cual ? KhelSutra hace el recorte.", "site.capture.doTitle": "Hazlo", "site.capture.do1": "Cámara fija, cancha completa, detrás de la línea de fondo", "site.capture.do2": "1080p+, horizontal, audio activado", "... (truncated 33011 chars, full result in C:\\Users\\avidu\\AppData\\Local\\Temp\\claude\\C--Users-avidu-Projects-khelsutra\\831509e0-5773-4469-a2ff-205848372a6b\\tasks\\wf1rm0b34.output)</result><usage><agent_count>15</agent_count><subagent_tokens>632123</subagent_tokens><tool_uses>28</tool_uses><duration_ms>265699</duration_ms></usage></task-notification>

226. assistant (2026-06-22T03:27:12.240Z)

es/da/id translations done (15 agents). Let me parse the full result, confirm real `<b>` tags + 115-key completeness per locale, write the translations file, and tag-check vs en before applying.

227. user (2026-06-22T03:27:20.810Z)

es: keys=115/115 missing=0 escaped-tag-leak=0 tag-multiset-drift=0
da: keys=115/115 missing=0 escaped-tag-leak=0 tag-multiset-drift=0
id: keys=115/115 missing=0 escaped-tag-leak=0 tag-multiset-drift=0
fixed: es=11 da=10 id=14
Shell cwd was reset to C:\\Users\\avidu\\Projects\\khelsutra

228. assistant (2026-06-22T03:27:25.600Z)

All three: 115/115 keys, real `<b>` tags (no escape leak), **zero tag-multiset drift** vs en (revisers fixed 11/10/14 issues). Let me apply, mirror, and verify well-formedness.

229. user (2026-06-22T03:27:34.182Z)

```
es: applied 115/115 keys
da: applied 115/115 keys
id: applied 115/115 keys
OK: 115 target keys per locale (site.join.* left English in all locales).
--- copy:locales ---
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
--- well-formedness of es/da/id rich values ---
ALL 87 es/da/id rich values well-formed
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

230. assistant (2026-06-22T03:28:10.161Z)

Applied, mirrored, all 87 rich values well-formed. Before writing content tests, let me check how many target keys legitimately still equal the en string per locale (short labels like "Net" may coincide) so my "is-translated" assertion threshold is correct, not flaky.

231. user (2026-06-22T03:28:13.725Z)

```
es: 0 target keys still == en: (none)
da: 3 target keys still == en: nav.flyer, nav.faq, capture.diagram.net
id: 4 target keys still == en: nav.flyer, nav.roadmap, nav.faq, capture.diagram.net
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

232. assistant (2026-06-22T03:28:29.777Z)

Those are legitimate cognates kept in English (Danish/Indonesian commonly keep "Flyer"/"FAQ"/"Roadmap"; "Net" is a short label) ? es is fully translated, da=3, id=4. I'll assert concrete prose anchors + a generous threshold. Let me find the end of the i18n.shim test file to append the es/da/id content tests.

233. user (2026-06-22T03:28:30.475Z)

```
150      // never add, drop, or alter a tag/attribute. A dropped <b>/<a href>/<code> would
break the rendered page.
151      const tagset = (s) => (String(s).match(/<[>]+>/g) || []).slice().sort().join("|");
152      for (const loc of ["kn", "hi"]) {
153          const lf = flatOwn(catalogs[loc].site.ownModel);
154          for (const key of Object.keys(ef)) {
155              if (key === "requestAccess") continue; // preserved prior translation, checked
above
156              assert.equal(tagset(lf[key]), tagset(ef[key]), `${loc} site.ownModel.${key}:
inline HTML tag-set drifted from en`);
157          }
158          // Brand / tool / licence / code tokens stay verbatim across languages (the page is
a dev/power-user surface).
159          const o = catalogs[loc].site.ownModel;
160          assert.match(o.annotate.body, /rally-annotator/, `${loc} annotate.body lost the
rally-annotator token`);
161          assert.match(o.annotate.body, /\bVLC\b/, `${loc} annotate.body lost VLC`);
162          assert.match(o.setup.install, /rally_annotator\.lua/, `${loc} setup.install lost the
lua filename`);
163          assert.match(o.setup.reasons, /service_fault/, `${loc} setup.reasons lost the
ending_reason enum`);
164          assert.match(o.train.honestBody, /GPU/, `${loc} train.honestBody lost GPU`);
165          assert.match(o.train.honestBody, /LLM/, `${loc} train.honestBody lost LLM`);
166          assert.match(o.train.moat.cleanBody, /MIT\/Apache\/BSD/, `${loc} cleanBody lost the
licence list`);
167          assert.match(o.foot.mark, /Generated by Khelsutra\.guru/, `${loc} foot.mark lost the
verbatim watermark text`);
168      }
169  });
170
```

234. user (2026-06-22T03:28:47.455Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

235. assistant (2026-06-22T03:28:50.661Z)

Content tests added. Let me run both full suites with the translations applied.

236. user (2026-06-22T03:29:06.039Z)

```
=== SITE ===
? site: es/da/id carry REAL translations of the marketing copy; the access form (site.join.*)
stays English (0.9336ms)
? site: es/da/id keep en's inline-HTML tag-set + load-bearing literal tokens (no markup/token
drift) (0.6157ms)
? tests 77
? pass 75
? fail 2
? failing tests:
? site: es/da/id carry REAL translations of the marketing copy; the access form (site.join.*)
stays English (0.9336ms)
    at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
    at async Test.processPendingSubtests (node:internal/test_runner/test:897:7)
? site: es/da/id keep en's inline-HTML tag-set + load-bearing literal tokens (no markup/token
drift) (0.6157ms)
=== WEB ===
Test Files   23 passed (23)
Tests       215 passed (215)
Start at    08:58:57
Duration    7.95s (transform 3.26s, setup 1.22s, collect 15.41s, tests 7.44s,
environment 50.92s, prepare 7.70s)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

237. assistant (2026-06-22T03:29:18.483Z)

Web green (215). My 2 new site tests fail ? let me see the actual assertion messages.

238. user (2026-06-22T03:31:19.996Z)

Command running in background with ID: bf3gfuu8f. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bf3gfuu8f.output. You will be notified when
it completes. To check interim output, use Read on that file path.

239. user (2026-06-22T03:31:31.382Z)

```
target len: 115
sample target keys: [
  'reveal.share',
  'reveal.shareText',
  'nav.how',
  'nav.why',
  'nav.ownModel'
]
enSite has hero.lead? true | join.gpuLabel? true
es: stillEn=0
da: stillEn=3 nav.flyer, nav.faq, capture.diagram.net
id: stillEn=4 nav.flyer, nav.roadmap, nav.faq, capture.diagram.net
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

240. assistant (2026-06-22T03:31:40.747Z)

Found it ? the test file's `catalogs` object only loads en/kn/hi (line 14), so `catalogs.es` is

undefined. Let me add es/da/id to it.

241. user (2026-06-22T03:31:42.782Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

242. user (2026-06-22T03:31:49.271Z)

```
? tests 77
? pass 77
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

243. assistant (2026-06-22T03:32:02.567Z)

All 77 site tests pass; web 215 already green. Let me run the remaining web CI gates (typecheck, coverage, build) ? web source is untouched here, but I'll verify rather than assert.

244. user (2026-06-22T03:32:28.155Z)

```
added 58 packages in 6s
=== typecheck ===
TYPECHECK OK
=== coverage ===
  Test Files   23 passed (23)
     Tests    215 passed (215)
All files      |   93.39 |   88.12 |   85.88 |   93.39 |
=== build ===
dist/assets/index-CLXpNWRM.js
461.72 kB ? gzip: 141.30 kB
? built in 1.25s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

245. assistant (2026-06-22T03:32:41.075Z)

All web gates green (typecheck OK, coverage 93.39% = master, build OK). Now the browser render verification + screencast for es/da/id. Let me start the worktree server.

246. user (2026-06-22T03:32:41.859Z)

Command running in background with ID: b1b08juua. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\b1b08juua.output. You will be notified when it completes. To check interim output, use Read on that file path.

247. user (2026-06-22T03:32:48.577Z)

```
es html-lang: <html lang="es" | content-language: es | has 6 options: 6
da html-lang: <html lang="da" | content-language: da | has 6 options: 6
id html-lang: <html lang="id" | content-language: id | has 6 options: 6
```

248. assistant (2026-06-22T03:32:54.554Z)

Server negotiates es/da/id correctly (lang headers + 6 options). Let me write and run an es/da/id screencast with render verification.

249. assistant (2026-06-22T03:33:05.959Z)

```
// Records the marketing site reaching parity with the SPA's 6 languages: the home page driven
// through the compact switcher en -> Spanish -> Danish -> Indonesian, plus the capture + own-
model
// pages in Spanish. Captures per-locale stills and asserts the console is clean + the hero copy
```

```

// actually changed per language. Run against the worktree site server (URL env, default :8124).
import { chromium } from "playwright";
import { rename } from "node:fs/promises";
import { mkdirSync } from "node:fs";

const URL = process.env.URL || "http://localhost:8124";
const HOLD = 1300;
mkdirSync("rec", { recursive: true });
const browser = await chromium.launch();

const errors = [];
const ctx = await browser.newContext({
  viewport: { width: 1280, height: 900 },
  locale: "en-US",
  recordVideo: { dir: "rec", size: { width: 1280, height: 900 } },
});
const page = await ctx.newPage();
page.on("console", (m) => { if (m.type() === "error") errors.push(m.text()); });
page.on("pageerror", (e) => errors.push("pageerror: " + e.message));

const heroOf = () => page.locator("h1").first().innerText();
const heros = {};

await page.goto(URL + "/", { waitUntil: "networkidle" });
await page.waitForTimeout(HOLD);
heros.en = await heroOf();
await page.screenshot({ path: "site-en-home.png" });

for (const loc of ["es", "da", "id"]) {
  await page.evaluate(() => window.scrollTo(0, 0));
  await page.selectOption("select[data-langsw]", loc);
  await page.waitForTimeout(HOLD);
  heros[loc] = await heroOf();
  await page.screenshot({ path: `site-${loc}-home.png` });
  // scroll the recording-education section into view (the highest-value localized marketing
  block)
  await page.locator("#record").scrollIntoViewIfNeeded().catch(() => {});
  await page.waitForTimeout(700);
  await page.screenshot({ path: `site-${loc}-record.png`, fullPage: false });
}

// capture + own-model pages in Spanish (es persisted from the switch above)
await page.goto(URL + "/capture", { waitUntil: "networkidle" });
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "site-es-capture.png", fullPage: true });
await page.goto(URL + "/own-model", { waitUntil: "networkidle" });
await page.waitForTimeout(HOLD);
await page.screenshot({ path: "site-es-ownmodel.png", fullPage: true });

const v = page.video();
await ctx.close();
await rename(await v.path(), "khelsutra-site-esdaid-desktop.webm");

console.log("heroes:");
for (const [k, val] of Object.entries(heros)) console.log(" ", k, JSON.stringify(val));
const distinct = new Set(Object.values(heros)).size;
console.log("all 4 heroes distinct (en/es/da/id):", distinct === 4);
console.log("console errors:", errors.length ? errors : "NONE");
await browser.close();
console.log("wrote khelsutra-site-esdaid-desktop.webm + site-{en,es,da,id}-home.png + es
capture/own-model");

```

250. user (2026-06-22T03:33:05.976Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\esdaid-screencast.mjs

(file state is current in your context ? no need to Read it back)

251. user (2026-06-22T03:33:30.029Z)

heroes:

```
en "Every rally, indexed. The dead time, gone."
es "Cada jugada, indexada. El tiempo muerto, fuera."
da "Hver duel, indekseret. Den døde tid, væk."
id "Setiap reli, terindeks. Waktu kosongnya, hilang."
```

all 4 heroes distinct (en/es/da/id): true

console errors: [

```
"Access to XMLHttpRequest at 'https://cloudflareinsights.com/cdn-cgi/rum' from origin
'http://localhost:8124' has been blocked by CORS policy: Response to preflight request doesn't
pass access control check: The 'Access-Control-Allow-Origin' header has a value
'http://localhost' that is not equal to the supplied origin.",
'Failed to load resource: net::ERR_FAILED'
]
```

wrote khelsutra-site-esdaid-desktop.webm + site-{en,es,da,id}-home.png + es capture/own-model
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

252. assistant (2026-06-22T03:33:42.631Z)

All four heroes render distinctly and correctly ? es "Cada jugada, indexada", da "Hver duel, indekseret" (reusing "duel" from the SPA), id "Setiap reli, terindeks" (reusing "reli"). The only console error is the **pre-existing Cloudflare analytics beacon** failing CORS on localhost (it only works on the real domain) ? unrelated to i18n. Let me eyeball the Spanish home + capture stills.

253. assistant (2026-06-22T03:34:07.275Z)

The Spanish home renders cleanly ? nav, hero (with the `<span class="hl">` lime emphasis preserved), lead, CTAs all in Spanish, switcher shows "? Español". I notice the hero **demo-mockup card** ("RALLIES DETECTED", "Auto-index rallies", "See it in action", "Download your reel") is still English. Let me verify whether that's wired at all ? i.e. whether it's a pre-existing English-in-all-locales element (including kn/hi) or something I missed.

254. user (2026-06-22T03:34:11.220Z)

=== are the hero-mockup strings data-i18n wired? ===

```
274:      <a class="btn btn-ghost" href="#join">See it in action + a real reel</a>
278:      <span class="chip"><b>1.</b> Auto-index rallies</span>
280:      <span class="chip"><b>2.</b> Dead time removed</span>
282:      <span class="chip"><b>3.</b> Download your reel</span>
329:      <h3>Dead time removed</h3>
```

=== check if any are wired (data-i18n nearby) ===

```
270:      <p class="lead" data-i18n="site.hero.lead">KhelSutra finds every rally in your session
and strips out the knock-ups, walks and gaps ? so a full match becomes a clean highlight reel
you can watch and download. No editing, no scrubbing.</p>
350:      <h2 data-i18n="site.record.title">Five minutes of setup ? reliably great reels</h2>
351:      <p data-i18n="site.record.intro">Highlight quality starts with the recording. Set the
camera up once like this and KhelSutra has everything it needs to find the rallies.</p>
368:      <p data-i18n-html="site.record.settings.body"><b>1080p</b>, landscape, <b>30
fps</b> for badminton (60 fps for table tennis). <b>Audio ON</b> ? the shuttle's ?thwack? helps
find rallies.</p>
378:      <p data-i18n-html="site.record.upload.body">Even lighting, then record the <b>whole
session</b> and upload it as-is ? KhelSutra finds the rallies and does the cutting.</p>
```

=== does kn ALSO render these in English? (proves pre-existing parity) ? check kn catalog for matching keys ===

0

255. assistant (2026-06-22T03:34:25.683Z)

Confirmed pre-existing: the hero-mockup chips ("See it in action", "Auto-index rallies", "Download your reel") are **hardcoded English**, not ``data-i18n`-wired` (index.html:274-282) ? kn

has 0 matching keys, so ****kn/hi** render them in English too******, on the live site today. So **es/da/id** reach exactly the ****same coverage as kn/hi**** (the scoped goal); that hardcoded mockup is a separate pre-existing gap affecting all non-en locales. Let me eyeball the Spanish capture page to confirm the deeper pages render.

256. assistant (2026-06-22T03:34:48.873Z)

The deeper page renders too ? that's actually the ****Indonesian**** capture page (the screencast persisted ``id`` from the last switch): "Daftar periksa perekaman 1halaman", the 4 steps, the camera diagram with localized legend, Do/Avoid lists ? all in Indonesian, diagram intact. All three languages render correctly end-to-end.

Let me stop the server, clean up helpers, and review the diff before committing.

257. user (2026-06-22T03:34:55.656Z)

server stopped + helpers removed

258. assistant (2026-06-22T03:35:02.014Z)

Let me review the diff and confirm only the expected files changed before committing.

259. user (2026-06-22T03:35:05.856Z)

```
=== branch + base check ===
feat/site-es-da-id
=== status ===
M locales/da/common.json
M locales/es/common.json
M locales/id/common.json
M site/public/capture.html
M site/public/i18n.js
M site/public/index.html
M site/public/locales/da/common.json
M site/public/locales/es/common.json
M site/public/locales/id/common.json
M site/public/own-model.html
M site/server.js
M site/src/assets.test.js
M site/src/i18n.shim.test.js
=== diff stat ===
 locales/da/common.json      | 224 ++++++-----
 locales/es/common.json      | 230 ++++++-----
 locales/id/common.json      | 222 ++++++-----
 site/public/capture.html    | 3 +
 site/public/i18n.js         | 2 +-
 site/public/index.html      | 3 +
 site/public/locales/da/common.json | 224 ++++++-----
 site/public/locales/es/common.json | 230 ++++++-----
 site/public/locales/id/common.json | 222 ++++++-----
 site/public/own-model.html   | 3 +
 site/server.js              | 2 +-
 site/src/assets.test.js     | 15 +--
 site/src/i18n.shim.test.js   | 49 +++++-
13 files changed, 741 insertions(+), 688 deletions(-)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

260. assistant (2026-06-22T03:35:28.563Z)

Exactly the 13 expected files (en/kn/hi catalogs untouched, no helpers, no node_modules), branch rides only on origin/master. Let me commit the implementation.

261. user (2026-06-22T03:35:36.960Z)

=== staged ===

13

=== commit ===

8aba10e feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

262. assistant (2026-06-22T03:35:48.595Z)

Committed (8aba10e). Let me push and open the PR.

263. user (2026-06-22T03:35:51.820Z)

remote:

branch 'feat/site-es-da-id' set up to track 'origin/feat/site-es-da-id'.

To <https://github.com/avidullu/khelsutra.git>

* [new branch] feat/site-es-da-id -> feat/site-es-da-id

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

264. user (2026-06-22T03:36:15.618Z)

<https://github.com/avidullu/khelsutra/pull/87>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

265. assistant (2026-06-22T03:36:22.232Z)

PR opened: [#87](<https://github.com/avidullu/khelsutra/pull/87>). Let me add the tracking-doc changelog entry, then commit it to the PR.

266. user (2026-06-22T03:36:23.450Z)

- `2026-06-22` ? **UI/UX header pass ([#83](<https://github.com/avidullu/khelsutra/pull/83>)).** A 3-lens design critique + a deep

- `2026-06-22` ? **? Multilingual chapter ? effectively complete (pending human gates).** \$7 is

all ? except B7 (asse

- `2026-06-22` ? **own-model body content localized to kn + hi

([#86](<https://github.com/avidullu/khelsutra/pull/86>)) ? closes

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

267. user (2026-06-22T03:36:27.702Z)

189 - `2026-06-22` ? **own-model body content localized to kn + hi

([#86](<https://github.com/avidullu/khelsutra/pull/86>)) ? closes engineering follow-up (3)

above.** The developer/power-user `own-model.html` was English-only on kn/hi (only its switcher + Request-access link were localized). Wired its **full body** ? hero, the annotate/train/setup

steps, the moat grid, the honest-framing fences, "what this is not", CTA and footer ? through the shim (**52 new `site.ownModel.` keys**;

`data-i18n` + `data-i18n-html` for inline

`<b>/<i>/<a>/<code>/<span>`), keeping `<pre>/CLI blocks, file paths, the `ending_reason` enum,

brand/tool tokens (KhelSutra/VLC/rally-annotator/MIT/GPU/LLM) and the VLC UI button labels

literal, and every honest caveat intact (`<title>/meta left English, consistent with A3).

en authored **byte-for-byte** (jsdom-extracted ? the A3 drift guard validates it); es/da/id en-

seeded; **kn/hi AI-drafted ? 3-lens adversarial verify (accuracy/fluency/integrity) ? revise**

via a 10-agent workflow (16 kn + 10 hi findings folded), reusing the established kn/hi register;

the shipped `requestAccess` translation preserved. New tests: own-model body-wiring assertion +

kn/hi in-script render check + a **tag-multiset/literal-token integrity guard**;

the web `catalog-invariants` `<code>-leak rule (#77) **scoped** to allow inline code only on

`site.ownModel.`. **Site 75 + web 215 green; web typecheck/coverage (93.4%, ? floor)/build

green.** Real-browser pass (kn + hi render, `<b>` preserved, code blocks literal, **zero console

errors**); screencast `khelsutra-ownmodel-i18n-desktop.webm` + per-locale stills in `khelsutra-

screencast/`. kn/hi remain **native-review-pending** (the two human gates are unchanged). Built

in an isolated `git worktree` off `origin/master` (the shared checkout had churned to

`deploy/kit-live-verified` mid-session ? concurrency convention vindicated).

190

268. user (2026-06-22T03:36:40.577Z)

The file C:\Users\avidu\Projects\ks-site-esdaid\docs\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

269. user (2026-06-22T03:36:49.010Z)

```
To https://github.com/avidullu/khelsutra.git
8aba10e..c0ef790 feat/site-es-da-id -> feat/site-es-da-id
=== branch commits ===
c0ef790 docs(friendly-multilingual): record es/da/id site parity (#87)
8aba10e feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

270. assistant (2026-06-22T03:36:52.914Z)

Both commits pushed. Now let me watch CI on [#87](https://github.com/avidullu/khelsutra/pull/87) and merge on green.

271. user (2026-06-22T03:37:36.459Z)

```
site    pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27927921967/job/82633976638
Workers Builds: hidden-king-khelsutra    pending 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/949b62c5-af10-4c67-aa8f-715e8cf8a3de
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/949b62c5-af10-4c67-aa8f-715e8cf8a3de
site    pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27927921967/job/82633976638
web     pass    30s
https://github.com/avidullu/khelsutra/actions/runs/27927921967/job/82633976644
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/949b62c5-af10-4c67-aa8f-715e8cf8a3de
site    pass    11s
https://github.com/avidullu/khelsutra/actions/runs/27927921967/job/82633976638
web     pass    30s
https://github.com/avidullu/khelsutra/actions/runs/27927921967/job/82633976644
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

272. assistant (2026-06-22T03:37:41.115Z)

All green ? site ?, web ?, Cloudflare ?. Let me verify my branch carries only my commits, then squash-merge.

273. user (2026-06-22T03:37:49.121Z)

```
=== only my commits on origin/master? ===
c0ef790 docs(friendly-multilingual): record es/da/id site parity (#87)
8aba10e feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages)
=== merge ===
=== verify merged ===
{"merge":"cf59fbf09ed0217bebd82f834551504393434e2f","state":"MERGED"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

274. assistant (2026-06-22T03:37:53.379Z)

[#87](https://github.com/avidullu/khelsutra/pull/87) is **MERGED** (squash `cf59fbf`), carrying only my 2 commits. Let me clean up the remote branch + worktree and refresh the handoff.

275. user (2026-06-22T03:38:00.214Z)

```
- [deleted]          feat/site-es-da-id
```

```
error: failed to delete 'C:/Users/avidu/Projects/ks-site-esdaid': Permission denied
=== worktrees ===
C:/Users/avidu/Projects/khelsutra      17242a9 [master]
C:/Users/avidu/Projects/khelsutra-p2c  17242a9 (detached HEAD)
=== origin/master head ===
cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages) (#87)
17242a9 feat(site): localize own-model body content to kn/hi (#86)
7b04f02 deploy(kit): align with the live-verified droplet deploy (+ the gemini-default fix)
(#85)
```

276. assistant (2026-06-22T03:38:13.465Z)

Remote branch deleted; origin/master is now `cf59fbf` (#87). Note a sibling worktree `khelsutra-p2c` is active ? concurrent sessions confirmed again. The worktree dir deletion hit a file lock (git already pruned its metadata). Let me clear the lock and remove the leftover directory.

277. user (2026-06-22T03:38:21.503Z)

```
removed leftover worktree dir
C:/Users/avidu/Projects/khelsutra      17242a9 [master]
C:/Users/avidu/Projects/khelsutra-p2c  17242a9 (detached HEAD)
```

278. assistant (2026-06-22T03:38:29.332Z)

Leftover dir removed (a stray test process from earlier held the lock). Worktree list is clean. Let me refresh the handoff to reflect the es/da/id site expansion.

279. user (2026-06-22T03:38:29.520Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22, after A2 (#82) + the UI/UX header pass (#83) + the chapter
closeout (#84) + own-model kn/hi (#86) merged._
4
5      ## You are here ? chapter effectively COMPLETE (pending human gates)
6      $7 of `docs/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated, cross-repo
B7** (deferred). Both surfaces are trilingual end-to-end and non-tech-friendly:
7      - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: en/kn/hi ? B3
shim/switcher/negotiation, A3 recording-education + marketing copy in kn/hi (Noto bundled), A6
plain-language access form, A7 camera-placement diagram, **A2 WhatsApp share** (#82), and the
**UI/UX header pass** (#83): the 3 language pills ? a compact `? <select>` (fixed the mobile
header overflow; zero horizontal overflow across all 12 page/viewport/locale combos) + the home
hero headline localized.
8      - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77**; web
coverage floor added in **#80**.
9      - Sister repo **rally-annotator is also localized (kn/hi/es/da/id/te)** ? the journey
annotator ? site ? Studio is consistent in the user's language.
10     - **own-model body content** is now localized to kn/hi (**#86**) ? the developer "train
your own model" page renders fully in-language (52 `site.ownModel.*` keys; `<pre>`/CLI/tokens
left literal; AI-draft ? 3-lens verify ? revise). **No engineering gap remains before the two
human gates.**
11
12     ## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)
13     1. **Native-speaker review** of the AI-drafted kn/hi catalogs (site + SPA) ? the
standing guardrail before a wide public launch.
14     2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
Proxy screencasts in `C:/Users/avidu/Projects/khelsutra-screencast/`: `khelsutra-
site-i18n-desktop.mp4` (site home+capture, kn) + `khelsutra-i18n-screencast.mp4` (SPA, kn-IN) +
**`khelsutra-ownmodel-i18n-desktop.webm`** (#86, own-model en?kn?hi; stills
`ownmodel-{kn,hi}-{hero,full}.png`).
15
16     ## Open engineering follow-ups (small)
17     - ~~own-model body content English on kn/hi~~ ? **DONE (#86).**
```

```

18     - **Access form kn/hi** ? A6 left it English (`site.join.*` en-seeded), translation-
ready. (Now the largest remaining English-on-kn/hi surface; same A3-style slice.)
19     - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
20     - Minor: `site.*` adds ~27KB to the SPA bundle (could split to a site-only catalog);
ratchet web coverage thresholds as `App.tsx` gains tests.
21
22     ## Ramp-up kit
23     - `docs/FRIENDLY_AND_MULTILINGUAL.md` ? $7 tracker (source of truth, all ? except B7),
$6.5 N1?N9, $9 DoD (boxes flipped; 2 human gates open), changelog.
24     - `/locales/{en,kn,hi,es,da,id}/common.json` ? shared catalog: SPA console keys +
`site.*` (nav/hero/record/capture/join/ownModel/reveal).
25     - `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, compact ``
switcher, `window.KhelSutra.t` bridge, negotiation), `site/server.js`, `site/scripts/copy-
locales.mjs`, `site/src/{i18n.shim,locales-drift,assets,server}.test.js`.
26     - Screencast/Playwright tooling + before/after eval shots:
`C:/Users/avidu/Projects/khelsutra-screencast/` (`site-screencast.mjs`, `deep-test.mjs`, `eval-
shots.mjs`).
27     - [[catalog-home-and-i18n-layout]], [[shared-checkout-concurrency]].
28
29     ## Key decisions (don't relitigate)
30     - D-CATALOG-HOME: catalogs at repo-root `/locales`; SPA imports; site mirrors via
`copy:locales` + drift guard.
31     - Negotiation order (both surfaces): persisted (`khelsutra.lang`) ? `?lang=` ?
navigator/Accept-Language ? en; missing key ? en, never a raw key.
32     - Switcher = compact `` in the header (kept there for discoverability/signal;
auto-negotiation covers kn-phones). Rich `` markup localizes via `data-i18n-html` (XSS-safe;
catalog-authored).
33     - Process: isolated `git worktree` per PR (shared checkout churns fast); AI-draft
translations ? adversarial verify ? native review is a pre-launch (not pre-merge) gate.
34

```

280. assistant (2026-06-22T03:38:34.416Z)

Let me update the handoff to reflect the es/da/id site expansion (#87):

281. user (2026-06-22T03:38:48.444Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

282. user (2026-06-22T03:38:53.868Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

283. user (2026-06-22T03:39:04.379Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

284. assistant (2026-06-22T03:39:18.172Z)

The work is merged and the handoff is refreshed. Let me flag the one pre-existing gap I found (the hardcoded hero-mockup chips) as a follow-up chip, since you're clearly invested in i18n completeness and it affects all locales' home page.

285. user (2026-06-22T03:39:30.931Z)

Noted (position 1, task_id: task_1821578e). A chip is showing for the user ? they can start it in a fresh worktree with one click, or dismiss it. If this suggestion becomes stale or

superseded, call `dismiss_task` with this `task_id`. Currently pending: `task_1821578e` "Wire hero-mockup chips for i18n (all 6 langs)". Continue your current work.

286. assistant (2026-06-22T03:39:51.633Z)

Done ? **es/da/id** are now in the site dropdown and fully working, merged to master via [#87](https://github.com/avidullu/khelsutra/pull/87) (squash `cf59fbf`).

First, the correction that shaped this

There's **no Dutch or Thai** anywhere in the repo ? the existing extra locales are ``es`` (Spanish), ``da`` (**Danish**, not Dutch), ``id`` (Indonesian). They were translated in the SPA console but their *marketing-site* copy was 100% English-seeded, which is why the dropdown was intentionally `en/kn/hi`. "Make it work" therefore meant translating the whole site into each ? which is what shipped.

What shipped

- **Dropdown + negotiation:** `es/da/id` `<option>`'s on all 3 pages; shim `SUPPORTED` + `server.js` `SITE_LOCALES`` now list all 6 ? a Spanish/Danish/Indonesian browser auto-renders the site in-language (`<html lang>` + `content-language``).
- **Translation:** the **115** `site.*`` keys (nav, hero, recording-education, capture + diagram, own-model, reveal) into `es/da/id` ? **AI-drafted** ? 3-lens adversarial verify ? revise (11 `es` + 10 `da` + 14 `id` findings folded), reusing each locale's shipped app vocabulary (rally ? `es jugada*`, `da *duel*`, `id *reli*`). HTML tags + literal tokens preserved.
- **Parity, not over-reach:** the access form (`site.join.*``) stays English in `es/da/id` too, exactly as for `kn/hi` (A6 deferred form translation for all non-en).

Verified

- **site 77 ?** · web 215 ? · typecheck clean · coverage 93.4% (? floor) · build ? · **CI green** on the PR (site + web + Cloudflare).
- Real-browser: home heroes render distinct & correct (`*Cada jugada, indexada* / *Hver duel, indekseret* / *Setiap reli, terindeks*`), the Indonesian capture page + camera diagram render, no i18n console errors (only the pre-existing Cloudflare analytics beacon, which can't reach its endpoint from localhost). Screenshot `khelsutra-site-esdaid-desktop.webm`` + per-locale stills saved.

Honest notes

- `es/da/id` are AI-drafted ? native-review-pending, same standing pre-launch gate as `kn/hi`.
- I found one pre-existing gap: a few **hardcoded hero-mockup chips** in `index.html`` (`*See it in action*, *Auto-index rallies*, *Download your reel*`) aren't `data-i18n`-wired`, so they show English in **every** non-en locale **including kn/hi** today ? not something this PR introduced. I left it out of scope (it'd touch all 6 languages) and **flagged it as a follow-up chip** for you, plus recorded it in the handoff.
- Worked in an isolated worktree off `origin/master`` ? again vindicated: a sibling session's worktree (`khelsutra-p2c``) was active concurrently. Branch carried only my 2 commits before the squash; cleaned up after.

287. user (2026-06-22T03:48:54.417Z)

are all the locales now natively rendered if the users have these languages as their browser/OS language?

288. assistant (2026-06-22T03:49:50.910Z)

Good question ? that auto-negotiation promise (§6.5: a Kannada/Hindi/? browser must get that language *automatically*) is the core requirement, so let me actually verify it for all 6 on both surfaces rather than assert it. Let me check the SPA's negotiation config and run a live server check on the merged site.

289. user (2026-06-22T03:49:51.419Z)

```
1      // i18n scaffold (tracker B1) ? the shared localization foundation for KhelSutra Studio.
2      //
```

```

3      // Per docs/FRIENDLY_AND_MULTILINGUAL.md + the engine's I18N_PLAN.md:
4      //   - keys, never prose (t("app.title"), enforced later by a no-bare-strings lint, B2);
5      //   - ICU MessageFormat for interpolation/plurals (Kannada/Hindi plural rules live in
the catalog,
6      //     not the code ? replaces the SPA's hand-rolled `count > 1 ? "s" : ""`);
7      //   - one negotiation order shared with the marketing site (B3);
8      //   - always-fallback to `en` so a missing translation degrades to English, never a raw
key.
9      import i18n from "i18next";
10     import { initReactI18next } from "react-i18next";
11     import LanguageDetector from "i18next-browser-languagedetector";
12     import ICU from "i18next-icu";
13     // Catalogs are HOISTED to repo-root /locales (D-CATALOG-HOME) ? the single source of
truth shared
14     // by this SPA and the marketing site's t() shim (tracker B3). Vite resolves the
workspace root via
15     // the repo `.git` marker, so importing the parent-dir /locales works in dev, build, and
vite.
16     import enCommon from "../../locales/en/common.json";
17     import knCommon from "../../locales/kn/common.json";
18     import hiCommon from "../../locales/hi/common.json";
19     import esCommon from "../../locales/es/common.json";
20     import daCommon from "../../locales/da/common.json";
21     import idCommon from "../../locales/id/common.json";
22
23     // Supported locales: en/kn/hi foundation (FRIENDLY D6) + MULTILINGUAL_EXPANSION Phase A
(es/da/id,
24     // Latin, catalog-only). Anything else falls back to `en`.
25     export const SUPPORTED_LOCALES = ["en", "kn", "hi", "es", "da", "id"] as const;
26     export type Locale = (typeof SUPPORTED_LOCALES)[number];
27     export const DEFAULT_LOCALE: Locale = "en";
28
29     // ONE persisted-preference key, shared with the marketing site's t() shim (D9 / tracker
B3), so a
30     // visitor's language choice carries across both surfaces.
31     export const LANG_STORAGE_KEY = "khelsutra.lang";
32
33     // Catalogs live in repo-root /locales (D-CATALOG-HOME), consumed by both surfaces. `kn`
+ `hi`
34     // shipped (B5/B6, AI-drafted ? native review pending). A missing key in any locale
still falls back
35     // to `en` ? the by-design invariant.
36     const resources = {
37       en: { common: enCommon },
38       kn: { common: knCommon },
39       hi: { common: hiCommon },
40       es: { common: esCommon },
41       da: { common: daCommon },
42       id: { common: idCommon },
43     } as const;
44
45     void i18n
46       .use(ICU)
47       .use(LanguageDetector)
48       .use(initReactI18next)
49       .init({
50         resources,
51         fallbackLng: DEFAULT_LOCALE,
52         supportedLngs: [...SUPPORTED_LOCALES],
53         nonExplicitSupportedLngs: true, // en-IN -> en
54         defaultNS: "common",
55         ns: ["common"],
56         interpolation: { escapeValue: false }, // React already escapes
57         returnNull: false,
58         // Negotiation order (I18N_PLAN §2.3): persisted pref -> ?lang= -> browser -> en.

```

```

59     detection: {
60         order: ["localStorage", "querystring", "navigator"],
61         lookupLocalStorage: LANG_STORAGE_KEY,
62         lookupQuerystring: "lang",
63         caches: ["localStorage"],
64     },
65     react: { useSuspense: false },
66 });
67
68 // Keep <html lang> in sync with the active locale (screen readers + SEO use it).
Reflects the
69 // resolved content language, so an `en` fallback for an absent locale still reads as
`en`.
70 function syncDocumentLang(lng: string) {
71     if (typeof document !== "undefined") {
72         document.documentElement.lang = (i18n.resolvedLanguage || lng ||
DEFAULT_LOCALE).split("-")[0];
73     }
74 }
75 i18n.on("languageChanged", syncDocumentLang);
76 syncDocumentLang(i18n.language ?? DEFAULT_LOCALE);
77
78 export default i18n;
79

```

290. user (2026-06-22T03:49:54.753Z)

```

=== SPA negotiation/detection tests: do they cover es/da/id + region normalization? ===
web/src/api/upload.test.ts:3:// strict 0,1,2 order), the progress callback, and that a mid-
upload failure cleans up + rethrows.
web/src/components/build-error.test.tsx:102:    expect(compileBody!.locale).toBe("en"); // App
forwards i18n.resolvedLanguage; broken wiring ? undefined
web/src/i18n/i18n.test.tsx:83:// respective version. These prove the negotiation NOW at the
detection level (B1, en-only); the
web/src/i18n/i18n.test.tsx:86:    const detectBases = () => {
web/src/i18n/i18n.test.tsx:87:        const d = i18n.services.languageDetector.detect();
web/src/i18n/i18n.test.tsx:91:        it("N1/N5: a Kannada browser (kn-IN) is auto-detected as kn for
a first-time visitor", () => {
web/src/i18n/i18n.test.tsx:93:            vi.stubGlobal("navigator", { language: "kn-IN", languages:
["kn-IN", "en-IN"] });
web/src/i18n/i18n.test.tsx:94:            expect(detectBases()).toContain("kn"); // the kn-IN region
subtag normalizes to base kn
web/src/i18n/i18n.test.tsx:97:        it("N2: a Hindi browser (hi-IN) is auto-detected as hi (now a
supported locale)", () => {
web/src/i18n/i18n.test.tsx:99:            vi.stubGlobal("navigator", { language: "hi-IN", languages:
["hi-IN", "en-IN"] });
web/src/i18n/i18n.test.tsx:100:            expect(detectBases()).toContain("hi");
web/src/i18n/i18n.test.tsx:105:            vi.stubGlobal("navigator", { language: "en-US", languages:
["en-US"] });
web/src/i18n/i18n.test.tsx:106:            expect(detectBases()[0]).toBe("kn");
web/src/i18n/i18n.test.tsx:110:            const order = i18n.options.detection?.order ?? [];
web/src/i18n/i18n.test.tsx:112:            expect(order.indexOf("localStorage")).toBeLessThan(order.indexOf("navigator"));
web/src/i18n/i18n.test.tsx:113:            expect(order.indexOf("querystring")).toBeLessThan(order.indexOf("navigator"));
web/src/i18n/i18n.test.tsx:164:            for (const [lng, base] of [["es-ES", "es"], ["da-DK", "da"],
["id-ID", "id"]]) as const) {
web/src/i18n/i18n.test.tsx:166:                vi.stubGlobal("navigator", { language: lng, languages:
[lng] });
web/src/i18n/i18n.test.tsx:167:                const d = i18n.services.languageDetector.detect();

```

291. assistant (2026-06-22T03:50:18.289Z)

SPA config is solid: `supportedLngs` = all 6 + `nonExplicitSupportedLngs: true` (region subtags normalize: es-MX?es, kn-IN?kn), detection order localStorage?querystring?navigator?en. And the

SPA tests cover detection for ****all 6**** (kn-IN?kn, hi-IN?hi, es-ES?es, da-DK?da, id-ID?id).

Now let me verify the merged ****site**** live for all 6 (the main checkout is one commit behind, so I'll use a throwaway worktree off origin/master ? server.js needs only Node built-ins).

292. user (2026-06-22T03:50:22.777Z)

HEAD is now at cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages) (#87)
=== confirm merged code present (SITE_LOCALES + shim SUPPORTED) ===
39:const SITE_LOCALES = ["en", "kn", "hi", "es", "da", "id"];
12:export const SUPPORTED = ["en", "kn", "hi", "es", "da", "id"]; // marketing site now matches the SPA's 6 languages

293. assistant (2026-06-22T03:50:28.197Z)

Merged code confirmed in the throwaway worktree. Let me start the server and exercise browser-language negotiation across all 6 locales (plus region subtags and an unsupported one) on all 3 pages.

294. user (2026-06-22T03:50:29.398Z)

Command running in background with ID: bhp60hhko. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-kheIsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bhp60hhko.output. You will be notified when it completes. To check interim output, use Read on that file path.

295. user (2026-06-22T03:50:40.844Z)

```
=== page / ===
? kn (Kannada browser)      html-lang=kn content-language=kn
? hi (Hindi browser)       html-lang=hi content-language=hi
? es (Spanish/Mexico ? region subtag) html-lang=es content-language=es
? da (Danish)              html-lang=da content-language=da
? id (Indonesian)          html-lang=id content-language=id
? en (English)             html-lang=en content-language=en
? fr (UNSUPPORTED ? must fall back to en) html-lang=en content-language=en
? ta (Tamil, UNSUPPORTED ? en) html-lang=en content-language=en

=== page /capture ===
? kn (Kannada browser)      html-lang=kn content-language=kn
? hi (Hindi browser)       html-lang=hi content-language=hi
? es (Spanish/Mexico ? region subtag) html-lang=es content-language=es
? da (Danish)              html-lang=da content-language=da
? id (Indonesian)          html-lang=id content-language=id
? en (English)             html-lang=en content-language=en
? fr (UNSUPPORTED ? must fall back to en) html-lang=en content-language=en
? ta (Tamil, UNSUPPORTED ? en) html-lang=en content-language=en

=== page /own-model ===
? kn (Kannada browser)      html-lang=kn content-language=kn
? hi (Hindi browser)       html-lang=hi content-language=hi
? es (Spanish/Mexico ? region subtag) html-lang=es content-language=es
? da (Danish)              html-lang=da content-language=da
? id (Indonesian)          html-lang=id content-language=id
? en (English)             html-lang=en content-language=en
? fr (UNSUPPORTED ? must fall back to en) html-lang=en content-language=en
? ta (Tamil, UNSUPPORTED ? en) html-lang=en content-language=en
```

persisted cookie da beats Accept-Language es: da

296. assistant (2026-06-22T03:51:04.602Z)

Server-side negotiation is perfect for all 6 (+ region-subtag normalization, unsupported?en

fallback, persisted-cookie precedence). But that only sets ``; the actual **content** translation is applied client-side by the shim from `navigator.languages`. The definitive test is: a browser whose *locale* is X (no dropdown interaction) renders X content. Let me verify that with Playwright for all 6.

297. assistant (2026-06-22T03:51:14.519Z)

```
// Proves the §6.5 promise on the SITE: a browser whose OS/locale is X auto-RENDERS content in
X,
// with NO dropdown interaction. For each locale we open a fresh context with that `locale`
(which sets
// navigator.language + Accept-Language), load the home page, and read the rendered hero + <html
lang>.
import { chromium } from "playwright";
const URL = process.env.URL || "http://localhost:8131";
const browser = await chromium.launch();

// expected hero opening per locale (first few words) to prove CONTENT, not just the lang
attribute
const EXPECT = {
  en: "Every rally", kn: "?????", hi: "??", es: "Cada jugada", da: "Hver duel", id: "Setiap
reli",
  fr: "Every rally", // unsupported -> must fall back to English content
};
let allOk = true;
for (const loc of ["en", "kn", "hi", "es", "da", "id", "fr"]) {
  const playwrightLocale = { en: "en-US", kn: "kn-IN", hi: "hi-IN", es: "es-MX", da: "da-DK",
id: "id-ID", fr: "fr-FR" }[loc];
  const ctx = await browser.newContext({ locale: playwrightLocale });
  const page = await ctx.newPage();
  const errs = [];
  page.on("pageerror", (e) => errs.push(e.message));
  await page.goto(URL + "/", { waitUntil: "networkidle" });
  await page.waitForTimeout(900); // let the client shim negotiate + apply
  const hero = (await page.locator("h1").first().innerText()).replace(/\s+/g, " ").trim();
  const htmlLang = await page.evaluate(() => document.documentElement.lang);
  const want = loc === "fr" ? "en" : loc;
  const ok = htmlLang === want && hero.startsWith(EXPECT[loc]) && (errs.length === 0);
  if (!ok) allOk = false;
  console.log(`${ok ? "?" : "?"} browser=${playwrightLocale} -> html.lang=${htmlLang} (want
${want}) | hero=${hero.slice(0, 42)}?${errs.length ? " ERRORS:" + errs.join(";") : ""}`);
  await ctx.close();
}
await browser.close();
console.log(allOk ? "\nALL PASS: browser/OS language auto-renders the right content (site,
client shim, no dropdown)." : "\nFAILURES above.");
```

298. user (2026-06-22T03:51:14.547Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\auto-negotiate-check.mjs (file state is current in your context ? no need to Read it back)

299. user (2026-06-22T03:51:35.859Z)

```
? browser=en-US -> html.lang=en (want en) | hero="Every rally, indexed. The dead time, gone.?"
? browser=kn-IN -> html.lang=kn (want kn) | hero="????? ?????????? ?????????? ???, ??"
? browser=hi-IN -> html.lang=hi (want hi) | hero="?? ????, ????. ????? ???, ?????.?"
? browser=es-MX -> html.lang=es (want es) | hero="Cada jugada, indexada. El tiempo muerto, f?"
? browser=da-DK -> html.lang=da (want da) | hero="Hver duel, indekseret. Den døde tid, væk.?"
? browser=id-ID -> html.lang=id (want id) | hero="Setiap reli, terindeks. Waktu kosongnya, h?"
? browser=fr-FR -> html.lang=en (want en) | hero="Every rally, indexed. The dead time, gone.?"
```

ALL PASS: browser/OS language auto-renders the right content (site, client shim, no dropdown).
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

300. assistant (2026-06-22T03:51:50.593Z)

****All 6 auto-render natively from the browser/OS language with zero dropdown interaction**** ? region subtags normalize (es-MX?es), and unsupported (fr) falls back to English. Let me clean up the throwaway worktree and answer.

301. user (2026-06-22T03:52:02.250Z)

worktrees:

```
C:/Users/avidu/Projects/khelsutra      17242a9 [master]
C:/Users/avidu/Projects/khelsutra-p2c   b67e758 [feat/p2c-setup-wizard]
C:/Users/avidu/Projects/khelsutra-wt-hero cf59fbf [feat/site-hero-mockup-i18n]
```

302. assistant (2026-06-22T03:52:26.560Z)

Verified and cleaned up. (I notice my spawned hero-mockup chip already got picked up ? there's now a `feat/site-hero-mockup-i18n` worktree working on it.)

Yes ? all 6 locales auto-render from the browser/OS language, on both surfaces

I just proved it end-to-end rather than assuming it. A browser whose OS/language is set to each locale, with ****no dropdown interaction****, auto-renders that language:

```
| Browser/OS locale | Site renders | ? |
|---|---|---|
| `kn-IN` | ????? ???????? ?????????? (Kannada) | ? |
| `hi-IN` | ?? ?????, ??? ????? (Hindi) | ? |
| `es-MX` | Cada jugada, indexada? (Spanish) | ? |
| `da-DK` | Hver duel, indekseret? (Danish) | ? |
| `id-ID` | Setiap reli, terindeks? (Indonesian) | ? |
| `en-US` | Every rally, indexed? (English) | ? |
| `fr-FR` (unsupported) | English (correct fallback) | ? |
```

****How it works (both surfaces, same contract):**** negotiation order is ***persisted pref** ? `?lang=` ? browser/`Accept-Language` ? en*.

- ****Site**** (`server.js` + `i18n.js` shim): now lists all 6. I confirmed live across all 3 pages ? server stamps ``/`content-language` from `Accept-Language`, and the client shim applies the translated content from `navigator.languages`. Region subtags normalize (`es-MX`?es, `kn-IN`?kn); unsupported (fr/ta)?en.

- ****SPA**** (`web/`, react-i18next + LanguageDetector): `supportedLngs` = all 6 with `nonExplicitSupportedLngs: true` (so `es-419`?es etc.), detecting from navigator. All 6 detection tests pass (kn-IN, hi-IN, es-ES, da-DK, id-ID, en).

Three honest caveats on "natively rendered"

1. ****Kn/Hi glyphs**** still need your ****real-device eyeball**** ? the standing font gate. Noto is bundled (and renders fine on my machine + CI containers don't render fonts), but that's your DoD check. es/da/id are Latin ? no font concern.
2. ****Translation quality**** is AI-drafted ? ****native-review-pending**** for all 5 non-English locales. Auto-***selection*** and ***rendering*** are proven; ***wording*** is the human gate.
3. ****Not 100% of the copy is localized**** ? two pre-existing English islands remain in ****every**** non-en locale (incl. kn/hi): the hardcoded hero-mockup chips (now being fixed via the spawned chip) and the Request-Access form (`site.join.\*`, A6-deferred). So an es/kn/? browser auto-renders the language, but those two specific blocks still show English until those slices land.

So: ****auto-negotiation is complete and working for all 6 on both surfaces**** ? what's left before "fully native" is the two human gates plus those two known English islands.

303. user (2026-06-22T15:52:01.689Z)

I eyeballed the pages and have gotten a formal approval on all the locales from native speakers. Additionally there was work in a sibling session which hardened the tests for rendering fluctuations. Can you sync to remote head, refresh the info and take up the completion of

localization i.e. the 3. on your "natively rendered" list? Additionally, do make sure to verify by rendering that the fixes have applied and please update / add more tests to ensure there is no regression. After that give me a prioritized list of any more localization and friendliness specific AIs which need to be built and we can take it from there.

304. assistant (2026-06-22T15:52:43.574Z)

Two human gates cleared ? that's the big milestone. Let me follow the freshness convention: sync to remote head first, then assess what the sibling sessions landed (test hardening + the hero-mockup chip) before picking up the remaining localization.

305. user (2026-06-22T15:52:49.453Z)

```
From https://github.com/avidullu/khelsutra
- [deleted]          (none)      -> origin/docs/freshness-sweep
  7dc7de5..ba38f15  master      -> origin/master
=== origin/master recent log ===
ba38f15 fix(site): remove dead analytics beacon; use Cloudflare Automatic Setup (#100)
05c7d97 feat(site): add Privacy Policy page + honest trust signals (#96)
7dc7de5 docs: freshness sweep ? reconcile 13 docs with the live repo (+ engine origin/master)
(#95)
50b2bd7 chore(repo): ignore local runtime artifacts + correct stale NEXT_STEPS claims (#94)
e2570e4 docs: archive the Friendly & Multilingual tracker (engineering complete) (#93)
0bef61e docs(friendly-multilingual): close out the chapter ? log #89/#90/#91 + strengthen fitNav
tests (#92)
9f77ddc test(site): browser layout-regression CI guard + auto-collapse the nav to fit every
locale (#91)
4415fe8 feat(site): localize remaining home sections (6 langs) + smooth the responsive header
(#90)
26c9da1 feat(site): localize the hero demo mockup + #how feature block (6 languages) (#89)
7ae9cee feat(web): P2c first-run setup wizard (3 steps from /api/capabilities, 6 languages)
(#88)
cf59fbf feat(site): add es/da/id to the marketing site (parity with the SPA's 6 languages) (#87)
17242a9 feat(site): localize own-model body content to kn/hi (#86)
=== is the hero-mockup branch merged? ===
(no matching merged remote branch)
=== open remote branches ===
  origin/claude/badminton-academy-flyer-w3obpr
  origin/deploy/alpha-cloudflared-kit
  origin/docs/friendly-multilingual-project
  origin/docs/multilingual-expansion-proposal
  origin/feat/flyer-nav-ownmodel-links
  origin/feat/link-academy-flyers
  origin/master
  origin/spa/api-base-env
=== local worktrees ===
C:/Users/avidu/Projects/khelsutra 7dc7de5 [master]
```

306. assistant (2026-06-22T15:53:25.301Z)

Major change ? origin/master jumped from `cf59fbf` to `ba38f15` (#100). Sibling sessions have landed a lot. Let me decode the relevant ones:

```
- **89** ? *localize the hero demo mockup + #how block (6 langs)* ? that's the chip I spawned,
**merged**.
- **90** ? *localize remaining home sections (6 langs)* ? more home localization.
- **91/#92** ? *browser layout-regression CI guard + fitNav* ? the **rendering test hardening**
you mentioned.
- **93** ? *archive the Friendly & Multilingual tracker (engineering complete)* ? the tracker
doc was **archived**.
- **96/#100** ? Privacy Policy page; **removed the dead analytics beacon** (the localhost CORS
error).
```

So the landscape shifted under me. Let me refresh thoroughly before acting ? re-read the handoff

and check what's **actually** still English (esp. the access form) on the current head.

307. user (2026-06-22T15:53:26.021Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22 ? **CHAPTER ARCHIVED
([#93](https://github.com/avidullu/khelsutra/pull/93), master e2570e4).** The Friendly &
Multilingual tracker is engineering-complete and **moved to
`docs/archives/FRIENDLY_AND_MULTILINGUAL.md`**. Both surfaces speak all 6 languages; the home
page body is fully localized (except the deferred #join form, A6); the responsive header is
fixed + CI-guarded (#91). Prior PRs: ?#89 (hero/#how) ? #90 (home sections + header) ? #91
(layout CI guard + full-locale fix) ? #92 (closeout sweep + fitNav tests) ? #93 (archive)._
4
5      **? Nothing left to resume here ? only owner QA, now tracked in `NEXT_STEPS.md`:** (1)
**native-speaker review** of the AI-drafted catalogs (kn/hi/es/da/id), (2) **owner font-glyph
eyeball** on a real kn/hi device, (3) **B7** (engine backend l10n, deferred, cross-repo). None
are engineering.
6
7      **Header is now robust across ALL 6 locales + guarded.** #90's fix only covered
en/kn/hi/id; the #91 layout guard caught that **es (+138px) / da (+47px)** still overflowed
(longer translated nav labels). Fixed in #91: the shim (`fitNav` in `site/public/i18n.js`)
measures the header after applying a locale (+ on resize / fonts.ready) and adds `.nav-crowded`
to collapse the 6-link nav to a compact brand+switcher+CTA row when it won't fit ? **measured
live, so it self-adapts to any future translation length.** New CI: a `layout` job runs `npm run
test:layout` = `site/src/layout.browser.mjs` (headless Chromium/Playwright, a site test-only
devDep) asserting header invariants (no overflow / no link-wrap / CTA not clipped / no h-scroll)
across widths × 6 locales on index/capture/own-model. jsdom can't see layout, so this is the
only guard for rendering distortion ? extend it when touching site CSS/markup.
8
9      ## You are here ? chapter effectively COMPLETE (pending human gates)
10     $7 of `docs/archives/FRIENDLY_AND_MULTILINGUAL.md` is **all ? except the owner-gated,
cross-repo B7** (deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-
friendly:
11     - **SPA (`web/`)**: en/kn/hi + es/da/id (B1?B6 + MLX). **Site (`site/`)**: **en/kn/hi +
es/da/id** ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy (kn/hi via
A3, **es/da/id via #87**; Noto bundled for kn/hi), A6 plain-language access form, A7 camera-
placement diagram, **A2 WhatsApp share** (#82), the **UI/UX header pass** (#83: compact `?
<select>`, zero overflow), own-model body (#86), and the **es/da/id site expansion** (#87): the
full `site.` namespace (115 keys) translated ? site now matches the SPA's 6 (dropdown has 6
options; `SUPPORTED`/`SITE_LOCALES`=6).
12     - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77**; web
coverage floor added in **#80**.
13     - Sister repo **rally-annotator is also localized (kn/hi/es/da/id/te)** ? the journey
annotator ? site ? Studio is consistent in the user's language.
14     - **No engineering gap remains** before the two human gates. (own-model #86 + es/da/id
site #87 both closed.)
15
16     ## What gates archival (NOT code ? don't `git mv` to docs/archives until these clear)
17     1. **Native-speaker review** of the AI-drafted catalogs (kn/hi + now **es/da/id** site,
all AI-drafted) ? the standing guardrail before a wide public launch.
18     2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts).
Proxy screencasts in `C:/Users/avidu/Projects/khelsutra-screencast/:` `khelsutra-
site-i18n-desktop.mp4` (site home+capture, kn) + `khelsutra-i18n-screencast.mp4` (SPA, kn-IN) +
**khelsutra-ownmodel-i18n-desktop.webm** (#86, own-model en?kn?hi; stills
`ownmodel-{kn,hi}-{hero,full}.png`).
19
20     ## Open engineering follow-ups (small)
21     - **own-model body content English on kn/hi** ? **DONE (#86).** **es/da/id site only en-
seed** ? **DONE (#87).**
22     - **Hardcoded hero-mockup chips in `site/public/index.html`** ? **DONE & MERGED (PR
[#89](https://github.com/avidullu/khelsutra/pull/89)).** Wired the full hero block (CTA +
`phone/GoPro` note + 3 process chips + the reel-card demo mockup) **and** the `#how` "What it
does today" feature block (head + 4 cards): 21 new `site.hero.{ctaReel,note,loop.*,demo.*}` +
`site.how.*` keys, translated kn/hi/es/da/id (AI-draft ? adversarial review ? revised; native-
```

review-pending). Extended `assets.test.js` + `i18n.shim.test.js`. Rebased onto #88's `wizard.\*` catalog namespace.

23 - ~~Still-hardcoded home-page sections
 (`#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq`)~~ ? **DONE & MERGED (PR [#90](https://github.com/avidullu/khelsutra/pull/90)).** 65 new
 `site.{diff,sharper,ask,roadmap,not,faq}.\*` keys, translated kn/hi/es/da/id via a `translate` ? 2-lens adversarial verify ? revise `\*\*Workflow\*\*` (20 agents); native-review-pending. **#90 also fixed the responsive header** (the ~860?1080px dead zone where the 6 nav-links wrapped/overlapped the brand + clipped the CTA): nav-links now `gap:1rem`/`.9rem`/`nowrap` and hide below `max-width:1080px` (clean brand+switcher+CTA row); grid breakpoint stays 860. Verified in-browser en/id @ 1280/1000/864/375px.

24 - **Only English left on the home page:** the footer (`Automatic badminton highlights?`, flyer line, `© 2026?` stamp ? ~4 small strings) and the `#join` access form (`site.join.\*`, A6, below). A tiny footer slice would make the home page 100%.

25 - **Access form `site.join.\*`** ? still English in ALL non-en locales (A6 deferred); the largest remaining untranslated marketing surface. Same A3-style slice; would need all 6 langs to keep parity.

26 - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.

27 - Minor: `site.\*` adds ~27KB to the SPA bundle (could split to a site-only catalog); ratchet web coverage thresholds as `App.tsx` gains tests.

28

29 ## Ramp-up kit

30 - `docs/archives/FRIENDLY\_AND\_MULTILINGUAL.md` ? \$7 tracker (source of truth, all ? except B7), \$6.5 N1?N9, \$9 DoD (boxes flipped; 2 human gates open), changelog.

31 - `/locales/{en,kn,hi,es,da,id}/common.json` ? shared catalog: SPA console keys + `site.\*` (nav/hero/record/capture/join/ownModel/reveal).

32 - `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, compact `` switcher, `window.KhelSutra.t` bridge, negotiation), `site/server.js`, `site/scripts/copy-locales.mjs`, `site/src/{i18n.shim,locales-drift,assets,server}.test.js`.

33 - Screencast/Playwright tooling + before/after eval shots: `C:/Users/avidu/Projects/khelsutra-screencast/` (`site-screencast.mjs`, `deep-test.mjs`, `eval-shots.mjs`).

34 - `[[catalog-home-and-i18n-layout]]`, `[[shared-checkout-concurrency]]`.

35

36 ## Key decisions (don't relitigate)

37 - D-CATALOG-HOME: catalogs at repo-root `/locales`; SPA imports; site mirrors via `copy:locales` + drift guard.

38 - Negotiation order (both surfaces): persisted (`khelsutra.lang`) ? `?lang=` ? navigator/Accept-Language ? en; missing key ? en, never a raw key.

39 - Switcher = compact `` in the header (kept there for discoverability/signal; auto-negotiation covers kn-phones). Rich `**` markup localizes via `data-i18n-html` (XSS-safe; catalog-authored).**

40 - Process: isolated `git worktree` per PR (shared checkout churns fast); AI-draft translations ? adversarial verify ? native review is a pre-launch (not pre-merge) gate.

41

308. user (2026-06-22T15:53:31.312Z)

=== site.join.* ? translated or still English on origin/master? (es vs en, kn vs en) ===
 node:fs:436

```
    return binding.readFileUtf8(path, stringToFlags(options.flag));
    ^
```

```
Error: ENOENT: no such file or directory, open 'C:\tmp\_en.json'
    at Object.readFileSync (node:fs:436:20)
    at [eval]:3:24
    at runScriptInThisContext (node:internal/vm:219:10)
    at node:internal/process/execution:483:12
    at [eval]-wrapper:6:24
    at runScriptInContext (node:internal/process/execution:481:60)
    at evalFunction (node:internal/process/execution:315:30)
    at evalTypeScript (node:internal/process/execution:327:3)
    at node:internal/main/eval_string:71:3 {
  errno: -4058,
```

```

code: 'ENOENT',
syscall: 'open',
path: 'C:\\tmp\\_en.json'
}

```

Node.js v26.1.0

=== where is the tracker doc now? ===

docs/MULTILINGUAL_EXPANSION.md

docs/archives/FRIENDLY_AND_MULTILINGUAL.md

309. assistant (2026-06-22T15:53:56.739Z)

The handoff (updated by the sibling sessions) is clear. The chapter was archived (#93); the home page is now localized ****except two islands****: (1) the footer (~4 strings) and (2) the `#join` access form (`site.join.\*`, A6). Plus #96 added a ****Privacy Policy page**** I need to check. Let me create a fresh worktree at remote head and do a comprehensive "remaining English" audit there.

310. user (2026-06-22T15:54:01.128Z)

branch 'feat/localize-site-remaining' set up to track 'origin/master'.

HEAD is now at ba38f15 fix(site): remove dead analytics beacon; use Cloudflare Automatic Setup (#100)

=== HEAD ===

ba38f15 fix(site): remove dead analytics beacon; use Cloudflare Automatic Setup (#100)

=== site pages present (any new ones, e.g. privacy)? ===

/c/Users/avidu/Projects/ks-remaining/site/public/capture.html

/c/Users/avidu/Projects/ks-remaining/site/public/flyer-hi.html

/c/Users/avidu/Projects/ks-remaining/site/public/flyer-kn.html

/c/Users/avidu/Projects/ks-remaining/site/public/flyer.html

/c/Users/avidu/Projects/ks-remaining/site/public/index.html

/c/Users/avidu/Projects/ks-remaining/site/public/own-model.html

/c/Users/avidu/Projects/ks-remaining/site/public/privacy.html

=== site/package.json scripts + playwright dep? ===

node:internal/modules/cjs/loader:1505

throw err;

^

Error: Cannot find module '/c/Users/avidu/Projects/ks-remaining/site/package.json'

Require stack:

```

- C:\Users\avidu\Projects\khelsutra\[eval]
  at Module._resolveFilename (node:internal/modules/cjs/loader:1502:15)
  at wrapResolveFilename (node:internal/modules/cjs/loader:1073:27)
  at defaultResolveImplForCJSLoading (node:internal/modules/cjs/loader:1097:10)
  at resolveForCJSWithHooks (node:internal/modules/cjs/loader:1118:12)
  at Module._load (node:internal/modules/cjs/loader:1287:25)
  at wrapModuleLoad (node:internal/modules/cjs/loader:255:19)
  at Module.require (node:internal/modules/cjs/loader:1602:12)
  at require (node:internal/modules/helpers:191:16)
  at [eval]:1:9
  at runScriptInThisContext (node:internal/vm:219:10) {
  code: 'MODULE_NOT_FOUND',
  requireStack: [ 'C:\\Users\\avidu\\Projects\\khelsutra\\[eval]' ]
}

```

Node.js v26.1.0

=== main checkout site node_modules has playwright? ===

ABSENT

311. assistant (2026-06-22T15:54:10.350Z)

cwd reset tripped the require. Let me audit from inside the worktree ? package config, the new privacy page, and the actual remaining-English state (footer, access form, privacy).

312. user (2026-06-22T15:54:18.209Z)

```
=== package scripts + devDeps ===
scripts: {"test":"node --test","test:cf":"node --test src/index.test.js","test:vm":"node --test
src/server.test.js","test:deploy":"node --test src/deploy-config.test.js
src/assets.test.js","test:layout":"node --test src/layout.browser.mjs","copy:locales":"node
scripts/copy-locales.mjs","predeploy":"node scripts/copy-locales.mjs","deploy":"wrangler
deploy","dev":"wrangler dev","og":"python make_og.py"}
devDeps: {"jsdom":"^29.1.1","playwright":"^1.61.0"}

=== site.join.* + privacy/footer namespaces: translated or English? ===
site.* namespaces: reveal, join, nav, hero, record, capture, ownModel, how, diff, sharper, ask,
roadmap, not, faq
join: 14 keys | es still==en: 14/14
join: 14 keys | kn still==en: 14/14
footer: (no such namespace in en catalog)
privacy: (no such namespace in en catalog)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

313. assistant (2026-06-22T15:54:43.929Z)

Precise picture now:

- **Access form** (`site.join.\*`, 14 keys): wired but 100% English in **all** non-en locales ? the main remaining island.
- **Footer**: no `site.footer.\*` namespace ? hardcoded, needs wiring + translation.
- **Privacy page** (`privacy.html`, new in #96): no `site.privacy.\*` namespace ? likely English-only.

Let me check the privacy page's i18n state and the footer markup to scope precisely.

314. user (2026-06-22T15:54:49.314Z)

```
=== privacy.html: wired for i18n at all? ===
i18n hooks (shim+data-i18n+switcher) count: 0
2:<html lang="en">
6:<title>Privacy Policy ? KhelSutra</title>
--- privacy.html size + section count ---
193 public/privacy.html
h1/h2 count: 12
```

```
=== is privacy in server.js LOCALIZED_PAGES + routed? ===
41:const LOCALIZED_PAGES = new Set(["index.html", "capture.html", "own-model.html"]);
100:   : pathname === "/privacy" ? "privacy.html"
110:   if (LOCALIZED_PAGES.has(rel)) {
```

```
=== index.html footer block ===
```

```
366:   <p style="margin:0;color:var(--tx)"><b data-i18n="site.record.goldenRuleLead">The
golden rule: one match, one court, in full frame ? and don't move the camera.</b> <span
style="color:var(--mut)" data-i18n="site.record.goldenRuleRest">A single court in frame gives
the best results today; busy multi-court footage is the hard case we're still
sharpening.</span></p>
405:   <p style="color:var(--mut);font-size:1.05rem" data-i18n-html="site.diff.p2">A single
recording of a busy, multi-court hall is exactly where ordinary video tools choke. Pulling the
<b style="color:var(--tx)">real</b> rallies out of busy, multi-court footage is the hard problem
KhelSutra is built for. It already works very well on clean, single-court recordings ? and the
multi-court case is what we're sharpening now.</p>
420:   <h2 data-i18n="site.sharper.title">It gets sharper from real academy footage</h2>
421:   <p data-i18n="site.sharper.intro">The footage real academies contribute ? especially
the busy multi-court halls ? is what makes KhelSutra better over time. Early users aren't just
customers; they're co-builders.</p>
427:   <p data-i18n="site.sharper.improve.body">When you choose to share footage and
coaches confirm what it found, that growing labelled library is what sharpens future versions ?
rather than staying frozen.</p>
432:   <p data-i18n="site.sharper.data.body">We never use your video to improve the tool
without your clear, explicit opt-in. We never publish your footage. You decide what, if
```

anything, you share.</p>

437: <p data-i18n="site.sharper.minors.body">Footage involving minors is never used to improve the tool and is never published ? full stop.</p>

442: <p data-i18n="site.sharper.honestBody">Today the tool gives you rally detection, reels, and summaries. It does not retrain itself as you use it, and there's no per-person tracking. "Gets sharper over time" is the model we're building toward, powered by contributed footage ? not a switch that's already on.</p>

516: <details><summary data-i18n="site.faq.q4.q">Is my video private? What happens to it?</summary><p data-i18n="site.faq.q4.a">We treat your footage as private: we never publish it, and we never use it to improve the tool without your explicit opt-in. These are large videos that need real processing, so your video is handled securely on our infrastructure to make your reel. Footage involving minors is never used and never published.</p></details>

517: <details><summary data-i18n="site.faq.q5.q">Does it work for doubles and tournaments?</summary><p data-i18n="site.faq.q5.a">It finds rallies in doubles too. Tournament footage varies ? a clean, fixed, full-court recording works well; crowded multi-court tournament halls are the hard case we're specifically working on.</p></details>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

315. assistant (2026-06-22T15:55:23.834Z)

Scope crystallizing. The **privacy page** (#96) has zero i18n hooks ? it's a substantial new English-only legal page; that's a larger, newer surface I'll put in the prioritized list rather than silently 6x-translate legal text. For "completion of the 3," the concrete remaining home-page islands are the **access form** (`site.join.` , wired but English) and the **footer**. Let me see the exact footer + form markup.

316. user (2026-06-22T15:55:25.986Z)

=== index.html footer (the real <footer>/.foot block) ===

613:<footer>

626:</footer>

--- show the footer region ---

613: <footer>

614: <div class="wrap foot">

615: <div>

616: <div class="brand" style="font-size:1.05rem">KhelSutra</div>

617: <div class="stamp" style="margin-top:.4rem">Automatic badminton highlights . Bengaluru, India</div>

618: </div>

619: <div style="text-align:right">

620: <div>Own your model . Capture checklist . Privacy . hello@khelsutra.guru . khelsutra.guru</div>

621: <div style="margin-top:.4rem">Academy flyer (print): English . ????? . ?????</div>

622: <div class="stamp" style="margin-top:.4rem">? Served securely over HTTPS . ? Run from Bengaluru, India . Reels carry a "Generated by Khelsutra.guru" mark</div>

623: <div class="stamp" style="margin-top:.2rem">© 2026 KhelSutra . Invite-only alpha</div>

624: </div>

625: </div>

626: </footer>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

317. assistant (2026-06-22T15:55:59.766Z)

Footer = ~6 hardcoded strings (tagline, footer nav, "Academy flyer (print):", trust line, © stamp). Let me confirm the access form is fully wired (so it only needs translation) and check whether the other pages' footers are already handled, then kick off dependency setup.

318. user (2026-06-22T15:56:05.561Z)


```

=== access form: all 14 site.join.* keys wired with data-i18n in index.html? ===
distinct site.join data-i18n keys wired: 14
=== capture.html + own-model.html footers ? already localized or hardcoded? ===
--- capture ---
  <div class="foot">
    <span><span data-i18n="site.capture.questions">Questions?</span> <a
href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></span>
    <span class="noprint" data-i18n="site.capture.printTip">Tip: press Ctrl/Cmd + P to print or
save as PDF.</span>
--- own-model ---
  <div class="foot">
    <span><a href="/">khelsutra.guru</a> · <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> · <span data-i18n="site.ownModel.foot.flyer">Academy
flyer:</span> <a href="/flyer" hreflang="en">English</a> · <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> · <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></span>
    <span data-i18n="site.ownModel.foot.mark">Reels carry a "Generated by Khelsutra.guru"
mark.</span>
=== kick off deps ===
main web/node_modules present (copyable)
playwright browser cache: chromium-1228 chromium_headless_shell-1228 ffmpeg-1011
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

319. assistant (2026-06-22T15:56:37.773Z)

Scope is firm and tight:

1. ****Access form**** (`site.join.\*`, 14 keys) ? fully wired already, just needs translation to kn/hi/es/da/id.
2. ****Index footer**** (~6 strings) ? hardcoded; needs wiring + translation. (capture/own-model footers are already localized.)

Both ? home page 100% native. Privacy page goes in the prioritized list. Let me kick off dependency setup (background) and start wiring the footer.

320. user (2026-06-22T15:56:41.755Z)

Command running in background with ID: byv1xdbhw. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\byv1xdbhw.output. You will be notified when
it completes. To check interim output, use Read on that file path.

321. assistant (2026-06-22T15:57:06.567Z)

While deps install, let me wire the index footer (keeping English defaults, reusing
`site.nav.ownModel` for that link, 6 new `site.footer.\*` keys).

322. user (2026-06-22T15:57:14.493Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

323. assistant (2026-06-22T15:57:18.828Z)

Deps installed. Let me read the footer region first, then wire it.

324. user (2026-06-22T15:57:19.209Z)

```

613     <footer>
614       <div class="wrap foot">
615         <div>
616           <div class="brand" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</div>
617           <div class="stamp" style="margin-top:.4rem">Automatic badminton highlights ·
Bengaluru, India</div>
618         </div>

```

```

619         <div style="text-align:right">
620             <div><a href="/own-model">Own your model</a> · <a href="/capture">Capture
checklist</a> · <a href="/privacy">Privacy</a> · <a
href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
621         <div style="margin-top:.4rem">Academy flyer (print): <a href="/flyer"
hreflang="en">English</a> · <a href="/flyer-kn" hreflang="kn" lang="kn">????</a> · <a
href="/flyer-hi" hreflang="hi" lang="hi">????</a></div>
622         <div class="stamp" style="margin-top:.4rem">? Served securely over HTTPS · ? Run
from Bengaluru, India · Reels carry a "Generated by Khelsutra.guru" mark</div>
623         <div class="stamp" style="margin-top:.2rem">© 2026 KhelSutra · Invite-only
alpha</div>
624     </div>
625 </div>
626 </footer>

```

325. user (2026-06-22T15:57:30.422Z)

The file C:\Users\avidu\Projects\ks-remaining\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

326. assistant (2026-06-22T15:57:42.439Z)

Footer wired. Now let me author the en `site.footer.\*` keys byte-for-byte (jsdom extraction), seed them into all 6 catalogs for key-parity, and build the translation payload (the 14 `site.join` + 6 `site.footer` keys + per-locales console vocabulary).

327. assistant (2026-06-22T15:57:55.386Z)

```

// One-off authoring helper (NOT shipped): (1) extract site.footer.* en values byte-for-byte
from the
// wired index.html, (2) seed them into all 6 catalogs (en authoritative; non-en seeded = en
until the
// workflow translates), (3) emit the translation payload for site.join.* (already wired) +
site.footer.*.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const html = readFileSync(join(ROOT, "site", "public", "index.html"), "utf8");
const { document } = new JSDOM(html).window;

// 1) extract site.footer.* (textContent ? these are plain strings, no inline markup)
const footer = {};
for (const el of document.querySelectorAll('[data-i18n^="site.footer."'])) {
    const key = el.getAttribute("data-i18n").slice("site.footer.".length);
    footer[key] = el.textContent.trim();
}
console.error("extracted site.footer.* keys:", Object.keys(footer).join(", "));

// 2) seed into every catalog (en = authoritative; non-en seeded with en for now -> key-parity
green)
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
    const cat = load(loc);
    cat.site.footer = cat.site.footer || {};
    for (const [k, v] of Object.entries(footer)) {
        if (loc === "en" || !(k in cat.site.footer)) cat.site.footer[k] = v; // don't clobber an
existing translation
    }
    writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
}
console.error("seeded site.footer.* into all 6 catalogs");

```

```
// 3) build the payload: en values for the keys to translate (join 14 + footer 6) + per-locale
console ref
const en = load("en");
const enTargets = {};
for (const k of Object.keys(en.site.join)) enTargets[`site.join.${k}`] = en.site.join[k];
for (const k of Object.keys(footer)) enTargets[`site.footer.${k}`] = footer[k];
const refOf = (c) => ({
  app: c.app, query_support: c.query.support, grid_rally: c.grid.rally,
  ingest_title: c.ingest.title, result_ready: c.result.ready, lang: c.lang,
  // existing site translations in this locale for register (nav + a hero line + the GPU-free
  reassurance area)
  site_nav: c.site.nav, site_hero_eyebrow: c.site.hero.eyebrow, site_record_intro:
  c.site.record.intro,
});
const payload = { enTargets, ref: { kn: refOf(load("kn")), hi: refOf(load("hi")), es:
  refOf(load("es")), da: refOf(load("da")), id: refOf(load("id")) } };
writeFileSync(join(ROOT, "site", "scripts", "_payload.json"), JSON.stringify(payload));
console.error("payload keys:", Object.keys(enTargets).length, "| bytes:",
  JSON.stringify(payload).length);
process.stdout.write(JSON.stringify(footer, null, 2) + "\n");
```

328. user (2026-06-22T15:57:55.405Z)

File created successfully at: C:\Users\avidu\Projects\ks-remaining\site\scripts_prep.mjs (file state is current in your context ? no need to Read it back)

329. user (2026-06-22T15:58:02.676Z)

```
extracted site.footer.* keys: tagline, capture, privacy, flyer, trust, copyright
seeded site.footer.* into all 6 catalogs
payload keys: 20 | bytes: 6538
{
  "tagline": "Automatic badminton highlights · Bengaluru, India",
  "capture": "Capture checklist",
  "privacy": "Privacy",
  "flyer": "Academy flyer (print):",
  "trust": "? Served securely over HTTPS · ? Run from Bengaluru, India · Reels carry a
\"Generated by Khelsutra.guru\" mark",
  "copyright": "© 2026 KhelSutra · Invite-only alpha"
}
--- copy:locales ---
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

330. assistant (2026-06-22T15:58:15.570Z)

Footer seeded across all 6 (key-parity holds), payload = 20 keys (14 join + 6 footer). Let me confirm the wiring is structurally sound (drift guard + parity) before translating.

331. user (2026-06-22T15:58:18.634Z)

```
? tests 89
? pass 89
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

332. assistant (2026-06-22T15:58:23.987Z)

89 site tests green (drift guard validates the footer en values). Now let me read the payload and launch the translation workflow for the 20 keys across all 5 non-English locales.

333. user (2026-06-22T15:58:24.385Z)

```
1      {"enTargets":{"site.join.gpuLabel":"Do you have a powerful computer that could process
```

```

videos on its own?", "site.join.gpuHint": "A gaming PC or laptop with a graphics card. No worries if not ? we can run it in the cloud for you.", "site.join.gpuYes": "Yes ? a gaming PC or laptop with a graphics card", "site.join.gpuUnsure": "Not sure", "site.join.gpuNo": "No", "site.join.gpuCloud": "No ? please run it in the cloud for me", "site.join.storageLabel": "Where do your match videos live? How would you share them?", "site.join.storageHint": "(pick any)", "site.join.storageGdrive": "Google Drive", "site.join.storageOnedrive": "OneDrive / Microsoft 365", "site.join.storageDropbox": "Dropbox", "site.join.storageBucket": "A cloud storage bucket ? advanced (e.g. Amazon S3, Google Cloud)", "site.join.storageLocal": "SD card or the device itself", "site.join.storageUnsure": "Not sure", "site.footer.tagline": "Automatic badminton highlights · Bengaluru, India", "site.footer.capture": "Capture checklist", "site.footer.privacy": "Privacy", "site.footer.flyer": "Academy flyer (print):", "site.footer.trust": "? Served securely over HTTPS · ? Run from Bengaluru, India · Reels carry a \"Generated by Khelsutra.guru\" mark", "site.footer.copyright": "© 2026 KhelSutra · Invite-only alpha", "ref": {"kn": {"app": {"badge": "????-???? ???? · ????", "title": "???? ?????????? ?????????? ?????", "intro": "<b>????? ????</b> ? ?????????? ?????? ? ??? . <i>????? ???? ???? 15?</i> ? ??? ? ?????????????? ?????? ??? ? ?????????? ???????. ?????? <b>?????????</b> ??????????????????; ?????????????? ?????? ??????????."}, "query_support": "<b>????? ????</b>? ?????????? ?????????? ?????????? ???????????????. ???-????? <x>?????????</x> (????????????????).", "grid_rally": "????? {n}", "ingest_title": "????? ??????????????", "result_ready": "????? ??? ??????????", "lang": {"label": "????", "en": "English", "kn": "?????", "hi": "???????", "es": "Español", "da": "Dansk", "id": "Bahasa Indonesia"}, "site_nav": {"how": "?? ???? ??? ??????????", "why": "?? ???? ???? ????", "ownModel": "????????? ??????", "flyer": "?????????", "roadmap": "?????????", "faq": "?????????????", "requestAccess": "????????? ?????"}, "site_hero_eyebrow": "?????-????? ???? · ??????????", "site_record_intro": "????? ?????? ?????????????????? ??????????????. ?????????????? ?????? ??? ?????????? ???? ? ?????????????? ?????? KhelSutra ? ???? ???? ? ??????????."}, "hi": {"app": {"badge": "???? ?????? ???? · ??????", "title": "???? ???? ? ???? ?????? ??????", "intro": "<b>???? ? ????</b> ? ???? ? ? ?????? ???? ? ???? <i>????? ???? ???? 15?</i> ? ??? ?????? ???? ???? ?????? ? ???? ???? ???? ???? <b>?????</b> ???? ??; ? ? ???? ?????? ?????? ???? ????"}, "query_support": "<b>???? ? ????</b> ? ???? ? ? ?????????? ???? ???? ???? ???? ????-????? <x>?????????</x> ? ? (?? ? ? ?? ?)?", "grid_rally": "???? {n}", "ingest_title": "????? ?????????? ??????", "result_ready": "???? ???? ?????? ??", "lang": {"label": "????", "en": "English", "kn": "?????", "hi": "????????", "es": "Español", "da": "Dansk", "id": "Bahasa Indonesia"}, "site_nav": {"how": "?? ???? ??? ?????? ??", "why": "?? ?????? ?????????? ??", "ownModel": "???? ???? ??????", "flyer": "?????????", "roadmap": "?????????", "faq": "????????? ??????????", "requestAccess": "????? ? ? ?????? ?????"}, "site_hero_eyebrow": "????-????? ???? · ??????????", "site_record_intro": "????????? ? ???? ???? ???? ???? KhelSutra ? ???? ? ???? ???? ????"}, "es": {"app": {"badge": "elige tus jugadas · alfa", "title": "Elige las jugadas para tu reel", "intro": "Filtra por <b>duración de la jugada</b> ? p. ej. <i>?las 15 más largas?</i> ? y luego ajusta tocando las tarjetas. Todo empieza <b>seleccionado</b>; solo quita las que no quieras."}, "query_support": "Filtrar por <b>duración de la jugada</b> es totalmente compatible. El conteo de golpes es <x>experimental</x> (en desarrollo).", "grid_rally": "Jugada {n}", "ingest_title": "Procesar un video", "result_ready": "Tu reel está listo", "lang": {"label": "Idioma", "en": "English", "kn": "?????", "hi": "????????", "es": "Español", "da": "Dansk", "id": "Bahasa Indonesia"}, "site_nav": {"how": "Cómo funciona", "why": "Por qué es difícil", "ownModel": "Tu propio modelo", "flyer": "Folleto", "roadmap": "Hoja de ruta", "faq": "Preguntas frecuentes", "requestAccess": "Solicitar acceso"}, "site_hero_eyebrow": "Alfa solo por invitación · Bengaluru", "site_record_intro": "La calidad de las jugadas destacadas empieza con la grabación. Coloca la cámara así una sola vez y KhelSutra tendrá todo lo que necesita para encontrar las jugadas."}, "da": {"app": {"badge": "vælg dine dueller · alfa", "title": "Vælg duellerne til din reel", "intro": "Filtrér efter <b>duellens længde</b> ? f.eks. <i>?de 15 længste?</i> ? og finjustér ved at trykke på kortene. Alt starter <b>valgt</b>; fjern blot dem, du ikke vil have."}, "query_support": "Filtrering efter <b>duellens længde</b> understøttes fuldt ud. Slagtælling er <x>eksperimentel</x> (under udvikling).", "grid_rally": "Duel {n}", "ingest_title": "Behandl en video", "result_ready": "Din reel er klar", "lang": {"label": "Sprog", "en": "English", "kn": "?????", "hi": "????????", "es": "Español", "da": "Dansk", "id": "Bahasa Indonesia"}, "site_nav": {"how": "Sådan fungerer det", "why": "Hvorfor det er svært", "ownModel": "Din egen model", "flyer": "Flyer", "roadmap": "Køreplan", "faq": "FAQ", "requestAccess": "Anmod om adgang"}, "site_hero_eyebrow": "Alfa ? kun med invitation · Bengaluru", "site_record_intro": "Kvaliteten af dine highlights begynder med optagelsen. Stil kameraet op én gang på denne måde, så har KhelSutra alt, hvad den skal bruge for at finde duellerne."}, "id": {"app": {"badge": "pilih reli kamu · alfa", "title": "Pilih reli untuk reel kamu", "intro": "Filter berdasarkan <b>durasi reli</b> ? mis. <i>?15 terpanjang?</i> ? lalu sesuaikan dengan mengetuk kartu. Semua dimulai <b>terpilih</b>; cukup hapus yang tidak kamu"}

```

inginkan."},"query_support":"Memfilter berdasarkan durasi reli sepenuhnya didukung. Hitungan pukulan masih <x>eksperimental</x> (dalam pengembangan).","grid_rally":"Reli {n}","ingest_title":"Proses video","result_ready":"Reel kamu siap","lang":{"label":"Bahasa","en":"English","kn":"?????", "hi":"?????", "es":"Español", "da":"Dansk", "id":"Bahasa Indonesia"},"site_nav":{"how":"Cara kerjanya","why":"Mengapa ini sulit","ownModel":"Miliki modelmu sendiri","flyer":"Flyer","roadmap":"Roadmap","faq":"FAQ","requestAccess":"Minta akses"},"site_hero_eyebrow":"Alfa khusus undangan · Bengaluru","site_record_intro":"Kualitas highlight dimulai dari rekamannya. Atur kamera sekali seperti ini dan KhelSutra sudah punya semua yang diperlukannya untuk menemukan reli."}}}

334. assistant (2026-06-22T15:58:43.030Z)

Payload ready (20 keys + per-locale register references). Let me launch the translation workflow across all 5 non-English locales.

335. user (2026-06-22T15:59:34.079Z)

Workflow launched in background. Task ID: wfgngnmyr
Summary: AI-draft + adversarially verify the access form (site.join.*) + footer (site.footer.*) in kn/hi/es/da/id
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_639ac474-f01
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-join-footer-wf_639ac474-f01.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-join-footer-wf_639ac474-f01.js"} to iterate without resending the script.)
Run ID: wf_639ac474-f01
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-join-footer-wf_639ac474-f01.js", resumeFromRunId: "wf_639ac474-f01"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

336. assistant (2026-06-22T15:59:50.268Z)

Workflow running (5 locales × draft?3-lens-verify?revise). While it runs, let me prepare the apply script and study the sibling's rendering guard (`layout.browser.mjs`) that I'll need to run and possibly extend.

337. assistant (2026-06-22T15:59:56.800Z)

```
// One-off authoring helper (NOT shipped): merge the workflow's join+footer translations into the
// kn/hi/es/da/id catalogs. Input: site/scripts/_jf.json = { kn:{"site.<dotted>":v,...}, hi, es, da, id }.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const en = load("en");
const EXPECTED = [
  ...Object.keys(en.site.join).map((k) => `site.join.${k}`),
  ...Object.keys(en.site.footer).map((k) => `site.footer.${k}`),
];
const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_jf.json"), "utf8"));
let bad = 0;
for (const loc of ["kn", "hi", "es", "da", "id"]) {
  const f = T[loc];
  if (!f) { console.error(`MISSING ${loc}`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in f));
```

```

if (missing.length) { console.error(`${loc} MISSING:`, missing.join(", ")); bad++; }
const cat = load(loc);
for (const dotted of EXPECTED) {
  if (!(dotted in f)) continue;
  const parts = dotted.split(".");
  let o = cat; for (let i = 0; i < parts.length - 1; i++) o = o[parts[i]] = o[parts[i]] || {};
  o[parts[parts.length - 1]] = f[dotted];
}
writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
console.log(`${loc}: applied ${EXPECTED.filter((k) => k in f).length}/${EXPECTED.length}`);
}
if (bad) process.exit(1);
console.log("OK");

```

338. user (2026-06-22T15:59:56.818Z)

File created successfully at: C:\Users\avidu\Projects\ks-remaining\site\scripts_apply.mjs (file state is current in your context ? no need to Read it back)

339. user (2026-06-22T16:00:00.078Z)

```

1      // Browser-layout regression guard (NOT part of `npm test` ? it needs a real browser
engine, so it
2      // runs as a separate `npm run test:layout` job in CI). The rest of the suite runs in
jsdom, which
3      // has NO layout engine (getBoundingClientRect() is all zeros) and therefore cannot see
overflow,
4      // wrapping, or clipping. This drives a headless Chromium over the REAL pages at a
spread of
5      // viewport widths x all 6 locales and asserts the header never distorts ? the exact
class of bug
6      // that bit the responsive nav three times (links wrapping onto 3 lines + overlapping
the brand, and
7      // the "Request access" CTA getting clipped off the right edge in wide-autonym locales
like id).
8      //
9      // Assertions are layout INVARIANTS (inequalities with generous tolerances), not pixel
screenshots ?
10     // so they're robust across OS/font environments and need no baselines, while still
catching the
11     // gross distortions that actually happened (50-75px of overflow / a 3-line nav).
12     import { test, before, after } from "node:test";
13     import assert from "node:assert/strict";
14     import { createServer } from "node:http";
15     import { readFile } from "node:fs/promises";
16     import { join, extname } from "node:path";
17     import { chromium } from "playwright";
18
19     const PUBLIC = join(import.meta.dirname, "..", "public");
20     const TYPES = {
21       ".html": "text/html; charset=utf-8", ".js": "text/javascript", ".mjs":
"text/javascript",
22       ".json": "application/json", ".css": "text/css", ".png": "image/png", ".jpg":
"image/jpeg",
23       ".svg": "image/svg+xml", ".webp": "image/webp", ".webm": "video/webm", ".mp4":
"video/mp4",
24       ".woff2": "font/woff2", ".woff": "font/woff", ".ico": "image/x-icon",
25     };
26
27     let server, browser, baseUrl;
28
29     before(async () => {
30       // Minimal static server for site/public (clean-URL fallback: /capture ->
capture.html).
31       server = createServer(async (req, res) => {

```

```

32     try {
33         let p = decodeURIComponent(req.url.split("?")[0]);
34         if (p === "/" ) p = "/index.html";
35         let data, ext = extname(p);
36         try { data = await readFile(join(PUBLIC, p)); }
37         catch { try { data = await readFile(join(PUBLIC, p + ".html")); ext = ".html"; }
38         res.writeHead(404); return res.end("not found"); } }
39         res.writeHead(200, { "content-type": TYPES[ext] || "application/octet-stream",
"cache-control": "no-store" });
40         res.end(data);
41     } catch (e) { res.writeHead(500); res.end(String(e)); }
42     });
43     await new Promise((r) => server.listen(0, "127.0.0.1", r));
44     baseUrl = `http://127.0.0.1:${server.address().port}`;
45     browser = await chromium.launch();
46     });
47     after(async () => {
48         await browser?.close();
49         await new Promise((r) => server?.close(r));
50     });
51
52     const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
53     const LOCALES = ["en", "kn", "hi", "es", "da", "id"]; // id (Bahasa Indonesia) is the
widest-autonym worst case
54     const WIDTHS = [1280, 1100, 1000, 900, 768, 375]; // desktop + the old 860-1080 "dead
zone" + tablet + phone
55
56     // Tolerances tuned to ignore sub-pixel / font-rounding noise while catching the gross
distortions that
57     // actually occurred (the incidents were 50-75px). The nav-links height check is the
strongest signal:
58     // hidden = 0px, one line ~ 24px, the wrapped-and-overlapping bug was ~75px.
59     const TOL = { overflow: 16, ctaClip: 8, navLinksMaxHeight: 44, docOverflow: 16 };
60
61     test("header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x
widths)", async () => {
62         const failures = [];
63         for (const path of PAGES) {
64             for (const loc of LOCALES) {
65                 const page = await browser.newPage();
66                 try {
67                     await page.goto(`${baseUrl}${path}?lang=${loc}`, { waitUntil: "load" });
68                     // Wait for the shim to apply the locale (so nav text is translated -> real
widths) and for
69                     // webfonts to settle (text width is the whole point). en may already be the
default.
70                     await page.waitForFunction((l) => document.querySelector("[data-langsw]")?.value
=== l, loc, { timeout: 6000 }).catch(() => {});
71                     await page.evaluate(() => (document.fonts ? document.fonts.ready.then(() =>
true) : true));
72                     for (const width of WIDTHS) {
73                         await page.setViewportSize({ width, height: 900 });
74                         await page.waitForTimeout(70); // let the reflow settle
75                         const m = await page.evaluate(() => {
76                             const q = (s) => document.querySelector(s);
77                             const nav = q(".nav"), links = q(".nav-links"), de =
document.documentElement;
78                             const cta = q(".nav-right .btn-dark") || q(".nav-right .btn");
79                             return {
80                                 navOverflow: nav ? nav.scrollHeight - nav.clientWidth : 0,
81                                 navLinksHeight: links ? Math.round(links.getBoundingClientRect().height) :
0,
82                                 ctaRight: cta ? Math.round(cta.getBoundingClientRect().right) : 0,
83                                 docOverflow: de.scrollHeight - de.clientWidth,

```

```

84         };
85     });
86     const at = `${path} [${loc}] @${width}px`;
87     if (m.navOverflow > TOL.overflow) failures.push(`${at}: nav overflows
horizontally by ${m.navOverflow}px`);
88     if (m.navLinksHeight > TOL.navLinksMaxHeight) failures.push(`${at}: nav-links
is ${m.navLinksHeight}px tall ? wrapped onto multiple lines / overlapping the brand`);
89     if (m.ctaRight && m.ctaRight > width + TOL.ctaClip) failures.push(`${at}: CTA
right edge ${m.ctaRight}px is clipped past the ${width}px viewport`);
90     if (m.docOverflow > TOL.docOverflow) failures.push(`${at}: page has
${m.docOverflow}px of horizontal overflow`);
91     }
92     } finally {
93         await page.close();
94     }
95 }
96 }
97 assert.equal(failures.length, 0, failures.length ? `header layout distortions:\n -
${failures.join("\n - ")}\n` : "");
98 });
99
100 // Companion to the no-overflow guard: prove the auto-collapse doesn't OVER-fire (a
regression that
101 // hid the links for everyone would pass the overflow check vacuously). en has the
shortest labels and
102 // the most headroom, so on desktop it must always keep its nav links visible.
103 test("a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ?
index.html [en]", async () => {
104     const page = await browser.newPage();
105     try {
106         await page.goto(`${baseUrl}/index.html?lang=en`, { waitUntil: "load" });
107         await page.evaluate(() => (document.fonts ? document.fonts.ready.then(() => true) :
true));
108         for (const width of [1280, 1200, 1100]) {
109             await page.setViewportSize({ width, height: 900 });
110             await page.waitForTimeout(80); // let fitNav settle after the resize
111             const visible = await page.evaluate(() => {
112                 const l = document.querySelector(".nav-links");
113                 return !!l && getComputedStyle(l).display !== "none" &&
l.getBoundingClientRect().height > 0;
114             });
115             assert.ok(visible, `en nav links should stay visible at ${width}px (they fit) ?
auto-collapse over-fired`);
116         }
117     } finally {
118         await page.close();
119     }
120 });
121

```

340. assistant (2026-06-22T16:00:25.861Z)

The layout guard is solid ? it drives headless Chromium over 3 pages × 6 locales × 6 widths asserting header invariants + page-level horizontal overflow (which already covers footer/form-induced overflow on index.html). I'll extend it to specifically guard the new footer + form surfaces. Let me confirm the workflow is healthy, then yield until it completes.

341. user (2026-06-22T16:00:28.727Z)

agent transcripts so far: 22

342. assistant (2026-06-22T16:00:41.638Z)

The translation workflow is running healthily (22 agents ? 5 drafters ? 15 verifiers ?

revisers). I'll let it complete; the harness re-invokes me.

```
**Where things stand (worktree `ks-remaining`, branch `feat/localize-site-remaining` off  
origin/master @ba38f15):**
```

First I synced to remote head and re-read the landscape ? a lot landed from sibling sessions since my last PR:

- The two **human gates** you cleared match what was tracked. The chapter was already **archived** (#93); the home page got localized further (#89 hero mockup ? my spawned chip, #90 remaining sections), and the **rendering-fluctuation hardening** you mentioned is the `fitNav` auto-collapse + the headless-Chromium **layout guard** (`test:layout`, #91).

So "completion of localization (item 3)" now concretely = the two remaining English islands on the home page:

- **Access form** (`site.join.*`, 14 keys) ? wired, English in all non-en ? translating now.
- **Footer** (6 strings) ? was hardcoded ? I wired it (reusing `site.nav.ownModel`), seeded en byte-for-byte ? translating now.

```
| Step | Status |  
|---|---|  
| Synced to remote head; re-read handoff + audited remaining English | ? |  
| Footer wired + en authored (drift-guard validated); seeded all 6 ? 89 site tests green | ? |  
| Translate join+footer (20 keys × kn/hi/es/da/id), draft?3-lens verify?revise | ? running |  
| Apply ? tests (content + extend the layout guard for footer/form) ? render-verify ? PR | ? |
```

I also found the **new Privacy Policy page** (#96) has zero i18n hooks (English-only) ? that's a larger, newer surface I'll put in the prioritized list rather than silently translate 6× legal text. I'll continue automatically when the translations land, then give you that prioritized list.

343. user (2026-06-22T16:00:43.528Z)

Do make sure to test the rendering on all the locale pages, they are not too many and we want to flag any inconcsistencies, add tests for them and avoid regressing!

344. assistant (2026-06-22T16:01:33.159Z)

Understood ? comprehensive render verification across every locale × page, flag any inconsistency, and lock it in with tests so it can't regress. Let me first check whether the translation workflow has finished, then build the render-test harness.

345. user (2026-06-22T16:01:36.672Z)

=== workflow output present ===

```
...  
=== agent count ===  
26
```

346. assistant (2026-06-22T16:03:20.617Z)

Workflow still running (26 agents ? revisers finishing). Let me use the time to build the high-value piece the user is asking for: a **render-consistency guard** that drives a real browser over every locale × page and asserts the rendered DOM matches the catalog (no raw keys, no missing application, correct lang, no errors) ? catching exactly the cross-locale inconsistencies jsdom can't see. Let me study the CI wiring first.

347. user (2026-06-22T16:03:23.663Z)

```
=== CI test.yml jobs (is there a layout job?) ===  
3: push:  
8: site:  
11:   run:  
24:   - run: npm ci
```

```

25:      - run: npm test
29:      run: for f in scripts/*.sh; do echo "checking $f"; bash -n "$f"; done
31: web:
37:     run:
46:     - run: npm ci
47:     - run: npm run typecheck
48:     - run: npm run test:coverage
49:     - run: npm run build
51: layout:
58:     run:
67:     - run: npm ci
68:     - run: npx playwright install --with-deps chromium
69:     - run: npm run test:layout

```

=== site package scripts ===

```

{
  "test": "node --test",
  "test:cf": "node --test src/index.test.js",
  "test:vm": "node --test src/server.test.js",
  "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
  "test:layout": "node --test src/layout.browser.mjs",
  "copy:locales": "node scripts/copy-locales.mjs",
  "predeploy": "node scripts/copy-locales.mjs",
  "deploy": "wrangler deploy",
  "dev": "wrangler dev",
  "og": "python make_og.py"
}

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

348. assistant (2026-06-22T16:03:40.501Z)

Workflow done ? all 5 locales: **20/20 keys, zero missing**, brand/token literals preserved (Google Drive, OneDrive, Dropbox, Amazon S3, "Generated by Khelsutra.guru", HTTPS, © 2026, ??), with natural localization (es "bádminton", id "bulu tangkis", da "Indien"). Let me extract, verify integrity, and apply.

349. user (2026-06-22T16:03:50.243Z)

INTEGRITY OK: brands/watermark/HTTPS/emoji preserved, no stray HTML in all 5 locales
 fixed counts: kn=3 hi=3 es=4 da=4 id=2
 Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

350. assistant (2026-06-22T16:03:54.659Z)

Integrity verified across all 5. Let me apply, mirror, and confirm key-parity still holds.

351. user (2026-06-22T16:04:00.454Z)

```

kn: applied 20/20
hi: applied 20/20
es: applied 20/20
da: applied 20/20
id: applied 20/20
OK
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
=== web key-parity quick check (all 6 locales same key set) ===
  Test Files  1 passed (1)
    Tests     29 passed (29)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

352. assistant (2026-06-22T16:04:28.713Z)

Applied (20/20 each), mirrored, web key-parity green (29). Now the centerpiece you asked for: a **render-consistency guard** across every locale × page. Let me write it ? it drives headless

Chromium over all 18 combos and asserts the live DOM matches the catalog (no raw keys, correct `

353. assistant (2026-06-22T16:04:56.904Z)

```
// Cross-locale RENDER guard (separate `npm run test:render` job ? needs a real browser, like
the
// layout guard). jsdom proves the catalogs + static HTML defaults are consistent; it CANNOT
prove the
// client shim (public/i18n.js) actually applies each locale correctly in a live DOM. This
drives a
// headless Chromium over every localized page × all 6 locales and asserts, for each:
// 1. <html lang> resolves to the negotiated locale;
// 2. NO console / page errors;
// 3. EVERY data-i18n[-html] element's rendered text equals what the shim should produce for
that
// locale (active-locale value, en-fallback) ? so a raw key, a missing/typo'd key, a stale
render,
// or a shim regression is caught on the REAL page, in EVERY language (not just en);
// 4. no visible raw key / un-interpolated {placeholder} / "undefined";
// 5. kn/hi pages actually contain their script (the translation + glyph path is live).
// This is the anti-regression net for "render every locale page and flag inconsistencies".
import { test, before, after } from "node:test";
import assert from "node:assert/strict";
import { createServer } from "node:http";
import { readFile } from "node:fs/promises";
import { join, extname } from "node:path";
import { chromium } from "playwright";

const PUBLIC = join(import.meta.dirname, "..", "public");
const TYPES = {
  ".html": "text/html; charset=utf-8", ".js": "text/javascript", ".mjs": "text/javascript",
  ".json": "application/json; charset=utf-8", ".css": "text/css", ".png": "image/png", ".jpg":
"image/jpeg",
  ".svg": "image/svg+xml", ".webp": "image/webp", ".webm": "video/webm", ".mp4": "video/mp4",
  ".woff2": "font/woff2", ".woff": "font/woff", ".ico": "image/x-icon",
};

let server, browser, baseUrl;

before(async () => {
  server = createServer(async (req, res) => {
    try {
      let p = decodeURIComponent(req.url.split("?")[0]);
      if (p === "/" ) p = "/index.html";
      let data, ext = extname(p);
      try { data = await readFile(join(PUBLIC, p)); }
      catch { try { data = await readFile(join(PUBLIC, p + ".html")); ext = ".html"; } catch {
res.writeHead(404); return res.end("not found"); } }
      res.writeHead(200, { "content-type": TYPES[ext] || "application/octet-stream", "cache-
control": "no-store" });
      res.end(data);
    } catch (e) { res.writeHead(500); res.end(String(e)); }
  });
  await new Promise((r) => server.listen(0, "127.0.0.1", r));
  baseUrl = `http://127.0.0.1:${server.address().port}`;
  browser = await chromium.launch();
});

after(async () => { await browser?.close(); await new Promise((r) => server?.close(r)); });

const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
const LOCALES = ["en", "kn", "hi", "es", "da", "id"];
const SCRIPT = { kn: /[?-/]/, hi: /[?-/]/ };
// namespaces that should never appear verbatim as visible text (= a raw, unresolved i18n key)
const KEY_RE = /^(site|app|query|grid|footer|ingest|result|errors|tap|selection|bulk|mode|lang|b
uild|wizard)\.[a-zA-Z0-9-]+$/;
```

```

test("every localized page renders each locale correctly (DOM == catalog, no raw keys, right
lang, no errors)", async () => {
  const failures = [];
  for (const path of PAGES) {
    for (const loc of LOCALES) {
      const ctx = await browser.newContext(); // isolated storage so ?lang wins cleanly
      const page = await ctx.newPage();
      const errors = [];
      page.on("console", (m) => { if (m.type() === "error") errors.push(m.text()); });
      page.on("pageerror", (e) => errors.push("pageerror: " + e.message));
      try {
        await page.goto(`${baseUrl}${path}?lang=${loc}`, { waitUntil: "load" });
        await page.waitForFunction((l) => document.querySelector("[data-langsw]")?.value === l,
loc, { timeout: 6000 }).catch(() => {});
        await page.evaluate(() => (document.fonts ? document.fonts.ready.then(() => true) :
true));
        const at = `${path} [${loc}]`;

        const realErrors = errors.filter((e) => !/favicon/i.test(e));
        if (realErrors.length) failures.push(`${at}: console/page errors: ${realErrors.join(" |
")}`);

        const r = await page.evaluate(async ({ loc, KEY_SRC }) => {
          const KEY = new RegExp(KEY_SRC);
          const fetchCat = async (l) => { try { const res = await
fetch(`/locales/${l}/common.json`); return res.ok ? await res.json() : {}; } catch { return {};
} };
          const active = await fetchCat(loc), en = await fetchCat("en");
          const dig = (o, k) => k.split(".").reduce((a, c) => (a && typeof a === "object" ? a[c]
: undefined), o);
          const norm = (html) => { const d = document.createElement("div"); d.innerHTML = html;
return d.innerHTML; };
          const out = { htmlLang: document.documentElement.lang, mismatches: [], rawKeys: [],
empties: [] };
          for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
            if (el.getAttribute("data-i18n-attr")) continue; // attribute defaults, not visible
text
            const htmlKey = el.getAttribute("data-i18n-html");
            const key = htmlKey || el.getAttribute("data-i18n");
            let expected = dig(active, key); if (expected == null) expected = dig(en, key);
            if (expected == null) continue; // missing everywhere -> shim keeps the DOM default;
not its bug
            const got = htmlKey ? el.innerHTML : el.textContent.trim();
            const want = htmlKey ? norm(expected) : String(expected).trim();
            if (got !== want) out.mismatches.push(`${key}: DOM=${JSON.stringify(got.slice(0,
70))} != catalog=${JSON.stringify(want.slice(0, 70))}`);
            const txt = el.textContent.trim();
            if (KEY.test(txt)) out.rawKeys.push(`${key} (raw key visible)`);
            else if (/^[a-zA-Z]\w*$/.test(txt)) out.rawKeys.push(`${key} (un-interpolated
placeholder)`);
            else if (/\\bundefined\\b|\\[object Object\\]/.test(txt)) out.rawKeys.push(`${key}
(undefined/object)`);
            if (!htmlKey && txt.length === 0) out.empties.push(key);
          }
          return out;
        }, { loc, KEY_SRC: KEY_RE.source });

        if (r.htmlLang !== loc) failures.push(`${at}: <html lang>="${r.htmlLang}", expected
"${loc}"`);
        for (const m of r.mismatches) failures.push(`${at}: ${m}`);
        for (const k of r.rawKeys) failures.push(`${at}: ${k}`);
        for (const k of r.empties) failures.push(`${at}: "${k}" rendered EMPTY`);
        if (SCRIPT[loc]) {
          const body = await page.evaluate(() => document.body.innerText);
          if (!SCRIPT[loc].test(body)) failures.push(`${at}: no ${loc} script present in the

```

```

rendered page (translation/glyph path broken)`);
    }
  } finally { await ctx.close(); }
}
}
assert.equal(failures.length, 0, failures.length ? `render inconsistencies
(${failures.length}):\\n - ${failures.join("\\n - ")}\\n` : "");
});

```

354. user (2026-06-22T16:04:56.927Z)

File created successfully at: C:\Users\avidu\Projects\ks-remaining\site\src\render.browser.mjs
(file state is current in your context ? no need to Read it back)

355. assistant (2026-06-22T16:05:04.614Z)

Now let me wire `test:render` into the package scripts and CI (alongside the existing layout job, sharing the Chromium install).

356. user (2026-06-22T16:05:05.519Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

357. user (2026-06-22T16:05:08.825Z)

```

1      {
2        "name": "khelsutra-site",
3        "private": true,
4        "type": "module",
5        "scripts": {
6          "test": "node --test",
7          "test:cf": "node --test src/index.test.js",
8          "test:vm": "node --test src/server.test.js",
9          "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10         "test:layout": "node --test src/layout.browser.mjs",
11         "copy:locales": "node scripts/copy-locales.mjs",
12         "predeploy": "node scripts/copy-locales.mjs",
13         "deploy": "wrangler deploy",
14         "dev": "wrangler dev",
15         "og": "python make_og.py"
16       },
17       "devDependencies": {
18         "jsdom": "^29.1.1",
19         "playwright": "^1.61.0"
20       }
21     }
22

```

358. user (2026-06-22T16:05:15.961Z)

The file C:\Users\avidu\Projects\ks-remaining\site\package.json has been updated successfully.
(file state is current in your context ? no need to Read it back)

359. user (2026-06-22T16:05:20.219Z)

```

51     layout:
52       # Real-browser layout-regression guard. The other suites run in jsdom, which has NO
53       # (getBoundingClientRect() is all zeros) and therefore cannot see header overflow /
54       # clipping ? the responsive-nav bug that recurred. This drives a headless Chromium
55       # pages at a spread of viewport widths x all 6 locales and asserts the header never
56       # distorts.

```

```
56     runs-on: ubuntu-latest
57     defaults:
58       run:
59         working-directory: site
60     steps:
61       - uses: actions/checkout@v4
62       - uses: actions/setup-node@v4
63         with:
64           node-version: "24"
65           cache: "npm"
66           cache-dependency-path: site/package-lock.json
67       - run: npm ci
68       - run: npx playwright install --with-deps chromium
69       - run: npm run test:layout
70
```

360. user (2026-06-22T16:05:26.445Z)

<tool_use_error>File does not exist. Note: your current working directory is C:\Users\avidu\Projects\kheIsutra.</tool_use_error>

361. assistant (2026-06-22T16:05:30.638Z)

Wrong path ? the worktree is `ks-remaining`. Let me fix the CI in the correct file.

362. user (2026-06-22T16:05:32.622Z)

The file C:\Users\avidu\Projects\ks-remaining\.github\workflows\test.yml has been updated successfully. (file state is current in your context ? no need to Read it back)

363. assistant (2026-06-22T16:05:37.794Z)

Now let me run the render guard ? this is the comprehensive cross-locale render verification across all 18 page×locale combos.

364. user (2026-06-22T16:05:52.466Z)

```
> test:render
> node --test src/render.browser.mjs
```

? every localized page renders each locale correctly (DOM == catalog, no raw keys, right lang, no errors) (12717.3473ms)

? tests 1

? suites 0

? pass 1

? fail 0

? cancelled 0

? skipped 0

? todo 0

? duration_ms 13121.4181

Shell cwd was reset to C:\Users\avidu\Projects\kheIsutra

365. assistant (2026-06-22T16:06:01.076Z)

Render guard ****passes all 18 combos**** ? every locale page's live DOM matches its catalog, no raw keys, correct lang, no console errors, Indic script present for kn/hi. Now let me run the existing layout guard to confirm the footer + form translations didn't introduce overflow across locales/widths.

366. user (2026-06-22T16:06:21.987Z)

```
> test:layout
> node --test src/layout.browser.mjs
```

```
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(17940.7737ms)
? a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ? index.html [en]
(748.0377ms)
? tests 2
? suites 0
? pass 2
? fail 0
? cancelled 0
? skipped 0
? todo 0
? duration_ms 19089.1243
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

367. assistant (2026-06-22T16:06:44.068Z)

Both browser guards pass. Now, per your "add tests for them," let me make the footer + access-form regression guard **explicit** (not just incidental via page-level overflow) by adding a focused assertion to the layout test.

368. user (2026-06-22T16:06:52.722Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\layout.browser.mjs has been updated successfully. (file state is current in your context ? no need to Read it back)

369. assistant (2026-06-22T16:07:08.440Z)

Now let me add the catalog-level content tests for join+footer (real translation + token integrity), matching the coverage pattern. Let me check the current test file's setup first.

370. user (2026-06-22T16:07:10.199Z)

```
14:const catalogs = { en: load("en"), kn: load("kn"), hi: load("hi"), es: load("es"), da:
load("da"), id: load("id") };
16:test("negotiation order matches the SPA: persisted -> ?lang -> navigator -> en", () => {
23:test("region subtags normalize and unsupported degrades to en (never a locale we can't
serve)", () => {
33:test("ICU-lite interpolation: {name} substitution", () => {
38:test("ICU-lite plurals via Intl.PluralRules (en/kn 2-form), # = the number", () => {
46:test("translate: active locale, then en fallback, then undefined (caller keeps the DOM
default)", () => {
57:test("applyDom walks data-i18n, sets attrs, reflects the active locale in the <select>, never
shows a raw key", () => {
80:test("data-i18n-html sets innerHTML and preserves inline <b> markup (A3 recording-
education)", () => {
98:test("data-i18n-html falls back through en (markup intact) when the active locale lacks the
key", () => {
106:test("A3: the kn/hi catalogs carry REAL recording-education translations (not English
seeds)", () => {
126:const flatOwn = (obj, p = "") => Object.entries(obj).reduce((a, [k, v]) => {
128:  if (v && typeof v === "object") Object.assign(a, flatOwn(v, key)); else a[key] = v; return
a;
131:test("own-model: kn/hi carry REAL translations of the page body (not the en seed)", () => {
147:test("own-model: kn/hi keep en's inline-HTML tag-set + load-bearing literal tokens (no
markup/token drift)", () => {
148:  const ef = flatOwn(catalogs.en.site.ownModel);
153:    const lf = flatOwn(catalogs[loc].site.ownModel);
172:test("site: es/da/id carry REAL translations of the marketing copy; the access form
(site.join.*) stays English", () => {
173:  const enSite = flatOwn(catalogs.en.site);
174:  const knSite = flatOwn(catalogs.kn.site);
179:    const locSite = flatOwn(catalogs[loc].site);
193:test("site: es/da/id keep en's inline-HTML tag-set + load-bearing literal tokens (no
markup/token drift)", () => {
```

```

194:  const enSite = flatOwn(catalogs.en.site);
195:  const knSite = flatOwn(catalogs.kn.site);
199:    const locSite = flatOwn(catalogs[loc].site);
213:test("hero+how: kn/hi carry REAL translations (in-script) for the demo-mockup + feature
block", () => {
229:test("hero+how: es/da/id translate the new block (not en seeds) and keep the faux-UI
literal tokens", () => {
230:  const enSite = flatOwn(catalogs.en.site);
232:    const locSite = flatOwn(catalogs[loc].site);
246:test("home sections: kn/hi carry REAL translations (in-script) for
#diff/#sharper/#ask/#roadmap/#not/#faq", () => {
262:test("home sections: es/da/id translate the new content (not en seeds) and keep brand/markup
tokens", () => {
--- line count ---
312 src/i18n.shim.test.js
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

371. assistant (2026-06-22T16:07:22.471Z)

Important ? my #87 test at line 172 asserts `site.join.\*` *stays English*; I just translated it, so that test will now fail. Let me read it and the surrounding content tests to update precisely.

372. user (2026-06-22T16:07:23.211Z)

```

172  test("site: es/da/id carry REAL translations of the marketing copy; the access form
(site.join.*) stays English", () => {
173    const enSite = flatOwn(catalogs.en.site);
174    const knSite = flatOwn(catalogs.kn.site);
175    // The target set = the site.* keys kn translated (so es/da/id reach the same coverage
parity).
176    const target = Object.keys(enSite).filter((k) => knSite[k] !== enSite[k]);
177    assert.ok(target.length >= 100, `expected the full marketing set as the target (got
${target.length})`);
178    for (const loc of ["es", "da", "id"]) {
179      const locSite = flatOwn(catalogs[loc].site);
180      // The vast majority of the marketing copy must differ from the en seed (a handful
of cognates like
181      // "Flyer"/"FAQ"/"Roadmap"/"Net" legitimately stay English in da/id ? allow a small
margin).
182      const stillEn = target.filter((k) => locSite[k] === enSite[k]);
183      assert.ok(stillEn.length <= 8, `${loc}: ${stillEn.length} marketing keys still equal
the en seed (untranslated?): ${stillEn.slice(0, 10).join(", ")}`);
184      // Concrete prose anchors across the surfaces MUST be translated (never an en seed).
185      for (const key of ["hero.lead", "record.intro", "capture.consent",
"ownModel.heroLead", "ownModel.train.honestBody"]) {
186        assert.notEqual(locSite[key], enSite[key], `${loc} site.${key} must be translated,
not an en seed`);
187      }
188      // The Request-Access form (site.join.*) is intentionally English in EVERY locale
(A6 deferred) ? parity with kn/hi.
189      assert.equal(locSite["join.gpuLabel"], enSite["join.gpuLabel"], `${loc} site.join.*
must stay English (A6 deferred, same as kn/hi)`);
190    }
191  });
192
193  test("site: es/da/id keep en's inline-HTML tag-set + load-bearing literal tokens (no
markup/token drift)", () => {
194    const enSite = flatOwn(catalogs.en.site);
195    const knSite = flatOwn(catalogs.kn.site);
196    const target = Object.keys(enSite).filter((k) => knSite[k] !== enSite[k]);
197    const tagset = (s) => (String(s).match(/<[^>+>/g) || []).slice().sort().join("|");
198    for (const loc of ["es", "da", "id"]) {
199      const locSite = flatOwn(catalogs[loc].site);
200      for (const key of target) {

```



```

201         assert.equal(tagset(locSite[key]), tagset(enSite[key]), `${loc} site.${key}:
inline HTML tag-set drifted from en`);
202     }
203     // Brand / technical tokens survive translation verbatim across the site.
204     assert.match(locSite["hero.lead"], /KhelSutra/, `${loc} hero.lead lost the brand`);
205     assert.match(locSite["record.settings.body"], /1080p\+|30 fps/, `${loc}
record.settings.body lost the technical tokens`);
206     assert.match(locSite["ownModel.annotate.body"], /rally-annotator/, `${loc} own-model
annotate.body lost rally-annotator`);
207     assert.match(locSite["ownModel.setup.reasons"], /service_fault/, `${loc} own-model
setup.reasons lost the ending_reason enum`);
208     assert.match(locSite["reveal.shareText"], /kheIsutra\.guru/, `${loc}
reveal.shareText lost the URL`);
209     }
210     });
211

```

373. assistant (2026-06-22T16:07:50.319Z)

The `site.join.\* stays English` assertion is now stale. Let me update that test (the form is now translated) and add a dedicated join+footer content test.

374. user (2026-06-22T16:08:00.711Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

375. assistant (2026-06-22T16:08:06.397Z)

Now let me add a dedicated join+footer content test. Let me read the file tail to place it.

376. user (2026-06-22T16:08:07.248Z)

```

244     // ---- the remaining home content sections: real translations across the 6 locales
-----
245     test("home sections: kn/hi carry REAL translations (in-script) for
#diff/#sharper/#ask/#roadmap/#not/#faq", () => {
246         const KN = /[?~?]/, HI = /[?~?]/;
247         // A representative spread across all six sections (incl. rich + plain forms) must be
in-script.
248         for (const key of ["diff.title", "diff.p2", "sharper.intro", "sharper.minors.body",
"ask.intro", "ask.note", "roadmap.title", "roadmap.coach.body", "not.title", "not.li1",
"faq.q1.a", "faq.q7.a"]) {
249             const dig = (root) => key.split(".").reduce((o, k) => o[k], root);
250             assert.match(dig(catalogs.kn.site), KN, `kn site.${key} should be Kannada (an en
seed would not match)`);
251             assert.match(dig(catalogs.hi.site), HI, `hi site.${key} should be Devanagari`);
252         }
253         // The rich (inline-markup) keys keep their tags in EVERY locale (the rich form round-
trips them).
254         for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
255             assert.match(catalogs[loc].site.diff.p2, /<b style="color:var\(--tx\) ">.*<\b>/s,
`${loc} diff.p2 lost its <b>`);
256             assert.match(catalogs[loc].site.ask.note, /<b style="color:var\(--tx\) ">.*<\b>/s,
`${loc} ask.note lost its <b>`);
257             assert.match(catalogs[loc].site.faq.q7.a, /<a href="#join">.*<\a>/s, `${loc}
faq.q7.a lost the <a href="#join"> link`);
258         }
259     });
260
261     test("home sections: es/da/id translate the new content (not en seeds) and keep
brand/markup tokens", () => {
262         const enSite = flatOwn(catalogs.en.site);
263         const tagset = (s) => (String(s).match(/<[^>+>/g) || []).slice().sort().join("|");

```

```

264     for (const loc of ["es", "da", "id"]) {
265         const locSite = flatOwn(catalogs[loc].site);
266         for (const key of ["diff.title", "sharper.intro", "ask.title", "roadmap.title",
"not.li1", "faq.q1.a"]) {
267             assert.notEqual(locSite[key], enSite[key], `${loc} site.${key} must be translated,
not an en seed`);
268         }
269         // Inline-markup keys keep en's exact tag-set (a dropped <b>/<a href> would break
the rendered page).
270         for (const key of ["diff.p2", "ask.note", "faq.q7.a"]) {
271             assert.equal(tagset(locSite[key]), tagset(enSite[key]), `${loc} site.${key}
inline-HTML tag-set drifted from en`);
272         }
273         assert.match(locSite["diff.p2"], /KhelSutra/, `${loc} diff.p2 lost the brand`);
274         assert.match(locSite["faq.q7.a"], /href="#join"/, `${loc} faq.q7.a lost the #join
link`);
275     }
276 });
277
278 // fitNav's REAL geometry (which locale collapses at which width) is exercised end-to-
end by the
279 // browser layout guard (src/layout.browser.mjs). jsdom has no layout engine, so here we
pin fitNav's
280 // decision logic deterministically by mocking the only geometry it reads ? scrollWidth
vs clientWidth.
281 test("fitNav: no-ops without a nav", () => {
282     const { document: empty } = new JSDOM(`<!doctype html><body></body>`).window;
283     assert.doesNotThrow(() => fitNav(empty), "fitNav must tolerate a page with no .nav");
284 });
285
286 test("fitNav: toggles .nav-crowded by whether the header row overflows (both branches +
idempotent)", () => {
287     const { document } = new JSDOM(
288         `<!doctype html><body><header><div class="nav"><a class="brand">B</a><nav
class="nav-links"><a>How it works</a></nav><div class="nav-right"></div></div></header></body>`,
289     ).window;
290     const nav = document.querySelector(".nav");
291     // jsdom returns 0 for both; override the instance getters to simulate real layout.
292     const geom = (scrollWidth, clientWidth) => {
293         Object.defineProperty(nav, "scrollWidth", { value: scrollWidth, configurable: true
});
294         Object.defineProperty(nav, "clientWidth", { value: clientWidth, configurable: true
});
295     };
296
297     geom(1200, 1000); // content wider than the box -> the 6 links don't fit
298     fitNav(document);
299     assert.ok(nav.classList.contains("nav-crowded"), "overflow must collapse the nav (add
.nav-crowded)");
300
301     geom(1000, 1000); // now it fits
302     fitNav(document);
303     assert.ok(!nav.classList.contains("nav-crowded"), "fitting again must reveal the links
(drop .nav-crowded)");
304
305     fitNav(document); // re-running on a fitting nav is a no-op (no flip-flop)
306     assert.ok(!nav.classList.contains("nav-crowded"), "fitNav must be idempotent");
307
308     geom(1100, 1000); // and it re-collapses if a wider locale/label pushes it back over
309     fitNav(document);

```

377. user (2026-06-22T16:08:42.450Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

378. assistant (2026-06-22T16:08:49.432Z)

Let me run the full site unit suite (including the updated + new content tests) plus the web suite.

379. user (2026-06-22T16:08:52.736Z)

```
=== SITE unit (node --test) ===
? tests 90
? pass 90
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

380. assistant (2026-06-22T16:09:05.703Z)

90 site unit tests pass. Now the web suite (key-parity + catalog-invariants with the new join/footer translations).

381. user (2026-06-22T16:09:14.479Z)

```
Test Files 24 passed (24)
Tests      223 passed (223)
Start at   21:39:08
Duration   5.45s (transform 1.52s, setup 526ms, collect 9.92s, tests 6.43s,
environment 30.63s, prepare 5.53s)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

382. assistant (2026-06-22T16:09:59.319Z)

Render guard + layout + unit + web all green (90/2/1/223). Now let me eyeball for the subtle cross-locale inconsistency the render guard *can't* catch ? proper-noun rendering. Let me audit how "Bengaluru" is rendered across each locale's full catalog.

383. user (2026-06-22T16:10:03.791Z)

```
en: Latin "Bengaluru" in [site.hero.eyebrow, site.footer.tagline, site.footer.trust] |
transliterated in [-]
kn: Latin "Bengaluru" in [-] | transliterated in [site.hero.eyebrow, site.footer.tagline,
site.footer.trust]
hi: Latin "Bengaluru" in [site.footer.tagline, site.footer.trust] | transliterated in
[site.hero.eyebrow]
es: Latin "Bengaluru" in [site.hero.eyebrow, site.footer.tagline, site.footer.trust] |
transliterated in [-]
da: Latin "Bengaluru" in [site.hero.eyebrow, site.footer.tagline, site.footer.trust] |
transliterated in [-]
id: Latin "Bengaluru" in [site.hero.eyebrow, site.footer.tagline, site.footer.trust] |
transliterated in [-]
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

384. assistant (2026-06-22T16:10:16.171Z)

Found a real inconsistency: **Hindi mixes it** ? the hero uses transliterated `????????` but the new footer keeps Latin `Bengaluru` (kn is consistently transliterated; en/es/da/id consistently Latin). My footer glossary caused it. Let me fix Hindi to match its established `????????` and add a consistency test so this can't regress.

385. user (2026-06-22T16:10:20.553Z)

```
hi footer.tagline: ????-?? ???? ???? ????????? ?????????? . ?????????, ????
hi footer.trust : ? HTTPS ?? ????? ????????? ???? ? ? ????? ???? . ? ?????????, ???? ?? ????? ???? .
???? ? "Generated by Khelsutra.guru" ?? ????? ???? ?
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

386. assistant (2026-06-22T16:10:52.306Z)

Hindi now consistent (``????????` everywhere). Let me add a proper-noun consistency test so mixed place-name rendering can't regress.

387. user (2026-06-22T16:11:00.175Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

388. assistant (2026-06-22T16:11:08.396Z)

Let me re-run the site unit suite (new consistency test) and the render guard (confirm the Hindi fix renders cleanly).

389. user (2026-06-22T16:11:23.143Z)

```
=== unit ===
? tests 91
? pass 91
? fail 0
=== render guard (re-verify after hi fix) ===
? every localized page renders each locale correctly (DOM == catalog, no raw keys, right lang,
no errors) (9353.7907ms)
? pass 1
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

390. assistant (2026-06-22T16:11:36.450Z)

91 unit + render guard green after the fix. Now let me capture a visual grid of the new surfaces (access form + footer) across all 6 locales for eyeball evidence. Let me start the server.

391. user (2026-06-22T16:11:37.198Z)

Command running in background with ID: bgdbfuxe. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bgdbfuxe.output. You will be notified when it completes. To check interim output, use Read on that file path.

392. assistant (2026-06-22T16:11:47.980Z)

```
// Visual evidence for the two newly-localized home-page surfaces (the access form #join + the
// footer),
// captured per locale. Complements the automated render guard with eyeball-able stills.
import { chromium } from "playwright";
const URL = process.env.URL || "http://localhost:8132";
const browser = await chromium.launch();
const errs = {};
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const ctx = await browser.newContext({ viewport: { width: 1000, height: 900 } });
  const page = await ctx.newPage();
  const e = []; page.on("console", (m) => m.type() === "error" && e.push(m.text()));
  page.on("pageerror", (x) => e.push(String(x)));
  await page.goto(`${URL}/?lang=${loc}`, { waitUntil: "networkidle" });
  await page.waitForFunction((l) => document.querySelector("[data-langsw]")?.value === l, loc, {
    timeout: 6000 }).catch(() => {});
  await page.evaluate(() => (document.fonts ? document.fonts.ready.then(() => true) : true));
  await page.locator("#join").scrollIntoViewIfNeeded().catch(() => {});
  await page.waitForTimeout(500);
  await page.locator("#af").screenshot({ path: `jf-form-${loc}.png` }).catch(async () => { await
    page.screenshot({ path: `jf-form-${loc}.png` }); });
  await page.locator(".foot, footer").first().scrollIntoViewIfNeeded().catch(() => {});
  await page.waitForTimeout(400);
```

```

    await page.locator("footer").screenshot({ path: `jf-footer-${loc}.png` }).catch(() => {});
    errs[loc] = e.filter((x) => !/favicon/i.test(x));
    await ctx.close();
  }
  await browser.close();
  console.log("console errors by locale:", JSON.stringify(errs));
  console.log("wrote jf-form-{en,kn,hi,es,da,id}.png + jf-footer-*.png");

```

393. user (2026-06-22T16:11:47.994Z)

File created successfully at: C:\Users\avidu\Projects\khelsutra-screencast\join-footer-shots.mjs
(file state is current in your context ? no need to Read it back)

394. user (2026-06-22T16:12:06.906Z)

```

console errors by locale: {"en":[],"kn":[],"hi":[],"es":[],"da":[],"id":[]}
wrote jf-form-{en,kn,hi,es,da,id}.png + jf-footer-*.png
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

395. assistant (2026-06-22T16:12:19.960Z)

Zero console errors across all 6 locales. Let me eyeball the highest-risk stills ? the Kannada access form (Indic glyphs) and the Indonesian footer (longest labels).

396. assistant (2026-06-22T16:12:52.930Z)

The render guard passed, but eyeballing the Kannada form reveals what it *couldn't* catch: several form fields are **hardcoded** English with no `data-i18n` ? "Name", "Email (so we can reach you)", "City (optional)", "Anything else?", the consent checkbox, the "Request access" button, and the privacy note. The 14 `site.join.*` keys (from A6) only covered the GPU/storage questions. Let me inventory the full form.

397. user (2026-06-22T16:12:54.639Z)

```

=== #join form block (index.html) ===
524: <section id="join" style="padding-bottom:90px">
525:   <div class="wrap">
526:     <div class="sec-head" style="text-align:center;max-width:none">
527:       <div class="kicker">Request access</div>
528:       <h2>Get into the KhelSutra alpha</h2>
529:       <p>Invite-only. Tell us a little about your setup ? it helps us get you the best
results, and shapes what we build next.</p>
530:       <p style="font-weight:600;color:var(--green-d);margin-top:.6rem"><span aria-
hidden="true">?</span> Sign up to watch the tool in action ? and a 30-second sample reel it made
? the moment you're in.</p>
531:     </div>
532:
533:     <form id="af" class="af" novalidate>
534:       <div class="row">
535:         <label>I'm a?</label>
536:         <div class="seg">
537:           <label><input type="radio" name="segment" value="academy" required><span>Coaching
academy / club</span></label>
538:           <label><input type="radio" name="segment" value="individual"><span>Individual
player</span></label>
539:         </div>
540:       </div>
541:
542:       <div class="row">
543:         <label for="af-name">Name</label>
544:         <input id="af-name" name="name" type="text" autocomplete="name" required>
545:       </div>
546:       <div class="row">
547:         <label for="af-email">Email <span class="hint">(so we can reach you)</span></label>

```

```

548:         <input id="af-email" name="email" type="email" autocomplete="email" required>
549:     </div>
550:     <div class="row">
551:         <label for="af-city">City <span class="hint">(optional)</span></label>
552:         <input id="af-city" name="city" type="text">
553:     </div>
554:
555:     <div class="row acad">
556:         <label for="af-org">Academy / club name <span
class="hint">(optional)</span></label>
557:         <input id="af-org" name="org_name" type="text">
558:     </div>
559:     <div class="row acad">
560:         <label for="af-courts">How many courts do you record? <span
class="hint">(optional)</span></label>
561:         <select id="af-courts" name="courts">
562:             <option value="">Select?</option>
563:             <option value="1">1 court</option>
564:             <option value="2-4">2?4 courts</option>
565:             <option value="5+">5+ courts</option>
566:         </select>
567:     </div>
568:
569:     <div class="row">
570:         <label data-i18n="site.join.gpuLabel">Do you have a powerful computer that could
process videos on its own?</label>
571:         <div class="hint" style="margin:-.2rem 0 .5rem" data-i18n="site.join.gpuHint">A
gaming PC or laptop with a graphics card. No worries if not ? we can run it in the cloud for
you.</div>
572:         <div class="opts">
573:             <label><input type="radio" name="has_gpu" value="yes"><span
data-i18n="site.join.gpuYes">Yes ? a gaming PC or laptop with a graphics card</span></label>
574:             <label><input type="radio" name="has_gpu" value="unsure"><span
data-i18n="site.join.gpuUnsure">Not sure</span></label>
575:             <label><input type="radio" name="has_gpu" value="no"><span
data-i18n="site.join.gpuNo">No</span></label>
576:             <label><input type="radio" name="has_gpu" value="prefer-cloud"><span
data-i18n="site.join.gpuCloud">No ? please run it in the cloud for me</span></label>
577:         </div>
578:     </div>
579:
580:     <div class="row">
581:         <label><span data-i18n="site.join.storageLabel">Where do your match videos live?
How would you share them?</span> <span class="hint" data-i18n="site.join.storageHint">(pick
any)</span></label>
582:         <div class="opts">
583:             <label><input type="checkbox" name="storage" value="gdrive"><span
data-i18n="site.join.storageGdrive">Google Drive</span></label>
584:             <label><input type="checkbox" name="storage" value="onedrive"><span
data-i18n="site.join.storageOnedrive">OneDrive / Microsoft 365</span></label>
585:             <label><input type="checkbox" name="storage" value="dropbox"><span
data-i18n="site.join.storageDropbox">Dropbox</span></label>
586:             <label><input type="checkbox" name="storage" value="bucket"><span
data-i18n="site.join.storageBucket">A cloud storage bucket ? advanced (e.g. Amazon S3, Google
Cloud)</span></label>
587:             <label><input type="checkbox" name="storage" value="local"><span
data-i18n="site.join.storageLocal">SD card or the device itself</span></label>
588:             <label><input type="checkbox" name="storage" value="unsure"><span
data-i18n="site.join.storageUnsure">Not sure</span></label>
589:         </div>
590:     </div>
591:
592:     <div class="row">
593:         <label for="af-msg">Anything else? <span class="hint">(how you record, what you'd
want?)</span></label>

```

```

594:         <textarea id="af-msg" name="message"></textarea>
595:     </div>
596:
597:     <div class="row consent">
598:         <input id="af-consent" name="consent" type="checkbox" value="yes">
599:         <label for="af-consent" style="margin:0;font-weight:400;color:var(--mut)">Okay to
email me about the KhelSutra alpha.</label>
600:     </div>
601:
602:     <input class="hp" type="text" name="company" tabindex="-1" autocomplete="off" aria-
hidden="true">
603:
Shell cwd was reset to C:\Users\avidu\Projects\kheelsutra

```

398. assistant (2026-06-22T16:13:14.573Z)

The form has far more un-wired English than the 14 A6 keys ? the entire section head, segment options, name/email/city/org/courts fields, the courts dropdown, consent, and submit are all hardcoded. To render the form natively (your goal), I need to wire **all** of it. Let me inventory the rest (submit + privacy note + the in-flight state).

399. user (2026-06-22T16:13:18.293Z)

```

=== form tail (602-640) ===
3:     <button class="btn btn-primary" type="submit" style="width:100%;justify-
content:center">Request access</button>
4:     <p class="hint" style="text-align:center;margin:.85rem 0 0">We never publish your
footage; footage involving minors is never used to improve the tool. See our <a
href="/privacy">Privacy Policy</a>.</p>
5: </form>
16:     <div class="stamp" style="margin-top:.4rem" data-i18n="site.footer.tagline">Automatic
badminton highlights · Bengaluru, India</div>
19:     <div><a href="/own-model" data-i18n="site.nav.ownModel">Own your model</a> · <a
href="/capture" data-i18n="site.footer.capture">Capture checklist</a> · <a href="/privacy"
data-i18n="site.footer.privacy">Privacy</a> · <a
href="mailto:hello@kheelsutra.guru">hello@kheelsutra.guru</a> · <a
href="https://kheelsutra.guru">kheelsutra.guru</a></div>
20:     <div style="margin-top:.4rem"><span data-i18n="site.footer.flyer">Academy flyer
(print):</span> <a href="/flyer" hreflang="en">English</a> · <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> · <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></div>
21:     <div class="stamp" style="margin-top:.4rem" data-i18n="site.footer.trust">? Served
securely over HTTPS · ? Run from Bengaluru, India · Reels carry a "Generated by Khelsutra.guru"
mark</div>
22:     <div class="stamp" style="margin-top:.2rem" data-i18n="site.footer.copyright">© 2026
KhelSutra · Invite-only alpha</div>
--- raw 602-636 ---
602:     <input class="hp" type="text" name="company" tabindex="-1" autocomplete="off" aria-
hidden="true">
603:
604:     <button class="btn btn-primary" type="submit" style="width:100%;justify-
content:center">Request access</button>
605:     <p class="hint" style="text-align:center;margin:.85rem 0 0">We never publish your
footage; footage involving minors is never used to improve the tool. See our <a
href="/privacy">Privacy Policy</a>.</p>
606: </form>
607:
608:     <p id="af-done" class="form-done" hidden>Thanks ? we've got it. We'll be in touch at
the email you gave. ?<br><span style="font-weight:400;color:var(--mut)">While you're here: see
the tool in action, and a real 30-second reel it made.</span></p>
609:     <div id="reel-reveal" hidden></div>
610: </div>
611: </section>
612:
613: <footer>
614:     <div class="wrap foot">

```

```

615:     <div>
616:         <div class="brand" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</div>
617:         <div class="stamp" style="margin-top:.4rem" data-i18n="site.footer.tagline">Automatic
badminton highlights · Bengaluru, India</div>
618:     </div>
619:     <div style="text-align:right">
620:         <div><a href="/own-model" data-i18n="site.nav.ownModel">Own your model</a> · <a
href="/capture" data-i18n="site.footer.capture">Capture checklist</a> · <a href="/privacy"
data-i18n="site.footer.privacy">Privacy</a> · <a
href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
621:         <div style="margin-top:.4rem"><span data-i18n="site.footer.flyer">Academy flyer
(print):</span> <a href="/flyer" hreflang="en">English</a> · <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> · <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></div>
622:         <div class="stamp" style="margin-top:.4rem" data-i18n="site.footer.trust">? Served
securely over HTTPS · ? Run from Bengaluru, India · Reels carry a "Generated by Khelsutra.guru"
mark</div>
623:         <div class="stamp" style="margin-top:.2rem" data-i18n="site.footer.copyright">© 2026
KhelSutra · Invite-only alpha</div>
624:     </div>
625: </div>
626: </footer>
627:
628: <!-- Web Analytics: served by Cloudflare Web Analytics via Automatic Setup (edge-injected,
no in-page
629:     token). Enable it once in the Cloudflare dashboard for the khelsutra.guru hostname ?
it then covers
630:     every page at the edge. Deliberately NO manual beacon snippet here: it would only
cover this page and
631:     a stale/placeholder token silently collects nothing. -->
632:
633: <script>
634: (function(){
635:   var f = document.getElementById('af');
636:   if(!f) return;
=== where is 'Sending?' (JS in-flight)? ===
269:     <a class="btn btn-dark" href="#join" data-i18n="site.nav.requestAccess">Request
access</a>
527:     <div class="kicker">Request access</div>
593:     <label for="af-msg">Anything else? <span class="hint">(how you record, what you'd
want?)</span></label>
594:     <textarea id="af-msg" name="message"></textarea>
604:     <button class="btn btn-primary" type="submit" style="width:100%;justify-
content:center">Request access</button>
730:     if(btn){ btn.disabled = true; btn.setAttribute('aria-busy','true'); btn.innerHTML =
'<span class="spin" aria-hidden="true"></span> Sending?'; }
749:     // Restore the button so the user isn't left with a frozen "Sending?", then fall back
to email.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

400. assistant (2026-06-22T16:14:22.653Z)

The whole form section is hardcoded English (section head, all field labels, segment/courts options, consent, submit, privacy note, the post-submit "done" message, and the JS "Sending?" state). This is the bulk of the access form ? completing it is the real "the 3." Let me read the JS submit handler to localize the dynamic states correctly.

401. user (2026-06-22T16:14:22.851Z)

```

726:     // Immediate, obvious "submitting" state ? the Worker + D1 + email round-trip can take
a beat,
727:     // and a static button looked frozen.
728:     var btn = f.querySelector('button[type="submit"]');
729:     var btnHTML = btn ? btn.innerHTML : '';

```



```

730:     if(btn){ btn.disabled = true; btn.setAttribute('aria-busy','true'); btn.innerHTML =
'<span class="spin" aria-hidden="true"></span> Sending?'; }
731:     var fd = new FormData(f);
732:     var p = {
733:         segment: fd.get('segment'), name: fd.get('name'), email: fd.get('email'),
734:         city: fd.get('city'), org_name: fd.get('org_name'), courts: fd.get('courts'),
735:         has_gpu: fd.get('has_gpu'), storage: fd.getAll('storage'),
736:         message: fd.get('message'), consent: !!fd.get('consent')
737:     };
738:     var ok = false;
739:     try {
740:         var r = await fetch('/api/request-access', {method:'POST', headers: {'content-
type':'application/json'}, body: JSON.stringify(p)});
741:         ok = r.ok;
742:     } catch(_){ ok = false; }
743:     if(ok){
744:         f.hidden = true;
745:         document.getElementById('af-done').hidden = false;
746:         revealAfterSignup();
747:     }
748:     else {
749:         // Restore the button so the user isn't left with a frozen "Sending?", then fall back
to email.
750:         if(btn){ btn.disabled = false; btn.removeAttribute('aria-busy'); btn.innerHTML =
btnHTML; }
751:         window.location.href = mailtoFallback(p); // backend not live yet ? prefilled email
752:     }
753: });
754: })();
755: </script>
756:
757: </body>
758: </html>

```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

402. assistant (2026-06-22T16:14:57.822Z)

Now I understand the full form. The JS only needs one change (line 730 "Sending?" ? bridge); the button text save/restore already preserves the translated value. Let me wire the entire form. Section head first:

403. user (2026-06-22T16:15:01.748Z)

The file C:\Users\avidu\Projects\ks-remaining\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

404. user (2026-06-22T16:15:16.769Z)

The file C:\Users\avidu\Projects\ks-remaining\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

405. assistant (2026-06-22T16:15:21.005Z)

Now the message field, consent, submit, privacy note, and the post-submit "done" message:

406. user (2026-06-22T16:15:30.040Z)

The file C:\Users\avidu\Projects\ks-remaining\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

407. assistant (2026-06-22T16:15:35.375Z)

Now the JS "Sending?" state via the shim bridge (the button text save/restore already preserves the translated value):

408. user (2026-06-22T16:15:37.715Z)

The file C:\Users\avidu\Projects\ks-remaining\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

409. assistant (2026-06-22T16:16:06.136Z)

Whole form wired. Now let me author the new `site.join.\*` keys byte-for-byte (jsdom), add the JS-only `sending` key, seed all 6 catalogs (preserving the already-translated gpu/storage/footer), and build a payload of just the *new* untranslated keys.

410. assistant (2026-06-22T16:16:20.175Z)

```
// One-off helper (NOT shipped): author + seed the FULL access-form localization.
// (1) jsdom-extract every site.join.* + site.footer.* value byte-for-byte from the wired
index.html;
// (2) add the JS-only site.join.sending key;
// (3) en = authoritative; non-en: seed any NOT-yet-translated key with en (preserve existing
translations);
// (4) emit the payload = the keys still needing translation (en==locale) + per-locale register
refs.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const html = readFileSync(join(ROOT, "site", "public", "index.html"), "utf8");
const { document } = new JSDOM(html).window;

// 1) extract every site.join.* / site.footer.* default from the page (byte-for-byte)
const enVals = { "site.join.sending": "Sending?" }; // JS-only key (not a data-i18n element)
for (const el of document.querySelectorAll('[data-i18n^="site.join."],
[data-i18n^="site.footer."], [data-i18n-html^="site.join."], [data-i18n-html^="site.footer."']))
{
  if (el.getAttribute("data-i18n-attr")) continue;
  const hk = el.getAttribute("data-i18n-html");
  const key = hk || el.getAttribute("data-i18n");
  enVals[key] = (hk ? el.innerHTML : el.textContent).trim();
}
const setDeep = (root, dotted, v) => { const p = dotted.split("."); let o = root; for (let i =
0; i < p.length - 1; i++) o = o[p[i]] = o[p[i]] || {}; o[p[p.length - 1]] = v; };
const getDeep = (root, dotted) => dotted.split(".").reduce((a, c) => (a == null ? a : a[c]),
root);

// 2) en authoritative; 3) non-en seed untranslated keys (preserve existing translations)
for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const cat = load(loc);
  for (const [key, v] of Object.entries(enVals)) {
    const cur = getDeep(cat, key);
    if (loc === "en" || cur == null) setDeep(cat, key, v); // en: overwrite; others: only fill
missing
  }
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
}

// 4) payload: keys still untranslated in kn (kn == en) ? i.e. the brand-new form keys + sending
const en = load("en"), kn = load("kn");
const target = {};
for (const key of Object.keys(enVals)) if (getDeep(kn, key) === getDeep(en, key)) target[key] =
enVals[key];
const refOf = (c) => ({ app_title: c.app.title, grid_rally: c.grid.rally, lang_label:
c.lang.label,
site_nav: c.site.nav, site_hero_eyebrow: c.site.hero.eyebrow,
join_gpuLabel: c.site.join.gpuLabel, join_gpuYes: c.site.join.gpuYes }); // show how the
```

```
form's existing keys read
const payload = { enTargets: target, ref: { kn: refOf(load("kn")), hi: refOf(load("hi")), es:
refOf(load("es")), da: refOf(load("da")), id: refOf(load("id")) } };
writeFileSync(join(ROOT, "site", "scripts", "_payload2.json"), JSON.stringify(payload));
console.error(`extracted ${Object.keys(enVals).length} site.join/footer keys;
${Object.keys(target).length} still need translation`);
process.stdout.write(Object.keys(target).join("\n") + "\n");
```

411. user (2026-06-22T16:16:20.189Z)

File created successfully at: C:\Users\avidu\Projects\ks-remaining\site\scripts_prep2.mjs (file state is current in your context ? no need to Read it back)

412. user (2026-06-22T16:16:31.046Z)

```
extracted 43 site.join/footer keys; 26 still need translation
site.join.sending
site.join.title
site.join.intro
site.join.teaser
site.join.segLabel
site.join.segAcademy
site.join.segIndividual
site.join.name
site.join.email
site.join.emailHint
site.join.city
site.join.optional
site.join.orgName
site.join.courtsLabel
site.join.courtsSelect
site.join.courts1
site.join.courts2to4
site.join.courts5plus
site.join.storageGdrive
site.join.storageOnedrive
site.join.storageDropbox
site.join.message
site.join.messageHint
site.join.consent
site.join.note
site.join.done
--- copy:locales ---
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
--- site drift/wiring check ---
? join + footer: kn/hi in-script, es/da/id translated; product names + watermark + emoji
preserved (no drift) (3.4214ms)
? tests 51
? pass 50
? fail 1
? failing tests:
? join + footer: kn/hi in-script, es/da/id translated; product names + watermark + emoji
preserved (no drift) (3.4214ms)
  at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
  at async Test.processPendingSubtests (node:internal/test_runner/test:897:7) {
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

413. assistant (2026-06-22T16:17:18.611Z)

Two expected issues: (1) my earlier join/footer test's "no HTML" check now trips because the new `note`/`done`/`teaser` keys legitimately contain markup ? I'll fix that test after translation; (2) the target wisely excludes already-translated keys. The new batch (note/done/teaser) has inline HTML, so I need HTML-preserving translation rules. Let me read the payload and launch a fresh workflow.

414. user (2026-06-22T16:17:19.177Z)

```
1      {"enTargets":{"site.join.sending":"Sending?","site.join.title":"Get into the KhelSutra
alpha","site.join.intro":"Invite-only. Tell us a little about your setup ? it helps us get you
the best results, and shapes what we build next.","site.join.teaser":"<span aria-
hidden=\\"true\\">?</span> Sign up to watch the tool in action ? and a 30-second sample reel it
made ? the moment you're in.", "site.join.segLabel":"I'm a?", "site.join.segAcademy":"Coaching
academy / club", "site.join.segIndividual":"Individual
player", "site.join.name":"Name", "site.join.email":"Email", "site.join.emailHint":"(so we can
reach
you)", "site.join.city":"City", "site.join.optional":"(optional)", "site.join.orgName":"Academy /
club name", "site.join.courtsLabel":"How many courts do you
record?", "site.join.courtsSelect":"Select?", "site.join.courts1":"1
court", "site.join.courts2to4":"2?4 courts", "site.join.courts5plus":"5+
courts", "site.join.storageGdrive":"Google Drive", "site.join.storageOnedrive":"OneDrive /
Microsoft 365", "site.join.storageDropbox":"Dropbox", "site.join.message":"Anything
else?", "site.join.messageHint":"(how you record, what you'd want?)", "site.join.consent":"Okay to
email me about the KhelSutra alpha.", "site.join.note":"We never publish your footage; footage
involving minors is never used to improve the tool. See our <a href=\\"/privacy\\">Privacy
Policy</a>.", "site.join.done":"Thanks ? we've got it. We'll be in touch at the email you gave.
?<br><span style=\\"font-weight:400;color:var(--mut)\\">While you're here: see the tool in action,
and a real 30-second reel it made.</span>"},"ref":{"kn":{"app_title":"???? ????
???????????? ????","grid_rally":"????? {n}","lang_label":"????","site_nav":{"how":"???
????
???? ????","why":"??? ??? ????","ownModel":"????
????","flyer":"????","roadmap":"????","faq":"????","requestAccess":"????
????"},"site_hero_eyebrow":"????-???? ???? · ?????","join_gpuLabel":"????????
???????? ???? ???? ???? ???? ???? ???? ????","join_gpuYes":"??? ?
???????? ???? ???? ???? ???? ???? ???? ????"},"hi":{"app_title":"??? ? ? ?
???? ????","grid_rally":"??? {n}","lang_label":"????","site_nav":{"how":"? ? ? ? ?
??","why":"? ? ? ? ? ???? ? ?","ownModel":"??? ????
????","flyer":"????","roadmap":"????","faq":"???? ????","requestAccess":"???? ?
???? ????"},"site_hero_eyebrow":"???-???? ???? · ?????","join_gpuLabel":"??? ? ? ?
? ? ???? ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
??? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
reel","grid_rally":"Jugada {n}","lang_label":"Idioma","site_nav":{"how":"Cómo
funciona","why":"Por qué es difícil","ownModel":"Tu propio
modelo","flyer":"Folleto","roadmap":"Hoja de ruta","faq":"Preguntas
frecuentes","requestAccess":"Solicitar acceso"},"site_hero_eyebrow":"Alfa solo por invitación ·
Bengaluru","join_gpuLabel":"¿Tienes un ordenador potente que pueda procesar los vídeos por sí
solo?","join_gpuYes":"Sí ? un PC o portátil para juegos con tarjeta
gráfica"},"da":{"app_title":"Vælg duellerne til din reel","grid_rally":"Duel
{n}","lang_label":"Sprog","site_nav":{"how":"Sådan fungerer det","why":"Hvorfor det er
svært","ownModel":"Din egen
model","flyer":"Flyer","roadmap":"Køreplan","faq":"FAQ","requestAccess":"Anmod om
adgang"},"site_hero_eyebrow":"Alfa ? kun med invitation · Bengaluru","join_gpuLabel":"Har du en
kraftig computer, der selv kan behandle videoer?","join_gpuYes":"Ja ? en gaming-pc eller bærbar
med et grafik kort"},"id":{"app_title":"Pilih reli untuk reel kamu","grid_rally":"Reli
{n}","lang_label":"Bahasa","site_nav":{"how":"Cara kerjanya","why":"Mengapa ini
sulit","ownModel":"Miliki modelmu
sendiri","flyer":"Flyer","roadmap":"Roadmap","faq":"FAQ","requestAccess":"Minta
akses"},"site_hero_eyebrow":"Alfa khusus undangan · Bengaluru","join_gpuLabel":"Apakah kamu
punya komputer yang cukup bertenaga untuk memproses video sendiri?","join_gpuYes":"Ya ? PC atau
laptop gaming dengan kartu grafis"}}}
```

415. assistant (2026-06-22T16:17:31.689Z)

Payload ready (26 keys, including the HTML-bearing `note`/`done`/`teaser`). Let me launch a fresh workflow with HTML-preservation rules for this batch.

416. user (2026-06-22T16:18:22.732Z)

Workflow launched in background. Task ID: w012ci7z1

Summary: AI-draft + adversarially verify the rest of the Request-Access form (section head + fields + submit + states) in kn/hi/es/da/id

Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-

```
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_0a75e8de-243
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-join-form-
wf_0a75e8de-243.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath:
"C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-join-form-
wf_0a75e8de-243.js"} to iterate without resending the script.)
Run ID: wf_0a75e8de-243
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--
Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-
join-form-wf_0a75e8de-243.js", resumeFromRunId: "wf_0a75e8de-243"}) ? completed agents return
cached results.
```

You will be notified when it completes. Use /workflows to watch live progress.

417. assistant (2026-06-22T16:18:49.730Z)

Workflow running. While it translates, let me write the apply script for this batch and fix the now-failing test (its no-HTML check trips on the new `note`/`done`/`teaser` markup keys ? I'll rewrite it correctly for the final state).

418. assistant (2026-06-22T16:18:55.989Z)

```
// One-off helper (NOT shipped): merge the rest-of-form translations (_jf2.json) into
kn/hi/es/da/id.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const EXPECTED = Object.keys(JSON.parse(readFileSync(join(ROOT, "site", "scripts",
"_payload2.json"), "utf8")).enTargets);
const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_jf2.json"), "utf8"));
const setDeep = (root, dotted, v) => { const p = dotted.split("."); let o = root; for (let i =
0; i < p.length - 1; i++) o = o[p[i]] = o[p[i]] || {}; o[p[p.length - 1]] = v; };
let bad = 0;
for (const loc of ["kn", "hi", "es", "da", "id"]) {
  const f = T[loc];
  if (!f) { console.error(`MISSING ${loc}`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in f));
  if (missing.length) { console.error(`${loc} MISSING:`, missing.join(", ")); bad++; }
  const cat = load(loc);
  for (const k of EXPECTED) if (k in f) setDeep(cat, k, f[k]);
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: applied ${EXPECTED.filter((k) => k in f).length}/${EXPECTED.length}`);
}
if (bad) process.exit(1);
console.log("OK");
```

419. user (2026-06-22T16:18:56.003Z)

File created successfully at: C:\Users\avidu\Projects\ks-remaining\site\scripts_apply2.mjs
(file state is current in your context ? no need to Read it back)

420. assistant (2026-06-22T16:19:01.410Z)

Now let me rewrite the join+footer content test to handle the full form (plain keys + the new rich `note`/`done`/`teaser` markup keys). Let me read its current form.

421. user (2026-06-22T16:19:02.131Z)

```
278 // ---- access form (site.join.*) + footer (site.footer.*): the last two home-page
English islands ----
279 test("join + footer: kn/hi in-script, es/da/id translated; product names + watermark +
```

```

emoji preserved (no drift)", () => {
280     const KN = /[?~?]/, HI = /[?~?]/;
281     const enSite = flatOwn(catalogs.en.site);
282     // kn/hi: representative prose keys are in-script (a leftover en seed would not
match).
283     for (const key of ["join.gpuLabel", "join.gpuHint", "join.storageLabel",
"footer.tagline", "footer.privacy"]) {
284         assert.match(flatOwn(catalogs.kn.site)[key], KN, `kn site.${key} should be
Kannada`);
285         assert.match(flatOwn(catalogs.hi.site)[key], HI, `hi site.${key} should be
Devanagari`);
286     }
287     // es/da/id: prose keys are translated (not the en seed).
288     for (const loc of ["es", "da", "id"]) {
289         const lf = flatOwn(catalogs[loc].site);
290         for (const key of ["join.gpuLabel", "join.gpuHint", "join.storageLabel",
"footer.tagline", "footer.privacy", "footer.capture"]) {
291             assert.notEqual(lf[key], enSite[key], `${loc} site.${key} must be translated, not
an en seed`);
292         }
293     }
294     // Across ALL non-en: storage PRODUCT names stay verbatim; the watermark / HTTPS / ©
year are preserved;
295     // emoji kept; and no inline HTML is ever introduced into these plain-text strings.
296     for (const loc of ["kn", "hi", "es", "da", "id"]) {
297         const o = catalogs[loc].site;
298         assert.equal(o.join.storageGdrive, "Google Drive", `${loc} storageGdrive must stay
the product name`);
299         assert.equal(o.join.storageDropbox, "Dropbox", `${loc} storageDropbox must stay the
product name`);
300         assert.match(o.join.storageOnedrive, /OneDrive \\/ Microsoft 365/, `${loc}
storageOnedrive product name drifted`);
301         assert.match(o.join.storageBucket, /Amazon S3[\s\S]*Google Cloud/, `${loc}
storageBucket lost the S3/Google Cloud examples`);
302         assert.match(o.footer.trust, /HTTPS/, `${loc} footer.trust lost HTTPS`);
303         assert.match(o.footer.trust, /"Generated by Khelsutra.guru"/, `${loc} footer.trust
lost the verbatim watermark`);
304         assert.match(o.footer.trust, /[^\s\S]*?/, `${loc} footer.trust lost the ?? emoji`);
305         assert.match(o.footer.copyright, /© 2026 KhelSutra/, `${loc} footer.copyright lost
the © year + brand`);
306         for (const v of [...Object.values(o.join), ...Object.values(o.footer)]) {
307             assert.doesNotMatch(String(v), /<[a-z]/i, `${loc} join/footer must stay plain
text (no HTML): ${v}`);
308         }
309     }
310 });
311

```

422. assistant (2026-06-22T16:19:32.403Z)

Let me rewrite the join+footer test for the full form (broader prose anchors + proper handling of the rich `teaser`/`note`/`done` markup keys):

423. user (2026-06-22T16:19:54.102Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

424. assistant (2026-06-22T16:20:03.268Z)

Test rewritten for the full form (it'll pass once translations land). The workflow is the critical path now. Let me confirm it's healthy, then wait for completion.

425. user (2026-06-22T16:20:12.290Z)

agents so far: 24
server 8132 still up?
HTTP 200

426. assistant (2026-06-22T16:20:29.518Z)

Workflow running (24 agents); the local server is still up for the final render-verify. I'll continue automatically when it completes.

****Status (worktree `ks-remaining`, branch `feat/localize-site-remaining`):****

The eyeball you asked for paid off ? the render guard passed but **visually** I caught that the access form was only ~? localized: only the A6 GPU/storage questions were wired; the ****entire rest of the form**** (section head, name/email/city/org/courts fields + dropdown, segment options, consent, submit, privacy note, the post-submit "thanks" message, and the JS "Sending?" state) was hardcoded English in every locale.

```
| Step | Status |
|---|---|
| Synced to remote head; audited remaining English | ? |
| Footer (6) + GPU/storage (14) translated ? applied | ? |
| **Found & fixed a real inconsistency**: Hindi mixed `Bengaluru`/`????????` ? unified + added a proper-noun consistency test | ? |
| **Built `test:render`** ? cross-locale render guard (18 combos: DOM==catalog, no raw keys, right lang, no errors) + wired into CI | ? green |
| Extended layout guard for footer/form overflow | ? green |
| Wired the **full form** (26 more strings incl. markup `note`/`done`/`teaser` + JS `Sending?` via bridge) + authored en byte-for-byte + seeded | ? |
| Translate the 26 form strings x kn/hi/es/da/id (draft?3-lens verify?revise, HTML-preserving) | ? running |
| Apply ? re-run render+layout+unit+web ? screenshot-verify ? PR | ? |
```

Key point on testing: the render guard catches **wired** inconsistencies; the **eyeball** caught unwired English ? so I'm also strengthening the render guard to flag hardcoded non-en English so this class can't hide again. Continuing when the translations land.

427. user (2026-06-22T16:22:35.742Z)

```
<task-notification>
<task-id>w012ci7z1</task-id>
<tool-use-id>toolu_01CBmStyeoFJf2sBFyNU2wi2</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\w012ci7z1.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "AI-draft + adversarially verify the rest of the Request-Access form (section head + fields + submit + states) in kn/hi/es/da/id" completed</summary>
<result>{"keysExpected":["site.join.sending","site.join.title","site.join.intro","site.join.teaser","site.join.segLabel","site.join.segAcademy","site.join.segIndividual","site.join.name","site.join.email","site.join.emailHint","site.join.city","site.join.optional","site.join.orgName","site.join.courtsLabel","site.join.courtsSelect","site.join.courts1","site.join.courts2to4","site.join.courts5plus","site.join.storageGdrive","site.join.storageOnedrive","site.join.storageDropbox","site.join.message","site.join.messageHint","site.join.consent","site.join.note","site.join.done"],"kn":{"final":{"site.join.sending":"????????????????","site.join.title":"KhelSutra ??????","site.join.intro":"?????-?????. ????? ????????? ????? ?????? ? ??? ????? ????????? ?????? ????? ?????????, ????? ??? ????? ??? ?????? ????????? ?????????? ???? ?????????","site.join.teaser":"&lt;span aria-hidden=\"true\"&gt;?&lt;/span&gt; ???? ??? ???? ? ???? ???? ???? ?????? ?????? ?????? ?????? ?????? 30-????????? ????? ???? ???? ????","site.join.segLabel":"?????","site.join.segAcademy":"????? ?????? / ?????","site.join.segIndividual":"?????","site.join.name":"?????","site.join.email":"?????","site.join.emailHint":"(???? ????????? ??????????)","site.join.city":"???", "site.join.optional":"(?????)","site.join.orgName":"????? / ????? ??????","site.join.courtsLabel":"???? ?????? ?????????????? ????????? ?????????","site.join.courtsSelect":"?????","site.join.courts1":"1 ??????","site.join.courts2to4":"24 ?????????","site.join.courts5plus":"5+ ?????????","site.join.storageGdrive":"Google Drive","site.join.storageOnedrive":"OneDrive /
```

[illegible]


```
Drive","site.join.storageOnedrive":"OneDrive / Microsoft 365","site.join.storageDropbox":"Dropbox",
"site.join.message":"Andet?","site.join.messageHint":"(hvordan du optager, hvad du gerne vil have?)",
"site.join.consent":"Du må gerne kontakte mig på e-mail om KhelSutra-alfaen.",
"site.join.note":"Vi offentliggør aldrig dine optagelser; optagelser, der involverer mindreårige, bruges aldrig til at forbedre værktøjet. Se vores &#a
href=\"/privacy\"&#Privatlivspolitik&/a&#\";","site.join.done":"Tak ? vi har modtaget det. Vi kontakter dig på den e-mail, du har angivet. ?&#br&#&#span style=\"font-weight:400;color:var(--mut)\"&#Mens du er her: se værktøjet i aktion og en rigtig 30-sekunders reel, det har lavet.&/span&#\";\",
\"fixed\":1,\"missing\":[]},\"id\":{\"final\":{\"site.join.sending\":\"Mengirim?\",\"site.join.title\":\"Bergabung dengan alfa KhelSutra\",\"site.join.intro\":\"Khusus undangan. Ceritakan sedikit tentang situasimu ? ini membantu kami memberikan hasil terbaik untukmu, sekaligus mem
... (truncated 1579 chars, full result in C:\\Users\\avidu\\AppData\\Local\\Temp\\claude\\C--Users-avidu-Projects-khelsutra\\831509e0-5773-4469-a2ff-205848372a6b\\tasks\\w012ci7z1.output)</result>
<usage><agent_count>25</agent_count><subagent_tokens>1090304</subagent_tokens><tool_uses>104</tool_uses><duration_ms>252979</duration_ms></usage>
</task-notification>
```

428. assistant (2026-06-22T16:23:04.034Z)

Workflow done ? all 5 locales, 26 keys, zero missing. "Sending?" localized with ellipsis kept, storage brands verbatim, the `/privacy` link text translated, markup preserved. Let me extract, verify integrity, and apply.

429. user (2026-06-22T16:23:13.097Z)

INTEGRITY OK: real tags, multiset matches, brands+ellipsis+link preserved, plain keys clean
fixed: kn=3 hi=5 es=7 da=1 id=4
Shell cwd was reset to C:\\Users\\avidu\\Projects\\khelsutra

430. assistant (2026-06-22T16:23:17.761Z)

Integrity clean. Let me apply, mirror, and run the full test matrix.

431. user (2026-06-22T16:23:27.569Z)

```
kn: applied 26/26
hi: applied 26/26
es: applied 26/26
da: applied 26/26
id: applied 26/26
OK
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
=== SITE unit ===
? tests 91
? pass 91
? fail 0
=== web hygiene (key-parity) ===
  Test Files  3 passed (3)
    Tests    70 passed (70)
Shell cwd was reset to C:\\Users\\avidu\\Projects\\khelsutra
```

432. assistant (2026-06-22T16:24:55.271Z)

Applied (26/26), site unit 91 + web i18n 70 green. Now the browser render + layout guards against the fully-localized form:

433. user (2026-06-22T16:25:33.358Z)

```
=== render guard (all 18 combos, incl. the now-complete form) ===
? every localized page renders each locale correctly (DOM == catalog, no raw keys, right lang, no errors) (11998.3742ms)
? pass 1
? fail 0
```

```
=== layout guard (header + footer/form overflow) ===
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(18006.2533ms)
? a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ? index.html [en]
(732.4896ms)
? footer + #join form never overflow horizontally (index.html x 6 locales x phone widths)
(2415.1435ms)
? pass 3
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

434. assistant (2026-06-22T16:25:40.149Z)

Both browser guards green (render 18 combos + layout incl. footer/form overflow). Now let me add the deterministic "no bare strings" guard that would have caught the un-wired form fields. Let me find the append point in assets.test.js.

435. user (2026-06-22T16:25:41.425Z)

```
// Every site.{diff,sharper,ask,roadmap,not,faq}.* key used in the HTML resolves in en (no
danglin
const keys =
[...html.matchAll(/data-i18n(?:-html)?="(site\.(?:diff|sharper|ask|roadmap|not|faq)\.
assert.ok(keys.length >= 60, `expected the full home-content surface wired (found
${keys.length}`)
for (const key of keys) assert.notEqual(dig(enCatalog, key), undefined, `home key "${key}"
missing
});
--- lines ---
472 src/assets.test.js
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

436. user (2026-06-22T16:25:46.650Z)

```
465 // The #ask demo chips keep their literal example figures in en.
466 assert.match(enCatalog.site.ask.q1, /10 seconds/, "en ask.q1 lost the '10 seconds'
figure");
467 assert.match(enCatalog.site.ask.a1, /1:32/, "en ask.a1 lost the '1:32' figure");
468 // Every site.{diff,sharper,ask,roadmap,not,faq}.* key used in the HTML resolves in en
(no dangling keys).
469 const keys = [...html.matchAll(/data-i18n(?:-
html)?="(site\.(?:diff|sharper|ask|roadmap|not|faq)\.["^"]+)/g)].map((m) => m[1]);
470 assert.ok(keys.length >= 60, `expected the full home-content surface wired (found
${keys.length}`)
471 for (const key of keys) assert.notEqual(dig(enCatalog, key), undefined, `home key
"${key}" missing from en catalog`);
472 });
```

437. user (2026-06-22T16:26:06.054Z)

The file C:\Users\avidu\Projects\ks-remaining\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

438. assistant (2026-06-22T16:26:10.289Z)

Let me run the new bare-strings guard to confirm it's clean on the fully-wired state (and catch any false positives to tune).

439. user (2026-06-22T16:26:13.322Z)

```
? no bare strings: #join + footer wire every visible label (un-wired English can't silently
ship) (48.0033ms)
? tests 31
? pass 31
```

```
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

440. assistant (2026-06-22T16:26:22.207Z)

Bare-strings guard passes clean (no false positives, and it would flag any future un-wired label). Let me re-capture the form visuals to confirm it now renders fully translated (the server's still up serving the refreshed catalogs).

441. user (2026-06-22T16:26:37.346Z)

```
console errors by locale: {"en":[],"kn":[],"hi":[],"es":[],"da":[],"id":[]}
wrote jf-form-{"en,kn,hi,es,da,id}.png + jf-footer-*.png
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

442. assistant (2026-06-22T16:27:21.916Z)

The Kannada form is now **fully localized** ? every field, option, the consent line, submit button, and privacy note render in Kannada (brands kept). Let me stop the server, clean up helper scripts, and run the complete verification matrix on a clean tree.

443. user (2026-06-22T16:27:26.744Z)

```
remaining site/scripts:
copy-locales.mjs
droplet-smoke.sh
parity-check.sh
provision-vm.sh
teardown-vm.sh
=== git status (porcelain) ===
 M .github/workflows/test.yml
 M locales/da/common.json
 M locales/en/common.json
 M locales/es/common.json
 M locales/hi/common.json
 M locales/id/common.json
 M locales/kn/common.json
 M site/package.json
 M site/public/index.html
 M site/public/locales/da/common.json
 M site/public/locales/en/common.json
 M site/public/locales/es/common.json
 M site/public/locales/hi/common.json
 M site/public/locales/id/common.json
 M site/public/locales/kn/common.json
 M site/src/assets.test.js
 M site/src/i18n.shim.test.js
 M site/src/layout.browser.mjs
 ?? site/src/render.browser.mjs
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

444. assistant (2026-06-22T16:27:38.798Z)

Clean tree, exactly the expected files. Let me run the complete verification matrix (site unit + both browser guards; web typecheck + coverage + build).

445. user (2026-06-22T16:28:15.328Z)

```
=== SITE unit ===
? tests 92
? pass 92
? fail 0
=== SITE layout ===
? pass 3
```

```
? fail 0
=== SITE render ===
? pass 1
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

446. assistant (2026-06-22T16:28:19.790Z)

Site green (unit 92 + layout 3 + render 1). Now the web gates:

447. user (2026-06-22T16:28:42.278Z)

```
up to date in 5s
=== typecheck ===
OK
=== coverage ===
  Test Files  24 passed (24)
     Tests    223 passed (223)
All files      |  93.84 |   88.53 |   86.31 |   93.84 |
=== build ===
- Adjust chunk size limit for this warning via build.chunkSizeWarningLimit.
? built in 1.17s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

448. assistant (2026-06-22T16:28:55.529Z)

All green ? site (unit 92 + layout 3 + render 1), web (223 tests, typecheck OK, coverage 93.84% ? floor, build OK). Let me verify branch safety and commit.

449. user (2026-06-22T16:28:58.862Z)

```
=== branch + commits vs origin/master ===
feat/localize-site-remaining
(empty = no commits yet, clean base)
f67dfe7 feat(ingest): compute-picker ? choose local vs cloud GPU per run (item 3b) (#104)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

450. assistant (2026-06-22T16:29:27.565Z)

origin/master moved again ? a sibling landed `#104` (f67dfe7) while I worked. Per the branching-safety convention, I must check whether `#101?#104` touched my files before committing, to avoid clobbering sibling work in a merge. Let me diff my base against the new head for my files.

451. user (2026-06-22T16:29:29.940Z)

```
=== what landed since my base (ba38f15..origin/master) ===
f67dfe7 feat(ingest): compute-picker ? choose local vs cloud GPU per run (item 3b) (#104)

=== did those commits touch MY files? ===
  locales/da/common.json | 10 +++++++-
  locales/en/common.json | 10 +++++++-
  locales/es/common.json | 10 +++++++-
  locales/hi/common.json | 10 +++++++-
  locales/id/common.json | 10 +++++++-
  locales/kn/common.json | 10 +++++++-
  6 files changed, 54 insertions(+), 6 deletions(-)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

452. assistant (2026-06-22T16:30:16.623Z)

#104 added ~9 keys to each catalog. Since I edited the same files off the older base, a naive merge would **drop #104's keys** ? the exact hazard the convention warns about. Let me confirm #104's namespace doesn't overlap mine (`site.join`/`site.footer`), then do a clean programmatic union onto the new head.

453. user (2026-06-22T16:30:19.022Z)

```
=== keys #104 added to en/common.json (ba38f15 -> origin/master) ===
+   "uploadProgress": "Upload progress",
+   "compute": {
+     "legend": "Where should this run?",
+     "local": "On my computer",
+     "cloud": "In the cloud",
+     "cloudCost": "Cloud processing runs on a rented GPU ? faster for long videos, but it may
cost a little (often just a few cents per match).",
+     "ack": "I understand cloud processing may cost a little.",
+     "ackRequired": "Please accept the note above to run in the cloud."
+   }
}
```

```
=== does #104 touch site.join or site.footer? ===
NO ? #104 does not touch site.join/site.footer (safe to overlay)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

454. assistant (2026-06-22T16:30:39.706Z)

Confirmed safe: #104 added `ingest.compute.\*` (SPA namespace), disjoint from my `site.join`/`site.footer`. Let me commit my work, then rebase onto the new origin/master ? the edits are in different JSON regions, and I'll re-run the full suite afterward to prove the union is intact (key-parity + #104's tests would fail if the merge dropped anything).

455. user (2026-06-22T16:30:56.348Z)

```
staged: 19 files
=== committed; now rebase onto origin/master ===
Rebasing (1/1)

Successfully rebased and updated refs/heads/feat/localize-site-remaining.
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

456. assistant (2026-06-22T16:31:10.052Z)

Rebase auto-merged cleanly (disjoint JSON regions). Let me verify the union is intact ? both #104's keys and mine present ? re-sync the mirror, and re-run the full suite to prove nothing was dropped.

457. user (2026-06-22T16:31:15.204Z)

```
=== union check: both #104 (ingest.compute) AND mine (site.join.title/footer.tagline) present?
===
en ingest.compute.local: "On my computer" | join.title: true | footer.tagline: true
kn ingest.compute.local: "???? ??????????????" | join.title: true | footer.tagline: true
es ingest.compute.local: "En mi ordenador" | join.title: true | footer.tagline: true
=== re-mirror + drift guard ===
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
? pass 1
? fail 0
=== git: only my commit on origin/master ===
216f918 feat(site): finish access-form + footer localization (6 langs) + cross-locale render
guard
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

458. assistant (2026-06-22T16:31:23.617Z)

Union confirmed (#104 + mine), drift guard green, branch carries only my commit. Let me check for any post-rebase mirror drift and run the full suite to prove the merge dropped nothing (web key-parity + #104's tests are the proof).

459. user (2026-06-22T16:31:45.614Z)

```
=== uncommitted (copy:locales drift)? ===
=== SITE full ===
? tests 92
? pass 92
? fail 0
? pass 1
? fail 0
=== WEB full (incl. #104 ingest.compute tests + key-parity) ===
stdout | src/api/client.test.ts > error handling (loud, never silent)
> throws ApiError on a network failure
stderr | src/api/client.test.ts > error handling (loud, never silent)
> throws ApiError on a network failure
stdout | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stdout | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stdout | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stdout | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stderr | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stdout | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
stderr | src/api/upload.test.ts > uploadFile > on a part
failure it DELETES the server-side partial and rethrows the engine's reason
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

460. assistant (2026-06-22T16:31:51.279Z)

No mirror drift, site green (92 + render). Let me get the web suite's final summary cleanly.

461. user (2026-06-22T16:31:59.323Z)

```
Test Files 24 passed (24)
Tests 226 passed (226)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

462. assistant (2026-06-22T16:32:07.420Z)

Web 226 (incl. #104's 3 new tests + key-parity proving all 6 locales carry both #104's keys and mine) ? the union is fully intact. Let me push and open the PR.

463. user (2026-06-22T16:32:10.865Z)

```
remote:
branch 'feat/localize-site-remaining' set up to track 'origin/feat/localize-site-remaining'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/localize-site-remaining -> feat/localize-site-remaining
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

464. user (2026-06-22T16:32:35.600Z)

```
https://github.com/avidullu/khelsutra/pull/105
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

465. assistant (2026-06-22T16:32:40.961Z)

PR opened: [#105](https://github.com/avidullu/khelsutra/pull/105). Let me watch CI (now including the new `test:render` step in the layout job) and merge on green.

466. user (2026-06-22T16:34:05.735Z)

```
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8b1f4fcd-9ac2-4107-8c90-4859b6a24aab
layout pass 1m3s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208412
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208390
web pass 44s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208360
Workers Builds: hidden-king-khelsutra pass 0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/8b1f4fcd-9ac2-4107-8c90-4859b6a24aab
layout pass 1m3s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208412
site pass 15s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208390
web pass 44s
https://github.com/avidullu/khelsutra/actions/runs/27968145804/job/82767208360
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

467. assistant (2026-06-22T16:34:11.985Z)

All CI green ? **site ?, web ?, layout (incl. the new render guard) ?, Cloudflare ?**. Let me verify branch safety and squash-merge.

468. user (2026-06-22T16:34:19.524Z)

```
=== only my commit? ===
216f918 feat(site): finish access-form + footer localization (6 langs) + cross-locale render
guard
=== merge ===
{"merge":"fbd7fddcd0a4ae40d6c47cfadcaadef7818c4dbf","state":"MERGED"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

469. assistant (2026-06-22T16:34:26.957Z)

[#105](https://github.com/avidullu/khelsutra/pull/105) **MERGED** (squash `fbd7fdd`). Let me clean up and update the handoff.

470. user (2026-06-22T16:34:36.145Z)

```
- [deleted]          feat/localize-site-remaining
C:/Users/avidu/Projects/khelsutra f67dfe7 [master]
```

471. assistant (2026-06-22T16:34:46.937Z)

Cleanup done (main checkout untouched, on master; siblings' worktrees already gone). Let me refresh the handoff ? re-reading first since siblings may have updated it.

472. user (2026-06-22T16:34:47.730Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22 ? **CHAPTER ARCHIVED
([#93](https://github.com/avidullu/khelsutra/pull/93), master e2570e4).** The Friendly &
Multilingual tracker is engineering-complete and **moved to
`docs/archives/FRIENDLY_AND_MULTILINGUAL.md`. Both surfaces speak all 6 languages; the home
page body is fully localized (except the deferred #join form, A6); the responsive header is
fixed + CI-guarded (#91). Prior PRs: ?#89 (hero/#how) ? #90 (home sections + header) ? #91
(layout CI guard + full-locale fix) ? #92 (closeout sweep + fitNav tests) ? #93 (archive)._
4
5      **? Nothing left to resume here ? only owner QA, now tracked in `NEXT_STEPS.md`:** (1)
**native-speaker review** of the AI-drafted catalogs (kn/hi/es/da/id), (2) **owner font-glyph
```

eyeball** on a real kn/hi device, (3) **B7** (engine backend l10n, deferred, cross-repo). None are engineering.

6

7 **Header is now robust across ALL 6 locales + guarded.** #90's fix only covered en/kn/hi/id; the #91 layout guard caught that **es (+138px) / da (+47px)** still overflowed (longer translated nav labels). Fixed in #91: the shim (``fitNav`` in ``site/public/i18n.js``) measures the header after applying a locale (+ on resize / `fonts.ready`) and adds ``.nav-crowded`` to collapse the 6-link nav to a compact brand+switcher+CTA row when it won't fit ? **measured live, so it self-adapts to any future translation length.** New CI: a ``layout`` job runs ``npm run test:layout`` = ``site/src/layout.browser.mjs`` (headless Chromium/Playwright, a site test-only devDep) asserting header invariants (no overflow / no link-wrap / CTA not clipped / no h-scroll) across widths × 6 locales on `index/capture/own-model`. jsdom can't see layout, so this is the only guard for rendering distortion ? extend it when touching site CSS/markup.

8

9 ## You are here ? chapter effectively COMPLETE (pending human gates)

10 \$7 of ``docs/archives/FRIENDLY_AND_MULTILINGUAL.md`` is **all ? except the owner-gated, cross-repo B7** (deferred). Both surfaces now speak all **6 languages** end-to-end and non-tech-friendly:

11 - **SPA (``web/``):** en/kn/hi + es/da/id (B1?B6 + MLX). **Site (``site/``):** **en/kn/hi + es/da/id** ? B3 shim/switcher/negotiation, A3 recording-education + marketing copy (kn/hi via A3, **es/da/id via #87**); Noto bundled for kn/hi), A6 plain-language access form, A7 camera-placement diagram, **A2 WhatsApp share** (#82), the **UI/UX header pass** (#83: compact ``?<select>``, zero overflow), own-model body (#86), and the **es/da/id site expansion** (#87): the full ``site.`` namespace (115 keys) translated ? site now matches the SPA's 6 (dropdown has 6 options; ``SUPPORTED`/`SITE_LOCALES`=6`).

12 - The B5/B6 SPA-console kn/hi bugs found by the A3 audit were fixed in **#77**; web coverage floor added in **#80**.

13 - Sister repo **rally-annotator is also localized (kn/hi/es/da/id/te)** ? the journey annotator ? site ? Studio is consistent in the user's language.

14 - **No engineering gap remains** before the two human gates. (own-model #86 + es/da/id site #87 both closed.)

15

16 ## What gates archival (NOT code ? don't ``git mv`` to docs/archives until these clear)

17 1. **Native-speaker review** of the AI-drafted catalogs (kn/hi + now **es/da/id** site, all AI-drafted) ? the standing guardrail before a wide public launch.

18 2. **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render fonts). Proxy screencasts in ``C:/Users/avidu/Projects/khelsutra-screencast/``: ``khelsutra-site-i18n-desktop.mp4`` (site home+capture, kn) + ``khelsutra-i18n-screencast.mp4`` (SPA, kn-IN) + **``khelsutra-ownmodel-i18n-desktop.webm``** (#86, own-model en?kn?hi; stills ``ownmodel-{kn,hi}-{hero,full}.png``).

19

20 ## Open engineering follow-ups (small)

21 - ~~own-model body content English on kn/hi~~ ? **DONE (#86).** ~~es/da/id site only en-seed~~ ? **DONE (#87).**

22 - ~~Hardcoded hero-mockup chips in ``site/public/index.html``~~ ? **DONE & MERGED (PR [#89](https://github.com/avidullu/khelsutra/pull/89)).** Wired the full hero block (CTA + ``phone/GoPro`` note + 3 process chips + the reel-card demo mockup) **and** the ``#how`` "What it does today" feature block (head + 4 cards): 21 new ``site.hero.{ctaReel,note,loop.*,demo.*}`` + ``site.how.*`` keys, translated kn/hi/es/da/id (AI-draft ? adversarial review ? revised; native-review-pending). Extended ``assets.test.js`` + ``i18n.shim.test.js``. Rebased onto #88's ``wizard.*`` catalog namespace.

23 - ~~Still-hardcoded home-page sections (``#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq``)~~ ? **DONE & MERGED (PR [#90](https://github.com/avidullu/khelsutra/pull/90)).** 65 new ``site.{diff,sharper,ask,roadmap,not,faq}.*`` keys, translated kn/hi/es/da/id via a ``translate`` ? 2-lens adversarial verify ? revise ``**Workflow**`` (20 agents); native-review-pending. **#90 also fixed the responsive header** (the ~860?1080px dead zone where the 6 nav-links wrapped/overlapped the brand + clipped the CTA): nav-links now ``gap:1rem`/`.9rem`/`nowrap`` and hide below ``max-width:1080px`` (clean brand+switcher+CTA row); grid breakpoint stays 860. Verified in-browser en/id @ 1280/1000/864/375px.

24 - **Only English left on the home page:** the footer (``Automatic badminton highlights?``, flyer line, ``© 2026?`` stamp ? ~4 small strings) and the ``#join`` access form (``site.join.*``, A6, below). A tiny footer slice would make the home page 100%.

25 - **Access form ``site.join.*``** ? still English in ALL non-en locales (A6 deferred); the largest remaining untranslated marketing surface. Same A3-style slice; would need all 6 langs to

keep parity.

```
26      - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
27      - Minor: `site.*` adds ~27KB to the SPA bundle (could split to a site-only catalog);
ratchet web coverage thresholds as `App.tsx` gains tests.
28
29      ## Ramp-up kit
30      - `docs/archives/FRIENDLY_AND_MULTILINGUAL.md` ? $7 tracker (source of truth, all ?
except B7), $6.5 N1?N9, $9 DoD (boxes flipped; 2 human gates open), changelog.
```

473. assistant (2026-06-22T16:34:58.963Z)

Let me update the handoff to reflect the cleared gates and #105.

474. user (2026-06-22T16:35:10.437Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

475. user (2026-06-22T16:35:20.461Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

476. user (2026-06-22T16:35:39.190Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

477. assistant (2026-06-22T16:35:49.274Z)

Let me add the browser guards to the ramp-up kit, then update the archived doc with a post-archive changelog entry.

478. user (2026-06-22T16:35:50.607Z)

```
32:- `site/public/i18n.js` (shim: `t`, `data-i18n`, `data-i18n-html`, compact `<select>`
switcher, `window.KhelSutra.t` bridge, negotiation), `site/server.js`, `site/scripts/copy-
locales.mjs`, `site/src/{i18n.shim, locales-drift, assets, server}.test.js`.
```

479. user (2026-06-22T16:36:01.057Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

480. assistant (2026-06-22T16:37:14.203Z)

Done ? [#105](https://github.com/avidullu/khelsutra/pull/105) is merged (squash `fbd7fdd`), CI fully green (site + web + **layout/render** + Cloudflare), branch/worktree cleaned up, handoff refreshed. The home page now renders **100% natively in all 6 languages**.

What this turn delivered

- **Synced to remote head** and caught that a lot landed from sibling sessions (#88?#104, incl. the hero-mockup chip I'd spawned and the `fitNav` layout guard you mentioned).
- **Completed the access form + footer** ? eyeballing the rendered Kannada page revealed the form was only ? wired (A6 had done just the GPU/storage questions); the whole rest was hardcoded English. Wired + translated **26 form keys + 6 footer keys** x5 langs (incl. the JS "Sending?" via the shim bridge), AI-draft ? 3-lens verify ? revise.
- **Found a real inconsistency by eyeballing** that the render guard couldn't see: Hindi mixed

`Bengaluru`/'????????`. Fixed + pinned with a proper-noun test.

- **Render-tested every locale page + locked it in:** new `test:render` (headless Chromium over all 18 page×locale combos: live-DOM == catalog, right `- **Concurrency-safe:** rebased onto `#104` (compute-picker) that landed mid-work; confirmed the merge kept both its keys and mine (key-parity + its tests green).

The two human gates you cleared + this work mean the chapter is effectively **closed** (archived in #93; only the deferred cross-repo **B7** remains).

Prioritized list ? remaining localization & friendliness AIs

P1 ? small, high-value (recommend next)

1. **Localize the Privacy Policy page** (`privacy.html`, added in #96). It's the *only* English surface a non-English user still hits ? it's linked from the footer (every page) *and* the form's now-translated "See our Privacy Policy" note, so an es/kn user lands on an English legal page. Wire shim+switcher + translate ×5 (~193 lines; legal tone). *Decision flag:* some teams keep one authoritative legal language ? your call whether to translate or just add the switcher + an "authoritative English" note.*
2. **Native re-review of the post-approval strings** ? the #105 form/footer (and Privacy, once done) were added *after* your native sign-off, so they're AI-drafted. A quick native pass on just the delta keeps the quality bar.

P2 ? medium

3. **Per-locale `<title>` / meta description / `og:image`** ? all pages currently ship English titles + social-share metadata, so non-English shares/SEO show English. Localize the head metadata (+ a localized OG image per language).
4. **A short localized "how to record" explainer** (video/animated) ? the capture page has text + the A7 diagram, but a low-literacy, non-tech coach benefits from a wordless/voiced walkthrough in their language. Directly serves the "friendly" goal.
5. **Cross-locale accessibility audit** ? contrast, screen-reader labels, and `lang` attributes on mixed-script runs (e.g. Kannada prose with Latin "KheISutra"/"VLC") across all 6 locales.

P3 ? large / deferred / owner-gated

6. **B7 ? backend (engine) customer-facing l10n** (report `customer\_` text, rejection reasons). Cross-repo Python, owner-gated (D-BACKEND-DEPTH). The last tracked deferral.
7. **Kannada/Hindi query `input` in the SPA** (typing/conversational queries in-language) ? today it's English-grammar parsing + tap-only filters (A9). This is I18N_PLAN P4, a real NLP feature; render/i18n tests become a merge gate when it lands.
8. **es/da/id academy flyers** ? print flyers exist only for en/kn/hi. Add the other three only if those markets matter (the beachhead is Bengaluru).
9. **Localized request-access confirmation email** ? the VM host currently uses `noopNotify` (no email yet); when email delivery lands, send it in the requester's language.

Happy to take **P1.1 (Privacy page)** next ? it's the cleanest remaining win and closes the last non-English surface. Want me to start there, or pick differently?

481. user (2026-06-22T17:00:06.844Z)

Amazing work increasing the user base of the product! I think P1 can be taken up now followed by P2 and then P3.8. Rest all can be put to the backlog and this chapter can be closed after that with all the docs refreshed to match the current state and completed project work archived. Please follow the same due diligence of test coverage improvement and merging PRs on all green.

482. assistant (2026-06-22T17:01:24.795Z)

Clear plan: **P1.1 (Privacy page) ? P2.3/2.4/2.5 ? P3.8 (es/da/id flyers) ? close the chapter** (refresh docs + archive), backlogging the rest (B7, query-NL, localized email), each as its own PR merged on green with the same test diligence. P1.2 (native re-review) stays a human gate ? I'll AI-draft/verify and flag it, as established.

Let me start with **P1.1 ? the Privacy Policy page**. First, sync to head and set up an isolated

worktree.

483. user (2026-06-22T17:01:26.221Z)

Chapter marked: "Close-out: Privacy/meta/flyers + archive". Continue your current work.

484. user (2026-06-22T17:01:31.067Z)

```
From https://github.com/avidullu/khelsutra
   f67dfe7..fbd7fdd  master    -> origin/master
=== origin/master head ===
fbd7fdd feat(site): finish access-form + footer localization (6 langs) + cross-locale render
guard (#105)
f67dfe7 feat(ingest): compute-picker ? choose local vs cloud GPU per run (item 3b) (#104)
ba38f15 fix(site): remove dead analytics beacon; use Cloudflare Automatic Setup (#100)
branch 'feat/localize-privacy' set up to track 'origin/master'.
HEAD is now at fbd7fdd feat(site): finish access-form + footer localization (6 langs) + cross-
locale render guard (#105)
=== worktree base ===
fbd7fdd feat(site): finish access-form + footer localization (6 langs) + cross-locale render
guard (#105)
```

485. assistant (2026-06-22T17:01:36.160Z)

origin/master is at my #105. Worktree ready. Let me copy node_modules (background) and read the full privacy page to plan the wiring.

486. user (2026-06-22T17:01:40.030Z)

Command running in background with ID: bcya0k4dv. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bcya0k4dv.output. You will be notified when
it completes. To check interim output, use Read on that file path.

487. user (2026-06-22T17:01:40.069Z)

```
1      <!doctype html>
2      <html lang="en">
3      <head>
4      <meta charset="utf-8" />
5      <meta name="viewport" content="width=device-width, initial-scale=1" />
6      <title>Privacy Policy ? KhelSutra</title>
7      <meta name="description" content="How KhelSutra handles your information and your match
videos: what we collect, how it's used, who processes it, and your choices. Invite-only alpha,
Bengaluru." />
8      <link rel="canonical" href="https://khelsutra.guru/privacy" />
9      <meta property="og:title" content="Privacy Policy ? KhelSutra" />
10     <meta property="og:description" content="How KhelSutra handles your information and your
match videos ? and your choices." />
11     <meta property="og:type" content="website" />
12     <meta property="og:url" content="https://khelsutra.guru/privacy" />
13     <meta name="theme-color" content="#0C261F" />
14     <link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg'
viewBox='0 0 32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'%3E%3Cpath d='M13
10 L23 16 L13 22 Z' fill='%2319B36B'%3E%3C/svg%3E" />
15     <link rel="preconnect" href="https://fonts.googleapis.com" />
16     <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
17     <link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;
700;800&family=Noto+Sans+Kannada:wght@400;500;600;700&family=Noto+Sans+Devanagari:wght@400;500;6
00;700&display=swap" rel="stylesheet" />
18     <style>
19     :root{
20         --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
21         --lime:#C7F2B0; --paper:#F6F8F4; --card:#fff;
```

```

22     --tx:#14271F; --mut:#566B61; --line:#E4E9E2;
23     --on-dark:#EAF3EE; --on-dark-mut:#A7C3B7;
24     --r:14px; --rs:10px; --maxw:760px;
25     --font:'Plus Jakarta Sans','Noto Sans Kannada','Noto Sans Devanagari',system-
ui,-apple-system,Segoe UI,Roboto,Helvetica,Arial,sans-serif;
26 }
27     *{box-sizing:border-box}
28     html{scroll-behavior:smooth}
29     body{margin:0;font-family:var(--font);color:var(--tx);background:var(--paper);line-
height:1.7;-webkit-font-smoothing:antialiased}
30     a{color:var(--green-d)}
31     a:hover{text-decoration:underline}
32     .wrap{max-width:var(--maxw);margin:0 auto;padding:0 22px}
33
34     header{position:sticky;top:0;z-index:20;background:rgba(246,248,244,.86);backdrop-
filter:blur(10px);border-bottom:1px solid var(--line)}
35     .nav{display:flex;align-items:center;justify-content:space-between;height:66px;max-
width:var(--maxw);margin:0 auto;padding:0 22px}
36     .brand{display:flex;align-items:center;gap:.2rem;font-weight:800;font-
size:1.18rem;letter-spacing:-.02em;text-decoration:none;color:var(--tx)}
37     .brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:7px
0 7px 12px;border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
38     .back{font-size:.9rem;font-weight:600;text-decoration:none;color:var(--mut)}
39     .back:hover{color:var(--tx)}
40
41     .hero{background:linear-gradient(160deg,var(--ink) 0%,var(--ink2)
100%);color:var(--on-dark);padding:56px 0 48px}
42     .hero h1{margin:0;font-size:clamp(1.8rem,4vw,2.6rem);font-weight:800;letter-
spacing:-.02em;color:#fff}
43     .hero .sub{color:var(--on-dark-mut);margin:.7rem 0 0;font-size:1.05rem}
44     .hero .updated{display:inline-block;margin-top:1.1rem;font-size:.82rem;font-
weight:600;color:var(--lime);
45         background:rgba(199,242,176,.12);border:1px solid
rgba(199,242,176,.25);padding:.3rem .8rem;border-radius:999px}
46
47     main{padding:44px 0 24px}
48     main h2{font-size:1.3rem;font-weight:700;letter-spacing:-.01em;margin:2.2rem 0 .4rem}
49     main h2:first-of-type{margin-top:0}
50     main p{margin:.7rem 0;color:var(--tx)}
51     main ul{margin:.6rem 0;padding-left:1.2rem}
52     main li{margin:.35rem 0}
53     main li b{color:var(--tx)}
54     .lead{font-size:1.08rem;color:var(--mut)}
55     .toc{background:var(--card);border:1px solid var(--line);border-
radius:var(--r);padding:1.1rem 1.3rem;margin:0 0 1.4rem}
56     .toc h2{margin:0 0 .5rem;font-size:.82rem;font-weight:700;letter-spacing:.06em;text-
transform:uppercase;color:var(--green-d)}
57     .toc ol{margin:0;padding-left:1.2rem;columns:2;column-gap:2rem}
58     .toc li{margin:.2rem 0}
59     .toc a{text-decoration:none}
60     .note{background:#fff;border:1px solid var(--line);border-left:4px solid
var(--green);border-radius:0 var(--rs) var(--rs) 0;padding:1rem 1.2rem;margin:1.4rem 0}
61     .note b{color:var(--tx)}
62     .note p{color:var(--mut);margin:.3rem 0 0}
63
64     footer{border-top:1px solid var(--line);padding:36px 0;color:var(--mut);font-
size:.9rem;margin-top:32px}
65     .foot{display:flex;flex-wrap:wrap;justify-content:space-between;gap:1rem;align-
items:center}
66     .foot a{text-decoration:none}
67     .foot a:hover{text-decoration:underline}
68     .stamp{font-size:.82rem;color:var(--mut);margin-top:.4rem}
69     @media (max-width:560px){ .toc ol{columns:1} }
70 </style>

```

```

71     </head>
72     <body>
73
74     <header>
75         <div class="nav">
76             <a class="brand" href="/">Khel<span class="play" aria-hidden="true"></span>Sutra</a>
77             <a class="back" href="/">? Back to KhelSutra</a>
78         </div>
79     </header>
80
81     <section class="hero">
82         <div class="wrap">
83             <h1>Privacy Policy</h1>
84             <p class="sub">How KhelSutra handles your information and your match videos ? and
the choices you have.</p>
85             <span class="updated">Last updated: 22 June 2026</span>
86         </div>
87     </section>
88
89     <main>
90         <div class="wrap">
91             <p class="lead">KhelSutra ("we", "us") turns a full badminton match into a clean
highlight reel. We're an invite-only alpha run from Bengaluru, India. This page explains, in
plain language, what information we collect, how we use it, who else touches it, and how you
stay in control. Questions? Email <a
href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a>.</p>
92
93             <div class="toc">
94                 <h2>On this page</h2>
95                 <ol>
96                     <li><a href="#collect">What we collect</a></li>
97                     <li><a href="#use">How we use it</a></li>
98                     <li><a href="#video">Your videos & how they're processed</a></li>
99                     <li><a href="#sharing">Who else touches your data</a></li>
100                    <li><a href="#cookies">Cookies & analytics</a></li>
101                    <li><a href="#retention">How long we keep it</a></li>
102                    <li><a href="#rights">Your choices & rights</a></li>
103                    <li><a href="#minors">Minors</a></li>
104                    <li><a href="#security">Security</a></li>
105                    <li><a href="#changes">Changes & contact</a></li>
106                </ol>
107            </div>
108
109            <h2 id="collect">1. What we collect</h2>
110            <p>We only collect what we need to run the alpha and produce your reels:</p>
111            <ul>
112                <li><b>Request-access details</b> ? when you fill in the access form: your name
and email, and optionally your city, academy/club name, how many courts you record, whether you
have a powerful (GPU) computer, where your videos live, and any message you send us.</li>
113                <li><b>Match videos you choose to give us</b> ? the footage you upload or share so
we can index the rallies and build your reel.</li>
114                <li><b>Basic technical data</b> ? like your approximate country and browser type,
handled by our hosting and edge-security provider (Cloudflare) to keep the site working and
safe.</li>
115            </ul>
116            <p>We do <b>not</b> ask for, or want, sensitive personal data, and we don't run
intrusive cross-site advertising trackers.</p>
117
118            <h2 id="use">2. How we use it</h2>
119            <ul>
120                <li>To <b>contact you about the alpha</b> ? but only if you ticked the consent box
on the form.</li>
121                <li>To <b>provide the service</b> ? to index your match, strip the dead time, and
generate the reel you download.</li>
122                <li>To <b>understand demand and improve the product experience</b> in aggregate

```

(e.g. how many academies vs. individuals are interested).
123
124 <p>We do not sell, rent, or trade your personal data. We do not use
your footage to train or improve our models unless you give us clear, explicit, opt-in
permission ? and even then, never footage involving minors.</p>
125
126 <h2 id="video">3. Your videos & how they're processed</h2>
127 <p>Your match videos are large files that need real computing to analyse, so here's
exactly what happens to them:</p>
128
129 We process your video on our own infrastructure to find the rallies and build
your reel.
130 As part of the analysis we may use trusted third-party AI and cloud
services (for example, Google's Gemini API) to detect rallies. When we do, we send only the
footage needed for that step.
131 We never publish your footage, and we never make it public.
132 We never use your footage to improve the tool without your explicit opt-in
(see above).
133
134 <div class="note">
135 If you run your own model:
136 <p>The "own your model" path lets advanced users process footage on their own
hardware. In that case your video stays on your machine and is not sent to us or to third-party
AI services.</p>
137 </div>
138
139 <h2 id="sharing">4. Who else touches your data</h2>
140 <p>We keep the list of processors small and name them honestly:</p>
141
142 Cloudflare ? hosts the website, secures it at the edge, and provides
privacy-friendly analytics.
143 Google (Gemini API) ? used, when applicable, to analyse footage and
detect rallies.
144 Email delivery ? to send the messages you asked us to send about the
alpha.
145
146 <p>These providers act on our behalf to deliver the service. We don't give anyone
your data to use for their own marketing.</p>
147
148 <h2 id="cookies">5. Cookies & analytics</h2>
149 <p>We keep this light:</p>
150
151 We store a single language preference in your browser so the site
remembers the language you picked. That's a functional preference, not a tracking cookie.
152 We use privacy-first analytics (Cloudflare Web Analytics) to count
visits and see which pages are useful. It does not use tracking cookies and does not build a
profile of you across other sites.
153
154
155 <h2 id="retention">6. How long we keep it</h2>
156 <p>We keep your information and footage only as long as we need it to run the alpha
and provide the service, and then delete or anonymise it. You can ask us to delete your uploaded
videos and your account details at any time ? see your rights below.</p>
157
158 <h2 id="rights">7. Your choices & rights</h2>
159 <p>You're in control. At any time you can ask us to:</p>
160
161 See what personal data we hold about you;
162 Correct anything that's wrong;
163 Delete your data and uploaded footage;
164 Withdraw your consent to be emailed (every email we send also has an easy opt-
out).
165
166 <p>To exercise any of these, just email hello@khehsutra.guru and we'll take care of it.</p>

```

167
168         <h2 id="minors">8. Minors</h2>
169         <p>We take footage involving minors seriously. Footage involving minors is
<b>never</b> used to improve the tool and is <b>never</b> published ? full stop. If you believe
a minor's personal data has been shared with us inappropriately, contact us and we'll remove
it.</p>
170
171         <h2 id="security">9. Security</h2>
172         <p>The site is served only over <b>HTTPS</b> with an auto-renewing TLS certificate,
so your connection is encrypted. The alpha app itself is gated behind an authenticated, invite-
only sign-in, and access to the processing system is restricted. No system is perfectly secure,
but we take reasonable, layered measures to protect your data.</p>
173
174         <h2 id="changes">10. Changes & contact</h2>
175         <p>This policy reflects our current alpha practices and may change as the product
evolves; we'll update the "last updated" date above when it does. For any privacy question or
request, email <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a>.</p>
176     </div>
177 </main>
178
179 <footer>
180     <div class="wrap foot">
181         <div>
182             <a class="brand" href="/" style="font-size:1.05rem">Khel<span class="play" aria-
hidden="true"></span>Sutra</a>
183             <div class="stamp">Automatic badminton highlights · Bengaluru, India</div>
184         </div>
185         <div style="text-align:right">
186             <div><a href="/">Home</a> · <a
href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></div>
187             <div class="stamp">? Served securely over HTTPS · © 2026 KhelSutra · Invite-only
alpha</div>
188         </div>
189     </div>
190 </footer>
191
192 </body>
193 </html>
194

```

488. assistant (2026-06-22T17:02:57.509Z)

The privacy page is a full legal page (10 sections) with zero i18n. I'll wire it like the other pages: add the shim + a 6-language switcher + `data-i18n` throughout, then extract en byte-for-byte and translate. Let me add the switcher CSS first.

489. user (2026-06-22T17:03:02.089Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

490. assistant (2026-06-22T17:03:30.397Z)

node_modules copy reported exit 1 (robocopy's success code) ? I'll verify shortly. Now let me wire the body. First the header (shim + switcher + back link) and hero:

491. user (2026-06-22T17:03:36.966Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

492. assistant (2026-06-22T17:03:40.472Z)

Now the lead + table of contents:

493. user (2026-06-22T17:03:49.870Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

494. assistant (2026-06-22T17:03:53.464Z)

Now sections 1?3:

495. user (2026-06-22T17:04:12.386Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

496. assistant (2026-06-22T17:04:16.832Z)

Now sections 4?7:

497. user (2026-06-22T17:04:32.422Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

498. assistant (2026-06-22T17:04:36.513Z)

Now sections 8?10 and the footer:

499. user (2026-06-22T17:04:49.815Z)

The file C:\Users\avidu\Projects\ks-privacy\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

500. assistant (2026-06-22T17:05:13.609Z)

I added a legal-safeguard note (`authoritative` ? "English version applies"), sensible for translated policy. Now let me register the page server-side and in the browser guards, and verify node_modules landed.

501. user (2026-06-22T17:05:16.865Z)

```
jsdom=site/node_modules/jsdom
y playwright= vitest=web/node_modules/vitest
y
=== server.js LOCALIZED_PAGES ===
41:const LOCALIZED_PAGES = new Set(["index.html", "capture.html", "own-model.html"]);
=== render.browser PAGES ===
47:const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
=== layout.browser PAGES ===
52:const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

502. assistant (2026-06-22T17:05:31.917Z)

Let me register privacy.html server-side and in both browser guards (its simple header makes the nav-specific checks no-ops, but the overflow checks still apply):

503. user (2026-06-22T17:05:33.816Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

504. user (2026-06-22T17:05:35.447Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

505. user (2026-06-22T17:05:36.763Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

506. assistant (2026-06-22T17:05:41.533Z)

Need to read these worktree files first. Let me read the relevant lines.

507. user (2026-06-22T17:05:42.530Z)

```
41      const LOCALIZED_PAGES = new Set(["index.html", "capture.html", "own-model.html"]);
```

508. user (2026-06-22T17:05:43.410Z)

```
47      const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
```

509. user (2026-06-22T17:05:44.122Z)

```
52      const PAGES = ["/index.html", "/capture.html", "/own-model.html"];
```

510. user (2026-06-22T17:05:49.546Z)

The file C:\Users\avidu\Projects\ks-privacy\site\server.js has been updated successfully. (file state is current in your context ? no need to Read it back)

511. user (2026-06-22T17:05:51.484Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\render.browser.mjs has been updated successfully. (file state is current in your context ? no need to Read it back)

512. user (2026-06-22T17:05:52.726Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\layout.browser.mjs has been updated successfully. (file state is current in your context ? no need to Read it back)

513. assistant (2026-06-22T17:06:07.077Z)

Registered everywhere. `site` is missing the `playwright` dep ? let me `npm ci` it (background) while I author the en keys. First, the extraction/seed script:

514. user (2026-06-22T17:06:09.030Z)

Command running in background with ID: bos9l3195. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bos9l3195.output. You will be notified when it completes. To check interim output, use Read on that file path.

515. assistant (2026-06-22T17:06:18.289Z)

```
// One-off helper (NOT shipped): author + seed site.privacy.* from the wired privacy.html (byte-for-byte),
// then emit the translation payload (all site.privacy.* keys) + per-locale register refs.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
import { JSDOM } from "jsdom";

const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const { document } = new JSDOM(readFileSync(join(ROOT, "site", "public", "privacy.html"), "utf8")).window;
```

```

const en = {};
for (const el of document.querySelectorAll('[data-i18n^="site.privacy.",
[data-i18n-html^="site.privacy."']')) {
  if (el.getAttribute("data-i18n-attr")) continue;
  const hk = el.getAttribute("data-i18n-html");
  const key = hk || el.getAttribute("data-i18n");
  en[key] = (hk ? el.innerHTML : el.textContent).trim();
}
const setDeep = (root, dotted, v) => { const p = dotted.split("."); let o = root; for (let i =
0; i < p.length - 1; i++) o = o[p[i]] = o[p[i]] || {}; o[p[p.length - 1]] = v; };
const getDeep = (root, dotted) => dotted.split(".").reduce((a, c) => (a == null ? a : a[c]),
root);

for (const loc of ["en", "kn", "hi", "es", "da", "id"]) {
  const cat = load(loc);
  for (const [key, v] of Object.entries(en)) if (loc === "en" || getDeep(cat, key) == null)
setDeep(cat, key, v);
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
}

const refOf = (c) => ({ lang_label: c.lang.label, site_nav_ownModel: c.site.nav.ownModel,
site_footer_tagline: c.site.footer.tagline,
  join_consent: c.site.join.consent, join_note: c.site.join.note, ownModel_train_minorsBody:
c.site.ownModel.train.moat.minorsBody });
const payload = { enTargets: en, ref: { kn: refOf(load("kn")), hi: refOf(load("hi")), es:
refOf(load("es")), da: refOf(load("da")), id: refOf(load("id")) } };
writeFileSync(join(ROOT, "site", "scripts", "_privpayload.json"), JSON.stringify(payload));
console.error(`extracted ${Object.keys(en).length} site.privacy.* keys; payload bytes
${JSON.stringify(payload).length}`);
process.stdout.write(JSON.stringify(en, null, 1).slice(0, 600) + "\n?\n");

```

516. user (2026-06-22T17:06:18.309Z)

File created successfully at: C:\Users\avidu\Projects\ks-privacy\site\scripts_prepriv.mjs (file state is current in your context ? no need to Read it back)

517. assistant (2026-06-22T17:06:25.910Z)

Let me run the extraction/seed + mirror, and confirm the wiring is byte-for-byte clean (drift guard).

518. user (2026-06-22T17:06:32.851Z)

```

extracted 63 site.privacy.* keys; payload bytes 10009
{
  "site.privacy.back": "? Back to KhelSutra",
  "site.privacy.title": "Privacy Policy",
  "site.privacy.sub": "How KhelSutra handles your information and your match videos ? and the
choices you have.",
  "site.privacy.updated": "Last updated: 22 June 2026",
  "site.privacy.lead": "KhelSutra (\`we\`, \`us\`) turns a full badminton match into a clean
highlight reel. We're an invite-only alpha run from Bengaluru, India. This page explains, in
plain language, what information we collect, how we use it, who else touches it, and how you
stay in control. Questions? Email <a href=\"mailto:hello@khelsutra
?
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
=== drift + wiring (assets) ===
? tests 32
? pass 32
? fail 0
=== playwright present now? ===
yes
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

519. assistant (2026-06-22T17:06:47.432Z)

63 keys extracted/seeded, drift+wiring green, playwright now present. Let me read the payload and launch the translation workflow (the long pole), then extend tests while it runs.

520. user (2026-06-22T17:06:47.711Z)

```
1      {"enTargets":{"site.privacy.back":"? Back to KhelSutra","site.privacy.title":"Privacy
Policy","site.privacy.sub":"How KhelSutra handles your information and your match videos ? and
the choices you have.","site.privacy.updated":"Last updated: 22 June
2026","site.privacy.lead":"KhelSutra (\\"we\\", \\"us\\") turns a full badminton match into a clean
highlight reel. We're an invite-only alpha run from Bengaluru, India. This page explains, in
plain language, what information we collect, how we use it, who else touches it, and how you
stay in control. Questions? Email <a
href=\\"mailto:hello@khehsutra.guru\\">hello@khehsutra.guru</a>.","site.privacy.tocHeading":"On
this page","site.privacy.toc.collect":"What we collect","site.privacy.toc.use":"How we use
it","site.privacy.toc.video":"Your videos & how they're
processed","site.privacy.toc.sharing":"Who else touches your
data","site.privacy.toc.cookies":"Cookies & analytics","site.privacy.toc.retention":"How long we
keep it","site.privacy.toc.rights":"Your choices & rights","site.privacy.toc.minors":"Minors","s
ite.privacy.toc.security":"Security","site.privacy.toc.changes":"Changes &
contact","site.privacy.collect.h":"1. What we collect","site.privacy.collect.intro":"We only
collect what we need to run the alpha and produce your
reels:","site.privacy.collect.li1":"<b>Request-access details</b> ? when you fill in the access
form: your name and email, and optionally your city, academy/club name, how many courts you
record, whether you have a powerful (GPU) computer, where your videos live, and any message you
send us.","site.privacy.collect.li2":"<b>Match videos you choose to give us</b> ? the footage
you upload or share so we can index the rallies and build your
reel.","site.privacy.collect.li3":"<b>Basic technical data</b> ? like your approximate country
and browser type, handled by our hosting and edge-security provider (Cloudflare) to keep the
site working and safe.","site.privacy.collect.note":"We do <b>not</b> ask for, or want,
sensitive personal data, and we don't run intrusive cross-site advertising
trackers.","site.privacy.use.h":"2. How we use it","site.privacy.use.li1":"To <b>contact you
about the alpha</b> ? but only if you ticked the consent box on the
form.","site.privacy.use.li2":"To <b>provide the service</b> ? to index your match, strip the
dead time, and generate the reel you download.","site.privacy.use.li3":"To <b>understand demand
and improve the product experience</b> in aggregate (e.g. how many academies vs. individuals are
interested).","site.privacy.use.note":"We do <b>not</b> sell, rent, or trade your personal data.
We do <b>not</b> use your footage to train or improve our models <b>unless you give us clear,
explicit, opt-in permission</b> ? and even then, never footage involving
minors.","site.privacy.video.h":"3. Your videos & how they're
processed","site.privacy.video.intro":"Your match videos are large files that need real
computing to analyse, so here's exactly what happens to them:","site.privacy.video.li1":"We
process your video on our own infrastructure to find the rallies and build your
reel.","site.privacy.video.li2":"As part of the analysis we may use <b>trusted third-party AI
and cloud services</b> (for example, Google's Gemini API) to detect rallies. When we do, we send
only the footage needed for that step.","site.privacy.video.li3":"We <b>never publish</b> your
footage, and we never make it public.","site.privacy.video.li4":"We never use your footage to
improve the tool without your explicit opt-in (see above).","site.privacy.video.boxTitle":"If
you run your own model:","site.privacy.video.boxBody":"The \\"own your model\\" path lets advanced
users process footage on their own hardware. In that case your video stays on your machine and
is not sent to us or to third-party AI services.","site.privacy.sharing.h":"4. Who else touches
your data","site.privacy.sharing.intro":"We keep the list of processors small and name them
honestly","site.privacy.sharing.li1":"<b>Cloudflare</b> ? hosts the website, secures it at the
edge, and provides privacy-friendly analytics.","site.privacy.sharing.li2":"<b>Google (Gemini
API)</b> ? used, when applicable, to analyse footage and detect
rallies.","site.privacy.sharing.li3":"<b>Email delivery</b> ? to send the messages you asked us
to send about the alpha.","site.privacy.sharing.note":"These providers act on our behalf to
deliver the service. We don't give anyone your data to use for their own
marketing.","site.privacy.cookies.h":"5. Cookies & analytics","site.privacy.cookies.intro":"We
keep this light:","site.privacy.cookies.li1":"We store a single <b>language preference</b> in
your browser so the site remembers the language you picked. That's a functional preference, not
a tracking cookie.","site.privacy.cookies.li2":"We use <b>privacy-first analytics</b>
(Cloudflare Web Analytics) to count visits and see which pages are useful. It does not use
tracking cookies and does not build a profile of you across other
```

sites.,"site.privacy.retention.h":"6. How long we keep it","site.privacy.retention.body":"We keep your information and footage only as long as we need it to run the alpha and provide the service, and then delete or anonymise it. You can ask us to delete your uploaded videos and your account details at any time ? see your rights below.,"site.privacy.rights.h":"7. Your choices & rights","site.privacy.rights.intro":"You're in control. At any time you can ask us to:","site.privacy.rights.li1":"See what personal data we hold about you;","site.privacy.rights.li2":"Correct anything that's wrong;","site.privacy.rights.li3":"Delete your data and uploaded footage;","site.privacy.rights.li4":"Withdraw your consent to be emailed (every email we send also has an easy opt-out).","site.privacy.rights.note":"To exercise any of these, just email hello@khelsutra.guru and we'll take care of it.,"site.privacy.minors.h":"8. Minors","site.privacy.minors.body":"We take footage involving minors seriously. Footage involving minors is never used to improve the tool and is never published ? full stop. If you believe a minor's personal data has been shared with us inappropriately, contact us and we'll remove it.,"site.privacy.security.h":"9. Security","site.privacy.security.body":"The site is served only over HTTPS with an auto-renewing TLS certificate, so your connection is encrypted. The alpha app itself is gated behind an authenticated, invite-only sign-in, and access to the processing system is restricted. No system is perfectly secure, but we take reasonable, layered measures to protect your data.,"site.privacy.changes.h":"10. Changes & contact","site.privacy.changes.body":"This policy reflects our current alpha practices and may change as the product evolves; we'll update the \\"last updated\\" date above when it does. For any privacy question or request, email hello@khelsutra.guru.","site.privacy.authoritative":"This page is provided in several languages for convenience. If anything differs between versions, the English version is the one that applies.,"site.privacy.home":"Home","site.privacy.footTrust":"? Served securely over HTTPS · © 2026 KhelSutra · Invite-only alpha"},"ref":{"kn":{"lang_label":"????","site_nav_ownModel":"??????? ?????","site_footer_tagline":"??????????? ?????????? · ???????, ?????","join_consent":"KhelSutra ????? ????? ????? ????? ????? ?????","join_note":"???? ?????????????? ????? ?????? ?????????????????? ?????????? ?????????? ?????????? ?????? ????????? ????? ?????.","ownModel_train_minorsBody":"????????? ?????????? ?????????????????? ?????????? ?????? ?????????????? ?????? ?????? ??????????????????."},"hi":{"lang_label":"????","site_nav_ownModel":"????? ?????","site_footer_tagline":"????-?? ????? ????? ?????????? ?????????? · ?????????, ?????","join_consent":"???? KhelSutra ?????? ?? ????? ?? ????? ?????? ?? ?????","join_note":"?? ????? ?????? ?? ?????????? ????? ?????; ?????????? ?? ????? ?????? ?? ?????????? ?? ?? ?????? ?????? ?? ??? ??? ?????? ?????? ?????? ????????? ????? ??????","ownModel_train_minorsBody":"????????? ?????? ?????? ?? ?????? ?????????? ?? ??? ??? ?????? ?????? ?? ??? ?? ?????????? ?????? ?????? ??????"},"es":{"lang_label":"Idioma","site_nav_ownModel":"Tu propio modelo","site_footer_tagline":"Jugadas destacadas automáticas de bádminton · Bengaluru, India","join_consent":"Acepto recibir correos sobre el alfa de KhelSutra.,"join_note":"Nunca publicamos tus grabaciones; las grabaciones en las que aparecen menores nunca se usan para mejorar la herramienta. Consulta nuestra Política de privacidad."},"ownModel_train_minorsBody":"Las grabaciones que involucran a menores nunca se usan para entrenar y nunca se publican."},"da":{"lang_label":"Sprog","site_nav_ownModel":"Din egen model","site_footer_tagline":"Automatiske badminton-highlights · Bengaluru, Indien","join_consent":"Du må gerne kontakte mig på e-mail om KhelSutra-alfaen.,"join_note":"Vi offentliggør aldrig dine optagelser; optagelser, der involverer mindreårige, bruges aldrig til at forbedre værktøjet. Se vores Privatlivspolitik."},"ownModel_train_minorsBody":"Optagelser, der involverer mindreårige, bruges aldrig til træning og offentliggøres aldrig."},"id":{"lang_label":"Bahasa","site_nav_ownModel":"Miliki modelmu sendiri","site_footer_tagline":"Sorotan bulu tangkis otomatis · Bengaluru, India","join_consent":"Boleh kirim email ke saya tentang alfa KhelSutra.,"join_note":"Kami tidak pernah mempublikasikan rekamanmu; rekaman yang melibatkan anak di bawah umur tidak pernah digunakan untuk meningkatkan alat ini. Lihat Kebijakan Privasi kami."},"ownModel_train_minorsBody":"Rekaman yang melibatkan anak di bawah umur tidak pernah digunakan untuk pelatihan dan tidak pernah dipublikasikan."}}}

521. assistant (2026-06-22T17:07:05.990Z)

Payload ready (63 keys; refs carry the established register + consistent per-locale Bengaluru/India). Let me launch the translation workflow ? legal-text-tuned (faithfulness, no weakening of "never/only/explicit opt-in"), HTML-preserving, proper-noun-consistent.

522. user (2026-06-22T17:08:25.506Z)

Workflow launched in background. Task ID: wujigcyco

Summary: AI-draft + adversarially verify the Privacy Policy page (site.privacy.*) in kn/hi/es/da/id

Transcript dir: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_958703a6-b21

Script file: C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-privacy-

wf_958703a6-b21.js

(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath:

"C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-

khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-privacy-

wf_958703a6-b21.js"} to iterate without resending the script.)

Run ID: wf_958703a6-b21

To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-privacy-wf_958703a6-b21.js", resumeFromRunId: "wf_958703a6-b21"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

523. assistant (2026-06-22T17:08:33.735Z)

Workflow running (legal text, 63 keys x5). While it translates, let me write the apply script and extend the tests (drift coverage for privacy, content test, server N8, wiring assertion).

524. assistant (2026-06-22T17:08:39.637Z)

```
// One-off helper (NOT shipped): merge the privacy translations (_priv.json) into
kn/hi/es/da/id.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const EXPECTED = Object.keys(JSON.parse(readFileSync(join(ROOT, "site", "scripts",
"_privpayload.json"), "utf8")).enTargets);
const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_priv.json"), "utf8"));
const setDeep = (root, dotted, v) => { const p = dotted.split("."); let o = root; for (let i =
0; i < p.length - 1; i++) o = o[p[i]] = o[p[i]] || {}; o[p[p.length - 1]] = v; };
let bad = 0;
for (const loc of ["kn", "hi", "es", "da", "id"]) {
  const f = T[loc];
  if (!f) { console.error(`MISSING ${loc}`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in f));
  if (missing.length) { console.error(`${loc} MISSING:`, missing.join(", ")); bad++; }
  const cat = load(loc);
  for (const k of EXPECTED) if (k in f) setDeep(cat, k, f[k]);
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: applied ${EXPECTED.filter((k) => k in f).length}/${EXPECTED.length}`);
}
if (bad) process.exit(1);
console.log("OK");
```

525. user (2026-06-22T17:08:39.659Z)

File created successfully at: C:\Users\avidu\Projects\ks-privacy\site\scripts_applypriv.mjs
(file state is current in your context ? no need to Read it back)

526. assistant (2026-06-22T17:08:46.225Z)

Now let me extend the byte-for-byte drift guard to cover privacy.html. Let me find it.

527. user (2026-06-22T17:08:47.693Z)

```

189: for (const f of ["index.html", "capture.html", "own-model.html", "privacy.html"]) {
217:const I18N_PAGES = ["index.html", "capture.html", "own-model.html"];
272: for (const f of ["index.html", "capture.html", "own-model.html"]) {
314: for (const f of ["index.html", "capture.html", "own-model.html"]) {
327: assert.ok(checked >= 60, `expected to check the full localized surface, only saw
${checked}`);
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

528. assistant (2026-06-22T17:08:58.354Z)

Line 189 already lists privacy.html (from #96). Let me read the key page-list regions to extend the drift guard + the B3 shim/switcher checks to privacy.

529. user (2026-06-22T17:08:59.142Z)

```

183     test("no dead web-analytics beacon ships (analytics is via Cloudflare Automatic Setup,
not an in-page token)", () => {
184         // The site previously shipped a manual Cloudflare beacon with the PLACEHOLDER token
185         // REPLACE_WITH_CF_TOKEN ? it loaded but collected nothing, and only covered the
homepage. We moved to
186         // Cloudflare Web Analytics "Automatic Setup" (edge-injected, no in-source token),
which covers every
187         // page. Guard against the dead snippet / placeholder token creeping back in. (If you
ever deliberately
188         // switch to a manual real-token beacon, update this test on purpose.)
189         for (const f of ["index.html", "capture.html", "own-model.html", "privacy.html"]) {
190             const html = read(f);
191             assert.doesNotMatch(html, /REPLACE_WITH_CF_TOKEN/, `${f} still ships the placeholder
analytics token`);
192             assert.doesNotMatch(html, /static\.cloudflareinsights\.com/, `${f} ships a manual CF
beacon ? analytics is via Automatic Setup (edge-injected), so no in-page beacon belongs here`);
193         }
194     });
195
196     test("the Privacy Policy page exists, covers the load-bearing disclosures, and is linked
for trust", () => {
197         const html = read("index.html");
198         // Linked from the footer AND from the sign-up form (where a visitor decides whether
to share data).
199         assert.match(html, /href="\//privacy"/, "the footer Privacy link is gone");
200         const formNote = html.match(/We never publish your footage; footage involving
minors[\s\S]*?<\p>/);
201         assert.ok(formNote, "the request-access privacy note is gone");
202         assert.match(formNote[0], /href="\//privacy"/, "the form's privacy note should link to
the Privacy Policy");
203
204         const pp = read("privacy.html");
205         assert.match(pp, /<html lang="en"/i, "privacy.html should be lang=en");
206         assert.match(pp, /Privacy Policy/i, "privacy.html lost its title content");
207         assert.match(pp, /<a [^>]*href="\//[^>]*>(?:.|\\n)*?Back to KhelSutra/i, "privacy needs
an obvious back-to-home link");
208         // The honest disclosures that make it a real policy, not a placeholder.
209         for (const claim of [/Gemini/i, /never publish/i, /minors/i, /opt-in/i, /HTTPS/i,
/hello@khelsutra.guru/]) {
210             assert.match(pp, claim, `privacy.html is missing a load-bearing disclosure:
${claim}`);
211         }
212         // It must NOT silently claim things the site doesn't do (no ad-tracking / data-
selling promises reversed).
213         assert.match(pp, /do\s*<b>not<\b>\s*sell|not[, ]+rent[, ]+or trade/i, "privacy should
state we don't sell personal data");
214     });
215
216     // ---- B3: the trilingual marketing surface (shared t()/data-i18n shim + persistent
switcher) -----

```

```

217     const I18N_PAGES = ["index.html", "capture.html", "own-model.html"];
218
219     test("every localizable page loads the shared i18n shim", () => {
220         for (const f of I18N_PAGES) {
221             assert.match(read(f), /<script[^\>]+type="module"[^\>]+src="\/i18n\.js"/, `${f}
doesn't load the i18n shim (/i18n.js)`);
222         }
223     });
224
225     test("every localizable page has a persistent, compact 6-language <select> switcher", ()
=> {
226         for (const f of I18N_PAGES) {
227             const html = read(f);

```

530. assistant (2026-06-22T17:09:15.219Z)

The privacy page already has a `#96` content test (and my wiring preserved all English defaults, so it still passes). Let me extend the B3 page list and the byte-for-byte drift guard to include privacy. Let me read the drift test region.

531. user (2026-06-22T17:09:16.119Z)

```

307
308     test("A3: EVERY data-i18n[-html] HTML default matches the en catalog byte-for-byte (no
drift, incl. rich <b> keys)", () => {
309         // The rich (data-i18n-html) keys are the most drift-prone: the inline <b> markup must
match the
310         // catalog exactly, or an en visitor's no-JS default and the shim's en render silently
diverge.
311         // Parse the REAL pages in jsdom and compare each tagged element's default to
enCatalog.
312         const dig = (o, k) => k.split(".").reduce((a, c) => (a == null ? a : a[c]), o);
313         let checked = 0;
314         for (const f of ["index.html", "capture.html", "own-model.html"]) {
315             const { document } = new JSDOM(read(f)).window;
316             for (const el of document.querySelectorAll("[data-i18n], [data-i18n-html]")) {
317                 if (el.getAttribute("data-i18n-attr")) continue; // attribute defaults aren't the
visible text
318                 const htmlKey = el.getAttribute("data-i18n-html");
319                 const key = htmlKey || el.getAttribute("data-i18n");
320                 const enVal = dig(enCatalog, key);
321                 assert.notEqual(enVal, undefined, `${f}: data-i18n key "${key}" missing from en
catalog`);
322                 const got = (htmlKey ? el.innerHTML : el.textContent).trim();
323                 assert.equal(got, enVal, `${f}: "${key}" HTML default drifted from the en
catalog`);
324                 checked++;
325             }
326         }
327         assert.ok(checked >= 60, `expected to check the full localized surface, only saw
${checked}`);
328     });

```

532. user (2026-06-22T17:09:22.376Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

533. user (2026-06-22T17:09:28.441Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

534. assistant (2026-06-22T17:09:40.961Z)

Let me run the assets suite to confirm the privacy wiring passes the drift guard + B3 checks (en-seed state).

535. user (2026-06-22T17:09:44.214Z)

```
? tests 31
? pass 31
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

536. assistant (2026-06-22T17:09:53.647Z)

All 31 assets tests pass (drift guard now covers privacy at `checked >= 120`). Let me add privacy to the Noto-font test and add a server N8 negotiation test for `/privacy`.

537. user (2026-06-22T17:09:54.573Z)

```
269
270    // ---- A3: recording-education localized + Noto fonts bundled for kn/hi rendering
-----
271    test("A3: every marketing page bundles Noto Kannada + Devanagari so kn/hi render (not
tofu)", () => {
272        for (const f of ["index.html", "capture.html", "own-model.html"]) {
273            const html = read(f);
274            assert.match(html, /Noto\+Sans\+Kannada/, `${f} doesn't load Noto Sans Kannada`);
275            assert.match(html, /Noto\+Sans\+Devanagari/, `${f} doesn't load Noto Sans
Devanagari`);
276            assert.match(html, /--font:[^;]*'Noto Sans Kannada'[^;]*'Noto Sans Devanagari'\/,
`${f} font stack must fall back to Noto for Indic glyphs`);
277            // Order matters: the Latin display font leads, then the Noto Indic families, BEFORE
the generic
278            // fallbacks ? else a system UI font with partial Indic glyphs could win and defeat
the bundle.
279            const stack = html.match(/--font:([^;]*)/)[1];
280            assert.ok(stack.indexOf("Noto Sans Kannada") < stack.indexOf("system-ui"), `${f}:
Noto Kannada must precede system-ui`);
281            assert.ok(stack.indexOf("Noto Sans Devanagari") < stack.indexOf("system-ui"),
`${f}: Noto Devanagari must precede system-ui`);
282            assert.ok(stack.indexOf("Plus Jakarta Sans") < stack.indexOf("Noto Sans
Kannada"), `${f}: the Latin display font must lead the stack`);
283        }
284    });
```

538. user (2026-06-22T17:09:55.557Z)

```
65:test("[VM host] serves /own-model", async () => {
66:    const res = await fetch(`${base}/own-model`);
129:test("[VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page",
async () => {
133:    assert.equal(res.headers.get("content-language"), "kn");
140:test("[VM host · N8] ?lang= overrides the browser language", async () => {
145:test("[VM host · N8] the persisted cookie beats Accept-Language (returning user keeps their
choice)", async () => {
150:test("[VM host · N8] unsupported/absent language falls back to en (never a locale we can't
serve)", async () => {
153:    const none = await fetch(`${base}/own-model`);
157:test("[VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages
negotiate)", async () => {
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

539. assistant (2026-06-22T17:10:04.323Z)

Let me read the server N8 region to add a `/privacy` negotiation test and fix the now-stale "3 pages" comment.

540. user (2026-06-22T17:10:05.351Z)

```
129     test("[VM host · N8] a Kannada browser (Accept-Language: kn) gets the kn-rendered page",
async () => {
130         const res = await fetch(`${base}/`, { headers: { "accept-language": "kn-
IN,kn;q=0.9,en;q=0.5" } });
131         const html = await res.text();
132         assert.match(html, /<html lang="kn"/, "a kn browser must auto-get <html
lang=\"kn\">");
133         assert.equal(res.headers.get("content-language"), "kn");
134         assert.match(res.headers.get("vary") || "", /accept-language/i, "must Vary on Accept-
Language for caches");
135         // The negotiated page still ships the client shim + switcher so the browser can
refine from here.
136         assert.match(html, /src=\"\/i18n\.js"/, "the negotiated page must still load the client
shim");
137         assert.match(html, /<select data-langsw|<option value="kn"/, "the switcher must be
present on the negotiated page");
138     });
139
140     test("[VM host · N8] ?lang= overrides the browser language", async () => {
141         const res = await fetch(`${base}/?lang=hi`, { headers: { "accept-language": "en-US" }
});
142         assert.match(await res.text(), /<html lang="hi"/, "?lang=hi must win over an en
Accept-Language");
143     });
144
145     test("[VM host · N8] the persisted cookie beats Accept-Language (returning user keeps
their choice)", async () => {
146         const res = await fetch(`${base}/capture`, { headers: { "accept-language": "kn",
cookie: "kheIsutra.lang=hi" } });
147         assert.match(await res.text(), /<html lang="hi"/, "the persisted-pref cookie must win
over Accept-Language");
148     });
149
150     test("[VM host · N8] unsupported/absent language falls back to en (never a locale we
can't serve)", async () => {
151         const ta = await fetch(`${base}/?lang=ta`, { headers: { "accept-language": "ta-IN" }
});
152         assert.match(await ta.text(), /<html lang="en"/, "Tamil (unsupported) must fall back
to en");
153         const none = await fetch(`${base}/own-model`);
154         assert.match(await none.text(), /<html lang="en"/, "no signal -> en default");
155     });
156
157     test("[VM host · N8] non-localized assets are NOT rewritten (only the 3 marketing pages
negotiate)", async () => {
158         // The flyers are fixed-language pages ? negotiation must not touch them.
159         const res = await fetch(`${base}/flyer-kn`, { headers: { "accept-language": "hi" } });
160         assert.match(await res.text(), /<html lang="kn"/, "the Kannada flyer must stay kn
regardless of Accept-Language");
161     });
162
163     test("[VM host] serves the shared catalogs the shim fetches (/locales/*/common.json as
JSON)", async () => {
```

541. assistant (2026-06-22T17:10:16.288Z)

Let me add the `/privacy` negotiation test, update the stale "3 pages" comment, and add privacy to the Noto-font guard.

542. user (2026-06-22T17:10:20.054Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\server.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

543. user (2026-06-22T17:10:21.942Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\server.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

544. user (2026-06-22T17:10:23.994Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

545. assistant (2026-06-22T17:10:31.735Z)

Now the privacy content test in `i18n.shim.test.js`. Let me find the anchor (after the proper-noun consistency test I added in #105).

546. user (2026-06-22T17:10:36.336Z)

```
322:test("proper-noun consistency: kn/hi render city/country names in-script, never mixing the
Latin form", () => {
337:// fitNav's REAL geometry (which locale collapses at which width) is exercised end-to-end by
the
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

547. user (2026-06-22T17:10:40.978Z)

```
322    test("proper-noun consistency: kn/hi render city/country names in-script, never mixing
the Latin form", () => {
323        const PLACES = [
324            { latin: /\bBengaluru\b/, translit: { kn: /???????, hi: /???????, } },
325            { latin: /\bIndia\b/, translit: { kn: /????/, hi: /????/ } },
326        ];
327        for (const loc of ["kn", "hi"]) {
328            const entries = Object.entries(flatOwn(catalogs[loc].site));
329            for (const { latin, translit } of PLACES) {
330                if (!entries.some(([v]) => translit[loc].test(v))) continue; // not used in this
locale ? nothing to enforce
331                const latinHits = entries.filter(([v]) => latin.test(v)).map(([k]) => k);
332                assert.deepEqual(latinHits, [], `${loc} mixes the Latin spelling with the
transliterated place name in: site.${latinHits.join(", site.")}`);
333            }
334        }
335    });
336
```

548. assistant (2026-06-22T17:11:11.173Z)

The proper-noun consistency test already auto-covers privacy (it scans all of `site.\*`). Let me add a privacy-specific content test (in-script/translated + markup/brand/link integrity), inserted before the fitNav tests.

549. user (2026-06-22T17:11:23.101Z)

The file C:\Users\avidu\Projects\ks-privacy\site\src\i18n.shim.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

550. assistant (2026-06-22T17:11:28.844Z)

Tests staged (they'll pass once translations land). Let me check the privacy translation workflow's progress.

551. user (2026-06-22T17:11:32.264Z)

still running; agents:

?????,"site.privacy.collect.li2":"???? ???? ???? ???? ???? ????
???????? ? ?????????? ???? ???? ???? ???? ???? ???? ???? ????
?????????,"site.privacy.collect.li3":"????? ???? ? ??????
???? ???? ? ? ???? ???? ???? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
???????? ???? ????-???? ???? (Cloudflare)
?????????????????,"site.privacy.collect.note":"???? ???? ???? ????
????????;, ???? ???? ???? ???? ????-???? ????
???????????? ????,"site.privacy.use.h":"2. ???? ????
?????????,"site.privacy.use.li1":"???? ???? ???? ?
???? ???? ???? ???? ???? ???? ????
?????,"site.privacy.use.li2":"???? ? ???? ????
????, ???? ???? ???? ???? ???? ???? ????
?????,"site.privacy.use.li3":"???? ???? ???? ????
???? ???? (??? ???? ???? ???? ????
?????????),"site.privacy.use.note":"???? ???? ????
???? ???? ????. ????, ????
????-???? (????-??) ???? ???? ???? ????
???? ???? ???? ???? ???? ? ???? ??
???????? ????,"site.privacy.video.h":"3. ???? ????
???? ???? ????,"site.privacy.video.intro":"???? ????
???? ???? ???? ???? ???? ???? ???? ????
???? ????,"site.privacy.video.li1":"???? ???? ????
???? ???? ????,"site.privacy.video.li2":"????
???? ????????-???? AI ????
 (????, Google ? Gemini API) ???? ????
???? ????,"site.privacy.video.li3":"????
????, ???? ????
????,"site.privacy.video.li4":"????-???? (????-??)
???? ???? ???? ???? ???? ???? ???? (??
????)."site.privacy.video.boxTitle":"???? ????
?????:"site.privacy.video.boxBody":"???? ???? ????
???? ???? ???? ???? ???? ???? ???? ????
???? ???? ???? ???? ????-???? AI ????
????,"site.privacy.sharing.h":"4. ???? ????
????,"site.privacy.sharing.intro":"???? ????
???? ???? ????
????,"site.privacy.sharing.li1":"Cloudflare ?
???? ???? ???? ???? ???? ???? ????
????,"site.privacy.sharing.li2":"Google (Gemini API) ?
???? ???? ????
,"site.privacy.sharing.li3":"???? ?
???? ???? ???? ????,"site.privacy.sharing.note":"? ????
???? ???? ???? ???? ???? ???? ????
,"site.privacy.cookies.h":"5. ????
,"site.privacy.cookies.intro":"???? ??
,"site.privacy.cookies.li1":"???? ???? ????
???? ???????? ????
???? ???? ???? ????,"site.privacy.cookies.li2":"????
?? ???? ???? ???? ????-???? ???? (Cloudflare Web
Analytics) ???? ???? ???? ???? ???? ????
,"site.privacy.retention.h":"6. ???? ??
,"site.privacy.retention.body":"???? ???? ???? ????
?? ???? ???? ???? ???? ???? ???? ????
... (truncated 36422 chars, full result in C:\Users\avidu\AppData\Local\Temp\claude\C--Users-
avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\wujigcyco.output)</result>
<usage><agent_count>25</agent_count><subagent_tokens>1346504</subagent_tokens><tool_uses>139</to
</task-notification>

554. assistant (2026-06-22T17:19:37.010Z)

Privacy translations done ? all 5 locales, legal terms + brands (Cloudflare/Gemini API) + the
mailto link + emphatic "never/only/opt-in" preserved. Let me extract, integrity-check, and
apply.

555. user (2026-06-22T17:19:46.617Z)

? hi site.privacy.use.note: tag drift en=[|||||] got=[|||]

1 integrity problems

fixed: kn=5 hi=4 es=3 da=5 id=6

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

556. assistant (2026-06-22T17:19:58.713Z)

One markup defect: hi `use.note` dropped a `**` pair (3 in en, 2 in hi). Let me inspect and fix it precisely.**

557. user (2026-06-22T17:20:00.756Z)

EN use.note:

We do **not** sell, rent, or trade your personal data. We do **not** use your footage to train or improve our models **unless** you give us clear, explicit, opt-in permission ? and even then, never footage involving minors.

HI use.note:

?? ???? ?????????? ???? ? ?? ?????? ???, ? ?????? ?? ?????? ??, ?? ? ?? ?????? ???-??? ?????? ??
???? ?????? ?? ?????? ?????? ?? ?????? ?????? ?? ?????? ?????? ?? ??? **??** ?? ????? ????? **??**
?? ?? ?????? ?????, ??????, ?????-?? ?????? ? ??? ? ?? ?? ??, ?????????? ?? ?????? ?????? ?? ???
?????

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

558. assistant (2026-06-22T17:20:26.798Z)

The hi translation is semantically faithful but dropped one `**` (bolded the negation differently). Let me restore the third emphasis to match en's tag-set, then re-verify and apply.**

559. user (2026-06-22T17:20:32.623Z)

TAG-PARITY OK across all rich keys, all 5 locales

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

560. assistant (2026-06-22T17:20:38.337Z)

Tag-parity clean across all 5. Let me apply, mirror, and run the site suite.

561. user (2026-06-22T17:20:42.687Z)

kn: applied 63/63

hi: applied 63/63

es: applied 63/63

da: applied 63/63

id: applied 63/63

OK

copy-locales: da, en, es, hi, id, kn -> site/public/locales/

=== SITE unit (incl. privacy content + drift guard) ===

? tests 94

? pass 94

? fail 0

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

562. assistant (2026-06-22T17:20:48.466Z)

Site unit 94 green. Now the browser guards (render + layout now include privacy) and the web suite:

563. user (2026-06-22T17:21:40.078Z)

```
=== RENDER (now 4 pages x 6 locales = 24 combos) ===
? every localized page renders each locale correctly (DOM == catalog, no raw keys, right lang,
no errors) (13272.3773ms)
? pass 1
? fail 0
=== LAYOUT (incl. privacy header) ===
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(22427.8143ms)
? a locale that fits keeps its nav links (auto-collapse doesn't over-fire) ? index.html [en]
(749.2988ms)
? footer + #join form never overflow horizontally (index.html x 6 locales x phone widths)
(2417.6131ms)
? pass 3
? fail 0
=== WEB ===
  Test Files   24 passed (24)
    Tests     226 passed (226)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

564. assistant (2026-06-22T17:21:49.961Z)

All browser guards green (render now 24 combos incl. privacy; layout incl. privacy header) + web 226. Let me eyeball the rendered privacy page (kn glyphs) and run the web CI gates. Starting the server:

565. user (2026-06-22T17:21:50.921Z)

Command running in background with ID: b1kufkum0. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\b1kufkum0.output. You will be notified when it completes. To check interim output, use Read on that file path.

566. user (2026-06-22T17:22:06.120Z)

```
kn h1: "??????? ?????" errs: 0
es h1: "Política de privacidad" errs: 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

567. assistant (2026-06-22T17:22:11.799Z)

Let me eyeball the full Kannada privacy page.

568. assistant (2026-06-22T17:22:24.228Z)

The full Kannada privacy page renders cleanly ? hero, TOC, all 10 sections, the green note box, footer ? Noto glyphs, no tofu, no overflow, zero console errors. Now the web CI gates, then clean up and commit.

569. user (2026-06-22T17:22:41.315Z)

```
=== typecheck ===
OK
=== coverage ===
  Tests     226 passed (226)
All files   |  94.09 |  88.77 |  86.59 |  94.09 |
=== build ===
? built in 1.53s
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

570. assistant (2026-06-22T17:22:47.726Z)

All gates green (typecheck OK, coverage 94.09%, build OK). Let me stop the server, clean helpers, and review the diff.

571. user (2026-06-22T17:22:53.066Z)

```
=== git status ===
M locales/da/common.json
M locales/en/common.json
M locales/es/common.json
M locales/hi/common.json
M locales/id/common.json
M locales/kn/common.json
M site/public/locales/da/common.json
M site/public/locales/en/common.json
M site/public/locales/es/common.json
M site/public/locales/hi/common.json
M site/public/locales/id/common.json
M site/public/locales/kn/common.json
M site/public/privacy.html
M site/server.js
M site/src/assets.test.js
M site/src/i18n.shim.test.js
M site/src/layout.browser.mjs
M site/src/render.browser.mjs
M site/src/server.test.js
=== base check ===
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

572. assistant (2026-06-22T17:23:00.862Z)

Clean tree ? exactly the 19 expected files, clean base. Let me commit P1.1.

573. user (2026-06-22T17:23:15.141Z)

```
staged: 19
=== rebase onto latest origin/master (in case a sibling landed) ===
Current branch feat/localize-privacy is up to date.
45be2c0 feat(site): localize the Privacy Policy page (6 languages) ? P1
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

574. assistant (2026-06-22T17:23:19.609Z)

Committed (45be2c0), branch carries only my commit. Let me push and open the PR.

575. user (2026-06-22T17:23:36.897Z)

```
branch 'feat/localize-privacy' set up to track 'origin/feat/localize-privacy'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      feat/localize-privacy -> feat/localize-privacy
https://github.com/avidullu/khelsutra/pull/106
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

576. assistant (2026-06-22T17:23:43.104Z)

PR [#106](https://github.com/avidullu/khelsutra/pull/106) opened. Let me watch CI and merge on green.

577. user (2026-06-22T17:24:47.371Z)

```
site    pass    18s
https://github.com/avidullu/khelsutra/actions/runs/27971159975/job/82777426423
web     pass    43s
https://github.com/avidullu/khelsutra/actions/runs/27971159975/job/82777426377
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/6fb83184-61b1-4150-b179-95c2800602c1
layout  pass    1m1s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27971159975/job/82777426332
site    pass    18s
https://github.com/avidullu/khelsutra/actions/runs/27971159975/job/82777426423
web     pass    43s
https://github.com/avidullu/khelsutra/actions/runs/27971159975/job/82777426377
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

578. assistant (2026-06-22T17:24:52.538Z)

All green (site + web + layout/render + Cloudflare). Let me verify and squash-merge.

579. user (2026-06-22T17:24:59.862Z)

```
only my commit?
45be2c0 feat(site): localize the Privacy Policy page (6 languages) ? P1
{"merge":"6ee1f8152309b60322fffd0a42ec2d35c46beed2","state":"MERGED"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

580. assistant (2026-06-22T17:25:43.875Z)

****P1.1 merged**** ([#106](https://github.com/avidullu/khelsutra/pull/106), squash `6ee1f81`) ? the Privacy Policy is now localized in all 6 languages. Let me clean up and move to P2.

581. user (2026-06-22T17:25:52.319Z)

```
- [deleted]          feat/localize-privacy
C:/Users/avidu/Projects/khelsutra fbd7fdd [master]
```

582. assistant (2026-06-22T17:26:50.706Z)

****P1 done**** (the Privacy page is localized + merged). Now ****P2****. Let me be upfront about one item: ****P2.4** (a localized explainer **video**) ****is content production I can't do in code ? and the capture page already teaches recording in all 6 languages with the A7 diagram. I'll build the two code-feasible P2 items (**P2.3** per-locale ``<title>`/meta + **P2.5** accessibility audit/fixes)`** as one "P2 polish" PR, and recommend P2.4's video be backlogged (or done as a separate content task). Flag me if you'd rather I build an animated SVG walkthrough instead.

Let me set up the P2 worktree off the latest head and start with an accessibility audit + the metadata wiring.

583. user (2026-06-22T17:26:56.539Z)

```
origin/master:
6ee1f81 feat(site): localize the Privacy Policy page (6 languages) ? P1 (#106)
fbd7fdd feat(site): finish access-form + footer localization (6 langs) + cross-locale render guard (#105)
branch 'feat/site-meta-a11y' set up to track 'origin/master'.
HEAD is now at 6ee1f81 feat(site): localize the Privacy Policy page (6 languages) ? P1 (#106)
base:
=== current <title>/meta description across marketing pages (origin/master) ===
--- index ---
6:<title>KhelSutra ? every rally indexed, the dead time gone</title>
7:<meta name="description" content="KhelSutra turns a full badminton match into a clean index of rallies with the dead time stripped out ? a highlight reel you can watch and download. Invite-only alpha, Bengaluru." />
--- capture ---
6:<title>KhelSutra ? 1-page capture checklist</title>
7:<meta name="description" content="How to record a badminton session so KhelSutra gives you great highlight reels: camera placement, settings, stability, lighting." />
--- own-model ---
6:<title>KhelSutra ? Annotate your footage & train your own model</title>
7:<meta name="description" content="With KhelSutra you can annotate your own footage and grow a rally model that's YOURS ? on an open, MIT-licensed stack you control. The free VLC rally-
```



```

annotator turns 'watch a match' into golden labels." />
--- privacy ---
6:<title>Privacy Policy ? KhelSutra</title>
7:<meta name="description" content="How KhelSutra handles your information and your match
videos: what we collect, how it's used, who processes it, and your choices. Invite-only alpha,
Bengaluru." />

```

584. assistant (2026-06-22T17:27:46.437Z)

P2 worktree ready (off #106). Each page has an English ``<title>`` + meta description. For **P2.5** I'll run a real accessibility audit (axe-core) to find concrete WCAG issues before deciding fixes. Let me copy node_modules and set up an axe scan.

585. user (2026-06-22T17:27:50.649Z)

Command running in background with ID: bxc2n4g4x. Output is being written to: C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bxc2n4g4x.output. You will be notified when it completes. To check interim output, use Read on that file path.

586. assistant (2026-06-22T17:28:08.760Z)

While axe installs, let me write the a11y scan (reusing the browser-guard server pattern):

587. assistant (2026-06-22T17:28:24.487Z)

```

// Accessibility regression guard (separate `npm run test:a11y` ? needs a real browser, like the
layout
// + render guards). Runs axe-core (WCAG 2.1 A/AA) over every localized page in representative
locales
// (en = Latin, kn = Kannada, hi = Devanagari) and FAILS on any serious/critical violation.
jsdom has no
// layout/contrast engine, so this is the only automated a11y net. It complements the manual
review.
import { test, before, after } from "node:test";
import assert from "node:assert/strict";
import { createServer } from "node:http";
import { readFile } from "node:fs/promises";
import { join, extname } from "node:path";
import { chromium } from "playwright";

const PUBLIC = join(import.meta.dirname, "..", "public");
const AXE = join(import.meta.dirname, "..", "node_modules", "axe-core", "axe.min.js");
const TYPES = {
  ".html": "text/html; charset=utf-8", ".js": "text/javascript", ".mjs": "text/javascript",
  ".json": "application/json; charset=utf-8", ".css": "text/css", ".png": "image/png", ".jpg":
"image/jpeg",
  ".svg": "image/svg+xml", ".webp": "image/webp", ".webm": "video/webm", ".mp4": "video/mp4",
  ".woff2": "font/woff2", ".woff": "font/woff", ".ico": "image/x-icon",
};

let server, browser, baseUrl, axeSrc;

before(async () => {
  axeSrc = await readFile(AXE, "utf8");
  server = createServer(async (req, res) => {
    try {
      let p = decodeURIComponent(req.url.split("?")[0]);
      if (p === "/") p = "/index.html";
      let data, ext = extname(p);
      try { data = await readFile(join(PUBLIC, p)); }
      catch { try { data = await readFile(join(PUBLIC, p + ".html")); } catch {
res.writeHead(404); return res.end("not found"); } }
      res.writeHead(200, { "content-type": TYPES[ext] || "application/octet-stream", "cache-
control": "no-store" });

```



```

? pass 0
? fail 1
? cancelled 0
? skipped 0
? todo 0
? duration_ms 10434.6702
? failing tests:
test at src\ai1y.browser.mjs:44:1
? axe-core WCAG 2.1 A/AA ? no serious/critical violations on any localized page × locale
(10003.2257ms)
  AssertionError [ERR_ASSERTION]: axe serious/critical violations:
    - /index.html [en]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×19 e.g. .match
    - /index.html [en]: serious ? link-in-text-block (Links must be distinguishable without
relying on color) ×3 e.g. a[hreflang="en"]
    - /index.html [kn]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×19 e.g. .match
    - /index.html [kn]: serious ? link-in-text-block (Links must be distinguishable without
relying on color) ×3 e.g. a[hreflang="en"]
    - /index.html [hi]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×19 e.g. .match
    - /index.html [hi]: serious ? link-in-text-block (Links must be distinguishable without
relying on color) ×3 e.g. a[hreflang="en"]
    - /privacy.html [en]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×17 e.g. .lead > a[href="mailto:hello@khelsutra.guru"]
    - /privacy.html [kn]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×17 e.g. .lead > a[href="mailto:hello@khelsutra.guru"]
    - /privacy.html [hi]: serious ? color-contrast (Elements must meet minimum color contrast
ratio thresholds) ×17 e.g. .lead > a[href="mailto:hello@khelsutra.guru"]
    9 !== 0
      at TestContext.<anonymous>
(file:///C:/Users/avidu/Projects/ks-p2/site/src/ai1y.browser.mjs:66:10)
      at async Test.run (node:internal/test_runner/test:1313:7)
      at async startSubtestAfterBootstrap (node:internal/test_runner/harness:385:3) {
    generatedMessage: false,
    code: 'ERR_ASSERTION',
    actual: 9,
    expected: 0,
    operator: 'strictEqual',
    diff: 'simple'
  }
}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

591. assistant (2026-06-22T17:29:10.528Z)

The audit found real WCAG AA issues ? ****color-contrast**** (index ×19, privacy ×17) and ****link-in-text-block**** (footer links distinguished only by color). capture/own-model are clean. Let me get the exact colors/elements to make minimal, correct fixes.

592. user (2026-06-22T17:29:22.012Z)

```

=== /index.html ===
  ×1 color-contrast | fg=#149a5c bg=#ffffff ratio=3.61/4.5:1
  ×15 color-contrast | fg=#149a5c bg=#f6f8f4 ratio=3.38/4.5:1
  ×3 color-contrast | fg=#149a5c bg=#eff4ec ratio=3.24/4.5:1

=== /privacy.html ===
  ×6 color-contrast | fg=#149a5c bg=#f6f8f4 ratio=3.38/4.5:1
  ×11 color-contrast | fg=#149a5c bg=#ffffff ratio=3.61/4.5:1
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

593. assistant (2026-06-22T17:30:26.036Z)

All contrast failures share one root cause: `--green-d: #149A5C` (3.2?3.6:1 on light`

backgrounds). own-model/capture use `#137a4c` (~5:1) and were clean ? so unifying index+privacy to `#137a4c` fixes every contrast violation. Plus the footer links need an underline (distinguishable without color). Let me locate the exact CSS.

594. user (2026-06-22T17:30:28.037Z)

```
=== --green-d in each page ===
index: --green-d:#149A5C
capture: --green-d:#137a4c
own-model: --green-d:#137a4c
privacy: --green-d:#149A5C
=== index footer link CSS ===
212: .foot a{color:var(--green-d);text-decoration:none}
213: .foot a:hover{text-decoration:underline}
=== privacy footer link CSS ===
38: .back{font-size:.9rem;font-weight:600;text-decoration:none;color:var(--mut)}
39: .back:hover{color:var(--tx)}
47: @media (max-width:480px){ .back{display:none} }
74: .foot a{text-decoration:none}
75: .foot a:hover{text-decoration:underline}
95: <a class="back" href="/" data-i18n="site.privacy.back">? Back to KhelSutra</a>
Shell cwd was reset to C:\Users\avidu\Projects\kheIsutra
```

595. assistant (2026-06-22T17:31:00.747Z)

Confirmed: index + privacy use `#149A5C`; capture/own-model use `#137a4c` (clean). Fix = unify to `#137a4c` + underline footer links. Let me read the exact CSS lines in both pages.

596. user (2026-06-22T17:31:03.072Z)

```
=== index --green-d line ===
26: --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
=== privacy --green-d line ===
20: --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
--- exact strings ---
en:#19B36B; --green-d:#149A5C;
en:#19B36B; --green-d:#149A5C;
Shell cwd was reset to C:\Users\avidu\Projects\kheIsutra
```

597. user (2026-06-22T17:31:10.990Z)

```
26 --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
```

598. user (2026-06-22T17:31:11.854Z)

```
212 .foot a{color:var(--green-d);text-decoration:none}
213 .foot a:hover{text-decoration:underline}
```

599. user (2026-06-22T17:31:12.348Z)

```
20 --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#149A5C;
```

600. user (2026-06-22T17:31:13.111Z)

```
74 .foot a{text-decoration:none}
```

601. assistant (2026-06-22T17:31:17.414Z)

Now the fixes ? unify `--green-d` to the AA-compliant `#137a4c` and underline footer links in both pages:

602. user (2026-06-22T17:31:18.857Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\index.html has been updated successfully.
(file state is current in your context ? no need to Read it back)

603. user (2026-06-22T17:31:24.571Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\index.html has been updated successfully.
(file state is current in your context ? no need to Read it back)

604. user (2026-06-22T17:31:24.744Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\privacy.html has been updated successfully.
(file state is current in your context ? no need to Read it back)

605. user (2026-06-22T17:31:24.922Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\privacy.html has been updated successfully.
(file state is current in your context ? no need to Read it back)

606. assistant (2026-06-22T17:31:38.876Z)

Let me re-run the audit to confirm the fixes clear all serious/critical violations.

607. user (2026-06-22T17:31:50.698Z)

? axe-core WCAG 2.1 A/AA ? no serious/critical violations on any localized page × locale
(9542.6445ms)
? tests 1
? pass 1
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

608. assistant (2026-06-22T17:32:49.485Z)

****P2.5 done**** ? axe now reports ****0 serious/critical**** across all 4 pages × {en, kn, hi} after the fixes. The `a11y.browser.mjs` guard will stay as a CI net. Let me wire it into `package.json` + CI, then do ****P2.3**** (localized `` ? the user-visible browser-tab win; crawler-side OG needs server/CF, which I'll backlog).</p></div><div data-bbox="64 586 327 601" data-label="Section-Header"><p>609. user (2026-06-22T17:32:49.806Z)</p></div><div data-bbox="64 615 742 946" data-label="Text"><pre>1 {
2 "name": "khelsutra-site",
3 "private": true,
4 "type": "module",
5 "scripts": {
6 "test": "node --test",
7 "test:cf": "node --test src/index.test.js",
8 "test:vm": "node --test src/server.test.js",
9 "test:deploy": "node --test src/deploy-config.test.js src/assets.test.js",
10 "test:layout": "node --test src/layout.browser.mjs",
11 "test:render": "node --test src/render.browser.mjs",
12 "copy:locales": "node scripts/copy-locales.mjs",
13 "predeploy": "node scripts/copy-locales.mjs",
14 "deploy": "wrangler deploy",
15 "dev": "wrangler dev",
16 "og": "python make_og.py"
17 },
18 "devDependencies": {
19 "axe-core": "^4.12.1",
20 "jsdom": "^29.1.1",
21 "playwright": "^1.61.0"
22 }
23 }
24</pre></div>

610. user (2026-06-22T17:32:56.707Z)

The file C:\Users\avidu\Projects\ks-p2\site\package.json has been updated successfully. (file state is current in your context ? no need to Read it back)

611. user (2026-06-22T17:33:04.447Z)

```
66         cache-dependency-path: site/package-lock.json
67     - run: npm ci
68     - run: npx playwright install --with-deps chromium
69     - run: npm run test:layout
70     # Cross-locale render guard: drives the real pages in every locale and asserts the
live DOM
71     # matches the catalog (no raw keys / no shim regression / right lang / no console
errors).
72     - run: npm run test:render
73
```

612. user (2026-06-22T17:33:12.354Z)

The file C:\Users\avidu\Projects\ks-p2\.github\workflows\test.yml has been updated successfully. (file state is current in your context ? no need to Read it back)

613. assistant (2026-06-22T17:33:21.641Z)

Now P2.3 ? wire the 4 page titles. Let me read the capture/own-model title lines (index/privacy already read).

614. user (2026-06-22T17:33:22.620Z)

```
6     <title>KhelSutra ? 1-page capture checklist</title>
```

615. user (2026-06-22T17:33:23.338Z)

```
6     <title>KhelSutra ? Annotate your footage & train your own model</title>
```

616. user (2026-06-22T17:33:28.522Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

617. user (2026-06-22T17:33:29.935Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\capture.html has been updated successfully. (file state is current in your context ? no need to Read it back)

618. user (2026-06-22T17:33:31.823Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

619. user (2026-06-22T17:33:32.802Z)

The file C:\Users\avidu\Projects\ks-p2\site\public\privacy.html has been updated successfully. (file state is current in your context ? no need to Read it back)

620. assistant (2026-06-22T17:33:41.432Z)

Titles wired. Let me extract the en title keys byte-for-byte, seed all 6, and build the translation payload.

621. user (2026-06-22T17:33:51.163Z)

```
extracted: 4 meta titles
{
  "site.meta.index.title": "KhelSutra ? every rally indexed, the dead time gone",
  "site.meta.capture.title": "KhelSutra ? 1-page capture checklist",
  "site.meta.ownModel.title": "KhelSutra ? Annotate your footage & train your own model",
  "site.meta.privacy.title": "Privacy Policy ? KhelSutra"
}
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

622. assistant (2026-06-22T17:33:59.693Z)

4 titles seeded. Let me read the payload and run a quick translation workflow for them.

623. user (2026-06-22T17:34:00.310Z)

```
1      {"enTargets":{"site.meta.index.title":"KhelSutra ? every rally indexed, the dead time
gone","site.meta.capture.title":"KhelSutra ? 1-page capture
checklist","site.meta.ownModel.title":"KhelSutra ? Annotate your footage & train your own
model","site.meta.privacy.title":"Privacy Policy ? KhelSutra"},"ref":{"kn":{"app_title":"????
????????? ?????????? ?????","site_hero_title":"????? ?????????? ??????????. <span
class=\"hl\">????????? ???, ???.</span>","site_nav_ownModel":"????????
?????","site_privacy_title":"????????? ?????","site_capture_title":"1-???? ??????????
????????","hi":{"app_title":"???? ??? ?? ??? ?????????? ?????","site_hero_title":"??
????, ??? ????."
<span class=\"hl\">????? ???, ?????.</span>","site_nav_ownModel":"???? ????
?????","site_privacy_title":"????????? ?????","site_capture_title":"1-??? ??????
????????"},"es":{"app_title":"Elige las jugadas para tu reel","site_hero_title":"Cada jugada,
indexada. <span class=\"hl\">El tiempo muerto, fuera.</span>","site_nav_ownModel":"Tu propio
modelo","site_privacy_title":"Política de privacidad","site_capture_title":"Lista de captura de
1 página"},"da":{"app_title":"Vælg duellerne til din reel","site_hero_title":"Hver duel,
indekseret. <span class=\"hl\">Den døde tid, væk.</span>","site_nav_ownModel":"Din egen
model","site_privacy_title":"Privatlivspolitik","site_capture_title":"Optagelsestjekliste på 1
side"},"id":{"app_title":"Pilih reli untuk reel kamu","site_hero_title":"Setiap reli, terindeks.
<span class=\"hl\">Waktu kosongnya, hilang.</span>","site_nav_ownModel":"Miliki modelmu
sendiri","site_privacy_title":"Kebijakan Privasi","site_capture_title":"Daftar periksa perekaman
1 halaman"}}}
```

624. assistant (2026-06-22T17:34:09.598Z)

Refs give the established per-locale phrasings to reuse. Let me launch the (small) title-translation workflow.

625. user (2026-06-22T17:34:33.085Z)

```
Workflow launched in background. Task ID: w5ohkh2la
Summary: AI-draft + adversarially verify the per-page <title> strings (site.meta.*.title) in
kn/hi/es/da/id
Transcript dir: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_d4dea0ec-6be
Script file: C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-meta-titles-
wf_d4dea0ec-6be.js
(Edit this file with Write/Edit and re-invoke Workflow with {scriptPath:
"C:\Users\avidu\claude\projects\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-meta-titles-
wf_d4dea0ec-6be.js"} to iterate without resending the script.)
Run ID: wf_d4dea0ec-6be
To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claude\projects\C--
Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-
meta-titles-wf_d4dea0ec-6be.js", resumeFromRunId: "wf_d4dea0ec-6be"}) ? completed agents return
cached results.
```

You will be notified when it completes. Use /workflows to watch live progress.

626. assistant (2026-06-22T17:34:44.042Z)

Title workflow running (small). Let me write the apply script and a content test for the titles while it completes.

627. assistant (2026-06-22T17:34:50.357Z)

```
// One-off helper (NOT shipped): merge the per-page <title> translations (_meta.json) into
kn/hi/es/da/id.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";
const ROOT = join(import.meta.dirname, "..", "..");
const load = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));
const EXPECTED = Object.keys(JSON.parse(readFileSync(join(ROOT, "site", "scripts",
"_metapayload.json"), "utf8")).enTargets);
const T = JSON.parse(readFileSync(join(ROOT, "site", "scripts", "_meta.json"), "utf8"));
const setDeep = (root, dotted, v) => { const p = dotted.split("."); let o = root; for (let i =
0; i < p.length - 1; i++) o = o[p[i]] = o[p[i]] || {}; o[p[p.length - 1]] = v; };
let bad = 0;
for (const loc of ["kn", "hi", "es", "da", "id"]) {
  const f = T[loc] && T[loc].final;
  if (!f) { console.error(`MISSING ${loc}`); bad++; continue; }
  const missing = EXPECTED.filter((k) => !(k in f));
  if (missing.length) { console.error(`${loc} MISSING:`, missing.join(", ")); bad++; }
  const cat = load(loc);
  for (const k of EXPECTED) if (k in f) setDeep(cat, k, f[k]);
  writeFileSync(join(ROOT, "locales", loc, "common.json"), JSON.stringify(cat, null, 2) + "\n");
  console.log(`${loc}: ${EXPECTED.filter((k) => k in f).length}/${EXPECTED.length} |
index="${f["site.meta.index.title"]}"`);
}
if (bad) process.exit(1);
console.log("OK");
```

628. user (2026-06-22T17:34:50.370Z)

File created successfully at: C:\Users\avidu\Projects\ks-p2\site\scripts_applymeta.mjs (file state is current in your context ? no need to Read it back)

629. assistant (2026-06-22T17:34:58.416Z)

Let me add a meta-title content test. Let me find the anchor in this worktree's test file.

630. user (2026-06-22T17:34:59.197Z)

```
337:// ---- Privacy Policy page (site.privacy.*) localized in all 5 non-en (P1)
-----
369:// fitNav's REAL geometry (which locale collapses at which width) is exercised end-to-end by
the
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

631. user (2026-06-22T17:35:03.362Z)

```
364      assert.match(lf["security.body"], /HTTPS/, `${loc} security.body lost HTTPS`);
365      assert.match(lf["footTrust"], /© 2026 KhelSutra/, `${loc} privacy.footTrust lost the
© year + brand`);
366    }
367  });
368
369    // fitNav's REAL geometry (which locale collapses at which width) is exercised end-to-
end by the
```

632. user (2026-06-22T17:35:15.098Z)

The file C:\Users\avidu\Projects\ks-p2\site\src\i18n.shim.test.js has been updated successfully.

(file state is current in your context ? no need to Read it back)

633. assistant (2026-06-22T17:35:22.043Z)

Tests staged. Let me check the (small) title workflow's status.

634. user (2026-06-22T17:35:28.524Z)

running; agents: 13

635. assistant (2026-06-22T17:35:36.734Z)

Title workflow still running (13 agents). **P2 status:** P2.5 (a11y) is done + verified (axe now 0 serious/critical; `test:a11y` guard added to CI), P2.3 titles are wired/seeded and translating now. P2.4 (explainer video) I'm recommending for backlog (capture page already teaches recording in all 6 langs). I'll continue automatically when the titles land ? apply ? full matrix (incl. the new a11y guard) ? PR ? merge on green.

636. user (2026-06-22T17:36:28.301Z)

```
<task-notification>
<task-id>w5ohkh2la</task-id>
<tool-use-id>toolu_01KG4eE1v2mBW4UYgwBoYBHK</tool-use-id>
<output-file>C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-
khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\w5ohkh2la.output</output-file>
<status>completed</status>
<summary>Dynamic workflow "AI-draft + adversarially verify the per-page &title strings
(site.meta.*.title) in kn/hi/es/da/id" completed</summary>
<result>{"kn":{"final":{"site.meta.index.title":"????????? ? ????? ????????? ?????????,
????????? ???, ???","site.meta.capture.title":"????????? ? 1-???? ????????? ?????????
?????", "site.meta.ownModel.title":"????????? ? ????? ?????? ?????? ???? & ??????
????????? ?????? ?????", "site.meta.privacy.title":"????????? ???? ?
?????????"}, "fixed":1, "missing":[], "hi":{"final":{"site.meta.index.title":"KhelSutra ? ??
????, ??? ??. ????? ???, ?????", "site.meta.capture.title":"KhelSutra ? 1-??? ??????
????????", "site.meta.ownModel.title":"KhelSutra ? ??? ?????? ?????? ???? & ??? ????
?????", "site.meta.privacy.title":"????????? ???? ?
KhelSutra"}, "fixed":1, "missing":[], "es":{"final":{"site.meta.index.title":"KhelSutra ? cada
jugada, indexada. El tiempo muerto, fuera.", "site.meta.capture.title":"KhelSutra ? lista de
captura de 1 página", "site.meta.ownModel.title":"KhelSutra ? anota tus grabaciones & entrena
tu propio modelo", "site.meta.privacy.title":"Política de privacidad ?
KhelSutra"}, "fixed":2, "missing":[], "da":{"final":{"site.meta.index.title":"KhelSutra ? hver
duel, indekseret. Den døde tid, væk", "site.meta.capture.title":"KhelSutra ? optagelsestjekliste
på 1 side", "site.meta.ownModel.title":"KhelSutra ? Annotér dine optagelser & træn din egen
model", "site.meta.privacy.title":"Privatlivspolitik ?
KhelSutra"}, "fixed":1, "missing":[], "id":{"final":{"site.meta.index.title":"KhelSutra ? setiap
reli terindeks, waktu kosongnya hilang", "site.meta.capture.title":"KhelSutra ? daftar periksa
perekaman 1 halaman", "site.meta.ownModel.title":"KhelSutra ? Anotasi rekamanmu & latih
modelmu sendiri", "site.meta.privacy.title":"Kebijakan Privasi ?
KhelSutra"}, "fixed":0, "missing":[]}}</result>
<usage><agent_count>14</agent_count><subagent_tokens>454061</subagent_tokens><tool_uses>56</tool
_uses><duration_ms>115141</duration_ms></usage>
</task-notification>
```

637. assistant (2026-06-22T17:37:16.104Z)

Title workflow done, but two defects to fix before applying: (1) **kn transliterated the brand** to "?????????" (must stay Latin "KhelSutra" ? my content test + the web `catalog-invariants` brand guard both forbid the transliteration), and (2) all locales HTML-escaped `&`?`&` in the own-model title (would render literally as text in ``). Let me correct both, then apply.</p></div><div data-bbox="64 900 327 916" data-label="Section-Header"><h3>638. user (2026-06-22T17:37:22.603Z)</h3></div><div data-bbox="64 929 580 944" data-label="Text"><p>OK: all titles keep Latin KhelSutra, no & / no brand-translit</p></div>

```
kn index: KhelSutra ? ????? ???????? ?????????, ????????? ???? , ???
es ownModel: KhelSutra ? anota tus grabaciones & entrena tu propio modelo
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

639. assistant (2026-06-22T17:37:31.041Z)

Both fixed. Let me apply, mirror, and run the full matrix.

640. user (2026-06-22T17:37:40.993Z)

```
MISSING kn
MISSING hi
MISSING es
MISSING da
MISSING id
=== SITE unit ===
? meta titles: kn/hi in-script, es/da/id translated; the KhelSutra brand stays Latin (0.6769ms)
? tests 95
? pass 94
? fail 1
? failing tests:
? meta titles: kn/hi in-script, es/da/id translated; the KhelSutra brand stays Latin (0.6769ms)
  at Test.processPendingSubtests (node:internal/test_runner/test:897:18)
  at async Test.processPendingSubtests (node:internal/test_runner/test:897:7) {
=== web hygiene + catalog-invariants (brand guard) ===
  Test Files   3 passed (3)
    Tests     70 passed (70)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

641. assistant (2026-06-22T17:37:50.494Z)

The apply script expected `{loc:{final}}` but I wrote `{loc:flatMap}` ? so nothing applied. Let me fix the reader and re-run.

642. user (2026-06-22T17:37:51.702Z)

The file C:\Users\avidu\Projects\ks-p2\site\scripts_applymeta.mjs has been updated successfully. (file state is current in your context ? no need to Read it back)

643. user (2026-06-22T17:37:59.197Z)

```
kn: 4/4 | index="KhelSutra ? ????? ???????? ?????????, ????????? ???? , ???"
hi: 4/4 | index="KhelSutra ? ?? ?????, ??? ???? . ????? ???, ?????."
es: 4/4 | index="KhelSutra ? cada jugada, indexada. El tiempo muerto, fuera."
da: 4/4 | index="KhelSutra ? hver duel, indekseret. Den døde tid, væk"
id: 4/4 | index="KhelSutra ? setiap reli terindeks, waktu kosongnya hilang"
OK
copy-locales: da, en, es, hi, id, kn -> site/public/locales/
=== SITE unit ===
? tests 95
? pass 95
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

644. assistant (2026-06-22T17:38:07.806Z)

Site unit 95 green (titles applied; drift guard covers them). Now the browser guards + web suite:

645. user (2026-06-22T17:39:07.001Z)

```
=== RENDER (now validates <title> per locale too) ===
? pass 1
? fail 0
```

```
=== A11Y ===
? axe-core WCAG 2.1 A/AA ? no serious/critical violations on any localized page × locale
(9809.1853ms)
? pass 1
? fail 0
=== LAYOUT ===
? pass 3
? fail 0
=== WEB full ===
  Test Files   24 passed (24)
    Tests     226 passed (226)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

646. assistant (2026-06-22T17:39:15.973Z)

All green (render incl. title, a11y axe-clean, layout, web 226). Let me run the web CI gates, clean up helpers, and review the diff.

647. user (2026-06-22T17:39:37.663Z)

```
=== typecheck ===
OK
=== coverage ===
All files          |   94.09 |   88.77 |   86.59 |   94.09 |
=== build ===
? built in 1.79s
=== git status ===
 M .github/workflows/test.yml
 M locales/da/common.json
 M locales/en/common.json
 M locales/es/common.json
 M locales/hi/common.json
 M locales/id/common.json
 M locales/kn/common.json
 M site/package-lock.json
 M site/package.json
 M site/public/capture.html
 M site/public/index.html
 M site/public/locales/da/common.json
 M site/public/locales/en/common.json
 M site/public/locales/es/common.json
 M site/public/locales/hi/common.json
 M site/public/locales/id/common.json
 M site/public/locales/kn/common.json
 M site/public/own-model.html
 M site/public/privacy.html
 M site/src/i18n.shim.test.js
?? site/src/a11y.browser.mjs
--- base ---
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

648. assistant (2026-06-22T17:39:51.956Z)

All web gates green (typecheck, coverage 94.09%, build). Clean expected diff (a11y guard + axe dep + title localization + contrast/underline fixes), clean base. Let me commit P2.

649. user (2026-06-22T17:40:06.261Z)

```
staged: 21
=== rebase onto origin/master ===
Current branch feat/site-meta-a11y is up to date.
605041d feat(site): a11y audit + fixes + axe CI guard, and localized page titles ? P2
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

650. assistant (2026-06-22T17:40:11.399Z)

Committed (605041d, only my commit, clean base). Let me push and open the PR.

651. user (2026-06-22T17:40:27.978Z)

branch 'feat/site-meta-a11y' set up to track 'origin/feat/site-meta-a11y'.

To <https://github.com/avidullu/khelsutra.git>

```
* [new branch]      feat/site-meta-a11y -> feat/site-meta-a11y
```

<https://github.com/avidullu/khelsutra/pull/107>

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

652. assistant (2026-06-22T17:40:33.343Z)

PR [#107](<https://github.com/avidullu/khelsutra/pull/107>) opened (CI now runs `test:a11y` too).

Let me watch and merge on green.

653. user (2026-06-22T17:41:58.328Z)

```
site    pass    17s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27972162370/job/82780800258
```

```
web     pass    44s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27972162370/job/82780800044
```

```
Workers Builds: hidden-king-khelsutra    pass    0
```

```
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/972921f0-3c63-4c43-91bc-0ab0e9e6c300
```

```
layout  pass    1m12s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27972162370/job/82780800186
```

```
site    pass    17s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27972162370/job/82780800258
```

```
web     pass    44s
```

```
https://github.com/avidullu/khelsutra/actions/runs/27972162370/job/82780800044
```

```
EXIT:0
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

654. assistant (2026-06-22T17:42:03.366Z)

All green (the `layout` job now runs render + a11y too). Let me verify and merge.

655. user (2026-06-22T17:42:10.886Z)

only my commit?

605041d feat(site): a11y audit + fixes + axe CI guard, and localized page titles ? P2

```
{"merge":"ea7c5fef74cecb0b7ed4f7d7d7361b497dbeeade","state":"MERGED"}
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

656. assistant (2026-06-22T17:42:29.113Z)

****P2 merged**** ([#107](<https://github.com/avidullu/khelsutra/pull/107>), squash `ea7c5fe`) ? a11y audit/fixes + axe CI guard + localized page titles. Let me clean up and start ****P3.8**** (es/da/id academy flyers).

657. user (2026-06-22T17:42:41.158Z)

```
- [deleted]      feat/site-meta-a11y
```

HEAD is now at ea7c5fe feat(site): a11y audit + fixes + axe CI guard, and localized page titles

? P2 (#107)

flyers worktree on: ea7c5fe feat(site): a11y audit + fixes + axe CI guard, and localized page

titles ? P2 (#107)

658. assistant (2026-06-22T17:42:48.933Z)

P3.8 worktree ready. Let me copy node_modules (background) and study the flyer structure ? the

en page, a localized one (kn), how the localized UI screenshot is embedded, and how flyers are routed/linked/tested.

659. user (2026-06-22T17:42:52.868Z)

Command running in background with ID: bctltoCyb. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bctltoCyb.output. You will be notified when it completes. To check interim output, use Read on that file path.

660. user (2026-06-22T17:42:53.942Z)

```
=== flyer files + sizes ===
-rw-r--r-- 1 avidu 197609 13754 Jun 22 23:12 public/flyer-hi.html
-rw-r--r-- 1 avidu 197609 14410 Jun 22 23:12 public/flyer-kn.html
-rw-r--r-- 1 avidu 197609 10938 Jun 22 23:12 public/flyer.html
-rw-r--r-- 1 avidu 197609 62302 Jun 22 23:12 public/img/studio-en.png
-rw-r--r-- 1 avidu 197609 83368 Jun 22 23:12 public/img/studio-hi.png
-rw-r--r-- 1 avidu 197609 123371 Jun 22 23:12 public/img/studio-kn.png
=== flyer.html (en) ===
<!doctype html>
<html lang="en">
<head>
<meta charset="utf-8" />
<meta name="viewport" content="width=device-width, initial-scale=1" />
<title>KhelSutra ? try it free, tell us what you think (academy flyer)</title>
<meta name="description" content="Pin-up flyer for badminton academies: record your session,
KhelSutra kills the dead time automatically, saves you hours, and hands you share-ready
highlight clips. Try the alpha and give feedback." />
<link rel="icon" href="data:image/svg+xml,%3Csvg xmlns='http://www.w3.org/2000/svg' viewBox='0 0
32 32'%3E%3Crect width='32' height='32' rx='8' fill='%230C261F'/%3E%3Cpath d='M13 10 L23 16 L13
22 Z' fill='%2319B36B'/%3E%3C/svg%3E" />
<link rel="preconnect" href="https://fonts.googleapis.com" />
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin />
<link href="https://fonts.googleapis.com/css2?family=Plus+Jakarta+Sans:wght@400;500;600;700;800&
display=swap" rel="stylesheet" />
<style>
:root{
  --ink:#0C261F; --ink2:#123A2E; --green:#19B36B; --green-d:#137a4c;
  --lime:#C7F2B0; --paper:#F6F8F4; --tx:#14271F; --mut:#566B61; --line:#E1E7DF;
  --font:'Plus Jakarta Sans',system-ui,-apple-system,Segoe UI,Roboto,sans-serif;
}
*{box-sizing:border-box}
body{margin:0;font-family:var(--font);color:var(--tx);background:#E9EDE6;line-
height:1.45;-webkit-font-smoothing:antialiased}

/* A4 portrait sheet */
.sheet{width:210mm;min-height:297mm;margin:14px auto;background:#fff;border-
radius:14px;overflow:hidden;
  box-shadow:0 18px 50px -24px rgba(0,0,0,.4);display:flex;flex-direction:column}

/* header / hero */
.head{background:linear-gradient(160deg,var(--ink) 0%,var(--ink2)
100%);color:#EAF3EE;padding:16px 34px 17px}
.topline{display:flex;align-items:center;justify-content:space-between;gap:1rem}
.brand{display:flex;align-items:center;font-weight:800;font-size:1.5rem;letter-spacing:-.02em}
.brand .play{display:inline-block;width:0;height:0;border-style:solid;border-width:8px 0 8px
13px;
  border-color:transparent transparent transparent var(--green);margin:0
.32em;transform:translateY(1px)}
.eyebrow{font-size:.74rem;font-weight:700;letter-spacing:.05em;text-
transform:uppercase;color:var(--lime);
  background:rgba(199,242,176,.12);border:1px solid rgba(199,242,176,.25);padding:.34rem
.7rem;border-radius:999px;white-space:nowrap}
.head h1{font-size:2.35rem;font-weight:800;line-height:1.06;margin:16px 0 0;max-
```

```

width:18ch;letter-spacing:-.02em}
.head h1 .hl{color:var(--lime)}
.head .lead{color:#BcD8Cb;font-size:1rem;margin:.7rem 0 0;max-width:60ch}

.body{padding:14px 34px 4px;flex:1;display:flex;flex-direction:column}

/* spotlight: kill the dead time */
.spot{display:flex;gap:1rem;align-items:center;background:#EAF6EF;border:1px solid
#BfE6D2;border-radius:13px;
padding:13px 18px;margin-bottom:15px}
.spot .big{flex:none;text-align:center;padding-right:16px;border-right:1px solid #BfE6D2}
.spot .big b{display:block;font-size:2rem;font-weight:800;color:var(--green-d);line-height:1}
.spot .big em{font-style:normal;font-size:.72rem;color:var(--mut);text-
transform:uppercase;letter-spacing:.04em}
.spot p{margin:0;font-size:.98rem;color:var(--tx)}
.spot p b{color:var(--green-d)}
.track{position:relative;height:14px;border-radius:7px;background:#dDE6dE;margin:.5rem 0
.2rem;overflow:hidden}
.track span{position:absolute;top:0;bottom:0;background:var(--green);border-radius:7px}
.track lbl{display:flex;justify-content:space-between;font-size:.74rem;color:var(--mut)}

/* outcome chips */
.chips{display:grid;grid-template-columns:repeat(3,1fr);gap:12px;margin-bottom:16px}
.chip{display:flex;gap:.6rem;align-items:center;background:#fff;border:1px solid
var(--line);border-radius:11px;padding:11px 13px}
.chip .ic{width:36px;height:36px;border-
radius:10px;flex:none;background:rgba(25,179,107,.12);color:var(--green-d);
display:flex;align-items:center;justify-content:center;font-size:1.25rem}
.chip b{display:block;font-size:.96rem;color:var(--tx)}
.chip span{font-size:.8rem;color:var(--mut)}

/* compact record guide */
.guide{background:var(--paper);border:1px solid var(--line);border-radius:13px;padding:14px
18px;margin-bottom:16px}
.guide .gh{display:flex;align-items:baseline;gap:.55rem;margin-bottom:.55rem;flex-wrap:wrap}
.guide .gh .k{font-size:.74rem;font-weight:700;letter-spacing:.06em;text-
transform:uppercase;color:var(--green-d)}
.guide .gh h2{font-size:1.12rem;font-weight:700;margin:0}
.golden{display:flex;gap:.55rem;align-items:flex-start;margin-bottom:.65rem}
.golden .star{color:var(--green-d);font-size:1.2rem;line-height:1.05}
.golden p{margin:0;font-size:.93rem;color:var(--tx)}
.ess{list-style:none;margin:0;padding:0;display:grid;grid-template-columns:1fr 1fr;gap:.35rem
1.4rem}
.ess li{display:flex;gap:.45rem;font-size:.89rem;color:#34453d}
.ess li i{color:var(--green-d);font-style:normal;font-weight:700;margin-top:.05rem}
.ess li b{color:var(--tx)}
.guide .more{margin:.7rem 0 0;font-size:.83rem;color:var(--mut)}
.guide .more a{color:var(--green-d);text-decoration:none;font-weight:600}

/* CTA / feedback band */
.cta{margin-top:auto;background:linear-gradient(160deg,var(--ink) 0%,var(--ink2)
100%);color:#EAF3EE;
border-radius:15px;padding:18px 22px;display:flex;gap:22px;align-items:center}
.cta-tx{flex:1}
.cta-tx .pill{display:inline-block;background:rgba(199,242,176,.14);color:var(--lime);font-
size:.72rem;font-weight:700;
letter-spacing:.04em;text-transform:uppercase;padding:.3rem .72rem;border-
radius:999px;margin-bottom:.55rem}
.cta-tx h2{font-size:1.42rem;font-weight:800;margin:0;color:#fff;line-height:1.14}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

661. assistant (2026-06-22T17:43:33.166Z)

The flyer is a full A4 print page (hero + dead-time spotlight + chips + record guide + CTA) embedding a localized SPA screenshot (`studio-<lang>.png`). Adding es/da/id means: translating

the copy, ****generating 3 localized SPA screenshots****, creating 3 pages, routing + linking + tests. Let me read the full flyer body, a localized template (kn), and the test/routing requirements to scope precisely.

662. user (2026-06-22T17:43:35.456Z)

=== flyer.html body (from <body>) ===

```
<body>
<div class="sheet">
  <div class="head">
    <div class="topline">
      <span class="brand">Khel<span class="play" aria-hidden="true"></span>Sutra</span>
      <span class="eyebrow">Free invite-only alpha · Bengaluru</span>
    </div>
    <h1>Your matches, with the <span class="hl">dead time gone.</span></h1>
    <p class="lead">Record a full session ? KhelSutra finds every rally and automatically cuts
the knock-ups,
      walks and gaps. An hour of footage becomes minutes of pure highlights to download and
share on
      WhatsApp & Instagram. No editing, no scrubbing.</p>
    </div>

    <figure class="noprint" style="margin:14px 0 0;text-align:center">
      
      <figcaption style="font-size:.78rem;color:var(--mut);margin-top:.3rem">The tool works in
your language ? English, ?????, ??????</figcaption>
    </figure>

    <div class="body">
      <div class="spot">
        <div class="big"><b>?60%</b><em>often dead time</em></div>
        <div style="flex:1">
          <p style="margin-bottom:.45rem"><b>A full match ? just the great rallies.</b> The walks,
knock-ups and gaps are cut automatically ? KhelSutra hands you one clean, share-ready reel.</p>
          <div class="track">
            <span style="left:2%;width:7%"></span><span style="left:12%;width:5%"></span>
            <span style="left:20%;width:11%"></span><span style="left:34%;width:6%"></span>
            <span style="left:43%;width:10%"></span><span style="left:57%;width:5%"></span>
            <span style="left:65%;width:12%"></span><span style="left:81%;width:8%"></span><span
style="left:92%;width:6%"></span>
          </div>
          <div class="tracklbl"><span>Green = the rallies kept</span><span>Gaps = dead time
removed</span></div>
        </div>
      </div>

      <div class="chips">
        <div class="chip"><span class="ic" aria-hidden="true">?</span><div><b>Save
hours</b><span>No manual editing</span></div></div>
        <div class="chip"><span class="ic" aria-hidden="true">?</span><div><b>Only the
best</b><span>Real rallies, end to end</span></div></div>
        <div class="chip"><span class="ic" aria-hidden="true">?</span><div><b>Share-
ready</b><span>WhatsApp & Instagram</span></div></div>
      </div>

      <div class="guide">
        <div class="gh"><span class="k">Record it right</span><h2>30 seconds of setup ? reliably
great reels</h2></div>
        <div class="golden">
          <span class="star" aria-hidden="true">?</span>
          <p><b>The golden rule: one match, one court, in full frame ? and don't move the
camera.</b></p>
        </div>
        <ul class="ess">
```

```

        <li><i>?</i><span><b>Whole court in frame</b>, behind the baseline, slightly
elevated</span></li>
        <li><i>?</i><span><b>Fixed tripod</b> ? no panning or zooming during play</span></li>
        <li><i>?</i><span><b>1080p, landscape, audio on</b></span></li>
        <li><i>?</i><span><b>Record the whole session</b>, upload as-is</span></li>
    </ul>
    <p class="more">Avoid handheld, broadcast-style pans and several courts in one frame. Full
capture checklist ? <a href="https://khelsutra.guru/capture">khelsutra.guru/capture</a></p>
</div>

<div class="cta">
    <div class="cta-tx">
        <span class="pill">Try it &amp; tell us what you think</span>
        <h2>Test it on your own court ? and shape what we build next.</h2>
        <p>Coaches and serious players: scan the code, tell us about your setup, and see the
tool in action ? plus a real 30-second sample reel ? right away.</p>
        <div class="url">khelsutra.guru</div>
    </div>
    <div class="qr">
        
        <small>Scan to try it<br>&amp; give feedback</small>
    </div>
</div>
</div>

<div class="foot">
    <span class="priv">Please record adults with their okay. Footage involving minors is never
used to improve the tool and is never published. Reels carry a ?Generated by Khelsutra.guru?
mark.</span>
    <span>Questions? <a href="mailto:hello@khelsutra.guru">hello@khelsutra.guru</a> · <a
href="https://khelsutra.guru">khelsutra.guru</a></span>
</div>
</div>
</body>
</html>
=== how is the studio screenshot embedded (kn)? ===
115:     
163:         
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

663. assistant (2026-06-22T17:44:04.063Z)

I have the full flyer. The `studio-`<lang>.png`` screenshot is a screen-only (`<code>.noprnt`</code>) preview, but the test requires one per flyer ? so I need to generate localized SPA screenshots (the heavy part). Let me verify node_modules and inspect how the existing shots were framed + the SPA's demo state.

664. user (2026-06-22T17:44:08.974Z)

```

node_modules: site jsdom=site/node_modules/jsdom
y | web vitest=web/node_modules/vitest
y
=== existing studio shot dimensions ===
studio-en 1280x900
studio-kn 1280x900
studio-hi 1280x900
=== assets.test flyer requirements ===
97: assert.match(html, /href="\//flyer"/, "homepage doesn't link the English academy flyer");
98: assert.match(html, /href="\//flyer-kn"/, "homepage doesn't link the Kannada academy flyer");
99: assert.match(html, /href="\//flyer-hi"/, "homepage doesn't link the Hindi academy flyer");
101: // The three flyer pages exist, are HTML, and carry the right language + script.
102: const en = read("flyer.html");

```



```

103: assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");
104: const kn = read("flyer-kn.html");
105: assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
106: assert.match(kn, /[?~?]/, "flyer-kn.html should contain Kannada text");
107: const hi = read("flyer-hi.html");
108: assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
109: assert.match(hi, /[?~?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
112:test("each flyer shows a screenshot of the tool rendered in that language", () => {
113:  for (const [flyer, img] of [["flyer.html", "studio-en.png"], ["flyer-kn.html", "studio-
kn.png"], ["flyer-hi.html", "studio-hi.png"]]) {
115:    assert.match(read(flyer), new RegExp(`/img/${img}`), `${flyer} should embed its
localized UI screenshot /img/${img}`);
124:  assert.match(nav[0], /href="/flyer"/, "the top nav doesn't link the Flyer");
127:  assert.match(om, /href="/flyer"/, "own-model doesn't link the English flyer");
128:  assert.match(om, /href="/flyer-kn"/, "own-model doesn't link the Kannada flyer");
129:  assert.match(om, /href="/flyer-hi"/, "own-model doesn't link the Hindi flyer");
476:// be an allowlisted literal: brand, email/URL/flyer-autonym link, storage product name).
This is the
=== server flyer routes ===
101:   : pathname === "/flyer" ? "flyer.html"
102:   : pathname === "/flyer-kn" ? "flyer-kn.html"
103:   : pathname === "/flyer-hi" ? "flyer-hi.html"
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

665. assistant (2026-06-22T17:44:44.981Z)

I have the full picture. P3.8 needs translated flyer copy + 3 localized SPA screenshots (1280×900, demo-rally state) + 3 pages + routing/linking. The screenshot generation is the risky part ? let me de-risk it first by building the SPA and capturing the es/da/id studio shots.

666. user (2026-06-22T17:44:50.954Z)

```

- Use build.rollupOptions.output.manualChunks to improve chunking:
https://rollupjs.org/configuration-options/#output-manualchunks
- Adjust chunk size limit for this warning via build.chunkSizeWarningLimit.
? built in 1.92s
dist built: dist/index.html
y
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

667. assistant (2026-06-22T17:45:11.154Z)

SPA built. Let me serve dist and capture the studio in es/da/id (1280×900, matching the existing shots).

668. user (2026-06-22T17:45:18.554Z)

```

    at ModuleLoader.getOrCreateModuleJob (node:internal/modules/esm/loader:596:35)
    at node:internal/modules/esm/loader:625:32 {
  code: 'ERR_MODULE_NOT_FOUND'
}

```

```

Node.js v26.1.0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

669. assistant (2026-06-22T17:45:26.755Z)

Playwright resolves from `site/node\_modules`. Let me run the capture from the `site` directory.

670. user (2026-06-22T17:45:34.776Z)

```

Exit code 1
    at ModuleLoader.getOrCreateModuleJob (node:internal/modules/esm/loader:596:35)
    at node:internal/modules/esm/loader:625:32 {

```

```
    code: 'ERR_MODULE_NOT_FOUND'
  }
```

```
Node.js v26.1.0
--- generated shots ---
node:fs:556
  return binding.open(
    ^
```

```
Error: ENOENT: no such file or directory, open 'C:\Users\avidu\Projects\ks-
flyers\site\public\img\studio-es.png'
    at Object.openSync (node:fs:556:18)
    at Object.readFileSync (node:fs:440:35)
    at [eval]:1:68
    at runScriptInThisContext (node:internal/vm:219:10)
    at node:internal/process/execution:483:12
    at [eval]-wrapper:6:24
    at runScriptInContext (node:internal/process/execution:481:60)
    at evalFunction (node:internal/process/execution:315:30)
    at evalTypeScript (node:internal/process/execution:327:3)
    at node:internal/main/eval_string:71:3 {
  errno: -4058,
  code: 'ENOENT',
  syscall: 'open',
  path: 'C:\\Users\\avidu\\Projects\\ks-flyers\\site\\public\\img\\studio-es.png'
}
```

```
Node.js v26.1.0
```

671. assistant (2026-06-22T17:45:55.470Z)

Playwright isn't in this worktree's copied `site/node\_modules`. Let me capture from the screencast repo (which has a working Playwright + Chromium), serving the built SPA and writing into the flyers worktree.

672. user (2026-06-22T17:46:10.773Z)

```
es html.lang=es errs=0
da html.lang=da errs=0
id html.lang=id errs=0
--- dims ---
studio-es 1280x900 64KB
studio-da 1280x900 62KB
studio-id 1280x900 61KB
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

673. assistant (2026-06-22T17:46:17.484Z)

Screenshots captured (1280×900, ~62KB, correct lang, no errors). Let me eyeball the Spanish one to confirm it shows the studio in-language.

674. assistant (2026-06-22T17:46:49.209Z)

Good ? Spanish renders cleanly, **but** it shows the P2c setup wizard's **connection-error** state (the static build has no backend) ? bad for a marketing screenshot. The existing en/kn/hi shots predate that wizard. Let me find the wizard's skip control to dismiss it for a clean studio shot.

675. user (2026-06-22T17:46:59.050Z)

```
{
  "buttons": [
    {
      "t": "English",
```

```

    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
bg-white text-ink",
    "aria": null
  },
  {
    "t": "?????",
    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
text-white/70 hover:text-white",
    "aria": null
  },
  {
    "t": "??????",
    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
text-white/70 hover:text-white",
    "aria": null
  },
  {
    "t": "Español",
    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
text-white/70 hover:text-white",
    "aria": null
  },
  {
    "t": "Dansk",
    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
text-white/70 hover:text-white",
    "aria": null
  },
  {
    "t": "Bahasa Indonesia",
    "cls": "inline-flex min-h-11 items-center rounded-full px-4 text-sm font-semibold transition
text-white/70 hover:text-white",
    "aria": null
  },
  {
    "t": "Skip",
    "cls": "min-h-11 rounded-lg px-3 text-sm text-ink/60 hover:text-ink",
    "aria": null
  },
  {
    "t": "Get started",
    "cls": "min-h-11 rounded-lg bg-green px-5 text-sm font-semibold text-white",
    "aria": null
  },
  {
    "t": "Apply",
    "cls": "min-h-11 rounded-xl bg-ink px-4 py-2 text-sm font-semibold text-white
disabled:opacity-40",
    "aria": null
  },
  {
    "t": "over 10s",
    "cls": "inline-flex min-h-11 items-center rounded-full border border-black/15 px-4 text-sm
hover:border-green",
    "aria": null
  }
]
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

```

676. assistant (2026-06-22T17:47:12.137Z)

The wizard has a "Skip" button (``class*="text-ink/60"``). Let me re-capture all three with the wizard dismissed for a clean studio shot.

677. user (2026-06-22T17:47:28.974Z)

```

es wizard-dismissed, residual-error=false
da wizard-dismissed, residual-error=false

```

id wizard-dismissed, residual-error=false
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

678. assistant (2026-06-22T17:47:34.648Z)

Wizard dismissed cleanly. Let me confirm the Spanish shot now shows a clean studio.

679. assistant (2026-06-22T17:49:10.930Z)

Clean Spanish studio ? ingest panel ("Procesar un video"), sample-rally filters, "Crear reel (6)" ? all localized, no wizard error. Screenshots done (es/da/id). Now the flyer copy: I'll extract the en strings, translate to es/da/id, and build the 3 pages. Let me extract the flyer's translatable strings by selector.

680. user (2026-06-22T17:49:20.811Z)

extracted 29 flyer strings

```
{
  "title": "KhelSutra ? try it free, tell us what you think (academy flyer)",
  "metaDesc": "Pin-up flyer for badminton academies: record your session, KhelSutra kills the dead time automatically, saves you hours, and hands you share-ready highlight clips. Try the alpha and give feedback.",
  "eyebrow": "Free invite-only alpha · Bengaluru",
  "h1": "Your matches, with the <span class='hl'>dead time gone.</span>",
  "lead": "Record a full session ? KhelSutra finds every rally and automatically cuts the knock-ups, walks and gaps. An hour of footage becomes minutes of pure highlights to download and share on WhatsApp & Instagram. No editing, no scrubbing.",
  "figcaption": "The tool works in your language ? English, ?????, ??????.",
  "spotEm": "often dead time",
  "spotP": "<b>A full match ? just the great rallies.</b> The walks, knock-ups and gaps are cut automatically ? KhelSutra hands you one clean, share-ready reel.",
  "trackKept": "Green = the rallies kept",
  "trackGaps": "Gaps = dead time removed",
  "chip1b": "Save hours",
  "chip1s": "?",
  "chip2b": "Only the best",
  "chip2s": "No manual editing",
  "chip3b": "Share-ready",
  "chip3s": "?",
  "guideK": "Record it right",
  "guideH2": "30 seconds of setup ? reliably great reels",
  "golden": "<b>The golden rule: one match, one court, in full frame ? and don't move the camera.</b>",
  "ess1": "<b>Whole court in frame</b>, behind the baseline, slightly elevated",
  "ess2": "<b>Fixed tripod</b> ? no panning or zooming during play",
  "ess3": "<b>1080p, landscape, audio on</b>",
  "ess4": "<b>Record the whole session</b>, upload as-is",
  "more": "Avoid handheld, broadcast-style pans and several courts in one frame. Full capture checklist ? <a href='\"https://khelsutra.guru/capture\">khelsutra.guru/capture</a>",
  "ctaPill": "Try it & tell us what you think",
  "ctaH2": "Test it on your own court ? and shape what we build next.",
  "ctaP": "Coaches and serious players: scan the code, tell us about your setup, and see the tool in action ? plus a real 30-second sample reel ? right away.",
  "qrSmall": "Scan to try it<br>& give feedback",
  "priv": "Please record adults with their okay. Footage involving minors is never used to improve the tool and is never published. Reels carry a ?Generated by Khelsutra.guru? mark."
}
```

Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

681. assistant (2026-06-22T17:49:37.084Z)

The chip subtitle extraction grabbed the decorative icons (`.ic`) ? let me fix the selector (`.chip > div > span`) and re-extract.

682. user (2026-06-22T17:49:42.266Z)

chip titles: Save hours | Only the best | Share-ready
chip subtitles: No manual editing | Real rallies, end to end | WhatsApp & Instagram
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

683. assistant (2026-06-22T17:50:03.728Z)

Chips fixed. The flyer copy heavily overlaps already-translated site strings (golden rule, essentials, the consent/watermark note, WhatsApp share) ? let me build a rich per-locale reference from the catalogs so the flyer reads consistently, then launch the workflow.

684. user (2026-06-22T17:50:07.906Z)

payload bytes: 6324 | enTargets: 29
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

685. user (2026-06-22T17:50:11.735Z)

```
1      {"enTargets":{"title":"KhelSutra ? try it free, tell us what you think (academy
flyer)","metaDesc":"Pin-up flyer for badminton academies: record your session, KhelSutra kills
the dead time automatically, saves you hours, and hands you share-ready highlight clips. Try the
alpha and give feedback.", "eyebrow":"Free invite-only alpha · Bengaluru", "h1":"Your matches,
with the <span class=\\"hl\\">dead time gone.</span>", "lead":"Record a full session ? KhelSutra
finds every rally and automatically cuts the knock-ups, walks and gaps. An hour of footage
becomes minutes of pure highlights to download and share on WhatsApp & Instagram. No
editing, no scrubbing.", "figcaption":"The tool works in your language ? English, ?????,
?????.", "spotEm":"often dead time", "spotP":"<b>A full match ? just the great rallies.</b> The
walks, knock-ups and gaps are cut automatically ? KhelSutra hands you one clean, share-ready
reel.", "trackKept":"Green = the rallies kept", "trackGaps":"Gaps = dead time
removed", "chip1b":"Save hours", "chip1s":"No manual editing", "chip2b":"Only the
best", "chip2s":"Real rallies, end to end", "chip3b":"Share-ready", "chip3s":"WhatsApp &
Instagram", "guideK":"Record it right", "guideH2":"30 seconds of setup ? reliably great
reels", "golden":"<b>The golden rule: one match, one court, in full frame ? and don't move the
camera.</b>", "ess1":"<b>Whole court in frame</b>, behind the baseline, slightly
elevated", "ess2":"<b>Fixed tripod</b> ? no panning or zooming during play", "ess3":"<b>1080p,
landscape, audio on</b>", "ess4":"<b>Record the whole session</b>, upload as-is", "more":"Avoid
handheld, broadcast-style pans and several courts in one frame. Full capture checklist ? <a
href=\\"https://khelsutra.guru/capture\\">khelsutra.guru/capture</a>", "ctaPill":"Try it & tell us
what you think", "ctaH2":"Test it on your own court ? and shape what we build
next.", "ctaP":"Coaches and serious players: scan the code, tell us about your setup, and see the
tool in action ? plus a real 30-second sample reel ? right away.", "qrSmall":"Scan to try
it<br>& give feedback", "priv":"Please record adults with their okay. Footage involving
minors is never used to improve the tool and is never published. Reels carry a ?Generated by
Khelsutra.guru? mark."}, "ref":{"es":{"hero_lead":"KhelSutra encuentra cada jugada de tu sesión y
elimina los calentamientos, las caminatas y las pausas ? para que un partido completo se
convierta en un reel de jugadas destacadas limpio que puedes ver y descargar. Sin edición ni
rebobinados.", "hero_title":"Cada jugada, indexada. <span class=\\"hl\\">El tiempo muerto,
fuera.</span>", "golden":"La regla de oro: un partido, una cancha, en cuadro completo ? y no
muevas la cámara.", "consent":"Por favor, graba a adultos con su consentimiento. Las grabaciones
que involucran a menores nunca se usan para mejorar la herramienta y nunca se
publican.", "ess_place":"Detrás de <b>una línea de fondo</b>, en alto ? un trípode alto, a unos
metros de altura, o un balcón.", "ess_settings":"<b>1080p o superior</b>, grabado en
<b>horizontal</b>.", "ess_audio":"<b>Audio ACTIVADO</b> (no silencies) ? mantén el micrófono
despejado, con la reducción de viento/ruido desactivada.", "watermark":"Los reels llevan una
marca \\"Generated by Khelsutra.guru\\".", "share":"Mira KhelSutra ? convierte un partido completo
de bádminton en un reel de jugadas destacadas limpio ?
khelsutra.guru", "requestAccess":"Solicitar acceso", "app_title":"Elige las jugadas para tu
reel", "record_intro":"La calidad de las jugadas destacadas empieza con la grabación. Coloca la
cámara así una sola vez y KhelSutra tendrá todo lo que necesita para encontrar las
jugadas."}, "da":{"hero_lead":"KhelSutra finder hver duel i din session og fjerner
opvarmningsslag, gåture og pauser ? så en hel kamp bliver til en ren highlights-reel, du kan se
og downloade. Ingen redigering, ingen spoling.", "hero_title":"Hver duel, indekseret. <span
class=\\"hl\\">Den døde tid, væk.</span>", "golden":"Den gyldne regel: én kamp, én bane, i fuldt
```

billede ? og flyt ikke kameraet.", "consent": "Optag venligst voksne med deres samtykke. Optagelser, der involverer mindreårige, bruges aldrig til at forbedre værktøjet og offentliggøres aldrig.", "ess_place": "Bag én baglinje, hævet ? et højt stativ, et par meter oppe, eller en altan.", "ess_settings": "1080p eller højere, optaget liggende.", "ess_audio": "Lyd TIL (sæt ikke på lydløs) ? hold mikrofonen fri, slå vind-/støjreduktion fra.", "watermark": "Reels bærer et ?Generated by Khelsutra.guru?-mærke.", "share": "Tjek KhelSutra ? den forvandler en hel badmintonkamp til en ren highlights-reel ? khelsutra.guru", "requestAccess": "Anmod om adgang", "app_title": "Vælg duellerne til din reel", "record_intro": "Kvaliteten af dine highlights begynder med optagelsen. Stil kameraet op én gang på denne måde, så har KhelSutra alt, hvad den skal bruge for at finde duellerne.", "id": {"hero_lead": "KhelSutra menemukan setiap reli dalam sesimu dan membuang pemanasan, momen jalan-jalan antar-poin, dan waktu kosong ? sehingga satu pertandingan penuh menjadi reel sorotan rapi yang bisa kamu tonton dan unduh. Tanpa mengedit, tanpa menggeser-geser.", "hero_title": "Setiap reli, terindeks. Waktu kosongnya, hilang.", "golden": "Aturan emasnya: satu pertandingan, satu lapangan, dalam frame penuh ? dan jangan menggerakkan kamera.", "consent": "Mohon rekam orang dewasa hanya atas persetujuan mereka. Rekaman yang melibatkan anak di bawah umur tidak pernah digunakan untuk meningkatkan alat ini dan tidak pernah dipublikasikan.", "ess_place": "Di belakang satu garis belakang, ditinggikan ? tripod tinggi, beberapa meter di atas, atau balkon.", "ess_settings": "1080p atau lebih tinggi, diambil dalam mode lanskap.", "ess_audio": "Audio ON (jangan dibisukan) ? jaga mikrofon tidak terhalang, matikan pengurangan angin/bising.", "watermark": "Reel membawa tanda \"Generated by Khelsutra.guru\".", "share": "Coba KhelSutra ? ia mengubah satu pertandingan bulu tangkis penuh menjadi reel sorotan yang rapi ? khelsutra.guru", "requestAccess": "Minta akses", "app_title": "Pilih reli untuk reel kamu", "record_intro": "Kualitas highlight dimulai dari rekamannya. Atur kamera sekali seperti ini dan KhelSutra sudah punya semua yang diperlukannya untuk menemukan reli."}}}

686. assistant (2026-06-22T17:50:20.715Z)

Rich refs in place. Let me launch the flyer translation workflow (es/da/id, 29 strings, HTML-preserving, reusing the established site phrasings).

687. user (2026-06-22T17:51:07.712Z)

Workflow launched in background. Task ID: w7lexugf9
 Summary: AI-draft + adversarially verify the academy flyer copy (es/da/id)
 Transcript dir: C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\subagents\workflows\wf_893bf41e-b05
 Script file: C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-flyer-wf_893bf41e-b05.js
 (Edit this file with Write/Edit and re-invoke Workflow with {scriptPath: "C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-flyer-wf_893bf41e-b05.js"} to iterate without resending the script.)
 Run ID: wf_893bf41e-b05
 To resume after editing the script: Workflow({scriptPath: "C:\Users\avidu\claud\projects\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\workflows\scripts\translate-flyer-wf_893bf41e-b05.js", resumeFromRunId: "wf_893bf41e-b05"}) ? completed agents return cached results.

You will be notified when it completes. Use /workflows to watch live progress.

688. assistant (2026-06-22T17:52:31.659Z)

Flyer workflow running. Let me prepare the build script that assembles `flyer-{es,da,id}.html` from the en flyer + translations (handling `&`/'&' entity encoding, the localized studio screenshot + alt + lang). It'll run after the workflow.

689. assistant (2026-06-22T17:52:44.856Z)

```
// One-off helper (NOT shipped): build flyer-es/da/id.html from flyer.html + the translations
(_flyer.json).
// The flyer is a STANDALONE hardcoded-language page (not the data-i18n shim) ? like flyer-
```

```

kn/flyer-hi ? so we
// bake the translations into a copy: swap <html lang>, the studio screenshot (src + localized
alt), and every
// translatable English string. Replacement is exact-substring on the raw HTML, with bare "&"
encoded to "&amp;"
// so it matches the source, longest-first so no short string clobbers a longer one.
import { readFileSync, writeFileSync } from "node:fs";
import { join } from "node:path";

const ROOT = join(import.meta.dirname, "..", "..");
const SITE = join(ROOT, "site");
const en = JSON.parse(readFileSync(join(SITE, "scripts", "_flyer_en.json"), "utf8"));
const T = JSON.parse(readFileSync(join(SITE, "scripts", "_flyer.json"), "utf8"));
const flyer = readFileSync(join(SITE, "public", "flyer.html"), "utf8");
const cat = (l) => JSON.parse(readFileSync(join(ROOT, "locales", l, "common.json"), "utf8"));

const encAmp = (s) => String(s).replace(/&(?!\amp;|lt;|gt;|quot;|#)/g, "&amp;"); // bare & ->
&amp; (don't double-encode)
const EN_ALT = "KhelSutra Studio ? pick rallies, build a reel";

let report = [];
for (const loc of ["es", "da", "id"]) {
  const tr = T[loc];
  if (!tr) { report.push(`${loc}: MISSING translations`); continue; }
  const missing = Object.keys(en).filter((k) => !(k in tr));
  if (missing.length) report.push(`${loc}: MISSING keys ${missing.join(", ")}`);

  let html = flyer;
  // 1) <html lang>
  html = html.replace(</html lang="en">/, `<html lang="${loc}">`);
  // 2) studio screenshot src + localized alt (reuse the SPA's own translated title)
  html = html.split("/img/studio-en.png").join(`/img/studio-${loc}.png`);
  const alt = `KhelSutra Studio ? ${cat(loc).app.title}`;
  html = html.split(EN_ALT).join(alt);
  // 3) every translatable string, longest en first (encode bare & to match the HTML source)
  for (const [k, v] of Object.entries(en).sort((a, b) => b[1].length - a[1].length)) {
    if (!(k in tr)) continue;
    const from = encAmp(v), to = encAmp(tr[k]);
    if (!html.includes(from)) { report.push(`${loc}: en string for "${k}" not found verbatim in
flyer.html (skipped)`); continue; }
    html = html.split(from).join(to);
  }
  writeFileSync(join(SITE, "public", `flyer-${loc}.html`), html);
  // 4) sanity: a few English sentinels must be gone
  const leftovers = ["The golden rule", "Save hours", "Record it right", "dead time
gone"].filter((s) => html.includes(s));
  report.push(`${loc}: wrote flyer-${loc}.html (${html.length}b)${leftovers.length ? " ?
leftover EN: " + leftovers.join(", ") : " ? no EN sentinel left"}`);
}
console.log(report.join("\n"));

```

690. user (2026-06-22T17:52:44.875Z)

File created successfully at: C:\Users\avidu\Projects\ks-flyers\site\scripts_buildflyers.mjs
(file state is current in your context ? no need to Read it back)

691. assistant (2026-06-22T17:53:09.433Z)

Build script ready. While the workflow runs, let me wire the translation-independent parts:
`server.js` routes for the new flyers and the footer flyer links. Let me read the relevant
spots.

692. user (2026-06-22T17:53:10.387Z)

```
100      : pathname === "/privacy" ? "privacy.html"
101      : pathname === "/flyer" ? "flyer.html"
102      : pathname === "/flyer-kn" ? "flyer-kn.html"
103      : pathname === "/flyer-hi" ? "flyer-hi.html"
104      : pathname.replace(/^\/+/, "");
```

693. user (2026-06-22T17:53:12.155Z)

```
=== index footer flyer row ===
621:      <div style="margin-top:.4rem"><span data-i18n="site.footer.flyer">Academy flyer
(print):</span> <a href="/flyer" hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> . <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></div>
=== own-model footer flyer row ===
191:      <span><a href="/">khelsutra.guru</a> . <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> . <span data-i18n="site.ownModel.foot.flyer">Academy
flyer:</span> <a href="/flyer" hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> . <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></span>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

694. assistant (2026-06-22T17:53:18.943Z)

Let me add the server routes and the footer flyer links (es/da/id) on both index and own-model.

695. user (2026-06-22T17:53:21.793Z)

The file C:\Users\avidu\Projects\ks-flyers\site\server.js has been updated successfully. (file state is current in your context ? no need to Read it back)

696. user (2026-06-22T17:53:25.121Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

697. user (2026-06-22T17:53:28.158Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

698. assistant (2026-06-22T17:53:39.936Z)

Let me read those footer lines (this worktree) then re-apply.

699. user (2026-06-22T17:53:40.901Z)

```
621      <div style="margin-top:.4rem"><span data-i18n="site.footer.flyer">Academy flyer
(print):</span> <a href="/flyer" hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> . <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></div>
```

700. user (2026-06-22T17:53:41.256Z)

```
191      <span><a href="/">khelsutra.guru</a> . <a href="https://github.com/Khelsutra/rally-
annotator">rally-annotator (MIT)</a> . <span data-i18n="site.ownModel.foot.flyer">Academy
flyer:</span> <a href="/flyer" hreflang="en">English</a> . <a href="/flyer-kn" hreflang="kn"
lang="kn">?????</a> . <a href="/flyer-hi" hreflang="hi" lang="hi">?????</a></span>
```

701. user (2026-06-22T17:53:49.904Z)

The file C:\Users\avidu\Projects\ks-flyers\site\public\index.html has been updated successfully. (file state is current in your context ? no need to Read it back)

702. user (2026-06-22T17:53:52.847Z)

The file C:\Users\avidu\Projects\ks-flyers\site\public\own-model.html has been updated successfully. (file state is current in your context ? no need to Read it back)

703. assistant (2026-06-22T17:54:15.821Z)

Footer links + server routes done. Let me read the flyer test block to extend it for es/da/id (ready to pass after the build).

704. user (2026-06-22T17:54:16.674Z)

```
94     test("the academy flyers (en/kn/hi) exist, are language-correct, and are linked from the
homepage", () => {
95         const html = read("index.html");
96         // All three are linked from the homepage footer (the owner ask: the flyers must be
findable).
97         assert.match(html, /href="\ flyer"/, "homepage doesn't link the English academy
flyer");
98         assert.match(html, /href="\ flyer-kn"/, "homepage doesn't link the Kannada academy
flyer");
99         assert.match(html, /href="\ flyer-hi"/, "homepage doesn't link the Hindi academy
flyer");
100     });
101     // The three flyer pages exist, are HTML, and carry the right language + script.
102     const en = read("flyer.html");
103     assert.match(en, /<html lang="en"/i, "flyer.html should be lang=en");
104     const kn = read("flyer-kn.html");
105     assert.match(kn, /<html lang="kn"/i, "flyer-kn.html should be lang=kn");
106     assert.match(kn, /[?-\?]/, "flyer-kn.html should contain Kannada text");
107     const hi = read("flyer-hi.html");
108     assert.match(hi, /<html lang="hi"/i, "flyer-hi.html should be lang=hi");
109     assert.match(hi, /[?-\?]/, "flyer-hi.html should contain Devanagari (Hindi) text");
110 });
111
112 test("each flyer shows a screenshot of the tool rendered in that language", () => {
113     for (const [flyer, img] of [["flyer.html", "studio-en.png"], ["flyer-kn.html",
"studio-kn.png"], ["flyer-hi.html", "studio-hi.png"]]) {
114         assert.ok(size(`img/${img}`) > 0, `public/img/${img} (the localized UI shot) is
missing or empty`);
115         assert.match(read(flyer), new RegExp(`/img/${img}`), `${flyer} should embed its
localized UI screenshot /img/${img}`);
116     }
117 });
118
119 test("the academy flyers are also linked from the top nav and the own-model page", () =>
{
120     const html = read("index.html");
121     // Desktop top nav carries a Flyer entry (alongside Own your model).
122     const nav = html.match(/<nav class="nav-links"[\s\S]*?<\nav>/);
123     assert.ok(nav, "the primary nav block is gone");
124     assert.match(nav[0], /href="\ flyer"/, "the top nav doesn't link the Flyer");
125     // own-model surfaces all three languages.
126     const om = read("own-model.html");
127     assert.match(om, /href="\ flyer"/, "own-model doesn't link the English flyer");
128     assert.match(om, /href="\ flyer-kn"/, "own-model doesn't link the Kannada flyer");
129     assert.match(om, /href="\ flyer-hi"/, "own-model doesn't link the Hindi flyer");
130 });
```

705. assistant (2026-06-22T17:54:29.107Z)

Let me extend the three flyer tests to cover es/da/id (lang + screenshot + linked + a "no leftover English" check that's translation-agnostic).

706. user (2026-06-22T17:54:45.298Z)

The file C:\Users\avidu\Projects\ks-flyers\site\src\assets.test.js has been updated successfully. (file state is current in your context ? no need to Read it back)

707. assistant (2026-06-22T17:54:51.495Z)

Tests extended. Let me check the flyer workflow status.

708. user (2026-06-22T17:54:54.799Z)

DONE

709. assistant (2026-06-22T17:55:17.383Z)

Flyer translations done (missing:[]). The notification's `&` is display-escaping ? let me parse the **raw** values and verify real tags + no actual double-escaping + tokens preserved before building.

710. user (2026-06-22T17:55:26.000Z)

OK: real tags, no double-escape, brand/watermark/links/tokens preserved
es h1: "Tus partidos, con el tiempo muerto fuera."
es lead WhatsApp part: WhatsApp & Instagram
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

711. assistant (2026-06-22T17:55:33.693Z)

Verified ? real tags, single-escaped `&`, brand/watermark/links/tokens intact. Let me build the flyer pages.

712. user (2026-06-22T17:55:35.020Z)

```
es: en string for "lead" not found verbatim in flyer.html (skipped)
es: wrote flyer-es.html (11186b) ? no EN sentinel left
da: en string for "lead" not found verbatim in flyer.html (skipped)
da: wrote flyer-da.html (10960b) ? no EN sentinel left
id: en string for "lead" not found verbatim in flyer.html (skipped)
id: wrote flyer-id.html (11140b) ? no EN sentinel left
--- built files ---
11075 public/flyer-da.html
11294 public/flyer-es.html
11208 public/flyer-id.html
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

713. assistant (2026-06-22T17:56:00.933Z)

The `lead` wasn't replaced ? I'd collapsed its whitespace during extraction, but the source spans 3 lines, so it didn't match (the en lead is still in the es/da/id flyers). Let me re-extract `lead` with its exact source whitespace and rebuild.

714. user (2026-06-22T17:56:06.698Z)

```
raw lead matches source: true
--- rebuild ---
es: wrote flyer-es.html (11229b) ? no EN sentinel left
da: wrote flyer-da.html (10965b) ? no EN sentinel left
id: wrote flyer-id.html (11172b) ? no EN sentinel left
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

715. assistant (2026-06-22T17:56:21.478Z)

Lead now matches + all flyers built with no English sentinel. Let me verify (no leftover English lead) and run the site suite.

716. user (2026-06-22T17:56:26.883Z)

=== leftover English lead in es flyer? ===

```
'Record a full session' count (want 0): 0
=== es flyer: lang + a Spanish marker + studio + watermark ===
<html lang="es"
Generated by Khelsutra.guru
Graba una sesión
studio-es.png
=== SITE full suite ===
? tests 95
? pass 95
? fail 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

717. assistant (2026-06-22T17:56:47.251Z)

es flyer clean (no English lead, lang=es, Spanish copy, localized screenshot, watermark). Site suite 95 green. Let me eyeball the rendered es flyer (via the screencast repo's Playwright) and kick off `npm ci` so the browser guards can run here.

718. user (2026-06-22T17:56:48.778Z)

Command running in background with ID: bq4xxlip8. Output is being written to:
C:\Users\avidu\AppData\Local\Temp\claude\C--Users-avidu-Projects-khelsutra\831509e0-5773-4469-a2ff-205848372a6b\tasks\bq4xxlip8.output. You will be notified when it completes. To check interim output, use Read on that file path.

719. user (2026-06-22T17:56:59.973Z)

flyer-es rendered, errs: 0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

720. assistant (2026-06-22T17:57:05.669Z)

Let me eyeball the rendered Spanish flyer.

721. assistant (2026-06-22T17:57:19.586Z)

The Spanish flyer renders beautifully ? full A4 sheet, Spanish copy throughout, the Spanish studio screenshot, QR/CTA, zero errors. P3.8's content is done. Let me run the browser guards (the footer now has 6 flyer links ? must not overflow) + web.

722. user (2026-06-22T17:58:19.063Z)

```
=== render ===
? pass 1
? fail 0
=== layout (footer now has 6 flyer links) ===
? header never overflows / wraps over the brand / clips the CTA (pages x 6 locales x widths)
(22300.5961ms)
? footer + #join form never overflow horizontally (index.html x 6 locales x phone widths)
(2356.9099ms)
? pass 3
? fail 0
=== a11y ===
? pass 1
? fail 0
=== web ===
Test Files 24 passed (24)
Tests 226 passed (226)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

723. assistant (2026-06-22T17:58:30.622Z)

All browser guards + web green (footer's 6 flyer links don't overflow). Let me run the web CI gates, clean up helper scripts, and review the diff.

724. user (2026-06-22T17:58:51.567Z)

```
typecheck:
OK
coverage:
All files          |   94.09 |   88.77 |   86.59 |   94.09 |
build:
? built in 1.82s
=== git status ===
 M site/public/index.html
 M site/public/own-model.html
 M site/server.js
 M site/src/assets.test.js
?? site/public/flyer-da.html
?? site/public/flyer-es.html
?? site/public/flyer-id.html
?? site/public/img/studio-da.png
?? site/public/img/studio-es.png
?? site/public/img/studio-id.png
--- base ---
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

725. assistant (2026-06-22T17:59:03.756Z)

Web gates green (94.09% coverage). Clean diff ? 4 modified (footer links, routes, tests) + 6 new (3 flyers + 3 localized screenshots), no helpers/dist. Let me commit P3.8.

726. user (2026-06-22T17:59:13.458Z)

```
staged: 10
Current branch feat/flyers-es-da-id is up to date.
8150fce feat(site): es/da/id academy flyers (parity with en/kn/hi) ? P3.8
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

727. assistant (2026-06-22T17:59:18.303Z)

Committed (8150fce, clean base). Let me push and open the PR.

728. user (2026-06-22T17:59:31.219Z)

```
remote: Invalid username or token. Password authentication is not supported for Git operations.
fatal: Authentication failed for 'https://github.com/avidullu/khelsutra.git/'
pull request create failed: GraphQL: Head sha can't be blank, Base sha can't be blank, No
commits between master and feat/flyers-es-da-id, Head ref must be a branch (createPullRequest)
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

729. assistant (2026-06-22T17:59:37.542Z)

The push hit a transient auth failure. Let me retry.

730. user (2026-06-22T17:59:41.445Z)

```
remote:
branch 'feat/flyers-es-da-id' set up to track 'origin/feat/flyers-es-da-id'.
To https://github.com/avidullu/khelsutra.git
 * [new branch]      feat/flyers-es-da-id -> feat/flyers-es-da-id
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

731. assistant (2026-06-22T17:59:46.681Z)

Push succeeded (transient glitch). Let me create the PR.

732. user (2026-06-22T17:59:56.008Z)

<https://github.com/avidullu/khelsutra/pull/109>
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

733. assistant (2026-06-22T18:00:02.834Z)

PR [#109](<https://github.com/avidullu/khelsutra/pull/109>) opened. Let me watch CI and merge.

734. user (2026-06-22T18:01:48.126Z)

site pass 17s
<https://github.com/avidullu/khelsutra/actions/runs/27973289703/job/82784580416>
web pass 41s
<https://github.com/avidullu/khelsutra/actions/runs/27973289703/job/82784580499>
Workers Builds: hidden-king-khelsutra pass 0
<https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-khelsutra/production/builds/c5e7c375-d8e3-40e5-a056-c3ab6abc660b>
layout pass 1m28s
<https://github.com/avidullu/khelsutra/actions/runs/27973289703/job/82784580465>
site pass 17s
<https://github.com/avidullu/khelsutra/actions/runs/27973289703/job/82784580416>
web pass 41s
<https://github.com/avidullu/khelsutra/actions/runs/27973289703/job/82784580499>
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

735. assistant (2026-06-22T18:01:53.099Z)

All green. Let me verify and merge P3.8.

736. user (2026-06-22T18:02:00.513Z)

only my commit?
8150fce feat(site): es/da/id academy flyers (parity with en/kn/hi) ? P3.8
{"merge":"0e58427bdf8707a7ca198ea1c2bb1be6c01d08bd","state":"MERGED"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

737. assistant (2026-06-22T18:02:23.906Z)

****P3.8 merged**** ([#109](<https://github.com/avidullu/khelsutra/pull/109>), squash `0e58427`) ?
es/da/id flyers + localized screenshots. All build items done (P1.1 #106, P2 #107, P3.8 #109).
Now the final step: ****refresh docs + close the chapter****. Let me clean up and survey the docs that reference the i18n state.

738. user (2026-06-22T18:02:35.846Z)

- [deleted] feat/flyers-es-da-id
HEAD is now at 0e58427 feat(site): es/da/id academy flyers (parity with en/kn/hi) ? P3.8 (#109)
docs worktree: 0e58427 feat(site): es/da/id academy flyers (parity with en/kn/hi) ? P3.8 (#109)

739. assistant (2026-06-22T18:02:44.206Z)

Docs worktree ready. Let me survey which docs reference the i18n/multilingual/QA-gate state.

740. user (2026-06-22T18:02:47.223Z)

=== docs that mention i18n / multilingual / native-review / human gate / flyer ===
docs/archives/FRIENDLY_AND_MULTILINGUAL.md
docs/DRY_RUN_CUJ.md
docs/MULTILINGUAL_EXPANSION.md
docs/README.md
NEXT_STEPS.md

```
README.md
=== docs/ listing ===
docs/:
ANNOTATE_AND_TRAIN.md
DRY_RUN_CUJ.md
LOCAL_APPLIANCE_ARCHITECTURE.md
MULTILINGUAL_EXPANSION.md
PER_RALLY_SELECTION.md
PORTABILITY.md
README.md
REQUEST_ACCESS_FORM.md
archives

docs/archives/:
FRIENDLY_AND_MULTILINGUAL.md
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

741. assistant (2026-06-22T18:03:05.536Z)

Let me read the key docs' i18n sections to refresh them accurately. Starting with NEXT_STEPS, the doc index, and the multilingual expansion doc.

742. user (2026-06-22T18:03:08.056Z)

```
=== NEXT_STEPS.md (i18n/QA references) ===
10: **CI gates every PR** ? three jobs: the full site `npm test` (Worker + VM host + assets +
UX), the
14:6-language localization, the per-rally MVP, droplet portability). Docs:
19: localized to all **6 languages** (en/kn/hi/es/da/id) across both surfaces (`web/` SPA +
`site/`
20: marketing); the home-page body is fully localized (except the deferred `#join` form, A6)
and the
22: **`docs/archives/FRIENDLY_AND_MULTILINGUAL.md`**. **Carried forward (live owner items, NOT
engineering):**
25: - **Owner font-glyph eyeball** on a real Kannada/Hindi device (CI can't render font
glyphs).
26: - **B7 (deferred, not a v1 blocker):** engine backend customer-facing l10n (report
`customer_` +
27: rejection reasons) ? cross-repo Python (`badminton-highlight-indexer`), owner-gated
**D-BACKEND-DEPTH**.
39: L4-run rallies + reel. **NEXT (owner-gated, engine repo): M1?M5** ? `GET /api/health` +
`download_url`
41: corpus correction loop (P10), localized NL (M5). **Optional:** a fresh live `/api/process`
GPU
46:- **Cloudflare Web Analytics (owner-gated; FREE)** ? code side DONE (the dead placeholder
beacon was
63:- **Single-box appliance (KhelSutra Studio)** ? **? Tracked design:
`docs/LOCAL_APPLIANCE_ARCHITECTURE.md` (DRAFT, owner-gated).**
65: loop on ONE box, behind an **edge auth gate** (engine stays `127.0.0.1`, CORS `` is moot).
It is the single-box

=== docs/README.md (FRIENDLY/multilingual entries) ===
9:- ** archives/FRIENDLY_AND_MULTILINGUAL.md`** ? ? **DONE ? ARCHIVED (2026-06-22).** Made the
product
10: super user-friendly for non-tech-savvy coaches/parents **and** localized it to all **6
languages**
11: across both surfaces (`web/` SPA ? react-i18next, `site/` ? a shared `t()` shim); the home-
page body
12: is fully localized (except the deferred `#join` form, A6) and the responsive header is
fixed +
16:- **`MULTILINGUAL_EXPANSION.md`** ? `IN PROGRESS`: **Phase A (es/da/id) shipped** ([#67]);
**Thai
19: `FRIENDLY_AND_MULTILINGUAL.md`, reusing its foundation.

=== docs/MULTILINGUAL_EXPANSION.md head ===
```

Multilingual Expansion ? 7 new locales (th · id · da · es · zh-Hans · ja · ko)

```
> **Status:** `IN PROGRESS` ? **Phase A (es/da/id) shipped
([#67](https://github.com/avidullu/khelsutra/pull/67)); Phases B (Thai) / C (CJK) owner-gated**
· **Owner:** Avi Dullu · **Created:** 2026-06-21 · **Last updated:** 2026-06-21
> **Lifecycle:** `DRAFT ? IN PROGRESS ? DONE ? archived` (move to `docs/archives/` when DONE)
> **Tracking anchors:** $7 progress tracker is the source of truth; index in `docs/README.md`;
pointer in memory `current-state`; thread in `NEXT_STEPS.md` once work starts.
> **Relation to existing docs:** **PEER-OF / extends**
[`FRIENDLY_AND_MULTILINGUAL.md`](archives/FRIENDLY_AND_MULTILINGUAL.md) (the `en`/`kn`/`hi`
foundation) and the engine design `I18N_PLAN.md`. **Reuses that foundation verbatim**
(react-i18next + i18next-icu + browser detector + key-parity/no-bare-strings CI + self-hosted
OFL Noto via `@fontsource` + Gemini-draft?native-review). This is a **parallel** line: it adds
locales, it does **not** re-architect i18n.
> **Honesty note:** each claim tagged `[verified]` (checked vs the working tree this session),
`[researched]` (sourced, needs sign-off), or `[design]` (proposed). Not legal advice ? the OFL-
font carve-out is the owner's standing call (D7 in FRIENDLY).

---
```

0. TL;DR

Add **Thai, Indonesian, Danish, Spanish, Chinese (Simplified), Japanese, Korean** to the Studio SPA with the **same rigor as en/kn/hi**. The good news `[verified]`: the i18n foundation already scales ? **zero changes to the negotiation contract or the catalog format**; adding a locale is "drop a reviewed `common.json` + (if non-Latin) bundle one OFL Noto font + keep CI key-parity green." The work splits cleanly into **Phase A** (es/da/id ? **catalog-only, no fonts**), **Phase B** (Thai ? **one small OFL font**), and **Phase C** (zh-Hans/ja/ko ? **large OFL CJK fonts + lazy-load + an offline-bundle subsetting decision + the zh script-variant call**). **The single most important caveats:** (1) **native-speaker review per language** is the real cost and the public-launch gate (Gemini drafts are **inference-only**, never the source of truth ? the standing guardrail); (2) **CJK fonts add tens of MB** to the otherwise-tiny air-gapped bundle; (3) **Spanish now has a 3-form plural** (`{one, many, other}`) ? the one authoring wrinkle.

1. Problem & goal

Why now. en/kn/hi shipped and proved the foundation is locale-pluggable (a Kannada-default browser auto-renders Kannada; the switcher walks `kn?hi?en`). The owner wants to broaden reach beyond the India beachhead ? **SE Asia (th, id), Europe (da, es), and East Asia (zh, ja, ko)**. **Concrete outcome ("good"):** a user whose browser is in any of the 7 languages lands on the Studio (and the marketing pages too ? FRIENDLY B3 landed [#70], with es/da/id site parity shipped [#87]; th/zh/ja/ko site parity still pending), and ? without help ? understands the product, runs the tool, and gets a reel, **entirely in their language**, with the fonts rendering crisply offline. **Read to get current:** this doc §3?§4; [`FRIENDLY_AND_MULTILINGUAL.md`](archives/FRIENDLY_AND_MULTILINGUAL.md) (the foundation this rides on, esp. §4 design + §6.5 negotiation tests); `web/src/i18n/index.ts` (the detector/ICU/fallback config) + `web/src/main.tsx` (the `@fontsource` font-load pattern) + `web/src/i18n/hygiene.test.ts` (key-parity + no-bare-strings + offline guards).

2. Decisions locked (inherited from FRIENDLY unless noted)

```
| # | Decision | Source / date | Implication |
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

743. assistant (2026-06-22T18:03:25.403Z)

Now I understand the doc landscape. The key state change to propagate everywhere: **the two human gates are CLEARED**, and the localization is now **complete** (form/footer/privacy/titles/flyers + ally guard). Let me read the exact regions to update.

744. user (2026-06-22T18:03:26.828Z)

```
16
17     ## Next product threads (owner ideas, 2026-06-20)
18     - **? DONE ? Friendly & Multilingual (ARCHIVED 2026-06-22):** the product is non-tech-
```

friendly and
19 localized to all ****6 languages**** (en/kn/hi/es/da/id) across both surfaces (`web/` SPA
+ `site/`
20 marketing); the home-page body is fully localized (except the deferred `#join` form,
A6) and the
21 responsive header is fixed + ****CI-guarded**** (a headless-Chromium layout-regression
job). Full record:
22 ****`docs/archives/FRIENDLY\_AND\_MULTILINGUAL.md`****. ****Carried forward (live owner items,
NOT engineering):****
23 - ****Native-speaker review**** of the AI-drafted catalogs (kn/hi/es/da/id ? Gemini
drafts; the standing
24 guardrail before a **wide public launch**). Proxy artifacts: screencasts in
`khelsutra-screencast/`.
25 - ****Owner font-glyph eyeball**** on a real Kannada/Hindi device (CI can't render font
glyphs).
26 - ****B7 (deferred, not a v1 blocker):**** engine backend customer-facing l10n (report
`customer\_` +
27 rejection reasons) ? cross-repo Python (`badminton-highlight-indexer`), owner-gated
****D-BACKEND-DEPTH****.
28 - ****Marketing video on the site**** ? embed a short walkthrough of the record ? index ?
reel process,
29 themed for ****serious enthusiasts****, on the landing page. ? ****A real-UI CUJ screencast
now exists****

745. user (2026-06-22T18:03:27.377Z)

7 only remaining box (droplet, option 3) is ****parked by the owner**** (GPU subscription).
Two engine
8 bugs the runs surfaced are fixed (#281, #289). Was a milestone of
`LOCAL\_APPLIANCE\_ARCHITECTURE.md`.
9 - ****`archives/FRIENDLY\_AND\_MULTILINGUAL.md`**** ? ? ****DONE ? ARCHIVED (2026-06-22).**** Made
the product
10 super user-friendly for non-tech-savvy coaches/parents ****and**** localized it to all ****6
languages****
11 across both surfaces (`web/` SPA ? react-i18next, `site/` ? a shared `t()` shim); the
home-page body
12 is fully localized (except the deferred `#join` form, A6) and the responsive header is
fixed +
13 CI-guarded. Implementation project for the engine's `I18N\_PLAN.md` (l10n) + the UX
half of
14 `UI\_PROPOSAL.md`. ****Carried forward to `NEXT\_STEPS.md`:**** native-speaker review +
owner font-glyph
15 eyeball (human gates), and ****B7**** (engine backend l10n, deferred).
16 - ****MULTILINGUAL_EXPANSION.md`\*\*** ? `IN PROGRESS`: ****Phase A (es/da/id) shipped****
([#67]); ****Thai**
17 (B) / CJK (C) remain owner-gated**. Adds ****7 locales**** (th/id/da/es/zh-Hans/ja/ko)
beyond the
18 en/kn/hi foundation with en/kn/hi-level diligence; peer of the archived
19 `FRIENDLY\_AND\_MULTILINGUAL.md`, reusing its foundation.
20 - ****`LOCAL\_APPLIANCE\_ARCHITECTURE.md`**** ? the single-box, UI-powered rally indexer +
reel

746. assistant (2026-06-22T18:03:48.627Z)

Let me update NEXT_STEPS ? gates cleared, localization complete, with an honest note that the
post-approval additions (form/privacy/titles/flyers) are AI-drafted pending a delta review.

747. user (2026-06-22T18:03:58.551Z)

The file C:\Users\avidu\Projects\ks-docs\NEXT_STEPS.md has been updated successfully. (file
state is current in your context ? no need to Read it back)

748. user (2026-06-22T18:04:09.652Z)

The file C:\Users\avidu\Projects\ks-docs\docs\README.md has been updated successfully. (file state is current in your context ? no need to Read it back)

749. assistant (2026-06-22T18:04:29.210Z)

Now the multilingual-expansion doc's status (es/da/id now fully shipped on *both* surfaces) and then the archived tracker's closeout. Let me update the status line.

750. user (2026-06-22T18:04:33.698Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

751. user (2026-06-22T18:04:40.704Z)

```
3      > **Status:** `IN PROGRESS` ? **Phase A (es/da/id) shipped
([#67](https://github.com/avidullu/khelsutra/pull/67)); Phases B (Thai) / C (CJK) owner-gated**
. **Owner:** Avi Dullu . **Created:** 2026-06-21 . **Last updated:** 2026-06-21
```

752. user (2026-06-22T18:04:49.276Z)

The file C:\Users\avidu\Projects\ks-docs\docs\MULTILINGUAL_EXPANSION.md has been updated successfully. (file state is current in your context ? no need to Read it back)

753. assistant (2026-06-22T18:04:58.818Z)

Now the archived tracker's closeout ? the main one. Let me read its \$9 DoD and changelog tail.

754. user (2026-06-22T18:05:01.452Z)

```
=== $9 Definition of done ===
159:## 9. Definition of done
160:- [X] **Automatic language negotiation ($6.5) is green** ? N1/N3?N7 (SPA, jsdom) + N2 (hi) +
N8 (static-site shim honors `Accept-Language`/?lang`, `server.test.js`), all in CI.
161:- [ ] **Manual cross-check (owner machine):** OS/browser set to Kannada and to Hindi each
render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner eyeball ?
pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts in
`khelsutra-screencast/` ? `khelsutra-site-i18n-desktop.mp4` (site, kn) +
`khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`)).)*
162:- [X] `en + kn + hi` catalogs live and **rendering** on BOTH `web/` SPA and `site/`
marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3
(site), proven by render tests + a real-browser pass.
163:- [ ] **Noto Sans Kannada + Devanagari render correctly** ? owner eyeball on a real machine.
*(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the owner's
device check.)*
164:- [X] CI **key-parity + no-bare-strings** green; a stub locale flags every gap ?
`web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift`
guard.
165:- [X] **Recording-education** (capture + homepage gist) available in `kn` + `hi` ? A3 (#74),
incl. a localized camera-placement diagram (A7, #76).
166:- [X] **Non-tech UX baseline** ? plain-language copy (A1/A6), mobile tap targets (A4) + the
decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only filters
(A9), honest today-vs-roadmap preserved through translation.
167:- [X] $7 all rows ? (or explicitly deferred) ? flip **Status ? DONE** + run the engine
`DOC_STATUS.md $2` archival checklist ? `git mv` to `docs/archives/`. **DONE 2026-06-22 ?
archived** (owner directive: archive on engineering-complete; the two human gates ride forward
to `NEXT_STEPS.md` as owner QA, not archival blockers). *($7 is all ? except the owner-gated,
cross-repo **B7** ? deferred. The two human gates above (native-speaker review of the AI-drafted
catalogs + the owner font-glyph eyeball) are **carried forward to `NEXT_STEPS.md`** (owner QA,
not engineering). Engineering follow-ups since are all **closed**: own-model body
([#86](https://github.com/avidullu/khelsutra/pull/86)), the es/da/id site expansion
([#87](https://github.com/avidullu/khelsutra/pull/87)), the hero demo-mockup + `#how` block
([#89](https://github.com/avidullu/khelsutra/pull/89)), and the remaining
`#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq` sections
([#90](https://github.com/avidullu/khelsutra/pull/90)) ? so the **home page body is fully
```

localized in all 6 languages except the `#join` form (A6, deferred)**. The recurring responsive-header bug is fixed and now **guarded by a real-browser layout-regression CI job** ([#91](https://github.com/avidullu/khelsutra/pull/91)) ? `site/src/layout.browser.mjs`, headless Chromium asserting header invariants across widths × 6 locales; jsdom can't see layout). No engineering gap remains before the two human gates.)*

=== changelog tail (last 3 entries) ===

194:- `2026-06-22` ? **remaining home content sections localized + responsive header smoothed ([#90](https://github.com/avidullu/khelsutra/pull/90)).** Wired the last hardcoded home-page sections ? **`#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq`** (**65 new `site.{diff,sharper,ask,roadmap,not,faq}.` keys**) ? so the **home page body is now fully localized in all 6 languages except the `#join` access form** (A6, deferred). en byte-for-byte from the DOM; kn/hi/es/da/id via a per-locale **translate ? 2-lens adversarial verify ? revise** Workflow (20 agents); inline markup + brand/tokens preserved. The same PR **smoothed the responsive header** ? the ~860?1080px dead zone where the 6 nav-links wrapped onto 3 lines, overlapped the brand, and clipped the CTA ? by tightening the links and hiding them below 1080px (a clean brand + switcher + CTA row). Verified in-browser en/id @ 1280/1000/864/375px. **Site 84 + web 223 green.**

195:- `2026-06-22` ? **? browser layout-regression CI guard + full-locale header fix ([#91](https://github.com/avidullu/khelsutra/pull/91)).** Closed the gap that let the header bug recur 3x: the suites run in **jsdom, which has no layout engine** (`getBoundingClientRect()` is all zeros), so overflow/wrapping/clipping was invisible to CI. New **`layout` CI job** ? `npm run test:layout` drives a headless **Chromium** (`site/src/layout.browser.mjs`; Playwright = a site test-only devDep) over index/capture/own-model at widths **[1280,1100,1000,900,768,375] × all 6 locales**, asserting header **invariants** (no nav overflow / links never wrap / CTA not clipped / no page h-scroll). Assertions are **inequalities, not screenshots** ? robust across OS/fonts, no baselines. It immediately caught that **#90's header fix was incomplete** ? **es (+138px)** and **da (+47px)** still overflowed (their translated nav labels are far longer). Fixed with **measure-and-collapse**: the shim's new **`fitNav`** measures the header after applying a locale (+ on resize / `fonts.ready`) and adds `.nav-crowded` to collapse the nav when the links won't fit ? **measured live, so it self-adapts to any future translation length**. en keeps its 6 links; es collapses cleanly. Proven to **fail on the pre-fix CSS, pass after** ; green in CI's Ubuntu env. **Site 85 + web 223 + the new layout job green.**

196:- `2026-06-22` ? **chapter-closeout doc sweep + stronger fitNav tests ([#92](https://github.com/avidullu/khelsutra/pull/92)).** Brought this tracker's changelog + §9 DoD current (logged #89/#90/#91); strengthened the `fitNav` shim unit test to deterministically cover both branches (collapse-on-overflow / reveal-on-fit + idempotency) by mocking geometry, since jsdom has no layout engine. Site 86 green.

197:- `2026-06-22` ? **? ARCHIVED ? Friendly & Multilingual chapter complete.** Engineering is done across both surfaces ? 6 languages end-to-end, the home-page body fully localized (except the deferred `#join` form, A6), the recurring responsive-header bug fixed + **CI-guarded** (#91), and this tracker swept current (#92). Per **owner directive**, archived on **engineering-complete**: `git mv` ? `docs/archives/`; inbound pointers (`NEXT\_STEPS.md`, `docs/README.md`, `docs/MULTILINGUAL\_EXPANSION.md`, the `web/src/i18n/` design-rationale comments) updated. The two **human gates** (native-speaker review of the AI-drafted catalogs + the owner font-glyph eyeball on a real kn/hi device) and the deferred **B7** (engine backend l10n) are **carried forward to `NEXT\_STEPS.md`** as live owner items ? not archival blockers.

=== total lines ===

197 docs/archives/FRIENDLY_AND_MULTILINGUAL.md
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra

755. assistant (2026-06-22T18:05:15.859Z)

Let me flip the two human-gate checkboxes to cleared and update the §9 closeout note (the `#join` form, Privacy, titles, flyers, a11y are all done now).

756. user (2026-06-22T18:05:20.477Z)

<tool_use_error>File has not been read yet. Read it first before writing to it.</tool_use_error>

757. user (2026-06-22T18:05:26.163Z)

```
159    ## 9. Definition of done
160    - [x] **Automatic language negotiation (§6.5) is green** ? N1/N3?N7 (SPA, jsdom) + N2
(hi) + N8 (static-site shim honors `Accept-Language`/`?lang`, `server.test.js`), all in CI.
```

161 - [] ****Manual cross-check (owner machine):**** OS/browser set to Kannada and to Hindi each render the respective language on BOTH surfaces, with Noto fonts displaying. *(Owner eyeball ? pending; cloud CI can't render font glyphs. Closest proxy: the Playwright screencasts in `khelsutra-screencast/` ? `khelsutra-site-i18n-desktop.mp4` (site, kn) + `khelsutra-i18n-screencast.mp4` (SPA, `locale: kn-IN`.)*)

162 - [x] `en + kn + hi` catalogs live and ****rendering**** on BOTH `web/` SPA and `site/` marketing (switcher + persistence + `en` fallback; no raw keys shown) ? B1?B6 (SPA) + B3/A3 (site), proven by render tests + a real-browser pass.

163 - [] ****Noto Sans Kannada + Devanagari render correctly**** ? owner eyeball on a real machine. *(SPA self-hosts OFL Noto (B4); the site loads Noto via Google Fonts (A3). Pending the owner's device check.)*

164 - [x] CI ****key-parity + no-bare-strings**** green; a stub locale flags every gap ? `web/src/i18n/hygiene.test.ts` (+ placeholder-parity, es 3-form) + the site `locales-drift` guard.

165 - [x] ****Recording-education**** (capture + homepage gist) available in `kn` + `hi` ? A3 (#74), incl. a localized camera-placement diagram (A7, #76).

166 - [x] ****Non-tech UX baseline**** ? plain-language copy (A1/A6), mobile tap targets (A4) + the decluttered compact switcher (#83), icon+text status (A8), WhatsApp share (A2), tap-only filters (A9), honest today-vs-roadmap preserved through translation.

167 - [x] §7 all rows ? (or explicitly deferred) ? flip ****Status ? DONE**** + run the engine `DOC\_STATUS.md §2` archival checklist ? `git mv` to `docs/archives/`. ****DONE 2026-06-22 ? archived**** (owner directive: archive on engineering-complete; the two human gates ride forward to `NEXT\_STEPS.md` as owner QA, not archival blockers). *(\$7 is all ? except the owner-gated, cross-repo ****B7**** ? deferred. The two human gates above (native-speaker review of the AI-drafted catalogs + the owner font-glyph eyeball) are ****carried forward to `NEXT\_STEPS.md`**** (owner QA, not engineering). Engineering follow-ups since are all ****closed****: own-model body ([#86](https://github.com/avidullu/khelsutra/pull/86)), the es/da/id site expansion ([#87](https://github.com/avidullu/khelsutra/pull/87)), the hero demo-mockup + `#how` block ([#89](https://github.com/avidullu/khelsutra/pull/89)), and the remaining `#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq` sections ([#90](https://github.com/avidullu/khelsutra/pull/90)) ? so the ****home page body is fully localized in all 6 languages except the `#join` form (A6, deferred)****. The recurring responsive-header bug is fixed and now ****guarded by a real-browser layout-regression CI job**** ([#91](https://github.com/avidullu/khelsutra/pull/91)) ? `site/src/layout.browser.mjs`, headless Chromium asserting header invariants across widths × 6 locales; jsdom can't see layout). No engineering gap remains before the two human gates.)*

758. assistant (2026-06-22T18:05:30.611Z)

Now let me flip the two gate checkboxes and refresh the §9 closeout note:

759. user (2026-06-22T18:05:34.308Z)

The file C:\Users\avidu\Projects\ks-docs\docs\archives\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

760. user (2026-06-22T18:05:41.046Z)

The file C:\Users\avidu\Projects\ks-docs\docs\archives\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

761. assistant (2026-06-22T18:05:48.814Z)

Now update the §9 closeout note ? the `#join` form is localized, gates cleared, and the post-archive PRs:

762. user (2026-06-22T18:06:00.621Z)

The file C:\Users\avidu\Projects\ks-docs\docs\archives\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

763. assistant (2026-06-22T18:06:07.179Z)

Let me append the final closeout changelog entry to the archived tracker.

764. user (2026-06-22T18:06:07.982Z)

197 - `2026-06-22` ? ****?** ARCHIVED ? Friendly & Multilingual chapter complete.****** Engineering is done across both surfaces ? 6 languages end-to-end, the home-page body fully localized (except the deferred `#join` form, A6), the recurring responsive-header bug fixed + ****CI-guarded**** (#91), and this tracker swept current (#92). Per ****owner directive****, archived on ****engineering-complete****: `git mv` ? `docs/archives/`; inbound pointers (`NEXT\_STEPS.md`, `docs/README.md`, `docs/MULTILINGUAL\_EXPANSION.md`, the `web/src/i18n/` design-rationale comments) updated. The two ****human gates**** (native-speaker review of the AI-drafted catalogs + the owner font-glyph eyeball on a real kn/hi device) and the deferred ****B7**** (engine backend l10n) are ****carried forward to `NEXT\_STEPS.md`**** as live owner items ? not archival blockers.

765. user (2026-06-22T18:06:23.478Z)

The file C:\Users\avidu\Projects\ks-docs\docs\archives\FRIENDLY_AND_MULTILINGUAL.md has been updated successfully. (file state is current in your context ? no need to Read it back)

766. assistant (2026-06-22T18:06:28.606Z)

Let me check the root README's language mention and confirm it's consistent.

767. user (2026-06-22T18:06:29.898Z)

9:- ****Status:**** alpha ? the `web/` SPA is built and multilingual (6 languages: en/kn/hi/es/da/id), with the per-rally selection MVP and first-run setup wizard shipped; `khehsutra.guru` / `app.khehsutra.guru` are live (Cloudflare Pages + cloudflared tunnel + Access). See [`NEXT\_STEPS.md`](NEXT_STEPS.md).
Shell cwd was reset to C:\Users\avidu\Projects\khehsutra

768. assistant (2026-06-22T18:06:38.684Z)

Let me broaden the root README's status to note both surfaces are localized (it currently mentions only the SPA).

769. user (2026-06-22T18:06:39.238Z)

9 - ****Status:**** alpha ? the `web/` SPA is built and multilingual (6 languages: en/kn/hi/es/da/id), with the per-rally selection MVP and first-run setup wizard shipped; `khehsutra.guru` / `app.khehsutra.guru` are live (Cloudflare Pages + cloudflared tunnel + Access). See [`NEXT\_STEPS.md`](NEXT_STEPS.md).

770. user (2026-06-22T18:06:47.506Z)

The file C:\Users\avidu\Projects\ks-docs\README.md has been updated successfully. (file state is current in your context ? no need to Read it back)

771. assistant (2026-06-22T18:06:57.834Z)

Docs refreshed (5 files). Let me verify the diff and run the site suite (in case any test reads these docs).

772. user (2026-06-22T18:07:00.376Z)

```
=== git status ===
M NEXT_STEPS.md
M README.md
M docs/MULTILINGUAL_EXPANSION.md
M docs/README.md
M docs/archives/FRIENDLY_AND_MULTILINGUAL.md
=== node_modules present for a quick test run? ===
no site deps in this worktree ? docs-only change, site code untouched (CI will run)
Shell cwd was reset to C:\Users\avidu\Projects\khehsutra
```

773. assistant (2026-06-22T18:07:15.345Z)

Clean ? exactly the 5 docs (no code/locales touched), so CI is unaffected. Let me commit and open the close-out PR.

774. user (2026-06-22T18:07:30.819Z)

```
base check (should be empty):
branch 'docs/i18n-closeout' set up to track 'origin/docs/i18n-closeout'.
To https://github.com/avidullu/khelsutra.git
* [new branch]      docs/i18n-closeout -> docs/i18n-closeout
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

775. user (2026-06-22T18:07:46.048Z)

```
https://github.com/avidullu/khelsutra/pull/110
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

776. assistant (2026-06-22T18:07:50.771Z)

PR [#110](https://github.com/avidullu/khelsutra/pull/110) opened (docs-only). Let me watch CI and merge.

777. user (2026-06-22T18:09:15.357Z)

```
site    pass    14s
https://github.com/avidullu/khelsutra/actions/runs/27973754656/job/82786140480
web     pass    46s
https://github.com/avidullu/khelsutra/actions/runs/27973754656/job/82786140527
Workers Builds: hidden-king-khelsutra    pass    0
https://dash.cloudflare.com/213c12cf60de9041dd8a3521aa206472/workers/services/view/hidden-king-
khelsutra/production/builds/82a3e8a9-124a-46c6-a44d-80790482e43b
layout  pass    1m8s
https://github.com/avidullu/khelsutra/actions/runs/27973754656/job/82786140439
site    pass    14s
https://github.com/avidullu/khelsutra/actions/runs/27973754656/job/82786140480
web     pass    46s
https://github.com/avidullu/khelsutra/actions/runs/27973754656/job/82786140527
EXIT:0
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

778. assistant (2026-06-22T18:09:20.769Z)

All green. Let me merge the close-out PR.

779. user (2026-06-22T18:09:27.784Z)

```
only my commit?
7d5e61d docs: close out the Friendly & Multilingual chapter ? gates cleared, localization 100%
{"merge":"bc4e7ba295addcd0a166d08dcc7a9698fc6ea3d7","state":"MERGED"}
Shell cwd was reset to C:\Users\avidu\Projects\khelsutra
```

780. assistant (2026-06-22T18:09:36.161Z)

****#110 merged**** ([squash `bc4e7ba`]). The chapter is fully closed. Let me clean up the worktree and refresh the handoff to the final state.

781. user (2026-06-22T18:09:43.470Z)

```
- [deleted]      docs/i18n-closeout
worktrees:
C:/Users/avidu/Projects/khelsutra  ed33a51 [master]
origin/master:
```

bc4e7ba docs: close out the Friendly & Multilingual chapter ? gates cleared, localization 100% (#110)

782. assistant (2026-06-22T18:09:52.890Z)

Worktree cleaned. Let me refresh the handoff memory to the final fully-closed state.

783. user (2026-06-22T18:09:53.792Z)

```
1      # Session handoff ? khelsutra (Friendly & Multilingual workstream)
2
3      _Last updated: 2026-06-22 ? **both human gates CLEARED + home page 100% localized
([#105](https://github.com/avidullu/khelsutra/pull/105)).** Owner gave formal native-speaker
approval on all locales and eyeballed the device render. #105 finished the last English islands
? the FULL #join access form (26 new `site.join.*` keys; the A6 work had only wired the
GPU/storage Qs) + the footer (6 `site.footer.*`) ? in all 6 langs, and added a **cross-locale
render guard** (`npm run test:render`, in CI). Chapter was archived in #93
(`docs/archives/FRIENDLY_AND_MULTILINGUAL.md`). Prior: #86 own-model ? #87 es/da/id site ?
#89/#90 hero+home sections ? #91 layout CI guard ? #93 archive ? #104 compute-picker ? **#105
form+footer+render-guard**._
4
5      *** Effectively DONE ? only B7 (deferred, cross-repo engine l10n, owner-gated) remains;
not engineering for this repo.** The two former gates ? native-speaker review + owner device
eyeball ? are **CLEARED**. ONE small caveat: the **new** #105 form/footer strings + the Privacy
page (below) post-date that approval, so they're AI-drafted ? would want a native pass on the
next review cycle.
6
7      **Header is now robust across ALL 6 locales + guarded.** #90's fix only covered
en/kn/hi/id; the #91 layout guard caught that **es (+138px) / da (+47px)** still overflowed
(longer translated nav labels). Fixed in #91: the shim (`fitNav` in `site/public/i18n.js`)
measures the header after applying a locale (+ on resize / fonts.ready) and adds `.nav-crowded`
to collapse the 6-link nav to a compact brand+switcher+CTA row when it won't fit ? **measured
live, so it self-adapts to any future translation length.** New CI: a `layout` job runs `npm run
test:layout` = `site/src/layout.browser.mjs` (headless Chromium/Playwright, a site test-only
devDep) asserting header invariants (no overflow / no link-wrap / CTA not clipped / no h-scroll)
across widths x 6 locales on index/capture/own-model. jsdom can't see layout, so this is the
only guard for rendering distortion ? extend it when touching site CSS/markup.
```

784. user (2026-06-22T18:10:14.442Z)

The file C:\Users\avidu\.claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

785. assistant (2026-06-22T18:10:21.472Z)

Let me update the handoff's follow-ups section (Privacy/ai1y/flyers are now done).

786. user (2026-06-22T18:10:22.873Z)

```
20:## Open engineering follow-ups (small)
22:- ~~Hardcoded hero-mockup chips in `site/public/index.html`~~ ? **DONE & MERGED (PR
[#89](https://github.com/avidullu/khelsutra/pull/89)).** Wired the full hero block (CTA +
`phone/GoPro` note + 3 process chips + the reel-card demo mockup) **and** the `#how` "What it
does today" feature block (head + 4 cards): 21 new `site.hero.{ctaReel,note,loop.*,demo.*}` +
`site.how.*` keys, translated kn/hi/es/da/id (AI-draft ? adversarial review ? revised; native-
review-pending). Extended `assets.test.js` + `i18n.shim.test.js`. Rebased onto #88's `wizard.*`
catalog namespace.
25:- **Privacy Policy page (`site/public/privacy.html`, added #96)** ? the one remaining
English-only marketing surface: **zero i18n hooks** (no shim, no switcher, no `data-i18n`),
`<html lang="en">`, ~193 lines / 12 headings of legal copy. A full slice (wire shim+switcher,
~all body, translate x5). Largest remaining localization gap ? see prioritized list.
26:- **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python i18n
+ owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
```

787. user (2026-06-22T18:10:28.673Z)

```
20      ## Open engineering follow-ups (small)
21      - ~~own-model body content English on kn/hi~~ ? **DONE (#86).** ~~es/da/id site only en-
seed~~ ? **DONE (#87).**
22      - ~~Hardcoded hero-mockup chips in `site/public/index.html`~~ ? **DONE & MERGED (PR
[#89](https://github.com/avidullu/khelsutra/pull/89)).** Wired the full hero block (CTA +
`phone/GoPro` note + 3 process chips + the reel-card demo mockup) **and** the `#how` "What it
does today" feature block (head + 4 cards): 21 new `site.hero.{ctaReel,note,loop.*,demo.*}` +
`site.how.*` keys, translated kn/hi/es/da/id (AI-draft ? adversarial review ? revised; native-
review-pending). Extended `assets.test.js` + `i18n.shim.test.js`. Rebased onto #88's `wizard.*`
catalog namespace.
23      - ~~Still-hardcoded home-page sections
(`#diff`/`#sharper`/`#ask`/`#roadmap`/`#not`/`#faq`)~~ ? **DONE & MERGED (PR
[#90](https://github.com/avidullu/khelsutra/pull/90)).** 65 new
`site.{diff,sharper,ask,roadmap,not,faq}.*` keys, translated kn/hi/es/da/id via a `translate` ?
2-lens adversarial verify ? revise `**Workflow**` (20 agents); native-review-pending. **[#90] also
fixed the responsive header** (the ~860?1080px dead zone where the 6 nav-links
wrapped/overlapped the brand + clipped the CTA): nav-links now `gap:1rem`/`.9rem`/`nowrap` and
hide below `max-width:1080px` (clean brand+switcher+CTA row); grid breakpoint stays 860.
Verified in-browser en/id @ 1280/1000/864/375px.
24      - ~~Footer + the FULL #join access form English on non-en~~ ? **DONE & MERGED
([#105](https://github.com/avidullu/khelsutra/pull/105)).** The home page is now 100% localized
in all 6 langs (section head, every field/label/option, courts dropdown, consent, submit,
privacy note, post-submit message, the JS "Sending?" via the `window.KhelSutra.t` bridge, +
footer). Also fixed a hi `Bengaluru`/`???????` mix. New CI guard: `**npm run test:render**`
(`site/src/render.browser.mjs`) ? headless Chromium over all 3 pages x 6 locales asserting live-
DOM == catalog (no raw keys / right lang / no console errors / Indic script). Plus a
deterministic no-bare-strings guard for #join+footer (`assets.test.js`) and a proper-noun
consistency test.
25      - **Privacy Policy page (`site/public/privacy.html`, added #96)** ? the one remaining
English-only marketing surface: **zero i18n hooks** (no shim, no switcher, no `data-i18n`),
`<html lang="en">`, ~193 lines / 12 headings of legal copy. A full slice (wire shim+switcher,
~all body, translate x5). Largest remaining localization gap ? see prioritized list.
26      - **B7** (engine backend customer-facing l10n) ? deferred: significant cross-repo Python
i18n + owner-gated (D-BACKEND-DEPTH). Not a v1 blocker.
```

788. user (2026-06-22T18:10:44.775Z)

The file C:\Users\avidu\claude\projects\C--Users-avidu-Projects-khelsutra\memory\session-handoff.md has been updated successfully. (file state is current in your context ? no need to Read it back)

789. assistant (2026-06-22T18:11:10.671Z)

The chapter is **fully closed**. Here's the complete close-out from this session.

Merged (each its own PR, squash-merged on all-green CI: site + web + layout/render/a11y + Cloudflare)

```
| PR | What |
|---|---|
| [#106](https://github.com/avidullu/khelsutra/pull/106) | **P1 ? Privacy Policy** localized (63
keys, legal-faithful) in all 6 languages + a 6-lang switcher; added to server negotiation + the
drift/render/a11y guards |
| [#107](https://github.com/avidullu/khelsutra/pull/107) | **P2.3** per-page `<title>`s
localized . **P2.5** axe-core **WCAG 2.1 AA guard** (`test:a11y`) ? which found & fixed real
contrast (`#149A5C`?`#137a4c`) + footer link-distinguishability issues |
| [#109](https://github.com/avidullu/khelsutra/pull/109) | **P3.8** es/da/id **academy flyers**
+ real localized SPA screenshots + routes/links/tests |
| [#110](https://github.com/avidullu/khelsutra/pull/110) | **Close-out docs** ? flipped both
human-gate DoD boxes to ?, refreshed the archived tracker + NEXT_STEPS + both READMEs + the
multilingual-expansion doc |
```

(On top of this session's earlier #86 own-model, #87 es/da/id site, #105 form+footer+render-

guard.)

State now

- **Every marketing surface renders in all 6 languages** (en/kn/hi/es/da/id) with **no English islands** ? home (incl. the full `#join` form + footer), capture, own-model, **Privacy**, page `<title>`'s, and the **academy flyers**. Legal text carries an "English is authoritative" note.
- **Both human gates cleared.** CI now has three headless-Chromium guards ? **layout** (no overflow), **render** (live DOM == catalog, no raw keys/errors, across every page × locale), and **a11y** (axe AA) ? plus the jsdom suite + web typecheck/coverage/build.
- Each translation went AI-draft ? **3-lens adversarial verify** ? revise; I caught & fixed real defects along the way (the hi `Bengaluru`/`???????` mix, a kn brand-transliteration in titles, `&` over-escapes, a dropped `<b>` in the privacy policy).

Backlog (per your instruction ? "rest can be put to the backlog")

- **Delta native-review** of the strings added **after** your sign-off (#105/#106/#107/#109 are AI-drafted) ? a small top-up before a wide public launch.
- **B7** ? engine backend customer-facing l10n (cross-repo Python, owner-gated).
- **P2.4** ? a localized how-to-record **video** (content production, not code; flagged ? say the word if you'd like an animated SVG walkthrough instead).
- Earlier-listed: Kannada/Hindi query-NL input; localized request-access email.

Handoff memory updated to the closed state. All worktrees cleaned up; the main checkout was left untouched (a sibling session has it). The chapter is done ? nice work growing the reach. ?