# CS2014 Systems Programming

Lectures:

Stephen Farrell

stephen.farrell@cs.tcd.ie, x2354

Room: WR3.4 (impossible to find!)

Teaching Assistant:
Christian Cabrera
cabrerac@scss.tcd.ie, xNNNN
See Christian @ labs

## C Programming

- Learn by doing!
- Today: memory, structures, unions...
- If you're interested in programming, play with doing the examples in some other programming language, e.g. python, PHP or whatever you prefer
  - Eventually, you'll see the common concepts, the different concepts, and the syntactic sugar
  - But you don't have to do that to pass the course or even to do well in the exam, C is enough for that
- Today: memory, structures, unions...
- Learn by doing! (Did I say that already?)

## Layout of an array in memory

- From the perspective of your program, octets of an array are laid out in sequence
- Special case: strings are arrays of chars
  - Strings are often null-terminated, i.e. have a zero valued octet at the end
  - Some functions assume that, great source of bugs

## Layout of two arrays in memory

- From the perspective of your program, two arrays on the stack are sequential
  - Not true of heap, when storage is allocated via malloc()
- DANGER!!! DANGER!!!
  - And somewhat fictional

### Word size counts

- 8,16,32,64 bit processors differ
  - Endian-ness matters (and little-endian now dominant)
  - https://en.wikipedia.org/wiki/Endianness
- Different OSes differ
- Portable C can work on all those if done well
- Bugs can manifest very differently

```
int my_int;
char *my_other_str;
```

#### Structured Data

- Lots of data is structured, e.g. account numbers and user information go together
- Struct in C allows you to handle that
- Similar to class concept in Java, C++ but limited to data, no code, no public/private
- Mostly used with typedef so struct can be used as a type, like int, char, ....

```
// structure with some info about a file
typedef struct _finfo {
   char *name;
   char *link;
   char isdir;
} finfo, *finfo_p;
finfo myvar;
   myvar.name="foo";
   myvar.link=NULL;
   myvar.isdir=0;
```

## Layout in memory

 Items in a struct are laid out as they would be if they were on the stack (and defined in the same sequence and the compiler hasn't optimised things)

```
typedef struct _finfo {
   char *name;
   char *link;
   char isder;
} finfo, *finfo_p;
```

```
+-----+
| 8 octets name pointer |
+ - - - - - - - - - +
| | | | | | | |
+------+
| 8 octets link pointer |
+ - - - - - - - - +
| | | | | | | |
+-----+
| 1 octet| char (sorta!)
+-----+
```

### Unions

- Rarely used (we'll see use in sockaddr later)
- Kind of like a choice
- Memory layout: enough octets to fit biggest element of union

## C Programming Examples

Ok, let's go play with more examples

https://down.dsg.cs.tcd.ie/cs2014/examples/c-progs-3/README.html